




(22) Date de dépôt/Filing Date: 1996/04/26
 (41) Mise à la disp. pub./Open to Public Insp.: 1996/10/29
 (45) Date de délivrance/Issue Date: 2005/07/05
 (30) Priorité/Priority: 1995/04/28 (0505/95) DK

(51) Cl.Int.⁶/Int.Cl.⁶ E05C 17/04
 (72) Inventeurs/Inventors:
 HAMMER, CARL JOHANNES, DK;
 FEJER, OLE, DK
 (73) Propriétaire/Owner:
 VKR HOLDING A/S, DK
 (74) Agent: BORDEN LADNER GERVAIS LLP

(54) Titre : DISPOSITIF DE COUPLAGE A LIBERATION MANUELLE SERVANT A RELIER UN MECANISME D'OUVERTURE ALLONGE ET UN CADRE OU UN ELEMENT PRINCIPAL DE CADRE DE FENETRE ET FENETRE A MECANISME D'OUVERTURE PIVOTANT ET A CHAINE COMPORTANT UN TEL DISPOSITIF
 (54) Title: MANUALLY RELEASABLE COUPLING DEVICE FOR CONNECTING AN ELONGATE OPERATOR MEANS WITH A FRAME OR MAIN FRAME MEMBER OF A WINDOW AND A PIVOTAL, CHAIN OPENER OPERATED WINDOW WITH SUCH A COUPLING DEVICE



(57) Abrégé/Abstract:

A manually releasable coupling device for connecting an elongate operator means (2) with a frame or main frame member of a window comprises a first coupling member (3) for connection with a free end of the operator means (2) and a second coupling



(57) Abrégé(suite)/Abstract(continued):

member (6-10) designed for mounting in or on the frame or main frame member. The first coupling member is a flat disc-shaped element (3) with a substantially keyhole-shaped recess (5), while the second coupling member comprises a shaft section (6) for mounting in a bore in the frame member or the main frame member in connection with a turning handle (7). The shaft section (6) has a local constriction (8) for releasable engagement with the keyhole-shaped recess (5) in the disc-shaped element (3). With a view to allowing manual closing of the window under surmounting of sealing pressure, the shaft section may be eccentric relative to the rotational axis of the turning handle.

A MANUALLY RELEASABLE COUPLING DEVICE FOR CONNECTING AN ELONGATE OPERATOR MEANS WITH A FRAME OR MAIN FRAME MEMBER OF A WINDOW AND A PIVOTAL, CHAIN OPENER OPERATED WINDOW WITH SUCH A COUPLING DEVICE

5

A b s t r a c t

A manually releasable coupling device for connecting an elongate operator means (2) with a frame or main frame member of a window comprises a first coupling member (3) for connection with a free end of the operator means (2) and a second coupling member (6-10) designed for mounting in or on the frame or main frame member. The first coupling member is a flat disc-shaped element (3) with a substantially keyhole-shaped recess (5), while the second coupling member comprises a shaft section (6) for mounting in a bore in the frame member or the main frame member in connection with a turning handle (7). The shaft section (6) has a local constriction (8) for releasable engagement with the keyhole-shaped recess (5) in the disc-shaped element (3).

With a view to allowing manual closing of the window under surmounting of sealing pressure, the shaft section may be eccentric relative to the rotational axis of the turning handle.

25

(Fig. 1)

A MANUALLY RELEASABLE COUPLING DEVICE FOR CONNECTING AN ELONGATE OPERATOR MEANS WITH A FRAME OR MAIN FRAME MEMBER OF A WINDOW AND A PIVOTAL, Chain operator OPERATED WINDOW WITH SUCH A COUPLING DEVICE

5

The present invention relates to a manually releasable coupling device for connecting an elongate operator means with a frame or main frame member of a window, comprising a first coupling member for connection with a free end of the operator means facing said frame or main frame member and a second coupling member designed for mounting in or on the frame or main frame member.

DK Patent No. 168405 discloses a coupling device of this type, in which the first coupling member comprises a coupling head pivotally connected with operator means, while the second coupling member comprises a basis plate element with a recess or a hole, in which a locking plate element is received. The basis plate element and the locking plate element are covered by a cover plate element with an aperture for the coupling head, and these plate elements are all positioned in mutually parallel planes. By means of an actuator means which is pivotal in a plane parallel thereto and engages the locking plate element, the locking plate element can be moved in position for locking and release, respectively, of the coupling head introduced through the aperture in the cover plate element, the locking taking place by engagement between the coupling head and edge portions of the locking plate element and the recess in the basis plate element, while an edge of the aperture in the cover plate element by release of the coupling device prevents the coupling head from following the movement of the locking plate element.

The construction of the second coupling member from several mutually co-operating individual parts with edges which with a view to a reliable functioning of locking and release have to be adapted to each other with comparatively small tolerances, complicates and makes the manufacture as

35

well as the building in of the second coupling member in a frame or a main frame member of a window more costly.

DK Patent No. 169999 further discloses a chain operator for opening and closing a window with a releasable coupling device, wherein the first and the second coupling members are shaped as elongate profiles which may be telescoped and each has a stationary locking element at one end and a releasable locking means at the other end, such that the stationary locking element on one coupling member may be held in releasable engagement with the locking means on the second coupling member. On the first coupling member the releasable locking means comprises a prestressed, longitudinally displaceable slider, whereas on the second coupling member it comprises a tilting locking means which by means of prestress is pivotal between two stable positions for release and holding of the stationary element on the first coupling member.

This known device has the advantage that after release a renewed coupling of the two coupling members is made possible under surmounting of the sealing pressure between frame and main frame, but also here the design of the two coupling members is comparatively complicated and expensive, and the building in comparatively difficult.

In relation to these known coupling devices it is the object of the invention to provide a design which is on one hand substantially more simple in respect of the design of the coupling member, such that in particular the second coupling member easily and discreetly may be built into a frame or main frame member or may be post-mounted on an existing window, and on the other hand ensures a reliable functioning of both the locking and the release of the coupling device in a single operation, which is easy for the user to make.

This is obtained according to the invention in that the first coupling member is a flat, disc-shaped element, which at one end portion is designed for connection with said free end of the operator means and which at an

opposite end portion has a substantially keyhole-shaped recess with a towards this portion open, constricted mouth in connection with a circular part of the recess, while the second coupling member comprises a shaft portion for mounting in a bore in the frame or main frame member or a fixture connected therewith perpendicular to the longitudinal direction of the frame or main frame member in connection with a turning handle, said shaft section having a local constriction with substantially rectangular cross-section, which in one direction has a dimension corresponding to the width of the mouth of the recess in the first coupling member and in a direction perpendicular thereto a dimension corresponding to the diameter of the circular part of the recess, whereby said second coupling member also comprises means for holding said shaft section and turning handle onto the frame or main frame member.

In the coupling device according to the invention the operative part of the second coupling member thus comprises substantially one shaft section with said local constriction which is easy to make with the desired tolerances on an automatic tooling machine and which is moreover simple to mount either directly in the frame or main frame member or in a separate fixture to be mounted thereon, whereby the coupling device according to the invention also is suited for post-mounting on existing windows.

The functioning of the coupling device according to the invention is moreover simple and reliable, as in one position of the turning handle of the second coupling member passage of the recess in the first coupling member may take place over the local constriction on the shaft section on the second coupling member. In the inserted position locking is established by turning the second coupling member by means of the turning handle through an angle which will typically be approx. 90°.

In a further embodiment of the invention the additional advantage is obtained - in the same way as in

the last-mentioned coupling device, but without its complicated coupling parts - that after release of the coupling device with a view to opening the window beyond the limited opening angle, which the operator means makes possible, a coupling of the first and the second coupling member may be made in such a way that the window frame in connection with locking of the coupling device is pulled towards the main frame under surmounting of the sealing pressure between the oppositely positioned frame and main frame members. According to the invention this embodiment is characteristic in that the shaft section with associated turning handle in the second coupling member is designed such that a part of the shaft section containing said local constriction has a longitudinal axis positioned eccentrically displaced relative to the rotational axis of the turning handle.

The coupling device according to the invention is particularly suited for use together with chain operators of the type which is for instance known from the above DK patent no. 169999 and EP published specification no. 0624703, wherein the housing of the chain operator is built into a main frame part, for instance in the bottom part of the main frame. When constructing the frame from hollow profile elements an embodiment of the coupling device according to the invention is characteristic in that the second coupling member is designed for direct mounting in a bore through the frame or main frame member which is made as a hollow element, and in that said holding means comprise a fixture to be fastened on a bottom wall of said hollow profile and provided with a guide for an end portion of the shaft section positioned opposite the turning handle.

The invention also relates to a pivotal window with a substantially rectangular main frame and a frame substantially consisting of hollow profile elements with a manual or electric chain operator for opening of the window to a ventilation position.

By use of the coupling device according to the invention such a window is according to the invention characteristic in that in a main frame member parallel with the axis of rotation of the pivotal movement of the window a housing for the chain operator is built in, that its operator chain which is passed through an opening in the main frame member in direction towards the oppositely positioned frame member which at its free end is connected with an end portion of a first coupling member shaped as a flat, disc-shaped element which at an opposite end portion has a substantially keyhole-shaped recess with a towards this portion open, constricted mouth in connection with a circular part of the recess, and in that a second coupling member is connected with the oppositely positioned frame member, said coupling member comprising a shaft portion for mounting in a bore in the frame member or a fixture for fastening thereon and being perpendicular to the longitudinal direction of the frame member in connection with a turning handle, said shaft section having a local constriction with substantially rectangular cross-section, which in one direction has a dimension corresponding to the width of the mouth of the recess in the first coupling member and in a direction perpendicular thereto a dimension corresponding to the diameter of the circular part of the recess.

The invention will now be explained in detail in the following with reference to the schematic drawing, in which

Fig. 1 is an exploded perspective view of an embodiment of the coupling device according to the invention for use with a chain operator of a design known per se,

Fig. 2 is a sectional view of oppositely positioned frame and main frame members in a window for illustration of the building in of the chain operator of the embodiment shown in Fig. 1,

Fig. 3 is a perspective view of a second coupling member of another embodiment of the coupling device

according to the invention, and

Fig. 4 illustrates the functioning of the embodiment according to Fig. 3 when the first and the second coupling members of the coupling device are coupled in connection with the closing of a window under surmounting of the sealing pressure between oppositely positioned frame and main frame parts.

Fig. 1 shows an electrically operated chain operator with a housing designed for being built into a main frame member of a window. The housing 1 receives the (not shown) drive and transmission means, just as the housing 1 is adapted to receive the operator chain 2 of the chain operator in the closed position of the window, which is in Fig. 1 shown as protruding from the housing 1 towards a window frame member opposite the main frame member, into which the housing 1 is built in.

According to the invention a first coupling member in form of a comparatively flat disc-shaped element 3 is connected with the outermost link of the operator chain 2, said element having at one end a hole 4 for connection with the outermost chain link by means of a rivet or the like and is at its opposite end provided with a keyhole-shaped recess 5, which is open towards the end edge, said recess comprising a constricted mouth 5a in connection with a substantially circular part 5b.

The active part of the second coupling member of the coupling device, which in the example shown is shown for being mounted in or on a frame member opposite the main frame member in which the chain operator housing 1 is built in, comprises according to the invention a shaft section 6 for mounting in a bore in the frame part in connection with a turning handle 7. The shaft section 6 is provided with a local constriction 8 with substantially rectangular cross-section, such that the constriction, as will be best seen in Fig. 4, in one direction has as a dimension a corresponding to the width of the mouth 5a of the recess 5 in the disc-shaped element 3 and in a direction

perpendicular thereto a dimension b corresponding to the diameter of the circular part 5b of the recess 5.

With a view to holding the second coupling member onto the frame part of the window, which by direct mounting in the frame part preferably consists of one or more hollow profile elements as shown in Fig. 2, the embodiment shown in Fig. 1 comprises a guide bushing 9 and a fixture 10 for mounting on a bottom wall of the hollow profile element, said fixture having a guide 11 for the end portion of the shaft section 6 positioned oppositely to the turning handle 7.

In the example shown in Fig. 2 of a window with the coupling device built in according to the invention the chain operator housing 1 is shown built in a hollow space 12a in a main frame member 12 designed as a wood profile. In the side facing the main frame member 12 a cover fixture 17 with an aperture 18 may be mounted, which allows passage of the operator chain 2 with the disc-shaped element 3 for engagement with the local constriction 8 on the shaft section. The cover fixture closes the aperture of the hollow space 12a facing the window frame and is fastened to the main frame member 12 by means of a flange portion 14 in a manner known per se.

The frame member 15 positioned opposite the main frame member 12 consists in a manner known per se of two coupled hollow profiles 15 and 16 which may for instance be of aluminium. The coupled profiles are in the horizontal profile walls provided with holes which provide a through bore for receiving the shaft section 6 of the second coupling member. In the end of the bore facing the aperture face of frame the guide bushing 9 shown in Fig. 1 is inserted, said bushing being of a plastics material, for instance nylon, while the holding fixture 10 is clipped to the underside of the hollow profile 15 and held by means of screws to a bottom wall of this profile.

In Fig. 1 the shaft section 6 of the second coupling member and turning handle 7 are shown in a position

corresponding to locking of the coupling between the two coupling members, wherein the local constriction on the shaft section 6 is prevented from being pulled out through the mouth 5a of the recess 5 of the disc-shaped element 3.

5 It will immediately be realized that by turning the turning handle 7, which in the embodiment shown comprises a handle extending substantially perpendicular to the shaft section 6, approx. 90° in the direction indicated by the arrow 19, the recess 5 in the disc-shaped element 3 will unimpededly

10 be releasable from engagement with the shaft section 6.

In a further embodiment shown in Fig. 3 of the second coupling member the shaft section 20 is mounted in a flat, substantially U-shaped fixture profile 21, which may be fastened directly on a frame or main frame member, which

15 makes this embodiment well suited for post-mounting on an existing window, irrespective of whether the electrically or manually controlled operator means is connected with a frame member or a main frame member.

Moreover, the shaft section 20 is in the embodiment according to Fig. 3 made such that on a part 23 of its length containing the local constriction 24 its longitudinal axis 25 is positioned eccentrically displaced relative to the rotational axis of the turning handle 22, the shaft section 20 thus getting a crank-like shape.

25 As shown in Fig. 4 by a-d this embodiment has the effect that in connection with the coupling of the two coupling parts in a situation, where, with closed window, they are disengaged with a view to opening of the window by establishing the engagement between the local constriction

30 24 on the eccentrically displaced part 23 of the shaft section 20 and the keyhole-like recess 5 in the disc-shaped element 3, a tight pull is created between the frame member and the main frame member under surmounting of the sealing pressure which is created by the compression of the sealing

35 element/s 27 and 28 fastened on the frame member and/or the main frame member.

Though the coupling device according to the invention

is described above only in connection with an electrically or manually controlled chain operator, the active parts of the coupling device, i.e. the first coupling member with the keyhole-shaped recess and the second coupling member with a shaft section containing a local constriction, it
5 may be used also in connection with other types of mechanical window operators just as the two coupling members by choice may be mounted on either a frame member or a main frame member.

THE EMBODIMENTS OF THE INVENTION IN WHICH AN EXCLUSIVE PROPERTY OR PRIVILEGE IS CLAIMED ARE DEFINED AS FOLLOWS:

1. A manually releasable coupling device for connecting an elongate operator means (2) with a frame or main frame member of a window, comprising a first coupling member (3) for connection with a free end of the operator means (2) facing said frame or main frame member and a second coupling member (6-10) designed for mounting in or on the frame or main frame member, characterized in that the first coupling member is a flat, disc-shaped element (3), which at one end portion is designed for connection with said free end of the operator means and which at an opposite end portion has a substantially keyhole-shaped recess (5) with a towards this portion open, constricted mouth (5a) in connection with a circular part (5b) of the recess, while the second coupling member comprises a shaft portion (6, 20) for mounting in a bore in the frame or main frame member or a fixture connected therewith perpendicular to the longitudinal direction of the frame or main frame member in connection with a turning handle (7, 22), said shaft section (6,20) having a local constriction (8,24) with substantially rectangular cross-section, which in one direction has a dimension (a) corresponding to the width of the mouth of the recess (5) in the first coupling member (3) and in a direction perpendicular thereto a dimension (b) corresponding to the diameter of the circular part (5b) of the recess, whereby said second coupling member also comprises means (9, 10) for holding said shaft section (6, 20) and turning handle (7, 22) onto the frame or main frame member.
2. A coupling device according to claim 1, characterized in that the shaft section (29) with associated turning handle (22) in the second coupling member is designed such that a part (23) of the shaft section containing said local constriction (24) has a longitudinal axis (25) positioned eccentrically displaced relative to the rotational axis (26) of the turning handle

(22).

3. A coupling device according to claims 1 or 2,
c h a r a c t e r i z e d in that the turning handle
(7,22) comprises a handle extending substantially
5 perpendicularly to the shaft section.

4. A coupling device according to claim 1,
c h a r a c t e r i z e d in that the second coupling
member is designed for direct mounting in a bore through
the frame or main frame member (15, 16) which is made as a
10 hollow element, and in that said holding means comprise a
fixture (10) to be fastened on a bottom wall of said hollow
profile (15) and provided with a guide for an end portion
of the shaft section positioned opposite the turning handle
(7, 22).

5. A coupling device according to claim 1, 2 or 3,
c h a r a c t e r i z e d in that the shaft section (20)
is mounted in a flat substantially U-shaped fixture profile
(21) for direct fastening on the frame or main frame
15 member.

6. A coupling device according to any one of claims 1
to 5, c h a r a c t e r i z e d in that the operator
means is an operator chain (2) for a chain operator built
into a main frame member of a window, said chain operator
comprising a housing (1) in which the operator chain (2) is
25 received in substantially its whole length in the closed
position of the window.

7. A pivotal window with a substantially rectangular
main frame and a frame substantially consisting of hollow
profile elements with a manual or electric chain operator
30 for opening of the window to a ventilation position,
c h a r a c t e r i z e d in that in a main frame member
(12) parallel with the axis of rotation of the pivotal
movement of the window a housing (1) for the chain operator
is built in, that its operator chain (2) which is passed
35 through an opening in the main frame member in direction
towards the oppositely positioned frame member (15, 16)
which at its free end is connected with an end portion of

a first coupling member shaped as a flat, disc-shaped element (3) which at an opposite end portion has a substantially keyhole-shaped recess (5) with a towards this portion open, constricted mouth (5a) in connection with a circular part (5b) of the recess, and in that a second coupling member is connected with the oppositely positioned frame member (15, 16), said coupling member comprising a shaft portion (6) for mounting in a bore in the frame member (15,16) or a fixture for fastening thereon and being perpendicular to the longitudinal direction of the frame member in connection with a turning handle (7), said shaft section (6) having a local constriction (8) with substantially rectangular cross-section, which in one direction has a dimension (a) corresponding to the width of the mouth (5a) of the recess (5) in the first coupling member (3) and in a direction perpendicular thereto a dimension (b) corresponding to the diameter of the circular part of the recess.




FIG. 1




FIG. 2




FIG. 3




FIG. 4

