

(12) **UK Patent Application** (19) **GB** (11) **2440217** (13) **A8**

(43) Date of A Publication

23.01.2008

(21) Application No: **0711554.6**

(22) Date of Filing: **14.06.2007**

(30) Priority Data:
(31) **11457613** (32) **14.07.2006** (33) **US**

(51) INT CL:
C10M 101/00 (2006.01) **C10M 109/00** (2006.01)
C10M 137/04 (2006.01) **C10N 10/10** (2006.01)
C10N 40/04 (2006.01) **C10N 40/25** (2006.01)

(52) UK CL (Edition X):
NOT CLASSIFIED

(71) Applicant(s):
Afton Chemical Corporation
(Incorporated in USA - Delaware)
500 Spring Street, Richmond, Virginia 23219,
United States of America

(56) Documents Cited:
GB 2416775 A **GB 2409462 A**
EP 1688476 A1 **EP 1657293 A2**
WO 2007/075831 A2 **WO 2002/064710 A3**
US 20060293193 A1

(72) Inventor(s):
John T Loper
Tze-Chi Jao
Mark T Devlin
Roger M Sheets
Gregory H Guinther

(58) Field of Search:
INT CL **C10M**
Other: **ONLINE - EPODOC, WPI**

(74) Agent and/or Address for Service:
Mathys & Squire LLP
120 Holborn, LONDON, EC1N 2SQ, United Kingdom

(54) Abstract Title: **Lubricant compositions**

(57) A lubricant composition comprising a phosphorus-containing compound and a base oil comprising less than about 3% by weight of tetracycloparaffins is disclosed. The aim is reduced thin-film friction and improved fuel economy. The phosphorus-containing compound may be e.g. amyl acid phosphate, neopentyl glycol phosphite or a salt thereof, or a phosphonate. A dispersant may also be present, e.g. a succinimide, a borated succinimide, a Mannich dispersant, a functionalized olefin copolymer or a poly(meth)acrylate copolymer. A friction modifier may also be present.

GB 2440217 A8