

(12) **Patent Application Publication** (10) **Pub. No.: US 2017/0112665 A1**
ANDINO et al. (43) **Pub. Date: Apr. 27, 2017**

(10) **Pub. No.:** US 2017/0112665 A1
(43) **Pub. Date:** Apr. 27, 2017

Publication Classification

(51) **Int. Cl.**

<i>A61F 9/00</i>	(2006.01)
<i>A61M 5/20</i>	(2006.01)
<i>A61M 5/48</i>	(2006.01)
<i>A61M 5/32</i>	(2006.01)
<i>A61M 5/46</i>	(2006.01)
<i>A61M 37/00</i>	(2006.01)
<i>A61J 1/20</i>	(2006.01)

(52) **U.S. Cl.**
CPC *A61F 9/0017* (2013.01); *A61M 37/0015*
(2013.01); *A61M 5/2053* (2013.01); *A61M*
5/2033 (2013.01); *A61J 1/2096* (2013.01);
A61J 1/2055 (2015.05); *A61J 1/201*
(2015.05); *A61M 5/3293* (2013.01); *A61M*
5/46 (2013.01); *A61M 5/482* (2013.01); *A61M*
2037/0023 (2013.01); *A61M 2037/0061*
(2013.01); *A61M 2210/0612* (2013.01)


(57) **ABSTRACT**

An apparatus includes a housing coupled to a medicament container, which is coupled to a needle. An injection assembly is disposed within the housing and includes an energy storage member and an actuation rod. A distal end portion of the actuation rod is disposed within the medicament container. The energy storage member can produce a force on a proximal end portion of the actuation rod sufficient to move the distal end portion of the actuation rod within the medicament container. This can convey at least a portion of a substance from the medicament container via the needle when a distal tip of the needle is disposed within a first region of a target location. The force is insufficient to move the distal end portion of the actuation rod within the medicament container when the distal tip of the needle is disposed within a second region of the target location.

(22) Filed: **Jan. 5, 2017**

Related U.S. Application Data

(60) Provisional application No. 61/953,147, filed on Mar. 14, 2014, provisional application No. 61/944,214, filed on Feb. 25, 2014, provisional application No. 61/827,371, filed on May 24, 2013, provisional application No. 61/819,052, filed on May 3, 2013, provisional application No. 61/819,048, filed on May 3, 2013.






Fig. 1

Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7





Fig. 8







Fig. 9



Q
Q
Q




Fig. 11

Fig. 12A




Fig. 12B





Fig. 12C








Fig. 14A




Fig. 14B




Fig. 15




Fig. 16A




Fig. 16B




Fig. 16C




Fig. 16D




Fig. 16E




Fig. 17




Fig. 18




Fig. 19





Fig. 20






Fig. 21

Fig. 22




Fig. 23A




Fig. 23B




Fig. 23C




Fig. 24A




Fig. 24B





Fig. 25






Fig. 26A




Fig. 26B

Fig. 27A





Fig. 27B









Fig. 29








Fig. 31C




Fig. 31A






Fig. 31B








Fig. 34




Fig. 35




Fig. 36




Fig. 37




Fig. 38




Fig. 39




Fig. 40A




Fig. 40B




Fig. 40C




Fig. 40D




Fig. 41A




Fig. 41B




Fig. 42A




Fig. 42C








Fig. 42B








Fig. 44A




Fig. 44B




Fig. 45A










Fig. 45B








Fig.55





Fig.54

Fig. 56






Fig. 58




Fig. 59




Fig. 60




Fig. 61




Fig. 62




Fig. 63




Fig. 64




Fig. 65




Fig. 66




Fig. 67




Fig. 68




Fig. 69




Fig. 70





Fig. 71






Fig. 72

Fig. 73




Fig. 74




Fig. 75





Fig. 76






Fig. 77

Fig. 78




Fig. 79




Fig. 80




Fig. 81




Fig. 82





Fig. 83







Fig. 85A




Fig. 85B




Fig. 86




Fig. 87




Fig. 88




Fig. 89A





Fig. 89B






Fig. 91




Fig. 92A




Fig. 92B




Fig. 93A




Fig. 93B




Fig. 93C




Fig. 94A




Fig. 94B




Fig. 95




Fig. 96




Fig. 97




Fig. 98A




Fig. 98B





Fig. 99



APPARATUS AND METHODS FOR OCULAR INJECTION

CROSS REFERENCE TO RELATED APPLICATIONS

[0001] This application is a continuation of U.S. patent application Ser. No. 14/268,687 entitled Apparatus and Methods for Ocular Injection, filed May 2, 2014, which claims priority to and benefit of U.S. Provisional Patent Application No. 61/953,147, entitled “Apparatus and Methods for Ocular Injection,” filed Mar. 14, 2014, U.S. Provisional Patent Application No. 61/944,214, entitled “Apparatus and Methods for Controlling the Insertion Depth of a Needle,” filed Feb. 25, 2014, U.S. Provisional Patent Application No. 61/827,371, entitled “Apparatus and Methods for Ocular Injection,” filed May 24, 2013, U.S. Provisional Patent Application No. 61/819,052, entitled “Apparatus and Methods for Delivering a Drug to Ocular Tissue,” filed May 3, 2013, and U.S. Provisional Patent Application No. 61/819,048, entitled “Apparatus and Methods for Controlling the Insertion Depth of a Needle,” filed May 3, 2013, the disclosures of each of which are incorporated herein by reference in their entirety.

BACKGROUND OF THE INVENTION

[0002] The embodiments described herein relate generally to the field of ophthalmic therapies and more particularly to the use of a microneedle for delivery and/or removal of a substance, such as a fluid therapeutic agent into and/or from ocular tissues for treatment of the eye.

[0003] Although needles are used in transdermal and intraocular drug delivery, there remains a need for improved microneedle devices and methods, particularly for delivery of substances (e.g., drugs) into the posterior region of the eye. Many inflammatory and proliferative diseases in the posterior region (or other regions) of the eye require long-term pharmacological treatment. Examples of such diseases include macular degeneration, diabetic retinopathy, and uveitis. It is often difficult to deliver effective doses of a drug to the back of the eye using conventional delivery methods such as topical application or an intravitreal administration (IVT), which has poor efficacy, and systemic administration, which often causes significant side effects. For example, while eye drops are useful in treating conditions affecting the exterior surface of the eye or tissues at the front of the eye, the eye drops are often not sufficiently conveyed to the back of the eye, as may be required for the treatment of some of the retinal diseases listed above.

[0004] Although there have been advances in the past decade regarding the utilization of systemically delivered substances, there are obstacles to wide spread adoption of such methods. For example, in certain situations, direct injection into the eye (e.g., into the vitreous) using conventional 27 gauge or 30 gauge needles and syringes can be effective. Direct injection, however, can be associated with significant safety risks, and physicians often require professional training to effectively perform such methods. Moreover, in some instances, targeted injection of a therapeutic agent is desirable. In such instances, however, the relatively small anatomic structures of the eye often result in significant challenges to placing a needle at a target location using known devices and methods, especially as they pertain to placing the distal end of the needle at the desired depth

within the eye. Furthermore, IVT administration can have side effects such as increased intraocular pressure or faster onset of cataract formation.

[0005] In addition, many known methods of direct injection of a drug into the eye include inserting a needle or a cannula at an acute angle relative to a surface of the eye, which can make controlling the depth of insertion challenging. For example, some such methods include controlling the angular orientation of the needle such that the injected substance exits the needle at a particular location. Moreover, some known methods of injecting substances into ocular tissue include using complicated visualization system or sensors to control the placement of the needle or cannula.

[0006] Known devices for ocular injection do not provide the mechanism for adjusting needle length so that the needle can be inserted into the eye to the desired depth. Known systems also do not provide a reliable mechanism for determining when the needle tip is in the desired location, for example, the suprachoroidal space (SCS) of the eye. Such shortcomings in known systems and methods are exacerbated because the size and thickness of various layers included in the eye can vary substantially from one person to another. For example, the thickness of the conjunctiva and the sclera can be substantially different and their true value cannot easily be predetermined via standard techniques. Furthermore, the thickness of these layers can also be different in different portions of the eye and at different times of the day in the same eye and location. Therefore, using known systems and methods it can be challenging to determine and/or adjust the length of the needle for puncturing the eye, such that a tip of the needle is at the desired depth, for example, the SCS. Too short a needle might not penetrate the sclera, and too long a needle can traverse beyond the SCS and damage the retina of the eye. Further, known systems do not provide a convenient way to detect the position of the needle tip within the eye.

[0007] Because of the sensitivities associated with intraocular injection (e.g., the sensitivity of the tissue, the potential impact on intraocular pressure and the like), many known systems involve manual injection. More particularly, many known devices and methods include the user manually applying a force (e.g., via pushing a plunger with their thumb or fingers) to expel a fluid (e.g., a drug) into the eye. Because of the small needle size and/or the characteristics of the injected drug, some such devices and methods involve the use of force levels higher than that which users are comfortable with applying. For example, some studies have shown that users generally do not like to apply more than 2N force against the eye during ocular injection. Accordingly, in certain situations a user may not properly deliver the medicament using known systems and methods because of their reluctance to apply the force to fully expel the medicament.

[0008] Moreover, injection into different target layers of the eye can cause variability in the amount of the force required for insertion of the needle and/or injection of the medicament. Different layers of the eye can have different densities. For example, the sclera generally has a higher density than the conjunctiva or the SCS. Differences in the density of the target region or layer can produce different backpressure against the needle exit, i.e., the tip of the needle from which the fluid emerges. Thus, injection into a relatively dense ocular material such as sclera requires more motive pressure to expel the medicament from the needle than is required when injecting a medicament into the SCS.

[0009] Furthermore, the injection force to expel the medicament also depends on the density and viscosity of the liquid medicament, length of the needle, and diameter of the needle. To inject certain medicaments into the eye via desired needles (e.g., 27 gauge, 30 gauge, or even smaller) can require more force than many practitioners are comfortable applying.

[0010] Intraocular injection can also lead to leakage of intraocular fluids (e.g., aqueous and vitreous humour) or the medicament from a delivery passageway formed by the needle penetrating into the ocular tissue. By way of example, if the medicament is delivered to the sclera instead of the target ocular tissue layer, for example, the SCS, the high backpressure of the sclera can force the medicament to leak from the insertion site. Known systems do not provide a convenient way to prevent leakage from insertion site, which can lead to discomfort and loss of medicament. This can prolong treatment as well as increase costs associated with the treatment.

[0011] Thus, a need exists for improved devices and methods, which can assist in determining if the needle is at the correct depth, can facilitate injection of the medicament into ocular tissue, and/or can prevent leakage of ocular fluids and/or medicament from the insertion site.

SUMMARY OF THE INVENTION

[0012] The embodiments described herein relate generally to the field of ophthalmic therapies and more particularly to the use of a microneedle for delivery and/or removal of a substance, such as a fluid therapeutic agent into and/or from ocular tissues for treatment of the eye.

[0013] In some embodiments, an apparatus includes a housing configured to be coupled to a medicament container. The medicament container is configured to be coupled to a needle. An injection assembly is disposed within the housing and includes an energy storage member and an actuation rod. A distal end portion of the actuation rod is configured to be disposed within the medicament container. The energy storage member is configured to produce a force on a proximal end portion of the actuation rod. The force is sufficient to move the distal end portion of the actuation rod within the medicament container to convey at least a portion of a substance from the medicament container via the needle when a distal tip of the needle is disposed within a first region of a target location. Furthermore, the force is insufficient to move the distal end portion of the actuation rod within the medicament container when the distal tip of the needle is disposed within a second region of the target location. In some embodiments, the first region of the target location has a first density and the second region of the target location has a second density, higher than the first density. In some embodiments, the first region of the target location produces a first backpressure and the second region of the target location produces a second backpressure, higher than the first backpressure.

[0014] In some embodiments, an apparatus includes a housing configured to receive a portion of a medicament container, and an adjustment member. A proximal end portion of the adjustment member is configured to be coupled to the medicament container. A distal end portion of the adjustment member is coupled to a needle. The adjustment member is movably disposed within the housing such that when the adjustment member is rotated relative to the housing, the needle is moved through a plurality of discrete

increments along a longitudinal axis of the housing. In some embodiments, the adjustment member defines a lumen configured to place the medicament container in fluid communication with the needle.

[0015] In some embodiments, an apparatus includes a hub configured to be coupled to a medical injector. The hub defines a passageway configured to receive a needle there-through. The hub has a convex distal end surface that is configured to contact a target surface of a target tissue when a substance is conveyed through the needle into the target tissue. In some embodiments, the distal end surface includes a sealing portion configured to define a substantially fluid-tight seal with the target surface when the distal end surface is in contact with the target surface. In such embodiments, the sealing portion can be symmetrical about the centerline of the passageway.

BRIEF DESCRIPTION OF THE DRAWINGS

[0016] FIG. 1 is a cross-sectional view of an illustration of the human eye.

[0017] FIG. 2 is a cross-sectional view of a portion of the human eye of FIG. 1 taken along the line 2-2.

[0018] FIGS. 3 and 4 are cross-sectional views of a portion of the human eye of FIG. 1 taken along the line 3-3, illustrating the suprachoroidal space without and with, respectively, the presence of a fluid.

[0019] FIG. 5 is a schematic illustration of an apparatus that includes a housing and an injection assembly in a first configuration, according to an embodiment.

[0020] FIG. 6 shows the apparatus of FIG. 5 in a second configuration, according to an embodiment.

[0021] FIG. 7 is a perspective view of a system for delivering a medicament to an eye, according to an embodiment.

[0022] FIG. 8 is an exploded view of the system shown in FIG. 7.

[0023] FIG. 9 is a perspective view of a system for delivering a medicament to an eye that includes an injector assembly, according to an embodiment.

[0024] FIG. 10 shows the system of FIG. 9 with a first portion of a housing removed to show the injector assembly.

[0025] FIG. 11 shows an exploded view of the system of FIG. 10.

[0026] FIG. 12A shows a side view, FIG. 12B shows a front view, and FIG. 12C shows a top view of an actuating member included in the system of FIG. 9.

[0027] FIG. 13A shows a side view, FIG. 13B shows a front view, and FIG. 13C shows a top view of a pawl included in the system of FIG. 9.

[0028] FIG. 14A shows a side view of an actuator included in the system of FIG. 9. FIG. 14B shows a side cross-section view of the actuator of FIG. 14A taken along the line 14B-14B.

[0029] FIG. 15 shows a side view of a guide rod included in the system of FIG. 9.

[0030] FIGS. 16A-E shows side views of the system of FIG. 9 with a first portion of the housing removed, the system shown in various states of operation.

[0031] FIG. 17 show a flow diagram of a method for determining the insertion depth in a target tissue of a needle included in a medicament delivery device using an injection assembly, according to an embodiment.

[0032] FIG. 18 show a flow diagram of a method for assisting a user in determining the insertion depth in a target

tissue of a needle included in a medicament delivery device, and assisting the user in medicament delivery using an injection assembly, according to an embodiment.

[0033] FIG. 19 shows a schematic illustration of a medical injector that includes an adjustment member in a first configuration, according to an embodiment.

[0034] FIG. 20 shows the medical injector of FIG. 19 in a second configuration.

[0035] FIG. 21 shows a perspective view of a system for delivering a medicament to an eye that includes a needle assembly, according to an embodiment.

[0036] FIG. 22 shows an exploded view of the needle assembly included in the system of FIG. 21.

[0037] FIG. 23A, shows a top view, FIG. 23B shows a side view, and FIG. 23C shows a side cross-section view (taken along the line 23C-23C) of a housing of the needle assembly of FIG. 22.

[0038] FIG. 24A shows a side view and FIG. 24B shows a top view of a plug included in the needle assembly of FIG. 22.

[0039] FIG. 25 shows a perspective view of an adjustment member, a lead screw and a puncturing member included in the needle assembly of FIG. 22.

[0040] FIG. 26A shows a side view of the adjustment member included in the needle assembly of FIG. 22. FIG. 26B shows a side cross-section of the adjustment member of FIG. 26A taken along the line 26B-26B.

[0041] FIG. 27A shows a side view of the lead screw included in the needle assembly of FIG. 22. FIG. 27B shows a cross-section view of the lead screw of FIG. 27A taken along the line 27B-27B.

[0042] FIG. 28A shows a side view and FIG. 28B shows a front view of a bushing included in the needle assembly of FIG. 22. FIG. 28C shows a cross-section view of the bushing of FIG. 28A taken along the line 28C-28C.

[0043] FIG. 29 shows a side view of a locking pin included in the needle assembly of FIG. 22.

[0044] FIG. 30A shows a side view and FIG. 30B shows a front view of a tab coupled to the locking pin included in the needle assembly of FIG. 22. FIG. 30C shows a cross-section view of the tab of FIG. 30A taken along the line 30C-30C.

[0045] FIG. 31A shows a side view and FIG. 31B shows a front view of a hub included in the needle assembly of FIG. 22, according to an embodiment. FIG. 31C shows a cross-section view of the hub of FIG. 31A taken along the line 31C-31C.

[0046] FIG. 32 shows a perspective view of the needle assembly of FIG. 22.

[0047] FIG. 33 shows a side cross-section view of the needle assembly of FIG. 32 taken along the line 33-33.

[0048] FIG. 34 is a cross-sectional view of a portion of a delivery device according to an embodiment.

[0049] FIG. 35 is an enlarged portion of the eye identified in FIG. 1 as region Z and the portion of the delivery device of FIG. 34 in use, in a first configuration.

[0050] FIG. 36 is the enlarged portion of the eye identified in FIG. 1 as region Z and the portion of the delivery device of FIG. 34 in use, in a second configuration.

[0051] FIG. 37 is a cross-sectional view of a portion of a delivery device according to an embodiment.

[0052] FIG. 38 is a cross-sectional view of a portion of a delivery device according to an embodiment.

[0053] FIG. 39 shows a schematic illustration of a system for delivering a medicament to an eye that includes a hub including a sealing portion, according to an embodiment.

[0054] FIG. 40A shows a distal end surface of a hub included in the system of FIG. 39 in contact with a conjunctiva of an eye and a puncturing member included in the system of FIG. 39 inserted into the sclera of the eye. FIG. 40B shows the distal end of the hub compressing the conjunctiva, FIG. 40C shows the hub further compressing the conjunctiva, and the distal end of the puncturing member is disposed in proximity of a suprachoroidal space of the eye and is delivering a medicament to the suprachoroidal space, such that the sealing portion forms a substantially fluid tight seal with the conjunctiva. FIG. 40D shows an angle θ formed between a centerline of a delivery passageway formed by the insertion of the puncturing member into the sclera of the eye and a surface line tangent to the conjunctiva.

[0055] FIG. 41A shows a finite element analysis (FEA) model of the hub of FIG. 40 A-D, pressed against the conjunctiva of an eye with a 1N force. FIG. 41B shows an enlarged view of a portion shown by the arrow 41B shown in FIG. 41A.

[0056] FIG. 42A shows a side view and FIG. 42B shows a front view of a hub that includes a convex distal end, according to an embodiment. FIG. 42C shows a cross-section view of the hub of FIG. 42A taken along the line 42C-42C.

[0057] FIG. 43A shows a side view and FIG. 43B shows a front view of a hub that includes a convex distal end, according to an embodiment. FIG. 43C shows a cross-section view of the hub of FIG. 43A taken along the line 43C-43C.

[0058] FIG. 44A-B show schematic illustrations of a hub included in a medicament delivery system in a first configuration and a second configuration respectively, according to an embodiment.

[0059] FIGS. 45A and 45B are schematic illustrations of a portion of a delivery device according to an embodiment.

[0060] FIGS. 46 and 47 are perspective views of a portion of a delivery device according to an embodiment.

[0061] FIG. 48 is a perspective view of a portion of a delivery device according to an embodiment.

[0062] FIG. 49 is a perspective view of a portion of a delivery device according to an embodiment.

[0063] FIG. 50 is a perspective view of a portion of a delivery device according to an embodiment.

[0064] FIG. 51 is a perspective view of a portion of a delivery device according to an embodiment.

[0065] FIG. 52 is a perspective view of a portion of a delivery device according to an embodiment.

[0066] FIG. 53 is a perspective view of a portion of a delivery device according to an embodiment.

[0067] FIG. 54 is a perspective view of a portion of a delivery device being used to facilitate an ocular injection, according to an embodiment.

[0068] FIG. 55 is a cross-sectional view of the portion of the delivery device shown in FIG. 54.

[0069] FIG. 56 shows a perspective view of a delivery device, according to an embodiment.

[0070] FIG. 57 shows an exploded view of the delivery device shown in FIG. 56.

[0071] FIG. 58 shows a perspective view of an actuator rod included in the delivery device of FIG. 56.

[0072] FIG. 59 shows a top perspective view of a plug included in the delivery device of FIG. 56.

[0073] FIG. 60 shows a bottom perspective view of the plug of FIG. 59.

[0074] FIG. 61 shows a top perspective view of an actuator included in the delivery device of FIG. 56.

[0075] FIG. 62 shows a side cross-section view of the actuator of FIG. 61, taken along the line 62-62 shown in FIG. 61.

[0076] FIG. 63 shows a top perspective view of a medicament containment chamber included in the delivery device of FIG. 56.

[0077] FIG. 64 shows a bottom perspective view of the medicament containment chamber of FIG. 63.

[0078] FIG. 65 shows a side cross-section view of the medicament containment chamber of FIG. 63 taken along the line 65-65 shown in FIG. 63.

[0079] FIG. 66 shows a top perspective view of a hub included in the delivery device of FIG. 56.

[0080] FIG. 67 shows a side cross-section view of the hub of FIG. 66 taken along the line 67-67 shown in FIG. 66.

[0081] FIG. 68 shows a top perspective view of a cap included in the delivery device of FIG. 56.

[0082] FIG. 69 shows a side cross-section view of the cap of FIG. 68 taken along the line 69-69 shown in FIG. 68.

[0083] FIGS. 70 and 71 show side cross-section views of the delivery device of FIG. 56 in a first configuration and a second configuration, respectively.

[0084] FIG. 72 shows a perspective view of an injection marker that can be included in a delivery system, according to an embodiment.

[0085] FIG. 73 shows the injection marker of FIG. 72 being used to mark an injection site on an eye.

[0086] FIG. 74 shows a perspective view of a delivery device and an extraction member configured to be coupled to the delivery device, according to an embodiment.

[0087] FIG. 75 shows a perspective view of the delivery device of FIG. 74 with the extraction member coupled thereto.

[0088] FIG. 76 shows a side cross-section view of the extraction member of FIG. 74.

[0089] FIG. 77 shows a perspective view of the delivery device of FIG. 75 and a medicament vial, the extraction member configured to be coupled to the vial.

[0090] FIG. 78 shows a side cross-section view of the extraction member and vial of FIG. 77 in an uncoupled configuration.

[0091] FIG. 79 shows the extraction member of the delivery device of FIG. 77 coupled to the vial.

[0092] FIG. 80 shows a side cross-section view of the extraction member and vial of FIG. 79 in a coupled configuration.

[0093] FIG. 81 shows a system for delivering a medicament to an eye, according to an embodiment, in a first configuration.

[0094] FIG. 82 shows an enlarged view of a portion of the system of FIG. 81 shown by the arrow 82 in FIG. 81.

[0095] FIG. 83 shows a perspective view of the system of FIG. 81 in a second configuration.

[0096] FIGS. 84A-B shows a schematic illustration of a delivery device that includes a mechanism to adjust the length of an insertion depth of a needle included in the delivery device in a first configuration and a second configuration respectively, according to an embodiment.

[0097] FIGS. 85A-B shows a schematic illustration of a delivery device that includes an injection assist assembly in a first configuration and a second configuration respectively, according to an embodiment.

[0098] FIG. 86 shows a schematic illustration of a delivery device that includes an adjustment member, according to an embodiment.

[0099] FIG. 87 shows a schematic illustration of a delivery device that includes an injection assembly, according to an embodiment.

[0100] FIG. 88 shows a schematic illustration of a portion of a delivery device that includes an adjustment member, according to an embodiment.

[0101] FIGS. 89A-B show schematic illustrations of a portion of a delivery device that includes an adjustment member in a first configuration and a second configuration respectively, according to an embodiment.

[0102] FIGS. 90A-C show schematic illustrations of a delivery device that includes a needle assembly in a first, second and third configuration, according to an embodiment.

[0103] FIG. 91 shows a schematic illustration of a delivery device that includes a needle assembly and an adjustment member, according to an embodiment.

[0104] FIG. 92A shows a perspective view and FIG. 92B shows a side cross-section view of a delivery device that includes a hub, according to an embodiment.

[0105] FIG. 93A shows a perspective view of a delivery device that includes a hub, according to an embodiment. FIG. 93B-C show side cross-section views of the delivery device of FIG. 93A in a first configuration and a second configuration.

[0106] FIG. 94A-B show schematic illustrations of a needle configured to communicate light inserted a first distance within ocular tissues and a second distance within the ocular tissue respectively, according to an embodiment.

[0107] FIG. 95 shows a speculum configured to position a delivery device for ocular injection into an eye, according to an embodiment.

[0108] FIG. 96 shows a speculum that includes markings for sizing an eye, according to an embodiment.

[0109] FIG. 97 shows a speculum that includes a mount configured to receive a mounting portion included in a delivery device and position the delivery device for ocular injection into an eye, according to an embodiment.

[0110] FIG. 98A shows a perspective view of a one-piece speculum, and FIG. 98B shows the speculum of FIG. 98A disposed on an eye and delivery device coupled thereto, according to an embodiment.

[0111] FIG. 99 shows a flow diagram of a method of injecting a substance into an eye using a medical injector that includes a hub such that a convex distal end of the hub forms a seal with a target surface to fluidically isolate a delivery passageway, according to an embodiment.

DETAILED DESCRIPTION OF THE INVENTION

[0112] The embodiments described herein relate to systems and devices for delivering a fluid (e.g., a drug) or extracting a fluid into the sclera of an eye. Furthermore, embodiments described herein are related to systems, devices, and methods to assist in the insertion of a delivery member, for example, a needle or microneedle into the eye, and/or assist in injecting a medicament into a target ocular tissue. Embodiments described herein are also related to

systems, devices, and methods for controlling the insertion depth of a delivery member, such as, for example, a microneedle, into the eye to deliver a therapeutic agent to, for example, a posterior region of the eye (e.g., via the suprachoroidal space). Embodiments, described herein are also related to systems, devices and methods to form a substantially fluid-tight seal around a delivery passageway formed by insertion of a delivery member, for example, a microneedle, into the eye to prevent leakage of the substance and/or ocular fluid from the insertion site.

[0113] In some embodiments, the microneedles included in the embodiments described herein include a bevel, which allows for ease of penetration into the sclera and/or suprachoroidal space with minimal collateral damage. Moreover, in some embodiments, the micro needles disclosed herein can define a narrow lumen (e.g., gauge size greater than or equal to 30 gauge, 32 gauge, 34 gauge, 36 gauge, etc.) to allow for suprachoroidal drug delivery while minimizing the diameter of the needle track caused by the insertion of the microneedle. In some embodiments, the lumen and bevel aspect ratio of the microneedles described herein are distinct from standard 27 gauge and 30 gauge needles, which are now commonly used for intraocular injection. For example, the microneedles included in the embodiments described herein can be any of those described in International Patent Application Publication No. WO2014/036009, entitled, "Apparatus and Methods for Drug Delivery Using Microneedles," filed on Aug. 27, 2013, the disclosure of which is incorporated by reference herein in its entirety (referred to henceforth as the "'009 PCT application").

[0114] In some embodiments, an apparatus includes a housing configured to be coupled to a medicament container. The medicament container is configured to be coupled to a needle. An injection assembly is disposed within the housing and includes an energy storage member and an actuation rod. A distal end portion of the actuation rod is configured to be disposed within the medicament container. The energy storage member is configured to produce a force on a proximal end portion of the actuation rod. The force is sufficient to move the distal end portion of the actuation rod within the medicament container to convey at least a portion of a substance from the medicament container via the needle when a distal tip of the needle is disposed within a first region of a target location. Furthermore, the force is insufficient to move the distal end portion of the actuation rod within the medicament container when the distal tip of the needle is disposed within a second region of the target location. In some embodiments, the first region of the target location has a first density and the second region of the target location has a second density, higher than the first density. In some embodiments, the first region of the target location produces a first backpressure and the second region of the target location produces a second backpressure, higher than the first backpressure.

[0115] In some embodiments, an apparatus includes a housing configured to receive at least a portion of a medicament container. The medicament container is configured to be coupled to a needle. An injection assembly is disposed within the housing. The injection assembly includes an energy storage member, an actuation rod, and a release member. A distal end portion of the actuation rod is configured to be disposed within the medicament container. The release member is configured to maintain a position of the actuation rod relative to the housing when the release

member is in a first position such that the movement of the housing relative to the medicament container moves the distal end portion of the actuation rod within the medicament container. The release member is configured to release the actuation rod when moved from the first position to a second position such that a force produced by the energy storage member moves the distal end portion of the actuation rod relative to the housing within the medicament container. This conveys at least a portion of a substance from the medicament container via the needle. In some embodiments, the force is sufficient to move the distal end portion of the actuation rod within the medicament container when a distal tip of the needle is disposed within a first region of a target location. The force however, is insufficient to move the distal end portion of the actuation rod within the medicament container when the distal tip of the needle is disposed within a second region of the target location.

[0116] In some embodiments, a method includes inserting a distal tip of a needle of a medical injector, which includes a medicament container and an injection assembly, a first distance into a target tissue. The medicament container is in fluid communication with the needle. The injection assembly includes an actuation rod and an energy storage member that is configured to produce a force on a proximal end portion of the actuation rod. The method further includes releasing the actuation rod of the injection assembly to allow a distal end portion of the actuation rod to move within the medicament container in response to the force. Finally, the method includes inserting, after releasing, the distal tip of the needle of the medical injector a second distance into the target tissue if the distal end portion of the actuation rod moves less than a threshold injection distance within the medicament container in response to the force, the second distance greater than the first distance. In some embodiments, the distal end portion of the actuation rod moves a first injection distance within the medicament container in response to the force. In such embodiments, the method can further include moving the injection assembly relative to the medicament container to move the distal end portion of the actuation rod a second injection distance, greater than the first injection distance, within the medicament container.

[0117] In some embodiments, an apparatus includes a housing configured to receive a portion of medicament container and an adjustment member. A proximal end portion of the adjustment member is configured to be coupled to the medicament container. A distal end portion of the adjustment member is coupled to a needle. The adjustment member is movably disposed within the housing such that when the adjustment member is rotated relative to the housing, the needle is moved through a plurality of discrete increments along a longitudinal axis of the housing. In some embodiments, the adjustment member defines a lumen configured to place the medicament container in fluid communication with the needle.

[0118] In some embodiments, an apparatus includes a housing configured to receive a portion of a medicament container and an adjustment member. A proximal end portion of the adjustment member is configured to be coupled to the medicament container. A distal end portion of the adjustment member is coupled to a needle. The adjustment member defines a plurality of detents such that a protrusion of the housing is configured to be removably disposed within each detent from the plurality of detents when the adjustment member is moved relative to the housing to

move the needle relative to the housing through a plurality of discrete increments. In some embodiments, the protrusion can be a bearing movably coupled within the housing. In such embodiments, the bearing is configured to be removably disposed within each detent from the plurality of detents when the adjustment member is moved relative to the housing to move the needle through the plurality of discrete increments. Furthermore, the apparatus can also include a bias member configured to maintain the bearing within a detent from the plurality of detents.

[0119] In some embodiments, an apparatus includes a hub configured to be coupled to a medical injector. The hub defines a passageway configured to receive a needle there-through. The hub has a convex distal end surface, which is configured to contact a target surface of a target tissue when a substance is conveyed through the needle into the target tissue. In some embodiments, the distal end surface includes a sealing portion configured to define a substantially fluid-tight seal with the target surface when the distal end surface is in contact with the target surface.

[0120] In some embodiments, a method includes inserting a distal end portion of a needle of a medical injector into a target tissue to define a delivery passageway within the target tissue. This is followed by placing a convex distal end surface of a hub of the medical injector into contact with a target surface of the target tissue to fluidically isolate the delivery passageway. Next, the method includes conveying, after the placing, a substance into the target tissue via the needle. In some embodiments, the target tissue is an eye and the target surface is the conjunctiva of the eye. In some embodiments, the delivery passageway extends through a sclera of the eye and the conveying includes conveying the substance into at least one of a suprachoroidal space or lower portion of the sclera. In such embodiments, the method can further include adjusting, before the conveying, a length of the needle extending from the distal end surface of the hub.

[0121] In some embodiments, a method includes inserting a distal end portion of a needle of a medical injector into a target tissue to define a delivery passageway within the target tissue. The inserting is performed such that a centerline of the needle is substantially normal to a target surface of the target tissue. This is followed by placing a distal end surface of a hub of the medical injector into contact with a target surface of the target tissue to fluidically isolate the delivery passageway. Next, the method includes conveying, after the placing, a substance into the target tissue via the needle. In some embodiments, the delivery is performed such that a centerline of the delivery passageway and a surface line tangent to the target surface defines an angle of entry of between about 75 degrees and about 105 degrees.

[0122] As used herein, the singular forms “a,” “an,” and “the” include plural referents unless the context clearly dictates otherwise. Thus, for example, the term “a member” is intended to mean a single member or a combination of members, “a material” is intended to mean one or more materials, or a combination thereof.

[0123] As used herein, the words “proximal” and “distal” refer to the direction closer to and away from, respectively, an operator (e.g., surgeon, physician, nurse, technician, etc.) who would insert the medical device into the patient, with the tip-end (i.e., distal end) of the device inserted inside a patient’s body first. Thus, for example, the end of a microneedle described herein first inserted inside the patient’s body would be the distal end, while the opposite

end of the microneedle (e.g., the end of the medical device being manipulated by the operator) would be the proximal end of the microneedle.

[0124] As used herein, a “set” can refer to multiple features or a singular feature with multiple parts. For example, when referring to set of walls, the set of walls can be considered as one wall with distinct portions, or the set of walls can be considered as multiple walls.

[0125] As used herein, the terms “about” and “approximately” generally mean plus or minus 10% of the value stated. For example, about 0.5 would include 0.45 and 0.55, about 10 would include 9 to 11, about 1000 would include 900 to 1100.

[0126] As used herein, the terms “delivery member”, “puncture member”, and “puncturing member” are used interchangeably to refer to an article configured to pierce tissue layers and deliver a substance to a target tissue layer, for example, a needle or a microneedle.

[0127] As used herein, the terms “medicament container”, and “medicament containment chamber” are used interchangeably to refer to an article configured to contain a volume of a substance, for example, a medicament.

[0128] The term “fluid-tight” is understood to encompass both a hermetic seal (i.e., a seal that is gas-impervious) as well as a seal that is liquid-impervious. The term “substantially” when used in connection with “fluid-tight,” “gas-impervious,” and/or “liquid-impervious” is intended to convey that, while total fluid imperviousness is desirable, some minimal leakage due to manufacturing tolerances, or other practical considerations (such as, for example, the pressure applied to the seal and/or within the fluid), can occur even in a “substantially fluid-tight” seal. Thus, a “substantially fluid-tight” seal includes a seal that prevents the passage of a fluid (including gases, liquids and/or slurries) therethrough when the seal is maintained at a constant position and at fluid pressures of less than about 5 psig, less than about 10 psig, less than about 20 psig, less than about 30 psig, less than about 50 psig, less than about 75 psig, less than about 100 psig and all values in between. Similarly, a “substantially liquid-tight” seal includes a seal that prevents the passage of a liquid (e.g., a liquid medicament) therethrough when the seal is maintained at a constant position and is exposed to liquid pressures of less than about 5 psig, less than about 10 psig, less than about 20 psig, less than about 30 psig, less than about 50 psig, less than about 75 psig, less than about 100 psig and all values in between.

[0129] The embodiments and methods described herein can be used to treat, deliver substances to and/or aspirate substances from, various target tissues in the eye. For reference, FIGS. 1-4 are a various views of a human eye 10 (with FIGS. 2-4 being cross-sectional views). While specific regions are identified, those skilled in the art will recognize that the proceeding identified regions do not constitute the entirety of the eye 10, rather the identified regions are presented as a simplified example suitable for the discussion of the embodiments herein. The eye 10 includes both an anterior segment 12 (the portion of the eye in front of and including the lens) and a posterior segment 14 (the portion of the eye behind the lens). The anterior segment 12 is bounded by the cornea 16 and the lens 18, while the posterior segment 14 is bounded by the sclera 20 and the lens 18. The anterior segment 12 is further subdivided into the anterior chamber 22, between the iris 24 and the cornea 16, and the posterior chamber 26, between the lens 18 and

the iris **24**. The cornea **16** and the sclera **20** collectively form a limbus **38** at the point at which they meet. The exposed portion of the sclera **20** on the anterior segment **12** of the eye is protected by a clear membrane referred to as the conjunctiva **45** (see e.g., FIGS. **2** and **3**). Underlying the sclera **20** is the choroid **28** and the retina **27**, collectively referred to as retinachoroidal tissue. A vitreous humour **30** (also referred to as the “vitreous”) is disposed between a ciliary body **32** (including a ciliary muscle and a ciliary process) and the retina **27**. The anterior portion of the retina **27** forms an ora serrata **34**. The loose connective tissue, or potential space, between the choroid **28** and the sclera **20** is referred to as the suprachoroid. FIG. **2** illustrates the cornea **16**, which is composed of the epithelium **40**, the Bowman’s layer **41**, the stroma **42**, the Descemet’s membrane **43**, and the endothelium **44**. FIG. **3** illustrates the sclera **20** with surrounding Tenon’s Capsule **46** or conjunctiva **45**, suprachoroidal space **36**, choroid **28**, and retina **27**, substantially without fluid and/or tissue separation in the suprachoroidal space **36** (i.e., in this configuration, the space is “potential” suprachoroidal space). As shown in FIG. **3**, the sclera **20** has a thickness between about 500 μm and 700 μm . FIG. **4** illustrates the sclera **20** with the surrounding Tenon’s Capsule **46** or the conjunctiva **45**, suprachoroidal space **36**, choroid **28**, and retina **27**, with fluid **50** in the suprachoroidal space **36**.

[0130] As used herein, the term “suprachoroidal space,” or SCS which is synonymous with suprachoroid, or suprachoroidia, describes the space (or volume) and/or potential space (or potential volume) in the region of the eye **10** disposed between the sclera **20** and choroid **28**. This region primarily is composed of closely packed layers of long pigmented processes derived from each of the two adjacent tissues; however, a space can develop in this region because of fluid or other material buildup in the suprachoroidal space and the adjacent tissues. The suprachoroidal space can be expanded by fluid buildup because of some disease state in the eye or because of some trauma or surgical intervention. In some embodiments, the fluid buildup is intentionally created by the delivery, injection and/or infusion of a drug formulation into the suprachoroid to create and/or expand further the suprachoroidal space **36** (i.e., by disposing a drug formulation therein). This volume may serve as a pathway for uveoscleral outflow (i.e., a natural process of the eye moving fluid from one region of the eye to the other through) and may become a space in instances of choroidal detachment from the sclera.

[0131] The dashed line in FIG. **1** represents the equator of the eye **10**. In some embodiments, the insertion site of any of the microneedles and/or methods described herein is between the equator and the limbus **38** (i.e., in the anterior portion **12** of the eye **10**). For example, in some embodiments, the insertion site is between about two millimeters and 10 millimeters (mm) posterior to the limbus **38**. In other embodiments, the insertion site of the microneedle is at about the equator of the eye **10**. In still other embodiments, the insertion site is posterior the equator of the eye **10**. In this manner, a drug formulation can be introduced (e.g., via the microneedle) into the suprachoroidal space **36** at the site of the insertion and can flow through the suprachoroidal space **36** away from the site of insertion during an infusion event (e.g., during injection).

[0132] In some embodiments, a system for ocular injection can include a medicament container at least a portion of

which is disposed in a housing that includes an injection assembly. The injection assembly can facilitate delivery of a substance disposed in a medicament container to a target tissue, for example, the SCS. For example, FIGS. **5-6**, show a system **100**, according to an embodiment. The system **100** includes a housing **110**, an injection assembly **111**, a medicament container **130**, and a needle **140**, in a first configuration and a second configuration, respectively. The system **100** can be configured to deliver a medicament to region and/or a layer of a target location, for example, an eye of a patient, (e.g., to the SCS of the eye), as described herein.

[0133] The housing **110** is configured to be coupled to the medicament container **130**, and the medicament container **130** is configured to be coupled to the needle **140**. For example, in some embodiments, at least a portion of the medicament container **130** can be disposed within an internal volume defined by the housing **110**. In some embodiments, the medicament container **130** can be slidably disposed within the housing **110**. The housing **110** can be a monolithic housing or include two or more portions which can be joined together to form the housing **110**. As shown, the housing **110** defines an internal volume within which the injection assembly **111** is disposed. Mounting features, for example, mounts, notches, grooves, indents, guide rods, slots, or any other suitable mounting features can be disposed in the interval volume defined by the housing **110** configured to secure at least a portion of the components included in the injection assembly **111**.

[0134] The injection assembly **111** includes an energy storage member **146** and an actuation rod **120**. In some embodiments, the energy storage member **146** can be a spring, for example, helical spring, compression, extension, spring washers, Belleville washer, tapered, any other type of spring. In other embodiments, the energy storage member **146** can include a compressed gas container, or a container containing a propellant. The energy storage member **146** is operatively coupled to a proximal end portion **122** of the actuation rod **120**, and produces a force on the proximal end portion **122** of the actuation rod **120**.

[0135] A distal end portion **124** of the actuation rod **120** is disposed within the medicament container **130**. The distal end portion **124** can be coupled to and/or in contact with a plug **128** which is in fluidic communication with a substance M (e.g., a medicament such as, for example, VEGF, a VEGF inhibitor, a combination thereof, or any other medicament described herein) disposed within an internal volume defined by the medicament container **130**. The distal end portion **124** of the actuation rod **120** is configured to be displaced within the internal volume defined by the medicament container **130**, for example, due to the force produced by the energy storage member **146**, as described herein. In this manner, the actuation rod **120** can displace the plug **128** within the medicament container **130** to draw in or expel the substance M from the distal tip **142** of the needle **140**, as described herein. The sidewalls of the plug **128** can be configured to contact the sidewalls of the medicament container **130** such that the plug **128** forms a substantially fluid-tight seal with the side wall of the medicament container **130**, for example, to prevent leakage of the substance M. The plug **128** can be made of an inert and/or biocompatible material which is rigid but soft. Example materials include rubber, silicone, plastic, polymers, any other suitable

material or combination thereof. In some embodiments, the plug **128** can be monolithically formed with the actuation rod **120**.

[0136] The needle **140** can be coupled to the medicament container **130** using any suitable coupling features, for example, Luer connectors, threads, snap-fit, latch, lock, friction fit, or any other suitable coupling features. The needle **140** can include any suitable needle described herein, for example, a micro needle (e.g., a 27 gauge, 30 gauge, or even smaller needle). The distal tip **142** of the needle **140** can define a sharp tip such that the needle **140** is configured to pierce a target location T, for example, a bodily tissue (e.g., ocular tissue). In this manner, the distal tip **142** can be disposed within a first region R1 and/or a second region R2 of the target location T, as described herein. The needle **140** defines a lumen **141**, which is in fluidic communication with the substance M disposed within the internal volume defined by the medicament container **130**. In this manner, the needle **140** is configured to establish fluid communication between the medicament container **130** and the target location T, for example, the first region R1 of the target location T, as described herein. In some embodiments, the first region R1 of the target location T can have a first density and the second region R2 can have a second density, which is higher than the first density. In some embodiments, the first region R1 of the target location T produces a first backpressure on the distal tip **142** of the needle **140**, and the second region R2 produces a second backpressure on the distal tip **142** of the needle **140**, which is higher than the first backpressure. In other words, the first region R1 of the target location T produces a first pressure that resists and/or opposes flow from the distal tip **142** of the needle **140**, and the second region R2 produces a second pressure that resists and/or opposes flow from the distal tip **142** of the needle **140**, which is higher than the first pressure. In some embodiments, the target location T can be an eye such that the first region R1 is a suprachoroidal space of the eye, and the second region R2 is a sclera of the eye.

[0137] The force produced on the proximal end portion **122** of the actuation rod **120** by the energy storage member **146** can be sufficient to move the distal end portion **124** of the actuation rod **120** within the medicament container **130** to convey at least a portion of the substance M from the medicament container **130** via the needle **140** when the distal tip **142** of the needle **140** is disposed within the first region R1 (e.g., an SCS of the eye) of the target location T. Furthermore, the force can be insufficient to move the distal end portion **124** of the actuation rod **120** within the medicament container **130** when the distal tip **142** of the needle **140** is disposed within the second region R2 (e.g., the sclera of the eye) of the target location T. Said another way, the injection assembly **111** can be configured to assist a user in delivering at least a portion of the substance M to the region R1, while be configured or “calibrated” to limit and/or prevent delivery to the region R2. In some embodiments, the injection assembly **111** can be configured to inform the user when the distal tip **142** of the needle **140** is in the target region of the target location T, for example, the region R1, such that the substance M can be delivered to the target region with high confidence.

[0138] Expanding further, FIG. 5 shows the apparatus **100** in the first configuration in which the distal tip **142** of the needle **140** is disposed in the second region R2. When the apparatus is actuated, the energy storage member **146** exerts

a force in a direction shown by the arrow F on the proximal end portion **122** of the actuation rod **120**. The force F exerted, however, is insufficient to move the distal end portion **124** of the actuation rod **120** within the medicament container **130**. For example, the second region R2 (e.g., the sclera of the eye) can produce a second backpressure which overcomes the force F, thereby preventing and/or limiting delivery of the substance M to the second region R2. In other words, the apparatus **100** is specifically configured or “calibrated” such that the force F is insufficient to convey the substance M to the second region R2.

[0139] In the second configuration shown in FIG. 6, the distal tip **142** of the needle is now disposed in the first region R1 (e.g., the SCS of the eye). Because of the anatomical differences and/or the differences in material properties between the first region R1 and the second region R2, the force F is sufficient to move the distal end portion **124** of the actuation rod **120** an injection distance within the medicament container **130**. For example, the force F can be sufficient to overcome a first backpressure produced by the first region R1. In this manner, the injection assembly **111** can be configured to ensure that the injection is initiated only when the distal tip **142** of the needle is in the first region R1 such that the substance M (e.g., a medicament such as, for example, VEGF, a VEGF inhibitor, a combination thereof, or any other medicament described herein) can be delivered only to the region R1. In some embodiments, the force F exerted by the energy storage member **146** can be between about 2 N and about 6 N, for example, about 3 N, about 4 N, or about 5 N, inclusive of all ranges therebetween. In some embodiments, the actuation rod **120** and the medicament container **130** can be collectively configured such that the force produces an injection pressure within the medicament container **130** of between about 100 kPa and about 500 kPa. For example, in some embodiments, the injection pressure can be about 100 kPa, 110 kPa, 120 kPa, 130 kPa, 140 kPa, 150 kPa, 160 kPa, 170 kPa, 180 kPa, 190 kPa, 200 kPa, 220 kPa, 240 kPa, 260 kPa, 280 kPa, 300 kPa, 320 kPa, 340 kPa, 360 kPa, 380 kPa, 400 kPa, 420 kPa, 440 kPa, 460 kPa, or about 480 kPa, inclusive of all ranges and values therebetween. The injection pressure can be sufficient to overcome the backpressure produced by region R1, but insufficient to overcome the backpressure produced by region R2. For example, the force F can be varied (e.g., by varying the energy storage member **146**) depending on the diameter of the medicament container **130** and/or the actuation rod, the viscosity of the substance M, and/or the material of the medicament container **130** and/or the actuation rod **120**. In this manner, regardless of the variations in the actuation rod **120**, the medicament container **130**, and/or the substance M, the injection assembly **111** produces an injection pressure within the medicament container of between about 100 kPa and about 500 kPa.

[0140] In some embodiments, the injection assembly **111** can be configured to be engaged or disengaged by a user reversibly on demand. For example, the injection assembly **111** can include an ON/OFF switch which can be engaged by the user to activate or deactivate the injection assembly and/or the energy storage member **146**. By way of example, in such embodiments, the injection assembly **111** can be activated by the user (e.g., by turning the injection assembly ON) to release the energy storage member **146** such that the energy storage member **146** exerts the force on the proximal end portion **122** of the actuation rod **120** (e.g., as shown in

FIG. 6) to move the distal end portion **124** of the energy storage member **146** within the medicament container **130**. The user can then deactivate the injection assembly **111** (e.g., by turning the injection assembly OFF). The disengaging can result in the force exerted on the proximal end portion **122** of the actuation rod **120** to be removed (e.g., to stop any further movement of the actuation rod **120** within the medicament container **130**) or reduced. In some embodiments, the injection assembly **111** can be configured such that the direction of the force **F** can be reversed or the actuation rod **120** and/or the energy storage member **146** can be moved in an opposite direction of the arrow **F** (FIG. 5). In this manner, the medical injector **100** can be returned to the first configuration such that, for example, the energy storage member **146** and/or the actuation rod **120** can be secured. This can, for example, allow more flexibility to the user to perform dry runs or correct a mistake, for example, inadvertent activation of the injection assembly **111** (e.g., during transportation to the target tissue), or injection in an incorrect insertion site (e.g., an undesired location on an eye). In such embodiments, the energy storage member **146** can include any suitable engagement member which can be reversibly engaged or disengaged by the user such as, for example, a valve (e.g., a flap valve, a butterfly valve, or the likes), a diaphragm, a mechanical actuator (e.g., a rack and pinion actuator, a lead screw and nut actuator, a cam, etc.), a hydraulic actuator (e.g., a hydraulic piston), an electromechanical actuator (e.g., a piezo electric actuator), a magnetic actuator, or any other suitable energy storage member **146** which can be reversibly engaged by the user. Such an energy storage member **146** can, for example, allow the medical injector **100** to be moved between the first configuration and the second configuration on demand.

[0141] In some embodiments, the injection assembly **111** can be configured such that injection distance traversed by the actuation rod **120** is sufficient to deliver substantially all of the desired dose of the substance **M** into the first region **R1**. In other embodiments, the injection assembly **111** can be configured such that the injection distance traversed by the actuation rod **120** is sufficient to deliver only a portion of the desired dose of the substance **M** into the first region **R1**. In such embodiments, the injection assembly **111** can be configured to initiate delivery of the substance **M** into the first region **R1**, for example, to inform the user that the distal tip **142** of the needle **140** is disposed within the first region **R1** (e.g., the user would see or otherwise detect that the actuation rod **120** has moved, thus indicating the desired positioning of the needle **140**). Said another way, the injection assembly **111** can assist the user in determining whether the distal tip **142** of the needle **140** is within the region **R1** or not by initiating delivery of the substance **M**. In such embodiments, the injection distance can be a first injection distance. The user can then move the distal end portion **124** of the actuation rod **120** a second injection distance, for example, by applying a manual force on the actuation rod **120** (e.g., by moving the housing **110** relative to the medicament container **130**, as described herein). In some embodiments, any suitable delivery mechanism (e.g., a mechanical actuator or a pump) can be used to move the distal end portion **122** of the actuation rod **120** the second injection distance such that substantially all of the desired dose of the substance **M** is delivered to the first region **R1**.

[0142] In some embodiments, the proximal end portion **122** of the actuation rod **120** moves relative to the housing

110 to move the distal end portion **124** of the actuation rod **120** within the medicament container **130**, for example, when the distal tip **142** of the needle **140** is disposed within the first region **R1** (e.g., the SCS of the eye) of the target location **T**. For example, in some embodiments, the proximal end portion **122** of the actuation rod **120** can be configured to move freely within the housing **110** such that, distal end portion **124** can move within the medicament container **130** without the housing **110** and the medicament container **130** moving relative to each other. This can, for example, ensure that force **F** exerted by the energy storage member **146** does not move the housing relative to the medicament container **130**. In this manner, substantially all of the force **F** can be transferred to the proximal end portion **122** of the actuation rod **120**. In such embodiments, the housing **110** and/or the medicament container **130** can include features, for example, ribs, notches, grooves, indents, locks, latches, high friction, or any other suitable mechanism, sufficient to prevent the housing **110** and the medicament container **130** from moving relative to each other due to the force **F**.

[0143] In some embodiments, the injection assembly **111** can include a release member (not shown) configure to selectively limit movement of the actuation rod **120** relative to the housing **110**. In such embodiments, the housing **110** can be configured to move relative to the medicament container **130** to move the distal end portion **124** of the actuation rod **120** within the medicament container **130** independently from the force **F**. In this manner, the release member can be configured to lock or otherwise secure the actuation rod **120**, for example, the proximal end portion **122** of the actuation rod **120**, and/or the energy storage member **146** in the first configuration. This can, for example, bias the energy storage member **146** to exert the force **F** on the distal end portion **122** of the actuation rod **120**. In this manner, the movement of the actuation rod **120** can be substantially limited within the housing **110** such that any movement of the housing **110** relative to the medicament container **130** also displaces the distal end portion **124** of the actuation rod **120** within the medicament container **130**. For example, the user can move the housing **110** relative to the medicament container **130** to move the distal end portion **124** of the actuation rod **120** within the medicament container **130**. The relative motion can be used to draw the substance **M** into the medicament container **130** and/or move the distal end portion **124** the second injection distance to expel substantially all of the substance **M** in the first region **R1** or any other target region of the target location, as described herein.

[0144] In some embodiments, the release member can be configured to move between a first position and a second position such that the release member is configured to release the energy storage member **146** when the release member is moved from the first position to the second position. The release member can include any suitable release member such as, for example, a pawl, lock, latch, or any other suitable release member. By way of example, in the first position the release member can secure or otherwise engage the proximal end portion **122** of the actuation rod **120**, and/or the energy storage member **146**, such that the energy storage member **146** is biased and/or the actuation rod **120** is locked within the housing **110**, as described herein. Once the distal tip **142** of the needle **140** is disposed within the second region **R2**, the release member can be moved into the second position to release the energy storage

member **146** and/or the actuation rod **120**. Said another way, the release member can be configured to maintain a position of the actuation rod **120** relative to the housing **110** when the release member is in the first position such that the movement of the housing **110** relative to the medicament container **130** moves the distal end portion **124** of actuation rod **120** within the medicament container. Furthermore, the release member can be configured to release the actuation rod **120** when moved from the first position to the second position. This can allow the force F produced by the energy storage member **146** to move the distal end portion **124** of the actuation rod **120** relative to the housing **110** and within the medicament container **130** and, thereby convey at least a portion of the substance M from the medicament container **130** via the needle **140**. In some embodiments, an actuation mechanism, for example, a button, a pull tab, or any other actuation mechanism can be coupled to the release member. The actuation mechanism can, for example, be configured to be engaged by the user to move the release member into the second position thereby releasing the actuation rod **120** and/or the energy storage member **146**.

[0145] In some embodiments, the injection assembly **111** can also include a guide rod (not shown) fixedly coupled to the housing **110**. The actuation rod **120** can be configured to slide about the guide rod when the energy storage member **146** is released. For example, in some embodiments, at least a portion of the guide rod can be disposed within a cavity defined in proximal end portion **122** of the actuation rod **120**. In some embodiments, the guide rod can be a hollow rod within which the proximal end portion **122** of the actuation rod **120** is disposed. The guide rod can be configured to ensure that the actuation rod **120** moves within the housing **110** and/or medicament container **130** substantially along a center line A_z of the apparatus **100**. In this manner, the guide rod can prevent any sideways (or lateral) movement of the actuation rod **120**.

[0146] In some embodiments, a system for ocular injection can include a medicament containment chamber at least a portion of which is disposed in a housing. Referring now to FIGS. 7-8, in some embodiments, a system **1000** includes at least a housing **1110**, a medicament containment chamber **1310**, and an actuator **1320**. The system **1000** can be configured to deliver a medicament to a region and/or layer of an eye of a patient, for example, to the SCS of the eye.

[0147] The housing **1110** includes a first portion **1110a** and a second portion **1110b**, that can be coupled to define an internal volume for housing at least a portion of the medicament containment chamber **1310** and the actuator **1320**. The first portion **1110a** and the second portion **1110b** can removably or fixedly coupled together using any suitable means, for examples, screws, nuts, bolts, rivets, adhesives, a snap-fit mechanism, notches, grooves, indents, lock, latch, or any other suitable coupling mechanism. The housing **1110** includes a gripping portion **1112**. A plurality of ribs **1113** are disposed on the gripping portion **1112** to allow a user to easily grip the housing **1110**, for example, between the user's index and/or middle finger, and thumb. A plurality of ridges **1114** are disposed on an outer surface of a distal portion of the housing **1110**. The ridges **1114** can provide an additional gripping surface for the user to securely hold the housing **1110**. For example, a user can grip the gripping portion **1112** with a first hand and grip the ridges **1114** with a second hand to limit any movement of the housing **1110** during injection of a medicament disposed in the medica-

ment containment chamber **1310**. A set of ribs (also referred to as sidewalls and/or protrusions) **1116** are disposed in the internal volume defined by the housing **1110**. The ribs **1116** are configured to engage an engagement portion **1312** and/or a flange **1313** of the medicament containment chamber **1310**, for example, to define a range of travel of the actuator **1320**, as described herein. Similarly stated, the ribs **1116** are configured to limit movement of the actuator **1320** and/or the flange **1313** relative to the housing **1110** during use.

[0148] A set of mounts **1118** are disposed at a proximal end, within the interior region, of the housing. The mounts **1118** are configured to mount and/or retain an engagement portion **1322** of the actuator **1320**, such that a linear translation of the housing **1110** along a longitudinal axis A_z of the system **1000** urges the actuator **1320** to also translate along the longitudinal axis A_z relative to the medicament containment chamber **1310**. A securing member **1119** can be disposed over a distal end of the housing. The securing member **1119** can be a ring-like member formed from a relatively elastic material, for example, rubber, silicone, plastics, polymers, any other suitable material or combination thereof. The securing member **1119** can be configured to secure the first portion **1110a** and the second portion **1110b** of the housing **1110** to each other at a distal end of the housing **1110**.

[0149] The medicament containment chamber **1310** defines an internal volume configured to house a medicament (e.g., triamcinolone acetonide, VEGF, VEGF inhibitor, or any other medicament described herein). The medicament containment chamber **1310** includes an engagement portion **1312** and a delivery portion **1314**. The delivery portion **1314** can include any suitable coupling feature, for example, a luer connector, threads, a snap-fit, a latch, a lock, a friction fit coupling, or any other suitable coupling features. The coupling features can be configured to couple the delivery portion **1314** with a puncturing member (not shown), for example, a microneedle (e.g., a 27 gauge, a 30 gauge needle, or even smaller micro needle). The puncturing member can be any suitable puncturing member (such as those described in the '009 PCT application") configured to pierce a portion of a patient's body, for example, an eye, and to establish fluidic communication between the medicament containment chamber **1310** and the portion of the user's body (e.g., the eye).

[0150] The engagement portion **1312** is disposed proximate to the user and includes a flange **1313**. The engagement portion **1312** is disposed in the housing **1110** such that the ribs **1116** are distal to the flange **1313**, and interact with the flange **1313** to define a range of motion of the actuator **1320** and/or the medicament containment chamber **1310**. In some embodiments, the medicament containment chamber **1310** can include a commercially available syringe such as, for example, a BD™ ICC syringe, or any other commercially available syringe.

[0151] The actuator **1320** includes an engagement portion **1322** and a plunger portion (not shown) movably disposed within the internal volume defined by the medicament containment chamber **1310**. At least a portion of the actuator **1320** is slidably disposed in the internal volume defined by the medicament containment chamber **1310**. Thus, the actuator **1320** can be displaced within the internal volume defined by the medicament containment chamber **1310** for drawing the medicament into or expelling the medicament from the internal volume defined by the medicament con-

tainment chamber 1310. The engagement portion 1322 is fixedly mounted in the mounts 1118 of the housing 1110. Thus, any linear displacement of the housing 1110 along the longitudinal axis A_L of the system 1000 also urges the actuator 1320 to slide within the internal volume of the medicament containment chamber 1310.

[0152] In use, a user can grip the housing 1110, for example, at the gripping portion 1112 with one hand, and with the other hand grip a portion of the medicament containment chamber 1310 disposed outside the housing 1110. The user can then displace the housing 1110 relative to the medicament containment chamber 1310. Displacement of the housing 1110 also urges the actuator 1320 to slide within the internal volume defined by the medicament containment chamber 1310. The ribs 1116 can prevent the user from sliding the housing 1110 beyond a predetermined threshold to prevent the actuator 1320 from being separated from the medicament containment chamber 1310. Furthermore, the range of motion can also define a maximum dose of the medicament that can be drawn into the internal volume of the medicament containment chamber 1310. In this manner, the user can draw a medicament into the medicament containment chamber 1310, or inject the medicament into an ocular tissue, for example, the SCS of an eye.

[0153] In some embodiments, a system for injecting a medicament into ocular tissue can include an injector assembly configured to produce a force to assist in the delivery of a medicament. Referring now to FIG. 9 to FIGS. 16A-C, a system 2000 includes a housing 2110, an injector assembly 2100, a medicament containment chamber 2310, and an actuator 2320. The system 2000 can be configured to deliver a medicament to a desired layer and/or region of an eye of patient, for example, to the SCS of the eye.

[0154] The housing 2110 includes a first portion 2110a and a second portion 2110b, that can be coupled to define an internal region for housing the components of the injector assembly 2100 and at least a portion of the medicament containment chamber 2310 and/or the actuator 2320. The first portion 2110a and the second portion 2110b can removably or fixedly coupled together using any suitable means, for examples, screws, nuts, bolts, rivets, adhesives, a snap-fit mechanism, notches, grooves, indents, lock, latch, or any other suitable coupling mechanism. The housing 2110 includes a gripping portion 2112. A plurality of ribs 2113 are disposed on the gripping portion 2112 to allow a user to easily grip the housing 2110, for example, between the user's index and/or middle finger, and thumb. A plurality of ridges 2114 are also disposed on an outer surface of a distal portion of the housing 2110, for example to allow easy gripping of the housing 2110 by the user. For example, a user can grip the gripping portion 2112 with a first hand and grip the ridges 2114 with a second hand to limit any movement of the housing 2110 during injection of a medicament disposed in the medicament containment chamber 2310. A set of ribs 2116 are disposed in the internal region defined by the housing 2110. The ribs 2116 (also referred to as shoulders or protrusions) are configured to engage a flange 2313 included in an engagement portion 2312 of the medicament containment chamber 2310, for example, to define a range of travel of the actuator 2320 and/or the medicament containment chamber 2310, as described herein. A proximal end of the housing 2110 includes slots 2117 (see FIG. 11) configured to receive at least a portion of an actuating member 2120 included in the injector assembly 2100, as described

herein. A set of mounts 2118 are disposed at a proximal end, within the interior region, of the housing. The mounts 2118, are configured to mount an engagement portion 2142 of a guide rod 2140 included in the injector assembly 2100. A securing member 2119 can be disposed over a distal end of the housing. The securing member 2119 can be a ring like member formed from a relatively elastic material, for example, rubber, silicone, plastics, polymers, any other suitable material or combination thereof. The securing member 2119 can be configured to secure the first portion 2110a and the second portion 2110b to each other at a distal end of the housing 2110.

[0155] The actuating member 2120 (FIGS. 12A-C) is disposed at the proximal end of the housing 2110 and is configured to actuate the injector assembly 2100, as described herein. The actuating member 2120 includes an engagement protrusion 2122 and a guide protrusion 2124. At least a portion of the engagement protrusion 2122 and the guide protrusion 2124 are slidably disposed in the slots 2117 (see FIG. 11). A user can engage an engagement surface 2121 of the actuating member 2120, and move the actuating member 2120 between a first configuration, in which the engagement protrusion 2122 and the guide protrusion 2124 are partially disposed within the internal volume defined by the housing 2110, and a second configuration, in which the engagement protrusion 2122 and the guide protrusion 2124 are substantially disposed within the internal volume defined by the housing 2110. Said another way, the actuating member 2120 can be moved relative to the housing 2110 between a first position (see FIG. 16D) and a second position (FIG. 16E).

[0156] The engagement protrusion 2122 is configured to engage a pawl 2130 included in the injector assembly 2100 in the second configuration (or position), as described herein (see FIG. 16E). The guide protrusion 2124 is configured to slide within the slots 2117 along with the engagement protrusion 2122, to prevent any angular motion of the actuating member 2120 about the longitudinal axis A_L . A biasing member 2123, for example, a spring (e.g., helical spring, compression, extension, spring washers, Belleville washer, tapered, any other type of spring) is coupled to the engagement protrusion 2122, for example, disposed around the engagement protrusion 2122. The biasing member 2123 is configured to bias the actuating member 2120 in the first configuration (or position). A washer 2125 is coupled to a proximal end of the guide protrusion 2124 and is disposed inside the internal volume defined by the housing 2110. The washer 2125 has a diameter, or otherwise cross-section, which is substantially larger than the diameter or otherwise cross-section of the slots 2117, such that the washer 2125 prevents the actuating member 2120 from being removed from the housing 2100.

[0157] The pawl 2130 (FIGS. 13A-C) is disposed at the proximal end of the internal volume defined by the housing 2110. The pawl 2130 includes an engagement portion 2132, a latch 2134, and a biasing portion 2136. A set of protrusions 2137 are disposed on the pawl 2130. The protrusions 2137 are configured to pivotally mount the pawl 2130 in the internal volume defined by the housing 2110. This allows the pawl 2130 to rotate about the protrusions 2137 between a first configuration (or angular position) and a second configuration (or angular position) as described herein. The engagement portion 2132 defines a flat surface, which is configured to be engaged by the engagement protrusion

2122 of the actuating member **2120** (see e.g., FIG. 16E). More particularly, when the actuating member **2120** is moved from its first configuration (or position) to its second configuration (or position), the engagement protrusion **2122** can urge the pawl **2130** from the first configuration into the second configuration. The latch **2134** defines a ledge or shoulder configured to engage an engagement portion **2322** of the actuator (or push rod) **2320** in the first configuration, as described herein. The biasing portion **2136** includes a thin, beam-like structure configured to elastically bend in the second configuration. In this manner, the biasing member **2136** can urge the pawl **2130** into the first configuration, as described herein. For example, in the first configuration, the latch **2134** can engage the engagement portion **2322** of the actuator **2320** (see FIGS. 16B-16D) and the biasing portion **2136** can be in an extended position (i.e., maintaining the position of the pawl **2130**). A user can engage the engagement portion **2121** of the actuating member **2120** and urge it into its second configuration (or position). In the second configuration of the actuating member **2120**, the engagement protrusion **2122** can engage the engagement portion **2132** of the pawl **2130**. This can urge the pawl **2130** to rotate about the protrusions **2137** and move into the second configuration. When the latch **2134** is in the second configuration, the latch **2134** can disengage from the engagement portion **2322** of the actuator **2320** such that the biasing portion **2136** is bent against the housing **2110** and is biased (or compressed). The user can then disengage the actuating member **2120**. The biasing member **2123** coupled to the engagement protrusion **2122** can urge the actuating member **2120** back into the first configuration. This disengages the engagement protrusion **2122** from the engagement surface **2132** of the pawl **2130** such that the biasing portion **2136** can urge the pawl **2130** into the first configuration.

[0158] The guide rod **2140** (FIG. 15) includes a mounting portion **2142** that is immovably mounted on the mounts **2118** included in the housing **2110**. Similarly stated, the guide rod **2140** is coupled within the housing **2110** such that movement (distal movement and proximal movement) is limited. At least a portion of the guide rod **2140** is disposed in a cavity **2326** defined within the actuator **2320**. The guide **2140** rod is configured to prevent lateral motion of the actuator **2320** when the actuator **2320** slides in a linear direction along the longitudinal axis A_L of the system **2000** within the housing **2110**, as described in further detail herein. The guide rod **2140** also couples a biasing member **2146** (or energy storage member which is disposed around the guide rod **2140**, see e.g. FIG. 16A) between the mounts **2118** and the actuator (or push rod) **2320**. The biasing member **2146** can include, for example, a spring, (e.g., a helical spring, compression, extension, spring washers, Belleville washer, tapered, any other type of spring), any other suitable biasing member or combination thereof. A proximal end of the biasing member **2146** is coupled to and/or engaged with the mounting portion **2142** of the guide rod **2140**, and a distal end of the biasing member **2146** is coupled to and/or engaged with the engagement portion **2322** of the actuator **2320**. The biasing member **2146** is configured to bias the actuator **2320** when the engagement portion **2322** of the actuator **2320** is disposed relative to the mounting portion **2142** of the guide rod **2140** in the “readied” position (see e.g., FIGS. 16B-16D). In this manner, the biasing member **2146** can exert a predetermined biasing force on the actuator **2320** to enable or otherwise assist the actuator **2320**

to expel a medicament from the medicament containment chamber **2310**, as described in further detail herein.

[0159] The medicament containment chamber **2310** defines an internal volume **2316** configured to house a medicament (e.g., a VEGF, a VEGF inhibitor, triamcinolone acetate, any other medicament described herein or a combination thereof). The medicament containment chamber **2310** includes an engagement portion **2312** and a delivery portion **2314**. The delivery portion **2314** can include coupling features, for example, luer connectors, threads, snap-fit, latch, lock, friction fit, or any other suitable coupling features. The coupling features can be configured to couple the delivery portion **2314** with a puncturing member (not shown), for example, a microneedle (e.g., a 27 gage, or 30 gage, or even smaller needle). The puncturing member can be any suitable puncturing member (such as those described in the ‘009 PCT application) which is configured to pierce a portion of a patient’s body, for example, an eye, and to establish fluidic communication between the medicament containment chamber **2310** and the portion of the user’s body (e.g., the eye). The engagement portion **2312** includes a flange **2313**. The engagement portion **2312** is disposed in the housing **2110** such that the ribs **2116** are distal to the flange **2313**, and interact with the flange **2313** to define a range of motion of the actuator **2320** and/or the medicament containment chamber **2310**. Said another way, the ribs **2116** and the flange **2313** can serve in combination as a locking mechanism to prevent the medicament containment chamber **2310** from moving beyond a threshold distance within the housing **2110**. In some embodiments, the medicament containment chamber **2310** can include a commercially available syringe such as, for example, a BD™ ICC syringe, or any other commercially available syringe.

[0160] The actuator (or actuation rod) **2320** (FIGS. 14A-B) includes an engagement portion **2322** and a plunger portion **2324**. As described before, the engagement portion **2322** defines a cavity **2326** configured to receive at least a portion of the guide rod **2140**. A proximal end of the engagement portion **2322** is coupled to and/or engaged with the biasing member **2146**, as described before herein. At least a portion of the actuator **2320**, for example, the plunger portion **2324**, is slidably disposed in the internal volume **2316** defined by the medicament containment chamber **2310**. Thus, the actuator **2320** can be displaced within the internal volume **2316** for drawing and/or expelling the medicament from the internal volume **2316** defined by the medicament containment chamber **2310**.

[0161] As shown in FIGS. 14A and 14B, a protrusion **2325** is disposed at a distal end of the plunger portion **2324**. The protrusion **2325** is configured to be inserted into a plug **2328** with close tolerance (e.g., friction-fit). The plug **2328** can be slidably disposed in the internal volume **2316** of the medicament containment chamber **2310**. A distal end of the plug **2328** can be in fluid communication with the medicament disposed in the internal volume **2316** defined by the medicament containment chamber **2310**. The sidewalls of the plug **2328** can be in contact with the sidewalls of the internal volume **2316** such that the plug forms a fluid tight seal to prevent leakage of the medicament. The plug **2328** can be made of an inert and/or biocompatible which is rigid but soft. Example materials include rubber, silicone, plastic, polymers, any other suitable material or combination thereof.

[0162] The injector assembly 2100 is configured to produce a force to inject or otherwise assist in injecting the medicament from the medicament containment chamber 2310 into the ocular tissue, for example, the SCS. Furthermore, the injector assembly 2100 can be configured to exert a predetermined force and/or a force within a desired range on the actuator 2320 sufficient to expel the medicament only when an outlet of a puncturing member (e.g., a needle such as a 27 gauge, a 30 gauge or any needle described herein) is within or otherwise near the target injection site, for example, the SCS. Similarly stated, the injector assembly 2100 can be configured to exert a predetermined force on the actuator (or push rod) 2320 and/or the plug 2328 such that the actuator 2320 and/or the plug 2328 move when the backpressure against the opening of a delivery member (e.g., a puncture member or needle, not shown) is below a desired level. As described below, the amount of backpressure against the delivery member can be a function of the tissue characteristics of the target tissue (e.g., tissue density, presence of voids, tissue type, etc.). Thus, the injector assembly 2100 can produce motive force when the opening of the delivery member is within a desired target location (e.g., the SCS). FIGS. 16A to 16E show the system 2000 that includes the injector assembly in various states of operation as described herein.

[0163] In a first state shown in FIG. 16A, a portion of the medicament containment chamber 2310 is disposed in the housing 2110 of the injector assembly 2100. The flange 2313 of the medicament containment chamber 2310 can be contiguous and/or in contact with the ribs 2116 of the housing 2110. The actuator 2320 is pushed into the medicament containment chamber 2310 such that the plunger portion 2324 of the actuator 2320 occupies substantially all of the internal volume 2316 of the medicament containment chamber 2310 and there is no medicament in the internal volume 2316. Additionally, the guide rod 2140 is disposed in a first relative position within the actuator (or push rod) 2320. In the first state, the biasing member 2146 is coupled to the engagement portion 2322 of the actuator 2320 and is unbiased (or in an expanded configuration). Said another way, the system 2000 is unarmed in the first state. Thus, in the first state (or configuration), the system 2000 can be shipped, stored or the like.

[0164] To move the system 2000 to the second state shown in FIG. 16B, the user moves the medicament containment chamber 2310 proximally relative to the injector assembly 2100. This can be achieved by applying a force on the housing 2110 and/or the medicament containment chamber 2310 such that the force pushes the medicament containment chamber 2310 into the housing 2110 in the direction shown by the arrow A. The housing 2110 is shaped and sized to prevent any rotational motion of the medicament containment chamber 2310 relative to the housing 2110. Motion of medicament containment chamber 2310 relative to the injector assembly 2100, also urges the actuator 2320 to slide over the guide rod 2140 and move relative to the injector assembly 2100. Thus, when the injector assembly 2100 is in the second state, the guide rod 2140 is disposed in a second relative position within the actuator (or push rod) 2320. Furthermore, the biasing member 2146 is biased (or compressed) when the injector assembly 2100 is in the second state. The force is maintained until the latch 2134 of the pawl 2130 engages and secures the engagement portion 2322 of the actuator 2320. The pawl 2130 includes an angled surface

such that the engagement portion 2322 can slide past the latch 2134 in a proximal direction but cannot move past the latch 2134 in a distal direction. Thus, in the second state, the system 2000 is “armed” and is ready to be filled with a medicament.

[0165] The user can now couple a transfer needle, puncture member and/or delivery member (not shown) to the delivery portion 2314 of the medicament containment chamber 2310. The puncturing member can be inserted into a container of the medicament, for example, inserted through a septum of a vial containing the medicament. The system 2000 can then be moved into a third state (or configuration) to fill the medicament containment chamber 2310 with a substance. To move the injector assembly 2100 to the third state shown in FIG. 16C, a force can be applied on the medicament containment chamber 2310 and/or the housing 2110 to move the medicament containment chamber 2310 distally relative to the injector assembly 2100 in the direction shown by the arrow B. In this manner, the medicament containment chamber 2310 is drawn out of (moved distally relative to) the housing 2110. The engagement portion 2322 of the actuator 2320 remains secured by the latch 2134 of the pawl 2130 in the third state. Therefore, the relative motion of the medicament containment chamber 2310 to the housing 2110 urges the plunger portion 2324 of the actuator 2320 to slide within the internal volume 2316 of the medicament containment chamber 2310 until the plunger portion 2324 is proximate to the engagement portion 2312 of the medicament containment chamber 2310. The displacement of the actuator 2320 and the plug 2328 creates a suction force within the internal volume 2316 of the medicament containment chamber 2310, which draws the medicament into the internal volume 2316.

[0166] To place the injector assembly 2100 in a fourth state (shown in FIG. 16D), the user can move the medicament containment chamber 2310 proximally relative to the injector assembly 2100 such that the medicament containment chamber 2310 moves into the housing 2110 as shown by the arrow C. In the fourth state, the medicament containment chamber 2310 is partially drawn into the housing 2110. Since the actuator 2320 is still secured by the pawl 2130 in the fourth state, moving the housing 2310 urges the plunger portion 2324 of the actuator 2320 (and thus the plug 2328) to also slide in the internal volume 2316 proximally relative to the medicament containment chamber 2310. In this manner, the plunger portion 2324 of the actuator 2320 expels a portion of the medicament from the internal volume 2316. Said another way, the user can expel air from the internal volume 2316 and/or adjust a dose of the medicament in the fourth state.

[0167] Prior to injecting the medicament (i.e., moving the injector assembly 2000 to a fifth state shown in FIG. 16E), a puncturing member (e.g., a 27 gauge needle, a 30 gauge needle, or any other puncturing members described herein), or a needle assembly (e.g., the needle assembly 3200 or any other needle assembly described herein) can be coupled to the delivery portion 2314 of the medicament containment chamber 2310. While not shown, a hub can also be coupled to the delivery portion 2314, which is configured to contact an ocular tissue. The hub can include a hub that includes a convex distal end, a flat distal end, features for aligning the system 2000 on a surface (e.g., conjunctiva) of the eye, or any other hub described herein. For example, in some embodiments, the hub can include a convex distal end

surface configured to form a substantially fluid-tight seal with a target surface around the insertion site (see e.g., hub 7270 included in the medical injector 7000).

[0168] The user can insert the puncturing member into an eye, until an outlet of the puncturing member is in or otherwise near a target delivery layer, for example, the SCS. The user can manually adjust the insertion depth of the puncturing member or a needle assembly to increase or decrease the insertion depth of the puncturing member (e.g., as described in further detail with reference to needle assembly 3200). To initiate injection (i.e., to move the injector assembly 2100 to the fifth configuration), the user can then exert a force on the engagement surface 2121 of the actuating member 2120 in the direction shown by the arrow D. This urges the engagement protrusion 2122 to slide in the slot 2117 distally to the user into the housing 2110 and engage the engagement surface 2132 of the pawl 2130. The engagement protrusion 2122 can urge the pawl 2130 to rotate about the protrusions 2137, such the biasing portion 2136 is biased and the latch 2134 disengages from the engagement portion 2322 of the actuator 2320. The biasing member 2146 exerts a force on the engagement portion 2322 of the actuator 2320 and urges the actuator 2320 to displace proximally relative to the medicament containment chamber 2310. Thus, the plunger portion 2324 of the actuator slides an injection distance within the internal volume 2316 of the medicament containment chamber 2310 and expels the medicament into the eye via the puncturing member. The housing 2110 and/or the medicament containment chamber 2310 can be configured to prevent the housing 2110 from displacing distally relative to the medicament containment chamber 2310 in the fifth state. For example, in some embodiments, the flange 2313 of the medicament containment chamber 2310 and/or an inner surface of the housing 2110 can have a high friction surface. The flange 2313 and the inner surface of the housing 2110 can contact each other to yield a high friction interface which can prevent the housing 2110 from displacing distally relative to the medicament containment chamber 2310 in the fifth state. In some embodiments, notches, grooves, indents, or any other features can be defined in the internal volume of the housing 2110, and/or the flange 2313. In some embodiments, a locking mechanism, for example, a twist lock mechanism, a push pin, a latch, a ledge, or any other suitable locking mechanism can be included in the housing 2110. In such embodiments, the user can engage the locking mechanism (e.g., twist the housing 2110 relative to the medicament containment chamber 2310, depress a pin, etc.) such that the housing 2110 can be prevented from displacing distally relative to the medicament containment chamber 2310 in the fifth state. In this manner, the force exerted by the biasing member 2146 is applied to move the actuator (or actuation rod) 2320 distally relative to (and/or within) the medicament containment chamber 2310, as opposed to being applied to move the entirety of the medicament containment chamber 2310 relative to the housing 2110.

[0169] In some embodiments, the injector assembly 2100 can be used as an injection-assist assembly to enable a user to inject the medicament into a desired tissue of the eye, for example, the SCS. In such embodiments, the biasing member 2146 can be configured to exert a predetermined force on the actuator 2320, for example a force of less than about 6N, less than about 5 N, less than about 4N, less than about 3 N, or less than about 2 N, inclusive of all ranges therebetween.

The force can be sufficient to expel the medicament from the medicament containment chamber 2310 when the backpressure, existing or applied at an outlet of the puncturing member, is below a certain threshold. As described before herein, different layers of the eye can have different densities, for example, the sclera is much denser than the SCS. Therefore, a puncturing member inserted into the sclera will experience a much higher backpressure than a puncturing member near or within the SCS. The biasing member 2146 can be configured to exert a force, which is only sufficient to overcome the backpressure experienced in the target layer, for example, the SCS, but is not sufficient to overcome the backpressure of any other layer, for example, the sclera. In this manner, the biasing member 2146 urges the actuator 2320 to expel the medicament only into the target layer, for example, the SCS. The backpressure experienced by the actuator can vary based on the medicament used, the size of the puncturing member, the target ocular tissue layer, and/or thickness of the target layer. If the force delivered by the biasing member 2146 is too high, injection can occur in the incorrect target layer, for example, the sclera. Conversely, if the biasing force is too small, injection might not occur even when the outlet of the puncturing member is within or near the target layer, for example, the SCS. To overcome this, the biasing member 2146 can be tailored based on the medicament used, the needle size, the size of the medicament containment chamber 2310, the actuator 2320, and/or target layer. In some embodiments, the actuator 2320 and the medicament containment chamber 2310 can be collectively configured such that the force exerted by the biasing member 2146 produces an injection pressure within the internal volume 2316 of the medicament containment chamber 2310 of between about 100 kPa and about 500 kPa. For example, the system 2000 can be configured such that the same injection pressure is produced within the medicament containment chamber 2310, regardless of the size (e.g., diameter or otherwise cross-section) of the medicament containment chamber 2310 and/or the actuator 2320, the material of the actuator 2320 or the medicament containment chamber 2310, the volume of the medicament, the viscosity of the medicament, and/or the size of the puncture member. In some embodiments, the pressure produced in the medicament containment chamber 2310 can be about 100 kPa, 110 kPa, 120 kPa, 130 kPa, 140 kPa, 150 kPa, 160 kPa, 170 kPa, 180 kPa, 190 kPa, 200 kPa, 220 kPa, 240 kPa, 260 kPa, 280 kPa, 300 kPa, 320 kPa, 340 kPa, 360 kPa, 380 kPa, 400 kPa, 420 kPa, 440 kPa, 460 kPa, or about 480 kPa, inclusive of all ranges and values therebetween.

[0170] Furthermore, in some embodiments, the injector assembly 2100 can also be used to inform the user when the puncturing member is within or near the target layer. For example, the housing 2110 can be transparent such that the user can see the actuator 2320 and/or the medicament containment chamber 2310. The user can insert the puncturing member into the eye and engage the actuating member 2120 such that the latch 2134 disengages the engagement portion 2322 of the actuator 2320. If the puncturing member is within or near the target layer, for example, the SCS, the biasing member 2146 overcomes the backpressure exerted by the target layer and displaces the actuator 2320 to move the injection distance and initiate injection of the medicament into the target layer. The user can visibly observe the actuator 2320 and/or the plug 2328 displacing within the housing 2110 and can be informed that the

puncturing member is within or otherwise near the target layer, for example, the SCS. If the puncturing member is in a layer other than the target layer, for example, the sclera, the biasing member **2146** will not overcome the backpressure of the other layer and the actuator **2320** will not displace proximally relative to the medicament containment chamber **2310**. This can inform the user that the puncturing member is not within or near the target layer. The user can then manipulate the puncturing member to reach within or near the target layer and initiate injection of the medicament. In some embodiments, any other communication mechanism, for example, audible alarm, LED light, a message, a display, a tactile alert, or any other communication mechanism can be used to inform the user about the location of the puncturing member. In some embodiments, the biasing member **2146** can be configured to exert a force sufficient to expel substantially all of the medicament into the target layer, for example, the SCS. In some embodiments, the biasing member **2146** can be configured to exert a force sufficient to initiate injection but not enough to expel all of the medicament into the target layer. In such embodiments, the injection distance can be a first injection distance. Once the injection is initiated, the user can then move the injection assembly **2100** and thereby the actuator **2320** a second injection distance proximally relative to the medicament containment chamber **2310**. In this manner, the remaining medicament can be delivered to the target layer of the eye.

[0171] FIG. 17 shows a schematic flow diagram of a method **200** of delivering a medicament to a target layer of a target tissue (or at a predetermined distance within the target tissue) using a medical injector that includes an injection assembly. The method **200** includes inserting a distal tip of a needle of a medical injector (e.g., the system **100**, **1000**, **2000**, or any other system described herein) a first distance into a target tissue, at **202**. The needle can include any suitable needle, for example, the needle **140** or any other needle described herein. The medical injector includes a medicament container (e.g., the medicament container **130**, **1310**, **2310**, or any other medicament container described herein) and an injection assembly (e.g., the injection assembly **111**, **2100**, or any other injection assembly described herein). The medicament container is in fluid communication with the needle. The injection assembly includes an actuation rod (e.g., the actuation rod **120**, the actuator **2320**, or any other actuator described herein) and an energy storage member (e.g., the energy storage member **146**, **2146**, or any other energy storage member described herein). The energy storage member is configured to produce a force on a proximal end portion of the actuation rod.

[0172] The method **200** further includes releasing the actuation rod of the injection assembly allowing a distal end portion of the actuation rod to move within the medicament container in response to the force, at **204**. For example, a proximal end portion of the actuation rod can be secured or otherwise engaged by a release member, for example, a pawl (e.g., the pawl **2130**) or any other release member described herein. The release member can, for example, be moved from a first position in which the actuation rod is secured to a second position in which the actuation rod is released. As described herein, in certain situations the force will be insufficient to overcome the viscous forces, tissue backpressure, frictional losses or the like within the fluid delivery path defined by the medicament container, the needle and the target tissue when the needle at the first distance within the

tissue. Thus, the actuation rod may not move, or may move less than a threshold “injection distance.”

[0173] Accordingly, the distal tip of the needle included in the medical injector can be inserted, after the releasing, a second distance greater than the first distance into the target tissue (e.g., the ocular tissue of an eye) if the distal end portion of the actuation rod moves less than a threshold injection distance within the medicament container in response to the force, at **206**. The injection distance can be a distance that the distal end portion of the actuation rod moves within the medicament container after the releasing. In some embodiments, the injection distance is less than about 1 cm. In this manner, the lack of movement and/or the limited movement of the actuation rod in operation **204** provides an indication to the user that additional movement and/or repositioning of the needle tip is desirable. Conversely, when the distal end portion of the actuation rod moves through the injection distance within the medicament container, the user is aware that the needle tip is in a suitable region of the target tissue.

[0174] In some embodiments, the distal end portion of the actuation rod can move a first injection distance within the medicament container in response to the force, for example, to deliver a portion of the medicament to the target tissue, for example, the SCS. In such embodiments, the method **200** can further include moving the injection assembly relative to the medicament container to move the distal end portion of the actuation rod a second injection distance greater than the first injection distance within the medicament container **208**. For example, the force can move the actuation rod the first injection distance once the distal tip of the needle is disposed within or near a desired region of the target tissue. This can indicate to a user that the distal tip of the needle is disposed within or near a desired region of the target tissue. The actuation rod can then be moved proximally relative to the medicament container such that the actuation rod moves the second injection distance within the medicament container. In some embodiments, the distal end portion of the actuation rod can be moved the second injection distance manually by a user, for example, by moving the housing proximally to the medicament container. In other embodiments, the medical injector can include an automated delivery mechanism (e.g., a mechanical actuator, a pump, or any other suitable automated delivery mechanism) configured to move the actuation rod the second injection distance and deliver substantially all of the medicament to the target tissue.

[0175] In some embodiments, the target tissue can be an eye. In such embodiments, the inserting of the distal tip of the needle of the medical injector the second distance into the eye includes inserting at least a portion of the distal tip into a suprachoroidal space of the eye. In some embodiments, inserting the distal tip of needle of the medical injector the second distance includes contacting a surface of the eye with a hub coupled to the needle. The hub can include the hub **7270**, **8270**, **9270** or any other hub described herein in further detail below.

[0176] FIG. 18 shows a schematic flow diagram of a method **300** for delivering a medicament to a target layer of a target tissue or a predetermined distance within the target tissue using a medical injector that includes an injection assembly. The method **300** includes inserting a distal tip of a needle of a medical injector (e.g., the medical injector **100**, **1000**, **2000** or any other medical injector described herein, into a medicament contained within a medicament vial **302**.

The medicament vial can be any suitable commercially available medicament vial, bottle, container, or any other vessel housing a medicament. The medicament can include any suitable medicament (e.g., VEGF, a VEGF inhibitor, a combination thereof, or any other medicament described herein) formulated to be delivered to a target tissue (e.g., the SCS of the eye). The medical injector includes a medicament container and an injection assembly, and is in fluidic communication with the needle. The injection assembly includes an actuation rod, and energy storage member, a release member and an actuation member. In some embodiments, the injection assembly and the components of the injection assembly described herein can be substantially similar to the components of the injection assembly **111**, **2100**, or any other injection assembly described herein. The energy storage member (e.g., a spring, a compressed gas container, or a container containing a propellant) is configured to produce a force on a proximal end portion of the actuation rod. The proximal end portion of the actuation rod can be engaged and secured by the release member. For example, the securing can lock the movement of the actuation rod with respect to a housing within which the actuation rod, the injection assembly, and/or at least a portion of the medicament container is disposed. Said another way, the securing of the proximal end portion of the actuation rod by the release member prevents a distal end portion of the actuation rod from moving relative to the housing. Furthermore, any movement of the housing relative to the medicament container also urges the distal end portion of the actuation rod to move within the medicament container.

[0177] Next, the method includes moving the distal end portion of the actuation rod distally relative to the medicament container to draw a volume of the medicament within the medicament container, at **304**. Then, the medicament container is moved proximally relative to the actuation rod to expel a volume of the medicament from the distal tip of the needle and leave a dose volume of the medicament remaining in the medicament container, at **306**. Said another way, any excess medicament drawn into the medicament container can be expelled from the medicament container by moving the medicament container proximally relative to the actuation rod.

[0178] The distal tip of the needle is then inserted a first distance into a target tissue, for example, an ocular tissue, at **308**. The actuation member is activated (e.g., by a user) to disengage the release member from the actuation rod, thereby releasing the proximal end portion of the actuation rod. This allows the distal end portion of the actuation rod to move a first injection distance within the medicament container in response to the force produced by the energy storage member, at **310**. As described herein, the actuation rod will move the first injection distance (or a great amount) when the needle tip is disposed within a desired region of the target tissue. Conversely, when the needle tip is not disposed within a desired region of the target tissue, the force produced by the energy storage member is insufficient to move the actuation rod by the first injection distance.

[0179] The method **300** then includes determining if the actuation rod has moved a threshold injection distance, at **312**, for example, the first injection distance. For example, a user can visually observe if the distal end portion of the actuation rod moved within the medicament container or not (e.g., through a transparent housing of the medical injector). If the actuation rod did not move, the distal tip of the needle

of the medical injector is inserted, after the releasing, a second distance greater than the first distance into the target tissue, at **314**. In this manner, the user can reposition the needle tip (e.g., by inserting further, or removing from the tissue) in response to the indication produced by the actuation rod.

[0180] For example, the first distance can correspond to a sclera of the eye, which has a backpressure that, in conjunction with the frictional losses, viscous losses and the like via the fluid flow path, cannot be overcome by the force of the energy storage member. Thus, the actuation member does move the first injection distance to deliver at least a portion of the medicament into the sclera. The distal tip of the needle is then moved the second distance which can correspond to a target region of the target tissue, for example, the SCS. The method then returns to operation **312** to determine if the actuation rod has moved the first injection distance. If the actuation rod has moved the first injection distance, this confirms that the distal tip of the needle is disposed in the desired target region. For example, the target region can be SCS, which has a lower backpressure than that produced by the sclera. The force exerted by the energy storage member can be configured to overcome this backpressure such that the distal end portion of the actuation rod can be moved the first injection distance and deliver at least a portion of the medicament into the target tissue via the distal tip of the needle. In some embodiments, the force can be between about 2 N to about 6 N. Finally, the distal end portion of the actuation rod is moved a second injection distance until substantially all of the medicament is expelled from the medicament container into the target tissue (e.g., the SCS) at **316**, via the distal tip of the needle. For example, the user can manually move the distal end portion of the actuation rod, or use any suitable actuation mechanism included in the medical injector to move the distal end portion of the actuator the second injection distance.

[0181] In some embodiments, a medical injector can include a needle assembly configured to adjust the length of a needle, for example, to adjust a distance the needle penetrates into a target tissue, for example, an ocular tissue. FIGS. **19** and **20** are schematic illustration of a medical injector **400** in a first configuration and a second configuration, according to an embodiment. The medical injector **400** includes a housing **410**, an actuator rod **420**, a medicament container **430**, a needle **440**, and an adjustment member **423**. Optionally, the medical injector **400** can also include a hub **470** coupled to the housing **410**. The housing **410** is configured to receive a portion of the medicament container **430**. The housing **410** can include any suitable housing, for example, the housing **3210**, or any other housing described herein with respect to a needle assembly.

[0182] The needle **440** can be any suitable puncture member configured to puncture a target tissue. For example, the needle **440** can be a microneedle configured to puncture ocular tissue. In some embodiments, the needle **440** can be a 32-gauge microneedle or a 34-gauge microneedle. In some embodiments, such a microneedle can be substantially similar to or the same as the microneedles described in the '009 PCT application incorporated by reference above. In some embodiments, the shape and/or size of the needle **440** can correspond, at least partially, with at least a portion of a target tissue. For example, in some embodiments, the length of the needle **440** can correspond with a thickness of a portion of ocular tissue such that when the needle **440** is

inserted into the ocular tissue, at least a portion of the needle 440 is disposed within the sclera or suprachoroidal space of the eye, as described in further detail herein. The needle 440 defines a lumen 441 that extends through a proximal end portion 443 and a distal end portion 442 of the needle 440. The distal end portion 442 of the needle 440 can include a bevel or a sharpened tip configured to puncture a target tissue. At least a portion of the proximal end portion of the needle 440 can be disposed in a passageway defined by the hub 470, as described herein.

[0183] The medicament container 430 of the medical injector 400 has a proximal end portion 432 and a distal end portion 434. The medicament container 430 defines an inner volume 436 that can store, house, and/or otherwise contain a substance (e.g., a medicament, a prophylactic agent, a therapeutic agent, and/or a diagnostic agent). For example, in some embodiments, a cartridge or the like containing a drug formulation can be disposed within the inner volume 436 of the medicament container 430. In other embodiments, a drug formulation can be disposed directly within the inner volume 436 (e.g., without a cartridge or other intermediate reservoir). In some embodiments, the inner volume 436 can contain a drug formulation with a volume of about 0.5 mL or less. In other embodiments, the inner volume 436 can contain a drug formulation with a volume of about 0.1 mL. In still other embodiments, the inner volume 436 can contain a drug formulation with a volume greater than about 0.5 mL. In some embodiments, the medicament container 430 can be substantially similar to the medicament container 1310, 2310, 3310, or any other medicament container described herein.

[0184] The proximal end portion 432 of the medicament container 430 is substantially open to receive the actuation rod 420. More specifically, a distal end portion 424 of the actuation rod 420 is disposed within the inner volume 436 and can be moved between a first position (e.g., a proximal position) and a second position (e.g., a distal position). Said another way, the distal end portion 424 of the actuation rod 420 can move an injection distance within the inner volume 426. A sealing member such as, for example, a plug can be coupled to the distal end portion 424 of the actuation rod 420. The sealing member can be configured to form a friction fit with one or more surfaces of the medicament container 430 that define the inner volume 436. In this manner, the seal member and the medicament container 430 can form a fluidic seal that substantially isolates a portion of the inner volume 436 that is distal to the seal member from a portion of the inner volume 436 that is proximal to the seal member. Said another way, the medicament container 430 and the actuation rod 420 form at least a portion of a syringe.

[0185] In some embodiments, the distal end portion 434 of the medicament container 430 is physically and fluidically coupled to the hub 470. For example, in some embodiments, the hub 470 and the distal end portion 434 of the medicament container 430 can form a press fit, a snap fit, a threaded coupling, and/or the like. In other embodiments, the hub 470 can be monolithically formed with the medicament container 430. The hub 470 can define a passageway configured to receive the needle 440 therethrough such that the distal end portion 442 of the needle extends past a distal end surface of the hub 470 by a distance, for example, a first distance d_1 (see e.g., FIG. 19) that can change, for example, to a second distance d_2 (see e.g., FIG. 20) or any other distance, when the needle is moved through a plurality of

discrete increments along the longitudinal axis of the housing 410, as described herein. In some embodiments, the hub 470 can also be configured to limit movement of the adjustment member 422 within the housing 410.

[0186] A proximal end portion of the adjustment member 423 is configured to be coupled to the medicament container 430. The coupling can be performed using any suitable coupling mechanism, for example, a Luer lock, threads, snap-fit, friction-fit, or any other suitable coupling mechanism. A distal end portion of the adjustment member 423 is coupled to the needle 440, for example, to the proximal end portion 443 of the needle 440. In some embodiments, the adjustment member 423 can define a lumen configured to place the medicament container 430 in fluid communication with the needle 440. In some embodiments, the proximal end portion of the adjustment member 423 can also include a flange configured to be removably coupled to the medicament container 430. The adjustment member 420 is configured to transition between a first configuration (FIG. 19) and a second configuration (FIG. 20) to adjust the distance that the distal end portion 442 of the needle 440 extends past the distal end surface of the hub 470. For example, the adjustment member 423 can be movably disposed within the housing 410 such that when the adjustment member 423 is rotated relative to the housing 410, the needle 440 is moved through a plurality of discrete increments along a longitudinal axis of the housing 410. In this manner, the adjustment member 423 can adjust the effective length of the needle 440 in the plurality of discrete increments. Said another way, the adjustment member 423 can allow digital adjustment of the length of the needle 440. While not shown, in some embodiments, the adjustment member 423 and/or the housing 410 can include a plurality of detents. The detents can be configured such that each increment from the plurality of discrete increments is associated with a corresponding detent from the plurality of detents defined by at least one of the adjustment member 423 and/or the housing 410. For example, the housing 410 can include a protrusion configured to be removably disposed within each detent from the plurality of detents when the adjustment member 423 is rotated relative to the housing 410 to move the needle 440 through the plurality of discrete increments. As another example, in some embodiments, a bearing can be coupled within the housing 410 and configured to be removably disposed within each detent from the plurality of detents when the adjustment member 422 is rotated within the housing 410 to move the needle through the plurality of discrete increments. In such embodiments, a bias member can also be disposed in the housing 410 and configured to maintain the bearing within a detent from the plurality of detents. In some embodiments, the medical injector 400 can also include a lock member, for example, a lock, a latch, a tab, a rod, or any other suitable lock member removably coupled to the housing 410. The lock member can be configured to engage the adjustment member 423 to limit movement of the adjustment member 423 relative to the housing 410. In some embodiments, at least a portion of the adjustment member 423 can include an indication portion, for example, a portion including a plurality of markings. The markings can be configured to indicate a distance that the needle 440 extends beyond the housing 410 (e.g., extends beyond the distal end surface of the hub 470). In such embodiments, the housing 410 can define a window such that the indication portion is visible through the window. For

example, a user can view the indication portion through the window to determine the distance that the needle 440 extends beyond the housing 410 and estimate an insertion depth of the distal end 442 of the needle 440 into a target tissue.

[0187] As shown in FIG. 19, in the first configuration of the adjustment member 423, the distal end portion 442 of the needle 440 can be spaced apart from a distal end surface of the hub 470 by a first distance d_1 . The adjustment member 423 can then be moved into a second configuration by moving (e.g., rotating, translating or rotating and translating) the adjustment member 423 within the housing 410. This urges the needle 440 to move in a discrete increment such that distal end portion 442 of the needle 440 extends a second distance d_2 , larger than d_1 , beyond the distal end surface of the hub 470, as shown in FIG. 20. In this manner, a length of the needle 440 extending beyond the distal edge surface of the hub 470 can be adjusted.

[0188] In use, an operator (e.g., a doctor, technician, nurse, physician, ophthalmologist, etc.) can manipulate the delivery device 400 to insert the needle 440 into, for example, an ocular tissue. In this manner, the distal end portion 442 of the needle 440 can be advanced within the target tissue to pierce the sclera and place the hub 470 in contact with an outer surface of the sclera. Moreover, with the adjustment member 422 in the first configuration, the first distance d_1 between the distal end surface of the hub 470 and the distal end portion 442 of the needle 440 can substantially correspond to the thickness of the sclera. In this manner, a distal tip of the needle 440 can be disposed within the sclera (e.g., the sclera 20 of the eye 10 in FIG. 1).

[0189] The adjustment member 423 can be transitioned from the first configuration to the second configuration by moving, translating or rotating the adjustment member 423 within the housing 410. In some embodiments, the moving of the adjustment member 423 can be performed by moving (e.g., rotating) the medicament container 430 relative to the housing 410. This can increase the distance between the distal end surface of the hub 470 and the distal end portion 423 of the needle 440 from the first distance d_1 to the second distance d_2 (as described above). In this manner, when the adjustment member 422 is in the second configuration, the distal tip of the needle 440 can be moved further proximally relative to the ocular tissue to place the lumen 441 of the needle 440 in fluid communication with the suprachoroidal space (e.g., the suprachoroidal space 36 of the eye 10 in FIG. 1). With the lumen 441 of the needle 440 in fluid communication with the suprachoroidal space, the actuation rod 420 can be moved relative to the medicament container 430 from its first position to its second position. With the distal end portion 424 of the actuation rod 420 forming a substantially fluidic seal (i.e., a substantially hermetic seal) with an inner surface of the medicament container 430, the movement of the actuation rod 420 to its second position expels the drug formulation (contained within the inner volume of the medicament container 430) through the lumen 441 of the needle 440. Thus, the medical injector 400 can deliver the drug formulation to the SCS of the eye and the drug formulation can flow within the suprachoroidal space to be delivered to, for example, the posterior region of the eye.

[0190] By adjusting the distance between the distal edge surface of the hub 470 and the distal end portion 442 of the needle 440 in discrete increments using the adjustment member 423, the distal end portion 442 of the needle 440 can

be placed within the SCS with more accuracy and precision than would otherwise be achieved with a fixed distance therebetween. For example, in some instances, the adjustment member 423 can be arranged such that the first distance d_1 between the distal end surface of the hub 470 and the distal end portion 442 of the needle 440 is less than the thickness of the sclera. Thus, the adjustment member 423 can be moved to the second configuration to increase the distance between the distal edge surface of the hub 470 and the distal end portion 442 of the needle 440 (e.g., to the second distance d_2) that is greater than the thickness of the sclera, thereby placing the distal end portion 442 of the needle 440 in contact with the SCS. Moreover, the second distance d_2 can be less than a combined thickness of the sclera and the SCS such that when the adjustment member 423 is moved to the second configuration, the distal end portion 442 of the needle 440 does not pierce the choroid (e.g., the choroid 28 of the eye 10 in FIG. 1).

[0191] The arrangement of the adjustment member 423, the needle 440, and the hub 470 allows for control of the effective length of the needle 440. Accordingly, the medical injector 400 can be used for procedures involving different portions of a target tissue (e.g., the eye) having different thicknesses. Moreover, control over the effective length of the needle 440, as described herein, allows the medical injector 400 to be used on a variety of patients having a range of anatomical differences (e.g., the device can be used in adult applications and pediatric applications).

[0192] The transition of the adjustment member 423 (and any of the needle assemblies described herein) between the first configuration and the second configuration can be performed at any suitable time before and/or during a procedure. For example, in some embodiments, the adjustment member 423 can be transitioned to the second configuration to set and/or adjust the effective length of the needle 440 before insertion of the needle 440 into the target tissue. The desired effective length of the needle 440 in such embodiments can be based on the known thickness of the sclera based on pre-operation measurements or the like. In other embodiments, however, the adjustment member 422 can be transitioned to the second configuration after the needle 440 has been inserted into the target tissue. In this manner, the adjustment member 422 can provide the operator with a mechanism for adjusting the effective length of the needle 440 in discrete increments during the procedure (e.g., based on tactile feedback, optical feedback or the like).

[0193] The medical injector 400 is shown in FIGS. 19-20 by way of example to provide context to the proceeding discussion. In this manner and for simplicity, only portions of a medical injector according to specific embodiments are shown. It should be understood that any of the embodiments described herein can be disposed in a similar arrangement as described above with reference to FIGS. 19-20. Moreover, while the delivery device 400 is shown and described with reference to FIGS. 19-20 as having a particular arrangement, the embodiments described herein can be used with any suitable delivery mechanism or device.

[0194] In some embodiments, a system for injecting a medicament into ocular tissue can include a needle assembly configured to perform any of the functions described herein. In other embodiments, a needle assembly can be configured to adjust the length and/or insertion depth of the needle. Referring now to FIGS. 21-33 a system 3000 can include at least a housing 3110, a medicament containment chamber

3310, an actuator **3320**, and a needle assembly **3200**. The needle assembly **3200** can be configured to adjust a length of a puncturing member **3240** (also referred to as a delivery member and/or a needle) included in the needle assembly **3200**, as described herein. The system **3000** can be configured to deliver a medicament to a layer or region of an eye of patient, for example, to the SCS of the eye.

[0195] The housing **3110** can include any of the housings described herein and is configured to receive at least a portion of the medicament containment chamber **3310**. In some embodiments, the housing **3110** can be substantially similar to the housing **1110** described with respect to the system **1000**. In such embodiments, the housing **3110** can be configured for manual manipulation of the actuator **3320** to inject the medicament. In some embodiments, an injector assembly can be disposed in the housing **3110**. The injector assembly can be substantially similar to the injector assembly **2100** or any other injector assembly described herein, and is therefore not described in further detail herein.

[0196] The medicament containment chamber **3310** defines an internal volume **3316** configured to house a medicament (e.g., a VEGF, a VEGF inhibitor, triamcinolone acetonide, any other medicament described herein, or a combination thereof). The medicament containment chamber **3310** includes an engagement portion disposed inside the internal volume defined by the housing **3110**. The medicament containment chamber **3310** also includes a delivery portion disposed outside the internal volume defined by the housing **3110** and coupled to the needle assembly **3200**. The medicament containment chamber **3310** can be substantially similar to the medicament containment chamber **1310**, **2310** or any other medicament containment chamber described herein, and is therefore not described in further detail herein.

[0197] The actuator **3320** includes an engagement portion and a plunger portion. The plunger portion is slidably disposed inside the internal volume **3316** defined by the medicament containment chamber **3310** and is configured to draw the medicament into or expel the medicament from the internal volume **3316** defined by the medicament containment chamber **3310**. The actuator **3320** can be substantially similar to the actuator **1320**, **2320** or any other actuator described herein, and is therefore not described in further detail herein.

[0198] As shown in FIG. 22, the needle assembly **3200** includes a housing **3210**, a bearing (or lock ball) **3220**, an adjustment member **3230**, a puncturing member **3240**, a lead screw **3242**, a bushing **3250**, a locking pin **3260**, and a hub **3270**. The needle assembly **3200** is configured to enable linear translation of the puncturing member **3240** in fixed and/or discrete increments to allow a user to insert the puncturing member to a desired depth within the eye, for example, insertion to the depth of the SCS.

[0199] The housing **3210** (FIGS. 23A-C, FIGS. 32 and 33) includes a proximal portion **3211** and a distal portion **3212**. The housing **3210** can be substantially cylindrical in shape and tapers towards the distal portion **3212**. The housing **3210** defines an internal **3213** volume within which the bearing **3220**, the adjustment member **3230**, at least a portion of the puncturing member **3240**, the lead screw **3242**, the bushing **3250**, and at least a portion of the locking pin **3260** can be disposed. The internal volume **3213** defines a substantially circular cross-section to allow one or more components, for example, the adjustment member **3230** and/or the lead screw **3242** to rotate about a longitudinal axis

A_L of the system **3000** within the internal volume **3213**. A delivery portion of the medicament containment chamber **3310** can also be disposed in the internal volume **3213**. The distal portion **3212** of the housing **3210** is configured to receive a proximal end **3272** of the hub **3270** (see FIGS. 31A-31C) or any other hub described herein. Coupling features can be included in the distal portion **3212** to removably or fixedly couple the proximal end **3272** of the hub **3270**. Suitable coupling features can include, for example, a friction fit mechanism, threads, a Luer assembly, adhesive, lock, latch, groove, indents, detents, a snap-fit mechanism, or any other suitable coupling mechanism. A multiplicity of ridges **3214** are disposed on an outer surface of the housing **3210**. The ridges **3214** can be configured to allow the user to ergonomically grip the housing **3210**, for example, when performing an injection of a medicament into the eye. A window **3216** is defined in the housing **3210**. The window **3216** is configured to align with an intermediate portion **3233** of the adjustment member **3230**, such that the user can see a set of markings **3236** defined on an outer surface of the intermediate portion **3233**. The markings **3236** can indicate a length of the puncturing member **3240** protruding from a distal end **3274** of the hub **3270**, which can correspond to the insertion depth of the puncturing member **3240** (e.g., a distance that a distal tip of the puncturing member **3240** traverses into the ocular tissue). A cavity **3218** is defined in the housing **3210**. The cavity **3218** is configured to receive the bearing **3220**, a biasing member **3221** and a plug **3222**, as described in further detail herein. A set of through holes **3219** are defined in the sidewall of the housing **3210**. The locking pin **3260** is inserted through the through holes **3219**, such that the locking pin passes through the internal volume **3213** defined by the housing **3210**, and at least a portion of the locking pin **3260** is disposed within the internal volume **3213**.

[0200] The bearing (or lock ball) **3220** is disposed in the cavity **3218** of the housing **3210**. The bearing can be any suitable bearing, for example, a metallic, plastic, or wooden bearing, a contoured cylindrical member, or any other suitable bearing. A first end of the biasing member **3221** is coupled and/or engaged with to the bearing **3220**, and a second end of the biasing member **3221** is coupled to the plug **3222**. The biasing member **3221** can include a spring, for example, helical, compression, extension, spring washers, Belleville washers, tapered, any other type of spring, or any other suitable biasing member. At least a portion of the plug **3222** (FIGS. 24A-B) is disposed within the cavity such that the plug **3222** secures the biasing member **3221** and the bearing **3220** inside the cavity **3218**. The plug **3222** can include a dome shaped surface with rounded edges. In some embodiments, the plug **3222** can be fixedly coupled to the cavity **3218**, for example, via adhesives. In some embodiments, the plug **3222** can be removably coupled to the cavity **3218** using a suitable coupling mechanism such as, for example, friction-fit, threads, grooves, indents, detents, any other suitable coupling mechanism or combination thereof. The plug **3222** can be configured to exert a force on and/or maintain a position of the biasing member **3221** such that the biasing member **3221** exerts a force against the bearing **3220**. The bearing (or lock ball) **3220** is configured to engage at least one of a set of detents **3235** disposed on a distal portion **3234** of the adjustment member **3230**. The biasing member **3221** biases the bearing **3220** inward relative to the detents **3235** such that the bearing **3220** prevents

the adjustment member 3230 from rotating freely relative to the housing 3210 about the longitudinal axis A_L of the system 3000. In this manner, the bearing 3220 allows a digital length adjustment of a length of the puncturing member 3240, as described in further detail herein. Similarly stated, the engagement of the bearing 3220 in the detents 3235 allows the rotational position of the adjustment member 3230 (and thus the effective length of the puncturing member 3240) to be adjusted in discrete increments.

[0201] The adjustment member 3230 (FIG. 25, FIGS. 26A-B, FIG. 33) includes a proximal portion 3232, an intermediate portion 3233, and a distal portion 3234. The proximal portion 3232 is configured to couple to a delivery portion of the medicament containment chamber 3310. The proximal portion 3232 can include coupling features, for example, Luer lock connectors, threads, grooves, notches, indents, snap-fit, friction-fit, lock, latch, any other suitable coupling features or combination thereof. In this manner, the distal end portion of the medicament containment chamber 3310 can be coupled to the adjustment member 3230. In some embodiments, the delivery portion of the medicament containment chamber 3310 can be fixedly coupled to the proximal portion 3232, for example, by an adhesive. In other embodiments, the delivery portion of the medicament containment chamber 3310 can be removably coupled to the proximal portion 3232, for example, to allow the user to replace the medicament containment chamber 3310 to reuse the needle assembly 3200. In some embodiments, a locking feature (not shown), for example, a lock, a latch, or a friction fit, can be included in the proximal portion 3232. The locking feature can be configured to prevent uncoupling of the delivery portion of the medicament containment chamber 3310 from the proximal portion 3232 of the adjustment member 3230 due to a rotation of the medicament containment chamber 3310 (e.g., because of a rotation of the housing 3310 by the user). For example, a user can rotate the housing 3310 about the longitudinal axis A_L of the system 3000 urging the medicament containment chamber 3310 and thereby, the adjustment member 3230 to also rotate about the longitudinal axis A_L . In this manner, the adjustment member 3230 can be configured to vary the length of the puncturing member 3240 protruding through the distal end of the 3274 of the hub 3270, as described in further detail herein.

[0202] The intermediate portion 3233 of the adjustment member 3230 includes markings 3236 corresponding to the length of the puncturing member 3240 protruding through distal end 3274 the hub 3270. The intermediate portion 3233 is aligned with the window 3216 included in the housing 3210 such that the user can see the markings 3236 through the window 3216 and determine the protruding length of the puncturing member 3240. This can, for example, indicate the insertion depth of the puncturing member 3240 into the eye. In some embodiments, the markings 3236 can indicate a length in the range of about 850 microns, 950 microns, 1050 microns, 1150 microns, or about 1250 microns. In such embodiments, the length interval can be about 100 microns. The intermediate portion 3233 also includes a fluidic channel 3238 defined therethrough. The fluidic channel 3238 can be in fluidic communication with the internal volume 3316 of the medicament containment chamber 3310.

[0203] The distal portion 3234 is fixedly coupled to a proximal portion 3244 of the lead screw 3242. For example, the proximal portion 3244 of the lead screw 3242 can be welded, bonded, adhered, bolted, riveted, or fixedly

mounted using any other coupling mechanism to the distal portion 3234 of the adjustment member 3230. In this manner, a rotation of the adjustment member 3230 can also rotate the lead screw 3242 about the longitudinal axis A_L of the system 3000. The set of detents 3235 are defined on the outer surface of the distal portion 3234 and are configured to be engaged by the bearing 3220, as described herein. Although the lead screw 3242 and the adjustment member 3230 are shown and described as being separate components that are joined together, in other embodiments, the lead screw 3242 and the adjustment member 3230 can be monolithically formed.

[0204] The lead screw 3242 (FIGS. 22, 25, 27A-B, 33) includes the proximal portion 3244 and a distal portion 3246. The proximal portion 3244 is fixedly coupled to distal portion 3234 of the adjustment member 3230, as described herein. The distal portion 3246 is coupled to a proximal end of the puncturing member 3240 coupled thereto. The puncturing member 3240 can be a needle (e.g., a 27 gauge, a 30 gauge, or even smaller needle), or any other puncturing member described herein. The puncturing member 3240 defines a lumen 3241 (FIG. 33) configured to fluidically communicate the medicament to a target tissue of the eye, for example, the SCS. The puncturing member 3240 is fixedly coupled to the lead screw 3242 by any suitable mechanism. In this manner, a rotation of the adjustment member 3230 and lead screw 3242 about the longitudinal axis A_L , which causes a linear translation of the lead screw 3242 along the longitudinal axis A_L , also urges the puncturing member 3240 to rotate about or translate along the longitudinal axis A_L , respectively. The lead screw 3242 defines a lumen 3247 therethrough. The lumen 3247 is in fluidic communication with the fluidic channel 3238 of the adjustment member 3230 and the lumen 3241 of the puncturing member 3240. Thus, the fluidic channel 3238 of the adjustment member 3230, and the lumen 3247 of the lead screw 3242 provide a fluidic path for the medicament to be communicated between the internal volume 3316 of the medicament containment chamber 3310 and the lumen 3241 of the puncturing member 3240, for example, delivered to a target layer (e.g., the SCS) of the eye.

[0205] At least a portion of the outer surface of the lead screw 3242, for example, the distal portion 3246, includes threads 3248. The threads 3248 are configured to mate with mating threads 3254 included in the bushing 3250. The bushing 3250 (FIGS. 22, 28A-C, FIG. 33) is fixedly disposed inside the internal volume 3213 defined by the housing 3210. The bushing 3250 defines a lumen 3252 configured to receive the distal portion 3246 of the lead screw 3242 such that the threads 3248 of the lead screw 3242 are mated with the mating threads 3254 disposed along the surface of the lumen 3252 of the bushing 3250. Because the bushing 3250 is fixedly disposed in the housing 3210, a rotation of the adjustment member 3230 and the lead screw 3242 relative to the housing 3210 about the longitudinal axis A_L urges the lead screw 3242 to move linearly relative to the housing 3210 along the longitudinal axis A_L of the system 3000. Each full rotation of the lead screw 3242 can correspond to a predetermined translation distance of the lead screw 3242 and thereby, the puncturing member 3240, along the longitudinal axis A_L of the system 3000. In this manner, the adjustment member 3230 can be rotated (e.g., by rotating the housing 3110) to rotate the lead screw 3230 and thereby,

advance or retract a predetermined length of the puncturing member 3240 from the distal end 3274 of the hub 3270.

[0206] The locking pin 3260 (FIG. 29) is coupled to a tab 3262. As shown in FIGS. 30A-C, the tab 3262 includes a cavity 3264 configured to receive at least a portion of the locking pin 3260. In some embodiments, the tab 3262 can be removably coupled to the locking pin 3260, for example via, threads, grooves, notches, indents, detents, friction fit, or coupled using any other suitable coupling mechanism. In some embodiments, the tab 3262 can be fixedly coupled to the locking pin 3260, for example, via adhesives. At least a portion of the tab 3262 can be substantially flat. Although the locking pin 3260 is shown as being substantially cylindrical, in other embodiments, the locking pin can define a circular, oval, square, rectangular, polygonal, or any other suitable cross section. The locking pin 3260 is configured to be inserted through and/or within the through holes 3219 of the housing 3210, such that at least a portion of the locking pin 3260 is disposed in the internal volume 3213 defined by the housing 3210.

[0207] The locking pin 3260 is configured to be moved from a first configuration (or position) and a second configuration (or position). In the first configuration, the locking pin 3260 is inserted through the through holes 3219 and at least a portion of the locking pin 3260 is disposed in proximity of the intermediate portion 3233 of the adjustment member 3230. In the first configuration, the locking pin 3260 is configured to prevent a rotation of the adjustment member 3230 relative to the housing 3210, and thereby, the lead screw 3242. Thus, when the locking pin 3260 is in the first configuration, movement of the puncturing member 3240 along the longitudinal axis A_L of the system 3000 distally relative to the medicament containment chamber 3310, for example, because of the rotation of the adjustment member 3260, is limited. In a second configuration, the user can pull the tab 3262 and thereby the locking pin 3260 out of the through holes 3219 and the internal volume 3213. Thus, in the second configuration the adjustment member 3230 can be free to rotate relative to the housing 3210, and thus move linearly along the longitudinal axis A_L , for example, to advance a length of the puncturing member 3240 from a distal end 3274 of the hub 3270. Said another way, the locking pin 3260 can serve as a safety mechanism to prevent accidental activation of the needle assembly 3200 and prevent advancement of the puncturing member 3260 out of the distal end 3274 of the hub 3270.

[0208] The hub 3270 includes a proximal portion 3272 and a distal portion 3274. The proximal portion 3272 is configured to be coupled to the distal portion 3214 of the housing 3210 (or any other housing defined herein) using any suitable coupling mechanism, for example, friction-fit, threads, snap-fit, notches, grooves, indents, detents, any other suitable coupling mechanism or combination thereof. The hub 3270 defines a lumen 3276 therethrough. At least a portion of the puncturing member 3240 (or any other puncturing member described herein) can be disposed in the lumen 3276, and can be configured to advance through the lumen 3276 out of the distal end 3274. The distal end 3274 of the hub 3270 is substantially flat, and is configured to contact an outer surface of the conjunctiva of the eye. Although the hub 3270 is shown and described as having a flat distal end (or “contact”) surface, in some embodiments, a distal portion of a hub can define substantially convex or curved surface, as described in further detail herein.

[0209] In operation, the needle assembly 3200 is configured to allow a user to adjust a length of the puncturing member 3240 emerging from the distal end of the hub 3270. FIG. 32 shows a perspective view of the needle assembly 3200 and FIG. 33 shows a cross-section of the needle assembly 3200 taken along the line 33-33. While shown as including the hub 3270, any other hub can be coupled to the distal end 3212 of the housing 3210, for example, the hub 7270, 8270, 9270, or any other hub described herein. The proximal portion 3232 of the adjustment member 3230 can be coupled to the delivery portion 3314 of the medicament containment chamber 3310. In a first configuration, a first length of the puncturing member 3240 can be protruding from the distal end 3274 of the hub 3270, for example, about 850 microns. This information can be communicated to the user via the markings 3236 visible to the user through the window 3216. At least a portion of the bearing 3220 is disposed in a first indent 3235 defined on the outer surface of the distal portion 3234 of the adjustment member 3230. The bearing 3220 is biased against the first indent 3235 by the biasing member 3221, and prevents any inadvertent rotation of the adjustment member 3270, thus maintaining the position of adjustment member 3230. In the first configuration, the puncturing member 3240 can protrude a known distance from the distal end 3274 of the hub, for example a length of about 850 microns.

[0210] To enable actuation of the needle assembly 3200, the user can remove the locking pin 3260 by pulling on the tab 3262 to remove the locking pin 3260 from the housing 3210. The user then disposes the distal end 3274 of the hub 3270 against the outer surface of the conjunctiva of the eye, which results in the initial length of the puncturing member 3240 being inserted into the eye. Similarly stated, the user can apply a distal force on the system 3000 such that a distal end of the puncturing member 3240 pierces the conjunctiva and is disposed in an ocular tissue layer below the conjunctiva, for example, the sclera. The user can then determine, using any suitable technique, if a distal end of the puncturing member 3240 is within or otherwise near a target layer, for example, the SCS of the eye. In some embodiments, the user can determine that the distal end of the puncturing member 3240 is not in a target layer of the eye, for example, the SCS. For example, in some embodiments, a relative thickness of the ocular tissue layers can be known to the user via prior visualization techniques. In other embodiments the system 3000 can include an injection assembly, for example, the injection assembly 111, 2100, or any other injection assembly described herein, which can be activated and thereby inform the user that the distal end of the puncturing member 3240 is not in the target layer, as described before herein. More particularly, because the injection assembly provides an “injection assist” force within a predetermined range, when the end of the puncturing member 3240 has not reached the SCS, actuation of the injection assembly will not result in movement of the plug within the medicament containment chamber. Thus, the user will receive feedback that the puncturing member 3240 is not in the target region (i.e., by not seeing any movement of the plug).

[0211] To move the needle assembly 3200 to a second configuration, the user can apply a first torque to rotate or otherwise twist the medicament containment chamber 3310 such that the adjustment member 3230 rotates relative to the housing 3210 about the longitudinal axis A_L . The first torque can urge the bearing 3220 to slide out of the first indent 3235

such that the adjustment member **3230** is free to rotate by application of a second torque substantially smaller than the first torque. The rotation of the adjustment member **3230** urges the lead screw **3242** to also rotate in the bushing **3250**. Since the bushing **3250** is fixedly disposed in the internal volume **3213** of the housing **3210**, the lead screw **3242** translates linearly along the longitudinal axis A_L . This urges the puncturing member **3240** to also translate and advance deeper into the ocular tissue layers. The adjustment member **3230** can be rotated until the bearing **3220** approaches a second indent **3235** of the set of the indents **3235**. At least a portion of the bearing **3220** moves into the second indent **3235** and thus prevents further rotation of the adjustment member **3230** by the second torque. Each indent **3235** can correspond to predetermined length of the puncturing member **3240** protruding through the distal end **3274** of the hub **3270**. For example, the second indent **3235** can correspond to a protrusion length of the puncturing member **3240** of about 950 microns. A third indent **3235** can correspond to a protrusion length of the puncturing member **3240** of about 1050 microns, and so on. Thus, in some embodiments, each indent **3235** can correspond to a difference in protrusion length of the puncturing member **3240** of about 100 microns. Since, in the second configuration, the bearing **3220** is disposed in the second indent **3235**, the adjustment member **3230** can no longer be rotated by application of the second torque. The user can now apply a third torque, greater than the second torque (e.g., substantially equal to the first torque) to further rotate the adjustment member **3230**, thereby increasing the protrusion length or otherwise insertion depth of the puncturing member **3240**. In this manner, the needle assembly **3200** can serve as a digital length adjustment mechanism to allow the user to adjust a protrusion length or otherwise insertion depth of the puncturing member **3240** in discrete increments, reliably and repeatably. Furthermore, the different torques required for rotation of the adjustment member **3240** at different positions of the bearing **3220** relative to the indents **3235**, also provide a tactile feedback to the user in adjusting the protruding length or otherwise insertion depth of the puncturing member **3240**.

[0212] In some embodiments, a device includes an adjustment member configured to move relative to a hub and/or a puncture member. Moreover, although being described above as transitionable between a first configuration and a second configuration, in some embodiments, an adjustment member can be transitionable between any number of configurations and/or positions. For example, FIGS. **34-36** are schematic illustrations of a portion of a delivery device according to an embodiment. As shown in FIG. **34**, a hub **4270** is coupled to a puncture member **4240** and an adjustment member **4230**. The hub **4270** has a proximal end portion **4271** and a distal end portion **4272**. The proximal end portion **4271** can be physically and fluidically coupled to a fluid reservoir such as, for example, the housing **4230** of the delivery device **400**, **100**, **1000**, **2000**, **3000**, or any other delivery device or medical injector described herein). Although not shown in FIGS. **34-36**, the proximal end portion **4271** of the hub **4270** can be coupled to a housing of a delivery device using any suitable coupling method such as, for example, a press fit, a snap fit, a threaded coupling, a Luer connection, a mechanical fastener, an adhesive, and/or the like. In other embodiments, the hub **4270** can be monolithically formed with a housing of a delivery device. For example, the hub **4270** can be included in and/or form

distal end portion of a housing (e.g., the medical containment chamber **1310**, **2310**, **3310**, or any other medical containment chamber described herein). Thus, an inner volume of the hub **4270** can be placed in fluid communication with a drug formulation contained within a fluid reservoir (e.g., a medicament container or the like not shown in FIGS. **34-36**).

[0213] As shown in FIG. **34**, the distal end portion **4272** of the hub **4270** includes a substantially elongate portion that includes a set of annular walls **4274**. As described in further detail herein, the annular walls **4274** have an outer surface **4275** that includes and/or forms a set of threads **4277** that are configured to engage a portion of the adjustment member **4230**. The annular walls **4274** define a lumen **4276** that extends through the distal end portion **4272** of the hub **4270**. The lumen **4276** is configured to receive a portion of the puncture member **4240** to physically and fluidically couple the puncture member **4240** to the hub **4270**.

[0214] The puncture member **4240** (also referred to herein as “microneedle”) can be configured to puncture and/or penetrate a portion of the eye to deliver a drug formulation to, for example, the suprachoroidal space. In some embodiments, the puncture member **4240** can be a 32-gauge microneedle or a 34-gauge microneedle. The microneedle **4240** has a proximal end portion **4242** and a distal end portion **4244**, and defines a lumen **4241**. As shown in FIG. **34**, the proximal end portion **4242** is disposed within the lumen **4276** of the hub **4270**. For example, in some embodiments, the hub **4270** can be over-molded about the proximal end portion **4242** of the puncture member **4240**. In other embodiments, the hub **4270** and the puncture member **4240** can be monolithically formed (e.g., the puncture member **4240** can be a microcatheter or the like that is unitarily formed with the hub **4270**). Therefore, with the hub **4270** physically and fluidically coupled to a housing or fluid reservoir (as described above), the lumen **4241** of the puncture member **4240** can be placed in fluid communication with a drug formulation contained therein.

[0215] As described above, the lumen **4241** of the puncture member **4240** extends through the proximal end portion **4242** and the distal end portion **4244**. In this manner, the lumen **4241** can be placed in fluid communication with a volume substantially outside the microneedle **4240**. The distal end portion **4244** can be any suitable shape, size, or configuration. For example, in some embodiments, the distal end portion **4244** can form a bevel or the like. In some embodiments, the distal end portion **4244** can be substantially similar to or the same as those described in the '009 PCT application incorporated by reference above. In this manner, the distal end portion **4244** of the puncture member **4240** can be configured to pierce an ocular tissue while minimizing deformation of the tissue at the insertion site.

[0216] As shown, the microneedle **4240** extends from the distal end portion **4272** of the hub **4270** in the distal direction. In this manner, the microneedle **4240** can have a shaft length H between a distal edge **4245** of the puncture member **4240** and a distal surface of the hub **4270**. The shaft length H can be any suitable length. For example, in some embodiments, the shaft length H can substantially correspond to at least a portion of the eye. In some embodiments, the shaft length H can be such that when the microneedle **4240** is inserted into the eye, the distal end portion **4244** of the microneedle **4240** is disposed within the suprachoroidal space without puncturing the choroid. By way of example,

the shaft length H of the microneedle **4240** can be about 1000 μm or less, about 900 μm or less, about 850 μm or less, about 800 μm or less, about 750 μm or less, about 700 μm or less, about 650 μm or less, or about 600 μm or less. In some embodiments, the shaft length H of the microneedle **4240** can be about 750 μm . In other embodiments, the shaft length of the microneedle **4240** can be about 800 μm , or about 850 μm , or about 900 μm , or about 950 μm , or about 1 mm.

[0217] The adjustment member **4230** can be any suitable shape, size, or configuration and can be movably disposed about a portion of the hub **4270** and the puncture member **4240**. The adjustment member **4230** has a proximal end portion **4231** and a distal end portion **4232** and defines an opening **4236** therethrough. Moreover, the adjustment member **4230** includes an inner surface **4235** includes and/or forms a set of threads **4237** that can matingly engage the threads **4277** of the hub **4270** (described above). In this manner, the distal end portion **4272** of the hub **4270** can be movably disposed within a portion of the opening **4236**. For example, with the distal end portion **4272** of the hub **4270** disposed within the portion of the opening **4236**, the adjustment member **4230** can be rotated relative to the hub **4270** to advance the threads **4237** of the adjustment member **4230** along a length of the threads **4277** of the hub **4270**. Thus, the adjustment member **4230** can be moved between a first position relative to the hub **4270** (e.g., a distal position, see e.g., FIGS. **34** and **35**) and a second position relative to the hub **4270** (e.g., a proximal position, see e.g., FIG. **36**). Moreover, the adjustment member **4230** can be moved to any number of different positions relative to the hub **4270**.

[0218] The arrangement of the hub **4270**, the adjustment member **4230** and the puncture member **4240** is such that a portion of the puncture member **4240** is disposed within the opening **4236** defined by the adjustment member **4230** while the distal end portion **4244** of the puncture member **4240** extends beyond a distal surface **4234** of the adjustment member **4230**. For example, as shown in FIG. **34**, the distal end portion **4244** of the puncture member **4240** can extend a distance D_1 (also referred to as an effective length of the puncture member **310**) from the distal surface **4234** of the adjustment member **4230**. Similarly stated, the distal edge **4245** of the puncture member **4240** is spaced apart from the distal surface of the adjustment member **4230** by the distance D_1 . Thus, when the adjustment member **4230** is moved a given distance relative to the hub **4270**, the effective length of the puncture member **4240** (i.e., the distance D_1) is changed by a corresponding distance. By way of example, while the adjustment member **4230** is in the first position relative to the hub **4270** (e.g., the distal position), the distance D_1 can be, for example, 350 μm and when the adjustment member **4230** is moved to the second position relative to the hub **4270** (e.g., the proximal position), the distance D_1 can be increased to, for example, 650 μm . In other embodiments, the distance D_1 can be increased to, for example, 500 μm , 550 μm , 600 μm , 700 μm , 750 μm , 800 μm , 850 μm , 900 μm , 950 μm , or any suitable fraction thereof.

[0219] As shown in FIGS. **35** and **36**, in use, a user (e.g., a doctor, technician, nurse, physician, ophthalmologist, etc.) can manipulate a delivery device (not shown) to insert the puncture member **4240** into, for example, a portion of the eye **10**. In this manner, the distal end portion **4244** of the puncture member **4240** can be advanced through a portion of

the sclera **20** until the distal surface **4234** of the adjustment member **4230** is placed in contact with an outer surface of the sclera **20**. With the adjustment member **4230** in the first configuration, the distance D_1 (e.g., the first distance) between the distal surface **4234** of the adjustment member **4230** and the distal edge **4245** of the puncture member **4240** can substantially depend on and/or be associated with the thickness of the sclera **20**. For example, in some embodiments, when the adjustment member **4230** is in the first configuration, the distance D_1 (FIG. **34**) between the adjustment member **4230** and the distal edge **4245** can be about 450 μm . In other embodiments, the distance D_1 when the adjustment member **4230** is in the first configuration can be about 350 μm , 400 μm , 500 μm , 550 μm , 600 μm , 650 μm , 700 μm , 750 μm , or any fraction therebetween. In still other embodiments, the distance D_1 when the adjustment member **4230** is in the first configuration can be less than 350 μm . In this manner, the distal edge **4245** of the puncture member **4240** can be disposed within the sclera **20**, as shown in FIG. **35**. While shown in FIG. **35** as being disposed entirely in the sclera **20**, in other embodiments, at least a portion of the distal edge **4245** can be disposed within the suprachoroidal space **36**.

[0220] The adjustment member **4230** can be moved from its first position relative to the hub **4270** to its second position relative to the hub **4270** to increase the distance D_1 (FIG. **34**) between the adjustment member **4230** and the distal edge **4245** of the puncture member **4240** from the first distance (FIG. **35**) to a second distance, as shown in FIG. **36**. For example, in some embodiments, a user can manipulate a grip portion (e.g., a textured finish and/or a set of handles, ribs, detents, grooves, etc.) of the adjustment member **4230** to rotate the adjustment member **4230** relative to the hub **4270**, as indicated by the arrow AA in FIG. **36**. In this manner, the threads **4237** of the adjustment member **4230** are advanced along a length of the threads **4277** of the hub **4270**. Thus, the hub **4270** is moved in a distal direction relative to the adjustment member **4230** such that the adjustment member **4230** is placed its second position relative to the hub **4270**, as indicated by the arrow BB in FIG. **36**. The movement of the adjustment member **4230** can be performed at any suitable time, i.e., either before or while the puncture member **4240** is disposed within the sclera **20**.

[0221] Expanding further, by rotating the adjustment member **4230** relative to the hub **4270** (as indicated by the arrow AA), the adjustment member **4230** is placed in its second position relative to the hub **4270**. Thus, with the adjustment member **4230** in the second position, the distance D_1 (FIG. **34**) is increased between the distal surface **4234** of the adjustment member **4230** and the distal edge **4245** of the puncture member **4240** (e.g., to the second distance). In some embodiments, the distance D_1 can be increased to about 600 μm . In other embodiments, the distance D_1 can be increased to about 650 μm , 700 μm , 750 μm , 800 μm , 850 μm , 900 μm , 950 μm , 1000 μm , or any fraction therebetween. In still other embodiments, the distance D_1 can be increased to less than 600 μm (e.g., such as, for example, in use on pediatric eyes).

[0222] As shown in FIG. **36**, the distal movement of the hub **4270** can allow the distal end portion **4244** of the puncture member **4240** (e.g., in a distal direction) to be moved distally relative to the sclera **20** to place the lumen **4241** of the puncture member **4240** in fluid communication with the suprachoroidal space **36**. With the lumen **4241** of

the puncture member 4240 in fluid communication with the suprachoroidal space 36, a drug formulation (contained within a fluid reservoir that is in fluid communication with the lumen 4241, for example, as described above with reference to the medical injector 400 of FIGS. 19-20) can be expelled through the lumen 4241 of the puncture member 4240 and into the suprachoroidal space 36 of the eye 10. In this manner, the drug formulation can flow within the suprachoroidal space 36 to be delivered to, for example, the posterior region of the eye (e.g., the posterior region 14 of the eye 10 in FIG. 1). Moreover, with the adjustment member 4230 in the second configuration, the distance between the distal surface 4234 of the adjustment member 4230 and the distal edge 4245 of the puncture member 4240 (e.g., the distance D_1 in FIG. 34) can be less than a combined thickness of the sclera 20 and the suprachoroidal space 36 such that the distal end portion 4244 of the puncture member 4240 does not pierce the choroid 28.

[0223] In some embodiments, the relative position of the distal edge 4245 of the puncture member 4240 within the eye can be localized (e.g., determined, realized, etc.) via any suitable method. For example, in some instances, the amount of force exerted to advance the distal edge 4245 of the puncture member 4240 through the sclera 20 can be greater than an amount of force exerted to advance the distal edge 4245 through the suprachoroidal space 36. Thus, reduction in the amount of force that is exerted to advance the distal end portion 4244 of the puncture member 4240 can indicate to a user the relative position of the distal edge 4245 of the puncture member 4240 in the eye. In some instances, imaging techniques (e.g., fluoroscopy, X-ray Computed Tomography (CT) scans, or the like) can be used to provide an indication of the relative position of the distal edge 4245 with respect to the anatomy of the target tissue.

[0224] Although not shown in FIGS. 34-36, in some embodiments, the hub 4270 and/or the adjustment member 4230 can provide an indicator associated with the distance D_1 between the adjustment member 4230 and the distal edge 4245 of the puncture member 4240. In some embodiments, the indicator can be a visual indicator such as a measuring scale or the like. For example, in some embodiments, the puncture member 4240 can include indicia (e.g., lines, markings, tic marks, etc.) that represents a gradation of a length of the puncture member 4240 associated with the distance D_1 between the distal surface 4234 of the adjustment member 4230 and the distal edge 4245 of the puncture member 4240. In some embodiments, the markings can represent distances of 100 microns or less. In this manner, a user can view the indicia to determine, for example, a change in the distance D_1 that would otherwise be indeterminate. In other embodiments, the adjustment member 4230 and/or the hub 4270 can produce an audible or haptic indicator such as, for example, a “clicking” sound or the like.

[0225] Although the adjustment member 4230 is described above with reference to FIGS. 34-36 as rotating about the hub 4270 to change the distance (e.g., the distance D_1 in FIG. 34) between the distal surface 4234 of the adjustment member 4230 and the distal edge 4245 of the puncture member 4240, in other embodiments, an adjustment member can be transitioned relative to a hub in any suitable manner. For example, in some embodiments, an outer surface of a hub can include a set of protrusions that can engage a set of detents defined by an inner surface of an adjustment member (or vice versa). In such embodiments,

the adjustment member can be moved linearly relative to the hub such that the detents of the adjustment member sequentially engage the protrusions of the hub.

[0226] FIG. 37 is a schematic illustration of a portion of a delivery device according to an embodiment. As shown, a hub 5270 is coupled to a puncture member 5240 and an adjustment member 5230. The hub 5270 has a proximal end portion 5271 and a distal end portion 5272. The proximal end portion 5271 can be physically and fluidically coupled to a fluid reservoir such as, for example, the medicament container 430 of the medical injector 400 described above with reference to FIGS. 19-20, or any other medicament container described herein. Although not shown in FIG. 37, the proximal end portion 5271 of the hub 5270 can be coupled to a housing (e.g., a medicament container) of a delivery device using any suitable coupling method such as, for example, a press fit, a snap fit, a threaded coupling, a Luer connection, a mechanical fastener, an adhesive, and/or the like. In other embodiments, the hub 5270 can be monolithically formed with a housing of a delivery device. For example, the hub 5270 can be included in and/or form a distal end portion of a housing (e.g., distal end portion 434 of the medicament container 430). Thus, an inner volume of the hub 5270 can be placed in fluid communication with a drug formulation contained within a fluid reservoir (e.g., a medicament container), as described above with reference to the hub 4270 of FIGS. 34-36. As shown in FIG. 37, the distal end portion 5272 of the hub 5270 can be a substantially elongate portion that includes and/or is formed from a set of annular walls 5274. As described in further detail herein, the annular walls 5274 define a lumen 5276 that extends through the distal end portion 5272 of the hub 5270. The lumen 5276 is configured to receive a portion of the puncture member 5240 to physically and fluidically couple the puncture member 5240 to the hub 5270.

[0227] The puncture member 5240 (also referred to herein as “microneedle”) can be configured to puncture and/or penetrate a portion of the eye to deliver a drug formulation to, for example, the suprachoroidal space. The microneedle 5240 has a proximal end portion 5242 and a distal end portion 5244, and defines a lumen 5241. As shown in FIG. 37, the proximal end portion 5242 is disposed within the lumen 5276 of the hub 5270. For example, in some embodiments, the hub 5270 can be over-molded about the proximal end portion 5242 of the puncture member 5240. In other embodiments, the hub 5270 and the puncture member 5240 can be monolithically formed (e.g., the puncture member 5240 can be a microcatheter or the like that is unitarily formed with the hub 5270). Therefore, with the hub 5270 physically and fluidically coupled to a housing or fluid reservoir (as described above), the lumen 5241 of the puncture member 5240 can be placed in fluid communication with a drug formulation contained therein.

[0228] As shown, the microneedle 5240 extends from the distal end portion 5272 of the hub 5270 in the distal direction. In this manner, the microneedle 5240 can have a shaft length H between a distal edge 5245 of the puncture member 5240 and a distal surface of the hub 5270. In this manner, the puncture member 5240 can be substantially similar to or the same as the puncture member 4240 described above with reference to FIGS. 34-46. Thus, portions of the puncture member 5240 are not described in further detail herein.

[0229] The adjustment member 5230 can be any suitable shape, size, or configuration and is transitionable between a first configuration and a second configuration. The adjustment member 5230 is coupled to the distal end portion 5272 of the hub 5270. For example, in some embodiments, the adjustment member 5230 can be coupled to the hub 5270 via a press fit, a snap fit, a threaded coupling, mechanical fastener, an adhesive, and/or the like. In other embodiments, the adjustment member 5230 can be disposed about a portion of the puncture member 5240 such that a portion of the adjustment member 5230 is in contact with the distal end portion 5272 of the hub 5270 (e.g., adjacent to yet not coupled to the hub 5270). In this manner, the hub 5270 and the puncture member 5240 can be reusable (after sterilization) and can be temporarily coupled to a disposable adjustment member 5230. In some embodiments, the adjustment member 5230 and the hub 5270 can be monolithically formed. In some embodiments, the adjustment member 5230 can be over-molded about the distal end portion 5272 of the hub 5270. For example, in some embodiments, the hub 5270 can be formed from a relatively rigid material such as a metal or hard plastic and can act as a substrate about which the adjustment member 5230 is molded (e.g., from a relatively soft material such as an elastomeric material, thermoplastic, rubber, silicone, or the like). As shown in FIG. 37, when the adjustment member 5230 is in the first configuration, the adjustment member 5230 has a thickness T_1 . In some embodiments, the thickness T_1 of the adjustment member 460 can be, for example, about 25 μm , 50 μm , 100 μm , 400 μm , or any suitable fraction therebetween. In other embodiments, the adjustment member 5230 can have a thickness T_1 that is greater than 400 μm . In other embodiments, the overall thickness T_1 of the adjustment member 5230 can be less than about 25 μm .

[0230] The adjustment member 5230 is removably disposed about a portion of the puncture member 5240. More specifically, the puncture member 5240 can extend in the distal direction from the hub 5270 such that a portion of the puncture member 5240 extends through the adjustment member 5230. For example, as shown in FIG. 37, the distal end portion 5244 of the puncture member 5240 can extend a distance (i.e., D_2 or D_3) from a distal surface 5234 of the adjustment member 5230. Similarly stated, the distal edge 5245 of the puncture member 5240 is spaced apart from the distal surface 5234 of the adjustment member 5230 by the distance D_2 (also referred to as an effective length of the puncture member 5240). As described above, the adjustment member 5240 can be transitioned between a first configuration and a second configuration. More specifically, the first configuration can be associated with the first thickness T_1 of the adjustment member 5230 and the second configuration can be associated with a second thickness T_2 . Thus, when the adjustment member 5230 is moved from the first configuration to the second configuration (e.g., from the first thickness T_1 to the second thickness T_2), the effective length of the puncture member 5240 between the distal edge 5245 of the puncture member 5240 and the distal surface 5234 of the adjustment member 5230 is increased by a corresponding distance (e.g., increased from the first distance D_1 to a second distance D_3). Similarly stated, the nominal change in the thickness from the first thickness T_1 to the thickness T_2 substantially corresponds with (or is the same as) the nominal change in distance from the first distance D_2 to the second distance D_3 . By way of example, while the adjust-

ment member 5230 is in the first configuration, the first thickness T_1 can be, for example, 250 μm and the first distance D_2 can be, for example, about 450 μm . When the adjustment member 5230 is moved to the second configuration, the second thickness T_2 of the adjustment member 5230 can be, for example, 100 μm and the second distance D_3 can be, for example, about 600 μm .

[0231] In use, a user (e.g., a doctor, technician, nurse, physician, ophthalmologist, etc.) can manipulate a delivery device (not shown) to insert the puncture member 5240 into, for example, a portion of the eye (e.g., the eye 10 shown in FIG. 1). In this manner, the distal end portion 5244 of the puncture member 5240 can be advanced through a portion of the sclera until the distal surface 5234 of the adjustment member 5230 is placed in contact with an outer surface of the sclera. With the adjustment member 5230 in the first configuration, the distance D_2 (e.g., the first distance) between the distal surface 5234 of the adjustment member 5230 and the distal edge 5245 of the puncture member 5240 can substantially depend on and/or can be associated with the thickness of the sclera. For example, in some embodiments, when the adjustment member 5230 is in the first configuration, the distance D_2 between the distal surface 5234 of the adjustment member 5230 and the distal edge 5245 can be about 550 μm . In other embodiments, the distance D_2 when the adjustment member 5230 is in the first configuration can be about 350 μm , 400 μm , 450 μm , 500 μm , 600 μm , 650 μm , 700 μm , 750 μm , 800 μm , 850 μm , 900 μm , 950 μm , 1000 μm , or any fraction therebetween. In still other embodiments, the distance D_2 when the adjustment member 5230 is in the first configuration can be less than about 350 μm . In this manner, a distal edge 5245 of the puncture member 5240 can be disposed within the sclera (e.g., the sclera 20 of the eye 10 in FIG. 1).

[0232] The adjustment member 5230 can be moved from its first configuration to its second configuration to increase the distance between the distal surface 5234 of the adjustment member 5230 and the distal edge 5245 of the puncture member 5240 from the first distance D_2 to the second distance D_3 . For example, in some instances, a user can exert a force (either directly or indirectly) on the hub 5270 to advance the puncture member 5240 relative to the eye. With the distal surface 5234 of the adjustment member 5230 in contact with an outer surface of the sclera, the force exerted on the hub 5270 can be operable in compressing the adjustment member 5230 from the first thickness T_1 to the second thickness T_2 . Thus, the adjustment member 5230 is placed in the second configuration and the distance between the distal surface 5234 of the adjustment member 5230 is increased from the first distance D_2 to the second distance D_3 . For example, in some instances, the second distance D_3 can be about 600 μm . In other embodiments, the second distance D_3 can be about 650 μm , 700 μm , 750 μm , 800 μm , 850 μm , 900 μm , 950 μm , 1000 μm , or any fraction therebetween. In still other embodiments, the second distance D_3 can be increased to less than about 600 μm (e.g., such as, for example, in use on pediatric eyes).

[0233] As described above with reference to FIG. 36, the movement of the adjustment member 5230 to the second configuration can be such that further movement of the puncture member 5240 (e.g., in a distal direction) relative to the sclera places the lumen 5241 of the puncture member 5240 in fluid communication with the suprachoroidal space (e.g., the suprachoroidal space 36 of the eye 10 in FIG. 1).

Similarly stated, the increase in distance from the first distance D_2 to the second distance D_3 can be sufficiently large to extend the distal edge 5245 of the puncture member 5240 through the sclera such that the lumen 5241 is placed in fluid communication with the suprachoroidal space. With the lumen 5241 of the puncture member 5240 in fluid communication with the suprachoroidal space, a drug formulation (contained within a fluid reservoir as described above with reference to FIG. 36) can be expelled through the lumen 5241 of the puncture member 5240 and into the suprachoroidal space of the eye. In this manner, the drug formulation can flow within the suprachoroidal space to be delivered to, for example, the posterior region of the eye (e.g., the posterior region 14 of the eye 10 in FIG. 1). Moreover, with the adjustment member 5230 in the second configuration, the distance between the distal surface 5234 of the adjustment member 5230 and the distal edge 5245 of the puncture member 5230 (e.g., the second distance D_3) can be less than a combined thickness of the sclera and the suprachoroidal space such that the distal end portion 5244 of the puncture member 5240 does not pierce the choroid.

[0234] In addition to adjusting and/or controlling the effective length of the puncture member 5240 to enhance the likelihood that the lumen 5241 is placed in fluid communication with the desired region of the target tissue (e.g., the suprachoroidal space of the eye), in some embodiments, the adjustment member 5230 (and any of the adjustment members shown and described herein) can form a substantially fluid-tight seal and/or a substantially liquid-tight seal with the outer surface of the target tissue (e.g., the conjunctiva of the eye). In this manner, leakage of the injected medicament along the needle track during the injection event can be reduced and/or eliminated. Expanding further, in some embodiments, the anatomy of the target tissue and/or the arrangement of the delivery device can be such that, in use, a portion of the opening of the lumen 5241 may be placed in fluid communication with the suprachoroidal space 36 of the eye, while another portion of the opening of the lumen 5241 may be positioned within the sclera 20. Thus, when the drug formulation is conveyed into the eye via the puncture member 5240, a portion of the drug formulation may be prone to migrating away from the desired region (e.g., the suprachoroidal space 36) and out of the eye via the needle track. By forming a substantially fluid-tight seal and/or a substantially liquid-tight seal, the adjustment member 5230 can produce an area of high resistance to flow, thus minimizing and/or eliminating the flow migration and/or leakage.

[0235] Although the adjustment member 5230 is described above as being constructed from a relatively soft material, which can be well suited to forming a fluid-tight seal, in some embodiments, the adjustment member 5230 can be constructed from multiple materials. For example, in some embodiments, the distal end surface 5234 of the adjustment member 5230 can be constructed from and/or can include a layer or portion constructed from a material formulated to form a substantially fluid-tight seal with the outer surface of the target tissue (e.g., the conjunctiva).

[0236] Although not shown in FIG. 37, in some embodiments, the adjustment member 5230 and/or the puncture member 5240 can include a locking feature that can be configured to at least temporarily retain the adjustment member 5230 in the second configuration. For example, in some embodiments, the puncture member 5240 and/or hub

5270 can include one or more detents, grooves, protrusions, etc. that can matingly engage a portion of the adjustment member 5230 to retain the adjustment member 5230 in the second configuration. More specifically, in some embodiments, the adjustment member 5230 can include a set of protrusions (not shown) that extend from the adjustment member toward the puncture member 5240. In such embodiments, the adjustment member 5230 can be moved to the second configuration to decrease the thickness of the adjustment member (as described above). In this manner, the protrusions can move along a surface of the puncture member 5240 while the adjustment member 5230 is being moved to the second configuration. Once the adjustment member 5230 is in the second configuration, the protrusions can matingly engage a set of detents that can at least temporarily retain the protrusions therein. Thus, the adjustment member 5230 can be at least temporarily locked in the second configuration. In other embodiments, the adjustment member 5230 and the puncture member 5240 do not include a locking feature and a user can exert a substantially constant force to retain the adjustment member 5230 in the second configuration.

[0237] In some embodiments, the puncture member 5240 and/or the adjustment member 5230 can include a visual indicator that is associated with the distance between the distal surface 5234 of the adjustment member 5230 and the distal edge 5245 of the puncture member 5240. For example, in some embodiments, the puncture member 5240 can include a measurement indicator. In such embodiments, a user determine the distance between the distal surface 5234 of the adjustment member 5230 and the distal edge 5245 of the puncture member 5240 by visually inspecting the measurement indicator.

[0238] FIG. 38 is a schematic illustration of a portion of a delivery device according to an embodiment. As shown, a hub 6270 is coupled to a puncture member 6240 and an adjustment member 6230. The hub 6270 has a proximal end portion 6271 and a distal end portion 6272. The proximal end portion 6271 can be physically and fluidically coupled to a fluid reservoir such as, for example, the medicament container 430 of the medical injector 400 described above with reference to FIGS. 19-20. Although not shown in FIG. 38, the proximal end portion 6271 of the hub 6270 can be coupled to a housing (e.g., a medicament container) of a delivery device using any suitable coupling method such as, for example, a press fit, a snap fit, a threaded coupling, a Luer connection, a mechanical fastener, an adhesive, and/or the like. In other embodiments, the hub 6270 can be monolithically formed with a housing of a delivery device. For example, the hub 6270 can be included in and/or form a distal end portion of a housing (e.g., the distal end portion 343 of the housing 430). Thus, an inner volume of the hub 6270 can be placed in fluid communication with a drug formulation contained within a fluid reservoir (e.g., a housing), as described above with reference to the hub 6270 of FIGS. 34-36. As shown in FIG. 38, the distal end portion 6272 of the hub 6270 can be a substantially elongate portion that includes and/or is formed from a set of annular walls 6274. The annular walls 6274 define a lumen 6276 that extends through the distal end portion 6272 of the hub 6270. The lumen 6276 is configured to receive a portion of the puncture member 6270 to physically and fluidically couple the puncture member 6270 to the hub 6270.

[0239] The puncture member 6240 (also referred to herein as “microneedle”) can be configured to puncture and/or penetrate a portion of the eye to deliver a drug formulation to, for example, the suprachoroidal space. The microneedle 6240 has a proximal end portion 6242 and a distal end portion 6244, and defines a lumen 6241. As described above, the proximal end portion 6242 is disposed within the lumen 6276 of the hub 6270. For example, in some embodiments, the hub 6270 can be over-molded about the proximal end portion 6242 of the puncture member 6240. In other embodiments, the hub 6270 and the puncture member 6240 can be monolithically formed (e.g., the puncture member 6240 can be a microcatheter or the like that is unitarily formed with the hub 6270). Therefore, when the hub 6270 is physically and fluidically coupled to a housing or fluid reservoir (as described above), the lumen 6241 of the puncture member 6240 can be placed in fluid communication with a drug formulation contained therein.

[0240] As shown, the microneedle 6240 extends from the distal end portion 6272 of the hub 6270 in the distal direction. The microneedle 6240 has a shaft length H between a distal edge 6245 of the puncture member 6240 and a distal surface of the hub 6270. In this manner, the puncture member 6240 can be substantially similar to or the same as the puncture member 6240 described above with reference to FIGS. 34-36. Thus, portions of the puncture member 6240 are not described in further detail herein.

[0241] The adjustment member 6230 can be any suitable shape, size, or configuration and can be disposed about a portion of the hub 6270 and/or the puncture member 6240. For example, although some of the adjustment members are described herein as being monolithic, in other embodiments, such as here, an adjustment member can be constructed from multiple different components that are joined together. In particular, the adjustment member 6230 includes a base 6238 and a set of removable layers 6239. The base 6238 is coupled to the distal end portion 6272 of the hub 6270. For example, in some embodiments, the base 6238 can be removably coupled to the hub 6270 (e.g., via a press fit, a snap fit, a threaded coupling, mechanical fastener, and/or the like). In this manner, the hub 6270 can be reusable (after sterilization) and can be temporarily coupled to a disposable adjustment member 6230. In other embodiments, the base 6238 can be fixedly coupled to the hub 6270 (e.g., via an adhesive, ultrasonic welding, and/or the like).

[0242] The set of layers 6239 is comprised of relatively thin strips that are sequentially stacked on one another. More specifically, a first layer 6239 is removably coupled to the base 6238 and each subsequent layer 6239 is stacked on top of the preceding layer. In some embodiments, the layers 6239 can be relatively thin strips of a self-adhering flexible material such as sheets of polyethylene, polyvinylidene chloride, polypropylene, polyacrylate, or the like. In other embodiments, the layers 6239 can be at least temporarily retained to each other and/or to the hub via an adhesive. In such embodiments, the layers 6239 can be retained by one or more adhesive material having varying adhesive strengths. For example, in some embodiments, the adhesive strength between adjacent layers 6239 can increase from a first adhesive strength between the distal-most layer and its adjacent layer and a second adhesive strength between the proximal-most layer and its adjacent layer. In some embodiments, each layer can be adhered to an adjacent layer by a unique adhesive. In other embodiments, each layer can be

adhered to an adjacent layer by the same adhesive with, for example, varying adhesive strengths. In yet other embodiments, the layers can be retained via a combination of an adhesive and one or more self-adhesive material. In this manner, one or more layers 6239 can be removed from the set of layers 6239 to transition the adjustment member 6230 from the first configuration to the second configuration. Moreover, by varying the properties of the adhesive, the user can more easily remove the desired layer(s) without inadvertently removing additional layers.

[0243] As shown in FIG. 38, each layer 6239 has a thickness T_L . In some embodiments, the thickness T_L of each layer 6239 can be, for example, about 5 μm , 10 μm , 20 μm , 30 μm , 40 μm , 50 μm , 100 μm , or any suitable fraction therebetween. In other embodiments, a layer 6239 can have a thickness T_L that is greater than 100 μm . Although each layer 6239 is shown and described as having substantially the same thickness T_L , in other embodiments, the layers 6239 can have varying thickness. As shown in FIG. 38, the set of layers 6239 can have an overall thickness T_A that is the sum of the thicknesses T_L of each stacked layer 6239. For example, in some embodiments, the overall thickness T_A of the set of layers 6239 can be about 50 μm , 100 μm , 150 μm , 200 μm , 250 μm , 300 μm , 400 μm , 500 μm , 1000 μm , or any suitable fraction therebetween. In other embodiments, the overall thickness T_A of the set of layers 6239 can be less than about 50 μm . In still other embodiments, the overall thickness T_A of the set of layers 6239 can be greater than about 1000 μm . Although three removable layers 6239 are shown in FIG. 38, in other embodiments, an adjustment member can include any suitable number of removable layers (e.g., two layers, four layers, five layers, six layers, seven layers, eight layers, nine layers, ten layers, or more).

[0244] As described above, the adjustment member 6230 is disposed about a portion of the hub 6270 and the puncture member 6270. More specifically, the puncture member 6240 can extend in the distal direction from the hub 6240 such that a portion of the puncture member 6240 extends through the adjustment member 6230 (e.g., through the base 6238 and the set of layers 6239). For example, as shown in FIG. 38, the distal end portion 6244 of the puncture member 6240 can extend a distance D_4 from the outermost layer 6239 of the adjustment member 6230 (also referred to as an effective length of the puncture member 6240). Similarly stated, the distal edge 6245 of the puncture member 6240 is spaced apart from a distal surface of the adjustment member 6230 (e.g., the outermost layer 6239) by the distance D_4 . Thus, when a layer 6239 is removed from the set of layers 6239 of the adjustment member 6230, the effective length of the puncture member 6240 (e.g., the distance D_4) is increased by a distance that substantially corresponds to the thickness T_L of the layer 6239 that was removed. By way of example, while the adjustment member 6230 is in the first configuration (e.g., where all the layers included in the set of layers 6239 are stacked), the distance D_4 can be, for example, about 550 μm and when the adjustment member 6230 is moved to the second configuration (e.g., when one or more layers are removed from the set of layers 6239), the distance D_4 can be increased to, for example, about 650 μm . In other embodiments, the effective length of the puncture member 6240 can be increased to 600 μm , 700 μm , 750 μm , 800 μm , 850 μm , 900 μm , 950 μm , 1000 μm , or any suitable fraction therebetween.

[0245] In use, a user (e.g., a doctor, technician, nurse, physician, ophthalmologist, etc.) can manipulate a delivery device (not shown) to insert the puncture member 6240 into, for example, a portion of the eye (e.g., the eye 10 shown in FIG. 1). In this manner, the distal end portion 6244 of the puncture member 6240 can be advanced through a portion of the sclera until an outermost layer of the set of layers 6239 included in the adjustment member 6230 is placed in contact with an outer surface of the sclera. With the adjustment member 6230 in the first configuration, the distance D_4 (e.g., a first distance) between the outermost layer 6239 of the adjustment member 6230 and the distal edge 6245 of the puncture member 6240 can substantially depend on and/or can be associated with the thickness of the sclera. For example, in some embodiments, when the adjustment member 6230 is in the first configuration, the distance D_4 between the outermost layer 6239 of the adjustment member 6230 and the distal edge 6245 can be about 450 μm . In other embodiments, the distance D_4 when the adjustment member 6230 is in the first configuration can be about 350 μm , 400 μm , 500 μm , 550 μm , 600 μm , 650 μm , 700 μm , 750 μm , or any fraction therebetween. In still other embodiments, the distance D_4 when the adjustment member 6230 is in the first configuration can be less than about 350 μm . In yet other embodiments, the distance D_4 when the adjustment member 6230 is in the first configuration can be greater than 750 μm . In this manner, a distal edge 6245 of the puncture member 6240 can be disposed within the sclera (e.g., the sclera 20 of the eye 10 in FIG. 1).

[0246] The adjustment member 6230 can be moved from its first configuration to its second configuration to increase the distance D_4 between the outermost layer 6239 of the adjustment member 6230 and the distal edge 6245 of the puncture member 6240 from the first distance to a second distance. For example, in some embodiments, a user can manipulate an engagement portion 6280 of one or more layers to remove (e.g., peel, tear, shear, break away, etc.) the one or more layers from the stack of layers 6239 (i.e., the set of layers). In this manner, the overall thickness T_A of the set of layers 6239 is reduced by the combined thicknesses T_L of each layer that is removed. Expanding further, by removing the one or more layers, the overall thickness T_A of the set of layers 6239 is reduced, thereby placing the adjustment member in the second configuration. Thus, with the adjustment member 6230 in the second configuration, the distance D_4 is increased between the current outermost layer (e.g., the outermost layer after removing the one or more layers) and the distal edge 6245 of the puncture member 6240 (e.g., to a second distance). In some embodiments, the distance D_4 can be increased to about 600 μm . In other embodiments, the distance D_4 can be increased to about 650 μm , 700 μm , 750 μm , 800 μm , 850 μm , 900 μm , 950 μm , 1000 μm , or any fraction therebetween. In still other embodiments, the distance D_4 can be increased to less than about 600 μm (e.g., such as, for example, in use on pediatric eyes). By way of example, in some embodiments, the adjustment member 6230 can include a set of 10 layers 6239 with each layer having a thickness of about 50 μm . In such embodiments, the distance D_4 between the outermost layer 6239 and the distal edge 6245 can be, for example, about 450 μm . In some instances, three layers can be removed from the set of 10 layers 6239 to increase the distance D_4 to about 600 μm .

[0247] In addition to adjusting and/or controlling the effective length of the puncture member 6240 (e.g., by

manipulating a layer from the stack of layers 6239) to enhance the likelihood that the lumen 6241 is placed in fluid communication with the desired region of the target tissue (e.g., the suprachoroidal space of the eye), in some embodiments, the adjustment member 6230 (and any of the adjustment members shown and described herein) can form a substantially fluid-tight seal and/or a substantially liquid-tight seal with the outer surface of the target tissue (e.g., the conjunctiva of the eye). In this manner, leakage of the injected medicament along the needle track during the injection event can be reduced and/or eliminated. Expanding further, in some embodiments, the anatomy of the target tissue and/or the arrangement of the delivery device can be such that, in use, a portion of the opening of the lumen 6241 may be placed in fluid communication with the suprachoroidal space 36 of the eye, while another portion of the opening of the lumen 6241 may be positioned within the sclera 20. Thus, when the drug formulation is conveyed into the eye via the puncture member 6240, a portion of the drug formulation may be prone to migrating away from the desired region (e.g., the suprachoroidal space 36) and out of the eye via the needle track. By forming a substantially fluid-tight seal and/or a substantially liquid-tight seal, the adjustment member 6230 can produce an area of high resistance to flow, thus minimizing and/or eliminating the flow migration and/or leakage.

[0248] Although the adjustment member 6230 is described above as being constructed from a relatively soft material, which can be well suited to forming a fluid-tight seal, in some embodiments, the adjustment member 6230 can be constructed from multiple materials. For example, in some embodiments, the adjustment member 6230 can include a set of layers 6239 with a first layer constructed from and/or including a portion constructed from a first material, and a second layer constructed from and/or including a portion constructed from a second material different from the first material. Further to this example, at least a portion of the first material and/or at least a portion of the second material can be constructed from and/or can include a layer or portion constructed from a material formulated to form a substantially fluid-tight seal with the outer surface of the target tissue (e.g., the conjunctiva).

[0249] Although not shown in FIG. 38, in some embodiments, the layers 6239 can provide and/or include an indicator associated with the distance D_4 between the outermost layer 6269 and the distal edge 6245 of the puncture member 6230. In some embodiments, the indicator can be indicia such as, for example, a value associated with the distance D_4 (e.g., 500 μm). In other embodiments, the layers 6239 can be color coded with each layer having a different color and each color being associated with an effective length of the puncture member 6240.

[0250] Although not shown in FIG. 38, in some embodiments, at least a portion of the layers 6239 can be disposed, at least temporarily, within a housing or the like. For example, in some embodiments, the layers 6239 can be coupled to the base 6238, as described above, and a housing can be disposed about at least a portion of the layers 6239 and the base 6238. Expanding further, in some embodiments, the housing can be movably disposed about the base and can define a window through which the engagement portion 6280 of the layers 6239 can extend. Thus, a user can manipulate the engagement portion 6280 of a layer 6239 to remove the layer 6239 from the adjustment member 6230. In

some embodiments, the layer 6239 can be withdrawn through the window defined by the housing. In this manner, the housing can be moved in the proximal direction to be placed in contact with the outermost layer 6239, thereby allowing a shaft length of the puncture member 6240 between the distal edge 6245 and a distal surface of the housing to be increased. In some embodiments, the window can provide for visualization of the shaft length indicator (described above).

[0251] As described above with reference to FIG. 36, the increase in the distance D_4 can be such that further movement of the puncture member 6240 (e.g., in a distal direction) relative to the sclera places the lumen 6241 of the puncture member 6240 in fluid communication with the suprachoroidal space (e.g., the suprachoroidal space 36 of the eye 10 in FIG. 1). Similarly stated, the increase in the distance D_4 can be sufficiently large to extend the distal edge 6245 of the puncture member 6240 through the sclera such that the lumen 6241 is placed in fluid communication with the suprachoroidal space. Expanding further, by removing the one or more layers from the set of layers 6239 of the adjustment member 6230, the distance between the outermost layer 6239 of the adjustment member 6230 and the distal edge 6245 of the puncture member 6240 (e.g., the distance D_4) is increased and the user can move the hub 6270 (e.g., either directly or indirectly) place the current outermost layer in contact with the outer surface of the sclera.

[0252] With the lumen 6241 of the puncture member 6240 in fluid communication with the suprachoroidal space, a drug formulation (contained within a fluid reservoir as described above with reference to FIG. 36) can be expelled through the lumen 6241 of the puncture member 6240 and into the suprachoroidal space of the eye. In this manner, the drug formulation can flow within the suprachoroidal space to be delivered to, for example, the posterior region of the eye (e.g., the posterior region 14 of the eye 10 in FIG. 1). Moreover, with the adjustment member 6230 in the second configuration, the distance D_4 can be less than a thickness of the sclera and the suprachoroidal space such that the distal end portion 6244 of the puncture member 6240 does not pierce the choroid.

[0253] As described herein, a system, for example, the system 1000, 2000, 3000, or any other system described herein, can include a hub, for example, the hub 3270, 4270, 5270, or any other hub described herein. The hub can be configured to form a substantially fluid-tight zone around the insertion site of a puncturing member (e.g., the puncturing member 3240 or any other puncturing member described herein) into the eye. For example, in some embodiments, a system can include a hub or contact surface configured to contact a surface of a target tissue to produce the desired effects during medicament delivery (e.g., maintaining a position of the conjunctiva, forming a seal or the like).

[0254] FIG. 39 shows an apparatus 7000 that includes a medical injector 7310, an actuation rod 7320, a needle 7240, and a hub 7270, and optionally a needle adjustment mechanism 7230. The system 7000 can be configured to deliver a medicament to a target layer of an eye of patient, for example, to the SCS of the eye.

[0255] The medical injector 7310 defines an internal volume 7316 configured to house a medicament L (e.g., a VEGF, a VEGF inhibitor, triamcinolone acetonide, any other medicament described herein or a combination thereof). The

medical injector 7310 includes an engagement portion 7312 and a delivery portion 7314 coupled to the needle adjustment mechanism 7230. The medical injector 7310 can be substantially similar to the medicament containment chamber 1310, 2310, 3310, or any other medicament containment chamber described herein, and is therefore not described in further detail herein.

[0256] The actuation rod 7320 includes an engagement portion 7322 and a plunger portion 7324. The plunger portion 7324 is slidably disposed inside the internal volume 7316 defined by the medical injector 7310. The engagement portion 7322 is configured to be engaged by the user and urge the plunger portion 7324 to slide within the internal volume 7316 defined by the medical injector 7310. For example, the user can apply a force in the direction shown by the arrow F_1 on the engagement portion 7322 to move the plunger portion 7324 proximally relative to the medical injector 7310 thereby, expelling at least a portion of the medicament L through a lumen 7241 of the needle 7240. As shown, at least a portion of the actuation rod 7320 can be disposed around and concentric with the medical injector 7310. The plunger portion 7324 is configured to draw in the medicament L into or expel the medicament L from the internal volume 7316 defined by the medical injector 7310. In some embodiments, any other actuation rod can be included in the apparatus 7000, for example the actuator 1320, 2320, 3320 or any other actuator described herein.

[0257] The needle 7240 defines the lumen 7241 and is configured to pierce the eye and deliver the medicament L into a target tissue of the eye. The needle 7240 can be substantially similar to any of the puncturing members described herein, and is therefore not described in further detail herein. In some embodiments, the needle 7240 can be a microneedle movably disposed within a passageway 7276 of the hub 7270, as described herein. The needle adjustment mechanism 7230 can be coupled to the delivery portion 7314 of the medical injector 7310 and a proximal end of the needle 7240. In some embodiments, the needle adjustment mechanism 7230 is configured to move the needle 7240 within the passageway 7276 such that a distal end portion of the needle 7240 extends from the distal end surface 7275 of the hub 7270 by a predetermined amount. For example, the needle adjustment mechanism 7230 can urge the needle 7240 to translate linearly along the longitudinal axis A_z and thereby adjust a length of the needle 7240 protruding through a distal end 7274 of the hub 6270. The needle adjustment mechanism 7230 can be substantially similar to the adjustment member 422, 3200, 4230, 5230, 6230, or any other adjustment mechanism or adjustment member described herein.

[0258] The hub 7270 is configured to be coupled to the medical injector 7230. The hub 7270 includes a proximal end 7272 and a distal end 7274. The proximal end 7272 is coupled to a distal end portion of the needle adjustment mechanism 7230. In some embodiments, the proximal end 7272 can be coupled to a housing (not shown) which can be included in the system 7000. The hub 7270 defines the passageway 7276 configured to receive at least a portion of the needle 7240 therethrough. In this manner, the needle 7240 is configured to pass through the lumen 7276 and into the eye. The distal end surface 7275 of the hub 7270 is configured to contact a target tissue (e.g., the conjunctiva of the eye) when the medicament L (or any other substance disposed within the medical injector 7230) is conveyed

through the needle **7240** into the target tissue. In some embodiments, the distal end surface **7275** of the hub **7270** is configured to deform the target surface (e.g., the conjunctiva of the eye) when the distal end surface **7275** is in contact with the target surface. At least a portion of the distal end surface **7275** can have a substantially convex shape, for example, a hemispherical shape such that at least a portion of distal end surface **7275** defines a sealing portion **7277**. The sealing portion **7277** can be configured to define a substantially fluid-tight seal with the target surface when the distal end surface **7275** is in contact with the target surface. For example, the distal end surface **7275** can deform the target surface such that the sealing portion **7277** is contiguous with the target surface and forms the substantially fluid-tight seal. In some embodiments, the sealing portion **7277** can be symmetric about a center A_L of the apparatus **7000** and hence the passageway. This can, for example, facilitate perpendicular approach of the needle **7240** into the target tissue (e.g., ocular tissue). Thus, the size of the insertion zone can be minimized reducing damage. Furthermore, the needle **7240** can use the shortest path to reach a target region of the target tissue (e.g., the SCS of the eye). While shown as being a cross-section, the hub **7270** can be substantially cylindrical, for example, have a circular cross-section and such that the convex shape of the distal end surface **7275** resembles, for example, a hemisphere. In such embodiments, the sealing portion **7277** can circumferentially surround the needle **7240** to form a hemispherical substantially fluid-tight seal with the target surface. In some embodiments, only a small portion of the sealing portion **7277** surrounding the needle **7240** needs to contact and form the substantially fluid-tight seal with the target surface. For example, in some embodiments, only a small band of the sealing portion **7277** surrounding the needle **7240** can contact and form the substantially fluid-tight seal with the target surface.

[0259] In some embodiments, the target tissue is an eye and the target surface is a conjunctiva of the eye. For example, FIGS. 40A-C shows a portion of an eye which includes a conjunctiva C, the sclera S, the suprachoroidal space SCS (which can be the target layer), and a retina R. As shown in FIG. 40A, in a first configuration, the distal end **7274** of the hub **7270** is in contact with a conjunctiva C of an eye and a distal end of the needle **7240** is disposed in a sclera S of the eye. Further to this example, the curved shape of the distal end surface **7275** of the hub **7270** can allow for a desired distribution of force(s) to be applied to a portion of the eye, for example, the conjunctiva C. In some embodiments, the curved distal end surface **7275** of the hub **7270** can create a taut spherical injection site. For example, the hub **7274** can deform the conjunctiva C in a radial direction from the center point (i.e., away from where the needle **7240** penetrates) when the system **7000** moves from the first configuration to a second configuration (e.g., the second configuration shown in FIG. 40B). In this manner, the conjunctiva C can be moved into and/or held in a preferable position during the injection. In some instances, this can reduce the puncturing forces to penetrate the surface of the eye. In some embodiments, the “stretching” of the conjunctiva C can minimize and/or eliminate any “bunching” of the conjunctiva C that may otherwise occur, and instead can produce a surface layer (e.g., conjunctiva) having a substantially constant thickness. In some instances, the hub **7270** can, at least temporarily, adhere to a portion of the conjunc-

tiva C. In this manner, the hub **7270** can cause movement of and/or stabilize at least a portion of the conjunctiva C such that at least the portion of the conjunctiva C is in a preferable position during the injection.

[0260] In some embodiments, the inserting of the needle **7240** into the target tissue (i.e., the conjunctiva and the sclera) can be performed such that a centerline of the delivery passageway and a surface line tangent to the target surface define an angle of entry of between about 75 degrees and about 105 degrees. For example, as shown in FIG. 40D, a centerline C_L of the lumen **7241** of the needle **7240** can define an insertion angle θ with a surface line tangent ST formed relative to the surface of the conjunctiva C. The insertion angle θ can be in the range of between about 75 degrees and about 105 degrees, inclusive of all ranges therebetween. For example, in some embodiments, the insertion angle θ can be about 90 degrees. Said another way, the needle **7240** can be inserted into the target tissue (i.e., the conjunctiva C, and the sclera S) such that the centerline C_L defined by the lumen **7241** of the needle **7240** is substantially perpendicular or otherwise normal to the surface of the target tissue. In this manner, the size of the insertion zone can be reduced thereby minimizing injury and inflammation, which can be caused by any lateral travel of the needle **7240** within the target tissue. Furthermore, normal insertion can also provide the shortest path for the distal tip of the needle **7240** to reach the target tissue (e.g., the SCS) thereby, reducing the time required to reach the target tissue (e.g., the SCS).

[0261] Referring back to FIGS. 40A-C, to initiate delivery of the medicament L the user can apply a force F_2 on the system **7000**, for example, on the engagement portion **7322** of the actuation rod **7320**. The force F_2 can urge the plunger portion **7324** to slide within the internal volume **7316** of the medical injector **7310** proximally relative to the medical injector **7310** and urge the system into a second configuration. While not shown, in some embodiments, the system **7000** can include an injection assembly, for example, the injection assembly **100**, **2100** or any other injection assembly described herein configured to exert the force on the actuation rod **7320**. In the second configuration, the hub **7270** is pressed against the conjunctiva C, such that the conjunctiva C compresses and conforms around the convex shape of the distal end surface **7275** of the hub **7270**. This also pushes the needle **7240** further into the sclera S. Furthermore, at least a portion of the sealing portion **7277** defined by the distal end surface **7275** is contiguous with the deformed surface of the conjunctiva C such that the sealing portion **7277** defines a substantially fluid-tight seal with the conjunctiva C around the insertion site. In some embodiments, the sealing portion **7277** can be substantially symmetrical about the centerline C_L of the needle **7240** (e.g., as shown in FIG. 40D). In some embodiments, only a circular band of the sealing portion **7277** can contact and form a substantially fluid-tight seal with the conjunctiva C surrounding the needle **7240**. However, in the second configuration, the distal end of the needle **7240** can still be proximal relative to but not within the suprachoroidal space SCS, which can be the target layer for delivery of the medicament L.

[0262] In some embodiments, the hub **7270** can be a rigid member that has a stiffness substantially greater than the stiffness of the conjunctiva C (e.g., a stiffness substantially similar to a stiffness of stainless steel). In such embodiments,

application of the force F_2 only deforms the conjunctiva C, without causing any substantial deformation of the hub 7270. In some embodiments, the hub 7270 can have a stiffness that is intermediate to the stiffness of the conjunctiva C and the sclera S. In such embodiments, application of the force F_2 can urge the hub 7270 to deform the conjunctiva C (FIGS. 40B and 40C) until the distal end surface 7275 of the hub 7270 is proximate to the sclera S. Since the stiffness of the hub 7270 is less than the stiffness of the sclera S, further application of the force F_2 will urge the distal end surface 7275 of the hub 7270 to deform without any substantial deformation of the sclera S. In this manner, the hub 7270 can prevent application of an excessive force from causing damage to or otherwise deformation and/or piercing of the internal layers of the eye.

[0263] In a third configuration shown in FIG. 40C, the user can then maintain the force F_2 and increase the length of the needle 7240 protruding into the eye, for example, using the needle adjustment mechanism 7230. The length of the needle 7240 can be increased until a distal tip or outlet of the needle 7240 is within or otherwise near the suprachoroidal space SCS. The force F_2 can further depress the distal end surface 7275 of the hub 7270 into the conjunctiva C. This can urge substantially all of the sealing portion 7277 of the distal end surface 7275 to be contiguous with the conjunctiva C further strengthening the substantially fluid-tight seal. In this manner, leakage of the injected medicament L along the needle 7240 track during the injection event can be reduced and/or eliminated. Expanding further, in some embodiments, the anatomy of the target tissue and/or the arrangement of the system 7000 can be such that, in use, a portion of the opening of the lumen 7241 of the needle 7240 may be placed in fluid communication with the suprachoroidal space SCS of the eye, while another portion of the opening of the lumen 7241 may be positioned within the sclera S. Thus, when the medicament L is conveyed into the eye via the needle 7240, a portion of the medicament L may be prone to migrating away from the desired region, i.e., the suprachoroidal space SCS and out of the eye via the needle 7240 track. By forming a substantially fluid-tight seal and/or a substantially liquid-tight seal, the hub 7270 can produce an area of high resistance to flow, thus minimizing and/or eliminating the flow migration and/or leakage.

[0264] While not shown, in some embodiments, the system 7000 can include an injection assembly, for example, the injection assembly 100, 2100 or any other injection assembly described herein. As described before herein, the injection assembly can be configured to exert a force on the medicament L disposed in the internal volume 7316 of the medicament containment chamber 7310. The force can be sufficient to overcome a backpressure of the suprachoroidal space SCS exerted upon the needle opening, but not the backpressure of the sclera S. In such embodiments, the user can insert the needle 7240 into the sclera S as shown in FIG. 40A and activate the injection assembly. The injection assembly can pressurize the medicament L but the backpressure of the sclera S can prevent the medicament L from delivery into the sclera S. As shown in FIG. 40B, the user can continue the insertion of the needle 7240, for example, by maintaining or increasing a magnitude of the force F_2 . This can urge the hub 7240 to deform the conjunctiva C and initiate the formation of the fluid tight seal around the insertion site, as described herein. The force F_2 can be maintained until a distal end of the needle 7240 is within or

near the suprachoroidal space SCS. The force exerted by the injection assembly on the medicament L can now overcome the backpressure of the suprachoroidal space SCS thereby, initiating communication of the medicament L into or near the suprachoroidal space SCS as shown in FIG. 40C. In this manner, the injection assembly can assist the user in determining the location of the distal end of the needle 7240 such that the medicament L is delivered substantially only to the target layer (i.e., the suprachoroidal space SCS). Furthermore, over excursion of the puncturing member 7240 beyond the suprachoroidal space SCS (i.e., into the retina R) can be prevented.

[0265] In some embodiments, the needle adjustment mechanism 7230 can be used to ensure delivery to the target layer. In such embodiments, the user can insert the needle 7240 into the sclera S as shown in FIG. 40A and activate the injection assembly to pressurize the medicament L as described herein. While maintaining the force F_2 , the user can use the needle adjustment mechanism 7230 to advance the needle 7240 in predetermined increments (e.g., about 100 μ m increments) into the sclera S, for example, as described herein with reference to the needle assembly 422, 3200, or any other needle assembly described herein. In this manner, the needle adjustment mechanism 7230 can be used to advance the needle 7240 through the sclera S until a distal end of the needle 7240 is within or near the suprachoroidal space SCS. The force exerted by the injection assembly on the medicament L can now overcome the backpressure of the suprachoroidal space SCS thereby, initiating communication of the medicament L into or near the suprachoroidal space SCS as shown in FIG. 40C. Thus, by allowing the user to advance the needle 7240 in known discrete increments, the needle adjustment mechanism 7230 can assist the user in preventing over excursion of the needle 7240 beyond the suprachoroidal space SCS (i.e., into the retina R). In this manner, the injection assembly can assist the user in determining the location of the distal end of the needle 7240 such that communication of the medicament into a layer of the eye other than the target layer (i.e., the suprachoroidal space SCS) can be prevented. Furthermore, the needle adjustment mechanism 7230 can assist the user in precisely controlling the excursion length of the needle 7240, thereby eliminating the use of excessive force and/or preventing over excursion of the needle 7240 beyond the target layer (i.e., the suprachoroidal space SCS).

[0266] In some embodiments, the hub 7270 or any of the hubs described herein can be constructed from a relatively soft material, which can be well-suited to forming a fluid-tight seal. For example, in some embodiments, the system 7000, or any other system described herein can be used to deliver a medicament through the skin of a user (e.g., for intravenous or intramuscular delivery of the medicament). In such embodiments, the hub 7270 or any other hub described herein can have a stiffness less than the stratum corneum that forms the top layer of the skin. The distal end surface 7275 of the hub 7270 or any other hub described herein can deform about the stratum corneum as a force is applied on the system 7000. In this manner, the sealing portion 7277 defined by the distal end surface 7275 of the hub 7270 can form a fluid tight seal around the stratum corneum thereby preventing leakage of the medicament, an interstitial fluid, and/or blood from the injection site. In yet other embodiments, the hub 7270 can be constructed from multiple materials. For example, in some embodiments, the

distal end surface **7275** of the hub **7270** can be constructed from and/or can include a layer or portion constructed from a material formulated to form a substantially fluid-tight seal with the outer surface of the target tissue (e.g., the conjunctiva **C**).

[0267] FIGS. **41A** and **41B** show a finite element analysis (FEA) model of the distal portion **7274** of the hub **7270** compressed against the conjunctiva **C** of the eye. In this model, a force of 1N is exerted on the hub **7270**. At this force, the conjunctiva **C** is compressed by about 2 mm, which is substantially equal to the total thickness of the conjunctiva **C**. Furthermore, the conjunctiva **C** conforms around the distal end surface **7275** of the distal end portion **7274** of the hub **7270**. As shown, the sealing portion **7277** of the distal end surface forms a substantially fluid-tight seal around the injection site of the needle **7240**. The hub **7270** was modeled as a rigid and inflexible member. However, the hub **7270** or any other hub described herein can have any suitable stiffness based on the material used to form the hub. In some embodiments, the hub **7270** or any other hub described herein can have a stiffness substantially similar to the stiffness of rubber, silicone, polymers, plastics (e.g., polyethylene, polypropylene, polycarbonate, polytetrafluoroethylene, high density polyethylene, etc.), metals (e.g., aluminum, stainless steel, metal alloys, etc.), or any other material described herein.

[0268] FIGS. **42A-C** shows a hub **8270**, according to an embodiment. The hub **8270** includes a proximal end portion **8272** and a distal end portion **8274**. The proximal end portion **8272** can be configured to be coupled to a distal end of a housing (e.g., a distal end **3212** of the housing **3210** of the needle assembly **3200**, or any other housing described herein) using any suitable coupling mechanism, for example, friction-fit, threads, snap-fit, notches, grooves, indents, detents, any other suitable coupling mechanism or combination thereof. The hub **8270** defines a passageway **8276** therethrough. At least a portion of a needle (e.g., the puncturing member **3240**, the needle **7240**, or any other puncturing member described herein) can be disposed within the passageway **8276**, and can be configured to advance through the passageway **8276** out of the distal end **8274**. The distal end **8274** of the hub **8270** includes a contact surface that is curved, and for example, defines a convex or hemispherical shape. The contact surface of the distal portion **8274** is configured to (i.e., has a size and/or shape configured to) contact an outer surface of a conjunctive of the eye and define a sealing portion that forms a substantially fluid-tight seal around the insertion zone of the puncturing member **8240** into a target tissue, for example, the eye. Thus, the hub **8270** can prevent leakage of the medicament, and/or bodily fluid from the insertion site, as described in with respect to the hub **7270** included in the apparatus **7000**.

[0269] In some embodiments, a hub can be substantially hollow and/or can define an enlarged lumen therethrough. Referring now to FIGS. **43A-C**, a hub **9270** includes a proximal end portion **9272**, a distal end portion **9274**, and defines an internal volume **9275**. The proximal end portion **9272** can be configured to be coupled to a distal end of a housing (e.g., the distal end **3214** of the housing **3210** included in the needle assembly **3200**, or any other housing included in a needle assembly described herein). For example, a portion of a distal end of a housing (e.g., the housing **3210**) can be configured to slide into the internal volume **9275**. At least a portion of a needle (e.g., the

puncturing member **3240**, the needle **7240**, or any other puncturing member described herein) can be disposed in the internal volume **9275**. In some embodiments, at least a portion of a needle assembly, for example, the lead screw **3242** included in the needle assembly **3200** or any other component or any other needle assembly, can also be disposed in the internal volume **9275**. The distal end **9274** has a contact surface that is curved, for example, defines a convex or a hemispherical shape, such that the contact surface defines a sealing portion which can form a substantially fluid-tight seal around the insertion zone of the puncturing member (e.g., the puncturing member **3240**, or the needle **7240**), as described with respect to the hub **8270**. The distal end **9274** defines an opening **9276** configured to enable at least portion of the puncturing member (e.g., the puncturing member **3240**) to pass therethrough and into the ocular tissue of the eye.

[0270] In some embodiments, a hub can include one or more engagement structures that cooperatively function to surround the puncture member and/or contact a surface of the target tissue. Moreover, in some embodiments, a hub can also be configured to induce deformation and/or movement of a portion of the target tissue when placed into contact with the target tissue. In such embodiments, the adjustment member can minimize “bunching” of the surface tissue (e.g., the conjunctiva). For example, FIGS. **44A** and **44B** are schematic illustrations of a portion of a delivery device **10000** in a first configuration and a second configuration, respectively, according to an embodiment. The delivery device **10000** includes a hub **10270**, a puncture member **10240** (also referred to herein as a delivery member or a needle) and an engagement assembly **10280**. The engagement assembly **10280** includes a first elongate member **10281** and a second elongate member **10285**. The elongate members **10281**, **10285** can be any suitable structure configured to engage the target tissue and deform (as described herein). For example, in some embodiments, the first elongate member **10281** and/or the second elongate member **10285** can be a thin structure (e.g., feeler gauge, wire, etc.). In some embodiments, the first elongate member **10281** and/or the second elongate member **10285** can be any suitable structure configured to grip, hold, and/or deform a portion of the target tissue (e.g., the conjunctiva). Although not shown, additional elongate members (or “sleds”) can be coupled to the hub **10270**. For example, in some embodiments, the hub **10270** can include three elongate members attached thereto. In other embodiments, for example, the hub **10270** can include more than three elongate members (e.g., four, five, or more elongate members) attached thereto.

[0271] As shown, a proximal end portion **10286** of the first elongate member **10281** is coupled to the hub **10270**. The first elongate member **10281** has a contact portion **10284** (e.g., the portion where the first elongate member **10281** can contact a portion of the eye **10** shown in FIG. **1**, during use). The first elongate member **10281** has a distal end portion **10283**. At least a portion of the first elongate member **10281** can have a curved shape. The curved shape, for example, can be such that the contact portion **10284** is configured to contact a portion of the eye (e.g., the conjunctiva) along a line tangent to a portion of the first elongate member **10281**. Further to this example, the curved shape of the portion of the first elongate member **10281** can allow for a desired distribution of force(s) to be applied to a portion of the eye during use. For example, in this manner the contact portion

10284 does not contact the surface of the eye at a single point, but rather along a surface that is less likely to puncture the eye.

[0272] A proximal end portion **10286** of a second elongate member **10285** is coupled to the hub **10270**. The second elongate member **10285** has a contact portion **10288** (e.g., where the second elongate member **10285** contacts a portion of the eye **10** shown in FIG. 1). The second elongate member **10285** has a distal end portion **10287**. At least a portion of the second elongate member **10285** can have a curved shape. The curved shape, for example, can be such that the contact portion **10288** is configured to contact a portion of the eye (e.g., the conjunctiva) along a line tangent to a portion of the second elongate member **10285**. Further to this example, the curved shape of the portion of the second elongate member **10285** can allow for a desired distribution of force(s) to be applied to a portion of the eye, as discussed above with respect to the first elongate member **10281**.

[0273] When the delivery device **10000** is in a first configuration, as shown in FIG. 44A, the distal end portion **10283** of the first elongate member **10281** and the distal end portion **10287** of the second elongate member **10285** are separated by a distance **A1**. Similarly, in the first configuration, the contact portion **10284** of the first elongate member **10281** and the contact portion **10288** of the second elongate member **10285** are separated by a distance **B1**. Moreover, when the delivery device **10000** is in the first configuration, the distal tip of the puncture member **10240** is spaced apart from the contact portion **10284** and/or the contact portion **10288** by a distance **C1** taken along a center line of the puncture member **10240**, as shown in FIG. 44A. In some embodiments, the distal tip of the puncture member **10240** is spaced apart from a line defined by the contact portion **10284** and the contact portion **10288** by a distance **C1** taken along a center line of the puncture member **10240**.

[0274] In use, a user (e.g., a doctor, technician, nurse, physician, ophthalmologist, etc.) can manipulate a delivery device **10000** to insert the puncture member **10240** into, for example, a portion of the eye (e.g., the eye **10** shown in FIG. 1). In this manner, the user can apply a distal force to move the delivery device **10000** from the first configuration to a second configuration. Similarly stated, when the puncture member **10240** is inserted into the eye, the first elongate member **10281** and the second elongate member **10285** can both move from the first configuration to the second configuration. When the delivery device **10000** is in the second configuration, as shown in FIG. 44B, the distal end portion **10283** of the first elongate member **10281** and the distal end portion **10287** of the second elongate member **10285** can be separated by a distance **A2**, **A2** being greater than **A1**. In the second configuration, as shown in FIG. 44B, the contact portion **10284** of the first elongate member **10281** and the contact portion **10288** of the second elongate member **10285** can be separated by a distance **B2**, **B2** being greater than **B1**. Moreover, when the delivery device **10000** is in the second configuration, the distal tip of the puncture member **10240** is spaced apart from the contact portion **10284** and/or the contact portion **10288** by a distance **C2** taken along a center line of the puncture member **10240**, as shown in FIG. 44B, **C2** being greater than **C1**. In some embodiments, the distal tip of the puncture member **10240** is spaced apart from a line defined by the contact portion **10284** and the contact portion **10288** by a distance **C2** taken along a center line of the

puncture member **10240**, **C2** being greater than **C1** when the delivery device **10000** is in the second configuration.

[0275] In some embodiments, when the delivery device **10000** is moved from the first configuration to the second configuration, the contact portion **10284** of the first elongate member **10281** and the contact portion **10288** of the second elongate member **10285** can cause a portion of the eye to move, or instead, prevent a portion of the eye from moving. Similarly stated, in some embodiments, the deformation of the first elongate member **10281** and/or the second elongate member **10285** can move (or alternatively maintain a position of) a portion of the target tissue. For example, in some uses, at least one of the contact portion **10284** or the contact portion **10288** can contact the conjunctiva of the eye. In this manner, at least one of the contact portions **10284**, **10288** can stabilize, hold steady, grip, stretch, or mechanically fix a portion of the eye (e.g., the conjunctiva) when the device is moved from the first configuration to the second configuration.

[0276] In some embodiments, the contact portions **10284**, **10288** can create a taught spherical injection site. For example, the first elongate member **10281** and/or the second elongate member **10285** can deform in a radial direction from the center point (i.e., away from where the puncture member **10280** penetrates) when the delivery device **10000** moves from the first configuration to the second configuration. In this manner, the conjunctiva can be held in a preferable position during the injection. In some instances, this can reduce the puncturing force to penetrate the surface of the eye. In some embodiments, the “stretching” of the conjunctiva can minimize and/or eliminate any “bunching” of the conjunctiva that may otherwise occur, and instead can produce a surface layer (e.g., conjunctiva) having a substantially constant thickness. In some instances, the contact portions **10284**, **10288** can, at least temporarily, adhere to a portion of the surface layer (e.g., conjunctiva). In this manner, the contact portions **10284**, **10288** can cause movement of and/or stabilize at least a portion of the surface layer such that at least the portion of the surface layer is in a preferable position during the injection.

[0277] In some embodiments, the elongate member **10281** and/or the elongate member **10285** can be attached to the hub **10270** in any suitable manner, as shown in FIGS. 44A and 44B. In yet other embodiments, the elongate member **10281** and/or the elongate member **10285** can be coupled to an elongate member holder or interface (not shown). The elongate member holder can be coupled to the hub **10270**. In some embodiments, the elongate member holder (not shown) can be a ring.

[0278] The elongate members **10281**, **10285** can be any suitable material (e.g., metallic or plastic). In some embodiments, the sleds can contain a plurality of different materials. For example, the contact portion **10284** of the first elongate member **10281** may contain a material not contained on a different portion of the first elongate member **10281**. In some embodiments, for example, additional materials (e.g., a coating) can be applied to any portion of the elongate members **10281**, **10285**. Further to this example, the additional material can be configured to increase or decrease friction between the elongate members **10281**, **10285** and a surface layer (e.g., conjunctiva). In some embodiments, a plurality of additional materials can be applied to the elongate members **10281**, **10285**. Each additional material (e.g., coating) from the plurality of additional materials, for

example, can include relatively unique material properties (e.g., viscosity, density, surface tension, etc.).

[0279] In some embodiments, the elongate members **10281**, **10285** can provide an indicator associated with at least one of the distance **A1**, **A2**, **B1**, **B2**, **C1**, and/or **C2**. In some embodiments, the indicator can be a visual indicator such as a measuring scale, graduated marking or the like. For example, in some embodiments, the first elongate member **10281** can include indicia (e.g., lines, markings, tic marks, etc.). In some embodiments, the markings can represent a change in location of the distal tip of the puncture member **10240** from the first configuration to the second configuration. In yet another embodiment, the markings can represent a portion of the eye where the distal tip of the puncture member **10240** is located. For example, the markings can indicate whether the distal tip of the puncture member **10240** is located in the sclera, choroid, suprachoroidal space, or retina of the eye. For another example, the markings can indicate by term the location of the distal tip of the puncture member **10240** (e.g., sclera, choroid, suprachoroidal space, retina, etc.), and can further indicate a location within the termed location (e.g., a location within the choroid). In this manner, the markings can indicate, for example, the location of the distal tip of the puncture member **10240** relative to the sclera and/or the choroid when the distal tip is located within the suprachoroidal space.

[0280] Although shown as including multiple, deformable elongate members, in other embodiments an engagement assembly and/or an adjustment assembly, for example, included or coupled to a hub, can include a single deformable member. For example, FIGS. **45A** and **45B** are schematic illustrations of a portion of a delivery device **11000**, according to an embodiment. Specifically, FIG. **45A** illustrates a portion of a delivery device **11000** in a first configuration and a second configuration (e.g., illustrated with dashed lines), and FIG. **45B** illustrates a bottom view of the portion of the delivery device **11000**. The delivery device **11000** includes a hub **11270**, a puncture member **11240** (also referred to herein as a delivery member or a needle) and an engagement member **11280**. The engagement member **11280** can be any suitable structure configured to engage the target tissue.

[0281] As shown, a proximal portion **11282** of the engagement member **11280** is coupled to the delivery device **11000**. The engagement member **11280** is coupled to the delivery device **11000** via the hub **11270**. In yet other embodiments, the engagement member **11280** can be coupled to an engagement member holder (not shown). The engagement member holder can then be coupled to the hub **11270**. The engagement member **11280** has a contact portion **11284**.

[0282] When the delivery device **11000** is in a first configuration, as shown, in FIG. **45A**, a portion of the contact portion **11284** of the engagement member **11280** is spaced apart from the distal tip of the puncture member **11240** by a distance **A1** taken along a center line of the puncture member **11240**. In some embodiments, the distal tip of the puncture member **11240** is spaced apart from a line defined by the contact portion **11282** of the engagement member **11280** by a distance **A1** taken along a center line of the puncture member **11240**. In use, a user (e.g., a doctor, technician, nurse, physician, ophthalmologist, etc.) can manipulate a delivery device (not shown) to insert the puncture member **11240** into, for example, a portion of the eye (e.g., the eye **10** shown in FIG. **1**). In this manner, the

user can apply a distal force to move the delivery device **11000** from the first configuration to a second configuration. Similarly stated, when the puncture member **11240** is inserted into the eye, the engagement member **11280** can move from the first configuration to the second configuration, as illustrated by the dashed line in FIG. **45A**. When the delivery device **11000** is in the second configuration, as shown in FIG. **44A**, a portion of the contact portion **11284** of the engagement member **11280** and the distal tip of the puncture member **11240** are separated by a distance **A2** (see the distance indicated from the dashed lines), **A2** being greater than **A1**. In some embodiments, when the delivery device **11000** is in the second configuration, the distal tip of the puncture member **11240** is spaced apart from a line defined by the contact portion **11284** of the engagement member **11280** by a distance **A2** taken along a center line of the puncture member **11240**, **A2** being greater than **A1**.

[0283] In some embodiments, when the delivery device **11000** is moved from the first configuration to the second configuration, the contact portion **11284** can cause a portion of the eye to move, or instead, prevent a portion of the eye from moving. Similarly stated, in some embodiments, the deformation of the engagement member **11280** can move (or alternatively maintain a position of) a portion of the target tissue. For example, in some uses, the contact portion **11282** of the engagement member **11280** can stabilize, hold steady, grip, stretch, or mechanically fix a portion of the eye (e.g., the conjunctiva) when the delivery device **11000** is moved from the first configuration into the second configuration.

[0284] Although the engagement member **11280** is shown and described above as including a contact portion **11284** that is curved in a convex manner (i.e., curved outwardly, or in a manner that resembles an outer surface of a sphere), in other embodiments, a hub and/or an engagement member can include a contact portion that is curved in a concave manner (i.e., curved inwardly, or in a manner that resembles an inner surface of a sphere).

[0285] In some embodiments, the engagement member **11280** can deform at a variable rate. For example, the engagement member **11280** can provide variable resistance when a user manipulates the delivery device **11000**. In some embodiments, the engagement member **11280** can provide a hard stop (i.e., a user would be substantially prevented from further inserting the puncture member **11240** into a portion of the eye). In yet other embodiments, the engagement member **11280** can be configured to provide variable resistance based on its level of deformity. In this manner, the engagement member **11280** can be configured to provide a first level of resistance when the puncture member **11240** is in a first portion of the eye and a second level of resistance when the puncture member **11240** is in a second portion of the eye, the first level of resistance being different than the second level of resistance. In some embodiments, for example, the first portion of the eye can be the sclera and the second portion of the eye can be the suprachoroidal space.

[0286] In some embodiments, the engagement member **11000** can provide an indicator associated with at least one of the distance **A1** or **A2** (i.e., the depth of penetration of the puncture member **11240**). In some embodiments, the indicator can be a visual indicator such as a measuring scale, graduated marking or the like. For example, in some embodiments, the engagement member **11280** can include indicia (e.g., lines, markings, tic marks, etc.). In some embodiments, the markings can represent a change in loca-

tion of the distal tip of the puncture member **11240** from the first configuration to the second configuration. In yet other embodiments, the markings can represent a portion of the eye where the distal tip of the puncture member **11240** is located. For example, the markings can indicate whether the distal tip of the puncture member **11240** is located in the sclera, choroid, suprachoroidal space, or retina of the eye. For another example, the markings can indicate by the anatomical term the location of the distal tip of the puncture member **11240** (e.g., sclera, choroid, suprachoroidal space, retina, etc.) and can further indicate a location within the termed location (e.g., a location within the choroid). In this manner, the markings can indicate, for example, the location of the distal tip of the puncture member **11240** relative to the sclera and/or the choroid when the distal tip is located within the suprachoroidal space.

[0287] Although the engagement assembly **10000** is shown and described above as including two or more elongate members having contact portions that are curved in a convex manner (i.e., curved outwardly, or in a manner that resembles an outer surface of a sphere), in other embodiments, a hub, an engagement assembly and/or adjustment member can include a contact portion or surface that is curved in a concave manner (i.e., curved inwardly, or in a manner that resembles an inner surface of a sphere). Similarly stated, in some embodiments, a delivery device can include a hub, an engagement assembly and/or adjustment member having a surface that is configured to engage, fit and/or conform to the surface of the target tissue (e.g., the eye). As one example, FIGS. 46-47 are perspective views of a portion of a delivery device according to an embodiment. In particular, FIGS. 46-47 are perspective views of an engagement member **12280** configured to be used in conjunction with any of the delivery devices shown and described herein. The engagement member **12280** includes a proximal end portion **12281** and a distal end portion **12282** and defines a lumen or passageway therebetween.

[0288] The proximal end portion **12281** of the engagement member **12280** can be coupled to a delivery device (not shown in FIG. 46). In some embodiments, the proximal end portion **12281** of the engagement member **12280** can be coupled to the hub **10270** (not shown in FIGS. 45-46), or any other hub described herein. For example, in some embodiments, the engagement member **12280** can be threadedly coupled to a hub to control an effective length of a puncture member (also referred to as a delivery member or needle) as described above. In this manner, the engagement member **12280** can perform the function of a needle adjustment mechanism.

[0289] As shown in FIGS. 46 and 47, the distal end portion **12282** of the engagement member **12280** includes three contact members **12283**. Each of the contact members **12283** has a surface that includes an inverse-dimpled or “beaded” traction pattern **12284**. The contact members **12283** are configured to contact a surface of the target tissue (e.g., the conjunctiva of the eye) during use to facilitate insertion of a puncture member (not shown) and/or injection of a drug formulation into the target tissue. The distal end portion **12282** of the engagement member **12280** and/or the contact members **12283** can be any suitable structure configured to engage the target tissue (as described herein). For example, in some embodiments, the distal end portion **12282** of the engagement member **12280** and/or the contact members **12283** can be any suitable structure configured to grip,

hold, and/or deform a portion of the target tissue (e.g., the conjunctiva of the eye). As shown, at least a portion of the distal end portion **12282** and/or the contact members **12283** have a curved shape. The curved shape, for example, can be such that the contact members **12283** are configured to contact a portion of the eye (e.g., the conjunctiva) along a line tangent to a portion of the contact members **12283**. Further to this example, the curved shape of the portion of the contact members **12283** can allow for a desired distribution of force(s) to be applied to a portion of the eye.

[0290] In some embodiments, the contact members **12283** can create a taught spherical injection site. For example, the contact members **12283** can deform in a radial direction from the center point (i.e., away from where the puncture member penetrates) when the delivery device (not shown) moves from a first configuration to a second configuration. In this manner, the conjunctiva can be moved into and/or held in a preferable position during the injection. In some instances, this can reduce the puncturing forces to penetrate the surface of the eye. In some embodiments, the “stretching” of the conjunctiva can minimize and/or eliminate any “bunching” of the conjunctiva that may otherwise occur, and instead can produce a surface layer (e.g., conjunctiva) having a substantially constant thickness. In some instances, the contact members **12283** can, at least temporarily, adhere to a portion of the surface layer (e.g., the conjunctiva). In this manner, the contact members **12283** can cause movement of and/or stabilize at least a portion of the surface layer such that at least the portion of the surface layer is in a preferable position during the injection.

[0291] In some embodiments, the engagement member **12280** (and any of the engagement and/or adjustment members shown and described herein) can form a substantially fluid-tight seal and/or a substantially liquid-tight seal with the outer surface of the target tissue (e.g., the conjunctiva of the eye). In this manner, leakage of the injected medicament along the needle track during the injection event can be reduced and/or eliminated. Expanding further, in some embodiments, the anatomy of the target tissue and/or the arrangement of the delivery device can be such that, in use, a portion of the opening of the needle (not shown) may be placed in fluid communication with the suprachoroidal space (e.g., suprachoroidal space **36** in FIG. 1) of the eye, while another portion of the opening of the needle may be positioned within the sclera **20** (e.g., sclera **20** in FIG. 1). Thus, when the drug formulation is conveyed into the eye via the needle (not shown), a portion of the drug formulation may be prone to migrating away from the desired region (e.g., the suprachoroidal space **36** in FIG. 1) and out of the eye via the needle track. By forming a substantially fluid-tight seal and/or a substantially liquid-tight seal, the engagement member **12280** (e.g., the surface of the contact members **12283**) can produce an area of high resistance to flow, thus minimizing and/or eliminating the flow migration and/or leakage.

[0292] In some embodiments, the engagement member **12280** can be constructed from a relatively soft material, which can be well-suited to forming a fluid-tight seal. In yet other embodiments, the engagement member **12280** can be constructed from multiple materials. For example, in some embodiments, the contact members **12283** of the engagement member **12280** can be constructed from and/or can include a layer or portion constructed from a material formulated to form a substantially fluid-tight seal with the

outer surface of the target tissue (e.g., the conjunctiva). Although the contact members **12283** are shown and described above as including a beaded surface, in other embodiments, the contact members **883** can include any suitable surface features. For example, as shown in FIG. **48**, in some embodiments, an engagement member **13280** can include a series of contact members **13283** having a smooth surface. As another example, as shown in FIG. **49**, in some embodiments, an engagement member **14280** can include a series of contact members **14283** having a ridged and/or stepped surface. In other embodiments, for example, an engagement member can include a contact member having a ribbed surface (e.g., similar to that shown in FIG. **52**).

[0293] In other embodiments, an engagement member and/or contact members can include any combination of suitable surface features. In this manner, for example, an engagement member can include a first contact member with a smooth surface and a second contact member with a ribbed surface. As another example, a contact member can include a first portion having a ribbed surface and a second portion having a beaded surface.

[0294] Although shown as including three contact members, in other embodiments, an engagement member, hub and/or adjustment member can include any number of contact members. For example, FIGS. **50-55** are illustrations of delivery devices according to various embodiments. In particular, FIG. **50** is a perspective view of an engagement member **15280** according to some embodiments. FIG. **51** is a perspective view of an engagement member **16280** according to some embodiments. As shown, for example in FIGS. **50** and **51**, in some embodiments, the engagement member **15280**, **16280** can include contact members **15283**, **16283** that are curved in a spherical manner. Further to this example, in some embodiments, the contact member **15283** can include a dimpled surface (e.g., FIG. **50**). In yet other embodiments, for example, the contact member **16283** can include a smooth surface (e.g., FIG. **51**). FIG. **52** is a perspective view of an engagement member **17280** according to some embodiments. FIG. **53** is a perspective view of an engagement member **18280** according to some embodiments. As shown, for example in FIGS. **52** and **53**, in some embodiments, the engagement member **17280**, **18280** can include contact members **17283**, **18283** that are curved in a planar manner. Further to this example, in some embodiments, the contact member **17283** can include a ribbed surface (e.g., FIG. **52**). In yet other embodiments, for example, the contact member **18283** can include a smooth surface (e.g., FIG. **53**). FIG. **54** shows a perspective view of the engagement member **18280** in use with a delivery device **18000** to engage an eye and/or deliver a medicament thereto, according to an embodiment. The delivery device can be similar to the delivery device **100**, **400**, **1000**, **2000**, **3000**, **7000**, or any other delivery device or medical injector described herein. FIG. **55** shows a cross-sectional view of the perspective view shown in FIG. **54**. The delivery device **18000** includes a hub **18270**, a puncture member **18240** (also referred to herein as a delivery member or a needle) and an engagement member **18280**.

[0295] In use, a user (e.g., a doctor, technician, nurse, physician, ophthalmologist, etc.) can manipulate the delivery device **18000** to insert the puncture member **18240** into, for example, a portion of the eye (e.g., the eye **10** shown in FIG. **1**). In this manner, the user can apply a distal force such that puncture member **18240** is advanced distally relative to

and/or through the engagement member **18280** (e.g., as shown by arrow **F1** along longitudinal axis **AA** in FIG. **55**). In this manner, a portion of the puncture member **11080** can be advanced through a portion of the eye.

[0296] In some embodiments, a system for ocular injection can include any of the hubs described herein and/or a drug extraction device configured to matingly engage with a housing and/or a medicament delivery container. For example, referring now to FIGS. **56-71**, in some embodiments, a system **19000** can include housing **19110**, an actuator **19320**, an actuating member **19140**, a medicament containment chamber **19310**, a hub **19270**, a needle **19240**, and a cap **19280**. The system **19000** can be configured to deliver a substance, for example, a medicament to a target tissue, for example, the SCS of an eye.

[0297] The housing **19110** (FIG. **57**) includes a first portion **19110a**, and a second portion **19110b** (collectively “**19110**”) that can be coupled together to define an internal region for housing at least a portion of the medicament containment chamber **19310** and the actuator **19320**. The housing **19110** includes a gripping portion **19112** to allow a user to grip the housing **19110** between his index and middle finger. The housing **19110** also includes ridges **19114** to allow easy gripping of the housing **19110** by the user. For example, the user can grip the gripping portion **19112** with one hand and grip the ridges **19114** with the fingers of a second hand during injection, for example, delivery of a medicament into a target tissue (e.g., ocular tissue). In this manner, the user any sideways movement of the system **19000** during medicament delivery can be reduced. A set of windows **19116** are defined in a sidewall of the housing **19110**. The set of windows **19116** can be configured to allow the user to view the interior volume of the medicament containment chamber **19310**, for example, to view a level of a medicament remaining in the medicament containment chamber **19310**. The housing **19110** also include a set of slots **19118**, each slot configured to slidably receive a rib **19323** included in an engagement portion **19322** of the actuator **19320**, such that the set of slots are configured to keep the actuator **19320** aligned as the actuator **19320** is displaced within the housing **19110** and the medicament containment chamber **19310**.

[0298] As shown in FIGS. **57** and **58**, the actuator **19320** includes an engagement portion **19322** and a plunger portion **19324**. The engagement portion **19322** includes a set of ribs **19323** slidably disposed in the set of slots **19118** of the housing **19110**, as described before. A portion of the engagement portion **19322** is disposed in a cavity **19146** defined by the actuating member **19140** (see, e.g., FIG. **62**). The plunger portion **19324** includes a protrusion **19327** disposed on a distal end of the actuator **19320**. The protrusion **19327** can be configured to be disposed in a recess **19335** defined by a plug **19328** with close tolerance (e.g., friction fit), as described herein. The plug **19328** (FIGS. **59-60**) is disposed in the internal volume **19316** defined by the medicament containment chamber **19310**. The plug **19328** includes a proximal end **19332** coupled to the plunger portion **19324** of the actuator **19320** and a distal end **19334** in fluid communication with a medicament or any other liquid disposed in the internal volume **19316** defined by the medicament containment chamber **19310**. The plug **19328** can be made of a rigid but soft material, for example, rubber, and includes the recess **19335** configured to receive the protrusion **19327** of the actuator **19320** with close tolerance (e.g., friction fit).

The plug **19328** includes a first sidewall **19336a** and a second sidewall **19336b** (collectively referred to as the “sidewalls **19336**) in contact with a sidewall of the internal volume **19316** of the medicament containment chamber **19310**. The sidewalls **19336** form a substantially fluid-tight seal with the sidewalls of the inner volume **19316** defined by the medicament containment chamber **19310**. In this manner, the plug **19328** can prevent leakage of the liquid medicament from the internal volume **19316**, for example, leakage of the medicament into a portion of the internal volume **19316** within which the plunger portion **19324** of the actuator **19320** is disposed.

[0299] The actuation member **19140** (FIGS. **61-62**) includes a depression **19142**, shaped to conform to a thumb of a user, for example, to allow easy displacement of the actuating member **19140** by the user. The actuating member **19140** also includes ridges **19144** configured to allow easy gripping of the actuating member **19140**, for example, when loading a medicament into the medicament containment chamber **19310**. The actuation member **19140** also includes a cavity **19146**, configured to slidably receive a portion of the engagement portion **19322** of the actuator **19320** with close tolerance (e.g., friction fit). In some embodiments, the actuating member **19140** can be configured to be engaged by the user to manually move the plunger portion **19324** of the actuator **19320** within the internal volume **19316** of the medicament containment chamber **19310**. In some embodiments, the actuating member **19140** can be included in an injection assembly, for example, the injection assembly **100**, **2100**, or any other injection assembly described herein, that can be included in the system **19000**. The actuating member **19140** can be configured to activate the injection assembly, for example, to release and/or move the actuator **19320** such that the plunger portion **19324** moves within the internal volume **19316** and expels at least a portion of the medicament through the needle **19240** (e.g., into the SCS of the eye).

[0300] As shown in FIGS. **63-65**, the medicament containment chamber **19310** defines an internal volume **19316**, configured to house a medicament. The medicament containment chamber **19310** includes a delivery portion **19324**. A first set of threads **19318a** and a second set of threads **19318b** (FIG. **63**) are formed on an outer wall of the delivery portion **19314**. Said another way, the outer wall of the delivery portion **19314** includes double-start threads. The threads **19318** are configured to allow coupling of the medicament containment chamber **19310** to a coupling portion **19272** of the hub **19270**. In some embodiments, any other hub, an injection site marker, for example, the injection site marker **20280** described below, and/or an extraction device, for example extraction device **21280**, can be coupled to the delivery portion **19324** via the threads **19318**. The delivery portion **19314** includes a first cavity **19315** configured to receive an engagement portion **19273** (e.g., a nozzle) of the hub **19270**, such that a fluidic channel **19317** included in the delivery portion **19314** is in fluid communication with a first fluidic channel **19277** included in the engagement portion **19273** of the hub **19270**. The medicament containment chamber **19310** also includes a second cavity **19313**. The engagement portion **19322** of the actuator **19320** is disposed within the second cavity **19313** and is configured to be slidably displaced within the second cavity **19313**.

[0301] As shown in FIGS. **66-67**, the hub **19270** includes an engagement portion **19273**, a coupling portion **19272**,

and a delivery portion **19274**. An inner sidewall of the engagement portion **19273** and an outer sidewall of the coupling portion **19272** define a recess **19275** configured to receive the delivery portion **19314** of the medicament containment chamber **19310**. The inner sidewall of the coupling portion **19272** includes threads **19278**, configured to engage the threads **19318a** and/or **19318b** of the medicament containment chamber **19310**, thereby coupling the hub **19270** to the medicament containment chamber **19310**. An outer sidewall of the coupling portion **19272** includes a set of ridges **19276**. The ridges **19276** can facilitate a user to grip the hub **19270**, for example, for coupling or uncoupling the hub **19270** from the medicament containment chamber **19320**. The engagement portion **19273**, defines a fluidic channel **19277** configured to engage the fluidic channel **19317** of the medicament containment chamber **19310** and establish fluidic communication between the medicament containment chamber **19310** and the hub **19270**. The delivery portion **19274**, defines a second fluidic channel **19279** configured to removably receive the needle **19240**, for example, a microneedle (e.g., any suitable microneedle described herein). The needle **19240** is configured to be disposed within a target tissue, for example, ocular tissue and defines a lumen **19241** such that the needle **19240** is configured to establish fluidic communication between the medicament containment chamber **19310** and the portion of the user's body (e.g., the eye). In some embodiments, the needle **19240** can be fixedly disposed in the second fluidic channel **19279**. In some embodiments, the needle **19240** can be monolithically formed with the hub **19270** such that the second fluidic channel **19279** and the lumen of the needle **19241** are continuously and/or seamlessly formed.

[0302] As shown in FIGS. **68** and **69**, the cap **19280** includes a coupling portion **19282** that includes a first cavity **19283** configured to slidably receive the coupling portion **19272** of the hub **19270**. A set of grooves **19285** is formed on an inner sidewall of the coupling portion **19282** configured to mate with the set of ridges **19276** of the hub **19270** with close tolerance (e.g., friction fit). The cap **19280** also includes an engagement portion **19284** that defines a second cavity **19284** configured to receive the delivery portion **19274** of the hub **19270**. At least a portion of an outer sidewall of the engagement portion **19284** is substantially flat, for example, to allow a user to grip the cap **19280** with ease (e.g., to couple or uncouple the hub **19270** from the medicament containment chamber **1150**). The cap **19280** can thus enable safe coupling/uncoupling of hub **19270** to the medicament containment chamber **19310** and/or prevent accidental piercing of a portion of a user's body by the needle **19240** during handling of the system **19000**.

[0303] Referring now to FIGS. **70-71**, FIG. **70** shows the system **19000** in a first configuration, such that the actuator **19320** and the actuating member **19140** are in a first position and the internal volume **19316** of the medicament containment chamber **19310** is at least partially filled with the medicament. A user can now engage the actuating member **19140** by applying a force in the direction shown by the arrow **F** on the actuating member **19140**, for example, using a thumb of the user. This urges the actuator **19320**, which is coupled to the actuating member **19140**, to displace along a longitudinal axis **AA** of the system **19000** and urge the system **19000** into the second configuration as shown in FIG. **71**. In the second configuration, the actuator **19320** is displaced from the first position to a second position within

the internal volume **19316** of the medicament containment chamber **19310**. This displacement causes the plug **19328**, which is in fluid communication with the medicament, to slide from the first position to the second position within the internal volume **19316**. The movement expels the medicament from the internal volume **19316** into the fluidic channel **19277** of the hub **19270**, and further through the lumen **19241** of the needle **19240** into the target tissue (e.g., the eye).

[0304] In some embodiments, a system for ocular injection can include an injection marker for marking an injection site on a target tissue, for example, ocular tissue. FIG. 72-73 show perspective views of an injection site marker **20280** according to an embodiment. As shown, a proximal end **20282** of the injection site marker **20280** can be coupled to a delivery device, for example, coupled to the coupling portion **19272** of the hub **19270** included in the system **19000**. The injection site marker **20280** has a distal end **20284**, which includes a set of protrusions **20286** disposed on a distal end surface of the distal end **20284**. In some embodiments, the proximal end **20282** of the injection site marker **20280** can be used in conjunction with and/or coupled to any of the hubs, engagement members and/or adjustment members described herein. For example, in some embodiments, the injection site marker **20280** can be threadedly coupled to a hub of a delivery device (e.g., hub **19270** of delivery device **19000**). In other embodiments, for example, the injection site marker **20280** can be coupled by way of friction (e.g., interference fit, press fit, friction fit, etc.)

[0305] In some embodiments, the protrusions **20286** of the distal end **20284** of the injection site marker **20280** can be configured to contact a portion of the eye (e.g., the eye **10** shown in FIG. 1). In some embodiments, for example, the protrusions **20286** of the injection site marker **20280** can be configured leave a marking on a portion of the eye. The marking, for example, can indicate an injection site. For example, the markings can appear as parallel indentations on the conjunctiva of the eye indicating to the user that the injection is to be performed in the region between the parallel markings. Further to this example, in some embodiments, the injection site marker **20280** can be removably coupled to a delivery device (e.g., the delivery device **19000**). In such embodiments, the injection site marker **20280** can be removed from the delivery device after marking the injection site on the target tissue. A needle assembly and/or hub that includes a needle, for example, the needle **19240** coupled thereto, can then be coupled to the delivery device which can be used to deliver the medicament to the injection site marked by the injection site marker **20280**. In some embodiments, an injection site marker can define a passageway to allow a needle to pass therethrough. In such embodiments, the injection site marker can remain coupled to the delivery device during delivery of the medicament to the target tissue.

[0306] In some embodiments, a system for delivering medicaments can include an extraction device for extracting medicaments or any other fluid from a container, for example, a vial. Referring now to FIG. 74-80, a system **21000** includes a housing **21110**, an actuator (not shown), an actuating member **21140**, a medicament containment chamber **21310**, and an extraction member **21280**. The system **21000**, that includes the extraction member **21280**, can be used to extract a liquid medicament from a medicament

container **21294**. The housing **21110**, the actuator, the medicament containment chamber **21310**, and actuating member **21140** of the system **21000** can be substantially similar in structure and function to the components of the system **19000** described earlier, and are therefore not described in further detail herein.

[0307] FIG. 74 shows the extraction member **21280** uncoupled from the medicament containment chamber **21310** while FIG. 75 shows the extraction member **21280** coupled to the medicament containment chamber **21310**. As shown in FIG. 76, the extraction member **21280** includes a coupling portion **21281**, an engagement portion **21284** and an extraction portion **21288**. Threads **21282** are formed on an inner side wall of the coupling portion that are configured to mate with the threads of **21318a** and **21318b** of the medicament containment chamber **21310** and to couple the extraction member **21280** to the medicament containment chamber **21310**. A set of ridges **21283** are formed on an outer sidewall of the coupling portion **21281**. The ridges **21283** can, for example, serve as grips to facilitate a user to couple/uncouple the extraction member **21280** to the medicament containment chamber **21250**. The inner sidewall of the coupling portion **21281** and an outer sidewall of the engagement portion **21284** define a cavity **21285**, configured to receive a portion of the medicament containment chamber **21310**, when the extraction member **21280** is coupled to the medicament containment chamber **21310**. The engagement portion **21284** includes a fluidic channel **21286** configured to establish fluid communication between the extraction member **21280** and the medicament containment chamber **21250**, for example, to allow communication of fluid from the extraction member **21280** (e.g., liquid medicament extracted from a medicament vial) to the medicament containment chamber **21250**.

[0308] The extraction portion **21288** is configured to be releasably coupled to a container **21294** that contains a medicament, and establish fluid communication between the container **21294** and the medicament containment chamber **21310** via the extraction member **21280**. The extraction portion **21288** includes a set of arms **21289**. Each of the set of arms **21289** has an angled portion configured to flex open for receiving a cap of the container, for example, the container **21294**. Each of the set of arms **21289** also include a ledge **21290** configured to secure the cap of the container, for example container **21294** when the container is coupled to the extraction member **21280**, as shown in FIG. 75. The extraction portion **21288** also includes a puncturing member **21291** that defines a fluidic channel **21292**. The puncturing member **21291** is configured to puncture a seal of a container, for example, container **21294**, and establish fluid communication between the container and the medicament containment chamber **21310**, via the extraction member **21280**, as described herein.

[0309] FIG. 77 shows a perspective view of the system **21000** in a first configuration, such that the container **21294** is uncoupled from the extraction member **21280**. The container **21294** includes a cap **21296** that has a seal **21297**, for example, a septum (e.g., a rubber septum), and defines an internal volume for housing a liquid medicament. FIG. 78 shows a sectioned view of the perspective view shown in FIG. 77, but only the extraction member **21280** and the container **21294** are shown for clarity. A user can apply a force shown by the arrow F2 (FIG. 78) along a longitudinal axis BB of the system **21000** to urge the extraction member

21280 towards the container **21294**. Optionally, a force can also be applied to the container **21294** to urge the container **21294** towards the extraction member **21280**. This urges the system **21000** into the second configuration (FIGS. **79-80**) such that extraction member **21280** is releasably coupled to the cap **1296** of the container **21294**. As shown in the sectioned view of FIG. **80**, in the second configuration a surface of the ledge **21290** included in the each of the set of arms **21289** of the extraction member **21280**, are contacting a small portion of a bottom surface of the cap **21296** of the container **21294**. In this manner, the container **21294** is releasably secured to the extraction member **21280**. Furthermore, the puncturing member **21291** punctures the seal **21297** of the cap **21296** included in the container **21294** to establish fluid communication between the container **21294** and the medicament containment chamber **21310** via the extraction member **21280**. Medicament can now be extracted from the container **21294** by a user by engaging the actuating member **21240**, as described herein with reference to system **19000** (FIGS. **70-71**). To uncouple the container **21294** from the extraction member **21280**, the user can simply pull the container **21294** away from the extraction member in a direction opposing the direction indicated by arrow **F2** (FIG. **78**).

[0310] In some embodiments, a system for injection of a medicament into an ocular tissue, for example, the SCS can include a mechanism for insertion of the puncturing member as well as delivering the medicament. Referring now to FIGS. **81-83**, a system **22000** includes a housing **22110**, a needle assembly **22200** that includes a puncturing member **22240** and a hub **22270**, and a medicament containment chamber **22310**. At least a portion of an actuator (not shown) can be disposed in the medicament containment chamber **22310**. The actuator is configured to communicate a medicament disposed in an internal volume of the medicament containment chamber **22310** into an ocular tissue, for example, the SCS of an eye.

[0311] The housing **22110** has an ergonomic shape and includes ridges **22114** to allow a user to easily grip the housing **22110**. The housing **22110** can define an internal volume within which at least a portion of the medicament containment chamber **22310** and the actuator can be disposed. In some embodiments, an injector assembly, for example, the injector assembly **2100** or any other injector assembly described herein can be disposed in the housing **22110**. The housing **22110** is configured to move laterally along a longitudinal axis A_z of the system **22000**, between a first configuration shown in FIG. **81** and a second configuration shown in FIG. **83**. In this manner, the housing **22110** can move the actuator and draw in or expel out a medicament from the medicament containment chamber **22310**. In some embodiments, the housing **22110** can also be configured to insert the puncturing member **22240** into the ocular tissue.

[0312] The medicament containment chamber **22310** defines an internal volume within which a medicament can be disposed. A set of markings **22315** can be defined on an outer surface of the medicament containment chamber **22310**. The medicament containment chamber **22310** can be substantially transparent such that the user can visually observe a volume of the medicament disposed in the internal volume and use the markings **22315** to determine the quantity of the remaining medicament. In some embodiments, the medicament containment chamber **22310** can be

substantially similar to the medicament containment chamber **1310**, **2310**, **3310**, or any other medicament containment chamber described herein.

[0313] The needle assembly **22200** includes a housing **22210** that can define an internal volume configured to house the components of the needle assembly **22200**. A plurality of ridges **22216** are disposed on an outer surface of the housing **22210**. The ridges **22216** are configured to allow a user to easily grip the housing **22210** (e.g., for rotating the housing **22210**). The needle assembly **22200** can be configured to adjust a length of the puncturing member **22240** protruding from a distal end **22274** of the hub **22270**. For example, a user can rotate the needle assembly **22200** about the longitudinal axis A_z to adjust a length of the puncturing member **22240** protruding from a distal end **22272** of the hub **22270**. In some embodiments, the needle assembly **22200** can include an adjustment member, a lead screw, bushing, bearing, locking pin, markings, or any other components as described with respect to the needle assembly **3200** described herein.

[0314] The puncturing member **22240** is configured to be inserted into the eye and to deliver a medicament into the eye. The puncturing member **22240** can be substantially similar to the puncturing member **3240** or any other puncturing member described herein. At least a portion of the puncturing member **22240** is disposed in the hub **22270**. For example, a proximal end portion of the puncturing member **22240** can be disposed in a passageway defined by the hub **22270**. The hub **22270** includes a proximal end **22272** and a distal end **22274**. The distal end **22274** can be curved, for example, define a convex or hemispherical shape. A distal end surface of the distal end **22274** can define a sealing portion configured to contact an outer surface of the eye, for example, the conjunctiva, and form a substantially fluid-tight seal around an insertion site of the puncturing member **22240**, as described with respect to the hub **7270**. The proximal end **22272** of the hub **22270** can be removably or fixedly coupled to a distal portion of the housing **22210**. For example, the proximal end **22272** can include a friction fit, snap fit, threads, grooves, notches, indents, detents, or any other suitable coupling mechanism to couple the hub **22270** to the housing **22210**. In some embodiments, the hub **3270**, **7270**, **8270**, **9270**, or any other hub described herein can be coupled to the housing **22210**.

[0315] In a first configuration shown in FIG. **81**, the housing **22110** can be disposed distally relative to the needle assembly **22200** and the medicament containment chamber **22310**. The medicament can be disposed in the internal volume of the medicament containment chamber **22310**. In the second configuration, shown in FIG. **83**, a user can dispose the hub **22270** of the system **22000** on an outer layer of the eye (e.g., the conjunctiva **C**). The user can then exert a force on the housing **22110** in the direction shown by the arrow F_3 to move the housing **22110** proximally relative to the needle assembly **22200**. This can cause the puncturing member **22240** to be inserted into the ocular tissue, for example, a sclera of the eye, and the medicament to be expelled from the internal volume of the medicament containment chamber **22310**. The user can use the needle assembly **22200** to adjust an insertion depth of the puncturing member **22240** to ensure that the medicament is communicated to the target ocular tissue (e.g., the SCS).

[0316] In some embodiments, a needle adjustment mechanism can include adjusting the insertion depth of a needle

into a target tissue, for example, ocular tissue, by varying the force on an actuation rod included in a medical injector. For example, FIGS. 84A and 84B show a portion of a medical injector **23000**, that includes an actuation rod **23320** and a needle disposed in a target tissue in a first configuration and a second configuration, respectively, according to an embodiment. A distal end portion of the actuation rod **23320** is disposed in a medicament container included in the medical injector. The medical injector can be substantially similar to the medicament container **130**, **1310**, **2310**, **3310**, or any other medicament container described herein. The needle **23240** can be any suitable puncture member, for example, a microneedle (e.g., a 27 gauge needle, a 30 gauge needle, or even smaller). The medical injector **23000** also includes a needle adjustment mechanism that can be used to adjust the distance a distal tip of the needle **23240** travels into the target tissue, for example, ocular tissue based on the magnitude of force applied on an proximal portion, for example, an engagement portion of the actuation rod **23320**. By way of example, in some embodiments, the needle adjustment assembly can include any suitable mechanism configured to increase the distance that the distal tip of the needle **23240** travels into the target tissue based on the force applied on the actuation rod **23320**. The force applied on the actuation rod **23320** can continue to increase the distance traveled by the distal tip of the needle **23240** without delivering the medicament from the distal tip of the needle **23240**, until the distal tip of the needle **23240** is disposed within a target region (e.g., the SCS) of the target tissue. The force can then, for example, overcome the backpressure of the target region of the target tissue such that the distal tip of the needle **23240** does not travel any further into the target tissue and the medicament is delivered to the target region. The needle adjustment mechanism can include any suitable components such as, for example, a biasing member (e.g., a spring or a hydraulic biasing member), one or more valves, and, or a force sensing mechanism. In some embodiments, the force applied on the actuation rod **23320** can be adjusted manually, for example, via haptic feedback to a user engaging the actuation rod **23320**. In some embodiments, an automated force adjustment mechanism, for example, included in the needle adjustment mechanism or an injection assembly (e.g., the injection assembly **100**, **2100**, or any other injection assembly described herein) can be used to adjust the force and thereby, control the insertion depth of the distal tip of the needle **23240**.

[0317] For example, the distal tip of the needle **23240** can be inserted into an ocular tissue and configured to deliver a medicament to the SCS of the ocular tissue. In the first configuration shown in FIG. 84A, a first force F_1 is applied on the actuation rod **23320**. The first force F_1 (e.g., less than about 2N) can be sufficient to overcome the backpressure of the conjunctiva (not shown) and get inserted into the sclera S, but insufficient to urge the distal tip of the needle **23240** to travel across the thickness of the sclera S and be disposed in the SCS. The user can then apply a second force F_2 greater than the first force F_1 and sufficient to overcome a backpressure and/or density of the sclera S such that the distal tip of the needle **23240** travels through the sclera S and is disposed within or near the SCS. In some embodiments, the second force F_2 can be between about 2 N and about 6 N, for example, about 3 N, about 4 N, about 5 N, or any other range or value therebetween. The user can maintain the force F_2 such that once the distal tip of the needle **23240** reaches the

SCS, the force F_2 can overcome the backpressure of the SCS and thereby, deliver the medicament to the SCS. In some embodiments, the transition from the first force F_1 to the second force F_2 can be gradual. For example, the force applied on the actuator can be increased slowly from the force F_1 until the force has a sufficient magnitude (e.g., substantially equal to the second force F_2) to urge the distal tip of the needle **23240** to travel through the sclera S and be disposed in the SCS.

[0318] In some embodiments, a medical injector can include an injection assembly that includes an actuation member configured to actuate an actuation rod included in the medical injector. For example, FIGS. 85A and 85B show a medical injector **24000** that includes medicament container, a needle, and an injection assembly, in a first and a second configuration respectively, according to an embodiment. The injection assembly includes an actuation member **24120** and an actuation rod **24320**. The injection assembly can include other components such as, for example, an energy storage member (e.g., a spring, a compressed gas cylinder, or a propellant container), a release member (e.g., a lock, latch, a pawl), a guide rod, or any other components described with respect to the injection assembly **100**, **2100**, or any other injection assembly described herein. In some embodiments, the actuation member **24120** can be configured to engage and/or secure a proximal end portion of the actuation rod **24320**. In some embodiments, the actuation member **24120** can be configured to engage a release member that is configured to engage or otherwise secure a proximal end portion of the actuation rod **24120**. The actuation member **24120** can be engaged by a user such that the actuation member **24120** releases the actuation rod **24320** or urges the release member to release the actuation rod **24320**. This can enable a distal end portion of the actuation rod **24320** to move within the medicament container, as shown in FIG. 85B.

[0319] For example, as shown in FIG. 84A-B, the actuation member **24120** includes a lever like member that can be disposed on a sidewall of a housing coupled to the medicament container. In the first configuration shown in FIG. 84A, the actuation member can be in a first position in which a distal end of the actuation member **24120** is distally disposed from the medicament container. In the first configuration, a proximal end portion of the actuation member **24120** can be engaged by the actuation member **24120** or the release member and prevent a distal end portion of the actuation rod **24320** from moving within the medicament container. Furthermore, an energy storage member or a biasing member can be coupled to the proximal end portion of the actuation rod **24320**. In the second configuration shown in FIG. 84B, a user can engage the actuation member **24120**, for example, move a distal end of the actuation member **24120** proximally relative to the medicament containment chamber in a direction shown by the arrow A. This can urge the actuation member to release the proximal end portion of the actuation rod **24320**. In some embodiments, the engaging of the actuation member **24120** can engage a release member engaging or otherwise securing the proximal end portion of the actuation rod **2320** such that the release member releases the proximal end portion of the actuation rod **24320**. The energy storage member or biasing member coupled to the proximal end portion of the actuation rod **24320** can then urge the distal end portion of the

actuation rod **24320** to move within the medicament container and thereby, deliver medicament to a target tissue via the needle.

[0320] In some embodiments, a medical injector can include a needle adjustment mechanism that includes a wheel. For example, FIG. **86** shows a medical injector **25000** that can include a medicament container, a needle assembly **25200**, and a needle **25240**. The needle adjustment mechanism **25200** includes a wheel **25230**. The wheel **25230** is pivotally mounted in a housing of the medical injector **25000**. The wheel **25230** can include a plurality of protrusions defined thereon, which can be engaged by a user to move or otherwise rotate the wheel **25230**. The wheel **25230** can be configured to be rotated in discrete angular displacements, such that each discrete angular displacement corresponds to a discrete adjustment of the length of a portion of the needle **25240** emerging from a distal end of a housing, or a hub coupled to the housing. In some embodiments, each discrete angular displacement can correspond to a length adjustment of about 100 microns of the needle **25240**. In this manner, the wheel **25230** can allow for digital adjustment of the length of the needle **25240**. For example, a user can insert a distal tip of the needle a first distance (e.g., corresponding to the depth of the sclera) of a target tissue (e.g., ocular tissue). The user can then engage the wheel **25230** by rotating the wheel **25230** about its pivot mount in discrete increments as described herein. This can adjust the length of the needle **25240** such that a distal tip of the needle **25240** travels a second distance into the target tissue (e.g., corresponding to the depth of the SCS) such that the distal tip of the needle **25240** is disposed within or near a target region (e.g., the SCS) of the target tissue. The medical injector **25000** can deliver at least a portion of the medicament disposed within the medicament container into the target tissue (e.g., the SCS). For example, an injection assembly (e.g., the injection assembly **100**, **2100**, or any other injection assembly described herein) included in the medical injector **25000** can be configured to initiate delivery of the medicament into the target region (e.g., the SCS), thereby informing the user that the distal tip of the needle **25240** is disposed in the target region. In some embodiments, the wheel **25230** can also be configured to move a distal end of an actuation rod disposed within the medicament container, for example, to deliver the medicament to the target tissue via the needle **25240**.

[0321] In some embodiments, a medical injector can include a pressure assist assembly configured to exert a pressure on a proximal end portion of an actuation rod and assist, facilitate and/or affect the delivery of a medicament from a medicament container. For example, FIG. **87** shows a portion of a medical injector **26000** that includes a housing **26110**, a pressure assist assembly that includes an actuation member **26120**, and a medicament container **26310** coupled to the housing **26110**. A needle is also coupled to the medicament container **26310** and in fluidic communication with a medicament disposed within the medicament container **26310**. As shown, in some embodiments, the actuation member **26120** can be a button disposed within a sidewall of the housing **26110**. The pressure assist assembly can also include other components such as, for example, one or more energy storage members (e.g., a spring, a compressed gas container, or a propellant container). The energy storage member can be coupled to a proximal end portion of an actuation rod included in the medical injector **26000**. A distal

end portion of the actuation rod can be disposed within the medicament container **26310** and configured to move within the medicament container **26310**. In some embodiments, the pressure assist assembly can also include a release member configured to engage or otherwise secure the proximal end portion of the actuation rod in a first configuration in which the medicament container is filled with a volume of the medicament. In such embodiments, the actuation member **26120** can be configured to engage the release member and urge the release member to release the proximal end portion of the actuation rod. For example, in a second configuration, the actuation member **26120** can be engaged (e.g., depressed) by a user thereby urging the release member to release the proximal end portion of the actuation rod. The energy storage member can now exert a force on the proximal end portion of the actuation rod configured to move a distal end portion of the actuation rod within the medicament container **26310**. This applies a pressure on the medicament disposed within the medicament container **26310** and dispels the medicament through a distal end of the needle.

[0322] In some embodiments, a medical injector can include a needle adjustment mechanism that includes a leaf spring. For example, FIG. **88** shows a portion of a medical injector **27000** that includes a medicament container **27310**, a leaf spring **27230**, and a needle **27240** in a first position (solid lines) and a second configuration (dotted lines). The leaf spring **27230** can be coupled to the medicament container **27310** or a hub coupled to the medicament container **27310**, and configured to move from a first position to a second position in response to a force applied in a direction shown by the arrow F. The movement of the leaf spring **27230** is configured to allow a distal tip of the needle **27240** to be disposed within a target region. More force can be required to move the leaf spring **27230** more and move the distal tip of the needle deeper into the target tissue (e.g., an ocular tissue). For example, as shown in FIG. **88**, in the first configuration a distal end surface of the leaf spring **27230** can be in contact with the outer surface of the conjunctiva C of an eye. Furthermore, a limbus **27242** defined on a distal end of the needle **27240** can be disposed a first distance L_1 into the eye as measured from a distal end of the leaf spring **27230** such that the limbus **27242** is disposed in the sclera S of the eye. A force F can be applied to move or otherwise compress the leaf spring **27230** and move the limbus **27242** deeper into the eye. For example, a magnitude of the force F can be increased until the leaf spring **27230** moves into the second configuration. This also urges the distal end of the needle **27240** to move deeper into the eye, until in the second configuration, the limbus **27242** is disposed a second distance L_2 into the eye as measured from the distal end of the leaf spring **27230**. The second distance L_2 can correspond to a depth of the suprachoroidal space within the eye, such that the limbus **27242** is disposed within or near the suprachoroidal space SCS (e.g., the target region) in the second configuration. In this manner, the leaf spring **27230** can be used to adjust a length of the needle **27240** thereby, facilitating delivery of a medicament to the target region of a target tissue. In some embodiments, the movement of the leaf spring **27230** from the first position to the second position can be configured to move the needle a predetermined distance corresponding to the depth of a target region of a target tissue (e.g., the SCS).

[0323] In some embodiments, a needle adjustment mechanism can include an adjustment member movable between a first position and a second position to adjust a distance a distal tip of a needle travels within a target tissue. For example, FIGS. 89A and 89B show a portion of a medical injector 28000 that includes a medicament container 28310, a hub 28270, an adjustment member 28230 and a needle 28240 in a first configuration and a second configuration, respectively. The medicament container 28310 can be substantially similar to the medicament container 130, 1310, 2310, 3310, or any other medicament container described herein. The proximal end portion of the hub 28270 can be coupled to the medicament container 28310 and a distal end portion of the hub 28270 can be coupled to a proximal end of the needle 28240 such that a medicament contained within the medicament container 28310 is in fluid communication with the needle 28240. The hub 28270 can be substantially similar to the hub 7270, 8270, 9270, or any other hub described herein. The adjustment member 28230 can be slidably disposed about the needle 28240 and be configured to be movable between a first position A and a second position B. As shown, the adjustment member 28230 defines a curved surface, which can be configured to conform the curved surface of a target tissue, for example, an eye. The movement of the adjustment member 28230 can be used to adjust a distance that a distal tip of the needle 28240 can be inserted into the target tissue, for example, ocular tissue.

[0324] For example, in the first configuration shown in FIG. 89A, the adjustment member 28230 can be disposed at the first position A and a distal tip of the needle 28240 can be inserted a first distance into a target tissue (e.g., within the sclera of an eye). Furthermore, the curved surface of the adjustment member 28230 can be in contact with and conformal to an outer surface of the target tissue (e.g., the conjunctiva of the eye). A force can be applied on the medical injector 28000, for example, on a proximal end portion of the medicament container 28310, or a proximal end portion of an actuation rod included in the medical injector 28000. This can urge the adjustment member 28230 to slide and move about the needle 28240 proximally relative to the medicament container 28310. The force can be maintained until the adjustment member 28230 moves to position B. This increases the distance the distal tip of the needle 28240 travels within the target tissue (e.g., ocular tissue), for example, until the distal tip of the needle 28240 is disposed within or near a target region (e.g., the SCS) of the target tissue. In this manner, the medicament disposed within the medicament container 28310 can be delivered to the target region (e.g., the SCS) of the target tissue.

[0325] In some embodiments, a needle adjustment assembly can include an adjustment member configured to adjust the length of a needle in discrete increments. For example, FIGS. 90A-C show a medical injector 29000 that includes a medicament container 29310, a needle adjustment assembly 29200, and a needle 29240 fluidically coupled to the medicament container 29310, in a first, second, and third configuration, according to an embodiment. The medicament container 29310 can be substantially similar to the medicament container 130, 1310, 2310, 3310, or any other medicament container described herein. The needle 29240 can include any suitable puncture member, for example, a microneedle, or any other needle described herein. The needle adjustment mechanism 29200 includes an adjustment

member 29230 configured to be engaged by a user to adjust a length of the needle 29240, for example, to a control a distance a distal tip of the needle 29240 travels into a target tissue. By way of example, the adjustment member 29230 can be configured to move in discrete increments, for example, increments of 100 microns such that the length of the needle 29240 can be digitally adjusted. For example, as shown in the first configuration of FIG. 90A, the needle can have a first length L_1 (e.g., about 750 microns) measured from a distal tip of the needle to a distal end of the medicament container 29310, or a hub (e.g., any of the hubs described herein) coupled to the distal end of the medicament container 29310. The length L_1 can be sufficient to insert the distal tip of the needle 29240 in a target tissue such that the distal tip is disposed short of a target region (e.g., the SCS) of the target tissue (e.g., ocular tissue). The adjustment member 29230 can be engaged, for example, depressed into the medicament chamber by a first increment by applying a force F on the adjustment member 29230. This can increase the length of the needle 29240 to a second length L_2 (e.g., about 850 microns), as shown in FIG. 90B measured from the distal tip of the needle 29240 to the distal end of the medicament container 29310, or a hub (e.g., any of the hubs described herein) coupled to the distal end of the medicament container 29310. The second length L_2 can be sufficient to insert the distal tip of the needle 29240 deeper into the target tissue but still insufficient to dispose the distal tip of the needle 29240 into the target tissue. The adjustment member 29230 can be engaged a second time applying the force F again on the adjustment member 29230. This can further increase the length of the needle 29240 to a third length L_3 (e.g., about 950 microns) measured from the distal tip of the needle 29240 to the distal end of the medicament container 29310, as shown in FIG. 90C. The third length L_3 can be sufficient to insert the distal tip of the needle 29240 deeper into the target tissue such that the distal tip of the needle 29240 is disposed within the target region (e.g., the SCS) of the target tissue. Thus, delivery of the medicament contained within the medicament container 29310 can be initiated to the target region (e.g., the SCS) of the target tissue, for example, via an injection assembly included in the medical injector 29000.

[0326] In some embodiments, a medical injector can include a needle adjustment mechanism configured to allow adjustment of a length of a needle included in the medical injector in a small set of qualitative increments. For example, FIG. 91 shows a medical injector 30000 that includes a needle adjustment mechanism including an adjustment member 30230, and a needle 30240 fluidically coupled to a medicament container. The adjustment member 30230 is slidably disposed within a sidewall of a housing of the medical injector 30000. The adjustment member 30230 can be configured to be moved between three discrete positions corresponding to a short length, an intermediate (mid) length, and a long length of the needle emerging from a distal end of the medical injector 30000. The needle adjustment mechanism can include other components such as, for example, notches, grooves, indents, detents, a lock ball, a biasing member, or any other component configured to allow the adjustment member 30230 to be moved in the discrete increments as described herein.

[0327] In some embodiments, a medical injector can include a hub configured to allow adjustment of a length of a needle inserted into a target tissue. For example, FIGS.

92A and 92 B show a portion of a medical injector 31000 that includes a housing 31110, a hub 31270, and a needle 31240, according to an embodiment. The needle 31240 is fixedly coupled to a distal end of the housing 31110, for example, fluidically coupled with a medicament container disposed within the housing 31110. The hub 31270 is coupled to a distal end portion of the housing 31110 such that the distal end portion can move within a passageway defined by the hub 31270. Furthermore, the distal end portion of the hub 31270 can define a curved surface configured to conform to a curved surface of a target tissue, for example, an eye. The housing 31110 includes a first ridge 31114a and a second ridge 31114b configured to be matingly disposed within a groove 31272 defined on an inner surface of the hub 31270. While shown as including two ridges, the housing 31110 can include any number of ridges disposed thereon for example, 3, 4, 5, or even more. Furthermore, the hub 31270 can be formed from a flexible material, for example, rubber, plastics, polymers, or any other flexible material described herein. This can enable the ridges 31114 from sliding out of the groove 31272 into the channel defined by the hub 31270 by application of a force on the housing 31110. In this manner, either the first groove 31114a or the second groove 31114b can be mated with the groove 31272 to adjust the length of the needle 31240.

[0328] For example, as shown in FIG. 92B, in a first configuration the hub 31270 can be disposed on a conjunctiva of an eye, such that the curved surface of the distal end portion of the hub 31270 conformally contacts the curved conjunctiva. In the first configuration, the first ridge 31114a can be disposed in the groove 31272 such that a distal tip of the needle 31240 is not inserted into the eye. A force can be exerted on the housing 31110 to displace the housing 31110 within the channel defined by the hub 31270 while maintaining the curved surface of the hub 31270 in contact with the conjunctiva. This can urge the medical injector 31000 into a second configuration in which the second ridge 31114b is disposed within the groove 31272. The moving of the housing 31110 can also urge the needle 31240 to move within the channel defined by the hub 31270 until a distal tip of the needle 31240 pierces the eye. The distal tip of the needle 31240 can continue travelling into the eye tissue until the second ridge 31114b is disposed in the groove 31272. In some embodiments, the distal tip of the needle 31240 can be disposed within a target region, for example, the SCS in the second configuration. In some embodiments, the distal tip of the needle 31240 can be disposed near but not within the target region, for example, the SCS of the eye. In such embodiments, the user can increase the force on the housing 31110 to insert the distal tip of the needle 31240 further into the eye, for example, by a flexing of the sidewalls of the hub, such that the distal tip of the needle 31240 can be disposed within the target region (e.g., the SCS) of the target tissue.

[0329] In some embodiments, a medical injector can include a hub configured to contact an outer surface of the target tissue and flex or bend to allow a needle included in the medical injector to be inserted into the target tissue. For example, FIG. 93A shows a perspective view of a portion of a medical injector 32000. The medical injector includes a hub 32270, a medicament container 32310 and needle 32240 that can be fluidically coupled to a medicament container included in the medical injector 32000. The hub 32270 is coupled to a distal end portion of the medicament container 32310. The hub 32270 has a hemispherical or a semi-

hemispherical shape and defines a region therewithin. The hub 32270 is configured to be disposed on the distal end portion of the housing 32110 such that the needle 32240 is disposed within the region defined by the hub 32270. A distal end surface of the hub 32240 is configured to contact an outer surface of a target tissue, for example, the conjunctiva of an eye. Furthermore, the hub 32270 can be formed from a flexible material, for example, rubber, plastic, polymers, silicone, or any flexible material described herein or a combination thereof. The hub 32270 is configured to flex or bend, for example, by application of a force on the medicament container 32110. The bending or otherwise flexing can reduce the distance between a distal tip of the needle 32240 and the target tissue, such that the distal tip of the needle 32240 can be disposed within the target tissue.

[0330] For example, FIGS. 93B and 93C show the medical injector 32000 in a first configuration and a second configuration, respectively. In the first configuration, the distal end surface of the hub 32270 is disposed on a target tissue, for example, the conjunctiva of the eye such that a distal tip of the needle 32240 is distal from the outer surface of the target tissue. Said another way, in the first configuration no force is exerted on the hub 32270 such that the hub 32270 is not bent, and the needle 32240 is not inserted into the target tissue. In the second configuration, a force can be applied on the medicament container 32310, or any other portion of the medical injector 32000 such that the hub flexes or otherwise bends reducing the distance between the distal tip of the needle 32240 and the outer surface of the target tissue. The force can be maintained until the distal tip of the needle pierces target tissue and is disposed within a target tissue (e.g., the SCS) of the target tissue (e.g., an eye).

[0331] In some embodiments, a medical injector can include a puncture member included in a medical injector can be configured to sense light to determine the depth of insertion of the puncture member. For example, FIGS. 94A and 94B show a portion of a puncture member 32240 that can be included in a medical injector, for example, the medical injector 100, 1000, 2000, or any other medical injector described herein, in a first configuration and a second configuration, respectively, according to an embodiment. The puncture member 32240 can be configured to communicate light from the target tissue to a light sensor, for example, a photodiode included in the medical injector. The puncture member 32240 can be formed from any suitable optically transparent material, for example, an optical fiber. A distal end of the optical fiber can be beveled or otherwise formed into a sharp tip to pierce a target tissue. Furthermore, the distal tip can be optically transparent such that the puncture member can communicate light from the target tissue to the light sensor. The presence, absence, or otherwise amount of light communicated by the puncture member 32240 to the sensor can be used to determine the insertion depth and thereby, the region of the target tissue in which the distal end of the puncture member 32240 is disposed.

[0332] For example, in the first configuration shown in FIG. 94A, the distal end of the puncture member 32240 can be disposed in the sclera S of an eye. The sclera S is opaque so no light is communicated from the puncture member 32240 to the light sensor. In the second configuration, the distal tip of the puncture member 32240 is inserted deeper into the ocular tissue until at least a portion of the distal tip is disposed within the suprachoroidal space SCS which can be the target region for delivering a medicament. Since the

suprachoroidal space SCS is transparent, light entering the eye and impinging on the retina R also penetrates into the suprachoroidal space SCS. The light can be communicated from the distal tip of the puncture member **32240** to the light sensor included in the medical injector thus confirming that the distal tip of the puncture member **32240** is indeed disposed in the target region of the eye. In some embodiments, the medical injector that includes the puncture member **32240** can alert a user that the distal tip of the puncture member **32240** is disposed within the suprachoroidal space SCS using an audible alert (e.g., a beep, an alarm, etc.), a haptic alert (e.g., vibrations, or minor electric current), or a visible alert (e.g., a light such as, for example, an LED light, or a visual message). Thus, a user can initiate delivery of the medicament through the puncture member **32240** only when the distal tip of the puncture member **32240** is within the suprachoroidal space SCS.

[0333] In some embodiments, a kit that includes a medical injector for delivering a medicament to a target region of a target tissue can include all or parts of the concepts described herein. For example, in some embodiments, a kit can include a medical injector (e.g., the medical injector **10**, **1000**, **2000**, **3000**, **21000**, or any other medical injector described herein), a transfer assembly that can include, for example, an extraction member (e.g., the extraction member **21280**), an injection assist housing (e.g., the injection assembly **2100** or any other injection assembly described herein), a needle adjustment mechanism (e.g., the needle assembly **3200**, or any other needle assembly described herein), a container or vial of a substance, for example a medicament or any other substance described herein, replacement needles and/or hubs, one or more speculums, swabs, wipes, anti-biotic ointments, eye drops, or any other device or apparatus configured to facilitate delivery of the medicament to the target tissue, for example, the eye.

[0334] For example, FIG. 95 shows a speculum **33400** that can be included in a kit that includes a medical injector **33000**, according to an embodiment. The medical injector **33000** can be substantially similar to the medical injector **100**, **1000**, **2000**, **3000**, or any other medical injector described herein. The speculum **33400** can be configured to be placed on an outer surface of the conjunctiva of the eye and open the eye lids of a patient. In this manner, the speculum **33400** can facilitate access to the surface of the eye such that the medical injector can be used to deliver a medicament to a target tissue of the eye, for example, the SCS. The speculum **33400** can include an ergonomic handle, which can be comfortably gripped by a user during use. The speculum **33400** also includes a cavity **33410** configured to receive at least a portion of the medical injector **33000**. In use, a user can disposed the speculum **33400** on the conjunctiva of the eye such that the eyelids are forced open. Furthermore, the cavity **33410** can be located on a target portion of the eye. The user can dispose a distal end portion of the medical injector **33000** into the cavity **33410** and deliver the medicament to a target region (e.g., the SCS) of the eye. In some embodiments, the cavity **33410** can be oriented such that a center line of a delivery passageway of the medical injector **33000** and a surface line tangent of to the target surface of the eye (e.g., the conjunctiva, the sclera, and/or the suprachoroidal space SCS) defines an angle of entry of between about 75 degrees and about 105 degrees, for example, about 90 degrees. Moreover, the cavity **33410** can be configured to prevent lateral movement of the medi-

cal injector such that the centerline of the needle remains substantially normal to the target surface during delivery of the medicament.

[0335] In some embodiments, a speculum can include markings to enable measurement of a size, radius, diameter or otherwise cross-section of an eye. For example, FIG. 96 shows a speculum **34400** that can be included in a kit that includes a medical injector (e.g., the medical injector **100**, **1000**, **2000**, **3000**, or any other medical injector described herein). The speculum **34400** includes two arms. A distal end portion of the each of the arms is configured to disposed on the first and the second eyelid. The distal end portions can be moved apart to open the eyelids and allow access to the surface of the eye. The distal portions also include a plurality of markings or indicia. The markings can be used to measure a size of the eye, for example, a size, radius, diameter, or otherwise, cross section of the eye. Information on the size of the eye can be used to determine, for example, the thickness of individual layers, for example, the sclera and the SCS. In this manner, a user can predict how far a needle has to be penetrated into the eye such that a distal tip of the needle is disposed in a target region (e.g., the SCS) of the eye.

[0336] In some embodiments, a speculum can include mounting features to mount a medical injector. Referring now to FIG. 97, a speculum **35400** includes a set of arms configured to open the eyelids of a patient and provide access to the eye. The speculum **35400** includes a mount **35410** configured to receive mounting member **35114** included in a medical injector **35000**. The medical injector **35000** can be substantially similar to the medical injector **100**, **1000**, **2000**, **3000**, or any other medicament container described herein. The mounting member **35410** can include any suitable mounting features, for example, a magnet, threads, snap-fit mechanism, friction-fit mechanism, or any other suitable mounting mechanism configured to mount the medical injector **35000** via the mounting member **35114**. In some embodiments, the mount **35114** can include a magnet. In such embodiments, the mounting member **35114** can be formed from a magnetic material, for example, a ferrous material, such that mounting member **35114** can be coupled to the mount **35410** via magnetic coupling. In use, the speculum **35400** can be disposed on an eye of a patient. Each arm of the speculum **35400** can be used to open an eyelid of the patient to allow access to the eye. The medical injector **35000** can be mounted on the mount **35410** via the mounting feature **35114**, for example, via magnetic coupling. Mounting the medical injector **35000** can prevent inadvertent movements of the medical injector **34000** during medicament injection thereby minimizing the risk of injury to the eye. Furthermore, the speculum **35400** can reduce the risk of an error by the user by positioning the medical injector **35000** for the user so that the user can focus on delivering the medicament to a target region of the eye instead of correctly positioning the medical injector **35000** on the eye.

[0337] In some embodiments, a speculum can include a single piece speculum. For example, FIG. 98A shows a single piece speculum **36400** configured to be disposed on a surface of an eye and open the eyelids of the patient. The speculum **36400** defines a cavity **36410** configured to receive at least a portion of a medical injector, for example, the medical injector **33000** or any other medical injector described herein. For example, as shown in FIG. 98B, the speculum **36400** can be disposed on the eye such that the

cavity **36410** is disposed over a target location of the eye. At least a portion of the medical injector **33000** is then disposed in the cavity **36410** thereby positioning the medical injector **33000** over the target location of the eye for delivering the medicament to a target region within the target location.

[0338] FIG. 99 shows a schematic flow diagram of a method **500** for delivering a medicament to a target tissue using a medical injector that includes a hub having a convex distal end surface (e.g., the hub **7270**, **8270**, or the hub **9720**), coupled thereto. The medical injector can include any of the medical injectors described herein. The method includes inserting a distal end portion of a needle of a medical injector into a target tissue to define a delivery passageway within the target tissue **502**. The needle can include any suitable puncture member, for example, a microneedle (e.g., a 27 gauge needle, a 30 gauge needle, or even smaller), or any other puncture member described herein. In some embodiments, the target tissue can be ocular tissue including the conjunctiva, the sclera, and the suprachoroidal space. In some embodiments, the inserting is performed such that centerline of the delivery passageway and a surface line tangent to the target surface defines an angle of entry of between about 75 degrees and about 105 degrees, for example, about 90 degrees. In some embodiments, the inserting can be performed such that the centerline of the needle is substantially normal to the target surface. This can, for example, minimize tissue damage and provide the shortest path for a distal tip of the needle to reach a target region of the target tissue (e.g., the SCS). Next, the convex distal end surface of the hub is placed in contact with a target surface of the target tissue to fluidically isolate the delivery passageway **504**. In some embodiments, the placing can include deforming the target surface. For example, the distal end surface of the hub can include a sealing portion configured to contact and define a substantially fluid-tight seal with the target surface, for example, the conjunctiva of the eye (e.g., as defined with respect to the sealing portion **7277** included in the hub **7270**). In such embodiments, the sealing portion can be substantially symmetrical around a centerline of the needle. In some embodiments, the sealing portion can be convex. In some embodiments, only a portion of the sealing portion can be configured to contact the target surface of the target tissue to form the substantially fluid-tight seal. For example, a circular band of the sealing portion can contact the target surface and form the substantially fluid tight seal surrounding the centerline of the needle.

[0339] The method **500** further includes conveying, after the placing, a substance into the target tissue via the needle **506**. In some embodiments, the substance can include a medicament such as, for example, a VEGF, a VEGF inhibitor, or a combination thereof. The substance can be disposed within an internal volume of a medicament container included in the medical injector. An actuation rod can be included in the medical injector, which can be configured to be engaged by a user to fluidically communicate the substance from the medicament container to the target tissue via the needle. The medicament container and the actuation rod can be substantially similar to the medicament container and/or the actuation rod included in the system **100**, **1000**, **2000**, **3000**, or any other system or apparatus described herein. In some embodiments, the target tissue can be an eye, and the target surface can be a conjunctiva of the eye. In such embodiments, the delivery passageway can extend through a sclera of the eye such that the conveying includes

conveying the substance into at least one of a suprachoroidal space or a lower portion of the sclera.

[0340] In some embodiments, the method **500** can further include adjusting, before the conveying, a length of the needle extending from the distal end surface of the hub. For example, the medical injector can include a needle assembly, for example, the needle assembly **3200** or any other needle assembly described herein. The needle assembly can be used to adjust the length of the needle extending from the distal end surface of the hub until a distal tip of the needle is disposed within a target region, for example, the SCS of the eye. The substance, for example, as medicament as described herein, can then be conveyed to the target region of the eye.

[0341] The embodiments described herein can be formed or constructed of one or more biocompatible materials. Examples of suitable biocompatible materials include metals, glasses, ceramics, or polymers. Examples of suitable metals include pharmaceutical grade stainless steel, gold, titanium, nickel, iron, platinum, tin, chromium, copper, and alloys thereof. The polymer may be biodegradable or non-biodegradable. Examples of suitable biodegradable polymers include polylactides, polyglycolides, polylactide-coglycolides (PLGA), polyanhydrides, polyorthoesters, polyetheresters, polycaprolactones, polyesteramides, poly (butyric acid), poly(valeric acid), polyurethanes and copolymers and blends thereof. Examples of non-biodegradable polymers include nylons, polyesters, polycarbonates, polyacrylates, polymers of ethylene-vinyl acetates and other acyl substituted cellulose acetates, non-degradable polyurethanes, polystyrenes, polyvinyl chloride, polyvinyl fluoride, poly(vinyl imidazole), chlorosulphonate polyolefins, polyethylene oxide, blends and copolymers thereof.

[0342] The microneedles described herein can be fabricated by a variety of methods. For example, in some embodiments, the hollow microneedle is fabricated using a laser or similar optical energy source. In one example, a microcannula may be cut using a laser to represent the desired microneedle length. The laser may also be used to shape single or multiple tip openings. Single or multiple cuts may be performed on a single microcannula to shape the desired microneedle structure. In one example, the microcannula may be made of metal such as stainless steel and cut using a laser with a wavelength in the infrared region of the light spectrum (0.7-300 μm). Further refinement may be performed using metal electropolishing techniques familiar to those in the field. In another embodiment, the microneedle length and optional bevel is formed by a physical grinding process, which for example may include grinding a metal cannula against a moving abrasive surface. The fabrication process may further include precision grinding, micro-bead jet blasting and ultrasonic cleaning to form the shape of the desired precise tip of the microneedle.

[0343] A wide range of ocular diseases and disorders may be treated by the methods and devices described herein. Non-limiting examples of ocular diseases include uveitis, glaucoma, diabetic macular edema or retinopathy, macular degeneration, retinoblastoma, and genetic diseases. The methods described herein are particularly useful for the local delivery of drugs that need to be administered to the posterior region of the eye, for example the retinochoroidal tissue, macula, and optic nerve in the posterior segment of the eye. In one embodiment, the delivery methods and devices described herein may be used in gene-based therapy

applications. For example, the methods may administer a fluid drug formulation into the suprachoroidal space to deliver select DNA, RNA, or oligonucleotides to targeted ocular tissues.

[0344] The microneedles can be used to target delivery to specific tissues or regions within the eye or in neighboring tissue. In various embodiments, the methods may be designed for drug delivery specifically to the sclera, the choroid, the Bruch's membrane, the retinal pigment epithelium, the subretinal space, the retina, the macula, the optic disk, the optic nerve, the ciliary body, the trabecular meshwork, the aqueous humor, the vitreous humor, and other ocular tissue or neighboring tissue in need of treatment.

[0345] A wide range of drugs may be formulated for delivery to ocular tissues using the present systems and devices described herein. Moreover, any of the delivery devices and/or methods described herein can involve, include and/or contain any of the drugs described herein. For example, in some embodiments, the medicament containment chamber **1310**, **2310**, **3310**, or any other medicament containment chamber can contain any of the drugs and/or formulations described herein. As used herein, the term "drug" refers to any prophylactic, therapeutic, or diagnostic agent (e.g., a contrast agent). The drug may be selected from suitable proteins, peptides and fragments thereof, which can be naturally occurring, synthesized or recombinantly produced. Representative examples of types of drugs for delivery to ocular tissues include antibodies, anti-viral agents, chemotherapeutic agents (e.g., topoisomerase inhibitors), analgesics, anesthetics, aptamers, antihistamines, anti-inflammatory agents, and anti-neoplastic agents. In one embodiment, the drug is triamcinolone or triamcinolone acetonide.

[0346] The term "antibody" is intended to refer broadly to any immunologic binding agent such as IgG, IgM, IgA, IgD and IgE. An antibody can be monoclonal or polyclonal, and in one embodiment, is a humanized antibody. The term "antibody" is also used to refer to any antibody-like molecule that has an antigen binding region, and includes antibody fragments such as Fab', Fab, F(ab')₂, single domain antibodies (DABs), Fv, scFv (single chain Fv), and engineering multivalent antibody fragments such as dibodies, tribodies and multibodies. The techniques for preparing and using various antibody-based constructs and fragments are well known in the art (see, e.g., *Antibodies: A Laboratory Manual*, Cold Spring Harbor Laboratory, 1988; incorporated herein by reference).

[0347] Non-limiting examples of specific drugs and classes of drugs include β -adrenoceptor antagonists (e.g., carteolol, cetamolol, betaxolol, levobunolol, metipranolol, timolol), miotics (e.g., pilocarpine, carbachol, physostigmine), sympathomimetics (e.g., adrenaline, dipivefrine), carbonic anhydrase inhibitors (e.g., acetazolamide, dorzolamide), topoisomerase inhibitors (e.g., topotecan, irinotecan, camptothecin, lamellarin D, etoposide, teniposide, doxorubicin, mitoxantrone, amsacrine), prostaglandins, anti-microbial compounds, including anti-bacterials and anti-fungals (e.g., chloramphenicol, chlortetracycline, ciprofloxacin, framycetin, fusidic acid, gentamicin, neomycin, norfloxacin, ofloxacin, polymyxin, propamidine, tetracycline, tobramycin, quinolones), anti-viral compounds (e.g., acyclovir, cidofovir, idoxuridine, interferons), aldose reductase inhibitors, anti-inflammatory and/or anti-allergy compounds (e.g., steroidal compounds such as betamethasone,

clobetasone, dexamethasone, fluorometholone, hydrocortisone, prednisolone and non-steroidal compounds such as antazoline, bromfenac, diclofenac, indomethacin, lodoxamide, saprofen, sodium cromoglycate), artificial tear/dry eye therapies, local anesthetics (e.g., amethocaine, lignocaine, oxbuprocaine, proxymetacaine), cyclosporine, diclofenac, urogastrone and growth factors such as epidermal growth factor, mydriatics and cycloplegics, mitomycin C, and collagenase inhibitors and treatments of age-related macular degeneration such as pegaptanib sodium, ranibizumab, aflibercept and bevacizumab.

[0348] In one embodiment, the drug is an integrin antagonist, a selectin antagonist, an adhesion molecule antagonist (e.g., intercellular adhesion molecule (ICAM)-1, ICAM-2, ICAM-3, platelet endothelial adhesion molecule (PCAM), vascular cell adhesion molecule (VCAM)), a leukocyte adhesion-inducing cytokine or growth factor antagonist (e.g., tumor necrosis factor- α (TNF- α), interleukin-1 β (IL-1 β), monocyte chemoattractant protein-1 (MCP-1), or a vascular endothelial growth factor (VEGF)). In some embodiments, a vascular endothelial growth factor (VEGF) inhibitor is administered with one of the microneedles described herein. In some embodiments, two drugs are delivered by the methods described herein. The compounds may be administered in one formulation, or administered serially, in two separate formulations. For example, both a VEGF inhibitor and VEGF are provided. In some embodiments, the VEGF inhibitor is an antibody, for example a humanized monoclonal antibody. In further embodiments, the VEGF antibody is bevacizumab. In another embodiment, the VEGF inhibitor is ranibizumab, aflibercept or pegaptanib. In still other embodiments, the devices and methods described herein can be used to deliver one or more of the following VEGF antagonists: AL8326, 2C3 antibody, AT001 antibody, HyBEV, bevacizumab (Avastin), ANG3070, APX003 antibody, APX004 antibody, ponatinib (AP24534), BDM-E, VGX100 antibody (VGX100 CIRCADIANT), VGX200 (c-fos induced growth factor monoclonal antibody), VGX300, COSMIX, DLX903/1008 antibody, ENMD2076, Sutent (sunitinib malate), INDUS815C, R84 antibody, KDO19, NM3, allogenic mesenchymal precursor cells combined with an anti-VEGF agent or antibody, MGCD265, MG516, VEGF-Receptor kinase inhibitors, MP0260, NT503, anti-DLL4/VEGF bispecific antibody, PAN90806, Palomid 529, BD0801 antibody, XV615, lucitanib (AL3810, E3810), AMG706 (motesanib diphosphate), AAV2-sFLT01, soluble Flt1 receptor, Cediranib (Recentin), AV-951 (Tivozanib, KRN-951), Stivarga (regorafenib), Volasertib (BI6727), CEP11981, KH903, Lenvatinib (E7080), terameprocol (EM1421), ranibizumab (Lucentis), Votrient (pazopanib hydrochloride), PF00337210, PRS050, SP01 (curcumin), Carboxyamidotriazole orotate, hydroxychloroquine, linifanib (ABT869, RG3635), Iluvien (fluocinolone acetonide), ALG1001, AGN150998, DARPIN MP0112, AMG386, ponatinib (AP24534), AVA101, Vargatef (nintedanib), BMS690514, KH902, golvatinib (E7050), Afinitor (everolimus), Dovitinib lactate (TKI258, CHIR258), ORA101, ORA102, Axitinib (Inlyta, AG013736), Plitidepsin (Aplidin), Lenvatinib mesylate, PTC299, aflibercept (Zaltrap, Eylea), pegaptanib sodium (Macugen, LI900015), Visudyne (verteporfin), bucillamine (Rimatil, Lamin, Brimani, Lamit, Boomiq), R3 antibody, AT001/r84 antibody, troponin (BLS0597), EG3306, vatalanib (PTK787), Bmab100, GSK2136773, Anti-VEGFR

Alterase, Avila, CEP7055, CLT009, ESBA903, HuMax-VEGF antibody, GW654652, HMPL010, GEM220, HYB676, JNJ17029259, TAK593, XtendVEGF antibody, Nova21012, Nova21013, CP564959, Smart Anti-VEGF antibody, AG028262, AG13958, CVX241, SU14813, PRS055, PG501, PG545, PTI101, TG100948, ICS283, XL647, enzastaurin hydrochloride (LY317615), BC194, quinolines, COT601M06.1, COT604M06.2, MabionVEGF, SIR-Spheres coupled to anti-VEGF or VEGF-R antibody, Apatinib (YN968D1), and AL3818. In addition, delivery of a VEGF inhibitor or VEGF antagonist using the microneedle devices and methods disclosed herein may be combined with one or more agents listed herein or with other agents known in the art.

[0349] In one embodiment, delivery of a VEGF antagonist to the suprachoroidal space of the eye using the devices and methods disclosed herein is used to treat, prevent and/or ameliorate a disease or disorder selected from leukemia, relapsed/refractory leukemia, acute lymphoblastic leukemia, Acute myelogenous leukemia, relapsed or refractory acute myeloid leukemia, atopic dermatitis, recurrent or metastatic carcinoma of the urothelium, advanced urothelial carcinoma, blood disorders, myelofibrosis, brain tumor, glioblastoma, glioma, meningioma, cancer, carcinomatous meningitis (neoplastic meningitis), choroidal neovascularization (CNV), subfoveal choroidal neovascularization, chronic lymphocytic leukemia, chronic myelogenous leukemia, refractory chronic myelogenous leukemia, colon cancer, colorectal cancer, degenerative nerve diseases, Neurodegenerative diseases, diabetic macular edema, visual Impairment due to diabetic macular edema, diabetic retinopathy, dry eye syndrome (inflammation and corneal tissue damage of dry eye), endometrial cancer, eye diseases, ocular diseases, ocular neovascularization, eye cancer, Neurofibromatosis Type II, head and neck cancer, hematological malignancies, Kaposi's Sarcoma, Hepatocellular Carcinoma, Lung cancer, macular degeneration, age related macular degeneration, exudative age-related macular degeneration, neovascular (wet) age-related macular degeneration (AMD)), subfoveal Neovascular Age-Related macular degeneration, macular edema, macular edema associated with Branch Retinal Vein Occlusion, macular edema following retinal vein occlusion, macular edema with Retinal Vein Occlusion (RVO), multiple myeloma, relapsed or refractory multiple myeloma, multiple sclerosis, myopia, pathological myopia, neuroendocrine tumor, carcinoid tumor, neuroendocrine tumor, non-Hodgkin's Lymphoma, Diffuse Large B-Cell Lymphoma, Non-Small-Cell Lung cancer, Non-Squamous Non-Small-Cell Lung cancer, Non-small-cell-lung Adenocarcinoma, Squamous Non-Small-Cell Lung cancer, corneal graft rejection, osteoarthritis, recurrent symptomatic malignant ascites, peripheral T-cell lymphoma, androgen Independent Psoriasis, pulmonary Fibrosis, Idiopathic Pulmonary Fibrosis, respiratory diseases, retinal detachment, retinal disorders, retinitis pigmentosa, retinal vein occlusion, branch retinal vein occlusion, central retinal vein occlusion, rheumatoid arthritis, sarcoma, alveolar soft part sarcoma, soft tissue sarcoma, scleroderma/systemic sclerosis, solid tumors, refractory germ cell tumors, thyroid cancer, differentiated or medullary thyroid cancer, and West Syndrome (Infantile Spasm).

[0350] In certain embodiments, the drug delivered to the suprachoroidal space using the devices and methods disclosed herein is rapamycin (Sirolimus, Rapamune). In one

embodiment, the devices (e.g., microneedle devices) and methods disclosed herein are used in conjunction with rapamycin to treat, prevent and/or ameliorate a wide range of diseases or disorders including, but not limited to: abdominal neoplasms, acquired immunodeficiency syndrome, acute coronary syndrome, acute lymphoblastic leukemia, acute myelocytic leukemia, acute non-lymphoblastic leukemia, adenocarcinoma, adenoma, adenomyoepithelioma, adnexal diseases, anaplastic astrocytoma, anaplastic large cell lymphoma, anaplastic plasmacytoma, anemia, angina pectoris, angioimmunoblastic lymphadenopathy with dysproteinemia, angiomyolipoma, arterial occlusive diseases, arteriosclerosis, astrocytoma, atherosclerosis, autoimmune diseases, B-cell lymphomas, blood coagulation disorders, blood protein disorders, bone cancer, bone marrow diseases, brain diseases, brain neoplasms, breast neoplasms, bronchial neoplasms, carcinoid syndrome, carcinoid Tumor, carcinoma, squamous cell carcinoma, central nervous system diseases, central nervous system neoplasms, choroid diseases, choroid plexus neoplasms, choroidal neovascularization, choroiditis, chronic lymphocytic leukemia, chronic myeloid leukemia, chronic myelomonocytic leukemia, chronic myeloproliferative disorders, chronic neutrophilic leukemia, clear cell renal cell carcinoma, colonic diseases, colonic neoplasms, colorectal neoplasms, coronary artery disease, coronary disease, coronary Occlusion, coronary restenosis, coronary stenosis, coronary thrombosis, cutaneous T-cell lymphoma, diabetes mellitus, digestive system neoplasms, dry eye syndromes, ear diseases, edema, endocrine gland neoplasms, endocrine system diseases, endometrial neoplasms, Endometrial stromal tumors, Ewing's sarcoma, exanthema, eye neoplasms, fibrosis, follicular lymphoma, gastrointestinal diseases, gastrointestinal neoplasms, genital neoplasms, glioblastoma, glioma, gliosarcoma, graft vs host disease, hematologic diseases, hematologic neoplasms, hemorrhagic disorders, hemostatic disorders, Hodgkin disease, Hodgkin lymphoma, homologous wasting disease, immunoblastic lymphadenopathy, immunologic deficiency syndromes, immunoproliferative disorders, infarction, inflammation, intestinal diseases, intestinal neoplasms, ischemia, kidney cancer, kidney diseases, kidney neoplasms, leukemia, B-Cell, leukemia, lymphoid, liver cancer, liver diseases, lung diseases, lymphatic diseases, lymphoblastic lymphoma, lymphoma, macular degeneration, macular edema, melanoma, mouth neoplasms, multiple myeloma, myelodysplastic syndromes, myelofibrosis, myeloproliferative disorders, neuroectodermal tumors, neuroendocrine tumors, neuroepithelioma, neurofibroma, renal cancer, respiratory tract diseases, retinal degeneration, retinal diseases, retinal neoplasms, retinoblastoma, rhabdomyosarcoma, thoracic neoplasms, uveitis, vascular diseases, Waldenstrom Macroglobulinemia, and wet macular degeneration. In addition, delivery of rapamycin using the microneedle devices and methods disclosed herein may be combined with one or more agents listed herein or with other agents known in the art.

[0351] In one embodiment, the drug delivered to ocular tissue, for example the sclera or suprachoroidal space, using the microneedle devices and methods disclosed herein reduces, inhibits, prevents and/or ameliorates inflammation. Examples of drugs that reduce, inhibit, prevent and/or ameliorate inflammation include (but are not limited to): 19AV Agonists, 19GJ agonists, 2MD Analogs, 4SC101, 4SC102, 57-57, 5-HT2 Receptor Antagonist, 64G12,

A804598, A967079, AAD2004, AB1010, AB224050, abatacept, Abegrin, Abevac, AbGn134, AbGn168, Abki, ABN912, ABR215062, ABR224050, Abrammune, Abreva, ABS15, ABS4, ABS6, ABT122, ABT325, ABT494, ABT874, ABT963, ABXIL8, ABXRB2, AC430, Accenetra, Aceadam, ACE772, Acebid, Acebloc, aceclofenac, acetaminophen, chlorzoxazone, serrapeptase, tizanidine hydrochloride, betadex, Aceclogesic Plus, Aceclon, Acecloren, Aceclorism, accerona, Aceffein, acemetacin, Acenac, Acen-terine, Acetal-SP, ibuprofen, Acetyl-G, acetylsalicylate dl-lysine, acetylsalicylic acid, Acicot, Acifine, Acik, Aclocen, Acloflam-P, Aclofmore, Aclon, A-CQ, ACS15, actarit, Actemra, Acthelea liofilizado, Actifast, Actimab-B, Actiquim, Actirin, Actis PLUS, activated leukocyte cell adhesion molecule antibody, Acular X, AD452, adalimumab, ADAMTS5 Inhibitor, ADC1001, Adco-Diclofenac, Adco-Indomethacin, Adco-Meloxicam, Adco-Naproxen, Adco-Piroxicam, Adcort, Adco-Sulindac, adenosine triphosphate disodium, AdenosineA2a Receptor Agonist, Adimod, Adinos, Adiact, Adiodol, Adipoplus, adipose derived stem and/or regenerative cells, Adizen, Adpep, Advacan, Advagraf, Advcl, Adwiflam, AEB071, Aental, Afenac, Affen Plus, Afiancen, Afinitor, Aflamin, Aflazacort, Aflogen, Afloxan, AFM15, AFM16, AFM17, AFM23, Afpred-Dexa, AFX200, AG011, Agafen, aganirsan, AGI1096, Agidex, AGS010, Agudol, A-Hydrocort, AIK1, AIN457, Airtal, AIT110, AJM300, ajulemic acid, AK106, AL-24-2A1, AL4-1A1, Ala Cort, Alanz, Albumin immune-globulin, alclometasone dipropionate, ALD518, aldesleukin, Aldoderma, alefacept, alemtuzumab, Alequel, Alergolon, Alergosone, Aletraxon, Alfenac, Algason, Algin vek coat, Algioflex, Algirex, Algin Plus, alicaforsen sodium, Alin, Alinia, Aliviadol, Aliviosin, alkaline phosphatase, ALKS6931, allantoin, Allbupen, Allmol, Allochrysin, allogeneic endothelial cells, allogeneic mesenchymal precursor cells, allogeneic mesenchymal stem cells, alminoprofen, alpha 1 antitrypsin, Alpha 7 nicotinic agonists, alpha amylase, alpha chymotrypsin, alpha fetoprotein, alpha linolenic acid, Alpha-1-antitrypsin, Alpha2Beta1 Integrin Inhibitors, Alphacort, Alphafen, alpha-hexidine, alpha-trypsin, Alphinern, Alpinamed mobility omega 3, Alpoxen, AL-Rev1, Alterase, ALX0061, ALX0761, ALXN1007, ALXN1102, AM3840, AM3876, AMAB, AMAP102, Amason, Ambene, AmbezimG, amcinonide, AME133v, Amecin, Ameloteks, A-Methapred, Amevive, AMG108, AMG139, AMG162, AMG181, AMG191, AMG220, AMG623, AMG674, AMG714, AMG719, AMG729, AMG827, Amidol, amifampridine phosphate, Amifenac, Amimethacin, amiprilose hydrochloride, Amiprofen, Ammophos, Amoflam, AMP110, Ampikyy, Ampion, ampiroxicam, amtolmetin guacil, AMX256, AN6415, ANA004, ANA506, Anabu, Anacen, Anaflam, Anaflex ACI, Anaida, anakinra, Analgen Arthritis, Anapan, Anaprox, Anavan, Anax, Anco, andrographis, Aneol, Anergix, Anervax.RA, Anflene, ANG797, Anilixin, Anmerushin, Annexin 1 peptides, annexin A5, Anodyne, Ansaïd, Anspirin, Antarene, Anti BST2 antibody, Anti C5a MAb, Anti ILT7 antibody, Anti VLA1 antibody, Anti-alpha11 antibody, Anti-CD4 802-2, Anti-CD86 Monoclonal Antibody, Anti-chemokine, Anti-DC-SIGN, Anti-HMGB-1 MAb, Anti-IL-18 MAb, Anti-IL-1R MAb, Anti-IL-1R MAb, Anti-IL23 BRISTOL, Anti-inflammatory Peptides, Anti-interleukin 1Beta antibody, Anti-LIGHT antibody, Anti-LIGHT antibody, Anti-MIF Antibody, Anti-MIF Antibody, Anti-miR181a, antioxidant inflammation modulators,

Antiplamine, AntiRAGE MAb, antithrombin III, Anti-TIRC-7 MAb, Anusol-HC, Anyfen, AP105, AP1089, AP1189, AP401, AP501, apazone, APD334, Apentac, APG103, Apidone, apilimod mesylate, Apatac, Apitoxin, Apizel, APN Inhibitor, apo-Azathioprine, Apo-Dexamethasone, ApoE mimetics, ApoFasL, apo-Indomethacin, apomefenamic, apo-methotrexate, apo-nabumetone, Apo-Napro-NA, apo-Naproxen, aponidin, apo-Phenylbutazone, apo-Piroxicam, apo-Sulin, Apo-Tenoxicam, apo-Tiaprofenic, Apranax, apremilast, apricoxib, Aprofen, Aproses, Aproxen, APX001 antibody, APX007 antibody, APY0201, AqvoDex, AQX108, AQX1125, AQX131135, AQX140, AQX150, AQX200, AQX356, AQXMN100, AQXMN106, ARA290, Arava, Arcalyst, Arcoxia, Arechin, Arflur, ARG098, ARG301, arginine aescin, arginine deiminase (pegylated), ARGX109 antibody, ARGX110, Arheuma, Aristocort, Aristospan, Ark-AP, ARN4026, Arofen, Aroff EZ, Arolef, Arotal, Arpibru, Arpimune, Arpu Shuangxin, ARQ101, Arrestin SP, Arroxx, ARRY162, ARRY371797, ARRY614, ARRY872, ART621, Artamin, Arthfree, Artho Tech, Arthrexin, Arthrispray, Arthrotec, Arthrovas, Artifit, Artigo, Artin, Artinor, Artisid, Artoflex, Artren Hipergel, Artridol, Artrilase, Artrocaptin, Artrodiet, Artrofen, Artropan, Artrosil, Artrosilene, Artrotin, Artrox, Artyflam, Arzerra, AS604850, AS605858, Asacol, ASA-Grindeks, Asazipam, Aseclo, ASF1096, ASF1096, ASK8007, ASKP1240, ASLAN003, Asmo ID, Asonep, ASP015K, ASP2408, ASP2409, Aspagin, Aspeol, Aspicam, Aspirimex, aspirin, AST120, astaxanthin, AstroCort, Aszes, AT002 antibody, AT007, AT008 antibody, AT008 antibody, AT010, AT1001, atacicept, Ataspin, Atepadene, Atgam, ATG-Fresenius, Athrofen, ATI003, atiprimod, ATL1222, ATN103, ATN192, ATR107, Atri, Atrmin, Atrosab antibody, ATX3105, AU801, auranofin, Aurobin, Auropan, Aurothio, aurotioprol, autologous adipose derived regenerative cells, Autonec, Avandia, AVE9897, AVE9940, Avelox, Avent, AVI3378, Avloquin, AVP13546, AVP13748, AVP28225, AVX002, Axccl Diclofenac, Axccl Papain, Axen, AZ17, AZ175, Azacortid, AZA-DR, Azafrine, Azamun, Azanin, Azap, Azapin, Azapren, Azaprin, Azaram, Azasan, azathioprine, AZD0275, AZD0902, AZD2315, AZD5672, AZD6703, AZD7140, AZD8309, AZD8566, AZD9056, Azet, Azintrel, azithromycin, Az-od, Azofit, Azolid, Azoran, Azulene, Azulfidine, Azulfine, B1 antagonists, Baclonet, BAF312, BAFF Inhibitor, Bages, Baily S.P., Baleston, Balsolone, baminercept alfa, bardoxolone methyl, baricitinib, Barotase, Basecam, basiliximab, Baxmune, Baxo, BAY869766, BB2827, BCX34, BCX4208, Becfine, Beclate-C, Beclate-N, Beclolab Q, beclomethasone dipropionate, Beclorhin, Becmet-CG, Begita, Begti, belatacept, belimumab, Belosalic, Bemetsen, Ben, Benevat, Benexam, Benflogin, Benisan, Benlysta, Benlysta, benorilate, Benoson, benoxaprofen, Bentol, benzydamine hydrochloride, Benzymine, Beofenac, Berafen, Berinert, Berlofen, Bertanel, Bestamine, Bestofen, Beta Nicip, Betacort, Betacorten G, Betafoam, beta-glucan, Betalar, Beta-M, Betamed, Betamesol, betamethasone, betamethasone dipropionate, betamethasone sodium, betamethasone sodium phosphate, betamethasone valerate, Betane, Betanex, Betapanthen, Betapar, Betapred, Betason, Betasonate, Betasone, Betatrinta, Betaval, Betazon, Betazone, Betsil, Betecort, Betnesol, Betnovate, Bextra, BFPC13, BFPC18, BFPC21, BFPT6864, BG12, BG9924, BI695500, BI695501, BIA12, Big-Joint-D, BIIB023 antibody, Bi-ksikam, Bingo, BioBee,

Bio-Cartilage, Bio-C-Sinkki, Biodexone, Biofenac, Bioreucam, Biosone, Biosporin, BIRB796, Bitnoval, Bitvio, Bivigam, BKT140, BKTP46, BL2030, BL3030, BL4020, BL6040, BL7060, BLI1300, blisibimod, Blokium B12, Blokium Gestic, Blokium, BMS066, BMS345541, BMS470539, BMS561392, BMS566419, BMS582949, BMS587101, BMS817399, BMS936557, BMS945429, BMS-A, BN006, BN007, BNP166, Bonacort, Bonas, bone marrow stromal cell antigen 2 antibody, Bonflex, Bonifen, Boomiq, Borbit, Bosong, BR02001, BR3-FC, Bradykinin B1 Receptor Antagonist, Bredinin, Brexecam, Brexin, Brexodin, briakinumab, Brimani, briobacept, Bristaflam, Britten, Broben, brodalumab, Broen-C, bromelains, Bromelin, Bronax, Bropain, Brosiral, Bruace, Brufadol, Brufen, Brugel, Brukil, Brusil, BT061, BTI9, BTK kinase inhibitors, BTT1023 antibody, BTT1507, bucillamine, Bucillate, Buco Reigis, bucolome, Budenofalk, budesonide, Budex, Bufect, Bufencon, Bukwang Ketoprofen, Bunide, Bunofen, Busilvex, busulfan, Busulfex, Busulipo, Butartrol, Butarut B12, Butasona, Butazolidin, Butesone, Butidiona, BVX10, BXL628, BYM338, B-Zone, C1 esterase inhibitor, C243, c4462, c5997, C5aQb, c7198, c9101, C9709, c9787, CAB101, cadherin 11 antibody, caerulomycin A, CAL263, Calcort, Calmatel, CAM3001, Camelid Antibodies, Camlox, Camola, Campath, Camrox, Camtenam, canakinumab, *candida albicans* antigen, Candin, cannabidiol, CAP1.1, CAP1.2, CAP2.1, CAP2.2, CAP3.1, CAP3.2, Careram, Carimune, Cariodent, Cartifix, CartiJoint, Cartilago, Cartisafe-DN, Cartishine, Cartivit, Cartril-S, Carudol, CaspaCIDE, CaspaCIDE, Casyn, CAT1004, CAT1902, CAT2200, Cataflam, Cathepsin S inhibitor, Catlep, CB0114, CB2 agonist, CC0478765, CC10004, CC10015, CC1088, CC11050, CC13097, CC15965, CC16057, CC220, CC292, CC401, CC5048, CC509, CC7085, CC930, CCR1 Antagonist, CCR6 Inhibitor, CCR7 Antagonist, CCRL2 antagonist, CCX025, CCX354, CCX634, CD Diclofenac, CD102, CD103 Antibody, CD103 Antibody, CD137 antibody, CD16 antibody, CD18 antibody, CD19 antibody, CD1d Antibody, CD20 antibody, CD200Fc, CD209 antibody, CD24, CD3 antibody, CD30 antibody, CD32A antibody, CD32B antibody, CD4 antibody, CD40 ligand, CD44 antibody, CD64 antibody, CDC839, CDC998, CDIM4, CDIM9, CDK9-Inhibitor, CDP146, CDP323, CDP484, CDP6038, CDP870, CDX1135, CDX301, CE224535, Ceanel, Cebedex, Cebutid, Ceclonac, Ceex, CEL2000, Celact, Celbexx, Celcox, Celebiox, Celebrex, Celebrin, Celecox, celecoxib, Celedol, Celestone, Celevex, Cellex, CELG4, Cell adhesion molecule antagonists, CellCept, Cellmune, Celosti, Celoxib, Celprot, Celudex, cenicriviroc mesylate, cenplacel-1, CEP11004, CEP37247, CEP37248, Cephyr, Cefprofen, Certican, certolizumab pegol, Cetofenid, Cetoprofeno, cetylpyridinium chloride, CF101, CF402, CF502, CG57008, CGEN15001, CGEN15021, CGEN15051, CGEN15091, CGEN25017, CGEN25068, CGEN40, CGEN54, CGEN768, CGEN855, CGI1746, CGI560, CGI676, Cgtx-Peptides, CH1504, CH4051, CH4446, chaperonin 10, chemokine C-C motif ligand 2, chemokine C-C motif ligand 2 antibody, chemokine C-C motif ligand 5 antibody, chemokine C-C motif receptor 2 antibody, chemokine C-C motif receptor 4 antibody, chemokine C-X-C motif ligand 10 antibody, chemokine C-X-C motif ligand 12 aptamer, Chemotaxis Inhibitor, Chillmetacin, chitinase a-like 1, Chlocodemin, Chloquin, chlorhexidine gluconate, chloroquine phosphate, choline magnesium trisilicilate, chondroitin sulfate, Chon-

droscart, CHR3620, CHR4432, CHR5154, Chrysalin, Chuanxinlian, Chymapra, Chymotase, chymotrypsin, Chytmutrip, CI202, CI302, Cicloderma-C, Ciclopren, Cicporal, Cilamin, Cimzia, cinchophen, cinmetacin, cinnoxicam, Cinoderm, Cinolone-S, Cinryze, Cipcorlin, cipemastat, Cipol-N, Cipridanol, Cipzen, Citax F, Citogan, Citoken T, Civamide, CJ042794, CJ14877, c-Kit monoclonal antibody, cladribine, Clafen, Clanza, Claversal, clazakizumab, Clearoid, Clease, Clevegen, Clevian, Clidol, Clindac, Clinoril, Cliptol, Clobenate, Clobequad, clobetasol butyrate, clobetasol propionate, Clodol, clofarabine, Clofen, Clofenal LP, Clolar, Clonac, Clongamma, clonixin lysine, Clotasoc, Clovacort, Clovana, Cloxin, CLT001, CLT008, C-MAF Inhibitor, CMPX1023, Cnac, CNDO201, CNI1493, CNT0136, CNT0148, CNT01959, Cobefen, CoBenCoDerm, Cobix, Cofenac, Cofenac, COG241, COL179, colchicine, *Colchicum* Dispert, Colchimax, Colcibra, Coledes A, Colesol, Colifoam, Colirest, collagen, type V, Comcort, complement component (3b/4b) receptor 1, Complement Component C1s Inhibitors, complement component C3, complement factor 5a receptor antibody, complement factor 5a receptor antibody, complement factor D antibody, Condrosulf, Condrotec, Condrothin, conestat alfa, connective tissue growth factor antibody, Coolpan, Copaxone, Copiron, Cordeffa, Corhydron, Cort S, Cortan, Cortate, Cort-Dome, Cortecetine, Cortef, Corteroid, Corticap, Corticas, Cortic-DS, corticotropin, Cortiderm, Cortidex, Cortiflam, Cortinet M, Cortinil, Cortipyren B, Cortiran, Cortis, Cortisolu, cortisone acetate, Cortival, Cortone acetate, Cortopin, Cortoral, Cortril, Cortypiren, Cosamine, Cosone, cosyntropin, COT Kinase Inhibitor, Cotilam, Cotrisone, Cotson, Covox, Cox B, COX-2/5-LO Inhibitors, Coxeton, Coxflam, Coxicam, Coxitor, Coxtral, Coxypar, CP195543, CP412245, CP424174, CP461, CP629933, CP690550, CP751871, CPSI2364, C-quin, CR039, CR074, CR106, CRA102, CRAC channel inhibitor, CRACM Ion Channel Inhibitor, Cratisone, CRB15, CRC4273, CRC4342, C-reactive protein 2-methoxyethyl phosphorothioate oligonucleotide, CreaVax-RA, CRH modulators, critic-aid, Crocam, Crohns-vax, Cromoglycic acid, cromolyn sodium, Cronocortoid, Cronodicasone, CRTX803, CRx119, CRx139, CRx150, CS502, CS670, CS706, CSF1R Kinase Inhibitors, CSL324, CSL718, CSL742, CT112, CT1501R, CT200, CT2008, CT2009, CT3, CT335, CT340, CT5357, CT637, CTP05, CTP10, CT-P13, CTP17, Cuprenil, Cuprimine, Cuprindo, Cupripen, Curaquin, Cutfen, CWF0808, CWP271, CX1020, CX1030, CX1040, CX5011, Cx611, Cx621, Cx911, CXC chemokine receptor 4 antibody, CXCL13 antibodies, CXCR3 antagonists, CXCR4 antagonist, Cyathus 1104 B, Cyclo-2, Cyclocort, cyclooxygenase-2 inhibitor, cyclophosphamide, Cyclorine, Cyclosporin A Prodrug, Cyclosporin analogue A, cyclosporine, Cyrevia, Cyrin CLARIS, CYT007TNFQb, CYT013IL1bQb, CYT015IL17Qb, CYT020TNFQb, CYT107, CYT387, CYT99007, cytokine inhibitors, Cytopan, Cytoleg, CZC24832, D1927, D9421C, daclizumab, danazol, Danilase, Dantes, Danzen, dapsone, Dase-D, Daypro, Daypro Alta, Dayrun, Dazen, DB295, DBTP2, D-Cort, DD1, DD3, DE096, DE098, Debio0406, Debio0512, Debio0615, Debio0618, Debio1036, Decaderm, Decadrone, Decadron, Decadronal, Decalon, Decan, Decason, Decdan, Decilone, Declophen, Decopen, Decorex, Decorten, Dedema, Dedron, Deexa, Defcort, De-flam, Deflamat, Deflan, Deflanil, Deflaren, Deflaz, deflazacort, Defnac, Defnalone, Defnil, Defosalic, Defsure, Defza,

Dehydrocortison, Dekort, Delagil, delcasertib, delmitide, Delphicort, Deltacorsolone, Deltacortril, Deltafluorene, Deltasolone, Deltasone, Deltastab, Deltonin, Demarin, Demisone, Denebola, denileukin difitox, denosumab, Denzo, Depocortin, Depo-medrol, Depomethotrexate, Depopred, Deposet, Depyrin, Derinase, Dermol, Dermolar, Dermonate, Dermosone, Dersone, Desketo, desonide, desoxycorticosterone acetate, Deswon, Dexta, Dexabene, Dexacip, Dexacort, Dexacortisone, Dexacotisil, Dexadic, Dexadrin, Dexadron, Dexafar, Dexahil, Dexalab, Dexalaf, Dexalet, Dexalgen, Dexallion, Dexalocal, Dexalone, Dexa-M, Dexamecortin, Dexamend, Dexamedis, Dexameral, Dexameta, Dexamethasone, dexamethasone acetate, dexamethasone palmitate, dexamethasone phosphate, dexamethasone sodium metasulfobenzoate, dexamethasone sodium phosphate, Dexamine, Dexapanthen, Dexta-S, Dexason, Dexatab, Dexatopic, Dexaval, Dexaven, Dexazolidin, Dexazona, Dexazone, Dexcort, Dexibu, dexibuprofen, Dexico, Dexifen, Deximune, dexketoprofen, dexketoprofen trometamol, Dexmark, Dexomet, Dexon I, Dexonalin, Dexonex, Dexony, Dextoptifen, Dexpin, Dextan-Plus, dextran sulfate, Dezacor, Dfz, diacerein, Diannexin, Diastone, Dicarol, Dicasone, Dicknol, Diclo, Diclobon, Diclobonse, Diclobonzox, Diclofast, Diclofen, diclofenac, diclofenac beta-dimethylaminoethanol, diclofenac deanol, diclofenac diethylamine, diclofenac epolamine, diclofenac potassium, diclofenac resinate, diclofenac sodium, Diclogen AGIO, Diclogen Plus, Diclokim, Diclomed, Diclo-NA, Diclonac, Dicloramin, Dicloran, Dicloreum, Diclorism, Diclotec, Diclovit, Diclowal, Diclozem, Dico P, Dicofen, Dicoliv, Dicorsone, Dicon, Dicer, Difena, Diffutab, diflunisal, dilmapimod, Dilor, dimethyl sulfone, Dinac, D-Indomethacin, Dioxaflex Protect, Dipagesic, Dipenopen, Dipexin, Dipro AS, Diprobeta, Diprobetasone, Diproklenat, Dipromet, Dipronova, Diprosone, Diprovate, Diproxen, Disarmin, Diser, Disopain, Dispain, Dispercam, Distamine, Dizox, DLT303, DLT404, DM199, DM99, DMI9523, dnaJP1, DNX02070, DNX04042, DNX2000, DNX4000, docosanol, Docz-6, Dolamide, Dolaren, Dolchis, Dolex, Dolflam, Dolfre, Dolgit, Dolmax, Dolmina, Dolo Ketazon, Dolobest, Dolobid, Doloc, Dolocam, Dolocartigen, Dolofit, Dolokind, Dolomed, Dolonac, Dolonex, Dolotren, Dolozon, Dolquine, Dom0100, Dom0400, Dom0800, Domet, Dometon, Dominadol, Dongipap, Donica, Dontisanin, doramapimod, Dorixina Relax, Dormelox, Dorzine Plus, Doxatar, Doxtran, DP NEC, DP4577, DP50, DP6221, D-Penamine, DPIV/APN Inhibitors, DR1 Inhibitors, DR4 Inhibitors, DRA161, DRA162, Drenex, DRF4848, DRL15725, Drossadin, DSP, Duexis, Duo-Decadron, Duoflex, Duonase, DV1079, DV1179, DWJ425, DWP422, Dymol, DYN15, Dynapar, Dysmen, E5090, E6070, Easy Dayz, Ebetrexat, EBI007, EC0286, EC0565, EC0746, Ecax, *echinacea purpurea* extract, EC-Naprosyn, Econac, Ecosprin 300, Ecosprin 300, Ecradoxan, ecilizumab, Edecam, efalizumab, Efcortisol, Efligel, Eflagen, Efridol, EGFR Antibody, EGS21, eIF5A1 siRNA, Ekarzin, elafin, Eldoflam, Elidel, Eliflam, Elisone, Elmes, Elmetacin, ELND001, ELND004, elocalcitil, Elocor, elsibucol, Emanzen, Emcort, Emifen, Emifenac, emorfazone, Empynase, emricasan, Emtor, Enable, Enbrel, Enceid, EncorStat, Encortolon, Encorton, Endase, Endogesic, Endoxan, Enkorten, Ensera, Entocort, Enzytan, Epanova, Eparang, Epatec, Epicotil, epidermal growth factor receptor 2 antibody, epidermal growth factor receptor antibody, Epidixone, Epidron, Epiklin, EPPA1, epratu-

zumab, EquiO, Erac, Erazon, ERB041, ERB196, Erdon, EryDex, *escherichia coli* enterotoxin B subunit, Escin, E-Selectin Antagonists, Esfenac, ESN603, esonarimod, Esprofen, estetrol, Estopein, Estrogen Receptor beta agonist, etanercept, etaracizumab, ETC001, ethanol propolis extract, ETI511, etiprednol dicloacetate, Etodin, Etodine, Etodol, etodolac, Etody, etofenamate, Etol Fort, Etolac, Etopin, etoricoxib, Etorix, Etosafe, Etova, Etozox, Etura, Eucob, Eufans, eukaryotic translation initiation factor 5A oligonucleotide, Eunac, Eurocox, Eurogesic, everolimus, Evino-pon, EVT401, Exafam, EXEL9953, Exicort, Expen, Extra Feverlet, Extrapan, Extrauma, Exudase, F16, F991, Falcam, Falcol, Falzy, Farbovil, Farcomethacin, Farnerate, Farn-ezone, Farnezone, Farotrin, fas antibody, Fastflam, Fast-TRACK, Fastum, Fauldmetro, FcgammaRIA antibody, FE301, Febrofen, Febrofid, felbinac, Feldene, Feldex, Feloran, Felxica, Fenac, Fenacop, Fenadol, Fenaflan, Fenamic, Fenaren, Fenaton, Fenbid, fenbufen, Fengshi Gutong, Fenicort, Fenopine, fenoprofen calcium, Fenopron, Fenris, Fensupp, Fenxicam, fepradinol, Ferovisc, Feverlet, fezikin-umab, FG3019, FHT401, FHTCT4, FID114657, figitumumab, Fillexi, filgrastim, Fillase, Final, Findoxin, fingolimod hydrochloride, firategrast, Firdapse, Fisiodar, Fivasa, FK778, Flacoxto, Fladalgin, Flagon, Flamar, Flamid, Flamfort, Flamide, Flaminase, Flamirex Gesic, Flamid, Flazen, Flaren, Flaren, Flash Act, Flavonoid Anti-inflammatory Molecule, Flebogamma DIF, Flenac, Flex, Flexafen 400, Flexi, Flexidol, Flexium, Flexon, Flexono, Flogene, Flogiatrin B12, Flogomin, Flogoral, Flogosan, Flogoter, Flo-Pred, Flosteron, Flotrip Forte, Flt3 inhibitors, fluasterone, Flucam, Flucinar, fludrocortisone acetate, flufenamate aluminum, flumethasone, Flumidon, flunixin, fluocinolone, fluocinolone acetonide, fluocinonide, fluocortolone, Fluonid, fluorometholone, Flur, flurbiprofen, Fluribec, Fluometholone, Flutal, fluticasone, fluticasone propionate, Flutizone, Fluzone, FM101 antibody, fms-related tyrosine kinase 1 antibody, Folitraz, fontolizumab, formic acid, Fortecortin, Fospeg, fostamatinib disodium, FP1069, FP13XX, FPA008, FPA031, FPT025, FR104, FR167653, Framebin, Prime, Froben, Frolix, FROUNT Inhibitors, Fubifen PAP, Fucole ibuprofen, Fulamotol, Fulpen, Fungifin, Furotagin, fusidate sodium, FX002, FX141L, FX201, FX300, FX87L, Galectin modulators, gallium maltolate, Gamimune N, Gammagard, Gamma-I.V., GammaQuin, Gamma-Venin, Gamunex, Garzen, Gaspirin, Gattex, GBR500, GBR500 antibody, GBT009, G-CSF, GED0301, GED0414, Gefenec, Gelofen, Genepril, Gengraf, Genimmune, Geniquin, Genotropin, Genz29155, Gerbin, Gerbin, gevokizumab, GF01564600, Gilenia, Gilenya, givinostat, GL0050, GL2045, glatiramer acetate, Globulin, Glortho Forte, Glovalox, Glovenin-I, GLPG0259, GLPG0555, GLPG0634, GLPG0778, GLPG0974, Gluco, Glucocerin, glucosamine, glucosamine hydrochloride, glucosamine sulfate, Glucotin, Gludex, Glutilage, GLY079, GLY145, Glycanic, Glycefert up, Glygesic, Glysopep, GMCSF Antibody, GMI1010, GMI1011, GMI1043, GMR321, GN4001, Goanna Salve, Goflex, gold sodium thiomalate, golimumab, GP2013, GPCR modulator, GPR15 Antagonist, GPR183 antagonist, GPR32 antagonist, GPR83 antagonist, G-protein Coupled Receptor Antagonists, Gracaptor, Graftac, granulocyte colony-stimulating factor antibody, granulocyte-macrophage colony-stimulating factor antibody, Gravx, GRC4039, Grelyse, GS101, GS9973, GSC100, GSK1605786, GSK1827771, GSK2136525, GSK2941266,

GSK315234, GSK681323, GT146, GT442, Gucixiaotong, Gufisera, Gupisone, gusperimus hydrochloride, GW274150, GW3333, GW406381, GW856553, GWB78, GXP04, Gynestrel, Haloart, halopredone acetate, Haloxin, HANALL, Hanall Soludacortin, Havisco, Hawon Bucilamin, HB802, HC31496, HCQ 200, HD104, HD203, HD205, HDAC inhibitor, HE2500, HE3177, HE3413, Hecoria, Hectomitacin, Hefasolon, Helen, Helenil, Hema-Max, Hematom, hematopoietic stem cells, Hematrol, Hemner, Hemril, heparinoid, Heptax, HER2 Antibody, Herponil, hESC Derived Dendritic Cells, hESC Derived Hematopoietic stem cells, Hespercorbin, Hexacorton, Hexadrol, hexetidine, Hexoderm, Hexoderm Salic, HF0220, HF1020, HFT-401, hG-CSFR ED Fc, Hiberna, high mobility group box 1 antibody, Hiloneed, Hinocam, hirudin, Hirudoid, Hison, Histamine H4 Receptor Antagonist, Hitenercept, Hizentra, HL036, HL161, HMPL001, HMPL004, HMPL004, HMPL011, HMPL342, HMPL692, honey bee venom, Hongqiang, Hotemin, HPH116, HTI101, HuCAL Antibody, Human adipose mesenchymal stem cells, anti-MHC class II monoclonal antibody, Human Immunoglobulin, Human Placenta Tissue Hydrolysate, HuMaxCD4, HuMax-TAC, Humetone, Humicade, Humira, Huons Betamethasone sodium phosphate, Huons dexamethasone sodium phosphate, Huons Piroxicam, Huons Talniflumate, Hurofen, Huruma, Huvap, HuZAF, HX02, Hyalogel, hyaluronate sodium, hyaluronic acid, hyaluronidase, Hyaron, Hycocin, Hycort, Hy-Cortisone, hydrocortisone, hydrocortisone acetate, hydrocortisone butyrate, hydrocortisone hemisuccinate, hydrocortisone sodium phosphate, hydrocortisone sodium succinate, Hydrocortistab, Hydrocortone, Hydrolin, Hydroquine, Hydro-Rx, Hydrosone HIKMA, hydroxychloroquine, hydroxychloroquine sulfate, Hylase Dessau, HyMEX, Hypen, HyQ, Hysonate, HZN602, I.M.75, IAP Inhibitors, Ibalgin, Ibalgin, Ibex, ibrutinib, IBsolvMIR, Ibu, Ibuton, Ibutodor, Ibuten, Ibutam, Ibutlex, Ibutegic, Ibut-Hepa, Ibutkin, Ibutal, Ibutal, Ibupental, Ibupril, Ibuprof, ibuprofen, Ibuscent, Ibusoft, Ibusuki Penjeong, Ibususpen, Ibutard, Ibutop, Ibutop, Ibutrex, IC487892, ichthammol, ICRAC Blocker, IDEC131, IDECCE9.1, Ides, Idicin, Idizone, IDN6556, Idomethine, IDR1, Idyl SR, Ifen, iguratimod, IK6002, IKK-beta inhibitor, IL17 Antagonist, IL-17 Inhibitor, IL-17RC, IL18, IL1Hy1, IL1R1, IL-23 Adnectin, IL23 Inhibitor, IL23 Receptor Antagonist, IL-31 mAb, IL-6 Inhibitor, IL6Qb, Ilacox, Ilaris, ilodecakin, ILV094, ILV095, Imaxetil, IMD0560, IMD2560, Imesel Plus, Iminoral, Immodin, IMMUI03, IMMUI06, Immucept, Immufine, Immunex Syrup, immunoglobulin, immunoglobulin G, Immunoprin, Immunorel, Immurin, IMO8400, IMP731 antibody, Implants, Immunocell, Imuran, Imurek, Imusafe, Imusporin, Imutrex, IN0701, Inal, INCB039110, INCB18424, INCB28050, INCB3284, INCB3344, Indexon, Indic, Indo, Indo-A, Indobid, Indo-Bros, Indocaf, Indocarsil, Indocid, Indocin, Indomehotpas, Indomen, Indomet, Indometacin, indomethacin, Indomethasone, Indometin, Indomin, Indopal, Indoron, Indotroxin, INDUS830, INDUS83030, Infladase, Inflamac, Inflammasome inhibitor, Inflavis, Inflaxen, Inflectra, infliximab, Ingalipt, Inicox dp, Inmecin, Inmunoartro, Innamit, InnoD06006, IN07997, Inocin, Inoten, Inovan, Inpra, Inside Pap, Insider-P, Instacyl, Instracool, Intafenac, Intafam, Inteban, Inteban Spansule, integrin, alpha 1 antibody, integrin, alpha 2 antibody, Intenurse, interferon alfa, interferon beta-1a, interferon gamma, interferon gamma antibody, Interking, interleukin 1

Hyl, interleukin 1 antibody, interleukin 1 receptor antibody, interleukin 1, beta antibody, interleukin 10, interleukin 10 antibody, interleukin 12, interleukin 12 antibody, interleukin 13 antibody, interleukin 15 antibody, interleukin 17 antibody, interleukin 17 receptor C, interleukin 18, interleukin 18 binding protein, interleukin 18 antibody, interleukin 2 receptor, alpha antibody, interleukin 20 antibody, Interleukin 21 mAb, interleukin 23 aptamer, interleukin 31 antibody, interleukin 34, Interleukin 6 Inhibitor, interleukin 6 antibody, interleukin 6 receptor antibody, interleukin 7, interleukin 7 receptor antibody, interleukin 8, interleukin 8 antibody, interleukin-18 antibody, Intidrol, Intradex, Intragam P, Intragesic, Intraglobin F, Intratect, Inzel, Iomab B, IOR-T3, IP751, IPH2201, IPH2301, IPH24, IPH33, IP1145, Ipocort, IPP201007, I-Profen, Iprox, Ipson, Iputon, IRAK4 Inhibitor, Iremod, Irtonpyson, IRX3, IRX5183, ISA247, ISIS104838, ISIS2302, ISISCRPRx, Ismafron, IsoCQ inhibitor, Isox, ITF2357, Iveegam EN, Ivepred, IVIG-SN, IW001, Izilox, J607Y, J775Y, JAK Inhibitor, JAK3 inhibitor, JAK3 kinase inhibitor, JI3292, JI4135, Jinan Lida, JNJ10329670, JNJ18003414, JNJ26528398, JNJ27390467, JNJ28838017, JNJ31001958, JNJ38518168, JNJ39758979, JNJ40346527, JNJ7777120, JNT-Plus, Joflam, Joint Glucosamin, Jointec, Jointstem, Joinup, JPE1375, JSM10292, JSM7717, JSM8757, JTE051, JTE052, JTE522, JTE607, Jusgo, K412, K832, Kaflam, KAH101, KAH102, KAI9803, Kalymin, Kam Predsol, Kameton, KANAb071, Kappaproct, KAR2581, KAR3000, KAR3166, KAR4000, KAR4139, KAR4141, KB002, KB003, KD7332, KE298, keliximab, Kemanat, Kemrox, Kenacort, Kenalog, Kenaxir, Kenketsu Venoglobulin-III, Keplat, Ketalgipan, Keto Pine, Keto, Ketobos, Ketofan, Ketofen, Ketolgan, Ketonal, Ketoplus Kata Plasma, ketoprofen, Ketores, Ketorin, ketorolac, ketorolac tromethamine, Ketoselect, Ketotop, Ketovail, Ketricin, Ketroc, Ketum, Keyi, Keyven, KF24345, K-Fenac, K-Fenak, K-Gesic, Kifadene, Kilcort, Kildrol, KIMI27, Kimotab, Kinase Inhibitor 4SC, Kinase N, Kincort, Kindorase, Kineret, Kineto, Kitadol, Kitex, Kitolac, KLK1 Inhibitor, Klofen-L, Klotaren, KLS-40or, KLS-40ra, KM277, Knavon, Kodolo orabase, Kohakusanin, Koide, Koidexa, Kolbet, Konac, Kondro, Kondromin, Konshien, Kontab, Kordexa, Kosa, Kotase, KPE06001, KRP107, KRP203, KRX211, KRX252, KSB302, K-Sep, Kv 1.3 Blocker, Kv1.3 4SC, Kv1.3 inhibitor, KVK702, Kynol, L156602, Labizone, Labohydro, Labopen, Lacoza, Lamin, Lamit, Lanfetil, laquinimod, larazotide acetate, LAS186323, LAS187247, LAS41002, Laticort, LBEC0101, LCP3301, LCP-Siro, LCP-Tacro, LcSa, LDP392, Leap-S, Lederacort, Lederfen, Lederlon, Lederspan, Lefenine, leflunomide, Leflux, Lefno, Lefra, Leftose, Lefumide, Lefunodin, Lefva, lenalidomide, lenerecept, LentiRA, LEO15520, Leodase, Leukine, Leukocyte function-associated antigen-1 antagonist, leukocyte immunoglobulin-like receptor, subfamily A, member 4 antibody, Leukothesa, leuprolide acetate, levalbuterol, levomenthol, LFA-1 Antagonist, LFA451, LFA703, LFA878, LG106, LG267 Inhibitors, LG688 Inhibitors, LGD5552, Li Life, LidaMantle, Lidex, lidocaine, lidocaine hydrochloride, Lignocaine hydrochloride, LIM0723, LIM5310, Limethason, Limus, Limustin, Lindac, Linfonex, Linola acute, Lipcy, lisofylline, Listran, Liver X Receptor modulator, Lizak, LJP1207, LJP920, Lobafen, Lobu, Locaffluo, Locallyn, Locaseptil-Neo, Locpren, Lodine, Lodotra, Lofedic, Loflam, Lofnac, Lolcam, Lonac, lonazolac calcium, Lopro-

fen, Loracort, Lorcam, Lorfenamin, Lorinden Lotio, Lornacrat, lornoxicam, LoroX, losmapimod, loteprednol etabonate, Loteprednol, Lotirac, Low Molecular *Ganoderma Lucidum* Polysaccharide, Loxafen, Loxfenine, Loxicam, Loxofen, Loxonal, Loxonin, loxoprofen sodium, Loxoron, LP183A1, LP183A2, LP204A1, LPCN1019, LT1942, LT1964, LTNS101, LTNS103, LTNS106, LTNS108, LTS1115, LTZMP001, Lubor, lumiracoxib, Lumitect, LX2311, LX2931, LX2932, LY2127399, LY2189102, LY2439821, LY294002, LY3009104, LY309887, LY333013, lymphocyte activation gene 3 antibody, Lymphoglobuline, Lyser, lysine aspirin, Lysobact, Lysoflam, Lysozyme hydrochloride, M3000, M834, M923, mAb hG-CSF, MABP1, macrophage migration inhibitory factor antibody, Maitongna, Majamil prolongatum, major histocompatibility complex class II DR antibody, major histocompatibility complex class II antibody, Malidens, Malival, mannan-binding lectin, mannan-binding lectin-associated serine protease-2 antibody, MapKap Kinase 2 Inhibitor, maraviroc, Marlex, masitinib, Maso, MASP2 antibody, MAT304, Matrix Metalloprotease Inhibitor, mavrilimumab, Maxiflam, Maxilase, Maximus, Maxisona, Maxius, Maxpro, Maxrel, Maxsulid, Maxy12, Maxy30, MAXY4, Maxy735, Maxy740, Mayfenamic, MB11040, MBPY003b, MCAF5352A, McCam, McRofy, MCS18, MD707, MDAM, MDcort, MDR06155, MDT012, Mebicam, Mebuton, meclofenamate sodium, Meclophen, Mecox, Medacomb, Medafen, Medamol, Medesone, MEDI2070, MEDI5117, MEDI541, MEDI552, MEDI571, Medicox, Medifen, Medisolu, Medixon, Mednisol, Medrol, Medrolon, medroxyprogesterone acetate, Mefalgin, mefenamic acid, Mefenix, Mefentan, Meflen, Mefnetra forte, Meftagesic-DT, Meftal, Megakaryocyte Growth and Development Factor, Megaspas, Megaster, megestrol acetate, Meite, Meksun, Melbrex, Melcam, Melcam, Melflam, Melic, Melica, Melix, Melocam, Melocox, Mel-One, Meloprol, Melosteral, Melox, Meloxan, Meloxcam, Meloxic, Meloxicam, Meloxifen, Meloxin, Meloxiv, Melpred, Melpros, Melurjin, Menamin, Menisone, Menthomketo, Menthoneurin, Mentocin, Mepa, Mepharen, meprednisone, Mepresso, Mepsolone, mercaptopurine, Mervan, Mesadoron, mesalamine, Mesasal, Mesatec, Mesenchymal Precursor Cells, mesenchymal stem cell, Mesipol, Mesren, Mesulan, Mesulid, Metacin, Metadaxan, Metaflex, Metalcaptase, metalloenzyme inhibitors, Metapred, Metax, Metaz, Meted, Metedic, Methacin, Methaderm, Methasone, Methotrax, methotrexate, methotrexate sodium, Methpred, Methyl prednisolone acetate, methyl salicylate, methyl sulphonyl methane, Methylon, Methylpred, methylprednisolone, methylprednisolone acetate, methylprednisolone sodium succinate, methylprednisolone succinate, Methylprednisolone, Methysol, Metindol, Metoart, Metoject, Metolate, Metoral, Metosyn, Metotab, Metracin, Metrex, metronidazole, Metypred, Mevamax, Mevedal, Mevilox, Mevin SR, Mexilal, Mexpharm, Mext, Mextran, MF280, M-FasL, MHC class II beta chain peptide, Micar, Miclofen, Miclofenac, Micofenolato Mofetil, Micosone, Microdase, microRNA 181a-2 oligonucleotide, MIF Inhibitors, MIFQb, MIKA-Ketoprofen, Mikametan, milodistim, Miltax, Minafen, Minalfen, Minalfene, Minesulin, Minocort, Mioflex, Miolox, Miprofen, Miridacin, Mirloks, Misoclo, Misofenac, MISTB03, MISTB04, Mitilor, mizoribine, MK0359, MK0812, MK0873, MK2 Inhibitors, MK50, MK8457, MK8808, MKC204, MLN0002, MLN0415, MLN1202, MLN273,

MLN3126, MLN3701, MLN3897, MLNM002, MM093, MM7XX, MN8001, Mobic, Mobicam, Mobicox, Mobifen Plus, Mobilat, Mobitil, Mocox, Modigraf, Modrasone, Modulin, Mofecept, Mofetyl, mofezolac sodium, Mofetil, Molace, molgramostim, Molslide, Momekin, Momen Gele, Moment 100, Momesone, Momesun, Mometamed, mometasone, mometasone furoate, Monimate, monosodium alpha-luminol, Mopik, MOR103, MOR104, MOR105, MOR208 antibody, MORAb022, Moricam, morniflumate, Mosulit, Motoral, Movaxin, Mover, Movex, Movix, Movoxicam, Mox Forte, Moxen, moxifloxacin hydrochloride, Mozobil, MP, MP0210, MP0270, MP1000, MP1031, MP196, MP435, MPA, mPGES-1 inhibitor, MPSS, MRX7EAT, MSL, MT203, MT204, mTOR Inhibitor, MTRX1011A, Mucolase, Multicort, MultiStem, muramidase, muramidase, muramidase hydrochloride, muromonab-CD3, Muslax, Muspinil, Mutaze, Muvera, MX68, Mycept, Mycocell, Mycocept, Mycofenolatmofetil Actavis, Mycofet, Mycofit, Mycolate, Mycoldosa, Mycomun, Myconol, mycophenolate mofetil, mycophenolate sodium, mycophenolic acid, Mycotil, myeloid progenitor cells, Myfenax, Myfetil, Myfortic, Mygraft, Myochrysine, Myocrisin, Myprodol, Mysone, nab-Cyclosporine, Nabentac, nabiximols, Nabton, Nabuco, Nabucoc, Nabuflam, Nabumet, nabumetone, Nabuton, Nac Plus, Nacta, Nacton, Nadium, Naklofen SR, NAL1207, NAL1216, NAL1219, NAL1268, NAL8202, Nalfon, Nalgesin S, namilumab, Namsafe, nandrolone, Nanocort, Nanogam, Nanosomal Tacrolimus, Napageln, Napilac, Naprelan, Napro, Naprodil, Napronax, Napropal, Naprosone, Naprosyn, Naproval, Naprox, naproxen, naproxen sodium, Naproxin, Naprozen, Narbon, Narexin, Naril, Nasida, natalizumab, Naxdom, Naxen, Naxin, Nazovel, NC2300, ND07, NDC01352, Nebumetone, NecLipGCSF, Necsulide, Necsunim, Nelsid-S, Neo Clobenate, Neo Swiflox FC, Neocoflan, Neo-Drol, Neo-Eblimon, Neo-Hydro, Neoplanta, Neoporine, Neopreol, Neoprox, Neoral, Neotrexate, Neozen, Nepra, Nestacort, Neumega, Neupogen, Neuprex, Neurofenac, Neurogesic, Neurolab, Neuroteradol, Neuroxicam, Neutalin, neutrazumab, Neuzym, New Panazox, Newfenstop, NewGam, Newmafen, Newmatal, Newsicam, NEX1285, sFcRIIB, Nextomab, NF-kappaB Inhibitor, NF-kB inhibitor, NGD20001, NHP554B, NHP554P, NI0101 antibody, NI0401, NI0501 antibody, NI0701, NI1071, NI1201 antibody, NI1401, Nicip, Niconas, Nicool, NiCord, Nicox, Niflumate, Nigaz, Nikam, Nilitis, Nimace, Nimaid, Nimark-P, Nimaz, Nimcet Juicy, Nime, Nimed, Nimepast, nimesulide, Nimesulix, Nimesulon, Nimica Plus, Nimkul, Nimlin, Nimnat, Nimodol, Nimpidase, Nimsaid-S, Nimser, Nimsy-SP, Nimupep, Nimusol, Nimutal, Nimuwin, Nimvon-S, Nincort, Niofen, Nipan, Nipent, Nise, Nisolone, Nisopred, Nisoprex, Nisulid, nitazoxanide, Nitcon, nitric oxide, Nizhvisal B, Nizon, NL, NMR1947, NN8209, NN8210, NN8226, NN8555, NN8765, NN8828, NNC014100000100, NNC051869, Noak, Nodevex, Nodia, Nofenac, Noflagma, Noflam, Noflamin, Noflux, Non-antibacterial Tetracyclines, Nonpiron, Nopain, Normferon, Notpel, Notritis, Novacort, Novagent, Novarin, Novigesic, NOXA12, NOXD19, Noxen, Noxon, NPI1302a-3, NPI1342, NPI1387, NPI1390, NPRCS1, NPRCS2, NPRCS3, NPRCS4, NPRCS5, NPRCS6, NPS3, NPS4, nPTery, NU3450, nuclear factor NF-kappa-B p65 subunit oligonucleotide, Nucort, Nulojix, Numed-Plus, Nurokind Ortho, Nusone-H, Nutrikemia, Nuvion, NV07alpha, NX001, Nyclobate, Nyox, Nysa, Obarcort, OC002417,

OC2286, ocaratuzumab, OCTSG815, Oedemase, Oedemase-D, ofatumumab, Ofgyt-O, Ofvista, OHR118, OKi, Okifen, Oksamen, Olai, olokizumab, Omeprose E, Omnacortil, Omneed, Omniclor, Omnigel, Omniwel, onercept, ONO4057, ONS1210, ONS1220, Ontac Plus, Ontak, ONX0914, OPC6535, opebacan, OPN101, OPN201, OPN302, OPN305, OPN401, oprelvekin, OPT66, Optifer, Optiflur, OptiMIRA, Orabase Hca, Oradexon, Oraflex, Oral-Fenac, Oralog, Oralpred, Ora-sed, Orasone, orBec, Orbone forte, Orcl, ORE10002, ORE10002, Orenzia, Org214007, Org217993, Org219517, Org223119, Org37663, Org39141, Org48762, Org48775, Orgadron, Ormoxen, Orofen Plus, Oromylase Biogaran, Orthol Forte, Ortho Flex, Orthoclon OKT3, Orthofen, Orthoflam, Orthogesic, Orthoglu, Ortho-II, Orthomac, Ortho-Plus, Ortinims, Ortofen, Orudis, Oruvail, OS2, Oscan, Osmetone, Ospain, Ossilife, Ostelox, Osteluc, Osteocerin, osteopontin, Osteral, otelexizumab, Otixap, Ou Ning, OvaSave, OX40 Ligand Antibody, Oxa, Oxagesic CB, Oxalgin DP, oxaprozin, OXCQ, Oxeno, Oxib MD, Oxibut, Oxicam, Oxiklorin, Oximal, Oxynal, oxyphenbutazone, Oxyphenbutazone, ozoralizumab, P13 peptide, P1639, P21, P2X7 Antagonists, p38 Alpha Inhibitor, p38 Antagonist, p38 MAP kinase inhibitor, p38alpha MAP Kinase Inhibitor, P7 peptide, P7170, P979, PA401, PA517, Pabi-dexamethasone, PAC, PAC10649, paclitaxel, Painoxam, Paldon, Palima, pamapimod, Pamatase, Panafcort, Panafcortelone, Panewin, PanGraf, Panimun Bioral, Panmesone, Panodin SR, Panslay, Panzem, Panzem NCD, PAP1, papain, Papirzin, Pappen K Pap, Paptinim-D, paquinimod, PAR2 Antagonist, Paracetamol, Paradic, Parafen TAJ, Paramidin, Parana, Parapar, Parci, parecoxib, Parixam, Parry-S, Partaject Busulfan, pateclizumab, Paxceed, PBI0032, PBI1101, PBI1308, PBI1393, PBI1607, PBI1737, PBI2856, PBI4419, PBI4419, P-Cam, PCI31523, PCI32765, PCI34051, PCI45261, PCI45292, PCI45308, PD360324, PD360324, PDA001, PDE4 inhibitor, PDE-IV Inhibitor, PDL241 antibody, PDL252, Pdiapred, Pefree, pegacaristim, Peganax, Peg-Interleukin 12, pegsunercept, Pegsunercept, PEGylated arginine deiminase, peldesine, pelubiprofen, Penacle, penicillamine, Penostop, Pentalgin, Pentasa, Pentaud, pentostatin, Peon, Pepdase, Pepser, Pep-tirase, Pepzen, Pepzol, Percutalgine, Periochip, Peroxisome Proliferator Activated Receptor gamma modulators, Petizene, PF00344600, PF04171327, PF04236921, PF04308515, PF05230905, PF05280586, PF251802, PF3475952, PF3491390, PF3644022, PF4629991, PF4856880, PF5212367, PF5230896, PF547659, PF755616, PF9184, PG27, PG562, PG760564, PG8395, PGE3935199, PGE527667, PHS, PH797804, PHA408, Pharmaniaga Mefenamic acid, Pharmaniaga Meloxicam, Pheldin, Phenocept, phenylbutazone, PHY702, PI3K delta inhibitor, PI3K Gamma/Delta Inhibitor, PI3K Inhibitor, Picalm, pidotimod, piketoprofen, Pilelife, Pilopil, Pilovate, pimecrolimus, Pipethanen, Piractam, Pirexyl, Pirobet, Piroc, Pirocam, Pirofel, Pirogel, Piromed, Piroxol, Pirox, Piroxen, Piroxicam, piroxicam betadex, Piroxifar, Piroxil, Piroxim, Pixim, Pixykine, PKC Theta Inhibitor, PL3100, PL5100 Diclofenac, Placenta Polypeptide, Plaquenil, plerixafor, Plocfen, PLR14, PLR18, Plutin, PLX3397, PLX5622, PLX647, PLX-BMT, pms-Diclofenac, pms-Ibuprofen, pms-Leflunomide, pms-Meloxicam, pms-Piroxicam, pms-Prednisolone, pms-Sulfasalazine, pms-Tiaprofenic, PMX53, PN0615, PN100, PN951, podofilox, POL6326, Polcortolon, Polyderm, Polygam S/D, Polyphlogin, Poncif, Ponstan, Pon-

stil Forte, Porine-A Neoral, Potaba, potassium aminobenzoate, Potencort, Povidone, povidone iodine, pralnacasan, Prandin, Prebel, Precodil, Precortisyl Forte, Precortyl, Predfoam, Predicort, Predicorten, Predilab, Predilone, Predmetil, Predmix, Predna, Prednesol, Predni, prednicarbate, Prednicort, Prednidib, Prednifarma, Prednilasca, prednisolone, prednisolone acetate, prednisolone sodium phosphate, prednisolone sodium succinate, prednisolone sodium succinate, prednisone, prednisone acetate, Prednitop, Prednol-L, Prednox, Predone, Predonema, Predsol, Predsolone, Predsone, Predval, Prefflam, Prellon, Prenaxol, Prenolone, Preservex, Preservin, Presol, Preson, Prexige, Priliximab, Primacort, Primmuno, Primofenac, prinaberel, Privigen, Prixam, Probuxil, Procarne, Prochymal, Procider-EF, Proctocir, Prodase, Prodel B, Prodent, Prodent Verde, Proepa, Profecom, Profenac L, Profenid, Profenol, Proflam, Proflex, Progesic Z, proglumetacin, proglumetacin maleate, Prograf, Prolase, Prolisan, promethazine hydrochloride, Promostem, Promune, PronaB, pronase, Pronat, Prongs, Pronison, Pronto-flam, Propaderm-L, Propodezas, Propolisol, Proponol, propyl nicotinate, Prostaloc, Prostopol, Protacin, Protase, Protease Inhibitors, Protectan, Proteinase Activated Receptor 2 Inhibitor, Protoben, Protrin, Proxaloc, Proxolol, Proxigel, Proxil, Proxym, Prozym, PRT062070, PRT2607, PRTX100, PRTX200, PRX106, PRX167700, Prysolone, PS031291, PS375179, PS386113, PS540446, PS608504, PS826957, PS873266, Psorid, PT, PT17, PTL101, P-Transfer Factor peptides, PTX3, Pulminiq, Pulsonid, Purazen, Pursin, PVS40200, PX101, PX106491, PX114, PXS2000, PXS2076, PYM60001, Pyralvex, Pyranim, pyrazinobutazone, Pyrenol, Pyricam, Pyrodex, Pyroxi-Kid, QAX576, Qianbobiyuan, QPI1002, QR440, qT3, Quiacort, Quidofil, R107s, R125224, R1295, R132811, R1487, R1503, R1524, R1628, R333, R348, R548, R7277, R788, rabeximod, Radix Isatidis, Radofen, Raipack, Rambazole, Randazima, Rapa-can, Rapamune, Raptiva, Ravax, Rayos, RDEA119, RDEA436, RDP58, Reactine, Rebif, REC200, Recartix-DN, receptor for advanced glycation end products antibody, Reclast, Reclofen, recombinant HSA-TIMP-2, recombinant human alkaline Phosphatase, recombinant Interferon Gamma, Recombinant human alkaline phosphatase, Reconil, Rectagel HC, Recticin, Recto Menaderm, Rectos, Redipred, Redolet, Refastin, Regencia, REGN88, Relafen, Relaxib, Relev, Relax, Relifen, Relifex, Relitch, Rematof, remestemcel-1, Remesulidum, Remicade, Remsima, Remsima, Remsima, ReN1869, Renacept, Renfor, Renodapt, Renodapt-S, Renta, Reosan, Repare-AR, Reparilexin, reparixin, Reper-taxin, Repispin, Resochin, Resol, resolvin E1, Resurgil, Re-tin-colloid, Retoz, Reumacap, Reumacon, Reumadolor, Reumador, Reumanisal, Reumazin, Reumel, Reumotec, Reuquinol, revamilast, Revascor, Reviroc, Revlimid, Revmoksikam, Rewalk, Rexalgan, RG2077, RG3421, RG4934 antibody, RG7416, RG7624, Rheila, Rheoma, Rheprox, Rheudenolone, Rheufen, Rheugesic, Rheumacid, Rheumacort, Rheumatrex, Rheumesser, Rheumid, Rheumon, Rheumox, Rheuxib, Rhewlin, Rhucin, RhuDex, Rhulef, Ribox, Ribunal, Ridaura, rifaximin, rilonacept, rimacalib, Rimase, Rimate, Rimatil, Rimesid, risedronate sodium, Ritamine, Rito, Rituxan, rituximab, RNS60, RO1138452, Ro313948, RO3244794, RO5310074, Rob803, Rocamix, Rocas, Rofeb, rofecoxib, Rofee, Rofewal, Roficup Plus, Rojepen, Rokam, Rolodiquim, Romacox Fort, Romatim, romazarit, Ronaben, ronacaleret, Ronoxcin, ROR Gamma T Antagonist, ROR gamma t inverse agonists,

Rosecin, rosiglitazone, Rosmarinic acid, Rotan, Rotec, Rothacin, Roxam, Roxib, Roxicam, Roxopro, Roxygin DT, RP54745, RPI78, RPI78M, RPI78MN, RPIMN, RQ00000007, RQ00000008, RTA402, R-Tyflam, Rubicalm, Rubifen, Ruma pap, Rumalef, Rumidol, Rumifen, Runomex, rusalatide acetate, ruxolitinib, RWJ445380, RX10001, Rycloser MR, Rydol, S1P Receptor Agonists, S1P Receptor Modulators, S1P1 Agonist, S1P1 receptor agonist, S2474, S3013, SA237, SA6541, Saaz, S-adenosyl-L-methionine-sulfate-p-toluene sulfonate, Sala, Salazidin, Salazine, Salazopyrin, Salcon, Salicam, salsalate, Sameron, SAN300, Sanaven, Sandimmun, Sandoglobulin, Sanexon, SangCya, SAR153191, SAR302503, SAR479746, Sarapep, sargramostim, Sativex, Savantac, Save, Saxizon, Sazo, SB1578, SB210396, SB217969, SB242235, SB273005, SB281832, SB683698, SB751689, SBI087, SC080036, SC12267, SC409, Scaflam, SCD ketoprofen, SCIO323, SCIO469, SD-15, SD281, SDP051 antibody, Sd-rxRNA, secukinumab, Sedase, Sedilax, Sefdene, Seizyme, SEL113, Seladin, Selecox, selectin P ligand antibody, Glucocorticoid Receptor Agonist, Selectofen, Selektine, SelK1 antibody, Seloxx, Selspot, Selzen, Selzenta, Selzentry, semapimod, semapimod hydrochloride, semparatide, Semparatide, Senafen, Sendipen, Senterlic, SEP119249, Sepdase, Septirose, Seractil, Serafen-P, Serase, Seratid D, Seratiopeptidase, Serato-M, Seratoma Forte, Serazyme, Serezon, Sero, Serodase, Serpicam, Serra, serrapeptase, Serratin, Serratiopeptidase, Serrazyme, Servisone, Seven E P, SGI1252, SGN30, SGN70, SGX203, shark cartilage extract, Sheril, Shield, Shifazen, Shifazen-Fort, Shincort, Shincort, Shiosol, SHK186, Shuanghuangxiaoyan, SI615, SI636, Sigmasporin, Sigmasporin, SIM916, Simpone, Simulect, Sinacort, Sinalgia, Sinapol, Sinatrol, Sinsia, siponimod, Sirolim, sirolimus, Siropan, Sirota, Sirova, sirukumab, Sistol Forte, SKF105685, SKF105809, SKF106615, SKF86002, Skinalar, Skynim, Skytrip, SLAM family member 7 antibody, Slo-indo, SM101, SM201 antibody, SM401, SMAD family member 7 oligonucleotide, SMART Anti-IL-12 Antibody, SMP114, SNO030908, SNO070131, sodium aurothiomalate, sodium chondroitin sulfate, sodium deoxyribonucleotide, sodium gualenate, sodium naproxen, sodium salicylate, Sodixen, Sofeo, Soletom, Solhidrol, Solicam, Soliky, Soliris, Sol-Melcort, Solomet, Solondo, Solone, Solu-Cort, Solu-Cortef, Solu-Decortin H, Solufen, Solu-Ket, Solumark, Solu-Medrol, Solupred, Somalgen, somatropin, Sonap, Sone, sonecipzumab, Sonexa, Sonim, Sonim P, Soonil, Soral, Sorenil, sotrastaurin acetate, SP10, SP600125, Spanidin, SP-Cortil, SPD550, Spedace, sperm adhesion molecule 1, Spictol, spleen tyrosine kinase oligonucleotide, Sporin, S-prin, SPWF1501, SQ641, SQ922, SR318B, SR9025, SRT2104, SSR150106, SSR180575, SSS07 antibody, ST1959, STA5326, stabilin 1 antibody, Stacort, Stalogesic, stanozolol, Staren, Starmelox, Stedex IND-SWIFT, Stelara, Stemin, Stenirol, Sterapred, Steriderm S, Steno, Sterisone, Steron, stichodactyla *helianthus* peptide, Stickzenol A, Stiefcortil, Stimulan, STNM01, Store Operated Calcium Channel (SOCC) Modulator, STP432, STP900, Stratasin, Stridimmune, Strigraf, SU Medrol, Subreum, Subuton, Succicort, Succimed, Sulan, Sulcolon, Sulfasalazin Heyl, Sulfasalazin, sulfasalazine, Sulfovit, Sulidac, Sulide, sulindac, Sulindex, Sulinton, Sulphafine, Sumilu, SUN597, Suprafen, Supretic, Supsidine, Surgam, Surgamine, Surugamu, Suspend, Suton, Suvenyl, Suwei, SW Dexasone, Syk Family Kinase Inhibitor, Syn1002, Synacran, Synacthen, Synalar C,

Synalar, Synavive, Synercort, Sypresta, T cell cytokine-inducing surface molecule antibody, T cell receptor antibody, T5224, T5226, TA101, TA112, TA383, TA5493, tabalumab, Tacedin, Tacgraf, TACIFc5, Tacrobell, Tacrograf, Tacrol, tacrolimus, Tadekinig alpha, Tadolak, TAFA93, Tafirol Arno, Taizen, TAK603, TAK715, TAK783, Takfa, Taksta, talarozole, Talfin, Talmain, talmapimod, Talmea, Talnif, talniflumate, Talos, Talpain, Talumat, Tamalgen, Tamcetone, Tamezon, Tandrilax, tannins, Tannosynt, Tantum, tanzi-sertib, Tapain-beta, Tapoein, Tarenac, tarenflurbil, Tarimus, Tarproxen, Tauxib, Tazomust, TBR652, TC5619, T-cell, immune regulator 1, ATPase, H+ transporting, lysosomal V0 subunit A3 antibody, TCK1, T-cort, T-Dexa, Tecelac, Tecon, teduglutide, Teecort, Tegeline, Tementil, temoporfin, Tencam, Tendrone, Tenefuse, Tenfly, tenidap sodium, Tenocam, Tenoflex, Tenoksan, Tenotil, tenoxicam, Tenoxim, Tepadina, Teracort, Teradol, tetomilast, TG0054, TG1060, TG20, TG20, tgAAC94, Th1/Th2 Cytokine Synthase Inhibitor, Th-17 cell inhibitors, Thalido, thalidomide, Thalomid, Themisera, Thenil, Therafectin, Therapyace, thiarabine, Thiazolopyrimidines, thioctic acid, thiotepa, THR090717, THR0921, Threenofen, Thrombate III, Thymic peptide, Thymodepressin, Thymogam, Thymoglobulin, Thymoglobuline, Thymoject thymic peptides, thymomodulin, thymopentin, thymopolypeptides, tiaprofenic acid, tibezoneum iodide, Ticoflex, tilmacoxib, Tilur, T-immune, Timocon, Tiorase, Tissop, TKB662, TL011, TLR4 antagonists, TLR8 inhibitor, TM120, TM400, TMX302, TNF Alpha inhibitor, TNF alpha-TNF receptor antagonist, TNF antibody, TNF receptor superfamily antagonists, TNF TWEAK Bi-Specific, TNF-Kinoid, TNFQb, TNFR1 antagonist, TNR001, TNX100, TNX224, TNX336, TNX558, tocilizumab, tofacitinib, Tokuhon happ, TOL101, TOL102, Tolectin, Tolerimab, Tolerostem, Tolindol, toll-like receptor 4 antibody, toll-like receptor antibody, tolmetin sodium, Tongkeeper, Tonmex, Topflame, Topicort, Topleucon, Topnac, Toppin Ichthammol, toralizumab, Toraren, Torcoxia, Tororox, Tory, Toselac, Totaryl, Touch-med, Touchron, Tovok, Toxic apis, Toyolyzom, TP4179, TPCA1, TPI526, TR14035, Tradil Fort, Traficet-EN, Tramace, tramadol hydrochloride, tranilast, Transimmune, Transporina, Tratul, Trexall, Triacort, Triacort, Trialon, Triam, triamcinolone, triamcinolone acetate, triamcinolone acetonide, triamcinolone acetonide acetate, triamcinolone hexacetonide, Triamcort, Triamsicort, Trianex, Tricin, Tricort, Tricortone, TricOs T, Triderm, Trilac, Trilistate, Trinocort, Trinolone, Trioalex, triptolide, Trisfen, Trivaris, TRK170, TRK530, Trocade, trolamine salicylate, Trolovol, Trosera, Trosera D, Troycort, TRX1 antibody, TRX4, Trymoto, Trymoto-A, TT301, TT302, TT32, TT32, TT33, TTI314, tumor necrosis factor, tumor necrosis factor 2-methoxyethyl phosphorothioate oligonucleotide, tumor necrosis factor antibody, tumor necrosis factor kinoid, tumor necrosis factor oligonucleotide, tumor necrosis factor receptor superfamily, member 1B antibody, tumor necrosis factor receptor superfamily 1B oligonucleotide, tumor necrosis factor superfamily, member 12 antibody, tumor necrosis factor superfamily, member 4 antibody, tumor protein p53 oligonucleotide, tumour necrosis factor alpha antibody, TuNEX, TXA127, TX-RAD, TYK2 inhibitors, Tysabri, ubidecarenone, Ucerase, ulodesine, Ultiflam, Ultrafastin, Ultrafen, Ultralan, U-Nice-B, Uniplus, Unirexate, Unizen, Uphaxicam, UR13870, UR5269, UR67767, Uremol-HC, Urigon, U-Ritis, ustekinumab, V85546, Valcib, Valcox, valdecoxib, Valdez, Valdixx, Valdy, Valentac, Valoxib, Valtune,

Valus AT, Valz, Valzer, Vamid, Vantal, Vantelin, VAP1 SSAO Inhibitor, vapaliximab, varespladib methyl, Vari-cosin, Varidase, vascular adhesion protein-1 antibody, VB110, VB120, VB201, VBY285, Vectra-P, vedolizumab, Veffren, VEGFR-1 Antibody, Veldona, veltuzumab, Vendex-ine, Venimmun N, Venoforte, Venoglobulin-IH, Venozel, Veral, Verax, vercimon, vero-Dexamethasone, Vero-Kladribin, Vetazone, VGX1027, VGX750, Vibex MTX, vidofludimus, Vifenac, Vimovo, Vimultisa, Vincort, Vingraf, Vioform-HC, Vioxl, Vioxx, Virobron, visilizumab, Viva-globin, Vivalde Plus, Vivian-A, VLST002, VLST003, VLST004, VLST005, VLST007, Voalla, voclosporin, Vokam, Vokmor, Volmax, Volna-K, Voltadol, Voltagesic, Voltanase, Voltanec, Voltaren, Voltarile, Voltic, Voren, vorsetuzumab, Votan-SR, VR909, VRA002, VRP1008, VRS826, VRS826, VT111, VT214, VT224, VT310, VT346, VT362, VTX763, Vurdon, VX30 antibody, VX467, VX5, VX509, VX702, VX740, VX745, VX745, VX850, W54011, Walacort, Walix, WC3027, Wilgraf, Winflam, Winmol, Win-pred, Winsolve, Wintogeno, WIP901, Woncox, WSB711 antibody, WSB712 antibody, WSB735, WSB961, X071NAB, X083NAB, Xantomycin Forte, Xedenol, Xefo, Xefocam, Xenar, Xepol, X-Flam, Xibra, Xicam, Xicotil, Xifaxan, XL499, XmaB5483, XmaB5485, XmaB5574, XmaB5871, XOMA052, Xpress, XPro1595, XtendTNF, XToll, Xtra, Xylex-H, Xynofen SR, Yang Shu-IVIG, YHB14112, YM974, Youfeline, Youfenac, Yuma, Yumerol, Yuroben, YY piroxicam, Z104657A, Zacy, Zaltokin, zalto-profen, Zap70 Inhibitor, Zeepain, Zeloxim Fort, Zema-Pak, Zempack, Zempred, Zenapax, Zenas, Zenol, Zenos, Zenox-one, Zerax, Zerocam, Zerospasm, ZFNs, zinc oxide, Zipsoz, ziralimumab, Zitis, Zix-S, Zocort, Zodixam, Zoftadex, zole-dronic acid, Zolfin, Zolterol, Zopyrin, Zoralone, ZORprin, Zortress, ZP1848, zucapsaicin, Zunovate, Zwitterionic poly-saccharides, ZY1400, Zybodies, Zycel, Zyrofen, Zyrogen Inhibitors, Zyser, Zytrim, and Zywin-Forte. In addition, the anti-inflammatory drugs, as listed above, may be combined with one or more agents listed above or herein or with other agents known in the art.

[0352] In one embodiment, a drug that reduces, inhibits, prevents and/or ameliorates inflammation, for example, one of the drugs provided above, is delivered to the suprachoroidal space of the eye using the microneedle devices and methods disclosed herein, and is used to treat, prevent and/or ameliorate a disease or disorder selected from arthritis, degenerative arthritis, psoriatic arthritis, arthritic disorders, arthritic pain, arthrosis, autoimmune arthritis, autoimmune diseases, autoimmune disorders, axial spondyloarthritis, chronic prosthetic joint infection, collagen induced arthritis, osteoarthritis, rheumatoid arthritis, senile arthritis, seronegative oligoarthritis of the knee, allergic and autoimmune inflammatory diseases, inflammatory diseases, inflammatory disorders, collagen diseases, discoid Lupus Erythema-tosus, immune deficiencies, immune diseases, immune dis-orders, immunodeficiency diseases, immunodeficiency disorders, immunoglobulin (IgG2) deficiency, immuno-globulin deficiency, Inflammation, Lambert-Eaton myasthe-nia syndrome, polymyositis, dermatomyositis, polyneuritis, post-operative ocular inflammation, polychondritis, spo-radic inclusion body myositis, Systemic Lupus Erythema-tosus, T cell deficiency, TNF-receptor associated periodic syndrome, tropical spastic paraparesis, Wegener Granulo-matosis, X-linked severe combined immunodeficiency dis-ease, Behcet's disease, Crohn's disease, Crohn's Fistula,

cutaneous Lupus Erythematosus, acute inflammation, acute inflammatory edema, adrenocortical insufficiency, cerebral inflammation, chronic lung inflammation, corticoid-respon-sive inflammatory skin disorders, cutaneous inflammation, dermal inflammation, dry skin inflammatory disease, ear edema, ear inflammation, glossitis, inflammatory bowel disease, inflammatory degenerative disease, inflammatory disorders of the eye and/or ear, inflammatory lesions in fungal infections, inflammatory lesions, inflammatory pain, inflammatory skin diseases or disorders, mouth and gum inflammation, mouth and throat inflammation, musculoskel-et al disorders, otitis, pelvic inflammatory disease, perianal inflammation, post operative inflammation, pulmonary inflammation, rectal inflammation, refractory idiopathic inflammatory myopathies, seborrheic dermatitis, swelling, aphthous ulcerations, chronic polyarthritis, juvenile rheuma-toid arthritis, rheumatic diseases, Sjogren's syndrome, ophthalmic for Sjogren's syndrome, transplant rejection, acute allograft rejection, chronic graft rejection, graft versus host disease, humoral rejection in heart transplantation, humoral rejection in kidney transplantation, organ rejection in renal transplantation, solid organ transplant rejection, bronchiolitis obliterans after lung transplantation, rejection of bone marrow transplant, chronic lung transplant rejection, Corneal graft rejection, delayed graft function in kidney transplantation, heart transplant rejection, Homotransplan-tation rejection, immune rejection of hESC-derived thera-peutic grafts, kidney transplant rejection, liver transplant rejection, lung transplant rejection, organ rejection, pancre-atic islet transplantation rejection in type I diabetes, renal transplant rejection and xenograft rejection.

[0353] In one embodiment, the drug delivered to the suprachoroidal space using the microneedle devices and methods disclosed herein treats, prevents, and/or amelio-rates macular degeneration (e.g., age related macular degen-eration, dry age related macular degeneration, exudative age-related macular degeneration, geographic atrophy asso-ciated with age related macular degeneration, neovascular (wet) age-related macular degeneration, neovascular macu-lopathy and age related macular degeneration, occult with no classic choroidal neovascularization (CNV) in age-re-lated macular degeneration, Stargardt's disease, Subfoveal wet Age-Related macular degeneration, and Vitreomacular Adhesion (VMA) associated with Neovascular Age Related macular degeneration). Examples of drugs that treat, prevent and/or ameliorate macular degeneration that can be used in conjunction with the devices and methods described herein include, but are not limited to: A0003, A36 peptide, AAV2-sFLT01, ACE041, ACU02, ACU3223, ACU4429, AdPEDE, aflibercept, AG13958, aganirsen, AGN150998, AGN745, AL39324, AL78898A, AL8309B, ALN-VEG01, alprostadil, AM1101, amyloid beta antibody, anecortave acetate, Anti-VEGFR-2 Alterase, Aptocine, APX003, ARC1905, ARC1905 with Lucentis, ATG3, ATP-binding cassette, sub-family A, member 4 gene, ATXS10, Avastin with Visudyne, AVT101, AVT2, bertilimumab, bevacizumab with verte-porfin, bevasiranib sodium, bevasiranib sodium; with ranibi-zumab, brimonidine tartrate, BVA301, canakinumab, Cand5, Cand5 with Lucentis, CERE140, ciliary neuro-trophic factor, CLT009, CNT02476, collagen monoclonal antibody, complement component 5 aptamer (pegylated), complement component 5 aptamer (pegylated) with ranibi-zumab, complement component C3, complement factor B antibody, complement factor D antibody, copper oxide with

lutein, vitamin C, vitamin E, and zinc oxide, dalantercept, DE109, dexamethasone with ranibizumab and verteporfin, disiteride, DNA damage inducible transcript 4 oligonucleotide, E10030, E10030 with Lucentis, EC400, eculizumab, EGP, EHT204, embryonic stem cells, human stem cells, endoglin monoclonal antibody, EphB4 RTK Inhibitor, EphB4 Soluble Receptor, ESBA1008, ETX6991, Evizon, Eyebar, EyePromise Five, Eyevi, Eylea, F200, FCFD4514S, fenretinide, fluocinolone acetonide, fluocinolone acetonide with ranibizumab, fms-related tyrosine kinase 1 oligonucleotide, fms-related tyrosine kinase 1 oligonucleotide with kinase insert domain receptor 169, fosbretabulin tromethamine, Gamunex, GEM220, GS101, GSK933776, HC31496, Human n-CoDeR, HYB676, IBI-20089 with Lucentis, iCo-008, Icon1, I-Gold, Ilaris, Iluvien, Iluvien with Lucentis, immunoglobulins, integrin alpha5beta1 immunoglobulin fragments, Integrin inhibitor, IRIS Lutein, I-Sense Ocushield, Isonop, isopropyl unoprostone, JPE1375, JSM6427, KH902, LentiVue, LFG316, LP590, LPO1010AM, Lucentis, Lucentis with Visudyne, Lutein ekstra, Lutein with *myrtillus* extract, Lutein with zeaxanthin, M200, M200 with Lucentis, Macugen, MC1101, MCT355, mecamlamine, Microp lasmin, motexafin lutetium, MP0112, NADPH oxidase inhibitors, Neoretina, neurotrophin 4 gene, Nova21012, Nova21013, NT501, NT503, Nutri-Stulln, ocriplasmin, OcuXan, Oftan Macula, Optrin, ORA102 with Avastin, P144, P17, Palomid 529, PAN90806, Panzem, Panzem, PARP Inhibitors, pazopanib hydrochloride, pegaptanib sodium, PF4523655, PG11047, piribedil, platelet-derived growth factor beta polypeptide aptamer (pegylated), platelet-derived growth factor beta polypeptide aptamer (pegylated) with ranibizumab, PLG101, PMX20005, PMX53, POT4, PRS055, PTK787, ranibizumab, ranibizumab with triamcinolone acetonide, ranibizumab with verteporfin, ranibizumab with volociximab, RD27, Rescula, Retaane, retinal pigment epithelial cells, RetinoStat, RG7417, RN6G, RT101, RTU007, SB267268, serpin peptidase inhibitor, clade F, member 1 gene, shark cartilage extract, Shefl, SIR1046, SIR1076, Sirna027, sirolimus, SMTD004, Snelvit, SOD Mimetics, Soliris, sonepcizumab, squalamine lactate, ST602, StarGen, T2TrpRS, TA106, talaporfin sodium, Tauroursodeoxycholic acid, TG100801, TKI, TLCx99, TRC093, TRC105, triamcinolone acetonide with verteporfin, Trivastal Retard, TT30, Ursa, ursodiol, Vangiolum, VAR10200, vascular endothelial growth factor antibody, vascular endothelial growth factor B, vascular endothelial growth factor kinoid, vascular endothelial growth factor oligonucleotide, VAST Compounds, vatalanib, VEGF Inhibitor, verteporfin, Visudyne, Visudyne with Lucentis and dexamethasone, Visudyne with triamcinolone acetonide, Vivis, volociximab, Votrient, XV615, zeaxanthin, ZFP TF, zinc-monocysteine and Zybrestat. In one embodiment, one or more of the macular degeneration treating drugs described above is combined with one or more agents listed above or herein or with other agents known in the art.

[0354] In one embodiment, the methods and devices provided herein are used to delivery triamcinolone or triamcinolone acetonide to the suprachoroidal space of an eye of a patient in need thereof. In a further embodiment, the triamcinolone or triamcinolone acetonide is delivered for the treatment of sympathetic ophthalmia, temporal arteritis, uveitis and/or ocular inflammatory conditions. In one embodiment, triamcinolone or triamcinolone acetonide is

delivered to the suprachoroidal space of the eye in a patient in need of treatment of sympathetic ophthalmia with the methods and devices described herein. In another embodiment, triamcinolone or triamcinolone acetonide is delivered to the suprachoroidal space of the eye in a patient in need of treatment of temporal arteritis with the methods and devices described herein. In yet another embodiment, triamcinolone or triamcinolone acetonide is delivered to the suprachoroidal space of the eye in a patient in need of treatment of uveitis, with the methods and devices described herein. In another embodiment, triamcinolone or triamcinolone acetonide is delivered to the suprachoroidal space of the eye in a patient in need of treatment of one or more ocular inflammatory conditions, with the methods and devices described herein.

[0355] The triamcinolone composition provided herein, in one embodiment, is a suspension comprising microparticles or nanoparticles of triamcinolone or triamcinolone acetonide. The microparticles, in one embodiment, have a D_{50} of about 3 μm or less. In a further embodiment, the D_{50} is about 2 μm . In another embodiment, the D_{50} is about 2 μm or less. In even another embodiment, the D_{50} is about 1000 nm or less. The microparticles, in one embodiment, have a D_{99} of about 10 μm or less. In another embodiment, the D_{99} is about 10 μm . In another embodiment, the D_{99} is less than about 10 μm or less than about 9 μm or less.

[0356] In one embodiment, the triamcinolone composition comprises triamcinolone microparticles. In a further embodiment, the composition comprises polysorbate 80. In another embodiment, the triamcinolone composition comprises one or more of CaCl_2 , MgCl_2 , sodium acetate and sodium citrate. In one embodiment, the composition comprises polysorbate 80 at a w/v % of 0.02% or about 0.02%, 0.015% or about 0.015%.

[0357] In certain embodiments the drug delivered to ocular tissues using the microneedle devices and methods disclosed herein treats, prevents, and/or ameliorates fibrosis (e.g. myelofibrosis, fibrosis in diabetic nephropathy, cystic fibrosis, scarring, and skin fibrosis).

[0358] In one embodiment, a drug that treats, prevents and/or ameliorates fibrosis is used in conjunction with the devices and methods described herein, and is delivered to the suprachoroidal space of the eye. In a further embodiment, the drug is Actimmune with Pirfenidone, ACUHTRO28, AlphaVBeta5, aminobenzoate potassium, amyloid P, ANG1122, ANG1170, ANG3062, ANG3281, ANG3298, ANG4011, Anti-CTGF RNAi, Aplidin, *astragalus membranaceus* extract with *salvia* and *schisandra chinensis*, atherosclerotic plaque blocker, Azol, AZX100, BB3, connective tissue growth factor antibody, CT140, danazol, Esbriet, EXC001, EXC002, EXC003, EXC004, EXC005, F647, FG3019, Fibrocorin, Follistatin, FT011, Galectin-3 inhibitors, GKT137831, GMCT01, GMCT02, GRMD01, GRMD02, GRN510, Heberon Alfa R, interferon alfa-2b, interferon gamma-1b with pirfenidone, ITMN520, JKB119, JKB121, JKB122, KRX168, LPA1 receptor antagonist, MGN4220, MIA2, microRNA 29a oligonucleotide, MMI0100, noscapine, PBI4050, PBI4419, PDGFR inhibitor, PF-06473871, PGN0052, Pirespa, Pirfenex, pirfenidone, plitidepsin, PRM151, Px102, PYN17, PYN22 with PYN17, Relivergen, rhPTX2 Fusion Proteins, RXI109, secretin, STX100, TGF-beta Inhibitor, transforming growth factor, beta receptor 2 oligonucleotide, VA999260 or XV615. In one embodiment, one or more of the fibrosis treating drugs

described above is combined with one or more agents listed above or herein or with other agents known in the art.

[0359] In one embodiment, a drug that treats, prevents and/or ameliorates diabetic macular edema is used in conjunction with the devices and methods described herein, and is delivered to the suprachoroidal space of the eye. In a further embodiment, the drug is AKB9778, bevasiranib sodium, Candy, choline fenofibrate, Cortitect, c-raf 2-methoxyethyl phosphorothioate oligonucleotide, DE109, dexamethasone, DNA damage inducible transcript 4 oligonucleotide, FOV2304, iCo007, KH902, MP0112, NCX434, Optina, Ozurdex, PF4523655, SAR1118, sirolimus, SK0503 or TriLipix. In one embodiment, one or more of the diabetic macular edema treating drugs described above is combined with one or more agents listed above or herein or with other agents known in the art.

[0360] In one embodiment, a drug that treats, prevents and/or ameliorates macular edema is used in conjunction with the devices and methods described herein, and is delivered to the suprachoroidal space of the eye. In a further embodiment, the drug is denufosol tetrasodium, dexamethasone, ecallantide, pegaptanib sodium, ranibizumab or triamcinolone. In addition, the drugs delivered to ocular tissues using the microneedle devices and methods disclosed herein which treat, prevent, and/or ameliorate macular edema, as listed above, may be combined with one or more agents listed above or herein or with other agents known in the art.

[0361] In one embodiment, a drug that treats, prevents and/or ameliorates ocular hypertension is used in conjunction with the devices and methods described herein and is delivered to the suprachoroidal space of the eye. In a further embodiment, the drug is 2-MeS-beta gamma-CC12-ATP, Aceta Diazol, acetazolamide, Aristomol, Arteoptic, AZD4017, Betalmic, betaxolol hydrochloride, Betimol, Betoptic S, Brimodin, Brimonal, brimonidine, brimonidine tartrate, Brinidin, Calte, carteolol hydrochloride, Cosopt, CS088, DE092, DE104, DE111, dorzolamide, dorzolamide hydrochloride, Dorzolamide hydrochloride with Timolol maleate, Driptimol, Fortinol, Glaumol, Hypadil, Ismotec, isopropyl unoprostone, isosorbide, Latalux, latanoprost, Latanoprost with Timolol maleate, levobunolol hydrochloride, Lotensin, Mannigen, mannitol, metipranolol, mifepristone, Mikelan, Minims Metipranolol, Mirol, nipradilol, Nor Tenz, Ocupress, olmesartan, Ophtalol, pilocarpine nitrate, Piobaj, Rescula, RU486, Rysmon TG, SAD448, Saftutan, Shemol, Taflotan, tafluprost, tafluprost with timolol, Thiaboot, Timocomod, timolol, Timolol Actavis, timolol hemihydrate, timolol maleate, Travast, travoprost, Unilat, Xalacom, Xalatan or Zomilol. In addition, the drugs delivered to ocular tissues using the microneedle devices and methods disclosed herein which treat, prevent, and/or ameliorate ocular hypertension, as listed above, may be combined with one or more agents listed above or herein or with other agents known in the art.

[0362] In certain embodiments one or more drugs may be delivered to ocular tissues and/or into the suprachoroidal space via the systems and devices described herein. Delivery of one or more drugs into the suprachoroidal space using the microneedle device described herein may be accomplished by using one or more microneedles. In addition, combinations of one of more drugs may be delivered to the suprachoroidal space using the microneedle device described herein in combination with delivery of one or more drugs via intravitreal (IVT) administration (e.g., intravitreal injection,

intravitreal implant or eye drops). Methods of IVT administration are well known in the art. Examples of drugs that can be administered via IVT include, but are not limited to: A0003, A0006, Acedolone, AdPEDE, aflibercept, AG13958, aganirsen, AGN208397, AKB9778, AL78898A, amyloid P, Angiogenesis Inhibitor Gene Therapy, ARC1905, Aurocort, bevasiranib sodium, brimonidine, Brimonidine, brimonidine tartrate, bromfenac sodium, Cand5, CERE140, Ciganclor, CLT001, CLT003, CLT004, CLT005, complement component 5 aptamer (pegylated), complement factor D antibody, Cortitect, c-raf 2-methoxyethyl phosphorothioate oligonucleotide, cyclosporine, triamcinolone, DE109, denufosol tetrasodium, dexamethasone, dexamethasone phosphate, disiteride, DNA damage inducible transcript 4 oligonucleotide, E10030, ecallantide, EG3306, Eos013, ESBA1008, ESBA105, Eylea, FCFD4514S, fluocinolone acetonide, fms-related tyrosine kinase 1 oligonucleotide, fomivirsen sodium, fosbretabulin tromethamine, FOV2301, FOV2501, ganciclovir, ganciclovir sodium, GS101, GS156, hyaluronidase, IBI20089, iCo007, Iluvien, INS37217, Isonop, JSM6427, Kalbitor, KH902, lerdelimumab, LFG316, Lucentis, M200, Macugen, Makyueido, Microplasmin, MK0140, MP0112, NCX434, neurotrophin 4 gene, OC10X, ocriplasmin, ORA102, Ozurdex, P144, P17, Palomid 529, pazopanib hydrochloride, pegaptanib sodium, Plasma Kallikrein Inhibitors, platelet-derived growth factor beta polypeptide aptamer (pegylated), POT4, PRM167, PRS055, QP11007, ranibizumab, resveratrol, Retilone, retinal pigment epithelium-specific protein 65 kDa gene, Retisert, rod derived cone viability factor, RPE65 Gene Therapy, RPGR Gene Therapy, RTP801, Sd-rxRNA, serpin peptidase inhibitor clade F member 1 gene, Sirna027, sirolimus, sonepcizumab, SRT501, STP601, TG100948, Trabio, triamcinolone, triamcinolone acetonide, Trivaris, tumor necrosis factor antibody, VEGF/rGel-Op, verteporfin, Visudyne, Vitrase, Vitrasert, Vitravene, Vitreals, volociximab, Votrient, XG102, Xibrom, XV615, and Zybrestat. Accordingly, the methods of the present invention include administering via IVT one or more of the drugs listed above in combination with one or more drugs disclosed herein administered into the suprachoroidal space using the microneedle device described herein.

[0363] In one embodiment, the drug is formulated for storage and delivery via the microneedle device described herein. The “drug formulation” is a formulation of a drug, which typically includes one or more pharmaceutically acceptable excipient materials known in the art. The term “excipient” refers to any non-active ingredient of the formulation intended to facilitate handling, stability, dispersibility, wettability, release kinetics, and/or injection of the drug. In one embodiment, the excipient may include or consist of water or saline.

[0364] In one embodiment, the fluid drug formulation includes microparticles or nanoparticles, each of which can include at least one drug. Desirably, the microparticles or nanoparticles provide for the controlled release of drug into the ocular tissue. As used herein, the term “microparticle” encompasses microspheres, microcapsules, microparticles, and beads, having a number average diameter of 1 to 100 μm , most preferably 1 to 25 μm . The term “nanoparticles” are particles having a number average diameter of 1 to 1000 nm. Microparticles may or may not be spherical in shape. “Microcapsules” are defined as microparticles having an outer shell surrounding a core of another material. The core

can be liquid, gel, solid, gas, or a combination thereof. In one case, the microcapsule may be a “microbubble” having an outer shell surrounding a core of gas, wherein the drug is disposed on the surface of the outer shell, in the outer shell itself, or in the core. Microbubbles may respond to acoustic vibrations as known in the art for diagnosis and/or can be used to burst the microbubble to release its payload at/into a select ocular tissue site. “Microspheres” can be solid spheres, can be porous and include a sponge-like or honeycomb structure formed by pores or voids in a matrix material or shell, or can include multiple discrete voids in a matrix material or shell. The microparticle or nanoparticles may further include a matrix material. The shell or matrix material may be a polymer, amino acid, saccharide, or other material known in the art of microencapsulation.

[0365] The drug-containing microparticles or nanoparticles may be suspended in an aqueous or non-aqueous liquid vehicle. The liquid vehicle may be a pharmaceutically acceptable aqueous solution, and optionally may further include a surfactant. The microparticles or nanoparticles of drug themselves may include an excipient material, such as a polymer, a polysaccharide, a surfactant, etc., which are known in the art to control the kinetics of drug release from particles.

[0366] In one embodiment, the fluid drug formulation further includes an agent effective to degrade collagen or GAG fibers in the sclera, which may enhance penetration/release of the drug into the ocular tissues. This agent may be, for example, an enzyme, such as hyaluronidase, a collagenase, or a combination thereof. In a variation of this method, the enzyme is administered to the ocular tissue in a separate step from—preceding or following—infusion of the drug. The enzyme and drug are administered at the same site.

[0367] In another embodiment, the drug formulation is one that undergoes a phase change upon administration. For instance, a liquid drug formulation may be injected through hollow microneedles into the suprachoroidal space, where it then gels and the drug diffuses out from the gel for controlled release.

[0368] While the embodiments and methods herein describe delivering a medicament to a target tissue, the embodiments described herein can be configured to facilitate a biopsy procedure and/or removal of a substance from a target location.

[0369] While the embodiments have been described above in use on ocular tissue, in some instances, the embodiments and methods described herein can be used on any other suitable bodily tissue. For example, in some instances, the use of an adjustable length needle can be beneficial in conjunction with standard phlebotomy techniques during drug infusion and/or blood draw from a vein. Thus, while the embodiments and methods are specifically described above in use on ocular tissue, it should be understood that the embodiments and methods have been presented by way of example only, and not limitation.

[0370] While various embodiments have been described above, it should be understood that they have been presented by way of example only, and not limitation. Where methods described above indicate certain events occurring in certain order, the ordering of certain events may be modified. Additionally, certain of the events may be performed concurrently in a parallel process when possible, as well as performed sequentially as described above.

[0371] Although the systems and methods are shown and described herein as providing for delivery of medicaments in the suprachoroidal space, in other embodiments, the systems and the methods described herein can be applicable for delivery of any suitable therapeutic substance to any portion of the eye, such as, the cornea, the retinal area or the vitreous. In other embodiments, any of the systems, methods and devices described herein can be used to deliver any suitable therapeutic substance to any desired target tissue (including non-ocular tissue).

[0372] Where schematics and/or embodiments described above indicate certain components arranged in certain orientations or positions, the arrangement of components may be modified. Similarly, where methods and/or events described above indicate certain events and/or procedures occurring in certain order, the ordering of certain events and/or procedures may be modified. While the embodiments have been particularly shown and described, it will be understood that various changes in form and details may be made.

[0373] For example, although the injector assembly **2100** is shown and described as including a biasing member **2146** configured to exert a force to move the actuator **2320** to assist in the delivery of a medicament, in other embodiments, the injector assembly **2100** (and any other injector assemblies shown and described herein) can include any suitable mechanism for producing a force to move the actuator **2320**. For example, in some embodiments, an injector assembly can include a stored energy member, such as a propellant canister, a compressed gas container, a magnetic energy storage member, an electronic energy storage member (e.g., a battery or a capacitor) or the like.

[0374] Although various embodiments have been described as having particular features and/or combinations of components, other embodiments are possible having a combination of any features and/or components from any of embodiments as discussed above. For example, while the extraction member **21280** is described as being included in the system **21000** and configured to be coupled to the medicament container **21310**, in some embodiments, the device **2000**, **3000**, or any other device described herein can be used with and/or include the extraction member **21280**, or any other extraction member described herein. Furthermore, while the needle assembly **3200** is shown as being included in the system **3000**, in some embodiments, the system **2000**, **21000**, or any other medical injector described herein can also include the needle assembly **3200** or any other needle assembly described herein. Moreover, while the injection assembly **2100** is described as included with the system **2000**, in some embodiments, the injection assembly **2100** can also be included in the system **3000**, **21000** or any other system described herein. Similarly, any of the systems described herein (e.g., the system **2000**, **3000**, or **21000**) can include or configured to be coupled to a hub that includes a convex distal end surface such as, for example, the hub **7270**, **8270**, or **9270**.

1. A method, comprising:

inserting a distal end portion of a puncture member of a medical injector into a target tissue to define a delivery passageway within the target tissue and such that a distal end surface of a hub of the medical injector is in contact with a target surface of the target tissue;

exerting a force on an actuation rod of the medical injector when the distal end surface of the hub is in contact with

the target surface, the force having a magnitude of less than a threshold value, the force produces movement within the medical injector of both an adjustment member and the puncture member when the distal end portion of the puncture member is disposed within a first region of the target tissue, the puncture member being fixedly coupled to the adjustment member, movement of both the adjustment member and the puncture member within the medical injector being limited when the distal end portion of the puncture member is disposed within a second region of the target tissue; and conveying, in response to the exerting, a substance from the medicament container into the target tissue via the puncture member when the distal end portion of the puncture member is disposed within the second region of the target tissue.

2. The method of claim 1, wherein the force is insufficient to convey the substance from the medicament container into the target tissue via the puncture member when the distal end portion of the puncture member is disposed within the first region of the target tissue.

3. The method of claim 1, wherein the exerting the force on the actuation rod includes causing movement within the medical injector of the puncture member such that the distal end portion of the puncture member is moved from within the first region of the target tissue to the second region of the target tissue.

4. The method of claim 1, wherein the force is sufficient to overcome a backpressure of the second region such that movement of the distal end portion of the puncture member relative to the hub is reduced and the substance is conveyed into the target tissue when the distal end portion of the puncture member moves from the first region to the second region.

5. The method of claim 1, wherein the adjustment member is moved within the medical injector via hydraulics.

6. The method of claim 1, wherein the threshold value is about 6 N.

7. The method of claim 1, wherein:

the inserting is performed such that a centerline of the delivery passageway and a surface line tangential to the target surface defines an angle of entry of between about 75 degrees and about 105 degrees.

8. The method of claim 1, wherein the target tissue is an eye and the target surface is any one of a conjunctiva of the eye or a sclera of the eye, the substance being at least one of a VEGF, a VEGF inhibitor, a PDGFR inhibitor, or a combination thereof.

9. The method of claim 1, wherein:

the target tissue is an eye, the target surface is any one of a conjunctiva of the eye or a sclera of the eye, the second region includes at least one of a suprachoroidal space, a lower portion of the sclera, a choroid of the eye, a subretinal space of the eye, or a retina of the eye.

10. The method of claim 9, wherein the first region is an upper portion of a sclera of the eye.

11. The method of claim 1, wherein the inserting includes deforming the target surface with the distal end surface of the hub.

12. The method of claim 1, wherein the distal end surface of the hub includes a sealing portion configured to define a fluid-tight seal with the target surface, the sealing portion being symmetrical about a centerline of the puncture member.

13. The method of claim 1, wherein the inserting is performed before the exerting is performed.

14. The method of claim 1, wherein the exerting the force on the actuation rod causes the actuation rod, the adjustment member, and the puncture member to move linearly within the medical injector when the distal end portion of the puncture member is disposed within the first region of the target tissue.

15. The method of claim 14, wherein the exerting the force on the actuation rod causes the actuation rod to move linearly within the medical injector when the distal end portion of the puncture member is disposed within the second region of the target tissue such that the substance from the medicament container is conveyed into the target tissue via the puncture member.

16. The method of 1, further comprising:

during the exerting the force on the actuation rod, maintaining a force on the medical injector such that the hub forms a substantially fluid-tight seal with the target surface.

17. A method, comprising:

inserting a distal end portion of a puncture member of a medical injector into a target tissue to define a delivery passageway within the target tissue;

applying a force to a hub of the medical injector such that a distal end surface of the hub contacts a target surface of the target tissue to fluidically isolate the delivery passageway; and

while maintaining the force, moving the puncture member relative to the hub such that a distal end portion of the puncture member moves from a first region within the target tissue to a second region within the target tissue, a substance from a medicament container within the medical injector being conveyed to the target tissue in response to the distal end portion of the puncture member being disposed in the second region and not the first region.

18. The method of claim 17, wherein the adjustment member is moved within the medical injector via hydraulics.

19. The method of claim 17, wherein the force is less than about 6 N.

20. The method of claim 17, wherein:

the inserting is performed such that a centerline of the delivery passageway and a surface line tangent to the target surface defines an angle of entry of between about 75 degrees and about 105 degrees.

21. The method of claim 17, wherein the target tissue is an eye and the target surface is any one of a conjunctiva of the eye or a sclera of the eye, the substance being at least one of a VEGF, a VEGF inhibitor, a PDGFR inhibitor, or a combination thereof.

22. The method of claim 17, wherein:

the target tissue is an eye, the target surface is any one of a conjunctiva of the eye or a sclera of the eye, the second region includes at least one of a suprachoroidal space, a lower portion of the sclera, a choroid of the eye, a subretinal space of the eye, or a retina of the eye.

23. The method of claim 22, wherein the first region is an upper portion of a sclera of the eye.

24. A method, comprising:

inserting a distal end portion of a puncture member of a medical injector into a first region of a target tissue to define a delivery passageway within the target tissue, the puncture member placing a substance within a

medicament container of the medical injector in fluid communication with the first region, an adjustment member being movably disposed within the medical injector and forming a substantially fluid-tight seal with a side wall of medical injector;

after the inserting and with the distal end portion of the puncture member disposed in the first region of the target tissue, exerting a force on the adjustment member such that the force in conjunction with the substantially fluid-tight seal produces movement of the distal end portion of the puncture member from the first region to a second region of the target tissue; and

conveying, in response to the exerting, a substance from the medicament container into the target tissue via the puncture member when the distal end portion of the puncture member is disposed within the second region of the target tissue.

25. The method of claim **24**, wherein the force is insufficient to overcome a backpressure of the first region to convey the medicament into the target tissue via the puncture member when the distal end portion of the puncture member is disposed within the first region, the force being sufficient to overcome a frictional force formed by the

substantially fluid-tight seal such that the force produces distal movement of the adjustment member within the medical injector.

26. The method of claim **25**, wherein the force is sufficient to overcome a backpressure of the second region to convey the medicament into the target tissue via the puncture member when the distal end portion of the puncture member is disposed within the second region.

27. The method of claim **24**, wherein the adjustment member is moved within the medical injector via hydraulics.

28. The method of claim **24**, wherein:

the target tissue is an eye, the target surface is any one of a conjunctiva of the eye or a sclera of the eye, the second region includes at least one of a suprachoroidal space, a lower portion of the sclera, a choroid of the eye, a subretinal space of the eye, or a retina of the eye.

29. The method of claim **28**, wherein the first region is an upper portion of a sclera of the eye.

30. The method of **24**, further comprising:

during the exerting the force on the actuation rod, maintaining a force on the medical injector such that the hub forms a substantially fluid-tight seal with the target surface.

* * * * *