



US 20210095897A1

(19) **United States**

(12) **Patent Application Publication** (10) **Pub. No.: US 2021/0095897 A1**

KUMAKURA et al.

(43) **Pub. Date: Apr. 1, 2021**

(54) **HEAT SOURCE UNIT AND REFRIGERATION CYCLE APPARATUS**

Oct. 5, 2018	(JP)	PCT/JP2018/037483
Oct. 17, 2018	(JP)	PCT/JP2018/038746
Oct. 17, 2018	(JP)	PCT/JP2018/038747
Oct. 17, 2018	(JP)	PCT/JP2018/038748
Oct. 17, 2018	(JP)	PCT/JP2018/038749

(71) Applicant: **DAIKIN INDUSTRIES, LTD.**, Osaka (JP)

(72) Inventors: **Eiji KUMAKURA**, Osaka (JP); **Takuro YAMADA**, Osaka (JP); **Atsushi YOSHIMI**, Osaka (JP); **Ikuhiro IWATA**, Osaka (JP); **Mitsushi ITANO**, Osaka (JP); **Daisuke KARUBE**, Osaka (JP); **Yuuki YOTSUMOTO**, Osaka (JP); **Kazuhiro TAKAHASHI**, Osaka (JP); **Tatsuya TAKAKUWA**, Osaka (JP); **Yuzo KOMATSU**, Osaka (JP); **Shun OHKUBO**, Osaka (JP)

Publication Classification

(51) **Int. Cl.**
F25B 1/00 (2006.01)
C09K 5/04 (2006.01)
F24F 5/00 (2006.01)

(52) **U.S. Cl.**
 CPC *F25B 1/00* (2013.01); *C09K 5/045* (2013.01); *F24F 5/001* (2013.01); *F25B 2500/07* (2013.01); *C09K 2205/43* (2013.01); *C09K 2205/128* (2013.01); *C09K 2205/126* (2013.01)

(73) Assignee: **DAIKIN INDUSTRIES, LTD.**, Osaka (JP)

(21) Appl. No.: **16/954,745**

(22) PCT Filed: **Dec. 17, 2018**

(86) PCT No.: **PCT/JP2018/046428**

§ 371 (c)(1),

(2) Date: **Jun. 17, 2020**

(30) **Foreign Application Priority Data**

Dec. 18, 2017	(JP)	2017-242183
Dec. 18, 2017	(JP)	2017-242185
Dec. 18, 2017	(JP)	2017-242186
Dec. 18, 2017	(JP)	2017-242187

(57) **ABSTRACT**

A heat source unit and a refrigeration cycle apparatus that are able to reduce damage to a connection pipe when a refrigerant containing at least 1,2-difluoroethylene is used are provided. An outdoor unit (20) that is connected via a liquid-side connection pipe (6) and a gas-side connection pipe (5) to an indoor unit (30) including an indoor heat exchanger (31) and that is a component of an air conditioner (1) includes a compressor (21) and an outdoor heat exchanger (23). A refrigerant containing at least 1,2-difluoroethylene is used as a refrigerant. A design pressure of the outdoor unit (20) is lower than 1.5 times a design pressure of each of the liquid-side connection pipe (6) and the gas-side connection pipe (5).




Fig. 1




Fig. 2




Fig. 4




Fig. 5




Fig. 6




Fig. 7




Fig. 8




Fig. 9




Fig. 10




Fig. 11




Fig. 12




Fig. 13




Fig. 14





Fig. 15






FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21

HEAT SOURCE UNIT AND REFRIGERATION CYCLE APPARATUS

TECHNICAL FIELD

[0001] The present disclosure relates to a heat source unit and a refrigeration cycle apparatus.

BACKGROUND ART

[0002] Hitherto, in refrigeration cycle apparatuses, such as air conditioners, R410A is often used as a refrigerant. R410A is a two-component mixed refrigerant of difluoromethane (CH₂F₂; HFC-32, or R32) and pentafluoroethane (C₂HF₅; HFC-125, or R125) and is a pseudo-azeotropic composition.

[0003] However, the global warming potential (GWP) of R410A is 2088, and, in recent years, because of growing concern about global warming, R32 that is a refrigerant having a lower GWP is used more often.

[0004] For this reason, for example, PTL 1 (International Publication No. 2015/141678) suggests various types of low-GWP refrigerant mixtures as alternatives to R410A.

SUMMARY OF THE INVENTION

Technical Problem

[0005] However, for a case where a refrigerant containing at least 1,2-difluoroethylene is used as a refrigerant having a sufficiently low GWP, using a refrigeration cycle apparatus or its component device having any pressure resistance strength is not considered or suggested at all.

[0006] For example, for a refrigeration cycle apparatus in which a refrigerant, such as R410A and R32 that are often used so far, when existing connection pipes are used, and the refrigerant is replaced with a refrigerant containing at least 1,2-difluoroethylene, there are concerns about occurrence of damage to the existing connection pipes if a device that is a component of the refrigeration cycle apparatus operates under a pressure exceeding the withstanding pressure of the existing connection pipes.

[0007] The contents of the present disclosure are described in view of the above-described points, and it is an object to provide a heat source unit and a refrigeration cycle apparatus that are able to reduce damage to a connection pipe when a refrigerant containing at least 1,2-difluoroethylene is used.

Solution to Problem

[0008] A heat source unit according to a first aspect includes a compressor and a heat source-side heat exchanger. The heat source unit is connected via a connection pipe to a service unit and is a component of a refrigeration cycle apparatus. The service unit includes a service-side heat exchanger. In the heat source unit, a refrigerant containing at least 1,2-difluoroethylene is used as a refrigerant. A design pressure of the heat source unit is lower than 1.5 times a design pressure of the connection pipe.

[0009] A “design pressure” means a gauge pressure (hereinafter, the same applies).

[0010] Since the heat source unit has a design pressure lower than 1.5 times the design pressure of the connection pipe, the heat source unit is operated at a pressure lower than a withstanding pressure of the connection pipe. Therefore,

even when the heat source unit is connected to the connection pipe and used, damage to the connection pipe can be reduced.

[0011] A refrigeration cycle apparatus according to a second aspect includes a service unit, a connection pipe, and the heat source unit of the first aspect. In the refrigeration cycle apparatus, a refrigerant containing at least 1,2-difluoroethylene is used. The design pressure of the heat source unit is equivalent to a design pressure in a refrigeration cycle apparatus in which refrigerant R22 or refrigerant R407C is used.

[0012] Here, the “equivalent” pressure preferably falls within the range of $\pm 10\%$ of the design pressure in a refrigeration cycle apparatus in which refrigerant R22 or refrigerant R407C is used.

[0013] With this refrigeration cycle apparatus, even when a refrigeration cycle apparatus in which refrigerant R22 or refrigerant R407C is used is modified to a refrigeration cycle apparatus in which a refrigerant containing at least 1,2-difluoroethylene is used while the original connection pipe is used, damage to the connection pipe can be reduced when the design pressure of the heat source unit, equivalent to or the same as that of the pre-modified one, is used.

[0014] A refrigeration cycle apparatus according to a third aspect is the refrigeration cycle apparatus of the second aspect, and the design pressure of the heat source unit is higher than or equal to 3.0 MPa and lower than or equal to 3.7 MPa.

[0015] A refrigeration cycle apparatus according to a fourth aspect includes a service unit, a connection pipe, and the heat source unit of the first aspect. In the refrigeration cycle apparatus, a refrigerant containing at least 1,2-difluoroethylene is used. The design pressure of the heat source unit is equivalent to a design pressure in a refrigeration cycle apparatus in which refrigerant R410A or refrigerant R32 is used.

[0016] Here, the “equivalent” pressure preferably falls within the range of $\pm 10\%$ of the design pressure in a refrigeration cycle apparatus in which refrigerant R410A or refrigerant R32 is used.

[0017] With this refrigeration cycle apparatus, even when a refrigeration cycle apparatus in which refrigerant R410A or refrigerant R32 is used is modified to a refrigeration cycle apparatus in which a refrigerant containing at least 1,2-difluoroethylene is used while the original connection pipe is used, damage to the connection pipe can be reduced when the design pressure of the heat source unit, equivalent to or the same as that of the pre-modified one, is used.

[0018] A refrigeration cycle apparatus according to a fifth aspect is the refrigeration cycle apparatus of the fourth aspect, and the design pressure of the heat source unit is higher than or equal to 4.0 MPa and lower than or equal to 4.8 MPa.

[0019] A refrigeration cycle apparatus according to a sixth aspect includes a heat source unit, a service unit, and a connection pipe. The heat source unit includes a compressor and a heat source-side heat exchanger. The service unit includes a service-side heat exchanger. The connection pipe connects the heat source unit and the service unit. In the refrigeration cycle apparatus, a refrigerant containing at least 1,2-difluoroethylene is used. A design pressure of the heat source unit is equivalent to a design pressure in a refrigeration cycle apparatus in which refrigerant R22 or refrigerant R407C is used.

[0020] Here, the “equivalent” pressure preferably falls within the range of $\pm 10\%$ of the design pressure in a refrigeration cycle apparatus in which refrigerant R22 or refrigerant R407C is used.

[0021] With this refrigeration cycle apparatus, even when a refrigeration cycle apparatus in which refrigerant R22 or refrigerant R407C is used is modified to a refrigeration cycle apparatus in which a refrigerant containing at least 1,2-difluoroethylene is used while the original connection pipe is used, damage to the connection pipe can be reduced when the design pressure of the heat source unit, equivalent to or the same as that of the pre-modified one, is used.

[0022] A refrigeration cycle apparatus according to a seventh aspect is the refrigeration cycle apparatus of the sixth aspect, and the design pressure of the heat source unit is higher than or equal to 3.0 MPa and lower than or equal to 3.7 MPa.

[0023] A refrigeration cycle apparatus according to an eighth aspect includes a heat source unit, a service unit, and a connection pipe. The heat source unit includes a compressor and a heat source-side heat exchanger. The service unit includes a service-side heat exchanger. The connection pipe connects the heat source unit and the service unit. In the refrigeration cycle apparatus, a refrigerant containing at least 1,2-difluoroethylene is used. A design pressure of the heat source unit is equivalent to a design pressure in a refrigeration cycle apparatus in which refrigerant R410A or refrigerant R32 is used.

[0024] Here, the “equivalent” pressure preferably falls within the range of $\pm 10\%$ of the design pressure in a refrigeration cycle apparatus in which refrigerant R410A or refrigerant R32 is used.

[0025] With this refrigeration cycle apparatus, even when a refrigeration cycle apparatus in which refrigerant R410A or refrigerant R32 is used is modified to a refrigeration cycle apparatus in which a refrigerant containing at least 1,2-difluoroethylene is used while the original connection pipe is used, damage to the connection pipe can be reduced when the design pressure of the heat source unit, equivalent to or the same as that of the pre-modified one, is used.

[0026] A refrigeration cycle apparatus according to a ninth aspect is the refrigeration cycle apparatus of the eighth aspect, and the design pressure of the heat source unit is higher than or equal to 4.0 MPa and lower than or equal to 4.8 MPa.

[0027] A heat source unit according to a tenth aspect includes a compressor, a heat source-side heat exchanger, and a control device. The heat source unit is connected via a connection pipe to a service unit and is a component of a refrigeration cycle apparatus. The service unit includes a service-side heat exchanger. In the heat source unit, a refrigerant containing at least 1,2-difluoroethylene is used as a refrigerant. The control device is configured to set or be able to set an upper limit of a controlled pressure of the refrigerant such that the upper limit is lower than 1.5 times a design pressure of the connection pipe.

[0028] The heat source unit is configured to set or be able to set an upper limit of a controlled pressure of the refrigerant made by the control device such that the upper limit is lower than 1.5 times a design pressure of the connection pipe. Therefore, even when the heat source unit is connected to the connection pipe and used, operation control is ensured

at a pressure lower than the withstanding pressure of the connection pipe, so damage to the connection pipe can be reduced.

[0029] A refrigeration cycle apparatus according to an eleventh aspect includes a service unit, a connection pipe, and the heat source unit of the tenth aspect. In the refrigeration cycle apparatus, a refrigerant containing at least 1,2-difluoroethylene is used. The control device is configured to set or be able to set an upper limit of a controlled pressure of the refrigerant such that the upper limit is equivalent to an upper limit of a controlled pressure in a refrigeration cycle apparatus in which refrigerant R22 or refrigerant R407C is used.

[0030] Here, the “equivalent” pressure preferably falls within the range of $\pm 10\%$ of the controlled pressure in a refrigeration cycle apparatus in which refrigerant R22 or refrigerant R407C is used.

[0031] With this refrigeration cycle apparatus, even when a refrigeration cycle apparatus in which refrigerant R22 or refrigerant R407C is used is modified to a refrigeration cycle apparatus in which a refrigerant containing at least 1,2-difluoroethylene is used while the original connection pipe is used, the refrigeration cycle apparatus is configured to set or be able to set the upper limit of the controlled pressure of the refrigerant by the control device of the heat source unit such that the upper limit is equal to or the same as the upper limit of the controlled pressure of the heat source unit in a refrigeration cycle apparatus in which refrigerant R22 or refrigerant R407C is used, so damage to the connection pipe can be reduced.

[0032] A refrigeration cycle apparatus according to a twelfth aspect is the refrigeration cycle apparatus of the eleventh aspect, and the upper limit of the controlled pressure is set to be higher than or equal to 3.0 MPa and lower than or equal to 3.7 MPa.

[0033] A refrigeration cycle apparatus according to a thirteenth aspect includes a service unit, a connection pipe, and the heat source unit of the tenth aspect. In the refrigeration cycle apparatus, a refrigerant containing at least 1,2-difluoroethylene is used. The control device is configured to set or be able to set an upper limit of a controlled pressure of the refrigerant such that the upper limit is equivalent to an upper limit of a controlled pressure in a refrigeration cycle apparatus in which refrigerant R410A or refrigerant R32 is used.

[0034] Here, the “equivalent” pressure preferably falls within the range of $\pm 10\%$ of the controlled pressure in a refrigeration cycle apparatus in which refrigerant R410A or refrigerant R32 is used.

[0035] With this refrigeration cycle apparatus, even when a refrigeration cycle apparatus in which refrigerant R410A or refrigerant R32 is used is modified to a refrigeration cycle apparatus in which a refrigerant containing at least 1,2-difluoroethylene is used while the original connection pipe is used, the refrigeration cycle apparatus is configured to set or be able to set the upper limit of the controlled pressure of the refrigerant by the control device of the heat source unit such that the upper limit is equal to or the same as the upper limit of the controlled pressure of the heat source unit in a refrigeration cycle apparatus in which refrigerant R410A or refrigerant R32 is used, so damage to the connection pipe can be reduced.

[0036] A refrigeration cycle apparatus according to a fourteenth aspect is the refrigeration cycle apparatus of the

thirteenth aspect, and the upper limit of the controlled pressure is set to be higher than or equal to 4.0 MPa and lower than or equal to 4.8 MPa.

[0037] A refrigeration cycle apparatus according to a fifteenth aspect includes a heat source unit, a service unit, a connection pipe, and a control device. The heat source unit includes a compressor and a heat source-side heat exchanger. The service unit includes a service-side heat exchanger. The connection pipe connects the heat source unit and the service unit. In the refrigeration cycle apparatus, a refrigerant containing at least 1,2-difluoroethylene is used. The control device is configured to set or be able to set an upper limit of a controlled pressure of the refrigerant such that the upper limit is equivalent to an upper limit of a controlled pressure in a refrigeration cycle apparatus in which refrigerant R22 or refrigerant R407C is used.

[0038] Here, the “equivalent” pressure preferably falls within the range of $\pm 10\%$ of the controlled pressure in a refrigeration cycle apparatus in which refrigerant R22 or refrigerant R407C is used.

[0039] With this refrigeration cycle apparatus, even when a refrigeration cycle apparatus in which refrigerant R22 or refrigerant R407C is used is modified to a refrigeration cycle apparatus in which a refrigerant containing at least 1,2-difluoroethylene is used while the original connection pipe is used, the refrigeration cycle apparatus is configured to set or be able to set the upper limit of the controlled pressure of the refrigerant by the control device of the heat source unit such that the upper limit is equal to or the same as the upper limit of the controlled pressure of the heat source unit in a refrigeration cycle apparatus in which refrigerant R22 or refrigerant R407C is used, so damage to the connection pipe can be reduced.

[0040] A refrigeration cycle apparatus according to a sixteenth aspect is the refrigeration cycle apparatus of the fifteenth aspect, and the upper limit of the controlled pressure is set to be higher than or equal to 3.0 MPa and lower than or equal to 3.7 MPa.

[0041] A refrigeration cycle apparatus according to a seventeenth aspect includes a heat source unit, a service unit, a connection pipe, and a control device. The heat source unit includes a compressor and a heat source-side heat exchanger. The service unit includes a service-side heat exchanger. The connection pipe connects the heat source unit and the service unit. In the refrigeration cycle apparatus, a refrigerant containing at least 1,2-difluoroethylene is used. The control device is configured to set or be able to set an upper limit of a controlled pressure of the refrigerant such that the upper limit is equivalent to an upper limit of a controlled pressure in a refrigeration cycle apparatus in which refrigerant R410A or refrigerant R32 is used.

[0042] Here, the “equivalent” pressure preferably falls within the range of $\pm 10\%$ of the controlled pressure in a refrigeration cycle apparatus in which refrigerant R410A or refrigerant R32 is used.

[0043] With this refrigeration cycle apparatus, even when a refrigeration cycle apparatus in which refrigerant R410A or refrigerant R32 is used is modified to a refrigeration cycle apparatus in which a refrigerant containing at least 1,2-difluoroethylene is used while the original connection pipe is used, the refrigeration cycle apparatus is configured to set or be able to set the upper limit of the controlled pressure of the refrigerant by the control device of the heat source unit such that the upper limit is equal to or the same as the upper

limit of the controlled pressure of the heat source unit in a refrigeration cycle apparatus in which refrigerant R410A or refrigerant R32 is used, so damage to the connection pipe can be reduced.

[0044] A refrigeration cycle apparatus according to an eighteenth aspect is the refrigeration cycle apparatus of the seventeenth aspect, and the upper limit of the controlled pressure is set to be higher than or equal to 4.0 MPa and lower than or equal to 4.8 MPa.

[0045] A refrigeration cycle apparatus according to a nineteenth aspect is the refrigeration cycle apparatus according to any of the second to ninth and eleventh to eighteenth aspects, wherein

[0046] the refrigerant comprises trans-1,2-difluoroethylene (HFO-1132(E)), trifluoroethylene (HFO-1123), and 2,3,3,3-tetrafluoro-1-propene (R1234yf).

[0047] With this refrigeration cycle apparatus, a refrigerant having such performance that the refrigerant has a sufficiently low GWP and a refrigeration capacity (which may be referred to as cooling capacity or capacity) and a coefficient of performance (COP) equivalent to those of R410A is used, and damage to the connection pipe can be reduced.

[0048] A refrigeration cycle apparatus according to a twentieth aspect is the refrigeration cycle apparatus according to the nineteenth aspect, wherein

[0049] when the mass % of HFO-1132(E), HFO-1123, and R1234yf based on their sum in the refrigerant is respectively represented by x, y, and z, coordinates (x,y,z) in a ternary composition diagram in which the sum of HFO-1132(E), HFO-1123, and R1234yf is 100 mass % are within the range of a figure surrounded by line segments AA', A'B, BD, DC', C'C, CO, and OA that connect the following 7 points:

[0050] point A (68.6, 0.0, 31.4),

[0051] point A' (30.6, 30.0, 39.4),

[0052] point B (0.0, 58.7, 41.3),

[0053] point D (0.0, 80.4, 19.6),

[0054] point C' (19.5, 70.5, 10.0),

[0055] point C (32.9, 67.1, 0.0), and

[0056] point O (100.0, 0.0, 0.0),

or on the above line segments (excluding the points on the line segments BD, CO, and OA);

[0057] the line segment AA' is represented by coordinates (x, $0.0016x^2 - 0.9473x + 57.497$, $-0.0016x^2 - 0.0527x + 42.503$),

[0058] the line segment A'B is represented by coordinates (x, $0.0029x^2 - 1.0268x + 58.7$, $-0.0029x^2 + 0.0268x + 41.3$),

[0059] the line segment DC' is represented by coordinates (x, $0.0082x^2 - 0.6671x + 80.4$, $-0.0082x^2 - 0.3329x + 19.6$),

[0060] the line segment C'C is represented by coordinates (x, $0.0067x^2 - 0.6034x + 79.729$, $-0.0067x^2 - 0.3966x + 20.271$), and

[0061] the line segments BD, CO, and OA are straight lines.

[0062] A refrigeration cycle apparatus according to a twenty first aspect is the refrigeration cycle apparatus according to the nineteenth aspect, wherein

[0063] when the mass % of HFO-1132(E), HFO-1123, and R1234yf based on their sum in the refrigerant is respectively represented by x, y, and z, coordinates (x,y,z) in a ternary composition diagram in which the sum of HFO-1132(E), HFO-1123, and R1234yf is 100 mass % are within the range of a figure surrounded by line segments GI, IA, AA', A'B, BD, DC', C'C, and CG that connect the following 8 points:

[0064] point G (72.0, 28.0, 0.0),
 [0065] point I (72.0, 0.0, 28.0),
 [0066] point A (68.6, 0.0, 31.4),
 [0067] point A' (30.6, 30.0, 39.4),
 [0068] point B (0.0, 58.7, 41.3),
 [0069] point D (0.0, 80.4, 19.6),
 [0070] point C' (19.5, 70.5, 10.0), and
 [0071] point C (32.9, 67.1, 0.0),
 or on the above line segments (excluding the points on the line segments IA, BD, and CG);
 [0072] the line segment AA' is represented by coordinates $(x, 0.0016x^2 - 0.9473x + 57.497, -0.0016x^2 - 0.0527x + 42.503)$,
 [0073] the line segment A'B is represented by coordinates $(x, 0.0029x^2 - 1.0268x + 58.7, -0.0029x^2 + 0.0268x + 41.3)$,
 [0074] the line segment DC' is represented by coordinates $(x, 0.0082x^2 - 0.6671x + 80.4, -0.0082x^2 - 0.3329x + 19.6)$,
 [0075] the line segment C'C is represented by coordinates $(x, 0.0067x^2 - 0.6034x + 79.729, -0.0067x^2 - 0.3966x + 20.271)$, and
 [0076] the line segments GI, IA, BD, and CG are straight lines.
 [0077] A refrigeration cycle apparatus according to a twenty second aspect is the refrigeration cycle apparatus according to the nineteenth aspect, wherein
 [0078] when the mass % of HFO-1132(E), HFO-1123, and R1234yf based on their sum in the refrigerant is respectively represented by x, y, and z, coordinates (x,y,z) in a ternary composition diagram in which the sum of HFO-1132(E), HFO-1123, and R1234yf is 100 mass % are within the range of a figure surrounded by line segments JP, PN, NK, KA', A'B, BD, DC', C'C, and CJ that connect the following 9 points:
 [0079] point J (47.1, 52.9, 0.0),
 [0080] point P (55.8, 42.0, 2.2),
 [0081] point N (68.6, 16.3, 15.1),
 [0082] point K (61.3, 5.4, 33.3),
 [0083] point A' (30.6, 30.0, 39.4),
 [0084] point B (0.0, 58.7, 41.3),
 [0085] point D (0.0, 80.4, 19.6),
 [0086] point C' (19.5, 70.5, 10.0), and
 [0087] point C (32.9, 67.1, 0.0),
 or on the above line segments (excluding the points on the line segments BD and CJ);
 [0088] the line segment PN is represented by coordinates $(x, -0.1135x^2 + 12.112x - 280.43, 0.1135x^2 - 13.112x + 380.43)$,
 [0089] the line segment NK is represented by coordinates $(x, 0.2421x^2 - 29.955x + 931.91, -0.2421x^2 + 28.955x - 831.91)$,
 [0090] the line segment KA' is represented by coordinates $(x, 0.0016x^2 - 0.9473x + 57.497, -0.0016x^2 - 0.0527x + 42.503)$,
 [0091] the line segment A'B is represented by coordinates $(x, 0.0029x^2 - 1.0268x + 58.7, -0.0029x^2 + 0.0268x + 41.3)$,
 [0092] the line segment DC' is represented by coordinates $(x, 0.0082x^2 - 0.6671x + 80.4, -0.0082x^2 - 0.3329x + 19.6)$,
 [0093] the line segment C'C is represented by coordinates $(x, 0.0067x^2 - 0.6034x + 79.729, -0.0067x^2 - 0.3966x + 20.271)$, and
 [0094] the line segments JP, BD, and CG are straight lines.
 [0095] A refrigeration cycle apparatus according to a twenty third aspect is the refrigeration cycle apparatus according to the nineteenth aspect, wherein

[0096] when the mass % of HFO-1132(E), HFO-1123, and R1234yf based on their sum in the refrigerant is respectively represented by x, y, and z, coordinates (x,y,z) in a ternary composition diagram in which the sum of HFO-1132(E), HFO-1123, and R1234yf is 100 mass % are within the range of a figure surrounded by line segments JP, PL, LM, MA', A'B, BD, DC', C'C, and CJ that connect the following 9 points:
 [0097] point J (47.1, 52.9, 0.0),
 [0098] point P (55.8, 42.0, 2.2),
 [0099] point L (63.1, 31.9, 5.0),
 [0100] point M (60.3, 6.2, 33.5),
 [0101] point A' (30.6, 30.0, 39.4),
 [0102] point B (0.0, 58.7, 41.3),
 [0103] point D (0.0, 80.4, 19.6),
 [0104] point C' (19.5, 70.5, 10.0), and
 [0105] point C (32.9, 67.1, 0.0),
 or on the above line segments (excluding the points on the line segments BD and CJ);
 [0106] the line segment PL is represented by coordinates $(x, -0.1135x^2 + 12.112x - 280.43, 0.1135x^2 - 13.112x + 380.43)$
 [0107] the line segment MA' is represented by coordinates $(x, 0.0016x^2 - 0.9473x + 57.497, -0.0016x^2 - 0.0527x + 42.503)$,
 [0108] the line segment A'B is represented by coordinates $(x, 0.0029x^2 - 1.0268x + 58.7, -0.0029x^2 + 0.0268x + 41.3)$,
 [0109] the line segment DC' is represented by coordinates $(x, 0.0082x^2 - 0.6671x + 80.4, -0.0082x^2 - 0.3329x + 19.6)$,
 [0110] the line segment C'C is represented by coordinates $(x, 0.0067x^2 - 0.6034x + 79.729, -0.0067x^2 - 0.3966x + 20.271)$, and
 [0111] the line segments JP, LM, BD, and CG are straight lines.
 [0112] A refrigeration cycle apparatus according to a twenty fourth aspect is the refrigeration cycle apparatus according to the nineteenth aspect, wherein
 [0113] when the mass % of HFO-1132(E), HFO-1123, and R1234yf based on their sum in the refrigerant is respectively represented by x, y, and z, coordinates (x,y,z) in a ternary composition diagram in which the sum of HFO-1132(E), HFO-1123, and R1234yf is 100 mass % are within the range of a figure surrounded by line segments PL, LM, MA', A'B, BF, FT, and TP that connect the following 7 points:
 [0114] point P (55.8, 42.0, 2.2),
 [0115] point L (63.1, 31.9, 5.0),
 [0116] point M (60.3, 6.2, 33.5),
 [0117] point A' (30.6, 30.0, 39.4),
 [0118] point B (0.0, 58.7, 41.3),
 [0119] point F (0.0, 61.8, 38.2), and
 [0120] point T (35.8, 44.9, 19.3),
 or on the above line segments (excluding the points on the line segment BF);
 [0121] the line segment PL is represented by coordinates $(x, -0.1135x^2 + 12.112x - 280.43, 0.1135x^2 - 13.112x + 380.43)$,
 [0122] the line segment MA' is represented by coordinates $(x, 0.0016x^2 - 0.9473x + 57.497, -0.0016x^2 - 0.0527x + 42.503)$,
 [0123] the line segment A'B is represented by coordinates $(x, 0.0029x^2 - 1.0268x + 58.7, -0.0029x^2 + 0.0268x + 41.3)$,
 [0124] the line segment FT is represented by coordinates $(x, 0.0078x^2 - 0.7501x + 61.8, -0.0078x^2 - 0.2499x + 38.2)$,

[0125] the line segment TP is represented by coordinates $(x, 0.00672x^2 - 0.7607x + 63.525, -0.00672x^2 - 0.2393x + 36.475)$, and

[0126] the line segments LM and BF are straight lines.

[0127] A refrigeration cycle apparatus according to a twenty fifth aspect is the refrigeration cycle apparatus according to the nineteenth aspect, wherein

[0128] when the mass % of HFO-1132(E), HFO-1123, and R1234yf based on their sum in the refrigerant is respectively represented by x, y, and z, coordinates (x,y,z) in a ternary composition diagram in which the sum of HFO-1132(E), HFO-1123, and R1234yf is 100 mass % are within the range of a figure surrounded by line segments PL, LQ, QR, and RP that connect the following 4 points:

[0129] point P (55.8, 42.0, 2.2),

[0130] point L (63.1, 31.9, 5.0),

[0131] point Q (62.8, 29.6, 7.6), and

[0132] point R (49.8, 42.3, 7.9),

or on the above line segments;

[0133] the line segment PL is represented by coordinates $(x, -0.1135x^2 + 12.112x - 280.43, 0.1135x^2 - 13.112x + 380.43)$,

[0134] the line segment RP is represented by coordinates $(x, 0.00672x^2 - 0.7607x + 63.525, -0.00672x^2 - 0.2393x + 36.475)$, and

[0135] the line segments LQ and QR are straight lines.

[0136] A refrigeration cycle apparatus according to a twenty sixth aspect is the refrigeration cycle apparatus according to the nineteenth aspect, wherein

[0137] when the mass % of HFO-1132(E), HFO-1123, and R1234yf based on their sum in the refrigerant is respectively represented by x, y, and z, coordinates (x,y,z) in a ternary composition diagram in which the sum of HFO-1132(E), HFO-1123, and R1234yf is 100 mass % are within the range of a figure surrounded by line segments SM, MA', A'B, BF, FT, and TS that connect the following 6 points:

[0138] point S (62.6, 28.3, 9.1),

[0139] point M (60.3, 6.2, 33.5),

[0140] point A' (30.6, 30.0, 39.4),

[0141] point B (0.0, 58.7, 41.3),

[0142] point F (0.0, 61.8, 38.2), and

[0143] point T (35.8, 44.9, 19.3),

or on the above line segments,

[0144] the line segment MA' is represented by coordinates $(x, 0.0016x^2 - 0.9473x + 57.497, -0.0016x^2 - 0.0527x + 42.503)$,

[0145] the line segment A'B is represented by coordinates $(x, 0.0029x^2 - 1.0268x + 58.7, -0.0029x^2 + 0.0268x + 41.3)$,

[0146] the line segment FT is represented by coordinates $(x, 0.0078x^2 - 0.7501x + 61.8, -0.0078x^2 - 0.2499x + 38.2)$,

[0147] the line segment TS is represented by coordinates $(x, -0.0017x^2 - 0.7869x + 70.888, -0.0017x^2 - 0.2131x + 29.112)$, and

[0148] the line segments SM and BF are straight lines.

[0149] A refrigeration cycle apparatus according to a twenty seventh aspect is the refrigeration cycle apparatus according to any of the second to ninth and eleventh to eighteenth aspects, wherein

[0150] the refrigerant comprises trans-1,2-difluoroethylene (HFO-1132(E)) and trifluoroethylene (HFO-1123) in a total amount of 99.5 mass % or more based on the entire refrigerant, and

[0151] the refrigerant comprises 62.0 mass % to 72.0 mass % of HFO-1132(E) based on the entire refrigerant.

[0152] With this refrigeration cycle apparatus, a refrigerant having such performance that the refrigerant has a sufficiently low GWP and a coefficient of performance (COP) and a refrigeration capacity (which may be referred to as cooling capacity or capacity) equivalent to those of R410A and is classified with lower flammability (class 2L) under the standard of American Society of Heating Refrigeration and Air Conditioning Engineers (ASHRAE) is used, and damage to the connection pipe can be reduced.

[0153] A refrigeration cycle apparatus according to a twenty eighth aspect is the refrigeration cycle apparatus according to any of the second to ninth and eleventh to eighteenth aspects, wherein

[0154] the refrigerant comprises HFO-1132(E) and HFO-1123 in a total amount of 99.5 mass % or more based on the entire refrigerant, and

[0155] the refrigerant comprises 45.1 mass % to 47.1 mass % of HFO-1132(E) based on the entire refrigerant.

[0156] With this refrigeration cycle apparatus, a refrigerant having such performance that the refrigerant has a sufficiently low GWP and a coefficient of performance (COP) and a refrigeration capacity (which may be referred to as cooling capacity or capacity) equivalent to those of R410A and is classified with lower flammability (class 2L) under the standard of American Society of Heating Refrigeration and Air Conditioning Engineers (ASHRAE) is used, and damage to the connection pipe can be reduced.

[0157] A refrigeration cycle apparatus according to a twenty ninth aspect is the refrigeration cycle apparatus according to any of the second to ninth and eleventh to eighteenth aspects, wherein

[0158] the refrigerant comprises trans-1,2-difluoroethylene (HFO-1132(E)), trifluoroethylene (HFO-1123), 2,3,3,3-tetrafluoro-1-propene (R1234yf), and difluoromethane (R32),

wherein

[0159] when the mass % of HFO-1132(E), HFO-1123, R1234yf, and R32 based on their sum in the refrigerant is respectively represented by x, y, z, and a,

[0160] if $0 < a \leq 11.1$, coordinates (x,y,z) in a ternary composition diagram in which the sum of HFO-1132(E), HFO-1123, and R1234yf is $(100-a)$ mass % are within the range of a figure surrounded by straight lines GI, IA, AB, BD', D' C, and CG that connect the following 6 points:

[0161] point G $(0.026a^2 - 1.7478a + 72.0, -0.026a^2 + 0.7478a + 28.0, 0.0)$,

[0162] point I $(0.026a^2 - 1.7478a + 72.0, 0.0, -0.026a^2 + 0.7478a + 28.0)$,

[0163] point A $(0.0134a^2 - 1.9681a + 68.6, 0.0, -0.0134a^2 + 0.9681a + 31.4)$,

[0164] point B $(0.0, 0.0144a^2 - 1.6377a + 58.7, -0.0144a^2 + 0.6377a + 41.3)$,

[0165] point D' $(0.0, 0.0224a^2 + 0.968a + 75.4, -0.0224a^2 - 1.968a + 24.6)$, and

[0166] point C $(-0.2304a^2 - 0.4062a + 32.9, 0.2304a^2 - 0.5938a + 67.1, 0.0)$,

or on the straight lines GI, AB, and D'C (excluding point G, point I, point A, point B, point D', and point C);

[0167] if $11.1 < a \leq 18.2$, coordinates (x,y,z) in the ternary composition diagram are within the range of a figure surrounded by straight lines GI, IA, AB, BW, and WG that connect the following 5 points:

[0168] point G $(0.02a^2 - 1.6013a + 71.105, -0.02a^2 + 0.6013a + 28.895, 0.0)$,

[0169] point I ($0.02a^2-1.6013a+71.105$, 0.0 , $-0.02a^2+0.6013a+28.895$),

[0170] point A ($0.0112a^2-1.9337a+68.484$, 0.0 , $-0.0112a^2+0.9337a+31.516$),

[0171] point B (0.0 , $0.0075a^2-1.5156a+58.199$, $-0.0075a^2+0.5156a+41.801$), and

[0172] point W (0.0 , $100.0-a$, 0.0),

or on the straight lines GI and AB (excluding point G, point I, point A, point B, and point W);

[0173] if $18.2 < a \leq 26.7$, coordinates (x,y,z) in the ternary composition diagram are within the range of a figure surrounded by straight lines GI, IA, AB, BW, and WG that connect the following 5 points:

[0174] point G ($0.0135a^2-1.4068a+69.727$, $-0.0135a^2+0.4068a+30.273$, 0.0),

[0175] point I ($0.0135a^2-1.4068a+69.727$, 0.0 , $-0.0135a^2+0.4068a+30.273$),

[0176] point A ($0.0107a^2-1.9142a+68.305$, 0.0 , $-0.0107a^2+0.9142a+31.695$),

[0177] point B (0.0 , $0.009a^2-1.6045a+59.318$, $-0.009a^2+0.6045a+40.682$), and

[0178] point W (0.0 , $100.0-a$, 0.0),

or on the straight lines GI and AB (excluding point G, point I, point A, point B, and point W);

[0179] if $26.7 < a \leq 36.7$, coordinates (x,y,z) in the ternary composition diagram are within the range of a figure surrounded by straight lines GI, IA, AB, BW, and WG that connect the following 5 points:

[0180] point G ($0.0111a^2-1.3152a+68.986$, $-0.0111a^2+0.3152a+31.014$, 0.0),

[0181] point I ($0.0111a^2-1.3152a+68.986$, 0.0 , $-0.0111a^2+0.3152a+31.014$),

[0182] point A ($0.0103a^2-1.9225a+68.793$, 0.0 , $-0.0103a^2+0.9225a+31.207$),

[0183] point B (0.0 , $0.0046a^2-1.41a+57.286$, $-0.0046a^2+0.41a+42.714$), and

[0184] point W (0.0 , $100.0-a$, 0.0),

or on the straight lines GI and AB (excluding point G, point I, point A, point B, and point W); and

[0185] if $36.7 < a \leq 46.7$, coordinates (x,y,z) in the ternary composition diagram are within the range of a figure surrounded by straight lines GI, IA, AB, BW, and WG that connect the following 5 points:

[0186] point G ($0.0061a^2-0.9918a+63.902$, $-0.0061a^2-0.0082a+36.098$, 0.0),

[0187] point I ($0.0061a^2-0.9918a+63.902$, 0.0 , $-0.0061a^2-0.0082a+36.098$),

[0188] point A ($0.0085a^2-1.8102a+67.1$, 0.0 , $-0.0085a^2+0.8102a+32.9$),

[0189] point B (0.0 , $0.0012a^2-1.1659a+52.95$, $-0.0012a^2+0.1659a+47.05$), and

[0190] point W (0.0 , $100.0-a$, 0.0),

or on the straight lines GI and AB (excluding point G, point I, point A, point B, and point W).

[0191] With this refrigeration cycle apparatus, a refrigerant having such performance that the refrigerant has a sufficiently low GWP and a refrigeration capacity (which may be referred to as cooling capacity or capacity) and a coefficient of performance (COP) equivalent to those of R410A is used, and damage to the connection pipe can be reduced.

[0192] A refrigeration cycle apparatus according to a thirtieth aspect is the refrigeration cycle apparatus according to any of the second to ninth and eleventh to eighteenth aspects, wherein

[0193] the refrigerant comprises trans-1,2-difluoroethylene (HFO-1132(E)), trifluoroethylene (HFO-1123), 2,3,3,3-tetrafluoro-1-propene (R1234yf), and difluoromethane (R32),

wherein

[0194] when the mass % of HFO-1132(E), HFO-1123, R1234yf, and R32 based on their sum in the refrigerant is respectively represented by x, y, z, and a,

[0195] if $0 < a \leq 11.1$, coordinates (x,y,z) in a ternary composition diagram in which the sum of HFO-1132(E), HFO-1123, and R1234yf is (100-a) mass % are within the range of a figure surrounded by straight lines JK', K'B, BD', D'C, and CJ that connect the following 5 points:

[0196] point J ($0.0049a^2-0.9645a+47.1$, $-0.0049a^2-0.0355a+52.9$, 0.0),

[0197] point K' ($0.0514a^2-2.4353a+61.7$, $-0.0323a^2+0.4122a+5.9$, $-0.0191a^2+1.0231a+32.4$),

[0198] point B (0.0 , $0.0144a^2-1.6377a+58.7$, $-0.0144a^2+0.6377a+41.3$),

[0199] point D' (0.0 , $0.0224a^2+0.968a+75.4$, $-0.0224a^2-1.968a+24.6$), and

[0200] point C ($-0.2304a^2-0.4062a+32.9$, $0.2304a^2-0.5938a+67.1$, 0.0),

or on the straight lines JK', K'B, and D'C (excluding point J, point B, point D', and point C);

[0201] if $11.1 < a \leq 18.2$, coordinates (x,y,z) in the ternary composition diagram are within the range of a figure surrounded by straight lines JK', K'B, BW, and WJ that connect the following 4 points:

[0202] point J ($0.0243a^2-1.4161a+49.725$, $-0.0243a^2+0.4161a+50.275$, 0.0),

[0203] point K' ($0.0341a^2-2.1977a+61.187$, $-0.0236a^2+0.34a+5.636$, $-0.0105a^2+0.8577a+33.177$),

[0204] point B (0.0 , $0.0075a^2-1.5156a+58.199$, $-0.0075a^2+0.5156a+41.801$), and

[0205] point W (0.0 , $100.0-a$, 0.0),

or on the straight lines JK' and K'B (excluding point J, point B, and point W);

[0206] if $18.2 < a \leq 26.7$, coordinates (x,y,z) in the ternary composition diagram are within the range of a figure surrounded by straight lines JK', K'B, BW, and WJ that connect the following 4 points:

[0207] point J ($0.0246a^2-1.4476a+50.184$, $-0.0246a^2+0.4476a+49.816$, 0.0),

[0208] point K' ($0.0196a^2-1.7863a+58.515$, $-0.0079a^2-0.1136a+8.702$, $-0.0117a^2+0.8999a+32.783$),

[0209] point B (0.0 , $0.009a^2-1.6045a+59.318$, $-0.009a^2+0.6045a+40.682$), and

[0210] point W (0.0 , $100.0-a$, 0.0),

or on the straight lines JK' and K'B (excluding point J, point B, and point W);

[0211] if $26.7 < a \leq 36.7$, coordinates (x,y,z) in the ternary composition diagram are within the range of a figure surrounded by straight lines JK', K'A, AB, BW, and WJ that connect the following 5 points:

[0212] point J ($0.0183a^2-1.1399a+46.493$, $-0.0183a^2+0.1399a+53.507$, 0.0),

[0213] point K' ($-0.0051a^2+0.0929a+25.95$, 0.0 , $0.0051a^2-1.0929a+74.05$),

[0214] point A ($0.0103a^2-1.9225a+68.793$, 0.0 , $-0.0103a^2+0.9225a+31.207$),

[0215] point B (0.0 , $0.0046a^2-1.41a+57.286$, $-0.0046a^2+0.41a+42.714$), and

[0216] point W (0.0 , $100.0-a$, 0.0),

or on the straight lines JK', K'A, and AB (excluding point J, point B, and point W); and

[0217] if $36.7 < a \leq 46.7$, coordinates (x,y,z) in the ternary composition diagram are within the range of a figure surrounded by straight lines JK', K'A, AB, BW, and WJ that connect the following 5 points:

[0218] point J ($-0.0134a^2+1.0956a+7.13$, $0.0134a^2-2.0956a+92.87$, 0.0),

[0219] point K' ($-1.892a+29.443$, 0.0 , $0.892a+70.557$),

[0220] point A ($0.0085a^2-1.8102a+67.1$, 0.0 , $-0.0085a^2+0.8102a+32.9$),

[0221] point B (0.0 , $0.0012a^2-1.1659a+52.95$, $-0.0012a^2+0.1659a+47.05$), and

[0222] point W (0.0 , $100.0-a$, 0.0),

or on the straight lines JK', K'A, and AB (excluding point J, point B, and point W).

[0223] With this refrigeration cycle apparatus, a refrigerant having such performance that the refrigerant has a sufficiently low GWP and a refrigeration capacity (which may be referred to as cooling capacity or capacity) and a coefficient of performance (COP) equivalent to those of R410A is used, and damage to the connection pipe can be reduced.

[0224] A refrigeration cycle apparatus according to a thirty first aspect is the refrigeration cycle apparatus according to any of the second to ninth and eleventh to eighteenth aspects, wherein

[0225] the refrigerant comprises trans-1,2-difluoroethylene (HFO-1132(E)), difluoromethane(R32), and 2,3,3,3-tetrafluoro-1-propene (R1234yf), wherein

[0226] when the mass % of HFO-1132(E), R32, and R1234yf based on their sum in the refrigerant is respectively represented by x, y, and z, coordinates (x,y,z) in a ternary composition diagram in which the sum of HFO-1132(E), R32, and R1234yf is 100 mass % are within the range of a figure surrounded by line segments IJ, JN, NE, and EI that connect the following 4 points:

[0227] point I (72.0 , 0.0 , 28.0),

[0228] point J (48.5 , 18.3 , 33.2),

[0229] point N (27.7 , 18.2 , 54.1), and

[0230] point E (58.3 , 0.0 , 41.7),

or on these line segments (excluding the points on the line segment EI;

[0231] the line segment IJ is represented by coordinates ($0.0236y^2-1.7616y+72.0$, y , $-0.0236y^2+0.7616y+28.0$);

[0232] the line segment NE is represented by coordinates ($0.012y^2-1.9003y+58.3$, y , $-0.012y^2+0.9003y+41.7$); and

[0233] the line segments JN and EI are straight lines.

[0234] With this refrigeration cycle apparatus, a refrigerant having such performance that the refrigerant has a sufficiently low GWP and a refrigeration capacity (which may be referred to as cooling capacity or capacity) equivalent to that of R410A and is classified with lower flammability (class 2L) under the standard of American Society of Heating Refrigeration and Air Conditioning Engineers (ASHRAE) is used, and damage to the connection pipe can be reduced.

[0235] A refrigeration cycle apparatus according to a thirty second aspect is the refrigeration cycle apparatus according to any of the second to ninth and eleventh to eighteenth aspects, wherein

[0236] the refrigerant comprises HFO-1132(E), R32, and R1234yf, wherein

[0237] when the mass % of HFO-1132(E), R32, and R1234yf based on their sum in the refrigerant is respectively represented by x, y, and z, coordinates (x,y,z) in a ternary composition diagram in which the sum of HFO-1132(E), R32, and R1234yf is 100 mass % are within the range of a figure surrounded by line segments MM', M'N, NV, VG, and GM that connect the following 5 points:

[0238] point M (52.6 , 0.0 , 47.4),

[0239] point M' (39.2 , 5.0 , 55.8),

[0240] point N (27.7 , 18.2 , 54.1),

[0241] point V (11.0 , 18.1 , 70.9), and

[0242] point G (39.6 , 0.0 , 60.4),

or on these line segments (excluding the points on the line segment GM);

[0243] the line segment MM' is represented by coordinates ($0.132y^2-3.34y+52.6$, y , $-0.132y^2+2.34y+47.4$);

[0244] the line segment M'N is represented by coordinates ($0.0596y^2-2.2541y+48.98$, y , $-0.0596y^2+1.2541y+51.02$);

[0245] the line segment VG is represented by coordinates ($0.0123y^2-1.8033y+39.6$, y , $-0.0123y^2+0.8033y+60.4$); and

[0246] the line segments NV and GM are straight lines.

[0247] With this refrigeration cycle apparatus, a refrigerant having such performance that the refrigerant has a sufficiently low GWP and a refrigeration capacity (which may be referred to as cooling capacity or capacity) equivalent to that of R410A and is classified with lower flammability (class 2L) under the standard of American Society of Heating Refrigeration and Air Conditioning Engineers (ASHRAE) is used, and damage to the connection pipe can be reduced.

[0248] A refrigeration cycle apparatus according to a thirty third aspect is the refrigeration cycle apparatus according to any of the second to ninth and eleventh to eighteenth aspects, wherein

[0249] the refrigerant comprises HFO-1132(E), R32, and R1234yf, wherein

[0250] when the mass % of HFO-1132(E), R32, and R1234yf based on their sum in the refrigerant is respectively represented by x, y and z, coordinates (x,y,z) in a ternary composition diagram in which the sum of HFO-1132(E), R32, and R1234yf is 100 mass % are within the range of a figure surrounded by line segments ON, NU, and UO that connect the following 3 points:

[0251] point O (22.6 , 36.8 , 40.6),

[0252] point N (27.7 , 18.2 , 54.1), and

[0253] point U (3.9 , 36.7 , 59.4),

or on these line segments;

[0254] the line segment ON is represented by coordinates ($0.0072y^2-0.6701y+37.512$, y , $-0.0072y^2-0.3299y+62.488$);

[0255] the line segment NU is represented by coordinates ($0.0083y^2-1.7403y+56.635$, y , $-0.0083y^2+0.7403y+43.365$); and

[0256] the line segment UO is a straight line.

[0257] With this refrigeration cycle apparatus, a refrigerant having such performance that the refrigerant has a

sufficiently low GWP and a refrigeration capacity (which may be referred to as cooling capacity or capacity) equivalent to that of R410A and is classified with lower flammability (class 2L) under the standard of American Society of Heating Refrigeration and Air Conditioning Engineers (ASHRAE) is used, and damage to the connection pipe can be reduced.

[0258] A refrigeration cycle apparatus according to a thirty fourth aspect is the refrigeration cycle apparatus according to any of the second to ninth and eleventh to eighteenth aspects, wherein

[0259] the refrigerant comprises HFO-1132(E), R32, and R1234yf,

wherein

[0260] when the mass % of HFO-1132(E), R32, and R1234yf based on their sum in the refrigerant is respectively represented by x, y, and z, coordinates (x,y,z) in a ternary composition diagram in which the sum of HFO-1132(E), R32, and R1234yf is 100 mass % are within the range of a figure surrounded by line segments QR, RT, TL, LK, and KQ that connect the following 5 points:

[0261] point Q (44.6, 23.0, 32.4),

[0262] point R (25.5, 36.8, 37.7),

[0263] point T (8.6, 51.6, 39.8),

[0264] point L (28.9, 51.7, 19.4), and

[0265] point K (35.6, 36.8, 27.6),

or on these line segments;

[0266] the line segment QR is represented by coordinates $(0.0099y^2 - 1.975y + 84.765, y, -0.0099y^2 + 0.975y + 15.235)$;

[0267] the line segment RT is represented by coordinates $(0.0082y^2 - 1.8683y + 83.126, y, -0.0082y^2 + 0.8683y + 16.874)$;

[0268] the line segment LK is represented by coordinates $(0.0049y^2 - 0.8842y + 61.488, y, -0.0049y^2 - 0.1158y + 38.512)$;

[0269] the line segment KQ is represented by coordinates $(0.0095y^2 - 1.2222y + 67.676, y, -0.0095y^2 + 0.2222y + 32.324)$; and

[0270] the line segment TL is a straight line.

[0271] With this refrigeration cycle apparatus, a refrigerant having such performance that the refrigerant has a sufficiently low GWP and a refrigeration capacity (which may be referred to as cooling capacity or capacity) equivalent to that of R410A and is classified with lower flammability (class 2L) under the standard of American Society of Heating Refrigeration and Air Conditioning Engineers (ASHRAE) is used, and damage to the connection pipe can be reduced.

[0272] A refrigeration cycle apparatus according to a thirty fifth aspect is the refrigeration cycle apparatus according to any of the second to ninth and eleventh to eighteenth aspects, wherein

[0273] the refrigerant comprises HFO-1132(E), R32, and R1234yf,

wherein

[0274] when the mass % of HFO-1132(E), R32, and R1234yf based on their sum in the refrigerant is respectively represented by x, y, and z, coordinates (x,y,z) in a ternary composition diagram in which the sum of HFO-1132(E), R32, and R1234yf is 100 mass % are within the range of a

figure surrounded by line segments PS, ST, and TP that connect the following 3 points:

[0275] point P (20.5, 51.7, 27.8),

[0276] point S (21.9, 39.7, 38.4), and

[0277] point T (8.6, 51.6, 39.8),

or on these line segments;

[0278] the line segment PS is represented by coordinates $(0.0064y^2 - 0.7103y + 40.1, y, -0.0064y^2 - 0.2897y + 59.9)$;

[0279] the line segment ST is represented by coordinates $(0.0082y^2 - 1.8683y + 83.126, y, -0.0082y^2 + 0.8683y + 16.874)$; and

[0280] the line segment TP is a straight line.

[0281] With this refrigeration cycle apparatus, a refrigerant having such performance that the refrigerant has a sufficiently low GWP and a refrigeration capacity (which may be referred to as cooling capacity or capacity) equivalent to that of R410A and is classified with lower flammability (class 2L) under the standard of American Society of Heating Refrigeration and Air Conditioning Engineers (ASHRAE) is used, and damage to the connection pipe can be reduced.

[0282] A refrigeration cycle apparatus according to a thirty sixth aspect is the refrigeration cycle apparatus according to any of the second to ninth and eleventh to eighteenth aspects, wherein

[0283] the refrigerant comprises trans-1,2-difluoroethylene (HFO-1132(E)), trifluoroethylene (HFO-1123), and difluoromethane (R32),

wherein

[0284] when the mass % of HFO-1132(E), HFO-1123, and R32 based on their sum in the refrigerant is respectively represented by x, y, and z, coordinates (x,y,z) in a ternary composition diagram in which the sum of HFO-1132(E), HFO-1123, and R32 is 100 mass % are within the range of a figure surrounded by line segments IK, KB', B'H, HR, RG, and GI that connect the following 6 points:

[0285] point I (72.0, 28.0, 0.0),

[0286] point K (48.4, 33.2, 18.4),

[0287] point B' (0.0, 81.6, 18.4),

[0288] point H (0.0, 84.2, 15.8),

[0289] point R (23.1, 67.4, 9.5), and

[0290] point G (38.5, 61.5, 0.0),

or on these line segments (excluding the points on the line segments B'H and GI);

[0291] the line segment IK is represented by coordinates $(0.025z^2 - 1.7429z + 72.00, -0.025z^2 + 0.7429z + 28.0, z)$,

[0292] the line segment HR is represented by coordinates $(-0.3123z^2 + 4.234z + 11.06, 0.3123z^2 - 5.234z + 88.94, z)$,

[0293] the line segment RG is represented by coordinates $(-0.0491z^2 - 1.1544z + 38.5, 0.0491z^2 + 0.1544z + 61.5, z)$, and

[0294] the line segments KB' and GI are straight lines.

[0295] With this refrigeration cycle apparatus, a refrigerant having such performance that the refrigerant has a sufficiently low GWP and a coefficient of performance (COP) equivalent to that of R410A is used, and damage to the connection pipe can be reduced.

[0296] A refrigeration cycle apparatus according to a thirty seventh aspect is the refrigeration cycle apparatus according to any of the second to ninth and eleventh to eighteenth aspects, wherein

[0297] the refrigerant comprises HFO-1132(E), HFO-1123, and R32,

wherein

[0298] when the mass % of HFO-1132(E), HFO-1123, and R32 based on their sum in the refrigerant is respectively represented by x, y, and z, coordinates (x,y,z) in a ternary composition diagram in which the sum of HFO-1132(E), HFO-1123, and R32 is 100 mass % are within the range of a figure surrounded by line segments IJ, JR, RG, and GI that connect the following 4 points:

[0299] point I (72.0, 28.0, 0.0),

[0300] point J (57.7, 32.8, 9.5),

[0301] point R (23.1, 67.4, 9.5), and

[0302] point G (38.5, 61.5, 0.0),

or on these line segments (excluding the points on the line segment GI);

[0303] the line segment IJ is represented by coordinates $(0.025z^2 - 1.7429z + 72.0, -0.025z^2 + 0.7429z + 28.0, z)$,

[0304] the line segment RG is represented by coordinates $(-0.0491z^2 - 1.1544z + 38.5, 0.0491z^2 + 0.1544z + 61.5, z)$, and

[0305] the line segments JR and GI are straight lines.

[0306] With this refrigeration cycle apparatus, a refrigerant having such performance that the refrigerant has a sufficiently low GWP and a coefficient of performance (COP) equivalent to that of R410A is used, and damage to the connection pipe can be reduced.

[0307] A refrigeration cycle apparatus according to a thirty eighth aspect is the refrigeration cycle apparatus according to any of the second to ninth and eleventh to eighteenth aspects, wherein

[0308] the refrigerant comprises HFO-1132(E), HFO-1123, and R32,

wherein

[0309] when the mass % of HFO-1132(E), HFO-1123, and R32 based on their sum in the refrigerant is respectively represented by x, y, and z, coordinates (x,y,z) in a ternary composition diagram in which the sum of HFO-1132(E), HFO-1123, and R32 is 100 mass % are within the range of a figure surrounded by line segments MP, PB', B'H, HR, RG, and GM that connect the following 6 points:

[0310] point M (47.1, 52.9, 0.0),

[0311] point P (31.8, 49.8, 18.4),

[0312] point B' (0.0, 81.6, 18.4),

[0313] point H (0.0, 84.2, 15.8),

[0314] point R (23.1, 67.4, 9.5), and

[0315] point G (38.5, 61.5, 0.0),

or on these line segments (excluding the points on the line segments B'H and GM);

[0316] the line segment MP is represented by coordinates $(0.0083z^2 - 0.984z + 47.1, -0.0083z^2 - 0.016z + 52.9, z)$,

[0317] the line segment HR is represented by coordinates $(-0.3123z^2 + 4.234z + 11.06, 0.3123z^2 - 5.234z + 88.94, z)$,

[0318] the line segment RG is represented by coordinates $(-0.0491z^2 - 1.1544z + 38.5, 0.0491z^2 + 0.1544z + 61.5, z)$, and

[0319] the line segments PB' and GM are straight lines.

[0320] With this refrigeration cycle apparatus, a refrigerant having such performance that the refrigerant has a sufficiently low GWP and a coefficient of performance (COP) equivalent to that of R410A is used, and damage to the connection pipe can be reduced.

[0321] A refrigeration cycle apparatus according to a thirty ninth aspect is the refrigeration cycle apparatus according to any of the second to ninth and eleventh to eighteenth aspects, wherein

[0322] the refrigerant comprises HFO-1132(E), HFO-1123, and R32,

wherein

[0323] when the mass % of HFO-1132(E), HFO-1123, and R32 based on their sum in the refrigerant is respectively represented by x, y, and z, coordinates (x,y,z) in a ternary composition diagram in which the sum of HFO-1132(E), HFO-1123, and R32 is 100 mass % are within the range of a figure surrounded by line segments MN, NR, RG, and GM that connect the following 4 points:

[0324] point M (47.1, 52.9, 0.0),

[0325] point N (38.5, 52.1, 9.5),

[0326] point R (23.1, 67.4, 9.5), and

[0327] point G (38.5, 61.5, 0.0),

or on these line segments (excluding the points on the line segment GM);

[0328] the line segment MN is represented by coordinates $(0.0083z^2 - 0.984z + 47.1, -0.0083z^2 - 0.016z + 52.9, z)$,

[0329] the line segment RG is represented by coordinates $(-0.0491z^2 - 1.1544z + 38.5, 0.0491z^2 + 0.1544z + 61.5, z)$, and

[0330] the line segments JR and GI are straight lines.

[0331] With this refrigeration cycle apparatus, a refrigerant having such performance that the refrigerant has a sufficiently low GWP and a coefficient of performance (COP) equivalent to that of R410A is used, and damage to the connection pipe can be reduced.

[0332] A refrigeration cycle apparatus according to a fortieth aspect is the refrigeration cycle apparatus according to any of the second to ninth and eleventh to eighteenth aspects, wherein

[0333] the refrigerant comprises HFO-1132(E), HFO-1123, and R32,

wherein

[0334] when the mass % of HFO-1132(E), HFO-1123, and R32 based on their sum in the refrigerant is respectively represented by x, y, and z, coordinates (x,y,z) in a ternary composition diagram in which the sum of HFO-1132(E), HFO-1123, and R32 is 100 mass % are within the range of a figure surrounded by line segments PS, ST, and TP that connect the following 3 points:

[0335] point P (31.8, 49.8, 18.4),

[0336] point S (25.4, 56.2, 18.4), and

[0337] point T (34.8, 51.0, 14.2),

or on these line segments;

[0338] the line segment ST is represented by coordinates $(-0.0982z^2 + 0.9622z + 40.931, 0.0982z^2 - 1.9622z + 59.069, z)$,

[0339] the line segment TP is represented by coordinates $(0.0083z^2 - 0.984z + 47.1, -0.0083z^2 - 0.016z + 52.9, z)$, and

[0340] the line segment PS is a straight line.

[0341] With this refrigeration cycle apparatus, a refrigerant having such performance that the refrigerant has a sufficiently low GWP and a coefficient of performance (COP) equivalent to that of R410A is used, and damage to the connection pipe can be reduced.

[0342] A refrigeration cycle apparatus according to a forty first aspect is the refrigeration cycle apparatus according to any of the second to ninth and eleventh to eighteenth aspects, wherein

[0343] the refrigerant comprises HFO-1132(E), HFO-1123, and R32,

wherein

[0344] when the mass % of HFO-1132(E), HFO-1123, and R32 based on their sum in the refrigerant is respectively

represented by x, y, and z, coordinates (x,y,z) in a ternary composition diagram in which the sum of HFO-1132(E), HFO-1123, and R32 is 100 mass % are within the range of a figure surrounded by line segments QB", B"D, DU, and UQ that connect the following 4 points:

[0345] point Q (28.6, 34.4, 37.0),

[0346] point B" (0.0, 63.0, 37.0),

[0347] point D (0.0, 67.0, 33.0), and

[0348] point U (28.7, 41.2, 30.1),

or on these line segments (excluding the points on the line segment B"D);

[0349] the line segment DU is represented by coordinates $(-3.4962z^2+210.71z-3146.1, 3.4962z^2-211.71z+3246.1, z)$,

[0350] the line segment UQ is represented by coordinates $(0.0135z^2-0.9181z+44.133, -0.0135z^2-0.0819z+55.867, z)$, and

[0351] the line segments QB" and B"D are straight lines.

[0352] With this refrigeration cycle apparatus, a refrigerant having such performance that the refrigerant has a sufficiently low GWP and a coefficient of performance (COP) equivalent to that of R410A is used, and damage to the connection pipe can be reduced.

BRIEF DESCRIPTION OF THE DRAWINGS

[0353] FIG. 1 is a schematic view of an instrument used for a flammability test.

[0354] FIG. 2 is a diagram showing points A to T and line segments that connect these points in a ternary composition diagram in which the sum of HFO-1132(E), HFO-1123, and R1234yf is 100 mass %.

[0355] FIG. 3 is a diagram showing points A to C, D', G, I, J, and K', and line segments that connect these points to each other in a ternary composition diagram in which the sum of HFO-1132(E), HFO-1123, and R1234yf is (100-a) mass %.

[0356] FIG. 4 is a diagram showing points A to C, D', G, I, J, and K', and line segments that connect these points to each other in a ternary composition diagram in which the sum of HFO-1132(E), HFO-1123, and R1234yf is 92.9 mass % (the content of R32 is 7.1 mass %).

[0357] FIG. 5 is a diagram showing points A to C, D', G, I, J, K', and W, and line segments that connect these points to each other in a ternary composition diagram in which the sum of HFO-1132(E), HFO-1123, and R1234yf is 88.9 mass % (the content of R32 is 11.1 mass %).

[0358] FIG. 6 is a diagram showing points A, B, G, I, J, K', and W, and line segments that connect these points to each other in a ternary composition diagram in which the sum of HFO-1132(E), HFO-1123, and R1234yf is 85.5 mass % (the content of R32 is 14.5 mass %).

[0359] FIG. 7 is a diagram showing points A, B, G, I, J, K', and W, and line segments that connect these points to each other in a ternary composition diagram in which the sum of HFO-1132(E), HFO-1123, and R1234yf is 81.8 mass % (the content of R32 is 18.2 mass %).

[0360] FIG. 8 is a diagram showing points A, B, G, I, J, K', and W, and line segments that connect these points to each other in a ternary composition diagram in which the sum of HFO-1132(E), HFO-1123, and R1234yf is 78.1 mass % (the content of R32 is 21.9 mass %).

[0361] FIG. 9 is a diagram showing points A, B, G, I, J, K', and W, and line segments that connect these points to each other in a ternary composition diagram in which the sum of

HFO-1132(E), HFO-1123, and R1234yf is 73.3 mass % (the content of R32 is 26.7 mass %).

[0362] FIG. 10 is a diagram showing points A, B, G, I, J, K', and W, and line segments that connect these points to each other in a ternary composition diagram in which the sum of HFO-1132(E), HFO-1123, and R1234yf is 70.7 mass % (the content of R32 is 29.3 mass %).

[0363] FIG. 11 is a diagram showing points A, B, G, I, J, K', and W, and line segments that connect these points to each other in a ternary composition diagram in which the sum of HFO-1132(E), HFO-1123, and R1234yf is 63.3 mass % (the content of R32 is 36.7 mass %).

[0364] FIG. 12 is a diagram showing points A, B, G, I, J, K', and W, and line segments that connect these points to each other in a ternary composition diagram in which the sum of HFO-1132(E), HFO-1123, and R1234yf is 55.9 mass % (the content of R32 is 44.1 mass %).

[0365] FIG. 13 is a diagram showing points A, B, G, I, J, K', and W, and line segments that connect these points to each other in a ternary composition diagram in which the sum of HFO-1132(E), HFO-1123, and R1234yf is 52.2 mass % (the content of R32 is 47.8 mass %).

[0366] FIG. 14 is a view showing points A to C, E, G, and I to W; and line segments that connect points A to C, E, G, and I to W in a ternary composition diagram in which the sum of HFO-1132(E), R32, and R1234yf is 100 mass %.

[0367] FIG. 15 is a view showing points A to U; and line segments that connect the points in a ternary composition diagram in which the sum of HFO-1132(E), HFO-1123, and R32 is 100 mass %.

[0368] FIG. 16 is a schematic configuration diagram of a refrigerant circuit according to a first embodiment.

[0369] FIG. 17 is a schematic control block configuration diagram of a refrigeration cycle apparatus according to the first embodiment.

[0370] FIG. 18 is a schematic configuration diagram of a refrigerant circuit according to a second embodiment.

[0371] FIG. 19 is a schematic control block configuration diagram of a refrigeration cycle apparatus according to the second embodiment.

[0372] FIG. 20 is a schematic configuration diagram of a refrigerant circuit according to a third embodiment.

[0373] FIG. 21 is a schematic control block configuration diagram of a refrigeration cycle apparatus according to the third embodiment.

DESCRIPTION OF EMBODIMENTS

(1) Definition of Terms

[0374] In the present specification, the term "refrigerant" includes at least compounds that are specified in ISO 817 (International Organization for Standardization), and that are given a refrigerant number (ASHRAE number) representing the type of refrigerant with "R" at the beginning; and further includes refrigerants that have properties equivalent to those of such refrigerants, even though a refrigerant number is not yet given. Refrigerants are broadly divided into fluorocarbon compounds and non-fluorocarbon compounds in terms of the structure of the compounds. Fluorocarbon compounds include chlorofluorocarbons (CFC), hydrochlorofluorocarbons (HCFC), and hydrofluorocarbons (HFC). Non-fluorocarbon compounds include propane

(R290), propylene (R1270), butane (R600), isobutane (R600a), carbon dioxide (R744), ammonia (R717), and the like.

[0375] In the present specification, the phrase “composition comprising a refrigerant” at least includes (1) a refrigerant itself (including a mixture of refrigerants), (2) a composition that further comprises other components and that can be mixed with at least a refrigeration oil to obtain a working fluid for a refrigerating machine, and (3) a working fluid for a refrigerating machine containing a refrigeration oil. In the present specification, of these three embodiments, the composition (2) is referred to as a “refrigerant composition” so as to distinguish it from a refrigerant itself (including a mixture of refrigerants). Further, the working fluid for a refrigerating machine (3) is referred to as a “refrigeration oil-containing working fluid” so as to distinguish it from the “refrigerant composition.”

[0376] In the present specification, when the term “alternative” is used in a context in which the first refrigerant is replaced with the second refrigerant, the first type of “alternative” means that equipment designed for operation using the first refrigerant can be operated using the second refrigerant under optimum conditions, optionally with changes of only a few parts (at least one of the following: refrigeration oil, gasket, packing, expansion valve, dryer, and other parts) and equipment adjustment. In other words, this type of alternative means that the same equipment is operated with an alternative refrigerant. Embodiments of this type of “alternative” include “drop-in alternative,” “nearly drop-in alternative,” and “retrofit,” in the order in which the extent of changes and adjustment necessary for replacing the first refrigerant with the second refrigerant is smaller.

[0377] The term “alternative” also includes a second type of “alternative,” which means that equipment designed for operation using the second refrigerant is operated for the same use as the existing use with the first refrigerant by using the second refrigerant. This type of alternative means that the same use is achieved with an alternative refrigerant.

[0378] In the present specification, the term “refrigerating machine” refers to machines in general that draw heat from an object or space to make its temperature lower than the temperature of ambient air, and maintain a low temperature. In other words, refrigerating machines refer to conversion machines that gain energy from the outside to do work, and that perform energy conversion, in order to transfer heat from where the temperature is lower to where the temperature is higher.

[0379] In the present specification, a refrigerant having a “WCF lower flammability” means that the most flammable composition (worst case of formulation for flammability: WCF) has a burning velocity of 10 cm/s or less according to the US ANSI/ASHRAE Standard 34-2013. Further, in the present specification, a refrigerant having “ASHRAE lower flammability” means that the burning velocity of WCF is 10 cm/s or less, that the most flammable fraction composition (worst case of fractionation for flammability: WCFF), which is specified by performing a leakage test during storage, shipping, or use based on ANSI/ASHRAE 34-2013 using WCF, has a burning velocity of 10 cm/s or less, and that flammability classification according to the US ANSI/ASHRAE Standard 34-2013 is determined to be classified as “Class 2L.”

[0380] In the present specification, a refrigerant having an “RCL of x % or more” means that the refrigerant has a

refrigerant concentration limit (RCL), calculated in accordance with the US ANSI/ASHRAE Standard 34-2013, of x % or more. RCL refers to a concentration limit in the air in consideration of safety factors. RCL is an index for reducing the risk of acute toxicity, suffocation, and flammability in a closed space where humans are present. RCL is determined in accordance with the ASHRAE Standard. More specifically, RCL is the lowest concentration among the acute toxicity exposure limit (ATEL), the oxygen deprivation limit (ODL), and the flammable concentration limit (FCL), which are respectively calculated in accordance with sections 7.1.1, 7.1.2, and 7.1.3 of the ASHRAE Standard.

[0381] In the present specification, temperature glide refers to an absolute value of the difference between the initial temperature and the end temperature in the phase change process of a composition containing the refrigerant of the present disclosure in the heat exchanger of a refrigerant system.

(2) Refrigerant

(2-1) Refrigerant Component

[0382] Any one of various refrigerants such as refrigerant A, refrigerant B, refrigerant C, refrigerant D, and refrigerant E, details of these refrigerant are to be mentioned later, can be used as the refrigerant.

(2-2) Use of Refrigerant

[0383] The refrigerant according to the present disclosure can be preferably used as a working fluid in a refrigerating machine.

[0384] The composition according to the present disclosure is suitable for use as an alternative refrigerant for HFC refrigerant such as R410A, R407C and R404 etc, or HCFC refrigerant such as R22 etc.

(3) Refrigerant Composition

[0385] The refrigerant composition according to the present disclosure comprises at least the refrigerant according to the present disclosure, and can be used for the same use as the refrigerant according to the present disclosure. Moreover, the refrigerant composition according to the present disclosure can be further mixed with at least a refrigeration oil to thereby obtain a working fluid for a refrigerating machine.

[0386] The refrigerant composition according to the present disclosure further comprises at least one other component in addition to the refrigerant according to the present disclosure. The refrigerant composition according to the present disclosure may comprise at least one of the following other components, if necessary. As described above, when the refrigerant composition according to the present disclosure is used as a working fluid in a refrigerating machine, it is generally used as a mixture with at least a refrigeration oil. Therefore, it is preferable that the refrigerant composition according to the present disclosure does not substantially comprise a refrigeration oil. Specifically, in the refrigerant composition according to the present disclosure, the content of the refrigeration oil based on the entire refrigerant composition is preferably 0 to 1 mass %, and more preferably 0 to 0.1 mass %.

(3-1) Water

[0387] The refrigerant composition according to the present disclosure may contain a small amount of water. The water content of the refrigerant composition is preferably 0.1 mass % or less based on the entire refrigerant. A small amount of water contained in the refrigerant composition stabilizes double bonds in the molecules of unsaturated fluorocarbon compounds that can be present in the refrigerant, and makes it less likely that the unsaturated fluorocarbon compounds will be oxidized, thus increasing the stability of the refrigerant composition.

(3-2) Tracer

[0388] A tracer is added to the refrigerant composition according to the present disclosure at a detectable concentration such that when the refrigerant composition has been diluted, contaminated, or undergone other changes, the tracer can trace the changes.

[0389] The refrigerant composition according to the present disclosure may comprise a single tracer, or two or more tracers.

[0390] The tracer is not limited, and can be suitably selected from commonly used tracers. Preferably, a compound that cannot be an impurity inevitably mixed in the refrigerant of the present disclosure is selected as the tracer.

[0391] Examples of tracers include hydrofluorocarbons, hydrochlorofluorocarbons, chlorofluorocarbons, hydrochlorocarbons, fluorocarbons, deuterated hydrocarbons, deuterated hydrofluorocarbons, perfluorocarbons, fluoroethers, brominated compounds, iodinated compounds, alcohols, aldehydes, ketones, and nitrous oxide (N₂O). The tracer is particularly preferably a hydrofluorocarbon, a hydrochlorofluorocarbon, a chlorofluorocarbon, a fluorocarbon, a hydrochlorocarbon, a fluorocarbon, or a fluoroether.

[0392] The following compounds are preferable as the tracer.

- [0393]** FC-14 (tetrafluoromethane, CF₄)
- [0394]** HCC-40 (chloromethane, CH₃Cl)
- [0395]** HFC-23 (trifluoromethane, CHF₃)
- [0396]** HFC-41 (fluoromethane, CH₃Cl)
- [0397]** HFC-125 (pentafluoroethane, CF₃CHF₂)
- [0398]** HFC-134a (1,1,1,2-tetrafluoroethane, CF₃CH₂F)
- [0399]** HFC-134 (1,1,2,2-tetrafluoroethane, CHF₂CHF₂)
- [0400]** HFC-143a (1,1,1-trifluoroethane, CF₃CH₃)
- [0401]** HFC-143 (1,1,2-trifluoroethane, CHF₂CH₂F)
- [0402]** HFC-152a (1,1-difluoroethane, CHF₂CH₃)
- [0403]** HFC-152 (1,2-difluoroethane, CH₂FCH₂F)
- [0404]** HFC-161 (fluoroethane, CH₃CH₂F)
- [0405]** HFC-245fa (1,1,1,3,3-pentafluoropropane, CF₃CH₂CHF₂)
- [0406]** HFC-236fa (1,1,1,3,3,3-hexafluoropropane, CF₃CH₂CF₃)
- [0407]** HFC-236ea (1,1,1,2,3,3-hexafluoropropane, CF₃CHFCHF₂)
- [0408]** HFC-227ea (1,1,1,2,3,3,3-heptafluoropropane, CF₃CHFCF₃)
- [0409]** HCFC-22 (chlorodifluoromethane, CHClF₂)
- [0410]** HCFC-31 (chlorofluoromethane, CH₂ClF)
- [0411]** CFC-1113 (chlorotrifluoroethylene, CF₂=CClF)
- [0412]** HFE-125 (trifluoromethyl-difluoromethyl ether, CF₃OC₂CF₂)
- [0413]** HFE-134a (trifluoromethyl-fluoromethyl ether, CF₃OC₂H₂F)

[0414] HFE-143a (trifluoromethyl-methyl ether, CF₃OC₂H₃)

[0415] HFE-227ea (trifluoromethyl-tetrafluoroethyl ether, CF₃OCH₂CF₃)

[0416] HFE-236fa (trifluoromethyl-trifluoroethyl ether, CF₃OCH₂CF₃)

[0417] The tracer compound may be present in the refrigerant composition at a total concentration of about 10 parts per million (ppm) to about 1000 ppm. Preferably, the tracer compound is present in the refrigerant composition at a total concentration of about 30 ppm to about 500 ppm, and most preferably, the tracer compound is present at a total concentration of about 50 ppm to about 300 ppm.

(3-3) Ultraviolet Fluorescent Dye

[0418] The refrigerant composition according to the present disclosure may comprise a single ultraviolet fluorescent dye, or two or more ultraviolet fluorescent dyes.

[0419] The ultraviolet fluorescent dye is not limited, and can be suitably selected from commonly used ultraviolet fluorescent dyes.

[0420] Examples of ultraviolet fluorescent dyes include naphthalimide, coumarin, anthracene, phenanthrene, xanthene, thioxanthene, naphthoxanthene, fluorescein, and derivatives thereof. The ultraviolet fluorescent dye is particularly preferably either naphthalimide or coumarin, or both.

(3-4) Stabilizer

[0421] The refrigerant composition according to the present disclosure may comprise a single stabilizer, or two or more stabilizers.

[0422] The stabilizer is not limited, and can be suitably selected from commonly used stabilizers.

[0423] Examples of stabilizers include nitro compounds, ethers, and amines.

[0424] Examples of nitro compounds include aliphatic nitro compounds, such as nitromethane and nitroethane; and aromatic nitro compounds, such as nitro benzene and nitro styrene.

[0425] Examples of ethers include 1,4-dioxane.

[0426] Examples of amines include 2,2,3,3,3-pentafluoropropylamine and diphenylamine.

[0427] Examples of stabilizers also include butylhydroxyxylene and benzotriazole.

[0428] The content of the stabilizer is not limited. Generally, the content of the stabilizer is preferably 0.01 to 5 mass %, and more preferably 0.05 to 2 mass %, based on the entire refrigerant.

(3-5) Polymerization Inhibitor

[0429] The refrigerant composition according to the present disclosure may comprise a single polymerization inhibitor, or two or more polymerization inhibitors.

[0430] The polymerization inhibitor is not limited, and can be suitably selected from commonly used polymerization inhibitors.

[0431] Examples of polymerization inhibitors include 4-methoxy-1-naphthol, hydroquinone, hydroquinone methyl ether, dimethyl-t-butylphenol, 2,6-di-tert-butyl-p-cresol, and benzotriazole.

[0432] The content of the polymerization inhibitor is not limited. Generally, the content of the polymerization inhibitor

tor is preferably 0.01 to 5 mass %, and more preferably 0.05 to 2 mass %, based on the entire refrigerant.

(4) Refrigeration Oil—Containing Working Fluid

[0433] The refrigeration oil-containing working fluid according to the present disclosure comprises at least the refrigerant or refrigerant composition according to the present disclosure and a refrigeration oil, for use as a working fluid in a refrigerating machine. Specifically, the refrigeration oil-containing working fluid according to the present disclosure is obtained by mixing a refrigeration oil used in a compressor of a refrigerating machine with the refrigerant or the refrigerant composition. The refrigeration oil-containing working fluid generally comprises 10 to 50 mass % of refrigeration oil.

(4-1) Refrigeration Oil

[0434] The refrigeration oil is not limited, and can be suitably selected from commonly used refrigeration oils. In this case, refrigeration oils that are superior in the action of increasing the miscibility with the mixture and the stability of the mixture, for example, are suitably selected as necessary.

[0435] The base oil of the refrigeration oil is preferably, for example, at least one member selected from the group consisting of polyalkylene glycols (PAG), polyol esters (POE), and polyvinyl ethers (PVE).

[0436] The refrigeration oil may further contain additives in addition to the base oil. The additive may be at least one member selected from the group consisting of antioxidants, extreme-pressure agents, acid scavengers, oxygen scavengers, copper deactivators, rust inhibitors, oil agents, and antifoaming agents.

[0437] A refrigeration oil with a kinematic viscosity of 5 to 400 cSt at 40° C. is preferable from the standpoint of lubrication.

[0438] The refrigeration oil-containing working fluid according to the present disclosure may further optionally contain at least one additive. Examples of additives include compatibilizing agents described below.

(4-2) Compatibilizing Agent

[0439] The refrigeration oil-containing working fluid according to the present disclosure may comprise a single compatibilizing agent, or two or more compatibilizing agents.

[0440] The compatibilizing agent is not limited, and can be suitably selected from commonly used compatibilizing agents.

[0441] Examples of compatibilizing agents include polyoxyalkylene glycol ethers, amides, nitriles, ketones, chlorocarbons, esters, lactones, aryl ethers, fluoroethers, and 1,1,1-trifluoroalkanes. The compatibilizing agent is particularly preferably a polyoxyalkylene glycol ether.

(5) Various Refrigerants

[0442] Hereinafter, the refrigerants A to E, which are the refrigerants used in the present embodiment, will be described in detail.

[0443] In addition, each description of the following refrigerant A, refrigerant B, refrigerant C, refrigerant D, and refrigerant E is each independent. The alphabet which shows a point or a line segment, the number of an Examples, and

the number of a comparative examples are all independent of each other among the refrigerant A, the refrigerant B, the refrigerant C, the refrigerant D, and the refrigerant E. For example, the first embodiment of the refrigerant A and the first embodiment of the refrigerant B are different embodiments from each other.

(5-1) Refrigerant A

[0444] The refrigerant A according to the present disclosure is a mixed refrigerant comprising trans-1,2-difluoroethylene (HFO-1132(E)), trifluoroethylene (HFO-1123), and 2,3,3,3-tetrafluoro-1-propene (R1234yf).

[0445] The refrigerant A according to the present disclosure has various properties that are desirable as an R410A-alternative refrigerant, i.e., a refrigerating capacity and a coefficient of performance that are equivalent to those of R410A, and a sufficiently low GWP.

[0446] The refrigerant A according to the present disclosure is a composition comprising HFO-1132(E) and R1234yf, and optionally further comprising HFO-1123, and may further satisfy the following requirements. This refrigerant also has various properties desirable as an alternative refrigerant for R410A; i.e., it has a refrigerating capacity and a coefficient of performance that are equivalent to those of R410A, and a sufficiently low GWP.

Requirements

[0447] Preferable refrigerant A is as follows:

[0448] When the mass % of HFO-1132(E), HFO-1123, and R1234yf based on their sum in the refrigerant is respectively represented by x, y, and z, coordinates (x,y,z) in a ternary composition diagram in which the sum of HFO-1132(E), HFO-1123, and R1234yf is 100 mass % are within the range of a figure surrounded by line segments AA', A'B, BD, DC', C'C, CO, and OA that connect the following 7 points:

[0449] point A (68.6, 0.0, 31.4),

[0450] point A' (30.6, 30.0, 39.4),

[0451] point B (0.0, 58.7, 41.3),

[0452] point D (0.0, 80.4, 19.6),

[0453] point C' (19.5, 70.5, 10.0),

[0454] point C (32.9, 67.1, 0.0), and

[0455] point O (100.0, 0.0, 0.0),

or on the above line segments (excluding the points on the line CO);

[0456] the line segment AA' is represented by coordinates (x, $0.0016x^2 - 0.9473x + 57.497$, $-0.0016x^2 - 0.0527x + 42.503$),

[0457] the line segment A'B is represented by coordinates (x, $0.0029x^2 - 1.0268x + 58.7$, $-0.0029x^2 + 0.0268x + 41.3$),

[0458] the line segment DC' is represented by coordinates (x, $0.0082x^2 - 0.6671x + 80.4$, $-0.0082x^2 - 0.3329x + 19.6$),

[0459] the line segment C'C is represented by coordinates (x, $0.0067x^2 - 0.6034x + 79.729$, $-0.0067x^2 - 0.3966x + 20.271$), and

[0460] the line segments BD, CO, and OA are straight lines.

[0461] When the requirements above are satisfied, the refrigerant according to the present disclosure has a refrigerating capacity ratio of 85% or more relative to that of R410A, and a COP of 92.5% or more relative to that of R410A.

[0462] When the mass % of HFO-1132(E), HFO-1123, and R1234yf, based on their sum in the refrigerant A

according to the present disclosure is respectively represented by x , y , and z , the refrigerant is preferably a refrigerant wherein coordinates (x,y,z) in a ternary composition diagram in which the sum of HFO-1132(E), HFO-1123, and R1234yf is 100 mass % are within a figure surrounded by line segments GI, IA, AA', A'B, BD, DC', C'C, and CG that connect the following 8 points:

- [0463] point G (72.0, 28.0, 0.0),
- [0464] point I (72.0, 0.0, 28.0),
- [0465] point A (68.6, 0.0, 31.4),
- [0466] point A' (30.6, 30.0, 39.4),
- [0467] point B (0.0, 58.7, 41.3),
- [0468] point D (0.0, 80.4, 19.6),
- [0469] point C' (19.5, 70.5, 10.0), and
- [0470] point C (32.9, 67.1, 0.0),

or on the above line segments (excluding the points on the line segment CG);

[0471] the line segment AA' is represented by coordinates $(x, 0.0016x^2-0.9473x+57.497, -0.0016x^2-0.0527x+42.503)$,

[0472] the line segment A'B is represented by coordinates $(x, 0.0029x^2-1.0268x+58.7, -0.0029x^2+0.0268x+41.3)$,

[0473] the line segment DC' is represented by coordinates $(x, 0.0082x^2-0.6671x+80.4, -0.0082x^2-0.3329x+19.6)$,

[0474] the line segment C'C is represented by coordinates $(x, 0.0067x^2-0.6034x+79.729, -0.0067x^2-0.3966x+20.271)$, and

[0475] the line segments GI, IA, BD, and CG are straight lines.

[0476] When the requirements above are satisfied, the refrigerant A according to the present disclosure has a refrigerating capacity ratio of 85% or more relative to that of R410A, and a COP of 92.5% or more relative to that of R410A; furthermore, the refrigerant A has a WCF lower flammability according to the ASHRAE Standard (the WCF composition has a burning velocity of 10 cm/s or less).

[0477] When the mass % of HFO-1132(E), HFO-1123, and R1234yf based on their sum in the refrigerant according to the present disclosure is respectively represented by x , y , and z , the refrigerant is preferably a refrigerant wherein coordinates (x,y,z) in a ternary composition diagram in which the sum of HFO-1132(E), HFO-1123, and R1234yf is 100 mass % are within the range of a figure surrounded by line segments JP, PN, NK, KA', A'B, BD, DC', C'C, and CJ that connect the following 9 points:

- [0478] point J (47.1, 52.9, 0.0),
- [0479] point P (55.8, 42.0, 2.2),
- [0480] point N (68.6, 16.3, 15.1),
- [0481] point K (61.3, 5.4, 33.3),
- [0482] point A' (30.6, 30.0, 39.4),
- [0483] point B (0.0, 58.7, 41.3),
- [0484] point D (0.0, 80.4, 19.6),
- [0485] point C' (19.5, 70.5, 10.0), and
- [0486] point C (32.9, 67.1, 0.0),

or on the above line segments (excluding the points on the line segment CJ);

[0487] the line segment PN is represented by coordinates $(x, -0.1135x^2+12.112x-280.43, 0.1135x^2-13.112x+380.43)$,

[0488] the line segment NK is represented by coordinates $(x, 0.2421x^2-29.955x+931.91, -0.2421x^2+28.955x-831.91)$,

[0489] the line segment KA' is represented by coordinates $(x, 0.0016x^2-0.9473x+57.497, -0.0016x^2-0.0527x+42.503)$,

[0490] the line segment A'B is represented by coordinates $(x, 0.0029x^2-1.0268x+58.7, -0.0029x^2+0.0268x+41.3)$,

[0491] the line segment DC' is represented by coordinates $(x, 0.0082x^2-0.6671x+80.4, -0.0082x^2-0.3329x+19.6)$,

[0492] the line segment C'C is represented by coordinates $(x, 0.0067x^2-0.6034x+79.729, -0.0067x^2-0.3966x+20.271)$, and

[0493] the line segments JP, BD, and CG are straight lines.

[0494] When the requirements above are satisfied, the refrigerant A according to the present disclosure has a refrigerating capacity ratio of 85% or more relative to that of R410A, and a COP of 92.5% or more relative to that of R410A; furthermore, the refrigerant exhibits a lower flammability (Class 2L) according to the ASHRAE Standard (the WCF composition and the WCF composition have a burning velocity of 10 cm/s or less).

[0495] When the mass % of HFO-1132(E), HFO-1123, and R1234yf based on their sum in the refrigerant according to the present disclosure is respectively represented by x , y , and z , the refrigerant is preferably a refrigerant wherein coordinates (x,y,z) in a ternary composition diagram in which the sum of HFO-1132(E), HFO-1123, and R1234yf is 100 mass % are within the range of a figure surrounded by line segments JP, PL, LM, MA', A'B, BD, DC', C' C, and CJ that connect the following 9 points:

- [0496] point J (47.1, 52.9, 0.0),
- [0497] point P (55.8, 42.0, 2.2),
- [0498] point L (63.1, 31.9, 5.0),
- [0499] point M (60.3, 6.2, 33.5),
- [0500] point A' (30.6, 30.0, 39.4),
- [0501] point B (0.0, 58.7, 41.3),
- [0502] point D (0.0, 80.4, 19.6),
- [0503] point C' (19.5, 70.5, 10.0), and
- [0504] point (32.9, 67.1, 0.0),

or on the above line segments (excluding the points on the line segment CJ);

[0505] the line segment PL is represented by coordinates $(x, -0.1135x^2+12.112x-280.43, 0.1135x^2-13.112x+380.43)$,

[0506] the line segment MA' is represented by coordinates $(x, 0.0016x^2-0.9473x+57.497, -0.0016x^2-0.0527x+42.503)$,

[0507] the line segment A'B is represented by coordinates $(x, 0.0029x^2-1.0268x+58.7, -0.0029x^2+0.0268x+41.3)$,

[0508] the line segment DC' is represented by coordinates $(x, 0.0082x^2-0.6671x+80.4, -0.0082x^2-0.3329x+19.6)$,

[0509] the line segment C'C is represented by coordinates $(x, 0.0067x^2-0.6034x+79.729, -0.0067x^2-0.3966x+20.271)$, and

[0510] the line segments JP, LM, BD, and CG are straight lines.

[0511] When the requirements above are satisfied, the refrigerant according to the present disclosure has a refrigerating capacity ratio of 85% or more relative to that of R410A, and a COP of 92.5% or more relative to that of R410A; furthermore, the refrigerant has an RCL of 40 g/m³ or more.

[0512] When the mass % of HFO-1132(E), HFO-1123, and R1234yf based on their sum in the refrigerant A according to the present disclosure is respectively represented by x , y , and z , the refrigerant is preferably a refrigerant wherein

coordinates (x,y,z) in a ternary composition diagram in which the sum of HFO-1132(E), HFO-1123, and R1234yf is 100 mass % are within the range of a figure surrounded by line segments PL, LM, MA', A'B, BF, FT, and TP that connect the following 7 points:

- [0513] point P (55.8, 42.0, 2.2),
- [0514] point L (63.1, 31.9, 5.0),
- [0515] point M (60.3, 6.2, 33.5),
- [0516] point A' (30.6, 30.0, 39.4),
- [0517] point B (0.0, 58.7, 41.3),
- [0518] point F (0.0, 61.8, 38.2), and
- [0519] point T (35.8, 44.9, 19.3),

or on the above line segments (excluding the points on the line segment BF);

[0520] the line segment PL is represented by coordinates $(x, -0.1135x^2+12.112x-280.43, 0.1135x^2-13.112x+380.43)$,

[0521] the line segment MA' is represented by coordinates $(x, 0.0016x^2-0.9473x+57.497, -0.0016x^2-0.0527x+42.503)$,

[0522] the line segment A'B is represented by coordinates $(x, 0.0029x^2-1.0268x+58.7, -0.0029x^2+0.0268x+41.3)$,

[0523] the line segment FT is represented by coordinates $(x, 0.0078x^2-0.7501x+61.8, -0.0078x^2-0.2499x+38.2)$,

[0524] the line segment TP is represented by coordinates $(x, 0.00672x^2-0.7607x+63.525, -0.00672x^2-0.2393x+36.475)$, and

[0525] the line segments LM and BF are straight lines.

[0526] When the requirements above are satisfied, the refrigerant according to the present disclosure has a refrigerating capacity ratio of 85% or more relative to that of R410A, and a COP of 95% or more relative to that of R410A; furthermore, the refrigerant has an RCL of 40 g/m³ or more.

[0527] The refrigerant A according to the present disclosure is preferably a refrigerant wherein when the mass % of HFO-1132(E), HFO-1123, and R1234yf based on their sum in the refrigerant is respectively represented by x, y, and z, coordinates (x,y,z) in a ternary composition diagram in which the sum of HFO-1132(E), HFO-1123, and R1234yf is 100 mass % are within the range of a figure surrounded by line segments PL, LQ, QR, and RP that connect the following 4 points:

- [0528] point P (55.8, 42.0, 2.2),
- [0529] point L (63.1, 31.9, 5.0),
- [0530] point Q (62.8, 29.6, 7.6), and
- [0531] point R (49.8, 42.3, 7.9),

or on the above line segments;

[0532] the line segment PL is represented by coordinates $(x, -0.1135x^2+12.112x-280.43, 0.1135x^2-13.112x+380.43)$,

[0533] the line segment RP is represented by coordinates $(x, 0.00672x^2-0.7607x+63.525, -0.00672x^2-0.2393x+36.475)$, and

[0534] the line segments LQ and QR are straight lines.

[0535] When the requirements above are satisfied, the refrigerant according to the present disclosure has a COP of 95% or more relative to that of R410A, and an RCL of 40 g/m³ or more, furthermore, the refrigerant has a condensation temperature glide of 1° C. or less.

[0536] The refrigerant A according to the present disclosure is preferably a refrigerant wherein when the mass % of HFO-1132(E), HFO-1123, and R1234yf based on their sum in the refrigerant is respectively represented by x, y, and z,

coordinates (x,y,z) in a ternary composition diagram in which the sum of HFO-1132(E), HFO-1123, and R1234yf is 100 mass % are within the range of a figure surrounded by line segments SM, MA', A'B, BF, FT, and TS that connect the following 6 points:

- [0537] point S (62.6, 28.3, 9.1),
- [0538] point M (60.3, 6.2, 33.5),
- [0539] point A' (30.6, 30.0, 39.4),
- [0540] point B (0.0, 58.7, 41.3),
- [0541] point F (0.0, 61.8, 38.2), and
- [0542] point T (35.8, 44.9, 19.3),

or on the above line segments,

[0543] the line segment MA' is represented by coordinates $(x, 0.0016x^2-0.9473x+57.497, -0.0016x^2-0.0527x+42.503)$,

[0544] the line segment A'B is represented by coordinates $(x, 0.0029x^2-1.0268x+58.7, -0.0029x^2+0.0268x+41.3)$,

[0545] the line segment FT is represented by coordinates $(x, 0.0078x^2-0.7501x+61.8, -0.0078x^2-0.2499x+38.2)$,

[0546] the line segment TS is represented by coordinates $(x, -0.0017x^2-0.7869x+70.888, -0.0017x^2-0.2131x+29.112)$, and

[0547] the line segments SM and BF are straight lines.

[0548] When the requirements above are satisfied, the refrigerant according to the present disclosure has a refrigerating capacity ratio of 85% or more relative to that of R410A, a COP of 95% or more relative to that of R410A, and an RCL of 40 g/m³ or more furthermore, the refrigerant has a discharge pressure of 105% or more relative to that of R410A.

[0549] The refrigerant A according to the present disclosure is preferably a refrigerant wherein when the mass % of HFO-1132(E), HFO-1123, and R1234yf based on their sum in the refrigerant is respectively represented by x, y, and z, coordinates (x,y,z) in a ternary composition diagram in which the sum of HFO-1132(E), HFO-1123, and R1234yf is 100 mass % are within the range of a figure surrounded by line segments Od, dg, gh, and hO that connect the following 4 points:

- [0550] point d (87.6, 0.0, 12.4),
- [0551] point g (18.2, 55.1, 26.7),
- [0552] point h (56.7, 43.3, 0.0), and
- [0553] point o (100.0, 0.0, 0.0),

or on the line segments Od, dg, gh, and hO (excluding the points O and h);

[0554] the line segment dg is represented by coordinates $(0.0047y^2-1.5177y+87.598, y, -0.0047y^2+0.5177y+12.402)$,

[0555] the line segment gh is represented by coordinates $(-0.0134z^2-1.0825z+56.692, 0.0134z^2+0.0825z+43.308, z)$, and

[0556] the line segments hO and Od are straight lines.

[0557] When the requirements above are satisfied, the refrigerant according to the present disclosure has a refrigerating capacity ratio of 92.5% or more relative to that of R410A, and a COP ratio of 92.5% or more relative to that of R410A.

[0558] The refrigerant A according to the present disclosure is preferably a refrigerant wherein

[0559] when the mass % of HFO-1132(E), HFO-1123, and R1234yf, based on their sum is respectively represented by x, y, and z, coordinates (x,y,z) in a ternary composition diagram in which the sum of HFO-1132(E), HFO-1123, and

R1234yf is 100 mass % are within the range of a figure surrounded by line segments lg, gh, hi, and il that connect the following 4 points:

[0560] point l (72.5, 10.2, 17.3),

[0561] point g (18.2, 55.1, 26.7),

[0562] point h (56.7, 43.3, 0.0), and

[0563] point i (72.5, 27.5, 0.0) or

on the line segments lg, gh, and il (excluding the points h and i);

[0564] the line segment lg is represented by coordinates $(0.0047y^2 - 1.5177y + 87.598, y, -0.0047y^2 + 0.5177y + 12.402)$,

[0565] the line gh is represented by coordinates $(-0.0134z^2 - 1.0825z + 56.692, 0.0134z^2 + 0.0825z + 43.308, z)$, and

[0566] the line segments hi and il are straight lines.

[0567] When the requirements above are satisfied, the refrigerant according to the present disclosure has a refrigerating capacity ratio of 92.5% or more relative to that of R410A, and a COP ratio of 92.5% or more relative to that of R410A; furthermore, the refrigerant has a lower flammability (Class 2L) according to the ASHRAE Standard.

[0568] The refrigerant A according to the present disclosure is preferably a refrigerant wherein

[0569] when the mass % of HFO-1132(E), HFO-1123, and R1234yf based on their sum is respectively represented by x, y, and z, coordinates (x,y,z) in a ternary composition diagram in which the sum of HFO-1132(E), HFO-1123, and R1234yf is 100 mass % are within the range of a figure surrounded by line segments Od, de, ef, and fO that connect the following 4 points:

[0570] point d (87.6, 0.0, 12.4),

[0571] point e (31.1, 42.9, 26.0),

[0572] point f (65.5, 34.5, 0.0), and

[0573] point O (100.0, 0.0, 0.0),

or on the line segments Od, de, and ef (excluding the points O and f);

[0574] the line segment de is represented by coordinates $(0.0047y^2 - 1.5177y + 87.598, y, -0.0047y^2 + 0.5177y + 12.402)$,

[0575] the line segment ef is represented by coordinates $(-0.0064z^2 - 1.1565z + 65.501, 0.0064z^2 + 0.1565z + 34.499, z)$, and

[0576] the line segments fO and Od are straight lines.

[0577] When the requirements above are satisfied, the refrigerant according to the present disclosure has a refrigerating capacity ratio of 93.5% or more relative to that of R410A, and a COP ratio of 93.5% or more relative to that of R410A.

[0578] The refrigerant A according to the present disclosure is preferably a refrigerant wherein

[0579] when the mass % of HFO-1132(E), HFO-1123, and R1234yf based on their sum is respectively represented by x, y, and z,

[0580] coordinates (x,y,z) in a ternary composition diagram in which the sum of HFO-1132(E), HFO-1123, and R1234yf is 100 mass % are within the range of a figure surrounded by line segments le, ef, fi, and il that connect the following 4 points:

[0581] point l (72.5, 10.2, 17.3),

[0582] point e (31.1, 42.9, 26.0),

[0583] point f (65.5, 34.5, 0.0), and

[0584] point i (72.5, 27.5, 0.0),

or on the line segments le, ef, and il (excluding the points f and i);

[0585] the line segment le is represented by coordinates $(0.0047y^2 - 1.5177y + 87.598, y, -0.0047y^2 + 0.5177y + 12.402)$,

[0586] the line segment ef is represented by coordinates $(-0.0134z^2 - 1.0825z + 56.692, 0.0134z^2 + 0.0825z + 43.308, z)$, and

[0587] the line segments fi and il are straight lines.

[0588] When the requirements above are satisfied, the refrigerant according to the present disclosure has a refrigerating capacity ratio of 93.5% or more relative to that of R410A, and a COP ratio of 93.5% or more relative to that of R410A; furthermore, the refrigerant has a lower flammability (Class 2L) according to the ASHRAE Standard.

[0589] The refrigerant A according to the present disclosure is preferably a refrigerant wherein

[0590] when the mass % of HFO-1132(E), HFO-1123, and R1234yf based on their sum is respectively represented by x, y, and z,

[0591] coordinates (x,y,z) in a ternary composition diagram in which the sum of HFO-1132(E), HFO-1123, and R1234yf is 100 mass % are within the range of a figure surrounded by line segments Oa, ab, bc, and cO that connect the following 4 points:

[0592] point a (93.4, 0.0, 6.6),

[0593] point b (55.6, 26.6, 17.8),

[0594] point c (77.6, 22.4, 0.0), and

[0595] point O (100.0, 0.0, 0.0),

or on the line segments Oa, ab, and bc (excluding the points O and c);

[0596] the line segment ab is represented by coordinates $(0.0052y^2 - 1.5588y + 93.385, y, -0.0052y^2 + 0.5588y + 6.615)$,

[0597] the line segment bc is represented by coordinates $(-0.0032z^2 - 1.1791z + 77.593, 0.0032z^2 + 0.1791z + 22.407, z)$, and

[0598] the line segments cO and Oa are straight lines.

[0599] When the requirements above are satisfied, the refrigerant according to the present disclosure has a refrigerating capacity ratio of 95% or more relative to that of R410A, and a COP ratio of 95% or more relative to that of R410A.

[0600] The refrigerant A according to the present disclosure is preferably a refrigerant wherein

[0601] when the mass % of HFO-1132(E), HFO-1123, and R1234yf based on their sum is respectively represented by x, y, and z,

[0602] coordinates (x,y,z) in a ternary composition diagram in which the sum of HFO-1132(E), HFO-1123, and R1234yf is 100 mass % are within the range of a figure surrounded by line segments kb, bj, and jk that connect the following 3 points:

[0603] point k (72.5, 14.1, 13.4),

[0604] point b (55.6, 26.6, 17.8), and

[0605] point j (72.5, 23.2, 4.3),

or on the line segments kb, bj, and jk;

[0606] the line segment kb is represented by coordinates $(0.0052y^2 - 1.5588y + 93.385, y, -0.0052y^2 + 0.5588y + 6.615)$,

[0607] the line segment bj is represented by coordinates $(-0.0032z^2 - 1.1791z + 77.593, 0.0032z^2 + 0.1791z + 22.407, z)$, and

[0608] the line segment jk is a straight line.

[0609] When the requirements above are satisfied, the refrigerant according to the present disclosure has a refrigerating capacity ratio of 95% or more relative to that of R410A, and a COP ratio of 95% or more relative to that of R410A; furthermore, the refrigerant has a lower flammability (Class 2L) according to the ASHRAE Standard.

[0610] The refrigerant according to the present disclosure may further comprise other additional refrigerants in addition to HFO-1132(E), HFO-1123, and R1234yf, as long as the above properties and effects are not impaired. In this respect, the refrigerant according to the present disclosure preferably comprises HFO-1132(E), HFO-1123, and R1234yf in a total amount of 99.5 mass % or more, more preferably 99.75 mass % or more, and still more preferably 99.9 mass % or more, based on the entire refrigerant.

[0611] The refrigerant according to the present disclosure may comprise HFO-1132(E), HFO-1123, and R1234yf in a total amount of 99.5 mass % or more, 99.75 mass % or more, or 99.9 mass % or more, based on the entire refrigerant.

[0612] Additional refrigerants are not particularly limited and can be widely selected. The mixed refrigerant may contain one additional refrigerant, or two or more additional refrigerants.

(Examples of Refrigerant A)

[0613] The present disclosure is described in more detail below with reference to Examples of refrigerant A. However, refrigerant A is not limited to the Examples.

[0614] The GWP of R1234yf and a composition consisting of a mixed refrigerant R410A (R32=50%/R125=50%) was evaluated based on the values stated in the Intergovernmental Panel on Climate Change (IPCC), fourth report. The GWP of HFO-1132(E), which was not stated therein, was assumed to be 1 from HFO-1132a (GWP=1 or less) and HFO-1123 (GWP=0.3, described in Patent Literature 1). The refrigerating capacity of R410A and compositions each comprising a mixture of HFO-1132(E), HFO-1123, and R1234yf was determined by performing theoretical refrigeration cycle calculations for the mixed refrigerants using the National Institute of Science and Technology (NIST) and Reference Fluid Thermodynamic and Transport Properties Database (Refprop 9.0) under the following conditions.

[0615] Further, the RCL of the mixture was calculated with the LFL of HFO-1132(E) being 4.7 vol. %, the LFL of HFO-1123 being 10 vol. %, and the LFL of R1234yf being 6.2 vol. %, in accordance with the ASHRAE Standard 34-2013.

[0616] Evaporating temperature: 5° C.

[0617] Condensation temperature: 45° C.

[0618] Degree of superheating: 5 K

[0619] Degree of subcooling: 5 K

[0620] Compressor efficiency: 70%

[0621] Tables 1 to 34 show these values together with the GWP of each mixed refrigerant.

TABLE 1

Item	Unit	Comp.	Comp.	Comp.	Example 1	Example	Example 3	Comp.
		Ex. 1	Ex. 2	Ex. 3		2		Ex. 4
HFO-1132(E)	mass %	R410A	100.0	68.6	49.0	30.6	14.1	0.0
HFO-1123	mass %		0.0	0.0	14.9	30.0	44.8	58.7
R1234yf	mass %		0.0	31.4	36.1	39.4	41.1	41.3
GWP	—	2088	1	2	2	2	2	2
COP ratio	% (relative to 410A)	100	99.7	100.0	98.6	97.3	96.3	95.5
Refrigerating capacity ratio	% (relative to 410A)	100	98.3	85.0	85.0	85.0	85.0	85.0
Condensation glide	° C.	0.1	0.00	1.98	3.36	4.46	5.15	5.35
Discharge pressure	% (relative to 410A)	100.0	99.3	87.1	88.9	90.6	92.1	93.2
RCL	g/m ³	—	30.7	37.5	44.0	52.7	64.0	78.6

TABLE 2

Item	Unit	Comp.	Example 4	Example	Example 6	Comp.	Comp.	Example	Comp.
		Ex. 5		5		Ex. 6	Ex. 7	7	Ex. 8
HFO-1132(E)	mass %	32.9	26.6	19.5	10.9	0.0	58.0	23.4	0.0
HFO-1123	mass %	67.1	68.4	70.5	74.1	80.4	42.0	48.5	61.8
R1234yf	mass %	0.0	5.0	10.0	15.0	19.6	0.0	28.1	38.2
GWP	—	1	1	1	1	2	1	2	2
COP ratio	% (relative to 410A)	92.5	92.5	92.5	92.5	92.5	95.0	95.0	95.0
Refrigerating capacity ratio	% (relative to 410A)	107.4	105.2	102.9	100.5	97.9	105.0	92.5	86.9
Condensation glide	° C.	0.16	0.52	0.94	1.42	1.90	0.42	3.16	4.80
Discharge pressure	% (relative to 410A)	119.5	117.4	115.3	113.0	115.9	112.7	101.0	95.8
RCL	g/m ³	53.5	57.1	62.0	69.1	81.3	41.9	46.3	79.0

TABLE 3

Item	Unit	Comp. Ex. 9 J	Example 8 P	Example 9 L	Example 10 N	Example 11 N'	Example 12 K
HFO-1132(E)	mass %	47.1	55.8	63.1	68.6	65.0	61.3
HFO-1123	mass %	52.9	42.0	31.9	16.3	7.7	5.4
R1234yf	mass %	0.0	2.2	5.0	15.1	27.3	33.3
GWP	—	1	1	1	1	2	2
COP ratio	% (relative to 410A)	93.8	95.0	96.1	97.9	99.1	99.5
Refrigerating capacity ratio	% (relative to 410A)	106.2	104.1	101.6	95.0	88.2	85.0
Condensation glide	° C.	0.31	0.57	0.81	1.41	2.11	2.51
Discharge pressure	% (relative to 410A)	115.8	111.9	107.8	99.0	91.2	87.7
RCL	g/m ³	46.2	42.6	40.0	38.0	38.7	39.7

TABLE 4

Item	Unit	Example 13 L	Example 14 M	Example 15 Q	Example 16 R	Example 17 S	Example 18 S'	Example 19 T
HFO-1132(E)	mass %	63.1	60.3	62.8	49.8	62.6	50.0	35.8
HFO-1123	mass %	31.9	6.2	29.6	42.3	28.3	35.8	44.9
R1234yf	mass %	5.0	33.5	7.6	7.9	9.1	14.2	19.3
GWP	—	1	2	1	1	1	1	2
COP ratio	% (relative to 410A)	96.1	99.4	96.4	95.0	96.6	95.8	95.0
Refrigerating capacity ratio	% (relative to 410A)	101.6	85.0	100.2	101.7	99.4	98.1	96.7
Condensation glide	° C.	0.81	2.58	1.00	1.00	1.10	1.55	2.07
Discharge pressure	% (relative to 410A)	107.8	87.9	106.0	109.6	105.0	105.0	105.0
RCL	g/m ³	40.0	40.0	40.0	44.8	40.0	44.4	50.8

TABLE 5

Item	Unit	Comp. Ex. 10 G	Example 20 H	Example 21 I
HFO-1132(E)	mass %	72.0	72.0	72.0
HFO-1123	mass %	28.0	14.0	0.0
R1234yf	mass %	0.0	14.0	28.0
GWP	—	1	1	2
COP ratio	% (relative to 410A)	96.6	98.2	99.9

TABLE 5-continued

Item	Unit	Comp. Ex. 10 G	Example 20 H	Example 21 I
Refrigerating capacity ratio	% (relative to 410A)	103.1	95.1	86.6
Condensation glide	° C.	0.46	1.27	1.71
Discharge pressure	% (relative to 410A)	108.4	98.7	88.6
RCL	g/m ³	37.4	37.0	36.6

TABLE 6

Item	Unit	Comp. Ex. 11	Comp. Ex. 12	Example 22	Example 23	Example 24	Example 25	Example 26	Comp. Ex. 13
HFO-1132(E)	mass %	10.0	20.0	30.0	40.0	50.0	60.0	70.0	80.0
HFO-1123	mass %	85.0	75.0	65.0	55.0	45.0	35.0	25.0	15.0
R1234yf	mass %	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0
GWP	—	1	1	1	1	1	1	1	1
COP ratio	% (relative to 410A)	91.4	92.0	92.8	93.7	94.7	95.8	96.9	98.0
Refrigerating capacity ratio	% (relative to 410A)	105.7	105.5	105.0	104.3	103.3	102.0	100.6	99.1
Condensation glide	° C.	0.40	0.46	0.55	0.66	0.75	0.80	0.79	0.67
Discharge pressure	% (relative to 410A)	120.1	118.7	116.7	114.3	111.6	108.7	105.6	102.5
RCL	g/m ³	71.0	61.9	54.9	49.3	44.8	41.0	37.8	35.1

TABLE 7

Item	Unit	Comp. Ex. 14	Example 27	Example 28	Example 29	Example 30	Example 31	Example 32	Comp. Ex. 15
HFO-1132(E)	mass %	10.0	20.0	30.0	40.0	50.0	60.0	70.0	80.0
HFO-1123	mass %	80.0	70.0	60.0	50.0	40.0	30.0	20.0	10.0
R1234yf	mass %	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
GWP	—	1	1	1	1	1	1	1	1
COP ratio	% (relative to 410A)	91.9	92.5	93.3	94.3	95.3	96.4	97.5	98.6
Refrigerating capacity ratio	% (relative to 410A)	103.2	102.9	102.4	101.5	100.5	99.2	97.8	96.2
Condensation glide	° C.	0.87	0.94	1.03	1.12	1.18	1.18	1.09	0.88
Discharge pressure	% (relative to 410A)	116.7	115.2	113.2	110.8	108.1	105.2	102.1	99.0
RCL	g/m ³	70.5	61.6	54.6	49.1	44.6	40.8	37.7	35.0

TABLE 8

Item	Unit	Comp. Ex. 16	Example 33	Example 34	Example 35	Example 36	Example 37	Example 38	Comp. Ex. 17
HFO-1132(E)	mass %	10.0	20.0	30.0	40.0	50.0	60.0	70.0	80.0
HFO-1123	mass %	75.0	65.0	55.0	45.0	35.0	25.0	15.0	5.0
R1234yf	mass %	15.0	15.0	15.0	15.0	15.0	15.0	15.0	15.0
GWP	—	1	1	1	1	1	1	1	1
COP ratio	% (relative to 410A)	92.4	93.1	93.9	94.8	95.9	97.0	98.1	99.2
Refrigerating capacity ratio	% (relative to 410A)	100.5	100.2	99.6	98.7	97.7	96.4	94.9	93.2
Condensation glide	° C.	1.41	1.49	1.56	1.62	1.63	1.55	1.37	1.05
Discharge pressure	% (relative to 410A)	113.1	111.6	109.6	107.2	104.5	101.6	98.6	95.5
RCL	g/m ³	70.0	61.2	54.4	48.9	44.4	40.7	37.5	34.8

TABLE 9

Item	Unit	Example 39	Example 40	Example 41	Example 42	Example 43	Example 44	Example 45
HFO-1132(E)	mass %	10.0	20.0	30.0	40.0	50.0	60.0	70.0
HFO-1123	mass %	70.0	60.0	50.0	40.0	30.0	20.0	10.0
R1234yf	mass %	20.0	20.0	20.0	20.0	20.0	20.0	20.0
GWP	—	2	2	2	2	2	2	2
COP ratio	% (relative to 410A)	93.0	93.7	94.5	95.5	96.5	97.6	98.7
Refrigerating capacity ratio	% (relative to 410A)	97.7	97.4	96.8	95.9	94.7	93.4	91.9
Condensation glide	° C.	2.03	2.09	2.13	2.14	2.07	1.91	1.61
Discharge pressure	% (relative to 410A)	109.4	107.9	105.9	103.5	100.8	98.0	95.0
RCL	g/m ³	69.6	60.9	54.1	48.7	44.2	40.5	37.4

TABLE 10

Item	Unit	Example 46	Example 47	Example 48	Example 49	Example 50	Example 51	Example 52
HFO-1132(E)	mass %	10.0	20.0	30.0	40.0	50.0	60.0	70.0
HFO-1123	mass %	65.0	55.0	45.0	35.0	25.0	15.0	5.0
R1234yf	mass %	25.0	25.0	25.0	25.0	25.0	25.0	25.0
GWP	—	2	2	2	2	2	2	2
COP ratio	% (relative to 410A)	93.6	94.3	95.2	96.1	97.2	98.2	99.3
Refrigerating capacity ratio	% (relative to 410A)	94.8	94.5	93.8	92.9	91.8	90.4	88.8
Condensation glide	° C.	2.71	2.74	2.73	2.66	2.50	2.22	1.78
Discharge pressure	% (relative to 410A)	105.5	104.0	102.1	99.7	97.1	94.3	91.4
RCL	g/m ³	69.1	60.5	53.8	48.4	44.0	40.4	37.3

TABLE 11

Item	Unit	Example 53	Example 54	Example 55	Example 56	Example 57	Example 58
HFO-1132(E)	mass %	10.0	20.0	30.0	40.0	50.0	60.0
HFO-1123	mass %	60.0	50.0	40.0	30.0	20.0	10.0
R1234yf	mass %	30.0	30.0	30.0	30.0	30.0	30.0
GWP	—	2	2	2	2	2	2
COP ratio	% (relative to 410A)	94.3	95.0	95.9	96.8	97.8	98.9
Refrigerating capacity ratio	% (relative to 410A)	91.9	91.5	90.8	89.9	88.7	87.3
Condensation glide	° C.	3.46	3.43	3.35	3.18	2.90	2.47
Discharge pressure	% (relative to 410A)	101.6	100.1	98.2	95.9	93.3	90.6
RCL	g/m ³	68.7	60.2	53.5	48.2	43.9	40.2

TABLE 12

Item	Unit	Example 59	Example 60	Example 61	Example 62	Example 63	Comp. Ex. 18
HFO-1132(E)	mass %	10.0	20.0	30.0	40.0	50.0	60.0
HFO-1123	mass %	55.0	45.0	35.0	25.0	15.0	5.0
R1234yf	mass %	35.0	35.0	35.0	35.0	35.0	35.0
GWP	—	2	2	2	2	2	2
COP ratio	% (relative to 410A)	95.0	95.8	96.6	97.5	98.5	99.6
Refrigerating capacity ratio	% (relative to 410A)	88.9	88.5	87.8	86.8	85.6	84.1
Condensation glide	° C.	4.24	4.15	3.96	3.67	3.24	2.64
Discharge pressure	% (relative to 410A)	97.6	96.1	94.2	92.0	89.5	86.8
RCL	g/m ³	68.2	59.8	53.2	48.0	43.7	40.1

TABLE 13

Item	Unit	Example 64	Example 65	Comp.	Comp.	Comp.
				Ex. 19	Ex. 20	Ex. 21
HFO-1132(E)	mass %	10.0	20.0	30.0	40.0	50.0
HFO-1123	mass %	50.0	40.0	30.0	20.0	10.0
R1234yf	mass %	40.0	40.0	40.0	40.0	40.0
GWP	—	2	2	2	2	2
COP ratio	% (relative to 410A)	95.9	96.6	97.4	98.3	99.2

TABLE 13-continued

Item	Unit	Example 64	Example 65	Comp.	Comp.	Comp.
				Ex. 19	Ex. 20	Ex. 21
Refrigerating capacity ratio	% (relative to 410A)	85.8	85.4	84.7	83.6	82.4
Condensation glide	° C.	5.05	4.85	4.55	4.10	3.50
Discharge pressure	% (relative to 410A)	93.5	92.1	90.3	88.1	85.6
RCL	g/m ³	67.8	59.5	53.0	47.8	43.5

TABLE 14

Item	Unit	Example 66	Example 67	Example 68	Example 69	Example 70	Example 71	Example 72	Example 73
HFO-1132(E)	mass %	54.0	56.0	58.0	62.0	52.0	54.0	56.0	58.0
HFO-1123	mass %	41.0	39.0	37.0	33.0	41.0	39.0	37.0	35.0
R1234yf	mass %	5.0	5.0	5.0	5.0	7.0	7.0	7.0	7.0
GWP	—	1	1	1	1	1	1	1	1
COP ratio	% (relative to 410A)	95.1	95.3	95.6	96.0	95.1	95.4	95.6	95.8
Refrigerating capacity ratio	% (relative to 410A)	102.8	102.6	102.3	101.8	101.9	101.7	101.5	101.2
Condensation glide	° C.	0.78	0.79	0.80	0.81	0.93	0.94	0.95	0.95
Discharge pressure	% (relative to 410A)	110.5	109.9	109.3	108.1	109.7	109.1	108.5	107.9
RCL	g/m ³	43.2	42.4	41.7	40.3	43.9	43.1	42.4	41.6

TABLE 15

Item	Unit	Example 74	Example 75	Example 76	Example 77	Example 78	Example 79	Example 80	Example 81
HFO-1132(E)	mass %	60.0	62.0	61.0	58.0	60.0	62.0	52.0	54.0
HFO-1123	mass %	33.0	31.0	29.0	30.0	28.0	26.0	34.0	32.0
R1234yf	mass %	7.0	7.0	10.0	12.0	12.0	12.0	14.0	14.0
GWP	—	1	1	1	1	1	1	1	1
COP ratio	% (relative to 410A)	96.0	96.2	96.5	96.4	96.6	96.8	96.0	96.2
Refrigerating capacity ratio	% (relative to 410A)	100.9	100.7	99.1	98.4	98.1	97.8	98.0	97.7
Condensation glide	° C.	0.95	0.95	1.18	1.34	1.33	1.32	1.53	1.53
Discharge pressure	% (relative to 410A)	107.3	106.7	104.9	104.4	103.8	103.2	104.7	104.1
RCL	g/m ³	40.9	40.3	40.5	41.5	40.8	40.1	43.6	42.9

TABLE 16

Item	Unit	Example 82	Example 83	Example 84	Example 85	Example 86	Example 87	Example 88	Example 89
HFO-1132(E)	mass %	56.0	58.0	60.0	48.0	50.0	52.0	54.0	56.0
HFO-1123	mass %	30.0	28.0	26.0	36.0	34.0	32.0	30.0	28.0
R1234yf	mass %	14.0	14.0	14.0	16.0	16.0	16.0	16.0	16.0
GWP	—	1	1	1	1	1	1	1	1
COP ratio	% (relative to 410A)	96.4	96.6	96.9	95.8	96.0	96.2	96.4	96.7
Refrigerating capacity ratio	% (relative to 410A)	97.5	97.2	96.9	97.3	97.1	96.8	96.6	96.3
Condensation glide	° C.	1.51	1.50	1.48	1.72	1.72	1.71	1.69	1.67
Discharge pressure	% (relative to 410A)	103.5	102.9	102.3	104.3	103.8	103.2	102.7	102.1
RCL	g/m ³	42.1	41.4	40.7	45.2	44.4	43.6	42.8	42.1

TABLE 17

Item	Unit	Example 90	Example 91	Example 92	Example 93	Example 94	Example 95	Example 96	Example 97
HFO-1132(E)	mass %	58.0	60.0	42.0	44.0	46.0	48.0	50.0	52.0
HFO-1123	mass %	26.0	24.0	40.0	38.0	36.0	34.0	32.0	30.0
R1234yf	mass %	16.0	16.0	18.0	18.0	18.0	18.0	18.0	18.0
GWP	—	1	1	2	2	2	2	2	2
COP ratio	% (relative to 410A)	96.9	97.1	95.4	95.6	95.8	96.0	96.3	96.5
Refrigerating capacity ratio	% (relative to 410A)	96.1	95.8	96.8	96.6	96.4	96.2	95.9	95.7
Condensation glide	° C.	1.65	1.63	1.93	1.92	1.92	1.91	1.89	1.88
Discharge pressure	% (relative to 410A)	101.5	100.9	104.5	103.9	103.4	102.9	102.3	101.8
RCL	g/m ³	41.4	40.7	47.8	46.9	46.0	45.1	44.3	43.5

TABLE 18

Item	Unit	Example 98	Example 99	Example 100	Example 101	Example 102	Example 103	Example 104	Example 105
HFO-1132(E)	mass %	54.0	56.0	58.0	60.0	36.0	38.0	42.0	44.0
HFO-1123	mass %	28.0	26.0	24.0	22.0	44.0	42.0	38.0	36.0
R1234yf	mass %	18.0	18.0	18.0	18.0	20.0	20.0	20.0	20.0
GWP	—	2	2	2	2	2	2	2	2
COP ratio	% (relative to 410A)	96.7	96.9	97.1	97.3	95.1	95.3	95.7	95.9
Refrigerating capacity ratio	% (relative to 410A)	95.4	95.2	94.9	94.6	96.3	96.1	95.7	95.4
Condensation glide	° C.	1.86	1.83	1.80	1.77	2.14	2.14	2.13	2.12
Discharge pressure	% (relative to 410A)	101.2	100.6	100.0	99.5	104.5	104.0	103.0	102.5
RCL	g/m ³	42.7	42.0	41.3	40.6	50.7	49.7	47.7	46.8

TABLE 19

Item	Unit	Example 106	Example 107	Example 108	Example 109	Example 110	Example 111	Example 112	Example 113
HFO-1132(E)	mass %	46.0	48.0	52.0	54.0	56.0	58.0	34.0	36.0
HFO-1123	mass %	34.0	32.0	28.0	26.0	24.0	22.0	44.0	42.0
R1234yf	mass %	20.0	20.0	20.0	20.0	20.0	20.0	22.0	22.0
GWP	—	2	2	2	2	2	2	2	2
COP ratio	% (relative to 410A)	96.1	96.3	96.7	96.9	97.2	97.4	95.1	95.3
Refrigerating capacity ratio	% (relative to 410A)	95.2	95.0	94.5	94.2	94.0	93.7	95.3	95.1
Condensation glide	° C.	2.11	2.09	2.05	2.02	1.99	1.95	2.37	2.36
Discharge pressure	% (relative to 410A)	101.9	101.4	100.3	99.7	99.2	98.6	103.4	103.0
RCL	g/m ³	45.9	45.0	43.4	42.7	41.9	41.2	51.7	50.6

TABLE 20

Item	Unit	Example 114	Example 115	Example 116	Example 117	Example 118	Example 119	Example 120	Example 121
HFO-1132(E)	mass %	38.0	40.0	42.0	44.0	46.0	48.0	50.0	52.0
HFO-1123	mass %	40.0	38.0	36.0	34.0	32.0	30.0	28.0	26.0
R1234yf	mass %	22.0	22.0	22.0	22.0	22.0	22.0	22.0	22.0
GWP	—	2	2	2	2	2	2	2	2
COP ratio	% (relative to 410A)	95.5	95.7	95.9	96.1	96.4	96.6	96.8	97.0
Refrigerating capacity ratio	% (relative to 410A)	94.9	94.7	94.5	94.3	94.0	93.8	93.6	93.3
Condensation glide	° C.	2.36	2.35	2.33	2.32	2.30	2.27	2.25	2.21
Discharge pressure	% (relative to 410A)	102.5	102.0	101.5	101.0	100.4	99.9	99.4	98.8
RCL	g/m ³	49.6	48.6	47.6	46.7	45.8	45.0	44.1	43.4

TABLE 21

Item	Unit	Example 122	Example 123	Example 124	Example 125	Example 126	Example 127	Example 128	Example 129
HFO-1132(E)	mass %	54.0	56.0	58.0	60.0	32.0	34.0	36.0	38.0
HFO-1123	mass %	24.0	22.0	20.0	18.0	44.0	42.0	40.0	38.0
R1234yf	mass %	22.0	22.0	22.0	22.0	24.0	24.0	24.0	24.0
GWP	—	2	2	2	2	2	2	2	2
COP ratio	% (relative to 410A)	97.2	97.4	97.6	97.9	95.2	95.4	95.6	95.8
Refrigerating capacity ratio	% (relative to 410A)	93.0	92.8	92.5	92.2	94.3	94.1	93.9	93.7
Condensation glide	° C.	2.18	2.14	2.09	2.04	2.61	2.60	2.59	2.58
Discharge pressure	% (relative to 410A)	98.2	97.7	97.1	96.5	102.4	101.9	101.5	101.0
RCL	g/m ³	42.6	41.9	41.2	40.5	52.7	51.6	50.5	49.5

TABLE 22

Item	Unit	Example 130	Example 131	Example 132	Example 133	Example 134	Example 135	Example 136	Example 137
HFO-1132(E)	mass %	40.0	42.0	44.0	46.0	48.0	50.0	52.0	54.0
HFO-1123	mass %	36.0	34.0	32.0	30.0	28.0	26.0	24.0	22.0
R1234yf	mass %	24.0	24.0	24.0	24.0	24.0	24.0	24.0	24.0
GWP	—	2	2	2	2	2	2	2	2
COP ratio	% (relative to 410A)	96.0	96.2	96.4	96.6	96.8	97.0	97.2	97.5
Refrigerating capacity ratio	% (relative to 410A)	93.5	93.3	93.1	92.8	92.6	92.4	92.1	91.8
Condensation glide	° C.	2.56	2.54	2.51	2.49	2.45	2.42	2.38	2.33

TABLE 22-continued

Item	Unit	Example	Example	Example	Example	Example	Example	Example	Example
		130	131	132	133	134	135	136	137
Discharge pressure	% (relative to 410A)	100.5	100.0	99.5	98.9	98.4	97.9	97.3	96.8
RCL	g/m ³	48.5	47.5	46.6	45.7	44.9	44.1	43.3	42.5

TABLE 23

Item	Unit	Example	Example	Example	Example	Example	Example	Example	Example
		138	139	140	141	142	143	144	145
HFO-1132(E)	mass %	56.0	58.0	60.0	30.0	32.0	34.0	36.0	38.0
HFO-1123	mass %	20.0	18.0	16.0	44.0	42.0	40.0	38.0	36.0
R1234yf	mass %	24.0	24.0	24.0	26.0	26.0	26.0	26.0	26.0
GWP	—	2	2	2	2	2	2	2	2
COP ratio	% (relative to 410A)	97.7	97.9	98.1	95.3	95.5	95.7	95.9	96.1
Refrigerating capacity ratio	% (relative to 410A)	91.6	91.3	91.0	93.2	93.1	92.9	92.7	92.5
Condensation glide	° C.	2.28	2.22	2.16	2.86	2.85	2.83	2.81	2.79
Discharge pressure	% (relative to 410A)	96.2	95.6	95.1	101.3	100.8	100.4	99.9	99.4
RCL	g/m ³	41.8	41.1	40.4	53.7	52.6	51.5	50.4	49.4

TABLE 24

Item	Unit	Example	Example	Example	Example	Example	Example	Example	Example
		146	147	148	149	150	151	152	153
HFO-1132(E)	mass %	40.0	42.0	44.0	46.0	48.0	50.0	52.0	54.0
HFO-1123	mass %	34.0	32.0	30.0	28.0	26.0	24.0	22.0	20.0
R1234yf	mass %	26.0	26.0	26.0	26.0	26.0	26.0	26.0	26.0
GWP	—	2	2	2	2	2	2	2	2
COP ratio	% (relative to 410A)	96.3	96.5	96.7	96.9	97.1	97.3	97.5	97.7
Refrigerating capacity ratio	% (relative to 410A)	92.3	92.1	91.9	91.6	91.4	91.2	90.9	90.6
Condensation glide	° C.	2.77	2.74	2.71	2.67	2.63	2.59	2.53	2.48
Discharge pressure	% (relative to 410A)	99.0	98.5	97.9	97.4	96.9	96.4	95.8	95.3
RCL	g/m ³	48.4	47.4	46.5	45.7	44.8	44.0	43.2	42.5

TABLE 25

Item	Unit	Example	Example	Example	Example	Example	Example	Example	Example
		154	155	156	157	158	159	160	161
HFO-1132(E)	mass %	56.0	58.0	60.0	30.0	32.0	34.0	36.0	38.0
HFO-1123	mass %	18.0	16.0	14.0	42.0	40.0	38.0	36.0	34.0
R1234yf	mass %	26.0	26.0	26.0	28.0	28.0	28.0	28.0	28.0
GWP	—	2	2	2	2	2	2	2	2
COP ratio	% (relative to 410A)	97.9	98.2	98.4	95.6	95.8	96.0	96.2	96.3
Refrigerating capacity ratio	% (relative to 410A)	90.3	90.1	89.8	92.1	91.9	91.7	91.5	91.3
Condensation glide	° C.	2.42	2.35	2.27	3.10	3.09	3.06	3.04	3.01
Discharge pressure	% (relative to 410A)	94.7	94.1	93.6	99.7	99.3	98.8	98.4	97.9
RCL	g/m ³	41.7	41.0	40.3	53.6	52.5	51.4	50.3	49.3

TABLE 26

Item	Unit	Example 162	Example 163	Example 164	Example 165	Example 166	Example 167	Example 168	Example 169
HFO-1132(E)	mass %	40.0	42.0	44.0	46.0	48.0	50.0	52.0	54.0
HFO-1123	mass %	32.0	30.0	28.0	26.0	24.0	22.0	20.0	18.0
R1234yf	mass %	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0
GWP	—	2	2	2	2	2	2	2	2
COP ratio	% (relative to 410A)	96.5	96.7	96.9	97.2	97.4	97.6	97.8	98.0
Refrigerating capacity ratio	% (relative to 410A)	91.1	90.9	90.7	90.4	90.2	89.9	89.7	89.4
Condensation glide	° C.	2.98	2.94	2.90	2.85	2.80	2.75	2.68	2.62
Discharge pressure	% (relative to 410A)	97.4	96.9	96.4	95.9	95.4	94.9	94.3	93.8
RCL	g/m ³	48.3	47.4	46.4	45.6	44.7	43.9	43.1	42.4

TABLE 27

Item	Unit	Example 170	Example 171	Example 172	Example 173	Example 174	Example 175	Example 176	Example 177
HFO-1132(E)	mass %	56.0	58.0	60.0	32.0	34.0	36.0	38.0	42.0
HFO-1123	mass %	16.0	14.0	12.0	38.0	36.0	34.0	32.0	28.0
R1234yf	mass %	28.0	28.0	28.0	30.0	30.0	30.0	30.0	30.0
GWP	—	2	2	2	2	2	2	2	2
COP ratio	% (relative to 410A)	98.2	98.4	98.6	96.1	96.2	96.4	96.6	97.0
Refrigerating capacity ratio	% (relative to 410A)	89.1	88.8	88.5	90.7	90.5	90.3	90.1	89.7
Condensation glide	° C.	2.54	2.46	2.38	3.32	3.30	3.26	3.22	3.14
Discharge pressure	% (relative to 410A)	93.2	92.6	92.1	97.7	97.3	96.8	96.4	95.4
RCL	g/m ³	41.7	41.0	40.3	52.4	51.3	50.2	49.2	47.3

TABLE 28

Item	Unit	Example 178	Example 179	Example 180	Example 181	Example 182	Example 183	Example 184	Example 185
HFO-1132(E)	mass %	44.0	46.0	48.0	50.0	52.0	54.0	56.0	58.0
HFO-1123	mass %	26.0	24.0	22.0	20.0	18.0	16.0	14.0	12.0
R1234yf	mass %	30.0	30.0	30.0	30.0	30.0	30.0	30.0	30.0
GWP	—	2	2	2	2	2	2	2	2
COP ratio	% (relative to 410A)	97.2	97.4	97.6	97.8	98.0	98.3	98.5	98.7
Refrigerating capacity ratio	% (relative to 410A)	89.4	89.2	89.0	88.7	88.4	88.2	87.9	87.6
Condensation glide	° C.	3.08	3.03	2.97	2.90	2.83	2.75	2.66	2.57
Discharge pressure	% (relative to 410A)	94.9	94.4	93.9	93.3	92.8	92.3	91.7	91.1
RCL	g/m ³	46.4	45.5	44.7	43.9	43.1	42.3	41.6	40.9

TABLE 29

Item	Unit	Example 186	Example 187	Example 188	Example 189	Example 190	Example 191	Example 192	Example 193
HFO-1132(E)	mass %	30.0	32.0	34.0	36.0	38.0	40.0	42.0	44.0
HFO-1123	mass %	38.0	36.0	34.0	32.0	30.0	28.0	26.0	24.0
R1234yf	mass %	32.0	32.0	32.0	32.0	32.0	32.0	32.0	32.0
GWP	—	2	2	2	2	2	2	2	2
COP ratio	% (relative to 410A)	96.2	96.3	96.5	96.7	96.9	97.1	97.3	97.5
Refrigerating capacity ratio	% (relative to 410A)	89.6	89.5	89.3	89.1	88.9	88.7	88.4	88.2
Condensation glide	° C.	3.60	3.56	3.52	3.48	3.43	3.38	3.33	3.26

TABLE 29-continued

Item	Unit	Example	Example	Example	Example	Example	Example	Example	Example
		186	187	188	189	190	191	192	193
Discharge pressure	% (relative to 410A)	96.6	96.2	95.7	95.3	94.8	94.3	93.9	93.4
RCL	g/m ³	53.4	52.3	51.2	50.1	49.1	48.1	47.2	46.3

TABLE 30

Item	Unit	Example	Example	Example	Example	Example	Example	Example	Example
		194	195	196	197	198	199	200	201
HFO-1132(E)	mass %	46.0	48.0	50.0	52.0	54.0	56.0	58.0	60.0
HFO-1123	mass %	22.0	20.0	18.0	16.0	14.0	12.0	10.0	8.0
R1234yf	mass %	32.0	32.0	32.0	32.0	32.0	32.0	32.0	32.0
GWP	—	2	2	2	2	2	2	2	2
COP ratio	% (relative to 410A)	97.7	97.9	98.1	98.3	98.5	98.7	98.9	99.2
Refrigerating capacity ratio	% (relative to 410A)	88.0	87.7	87.5	87.2	86.9	86.6	86.3	86.0
Condensation glide	° C.	3.20	3.12	3.04	2.96	2.87	2.77	2.66	2.55
Discharge pressure	% (relative to 410A)	92.8	92.3	91.8	91.3	90.7	90.2	89.6	89.1
RCL	g/m ³	45.4	44.6	43.8	43.0	42.3	41.5	40.8	40.2

TABLE 31

Item	Unit	Example	Example	Example	Example	Example	Example	Example	Example
		202	203	204	205	206	207	208	209
HFO-1132(E)	mass %	30.0	32.0	34.0	36.0	38.0	40.0	42.0	44.0
HFO-1123	mass %	36.0	34.0	32.0	30.0	28.0	26.0	24.0	22.0
R1234yf	mass %	34.0	34.0	34.0	34.0	34.0	34.0	34.0	34.0
GWP	—	2	2	2	2	2	2	2	2
COP ratio	% (relative to 410A)	96.5	96.6	96.8	97.0	97.2	97.4	97.6	97.8
Refrigerating capacity ratio	% (relative to 410A)	88.4	88.2	88.0	87.8	87.6	87.4	87.2	87.0
Condensation glide	° C.	3.84	3.80	3.75	3.70	3.64	3.58	3.51	3.43
Discharge pressure	% (relative to 410A)	95.0	94.6	94.2	93.7	93.3	92.8	92.3	91.8
RCL	g/m ³	53.3	52.2	51.1	50.0	49.0	48.0	47.1	46.2

TABLE 32

Item	Unit	Example	Example	Example	Example	Example	Example	Example	Example
		210	211	212	213	214	215	216	217
HFO-1132(E)	mass %	46.0	48.0	50.0	52.0	54.0	30.0	32.0	34.0
HFO-1123	mass %	20.0	18.0	16.0	14.0	12.0	34.0	32.0	30.0
R1234yf	mass %	34.0	34.0	34.0	34.0	34.0	36.0	36.0	36.0
GWP	—	2	2	2	2	2	2	2	2
COP ratio	% (relative to 410A)	98.0	98.2	98.4	98.6	98.8	96.8	96.9	97.1
Refrigerating capacity ratio	% (relative to 410A)	86.7	86.5	86.2	85.9	85.6	87.2	87.0	86.8
Condensation glide	° C.	3.36	3.27	3.18	3.08	2.97	4.08	4.03	3.97
Discharge pressure	% (relative to 410A)	91.3	90.8	90.3	89.7	89.2	93.4	93.0	92.6
RCL	g/m ³	45.3	44.5	43.7	42.9	42.2	53.2	52.1	51.0

TABLE 33

Item	Unit	Example 218	Example 219	Example 220	Example 221	Example 222	Example 223	Example 224	Example 225
HFO-1132(E)	mass %	36.0	38.0	40.0	42.0	44.0	46.0	30.0	32.0
HFO-1123	mass %	28.0	26.0	24.0	22.0	20.0	18.0	32.0	30.0
R1234yf	mass %	36.0	36.0	36.0	36.0	36.0	36.0	38.0	38.0
GWP	—	2	2	2	2	2	2	2	2
COP ratio	% (relative to 410A)	97.3	97.5	97.7	97.9	98.1	98.3	97.1	97.2
Refrigerating capacity ratio	% (relative to 410A)	86.6	86.4	86.2	85.9	85.7	85.5	85.9	85.7
Condensation glide	° C.	3.91	3.84	3.76	3.68	3.60	3.50	4.32	4.25
Discharge pressure	% (relative to 410A)	92.1	91.7	91.2	90.7	90.3	89.8	91.9	91.4
RCL	g/m ³	49.9	48.9	47.9	47.0	46.1	45.3	53.1	52.0

TABLE 34

Item	Unit	Example 226	Example 227
HFO-1132(E)	mass %	34.0	36.0
HFO-1123	mass %	28.0	26.0
R1234yf	mass %	38.0	38.0
GWP	—	2	2
COP ratio	% (relative to 410A)	97.4	97.6
Refrigerating capacity ratio	% (relative to 410A)	85.6	85.3
Condensation glide	° C.	4.18	4.11
Discharge pressure	% (relative to 410A)	91.0	90.6
RCL	g/m ³	50.9	49.8

[0622] These results indicate that under the condition that the mass % of HFO-1132(E), HFO-1123, and R1234yf based on their sum is respectively represented by x, y, and z, when coordinates (x,y,z) in a ternary composition diagram in which the sum of HFO-1132(E), HFO-1123, and R1234yf is 100 mass % are within the range of a figure surrounded by line segments AA', A'B, BD, DC', C'C, CO, and OA that connect the following 7 points:

- [0623] point A (68.6, 0.0, 31.4),
- [0624] point A'(30.6, 30.0, 39.4),
- [0625] point B (0.0, 58.7, 41.3),
- [0626] point D (0.0, 80.4, 19.6),
- [0627] point C' (19.5, 70.5, 10.0),
- [0628] point C (32.9, 67.1, 0.0), and
- [0629] point O (100.0, 0.0, 0.0),
- [0630] or on the above line segments (excluding the points on the line segment CO);
- [0631] the line segment AA' is represented by coordinates (x, 0.0016x²-0.9473x+57.497, -0.0016x²-0.0527x+42.503),
- [0632] the line segment A'B is represented by coordinates (x, 0.0029x²-1.0268x+58.7, -0.0029x²+0.0268x+41.3),
- [0633] the line segment DC' is represented by coordinates (x, 0.0082x²-0.6671x+80.4, -0.0082x²-0.3329x+19.6),
- [0634] the line segment C'C is represented by coordinates (x, 0.0067x²-0.6034x+79.729, -0.0067x²-0.3966x+20.271), and
- [0635] the line segments BD, CO, and OA are straight lines,
- [0636] the refrigerant has a refrigerating capacity ratio of 85% or more relative to that of R410A, and a COP of 92.5% or more relative to that of R410A.

[0637] The point on the line segment AA' was determined by obtaining an approximate curve connecting point A, Example 1, and point A' by the least square method.

[0638] The point on the line segment A'B was determined by obtaining an approximate curve connecting point A', Example 3, and point B by the least square method.

[0639] The point on the line segment DC' was determined by obtaining an approximate curve connecting point D, Example 6, and point C' by the least square method.

[0640] The point on the line segment C'C was determined by obtaining an approximate curve connecting point C', Example 4, and point C by the least square method.

[0641] Likewise, the results indicate that when coordinates (x,y,z) are within the range of a figure surrounded by line segments AA', A'B, BF, FT, TE, EO, and OA that connect the following 7 points:

- [0642] point A (68.6, 0.0, 31.4),
- [0643] point A' (30.6, 30.0, 39.4),
- [0644] point B (0.0, 58.7, 41.3),
- [0645] point F (0.0, 61.8, 38.2),
- [0646] point T (35.8, 44.9, 19.3),
- [0647] point E (58.0, 42.0, 0.0) and
- [0648] point O (100.0, 0.0, 0.0),
- [0649] or on the above line segments (excluding the points on the line EO);
- [0650] the line segment AA' is represented by coordinates (x, 0.0016x²-0.9473x+57.497, -0.0016x²-0.0527x+42.503),
- [0651] the line segment A'B is represented by coordinates (x, 0.0029x²-1.0268x+58.7, -0.0029x²+0.0268x+41.3),
- [0652] the line segment FT is represented by coordinates (x, 0.0078x²-0.7501x+61.8, -0.0078x²-0.2499x+38.2), and
- [0653] the line segment TE is represented by coordinates (x, 0.0067x²-0.7607x+63.525, -0.0067x²-0.2393x+36.475), and
- [0654] the line segments BF, FO, and OA are straight lines,
- [0655] the refrigerant has a refrigerating capacity ratio of 85% or more relative to that of R410A, and a COP of 95% or more relative to that of R410A.
- [0656] The point on the line segment FT was determined by obtaining an approximate curve connecting three points, i.e., points T, E', and F, by the least square method.
- [0657] The point on the line segment TE was determined by obtaining an approximate curve connecting three points, i.e., points E, R, and T, by the least square method.

[0658] The results in Tables 1 to 34 clearly indicate that in a ternary composition diagram of the mixed refrigerant of HFO-1132(E), HFO-1123, and R1234yf in which the sum of these components is 100 mass %, a line segment connecting a point (0.0, 100.0, 0.0) and a point (0.0, 0.0, 100.0) is the base, the point (0.0, 100.0, 0.0) is on the left side, and the point (0.0, 0.0, 100.0) is on the right side, when coordinates (x,y,z) are on or below the line segment LM connecting point L (63.1, 31.9, 5.0) and point M (60.3, 6.2, 33.5), the refrigerant has an RCL of 40 g/m³ or more.

[0659] The results in Tables 1 to 34 clearly indicate that in a ternary composition diagram of the mixed refrigerant of HFO-1132(E), HFO-1123 and R1234yf in which their sum is 100 mass %, a line segment connecting a point (0.0, 100.0, 0.0) and a point (0.0, 0.0, 100.0) is the base, the point (0.0, 100.0, 0.0) is on the left side, and the point (0.0, 0.0, 100.0) is on the right side, when coordinates (x,y,z) are on the line segment QR connecting point Q (62.8, 29.6, 7.6) and point R (49.8, 42.3, 7.9) or on the left side of the line segment, the refrigerant has a temperature glide of 1° C. or less.

[0660] The results in Tables 1 to 34 clearly indicate that in a ternary composition diagram of the mixed refrigerant of HFO-1132(E), HFO-1123, and R1234yf in which their sum is 100 mass %, a line segment connecting a point (0.0, 100.0, 0.0) and a point (0.0, 0.0, 100.0) is the base, the point (0.0, 100.0, 0.0) is on the left side, and the point (0.0, 0.0, 100.0) is on the right side, when coordinates (x,y,z) are on the line segment ST connecting point S (62.6, 28.3, 9.1) and point T (35.8, 44.9, 19.3) or on the right side of the line segment, the refrigerant has a discharge pressure of 105% or less relative to that of 410A.

[0661] In these compositions, R1234yf contributes to reducing flammability, and suppressing deterioration of polymerization etc. Therefore, the composition preferably contains R1234yf.

and **906** refers to a ring filter. First, the mixed refrigerants used had a purity of 99.5% or more, and were degassed by repeating a cycle of freezing, pumping, and thawing until no traces of air were observed on the vacuum gauge. The burning velocity was measured by the closed method. The initial temperature was ambient temperature. Ignition was performed by generating an electric spark between the electrodes in the center of a sample cell. The duration of the discharge was 1.0 to 9.9 ms, and the ignition energy was typically about 0.1 to 1.0 J. The spread of the flame was visualized using schlieren photographs. A cylindrical container (inner diameter: 155 mm, length: 198 mm) equipped with two light transmission acrylic windows was used as the sample cell, and a xenon lamp was used as the light source. Schlieren images of the flame were recorded by a high-speed digital video camera at a frame rate of 600 fps and stored on a PC.

[0664] Each WCF concentration was obtained by using the WCF concentration as the initial concentration and performing a leak simulation using NIST Standard Reference Database REFLEAK Version 4.0.

[0665] Tables 35 and 36 show the results.

TABLE 35

	Item	Unit	G	H	I
WCF	HFO-1132(E)	mass %	72.0	72.0	72.0
	HFO-1123	mass %	28.0	9.6	0.0
	R1234yf	mass %	0.0	18.4	28.0
	Burning velocity (WCF)	cm/s	10	10	10

TABLE 36

	Item	Unit	J	P	L	N	N'	K
WCF	HFO-1132(E)	mass %	47.1	55.8	63.1	68.6	65.0	61.3
	HFO-1123	mass %	52.9	42.0	31.9	16.3	7.7	5.4
	R1234yf	mass %	0.0	2.2	5.0	15.1	27.3	33.3
	Leak condition that results in WCF		Storage/ Shipping -40° C., 92% release, liquid phase side	Storage/ Shipping -40° C., 90% release, liquid phase side	Storage/ Shipping -40° C., 90% release, gas phase side	Storage/ Shipping -40° C., 66% release, gas phase side	Storage/ Shipping -40° C., 12% release, gas phase side	Storage/ Shipping -40° C., 0% release, gas phase side
WCFF	HFO-1132(E)	mass %	72.0	72.0	72.0	72.0	72.0	72.0
	HFO-1123	mass %	28.0	17.8	17.4	13.6	12.3	9.8
	R1234yf	mass %	0.0	10.2	10.6	14.4	15.7	18.2
	Burning velocity (WCF)	cm/s	8 or less	8 or less	8 or less	9	9	8 or less
	Burning velocity (WCFF)	cm/s	10	10	10	10	10	10

[0662] Further, the burning velocity of these mixed refrigerants whose mixed formulations were adjusted to WCF concentrations was measured according to the ANSI/ASHRAE Standard 34-2013. Compositions having a burning velocity of 10 cm/s or less were determined to be classified as “Class 2L (lower flammability).”

[0663] A burning velocity test was performed using the apparatus shown in FIG. 1 in the following manner. In FIG. 1, reference numeral **901** refers to a sample cell, **902** refers to a high-speed camera, **903** refers to a xenon lamp, **904** refers to a collimating lens, **905** refers to a collimating lens,

[0666] The results in Table 35 clearly indicate that when a mixed refrigerant of HFO-1132(E), HFO-1123, and R1234yf contains HFO-1132(E) in a proportion of 72.0 mass % or less based on their sum, the refrigerant can be determined to have a WCF lower flammability.

[0667] The results in Tables 36 clearly indicate that in a ternary composition diagram of a mixed refrigerant of HFO-1132(E), HFO-1123, and R1234yf in which their sum is 100 mass %, and a line segment connecting a point (0.0, 100.0, 0.0) and a point (0.0, 0.0, 100.0) is the base, when

coordinates (x,y,z) are on or below the line segments JP, PN, and NK connecting the following 6 points:

[0668] point J (47.1, 52.9, 0.0),

[0669] point P (55.8, 42.0, 2.2),

[0670] point L (63.1,31.9,5.0)

[0671] point N' (65.0, 7.7, 27.3) and

[0672] point K (61.3, 5.4, 33.3),

[0673] the refrigerant can be determined to have a WCF lower flammability, and a WCF lower flammability.

[0674] In the diagram, the line segment PN is represented by coordinates $(x, -0.1135x^2+12.112x-280.43, 0.1135x^2-13.112x+380.43)$,

[0675] and the line segment NK is represented by coordinates $(x, 0.2421x^2-29.955x+931.91, -0.2421x^2+28.955x-83 1.91)$.

[0676] The point on the line segment PN was determined by obtaining an approximate curve connecting three points, i.e., points P, L, and N, by the least square method.

[0677] The point on the line segment NK was determined by obtaining an approximate curve connecting three points, i.e., points N, N', and K, by the least square method.

(5-2) Refrigerant B

[0678] The refrigerant B according to the present disclosure is

[0679] a mixed refrigerant comprising trans-1,2-difluoroethylene (HFO-1132(E)) and trifluoroethylene (HFO-1123) in a total amount of 99.5 mass % or more based on the entire refrigerant, and the refrigerant comprising 62.0 mass % to 72.0 mass % or 45.1 mass % to 47.1 mass % of HFO-1132 (E) based on the entire refrigerant, or

[0680] a mixed refrigerant comprising HFO-1132(E) and HFO-1123 in a total amount of 99.5 mass % or more based on the entire refrigerant, and the refrigerant comprising 45.1 mass % to 47.1 mass % of HFO-1132(E) based on the entire refrigerant.

[0681] The refrigerant B according to the present disclosure has various properties that are desirable as an R410A-alternative refrigerant, i.e., (1) a coefficient of performance equivalent to that of R410A, (2) a refrigerating capacity equivalent to that of R410A, (3) a sufficiently low GWP, and (4) a lower flammability (Class 2L) according to the ASHRAE standard.

[0682] When the refrigerant B according to the present disclosure is a mixed refrigerant comprising 72.0 mass % or less of HFO-1132(E), it has WCF lower flammability. When the refrigerant B according to the present disclosure is a composition comprising 47.1% or less of HFO-1132(E), it has WCF lower flammability and WCF lower flammability, and is determined to be "Class 2L," which is a lower flammable refrigerant according to the ASHRAE standard, and which is further easier to handle.

[0683] When the refrigerant B according to the present disclosure comprises 62.0 mass % or more of HFO-1132(E), it becomes superior with a coefficient of performance of 95% or more relative to that of R410A, the polymerization reaction of HFO-1132(E) and/or HFO-1123 is further suppressed, and the stability is further improved. When the refrigerant B according to the present disclosure comprises 45.1 mass % or more of HFO-1132(E), it becomes superior with a coefficient of performance of 93% or more relative to that of R410A, the polymerization reaction of HFO-1132(E) and/or HFO-1123 is further suppressed, and the stability is further improved.

[0684] The refrigerant B according to the present disclosure may further comprise other additional refrigerants in addition to HFO-1132(E) and HFO-1123, as long as the above properties and effects are not impaired. In this respect, the refrigerant according to the present disclosure preferably comprises HFO-1132(E) and HFO-1123 in a total amount of 99.75 mass % or more, and more preferably 99.9 mass % or more, based on the entire refrigerant.

[0685] Such additional refrigerants are not limited, and can be selected from a wide range of refrigerants. The mixed refrigerant may comprise a single additional refrigerant, or two or more additional refrigerants.

(Examples of Refrigerant B)

[0686] The present disclosure is described in more detail below with reference to Examples of refrigerant B. However, the refrigerant B is not limited to the Examples.

[0687] Mixed refrigerants were prepared by mixing HFO-1132(E) and HFO-1123 at mass % based on their sum shown in Tables 37 and 38.

[0688] The GWP of compositions each comprising a mixture of R410A (R32=50%/R125=50%) was evaluated based on the values stated in the Intergovernmental Panel on Climate Change (IPCC), fourth report. The GWP of HFO-1132(E), which was not stated therein, was assumed to be 1 from HFO-1132a (GWP=1 or less) and HFO-1123 (GWP=0.3, described in Patent Literature 1). The refrigerating capacity of compositions each comprising R410A and a mixture of HFO-1132(E) and HFO-1123 was determined by performing theoretical refrigeration cycle calculations for the mixed refrigerants using the National Institute of Science and Technology (NIST) and Reference Fluid Thermodynamic and Transport Properties Database (Refprop 9.0) under the following conditions.

[0689] Evaporating temperature: 5° C.

[0690] Condensation temperature: 45° C.

[0691] Superheating temperature: 5 K

[0692] Subcooling temperature: 5 K

[0693] Compressor efficiency: 70%

[0694] The composition of each mixture was defined as WCF. A leak simulation was performed using NIST Standard Reference Data Base Refleak Version 4.0 under the conditions of Equipment, Storage, Shipping, Leak, and Recharge according to the ASHRAE Standard 34-2013. The most flammable fraction was defined as WCF.

[0695] Tables 1 and 2 show GWP, COP, and refrigerating capacity, which were calculated based on these results. The COP and refrigerating capacity are ratios relative to R410A.

[0696] The coefficient of performance (COP) was determined by the following formula.

$$\text{COP} = \frac{\text{refrigerating capacity or heating capacity}}{\text{power consumption}}$$

[0697] For the flammability, the burning velocity was measured according to the ANSI/ASHRAE Standard 34-2013. Both WCF and WCFE having a burning velocity of 10 cm/s or less were determined to be "Class 2L (lower flammability)."

[0698] A burning velocity test was performed using the apparatus shown in FIG. 1 in the following manner. First, the mixed refrigerants used had a purity of 99.5% or more, and were degassed by repeating a cycle of freezing, pumping, and thawing until no traces of air were observed on the vacuum gauge. The burning velocity was measured by the

TABLE 38-continued

Burning velocity (WCFF)	cm/sec	11	10.5	10.0	9.5	9.5	8.5	8 or less	8 or less	
ASHRAE flammability classification		2	2	2L	2L	2L	2L	2L	2L	2L

[0699] The compositions each comprising 62.0 mass % to 72.0 mass % of HFO-1132(E) based on the entire composition are stable while having a low GWP (GWP=1), and they ensure WCF lower flammability. Further, surprisingly, they can ensure performance equivalent to that of R410A. Moreover, compositions each comprising 45.1 mass % to 47.1 mass % of HFO-1132(E) based on the entire composition are stable while having a low GWP (GWP=1), and they ensure WCFF lower flammability. Further, surprisingly, they can ensure performance equivalent to that of R410A.

(5-3) Refrigerant C

[0700] The refrigerant C according to the present disclosure is a composition comprising trans-1,2-difluoroethylene (HFO-1132(E)), trifluoroethylene (HFO-1123), 2,3,3,3-tetrafluoro-1-propene (R1234yf), and difluoromethane (R32), and satisfies the following requirements. The refrigerant C according to the present disclosure has various properties that are desirable as an alternative refrigerant for R410A; i.e. it has a coefficient of performance and a refrigerating capacity that are equivalent to those of R410A, and a sufficiently low GWP.

Requirements

[0701] Preferable refrigerant C is as follows:

[0702] When the mass % of HFO-1132(E), HFO-1123, R1234yf, and R32 based on their sum is respectively represented by x, y, z, and a,

[0703] if $0 < a \leq 11.1$, coordinates (x,y,z) in a ternary composition diagram in which the sum of HFO-1132(E), HFO-1123, and R1234yf is (100-a) mass % are within the range of a figure surrounded by straight lines GI, IA, AB, BD', D'C, and CG that connect the following 6 points:

[0704] point G ($0.026a^2 - 1.7478a + 72.0$, $-0.026a^2 + 0.7478a + 28.0$, 0.0),

[0705] point I ($0.026a^2 - 1.7478a + 72.0$, 0.0, $-0.026a^2 + 0.7478a + 28.0$),

[0706] point A ($0.0134a^2 - 1.9681a + 68.6$, 0.0, $-0.0134a^2 + 0.9681a + 31.4$),

[0707] point B (0.0, $0.0144a^2 - 1.6377a + 58.7$, $-0.0144a^2 + 0.6377a + 41.3$),

[0708] point D' (0.0, $0.0224a^2 + 0.968a + 75.4$, $-0.0224a^2 - 1.968a + 24.6$), and

[0709] point C ($-0.2304a^2 - 0.4062a + 32.9$, $0.2304a^2 - 0.5938a + 67.1$, 0.0),

[0710] or on the straight lines GI, AB, and D'C (excluding point G, point I, point A, point B, point D', and point C);

[0711] if $11.1 < a \leq 18.2$, coordinates (x,y,z) in the ternary composition diagram are within the range of a figure surrounded by straight lines GI, IA, AB, BW, and WG that connect the following 5 points:

[0712] point G ($0.02a^2 - 1.6013a + 71.105$, $-0.02a^2 + 0.6013a + 28.895$, 0.0),

[0713] point I ($0.02a^2 - 1.6013a + 71.105$, 0.0, $-0.02a^2 + 0.6013a + 28.895$),

[0714] point A ($0.0112a^2 - 1.9337a + 68.484$, 0.0, $-0.0112a^2 + 0.9337a + 31.516$),

[0715] point B (0.0, $0.0075a^2 - 1.5156a + 58.199$, $-0.0075a^2 + 0.5156a + 41.801$) and

[0716] point W (0.0, 100.0-a, 0.0),

or on the straight lines GI and AB (excluding point G, point I, point A, point B, and point W);

[0717] if $18.2 < a \leq 26.7$, coordinates (x,y,z) in the ternary composition diagram are within the range of a figure surrounded by straight lines GI, IA, AB, BW, and WG that connect the following 5 points:

[0718] point G ($0.0135a^2 - 1.4068a + 69.727$, $-0.0135a^2 + 0.4068a + 30.273$, 0.0),

[0719] point I ($0.0135a^2 - 1.4068a + 69.727$, 0.0, $-0.0135a^2 + 0.4068a + 30.273$),

[0720] point A ($0.0107a^2 - 1.9142a + 68.305$, 0.0, $-0.0107a^2 + 0.9142a + 31.695$),

[0721] point B (0.0, $0.009a^2 - 1.6045a + 59.318$, $-0.009a^2 + 0.6045a + 40.682$) and

[0722] point W (0.0, 100.0-a, 0.0),

or on the straight lines GI and AB (excluding point G, point I, point A, point B, and point W);

[0723] if $26.7 < a \leq 36.7$, coordinates (x,y,z) in the ternary composition diagram are within the range of a figure surrounded by straight lines GI, IA, AB, BW, and WG that connect the following 5 points:

[0724] point G ($0.0111a^2 - 1.3152a + 68.986$, $-0.0111a^2 + 0.3152a + 31.014$, 0.0),

[0725] point I ($0.0111a^2 - 1.3152a + 68.986$, 0.0, $-0.0111a^2 + 0.3152a + 31.014$),

[0726] point A ($0.0103a^2 - 1.9225a + 68.793$, 0.0, $-0.0103a^2 + 0.9225a + 31.207$),

[0727] point B (0.0, $0.0046a^2 - 1.41a + 57.286$, $-0.0046a^2 + 0.41a + 42.714$) and

[0728] point W (0.0, 100.0-a, 0.0),

or on the straight lines GI and AB (excluding point G, point I, point A, point B, and point W); and

[0729] if $36.7 < a \leq 46.7$, coordinates (x,y,z) in the ternary composition diagram are within the range of a figure surrounded by straight lines GI, IA, AB, BW, and WG that connect the following 5 points:

[0730] point G ($0.0061a^2 - 0.9918a + 63.902$, $-0.0061a^2 - 0.0082a + 36.098$, 0.0),

[0731] point I ($0.0061a^2 - 0.9918a + 63.902$, 0.0, $-0.0061a^2 - 0.0082a + 36.098$),

[0732] point A ($0.0085a^2 - 1.8102a + 67.1$, 0.0, $-0.0085a^2 + 0.8102a + 32.9$),

[0733] point B (0.0, $0.0012a^2 - 1.1659a + 52.95$, $-0.0012a^2 + 0.1659a + 47.05$) and

[0734] point W (0.0, 100.0-a, 0.0),

or on the straight lines GI and AB (excluding point G, point I, point A, point B, and point W). When the refrigerant according to the present disclosure satisfies the above

requirements, it has a refrigerating capacity ratio of 85% or more relative to that of R410A, and a COP ratio of 92.5% or more relative to that of R410A, and further ensures a WCF lower flammability.

[0735] The refrigerant C according to the present disclosure is preferably a refrigerant wherein

[0736] when the mass % of HFO-1132(E), HFO-1123, and R1234yf based on their sum is respectively represented by x, y, and z,

[0737] if $0 < a \leq 11.1$, coordinates (x,y,z) in a ternary composition diagram in which the sum of HFO-1132(E), HFO-1123, and R1234yf is (100-a) mass % are within the range of a figure surrounded by straight lines JK', K'B, BD', D'C, and CJ that connect the following 5 points:

[0738] point J ($0.0049a^2 - 0.9645a + 47.1$, $-0.0049a^2 - 0.0355a + 52.9$, 0.0),

[0739] point K' ($0.0514a^2 - 2.4353a + 61.7$, $-0.0323a^2 + 0.4122a + 5.9$, $-0.0191a^2 + 1.0231a + 32.4$),

[0740] point B (0.0, $0.0144a^2 - 1.6377a + 58.7$, $-0.0144a^2 + 0.6377a + 41.3$),

[0741] point D' (0.0, $0.0224a^2 + 0.968a + 75.4$, $-0.0224a^2 - 1.968a + 24.6$), and

[0742] point C ($-0.2304a^2 - 0.4062a + 32.9$, $0.2304a^2 - 0.5938a + 67.1$, 0.0),

or on the straight lines JK', K'B, and D'C (excluding point J, point B, point D', and point C);

[0743] if $11.1 < a \leq 18.2$, coordinates (x,y,z) in the ternary composition diagram are within the range of a figure surrounded by straight lines JK', K'B, BW, and WJ that connect the following 4 points:

[0744] point J ($0.0243a^2 - 1.4161a + 49.725$, $-0.0243a^2 + 0.4161a + 50.275$, 0.0),

[0745] point K' ($0.0341a^2 - 2.1977a + 61.187$, $-0.0236a^2 + 0.34a + 5.636$, $-0.0105a^2 + 0.8577a + 33.177$),

[0746] point B (0.0, $0.0075a^2 - 1.5156a + 58.199$, $-0.0075a^2 + 0.5156a + 41.801$) and

[0747] point W (0.0, 100.0-a, 0.0),

or on the straight lines JK' and K'B (excluding point J, point B, and point W);

[0748] if $18.2 < a \leq 26.7$, coordinates (x,y,z) in the ternary composition diagram are within the range of a figure surrounded by straight lines JK', K'B, BW, and WJ that connect the following 4 points:

[0749] point J ($0.0246a^2 - 1.4476a + 50.184$, $-0.0246a^2 + 0.4476a + 49.816$, 0.0),

[0750] point K' ($0.0196a^2 - 1.7863a + 58.515$, $-0.0079a^2 - 0.1136a + 8.702$, $-0.0117a^2 + 0.8999a + 32.783$),

[0751] point B (0.0, $0.009a^2 - 1.6045a + 59.318$, $-0.009a^2 + 0.6045a + 40.682$) and

[0752] point W (0.0, 100.0-a, 0.0),

or on the straight lines JK' and K'B (excluding point J, point B, and point W);

[0753] if $26.7 < a \leq 36.7$, coordinates (x,y,z) in the ternary composition diagram are within the range of a figure surrounded by straight lines JK', K'A, AB, BW, and WJ that connect the following 5 points:

[0754] point J ($0.0183a^2 - 1.1399a + 46.493$, $-0.0183a^2 + 0.1399a + 53.507$, 0.0),

[0755] point K' ($-0.0051a^2 + 0.0929a + 25.95$, 0.0, $0.0051a^2 - 1.0929a + 74.05$),

[0756] point A ($0.0103a^2 - 1.9225a + 68.793$, 0.0, $-0.0103a^2 + 0.9225a + 31.207$),

[0757] point B (0.0, $0.0046a^2 - 1.41a + 57.286$, $-0.0046a^2 + 0.41a + 42.714$) and

[0758] point W (0.0, 100.0-a, 0.0),

or on the straight lines JK', K'A, and AB (excluding point J, point B, and point W); and

[0759] if $36.7 < a \leq 46.7$, coordinates (x,y,z) in the ternary composition diagram are within the range of a figure surrounded by straight lines JK', K'A, AB, BW, and WJ that connect the following 5 points:

[0760] point J ($-0.0134a^2 + 1.0956a + 7.13$, $0.0134a^2 - 2.0956a + 92.87$, 0.0),

[0761] point K' ($-1.892a + 29.443$, 0.0, $0.892a + 70.557$),

[0762] point A ($0.0085a^2 - 1.8102a + 67.1$, 0.0, $-0.0085a^2 + 0.8102a + 32.9$),

[0763] point B (0.0, $0.0012a^2 - 1.1659a + 52.95$, $-0.0012a^2 + 0.1659a + 47.05$) and

[0764] point W (0.0, 100.0-a, 0.0),

or on the straight lines JK', K'A, and AB (excluding point J, point B, and point W). When the refrigerant according to the present disclosure satisfies the above requirements, it has a refrigerating capacity ratio of 85% or more relative to that of R410A, and a COP ratio of 92.5% or more relative to that of R410A. Additionally, the refrigerant has a WCF lower flammability and a WCF lower flammability, and is classified as "Class 2L," which is a lower flammable refrigerant according to the ASHRAE standard.

[0765] When the refrigerant C according to the present disclosure further contains R32 in addition to HFO-1132 (E), HFO-1123, and R1234yf, the refrigerant may be a refrigerant wherein when the mass % of HFO-1132(E), HFO-1123, R1234yf, and R32 based on their sum is respectively represented by x, y, z, and a,

[0766] if $0 < a \leq 10.0$, coordinates (x,y,z) in a ternary composition diagram in which the sum of HFO-1132(E), HFO-1123, and R1234yf is (100-a) mass % are within the range of a figure surrounded by straight lines that connect the following 4 points:

[0767] point a ($0.02a^2 - 2.46a + 93.4$, 0, $-0.02a^2 + 2.46a + 6.6$),

[0768] point b' ($-0.008a^2 - 1.38a + 56$, $0.018a^2 - 0.53a + 26.3$, $-0.01a^2 + 1.91a + 17.7$),

[0769] point c ($-0.016a^2 + 1.02a + 77.6$, $0.016a^2 - 1.02a + 22.4$, 0), and

[0770] point o (100.0-a, 0.0, 0.0)

or on the straight lines oa, ab', and b'c (excluding point o and point c);

[0771] if $10.0 < a \leq 16.5$, coordinates (x,y,z) in the ternary composition diagram are within the range of a figure surrounded by straight lines that connect the following 4 points:

[0772] point a ($0.0244a^2 - 2.5695a + 94.056$, 0, $-0.0244a^2 + 2.5695a + 5.944$),

[0773] point b' ($0.1161a^2 - 1.9959a + 59.749$, $0.014a^2 - 0.3399a + 24.8$, $-0.1301a^2 + 2.3358a + 15.451$),

[0774] point c ($-0.0161a^2 + 1.02a + 77.6$, $0.0161a^2 - 1.02a + 22.4$, 0), and

[0775] point o (100.0-a, 0.0, 0.0),

or on the straight lines oa, ab', and b'c (excluding point o and point c); or

[0776] if $16.5 < a \leq 21.8$, coordinates (x,y,z) in the ternary composition diagram are within the range of a figure surrounded by straight lines that connect the following 4 points:

[0777] point a ($0.0161a^2 - 2.3535a + 92.742$, 0, $-0.0161a^2 + 2.3535a + 7.258$),

[0778] point b' $(-0.0435a^2-0.0435a+50.406, 0.0304a^2+1.8991a-0.0661, 0.0739a^2-1.8556a+49.6601)$,

[0779] point c $(-0.0161a^2+0.9959a+77.851, 0.0161a^2-0.9959a+22.149, 0)$, and

[0780] point o $(100.0-a, 0.0, 0.0)$,

or on the straight lines oa, ab', and b'c (excluding point o and point c). Note that when point b in the ternary composition diagram is defined as a point where a refrigerating capacity ratio of 95% relative to that of R410A and a COP ratio of 95% relative to that of R410A are both achieved, point b' is the intersection of straight line ab and an approximate line formed by connecting the points where the COP ratio relative to that of R410A is 95%. When the refrigerant according to the present disclosure meets the above requirements, the refrigerant has a refrigerating capacity ratio of 95% or more relative to that of R410A, and a COP ratio of 95% or more relative to that of R410A.

[0781] The refrigerant C according to the present disclosure may further comprise other additional refrigerants in addition to HFO-1132(E), HFO-1123, R1234yf, and R32 as long as the above properties and effects are not impaired. In this respect, the refrigerant according to the present disclosure preferably comprises HFO-1132(E), HFO-1123, R1234yf, and R32 in a total amount of 99.5 mass % or more, more preferably 99.75 mass % or more, and still more preferably 99.9 mass % or more, based on the entire refrigerant.

[0782] The refrigerant C according to the present disclosure may comprise HFO-1132(E), HFO-1123, R1234yf, and R32 in a total amount of 99.5 mass % or more, 99.75 mass % or more, or 99.9 mass % or more, based on the entire refrigerant.

[0783] Additional refrigerants are not particularly limited and can be widely selected. The mixed refrigerant may contain one additional refrigerant, or two or more additional refrigerants.

(Examples of Refrigerant C)

[0784] The present disclosure is described in more detail below with reference to Examples of refrigerant C. However, the refrigerant C is not limited to the Examples.

[0785] Mixed refrigerants were prepared by mixing HFO-1132(E), HFO-1123, R1234yf, and R32 at mass % based on their sum shown in Tables 39 to 96.

[0786] The GWP of compositions each comprising a mixture of R410A (R32=50%/R125=50%) was evaluated based on the values stated in the Intergovernmental Panel on Climate Change (IPCC), fourth report. The GWP of HFO-1132(E), which was not stated therein, was assumed to be 1 from HFO-1132a (GWP=1 or less) and HFO-1123 (GWP=0.3, described in Patent Literature 1). The refrigerating capacity of compositions each comprising R410A and a mixture of HFO-1132(E) and HFO-1123 was determined by performing theoretical refrigeration cycle calculations for the mixed refrigerants using the National Institute of Science and Technology (NIST) and Reference Fluid Thermodynamic and Transport Properties Database (Refprop 9.0) under the following conditions.

[0787] For each of these mixed refrigerants, the COP ratio and the refrigerating capacity ratio relative to those of R410 were obtained. Calculation was conducted under the following conditions.

[0788] Evaporating temperature: 5° C.

[0789] Condensation temperature: 45° C.

[0790] Superheating temperature: 5 K

[0791] Subcooling temperature: 5 K

[0792] Compressor efficiency: 70%

[0793] Tables 39 to 96 show the resulting values together with the GWP of each mixed refrigerant. The COP and refrigerating capacity are ratios relative to R410A.

[0794] The coefficient of performance (COP) was determined by the following formula.

$$\text{COP} = \frac{\text{refrigerating capacity or heating capacity}}{\text{power consumption}}$$

TABLE 39

Item	Unit	Comp. Ex. 1	Comp. Ex. 2 A	Comp. Ex. 3 B	Comp. Ex. 4 C	Comp. Ex. 5 D'	Comp. Ex. 6 G	Comp. Ex. 7 I	Comp. Ex. 8 J	Comp. Ex. 1 K'
HFO-1132(E)	Mass %	R410A	68.6	0.0	32.9	0.0	72.0	72.0	47.1	61.7
HFO-1123	Mass %		0.0	58.7	67.1	75.4	28.0	0.0	52.9	5.9
R1234yf	Mass %		31.4	41.3	0.0	24.6	0.0	28.0	0.0	32.4
R32	Mass %		0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
GWP	—	2088	2	2	1	2	1	2	1	2
COP ratio	% (relative to R410A)	100	100.0	95.5	92.5	93.1	96.6	99.9	93.8	99.4
Refrigerating capacity ratio	% (relative to R410A)	100	85.0	85.0	107.4	95.0	103.1	86.6	106.2	85.5

TABLE 40

Item	Unit	Comp. Ex. 9 A	Comp. Ex. 10 B	Comp. Ex. 11 C	Comp. Ex. 12 D'	Comp. Ex. 13 G	Comp. Ex. 14 I	Comp. Ex. 15 J	Comp. Ex. 16 K'
HFO-1132(E)	Mass %	55.3	0.0	18.4	0.0	60.9	60.9	40.5	47.0
HFO-1123	Mass %	0.0	47.8	74.5	83.4	32.0	0.0	52.4	7.2
R1234yf	Mass %	37.6	45.1	0.0	9.5	0.0	32.0	0.0	38.7
R32	Mass %	7.1	7.1	7.1	7.1	7.1	7.1	7.1	7.1
GWP	—	50	50	49	49	49	50	49	50
COP ratio	% (relative to R410A)	99.8	96.9	92.5	92.5	95.9	99.6	94.0	99.2

TABLE 40-continued

Item	Unit	Comp. Ex. 9 A	Comp. Ex. 10 B	Comp. Ex. 11 C	Comp. Ex. 12 D'	Comp. Ex. 13 G	Comp. Ex. 14 I	Comp. Ex. 15 J	Comp. Ex. 2 K'
Refrigerating capacity ratio	% (relative to R410A)	85.0	85.0	110.5	106.0	106.5	87.7	108.9	85.5

TABLE 41

Item	Unit	Comp. Ex. 16 A	Comp. Ex. 17 B	Comp. Ex. 18 C = D'	Comp. Ex. 19 G	Comp. Ex. 20 I	Comp. Ex. 21 J	Comp. Ex. 3 K'
HFO-1132(E)	Mass %	48.4	0.0	0.0	55.8	55.8	37.0	41.0
HFO-1123	Mass %	0.0	42.3	88.9	33.1	0.0	51.9	6.5
R1234yf	Mass %	40.5	46.6	0.0	0.0	33.1	0.0	41.4
R32	Mass %	11.1	11.1	11.1	11.1	11.1	11.1	11.1
GWP	—	77	77	76	76	77	76	77
COP ratio	% (relative to R410A)	99.8	97.6	92.5	95.8	99.5	94.2	99.3
Refrigerating capacity ratio	% (relative to R410A)	85.0	85.0	112.0	108.0	88.6	110.2	85.4

TABLE 42

Item	Unit	Comp. Ex. 22 A	Comp. Ex. 23 B	Comp. Ex. 24 G	Comp. Ex. 25 I	Comp. Ex. 26 J	Comp. Ex. 4 K'
HFO-1132(E)	Mass %	42.8	0.0	52.1	52.1	34.3	36.5
HFO-1123	Mass %	0.0	37.8	33.4	0.0	51.2	5.6
R1234yf	Mass %	42.7	47.7	0.0	33.4	0.0	43.4
R32	Mass %	14.5	14.5	14.5	14.5	14.5	14.5
GWP	—	100	100	99	100	99	100
COP ratio	% (relative to R410A)	99.9	98.1	95.8	99.5	94.4	99.5
Refrigerating capacity ratio	% (relative to R410A)	85.0	85.0	109.1	89.6	111.1	85.3

TABLE 43

Item	Unit	Comp. Ex. 27 A	Comp. Ex. 28 B	Comp. Ex. 29 G	Comp. Ex. 30 I	Comp. Ex. 31 J	Comp. Ex. 5 K'
HFO-1132(E)	Mass %	37.0	0.0	48.6	48.6	32.0	32.5
HFO-1123	Mass %	0.0	33.1	33.2	0.0	49.8	4.0
R1234yf	Mass %	44.8	48.7	0.0	33.2	0.0	45.3
R32	Mass %	18.2	18.2	18.2	18.2	18.2	18.2
GWP	—	125	125	124	125	124	125
COP ratio	% (relative to R410A)	100.0	98.6	95.9	99.4	94.7	99.8
Refrigerating capacity ratio	% (relative to R410A)	85.0	85.0	110.1	90.8	111.9	85.2

TABLE 44

Item	Unit	Comp. Ex. 32 A	Comp. Ex. 33 B	Comp. Ex. 34 G	Comp. Ex. 35 I	Comp. Ex. 36 J	Comp. Ex. 6 K'
HFO-1132(E)	Mass %	31.5	0.0	45.4	45.4	30.3	28.8
HFO-1123	Mass %	0.0	28.5	32.7	0.0	47.8	2.4
R1234yf	Mass %	46.6	49.6	0.0	32.7	0.0	46.9
R32	Mass %	21.9	21.9	21.9	21.9	21.9	21.9
GWP	—	150	150	149	150	149	150
COP ratio	% (relative to R410A)	100.2	99.1	96.0	99.4	95.1	100.0

TABLE 44-continued

Item	Unit	Comp. Ex.	Comp. Ex.	Comp. Ex.	Comp. Ex.	Comp. Ex.	Ex. 6
		32 A	33 B	34 G	35 I	36 J	K'
Refrigerating capacity ratio	% (relative to R410A)	85.0	85.0	111.0	92.1	112.6	85.1

TABLE 45

Item	Unit	Comp. Ex.	Comp. Ex.	Comp. Ex.	Comp. Ex.	Comp. Ex.	Comp. Ex.
		37 A	38 B	39 G	40 I	41 J	42 K'
HFO-1132(E)	Mass %	24.8	0.0	41.8	41.8	29.1	24.8
HFO-1123	Mass %	0.0	22.9	31.5	0.0	44.2	0.0
R1234yf	Mass %	48.5	50.4	0.0	31.5	0.0	48.5
R32	Mass %	26.7	26.7	26.7	26.7	26.7	26.7
GWP	—	182	182	181	182	181	182
COP ratio	% (relative to R410A)	100.4	99.8	96.3	99.4	95.6	100.4
Refrigerating capacity ratio	% (relative to R410A)	85.0	85.0	111.9	93.8	113.2	85.0

TABLE 46

Item	Unit	Comp. Ex.	Comp. Ex.	Comp. Ex.	Comp. Ex.	Comp. Ex.	Comp. Ex.
		43 A	44 B	45 G	46 I	47 J	48 K'
HFO-1132(E)	Mass %	21.3	0.0	40.0	40.0	28.8	24.3
HFO-1123	Mass %	0.0	19.9	30.7	0.0	41.9	0.0
R1234yf	Mass %	49.4	50.8	0.0	30.7	0.0	46.4
R32	Mass %	29.3	29.3	29.3	29.3	29.3	29.3
GWP	—	200	200	198	199	198	200
COP ratio	% (relative to R410A)	100.6	100.1	96.6	99.5	96.1	100.4
Refrigerating capacity ratio	% (relative to R410A)	85.0	85.0	112.4	94.8	113.6	86.7

TABLE 47

Item	Unit	Comp. Ex.	Comp. Ex.	Comp. Ex.	Comp. Ex.	Comp. Ex.	Comp. Ex.
		49 A	50 B	51 G	52 I	53 J	54 K'
HFO-1132(E)	Mass %	12.1	0.0	35.7	35.7	29.3	22.5
HFO-1123	Mass %	0.0	11.7	27.6	0.0	34.0	0.0
R1234yf	Mass %	51.2	51.6	0.0	27.6	0.0	40.8
R32	Mass %	36.7	36.7	36.7	36.7	36.7	36.7
GWP	—	250	250	248	249	248	250
COP ratio	% (relative to R410A)	101.2	101.0	96.4	99.6	97.0	100.4
Refrigerating capacity ratio	% (relative to R410A)	85.0	85.0	113.2	97.6	113.9	90.9

TABLE 48

Item	Unit	Comp. Ex.	Comp. Ex.	Comp. Ex.	Comp. Ex.	Comp. Ex.	Comp. Ex.
		55 A	56 B	57 G	58 I	59 J	60 K'
HFO-1132(E)	Mass %	3.8	0.0	32.0	32.0	29.4	21.1
HFO-1123	Mass %	0.0	3.9	23.9	0.0	26.5	0.0
R1234yf	Mass %	52.1	52.0	0.0	23.9	0.0	34.8
R32	Mass %	44.1	44.1	44.1	44.1	44.1	44.1
GWP	—	300	300	298	299	298	299
COP ratio	% (relative to R410A)	101.8	101.8	97.9	99.8	97.8	100.5

TABLE 48-continued

Item	Unit	Comp. Ex.	Comp. Ex.	Comp. Ex.	Comp. Ex.	Comp. Ex.	Comp. Ex.
		55 A	56 B	57 G	58 I	59 J	60 K'
Refrigerating capacity ratio to R410A	% (relative to R410A)	85.0	85.0	113.7	100.4	113.9	94.9

TABLE 49

Item	Unit	Comp. Ex.	Comp. Ex.	Comp. Ex.	Comp. Ex.	Comp. Ex.
		61 A = B	62 G	63 I	64 J	65 K'
HFO-1132(E)	Mass %	0.0	30.4	30.4	28.9	20.4
HFO-1123	Mass %	0.0	21.8	0.0	23.3	0.0
R1234yf	Mass %	52.2	0.0	21.8	0.0	31.8
R32	Mass %	47.8	47.8	47.8	47.8	47.8
GWP	—	325	323	324	323	324

TABLE 49-continued

Item	Unit	Comp. Ex.	Comp. Ex.	Comp. Ex.	Comp. Ex.	Comp. Ex.
		61 A = B	62 G	63 I	64 J	65 K'
COP ratio	% (relative to R410A)	102.1	98.2	100.0	98.2	100.6
Refrigerating capacity ratio to R410A	% (relative to R410A)	85.0	113.8	101.8	113.9	96.8

TABLE 50

Item	Unit	Comp.							
		Ex. 66	Ex. 7	Ex. 8	Ex. 9	Ex. 10	Ex. 11	Ex. 12	Ex. 13
HFO-1132(E)	Mass %	5.0	10.0	15.0	20.0	25.0	30.0	35.0	40.0
HFO-1123	Mass %	82.9	77.9	72.9	67.9	62.9	57.9	52.9	47.9
R1234yf	Mass %	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0
R32	Mass %	7.1	7.1	7.1	7.1	7.1	7.1	7.1	7.1
GWP	—	49	49	49	49	49	49	49	49
COP ratio	% (relative to R410A)	92.4	92.6	92.8	93.1	93.4	93.7	94.1	94.5
Refrigerating capacity ratio to R410A	% (relative to R410A)	108.4	108.3	108.2	107.9	107.6	107.2	106.8	106.3

TABLE 51

Item	Unit	Ex. 14	Ex. 15	Ex. 16	Ex. 17	Comp.			
						Ex. 67	Ex. 18	Ex. 19	Ex. 20
HFO-1132(E)	Mass %	45.0	50.0	55.0	60.0	65.0	10.0	15.0	20.0
HFO-1123	Mass %	42.9	37.9	32.9	27.9	22.9	72.9	67.9	62.9
R1234yf	Mass %	5.0	5.0	5.0	5.0	5.0	10.0	10.0	10.0
R32	Mass %	7.1	7.1	7.1	7.1	7.1	7.1	7.1	7.1
GWP	—	49	49	49	49	49	49	49	49
COP ratio	% (relative to R410A)	95.0	95.4	95.9	96.4	96.9	93.0	93.3	93.6
Refrigerating capacity ratio to R410A	% (relative to R410A)	105.8	105.2	104.5	103.9	103.1	105.7	105.5	105.2

TABLE 52

Item	Unit	Ex. 21	Ex. 22	Ex. 23	Ex. 24	Ex. 25	Ex. 26	Ex. 27	Ex. 28
HFO-1132(E)	Mass %	25.0	30.0	35.0	40.0	45.0	50.0	55.0	60.0
HFO-1123	Mass %	57.9	52.9	47.9	42.9	37.9	32.9	27.9	22.9
R1234yf	Mass %	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
R32	Mass %	7.1	7.1	7.1	7.1	7.1	7.1	7.1	7.1
GWP	—	49	49	49	49	49	49	49	49
COP ratio	% (relative to R410A)	93.9	94.2	94.6	95.0	95.5	96.0	96.4	96.9
Refrigerating capacity ratio to R410A	% (relative to R410A)	104.9	104.5	104.1	103.6	103.0	102.4	101.7	101.0

TABLE 68-continued

Item	Unit	Ex. 125	Ex. 126	Ex. 127	Ex. 128	Ex. 129	Ex. 130	Ex. 131	Ex. 132
COP ratio	% (relative to R410A)	95.6	95.9	96.1	96.4	96.7	97.1	97.5	97.9
Refrigerating capacity ratio	% (relative to R410A)	98.9	98.6	98.3	97.9	97.4	96.9	96.3	95.7

TABLE 69

Item	Unit	Comp.							
		Ex. 133	Ex. 87	Ex. 134	Ex. 135	Ex. 136	Ex. 137	Ex. 138	Ex. 139
HFO-1132(E)	Mass %	50.0	55.0	10.0	15.0	20.0	25.0	30.0	35.0
HFO-1123	Mass %	10.5	5.5	45.5	40.5	35.5	30.5	25.5	20.5
R1234yf	Mass %	25.0	25.0	30.0	30.0	30.0	30.0	30.0	30.0
R32	Mass %	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5
GWP	—	99	99	100	100	100	100	100	100
COP ratio	% (relative to R410A)	98.3	98.7	96.2	96.4	96.7	97.0	97.3	97.7
Refrigerating capacity ratio	% (relative to R410A)	95.0	94.3	95.8	95.6	95.2	94.8	94.4	93.8

TABLE 70

Item	Unit	Ex. 140	Ex. 141	Ex. 142	Ex. 143	Ex. 144	Ex. 145	Ex. 146	Ex. 147
HFO-1132(E)	Mass %	40.0	45.0	50.0	10.0	15.0	20.0	25.0	30.0
HFO-1123	Mass %	15.5	10.5	5.5	40.5	35.5	30.5	25.5	20.5
R1234yf	Mass %	30.0	30.0	30.0	35.0	35.0	35.0	35.0	35.0
R32	Mass %	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5
GWP	—	100	100	100	100	100	100	100	100
COP ratio	% (relative to R410A)	98.1	98.5	98.9	96.8	97.0	97.3	97.6	97.9
Refrigerating capacity ratio	% (relative to R410A)	93.3	92.6	92.0	92.8	92.5	92.2	91.8	91.3

TABLE 71

Item	Unit	Ex. 148	Ex. 149	Ex. 150	Ex. 151	Ex. 152	Ex. 153	Ex. 154	Ex. 155
HFO-1132(E)	Mass %	35.0	40.0	45.0	10.0	15.0	20.0	25.0	30.0
HFO-1123	Mass %	15.5	10.5	5.5	35.5	30.5	25.5	20.5	15.5
R1234yf	Mass %	35.0	35.0	35.0	40.0	40.0	40.0	40.0	40.0
R32	Mass %	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5
GWP	—	100	100	100	100	100	100	100	100
COP ratio	% (relative to R410A)	98.3	98.7	99.1	97.4	97.7	98.0	98.3	98.6
Refrigerating capacity ratio	% (relative to R410A)	90.8	90.2	89.6	89.6	89.4	89.0	88.6	88.2

TABLE 72

Item	Unit	Ex. 156	Ex. 157	Ex. 158	Ex. 159	Ex. 160	Comp. Ex. 88	Comp. Ex. 89	Comp. Ex. 90
HFO-1132(E)	Mass %	35.0	40.0	10.0	15.0	20.0	25.0	30.0	35.0
HFO-1123	Mass %	10.5	5.5	30.5	25.5	20.5	15.5	10.5	5.5
R1234yf	Mass %	40.0	40.0	45.0	45.0	45.0	45.0	45.0	45.0
R32	Mass %	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5
GWP	—	100	100	100	100	100	100	100	100
COP ratio	% (relative to R410A)	98.9	99.3	98.1	98.4	98.7	98.9	99.3	99.6
Refrigerating capacity ratio	% (relative to R410A)	87.6	87.1	86.5	86.2	85.9	85.5	85.0	84.5

TABLE 77-continued

Item	Unit	Comp.							
		Ex. 183	Ex. 184	Ex. 98	Ex. 185	Ex. 186	Ex. 187	Ex. 188	Ex. 189
GWP	—	149	149	149	149	149	149	149	149
COP ratio	% (relative to R410A)	97.2	97.5	97.9	96.1	96.3	96.5	96.8	97.1
Refrigerating capacity ratio	% (relative to R410A)	103.3	102.6	102.0	103.0	102.7	102.3	101.9	101.4

TABLE 78

Item	Unit	Comp.							
		Ex. 190	Ex. 191	Ex. 192	Ex. 99	Ex. 193	Ex. 194	Ex. 195	Ex. 196
HFO-1132(E)	Mass %	35.0	40.0	45.0	50.0	10.0	15.0	20.0	25.0
HFO-1123	Mass %	23.1	18.1	13.1	8.1	43.1	38.1	33.1	28.1
R1234yf	Mass %	20.0	20.0	20.0	20.0	25.0	25.0	25.0	25.0
R32	Mass %	21.9	21.9	21.9	21.9	21.9	21.9	21.9	21.9
GWP	—	149	149	149	149	149	149	149	149
COP ratio	% (relative to R410A)	97.4	97.7	98.0	98.4	96.6	96.8	97.0	97.3
Refrigerating capacity ratio	% (relative to R410A)	100.9	100.3	99.7	99.1	100.0	99.7	99.4	98.9

TABLE 79

Item	Unit	Comp.							
		Ex. 197	Ex. 198	Ex. 199	Ex. 200	Ex. 100	Ex. 201	Ex. 202	Ex. 203
HFO-1132(E)	Mass %	30.0	35.0	40.0	45.0	50.0	10.0	15.0	20.0
HFO-1123	Mass %	23.1	18.1	13.1	8.1	3.1	38.1	33.1	28.1
R1234yf	Mass %	25.0	25.0	25.0	25.0	25.0	30.0	30.0	30.0
R32	Mass %	21.9	21.9	21.9	21.9	21.9	21.9	21.9	21.9
GWP	—	149	149	149	149	149	150	150	150
COP ratio	% (relative to R410A)	97.6	97.9	98.2	98.5	98.9	97.1	97.3	97.6
Refrigerating capacity ratio	% (relative to R410A)	98.5	97.9	97.4	96.8	96.1	97.0	96.7	96.3

TABLE 80

Item	Unit	Comp.							
		Ex. 204	Ex. 205	Ex. 206	Ex. 207	Ex. 208	Ex. 209	Ex. 210	Ex. 211
HFO-1132(E)	Mass %	25.0	30.0	35.0	40.0	45.0	10.0	15.0	20.0
HFO-1123	Mass %	23.1	18.1	13.1	8.1	3.1	33.1	28.1	23.1
R1234yf	Mass %	30.0	30.0	30.0	30.0	30.0	35.0	35.0	35.0
R32	Mass %	21.9	21.9	21.9	21.9	21.9	21.9	21.9	21.9
GWP	—	150	150	150	150	150	150	150	150
COP ratio	% (relative to R410A)	97.8	98.1	98.4	98.7	99.1	97.7	97.9	98.1
Refrigerating capacity ratio	% (relative to R410A)	95.9	95.4	94.9	94.4	93.8	93.9	93.6	93.3

TABLE 81

Item	Unit	Comp.							
		Ex. 212	Ex. 213	Ex. 214	Ex. 215	Ex. 216	Ex. 217	Ex. 218	Ex. 219
HFO-1132(E)	Mass %	25.0	30.0	35.0	40.0	10.0	15.0	20.0	25.0
HFO-1123	Mass %	18.1	13.1	8.1	3.1	28.1	23.1	18.1	13.1
R1234yf	Mass %	35.0	35.0	35.0	35.0	40.0	40.0	40.0	40.0
R32	Mass %	21.9	21.9	21.9	21.9	21.9	21.9	21.9	21.9
GWP	—	150	150	150	150	150	150	150	150
COP ratio	% (relative to R410A)	98.4	98.7	99.0	99.3	98.3	98.5	98.7	99.0
Refrigerating capacity ratio	% (relative to R410A)	92.9	92.4	91.9	91.3	90.8	90.5	90.2	89.7

TABLE 82

Item	Unit	Ex. 220	Ex. 221	Ex. 222	Ex. 223	Ex. 224	Ex. 225	Ex. 226	Comp. Ex. 101
HFO-1132(E)	Mass %	30.0	35.0	10.0	15.0	20.0	25.0	30.0	10.0
HFO-1123	Mass %	8.1	3.1	23.1	18.1	13.1	8.1	3.1	18.1
R1234yf	Mass %	40.0	40.0	45.0	45.0	45.0	45.0	45.0	50.0
R32	Mass %	21.9	21.9	21.9	21.9	21.9	21.9	21.9	21.9
GWP	—	150	150	150	150	150	150	150	150
COP ratio	% (relative to R410A)	99.3	99.6	98.9	99.1	99.3	99.6	99.9	99.6
Refrigerating capacity ratio	% (relative to R410A)	89.3	88.8	87.6	87.3	87.0	86.6	86.2	84.4

TABLE 83

Item	Unit	Comp. Ex. 102	Comp. Ex. 103	Comp. Ex. 104
HFO-1132(E)	Mass %	15.0	20.0	25.0
HFO-1123	Mass %	13.1	8.1	3.1
R1234yf	Mass %	50.0	50.0	50.0
R32	Mass %	21.9	21.9	21.9
GWP	—	150	150	150

TABLE 83-continued

Item	Unit	Comp. Ex. 102	Comp. Ex. 103	Comp. Ex. 104
COP ratio	% (relative to R410A)	99.8	100.0	100.2
Refrigerating capacity ratio	% (relative to R410A)	84.1	83.8	83.4

TABLE 84

Item	Unit	Ex. 227	Ex. 228	Ex. 229	Ex. 230	Ex. 231	Ex. 232	Ex. 233	Comp. Ex. 105
HFO-1132(E)	Mass %	10.0	15.0	20.0	25.0	30.0	35.0	40.0	45.0
HFO-1123	Mass %	55.7	50.7	45.7	40.7	35.7	30.7	25.7	20.7
R1234yf	Mass %	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0
R32	Mass %	29.3	29.3	29.3	29.3	29.3	29.3	29.3	29.3
GWP	—	199	199	199	199	199	199	199	199
COP ratio	% (relative to R410A)	95.9	96.0	96.2	96.3	96.6	96.8	97.1	97.3
Refrigerating capacity ratio	% (relative to R410A)	112.2	111.9	111.6	111.2	110.7	110.2	109.6	109.0

TABLE 85

Item	Unit	Ex. 234	Ex. 235	Ex. 236	Ex. 237	Ex. 238	Ex. 239	Ex. 240	Comp. Ex. 106
HFO-1132(E)	Mass %	10.0	15.0	20.0	25.0	30.0	35.0	40.0	45.0
HFO-1123	Mass %	50.7	45.7	40.7	35.7	30.7	25.7	20.7	15.7
R1234yf	Mass %	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
R32	Mass %	29.3	29.3	29.3	29.3	29.3	29.3	29.3	29.3
GWP	—	199	199	199	199	199	199	199	199
COP ratio	% (relative to R410A)	96.3	96.4	96.6	96.8	97.0	97.2	97.5	97.8
Refrigerating capacity ratio	% (relative to R410A)	109.4	109.2	108.8	108.4	107.9	107.4	106.8	106.2

TABLE 86

Item	Unit	Ex. 241	Ex. 242	Ex. 243	Ex. 244	Ex. 245	Ex. 246	Ex. 247	Comp. Ex. 107
HFO-1132(E)	Mass %	10.0	15.0	20.0	25.0	30.0	35.0	40.0	45.0
HFO-1123	Mass %	45.7	40.7	35.7	30.7	25.7	20.7	15.7	10.7
R1234yf	Mass %	15.0	15.0	15.0	15.0	15.0	15.0	15.0	15.0
R32	Mass %	29.3	29.3	29.3	29.3	29.3	29.3	29.3	29.3
GWP	—	199	199	199	199	199	199	199	199
COP ratio	% (relative to R410A)	96.7	96.8	97.0	97.2	97.4	97.7	97.9	98.2
Refrigerating capacity ratio	% (relative to R410A)	106.6	106.3	106.0	105.5	105.1	104.5	104.0	103.4

TABLE 87

Item	Unit	Ex. 248	Ex. 249	Ex. 250	Ex. 251	Ex. 252	Ex. 253	Ex. 254	Comp. Ex. 108
HFO-1132(E)	Mass %	10.0	15.0	20.0	25.0	30.0	35.0	40.0	45.0
HFO-1123	Mass %	40.7	35.7	30.7	25.7	20.7	15.7	10.7	5.7
R1234yf	Mass %	20.0	20.0	20.0	20.0	20.0	20.0	20.0	20.0
R32	Mass %	29.3	29.3	29.3	29.3	29.3	29.3	29.3	29.3
GWP	—	199	199	199	199	199	199	199	199
COP ratio	% (relative to R410A)	97.1	97.3	97.5	97.7	97.9	98.1	98.4	98.7
Refrigerating capacity ratio	% (relative to R410A)	103.7	103.4	103.0	102.6	102.2	101.6	101.1	100.5

TABLE 88

Item	Unit	Ex. 255	Ex. 256	Ex. 257	Ex. 258	Ex. 259	Ex. 260	Ex. 261	Ex. 262
HFO-1132(E)	Mass %	10.0	15.0	20.0	25.0	30.0	35.0	40.0	10.0
HFO-1123	Mass %	35.7	30.7	25.7	20.7	15.7	10.7	5.7	30.7
R1234yf	Mass %	25.0	25.0	25.0	25.0	25.0	25.0	25.0	30.0
R32	Mass %	29.3	29.3	29.3	29.3	29.3	29.3	29.3	29.3
GWP	—	199	199	199	199	199	199	199	199
COP ratio	% (relative to R410A)	97.6	97.7	97.9	98.1	98.4	98.6	98.9	98.1
Refrigerating capacity ratio	% (relative to R410A)	100.7	100.4	100.1	99.7	99.2	98.7	98.2	97.7

TABLE 89

Item	Unit	Ex. 263	Ex. 264	Ex. 265	Ex. 266	Ex. 267	Ex. 268	Ex. 269	Ex. 270
HFO-1132(E)	Mass %	15.0	20.0	25.0	30.0	35.0	10.0	15.0	20.0
HFO-1123	Mass %	25.7	20.7	15.7	10.7	5.7	25.7	20.7	15.7
R1234yf	Mass %	30.0	30.0	30.0	30.0	30.0	35.0	35.0	35.0
R32	Mass %	29.3	29.3	29.3	29.3	29.3	29.3	29.3	29.3
GWP	—	199	199	199	199	199	200	200	200
COP ratio	% (relative to R410A)	98.2	98.4	98.6	98.9	99.1	98.6	98.7	98.9
Refrigerating capacity ratio	% (relative to R410A)	97.4	97.1	96.7	96.2	95.7	94.7	94.4	94.0

TABLE 90

Item	Unit	Ex. 271	Ex. 272	Ex. 273	Ex. 274	Ex. 275	Ex. 276	Ex. 277	Ex. 278
HFO-1132(E)	Mass %	25.0	30.0	10.0	15.0	20.0	25.0	10.0	15.0
HFO-1123	Mass %	10.7	5.7	20.7	15.7	10.7	5.7	15.7	10.7
R1234yf	Mass %	35.0	35.0	40.0	40.0	40.0	40.0	45.0	45.0
R32	Mass %	29.3	29.3	29.3	29.3	29.3	29.3	29.3	29.3
GWP	—	200	200	200	200	200	200	200	200
COP ratio	% (relative to R410A)	99.2	99.4	99.1	99.3	99.5	99.7	99.7	99.8
Refrigerating capacity ratio	% (relative to R410A)	93.6	93.2	91.5	91.3	90.9	90.6	88.4	88.1

TABLE 91

Item	Unit	Ex. 279	Ex. 280	Comp. Ex. 109	Comp. Ex. 110
HFO-1132(E)	Mass %	20.0	10.0	15.0	10.0
HFO-1123	Mass %	5.7	10.7	5.7	5.7
R1234yf	Mass %	45.0	50.0	50.0	55.0
R32	Mass %	29.3	29.3	29.3	29.3
GWP	—	200	200	200	200

TABLE 91-continued

Item	Unit	Ex. 279	Ex. 280	Comp. Ex. 109	Comp. Ex. 110
COP ratio	% (relative to R410A)	100.0	100.3	100.4	100.9
Refrigerating capacity ratio	% (relative to R410A)	87.8	85.2	85.0	82.0

TABLE 92

Item	Unit	Comp.							
		Ex. 281	Ex. 282	Ex. 283	Ex. 284	Ex. 285	Ex. 111	Ex. 286	Ex. 287
HFO-1132(E)	Mass %	10.0	15.0	20.0	25.0	30.0	35.0	10.0	15.0
HFO-1123	Mass %	40.9	35.9	30.9	25.9	20.9	15.9	35.9	30.9
R1234yf	Mass %	5.0	5.0	5.0	5.0	5.0	5.0	10.0	10.0
R32	Mass %	44.1	44.1	44.1	44.1	44.1	44.1	44.1	44.1
GWP	—	298	298	298	298	298	298	299	299
COP ratio	% (relative to R410A)	97.8	97.9	97.9	98.1	98.2	98.4	98.2	98.2
Refrigerating capacity ratio	% (relative to R410A)	112.5	112.3	111.9	111.6	111.2	110.7	109.8	109.5

TABLE 93

Item	Unit	Comp.							
		Ex. 288	Ex. 289	Ex. 290	Ex. 112	Ex. 291	Ex. 292	Ex. 293	Ex. 294
HFO-1132(E)	Mass %	20.0	25.0	30.0	35.0	10.0	15.0	20.0	25.0
HFO-1123	Mass %	25.9	20.9	15.9	10.9	30.9	25.9	20.9	15.9
R1234yf	Mass %	10.0	10.0	10.0	10.0	15.0	15.0	15.0	15.0
R32	Mass %	44.1	44.1	44.1	44.1	44.1	44.1	44.1	44.1
GWP	—	299	299	299	299	299	299	299	299
COP ratio	% (relative to R410A)	98.3	98.5	98.6	98.8	98.6	98.6	98.7	98.9
Refrigerating capacity ratio	% (relative to R410A)	109.2	108.8	108.4	108.0	107.0	106.7	106.4	106.0

TABLE 94

Item	Unit	Comp.							
		Ex. 295	Ex. 113	Ex. 296	Ex. 297	Ex. 298	Ex. 299	Ex. 300	Ex. 301
HFO-1132(E)	Mass %	30.0	35.0	10.0	15.0	20.0	25.0	30.0	10.0
HFO-1123	Mass %	10.9	5.9	25.9	20.9	15.9	10.9	5.9	20.9
R1234yf	Mass %	15.0	15.0	20.0	20.0	20.0	20.0	20.0	25.0
R32	Mass %	44.1	44.1	44.1	44.1	44.1	44.1	44.1	44.1
GWP	—	299	299	299	299	299	299	299	299
COP ratio	% (relative to R410A)	99.0	99.2	99.0	99.0	99.2	99.3	99.4	99.4
Refrigerating capacity ratio	% (relative to R410A)	105.6	105.2	104.1	103.9	103.6	103.2	102.8	101.2

TABLE 95

Item	Unit	Comp.							
		Ex. 302	Ex. 303	Ex. 304	Ex. 305	Ex. 306	Ex. 307	Ex. 308	Ex. 309
HFO-1132(E)	Mass %	15.0	20.0	25.0	10.0	15.0	20.0	10.0	15.0
HFO-1123	Mass %	15.9	10.9	5.9	15.9	10.9	5.9	10.9	5.9
R1234yf	Mass %	25.0	25.0	25.0	30.0	30.0	30.0	35.0	35.0
R32	Mass %	44.1	44.1	44.1	44.1	44.1	44.1	44.1	44.1
GWP	—	299	299	299	299	299	299	299	299
COP ratio	% (relative to R410A)	99.5	99.6	99.7	99.8	99.9	100.0	100.3	100.4
Refrigerating capacity ratio	% (relative to R410A)	101.0	100.7	100.3	98.3	98.0	97.8	95.3	95.1

TABLE 96

Item	Unit	Ex. 400
HFO-1132(E)	Mass %	10.0
HFO-1123	Mass %	5.9
R1234yf	Mass %	40.0
R32	Mass %	44.1
GWP	—	299
COP ratio	% (relative to R410A)	100.7
Refrigerating capacity ratio	% (relative to R410A)	92.3

[0795] The above results indicate that the refrigerating capacity ratio relative to R410A is 85% or more in the following cases:

[0796] When the mass % of HFO-1132(E), HFO-1123, R1234yf, and R32 based on their sum is respectively represented by x, y, z, and a, in a ternary composition diagram in which the sum of HFO-1132(E), HFO-1123, and R1234yf is (100-a) mass %, a straight line connecting a point (0.0, 100.0-a, 0.0) and a point (0.0, 0.0, 100.0-a) is the base, and the point (0.0, 100.0-a, 0.0) is on the left side, if 0<a≤11.1, coordinates (x,y,z) in the ternary composition diagram are

on, or on the left side of, a straight line AB that connects point A (0.0134a²-1.9681a+68.6, 0.0, -0.0134a²+0.9681a+31.4) and point B (0.0, 0.0144a²-1.6377a+58.7, -0.0144a²+0.6377a+41.3);

[0797] if 11.1<a≤18.2, coordinates (x,y,z) in the ternary composition diagram are on, or on the left side of, a straight line AB that connects point A (0.0112a²-1.9337a+68.484, 0.0, -0.0112a²+0.9337a+31.516) and point B (0.0, 0.0075a²-1.5156a+58.199, -0.0075a²+0.5156a+41.801);

[0798] if 18.2a<a≤26.7, coordinates (x,y,z) in the ternary composition diagram are on, or on the left side of, a straight line AB that connects point A (0.0107a²-1.9142a+68.305, 0.0, -0.0107a²+0.9142a+31.695) and point B(0.0, 0.009a²-1.6045a+59.318, -0.009a²+0.6045a+40.682);

[0799] if 26.7<a≤36.7, coordinates (x,y,z) in the ternary composition diagram are on, or on the left side of, a straight line AB that connects point A (0.0103a²-1.9225a+68.793, 0.0, -0.0103a²+0.9225a+31.207) and point B (0.0, 0.0046a²-1.41a+57.286, -0.0046a²+0.41a+42.714); and

[0800] if 36.7<a≤46.7, coordinates (x,y,z) in the ternary composition diagram are on, or on the left side of, a straight line AB that connects point A (0.0085a²-1.8102a+67.1, 0.0, -0.0085a²+0.8102a+32.9) and point B (0.0, 0.0012a²-1.1659a+52.95, -0.0012a²+0.1659a+47.05).

[0801] Actual points having a refrigerating capacity ratio of 85% or more form a curved line that connects point A and point B in FIG. 3, and that extends toward the 1234yf side. Accordingly, when coordinates are on, or on the left side of, the straight line AB, the refrigerating capacity ratio relative to R410A is 85% or more.

[0802] Similarly, it was also found that in the ternary composition diagram, if 0<a≤11.1, when coordinates (x,y,z) are on, or on the left side of, a straight line D'C that connects point D' (0.0, 0.0224a²+0.968a+75.4, -0.0224a²-1.968a+24.6) and point C (-0.2304a²-0.4062a+32.9, 0.2304a²-0.5938a+67.1, 0.0); or if 11.1<a≤46.7, when coordinates are in the entire region, the COP ratio relative to that of R410A is 92.5% or more.

[0803] In FIG. 3, the COP ratio of 92.5% or more forms a curved line CD. In FIG. 3, an approximate line formed by connecting three points: point C (32.9, 67.1, 0.0) and points

(26.6, 68.4, 5) (19.5, 70.5, 10) where the COP ratio is 92.5% when the concentration of R1234yf is 5 mass % and 10 mass % was obtained, and a straight line that connects point C and point D' (0, 75.4, 24.6), which is the intersection of the approximate line and a point where the concentration of HFO-1132(E) is 0.0 mass % was defined as a line segment D'C. In FIG. 4, point D'(0, 83.4, 9.5) was similarly obtained from an approximate curve formed by connecting point C (18.4, 74.5, 0) and points (13.9, 76.5, 2.5) (8.7, 79.2, 5) where the COP ratio is 92.5%, and a straight line that connects point C and point D' was defined as the straight line D'C.

[0804] The composition of each mixture was defined as WCF. A leak simulation was performed using NIST Standard Reference Database REFLEAK Version 4.0 under the conditions of Equipment, Storage, Shipping, Leak, and Recharge according to the ASHRAE Standard 34-2013. The most flammable fraction was defined as WCFF.

[0805] For the flammability, the burning velocity was measured according to the ANSI/ASHRAE Standard 34-2013. Both WCF and WCFF having a burning velocity of 10 cm/s or less were determined to be classified as "Class 2L (lower flammability)."

[0806] A burning velocity test was performed using the apparatus shown in FIG. 1 in the following manner. First, the mixed refrigerants used had a purity of 99.5% or more, and were degassed by repeating a cycle of freezing, pumping, and thawing until no traces of air were observed on the vacuum gauge. The burning velocity was measured by the closed method. The initial temperature was ambient temperature. Ignition was performed by generating an electric spark between the electrodes in the center of a sample cell. The duration of the discharge was 1.0 to 9.9 ms, and the ignition energy was typically about 0.1 to 1.0 J. The spread of the flame was visualized using schlieren photographs. A cylindrical container (inner diameter: 155 mm, length: 198 mm) equipped with two light transmission acrylic windows was used as the sample cell, and a xenon lamp was used as the light source. Schlieren images of the flame were recorded by a high-speed digital video camera at a frame rate of 600 fps and stored on a PC.

[0807] The results are shown in Tables 97 to 104.

TABLE 97

Item	Comp.	Comp.	Comp.	Comp.	Comp.	Comp.		
							Ex. 6	Ex. 13
WCF	HFO-1132(E)	Mass %	72.0	60.9	55.8	52.1	48.6	45.4
	HFO-1123	Mass %	28.0	32.0	33.1	33.4	33.2	32.7
	R1234yf	Mass %	0.0	0.0	0.0	0	0	0
	R32	Mass %	0.0	7.1	11.1	14.5	18.2	21.9
Burning velocity (WCF)		cm/s	10	10	10	10	10	10

TABLE 98

Item	Comp.	Comp.	Comp.	Comp.	Comp.		
						Ex. 39	Ex. 45
WCF	HFO-1132(E)	Mass %	41.8	40	35.7	32	30.4
	HFO-1123	Mass %	31.5	30.7	23.6	23.9	21.8
	R1234yf	Mass %	0	0	0	0	0
	R32	Mass %	26.7	29.3	36.7	44.1	47.8
Burning velocity (WCF)		cm/s	10	10	10	10	10

TABLE 99

Item			Comp. Ex. 7	Comp. Ex. 14	Comp. Ex. 20	Comp. Ex. 25	Comp. Ex. 30	Comp. Ex. 35
WCF	HFO-1132(E)	Mass %	72.0	60.9	55.8	52.1	48.6	45.4
	HFO-1123	Mass %	0.0	0.0	0.0	0	0	0
	R1234yf	Mass %	28.0	32.0	33.1	33.4	33.2	32.7
	R32	Mass %	0.0	7.1	11.1	14.5	18.2	21.9
	Burning velocity (WCF)	cm/s	10	10	10	10	10	10

TABLE 100

Item			Comp. Ex. 40	Comp. Ex. 46	Comp. Ex. 52	Comp. Ex. 58	Comp. Ex. 63
WCF	HFO-1132(E)	Mass %	41.8	40	35.7	32	30.4
	HFO-1123	Mass %	0	0	0	0	0
	R1234yf	Mass %	31.5	30.7	23.6	23.9	21.8
	R32	Mass %	26.7	29.3	36.7	44.1	47.8
	Burning velocity (WCF)	cm/s	10	10	10	10	10

TABLE 101

Item			Comp. Ex. 8	Comp. Ex. 15	Comp. Ex. 21	Comp. Ex. 26	Comp. Ex. 31	Comp. Ex. 36
WCF	HFO-1132(E)	Mass %	47.1	40.5	37.0	34.3	32.0	30.3
	HFO-1123	Mass %	52.9	52.4	51.9	51.2	49.8	47.8
	R1234yf	Mass %	0.0	0.0	0.0	0.0	0.0	0.0
	R32	Mass %	0.0	7.1	11.1	14.5	18.2	21.9
	Leak condition that results in WCF		Storage/ Shipping -40° C., 92% release, liquid phase side	Storage/ Shipping -40° C., 92% release, liquid phase side	Storage/ Shipping -40° C., 92% release, liquid phase side	Storage/ Shipping -40° C., 92% release, liquid phase side	Storage/ Shipping -40° C., 92% release, liquid phase side	Storage/ Shipping -40° C., 92% release, liquid phase side
WCF	HFO-1132(E)	Mass %	72.0	62.4	56.2	50.6	45.1	40.0
	HFO-1123	Mass %	28.0	31.6	33.0	33.4	32.5	30.5
	R1234yf	Mass %	0.0	0.0	0.0	20.4	0.0	0.0
	R32	Mass %	0.0	50.9	10.8	16.0	22.4	29.5
	Burning velocity (WCF)	cm/s	8 or less	8 or less	8 or less	8 or less	8 or less	8 or less
	Burning velocity (WCF)	cm/s	10	10	10	10	10	10

TABLE 102

Item			Comp. Ex. 41	Comp. Ex. 47	Comp. Ex. 53	Comp. Ex. 59	Comp. Ex. 64
WCF	HFO-1132(E)	Mass %	29.1	28.8	29.3	29.4	28.9
	HFO-1123	Mass %	44.2	41.9	34.0	26.5	23.3
	R1234yf	Mass %	0.0	0.0	0.0	0.0	0.0
	R32	Mass %	26.7	29.3	36.7	44.1	47.8
	Leak condition that results in WCF		Storage/ Shipping -40° C., 92% release, liquid phase side	Storage/ Shipping -40° C., 92% release, liquid phase side	Storage/ Shipping -40° C., 92% release, liquid phase side	Storage/ Shipping -40° C., 90% release, gas phase side	Storage/ Shipping -40° C., 86% release, gas phase side
WCF	HFO-1132(E)	Mass %	34.6	32.2	27.7	28.3	27.5
	HFO-1123	Mass %	26.5	23.9	17.5	18.2	16.7
	R1234yf	Mass %	0.0	0.0	0.0	0.0	0.0
	R32	Mass %	38.9	43.9	54.8	53.5	55.8
	Burning velocity (WCF)	cm/s	8 or less	8 or less	8.3	9.3	9.6
	Burning velocity (WCF)	cm/s	10	10	10	10	10

TABLE 103

Item			Comp. Ex. 9	Comp. Ex. 16	Comp. Ex. 22	Comp. Ex. 27	Comp. Ex. 32	Comp. Ex. 37
WCF	HFO-1132(E)	Mass %	61.7	47.0	41.0	36.5	32.5	28.8
	HFO-1123	Mass %	5.9	7.2	6.5	5.6	4.0	2.4
	R1234yf	Mass %	32.4	38.7	41.4	43.4	45.3	46.9
	R32	Mass %	0.0	7.1	11.1	14.5	18.2	21.9
	Leak condition that results in WCFF		Storage/Shipping -40° C., 0% release, gas phase side	Storage/Shipping -40° C., 0% release, gas phase side	Storage/Shipping -40° C., 0% release, gas phase side	Storage/Shipping -40° C., 92% release, liquid phase side	Storage/Shipping -40° C., 0% release, gas phase side	Storage/Shipping -40° C., 0% release, gas phase side
WCFF	HFO-1132(E)	Mass %	72.0	56.2	50.4	46.0	42.4	39.1
	HFO-1123	Mass %	10.5	12.6	11.4	10.1	7.4	4.4
	R1234yf	Mass %	17.5	20.4	21.8	22.9	24.3	25.7
	R32	Mass %	0.0	10.8	16.3	21.0	25.9	30.8
	Burning velocity (WCF)	cm/s	8 or less	8 or less	8 or less	8 or less	8 or less	8 or less
Burning velocity (WCFF)	cm/s	10	10	10	10	10	10	

TABLE 104

Item			Comp. Ex. 42	Comp. Ex. 48	Comp. Ex. 54	Comp. Ex. 60	Comp. Ex. 65
WCF	HFO-1132(E)	Mass %	24.8	24.3	22.5	21.1	20.4
	HFO-1123	Mass %	0.0	0.0	0.0	0.0	0.0
	R1234yf	Mass %	48.5	46.4	40.8	34.8	31.8
	R32	Mass %	26.7	29.3	36.7	44.1	47.8
	Leak condition that results in WCFF		Storage/Shipping -40° C., 0% release, gas phase side	Storage/Shipping -40° C., 0% release, gas phase side	Storage/Shipping -40° C., 0% release, gas phase side	Storage/Shipping -40° C., 0% release, gas phase side	Storage/Shipping -40° C., 0% release, gas phase side
WCFF	HFO-1132(E)	Mass %	35.3	34.3	31.3	29.1	28.1
	HFO-1123	Mass %	0.0	0.0	0.0	0.0	0.0
	R1234yf	Mass %	27.4	26.2	23.1	19.8	18.2
	R32	Mass %	37.3	39.6	45.6	51.1	53.7
	Burning velocity (WCF)	cm/s	8 or less	8 or less	8 or less	8 or less	8 or less
Burning velocity (WCFF)	cm/s	10	10	10	10	10	

[0808] The results in Tables 97 to 100 indicate that the refrigerant has a WCF lower flammability in the following cases:

[0809] When the mass % of HFO-1132(E), HFO-1123, R1234yf, and R32 based on their sum in the mixed refrigerant of HFO-1132(E), HFO-1123, R1234yf, and R32 is respectively represented by x, y, z, and a, coordinates (x,y,z) in a ternary composition diagram in which the sum of HFO-1132(E), HFO-1123, and R1234yf is (100-a) mass % and a straight line connecting a point (0.0, 100.0-a, 0.0) and a point (0.0, 0.0, 100.0-a) is the base, if 0<a≤11.1, coordinates (x,y,z) in the ternary composition diagram are on or below a straight line GI that connects point G (0.026a²-1.7478a+72.0, -0.026a²+0.7478a+28.0, 0.0) and point I (0.026a²-1.7478a+72.0, 0.0, -0.026a²+0.7478a+28.0);

[0810] if 11.1<a≤18.2, coordinates (x,y,z) in the ternary composition diagram are on or below a straight line GI that connects point G (0.02a²-1.6013a+71.105, -0.02a²+0.6013a+28.895, 0.0) and point I (0.02a²-1.6013a+71.105,

0.0, -0.02a²+0.6013a+28.895); if 18.2<a≤26.7, coordinates (x,y,z) in the ternary composition diagram are on or below a straight line GI that connects point G (0.0135a²-1.4068a+69.727, -0.0135a²+0.4068a+30.273, 0.0) and point I (0.0135a²-1.4068a+69.727, 0.0, -0.0135a²+0.4068a+30.273); if 26.7<a≤36.7, coordinates (x,y,z) in the ternary composition diagram are on or below a straight line GI that connects point G (0.0111a²-1.3152a+68.986, -0.0111a²+0.3152a+31.014, 0.0) and point I (0.0111a²-1.3152a+68.986, 0.0, -0.0111a²+0.3152a+31.014); and if 36.7<a≤46.7, coordinates (x,y,z) in the ternary composition diagram are on or below a straight line GI that connects point G (0.0061a²-0.9918a+63.902, -0.0061a²-0.0082a+36.098,0.0) and point I (0.0061a²-0.9918a+63.902, 0.0, -0.0061a²-0.0082a+36.098).

[0811] Three points corresponding to point G (Table 105) and point I (Table 106) were individually obtained in each of the following five ranges by calculation, and their approximate expressions were obtained.

TABLE 105

Item	11.1 ≥ R32 > 0			18.2 ≥ R32 ≥ 11.1			26.7 ≥ R32 ≥ 18.2		
R32	0	7.1	11.1	11.1	14.5	18.2	18.2	21.9	26.7
HFO-1132(E)	72.0	60.9	55.8	55.8	52.1	48.6	48.6	45.4	41.8

TABLE 105-continued

HFO-1123	28.0	32.0	33.1	33.1	33.4	33.2	33.2	32.7	31.5
R1234yf	0	0	0	0	0	0	0	0	0
R32	a			a			a		
HFO-1132(E)	$0.026a^2 - 1.7478a + 72.0$			$0.02a^2 - 1.6013a + 71.105$			$0.0135a^2 - 1.4068a + 69.727$		
Approximate expression									
HFO-1123	$-0.026a^2 + 0.7478a + 28.0$			$-0.02a^2 + 0.6013a + 28.895$			$-0.0135a^2 + 0.4068a + 30.273$		
Approximate expression									
R1234yf	0			0			0		
Approximate expression									
Item	$36.7 \geq R32 \geq 26.7$						$46.7 \geq R32 \geq 36.7$		
R32	26.7	29.3	36.7	36.7	44.1	47.8			
HFO-1132(E)	41.8	40.0	35.7	35.7	32.0	30.4			
HFO-1123	31.5	30.7	27.6	27.6	23.9	21.8			
R1234yf	0	0	0	0	0	0			
R32	a			a			a		
HFO-1132(E)	$0.0111a^2 - 1.3152a + 68.986$			$0.0061a^2 - 0.9918a + 63.902$					
Approximate expression									
HFO-1123	$-0.0111a^2 + 0.3152a + 31.014$			$-0.0061a^2 - 0.0082a + 36.098$					
Approximate expression									
R1234yf	0			0					
Approximate expression									

TABLE 106

Item	$11.1 \geq R32 > 0$			$18.2 \geq R32 \geq 11.1$			$26.7 \geq R32 \geq 18.2$		
R32	0	7.1	11.1	11.1	14.5	18.2	18.2	21.9	26.7
HFO-1132(E)	72.0	60.9	55.8	55.8	52.1	48.6	48.6	45.4	41.8
HFO-1123	0	0	0	0	0	0	0	0	0
R1234yf	28.0	32.0	33.1	33.1	33.4	33.2	33.2	32.7	31.5
R32	a			a			a		
HFO-1132(E)	$0.026a^2 - 1.7478a + 72.0$			$0.02a^2 - 1.6013a + 71.105$			$0.0135a^2 - 1.4068a + 69.727$		
Approximate expression									
HFO-1123	0			0			0		
Approximate expression									
R1234yf	$-0.026a^2 + 0.7478a + 28.0$			$-0.02a^2 + 0.6013a + 28.895$			$-0.0135a^2 + 0.4068a + 30.273$		
Approximate expression									
Item	$36.7 \geq R32 \geq 26.7$						$46.7 \geq R32 \geq 36.7$		
R32	26.7	29.3	36.7	36.7	44.1	47.8			
HFO-1132(E)	41.8	40.0	35.7	35.7	32.0	30.4			
HFO-1123	0	0	0	0	0	0			
R1234yf	31.5	30.7	23.6	23.6	23.5	21.8			
R32	x			x			x		
HFO-1132(E)	$0.0111a^2 - 1.3152a + 68.986$			$0.0061a^2 - 0.9918a + 63.902$					
Approximate expression									
HFO-1123	0			0					
Approximate expression									
R1234yf	$-0.0111a^2 + 0.3152a + 31.014$			$-0.0061a^2 - 0.0082a + 36.098$					
Approximate expression									

[0812] The results in Tables 101 to 104 indicate that the refrigerant is determined to have a WCFF lower flammability, and the flammability classification according to the ASHRAE Standard is “2L (flammability)” in the following cases:

[0813] When the mass % of HFO-1132(E), HFO-1123, R1234yf, and R32 based on their sum in the mixed refrigerant of HFO-1132(E), HFO-1123, R1234yf, and R32 is respectively represented by x, y, z, and a, in a ternary composition diagram in which the sum of HFO-1132(E), HFO-1123, and R1234yf is (100-a) mass % and a straight line connecting a point (0.0, 100.0-a, 0.0) and a point (0.0, 0.0, 100.0-a) is the base, if $0 < a \leq 11.1$, coordinates (x,y,z) in the ternary composition diagram are on or below a straight line JK' that connects point J ($0.0049a^2 - 0.9645a + 47.1$, $-0.0049a^2 - 0.0355a + 52.9$, 0.0) and point K' ($0.0514a^2 - 2.4353a + 61.7$, $-0.0323a^2 + 0.4122a + 5.9$, $-0.0191a^2 + 1.0231a + 32.4$); if $11.1 < a \leq 18.2$, coordinates are on a straight line JK' that connects point J ($0.0243a^2 - 1.4161a + 49.725$, $-0.0243a^2 + 0.4161a + 50.275$, 0.0) and point K' ($0.0341a^2 - 2.1977a + 61.187$, $-0.0236a^2 + 0.34a + 5.636$, $-0.0105a^2 + 0.$

$8577a + 33.177$); if $18.2 < a \leq 26.7$, coordinates are on or below a straight line JK' that connects point J ($0.0246a^2 - 1.4476a + 50.184$, $-0.0246a^2 + 0.4476a + 49.816$, 0.0) and point K' ($0.0196a^2 - 1.7863a + 58.515$, $-0.0079a^2 - 0.1136a + 8.702$, $-0.0117a^2 + 0.8999a + 32.783$); if $26.7 < a \leq 36.7$, coordinates are on or below a straight line JK' that connects point J ($0.0183a^2 - 1.1399a + 46.493$, $-0.0183a^2 + 0.1399a + 53.507$, 0.0) and point K' ($-0.0051a^2 + 0.0929a + 25.95$, 0.0, $0.0051a^2 - 1.0929a + 74.05$); and if $36.7 < a \leq 46.7$, coordinates are on or below a straight line JK' that connects point J ($-0.0134a^2 + 1.0956a + 7.13$, $0.0134a^2 - 2.0956a + 92.87$, 0.0) and point K' ($-1.892a + 29.443$, 0.0, $0.892a + 70.557$).

[0814] Actual points having a WCFF lower flammability form a curved line that connects point J and point K' (on the straight line AB) in FIG. 3 and extends toward the HFO-1132(E) side. Accordingly, when coordinates are on or below the straight line JK', WCFF lower flammability is achieved.

[0815] Three points corresponding to point J (Table 107) and point K' (Table 108) were individually obtained in each of the following five ranges by calculation, and their approximate expressions were obtained.

TABLE 107

Item	11.1 ≥ R32 > 0			18.2 ≥ R32 ≥ 11.1			26.7 ≥ R32 ≥ 18.2		
R32	0	7.1	11.1	11.1	14.5	18.2	18.2	21.9	26.7
HFO-1132(E)	47.1	40.5	37	37.0	34.3	32.0	32.0	30.3	29.1
HFO-1123	52.9	52.4	51.9	51.9	51.2	49.8	49.8	47.8	44.2
R1234yf	0	0	0	0	0	0	0	0	0
R32	a			a			a		
HFO-1132(E)	$0.0049a^2 - 0.9645a + 47.1$			$0.0243a^2 - 1.4161a + 49.725$			$0.0246a^2 - 1.4476a + 50.184$		
Approximate expression									
HFO-1123	$-0.0049a^2 - 0.0355a + 52.9$			$-0.0243a^2 + 0.4161a + 50.275$			$-0.0246a^2 + 0.4476a + 49.816$		
Approximate expression									
R1234yf	0			0			0		
Approximate expression									
Item	36.7 ≥ R32 ≥ 26.7			47.8 ≥ R32 ≥ 36.7					
R32	26.7	29.3	36.7	36.7	44.1	47.8			
HFO-1132(E)	29.1	28.8	29.3	29.3	29.4	28.9			
HFO-1123	44.2	41.9	34.0	34.0	26.5	23.3			
R1234yf	0	0	0	0	0	0			
R32	a			a					
HFO-1132(E)	$0.0183a^2 - 1.1399a + 46.493$			$-0.0134a^2 + 1.0956a + 7.13$					
Approximate expression									
HFO-1123	$-0.0183a^2 + 0.1399a + 53.507$			$0.0134a^2 - 2.0956a + 92.87$					
Approximate expression									
R1234yf	0			0					
Approximate expression									

TABLE 108

Item	11.1 ≥ R32 > 0			18.2 ≥ R32 ≥ 11.1			26.7 ≥ R32 ≥ 18.2		
R32	0	7.1	11.1	11.1	14.5	18.2	18.2	21.9	26.7
HFO-1132(E)	61.7	47.0	41.0	41.0	36.5	32.5	32.5	28.8	24.8
HFO-1123	5.9	7.2	6.5	6.5	5.6	4.0	4.0	2.4	0
R1234yf	32.4	38.7	41.4	41.4	43.4	45.3	45.3	46.9	48.5
R32	x			x			x		
HFO-1132(E)	$0.0514a^2 - 2.4353a + 61.7$			$0.0341a^2 - 2.1977a + 61.187$			$0.0196a^2 - 1.7863a + 58.515$		
Approximate expression									

TABLE 108-continued

HFO-1123 Approximate expression	$-0.0323a^2 + 0.4122a + 5.9$	$-0.0236a^2 + 0.34a + 5.636$	$-0.0079a^2 - 0.1136a + 8.702$
R1234yf Approximate expression	$-0.0191a^2 + 1.0231a + 32.4$	$-0.0105a^2 + 0.8577a + 33.177$	$-0.0117a^2 + 0.8999a + 32.783$
Item	36.7 ≥ R32 ≥ 26.7		46.7 ≥ R32 ≥ 36.7
R32	26.7	29.3	36.7
HFO-1132(E)	24.8	24.3	22.5
HFO-1123	0	0	0
R1234yf	48.5	46.4	40.8
R32	x		x
HFO-1132(E) Approximate expression	$-0.0051a^2 + 0.0929a + 25.95$		$-1.892a + 29.443$
HFO-1123 Approximate expression	0		0
R1234yf Approximate expression	$0.0051a^2 - 1.0929a + 74.05$		$0.892a + 70.557$

[0816] FIGS. 3 to 13 show compositions whose R32 content a (mass %) is 0 mass %, 7.1 mass %, 11.1 mass %, 14.5 mass %, 18.2 mass %, 21.9 mass %, 26.7 mass %, 29.3 mass %, 36.7 mass %, 44.1 mass %, and 47.8 mass %, respectively.

[0817] Points A, B, C, and D' were obtained in the following manner according to approximate calculation.

[0818] Point A is a point where the content of HFO-1123 is 0 mass %, and a refrigerating capacity ratio of 85% relative to that of R410A is achieved. Three points corresponding to point A were obtained in each of the following five ranges by calculation, and their approximate expressions were obtained (Table 109).

TABLE 109

Item	11.1 ≥ R32 > 0			18.2 ≥ R32 ≥ 11.1			26.7 ≥ R32 ≥ 18.2		
R32	0	7.1	11.1	11.1	14.5	18.2	18.2	21.9	26.7
HFO-1132(E)	68.6	55.3	48.4	48.4	42.8	37	37	31.5	24.8
HFO-1123	0	0	0	0	0	0	0	0	0
R1234yf	31.4	37.6	40.5	40.5	42.7	44.8	44.8	46.6	48.5
R32	a			a			a		
HFO-1132(E) Approximate expression	$0.0134a^2 - 1.9681a + 68.6$			$0.0112a^2 - 1.9337a + 68.484$			$0.0107a^2 - 1.9142a + 68.305$		
HFO-1123 Approximate expression	0			0			0		
R1234yf Approximate expression	$-0.0134a^2 + 0.9681a + 31.4$			$-0.0112a^2 + 0.69337a + 31.516$			$-0.0107a^2 + 0.9142a + 31.695$		
Item	36.7 ≥ R32 ≥ 26.7			46.7 ≥ R32 ≥ 36.7					
R32	26.7	29.3	36.7	36.7	44.1	47.8			
HFO-1132(E)	24.8	21.3	12.1	12.1	3.8	0			
HFO-1123	0	0	0	0	0	0			
R1234yf	48.5	49.4	51.2	51.2	52.1	52.2			
R32	a			a					
HFO-1132(E) Approximate expression	$0.0103a^2 - 1.9225a + 68.793$			$0.0085a^2 - 1.8102a + 67.1$					
HFO-1123 Approximate expression	0			0					
R1234yf Approximate expression	$-0.0103a^2 + 0.9225a + 31.207$			$-0.0085a^2 + 0.8102a + 32.9$					

[0819] Point B is a point where the content of HFO-1132 (E) is 0 mass %, and a refrigerating capacity ratio of 85% relative to that of R410A is achieved.

[0820] Three points corresponding to point B were obtained in each of the following five ranges by calculation, and their approximate expressions were obtained (Table 110).

TABLE 110

Item	11.1 ≥ R32 > 0			18.2 ≥ R32 ≥ 11.1			26.7 ≥ R32 ≥ 18.2		
	R32	0	7.1	11.1	11.1	14.5	18.2	18.2	21.9
HFO-1132(E)	0	0	0	0	0	0	0	0	0
HFO-1123	58.7	47.8	42.3	42.3	37.8	33.1	33.1	28.5	22.9
R1234yf	41.3	45.1	46.6	46.6	47.7	48.7	48.7	49.6	50.4
R32	a			a			a		
HFO-1132(E)	0			0			0		
Approximate expression									
HFO-1123	$0.0144a^2 - 1.6377a + 58.7$			$0.0075a^2 - 1.5156a + 58.199$			$0.009a^2 - 1.6045a + 59.318$		
Approximate expression									
R1234yf	$-0.0144a^2 + 0.6377a + 41.3$			$-0.0075a^2 + 0.5156a + 41.801$			$-0.009a^2 + 0.6045a + 40.682$		
Approximate expression									

Item	36.7 ≥ R32 ≥ 26.7			46.7 ≥ R32 ≥ 36.7		
	R32	26.7	29.3	36.7	36.7	44.1
HFO-1132(E)	0	0	0	0	0	0
HFO-1123	22.9	19.9	11.7	11.8	3.9	0
R1234yf	50.4	50.8	51.6	51.5	52.0	52.2
R32	a			a		
HFO-1132(E)	0			0		
Approximate expression						
HFO-1123	$0.0046a^2 - 1.41a + 57.286$			$0.0012a^2 - 1.1659a + 52.95$		
Approximate expression						
R1234yf	$-0.0046a^2 + 0.41a + 42.714$			$-0.0012a^2 + 0.1659a + 47.05$		
Approximate expression						

[0821] Point D' is a point where the content of HFO-1132 (E) is 0 mass %, and a COP ratio of 95.5% relative to that of R410A is achieved.

[0822] Three points corresponding to point D' were obtained in each of the following by calculation, and their approximate expressions were obtained (Table 111).

TABLE 111

Item	11.1 ≥ R32 > 0		
	R32	0	7.1
HFO-1132(E)	0	0	0
HFO-1123	75.4	83.4	88.9
R1234yf	24.6	9.5	0
R32	a		
HFO-1132(E)	0		
Approximate expression			
HFO-1123	$0.0224a^2 + 0.968a + 75.4$		
Approximate expression			
R1234yf	$-0.0224a^2 - 1.968a + 24.6$		
Approximate expression			

TABLE 112

Item	11.1 ≥ R32 > 0		
	R32	0	7.1
HFO-1132(E)	32.9	18.4	0
HFO-1123	67.1	74.5	88.9
R1234yf	0	0	0
R32	a		
HFO-1132(E)	$-0.2304a^2 - 0.4062a + 32.9$		
Approximate expression			
HFO-1123	$0.2304a^2 - 0.5938a + 67.1$		
Approximate expression			
R1234yf	0		
Approximate expression			

(5-4) Refrigerant D

[0825] The refrigerant D according to the present disclosure is a mixed refrigerant comprising trans-1,2-difluoroethylene (HFO-1132(E)), difluoromethane (R32), and 2,3,3,3-tetrafluoro-1-propene (R1234yf).

[0826] The refrigerant D according to the present disclosure has various properties that are desirable as an R410A-alternative refrigerant; i.e., a refrigerating capacity equiva-

lent to that of R410A, a sufficiently low GWP, and a lower flammability (Class 2L) according to the ASHRAE standard.

[0827] The refrigerant D according to the present disclosure is preferably a refrigerant wherein

[0828] when the mass % of HFO-1132(E), R32, and R1234yf based on their sum is respectively represented by x, y, and z, coordinates (x,y,z) in a ternary composition diagram in which the sum of HFO-1132(E), R32, and R1234yf is 100 mass % are within the range of a figure surrounded by line segments IJ, JN, NE, and EI that connect the following 4 points:

[0829] point I (72.0, 0.0, 28.0),

[0830] point J (48.5, 18.3, 33.2),

[0831] point N (27.7, 18.2, 54.1), and

[0832] point E (58.3, 0.0, 41.7),

or on these line segments (excluding the points on the line segment EI);

[0833] the line segment IJ is represented by coordinates $(0.0236y^2 - 1.7616y + 72.0, y, -0.0236y^2 + 0.7616y + 28.0)$;

[0834] the line segment NE is represented by coordinates $(0.012y^2 - 1.9003y + 58.3, y, -0.012y^2 + 0.9003y + 41.7)$; and

[0835] the line segments JN and EI are straight lines. When the requirements above are satisfied, the refrigerant according to the present disclosure has a refrigerating capacity ratio of 80% or more relative to R410A, a GWP of 125 or less, and a WCF lower flammability.

[0836] The refrigerant D according to the present disclosure is preferably a refrigerant wherein

[0837] when the mass % of HFO-1132(E), R32, and R1234yf based on their sum is respectively represented by x, y, and z, coordinates (x,y,z) in a ternary composition diagram in which the sum of HFO-1132(E), R32, and R1234yf is 100 mass % are within the range of a figure surrounded by line segments MM', M'N, NV, VG, and GM that connect the following 5 points:

[0838] point M (52.6, 0.0, 47.4),

[0839] point M' (39.2, 5.0, 55.8),

[0840] point N (27.7, 18.2, 54.1),

[0841] point V (11.0, 18.1, 70.9), and

[0842] point G (39.6, 0.0, 60.4),

or on these line segments (excluding the points on the line segment GM);

[0843] the line segment MM' is represented by coordinates $(0.132y^2 - 3.34y + 52.6, y, -0.132y^2 + 2.34y + 47.4)$;

[0844] the line segment M'N is represented by coordinates $(0.0596y^2 - 2.2541y + 48.98, y, -0.0596y^2 + 1.2541y + 51.02)$;

[0845] the line segment VG is represented by coordinates $(0.0123y^2 - 1.8033y + 39.6, y, -0.0123y^2 + 0.8033y + 60.4)$; and

[0846] the line segments NV and GM are straight lines. When the requirements above are satisfied, the refrigerant according to the present disclosure has a refrigerating capacity ratio of 70% or more relative to R410A, a GWP of 125 or less, and an ASHRAE lower flammability.

[0847] The refrigerant D according to the present disclosure is preferably a refrigerant wherein

[0848] when the mass % of HFO-1132(E), R32, and R1234yf based on their sum is respectively represented by x, y, and z, coordinates (x,y,z) in a ternary composition diagram in which the sum of HFO-1132(E), R32, and R1234yf is 100 mass % are within the range of a figure

surrounded by line segments ON, NU, and UO that connect the following 3 points:

[0849] point O (22.6, 36.8, 40.6),

[0850] point N (27.7, 18.2, 54.1), and

[0851] point U (3.9, 36.7, 59.4),

or on these line segments;

[0852] the line segment ON is represented by coordinates $(0.0072y^2 - 0.6701y + 37.512, y, -0.0072y^2 - 0.3299y + 62.488)$;

[0853] the line segment NU is represented by coordinates $(0.0083y^2 - 1.7403y + 56.635, y, -0.0083y^2 + 0.7403y + 43.365)$; and

[0854] the line segment UO is a straight line. When the requirements above are satisfied, the refrigerant according to the present disclosure has a refrigerating capacity ratio of 80% or more relative to R410A, a GWP of 250 or less, and an ASHRAE lower flammability.

[0855] The refrigerant D according to the present disclosure is preferably a refrigerant wherein

[0856] when the mass % of HFO-1132(E), R32, and R1234yf based on their sum is respectively represented by x, y, and z, coordinates (x,y,z) in a ternary composition diagram in which the sum of HFO-1132(E), R32, and R1234yf is 100 mass % are within the range of a figure surrounded by line segments QR, RT, TL, LK, and KQ that connect the following 5 points:

[0857] point Q (44.6, 23.0, 32.4),

[0858] point R (25.5, 36.8, 37.7),

[0859] point T (8.6, 51.6, 39.8),

[0860] point L (28.9, 51.7, 19.4), and

[0861] point K (35.6, 36.8, 27.6),

or on these line segments;

[0862] the line segment QR is represented by coordinates $(0.0099y^2 - 1.975y + 84.765, y, -0.0099y^2 + 0.975y + 15.235)$;

[0863] the line segment RT is represented by coordinates $(0.0082y^2 - 1.8683y + 83.126, y, -0.0082y^2 + 0.8683y + 16.874)$;

[0864] the line segment LK is represented by coordinates $(0.0049y^2 - 0.8842y + 61.488, y, -0.0049y^2 - 0.1158y + 38.512)$;

[0865] the line segment KQ is represented by coordinates $(0.0095y^2 - 1.2222y + 67.676, y, -0.0095y^2 + 0.2222y + 32.324)$; and

[0866] the line segment TL is a straight line. When the requirements above are satisfied, the refrigerant according to the present disclosure has a refrigerating capacity ratio of 92.5% or more relative to R410A, a GWP of 350 or less, and a WCF lower flammability.

[0867] The refrigerant D according to the present disclosure is preferably a refrigerant wherein

[0868] when the mass % of HFO-1132(E), R32, and R1234yf based on their sum is respectively represented by x, y, and z, coordinates (x,y,z) in a ternary composition diagram in which the sum of HFO-1132(E), R32, and R1234yf is 100 mass % are within the range of a figure surrounded by line segments PS, ST, and TP that connect the following 3 points:

[0869] point P (20.5, 51.7, 27.8),

[0870] point S (21.9, 39.7, 38.4), and

[0871] point T (8.6, 51.6, 39.8),

or on these line segments;

[0872] the line segment PS is represented by coordinates $(0.0064y^2 - 0.7103y + 40.1, y, -0.0064y^2 - 0.2897y + 59.9)$;

[0873] the line segment ST is represented by coordinates $(0.0082y^2 - 1.8683y + 83.126, y, -0.0082y^2 + 0.8683y + 16.874)$; and

[0874] the line segment TP is a straight line. When the requirements above are satisfied, the refrigerant according to

the present disclosure has a refrigerating capacity ratio of 92.5% or more relative to R410A, a GWP of 350 or less, and an ASHRAE lower flammability.

[0875] The refrigerant D according to the present disclosure is preferably a refrigerant wherein

[0876] when the mass % of HFO-1132(E), R32, and R1234yf based on their sum is respectively represented by x, y, and z, coordinates (x,y,z) in a ternary composition diagram in which the sum of HFO-1132(E), R32, and R1234yf is 100 mass % are within the range of a figure surrounded by line segments ac, cf, fd, and da that connect the following 4 points:

[0877] point a (71.1, 0.0, 28.9),

[0878] point c (36.5, 18.2, 45.3),

[0879] point f (47.6, 18.3, 34.1), and

[0880] point d (72.0, 0.0, 28.0),

or on these line segments;

[0881] the line segment ac is represented by coordinates $(0.0181y^2 - 2.2288y + 71.096, y, -0.0181y^2 + 1.2288y + 28.904)$;

[0882] the line segment fd is represented by coordinates $(0.02y^2 - 1.7y + 72, y, -0.02y^2 + 0.7y + 28)$; and

[0883] the line segments cf and da are straight lines. When the requirements above are satisfied, the refrigerant according to the present disclosure has a refrigerating capacity ratio of 85% or more relative to R410A, a GWP of 125 or less, and a lower flammability (Class 2L) according to the ASHRAE standard.

[0884] The refrigerant D according to the present disclosure is preferably a refrigerant wherein

[0885] when the mass % of HFO-1132(E), R32, and R1234yf based on their sum is respectively represented by x, y, and z, coordinates (x,y,z) in a ternary composition diagram in which the sum of HFO-1132(E), R32, and R1234yf is 100 mass % are within the range of a figure surrounded by line segments ab, be, ed, and da that connect the following 4 points:

[0886] point a (71.1, 0.0, 28.9),

[0887] point b (42.6, 14.5, 42.9),

[0888] point e (51.4, 14.6, 34.0), and

[0889] point d (72.0, 0.0, 28.0),

or on these line segments;

[0890] the line segment ab is represented by coordinates $(0.0181y^2 - 2.2288y + 71.096, y, -0.0181y^2 + 1.2288y + 28.904)$;

[0891] the line segment ed is represented by coordinates $(0.02y^2 - 1.7y + 72, y, -0.02y^2 + 0.7y + 28)$; and

[0892] the line segments be and da are straight lines. When the requirements above are satisfied, the refrigerant according to the present disclosure has a refrigerating capacity ratio of 85% or more relative to R410A, a GWP of 100 or less, and a lower flammability (Class 2L) according to the ASHRAE standard.

[0893] The refrigerant D according to the present disclosure is preferably a refrigerant wherein

[0894] when the mass % of HFO-1132(E), R32, and R1234yf based on their sum is respectively represented by x, y, and z, coordinates (x,y,z) in a ternary composition diagram in which the sum of HFO-1132(E), R32, and R1234yf is 100 mass % are within the range of a figure

surrounded by line segments gi, ij, and jg that connect the following 3 points:

[0895] point g (77.5, 6.9, 15.6),

[0896] point i (55.1, 18.3, 26.6), and

[0897] point j (77.5, 18.4, 4.1),

or on these line segments;

[0898] the line segment gi is represented by coordinates $(0.02y^2 - 2.4583y + 93.396, y, -0.02y^2 + 1.4583y + 6.604)$; and

[0899] the line segments ij and jg are straight lines. When the requirements above are satisfied, the refrigerant according to the present disclosure has a refrigerating capacity ratio of 95% or more relative to R410A and a GWP of 100 or less, undergoes fewer or no changes such as polymerization or decomposition, and also has excellent stability.

[0900] The refrigerant D according to the present disclosure is preferably a refrigerant wherein

[0901] when the mass % of HFO-1132(E), R32, and R1234yf based on their sum is respectively represented by x, y, and z, coordinates (x,y,z) in a ternary composition diagram in which the sum of HFO-1132(E), R32, and R1234yf is 100 mass % are within the range of a figure surrounded by line segments gh, hk, and kg that connect the following 3 points:

[0902] point g (77.5, 6.9, 15.6),

[0903] point h (61.8, 14.6, 23.6), and

[0904] point k (77.5, 14.6, 7.9),

or on these line segments;

[0905] the line segment gh is represented by coordinates $(0.02y^2 - 2.4583y + 93.396, y, -0.02y^2 + 1.4583y + 6.604)$; and

[0906] the line segments hk and kg are straight lines. When the requirements above are satisfied, the refrigerant according to the present disclosure has a refrigerating capacity ratio of 95% or more relative to R410A and a GWP of 100 or less, undergoes fewer or no changes such as polymerization or decomposition, and also has excellent stability.

[0907] The refrigerant D according to the present disclosure may further comprise other additional refrigerants in addition to HFO-1132(E), R32, and R1234yf, as long as the above properties and effects are not impaired. In this respect, the refrigerant according to the present disclosure preferably comprises HFO-1132(E), R32, and R1234yf in a total amount of 99.5 mass % or more, more preferably 99.75 mass % or more, and still more preferably 99.9 mass % or more based on the entire refrigerant.

[0908] Such additional refrigerants are not limited, and can be selected from a wide range of refrigerants. The mixed refrigerant may comprise a single additional refrigerant, or two or more additional refrigerants.

(Examples of Refrigerant D)

[0909] The present disclosure is described in more detail below with reference to Examples of refrigerant D. However, the refrigerant D is not limited to the Examples.

[0910] The composition of each mixed refrigerant of HFO-1132(E), R32, and R1234yf was defined as WCF. A leak simulation was performed using the NIST Standard Reference Database REFLEAK Version 4.0 under the conditions of Equipment, Storage, Shipping, Leak, and Recharge according to the ASHRAE Standard 34-2013. The most flammable fraction was defined as WCFF.

[0911] A burning velocity test was performed using the apparatus shown in FIG. 1 in the following manner. First, the mixed refrigerants used had a purity of 99.5% or more, and were degassed by repeating a cycle of freezing, pumping, and thawing until no traces of air were observed on the vacuum gauge. The burning velocity was measured by the closed method. The initial temperature was ambient tem

perature. Ignition was performed by generating an electric spark between the electrodes in the center of a sample cell. The duration of the discharge was 1.0 to 9.9 ms, and the ignition energy was typically about 0.1 to 1.0 J. The spread of the flame was visualized using schlieren photographs. A cylindrical container (inner diameter: 155 mm, length: 198

mm) equipped with two light transmission acrylic windows was used as the sample cell, and a xenon lamp was used as the light source. Schlieren images of the flame were recorded by a high-speed digital video camera at a frame rate of 600 fps and stored on a PC. Tables 113 to 115 show the results.

TABLE 113

Item	Unit	Comparative		Example		Example		Example	
		Example 13	Example 11	Example 12	Example 13	Example 14	Example 15	Example 16	
		I	11	J	13	K	15	L	
WCF	HFO-1132(E)	Mass %	72	57.2	48.5	41.2	35.6	32	28.9
	R32	Mass %	0	10	18.3	27.6	36.8	44.2	51.7
	R1234yf	Mass %	28	32.8	33.2	31.2	27.6	23.8	19.4
	Burning Velocity (WCF)	cm/s	10	10	10	10	10	10	10

TABLE 114

Item	Unit	Comparative		Example		Example		
		Example 14	Example 18	Example 19	Example 20	Example 21	Example 22	
		M	18	W	20	N	22	
WCF	HFO-1132(E)	Mass %	52.6	39.2	32.4	29.3	27.7	24.6
	R32	Mass %	0.0	5.0	10.0	14.5	18.2	27.6
	R1234yf	Mass %	47.4	55.8	57.6	56.2	54.1	47.8
	Leak condition that results in WCF	Storage, Shipping, -40° C., 0% release, on the gas phase side	Storage, Shipping, -40° C., 0% release, on the gas phase side	Storage, Shipping, -40° C., 0% release, on the gas phase side	Storage, Shipping, -40° C., 0% release, on the gas phase side	Storage, Shipping, -40° C., 0% release, on the gas phase side	Storage, Shipping, -40° C., 0% release, on the gas phase side	Storage, Shipping, -40° C., 0% release, on the gas phase side
WCF	HFO-1132(E)	Mass %	72.0	57.8	48.7	43.6	40.6	34.9
	R32	Mass %	0.0	9.5	17.9	24.2	28.7	38.1
	R1234yf	Mass %	28.0	32.7	33.4	32.2	30.7	27.0
	Burning Velocity (WCF)	cm/s	8 or less	8 or less	8 or less	8 or less	8 or less	8 or less
	Burning Velocity (WCF)	cm/s	10	10	10	10	10	10

TABLE 115

Item	Unit	Example 23	Example 24	Example 25	
		O		P	
WCF	HFO-1132 (E)	Mass %	22.6	21.2	20.5
	HFO-1123	Mass %	36.8	44.2	51.7
	R1234yf	Mass %	40.6	34.6	27.8
	Leak condition that results in WCF	Storage, Shipping, -40° C., 0% release, on the gas phase side	Storage, Shipping, -40° C., 0% release, on the gas phase side	Storage, Shipping, -40° C., 0% release, on the gas phase side	Storage, Shipping, -40° C., 0% release, on the gas phase side
WCF	HFO-1132 (E)	Mass %	31.4	29.2	27.1
	HFO-1123	Mass %	45.7	51.1	56.4
	R1234yf	Mass %	23.0	19.7	16.5
	Burning Velocity (WCF)	cm/s	8 or less	8 or less	8 or less
	Burning Velocity (WCF)	cm/s	10	10	10

[0912] The results indicate that under the condition that the mass % of HFO-1132(E), R32, and R1234yf based on their sum is respectively represented by x, y, and z, when coordinates (x,y,z) in the ternary composition diagram shown in FIG. 14 in which the sum of HFO-1132(E), R32, and R1234yf is 100 mass % are on the line segment that connects point I, point J, point K, and point L, or below these line segments, the refrigerant has a WCF lower flammability.

[0913] The results also indicate that when coordinates (x,y,z) in the ternary composition diagram shown in FIG. 14 are on the line segments that connect point M, point M', point W, point J, point N, and point P, or below these line segments, the refrigerant has an ASHRAE lower flammability.

[0914] Mixed refrigerants were prepared by mixing HFO-1132(E), R32, and R1234yf in amounts (mass %) shown in Tables 116 to 144 based on the sum of HFO-1132(E), R32, and R1234yf. The coefficient of performance (COP) ratio and the refrigerating capacity ratio relative to R410 of the mixed refrigerants shown in Tables 116 to 144 were determined. The conditions for calculation were as described below.

[0915] Evaporating temperature: 5° C.

[0916] Condensation temperature: 45° C.

[0917] Degree of superheating: 5 K

[0918] Degree of subcooling: 5 K

[0919] Compressor efficiency: 70%

[0920] Tables 116 to 144 show these values together with the GWP of each mixed refrigerant.

TABLE 116

Item	Unit	Comparative Example 1	Comparative Example 2 A	Comparative Example 3 B	Comparative Example 4 A'	Comparative Example 5 B'	Comparative Example 6 A''	Comparative Example 7 B''
HFO-1132(E)	Mass %	R410A	81.6	0.0	63.1	0.0	48.2	0.0
R32	Mass %		18.4	18.1	36.9	36.7	51.8	51.5
R1234yf	Mass %		0.0	81.9	0.0	63.3	0.0	48.5
GWP	—	2088	125	125	250	250	350	350
COP Ratio	% (relative to R410A)	100	98.7	103.6	98.7	102.3	99.2	102.2
Refrigerating Capacity Ratio	% (relative to R410A)	100	105.3	62.5	109.9	77.5	112.1	87.3

TABLE 117

Item	Unit	Comparative Example 8 C	Comparative Example 9	Comparative Example 10 C'	Example 1	Example 2 R	Example 3	Example 4 T
HFO-1132(E)	Mass %	85.5	66.1	52.1	37.8	25.5	16.6	8.6
R32	Mass %	0.0	10.0	18.2	27.6	36.8	44.2	51.6
R1234yf	Mass %	14.5	23.9	29.7	34.6	37.7	39.2	39.8
GWP	—	1	69	125	188	250	300	350
COP Ratio	% (relative to R410A)	99.8	99.3	99.3	99.6	100.2	100.8	101.4
Refrigerating Capacity Ratio	% (relative to R410A)	92.5	92.5	92.5	92.5	92.5	92.5	92.5

TABLE 118

Item	Unit	Comparative Example 11 E	Example 5	Example 6 N	Example 7	Example 8 U	Comparative Example 12 G	Example 9	Example 10 V
HFO-1132(E)	Mass %	58.3	40.5	27.7	14.9	3.9	39.6	22.8	11.0
R32	Mass %	0.0	10.0	18.2	27.6	36.7	0.0	10.0	18.1
R1234yf	Mass %	41.7	49.5	54.1	57.5	59.4	60.4	67.2	70.9
GWP	—	2	70	125	189	250	3	70	125
COP Ratio	% (relative to R410A)	100.3	100.3	100.7	101.2	101.9	101.4	101.8	102.3
Refrigerating Capacity Ratio	% (relative to R410A)	80.0	80.0	80.0	80.0	80.0	70.0	70.0	70.0

TABLE 119

Item	Unit	Comparative Example 13 I	Example 11	Example 12 J	Example 13	Example 14 K	Example 15	Example 16 L	Example 17 Q
HFO-1132(E)	Mass %	72.0	57.2	48.5	41.2	35.6	32.0	28.9	44.6
R32	Mass %	0.0	10.0	18.3	27.6	36.8	44.2	51.7	23.0

TABLE 119-continued

Item	Unit	Comparative Example 13 I	Example 11	Example 12 J	Example 13	Example 14 K	Example 15	Example 16 L	Example 17 Q
R1234yf	Mass %	28.0	32.8	33.2	31.2	27.6	23.8	19.4	32.4
GWP	—	2	69	125	188	250	300	350	157
COP Ratio	% (relative to R410A)	99.9	99.5	99.4	99.5	99.6	99.8	100.1	99.4
Refrigerating Capacity Ratio	% (relative to R410A)	86.6	88.4	90.9	94.2	97.7	100.5	103.3	92.5

TABLE 120

Item	Unit	Comparative Example 14 M	Example 18	Example 19 W	Example 20	Example 21 N	Example 22
HFO-1132(E)	Mass %	52.6	39.2	32.4	29.3	27.7	24.5
R32	Mass %	0.0	5.0	10.0	14.5	18.2	27.6
R1234yf	Mass %	47.4	55.8	57.6	56.2	54.1	47.9
GWP	—	2	36	70	100	125	188
COP Ratio	% (relative to R410A)	100.5	100.9	100.9	100.8	100.7	100.4
Refrigerating Capacity Ratio	% (relative to R410A)	77.1	74.8	75.6	77.8	80.0	85.5

TABLE 121

Item	Unit	Example 23 O	Example 24	Example 25 P	Example 26 S
HFO-1132(E)	Mass %	22.6	21.2	20.5	21.9
R32	Mass %	36.8	44.2	51.7	39.7
R1234yf	Mass %	40.6	34.6	27.8	38.4
GWP	—	250	300	350	270

TABLE 121-continued

Item	Unit	Example 23 O	Example 24	Example 25 P	Example 26 S
COP Ratio	% (relative to R410A)	100.4	100.5	100.6	100.4
Refrigerating Capacity Ratio	% (relative to R410A)	91.0	95.0	99.1	92.5

TABLE 122

Item	Unit	Comparative Example 15	Comparative Example 16	Comparative Example 17	Comparative Example 18	Example 27	Example 28	Comparative Example 19	Comparative Example 20
HFO-1132(E)	Mass %	10.0	20.0	30.0	40.0	50.0	60.0	70.0	80.0
R32	Mass %	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0
R1234yf	Mass %	85.0	75.0	65.0	55.0	45.0	35.0	25.0	15.0
GWP	—	37	37	37	36	36	36	35	35
COP Ratio	% (relative to R410A)	103.4	102.6	101.6	100.8	100.2	99.8	99.6	99.4
Refrigerating Capacity Ratio	% (relative to R410A)	56.4	63.3	69.5	75.2	80.5	85.4	90.1	94.4

TABLE 123

Item	Unit	Comparative Example 21	Comparative Example 22	Example 29	Comparative Example 23	Example 30	Comparative Example 24	Comparative Example 25	Comparative Example 26
HFO-1132(E)	Mass %	10.0	20.0	30.0	40.0	50.0	60.0	70.0	80.0
R32	Mass %	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
R1234yf	Mass %	80.0	70.0	60.0	50.0	40.0	30.0	20.0	10.0
GWP	—	71	71	70	70	70	69	69	69
COP Ratio	% (relative to R410A)	103.1	102.1	101.1	100.4	99.8	99.5	99.2	99.1
Refrigerating Capacity Ratio	% (relative to R410A)	61.8	68.3	74.3	79.7	84.9	89.7	94.2	98.4

TABLE 124

Item	Unit	Comparative Example 27	Example 31	Comparative Example 28	Example 32	Example 33	Comparative Example 29	Comparative Example 30	Comparative Example 31
HFO-1132(E)	Mass %	10.0	20.0	30.0	40.0	50.0	60.0	70.0	80.0
R32	Mass %	15.0	15.0	15.0	15.0	15.0	15.0	15.0	15.0
R1234yf	Mass %	75.0	65.0	55.0	45.0	35.0	25.0	15.0	5.0
GWP	—	104	104	104	103	103	103	103	102
COP Ratio	% (relative to R410A)	102.7	101.6	100.7	100.0	99.5	99.2	99.0	98.9
Refrigerating Capacity Ratio	% (relative to R410A)	66.6	72.9	78.6	84.0	89.0	93.7	98.1	102.2

TABLE 125

Item	Unit	Comparative Example 32	Comparative Example 33	Comparative Example 34	Comparative Example 35	Comparative Example 36	Comparative Example 37	Comparative Example 38	Comparative Example 39
HFO-1132(E)	Mass %	10.0	20.0	30.0	40.0	50.0	60.0	70.0	10.0
R32	Mass %	20.0	20.0	20.0	20.0	20.0	20.0	20.0	25.0
R1234yf	Mass %	70.0	60.0	50.0	40.0	30.0	20.0	10.0	65.0
GWP	—	138	138	137	137	137	136	136	171
COP Ratio	% (relative to R410A)	102.3	101.2	100.4	99.7	99.3	99.0	98.8	101.9
Refrigerating Capacity Ratio	% (relative to R410A)	71.0	77.1	82.7	88.0	92.9	97.5	101.7	75.0

TABLE 126

Item	Unit	Example 34	Comparative Example 40	Comparative Example 41	Comparative Example 42	Comparative Example 43	Comparative Example 44	Comparative Example 45	Example 35
HFO-1132(E)	Mass %	20.0	30.0	40.0	50.0	60.0	70.0	10.0	20.0
R32	Mass %	25.0	25.0	25.0	25.0	25.0	25.0	30.0	30.0
R1234yf	Mass %	55.0	45.0	35.0	25.0	15.0	5.0	60.0	50.0
GWP	—	171	171	171	170	170	170	205	205
COP Ratio	% (relative to R410A)	100.9	100.1	99.6	99.2	98.9	98.7	101.6	100.7
Refrigerating Capacity Ratio	% (relative to R410A)	81.0	86.6	91.7	96.5	101.0	105.2	78.9	84.8

TABLE 127

Item	Unit	Comparative Example 46	Comparative Example 47	Comparative Example 48	Comparative Example 49	Example 36	Example 37	Example 38	Comparative Example 50
HFO-1132(E)	Mass %	30.0	40.0	50.0	60.0	10.0	20.0	30.0	40.0
R32	Mass %	30.0	30.0	30.0	30.0	35.0	35.0	35.0	35.0
R1234yf	Mass %	40.0	30.0	20.0	10.0	55.0	45.0	35.0	25.0
GWP	—	204	204	204	204	239	238	238	238
COP Ratio	% (relative to R410A)	100.0	99.5	99.1	98.8	101.4	100.6	99.9	99.4
Refrigerating Capacity Ratio	% (relative to R410A)	90.2	95.3	100.0	104.4	82.5	88.3	93.7	98.6

TABLE 128

Item	Unit	Comparative Example 51	Comparative Example 52	Comparative Example 53	Comparative Example 54	Example 39	Comparative Example 55	Comparative Example 56	Comparative Example 57
HFO-1132(E)	Mass %	50.0	60.0	10.0	20.0	30.0	40.0	50.0	10.0
R32	Mass %	35.0	35.0	40.0	40.0	40.0	40.0	40.0	45.0
R1234yf	Mass %	15.0	5.0	50.0	40.0	30.0	20.0	10.0	45.0
GWP	—	237	237	272	272	272	271	271	306
COP Ratio	% (relative to R410A)	99.0	98.8	101.3	100.6	99.9	99.4	99.0	101.3
Refrigerating Capacity Ratio	% (relative to R410A)	103.2	107.5	86.0	91.7	96.9	101.8	106.3	89.3

TABLE 129

Item	Unit	Example 40	Example 41	Comparative Example 58	Comparative Example 59	Comparative Example 60	Example 42	Comparative Example 61	Comparative Example 62
HFO-1132(E)	Mass %	20.0	30.0	40.0	50.0	10.0	20.0	30.0	40.0
R32	Mass %	45.0	45.0	45.0	45.0	50.0	50.0	50.0	50.0
R1234yf	Mass %	35.0	25.0	15.0	5.0	40.0	30.0	20.0	10.0
GWP	—	305	305	305	304	339	339	339	338
COP Ratio	% (relative to R410A)	100.6	100.0	99.5	99.1	101.3	100.6	100.0	99.5
Refrigerating Capacity Ratio	% (relative to R410A)	94.9	100.0	104.7	109.2	92.4	97.8	102.9	107.5

TABLE 130

Item	Unit	Comparative Example 63	Comparative Example 64	Comparative Example 65	Comparative Example 66	Example 43	Example 44	Example 45	Example 46
HFO-1132(E)	Mass %	10.0	20.0	30.0	40.0	56.0	59.0	62.0	65.0
R32	Mass %	55.0	55.0	55.0	55.0	3.0	3.0	3.0	3.0
R1234yf	Mass %	35.0	25.0	15.0	5.0	41.0	38.0	35.0	32.0
GWP	—	373	372	372	372	22	22	22	22
COP Ratio	% (relative to R410A)	101.4	100.7	100.1	99.6	100.1	100.0	99.9	99.8
Refrigerating Capacity Ratio	% (relative to R410A)	95.3	100.6	105.6	110.2	81.7	83.2	84.6	86.0

TABLE 131

Item	Unit	Example 47	Example 48	Example 49	Example 50	Example 51	Example 52	Example 53	Example 54
HFO-1132(E)	Mass %	49.0	52.0	55.0	58.0	61.0	43.0	46.0	49.0
R32	Mass %	6.0	6.0	6.0	6.0	6.0	9.0	9.0	9.0
R1234yf	Mass %	45.0	42.0	39.0	36.0	33.0	48.0	45.0	42.0
GWP	—	43	43	43	43	42	63	63	63
COP Ratio	% (relative to R410A)	100.2	100.0	99.9	99.8	99.7	100.3	100.1	99.9
Refrigerating Capacity Ratio	% (relative to R410A)	80.9	82.4	83.9	85.4	86.8	80.4	82.0	83.5

TABLE 132

Item	Unit	Example 55	Example 56	Example 57	Example 58	Example 59	Example 60	Example 61	Example 62
HFO-1132(E)	Mass %	52.0	55.0	58.0	38.0	41.0	44.0	47.0	50.0
R32	Mass %	9.0	9.0	9.0	12.0	12.0	12.0	12.0	12.0
R1234yf	Mass %	39.0	36.0	33.0	50.0	47.0	44.0	41.0	38.0
GWP	—	63	63	63	83	83	83	83	83
COP Ratio	% (relative to R410A)	99.8	99.7	99.6	100.3	100.1	100.0	99.8	99.7
Refrigerating Capacity Ratio	% (relative to R410A)	85.0	86.5	87.9	80.4	82.0	83.5	85.1	86.6

TABLE 133

Item	Unit	Example 63	Example 64	Example 65	Example 66	Example 67	Example 68	Example 69	Example 70
HFO-1132(E)	Mass %	53.0	33.0	36.0	39.0	42.0	45.0	48.0	51.0
R32	Mass %	12.0	15.0	15.0	15.0	15.0	15.0	15.0	15.0
R1234yf	Mass %	35.0	52.0	49.0	46.0	43.0	40.0	37.0	34.0
GWP	—	83	104	104	103	103	103	103	103
COP Ratio	% (relative to R410A)	99.6	100.5	100.3	100.1	99.9	99.7	99.6	99.5
Refrigerating Capacity Ratio	% (relative to R410A)	88.0	80.3	81.9	83.5	85.0	86.5	88.0	89.5

TABLE 134

Item	Unit	Example 71	Example 72	Example 73	Example 74	Example 75	Example 76	Example 77	Example 78
HFO-1132(E)	Mass %	29.0	32.0	35.0	38.0	41.0	44.0	47.0	36.0
R32	Mass %	18.0	18.0	18.0	18.0	18.0	18.0	18.0	3.0
R1234yf	Mass %	53.0	50.0	47.0	44.0	41.0	38.0	35.0	61.0
GWP		124	124	124	124	124	123	123	23
COP Ratio	% (relative to R410A)	100.6	100.3	100.1	99.9	99.8	99.6	99.5	101.3
Refrigerating Capacity Ratio	% (relative to R410A)	80.6	82.2	83.8	85.4	86.9	88.4	89.9	71.0

TABLE 135

Item	Unit	Example 79	Example 80	Example 81	Example 82	Example 83	Example 84	Example 85	Example 86
HFO-1132(E)	Mass %	39.0	42.0	30.0	33.0	36.0	26.0	29.0	32.0
R32	Mass %	3.0	3.0	6.0	6.0	6.0	9.0	9.0	9.0
R1234yf	Mass %	58.0	55.0	64.0	61.0	58.0	65.0	62.0	59.0
GWP	—	23	23	43	43	43	64	64	63
COP Ratio	% (relative to R410A)	101.1	100.9	101.5	101.3	101.0	101.6	101.3	101.1
Refrigerating Capacity Ratio	% (relative to R410A)	72.7	74.4	70.5	72.2	73.9	71.0	72.8	74.5

TABLE 136

Item	Unit	Example 87	Example 88	Example 89	Example 90	Example 91	Example 92	Example 93	Example 94
HFO-1132(E)	Mass %	21.0	24.0	27.0	30.0	16.0	19.0	22.0	25.0
R32	Mass %	12.0	12.0	12.0	12.0	15.0	15.0	15.0	15.0
R1234yf	Mass %	67.0	64.0	61.0	58.0	69.0	66.0	63.0	60.0
GWP	—	84	84	84	84	104	104	104	104
COP Ratio	% (relative to R410A)	101.8	101.5	101.2	101.0	102.1	101.8	101.4	101.2
Refrigerating Capacity Ratio	% (relative to R410A)	70.8	72.6	74.3	76.0	70.4	72.3	74.0	75.8

TABLE 137

Item	Unit	Example 95	Example 96	Example 97	Example 98	Example 99	Example 100	Example 101	Example 102
HFO-1132(E)	Mass %	28.0	12.0	15.0	18.0	21.0	24.0	27.0	25.0
R32	Mass %	15.0	18.0	18.0	18.0	18.0	18.0	18.0	21.0
R1234yf	Mass %	57.0	70.0	67.0	64.0	61.0	58.0	55.0	54.0
GWP	—	104	124	124	124	124	124	124	144
COP Ratio	% (relative to R410A)	100.9	102.2	101.9	101.6	101.3	101.0	100.7	100.7
Refrigerating Capacity Ratio	% (relative to R410A)	77.5	70.5	72.4	74.2	76.0	77.7	79.4	80.7

TABLE 138

Item	Unit	Example 103	Example 104	Example 105	Example 106	Example 107	Example 108	Example 109	Example 110
HFO-1132(E)	Mass %	21.0	24.0	17.0	20.0	23.0	13.0	16.0	19.0
R32	Mass %	24.0	24.0	27.0	27.0	27.0	30.0	30.0	30.0
R1234yf	Mass %	55.0	52.0	56.0	53.0	50.0	57.0	54.0	51.0
GWP	—	164	164	185	185	184	205	205	205
COP Ratio	% (relative to R410A)	100.9	100.6	101.1	100.8	100.6	101.3	101.0	100.8
Refrigerating Capacity Ratio	% (relative to R410A)	80.8	82.5	80.8	82.5	84.2	80.7	82.5	84.2

TABLE 139

Item	Unit	Example 111	Example 112	Example 113	Example 114	Example 115	Example 116	Example 117	Example 118
HFO-1132(E)	Mass %	22.0	9.0	12.0	15.0	18.0	21.0	8.0	12.0
R32	Mass %	30.0	33.0	33.0	33.0	33.0	33.0	36.0	36.0
R1234yf	Mass %	48.0	58.0	55.0	52.0	49.0	46.0	56.0	52.0
GWP	—	205	225	225	225	225	225	245	245
COP Ratio	% (relative to R410A)	100.5	101.6	101.3	101.0	100.8	100.5	101.6	101.2
Refrigerating Capacity Ratio	% (relative to R410A)	85.9	80.5	82.3	84.1	85.8	87.5	82.0	84.4

TABLE 140

Item	Unit	Example 119	Example 120	Example 121	Example 122	Example 123	Example 124	Example 125	Example 126
HFO-1132(E)	Mass %	15.0	18.0	21.0	42.0	39.0	34.0	37.0	30.0
R32	Mass %	36.0	36.0	36.0	25.0	28.0	31.0	31.0	34.0
R1234yf	Mass %	49.0	46.0	43.0	33.0	33.0	35.0	32.0	36.0
GWP	—	245	245	245	170	191	211	211	231
COP Ratio	% (relative to R410A)	101.0	100.7	100.5	99.5	99.5	99.8	99.6	99.9
Refrigerating Capacity Ratio	% (relative to R410A)	86.2	87.9	89.6	92.7	93.4	93.0	94.5	93.0

TABLE 141

Item	Unit	Example 127	Example 128	Example 129	Example 130	Example 131	Example 132	Example 133	Example 134
HFO-1132(E)	Mass %	33.0	36.0	24.0	27.0	30.0	33.0	23.0	26.0
R32	Mass %	34.0	34.0	37.0	37.0	37.0	37.0	40.0	40.0
R1234yf	Mass %	33.0	30.0	39.0	36.0	33.0	30.0	37.0	34.0
GWP	—	231	231	252	251	251	251	272	272
COP Ratio	% (relative to R410A)	99.8	99.6	100.3	100.1	99.9	99.8	100.4	100.2
Refrigerating Capacity Ratio	% (relative to R410A)	94.5	96.0	91.9	93.4	95.0	96.5	93.3	94.9

TABLE 142

Item	Unit	Example 135	Example 136	Example 137	Example 138	Example 139	Example 140	Example 141	Example 142
HFO-1132(E)	Mass %	29.0	32.0	19.0	22.0	25.0	28.0	31.0	18.0
R32	Mass %	40.0	40.0	43.0	43.0	43.0	43.0	43.0	46.0
R1234yf	Mass %	31.0	28.0	38.0	35.0	32.0	29.0	26.0	36.0
GWP	—	272	271	292	292	292	292	292	312
COP Ratio	% (relative to R410A)	100.0	99.8	100.6	100.4	100.2	100.1	99.9	100.7
Refrigerating Capacity Ratio	% (relative to R410A)	96.4	97.9	93.1	94.7	96.2	97.8	99.3	94.4

TABLE 143

Item	Unit	Example 143	Example 144	Example 145	Example 146	Example 147	Example 148	Example 149	Example 150
HFO-1132(E)	Mass %	21.0	23.0	26.0	29.0	13.0	16.0	19.0	22.0
R32	Mass %	46.0	46.0	46.0	46.0	49.0	49.0	49.0	49.0
R1234yf	Mass %	33.0	31.0	28.0	25.0	38.0	35.0	32.0	29.0
GWP	—	312	312	312	312	332	332	332	332
COP Ratio	% (relative to R410A)	100.5	100.4	100.2	100.0	101.1	100.9	100.7	100.5
Refrigerating Capacity Ratio	% (relative to R410A)	96.0	97.0	98.6	100.1	93.5	95.1	96.7	98.3

TABLE 144

Item	Unit	Example 151	Example 152
HFO-1132(E)	Mass %	25.0	28.0
R32	Mass %	49.0	49.0
R1234yf	Mass %	26.0	23.0
GWP	—	332	332
COP Ratio	% (relative to R410A)	100.3	100.1
Refrigerating Capacity Ratio	% (relative to R410A)	99.8	101.3

[0921] The results also indicate that under the condition that the mass % of HFO-1132(E), R32, and R1234yf based on their sum is respectively represented by x, y, and z, when coordinates (x,y,z) in a ternary composition diagram in which the sum of HFO-1132(E), R32, and R1234yf is 100 mass % are within the range of a figure surrounded by line segments IJ, JN, NE, and EI that connect the following 4 points:

- [0922] point I (72.0, 0.0, 28.0),
- [0923] point J (48.5, 18.3, 33.2),
- [0924] point N (27.7, 18.2, 54.1), and
- [0925] point E (58.3, 0.0, 41.7),

or on these line segments (excluding the points on the line segment EI),

[0926] the line segment IJ is represented by coordinates $(0.0236y^2 - 1.7616y + 72.0, y, -0.0236y^2 + 0.7616y + 28.0)$,

[0927] the line segment NE is represented by coordinates $(0.012y^2 - 1.9003y + 58.3, y, -0.012y^2 + 0.9003y + 41.7)$, and

[0928] the line segments JN and EI are straight lines, the refrigerant D has a refrigerating capacity ratio of 80% or more relative to R410A, a GWP of 125 or less, and a WCF lower flammability.

[0929] The results also indicate that under the condition that the mass % of HFO-1132(E), R32, and R1234yf based on their sum is respectively represented by x, y, and z, when coordinates (x,y,z) in a ternary composition diagram in which the sum of HFO-1132(E), R32, and R1234yf is 100 mass % are within the range of a figure surrounded by line segments MM', M'N, NV, VG, and GM that connect the following 5 points:

- [0930] point M (52.6, 0.0, 47.4),
- [0931] point M' (39.2, 5.0, 55.8),
- [0932] point N (27.7, 18.2, 54.1),
- [0933] point V (11.0, 18.1, 70.9), and
- [0934] point G (39.6, 0.0, 60.4),

or on these line segments (excluding the points on the line segment GM),

[0935] the line segment MM' is represented by coordinates $(0.132y^2 - 3.34y + 52.6, y, -0.132y^2 + 2.34y + 47.4)$,

[0936] the line segment M'N is represented by coordinates $(0.0596y^2 - 2.2541y + 48.98, y, -0.0596y^2 + 1.2541y + 51.02)$,

[0937] the line segment VG is represented by coordinates $(0.0123y^2 - 1.8033y + 39.6, y, -0.0123y^2 + 0.8033y + 60.4)$, and [0938] the line segments NV and GM are straight lines, the refrigerant D according to the present disclosure has a refrigerating capacity ratio of 70% or more relative to R410A, a GWP of 125 or less, and an ASHRAE lower flammability.

[0939] The results also indicate that under the condition that the mass % of HFO-1132(E), R32, and R1234yf based on their sum is respectively represented by x, y, and z, when coordinates (x,y,z) in a ternary composition diagram in which the sum of HFO-1132(E), R32, and R1234yf is 100 mass % are within the range of a figure surrounded by line segments ON, NU, and UO that connect the following 3 points:

- [0940] point O (22.6, 36.8, 40.6),
- [0941] point N (27.7, 18.2, 54.1), and
- [0942] point U (3.9, 36.7, 59.4),

or on these line segments,

[0943] the line segment ON is represented by coordinates $(0.0072y^2 - 0.6701y + 37.512, y, -0.0072y^2 - 0.3299y + 62.488)$,

[0944] the line segment NU is represented by coordinates $(0.0083y^2 - 1.7403y + 56.635, y, -0.0083y^2 + 0.7403y + 43.365)$, and

[0945] the line segment UO is a straight line, the refrigerant D according to the present disclosure has a refrigerating capacity ratio of 80% or more relative to R410A, a GWP of 250 or less, and an ASHRAE lower flammability.

[0946] The results also indicate that under the condition that the mass % of HFO-1132(E), R32, and R1234yf based on their sum is respectively represented by x, y, and z, when coordinates (x,y,z) in a ternary composition diagram in which the sum of HFO-1132(E), R32, and R1234yf is 100 mass % are within the range of a figure surrounded by line segments QR, RT, TL, LK, and KQ that connect the following 5 points:

- [0947] point Q (44.6, 23.0, 32.4),
- [0948] point R (25.5, 36.8, 37.7),
- [0949] point T (8.6, 51.6, 39.8),
- [0950] point L (28.9, 51.7, 19.4), and
- [0951] point K (35.6, 36.8, 27.6),

or on these line segments,

[0952] the line segment QR is represented by coordinates $(0.0099y^2 - 1.975y + 84.765, y, -0.0099y^2 + 0.975y + 15.235)$,

[0953] the line segment RT is represented by coordinates $(0.0082y^2 - 1.8683y + 83.126, y, -0.0082y^2 + 0.8683y + 16.874)$,

[0954] the line segment LK is represented by coordinates $(0.0049y^2 - 0.8842y + 61.488, y, -0.0049y^2 - 0.1158y + 38.512)$,

[0955] the line segment KQ is represented by coordinates $(0.0095y^2 - 1.2222y + 67.676, y, -0.0095y^2 + 0.2222y + 32.324)$, and

[0956] the line segment TL is a straight line, the refrigerant D according to the present disclosure has a refrigerating capacity ratio of 92.5% or more relative to R410A, a GWP of 350 or less, and a WCF lower flammability.

[0957] The results further indicate that under the condition that the mass % of HFO-1132(E), R32, and R1234yf based on their sum is respectively represented by x, y, and z, when coordinates (x,y,z) in a ternary composition diagram in which the sum of HFO-1132(E), R32, and R1234yf is 100 mass % are within the range of a figure surrounded by line segments PS, ST, and TP that connect the following 3 points:

[0958] point P (20.5, 51.7, 27.8),

[0959] point S (21.9, 39.7, 38.4), and

[0960] point T (8.6, 51.6, 39.8),

or on these line segments,

[0961] the line segment PS is represented by coordinates $(0.0064y^2 - 0.7103y + 40.1, y, -0.0064y^2 - 0.2897y + 59.9)$,

[0962] the line segment ST is represented by coordinates $(0.0082y^2 - 1.8683y + 83.126, y, -0.0082y^2 + 0.8683y + 16.874)$, and

[0963] the line segment TP is a straight line, the refrigerant D according to the present disclosure has a refrigerating capacity ratio of 92.5% or more relative to R410A, a GWP of 350 or less, and an ASHRAE lower flammability.

(5-5) Refrigerant E

[0964] The refrigerant E according to the present disclosure is a mixed refrigerant comprising trans-1,2-difluoroethylene (HFO-1132(E)), trifluoroethylene (HFO-1123), and difluoromethane (R32).

[0965] The refrigerant E according to the present disclosure has various properties that are desirable as an R410A-alternative refrigerant, i.e., a coefficient of performance equivalent to that of R410A and a sufficiently low GWP.

[0966] The refrigerant E according to the present disclosure is preferably a refrigerant wherein

[0967] when the mass % of HFO-1132(E), HFO-1123, and R32 based on their sum is respectively represented by x, y, and z, coordinates (x,y,z) in a ternary composition diagram in which the sum of HFO-1132(E), HFO-1123, and R32 is 100 mass % are within the range of a figure surrounded by line segments IK, KB', B'H, HR, RG, and GI that connect the following 6 points:

[0968] point I (72.0, 28.0, 0.0),

[0969] point K (48.4, 33.2, 18.4),

[0970] point B' (0.0, 81.6, 18.4),

[0971] point H (0.0, 84.2, 15.8),

[0972] point R (23.1, 67.4, 9.5), and

[0973] point G (38.5, 61.5, 0.0),

or on these line segments (excluding the points on the line segments B'H and GI);

[0974] the line segment IK is represented by coordinates $(0.025z^2 - 1.7429z + 72.00, -0.025z^2 + 0.7429z + 28.0, z)$,

[0975] the line segment HR is represented by coordinates $(-0.3123z^2 + 4.234z + 11.06, 0.3123z^2 - 5.234z + 88.94, z)$,

[0976] the line segment RG is represented by coordinates $(-0.0491z^2 - 1.1544z + 38.5, 0.0491z^2 + 0.1544z + 61.5, z)$, and

[0977] the line segments KB' and GI are straight lines. When the requirements above are satisfied, the refrigerant according to the present disclosure has WCF lower flam-

mability, a COP ratio of 93% or more relative to that of R410A, and a GWP of 125 or less.

[0978] The refrigerant E according to the present disclosure is preferably a refrigerant wherein

[0979] when the mass % of HFO-1132(E), HFO-1123, and R32 based on their sum is respectively represented by x, y, and z, coordinates (x,y,z) in a ternary composition diagram in which the sum of HFO-1132(E), HFO-1123, and R32 is 100 mass % are within the range of a figure surrounded by line segments IJ, JR, RG, and GI that connect the following 4 points:

[0980] point I (72.0, 28.0, 0.0),

[0981] point J (57.7, 32.8, 9.5),

[0982] point R (23.1, 67.4, 9.5), and

[0983] point G (38.5, 61.5, 0.0),

or on these line segments (excluding the points on the line segment GI);

[0984] the line segment IJ is represented by coordinates $(0.025z^2 - 1.7429z + 72.0, -0.025z^2 + 0.7429z + 28.0, z)$,

[0985] the line segment RG is represented by coordinates $(-0.0491z^2 - 1.1544z + 38.5, 0.0491z^2 + 0.1544z + 61.5, z)$, and

[0986] the line segments JR and GI are straight lines. When the requirements above are satisfied, the refrigerant according to the present disclosure has WCF lower flammability, a COP ratio of 93% or more relative to that of R410A, and a GWP of 125 or less.

[0987] The refrigerant E according to the present disclosure is preferably a refrigerant wherein

[0988] when the mass % of HFO-1132(E), HFO-1123, and R32 based on their sum is respectively represented by x, y, and z, coordinates (x,y,z) in a ternary composition diagram in which the sum of HFO-1132(E), HFO-1123, and R32 is 100 mass % are within the range of a figure surrounded by line segments MP, PB', B'H, HR, RG, and GM that connect the following 6 points:

[0989] point M (47.1, 52.9, 0.0),

[0990] point P (31.8, 49.8, 18.4),

[0991] point B' (0.0, 81.6, 18.4),

[0992] point H (0.0, 84.2, 15.8),

[0993] point R (23.1, 67.4, 9.5), and

[0994] point G (38.5, 61.5, 0.0),

or on these line segments (excluding the points on the line segments B'H and GM);

[0995] the line segment MP is represented by coordinates $(0.0083z^2 - 0.984z + 47.1, -0.0083z^2 - 0.016z + 52.9, z)$,

[0996] the line segment HR is represented by coordinates $(-0.3123z^2 + 4.234z + 11.06, 0.3123z^2 - 5.234z + 88.94, z)$,

[0997] the line segment RG is represented by coordinates $(-0.0491z^2 - 1.1544z + 38.5, 0.0491z^2 + 0.1544z + 61.5, z)$, and

[0998] the line segments PB' and GM are straight lines. When the requirements above are satisfied, the refrigerant according to the present disclosure has ASHRAE lower flammability, a COP ratio of 93% or more relative to that of R410A, and a GWP of 125 or less.

[0999] The refrigerant E according to the present disclosure is preferably a refrigerant wherein

[1000] when the mass % of HFO-1132(E), HFO-1123, and R32 based on their sum is respectively represented by x, y, and z, coordinates (x,y,z) in a ternary composition diagram in which the sum of HFO-1132(E), HFO-1123, and R32 is 100 mass % are within the range of a figure surrounded by

line segments MN, NR, RG, and GM that connect the following 4 points:

[1001] point M (47.1, 52.9, 0.0),

[1002] point N (38.5, 52.1, 9.5),

[1003] point R (23.1, 67.4, 9.5), and

[1004] point G (38.5, 61.5, 0.0),

or on these line segments (excluding the points on the line segment GM);

[1005] the line segment MN is represented by coordinates $(0.0083z^2 - 0.984z + 47.1, -0.0083z^2 - 0.016z + 52.9, z)$,

[1006] the line segment RG is represented by coordinates $(-0.0491z^2 - 1.1544z + 38.5, 0.0491z^2 + 0.1544z + 61.5, z)$,

[1007] the line segments NR and GM are straight lines.

When the requirements above are satisfied, the refrigerant according to the present disclosure has ASHRAE lower flammability, a COP ratio of 93% or more relative to that of R410A, and a GWP of 65 or less.

[1008] The refrigerant E according to the present disclosure is preferably a refrigerant wherein

[1009] when the mass % of HFO-1132(E), HFO-1123, and R32 based on their sum is respectively represented by x, y, and z, coordinates (x,y,z) in a ternary composition diagram in which the sum of HFO-1132(E), HFO-1123, and R32 is 100 mass % are within the range of a figure surrounded by line segments PS, ST, and TP that connect the following 3 points:

[1010] point P (31.8, 49.8, 18.4),

[1011] point S (25.4, 56.2, 18.4), and

[1012] point T (34.8, 51.0, 14.2),

or on these line segments;

[1013] the line segment ST is represented by coordinates $(-0.0982z^2 + 0.9622z + 40.931, 0.0982z^2 - 1.9622z + 59.069, z)$,

[1014] the line segment TP is represented by coordinates $(0.0083z^2 - 0.984z + 47.1, -0.0083z^2 - 0.016z + 52.9, z)$, and

[1015] the line segment PS is a straight line. When the requirements above are satisfied, the refrigerant according to the present disclosure has ASHRAE lower flammability, a COP ratio of 94.5% or more relative to that of R410A, and a GWP of 125 or less.

[1016] The refrigerant E according to the present disclosure is preferably a refrigerant wherein

[1017] when the mass % of HFO-1132(E), HFO-1123, and R32 based on their sum is respectively represented by x, y, and z, coordinates (x,y,z) in a ternary composition diagram in which the sum of HFO-1132(E), HFO-1123, and R32 is 100 mass % are within the range of a figure surrounded by line segments QB", B"D, DU, and UQ that connect the following 4 points:

[1018] point Q (28.6, 34.4, 37.0),

[1019] point B" (0.0, 63.0, 37.0),

[1020] point D (0.0, 67.0, 33.0), and

[1021] point U (28.7, 41.2, 30.1),

or on these line segments (excluding the points on the line segment B"D);

[1022] the line segment DU is represented by coordinates $(-3.4962z^2 + 210.71z - 3146.1, 3.4962z^2 - 211.71z + 3246.1, z)$,

[1023] the line segment UQ is represented by coordinates $(0.0135z^2 - 0.9181z + 44.133, -0.0135z^2 - 0.0819z + 55.867, z)$, and

[1024] the line segments QB" and B"D are straight lines. When the requirements above are satisfied, the refrigerant according to the present disclosure has ASHRAE lower

flammability, a COP ratio of 96% or more relative to that of R410A, and a GWP of 250 or less.

[1025] The refrigerant E according to the present disclosure is preferably a refrigerant wherein

[1026] when the mass % of HFO-1132(E), HFO-1123, and R32 based on their sum is respectively represented by x, y, and z, coordinates (x,y,z) in a ternary composition diagram in which the sum of HFO-1132(E), HFO-1123, and R32 is 100 mass % are within the range of a figure surrounded by line segments Oc', c'd', d'e', e'a', and a'O that connect the following 5 points:

[1027] point O (100.0, 0.0, 0.0),

[1028] point c' (56.7, 43.3, 0.0),

[1029] point d' (52.2, 38.3, 9.5),

[1030] point e' (41.8, 39.8, 18.4), and

[1031] point a' (81.6, 0.0, 18.4),

or on the line segments c'd', d'e', and e'a' (excluding the points c' and a');

[1032] the line segment c'd' is represented by coordinates $(-0.0297z^2 - 0.1915z + 56.7, 0.0297z^2 + 1.1915z + 43.3, z)$,

[1033] the line segment d'e' is represented by coordinates $(-0.0535z^2 + 0.3229z + 53.957, 0.0535z^2 + 0.6771z + 46.043, z)$, and

[1034] the line segments Oc', e'a', and a'O are straight lines. When the requirements above are satisfied, the refrigerant according to the present disclosure has a COP ratio of 92.5% or more relative to that of R410A, and a GWP of 125 or less.

[1035] The refrigerant E according to the present disclosure is preferably a refrigerant wherein

[1036] when the mass % of HFO-1132(E), HFO-1123, and R32 based on their sum is respectively represented by x, y, and z, coordinates (x,y,z) in a ternary composition diagram in which the sum of HFO-1132(E), HFO-1123, and R32 is 100 mass % are within the range of a figure surrounded by line segments Oc, cd, de, ea', and a'O that connect the following 5 points:

[1037] point O (100.0, 0.0, 0.0),

[1038] point c (77.7, 22.3, 0.0),

[1039] point d (76.3, 14.2, 9.5),

[1040] point e (72.2, 9.4, 18.4), and

[1041] point a' (81.6, 0.0, 18.4),

or on the line segments cd, de, and ea' (excluding the points c and a');

[1042] the line segment cde is represented by coordinates $(-0.017z^2 + 0.0148z + 77.684, 0.017z^2 + 0.9852z + 22.316, z)$, and

[1043] the line segments Oc, ea', and a'O are straight lines. When the requirements above are satisfied, the refrigerant according to the present disclosure has a COP ratio of 95% or more relative to that of R410A, and a GWP of 125 or less.

[1044] The refrigerant E according to the present disclosure is preferably a refrigerant wherein

[1045] when the mass % of HFO-1132(E), HFO-1123, and R32 based on their sum is respectively represented by x, y, and z, coordinates (x,y,z) in a ternary composition diagram in which the sum of HFO-1132(E), HFO-1123, and R32 is 100 mass % are within the range of a figure surrounded by line segments Oc', c'd', d'a, and a'O that connect the following 5 points:

[1046] point O (100.0, 0.0, 0.0),

[1047] point c' (56.7, 43.3, 0.0),

[1048] point d' (52.2, 38.3, 9.5), and

[1049] point a (90.5, 0.0, 9.5),

TABLE 146-continued

Item	Unit	M	N	T	P	U	Q	
WCFF	HFO-1132(E)	mass %	72.0	58.9	51.5	44.6	31.4	27.1
	HFO-1123	mass %	28.0	32.4	33.1	32.6	23.2	18.3
	R32	mass %	0.0	8.7	15.4	22.8	45.4	54.6
	Burning velocity (WCF)	cm/s	8 or less	8 or less	8 or less	8 or less	8 or less	8 or less
	Burning velocity (WCFF)	cm/s	10	10	10	10	10	10

[1068] The results in Table 1 indicate that in a ternary composition diagram of a mixed refrigerant of HFO-1132 (E), HFO-1123, and R32 in which their sum is 100 mass %, a line segment connecting a point (0.0, 100.0, 0.0) and a point (0.0, 0.0, 100.0) is the base, the point (0.0, 100.0, 0.0) is on the left side, and the point (0.0, 0.0, 100.0) is on the right side, when coordinates (x,y,z) are on or below line segments IK and KL that connect the following 3 points:

[1069] point I (72.0, 28.0, 0.0),

[1070] point K (48.4, 33.2, 18.4), and

[1071] point L (35.5, 27.5, 37.0);

[1072] the line segment IK is represented by coordinates $(0.025z^2-1.7429z+72.00, -0.025z^2+0.7429z+28.00, z)$, and

[1073] the line segment KL is represented by coordinates $(0.0098z^2-1.238z+67.852, -0.0098z^2+0.238z+32.148, z)$,

[1074] it can be determined that the refrigerant has WCF lower flammability.

[1075] For the points on the line segment IK, an approximate curve $(x=0.025z^2-1.7429z+72.00)$ was obtained from three points, i.e., I (72.0, 28.0, 0.0), J (57.7, 32.8, 9.5), and K (48.4, 33.2, 18.4) by using the least-square method to determine coordinates $(x=0.025z^2-1.7429z+72.00, y=100-z-x=-0.00922z^2+0.2114z+32.443, z)$.

[1076] Likewise, for the points on the line segment KL, an approximate curve was determined from three points, i.e., K (48.4, 33.2, 18.4), Example 10 (41.1, 31.2, 27.7), and L (35.5, 27.5, 37.0) by using the least-square method to determine coordinates.

[1077] The results in Table 146 indicate that in a ternary composition diagram of a mixed refrigerant of HFO-1132 (E), HFO-1123, and R32 in which their sum is 100 mass %, a line segment connecting a point (0.0, 100.0, 0.0) and a point (0.0, 0.0, 100.0) is the base, the point (0.0, 100.0, 0.0) is on the left side, and the point (0.0, 0.0, 100.0) is on the right side, when coordinates (x,y,z) are on or below line segments MP and PQ that connect the following 3 points:

[1078] point M (47.1, 52.9, 0.0),

[1079] point P (31.8, 49.8, 18.4), and

[1080] point Q (28.6, 34.4, 37.0),

it can be determined that the refrigerant has ASHRAE lower flammability.

[1081] In the above, the line segment MP is represented by coordinates $(0.0083z^2-0.984z+47.1, -0.0083z^2-0.016z+52.9, z)$, and the line segment PQ is represented by coordinates $(0.0135z^2-0.9181z+44.133, -0.0135z^2-0.0819z+55.867, z)$.

[1082] For the points on the line segment MP, an approximate curve was obtained from three points, i.e., points M, N, and P, by using the least-square method to determine coordinates. For the points on the line segment PQ, an approximate curve was obtained from three points, i.e., points P, U, and Q, by using the least-square method to determine coordinates.

[1083] The GWP of compositions each comprising a mixture of R410A (R32=50%/R125=50%) was evaluated based on the values stated in the Intergovernmental Panel on Climate Change (IPCC), fourth report. The GWP of HFO-1132(E), which was not stated therein, was assumed to be 1 from HFO-1132a (GWP=1 or less) and HFO-1123 (GWP=0.3, described in Patent Literature 1). The refrigerating capacity of compositions each comprising R410A and a mixture of HFO-1132(E) and HFO-1123 was determined by performing theoretical refrigeration cycle calculations for the mixed refrigerants using the National Institute of Science and Technology (NIST) and Reference Fluid Thermodynamic and Transport Properties Database (Refprop 9.0) under the following conditions.

[1084] The COP ratio and the refrigerating capacity (which may be referred to as “cooling capacity” or “capacity”) ratio relative to those of R410 of the mixed refrigerants were determined. The conditions for calculation were as described below.

[1085] Evaporating temperature: 5° C.

[1086] Condensation temperature: 45° C.

[1087] Degree of superheating: 5K

[1088] Degree of subcooling: 5K

[1089] Compressor efficiency: 70%

[1090] Tables 147 to 166 show these values together with the GWP of each mixed refrigerant.

TABLE 147

Item	Unit	Comparative Example 1	Comparative Example 2 A	Comparative Example 3 B	Comparative Example 4 A'	Comparative Example 5 B'	Comparative Example 6 A''	Comparative Example 7 B''
HFO-1132(E)	mass %	R410A	90.5	0.0	81.6	0.0	63.0	0.0
HFO-1123	mass %		0.0	90.5	0.0	81.6	0.0	63.0
R32	mass %		9.5	9.5	18.4	18.4	37.0	37.0
GWP	—	2088	65	65	125	125	250	250

TABLE 147-continued

Item	Unit	Comparative Example 1	Comparative Example 2 A	Comparative Example 3 B	Comparative Example 4 A'	Comparative Example 5 B'	Comparative Example 6 A''	Comparative Example 7 B''
COP ratio	% (relative to R410A)	100	99.1	92.0	98.7	93.4	98.7	96.1
Refrigerating capacity ratio	% (relative to R410A)	100	102.2	111.6	105.3	113.7	110.0	115.4

TABLE 148

Item	Unit	Comparative Example 8 O	Comparative Example 9 C	Comparative Example 10	Example 1 U	Example 2	Comparative Example 11 D
HFO-1132(E)	mass %	100.0	50.0	41.1	28.7	15.2	0.0
HFO-1123	mass %	0.0	31.6	34.6	41.2	52.7	67.0
R32	mass %	0.0	18.4	24.3	30.1	32.1	33.0
GWP	—	1	125	165	204	217	228
COP ratio	% (relative to R410A)	99.7	96.0	96.0	96.0	96.0	96.0
Refrigerating capacity ratio	% (relative to R410A)	98.3	109.9	111.7	113.5	114.8	115.4

TABLE 149

Item	Unit	Comparative Example 12 E	Comparative Example 13	Example 3 T	Example 4 S	Comparative Example 14 F
HFO-1132(E)	mass %	53.4	43.4	34.8	25.4	0.0
HFO-1123	mass %	46.6	47.1	51.0	56.2	74.1
R32	mass %	0.0	9.5	14.2	18.4	25.9
GWP	—	1	65	97	125	176
COP ratio	% (relative to R410A)	94.5	94.5	94.5	94.5	94.5
Refrigerating capacity ratio	% (relative to R410A)	105.6	109.2	110.8	112.3	114.8

TABLE 150

Item	Unit	Comparative Example 15 G	Example 5	Example 6 R	Example 7	Comparative Example 16 H
HFO-1132(E)	mass %	38.5	31.5	23.1	16.9	0.0
HFO-1123	mass %	61.5	63.5	67.4	71.1	84.2
R32	mass %	0.0	5.0	9.5	12.0	15.8
GWP	—	1	35	65	82	107
COP ratio	% (relative to R410A)	93.0	93.0	93.0	93.0	93.0
Refrigerating capacity ratio	% (relative to R410A)	107.0	109.1	110.9	111.9	113.2

TABLE 151

Item	Unit	Comparative Example 17 I	Example 8 J	Example 9 K	Comparative Example 18	Comparative Example 19 L
HFO-1132(E)	mass %	72.0	57.7	48.4	41.1	35.5
HFO-1123	mass %	28.0	32.8	33.2	31.2	27.5
R32	mass %	0.0	9.5	18.4	27.7	37.0
GWP	—	1	65	125	188	250
COP ratio	% (relative to R410A)	96.6	95.8	95.9	96.4	97.1

TABLE 151-continued

Item	Unit	Comparative Example 17 I	Example 8 J	Example 9 K	Comparative Example 18	Comparative Example 19 L
Refrigerating capacity ratio	% (relative to R410A)	103.1	107.4	110.1	112.1	113.2

TABLE 152

Item	Unit	Comparative Example 20 M	Example 10 N	Example 11 P	Example 12 Q
HFO-1132(E)	mass %	47.1	38.5	31.8	28.6
HFO-1123	mass %	52.9	52.1	49.8	34.4
R32	mass %	0.0	9.5	18.4	37.0
GWP	—	1	65	125	250

TABLE 152-continued

Item	Unit	Comparative Example 20 M	Example 10 N	Example 11 P	Example 12 Q
COP ratio	% (relative to R410A)	93.9	94.1	94.7	96.9
Refrigerating capacity ratio	% (relative to R410A)	106.2	109.7	112.0	114.1

TABLE 153

Item	Unit	Comparative Example 22	Comparative Example 23	Comparative Example 24	Example 14	Example 15	Example 16	Comparative Example 25	Comparative Example 26
HFO-1132(E)	mass %	10.0	20.0	30.0	40.0	50.0	60.0	70.0	80.0
HFO-1123	mass %	85.0	75.0	65.0	55.0	45.0	35.0	25.0	15.0
R32	mass %	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0
GWP	—	35	35	35	35	35	35	35	35
COP ratio	% (relative to R410A)	91.7	92.2	92.9	93.7	94.6	95.6	96.7	97.7
Refrigerating capacity ratio	% (relative to R410A)	110.1	109.8	109.2	108.4	107.4	106.1	104.7	103.1

TABLE 154

Item	Unit	Comparative Example 27	Comparative Example 28	Comparative Example 29	Example 17	Example 18	Example 19	Comparative Example 30	Comparative Example 31
HFO-1132(E)	mass %	90.0	10.0	20.0	30.0	40.0	50.0	60.0	70.0
HFO-1123	mass %	5.0	80.0	70.0	60.0	50.0	40.0	30.0	20.0
R32	mass %	5.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
GWP	—	35	68	68	68	68	68	68	68
COP ratio	% (relative to R410A)	98.8	92.4	92.9	93.5	94.3	95.1	96.1	97.0
Refrigerating capacity ratio	% (relative to R410A)	101.4	111.7	111.3	110.6	109.6	108.5	107.2	105.7

TABLE 155

Item	Unit	Comparative Example 32	Example 20	Example 21	Example 22	Example 23	Example 24	Comparative Example 33	Comparative Example 34
HFO-1132(E)	mass %	80.0	10.0	20.0	30.0	40.0	50.0	60.0	70.0
HFO-1123	mass %	10.0	75.0	65.0	55.0	45.0	35.0	25.0	15.0
R32	mass %	10.0	15.0	15.0	15.0	15.0	15.0	15.0	15.0
GWP	—	68	102	102	102	102	102	102	102
COP ratio	% (relative to R410A)	98.0	93.1	93.6	94.2	94.9	95.6	96.5	97.4
Refrigerating capacity ratio	% (relative to R410A)	104.1	112.9	112.4	111.6	110.6	109.4	108.1	106.6

TABLE 156

Item	Unit	Comparative Example 35	Comparative Example 36	Comparative Example 37	Comparative Example 38	Comparative Example 39	Comparative Example 40	Comparative Example 41	Comparative Example 42
HFO-1132(E)	mass %	80.0	10.0	20.0	30.0	40.0	50.0	60.0	70.0
HFO-1123	mass %	5.0	70.0	60.0	50.0	40.0	30.0	20.0	10.0
R32	mass %	15.0	20.0	20.0	20.0	20.0	20.0	20.0	20.0
GWP	—	102	136	136	136	136	136	136	136
COP ratio	% (relative to R410A)	98.3	93.9	94.3	94.8	95.4	96.2	97.0	97.8
Refrigerating capacity ratio	% (relative to R410A)	105.0	113.8	113.2	112.4	111.4	110.2	108.8	107.3

TABLE 157

Item	Unit	Comparative Example 43	Comparative Example 44	Comparative Example 45	Comparative Example 46	Comparative Example 47	Comparative Example 48	Comparative Example 49	Comparative Example 50
HFO-1132(E)	mass %	10.0	20.0	30.0	40.0	50.0	60.0	70.0	10.0
HFO-1123	mass %	65.0	55.0	45.0	35.0	25.0	15.0	5.0	60.0
R32	mass %	25.0	25.0	25.0	25.0	25.0	25.0	25.0	30.0
GWP	—	170	170	170	170	170	170	170	203
COP ratio	% (relative to R410A)	94.6	94.9	95.4	96.0	96.7	97.4	98.2	95.3
Refrigerating capacity ratio	% (relative to R410A)	114.4	113.8	113.0	111.9	110.7	109.4	107.9	114.8

TABLE 158

Item	Unit	Comparative Example 51	Comparative Example 52	Comparative Example 53	Comparative Example 54	Comparative Example 55	Example 25	Example 26	Comparative Example 56
HFO-1132(E)	mass %	20.0	30.0	40.0	50.0	60.0	10.0	20.0	30.0
HFO-1123	mass %	50.0	40.0	30.0	20.0	10.0	55.0	45.0	35.0
R32	mass %	30.0	30.0	30.0	30.0	30.0	35.0	35.0	35.0
GWP	—	203	203	203	203	203	237	237	237
COP ratio	% (relative to R410A)	95.6	96.0	96.6	97.2	97.9	96.0	96.3	96.6
Refrigerating capacity ratio	% (relative to R410A)	114.2	113.4	112.4	111.2	109.8	115.1	114.5	113.6

TABLE 159

Item	Unit	Comparative Example 57	Comparative Example 58	Comparative Example 59	Comparative Example 60	Comparative Example 61	Comparative Example 62	Comparative Example 63	Comparative Example 64
HFO-1132(E)	mass %	40.0	50.0	60.0	10.0	20.0	30.0	40.0	50.0
HFO-1123	mass %	25.0	15.0	5.0	50.0	40.0	30.0	20.0	10.0
R32	mass %	35.0	35.0	35.0	40.0	40.0	40.0	40.0	40.0
GWP	—	237	237	237	271	271	271	271	271
COP ratio	% (relative to R410A)	97.1	97.7	98.3	96.6	96.9	97.2	97.7	98.2
Refrigerating capacity ratio	% (relative to R410A)	112.6	111.5	110.2	115.1	114.6	113.8	112.8	111.7

TABLE 160

Item	Unit	Example 27	Example 28	Example 29	Example 30	Example 31	Example 32	Example 33	Example 34
HFO-1132(E)	mass %	38.0	40.0	42.0	44.0	35.0	37.0	39.0	41.0
HFO-1123	mass %	60.0	58.0	56.0	54.0	61.0	59.0	57.0	55.0
R32	mass %	2.0	2.0	2.0	2.0	4.0	4.0	4.0	4.0
GWP	—	14	14	14	14	28	28	28	28
COP ratio	% (relative to R410A)	93.2	93.4	93.6	93.7	93.2	93.3	93.5	93.7
Refrigerating capacity ratio	% (relative to R410A)	107.7	107.5	107.3	107.2	108.6	108.4	108.2	108.0

TABLE 161

Item	Unit	Example 35	Example 36	Example 37	Example 38	Example 39	Example 40	Example 41	Example 42
HFO-1132(E)	mass %	43.0	31.0	33.0	35.0	37.0	39.0	41.0	27.0
HFO-1123	mass %	53.0	63.0	61.0	59.0	57.0	55.0	53.0	65.0
R32	mass %	4.0	6.0	6.0	6.0	6.0	6.0	6.0	8.0
GWP	—	28	41	41	41	41	41	41	55
COP ratio	% (relative to R410A)	93.9	93.1	93.2	93.4	93.6	93.7	93.9	93.0
Refrigerating capacity ratio	% (relative to R410A)	107.8	109.5	109.3	109.1	109.0	108.8	108.6	110.3

TABLE 162

Item	Unit	Example 43	Example 44	Example 45	Example 46	Example 47	Example 48	Example 49	Example 50
HFO-1132(E)	mass %	29.0	31.0	33.0	35.0	37.0	39.0	32.0	32.0
HFO-1123	mass %	63.0	61.0	59.0	57.0	55.0	53.0	51.0	50.0
R32	mass %	8.0	8.0	8.0	8.0	8.0	8.0	17.0	18.0
GWP	—	55	55	55	55	55	55	116	122
COP ratio	% (relative to R410A)	93.2	93.3	93.5	93.6	93.8	94.0	94.5	94.7
Refrigerating capacity ratio	% (relative to R410A)	110.1	110.0	109.8	109.6	109.5	109.3	111.8	111.9

TABLE 163

Item	Unit	Example 51	Example 52	Example 53	Example 54	Example 55	Example 56	Example 57	Example 58
HFO-1132(E)	mass %	30.0	27.0	21.0	23.0	25.0	27.0	11.0	13.0
HFO-1123	mass %	52.0	42.0	46.0	44.0	42.0	40.0	54.0	52.0
R32	mass %	18.0	31.0	33.0	33.0	33.0	33.0	35.0	35.0
GWP	—	122	210	223	223	223	223	237	237
COP ratio	% (relative to R410A)	94.5	96.0	96.0	96.1	96.2	96.3	96.0	96.0
Refrigerating capacity ratio	% (relative to R410A)	112.1	113.7	114.3	114.2	114.0	113.8	115.0	114.9

TABLE 164

Item	Unit	Example 59	Example 60	Example 61	Example 62	Example 63	Example 64	Example 65	Example 66
HFO-1132(E)	mass %	15.0	17.0	19.0	21.0	23.0	25.0	27.0	11.0
HFO-1123	mass %	50.0	48.0	46.0	44.0	42.0	40.0	38.0	52.0
R32	mass %	35.0	35.0	35.0	35.0	35.0	35.0	35.0	37.0
GWP	—	237	237	237	237	237	237	237	250
COP ratio	% (relative to R410A)	96.1	96.2	96.2	96.3	96.4	96.4	96.5	96.2
Refrigerating capacity ratio	% (relative to R410A)	114.8	114.7	114.5	114.4	114.2	114.1	113.9	115.1

TABLE 165

Item	Unit	Example 67	Example 68	Example 69	Example 70	Example 71	Example 72	Example 73	Example 74
HFO-1132(E)	mass %	13.0	15.0	17.0	15.0	17.0	19.0	21.0	23.0
HFO-1123	mass %	50.0	48.0	46.0	50.0	48.0	46.0	44.0	42.0
R32	mass %	37.0	37.0	37.0	0.0	0.0	0.0	0.0	0.0
GWP	—	250	250	250	237	237	237	237	237
COP ratio	% (relative to R410A)	96.3	96.4	96.4	96.1	96.2	96.2	96.3	96.4
Refrigerating capacity ratio	% (relative to R410A)	115.0	114.9	114.7	114.8	114.7	114.5	114.4	114.2

TABLE 166

Item	Unit	Example 75	Example 76	Example 77	Example 78	Example 79	Example 80	Example 81	Example 82
HFO-1132(E)	mass %	25.0	27.0	11.0	19.0	21.0	23.0	25.0	27.0
HFO-1123	mass %	40.0	38.0	52.0	44.0	42.0	40.0	38.0	36.0
R32	mass %	0.0	0.0	0.0	37.0	37.0	37.0	37.0	37.0
GWP	—	237	237	250	250	250	250	250	250
COP ratio	% (relative to R410A)	96.4	96.5	96.2	96.5	96.5	96.6	96.7	96.8
Refrigerating capacity ratio	% (relative to R410A)	114.1	113.9	115.1	114.6	114.5	114.3	114.1	114.0

[1091] The above results indicate that under the condition that the mass % of HFO-1132(E), HFO-1123, and R32 based on their sum is respectively represented by x, y, and z, when coordinates (x,y,z) in a ternary composition diagram in which the sum of HFO-1132(E), HFO-1123, and R32 is 100 mass %, a line segment connecting a point (0.0, 100.0, 0.0) and a point (0.0, 0.0, 100.0) is the base, and the point (0.0, 100.0, 0.0) is on the left side are within the range of a figure surrounded by line segments that connect the following 4 points:

[1092] point O (100.0, 0.0, 0.0),

[1093] point A" (63.0, 0.0, 37.0),

[1094] point B" (0.0, 63.0, 37.0), and

[1095] point (0.0, 100.0, 0.0),

[1096] or on these line segments,

[1097] the refrigerant has a GWP of 250 or less.

[1098] The results also indicate that when coordinates (x,y,z) are within the range of a figure surrounded by line segments that connect the following 4 points:

[1099] point O (100.0, 0.0, 0.0),

[1100] point A' (81.6, 0.0, 18.4),

[1101] point B' (0.0, 81.6, 18.4), and

[1102] point (0.0, 100.0, 0.0),

[1103] or on these line segments,

[1104] the refrigerant has a GWP of 125 or less.

[1105] The results also indicate that when coordinates (x,y,z) are within the range of a figure surrounded by line segments that connect the following 4 points:

[1106] point O (100.0, 0.0, 0.0),

[1107] point A (90.5, 0.0, 9.5),

[1108] point B (0.0, 90.5, 9.5), and

[1109] point (0.0, 100.0, 0.0),

[1110] or on these line segments,

[1111] the refrigerant has a GWP of 65 or less.

[1112] The results also indicate that when coordinates (x,y,z) are on the left side of line segments that connect the following 3 points:

[1113] point C (50.0, 31.6, 18.4),

[1114] point U (28.7, 41.2, 30.1), and

[1115] point D(52.2, 38.3, 9.5),

[1116] or on these line segments,

[1117] the refrigerant has a COP ratio of 96% or more relative to that of R410A.

[1118] In the above, the line segment CU is represented by coordinates $(-0.0538z^2+0.7888z+53.701, 0.0538z^2-1.7888z+46.299, z)$, and the line segment UD is represented by coordinates $(-3.4962z^2+210.71z-3146.1, 3.4962z^2-211.71z+3246.1, z)$.

[1119] The points on the line segment CU are determined from three points, i.e., point C, Comparative Example 10, and point U, by using the least-square method.

[1120] The points on the line segment UD are determined from three points, i.e., point U, Example 2, and point D, by using the least-square method.

[1121] The results also indicate that when coordinates (x,y,z) are on the left side of line segments that connect the following 3 points:

[1122] point E (55.2, 44.8, 0.0),

[1123] point T (34.8, 51.0, 14.2), and

[1124] point F (0.0, 76.7, 23.3),

[1125] or on these line segments,

the refrigerant has a COP ratio of 94.5% or more relative to that of R410A.

[1126] In the above, the line segment ET is represented by coordinates $(-0.0547z^2-0.5327z+53.4, 0.0547z^2-0.4673z+46.6, z)$, and the line segment TF is represented by coordinates $(-0.0982z^2+0.9622z+40.931, 0.0982z^2-1.9622z+59.069, z)$.

[1127] The points on the line segment ET are determined from three points, i.e., point E, Example 2, and point T, by using the least-square method.

[1128] The points on the line segment TF are determined from three points, i.e., points T, S, and F, by using the least-square method.

[1129] The results also indicate that when coordinates (x,y,z) are on the left side of line segments that connect the following 3 points:

[1130] point G (0.0, 76.7, 23.3),

[1131] point R (21.0, 69.5, 9.5), and

[1132] point H (0.0, 85.9, 14.1),

[1133] or on these line segments,

[1134] the refrigerant has a COP ratio of 93% or more relative to that of R410A.

[1135] In the above, the line segment GR is represented by coordinates $(-0.0491z^2-1.1544z+38.5, 0.0491z^2+0.1544z+61.5, z)$, and the line segment RH is represented by coordinates $(-0.3123z^2+4.234z+11.06, 0.3123z^2-5.234z+88.94, z)$.

[1136] The points on the line segment GR are determined from three points, i.e., point G, Example 5, and point R, by using the least-square method.

[1137] The points on the line segment RH are determined from three points, i.e., point R, Example 7, and point H, by using the least-square method.

[1138] In contrast, as shown in, for example, Comparative Examples 8, 9, 13, 15, 17, and 18, when R32 is not contained, the concentrations of HFO-1132(E) and HFO-1123, which have a double bond, become relatively high; this undesirably leads to deterioration, such as decomposition, or polymerization in the refrigerant compound.

(6) First Embodiment

[1139] Hereinafter, an air conditioner 1 that serves as a refrigeration cycle apparatus including an outdoor unit 20 as a heat source unit according to a first embodiment will be described with reference to FIG. 16 that is the schematic configuration diagram of a refrigerant circuit and FIG. 17 that is a schematic control block configuration diagram.

[1140] The air conditioner 1 is an apparatus that air-conditions a space to be air-conditioned by performing a vapor compression refrigeration cycle.

[1141] The air conditioner 1 mainly includes an outdoor unit 20, an indoor unit 30, a liquid-side connection pipe 6 and a gas-side connection pipe 5 connecting the outdoor unit 20 and the indoor unit 30, a remote control unit (not shown) serving as an input device and an output device, and a controller 7 that controls the operation of the air conditioner 1. The design pressure of each of the liquid-side connection pipe 6 and the gas-side connection pipe 5 may be, for example, higher than or equal to 4.5 MPa (for the one having a diameter of $\frac{3}{8}$ inches) and lower than or equal to 5.0 MPa (for the one having a diameter of $\frac{1}{2}$ inches).

[1142] In the air conditioner 1, the refrigeration cycle in which refrigerant sealed in a refrigerant circuit 10 is compressed, cooled or condensed, decompressed, heated or evaporated, and then compressed again is performed. In the present embodiment, the refrigerant circuit 10 is filled with refrigerant for performing a vapor compression refrigeration cycle. The refrigerant is a refrigerant containing 1,2-difluoroethylene, and any one of the above-described refrigerants A to E may be used. The refrigerant circuit 10 is filled with refrigerating machine oil together with the refrigerant.

(6-1) Outdoor Unit 20

[1143] The outdoor unit 20 has substantially a rectangular parallelepiped box shape from its appearance, and has a structure in which a fan chamber and a machine chamber are formed (so-called, trunk structure) when the inside is divided by a partition plate, or the like.

[1144] The outdoor unit 20 is connected to the indoor unit 30 via the liquid-side connection pipe 6 and the gas-side connection pipe 5, and makes up part of the refrigerant circuit 10. The outdoor unit 20 mainly includes a compressor 21, a four-way valve 22, an outdoor heat exchanger 23, an outdoor expansion valve 24, an outdoor fan 25, a liquid-side stop valve 29, and a gas-side stop valve 28.

[1145] The outdoor unit 20 has a design pressure (gauge pressure) that is lower than 1.5 times the design pressure of each of the liquid-side connection pipe 6 and the gas-side connection pipe 5 (the withstanding pressure of each of the liquid-side connection pipe 6 and the gas-side connection pipe 5). The design pressure of the outdoor unit 20 may be, for example, higher than or equal to 4.0 MPa and lower than or equal to 4.5 MPa.

[1146] The compressor 21 is a device that compresses low-pressure refrigerant into high pressure in the refrigeration cycle. Here, the compressor 21 is a hermetically sealed compressor in which a positive-displacement, such as a rotary type and a scroll type, compression element (not shown) is driven for rotation by a compressor motor. The compressor motor is used to change the displacement. The operation frequency of the compressor motor is controllable with an inverter. The compressor 21 is provided with an attached accumulator (not shown) at its suction side. The

outdoor unit 20 of the present embodiment does not have a refrigerant container larger than the attached accumulator (a low-pressure receiver disposed at the suction side of the compressor 21, a high-pressure receiver disposed at a liquid side of the outdoor heat exchanger 23, or the like).

[1147] The four-way valve 22 is able to switch between a cooling operation connection state and a heating operation connection state by switching the status of connection. In the cooling operation connection state, a discharge side of the compressor 21 and the outdoor heat exchanger 23 are connected, and the suction side of the compressor 21 and the gas-side stop valve 28 are connected. In the heating operation connection state, the discharge side of the compressor 21 and the gas-side stop valve 28 are connected, and the suction side of the compressor 21 and the outdoor heat exchanger 23 are connected.

[1148] The outdoor heat exchanger 23 is a heat exchanger that functions as a condenser for high-pressure refrigerant in the refrigeration cycle during cooling operation and that functions as an evaporator for low-pressure refrigerant in the refrigeration cycle during heating operation. The outdoor heat exchanger 23 includes a plurality of heat transfer fins and a plurality of heat transfer tubes fixedly extending through the heat transfer fins.

[1149] The outdoor fan 25 takes outdoor air into the outdoor unit 20, causes the air to exchange heat with refrigerant in the outdoor heat exchanger 23, and then generates air flow for emitting the air to the outside. The outdoor fan 25 is driven for rotation by an outdoor fan motor. In the present embodiment, only one outdoor fan 25 is provided.

[1150] The outdoor expansion valve 24 is able to control the valve opening degree, and is provided between a liquid-side end portion of the outdoor heat exchanger 23 and the liquid-side stop valve 29.

[1151] The liquid-side stop valve 29 is a manual valve disposed at a connection point at which the outdoor unit 20 is connected to the liquid-side connection pipe 6.

[1152] The gas-side stop valve 28 is a manual valve disposed at a connection point at which the outdoor unit 20 is connected to the gas-side connection pipe 5.

[1153] The outdoor unit 20 includes an outdoor unit control unit 27 that controls the operations of parts that make up the outdoor unit 20. The outdoor unit control unit 27 includes a microcomputer including a CPU, a memory, and the like. The outdoor unit control unit 27 is connected to an indoor unit control unit 34 of indoor unit 30 via a communication line, and sends or receives control signals, or the like, to or from the indoor unit control unit 34. The outdoor unit control unit 27 is electrically connected to various sensors (not shown), and receives signals from the sensors.

[1154] In the outdoor unit control unit 27 (and the controller 7 including this unit), an upper limit of a controlled pressure (gauge pressure) of refrigerant is set so as to be lower than 1.5 times the design pressure of each of the liquid-side connection pipe 6 and the gas-side connection pipe 5 (the withstanding pressure of each of the liquid-side connection pipe 6 and the gas-side connection pipe 5).

(6-2) Indoor Unit 30

[1155] The indoor unit 30 is placed on a wall surface, or the like, in a room that is the space to be air-conditioned. The indoor unit 30 is connected to the outdoor unit 20 via the liquid-side connection pipe 6 and the gas-side connection

pipe 5, and makes up part of the refrigerant circuit 10. The design pressure of the indoor unit 30, as well as the outdoor unit 20, may be, for example, higher than or equal to 4.0 MPa and lower than or equal to 4.5 MPa.

[1156] The indoor unit 30 includes an indoor heat exchanger 31, an indoor fan 32, and the like.

[1157] A liquid side of the indoor heat exchanger 31 is connected to the liquid-side connection pipe 6, and a gas side of the indoor heat exchanger 31 is connected to the gas-side connection pipe 5. The indoor heat exchanger 31 is a heat exchanger that functions as an evaporator for low-pressure refrigerant in the refrigeration cycle during cooling operation and that functions as a condenser for high-pressure refrigerant in the refrigeration cycle during heating operation. The indoor heat exchanger 31 includes a plurality of heat transfer fins and a plurality of heat transfer tubes fixedly extending through the heat transfer fins.

[1158] The indoor fan 32 takes indoor air into the indoor unit 30, causes the air to exchange heat with refrigerant in the indoor heat exchanger 31, and then generates air flow for emitting the air to the outside. The indoor fan 32 is driven for rotation by an indoor fan motor (not shown).

[1159] The indoor unit 30 includes an indoor unit control unit 34 that controls the operations of the parts that make up the indoor unit 30. The indoor unit control unit 34 includes a microcomputer including a CPU, a memory, and the like. The indoor unit control unit 34 is connected to the outdoor unit control unit 27 via a communication line, and sends or receives control signals, or the like, to or from the outdoor unit control unit 27.

[1160] The indoor unit control unit 34 is electrically connected to various sensors (not shown) provided inside the indoor unit 30, and receives signals from the sensors.

(6-3) Details of Controller 7

[1161] In the air conditioner 1, the outdoor unit control unit 27 and the indoor unit control unit 34 are connected via the communication line to make up the controller 7 that controls the operation of the air conditioner 1.

[1162] The controller 7 mainly includes a CPU (central processing unit) and a memory such as a ROM and a RAM. Various processes and controls made by the controller 7 are implemented by various parts included in the outdoor unit control unit 27 and/or the indoor unit control unit 34 functioning together.

(6-4) Operation Mode

[1163] Hereinafter, operation modes will be described.

[1164] The operation modes include a cooling operation mode and a heating operation mode.

[1165] The controller 7 determines whether the operation mode is the cooling operation mode or the heating operation mode and performs the selected operation mode based on an instruction received from the remote control unit, or the like.

[1166] (6-4-1) Cooling Operation Mode

[1167] In the air conditioner 1, in the cooling operation mode, the status of connection of the four-way valve 22 is set to the cooling operation connection state where the discharge side of the compressor 21 and the outdoor heat exchanger 23 are connected and the suction side of the compressor 21 and the gas-side stop valve 28 are connected, and refrigerant filled in the refrigerant circuit 10 is mainly

circulated in order of the compressor 21, the outdoor heat exchanger 23, the outdoor expansion valve 24, and the indoor heat exchanger 31.

[1168] More specifically, when the cooling operation mode is started, refrigerant is taken into the compressor 21, compressed, and then discharged in the refrigerant circuit 10.

[1169] In the compressor 21, displacement control commensurate with a cooling load that is required from the indoor unit 30 is performed. Gas refrigerant discharged from the compressor 21 passes through the four-way valve 22 and flows into the gas-side end of the outdoor heat exchanger 23.

[1170] Gas refrigerant having flowed into the gas-side end of the outdoor heat exchanger 23 exchanges heat in the outdoor heat exchanger 23 with outdoor-side air that is supplied by the outdoor fan 25 to condense into liquid refrigerant and flows out from the liquid-side end of the outdoor heat exchanger 23.

[1171] Refrigerant having flowed out from the liquid-side end of the outdoor heat exchanger 23 is decompressed when passing through the outdoor expansion valve 24. The outdoor expansion valve 24 is controlled such that the degree of sub cooling of refrigerant that passes through a liquid-side outlet of the outdoor heat exchanger 23 satisfies a predetermined condition.

[1172] Refrigerant decompressed in the outdoor expansion valve 24 passes through the liquid-side stop valve 29 and the liquid-side connection pipe 6 and flows into the indoor unit 30.

[1173] Refrigerant having flowed into the indoor unit 30 flows into the indoor heat exchanger 31, exchanges heat in the indoor heat exchanger 31 with indoor air that is supplied by the indoor fan 32 to evaporate into gas refrigerant, and flows out from the gas-side end of the indoor heat exchanger 31. Gas refrigerant having flowed out from the gas-side end of the indoor heat exchanger 31 flows to the gas-side connection pipe 5.

[1174] Refrigerant having flowed through the gas-side connection pipe 5 passes through the gas-side stop valve 28 and the four-way valve 22, and is taken into the compressor 21 again.

[1175] (6-4-2) Heating Operation Mode

[1176] In the air conditioner 1, in the heating operation mode, the status of connection of the four-way valve 22 is set to the heating operation connection state where the discharge side of the compressor 21 and the gas-side stop valve 28 are connected and the suction side of the compressor 21 and the outdoor heat exchanger 23 are connected, and refrigerant filled in the refrigerant circuit 10 is mainly circulated in order of the compressor 21, the indoor heat exchanger 31, the outdoor expansion valve 24, and the outdoor heat exchanger 23.

[1177] More specifically, when the heating operation mode is started, refrigerant is taken into the compressor 21, compressed, and then discharged in the refrigerant circuit 10.

[1178] In the compressor 21, displacement control commensurate with a heating load that is required from the indoor unit 30 is performed. Here, for example, at least one of the drive frequency of the compressor 21 and the volume of air of the outdoor fan 25 is controlled such that the maximum value of the pressure in the refrigerant circuit 10 is lower than 1.5 times the design pressure of the gas-side connection pipe 5. Gas refrigerant discharged from the

compressor **21** flows through the four-way valve **22** and the gas-side connection pipe **5** and then flows into the indoor unit **30**.

[1179] Refrigerant having flowed into the indoor unit **30** flows into the gas-side end of the indoor heat exchanger **31**, exchanges heat in the indoor heat exchanger **31** with indoor air that is supplied by the indoor fan **32** to condense into refrigerant in a gas-liquid two-phase state or liquid refrigerant, and flows out from the liquid-side end of the indoor heat exchanger **31**. Refrigerant having flowed out from the liquid-side end of the indoor heat exchanger **31** flows into the liquid-side connection pipe **6**.

[1180] Refrigerant having flowed through the liquid-side connection pipe **6** is decompressed to a low pressure in the refrigeration cycle in the liquid-side stop valve **29** and the outdoor expansion valve **24**. The outdoor expansion valve **24** is controlled such that the degree of subcooling of refrigerant that passes through a liquid-side outlet of the indoor heat exchanger **31** satisfies a predetermined condition. Refrigerant decompressed in the outdoor expansion valve **24** flows into the liquid-side end of the outdoor heat exchanger **23**.

[1181] Refrigerant having flowed in from the liquid-side end of the outdoor heat exchanger **23** exchanges heat in the outdoor heat exchanger **23** with outdoor air that is supplied by the outdoor fan **25** to evaporate into gas refrigerant, and flows out from the gas-side end of the outdoor heat exchanger **23**.

[1182] Refrigerant having flowed out from the gas-side end of the outdoor heat exchanger **23** passes through the four-way valve **22** and is taken into the compressor **21** again.

(6-5) Characteristics of First Embodiment

[1183] In the above-described air conditioner **1**, since refrigerant containing 1,2-difluoroethylene is used, a GWP can be sufficiently reduced.

[1184] The air conditioner **1** uses the outdoor unit **20** of which the design pressure is lower than 1.5 times the design pressure of each of the liquid-side connection pipe **6** and the gas-side connection pipe **5**. In the outdoor unit control unit **27** of the outdoor unit **20** of the air conditioner **1**, the upper limit of the controlled pressure of the refrigerant is set so as to be lower than 1.5 times the design pressure of each of the liquid-side connection pipe **6** and the gas-side connection pipe **5**. Therefore, even when the above-described specific refrigerants A to E are used, damage to the liquid-side connection pipe **6** or the gas-side connection pipe **5** can be reduced.

(6-6) Modification A of First Embodiment

[1185] In the above-described first embodiment, the air conditioner including only one indoor unit is described as an example; however, the air conditioner may include a plurality of indoor units (with no indoor expansion valve) connected in parallel with each other.

(6-7) Modification B of First Embodiment

[1186] In the above-described first embodiment, the case where the design pressure of the outdoor unit **20** is lower than 1.5 times the design pressure of each of the liquid-side connection pipe **6** and the gas-side connection pipe **5** and the outdoor unit control unit **27** of the outdoor unit **20** is set such that the upper limit of the controlled pressure of the refrigerant

is lower than 1.5 times the design pressure of each of the liquid-side connection pipe **6** and the gas-side connection pipe **5** is described as an example.

[1187] In contrast to this, for example, even when the outdoor unit **20** has a design pressure higher than or equal to 1.5 times the design pressure of each of the liquid-side connection pipe **6** and the gas-side connection pipe **5** but the outdoor unit **20** includes the outdoor unit control unit **27** that is configured to be able to select the upper limit of the controlled pressure of the refrigerant from among multiple types and that is able to set the upper limit of the controlled pressure of the refrigerant such that the upper limit is lower than 1.5 times the design pressure of each of the liquid-side connection pipe **6** and the gas-side connection pipe **5**, the outdoor unit **20** can be used in the air conditioner **1** of the above-described embodiment.

(7) Second Embodiment

[1188] Hereinafter, an air conditioner **1a** that serves as a refrigeration cycle apparatus including the outdoor unit **20** as a heat source unit according to a second embodiment will be described with reference to FIG. **18** that is the schematic configuration diagram of a refrigerant circuit and FIG. **19** that is a schematic control block configuration diagram.

[1189] Hereinafter, mainly, the air conditioner **1a** of the second embodiment will be described with a focus on a portion different from the air conditioner **1** of the first embodiment.

[1190] In the air conditioner **1a** as well, the refrigerant circuit **10** is filled with a refrigerant mixture that contains 1,2-difluoroethylene and that is any one of the above-described refrigerants A to E as a refrigerant for performing a vapor compression refrigeration cycle. The refrigerant circuit **10** is filled with refrigerating machine oil together with the refrigerant.

(7-1) Outdoor Unit **20**

[1191] In the outdoor unit **20** of the air conditioner **1a** of the second embodiment, a first outdoor fan **25a** and a second outdoor fan **25b** are provided as the outdoor fans **25**. The outdoor heat exchanger **23** of the outdoor unit **20** of the air conditioner **1a** has a wide heat exchange area so as to adapt to air flow coming from the first outdoor fan **25a** and the second outdoor fan **25b**. The outdoor unit **20**, as in the case of the above-described first embodiment, has a design pressure (gauge pressure) that is lower than 1.5 times the design pressure of each of the liquid-side connection pipe **6** and the gas-side connection pipe **5** (the withstanding pressure of each of the liquid-side connection pipe **6** and the gas-side connection pipe **5**). The design pressure of the outdoor unit **20** may be, for example, higher than or equal to 4.0 MPa and lower than or equal to 4.5 MPa.

[1192] In the outdoor unit **20** of the air conditioner **1a**, instead of the outdoor expansion valve **24** of the outdoor unit **20** in the above-described first embodiment, a first outdoor expansion valve **44**, an intermediate pressure receiver **41**, and a second outdoor expansion valve **45** are sequentially provided between the liquid side of the outdoor heat exchanger **23** and the liquid-side stop valve **29**. The first outdoor expansion valve **44** and the second outdoor expansion valve **45** each are able to control the valve opening degree. The intermediate pressure receiver **41** is a container that is able to store refrigerant. Both an end portion of a pipe

extending from the first outdoor expansion valve **44** side and an end portion of a pipe extending from the second outdoor expansion valve **45** side are located in the internal space of the intermediate pressure receiver **41**. The internal volume of the intermediate pressure receiver **41** is greater than the internal volume of the attached accumulator attached to the compressor **21** and is preferably greater than or equal to twice.

[1193] The outdoor unit **20** of the second embodiment has substantially a rectangular parallelepiped shape and has a structure in which a fan chamber and a machine chamber are formed (so-called, trunk structure) when divided by a partition plate, or the like, extending vertically.

[1194] The outdoor heat exchanger **23** includes, for example, a plurality of heat transfer fins and a plurality of heat transfer tubes fixedly extending through the heat transfer fins. The outdoor heat exchanger **23** is disposed in an L-shape in plan view.

[1195] For the outdoor unit **20** of the second embodiment as well, in the outdoor unit control unit **27** (and the controller **7** including this unit), the upper limit of the controlled pressure (gauge pressure) of the refrigerant is set so as to be lower than 1.5 times the design pressure of each of the liquid-side connection pipe **6** and the gas-side connection pipe **5** (the withstanding pressure of each of the liquid-side connection pipe **6** and the gas-side connection pipe **5**).

[1196] In the above air conditioner **1a**, in the cooling operation mode, the first outdoor expansion valve **44** is, for example, controlled such that the degree of subcooling of refrigerant that passes through the liquid-side outlet of the outdoor heat exchanger **23** satisfies a predetermined condition. In the cooling operation mode, the second outdoor expansion valve **45** is, for example, controlled such that the degree of superheating of refrigerant that the compressor **21** takes in satisfies a predetermined condition. In the heating operation mode, for example, at least any one of the drive frequency of the compressor **21** and the volume of air of the outdoor fan **25** is controlled such that the maximum value of the pressure in the refrigerant circuit **10** is lower than 1.5 times the design pressure of the gas-side connection pipe **5**.

(7-2) Indoor Unit **30**

[1197] The indoor unit **30** of the second embodiment is placed so as to be suspended in an upper space in a room that is a space to be air-conditioned or placed at a ceiling surface or placed on a wall surface and used. The indoor unit **30** is connected to the outdoor unit **20** via the liquid-side connection pipe **6** and the gas-side connection pipe **5**, and makes up part of the refrigerant circuit **10**. The design pressure of the indoor unit **30**, as well as the outdoor unit **20**, may be, for example, higher than or equal to 4.0 MPa and lower than or equal to 4.5 MPa.

[1198] The indoor unit **30** includes the indoor heat exchanger **31**, the indoor fan **32**, and the like.

[1199] The indoor heat exchanger **31** of the second embodiment includes a plurality of heat transfer fins and a plurality of heat transfer tubes fixedly extending through the heat transfer fins.

(7-3) Characteristics of Second Embodiment

[1200] In the above-described air conditioner **1a** according to the second embodiment as well, as well as the air

conditioner **1** according to the first embodiment, since refrigerant containing 1,2-difluoroethylene is used, a GWP can be sufficiently reduced.

[1201] The air conditioner **1a** uses the outdoor unit **20** of which the design pressure is lower than 1.5 times the design pressure of each of the liquid-side connection pipe **6** and the gas-side connection pipe **5**. In the outdoor unit control unit **27** of the outdoor unit **20** of the air conditioner **1a**, the upper limit of the controlled pressure of the refrigerant is set so as to be lower than 1.5 times the design pressure of each of the liquid-side connection pipe **6** and the gas-side connection pipe **5**. Therefore, even when the above-described specific refrigerants A to E are used, damage to the liquid-side connection pipe **6** or the gas-side connection pipe **5** can be reduced.

(7-4) Modification A of Second Embodiment

[1202] In the above-described second embodiment, the air conditioner including only one indoor unit is described as an example; however, the air conditioner may include a plurality of indoor units (with no indoor expansion valve) connected in parallel with each other.

(7-5) Modification B of Second Embodiment

[1203] In the above-described second embodiment, the case where the design pressure of the outdoor unit **20** is lower than 1.5 times the design pressure of each of the liquid-side connection pipe **6** and the gas-side connection pipe **5** and the outdoor unit control unit **27** of the outdoor unit **20** is set such that the upper limit of the controlled pressure of the refrigerant is lower than 1.5 times the design pressure of each of the liquid-side connection pipe **6** and the gas-side connection pipe **5** is described as an example.

[1204] In contrast to this, for example, even when the outdoor unit **20** has a design pressure higher than or equal to 1.5 times the design pressure of each of the liquid-side connection pipe **6** and the gas-side connection pipe **5** but the outdoor unit **20** includes the outdoor unit control unit **27** that is configured to be able to select the upper limit of the controlled pressure of the refrigerant from among multiple types and that is able to set the upper limit of the controlled pressure of the refrigerant such that the upper limit is lower than 1.5 times the design pressure of each of the liquid-side connection pipe **6** and the gas-side connection pipe **5**, the outdoor unit **20** can be used in the air conditioner **1a** of the above-described embodiment.

(8) Third Embodiment

[1205] Hereinafter, an air conditioner **1b** that serves as a refrigeration cycle apparatus including the outdoor unit **20** as a heat source unit according to a third embodiment will be described with reference to FIG. **20** that is the schematic configuration diagram of a refrigerant circuit and FIG. **21** that is a schematic control block configuration diagram.

[1206] Hereinafter, mainly, the air conditioner **1b** of the third embodiment will be described with a focus on a portion different from the air conditioner **1** of the first embodiment.

[1207] In the air conditioner **1b** as well, the refrigerant circuit **10** is filled with a refrigerant that contains 1,2-difluoroethylene and that is any one of the above-described refrigerants A to E as a refrigerant for performing a vapor

compression refrigeration cycle. The refrigerant circuit **10** is filled with refrigerating machine oil together with the refrigerant.

(8-1) Outdoor Unit **20**

[1208] In the outdoor unit **20** of the air conditioner **1b** of the third embodiment, a low-pressure receiver **26**, a subcooling heat exchanger **47**, and a subcooling circuit **46** are provided in the outdoor unit **20** in the above-described first embodiment. Preferably, the outdoor unit **20**, as in the case of the above-described first embodiment, has a design pressure (gauge pressure) that is lower than 1.5 times the design pressure of each of the liquid-side connection pipe **6** and the gas-side connection pipe **5** (the withstanding pressure of each of the liquid-side connection pipe **6** and the gas-side connection pipe **5**) and that is lower than the design pressure of each of branch pipes **5a**, **5b**, **6a**, **6b** (described later) in the air conditioner **1b** of the present embodiment, including a plurality of indoor units **30**, **35**. The design pressure of the outdoor unit **20** may be, for example, higher than or equal to 4.0 MPa and lower than or equal to 4.5 MPa.

[1209] The low-pressure receiver **26** is a container that is provided between one of connection ports of the four-way valve **22** and the suction side of the compressor **21** and that is able to store refrigerant. In the present embodiment, the low-pressure receiver **26** is provided separately from the attached accumulator of the compressor **21**. The internal volume of the low-pressure receiver **26** is greater than the internal volume of the attached accumulator attached to the compressor **21** and is preferably greater than or equal to twice.

[1210] The subcooling heat exchanger **47** is provided between the outdoor expansion valve **24** and the liquid-side stop valve **29**.

[1211] The subcooling circuit **46** is a circuit that branches off from a main circuit between the outdoor expansion valve **24** and the subcooling heat exchanger **47** and that merges with a portion halfway from one of the connection ports of the four-way valve **22** to the low-pressure receiver **26**. A subcooling expansion valve **48** that decompresses refrigerant passing therethrough is provided halfway in the subcooling circuit **46**. Refrigerant flowing through the subcooling circuit **46** and decompressed by the subcooling expansion valve **48** exchanges heat with refrigerant flowing through the main circuit side in the subcooling heat exchanger **47**. Thus, refrigerant flowing through the main circuit side is further cooled, and refrigerant flowing through the subcooling circuit **46** evaporates.

[1212] The outdoor unit **20** of the air conditioner **1b** according to the third embodiment may have, for example, a so-called up-blow structure that takes in air from the lower side and discharges air outward from the upper side.

[1213] Preferably, for the outdoor unit **20** of the third embodiment as well, in the outdoor unit control unit **27** (and the controller **7** including this unit), the upper limit of the controlled pressure (gauge pressure) of the refrigerant is set so as to be lower than 1.5 times the design pressure of each of the liquid-side connection pipe **6** and the gas-side connection pipe **5** (the withstanding pressure of each of the liquid-side connection pipe **6** and the gas-side connection pipe **5**) and is set so as to be lower than the design pressure of each of the branch pipes **5a**, **5b**, **6a**, **6b** (described later) in the air conditioner **1b** of the present embodiment, including the plurality of indoor units **30**, **35**.

(8-2) First Indoor Unit **30** and Second Indoor Unit **35**

[1214] In the air conditioner **1b** according to the third embodiment, instead of the indoor unit **30** in the above-described first embodiment, a first indoor unit **30** and a second indoor unit **35** are provided in parallel with each other. The design pressures of the first indoor unit **30** and second indoor unit **35**, as well as the outdoor unit **20**, each may be, for example, higher than or equal to 4.0 MPa and lower than or equal to 4.5 MPa.

[1215] The first indoor unit **30**, as well as the indoor unit **30** in the above-described first embodiment, includes a first indoor heat exchanger **31**, a first indoor fan **32**, and a first indoor unit control unit **34**, and further includes a first indoor expansion valve **33** at the liquid side of the first indoor heat exchanger **31**. The first indoor expansion valve **33** is able to control the valve opening degree. The liquid side of the first indoor unit **30** is connected to the first liquid-side branch pipe **6a** that branches and extends from an indoor unit-side end portion of the liquid-side connection pipe **6**, and the gas side of the first indoor unit **30** is connected to the first gas-side branch pipe **5a** that branches and extends from an indoor unit-side end portion of the gas-side connection pipe **5**.

[1216] The second indoor unit **35**, as well as the first indoor unit **30**, includes a second indoor heat exchanger **36**, a second indoor fan **37**, a second indoor unit control unit **39**, and a second indoor expansion valve **38** provided at the liquid side of the second indoor heat exchanger **36**. The second indoor expansion valve **38** is able to control the valve opening degree. The liquid side of the second indoor unit **35** is connected to the second liquid-side branch pipe **6b** that branches and extends from the indoor unit-side end portion of the liquid-side connection pipe **6**, and the gas side of the second indoor unit **35** is connected to the second gas-side branch pipe **5b** that branches and extends from the indoor unit-side end portion of the gas-side connection pipe **5**.

[1217] The design pressures of the first liquid-side branch pipe **6a**, second liquid-side branch pipe **6b**, first gas-side branch pipe **5a**, and second gas-side branch pipe **5b** each may be set to, for example, 4.5 MPa.

[1218] The specific structures of the first indoor unit **30** and second indoor unit **35** of the air conditioner **1b** according to the third embodiment each have a similar configuration to the indoor unit **30** of the second embodiment except the above-described first indoor expansion valve **33** and second indoor expansion valve **38**.

[1219] The controller **7** of the third embodiment is made up of the outdoor unit control unit **27**, the first indoor unit control unit **34**, and the second indoor unit control unit **39** communicably connected to one another.

[1220] In the above air conditioner **1b**, in the cooling operation mode, the outdoor expansion valve **24** is controlled such that the degree of subcooling of refrigerant that passes through the liquid-side outlet of the outdoor heat exchanger **23** satisfies a predetermined condition. In the cooling operation mode, the subcooling expansion valve **48** is controlled such that the degree of superheating of refrigerant that the compressor **21** takes in satisfies a predetermined condition. In the cooling operation mode, the first indoor expansion valve **33** and the second indoor expansion valve **38** are controlled to a fully open state.

[1221] In the heating operation mode, the first indoor expansion valve **33** is controlled such that the degree of

subcooling of refrigerant that passes through the liquid-side outlet of the first indoor heat exchanger **31** satisfies a predetermined condition. Similarly, the second indoor expansion valve **38** is also controlled such that the degree of subcooling of refrigerant that passes through the liquid-side outlet of the second indoor heat exchanger **36** satisfies a predetermined condition. In the heating operation mode, the outdoor expansion valve **45** is controlled such that the degree of superheating of refrigerant that the compressor **21** takes in satisfies a predetermined condition. In the heating operation mode, the subcooling expansion valve **48** is controlled such that the degree of superheating of refrigerant that the compressor **21** takes in satisfies a predetermined condition. In the heating operation mode, for example, at least any one of the drive frequency of the compressor **21** and the volume of air of the outdoor fan **25** is controlled such that the maximum value of the pressure in the refrigerant circuit **10** is lower than 1.5 times the design pressure of the gas-side connection pipe **5**. Preferably, at least any one of the drive frequency of the compressor **21** and the volume of air of the outdoor fan **25** is controlled such that the maximum value of the pressure in the refrigerant circuit **10** is lower than the design pressure of each of the first gas-side branch pipe **5a** and the second gas-side branch pipe **5b**.

(8-3) Characteristics of Third Embodiment

[1222] In the above-described air conditioner **1b** according to the third embodiment as well, as well as the air conditioner **1** according to the first embodiment, since refrigerant containing 1,2-difluoroethylene is used, a GWP can be sufficiently reduced.

[1223] The air conditioner **1b** uses the outdoor unit **20** of which the design pressure is lower than 1.5 times the design pressure of each of the liquid-side connection pipe **6** and the gas-side connection pipe **5**. In the outdoor unit control unit **27** of the outdoor unit **20** of the air conditioner **1b**, the upper limit of the controlled pressure of the refrigerant is set so as to be lower than 1.5 times the design pressure of each of the liquid-side connection pipe **6** and the gas-side connection pipe **5**. Therefore, even when the above-described specific refrigerants A to E are used, damage to the liquid-side connection pipe **6** or the gas-side connection pipe **5** can be reduced.

(8-4) Modification A of Third Embodiment

[1224] In the above-described third embodiment, the case where the design pressure of the outdoor unit **20** is lower than 1.5 times the design pressure of each of the liquid-side connection pipe **6** and the gas-side connection pipe **5** and the outdoor unit control unit **27** of the outdoor unit **20** is set such that the upper limit of the controlled pressure of the refrigerant is lower than 1.5 times the design pressure of each of the liquid-side connection pipe **6** and the gas-side connection pipe **5** is described as an example.

[1225] In contrast to this, for example, even when the outdoor unit **20** has a design pressure higher than or equal to 1.5 times the design pressure of each of the liquid-side connection pipe **6** and the gas-side connection pipe **5** but the outdoor unit **20** includes the outdoor unit control unit **27** that is configured to be able to select the upper limit of the controlled pressure of the refrigerant from among multiple types and that is able to set the upper limit of the controlled pressure of the refrigerant such that the upper limit is lower

than 1.5 times the design pressure of each of the liquid-side connection pipe **6** and the gas-side connection pipe **5**, the outdoor unit **20** can be used in the air conditioner **1b** of the above-described embodiment.

(9) Fourth Embodiment

[1226] In the above-described first to third embodiments and their modifications, the new outdoor unit **20** and air conditioners **1**, **1a**, **1b** in which any one of the above-described refrigerants A to E is used are described as examples.

[1227] In contrast to this, an air conditioner according to a fourth embodiment, as will be described below, is an air conditioner modified from an air conditioner in which another refrigerant is used by replacing the refrigerant to be used with any one of the above-described refrigerants A to E while the liquid-side connection pipe **6** and the gas-side connection pipe **5** are reused.

(9-1) Modified Air Conditioner from R22

[1228] The air conditioners **1**, **1a**, **1b** in the above-described first to third embodiments and their modifications may be the air conditioners **1**, **1a**, **1b** having used R22 and modified so as to use any one of the refrigerants A to E containing 1,2-difluoroethylene.

[1229] Here, the design pressure of each of the liquid-side connection pipe **6** and the gas-side connection pipe **5** in an air conditioner in which refrigerant R22 (refrigerant having a lower design pressure than any one of the above-described refrigerants A to E) has been used is determined based on the outer diameter and thickness of pipes and the material of copper pipes from which the pipes are made. Of copper pipes that are generally used for such the liquid-side connection pipe **6** and the gas-side connection pipe **5**, a combination of the outer diameter, thickness, and material of the pipe, of which the design pressure is the lowest, is a combination of $\phi 19.05$, 1.0 mm in thickness, and O-material from Copper Pipes for General Refrigerant Piping (JIS B 8607), and the design pressure is 3.72 MPa (gauge pressure).

[1230] For this reason, in the outdoor unit **20** of each of the air conditioners **1**, **1a**, **1b** modified so as to use any one of the above-described refrigerants A to E, the heat transfer area of the outdoor heat exchanger **23** and the volume of air in the outdoor heat exchanger **23** (the amount of air that is sent by the outdoor fan **25**) are set such that the upper limit of the controlled pressure of the refrigerant is lower than or equal to 3.7 MPa (gauge pressure). Alternatively, in the outdoor unit control unit **27** of the outdoor unit **20** of each of the air conditioners **1**, **1a**, **1b** modified so as to use any one of the above-described refrigerants A to E, the upper limit of the controlled pressure of the refrigerant is set so as to be lower than or equal to 3.7 MPa (gauge pressure). Thus, the outdoor unit control unit **27** adjusts the amount of circulating refrigerant by controlling the operating frequency of the compressor **21** and adjusts the volume of air of the outdoor fan **25** in the outdoor heat exchanger **23**.

[1231] As described above, the liquid-side connection pipe **6** and gas-side connection pipe **5** that have been used in an air conditioner (old machine) in which refrigerant R22 has been used can be reused when the air conditioners (new machines) **1**, **1a**, **1b** modified so as to use any one of the above-described refrigerants A to E are introduced, and, in

that case, damage to the liquid-side connection pipe **6** or the gas-side connection pipe **5** can be reduced.

[1232] In this case, preferably, the design pressure of the outdoor unit **20** of each of the air conditioners **1**, **1a**, **1b** modified so as to use any one of the refrigerants A to E is equivalent to the design pressure of an outdoor unit in an air conditioner in which R22 has been used, and is specifically higher than or equal to 3.0 MPa and lower than or equal to 3.7 MPa. An outdoor unit and indoor unit of the air conditioner in which R22 has been used may be reused or may be replaced with new ones.

[1233] When a new one is used for the outdoor unit **20**, the new one has a design pressure or an upper limit of a controlled pressure of the refrigerant, which is equivalent to the design pressure of the outdoor unit of the air conditioner in which R22 has been used or an upper limit of a controlled pressure of the refrigerant. For example, in the case where the design pressure of the outdoor unit of the air conditioner in which R22 has been used or the upper limit of the controlled pressure of the refrigerant is 3.0 MPa, even when the new outdoor unit **20** has a design pressure equivalent to 3.0 MPa or a further higher design pressure (the one that has a design pressure higher than or equal to 4.0 MPa and lower than or equal to 4.5 MPa and that can be connected to the liquid-side connection pipe **6** and the gas-side connection pipe **5** that are used for any one of the refrigerants A to E), the upper limit of the controlled pressure of the refrigerant is preferably set so as to be equivalent to 3.0 MPa.

[1234] For the air conditioner in which the plurality of indoor units **30**, **35** is connected via the branch pipes such as the first liquid-side branch pipe **6a**, the second liquid-side branch pipe **6b**, the first gas-side branch pipe **5a**, and the second gas-side branch pipe **5b** as described in the third embodiment, the design pressure of each of these branch pipes when R22 is used as a refrigerant is set to 3.4 MPa that is further lower than 3.7 MPa. Therefore, for the air conditioner **1b** that includes the plurality of indoor units **30**, **35** and in which a refrigerant to be used is replaced from R22 to any one of the above-described refrigerants A to E, preferably, the outdoor unit **20** having a design pressure lower than or equal to 3.4 MPa is used or the upper limit of the controlled pressure of the refrigerant is set by the outdoor unit control unit **27** of the outdoor unit **20** so as to be lower than or equal to 3.4 MPa in order for the pressure of refrigerant flowing through the branch pipes not to exceed 3.4 MPa.

(9-2) Modified Air Conditioner from R407C

[1235] The air conditioners **1**, **1a**, **1b** in the above-described first to third embodiments and their modifications may be the air conditioners **1**, **1a**, **1b** having used R407C and modified so as to use any one of the refrigerants A to E containing 1,2-difluoroethylene.

[1236] Here, the design pressure of each of the liquid-side connection pipe **6** and the gas-side connection pipe **5** in an air conditioner in which refrigerant R407C (refrigerant having a lower design pressure than any one of the above-described refrigerants A to E) has been used is similar to the case where R22 has been used, and the design pressure of pipes having the lowest design pressure for the liquid-side connection pipe **6** and the gas-side connection pipe **5** is 3.72 MPa (gauge pressure).

[1237] For this reason, in the outdoor unit **20** of each of the air conditioners **1**, **1a**, **1b** modified so as to use any one of

the above-described refrigerants A to E, as in the case of the modification from R22, the heat transfer area of the outdoor heat exchanger **23** and the volume of air in the outdoor heat exchanger **23** (the amount of air that is sent by the outdoor fan **25**) are set such that the upper limit of the controlled pressure of the refrigerant is lower than or equal to 3.7 MPa (gauge pressure). Alternatively, in the outdoor unit control unit **27** of the outdoor unit **20** of each of the air conditioners **1**, **1a**, **1b** modified so as to use any one of the above-described refrigerants A to E, the upper limit of the controlled pressure of the refrigerant is set so as to be lower than or equal to 3.7 MPa (gauge pressure). Thus, the outdoor unit control unit **27** adjusts the amount of circulating refrigerant by controlling the operating frequency of the compressor **21** and adjusts the volume of air of the outdoor fan **25** in the outdoor heat exchanger **23**.

[1238] As described above, the liquid-side connection pipe **6** and gas-side connection pipe **5** that have been used in an air conditioner (old machine) in which refrigerant R407C has been used can be reused when the air conditioners (new machines) **1**, **1a**, **1b** modified so as to use any one of the above-described refrigerants A to E are introduced, and, in that case, damage to the liquid-side connection pipe **6** or the gas-side connection pipe **5** can be reduced.

[1239] In this case, preferably, the design pressure of the outdoor unit **20** of each of the air conditioners **1**, **1a**, **1b** modified so as to use any one of the refrigerants A to E is equivalent to the design pressure of an outdoor unit in an air conditioner in which R407C has been used, and is specifically higher than or equal to 3.0 MPa and lower than or equal to 3.7 MPa. An outdoor unit and indoor unit of the air conditioner in which R407C has been used may be reused or may be replaced with new ones.

[1240] When a new one is used for the outdoor unit **20**, the new one has a design pressure or an upper limit of a controlled pressure of the refrigerant, which is equivalent to the design pressure of the outdoor unit of the air conditioner in which R407C has been used or an upper limit of a controlled pressure of the refrigerant. For example, in the case where the design pressure of the outdoor unit of the air conditioner in which R407C has been used or the upper limit of the controlled pressure of the refrigerant is 3.0 MPa, even when the new outdoor unit **20** has a design pressure equivalent to 3.0 MPa or a further higher design pressure (the one that has a design pressure higher than or equal to 4.0 MPa and lower than or equal to 4.5 MPa and that can be connected to the liquid-side connection pipe **6** and the gas-side connection pipe **5** that are used for any one of the refrigerants A to E), the upper limit of the controlled pressure of the refrigerant is preferably set so as to be equivalent to 3.0 MPa.

[1241] For the air conditioner in which the plurality of indoor units **30**, **35** is connected via the branch pipes such as the first liquid-side branch pipe **6a**, the second liquid-side branch pipe **6b**, the first gas-side branch pipe **5a**, and the second gas-side branch pipe **5b** as described in the third embodiment, the design pressure of each of these branch pipes when R407C is used as a refrigerant is set to 3.4 MPa, as in the case of R22, that is further lower than 3.7 MPa. Therefore, for the air conditioner **1b** that includes the plurality of indoor units **30**, **35** and in which a refrigerant to be used is replaced from R407C to any one of the above-described refrigerants A to E, preferably, the outdoor unit **20** having a design pressure lower than or equal to 3.4 MPa is

used or the upper limit of the controlled pressure of the refrigerant is set by the outdoor unit control unit **27** of the outdoor unit **20** so as to be lower than or equal to 3.4 MPa in order for the pressure of refrigerant flowing through the branch pipes not to exceed 3.4 MPa.

(9-3) Modified Air Conditioner from R410A

[1242] The air conditioners **1**, **1a**, **1b** in the above-described first to third embodiments and their modifications may be the air conditioners **1**, **1a**, **1b** having used R410A and modified so as to use any one of the refrigerants A to E containing 1,2-difluoroethylene.

[1243] Here, the design pressure of each of the liquid-side connection pipe **6** and the gas-side connection pipe **5** in an air conditioner in which refrigerant R410A (refrigerant having a design pressure substantially equivalent to that of any one of the above-described refrigerants A to E) has been used is set to 4.3 MPa (gauge pressure) for pipes having an outer diameter of $\frac{3}{8}$ inches and 4.8 MPa (gauge pressure) for pipes having an outer diameter of $\frac{1}{2}$ inches.

[1244] For this reason, in the outdoor unit **20** of each of the air conditioners **1**, **1a**, **1b** modified so as to use any one of the above-described refrigerants A to E, the heat transfer area of the outdoor heat exchanger **23** and the volume of air in the outdoor heat exchanger **23** (the amount of air that is sent by the outdoor fan **25**) are set such that the upper limit of the controlled pressure of the refrigerant is lower than or equal to 4.3 MPa for the case where connection pipes having an outer diameter of $\frac{3}{8}$ inches are used or is lower than or equal to 4.8 MPa for the case where connection pipes having an outer diameter of $\frac{1}{2}$ inches are used. Alternatively, in the outdoor unit control unit **27** of the outdoor unit **20** of each of the air conditioners **1**, **1a**, **1b** modified so as to use any one of the above-described refrigerants A to E, the upper limit of the controlled pressure of the refrigerant is set so as to be lower than or equal to 4.3 MPa for the case where connection pipes having an outer diameter of $\frac{3}{8}$ inches are used or so as to be lower than or equal to 4.8 MPa for the case where connection pipes having an outer diameter of $\frac{1}{2}$ inches are used. Thus, the outdoor unit control unit **27** adjusts the amount of circulating refrigerant by controlling the operating frequency of the compressor **21** and adjusts the volume of air of the outdoor fan **25** in the outdoor heat exchanger **23**.

[1245] As described above, the liquid-side connection pipe **6** and gas-side connection pipe **5** that have been used in an air conditioner (old machine) in which refrigerant R410A has been used can be reused when the air conditioners (new machines) **1**, **1a**, **1b** modified so as to use any one of the above-described refrigerants A to E are introduced, and, in that case, damage to the liquid-side connection pipe **6** or the gas-side connection pipe **5** can be reduced.

[1246] In this case, preferably, the design pressure of the outdoor unit **20** of each of the air conditioners **1**, **1a**, **1b** modified so as to use any one of the refrigerants A to E is equivalent to the design pressure of an outdoor unit in an air conditioner in which R410A has been used, and is specifically higher than or equal to 4.0 MPa and lower than or equal to 4.8 MPa. An outdoor unit and indoor unit of the air conditioner in which R410A has been used may be reused or may be replaced with new ones.

[1247] When a new one is used for the outdoor unit **20**, the new one has a design pressure or an upper limit of a controlled pressure of the refrigerant, which is equivalent to the design pressure of the outdoor unit of the air conditioner

in which R410A has been used or an upper limit of a controlled pressure of the refrigerant. For example, in the case where the design pressure of the outdoor unit of the air conditioner in which R410A has been used or the upper limit of the controlled pressure of the refrigerant is 4.2 MPa, even when the new outdoor unit **20** has a design pressure equivalent to 4.2 MPa or a further higher design pressure (the one that has a design pressure higher than or equal to 4.2 MPa and lower than or equal to 4.5 MPa and that can be connected to the liquid-side connection pipe **6** and the gas-side connection pipe **5** that are used for any one of the refrigerants A to E), the upper limit of the controlled pressure of the refrigerant is preferably set so as to be equivalent to 4.2 MPa.

[1248] For the air conditioner in which the plurality of indoor units **30**, **35** is connected via the branch pipes such as the first liquid-side branch pipe **6a**, the second liquid-side branch pipe **6b**, the first gas-side branch pipe **5a**, and the second gas-side branch pipe **5b** as described in the third embodiment, the design pressure of each of these branch pipes when R410A is used as a refrigerant is set to 4.2 MPa that is further lower than 4.8 MPa. Therefore, for the air conditioner **1b** that includes the plurality of indoor units **30**, **35** and in which a refrigerant to be used is replaced from R410A to any one of the above-described refrigerants A to E, preferably, the outdoor unit **20** having a design pressure lower than or equal to 4.2 MPa is used or the upper limit of the controlled pressure of the refrigerant is set by the outdoor unit control unit **27** of the outdoor unit **20** so as to be lower than or equal to 4.2 MPa in order for the pressure of refrigerant flowing through the branch pipes not to exceed 4.2 MPa.

(9-4) Modified Air Conditioner from R32

[1249] The air conditioners **1**, **1a**, **1b** in the above-described first to third embodiments and their modifications may be the air conditioners **1**, **1a**, **1b** having used R32 and modified so as to use any one of the refrigerants A to E containing 1,2-difluoroethylene.

[1250] Here, the design pressure of each of the liquid-side connection pipe **6** and the gas-side connection pipe **5** in an air conditioner in which refrigerant R32 (refrigerant having a design pressure substantially equivalent to that of any one of the above-described refrigerants A to E) has been used is set to 4.3 MPa (gauge pressure) for pipes having an outer diameter of $\frac{3}{8}$ inches and 4.8 MPa (gauge pressure) for pipes having an outer diameter of $\frac{1}{2}$ inches.

[1251] For this reason, in the outdoor unit **20** of each of the air conditioners **1**, **1a**, **1b** modified so as to use any one of the above-described refrigerants A to E, the heat transfer area of the outdoor heat exchanger **23** and the volume of air in the outdoor heat exchanger **23** (the amount of air that is sent by the outdoor fan **25**) are set such that the upper limit of the controlled pressure of the refrigerant is lower than or equal to 4.3 MPa for the case where connection pipes having an outer diameter of $\frac{3}{8}$ inches are used or is lower than or equal to 4.8 MPa for the case where connection pipes having an outer diameter of $\frac{1}{2}$ inches are used. Alternatively, in the outdoor unit control unit **27** of the outdoor unit **20** of each of the air conditioners **1**, **1a**, **1b** modified so as to use any one of the above-described refrigerants A to E, the upper limit of the controlled pressure of the refrigerant is set so as to be lower than or equal to 4.3 MPa for the case where connection pipes having an outer diameter of $\frac{3}{8}$ inches are used or

so as to be lower than or equal to 4.8 MPa for the case where connection pipes having an outer diameter of 1/2 inches are used. Thus, the outdoor unit control unit **27** adjusts the amount of circulating refrigerant by controlling the operating frequency of the compressor **21** and adjusts the volume of air of the outdoor fan **25** in the outdoor heat exchanger **23**.

[1252] As described above, the liquid-side connection pipe **6** and gas-side connection pipe **5** that have been used in an air conditioner (old machine) in which refrigerant R32 has been used can be reused when the air conditioners (new machines) **1**, **1a**, **1b** modified so as to use any one of the above-described refrigerants A to E are introduced, and, in that case, damage to the liquid-side connection pipe **6** or the gas-side connection pipe **5** can be reduced.

[1253] In this case, preferably, the design pressure of the outdoor unit **20** of each of the air conditioners **1**, **1a**, **1b** modified so as to use any one of the refrigerants A to E is equivalent to the design pressure of an outdoor unit in an air conditioner in which R32 has been used, and is specifically higher than or equal to 4.0 MPa and lower than or equal to 4.8 MPa. An outdoor unit and indoor unit of the air conditioner in which R32 has been used may be reused or may be replaced with new ones.

[1254] When a new one is used for the outdoor unit **20**, the new one has a design pressure or an upper limit of a controlled pressure of the refrigerant, which is equivalent to the design pressure of the outdoor unit of the air conditioner in which R32 has been used or an upper limit of a controlled pressure of the refrigerant. For example, in the case where the design pressure of the outdoor unit of the air conditioner in which R32 has been used or the upper limit of the controlled pressure of the refrigerant is 4.2 MPa, even when the new outdoor unit **20** has a design pressure equivalent to 4.2 MPa or a further higher design pressure (the one that has a design pressure higher than or equal to 4.2 MPa and lower than or equal to 4.5 MPa and that can be connected to the liquid-side connection pipe **6** and the gas-side connection pipe **5** that are used for any one of the refrigerants A to E), the upper limit of the controlled pressure of the refrigerant is preferably set so as to be equivalent to 4.2 MPa.

[1255] For the air conditioner in which the plurality of indoor units **30**, **35** is connected via the branch pipes such as the first liquid-side branch pipe **6a**, the second liquid-side branch pipe **6b**, the first gas-side branch pipe **5a**, and the second gas-side branch pipe **5b** as described in the third embodiment, the design pressure of each of these branch pipes when R32 is used as a refrigerant is set to 4.2 MPa that is further lower than 4.8 MPa. Therefore, for the air conditioner **1**, **1a**, **1b** that includes the plurality of indoor units **30**, **35** and in which a refrigerant to be used is replaced from R32 to any one of the above-described refrigerants A to E, preferably, the outdoor unit **20** having a design pressure lower than or equal to 4.2 MPa is used or the upper limit of the controlled pressure of the refrigerant is set by the outdoor unit control unit **27** of the outdoor unit **20** so as to be lower than or equal to 4.2 MPa in order for the pressure of refrigerant flowing through the branch pipes not to exceed 4.2 MPa.

[1256] The embodiments of the present disclosure are described above; however, it is understood that various modifications of modes and details are applicable without departing from the purport or scope of the present disclosure recited in the claims.

REFERENCE SIGNS LIST

- [1257] **1**, **1a**, **1b** air conditioner (refrigeration cycle apparatus)
- [1258] **5** gas-side connection pipe (connection pipe)
- [1259] **6** liquid-side connection pipe (connection pipe)
- [1260] **7** controller (control device)
- [1261] **10** refrigerant circuit
- [1262] **20** outdoor unit (heat source unit)
- [1263] **21** compressor
- [1264] **27** outdoor unit control unit (control device)
- [1265] **23** outdoor heat exchanger (heat source-side heat exchanger)
- [1266] **30** indoor unit, first indoor unit (service unit)
- [1267] **31** indoor heat exchanger, first indoor heat exchanger (service-side heat exchanger)
- [1268] **35** second indoor unit (service unit)
- [1269] **36** second indoor heat exchanger (service-side heat exchanger)

CITATION LIST

Patent Literature

- [1270] PTL 1 International Publication No. 2015/141678
 1. A heat source unit that is connected via a connection pipe to a service unit including a service-side heat exchanger and that is a component of a refrigeration cycle apparatus, the heat source unit comprising:
 - a compressor; and
 - a heat source-side heat exchanger, wherein
 - a refrigerant containing at least 1,2-difluoroethylene is used as a refrigerant, and
 - a design pressure of the heat source unit is lower than 1.5 times a design pressure of the connection pipe.
 2. A refrigeration cycle apparatus comprising the service unit, the connection pipe, and the heat source unit according to claim 1, wherein
 - a refrigerant that is used in the refrigeration cycle apparatus is a refrigerant containing at least 1,2-difluoroethylene, and
 - the design pressure of the heat source unit is equivalent to a design pressure in a refrigeration cycle apparatus in which refrigerant R22 or refrigerant R407C is used.
 3. The refrigeration cycle apparatus according to claim 2, wherein
 - the design pressure of the heat source unit is higher than or equal to 3.0 MPa and lower than or equal to 3.7 MPa.
 4. A refrigeration cycle apparatus comprising the service unit, the connection pipe, and the heat source unit according to claim 1, wherein
 - a refrigerant that is used in the refrigeration cycle apparatus is a refrigerant containing at least 1,2-difluoroethylene, and
 - the design pressure of the heat source unit is equivalent to a design pressure in a refrigeration cycle apparatus in which refrigerant R410A or refrigerant R32 is used.
 5. The refrigeration cycle apparatus according to claim 4, wherein
 - the design pressure of the heat source unit is higher than or equal to 4.0 MPa and lower than or equal to 4.8 MPa.
 6. A refrigeration cycle apparatus comprising:
 - a heat source unit including a compressor and a heat source-side heat exchanger; a service unit including a service-side heat exchanger; and

- a connection pipe connecting the heat source unit and the service unit, wherein
- a refrigerant that is used is a refrigerant containing at least 1,2-difluoroethylene, and
- the design pressure of the heat source unit is equivalent to a design pressure in a refrigeration cycle apparatus in which refrigerant R22 or refrigerant R407C is used.
- 7.** The refrigeration cycle apparatus according to claim **6**, wherein
- the design pressure of the heat source unit is higher than or equal to 3.0 MPa and lower than or equal to 3.7 MPa.
- 8.** A refrigeration cycle apparatus comprising:
- a heat source unit including a compressor and a heat source-side heat exchanger; a service unit including a service-side heat exchanger; and
- a connection pipe connecting the heat source unit and the service unit, wherein
- a refrigerant that is used is a refrigerant containing at least 1,2-difluoroethylene, and
- the design pressure of the heat source unit is equivalent to a design pressure in a refrigeration cycle apparatus in which refrigerant R410A or refrigerant R32 is used.
- 9.** The refrigeration cycle apparatus according to claim **8**, wherein
- the design pressure of the heat source unit is higher than or equal to 4.0 MPa and lower than or equal to 4.8 MPa.
- 10.** A heat source unit that is connected via a connection pipe to a service unit including a service-side heat exchanger and that is a component of a refrigeration cycle apparatus, the heat source unit comprising:
- a compressor;
- a heat source-side heat exchanger; and
- a control device, wherein
- a refrigerant containing at least 1,2-difluoroethylene is used as a refrigerant, and
- the control device is configured to set or be able to set an upper limit of a controlled pressure of the refrigerant such that the upper limit is lower than 1.5 times a design pressure of the connection pipe.
- 11.** A refrigeration cycle apparatus comprising the service unit, the connection pipe, and the heat source unit according to claim **10**, wherein
- a refrigerant that is used in the refrigeration cycle apparatus is a refrigerant containing at least 1,2-difluoroethylene, and
- the control device is configured to set or be able to set an upper limit of a controlled pressure of the refrigerant such that the upper limit is equivalent to an upper limit of a controlled pressure in a refrigeration cycle apparatus in which refrigerant R22 or refrigerant R407C is used.
- 12.** The refrigeration cycle apparatus according to claim **11**, wherein
- the upper limit of the controlled pressure is set to be higher than or equal to 3.0 MPa and lower than or equal to 3.7 MPa.
- 13.** A refrigeration cycle apparatus comprising the service unit, the connection pipe, and the heat source unit according to claim **10**, wherein
- a refrigerant that is used in the refrigeration cycle apparatus is a refrigerant containing at least 1,2-difluoroethylene, and
- the control device is configured to set or be able to set an upper limit of a controlled pressure of the refrigerant such that the upper limit is equivalent to an upper limit of a controlled pressure in a refrigeration cycle apparatus in which refrigerant R410A or refrigerant R32 is used.
- 14.** The refrigeration cycle apparatus according to claim **13**, wherein
- the upper limit of the controlled pressure is set to be higher than or equal to 4.0 MPa and lower than or equal to 4.8 MPa.
- 15.** A refrigeration cycle apparatus comprising:
- a heat source unit including a compressor and a heat source-side heat exchanger;
- a service unit including a service-side heat exchanger;
- a connection pipe connecting the heat source unit and the service unit; and
- a control device, wherein
- a refrigerant that is used is a refrigerant containing at least 1,2-difluoroethylene, and
- the control device is configured to set or be able to set an upper limit of a controlled pressure of the refrigerant such that the upper limit is equivalent to an upper limit of a controlled pressure in a refrigeration cycle apparatus in which refrigerant R22 or refrigerant R407C is used.
- 16.** The refrigeration cycle apparatus according to claim **15**, wherein
- the upper limit of the controlled pressure is set to be higher than or equal to 3.0 MPa and lower than or equal to 3.7 MPa.
- 17.** A refrigeration cycle apparatus comprising:
- a heat source unit including a compressor and a heat source-side heat exchanger;
- a service unit including a service-side heat exchanger;
- a connection pipe connecting the heat source unit and the service unit; and
- a control device, wherein
- a refrigerant that is used is a refrigerant containing at least 1,2-difluoroethylene, and
- the control device is configured to set or be able to set an upper limit of a controlled pressure of the refrigerant such that the upper limit is equivalent to an upper limit of a controlled pressure in a refrigeration cycle apparatus in which refrigerant R410A or refrigerant R32 is used.
- 18.** The refrigeration cycle apparatus according to claim **17**, wherein
- the upper limit of the controlled pressure is set to be higher than or equal to 4.0 MPa and lower than or equal to 4.8 MPa.
- 19.** The refrigeration cycle apparatus according to claim **2**, wherein
- the refrigerant comprises trans-1,2-difluoroethylene (HFO-1132(E)), trifluoroethylene (HFO-1123), and 2,3,3,3-tetrafluoro-1-propene (R1234yf).
- 20.** The refrigeration cycle apparatus according to claim **19**, wherein
- when the mass % of HFO-1132(E), HFO-1123, and R1234yf based on their sum in the refrigerant is respectively represented by x, y, and z, coordinates (x,y,z) in a ternary composition diagram in which the sum of HFO-1132(E), HFO-1123, and R1234yf is 100 mass % are within the range of a figure surrounded by line

segments AA', A'B, BD, DC', C'C, CO, and OA that connect the following 7 points:
 point A (68.6, 0.0, 31.4),
 point A' (30.6, 30.0, 39.4),
 point B (0.0, 58.7, 41.3),
 point D (0.0, 80.4, 19.6),
 point C' (19.5, 70.5, 10.0),
 point C (32.9, 67.1, 0.0), and
 point O (100.0, 0.0, 0.0),
 or on the above line segments (excluding the points on the line segments BD, CO, and OA);
 the line segment AA' is represented by coordinates $(x, 0.0016x^2 - 0.9473x + 57.497, -0.0016x^2 - 0.0527x + 42.503)$,
 the line segment A'B is represented by coordinates $(x, 0.0029x^2 - 1.0268x + 58.7, -0.0029x^2 + 0.0268x + 41.3)$,
 the line segment DC' is represented by coordinates $(x, 0.0082x^2 - 0.6671x + 80.4, -0.0082x^2 - 0.3329x + 19.6)$,
 the line segment C'C is represented by coordinates $(x, 0.0067x^2 - 0.6034x + 79.729, -0.0067x^2 - 0.3966x + 20.271)$, and
 the line segments BD, CO, and OA are straight lines.

21. The refrigeration cycle apparatus according to claim 19,

wherein

when the mass % of HFO-1132(E), HFO-1123, and R1234yf based on their sum in the refrigerant is respectively represented by x, y, and z, coordinates (x,y,z) in a ternary composition diagram in which the sum of HFO-1132(E), HFO-1123, and R1234yf is 100 mass % are within the range of a figure surrounded by line segments GI, IA, AA', A'B, BD, DC', C'C,

and CG that connect the following 8 points:

point G (72.0, 28.0, 0.0),
 point I (72.0, 0.0, 28.0),
 point A (68.6, 0.0, 31.4),
 point A' (30.6, 30.0, 39.4),
 point B (0.0, 58.7, 41.3),
 point D (0.0, 80.4, 19.6),
 point C' (19.5, 70.5, 10.0), and
 point C (32.9, 67.1, 0.0),

or on the above line segments (excluding the points on the line segments IA, BD, and CG);

the line segment AA' is represented by coordinates $(x, 0.0016x^2 - 0.9473x + 57.497, -0.0016x^2 - 0.0527x + 42.503)$,

the line segment A'B is represented by coordinates $(x, 0.0029x^2 - 1.0268x + 58.7, -0.0029x^2 + 0.0268x + 41.3)$,

the line segment DC' is represented by coordinates $(x, 0.0082x^2 - 0.6671x + 80.4, -0.0082x^2 - 0.3329x + 19.6)$,

the line segment C'C is represented by coordinates $(x, 0.0067x^2 - 0.6034x + 79.729, -0.0067x^2 - 0.3966x + 20.271)$, and

the line segments GI, IA, BD, and CG are straight lines.

22. The refrigeration cycle apparatus according to claim 19,

wherein

when the mass % of HFO-1132(E), HFO-1123, and R1234yf based on their sum in the refrigerant is respectively represented by x, y, and z, coordinates (x,y,z) in a ternary composition diagram in which the sum of HFO-1132(E), HFO-1123, and R1234yf is 100 mass % are within the range of a figure surrounded by line

segments JP, PN, NK, KA', A'B, BD, DC', C'C, and CJ that connect the following 9 points:

point J (47.1, 52.9, 0.0),
 point P (55.8, 42.0, 2.2),
 point N (68.6, 16.3, 15.1),
 point K (61.3, 5.4, 33.3),
 point A' (30.6, 30.0, 39.4),
 point B (0.0, 58.7, 41.3),
 point D (0.0, 80.4, 19.6),
 point C' (19.5, 70.5, 10.0), and
 point C (32.9, 67.1, 0.0),

or on the above line segments (excluding the points on the line segments BD and CJ);

the line segment PN is represented by coordinates $(x, -0.1135x^2 + 12.112x - 280.43, 0.1135x^2 - 13.112x + 380.43)$,

the line segment NK is represented by coordinates $(x, 0.2421x^2 - 29.955x + 931.91, -0.2421x^2 + 28.955x - 831.91)$,

the line segment KA' is represented by coordinates $(x, 0.0016x^2 - 0.9473x + 57.497, -0.0016x^2 - 0.0527x + 42.503)$,

the line segment A'B is represented by coordinates $(x, 0.0029x^2 - 1.0268x + 58.7, -0.0029x^2 + 0.0268x + 41.3)$,

the line segment DC' is represented by coordinates $(x, 0.0082x^2 - 0.6671x + 80.4, -0.0082x^2 - 0.3329x + 19.6)$,

the line segment C'C is represented by coordinates $(x, 0.0067x^2 - 0.6034x + 79.729, -0.0067x^2 - 0.3966x + 20.271)$, and

the line segments JP, BD, and CG are straight lines.

23. The refrigeration cycle apparatus according to claim 19,

wherein

when the mass % of HFO-1132(E), HFO-1123, and R1234yf based on their sum in the refrigerant is respectively represented by x, y, and z, coordinates (x,y,z) in a ternary composition diagram in which the sum of HFO-1132(E), HFO-1123, and R1234yf is 100 mass % are within the range of a figure surrounded by line segments JP, PL, LM, MA', A'B, BD, DC', C'C, and CJ that connect the following 9 points:

point J (47.1, 52.9, 0.0),
 point P (55.8, 42.0, 2.2),
 point L (63.1, 31.9, 5.0),
 point M (60.3, 6.2, 33.5),
 point A' (30.6, 30.0, 39.4),
 point B (0.0, 58.7, 41.3),
 point D (0.0, 80.4, 19.6),
 point C' (19.5, 70.5, 10.0), and
 point C (32.9, 67.1, 0.0),

or on the above line segments (excluding the points on the line segments BD and CJ);

the line segment PL is represented by coordinates $(x, -0.1135x^2 + 12.112x - 280.43, 0.1135x^2 - 13.112x + 380.43)$

the line segment MA' is represented by coordinates $(x, 0.0016x^2 - 0.9473x + 57.497, -0.0016x^2 - 0.0527x + 42.503)$,

the line segment A'B is represented by coordinates $(x, 0.0029x^2 - 1.0268x + 58.7, -0.0029x^2 + 0.0268x + 41.3)$,

the line segment DC' is represented by coordinates $(x, 0.0082x^2 - 0.6671x + 80.4, -0.0082x^2 - 0.3329x + 19.6)$,

the line segment C'C is represented by coordinates $(x, 0.0067x^2 - 0.6034x + 79.729, -0.0067x^2 - 0.3966x + 20.271)$, and

the line segments JP, LM, BD, and CG are straight lines.

24. The refrigeration cycle apparatus according to claim 19,

wherein

when the mass % of HFO-1132(E), HFO-1123, and R1234yf based on their sum in the refrigerant is respectively represented by x , y , and z , coordinates (x,y,z) in a ternary composition diagram in which the sum of HFO-1132(E), HFO-1123, and R1234yf is 100 mass % are within the range of a figure surrounded by line segments PL, LM, MA', A'B, BF, FT, and TP that connect the following 7 points:

point P (55.8, 42.0, 2.2),

point L (63.1, 31.9, 5.0),

point M (60.3, 6.2, 33.5),

point A' (30.6, 30.0, 39.4),

point B (0.0, 58.7, 41.3),

point F (0.0, 61.8, 38.2), and

point T (35.8, 44.9, 19.3),

or on the above line segments (excluding the points on the line segment BF);

the line segment PL is represented by coordinates $(x, -0.1135x^2 + 12.112x - 280.43, 0.1135x^2 - 13.112x + 380.43)$,

the line segment MA' is represented by coordinates $(x, 0.0016x^2 - 0.9473x + 57.497, -0.0016x^2 - 0.0527x + 42.503)$,

the line segment A'B is represented by coordinates $(x, 0.0029x^2 - 1.0268x + 58.7, -0.0029x^2 + 0.0268x + 41.3)$,

the line segment FT is represented by coordinates $(x, 0.0078x^2 - 0.7501x + 61.8, -0.0078x^2 - 0.2499x + 38.2)$,

the line segment TP is represented by coordinates $(x, 0.00672x^2 - 0.7607x + 63.525, -0.00672x^2 - 0.2393x + 36.475)$, and

the line segments LM and BF are straight lines.

25. The refrigeration cycle apparatus according to claim 19,

wherein

when the mass % of HFO-1132(E), HFO-1123, and R1234yf based on their sum in the refrigerant is respectively represented by x , y , and z , coordinates (x,y,z) in a ternary composition diagram in which the sum of HFO-1132(E), HFO-1123, and R1234yf is 100 mass % are within the range of a figure surrounded by line segments PL, LQ, QR, and RP that connect the following 4 points:

point P (55.8, 42.0, 2.2),

point L (63.1, 31.9, 5.0),

point Q (62.8, 29.6, 7.6), and

point R (49.8, 42.3, 7.9),

or on the above line segments;

the line segment PL is represented by coordinates $(x, -0.1135x^2 + 12.112x - 280.43, 0.1135x^2 - 13.112x + 380.43)$,

the line segment RP is represented by coordinates $(x, 0.00672x^2 - 0.7607x + 63.525, -0.00672x^2 - 0.2393x + 36.475)$, and

the line segments LQ and QR are straight lines.

26. The refrigeration cycle apparatus according to claim 19,

wherein

when the mass % of HFO-1132(E), HFO-1123, and R1234yf based on their sum in the refrigerant is respectively represented by x , y , and z , coordinates (x,y,z) in a ternary composition diagram in which the sum of HFO-1132(E), HFO-1123, and R1234yf is 100 mass % are within the range of a figure surrounded by line segments SM, MA', A'B, BF, FT, and TS that connect the following 6 points:

point S (62.6, 28.3, 9.1),

point M (60.3, 6.2, 33.5),

point A' (30.6, 30.0, 39.4),

point B (0.0, 58.7, 41.3),

point F (0.0, 61.8, 38.2), and

point T (35.8, 44.9, 19.3),

or on the above line segments,

the line segment MA' is represented by coordinates $(x, 0.0016x^2 - 0.9473x + 57.497, -0.0016x^2 - 0.0527x + 42.503)$,

the line segment A'B is represented by coordinates $(x, 0.0029x^2 - 1.0268x + 58.7, -0.0029x^2 + 0.0268x + 41.3)$,

the line segment FT is represented by coordinates $(x, 0.0078x^2 - 0.7501x + 61.8, -0.0078x^2 - 0.2499x + 38.2)$,

the line segment TS is represented by coordinates $(x, -0.0017x^2 - 0.7869x + 70.888, -0.0017x^2 - 0.2131x + 29.112)$, and

the line segments SM and BF are straight lines.

27. The refrigeration cycle apparatus according to claim 2,

wherein

the refrigerant comprises trans-1,2-difluoroethylene (HFO-1132(E)) and trifluoroethylene (HFO-1123) in a total amount of 99.5 mass % or more based on the entire refrigerant, and

the refrigerant comprises 62.0 mass % to 72.0 mass % of HFO-1132(E) based on the entire refrigerant.

28. The refrigeration cycle apparatus according to claim 2,

wherein

the refrigerant comprises trans-1,2-difluoroethylene (HFO-1132(E)) and trifluoroethylene (HFO-1123) in a total amount of 99.5 mass % or more based on the entire refrigerant, and

the refrigerant comprises 45.1 mass % to 47.1 mass % of HFO-1132(E) based on the entire refrigerant.

29. The refrigeration cycle apparatus according to claim 2,

wherein

the refrigerant comprises trans-1,2-difluoroethylene (HFO-1132(E)), trifluoroethylene (HFO-1123), 2,3,3,3-tetrafluoro-1-propene (R1234yf), and difluoromethane (R32),

wherein

when the mass % of HFO-1132(E), HFO-1123, R1234yf, and R32 based on their sum in the refrigerant is respectively represented by x , y , z , and a ,

if $0 < a \leq 11.1$, coordinates (x,y,z) in a ternary composition diagram in which the sum of HFO-1132(E), HFO-1123, and R1234yf is $(100-a)$ mass % are within the range of a figure surrounded by straight lines GI, IA, AB, BD', D'C, and CG that connect the following 6 points:

point G (0.026a²-1.7478a+72.0, -0.026a²+0.7478a+28.0, 0.0),

point I (0.026a²-1.7478a+72.0, 0.0, -0.026a²+0.7478a+28.0),

point A (0.0134a²-1.9681a+68.6, 0.0, -0.0134a²+0.9681a+31.4),

point B (0.0, 0.0144a²-1.6377a+58.7, -0.0144a²+0.6377a+41.3),

point D' (0.0, 0.0224a²+0.968a+75.4, -0.0224a²-1.968a+24.6), and

point C (-0.2304a²-0.4062a+32.9, 0.2304a²-0.5938a+67.1, 0.0),

or on the straight lines GI, AB, and D'C (excluding point G, point I, point A, point B, point D', and point C);

if 11.1<a≤18.2, coordinates (x,y,z) in the ternary composition diagram are within the range of a figure surrounded by straight lines GI, IA, AB, BW, and WG that connect the following 5 points:

point G (0.02a²-1.6013a+71.105, -0.02a²+0.6013a+28.895, 0.0),

point I (0.02a²-1.6013a+71.105, 0.0, -0.02a²+0.6013a+28.895),

point A (0.0112a²-1.9337a+68.484, 0.0, -0.0112a²+0.9337a+31.516),

point B (0.0, 0.0075a²-1.5156a+58.199, -0.0075a²+0.5156a+41.801), and

point W (0.0, 100.0-a, 0.0),

or on the straight lines GI and AB (excluding point G, point I, point A, point B, and point W);

if 18.2<a≤26.7, coordinates (x,y,z) in the ternary composition diagram are within the range of a figure surrounded by straight lines GI, IA, AB, BW, and WG that connect the following 5 points:

point G (0.0135a²-1.4068a+69.727, -0.0135a²+0.4068a+30.273, 0.0),

point I (0.0135a²-1.4068a+69.727, 0.0, -0.0135a²+0.4068a+30.273),

point A (0.0107a²-1.9142a+68.305, 0.0, -0.0107a²+0.9142a+31.695),

point B (0.0, 0.009a²-1.6045a+59.318, -0.009a²+0.6045a+40.682), and

point W (0.0, 100.0-a, 0.0),

or on the straight lines GI and AB (excluding point G, point I, point A, point B, and point W);

if 26.7<a≤36.7, coordinates (x,y,z) in the ternary composition diagram are within the range of a figure surrounded by straight lines GI, IA, AB, BW, and WG that connect the following 5 points:

point G (0.0111a²-1.3152a+68.986, -0.0111a²+0.3152a+31.014, 0.0),

point I (0.0111a²-1.3152a+68.986, 0.0, -0.0111a²+0.3152a+31.014),

point A (0.0103a²-1.9225a+68.793, 0.0, -0.0103a²+0.9225a+31.207),

point B (0.0, 0.0046a²-1.41a+57.286, -0.0046a²+0.41a+42.714), and

point W (0.0, 100.0-a, 0.0),

or on the straight lines GI and AB (excluding point G, point I, point A, point B, and point W); and

if 36.7<a≤46.7, coordinates (x,y,z) in the ternary composition diagram are within the range of a figure surrounded by straight lines GI, IA, AB, BW, and WG that connect the following 5 points:

point G (0.0061a²-0.9918a+63.902, -0.0061a²-0.0082a+36.098, 0.0),

point I (0.0061a²-0.9918a+63.902, 0.0, -0.0061a²-0.0082a+36.098),

point A (0.0085a²-1.8102a+67.1, 0.0, -0.0085a²+0.8102a+32.9),

point B (0.0, 0.0012a²-1.1659a+52.95, -0.0012a²+0.1659a+47.05), and

point W (0.0, 100.0-a, 0.0),

or on the straight lines GI and AB (excluding point G, point I, point A, point B, and point W).

30. The refrigeration cycle apparatus according to claim 2,

wherein

the refrigerant comprises trans-1,2-difluoroethylene (HFO-1132(E)), trifluoroethylene (HFO-1123), 2,3,3,3-tetrafluoro-1-propene (R1234yf), and difluoromethane (R32),

wherein

when the mass % of HFO-1132(E), HFO-1123, R1234yf, and R32 based on their sum in the refrigerant is respectively represented by x, y, z, and a,

if 0<a≤11.1, coordinates (x,y,z) in a ternary composition diagram in which the sum of HFO-1132(E), HFO-1123, and R1234yf is (100-a) mass % are within the range of a figure surrounded by straight lines JK', K'B, BD', D'C, and CJ that connect the following 5 points:

point J (0.0049a²-0.9645a+47.1, -0.0049a²-0.0355a+52.9, 0.0),

point K' (0.0514a²-2.4353a+61.7, -0.0323a²+0.4122a+5.9, -0.0191a²+1.0231a+32.4),

point B (0.0, 0.0144a²-1.6377a+58.7, -0.0144a²+0.6377a+41.3),

point D' (0.0, 0.0224a²+0.968a+75.4, -0.0224a²-1.968a+24.6), and

point C (-0.2304a²-0.4062a+32.9, 0.2304a²-0.5938a+67.1, 0.0),

or on the straight lines JK', K'B, and D'C (excluding point J, point B, point D', and point C);

if 11.1<a≤18.2, coordinates (x,y,z) in the ternary composition diagram are within the range of a figure surrounded by straight lines JK', K'B, BW, and WJ that connect the following 4 points:

point J (0.0243a²-1.4161a+49.725, -0.0243a²+0.4161a+50.275, 0.0),

point K' (0.0341a²-2.1977a+61.187, -0.0236a²+0.34a+5.636, -0.0105a²+0.8577a+33.177),

point B (0.0, 0.0075a²-1.5156a+58.199, -0.0075a²+0.5156a+41.801), and

point W (0.0, 100.0-a, 0.0),

or on the straight lines JK' and K'B (excluding point J, point B, and point W);

if 18.2<a≤26.7, coordinates (x,y,z) in the ternary composition diagram are within the range of a figure surrounded by straight lines JK', K'B, BW, and WJ that connect the following 4 points:

point J (0.0246a²-1.4476a+50.184, -0.0246a²+0.4476a+49.816, 0.0),

point K' (0.0196a²-1.7863a+58.515, -0.0079a²-0.1136a+8.702, -0.0117a²+0.8999a+32.783),

- point B (0.0, $0.009a^2-1.6045a+59.318$, $-0.009a^2+0.6045a+40.682$), and
 point W (0.0, $100.0-a$, 0.0),
 or on the straight lines JK' and K'B (excluding point J, point B, and point W);
 if $26.7 < a \leq 36.7$, coordinates (x,y,z) in the ternary composition diagram are within the range of a figure surrounded by straight lines JK', K'A, AB, BW, and WJ that connect the following 5 points:
 point J ($0.0183a^2-1.1399a+46.493$, $-0.0183a^2+0.1399a+53.507$, 0.0),
 point K' ($-0.0051a^2+0.0929a+25.95$, 0.0, $0.0051a^2-1.0929a+74.05$),
 point A ($0.0103a^2-1.9225a+68.793$, 0.0, $-0.0103a^2+0.9225a+31.207$),
 point B (0.0, $0.0046a^2-1.41a+57.286$, $-0.0046a^2+0.41a+42.714$), and
 point W (0.0, $100.0-a$, 0.0),
 or on the straight lines JK', K'A, and AB (excluding point J, point B, and point W); and
 if $36.7 < a \leq 46.7$, coordinates (x,y,z) in the ternary composition diagram are within the range of a figure surrounded by straight lines JK', K'A, AB, BW, and WJ that connect the following 5 points:
 point J ($-0.0134a^2+1.0956a+7.13$, $0.0134a^2-2.0956a+92.87$, 0.0),
 point K' ($-1.892a+29.443$, 0.0, $0.892a+70.557$),
 point A ($0.0085a^2-1.8102a+67.1$, 0.0, $-0.0085a^2+0.8102a+32.9$),
 point B (0.0, $0.0012a^2-1.1659a+52.95$, $-0.0012a^2+0.1659a+47.05$), and
 point W (0.0, $100.0-a$, 0.0),
 or on the straight lines JK', K'A, and AB (excluding point J, point B, and point W).
- 31.** The refrigeration cycle apparatus according to claim 2,
 wherein
 the refrigerant comprises trans-1,2-difluoroethylene (HFO-1132(E)), difluoromethane (R32), and 2,3,3,3-tetrafluoro-1-propene (R1234yf),
 wherein
 when the mass % of HFO-1132(E), R32, and R1234yf based on their sum in the refrigerant is respectively represented by x, y, and z, coordinates (x,y,z) in a ternary composition diagram in which the sum of HFO-1132(E), R32, and R1234yf is 100 mass % are within the range of a figure surrounded by line segments IJ, JN, NE, and EI that connect the following 4 points:
 point I (72.0, 0.0, 28.0),
 point J (48.5, 18.3, 33.2),
 point N (27.7, 18.2, 54.1), and
 point E (58.3, 0.0, 41.7),
 or on these line segments (excluding the points on the line segment EI;
 the line segment IJ is represented by coordinates ($0.0236y^2-1.7616y+72.0$, y, $-0.0236y^2+0.7616y+28.0$);
 the line segment NE is represented by coordinates ($0.012y^2-1.9003y+58.3$, y, $-0.012y^2+0.9003y+41.7$); and
 the line segments JN and EI are straight lines.
- 32.** The refrigeration cycle apparatus according to claim 2,
 wherein
 the refrigerant comprises trans-1,2-difluoroethylene (HFO-1132(E)), difluoromethane (R32), and 2,3,3,3-tetrafluoro-1-propene (R1234yf),
 wherein
 when the mass % of HFO-1132(E), R32, and R1234yf based on their sum in the refrigerant is respectively represented by x, y, and z, coordinates (x,y,z) in a ternary composition diagram in which the sum of HFO-1132(E), R32, and R1234yf is 100 mass % are within the range of a figure surrounded by line segments MM', M'N, NV, VG, and GM that connect the following 5 points:
 point M (52.6, 0.0, 47.4),
 point M' (39.2, 5.0, 55.8),
 point N (27.7, 18.2, 54.1),
 point V (11.0, 18.1, 70.9), and
 point G (39.6, 0.0, 60.4),
 or on these line segments (excluding the points on the line segment GM);
 the line segment MM' is represented by coordinates ($0.132y^2-3.34y+52.6$, y, $-0.132y^2+2.34y+47.4$);
 the line segment M'N is represented by coordinates ($0.0596y^2-2.2541y+48.98$, y, $-0.0596y^2+1.2541y+51.02$);
 the line segment VG is represented by coordinates ($0.0123y^2-1.8033y+39.6$, y, $-0.0123y^2+0.8033y+60.4$); and
 the line segments NV and GM are straight lines.
- 33.** The refrigeration cycle apparatus according to claim 2,
 wherein
 the refrigerant comprises trans-1,2-difluoroethylene (HFO-1132(E)), difluoromethane (R32), and 2,3,3,3-tetrafluoro-1-propene (R1234yf),
 wherein
 when the mass % of HFO-1132(E), R32, and R1234yf based on their sum in the refrigerant is respectively represented by x, y and z, coordinates (x,y,z) in a ternary composition diagram in which the sum of HFO-1132(E), R32, and R1234yf is 100 mass % are within the range of a figure surrounded by line segments ON, NU, and UO that connect the following 3 points:
 point O (22.6, 36.8, 40.6),
 point N (27.7, 18.2, 54.1), and
 point U (3.9, 36.7, 59.4),
 or on these line segments;
 the line segment ON is represented by coordinates ($0.0072y^2-0.6701y+37.512$, y, $-0.0072y^2-0.3299y+62.488$);
 the line segment NU is represented by coordinates ($0.0083y^2-1.7403y+56.635$, y, $-0.0083y^2+0.7403y+43.365$); and
 the line segment UO is a straight line.
- 34.** The refrigeration cycle apparatus according to claim 2,
 wherein
 the refrigerant comprises trans-1,2-difluoroethylene (HFO-1132(E)), difluoromethane (R32), and 2,3,3,3-tetrafluoro-1-propene (R1234yf),
 wherein
 when the mass % of HFO-1132(E), R32, and R1234yf based on their sum in the refrigerant is respectively

represented by x, y, and z, coordinates (x,y,z) in a ternary composition diagram in which the sum of HFO-1132(E), R32, and R1234yf is 100 mass % are within the range of a figure surrounded by line segments QR, RT, TL, LK, and KQ that connect the following 5 points:

point Q (44.6, 23.0, 32.4),
point R (25.5, 36.8, 37.7),
point T (8.6, 51.6, 39.8),
point L (28.9, 51.7, 19.4), and
point K (35.6, 36.8, 27.6),

or on these line segments;

the line segment QR is represented by coordinates $(0.0099y^2 - 1.975y + 84.765, y, -0.0099y^2 + 0.975y + 15.235)$;

the line segment RT is represented by coordinates $(0.0082y^2 - 1.8683y + 83.126, y, -0.0082y^2 + 0.8683y + 16.874)$;

the line segment LK is represented by coordinates $(0.0049y^2 - 0.8842y + 61.488, y, -0.0049y^2 - 0.1158y + 38.512)$;

the line segment KQ is represented by coordinates $(0.0095y^2 - 1.2222y + 67.676, y, -0.095y^2 + 0.2222y + 32.324)$; and

the line segment TL is a straight line.

35. The refrigeration cycle apparatus according to claim 2,

wherein

the refrigerant comprises trans-1,2-difluoroethylene (HFO-1132(E)), difluoromethane (R32), and 2,3,3,3-tetrafluoro-1-propene (R1234yf),

wherein

when the mass % of HFO-1132(E), R32, and R1234yf based on their sum in the refrigerant is respectively represented by x, y, and z, coordinates (x,y,z) in a ternary composition diagram in which the sum of HFO-1132(E), R32, and R1234yf is 100 mass % are within the range of a figure surrounded by line segments PS, ST, and TP that connect the following 3 points:

point P (20.5, 51.7, 27.8),
point S (21.9, 39.7, 38.4), and
point T (8.6, 51.6, 39.8),

or on these line segments;

the line segment PS is represented by coordinates $(0.0064y^2 - 0.7103y + 40.1, y, -0.0064y^2 - 0.2897y + 59.9)$;

the line segment ST is represented by coordinates $(0.0082y^2 - 1.8683y + 83.126, y, -0.0082y^2 + 0.8683y + 16.874)$; and

the line segment TP is a straight line.

36. The refrigeration cycle apparatus according to claim 2,

wherein

the refrigerant comprises trans-1,2-difluoroethylene (HFO-1132(E)), trifluoroethylene (HFO-1123), and difluoromethane (R32),

wherein

when the mass % of HFO-1132(E), HFO-1123, and R32 based on their sum in the refrigerant is respectively represented by x, y, and z, coordinates (x,y,z) in a ternary composition diagram in which the sum of HFO-1132(E), HFO-1123, and R32 is 100 mass %

are within the range of a figure surrounded by line segments IK, KB', B'H, HR, RG, and GI that connect the following 6 points:

point I (72.0, 28.0, 0.0),
point K (48.4, 33.2, 18.4),
point B' (0.0, 81.6, 18.4),
point H (0.0, 84.2, 15.8),
point R (23.1, 67.4, 9.5), and
point G (38.5, 61.5, 0.0),

or on these line segments (excluding the points on the line segments B'H and GI);

the line segment IK is represented by coordinates $(0.025z^2 - 1.7429z + 72.00, -0.025z^2 + 0.7429z + 28.0, z)$,

the line segment HR is represented by coordinates $(-0.3123z^2 + 4.234z + 11.06, 0.3123z^2 - 5.234z + 88.94, z)$,

the line segment RG is represented by coordinates $(-0.0491z^2 - 1.1544z + 38.5, 0.0491z^2 + 0.1544z + 61.5, z)$, and

the line segments KB' and GI are straight lines.

37. The refrigeration cycle apparatus according to claim 2,

wherein

the refrigerant comprises trans-1,2-difluoroethylene (HFO-1132(E)), trifluoroethylene (HFO-1123), and difluoromethane (R32),

wherein

when the mass % of HFO-1132(E), HFO-1123, and R32 based on their sum in the refrigerant is respectively represented by x, y, and z, coordinates (x,y,z) in a ternary composition diagram in which the sum of HFO-1132(E), HFO-1123, and R32 is 100 mass % are within the range of a figure surrounded by line segments IJ, JR, RG, and GI that connect the following 4 points:

point I (72.0, 28.0, 0.0),
point J (57.7, 32.8, 9.5),
point R (23.1, 67.4, 9.5), and
point G (38.5, 61.5, 0.0),

or on these line segments (excluding the points on the line segment GI);

the line segment IJ is represented by coordinates $(0.025z^2 - 1.7429z + 72.0, -0.025z^2 + 0.7429z + 28.0, z)$,

the line segment RG is represented by coordinates $(-0.0491z^2 - 1.1544z + 38.5, 0.0491z^2 + 0.1544z + 61.5, z)$, and

the line segments JR and GI are straight lines.

38. The refrigeration cycle apparatus according to claim 2,

wherein

the refrigerant comprises trans-1,2-difluoroethylene (HFO-1132(E)), trifluoroethylene (HFO-1123), and difluoromethane (R32),

wherein

when the mass % of HFO-1132(E), HFO-1123, and R32 based on their sum in the refrigerant is respectively represented by x, y, and z, coordinates (x,y,z) in a ternary composition diagram in which the sum of HFO-1132(E), HFO-1123, and R32 is 100 mass % are within the range of a figure surrounded by line segments MP, PB', B'H, HR, RG, and GM that connect the following 6 points:

point M (47.1, 52.9, 0.0),
 point P (31.8, 49.8, 18.4),
 point B' (0.0, 81.6, 18.4),
 point H (0.0, 84.2, 15.8),
 point R (23.1, 67.4, 9.5), and
 point G (38.5, 61.5, 0.0),

or on these line segments (excluding the points on the line segments B'H and GM);

the line segment MP is represented by coordinates $(0.0083z^2 - 0.984z + 47.1, -0.0083z^2 - 0.016z + 52.9, z)$,

the line segment HR is represented by coordinates $(-0.3123z^2 + 4.234z + 11.06, 0.3123z^2 - 5.234z + 88.94, z)$,

the line segment RG is represented by coordinates $(-0.0491z^2 - 1.1544z + 38.5, 0.0491z^2 + 0.1544z + 61.5, z)$, and

the line segments PB' and GM are straight lines.

39. The refrigeration cycle apparatus according to claim 2,

wherein

the refrigerant comprises trans-1,2-difluoroethylene (HFO-1132(E)), trifluoroethylene (HFO-1123), and difluoromethane (R32),

wherein

when the mass % of HFO-1132(E), HFO-1123, and R32 based on their sum in the refrigerant is respectively represented by x, y, and z, coordinates (x,y,z) in a ternary composition diagram in which the sum of HFO-1132(E), HFO-1123, and R32 is 100 mass % are within the range of a figure surrounded by line segments MN, NR, RG, and GM that connect the following 4 points:

point M (47.1, 52.9, 0.0),
 point N (38.5, 52.1, 9.5),
 point R (23.1, 67.4, 9.5), and
 point G (38.5, 61.5, 0.0),

or on these line segments (excluding the points on the line segment GM);

the line segment MN is represented by coordinates $(0.0083z^2 - 0.984z + 47.1, -0.0083z^2 - 0.016z + 52.9, z)$,

the line segment RG is represented by coordinates $(-0.0491z^2 - 1.1544z + 38.5, 0.0491z^2 + 0.1544z + 61.5, z)$, and

the line segments JR and GI are straight lines.

40. The refrigeration cycle apparatus according to claim 2,

wherein

the refrigerant comprises trans-1,2-difluoroethylene (HFO-1132(E)), trifluoroethylene (HFO-1123), and difluoromethane (R32),

wherein

when the mass % of HFO-1132(E), HFO-1123, and R32 based on their sum in the refrigerant is respectively represented by x, y, and z, coordinates (x,y,z) in a ternary composition diagram in which the sum of HFO-1132(E), HFO-1123, and R32 is 100 mass % are within the range of a figure surrounded by line segments PS, ST, and TP that connect the following 3 points:

point P (31.8, 49.8, 18.4),
 point S (25.4, 56.2, 18.4), and
 point T (34.8, 51.0, 14.2),

or on these line segments;

the line segment ST is represented by coordinates $(-0.0982z^2 + 0.9622z + 40.931, 0.0982z^2 - 1.9622z + 59.069, z)$,

the line segment TP is represented by coordinates $(0.0083z^2 - 0.984z + 47.1, -0.0083z^2 - 0.016z + 52.9, z)$, and

the line segment PS is a straight line.

41. The refrigeration cycle apparatus according to claim 2,

wherein

the refrigerant comprises trans-1,2-difluoroethylene (HFO-1132(E)), trifluoroethylene (HFO-1123), and difluoromethane (R32),

wherein

when the mass % of HFO-1132(E), HFO-1123, and R32 based on their sum in the refrigerant is respectively represented by x, y, and z, coordinates (x,y,z) in a ternary composition diagram in which the sum of HFO-1132(E), HFO-1123, and R32 is 100 mass % are within the range of a figure surrounded by line segments QB", B"D, DU, and UQ that connect the following 4 points:

point Q (28.6, 34.4, 37.0),
 point B" (0.0, 63.0, 37.0),
 point D (0.0, 67.0, 33.0), and
 point U (28.7, 41.2, 30.1),

or on these line segments (excluding the points on the line segment B"D);

the line segment DU is represented by coordinates $(-3.4962z^2 + 210.71z - 3146.1, 3.4962z^2 - 211.71z + 3246.1, z)$,

the line segment UQ is represented by coordinates $(0.0135z^2 - 0.9181z + 44.133, -0.0135z^2 - 0.0819z + 55.867, z)$, and

the line segments QB" and B"D are straight lines.

* * * * *