



US 20160002937A1

(19) **United States**
(12) **Patent Application Publication**
BRAUN

(10) **Pub. No.: US 2016/0002937 A1**
(43) **Pub. Date: Jan. 7, 2016**

(54) **WORKING DEVICE WITH STATIONARY MAST AND ROTARY HEAD**

(52) **U.S. Cl.**
CPC *E04G 21/0427* (2013.01); *E04G 21/0445* (2013.01)

(71) Applicant: **PUTZMEISTER ENGINEERING GMBH, Aichtal (DE)**

(57) **ABSTRACT**

(72) Inventor: **Matthias BRAUN, Stuttgart (DE)**

A working device has a base designed as a stationary support column, a motor-driven rotary head and a stack of arms made up of several mast arms which can be moved with respect to each other in pairs, using articulated or sliding joints, supporting a concrete transport line. The stack of arms is articulated on the rotary head about a horizontal rotational axis by a first mast arm. The working device also includes a control mechanism which can be actuated by a control element or a radio path and which is arranged in a control box, and a hydraulic assembly including an oil tank and a motor-driven hydraulic pump for controlling working groups for moving the rotary head and mast arm. A working platform fixed with respect to the frame is arranged in the region of the bearing block for emergency operations. In order to ensure that the components required for actuating the stack of arms are not in the way of the engine in the event of an emergency operation, the oil tank of the hydraulic assembly is arranged on the rotary head and includes a contour which is geometrically adapted to the rotary head, defining a window opening for the passage of a ballast boom which is detachably arranged on the rotary head. The oil tank also includes a holder for receiving the control cabinet which can pivot about at least 90° with respect to the window opening about an axis parallel to the rotational axis of the rotary head.

(73) Assignee: **PUTZMEISTER ENGINEERING GMBH, Aichtal (DE)**

(21) Appl. No.: **14/768,278**

(22) PCT Filed: **Feb. 27, 2014**

(86) PCT No.: **PCT/EP2014/053792**


§ 371 (c)(1),
(2) Date: **Aug. 17, 2015**

(30) **Foreign Application Priority Data**

Mar. 7, 2013 (DE) 10 2013 203 886.0

Publication Classification

(51) **Int. Cl.**
E04G 21/04 (2006.01)






Fig.1




Fig.2a




Fig.2b




Fig.2c




Fig. 3a




Fig. 3b




Fig. 3c




Fig. 3d




Fig.4

WORKING DEVICE WITH STATIONARY MAST AND ROTARY HEAD

[0001] The invention relates to a working device having a frame configured preferably as a stationary support column, having a motor-driven rotary head which is arranged on a bearing block, fixed to the frame, so as to be rotatable about a vertical rotation axis, having an arm assembly consisting of a plurality of boom arms that are movable in pairs relative to one another at articulated joints or sliding joints and carry a concrete delivery line, which arm assembly is articulated on the rotary head about a horizontal rotation axis by way of its first boom arm, having a control mechanism that is actuable either via control members or a radio link and has a hydraulic assembly for controlling drive units for the rotary-head and boom-arm movement, and having a working platform arranged in a manner fixed to the frame in the vicinity of the bearing block.

[0002] Working devices of this kind that are configured as concrete pumps have a distributor boom as outrigger, which carries a concrete delivery line that is connected to the pressure connector of a core pump arranged in a manner fixed to the frame. Such a working device having the features specified at the beginning is known per se (EP-1 235 965 B1). Therein, the components that belong to the drive mechanism of the rotary head are integrated into the bearing block fixed to the frame. A considerable disadvantage of this construction is that the working platform is constricted by the parts attached to the bearing block and therefore there is not enough space for the fitter to move. In addition, the hose assembly necessary for hydraulically controlling the arm assembly is relatively large and bulky and further restricts the space for the fitter to move at the point in question.

[0003] In the event of emergency operation, in which the fitter is active on the working platform, there is a not inconsiderable risk of injury if the rotary head with the arm assembly is controlled incorrectly. Depending on the boom position, in the event of emergency operation, the view of the fitter to the arm assembly is also impeded. Because of the relatively great height, on account of the fixtures, of the bearing block, safe operation from the working platform is not always ensured.

[0004] Taking this as a departure point, the invention is based on the problem of improving the known working device such that the fixtures necessary for the actuation of the arm assembly do not impede the fitter in the event of emergency operation.

[0005] In order to solve this problem, the combination of features specified in claim 1 is proposed. Advantageous configurations and developments of the invention can be gathered from the dependent claims.

[0006] The solution according to the invention consists substantially in that a liquid tank, which is expediently configured as an oil tank for the hydraulic assembly and has an external contour that is geometrically matched to the rotary head, is arranged on the rotary head above the bearing block. The liquid tank can in this case have a window bounded by its external contour, said window being intended for example for the passage of a ballast outrigger arranged releasably on the rotary head. Furthermore, a holder for receiving the control cabinet can be arranged on the liquid tank, said holder being pivotable through at least 90° about an axis parallel to the rotation axis of the rotary head with respect to the window. As a result of this measure, the holder with the control cabinet can be pivoted into the window when a ballast outrigger is not

present or can be pivoted out of said window parallel to a ballast outrigger that is present. The working platform free of fixtures allows the fitter to move around without stumbling and to have a good view of the arm assembly. As a result of the omission of the disruptive fixtures, the arm assembly can be placed close to the rotary head, with the result that the load torque produced thereby is reduced.

[0007] A preferred configuration of the invention provides for the rotary head to have a base part arranged on the bearing block and an adapter piece comprising a bearing point for the ballast outrigger, wherein the base part and the adapter piece are coupled together releasably via a separation point. In this case, the base part and the adapter piece expediently have coupling elements that are connectable together in a form-fitting manner in pairs at their separation point. In order to be able to lead the ballast outrigger to the separation point, the window arranged on the oil tank has to be free by pivoting out the control cabinet located on the holder.

[0008] According to an advantageous development of the invention, the arm assembly, too, is coupled releasably to the base part of the rotary head by means of further coupling elements that are connectable together in a form-fitting manner in pairs via a further adapter piece at a second separation point located opposite the separation point of the ballast outrigger. In this way, it is possible for the arm assembly, together with the further adapter piece, to be able to be separated from the base part of the rotary head in the region of the second separation point, while the base part, together with the bearing block, remains on the frame. It is particularly advantageous in this case for the base part and the adapter piece to have coupling elements that are connectable together in a form-fitting manner in pairs in the region of the second separation point.

[0009] The invention is explained in more detail in the following text with reference to an exemplary embodiment which is schematically illustrated in the drawing, in which:

[0010] FIG. 1 shows an exploded illustration of a detail of a working device, configured as a concrete distributor boom, having a support column, arm assembly and ballast outrigger;

[0011] FIGS. 2a, b and c show a diagrammatic illustration and two side views of a detail of the working device with fixtures on the rotary head;

[0012] FIG. 3a to d show four different diagrammatic illustrations of the rotary head with fixtures, mounted on the bearing block;

[0013] FIG. 4 shows a diagrammatic illustration of the rotary head with bearing block, arm assembly and ballast outrigger.

[0014] The working device illustrated in the drawing is configured as a concrete pump having a stationary frame 10. The frame 10 forms a support column, which has at its upper end a substructure 14 with a bearing block 35 for a rotary head 32 that is rotatable about a vertical rotation axis 30. Arranged on the rotary head 32 are respective outriggers 16, 116 that are directed toward opposite sides of the support column and are configured as an arm assembly 34 and as a ballast carrier 134. The arm assembly 34 has a plurality of boom arms 1, 2, 3, 4 that are pivotable with respect to one another in pairs and carry a concrete delivery line 22. As can be seen in particular in FIGS. 1 and 4, the outrigger 16 with the first boom arm 1 of the arm assembly 34 is mounted in a pivotable manner about a horizontal pivot axis in the mounted state at a bearing point 36 of the rotary head 32. In order to be able to pivot the outrigger 16 with respect to the rotary head 32, provision is

furthermore made of a hydraulic cylinder-piston unit **40** configured as a double-acting hydraulic cylinder, which is articulated with its end **42** fixed to the cylinder and with its end **44** fixed to the piston rod to an outrigger-side articulation point **46** arranged at a distance from the bearing point **36** and to a rotary-head-side articulation point **48** with a horizontal articulation axis, respectively.

[0015] The outrigger **16** configured as an arm assembly **34** of a concrete distributor boom is releasably coupled to the base part **50** of the rotary head **32** by means of coupling elements that are connectable together in a form-fitting manner in pairs via an adapter piece **52** at a separation point **54**. For this purpose, the adapter piece **52** has coupling elements configured as pin-like drop-in elements **56**, **57**, while the base part **50** is provided with receptacles **58**, **59**, peripherally open upwardly, for the drop-in elements **56**, **57**. The bores, discernible in FIG. 1, in the adapter piece **52** form the bearing point **36** for the outrigger **16** and the rotary-head-side articulation point **48** for the cylinder-piston unit **40**.

[0016] The outrigger **16** is transported to the frame **10** with the aid of a crane, which is fixed to the outrigger **16** at the centroid position **82** thereof via a crane gear **74**. As can be seen from FIG. 4, provision is additionally made, in the region of the separation point **54**, of a security device which is produced by means of a socket pin or latching pin **76** between the adapter piece **52** and the base part **50**. The socket pin or latching pin **76** can be fitted subsequently by a fitter from a working platform **78** fixed to the substructure (FIG. 1).

[0017] It can be seen in FIGS. 1 and 4 that the rotary head **32** has, in addition to the base part **50** arranged on the bearing block **35**, a second adapter piece **152** comprising a bearing point **136** for an additional outrigger **116**. The additional outrigger **116**, having a ballast carrier **134**, is releasably coupled to the base part **50** of the rotary head **32** by means of coupling elements that are connectable together in a form-fitting manner in pairs via the adapter piece **152** at the separation point **154**. In this case, a first group of coupling elements is configured as pin-like drop-in members **156** and a second group of coupling elements is configured as hooking members **157** provided with a peripherally open receptacle **158** for the drop-in members **156**. The drop-in members **156** are arranged on the base part **50**, while the hooking members **157** with a receptacle **158** that is peripherally open downwardly are arranged on the adapter piece **152**. The adapter piece **152** has a stop **120** that is arranged beneath the peripherally open receptacle **158** in the mounted state and bears against the base part **50** under the action of the load torque generated about the axis of the drop-in members **156** via the outrigger **116**. In the exemplary embodiment shown, the adapter piece **152** is connected to the outrigger **116** at two bearing points **136**, **137**, wherein the bearing points **136**, **137** are spaced apart from one another primarily in the vertical direction. In a similar manner to the outrigger **16**, the outrigger **116** can also be mounted on the base part **50** by means of a crane.

[0018] As can be seen from FIGS. 2 to 4, the rotary head is equipped with a relatively large number of fixtures, which have the following functions:

[0019] A hydraulic assembly **84** for controlling drive units for the rotary-head and boom-arm movement, said hydraulic assembly **84** having an oil tank **86** and a hydraulic pump **88** driven by means of an electric motor **87**,

[0020] a control mechanism **90** which is actuatable either via control members **91** or a radio link **89** and is accommodated in a control cabinet **92**,

[0021] a drive mechanism **33** which has a hydraulic drive motor **94** and a slewing gearbox **96** for driving the rotary head **32** in rotation with respect to the bearing block **35**,

[0022] and a working platform **78** arranged in a manner fixed to the frame close to the bearing block **35**.

[0023] One particular feature of the invention is that the oil tank **86** has an external and internal contour that is geometrically matched to the rotary head **32**. As can be seen in particular from FIGS. 3a to d and 4, the oil tank **86** is provided with a window **98** which is intended for the passage of a ballast outrigger **134** mounted on the rotary head **32**. However, the ballast outrigger **134** only has to be provided when the frame **10** is loaded so heavily on account of the load torque acting on the rotary head **32** via the arm assembly **34** that load balancing is required. When a ballast outrigger **134** is not provided, the window **98** can be used to receive the control cabinet **92** for the control mechanism **90**. In order to be ready for both cases, provision is made on the oil tank **86** of a holder **102** for receiving the control cabinet **92**, said holder **102** being pivotable about an axis **100** parallel to the rotation axis **30** of the rotary head **32** with respect to the window **98**. In this way it is possible, when the ballast outrigger **134** is present, to pivot the control cabinet **92** out of the window **98** via its holder **102**, such that it can be operated from the working platform **78**.

[0024] A further particular feature of the invention is that the control cabinet **92** with the control mechanism **90** and the hydraulic assembly **84** with the oil tank **86** and hydraulic pump **88** are arranged on the base part **50** of the rotary head **32** above the bearing block **35**. Likewise arranged on the rotary head **32** above the bearing block **35** is the hydraulic drive motor **94** together with the slewing gearbox **96** for driving the rotary head **32**. The control mechanism **90** is supplied with electric power via an external power source and an electrical cable that is routed via the support column fixed to the frame and bridges the rotary bearing between the bearing block **35** and rotary head **32**.

[0025] With the construction according to the invention, as a result of which the operationally necessary fixtures, such as the control cabinet **92**, hydraulic assembly **88** and drive mechanism **33**, are arranged directly on the rotary head **32** above the bearing block **35**, the freedom of movement of the fitter in the region of the working platform **78** is improved. The working platform **78** free of fixtures allows the fitter to move around without stumbling when rotating the rotary head **32** and also allows a good view of the arm assembly **34**. As a result of the omission of the disruptive fixtures, the arm assembly **34** can furthermore be placed close to the rotary head **32**, with the result that the load torque generated thereby and thus the deflection of the frame **10** can be reduced.

[0026] In summary: the invention relates to a working device having a frame **10** configured as a stationary support column, having a motor-driven rotary head **32** and having an arm assembly **34** consisting of a plurality of boom arms **1**, **2**, **3**, **4** that are movable in pairs relative to one another at articulated joints or sliding joints and carry a concrete delivery line. The arm assembly **34** is articulated on the rotary head **32** about a horizontal rotation axis with its first boom arm **1**. Provision is furthermore made of a control mechanism **90** that is actuatable via control members or a radio link and is arranged in a control cabinet **92**, and a hydraulic assembly **84**, having

an oil tank **86** and a motor-driven hydraulic pump **88**, for controlling drive units for the rotary-head and boom-arm movement. For emergency operation, a working platform **78** arranged in a manner fixed to the frame is located in the vicinity of the bearing block **35**. In order to ensure that the fixtures necessary for actuating the arm assembly **34** do not disrupt the operator in the event of emergency operation, the invention proposes that the oil tank **86** of the hydraulic assembly **84** is arranged on the rotary head **32** and has a contour that is geometrically matched to the rotary head **32** and bounds a window **98** for the passage of a ballast outrigger **116**, **134** arranged releasably on the rotary head **32**. Furthermore, a holder **102** for receiving the control cabinet **92** is arranged on the oil tank **86**, said holder **102** being pivotable through at least 90° about an axis **100** parallel to the rotation axis **30** of the rotary head **32** with respect to the window **98**.

LIST OF REFERENCE SIGNS

- [0027] **1, 2, 3, 4** Boom arms
- [0028] **10** Frame
- [0029] **14** Substructure
- [0030] **16** Outrigger
- [0031] **22** Concrete delivery line
- [0032] **30** Rotation axis
- [0033] **32** Rotary head
- [0034] **33** Drive mechanism
- [0035] **34** Arm assembly
- [0036] **35** Bearing block
- [0037] **36** Bearing point
- [0038] **40** Cylinder-piston unit
- [0039] **42** End fixed to the cylinder
- [0040] **44** End fixed to the piston rod
- [0041] **46, 48** Articulation points
- [0042] **50** Base part
- [0043] **52** Adapter piece
- [0044] **54** Separation point
- [0045] **56, 57** Drop-in elements
- [0046] **58, 59** Receptacles
- [0047] **74** Crane gear
- [0048] **76** Latching pin
- [0049] **78** Working platform
- [0050] **82** Centroid position
- [0051] **84** Hydraulic assembly
- [0052] **86** Oil tank
- [0053] **87** Electric motor
- [0054] **88** Hydraulic pump
- [0055] **89** Radio link
- [0056] **90** Control mechanism
- [0057] **91** Control members
- [0058] **92** Control cabinet
- [0059] **94** Drive motor
- [0060] **96** Slewing gearbox
- [0061] **98** Window
- [0062] **100** Axis
- [0063] **102** Holder
- [0064] **116** Outrigger
- [0065] **134** Ballast outrigger
- [0066] **136, 137** Bearing points
- [0067] **152** Adapter piece
- [0068] **154** Separation point
- [0069] **156** Drop-in member

[0070] **157** Hooking member

[0071] **158** Receptacles

1-11. (canceled)

12. A working device having a frame (**10**) configured preferably as a stationary support column, having a motor-driven rotary head (**32**) which is arranged on a bearing block (**35**), fixed to the frame, so as to be rotatable about a vertical rotation axis (**30**), having an arm assembly (**34**) comprising a plurality of boom arms (**1, 2, 3, 4**) that are movable in pairs relative to one another at articulated joints or sliding joints and carry a concrete delivery line (**22**), which arm assembly (**34**) is articulated on the rotary head (**32**) about a horizontal rotation axis with its first boom arm (**1**), and having a control mechanism that is actuable either via control members (**91**) or a radio link (**89**) and has a hydraulic assembly (**84**) for controlling drive units for the rotary-head and boom-arm movement, wherein a liquid tank which has an external contour that is geometrically matched to the rotary head (**32**) is arranged on the rotary head (**32**), and wherein the liquid tank bounds a window with its external contour.

13. The working device as claimed in claim **12**, wherein a ballast outrigger (**134**) that reaches through the window (**98**) is releasably arranged on the rotary head (**32**).

14. The working device as claimed in claim **12**, wherein the window is configured as a reach-through opening for assembly and disassembly work.

15. The working device as claimed in claim **12**, wherein a liquid tank which has an external contour that is geometrically matched to the rotary head (**38**) is arranged on the rotary head (**32**), said liquid tank being provided with a window (**98**) for the passage of a ballast outrigger mounted on the rotary head (**32**) and/or to be reached through for assembly and disassembly work.

16. The working device as claimed in claim **12**, wherein the liquid tank (**86**) is configured as an oil tank for the hydraulic assembly (**84**).

17. The working device as claimed in claim **12**, wherein the control mechanism (**90**) is arranged in a control cabinet (**92**), and wherein the liquid tank has a holder for receiving the control cabinet.

18. The working device as claimed in claim **17**, wherein the holder with the control cabinet (**92**) is pivotable through at least 90° about an axis (**100**) parallel to the rotation axis (**30**) of the rotary head (**32**) with respect to the window (**98**).

19. The working device as claimed in claim **13**, wherein the rotary head (**32**) has a base part (**50**) arranged on the bearing block (**35**) and an adapter piece (**152**) comprising a bearing point (**136, 137**) for the ballast outrigger (**134**), wherein the base part (**50**) and the adapter piece (**152**) are coupled together releasably via a separation point (**154**).

20. The working device as claimed in claim **19**, wherein the base part (**50**) and the adapter piece (**152**) have coupling elements that are connectable together in a form-fitting manner in pairs at their separation point (**154**).

21. The working device as claimed in claim **12**, wherein the arm assembly (**34**) is coupled releasably to the base part (**50**) of the rotary head (**32**) by means of coupling elements that are connectable together in a form-fitting manner in pairs via an adapter piece (**52**) at a separation point (**54**).

22. The working device as claimed in claim **12**, further comprising a working platform (**78**) arranged in a manner fixed to the frame in the vicinity of the bearing block (**35**).