



(19) **United States**

(12) **Patent Application Publication**

**Jones**

(10) **Pub. No.: US 2003/0093218 A1**

(43) **Pub. Date: May 15, 2003**

(54) **SYSTEM AND METHOD FOR AN ADVANCE NOTIFICATION SYSTEM FOR MONITORING AND REPORTING PROXIMITY OF A VEHICLE**

(76) Inventor: **Martin Kelly Jones, Dalton, GA (US)**

Correspondence Address:  
**THOMAS, KAYDEN, HORSTEMEYER & RISLEY, LLP**  
**100 GALLERIA PARKWAY, NW**  
**STE 1750**  
**ATLANTA, GA 30339-5948 (US)**

(21) Appl. No.: **10/322,956**

(22) Filed: **Dec. 18, 2002**

**Related U.S. Application Data**

(63) Continuation of application No. 09/908,471, filed on Jul. 18, 2001, which is a continuation of application No. 09/163,958, filed on Sep. 30, 1998, now Pat. No. 6,278,936. Continuation-in-part of application No. 08/852,119, filed on May 6, 1997, and which is a continuation-in-part of application No. 08/434,049, filed on May 2, 1995, now Pat. No. 5,623,260, and which is a continuation-in-part of application No. 08/432,898, filed on May 2, 1995, now Pat. No. 5,657,010, and which is a continuation-in-part of application No. 08/432,666, filed on May 2, 1995, now Pat. No. 5,668,543said application application number is a continuation-in-part of application No. 08/407,319, filed on Mar. 20, 1995, now abandoned, which is a continuation-in-part of application No. 08/063,533, filed on May 18, 1993, now Pat. No.

5,400,020said application application number is a continuation-in-part of application No. 08/407,319, filed on Mar. 20, 1995, now abandoned, which is a continuation-in-part of application No. 08/063,533, filed on May 18, 1993, now Pat. No. 5,400,020said application application number is a continuation-in-part of application No. 08/407,319, filed on Mar. 20, 1995, now abandoned, which is a continuation-in-part of application No. 08/063,533, filed on May 18, 1993, now Pat. No. 5,400,020.


(60) Provisional application No. 60/039,925, filed on Mar. 10, 1997.

**Publication Classification**

(51) **Int. Cl.<sup>7</sup> ..... G01C 21/00**  
(52) **U.S. Cl. .... 701/201; 701/200; 340/994**

**ABSTRACT**

(57) Generally, the present invention monitors and communicates travel data transmitted from vehicles being monitored by the system to users requesting travel information on a particular vehicle. A travel data storage unit receives and stores the travel data. When a user desires to view some or all of this travel data, the user submits a request to a data manager. In response, the data manager retrieves the appropriate information from the travel data stored in the travel data storage unit and transmits this information to the user. The data manager may communicate the information in a variety of mediums and preferably contact information is predefined that enables the data manager to determine which medium is preferable and how to establish communication once the medium is determined.






Fig. 1





Fig. 2



**Fig. 3**




Fig. 4




Fig. 5




Fig. 6




Fig. 7



**SYSTEM AND METHOD FOR AN ADVANCE NOTIFICATION SYSTEM FOR MONITORING AND REPORTING PROXIMITY OF A VEHICLE**

**CLAIM OF PRIORITY AND CROSS REFERENCE TO RELATED APPLICATIONS/PATENTS**

[0001] This document claims priority to and is a continuation of copending U.S. Patent Application entitled "SYSTEM AND METHOD FOR AN ADVANCE NOTIFICATION SYSTEM FOR MONITORING AND REPORTING PROXIMITY OF A VEHICLE" assigned Ser. No. 09/908,471; filed Jul. 18, 2001, which is a continuation of Ser. No. 09/163,958, and filed on Sep. 30, 1998, now U.S. Pat. No. 6,278,936; issued Aug. 21, 2001, entitled "SYSTEM AND METHOD FOR AN ADVANCE NOTIFICATION SYSTEM FOR MONITORING AND REPORTING PROXIMITY OF A VEHICLE." This document also claims priority to and is a continuation-in-part of copending U.S. Patent Application entitled "ADVANCE NOTIFICATION SYSTEMS AND METHODS UTILIZING A COMPUTER NETWORK," assigned Ser. No. 08/852,119, and filed on May 6, 1997, which claims priority to (a)-(d) hereafter, and which is a continuation-in-part of (b)-(d) hereafter:

[0002] (a) provisional application entitled, "ADVANCE NOTIFICATION SYSTEM AND METHOD UTILIZING A COMPUTER NETWORK," filed Mar. 7, 1997 by M. K. Jones and assigned serial No. 60/039,925;

[0003] (b) nonprovisional application entitled, "ADVANCE NOTIFICATION SYSTEM AND METHOD UTILIZING PASSENGER-DEFINABLE NOTIFICATION TIME PERIOD," filed May 2, 1995 by M. K. Jones and assigned Ser. No. 08/434,049, now U.S. Pat. No. 5,623,260 to M. K. Jones that issued on Apr. 22, 1997;

[0004] (c) nonprovisional application entitled, "ADVANCE NOTIFICATION SYSTEM AND METHOD UTILIZING VEHICLE PROGRESS REPORT GENERATOR," filed May 2, 1995 by M. K. Jones and assigned Ser. No. 08/432,898, now U.S. Pat. No. 5,657,010 to M. K. Jones that issued on Aug. 12, 1997; and

[0005] (d) nonprovisional application entitled, "ADVANCE NOTIFICATION SYSTEM AND METHOD UTILIZING PASSENGER CALLING REPORT GENERATOR," filed May 2, 1995 by M. K. Jones and assigned Ser. No. 08/432,666, now U.S. Pat. No. 5,668,543 to M. K. Jones that issued on Sep. 16, 1997;

[0006] where documents (b), (c), and (d) are each a continuation-in-part of the application entitled "ADVANCE NOTIFICATION SYSTEM AND METHOD UTILIZING A DISTINCTIVE TELEPHONE RING," filed Mar. 20, 1995 by M. K. Jones and assigned Ser. No. 08/407,319, now abandoned, which in turn is a continuation-in-part of an application entitled "ADVANCE NOTIFICATION SYSTEM AND METHOD" filed May 18, 1993 by M. K. Jones et al. and assigned Ser. No. 08/063,533, now U.S. Pat. No. 5,400,020 to M. K. Jones et al. that issued on Mar. 21, 1995.

[0007] All of the foregoing documents that are cited in this section are incorporated by reference as if set forth in full hereinbelow.

**BACKGROUND OF THE INVENTION**

[0008] 1. Field of the Invention

[0009] The present invention generally relates to data communications and information systems and, in particular, to an automated system and method for monitoring travel of a vehicle and for communicating vehicle travel information to a user at a remote location regarding the proximity of the vehicle relative to a predefined destination.

[0010] 2. Related Art

[0011] There are many situations when it is desirable to know the actual arrival time of a particular vehicle at a particular destination or other location. With this information, adjustments can be made to avoid waiting for a particular vehicle to reach the particular destination. For example, a person picking up a friend or relative at a commercial bus station usually either calls the bus station to find out the approximate arrival time (information which is oftentimes unavailable or unreliable) and/or arrives at the bus station prior to the scheduled arrival time of the bus hoping that the bus is not significantly delayed.

[0012] Another example involves school children that ride school buses. The arrival times of school buses at scheduled stops can be significantly affected by many factors such as maintenance problems, rush hour traffic, and congested urban/suburban conditions. As a result, school children typically wait at bus stops for long periods of time, oftentimes in adverse weather conditions, on unlit street corners, or in hazardous conditions near busy or secluded streets. A system informing the students of the school bus' proximity is desirable in order for the students to avoid waiting on the school bus at the school bus stop for extended times.

[0013] Yet another example is in the commercial overnight package delivery industry, wherein packages are delivered on a tight schedule. Customers oftentimes wait on delivery of important time-critical packages not knowing precisely when the delivery will occur. A system informing the customer of the precise arrival time is desirable in order to improve customer service and to allow the customer to better rely on the estimated arrival time of the delivery.

[0014] Thus, generally, it is desirable to know when a vehicle (such as a bus, truck, train, plane, user, or the like) is (a) a particular time period (for example, a certain number of minutes or seconds) away from arriving at a destination, (b) a particular distance (for example, number of feet or miles) away from the destination, or (c) at a particular location among a set of predetermined location points.

[0015] In order to alleviate the arrival time problem in the context of school buses, student notification systems in the past have been employed that use a transmitter on each bus and a receiver inside each student home. U.S. Pat. No. 4,713,661 to Boone et al. and U.S. Pat. No. 4,350,969 describe systems of this type. When the school bus and its on-board transmitter come within a certain range of a particular home receiver, the transmitter sends a signal to notify the student that the school bus is nearby. While such notification systems work satisfactorily under certain cir-

circumstances, nevertheless, these systems are limited by the range of the transmitters and require the purchase of relatively expensive receivers for each student. In addition, such systems provide little flexibility for providing additional information to the students, such as notifying them of the delayed arrival of a bus, alternative bus route information, or information regarding important school events.

[0016] Thus, a heretofore unaddressed need exists in the industry for a system and method for monitoring travel of a vehicle and for providing desirable travel information, such as, for example, an updated location of the vehicle.

#### SUMMARY OF THE INVENTION

[0017] The present invention overcomes the inadequacies and deficiencies of the prior art as discussed herein. In general, the present invention provides an automated system and method for monitoring travel of a vehicle and for communicating vehicle travel information to a user located at a remote location in response to a request by the user.

[0018] In a broad sense, the present invention utilizes a storage mechanism, a data manager, and communications devices. The storage mechanism receives and stores travel information transmitted from a vehicle at a remote location. The travel information preferably includes data that indicates a location of the vehicle, such as the coordinates of the vehicle relative to a predefined reference point, but the travel information may include various other information in lieu of or in combination with the location data. When a user at another remote location wishes to view all or some of this the travel information transmitted by the vehicle, the user establishes communication with the data manager and submits a request. In response to the request, the data manager retrieves the desired information and transmits a message containing the information from a communications device at associated with the data manager to another communications device associated with the user. By analyzing this retrieved information, the user can monitor the travel of a particular vehicle.

[0019] In accordance with another feature of the present invention, a mapping system is designed to receive the travel data retrieved by the data manager and to generate mapping data based on the retrieved travel data. The mapping data is transmitted to a device at the user's location which renders the mapping data as a graphical display indicating the location of the vehicle on a map. By viewing the map, the user can monitor the travel of the vehicle.

[0020] In accordance with another feature of the present invention, the data manager compares predefined preference data to travel data associated with a particular vehicle. When a comparison of the predefined preference data to the travel data associated with the particular vehicle indicates that there is an impending arrival of the vehicle at a particular location, the data manager transmits a notification message to the user.

[0021] In accordance with another feature of the present invention, the particular vehicle includes a sensor for determining a location of the particular vehicle relative to a predefined reference point. A communications device associated with the particular vehicle transmits travel data indicating the location of the particular vehicle to the storage mechanism. Preferably, the communications device associ-

ated with the particular vehicle transmits the travel data through a cellular network or some other wireless communications system.

[0022] In accordance with another feature of the present invention, contact information is retrieved by the data manager in order to enable communication between the communications devices. The contact information is preferably predefined by the user and indicates a preferred medium of communication with which to transmit the travel data to the user.

[0023] The present invention can also be viewed as providing a method for communicating travel data associated with a particular vehicle. Briefly described, the method can be broadly conceptualized by the following steps: receiving travel data transmitted from vehicles located at remote locations; storing the travel data; receiving a request from a user located at a remote location; retrieving travel data associated with a particular vehicle in response to the request; forming a message corresponding with the travel data retrieved in the retrieving step; and transmitting the message to a communications device associated with the user.

[0024] The present invention has many advantages, a few of which are delineated hereafter, as mere examples.

[0025] An advantage of the present invention is that a particular vehicle associated with the system can be monitored, and a user can be notified when an arrival of the vehicle at a predefined destination is imminent. As a result, the user can prepare for the arrival of the vehicle knowing the precise time of arrival of the vehicle.

[0026] Another advantage of the present invention is that a user at a remote location can monitor the travel of a particular vehicle by gaining access to the travel data used to monitor the vehicle.

[0027] Another advantage of the present invention is that a user at a remote location can receive, on demand, updated information pertaining to the travel or status of a particular vehicle.

[0028] Another advantage of the present invention is that it can be implemented in software, hardware, or a combination thereof.

[0029] Other features and advantages of the present invention will become apparent to one skilled in the art upon examination of the following detailed description, when read in conjunction with the accompanying drawings. It is intended that all such features and advantages be included herein within the scope of the present invention, as is defined by the claims.

#### BRIEF DESCRIPTION OF THE DRAWINGS

[0030] The invention can be better understood with reference to the following drawings. The elements of the drawings are not necessarily to scale relative to each other, emphasis instead being placed upon clearly illustrating the principles of the invention. Furthermore, like reference numerals designate corresponding parts throughout the several views.

[0031] FIG. 1 is a block diagram illustrating a vehicle monitoring system in accordance with the preferred embodiment of the present invention.

[0032] FIG. 2 is a block diagram illustrating an implementation of the vehicle manager of FIG. 1 in accordance with the preferred embodiment of the present invention.

[0033] FIG. 3 is a block diagram illustrating an implementation of the base station manager of FIG. 1 in accordance with the preferred embodiment of the present invention.

[0034] FIG. 4 is a detailed block diagram of the base station of FIG. 1.

[0035] FIG. 5 is a detailed block diagram of the data manager of FIG. 4.

[0036] FIG. 6 is a flowchart illustrating the functionality of the monitoring mechanism of FIG. 5.

[0037] FIG. 7 is a flowchart illustrating the functionality of the message manager of FIG. 5.

#### DETAILED DESCRIPTION OF THE INVENTION

[0038] FIG. 1 depicts an automated monitoring system 10 illustrating the principles of the present invention. Vehicle control unit (VCU) 15 can be attached to any mobile structure or vehicle capable of carrying or moving a sensor 18 over various distances. For example, VCU 15 can be attached to an automobile, an airplane, a train, a boat or any other structure capable of moving across or through the Earth's surface and/or atmosphere. VCU 15 can also be carried by a person while walking or running.

[0039] The sensor 18 within VCU 15 is configured to determine the location of VCU 15 relative to a predetermined reference point. For example, in the preferred embodiment, sensor 18 is a global positioning system (GPS) sensor coupled to VCU 15, although other types of positioning systems and/or sensors are also possible. The GPS sensor 18 is configured to receive signals 21a-21c from a plurality of GPS satellites 23, and as known in the art, sensor 18 is designed to analyze signals 21a-21c in order to determine the sensor's coordinate values relative to a predetermined reference point. For example, in the preferred embodiment where sensor 18 is a GPS sensor, the sensor 18 determines the sensor's coordinate values relative to the Earth's zero degree latitude and zero degree longitude reference point, which is located at the intersection of the Equator and the Prime Meridian. U.S. Pat. No. 5,781,156 entitled "GPS Receiver and Method for Processing GPS Signals" and filed on Apr. 23, 1997 by Krasner, which is incorporated herein by reference, discusses the processing of GPS signals 21a-21c received from GPS satellites 23 in order to determine the coordinate values. Since the sensor 18 is located within VCU 15, the coordinate values determined by the sensor 18 are assumed to match the coordinate values of the vehicle or other structure attached to the VCU 15.

[0040] It should be noted that the term "coordinate value" shall be defined herein to mean any value or set of values that may be used to determine a location of a point on the Earth. These values may be grid values, polar values, vector values, or any other type of value or values known in the art for indicating locations of points.

[0041] Sensor 18 is designed to transmit a signal 27 to vehicle manager 29 indicating the VCU's current coordinate values. Vehicle manager 29 is configured to receive signal

27 and to monitor the location of the VCU 15 over time by processing multiple signals 27. The vehicle manager 29 can be implemented in software, hardware, or a combination thereof. In the preferred embodiment, as illustrated by way of example in FIG. 2, the vehicle manager 29 of the present invention along with its associated methodology is implemented in software and stored in computer memory 30a of a computer system 31a.

[0042] Note that the vehicle manager 29 can be stored and transported on any computer-readable medium for use by or in connection with an instruction execution system, apparatus, or device, such as a computer-based system, processor-containing system, or other system that can fetch the instructions from the instruction execution system, apparatus, or device and execute the instructions. In the context of this document, a "computer-readable medium" can be any means that can contain, store, communicate, propagate, or transport the program for use by or in connection with the instruction execution system, apparatus, or device. The computer readable medium can be, for example but not limited to, an electronic, magnetic, optical, electromagnetic, infrared, or semiconductor system, apparatus, device, or propagation medium. More specific examples (a nonexhaustive list) of the computer-readable medium would include the following: an electrical connection (electronic) having one or more wires, a portable computer diskette (magnetic), a random access memory (RAM) (magnetic), a read-only memory (ROM) (magnetic), an erasable programmable read-only memory (EPROM or Flash memory) (magnetic), an optical fiber (optical), and a portable compact disc read-only memory (CDROM) (optical). Note that the computer-readable medium could even be paper or another suitable medium upon which the program is printed, as the program can be electronically captured, via for instance optical scanning of the paper or other medium, then compiled, interpreted or otherwise processed in a suitable manner if necessary, and then stored in a computer memory. As an example, the vehicle manager 29 may be magnetically stored and transported on a conventional portable computer diskette.

[0043] The preferred embodiment of the computer system 31a of FIG. 2 comprises one or more conventional processing elements 32a, such as a digital signal processor (DSP), that communicate to and drive the other elements within the system 31a via a local interface 33a, which can include one or more buses. Furthermore, an input device 34a, for example, a keyboard or a mouse, can be used to input data from a user of the system 31a, and screen display 35a or a printer 36a can be used to output data to the user. A disk storage mechanism 37a can be connected to the local interface 33a to transfer data to and from a nonvolatile disk (e.g., magnetic, optical, etc.). It should be noted that input device 34a, display 35a, printer 36a, and disk 37a are optional and are not a part of the preferred embodiment, although other embodiments may include these features.

[0044] The vehicle manager 29 is preferably configured to maintain a database of travel data. The travel data includes the vehicle location information as well as any other desirable information. For example, when VCU 15 is attached to a delivery vehicle, vehicle manager 29 can be configured to include a list of items to be delivered and to indicate which deliveries have been successfully attempted, which deliveries have been unsuccessfully attempted, and which deliver-

ies remain to be attempted. Vehicle manager 29 can also be configured to include the time that particular deliveries or other types of stops (e.g., bus stops) have been made and/or attempted. The travel data stored in vehicle manager 29 may include other desirable information not mentioned herein without departing from the principles of the present invention.

[0045] When desired, vehicle manager 29 is configured to transmit certain travel data (preferably including the location of VCU 15 and other desirable information) to base station control unit (BSCU) 38, which is remotely located from the VCU 15. Co-pending U.S. Patent Application entitled "System and Method for Enciphering and Communicating Vehicle Tracking Information" filed by Jones of even date herewith (Express Mail No. EL068353584US), which is incorporated herein by reference, describes a system and method for transmitting the vehicle data to BSCU 38.

[0046] BSCU 38 preferably includes a base station manager 39 designed to monitor the travel data of each VCU 15 associated with the system 10. The base station manager 39 can be implemented in software, hardware, or a combination thereof. In the preferred embodiment, as illustrated by way of example in FIG. 3, the base station manager 39 of the present invention along with its associated methodology is implemented in software and stored in computer memory 30b of a computer system 31b. The computer system 31b can be similar to computer system 31a, as can be seen by comparing FIG. 2 to FIG. 3. In this regard, the computer system 31b may include memory 30b for storing monitoring mechanism 39, and the computer system 31b may also include processing element 32b, local interface 33b, input 34b, display 35b, printer 36b, and storage disk 37b. It may also be desirable for computer system 31b to include a network interface 41 that allows the system 31b to exchange data with a network 42. It should be noted that input device 34b, display 35b, printer 36b, disk 37b, network interface 41, and network 42 are optional.

[0047] Vehicle manager 29 is configured to transmit travel data, via signal 43 (FIG. 1), to a communications device 44, which is capable of transmitting and receiving data to and from devices outside of VCU 15. In this regard, communications device 44 is preferably a cellular modem configured to transmit and receive wireless signals to and from a cellular network 48.

[0048] The communications device 44 can transmit the travel data over the voice channels associated with the cellular network 48, as is done by most cellular modems of the prior art. However, in order to reduce the cost associated with transmitting the travel data through the cellular network 48, the travel data may be communicated through the cellular network 48 via a data or control channel. In this regard, the travel data can be encoded by altering identifiers of communications device 44, such as the mobile identification number (MIN) or electronic serial number (ESN), transmitted over a data channel of the cellular network 48. Alternatively, travel data can be appended to a feature request transmitted over the data channel. U.S. Pat. No. 5,771,445 entitled "Data Messaging in a Communications Network using a Feature Request," filed on Dec. 15, 1995, by Kennedy, III, et al., and U.S. Pat. No. 5,546,444 entitled "Methods and Apparatus for Communicating Data Via a Cellular Network Control Channel" filed on Mar. 11, 1994,

by Roach, Jr., et al., which are both incorporated herein by reference, discuss the transmission of travel data over a data or control channel associated with cellular network 48 in further detail.

[0049] In order to transmit the travel data through a data channel by manipulating identifiers of the communications device 44, the MIN of communications device 44 is altered to include travel data, but the ESN remains fixed to be used as an identifier of the communications device 44. Therefore, after transmitting the identifiers through the data channel, the communications device 44 can be identified by the MIN, and the travel data can be determined from the MIN. Alternatively, the ESN of communications device 44 can be altered while the MIN is kept constant. It should be understood that the invention contemplates modification of the MIN, ESN, both the MIN and ESN, or other identifiers of the communications device 44 to accomplish the dual task of transmitting travel data and identifying the communications device 44.

[0050] Alternatively or in combination with the manipulation of the identifiers of the communications device 44, travel data can be communicated through the data channel by appending travel data to feature requests that are transmitted through the data channel. In this regard, most feature requests are generated by automatically or manually dialing the star key ("\*") followed by a two-digit feature request identification code, and 29 digits of data. Therefore, for each feature request generated, 29 digits of travel data can be appended to the two-digit feature request identification code and sent over the data channel of the cellular network 48. Other embodiments may transmit different amounts of travel data following the feature request. By utilizing the manipulation of identifiers or the appendage of travel data to feature requests, less data is transmitted through the voice channels of the cellular network 48, thereby reducing the cost of transmitting data through the cellular network 48.

[0051] Cellular network 48 is designed to transmit the travel data to a vehicle communications device 52 at the BSCU 38. Although not necessary for implementation of the present invention, cellular network 48 is preferably designed to transmit to vehicle communications device 52 via a public switched telephone network (PSTN) 55. In this regard, PSTN 55 establishes a link between communications device 52 and cellular network 48, whereby cellular network 48 and communications device 52 can communicate via signals 61 and 65. Therefore, communications device 52 is preferably designed as a PSTN modem capable of communicating signals 65 between base station manager 39 and PSTN network 55.

[0052] Although the preferred embodiment utilizes a cellular network 48 and a PSTN network 55 to communicate travel data to base station manager 39, one ordinarily skilled in the art should realize that other configurations are possible. For example, communications device 52 can be configured as a cellular modem capable of communicating signals directly with cellular network 48. Alternatively, utilization of communication networks 48 and 55 can be completely circumvented by configuring communications device 44 to communicate directly with communications device 52, for example. Any embodiment capable of communicating data between vehicle manager 29 and base station manager 39 should be suitable for implementing the principles of the present invention.

**[0053]** Base Station Manager

**[0054]** Base station manager **39** is designed to receive the travel data transmitted from vehicle manager **29** and to monitor the travel of the vehicle attached to the VCU **15** by monitoring the travel of the VCU **15**. In this regard, base station manager **39** is designed to include a data manager **67** configured to receive the travel data via signal **66** from communications device **52**, as depicted by **FIG. 4**. Data manager **67** is designed to store the travel data for each VCU **15** being monitored into a travel data storage unit **68**. Preferably, travel data storage unit **68** is a database configured to store travel data associated with each VCU **15** being monitored by the system **10**. The travel data storage unit **68** is configured to include a relational parameter (i.e., a unique identification value correlated with the VCU **15** and, therefore, the travel data associated with the VCU **15**) that enables determination of which travel data is associated with which VCU **15**. For example, travel data storage unit **68** can be configured as a data table with each entry in the data table assigned an identification number unique to a particular VCU **15**. Furthermore, each entry can include all of the travel data associated with the particular VCU **15**. For example, each entry can include information such as, but not limited to, the VCU's coordinate values (i.e., the VCU's **15** location relative to a predetermined reference point), information regarding delivery status of items to be delivered, and/or the times that the VCU **15** reached particular locations or stops. The travel data storage unit **68** can be configured to contain all of the desirable information to monitor the status of each VCU **15** associated with the system **10**.

**[0055]** Referring to **FIG. 5**, data manager **67** is configured to include a monitoring mechanism **69**. The functionality of monitoring mechanism **69** is depicted in **FIG. 6**. As shown by blocks **102-112** of **FIG. 6**, monitoring mechanism **69** is configured to receive travel data from VCU **15** and to compare the travel data with predefined preference data stored in travel data storage unit **68**. Preference data, as used herein, is data that defines the preferred parameters indicating when to notify a user of the impending arrival of the VCU **15** at a particular location. For example, preference data can be coordinates of a desired location whereby a notification message is sent to a user when the coordinates of the VCU **15** pass the coordinates of the desired location. In this context, the desired location defined by the preference data can, for example, represent a location that is a predetermined distance from the user's house, place of delivery/pick-up, or other particular location. Therefore, when the user receives the notification message, the user is aware of the approximate location of the VCU **15** or of the distance of the VCU **15** from a predetermined point (i.e., of the proximity of the VCU **15** from a predetermined point or location). Consequently, the user can prepare for the arrival of the VCU **15**, since the user knows that arrival of the VCU **15** is imminent.

**[0056]** Alternatively, the preference data can define a certain time before the VCU **15** reaches a destination or other particular location (i.e., a proximity of the VCU **15** from the predetermined point). In this regard, the monitoring mechanism **69** is designed to determine the location of the VCU **15** from the travel data stored in travel data storage unit **68**. The monitoring mechanism **69** is then designed to calculate the time it will take for the VCU **15** to reach the

location specified by the preference data based on the location of the VCU **15** and the location of the desired destination. In calculating the travel time, the monitoring mechanism **69** can be configured to make assumptions about the time necessary to travel to the specified location. For example, if the route of the VCU **15** is through congested areas, the monitoring mechanism **69** can assume a certain delay time for traveling certain distances, and if the route of the VCU **15** is through less congested areas, the monitoring mechanism **69** can assume another delay time that is less than the delay time assumed for the congested areas. Alternatively, the monitoring mechanism **69** can use an average of the times it has previously taken for vehicles **15** to travel over the same route during other deliveries. Therefore, by comparing the travel data transmitted from VCU **15** with preference data, the monitoring mechanism **69** can determine when to send a notification message to a user.

**[0057]** As depicted by blocks **102, 104, 114, and 116** of **FIG. 6**, the preference data can be stored in travel data storage unit **68** (**FIG. 5**). As stated hereinbefore, the travel data storage unit **68** is preferably configured to store the travel data associated with each VCU **15** in a respective entry uniquely identified with the associated VCU **15**. Accordingly, each data entry can also include the preference data associated with each VCU **15** that corresponds with the entry, or the preference data can be stored in separate entries which are correlated with corresponding VCU entries.

**[0058]** Once the monitoring mechanism **69** determines that a notification message should be sent to a user, the data manager **67** is designed to communicate a message to a user at a remote location **71**, such as a user's premises, via PSTN network **55** and communications devices **72** and **73** (**FIGS. 1, 4, and 5**). In this regard, communications devices **72** and **73** are preferably PSTN modems capable of communicating with PSTN network **55**. Data manager **67** is designed to transmit the message as signal **70** to user communications device **72**, which communicates the message with PTSN network **55** via signal **74**. PTSN network **55** then communicates the message to communications device **73**, which is preferably configured to communicate the message to a message device **75**. Message device **75** is configured to notify the user of the impending arrival of the VCU **15**. Preferably, message device **75** is a computer capable of displaying the notification through e-mail or some other communications software. Alternatively, message device **75** can be a telephone, a pager or any other device capable of notifying a user at location **71**.

**[0059]** Although the preferred embodiment utilizes a PSTN network **55** to communicate a notification message to message device **75**, one ordinarily skilled in the art should realize that other configurations are possible. For example, other communication networks can be utilized or utilization of communication networks can be completely circumvented by configuring communications device **72** to communicate directly with communications device **73**. Any embodiment capable of communicating data between data manager **67** and message device **75** should be suitable for implementing the principles of the present invention.

**[0060]** User Activation

**[0061]** In order for data manager **67** to transmit a notification message to a user at user premises **71**, data manager **67** should be aware of certain contact information enabling

data manager 67 to contact the message device 75. In this regard, data manager 67 is configured to include a user database 78 (FIG. 5) containing contact information pertaining to each user that is to receive a notification message from the data manager 67. The user database 78 is preferably a database capable of uniquely identifying each user of the system 10. In the preferred embodiment, the user database 78 is a data table having entries that specify contact information associated with each user. Each entry preferably includes a user identification number unique to each user that identifies the information in the entry as relating to a particular user.

[0062] Each entry preferably includes a value specifying the medium through which the user has specified to be contacted. For example, the value can indicate that the user is to be contacted through e-mail, in which case the entry should also include the user's e-mail address. Alternatively, the value can indicate that the user is to be contacted through a telephone call or a page. In these situations, the entry should also include the user's telephone number or pager number. The value can also indicate multiple methods of notification. For example, the value can indicate that the user is to be first contacted via telephone. If there is no answer when the data manager 67 attempts to deliver a notification message, then the data manager 67 can be configured to attempt notification via paging. If paging fails, then the data manager 67 can be configured to attempt notification through e-mail or other computer oriented messaging system. Accordingly, the order of notification media should be indicated by the data in the user database 78, and the contact information necessary for each method selected (e.g., the telephone number, pager number, and e-mail address of the user) should also be included in the entry. It should be noted that various other communications media and combinations of communications media can be employed without departing from the principles of the present invention.

[0063] The contact information (and preference data, which will be discussed in further detail hereinafter) can be manually entered or downloaded into the user database 78 in order to activate a user for the system 10. In this regard, a system operator can receive the contact information (and preference data) via a telephone call or e-mail, for example, and manually enter the information into the system 10.

[0064] However, in the preferred embodiment, the contact information is automatically entered into the user database 78 via a message manager 82, which is depicted by FIG. 5. The functionality of the message manager 82 is shown in FIG. 7. The message manager 82 (FIG. 5) is configured to receive, via communications device 72 (FIG. 1), an activation request from a user at user premises 71, as shown by blocks 131-137 of FIG. 7. In this regard, the request can be transmitted to user communications device 72, via any suitable technique known in the art, and the BSCU 38 can be configured to include a plurality of user communications devices 72, as depicted by FIG. 4.

[0065] Each of these user communications devices 72 can be configured to simultaneously communicate with a respective user of the system 10. The information received by the user communications devices 72 can be transmitted to message manager 82 (FIG. 5) via any suitable technique, such as time division multiplexing, for example. Each user communications device 72 can also be designed to commu-

nicate with different communications media. For example, one user communications device 72 can be designed as a modem to communicate with a modem at user premises 71. This user communications device 72 can be designed to send data configured to prompt the user to return data pertaining to contact information. An example of such a prompt, could be a template or web page where the user's message device 75 (i.e., a computer in this case) displays the template, and the user can fill in fields of the template with the appropriate contact information. Alternatively, another one of the user communications devices 72 can be designed to receive a telephone call from a user at user premises 71 and to prompt the user to enter data through touch-tone signaling. Other user communications devices 72 can be designed to communicate with other types of communications media known in the art.

[0066] Once the message manager 82 (FIG. 5) receives the request from the user, the message manager 82 is designed to determine that the request is a request for activation (i.e., a request for the user to be entered into the system 10). In response, the message manager 82 transmits data to the user, via user communications device 72, in order to prompt the user to transmit the necessary contact information, as shown by block 141 of FIG. 7. In this regard, the message manager 82 is configured to determine the type of medium used by the user to communicate the request for activation and to transmit a prompt to the user that is compatible with this medium. For example, when the user is communicating via a modem, the message manager 82 is configured to transmit signals compatible with the user's modem in order to prompt the user to enter the appropriate contact information. This data could be in the form of a web page transmitted through the Internet, or the prompt could simply be messages transmitted through e-mail or some other data communications system.

[0067] When the user is communicating via a telephone, the message manager 82 is preferably designed to transmit recorded messages to the user. The user can then select or enter data by transmitting touch-tone signals in response to the prompting messages, as is commonly known in the art. The message manager 82 may be configured to communicate with the user in other formats and media known in the art.

[0068] Once the message manager 82 receives the contact information from the user, the message manager 82 is designed to store the contact information as an entry in the user database 78, as depicted by block 143 of FIG. 7. When the monitoring mechanism 69 determines that a user should be notified of an impending arrival of a VCU 15, the monitoring mechanism 69 is designed to send a notification command to message manager 82. The notification command may include travel data to be sent to the user, such as data indicating that a particular vehicle is a certain proximity from the destination defined by the preference data. In response, the message manager 82 is designed to retrieve the contact information associated with the user from the user database 78 and to determine how to contact the user based on the retrieved contact information, as depicted by blocks 151 and 153 of FIG. 7.

[0069] The message manager 82 is then designed to transmit a message compatible with the medium previously selected by the user for notification, as depicted by block

**156** of **FIG. 7**. The message can include any travel data sent to the message manager **82** from the monitoring mechanism **69**. For example, when the contact information indicates that a phone call is the preferred medium for notification, the message manager **82** can send a recorded telephone message to the telephone number that is indicated by the contact information retrieved from the user database **78**. If the monitoring mechanism **69** included travel data indicating the time of arrival in the command to message manager **82**, then message manager **82** can be configured to include a message indicating the expected time of arrival at a particular location. Alternatively, the same information can be sent via e-mail, facsimile, page or other type of communications medium to the user, depending on the preferences selected by the user during activation.

**[0070]** During activation, the message manager **82** can be further configured to prompt for and receive preference data (i.e., data pertaining to when the user is to be notified) from the user, as shown by block **141** of **FIG. 7**. In this regard, the message manager **82** can be designed to prompt the user to return information indicating which VCU **15** is to be monitored on behalf of the user and when the notification is to be sent to the user. For example, the user can be prompted to select a VCU **15**, a destination (or other particular location), and a notification preference to indicate a time or distance that the VCU **15** should be from the selected destination or other particular location when a notification is to be sent to the user. In response, the user specifies, through any known suitable communications technique, which VCU **15** the user wishes the system **10** to monitor and how the user wishes to be notified of an impending arrival of the selected VCU **15** at the selected destination. If the user knows the coordinate values of the destination, the user can simply transmit the coordinate values to the data manager **67**. If the user selects the destination without supplying the coordinates of the destination (e.g., the user selects a destination from a list of locations) then the data manager **67** is preferably designed to determine the coordinate values transparently.

**[0071]** In some instances, the user may be aware of the vehicle number and stop number used by the system **10** to identify a particular VCU **15** and destination. For example, many buses are associated with a commonly known bus number, and the stops along the bus' route are associated with commonly known bus stop numbers. The data manager **67** can be configured to recognize the VCU **15** and destination associated with the bus number and stop number entered by the user in order to register the user with the system **10**.

**[0072]** As depicted by block **146** of **FIG. 7**, the message manager **82** is preferably designed to automatically transmit to monitoring mechanism **69** the preferences selected by the user that pertain to when the user is to be notified. The monitoring mechanism **69** is designed to store this preference information in the travel data storage unit **68** in the entry associated with the selected VCU **15**.

**[0073]** Once a user becomes activated with the system **10**, the user may make changes to the preferences specified by the user, as shown by blocks **161-169** of **FIG. 7**. The message manager **82** is configured to receive the request for changes from the user. The message manager **82** can be configured to request the user to resubmit all contact information and preference data, as updated, or can be configured

to request the user to only submit desired changes to the contact information or preference data. After receiving the new data, the message manager **82** is configured to update the contact information in user database **78** and to send a request to monitoring mechanism **69** to update the preference data relating to the monitoring of travel data. In response, monitoring mechanism **69** is designed to update the preference data in the travel data storage unit **68**, as shown by blocks **114** and **116** of **FIG. 6**.

**[0074]** It should be further noted that as described hereinabove, the preference data and travel data can be automatically received and stored in travel data storage unit **68** and selected vehicles **15** can be automatically monitored by the system **10**. As used herein, the term "automatic" shall be defined to mean without interruption or interference from a human operator. However, it is possible to implement the system **10** such that interference and interruption from a human operator is required.

#### **[0075]** Requests for Travel Data

**[0076]** In addition to providing the user with automatic advance notification of an impending arrival of a VCU **15**, the system **10** can also be used to provide the user with travel data on demand, as depicted by blocks **171-177**, **153** and **156** of **FIG. 7**. In this regard, the user communications device **72** is designed to receive a request for travel data from a user. For example, the user may call the communications device **72** on a telephone and through touch-tone signaling select, among other options, an option to discover the distance and/or time a particular VCU **15** is from the destination specified by the user's preference data or specified by the user during the request for travel data. The user communications device **72** is designed to transmit the user's selections to message manager **82**. Based on the selections, the message manager **82** is designed to determine that the user message is a request for travel data. In response, the message manager **82** sends a request to monitoring mechanism **69** to retrieve the requested data from travel data storage unit **68**.

**[0077]** The monitoring mechanism **69** is designed to receive the request for travel data from message manager **82** and to interpret the request in order to determine which travel information from the travel data in travel data storage unit **68** is desired by the user, as depicted by blocks **183** and **185** of **FIG. 6**. The monitoring mechanism **69** is then designed to retrieve from travel data storage unit **68** the desired travel data and to transmit the retrieved travel data to message manager **82**, as shown by blocks **188** and **191** of **FIG. 6**.

**[0078]** In the case where the user desires to know the time and/or distance the selected VCU **15** is from the selected location, the monitoring mechanism **69** is designed to retrieve from travel data storage unit **68** the coordinates of the destination specified by the user (if not provided in the request for travel data) and the current coordinates of the VCU **15** of interest to the user. Prior to retrieving this data, the monitoring mechanism **69** can be configured to update the travel data for the VCU **15** by transmitting an update request to the VCU **15** via vehicle communications device **52**. Similar to the user communications devices **72**, a plurality of vehicle communications devices **52** may be located at the BSCU **38** in order for multiple vehicles **15** to simultaneously communicate with the monitoring mechanism **69**, as depicted by **FIG. 5**. The vehicle communications devices

**52** are configured to communicate with the monitoring mechanism **69** through any suitable technique, such as time division multiplexing, for example.

[**0079**] After receiving the update request via communications devices **52** and **44**, the vehicle manager **29** is designed to transmit the current values of the vehicle travel data to the monitoring manager **69**. By updating the vehicle travel data before responding to the user's request for travel data, the monitoring mechanism **69** can ensure the accuracy of the response transmitted to the user.

[**0080**] After retrieving the coordinate values from the travel data storage unit **68**, the monitoring mechanism **69** is designed to calculate the distance that the VCU **15** is from the selected destination based on the coordinate values of the VCU **15** and the coordinate values of the destination. If the preference data and/or request for travel data indicates that the user is to be notified when the VCU **15** is a certain time from the selected destination, the monitoring mechanism **69** is then designed to determine the estimated time of arrival of the VCU **15** at the destination based on this distance. As described previously, the monitoring mechanism **69** is designed to either assume that certain distances will take a certain amount of time to travel based on the type of traffic conditions usually encountered on the route or to calculate an average time previously required for vehicles **15** of the system to travel the route. To increase the accuracy of the calculations, the route should be divided into sections where the time required to travel each section is independently calculated. Furthermore, time delays associated with scheduled stops or deliveries can be factored into the calculations by assuming a delay time for each stop or delivery depending on the type of stop or delivery expected.

[**0081**] After calculating the distance and, if requested, the time the VCU **15** is from the destination, the monitoring mechanism **69** is configured to transmit the calculated values to the message manager **82**. In response, the message manager **82** is designed to transmit the calculated information to the user via user communications device **72**. Since the user already has an established communications connection with user communications device **72** when requesting travel data, there is no need for the message manager **82** to consult the contact information in the user database **78**. The message manager **82** can simply transmit the data over the same connection. However, if desired, the message manager **82** may consult the contact information in the user database **78** to determine the user preferences in notification and notify the user of the distance and/or time accordingly.

[**0082**] The monitoring mechanism **69** can also be configured to transmit a command to a mapping system **86** (**FIG. 5**) to transmit mapping data to the message manager **82**, if the user's request for travel data or user's preference data in data storage unit **68** includes a request for a mapping. The mapping system **86** may be any system known in the art for supplying a user with mapping data for rendering a display of a map. The command to the mapping system **86** preferably includes the coordinate values of the VCU **15** and the destination. In response, the mapping system **86** transmits to message manager **82** mapping data sufficient for forming a display map with the locations of the VCU **15** and the destination graphically displayed by the display map. The message manager **82** is designed to retrieve the contact information for the user requesting the travel data and is

further configured to determine an address (e.g., an IP address or other type of address indicating how the mapping data is to be routed to user) associated with the user for sending the mapping data. The message manager **82** is then designed to transmit the mapping data to the retrieved address, which preferably identifies a computer at the user's premises **71**. When the user's message device **75** (i.e., a computer in this case) receives the mapping data, the user's computer is configured to render a graphical display depicting a map that shows the vehicle's location relative to the destination on the map.

[**0083**] If desired, the monitoring mechanism **69** can be configured to transmit the coordinate values of the VCU **15** to the mapping system **86** each time the coordinate values are updated. The user's request for travel data can request this feature or the user can indicate this desire in the preference data submitted during activation. Accordingly, for each update, the mapping system **86** is designed to transmit updated mapping data to the user's computer **75** via message manager **82**, as previously described. As a result, the position of the VCU **15** is updated, and the user can monitor the progress of the VCU **15** on the display map rendered by the computer **75**.

[**0084**] Although the preferred embodiment illustrates the requests for travel data by determining the distance the VCU **15** is from a particular location or by determining the time the VCU **15** is from the particular location, other information can be used to indicate the proximity of the VCU **15** from the particular location. For example, the message transmitted to the user in response to a request for travel data can indicate that the VCU **15** is currently at another particular location or landmark, preferably known to the user. Any other information indicating the proximity of the VCU **15** from a particular location can be used in implementing the principles of the present invention.

#### Operation

[**0085**] The preferred use and operation of the tracking system **10** and associated methodology are described hereafter with specific reference to **FIGS. 1, 4 and 5**.

[**0086**] Establishing User Preferences

[**0087**] Initially, a user at remote location **71** establishes communication with the message manager **82** via communications devices **72** and **73**. As used herein, the term "remote location" shall refer to any location off the site of the BSCU **38**. The user can establish communication via a telephone, an e-mail message, the Internet, or any other suitable communication medium. The message manager **82** preferably transmits a list of options to the user, such as whether the user would like to activate a monitoring of a particular vehicle, to retrieve travel data for a particular vehicle or to modify preferences previously selected by the user in an earlier communication session with the message manager **82**. In response, the user selects the activation option.

[**0088**] The message manager **82** then prompts the user to select certain preferences. For example, the message manager **82** can request the user to identify a particular VCU **15** that the user wishes the system **10** to track and a particular destination for the selected VCU **15**. If the user knows the identification number of the VCU **15** or vehicle stop number



used by the system **10** to identify the particular VCU **15** and/or destination, the user can simply transmit a message including this information. As an example, the bus numbers and/or bus stops of commercial and state operated buses are usually available to the public. Therefore, the user may be aware of the bus number and/or stop number of a particular bus that the user wishes to ride, and the user can simply transmit the bus number and/or stop number to the message manager **82**. Also, the user should be able to specify other identifying information such as the day or days of desired travel and the time of day of desired travel.

[0089] In the embodiment where the user is expecting to receive a package from a particular delivery vehicle, the user may be aware of the package number or delivery number used by the system **10**. Therefore, by specifying the package number and the address that the vehicle is to deliver the package, the particular VCU **15** of the vehicle that is to deliver the package can be located by the system **10**. In this regard, a database should be defined by the operators of the system **10** that relates package numbers to VCU **15** numbers.

[0090] Alternatively, if the user is unable to identify a particular vehicle or VCU **15**, the message manager **82** can send information to the user that can be used to help the user identify a particular VCU **15**. For example, the message manager **82** can transmit to the user a list of buses or a list of vehicle stops to the user. The user can use this information to select a particular VCU **15** that is suitable to the user.

[0091] Also, the message manager **82** can send map data from mapping system **86** to the user. The user can then view the map and select points on the map where the user would like to know when the VCU **15** reaches the selected point. The points available for selection can be predetermined, such as scheduled bus stops or other types of vehicle stops, or the user can be allowed to freely select any point on the map. In either case, the mapping logic preferably transmits the coordinates of the selected points to the message manager **82**, which can use this information to not only identify the selected destination, but to also choose an appropriate VCU **15**.

[0092] The message manager **82** also prompts the user to enter contact information such as how the user would like to be notified of an impending arrival of the selected VCU **15** at the selected destination. In response, the user selects a notification medium or combinations of media to be used to notify the user and supplies the necessary information to enable communication of the notification. For example, if the user selects a telephone as a notification medium, then the user provides a telephone number. In addition, if the user selects a computer as the notification medium, then the user provides a suitable address for the computer, such as an e-mail address or IP address. If the user selects a pager as the notification medium, then the user provides a pager number. It should be apparent to one skilled in the art when reading this disclosure that other types of notification media are possible without departing from the principles of the present invention. After receiving the desired contact information from the user, the message manager **82** stores the contact information in the user database **78**.

[0093] The message manager **82** also prompts the user to transmit travel data preferences, which is information pertaining to when the user would like to be notified. For example, the user can select to be notified a certain time

before the selected VCU **15** is to arrive at the selected destination. Also, the user can choose to be notified when the selected VCU **15** is within a certain distance of the destination, and the user can choose to be notified when the selected VCU **15** is a certain number of deliveries or stops away from the destination.

[0094] Since the monitoring mechanism **69** should have access to the travel data preferences in order to determine when a notification is appropriate, the message manager **82** preferably transmits the travel data preferences to the monitoring mechanism **69** along with a unique identification number that identifies the user and a unique identification number identifying the selected VCU **15**. The unique identification number identifying the selected VCU **15** can be the vehicle number entered by the user provided that the number entered by the user identifies the VCU **15** to be monitored. In turn, the monitoring mechanism **69** stores this information as an entry in the travel data storage unit **68**. All of the entries associated with a particular VCU **15** are preferably arranged together (based on the unique identification number) in the travel data storage unit **68**. For example, each entry associated with a particular VCU **15** can be stored within a certain area of memory, or each of the entries can have a pointer pointing to another one of the entries associated with the particular VCU **15**. Therefore, all of the entries associated with a particular VCU **15** can be easily located. Other methods known in the art for categorizing the entries and correlating the entries with a particular vehicle or with the travel data of a particular vehicle are also possible.

[0095] Once the message manager **82** has received the desired contact information and travel data preferences from the user, the communication between the message manager **82** and the user can be terminated. The base station manager **39** should now have sufficient information to monitor the selected VCU **15**. If the user wishes to change the contact information and/or the travel data preferences, the user can reestablish communication with the message manager **82**. The message manager **82** preferably recognizes the user's requests as an update rather than an activation and prompts the user to transmit the new information. In this regard, the message manager **82** can prompt the user for all of the desired contact information and/or preference data, similar to the activation session, and simply replace the previously stored contact information and/or preference data, or the message manager **82** can prompt the user for only the information to be updated and then merely update the previously stored information.

[0096] It should be noted that the information transferred between the user and the message manager **82** can be interfaced with the message manager **82** through a human operator during the activation session or update session described hereinabove and during other sessions, which will be described further hereinbelow. The human operator can prompt the user for certain information through a telephone call or other suitable medium of communication and can enter the response of the user into the message manager **82**.

[0097] Monitoring the Vehicle

[0098] GPS satellites **23** transmit wireless signals **21a-21c** to VCU **15** that can be analyzed through techniques well known in the art to determine a position of the VCU **15** relative to a particular reference point. For example, in GPS systems, the intersection of the Equator and the Prime

Meridian is typically used as the reference point. Sensor 18 receives the signals 21a-21c and determines coordinate values representing the position of the VCU 15 relative to the reference point and transmits these values to vehicle manager 29.

[0099] The vehicle manager 29 stores the coordinate values received from sensor 18. The vehicle manager 29 also stores any other desired information as travel data. For example, the vehicle manager 29 can maintain a list of scheduled stops and/or packages to be delivered. This information can be updated as the stops are reached and/or the packages are delivered. Other types of desirable information may also be monitored by the vehicle manager 29 as travel data.

[0100] At desired times, the vehicle manager 29 transmits, via communications device 44, the stored travel data to cellular network 48. In this regard, the vehicle manager 29 can transmit the travel data continuously or at predetermined times (e.g., every five minutes or predetermined times of the day). Also, the base station manager 39 can transmit a request for an update to vehicle manager 29 via communication devices 44 and 52. In response to this request, the vehicle manager 29 can retrieve the current set of stored travel data and transmit it to the base station manager 39. In addition, the vehicle manager 29 can transmit the travel data to the base station manager 39 when scheduled stops or deliveries are reached or when other predetermined locations are passed.

[0101] Also, the base station manager 39 can assume that the VCU 15 is proceeding along a predetermined route at a predetermined rate, and the vehicle manager 29 can transmit vehicle data only when the VCU 15 is off schedule by a predetermined amount. Accordingly, the base station manager 39 can assume that the proximity of the VCU 15 is changing according to the predetermined schedule unless the base station manager 39 receives travel data from the vehicle manager 29, at which point the base station manager 39 updates the travel data storage unit 68 with the received travel data.

[0102] For example, an entry correlated with the VCU 15 in the travel data storage unit 68 can include a plurality of coordinate values representing locations along the VCU's route of travel. When the monitoring mechanism 69 desires to know the current location of the VCU 15, the monitoring mechanism 69 retrieves one of the coordinate values in the entry, depending on the amount of time that has elapsed since the VCU 15 began the route. For example, each successive coordinate value in the entry can correspond to the assumed location of the VCU 15 after a predetermined time interval (e.g., five minutes) of travel since the previous assumed location of the VCU 15. Therefore, the first coordinate value represents the starting point of the route. The second coordinate value represents the assumed location of the VCU 15 after the predetermined time interval (e.g., five minutes) from the start of the trip, the third coordinate value represents the assumed location of the VCU 15 after two times the predetermined time interval (e.g., ten minutes) of travel from the start of the trip, and so on.

[0103] When the vehicle associated with VCU 15 starts its route of travel, the current time period from a clock (e.g., an internal clock associated with BSCU 38) is stored into the entry in the travel data storage unit 68 correlated with the

VCU 15. Therefore, the amount of time elapsed since the start of the route can be determined by comparing the current time period with the start time period stored in the travel data storage unit 68. To retrieve the current coordinate value of the VCU 15, the monitoring mechanism 69 retrieves the coordinate value corresponding with the amount of time that has elapsed since the start of the route. For example, assuming that the predetermined time interval between assumed locations is five minutes, the monitoring mechanism 69 retrieves the second coordinate value if approximately five minutes have elapsed since the start of the route and retrieves the third coordinate value if approximately ten minutes have elapsed since the start of the route.

[0104] However, if the VCU 15 is off schedule by a predetermined amount (e.g., one mile or two minutes from the assumed location or, in other words, is outside of a predetermined proximity from said assumed location), then the VCU 15 transmits its true coordinate values to the monitoring mechanism 69. In response, the monitoring mechanism 69 stores the true coordinate values in the entry corresponding with the VCU 15. Therefore, if a true coordinate value has been stored in the entry within the last five minutes (or some other threshold amount), then the monitoring mechanism 69 retrieves the last stored true coordinate value from VCU 15 instead of one of the assumed coordinate values.

[0105] The vehicle manager 29 can determine whether or not it is off schedule by comparing the coordinate values of the VCU's true location, as indicated by the GPS sensor 18, against the coordinate values of an assumed location. In this regard, the vehicle manager 29, like the monitoring mechanism 69 described hereinabove, maintains a list of coordinate values representing locations along the VCU's route of travel and determines the amount of time elapsed since the start of the route via a clock (such as an internal clock associated with the VCU 15). Like the monitoring mechanism 69, the vehicle manager 29 can retrieve the coordinate values of the assumed location of the VCU 15 depending on the amount of time elapsed since the start of the trip. Therefore, the coordinate values retrieved by the vehicle manager 29 for comparison with the current coordinate values indicated by the GPS sensor 18 represent the current location of the VCU 15, assuming the VCU 15 is on schedule. If the coordinate values of the assumed location differ from the coordinate values of the GPS sensor 18 by a predetermined amount, then the VCU 15 is off schedule, resulting in the transmission of the VCU's true location to monitoring mechanism 69.

[0106] Alternatively, the VCU 15 can transmit a value (such as a time period or distance) that the VCU 15 is off schedule, when the VCU 15 determines that it is off schedule by the predetermined amount. Therefore, monitoring mechanism 69 can determine the VCU's proximity by comparing the transmitted value against the assumed location of the VCU 15. When the VCU 15 transmits a time value (e.g., a value indicating the vehicle is off schedule by a certain time, such as two minutes for example), the monitoring mechanism 69 can determine an approximate arrival time at the selected destination by simply combining (i.e., adding or subtracting) the time indicated by the transmitted value with the total time that the route should take to travel. In this situation, the monitoring mechanism 69 does not need to keep track of the assumed locations of the VCU 15. Instead,

the monitoring mechanism 69 can simply assume the VCU 15 will arrive at the destination or notification point at a predetermined time (based on the time of start and the total estimated time to reach the destination or the notification point) unless a time value is received. When a time value is received, the monitoring mechanism 69 can update the predetermined time based on the time value. Therefore, when the predetermined time (as updated) expires, notification should be sent to the user. It should be noted that other references and methodologies may be employed to determine when to transmit travel data from vehicle manager 29 to base station manager 39.

[0107] When the cellular network 48 receives travel data from communications device 44, the cellular network 48 preferably transmits the travel data to base station manager 39 via PSTN network 55 and communication device 52. Base station manager 39 receives the travel data and monitors the vehicle's location based on the travel data.

[0108] In this regard, the monitoring mechanism 69 upon receiving travel data from VCU 15 stores the travel data, including the coordinate values of the VCU 15, into each entry of the travel data storage unit 68 that is configured to contain travel data and is associated with the VCU 15. After accessing an entry for storing travel data, the monitoring mechanism 69 compares the current travel data (either received from the VCU 15 or selected from a predetermined or assumed set of travel data, as described hereinabove) with the user preferences stored in the entry in order to determine whether a notification should be sent to the user. Alternatively, the monitoring mechanism 69 can be configured to periodically poll each entry in the travel data storage unit 68 and to compare the travel data in each entry with the corresponding preference data to determine which users should receive a notification.

[0109] In analyzing each entry, the monitoring mechanism 69 preferably subtracts the current coordinate values in the accessed entry of the VCU 15 with the coordinate values previously stored in travel data storage unit 68 that indicate the destination location selected by the user. If the resulting value is less than a predetermined value, then the monitoring mechanism 69 sends a notification command to message manager 82 instructing the message manager 82 to notify the user of the impending arrival of the VCU 15. This predetermined value corresponds to the distance that the VCU 15 should be from the destination before a notification is sent to the user. Preferably, this predetermined value is calculated from or is included in the preference data supplied by the user during activation or during an update to the activation.

[0110] The monitoring mechanism 69 can also send the notification command to the message manager 82 based on the estimated time the VCU 15 is from the destination. After calculating the value indicating the distance of the VCU 15 from the destination, the monitoring mechanism 69 can estimate how long it will take for the VCU 15 to reach the destination by assuming that the VCU 15 can travel certain distances in a certain amount of time. In order to increase the accuracy of the system 10, the monitoring mechanism 69 can vary the time for the distances according to the type of traffic that is typically encountered at the vehicle's location and route of travel. If traffic conditions are usually congested along the VCU's route, then the monitoring mechanism 69 can assume higher rates of time. Furthermore, if the travel

data indicates that the VCU 15 has a number of vehicle stops prior to reaching the destination, the monitoring mechanism 69 can factor in a delay time for each stop depending on the type of the stop.

[0111] Once the monitoring mechanism 69 determines the VCU's expected time of arrival at the destination, the monitoring mechanism 69 can determine whether the user should be notified based on this estimated time. If the estimated time is less than a predetermined value indicating the desired estimated time of arrival chosen by the user, then the monitoring mechanism 69 sends the notification command to the message manager 82.

[0112] The message manager 82, in response to the notification command from the monitoring mechanism 69, retrieves the contact information from user database 78 indicating how the user desires to be notified. Utilizing the contact information, the message manager 82 then sends a message to the user at remote location 71. The monitoring mechanism 69 preferably includes certain travel data in the notification command, such as the VCU's location. Consequently, the message manager 82 is able to include this travel data with the message sent to the user. For example, the message may indicate that the VCU 15 (and, therefore, that the vehicle attached to the VCU 15) is a certain amount of time or distance from the destination or the message may indicate the VCU's specific location, perhaps with reference to street names and/or street blocks.

[0113] If the contact information indicates that the user wishes to have map data sent to a computer at the remote location 71, the message manager 82 sends a request for map data to monitoring mechanism 69. In response, the monitoring mechanism 69 sends to the mapping system 86 the necessary data (e.g., the coordinates of the VCU 15 and the destination) for the mapping system 86 to transmit the appropriate mapping data. The mapping system 86 transmits the mapping data to message manager 82 which again utilizes the contact information retrieved from user data base 78 to communicate the mapping data to the appropriate message device 75 at remote location 71. The message device 75 then displays the mapping data in graphical form so that the user can see the vehicle's location relative to the destination within the map graphically displayed by the message device 75.

[0114] The notification message sent to the user indicates the impending arrival of the VCU 15 at the destination previously selected by the user. Accordingly, the user can prepare for the arrival of the VCU 15 knowing approximately how long it should take for the VCU 15 to arrive at the destination.

[0115] Requesting Travel Data

[0116] During the monitoring process described hereinabove, the user can discover the status of the VCU 15 or of the vehicle attached to the VCU 15, on demand, by contacting the base station manager 39 and requesting information pertaining to the travel data stored in the travel data storage unit 68. In this regard, the user establishes communication with the message manager 82 (FIG. 5) via communications devices 72 and 73. The medium used for communication can be any suitable medium known in the art (e.g., telephone, e-mail, Internet, cellular phone, etc.). The preferred operation of the present invention will be dis-

cussed hereinafter with the user establishing communication via telephone, although other media of communication are also suitable.

[0117] After the telephone connection is established, the message manager **82** prompts the user with a series of recorded questions or options in order to determine the user's request. The user responds to these prompts through touch-tone signaling which is well known in current telephony communications systems. Initially, the message manager **82** prompts the user to indicate whether the call is an activation, an update of an activation, or a request for travel data. The user selects the appropriate touch-tone number to indicate that the user is requesting travel data.

[0118] The message manager **82** receives and interprets the touch-tone signal to determine that the user is requesting travel data. In response, the message manager **82** prompts the user to transmit an identification number of the VCU **15** of concern for the user. This prompt can include information to aide the user in selecting a VCU **15**. The user responds by transmitting a series of touch-tone signals that indicate the identification number or other unique data of the particular VCU **15** of concern for the user. The message manager **82** receives and interprets the touch-tone signals and determines which VCU **15** is selected by the user based on the received touch-tone signals.

[0119] The message manager **82** can then, if desired, prompt the user to indicate which travel data the user desires to know. For example, it is likely that the user may want to know how far the VCU **15** is from the destination or how long it should take the VCU **15** to arrive at the destination. However, the user may want to know other information, such as, but not limited to, how many vehicle stops the VCU **15** encounters enroute or the type of vehicle that is enroute, etc. The user responds with touch-tone signals, as appropriate, to indicate what information the user is requesting.

[0120] The message manager **82** then transmits a request for data to the monitoring mechanism **69**. The request for data includes the unique identification number used to identify the VCU **15**, as well as any other information needed by the monitoring mechanism **69** to provide the desired information. For example, the message manager **82** may also transmit information indicating that the user wishes to discover information pertaining to the type of vehicle that is enroute. The monitoring mechanism **69**, in turn, retrieves the desired travel data from the travel data storage unit **68**.

[0121] After retrieving the desired travel data, the monitoring mechanism **69** transmits the retrieved data to the message manager **82**, which communicates the data information to the user in a message transmitted to the user. The message can include the travel data retrieved by the monitoring mechanism **69** or can be formed to indicate the information contained by the travel data. For example, when communication is over a telephone connection, a recorded message can be formed by the message manager **82** indicating the distance the VCU **15** is from the destination based on the travel data sent to the message manager **82**. When communication is via modem signals, travel data can be transmitted to the user by the message device **82**. In either case, the contents of the message is based on the travel data retrieved by the monitoring mechanism **69**. Since a communications line between the user and message manager **82** is already established in order for the user to make the request for travel data, the message manager **82** preferably transmits the data to the user over the established commu-

nication connection. When the user desires to receive map data (indicated by the selection of an option during the request for travel data or by the user preferences stored in the travel data storage unit **68**), the monitoring mechanism **69** transmits a map generation command and travel data of the selected VCU **15** to mapping system **86**. Mapping system **86** then transmits graphical data to message manager **82**.

[0122] Message manager **82** communicates the graphical data to message device **75** which is capable of generating a map display based on the graphical data. In order to communicate this data, the message manager **82** retrieves the user contact information from the user database **78**. The contact information indicates the address (and/or other pertinent information) of the message device **75** so that the message manager **82** knows where to transmit the graphical data. By viewing the map display generated by the message device **75**, the user can determine the location and estimated time of arrival of the VCU **15**. The map display preferably shows the intended route of travel by the VCU **15** and any scheduled vehicle stops along the route.

[0123] Since the system **10** stores certain travel information in order to monitor the travel of a VCU **15** for providing an advance notification of an impending arrival of a VCU **15**, the system **10** can also provide an easy and low cost way for a user to access information pertaining to the VCU **15**, on demand. Accordingly, the user does not have to wait for preselected preferences to be satisfied before learning of the VCU's (and, therefore, the vehicle's) location and/or estimated time of arrival. The user can monitor the travel of the VCU **15** at any time by submitting a request for travel data and can, therefore, know the location and status of the VCU **15** before receiving an advance notification signal that is based on comparisons between the VCU's travel data and the user's preselected preferences. As a result, the user can better prepare for an arrival of any particular VCU **15** or vehicle attached to the VCU **15** associated with the system **10**.

[0124] It should be apparent to one skilled in the art that at least a portion of the functionality of the data manager **67** can be implemented by the vehicle manager **29**, if desired. In this regard, preference data and/or travel data for the VCU **15** can be store in the computer system **31a** coupled to the VCU **15**. Accordingly, it is possible for the vehicle manager **29** to determine when to transmit a notification to the user and to transmit a notification to the user via communication device **52** and **72**. However, such an implementation can increase the complexity and cost of the system **10** and is therefore generally not desirable.

[0125] In concluding the detailed description, it should be noted that it will be obvious to those skilled in the art that many variations and modifications may be made to the preferred embodiment without substantially departing from the principles of the present invention. All such variations and modifications are intended to be included herein within the scope of the present invention, as set forth in the following claims.

Now, therefore, the following is claimed:

1. An advance notification method, comprising the steps of:

establishing communication with a remote communication device;

receiving data from said remote communication device;

identifying a notification time or notification time period based on said data;

monitoring travel of a vehicle in relation to a vehicle stop;

determining, based on said monitoring step, whether said vehicle has reached said notification time or is within said notification time period from said vehicle stop; and

establishing communication with said remote communication device or another remote communication device at said notification time or when said vehicle is within said notification time period from said vehicle stop.

**2.** A method to be performed by a base station computer system in an advance notification system, comprising the steps of:

establishing communication between a base station computer system and a remote communication device;

receiving at the base station computer system notification time data from said remote communication device;

monitoring travel of a vehicle in relation to a vehicle stop; and

establishing communication between said base station computer and said remote communication device or another remote communication device at a particular notification time before said vehicle arrives at said vehicle stop, based upon said notification time data that was received by said base station computer system from said remote communication device.

**3.** An advance notification system, comprising:

means for establishing communication with a remote communication device; means for receiving data from said remote communication device;

means for identifying a notification time or notification time period based on said data;

means for monitoring travel of a vehicle in relation to a vehicle stop;

means for determining, based on said monitoring step, whether said vehicle has reached said notification time or is within said notification time period from said vehicle stop; and

means for establishing communication with said remote communication device or II another remote communication device at said notification time or when said vehicle is within said notification time period from said vehicle stop.

**4.** A base station computer system in an advance notification system, comprising:

means for establishing communication between a base station computer system and a remote communication device;

means for receiving at the base station computer system notification time data from said remote communication device;

means for monitoring travel of a vehicle in relation to a vehicle stop; and

means for establishing communication between said base station computer and said remote communication device at a particular notification time before said vehicle arrives at said vehicle stop, based upon said notification time data that was received by said base station computer system from said remote communication device.

\* \* \* \* \*