



US 20090017699A1

(19) **United States**

(12) **Patent Application Publication**
Breen IV

(10) **Pub. No.: US 2009/0017699 A1**

(43) **Pub. Date: Jan. 15, 2009**

(54) **IN-LINE PUSH-IN WIRE CONNECTOR**

Publication Classification

(76) **Inventor: Dennis M. Breen IV**, West Chicago, IL (US)

(51) **Int. Cl. H01R 11/09** (2006.01)

Correspondence Address:
COOK ALEX LTD
SUITE 2850, 200 WEST ADAMS STREET
CHICAGO, IL 60606 (US)

(52) **U.S. Cl. 439/723**

(21) **Appl. No.: 12/167,854**


(57) **ABSTRACT**

(22) **Filed: Jul. 3, 2008**

Related U.S. Application Data

(60) **Provisional application No. 60/948,585**, filed on Jul. 9, 2007.

A push-in wire connector has enclosure made of left and right housings. Each housing has a wire entry port and a wire receptacle box aligned with the port of the other housing. The wire entry ports face in opposite directions. A terminal is mounted in the housing and includes a busbar which is tangentially mounted to both wire ports. A spring member has spring fingers for biasing inserted conductors into engagement with opposite sides of the busbar.






Fig. 1




Fig. 7




Fig. 3




Fig. 6





Fig. 10




Fig. 8














Fig. 9








Fig. 20




Fig. 23




Fig. 24

Fig. 21

Fig. 22




Fig. 25




Fig. 26




Fig. 27




Fig. 28




Fig. 31




Fig. 30




Fig. 29




Fig. 32

Fig. 33




Fig. 34




Fig. 35




Fig. 36

IN-LINE PUSH-IN WIRE CONNECTOR

CROSS-REFERENCE TO RELATED APPLICATION

[0001] This application claims the benefit of U.S. Provisional Application No. 60/948,585, filed Jul. 9, 2007, the disclosure of which is hereby incorporated herein by reference.

BACKGROUND OF THE INVENTION

[0002] This invention relates to push-in wire connectors. Push-in connectors operate, as the name implies, by simply pushing a stripped end of two or more wires or conductors into the connector. Once the wires are pushed into the connector no closing, crimping, twisting, insulation displacement or other manipulation of the connector is required to finish the connection, making the push-in connector advantageous from the standpoint of time needed to install it. The push-in connector must perform several tasks including electrically isolating its conductors from the surrounding environment, retaining the conductors in the connector, and providing good electrical conductivity between the conductors.

[0003] The electrical isolation function is typically performed by a housing made of electrically insulating material. The housing has a generally hollow interior. Openings in the housing provide access to the interior for the stripped ends of two or more electrical conductors. Once inside the housing the bared ends of the conductors are fully surrounded by the insulating housing.

[0004] The function of providing electrical conductivity is performed by an electrically-conductive shorting member. The shorting member, often called a busbar, is inside the housing and is disposed so as to be engageable with all conductors inserted into the housing. The shorting member provides a conductive path between all inserted conductors. Since the primary job of the busbar is conduction, it is typically made of a highly conductive material such as copper or tin-plated copper. But even a highly conductive busbar will not provide good conductivity between conductors if those conductors are not held firmly in contact with the busbar. Thus it is common to include a spring member which works in concert with the busbar to hold the conductors firmly against the busbar. Various arrangements of the spring member are possible, including building it into the housing, building it into the busbar, or making it a separate component in the interior of the housing. In any case, the spring member urges all conductors into solid mechanical and electrical engagement with the shorting member.

[0005] The function of holding the conductors in the housing is performed by a retention member that engages the ends of the inserted conductors and prevents axial retraction from the housing. As in the case of the spring member, the retention member could be built into the housing. Alternately, the retention member and spring member can be configured as a combined unit inside the housing. In either case the retention member grasps the conductors and prevents unintentional removal of the conductors from the housing. In some embodiments the retention member is releasable so that conductors may be selectively removed from the housing without damage to any of the components. In other embodiments where it is desired that the conductors not be removed from the connector under any circumstances the retention member is intentionally made to be non-releasable.

[0006] As just mentioned, the retention member is often configured in combination with the spring member to apply a force that urges the inserted conductor into contact with the shorting member and prevents retraction of the conductor. A common configuration is to have a resilient metal retention member having spring fingers formed therein. As a conductor is inserted into the housing it engages a spring finger and causes it to flex away from its rest position. The resulting deflection of the spring finger generates a compressive force on the conductor that presses it into solid contact with the busbar. The spring finger is angled to permit insertion of the conductor past the finger in one direction but withdrawal of the conductor in the opposite direction is not permitted due to the self-locking configuration of the spring finger. Thus, engagement of the spring finger with the conductor provides the dual functions of pressing the conductor into the busbar and preventing withdrawal of the conductor from the housing.

[0007] The pressing of the conductor into the busbar, of course, requires a stable structure for resisting the compressive force of the spring finger. While firm support for the busbar can be provided either by the spring member or the housing, or both, a problem can arise when the connector is used with stranded wire. Stranded wire tends to flatten out or splay when subjected to the compressive force of the spring finger. Since the compressive and resistive forces of the spring finger are only created upon deflection of the spring finger, the splaying of the stranded wire reduces or even eliminates this deflection which can then defeat the dual purpose of the spring finger. The present invention addresses this problem.

[0008] Another problem with some conventional push-in wire connectors is that while they are arranged to receive various numbers of wires, the connector housings are arranged to receive all incoming wires from the same direction. In other words, the openings in the connector housings all face the same way. If there are wires approaching the connector from opposite directions, the ends of at least some of them have to be bent back 180° to enable the wire to enter the connector. This requires additional time to install the connector. U.S. Pat. No. 6,132,238 is an example of this type of connector. However, U.S. Pat. Nos. 6,093,052 and 4,133,595 are examples of connectors that have wire ports facing different directions.

[0009] Other problems with existing push-in connectors include the fact that they tend to be rather bulky. This makes them more difficult to install in tight quarters. It also uses extra material in manufacture, thereby raising costs. A related problem is the amount of comparatively costly metals used in prior art push-in connectors. Some connectors have complicated contacts or terminals therein made of copper and the like. These contacts are often made from blanks by making multiple folds or bends, sometimes leading to overlapping layers of material. The blanks themselves have complex shapes that require stamping from sheets in a manner that leads to excessive generation of scrap. Many of these contact designs are wasteful of these materials, thereby needlessly increasing the overall cost of the connector.

SUMMARY OF THE INVENTION

[0010] The present invention concerns a push-in wire connector having an improved enclosure made of left and right housings which are permanently joined together. Each housing has a port facing one direction and a wire-receiving receptacle box facing in a different direction. Each wire-receiving

receptacle box is aligned with the wire port of the opposite housing and thus faces in a different direction from the wire entry port of its housing.

[0011] A terminal assembly is mounted in the enclosure. The terminal assembly includes a spring attached to a busbar. The spring has spring fingers on opposite sides of the busbar. The spring fingers are aligned with a wire port and engage conductors inserted into the enclosure to urge them into contact with the busbar. The busbar has a top face and a bottom face. The top face and bottom face also each define an entry edge, an exit edge, and at least one wire-crossing axis extending from the entry edge to the exit edge. The entry edges of the top and bottom faces are on opposite sides of the busbar.

[0012] The wires entering the connector through opposing ports overlap to permit the shortest possible enclosure. The terminal design permits optimum use of metal materials, thereby minimizing the cost of the connector. The busbar is disposed at an angle of about 17 degrees to the axis of the wire entry ports. Thus, the busbar somewhat interferes with the path of the wire to create a bump/angled surface for the wire to pass over as the spring member presses the wire into the bump or angled surface.

BRIEF DESCRIPTION OF THE DRAWINGS

- [0013] FIG. 1 is a perspective view of the push-in connector of the present invention.
- [0014] FIG. 2 is a section taken through the longitudinal center of FIG. 1.
- [0015] FIG. 3 is a side elevation view of the right housing.
- [0016] FIG. 4 is a top plan view of the right housing.
- [0017] FIG. 5 is a bottom plan view of the right housing.
- [0018] FIG. 6 is a right end elevation view of the right housing.
- [0019] FIG. 7 is a left end elevation view of the right housing.
- [0020] FIG. 8 is a section taken along line 8-8 of FIG. 6.
- [0021] FIG. 9 is a section taken along line 9-9 of FIG. 6.
- [0022] FIG. 10 is a section taken along line 10-10 of FIG. 6.
- [0023] FIG. 11 is a side elevation view of the left housing.
- [0024] FIG. 12 is a top plan view of the left housing.
- [0025] FIG. 13 is a bottom plan view of the left housing.
- [0026] FIG. 14 is a right end elevation view of the left housing.
- [0027] FIG. 15 is a left end elevation view of the left housing.
- [0028] FIG. 16 is a section taken along line 16-16 of FIG. 14.
- [0029] FIG. 17 is a section taken along line 17-17 of FIG. 14.
- [0030] FIG. 18 is a section taken along line 18-18 of FIG. 14.
- [0031] FIG. 19 is a section taken along line 19-19 of FIG. 14.
- [0032] FIG. 20 is a perspective view of a terminal assembly.
- [0033] FIG. 21 is an end elevation view of the terminal assembly of FIG. 20.
- [0034] FIG. 22 is a side elevation view of the terminal assembly.
- [0035] FIG. 23 is a view looking along line 23-23 of FIG. 22.
- [0036] FIG. 24 is a section taking along line 24-24 of FIG. 21.
- [0037] FIG. 25 is a perspective view of an alternate embodiment, which is similar to FIG. 1 but has six wire ports.

[0038] FIG. 26 is a perspective view a further alternate embodiment showing a 3-pole, 2-port in-line push-in connector.

[0039] FIG. 27 is a section through one of the poles of the connector of FIG. 26.

[0040] FIG. 28 is a perspective view of an alternate embodiment of a terminal assembly.

[0041] FIG. 29 is a section through the terminal assembly of FIG. 28, as generally indicated by the line 29-29 of FIG. 30.

[0042] FIG. 30 is a side elevation view of the busbar of the FIG. 28 terminal assembly.

[0043] FIG. 31 is a top plan view of the busbar of the FIG. 28 terminal assembly.

[0044] FIG. 32 is a perspective view of an alternate embodiment of a housing.

[0045] FIG. 33 is an exploded perspective view of the housing of FIG. 32.

[0046] FIG. 34 is a perspective view of a further alternate embodiment of a housing.

[0047] FIG. 35 is an exploded perspective view of the housing of FIG. 34.

[0048] FIG. 36 is a side elevation view of the housing of FIG. 34.

DETAILED DESCRIPTION OF THE INVENTION

[0049] FIG. 1 illustrates the push-in connector 10 of the present invention, The push-in connector has an enclosure shown generally at 12. In this embodiment the enclosure is formed in two pieces and includes a right housing 14 and a left housing 16. Each housing has a wire entry port facing one direction and a wire receptacle box facing the other direction. A test probe opening is formed next to the wire entry port.

[0050] Details of the right housing 14 are seen in FIGS. 2-10. As seen in FIG. 3, the housing generally has a lower section at the left which merges with a central section that in turn joins an upper section on the right. The lower section is formed by a generally U-shaped wall 18. Wall 18 is bounded at the central section by locking apertures 20A, 20B. The central section includes a wire receptacle box 22 which has an end wall 24 and a U-shaped guide wall 26. These walls define a hollow chamber which receives the end of a wire inserted into the connector. The guide wall 26 slopes downwardly to the left, as seen in FIG. 8, to help direct an inserted wire into the box 22. The left end of the guide wall 26 terminates at an angled spring support face 28. The top lands of the guide wall form a pair of laterally-spaced ledges 30. It can be seen in FIG. 8 that the wire receptacle box 22 opens or faces to the left as seen in that figure.

[0051] Continuing with FIG. 8, above the guide wall 26 and adjoining both of the top lands of the U-shaped wall 18 there is an S-shaped external flange 32. This flange interfits with a corresponding flange of the left housing, as will be explained below. The flange 32 merges with the upper section that includes a generally oval shell 34. Inside the left end of the shell there is a second spring support face 36, as best seen in FIG. 7. The right end of the shell is covered by an end wall 38. A wire entry port 40 is defined by a wire tube 42. The interior end of the tube 42 is tapered, as shown in FIG. 8, and adjoins a wire support block 44. The wire support block is just above the ledges 30. A test probe opening 46 is defined by a test tube 48 (FIG. 6).

[0052] FIGS. 11-19 illustrate details of the left housing 16. A main body portion 50 has a wire receptacle box 52 protruding upwardly from the body portion. The wire receptacle has

an end wall **54** (FIG. 16). An arcuate abutment section **56** extends from the wire receptacle box. An internal flange **58** is attached to the body portion **50** and the abutment section **56**. The internal flange is indented somewhat from the outer edges of the body and abutment, as best seen in FIG. 14. The flange is somewhat S-shaped in the side elevation view of FIG. 11 to match the shape of the external flange **32**. A curved skirt **60** extends below the body portion. Two arms **62** extend forwardly from the skirt **60**. The arms terminate at outwardly facing hooks **64**.

[0053] When the housings are joined the internal flange **58** fits inside the external flange **32** of the right housing, with the external flange abutting the end faces of the abutment section and the body portion. The skirt **60** and arms **62** fit inside the U-shaped wall **18** of the right housing. The hooks **64** slip into the locking apertures **20A**, **20B** to engage the ends of wall **18** and hold the two housings together.

[0054] A U-shaped cutout **66** (FIG. 15) is defined in an end wall **68** of the main body portion. Just above the cutout **66** is a wire entry port **70** which extends through the main body portion. The interior of the body has a tapered ring at **72** that defines the inner end of the wire port. The right end face of the ring defines a spring support face **74**. A wire support block **76** is attached to the upper edge of the tapered ring **72**. The wire support block **76**, the upper portion of the ring **72**, the wire receptacle box **52** and the end wall **54** define a hollow chamber which receives the end of a wire inserted into the connector. Underneath the internal flange there is a central rib **78** and two angled spring support ribs **80**. Ribs **80** join ledges **82**. The ledges and the wire support block **76** assist in positioning the busbar, as will be described below.

[0055] Turning to FIGS. 20-24 a terminal assembly **84** is shown. The terminal assembly comprises a busbar **86** supported on a spring member **88**. The spring member includes a foot **90** joined at a first fold line to a first, upstanding leg **92** and at a second fold line to a second, depending leg **94**. The foot has a pair of spaced bands **96**. The bands have apertures (not shown) for receiving rivets of the busbar as will be described below. Each leg **92**, **94** includes a U-shaped slit which defines a spring finger **98**. The spring finger is integrally connected to the leg at one end and has a free end **100** at its opposite end. As seen in FIGS. 22 and 24 the spring fingers **98** are bent out of the plane of the legs **92**, **94**. The free end **100** may be further angled somewhat relative to the remainder of the finger to provide an optimum angle for gripping a wire inserted under the spring finger. The spring member **88** is preferably formed of a resilient metal such as stainless steel.

[0056] When installed in the enclosure, the spring finger **92** is opposite the wire entry port **40** so that a wire inserted into the right housing will encounter the spring finger and move it upwardly as the wire enters the enclosure. The free end of the spring finger **92** will press on the conductor, preventing it from pulling out of the housing and pushing it into firm engagement with the top face of the busbar **86**. Spring finger **94** is similarly situated opposite the wire entry port **70**. A wire inserted into the left housing port **70** will encounter spring finger **94** and move it downwardly. The free end of the spring finger **94** will retain the conductor in the enclosure and bias it into engagement with the bottom face of the busbar.

[0057] Details of the busbar **86** will be described. The busbar is a generally rectangular member made of tin-plated copper. The busbar defines a thickness between a top face **102** and a bottom face **104**. It will be understood that the terms 'top' and 'bottom' are used herein for reference purposes only, as there is nothing inherent in the orientation of the busbar that would make one side or the other of the busbar a

top or bottom portion. The top face of the busbar **86** further defines an entry edge **106A**, an exit edge **108A**, and a wire-crossing axis **110A** extending from the entry edge to the exit edge. As used herein the entry edge will be considered the edge of the busbar first crossed by a conductor entering the housing and the exit edge will be considered the edge of the busbar last crossed by an entering conductor. The wire-crossing axis is the location where a conductor will lie, given the construction of the enclosure and the busbar's position in the enclosure. The bottom face of the busbar **86** similarly defines an entry edge **106B**, an exit edge **108B**, and a wire-crossing axis **110B** extending from the entry edge to the exit edge. It will be noted that the entry edges **106A**, **106B** are on opposite edges of the busbar.

[0058] The busbar **86** is attached to the foot **90** of the spring member **88** by means of rivets **112** extending into the apertures of the foot described above. The rivets **112** on the top face **102** may be formed by upsetting a portion of the busbar. It will be understood that other methods for attaching the busbar to the spring member could be used, such as crimping, adhesives or the like. Alternatively, the busbar may not be fixed to the spring at all. Rather, it could be supported by the housing.

[0059] As shown in FIGS. 22 and 24, the busbar has a wire-receiving pocket **114** extending below each face and on each of the wire-crossing axes. There is also a wire-engaging protrusion **116** extending above each face on each of the wire-crossing axes. The pockets **114** and protrusions **116** may be formed by coining the busbar, which creates a pocket on one face and a corresponding protrusion on the other face of the busbar. It can be seen that the pockets **114** and protrusions **116** form a serpentine path for the conductor to traverse over the face of the busbar. This configuration helps the spring finger **98** retain the conductors in the housing. The pockets **114** surround the conductor at least partially on three sides to prevent splaying of a stranded wire. Further details of this construction are explained in U.S. patent application Ser. No. 11/763,096, filed Jun. 14, 2007, the disclosure of which is incorporated by reference herein.

[0060] FIG. 2 illustrates the assembled connector and how the parts cooperate. As noted above, the external flange **32** of the right housing fits over the internal flange **58** of the left housing and adjoins the abutment section **56** and body portion **50** of the left housing. The hooks **64** hold the two housings together. The spring member **88** is held fixed between the housings. The busbar **86** is restrained laterally by the support block **76** on the left and the support block **44** on the right. Ledges **82** and **30** engage the busbar to prevent any up or down movement thereof. The upstanding leg **92** of the spring member is trapped between spring support face **36** of the right housing and spring support ribs **80** of the left housing. The depending leg **94** is trapped between the spring support face **28** of the right housing and the spring support face **74** of the left housing.

[0061] The use, operation and function of the connector are as follows. The stripped end of a wire is inserted into the wire entry port **40** of the right housing. It encounters the spring finger **98** of leg **92** and pushes the finger upwardly as it continues entry into the enclosure. The end of the conductor enters the wire receptacle box **52** of the left housing, which anchors it in position and prevents splaying of a stranded conductor. The stripped end of a second wire is inserted into the wire entry port **70** of the left housing. It encounters the spring finger **98** of leg **94** and pushes the finger downwardly as the conductor continues entry into the enclosure. The end

of the conductor enters the wire receptacle box 22 of the right housing, which anchors it in position and prevents splaying of a stranded conductor.

[0062] It will be noted that the wire entry ports and busbar are arranged such that the busbar is disposed at about a 17° angle to the axes of the wire ports. That is, the busbar is at an angle of about 17° and somewhat interferes with the path of the wire to create a bump/angled surface for the wire to pass over as the spring member presses the wire into the bump or angled surface. This enhances both the holding force of the spring and the electrical contact between the busbar and conductor. The busbar is located between the bottom of port 40 and tangential to the top of port 70. Accordingly, the conductors will contact the busbar on opposite sides thereof. This affords an efficient use of the busbar material and allows the conductors to overlap one another, enabling a smaller length enclosure. Also, formation of the wire port in one housing and the wire receptacle box in the other housing further contributes to the compact design of the enclosure. The housing construction also permits the elimination of any kind of cap for the back ends, i.e., the wire entry ends, of the housings. This is because the terminal assembly is held between the housings so a separate retention cap is not needed.

[0063] FIG. 25 illustrates a six-port version of an in-line push-in connector 118. The housing and terminal construction is essentially the same as in the previous embodiment, with the previous features being duplicated to add two additional wire ports to each housing and two additional spring fingers on both the top and bottom of the spring member.

[0064] FIGS. 26 and 27 illustrate a further alternate embodiment. This is a 3-pole, two-port in-line push-in connector 120. The construction of each pole is essentially similar to that of the FIG. 1 embodiment. Thus, there are left and right housings 122, 124. Each housing has a wire entry port 126 and a wire receptacle box 128 opposite the wire entry port of the other housing. The electrical terminal 130 is largely the same as terminal 84. Three separate terminals 130 are provided, each accommodating two wires. Thus, this connector makes separate connections between three pairs of wires. The poles are arcuately spaced 120° apart from one another in a plane transverse to the longitudinal axis. This arrangement allows the placement of three separate poles in a compact structure. Further details of this arcuate spacing are shown and described in U.S. patent application Ser. No. 11/774, 858m filed Jul. 9, 2007, the disclosure of which is incorporated herein by reference.

[0065] FIGS. 28 and 29 illustrate an alternate embodiment of an electrical terminal assembly 132. This terminal is largely similar to terminal 84 but with some differences in the relationship between the busbar and the spring. Thus, terminal assembly 132 has a busbar 134 supported on a spring member 136. The spring member includes a foot 138 joined to an upstanding leg 140 and a depending leg 142. The foot has a pair of spaced bands 144. A U-shaped slit in each leg defines a spring finger 146. The spring finger has a free end 148.

[0066] The busbar 134 has a top face 150 and a bottom face 152. As before, the terms 'top' and 'bottom' are used herein for reference purposes only. As seen in FIGS. 30 and 31, the top face 150 of the busbar 134 further defines an entry edge 154A, an exit edge 156A. Again, the entry edge will be considered the edge of the busbar first crossed by a conductor entering the housing and the exit edge will be considered the edge of the busbar last crossed by an entering conductor. The bottom face of the busbar 152 similarly defines an entry edge 154B, and an exit edge 156B. It will be noted that the entry edges 154A, 154B are on opposite edges of the busbar.

[0067] The busbar 134 is attached to the foot 138 of the spring member 88 by means of rivets 158 extending into apertures in the foot.

[0068] As shown in FIGS. 28-31, the busbar has a wire-receiving pocket 160 extending below each face. There is also a wire-engaging protrusion 162 extending above each face. The pockets 160 and protrusions 162 may be formed by coining the busbar, which creates a pocket on one face and a corresponding protrusion on the other face of the busbar. The pocket on one face is aligned with the protrusion on the other face, making the faces generally symmetrical.

[0069] FIGS. 32 and 33 illustrate an alternate embodiment of the housing. This is a two-part, snap-fit housing 164 which is generally the same as FIGS. 1-19 but with a different latching arrangement. Thus, there are left and right housings 166, 168. Left housing has a top wire entry port or opening 170 and a wire receptacle box 172. Right housing has a bottom wire entry port 174 and a wire receptacle box 176 opposite the top wire entry port 170 of the other housing. The wire entry ports face in opposite directions. The electrical terminal 132 fits in the interior of the housing. The top of the left housing has a latch plate 178 with an upwardly facing hook 180. The plate fits through a catch 182 on the right housing such that the hook 180 is engageable with the catch to hold the housing pieces together. A similar latch plate 184 is near the bottom of the left housing where it is engageable with a catch 186 on the bottom of the right housing.

[0070] A further alternate form of a housing is shown at 188 in FIGS. 34-36. This housing is also generally similar to that of FIGS. 1-19 with respect to the provision of top and bottom ports 190, 192 and wire receptacle boxes 194, 196. However, instead of the snap fit previously shown, housing 188 has upper and lower housing halves 198, 200 designed to be ultrasonically welded along mating surfaces 202. This affords a particularly compact construction. The electrical terminal 132 fits in the interior of the housing. As seen in FIG. 35, the interior of the lower housing half has a seat 204 for supporting the busbar or foot portion of the terminal. Ledges 206 below the seat 204 support the depending leg 142 of the spring 136 while an upper wall 208 supports the upstanding leg 140. Similar surfaces in the upper housing 198 serve to trap the terminal in position.

I claim:

1. A push-in wire connector, comprising:

- a housing including a hollow interior and at least first and second wire ports providing access to the interior for the ends of wires inserted into the first and second wire ports, the wire ports facing in opposite directions with the centers of the first and second wire ports being radially spaced apart from one another, each of the first and second wire ports including a longitudinal axis; and
- a busbar having a top face and a bottom face, the faces being engageable with wires inserted into the first and second wires ports, the busbar being mounted in the interior of the enclosure.

2. The push-in wire connector of claim 1 further including a first spring member mounted within the interior of the housing and configured to bias a first wire end inserted through the first wire port into engagement with the top face of the busbar, and a second spring member mounted within the interior of the housing and configured to bias a second wire end inserted through the second wire port into engagement with the bottom face of the busbar.

3. The push-in wire connector of claim 2 further characterized in that the first and second spring members are connected to one another.

4. The push-in wire connector of claim 2 wherein at least one of the spring members is attached to the busbar.

5. The push-in wire connector of claim 1 in which the top and bottom faces of the busbar each include a wire-receiving pocket and a wire-engaging protrusion.

6. The push-in wire connector of claim 5 in which the wire-receiving pockets and wire-engaging protrusions of the top and bottom faces are coined in the busbar.

7. The push-in wire connector of claim 5 in which at least a portion of the wire-receiving pocket of the top face forms the wire-engaging protrusion of the bottom face and at least a portion of the wire-receiving pocket of the bottom face forms the wire-engaging protrusion of the top face.

8. The push-in wire connector of claim 1 in which the housing includes a first testing port spaced from and extending in the same direction as the first wire port, and a second testing port spaced from and extending in the same direction as the second test port.

9. The push-in wire connector of claim 1 in which the housing includes a first wire receptacle box configured to receive a first wire end inserted into the connector through the first wire port and a second wire receptacle box configured to receive a second wire end inserted into the connector through the second wire box.

10. The push-in wire connector of claim 1 wherein a portion of the top face of the busbar extends at an angle with respect to the longitudinal axis of the first wire port, and a portion of the bottom face of the busbar extends at an angle with respect to the longitudinal axis of the second wire port.

11. A terminal assembly for use in a push-in wire connector, comprising:

- a foot having opposed first and second end portions and top and bottom surfaces,
- a first upstanding leg extending from the first end of the foot in a first direction and a second upstanding leg extending from the second end of the foot in a second direction generally opposite the first direction, each of the first and second legs including a spring member;
- a busbar connected to one of the top and bottom surfaces of the foot, the busbar including a top face and a bottom face; and
- the first spring member adapted to bias a first wire end into engagement with the top face of the busbar, and the second spring member adapted to bias a second wire end into engagement with the bottom face of the busbar.

12. The terminal assembly of claim 11 the top face and the bottom face of the busbar each includes a wire-receiving pocket and a wire-engaging protrusion.

13. The terminal assembly of claim 12 wherein the wire-receiving pockets and wire-engaging protrusions of the top and bottom faces are coined in the busbar

14. The terminal assembly of claim 13 wherein a portion of the top face of the busbar extends at an angle with respect to the foot, and a portion of the bottom face of the busbar extends at an angle with respect to the foot.

15. The terminal assembly of claim 12 in which at least a portion of the wire-receiving pocket of the top face forms the wire-engaging protrusion of the bottom face, and at least a portion of the wire-receiving pocket of the bottom face forms the wire-engaging protrusion of the top face.

16. A push-in wire connector, comprising:
- a housing having at least a top port and a bottom port, the ports each defining an axis and providing access to the interior of the housing for the ends of wires inserted into

the housing, the axes of the ports being spaced apart, the top and bottom ports facing in opposite directions;

- a busbar fixedly mounted in the interior of the housing, the busbar having a top face and a bottom face, the top face defining a first entry edge where a wire inserted into the top port first crosses the top face of the busbar, and the bottom face defining a second entry edge where a wire inserted into the bottom port first crosses the bottom face of the busbar, the first and second entry edges being on opposite sides of the busbar; and

- a spring member mounted in the interior of the housing and having an upstanding leg adjacent the first entry edge and a depending leg adjacent the second entry edge, the upstanding leg including a spring finger engageable with a wire inserted into the top port to bias the wire into engagement with the top face of the busbar, and the depending leg including a spring finger engageable with a wire inserted into the second port to bias the wire into engagement with the bottom face of the busbar.

17. The wire connector of claim 16 wherein the busbar further comprises a wire-receiving pocket extending below the top face, a wire-engaging protrusion extending above the top face, a wire-receiving pocket extending below the bottom face, and a wire-engaging protrusion extending above the bottom face.

18. The wire connector of claim 17 wherein the wire-receiving pocket in the top face is above the wire-engaging protrusion on the bottom face, and the wire-engaging protrusion on the top face is above the wire-receiving pocket in the bottom face.

19. A push-in wire connector, comprising:
- a housing having at least a top port and a bottom port, the ports each defining an axis and providing access to the interior of the housing for the ends of wires inserted into the housing, the axes of the ports being spaced apart, the top and bottom ports facing in opposite directions;
 - a busbar fixedly mounted in the interior of the housing, the busbar having a top face and a bottom face joined by first and second edges on opposite sides of the busbar; and
 - a spring member having a foot attached to the busbar and having an upstanding leg attached to the foot adjacent the first edge of the busbar and a depending leg attached to the foot adjacent the second edge of the busbar, the upstanding leg including a spring finger engageable with a wire inserted into one of the ports to bias the wire into engagement with the top face of the busbar, and the depending leg including a spring finger engageable with a wire inserted into the other of the ports to bias said wire into engagement with the bottom face of the busbar.

20. The wire connector of claim 19 wherein the busbar further comprises a wire-receiving pocket extending below the top face, a wire-engaging protrusion extending above the top face, a wire-receiving pocket extending below the bottom face, and a wire-engaging protrusion extending above the bottom face.

21. The wire connector of claim 20 wherein the wire-receiving pocket in the top face is above the wire-engaging protrusion on the bottom face, and the wire-engaging protrusion on the top face is above the wire-receiving pocket in the bottom face.