



(19) **United States**

(12) **Patent Application Publication**
CHANG et al.

(10) **Pub. No.: US 2020/0057248 A1**

(43) **Pub. Date: Feb. 20, 2020**

(54) **OPTICAL IMAGE CAPTURING MODULE**

G02B 5/20 (2006.01)

G02B 13/00 (2006.01)

(71) Applicant: **ABILITY OPTO-ELECTRONICS TECHNOLOGY CO., LTD.**, Taichung City (TW)

(52) **U.S. Cl.**

CPC *G02B 9/62* (2013.01); *G02B 7/021* (2013.01); *G02B 13/0045* (2013.01); *G02B 7/025* (2013.01); *G02B 5/20* (2013.01); *H04N 5/2254* (2013.01)

(72) Inventors: **YEONG-MING CHANG**, TAICHUNG CITY (TW); **CHIEN-HSUN LAI**, TAICHUNG CITY (TW); **YAO-WEI LIU**, TAICHUNG CITY (TW)

(57)

ABSTRACT

An optical image capturing module includes a lens assembly and a circuit assembly including a circuit substrate, a sensor holder, and an image sensing component connected to the circuit substrate. The circuit substrate has multiple circuit contacts. The sensor holder is disposed on the circuit substrate and on the image sensing component. The image sensing component has a sensing surface and multiple image contacts. Each image contact is electrically connected to one of the circuit contacts via multiple signal transmission elements embedded in the sensor holder. The lens assembly includes a fixed base, a movable base, and a lens group. The movable base has a receiving hole and is disposed in the fixed base. The lens group includes at least two lenses and is disposed on the movable base and is located in the receiving hole, thereby light could pass through the lens group and project onto the image sensing component.

(21) Appl. No.: **16/225,407**

(22) Filed: **Dec. 19, 2018**

(30) **Foreign Application Priority Data**

Aug. 16, 2018 (TW) 107128679


Publication Classification

(51) **Int. Cl.**

G02B 9/62 (2006.01)

G02B 7/02 (2006.01)

H04N 5/225 (2006.01)






FIG.1B




FIG.1C




FIG.1D




FIG.1E




FIG.1F




FIG.1G




FIG.2A




FIG.2B




FIG. 3A




FIG. 3B




FIG. 4A




FIG. 4B




FIG. 5A




FIG. 5B




FIG. 6A




FIG. 6B




FIG. 7A




FIG. 7B




FIG. 8A




FIG. 8B




FIG. 8C




FIG. 8D




FIG.8E




FIG.8F




FIG. 8G




FIG. 8H

OPTICAL IMAGE CAPTURING MODULE

BACKGROUND OF THE INVENTION

Technical Field

[0001] The present invention generally relates to an optical image capturing module, and more particularly to a compact optical image capturing module for an electronic device.

Description of Related Art

[0002] In recent years, with the rise of portable electronic devices having camera functionalities, the demand for an optical image capturing system is raised gradually. The image sensing device of the ordinary photographing camera is commonly selected from charge coupled device (CCD) or complementary metal-oxide semiconductor sensor (CMOS Sensor). Also, as advanced semiconductor manufacturing technology enables the minimization of the pixel size of the image sensing device, the development of the optical image capturing system towards the field of high pixels. Therefore, the requirement for high imaging quality is rapidly raised.

[0003] The conventional optical system of the portable electronic device usually has five or sixth lenses. However, the optical system is asked to take pictures in a dark environment, in other words, the optical system is asked to have a large aperture. The conventional optical system provides high optical performance as required.

[0004] It is an important issue to increase the quantity of light entering the lens. Also, the modem lens is also asked to have several characters, including high image quality.

BRIEF SUMMARY OF THE INVENTION

[0005] The aspect of embodiment of the present disclosure directs to an optical image capturing module which use structural size design and combination of refractive powers, convex and concave surfaces of at least two optical lenses (the convex or concave surface in the disclosure denotes the geometrical shape of an image-side surface or an object-side surface of each lens on an optical axis) to reduce the size and increase the quantity of incoming light of the optical image capturing module, thereby the optical image capturing module could has a better amount of light entering therein and could improve imaging total pixels and imaging quality for image formation, so as to be applied to minimized electronic products.

[0006] The term and its definition to the structural component parameter in the embodiment of the present are shown as below for further reference.

[0007] Take FIG. 1A as an example to illustrate the structural component of the optical image capturing module. The optical image capturing module mainly includes a circuit assembly and a lens assembly, wherein the circuit assembly includes a circuit substrate EB, a sensor holder SB, and an image sensing component S. In the present invention, the image sensing component S is fixed on the circuit substrate in a Chip On Board (COB) package.

[0008] The lens assembly includes a fixed base FB1, a movable base MB1, and a lens group L, wherein the fixed base FB1 is made of metal (such as aluminum, copper, silver, gold, and etc.), plastic (e.g. polycarbonate (PC)), or liquid crystal plastic (LCP), which are opaque materials. The fixed base FB1 is disposed on the sensor holder SB, and has

a focusing hole penetrating through both ends of the fixed base FB1, so that the fixed base FB1 is hollow. In addition, a maximum value of a minimum length on a periphery of the fixed base FB1 perpendicular to an optical axis of the lens group L is denoted by PhiD. The movable base MB1 is disposed in the fixed base FB1 and is located in the focusing hole to be located above the image sensing component S. The movable base MB1 is controllable to move relative to the fixed base FB1 in the focusing hole in a central axial direction of the focusing hole, and has a receiving hole penetrating through both ends of the movable base MB1, so that the movable base MB1 is hollow. More specifically, the movable base MB1 includes an inner holder LH1 and a lens barrel B1, wherein the inner holder LH1 is disposed in the fixed base FB1 and is located in the focusing hole, and is controllable to move relative to the fixed base FB1. The inner holder LH1 has an inner through hole penetrating through both ends of the inner holder LH1, so that the inner holder LH1 is hollow. The lens barrel B1 is disposed in the inner holder LH1 and is located in the inner through hole, and is capable of being driven by the inner holder LH1 to move relative to the fixed base FB1. The lens barrel B1 has the receiving hole penetrating through both ends of the lens barrel B1, so that the lens barrel B1 is hollow. Moreover, a distance from an outer wall of the fixed base FB1 to an inner wall of the inner through hole of the inner holder LH1 is denoted by TH1, and a minimum thickness of the lens barrel B1 is denoted by TH2.

[0009] The lens group L includes at least two lenses with refractive power which are disposed on the movable base MB1 and are located in the receiving hole. The term and its definition to the lens parameter in the embodiment of the present are shown as below for further reference.

[0010] The lens parameter related to a length or a height in the lens:

[0011] A maximum height for image formation of the optical image capturing module is denoted by HOI. A height of the optical image capturing module (i.e., a distance between an object-side surface of the first lens and an image plane on an optical axis) is denoted by HOS. A distance from the object-side surface of the first lens to the image-side surface of the seventh lens is denoted by InTL. A distance from the first lens to the second lens is denoted by IN12 (instance). A central thickness of the first lens of the optical image capturing module on the optical axis is denoted by TP1 (instance).

[0012] The lens parameter related to a material in the lens:

[0013] An Abbe number of the first lens in the optical image capturing module is denoted by NA1 (instance). A refractive index of the first lens is denoted by Nd1 (instance).

[0014] The lens parameter related to a view angle of the lens:

[0015] A view angle is denoted by AF. Half of the view angle is denoted by HAF. A major light angle is denoted by MRA.

[0016] The lens parameter related to exit/entrance pupil in the lens:

[0017] An entrance pupil diameter of the optical image capturing module is denoted by HEP. For any surface of any lens, a maximum effective half diameter (EHD) is a perpendicular distance between an optical axis and a crossing point on the surface where the incident light with a maximum viewing angle of the optical image capturing module passing

the very edge of the entrance pupil. For example, the maximum effective half diameter of the object-side surface of the first lens is denoted by EHD11, the maximum effective half diameter of the image-side surface of the first lens is denoted by EHD12, the maximum effective half diameter of the object-side surface of the second lens is denoted by EHD21, the maximum effective half diameter of the image-side surface of the second lens is denoted by EHD22, and so on. In the optical image capturing module, a maximum effective diameter of the image-side surface of the lens closest to the image plane is denoted by PhiA, which satisfies the condition: $\text{PhiA}=2*\text{EHD}$. If the surface is aspherical, a cut-off point of the largest effective diameter is the cut-off point containing the aspheric surface. An ineffective half diameter (IHD) of any surface of one single lens refers to a surface segment between cut-off points of the maximum effective half diameter of the same surface extending in a direction away from the optical axis, wherein said a cut-off point is an end point of the surface having an aspheric coefficient if said surface is aspheric. In the optical image capturing module, a maximum diameter of the image-side surface of the lens closest to the image plane is denoted by PhiB, which satisfies the condition: $\text{PhiB}=2*(\text{maximum effective half diameter EHD}+\text{maximum ineffective half diameter IHD})=\text{PhiA}+2*(\text{maximum ineffective half diameter IHD})$.

[0018] In the optical image capturing module, a maximum effective diameter of the image-side surface of the lens closest to the image plane (i.e., the image space) could be also called optical exit pupil, and is denoted by PhiA. If the optical exit pupil is located on the image-side surface of the third lens, then it is denoted by PhiA3; if the optical exit pupil is located on the image-side surface of the fourth lens, then it is denoted by PhiA4; if the optical exit pupil is located on the image-side surface of the fifth lens, then it is denoted by PhiA5; if the optical exit pupil is located on the image-side surface of the sixth lens, then it is denoted by PhiA6, and so on. A pupil magnification ratio of the optical image capturing module is denoted by PMR, which satisfies the condition: $\text{PMR}=\text{PhiA}/\text{HEP}$.

[0019] The lens parameter related to an arc length of the shape of a surface and a surface profile:

[0020] For any surface of any lens, a profile curve length of the maximum effective half diameter is, by definition, measured from a start point where the optical axis of the belonging optical image capturing module passes through the surface of the lens, along a surface profile of the lens, and finally to an end point of the maximum effective half diameter thereof. In other words, the curve length between the aforementioned start and end points is the profile curve length of the maximum effective half diameter, which is denoted by ARS. For example, the profile curve length of the maximum effective half diameter of the object-side surface of the first lens is denoted by ARS11, the profile curve length of the maximum effective half diameter of the image-side surface of the first lens is denoted by ARS12, the profile curve length of the maximum effective half diameter of the object-side surface of the second lens is denoted by ARS21, the profile curve length of the maximum effective half diameter of the image-side surface of the second lens is denoted by ARS22, and so on.

[0021] For any surface of any lens, a profile curve length of a half of the entrance pupil diameter (HEP) is, by definition, measured from a start point where the optical axis

of the belonging optical image capturing module passes through the surface of the lens, along a surface profile of the lens, and finally to a coordinate point of a perpendicular distance where is a half of the entrance pupil diameter away from the optical axis. In other words, the curve length between the aforementioned start point and the coordinate point is the profile curve length of a half of the entrance pupil diameter (HEP), and is denoted by ARE. For example, the profile curve length of a half of the entrance pupil diameter (HEP) of the object-side surface of the first lens is denoted by ARE11, the profile curve length of a half of the entrance pupil diameter (HEP) of the image-side surface of the first lens is denoted by ARE12, the profile curve length of a half of the entrance pupil diameter (HEP) of the object-side surface of the second lens is denoted by ARE21, the profile curve length of a half of the entrance pupil diameter (HEP) of the image-side surface of the second lens is denoted by ARE22, and so on.

[0022] The lens parameter related to a depth of the lens shape:

[0023] A displacement from a point on the object-side surface of the sixth lens, which is passed through by the optical axis, to a point on the optical axis, where a projection of the maximum effective semi diameter of the object-side surface of the sixth lens ends, is denoted by InRS61 (the depth of the maximum effective semi diameter). A displacement from a point on the image-side surface of the sixth lens, which is passed through by the optical axis, to a point on the optical axis, where a projection of the maximum effective semi diameter of the image-side surface of the sixth lens ends, is denoted by InRS62 (the depth of the maximum effective semi diameter). The depth of the maximum effective semi diameter (sinkage) on the object-side surface or the image-side surface of any other lens is denoted in the same manner.

[0024] The lens parameter related to the lens shape:

[0025] A critical point C is a tangent point on a surface of a specific lens, and the tangent point is tangent to a plane perpendicular to the optical axis and the tangent point cannot be a crossover point on the optical axis. Following the above description, a distance perpendicular to the optical axis between a critical point C51 on the object-side surface of the fifth lens and the optical axis is HVT51 (instance), and a distance perpendicular to the optical axis between a critical point C52 on the image-side surface of the fifth lens and the optical axis is HVT52 (instance). A distance perpendicular to the optical axis between a critical point C61 on the object-side surface of the sixth lens and the optical axis is HVT61 (instance), and a distance perpendicular to the optical axis between a critical point C62 on the image-side surface of the sixth lens and the optical axis is HVT62 (instance). A distance perpendicular to the optical axis between a critical point on the object-side or image-side surface of other lenses is denoted in the same manner.

[0026] The object-side surface of the seventh lens has one inflection point IF711 which is nearest to the optical axis, and the sinkage value of the inflection point IF711 is denoted by SGI711 (instance). A distance perpendicular to the optical axis between the inflection point IF711 and the optical axis is HIF711 (instance). The image-side surface of the seventh lens has one inflection point IF721 which is nearest to the optical axis, and the sinkage value of the inflection point IF721 is denoted by SGI721 (instance). A distance perpen-

dicular to the optical axis between the inflection point IF721 and the optical axis is HIF721 (instance).

[0027] The object-side surface of the seventh lens has one inflection point IF712 which is the second nearest to the optical axis, and the sinkage value of the inflection point IF712 is denoted by SGI712 (instance). A distance perpendicular to the optical axis between the inflection point IF712 and the optical axis is HIF712 (instance). The image-side surface of the seventh lens has one inflection point IF722 which is the second nearest to the optical axis, and the sinkage value of the inflection point IF722 is denoted by SGI722 (instance). A distance perpendicular to the optical axis between the inflection point IF722 and the optical axis is HIF722 (instance).

[0028] The object-side surface of the seventh lens has one inflection point IF713 which is the third nearest to the optical axis, and the sinkage value of the inflection point IF713 is denoted by SGI713 (instance). A distance perpendicular to the optical axis between the inflection point IF713 and the optical axis is HIF713 (instance). The image-side surface of the seventh lens has one inflection point IF723 which is the third nearest to the optical axis, and the sinkage value of the inflection point IF723 is denoted by SGI723 (instance). A distance perpendicular to the optical axis between the inflection point IF723 and the optical axis is HIF723 (instance).

[0029] The object-side surface of the seventh lens has one inflection point IF714 which is the fourth nearest to the optical axis, and the sinkage value of the inflection point IF714 is denoted by SGI714 (instance). A distance perpendicular to the optical axis between the inflection point IF714 and the optical axis is HIF714 (instance). The image-side surface of the seventh lens has one inflection point IF724 which is the fourth nearest to the optical axis, and the sinkage value of the inflection point IF724 is denoted by SGI724 (instance). A distance perpendicular to the optical axis between the inflection point IF724 and the optical axis is HIF724 (instance).

[0030] An inflection point, a distance perpendicular to the optical axis between the inflection point and the optical axis, and a sinkage value thereof on the object-side surface or image-side surface of other lenses is denoted in the same manner.

[0031] The lens parameter related to an aberration:

[0032] Optical distortion for image formation in the optical image capturing module is denoted by ODT. TV distortion for image formation in the optical image capturing module is denoted by TDT. Further, the range of the aberration offset for the view of image formation may be limited to 50%-100% field. An offset of the spherical aberration is denoted by DFS. An offset of the coma aberration is denoted by DFC.

[0033] The present invention provides an optical image capturing module, which is capable of focusing visible and infrared (i.e., dual-mode) at the same time and achieving certain performance, wherein the sixth lens thereof is provided with an inflection point at the object-side surface or at the image-side surface to adjust the incident angle of each view field and modify the ODT and the TDT. In addition, the surfaces of the sixth lens are capable of modifying the optical path to improve the imaging quality.

[0034] The optical image capturing module of the present invention includes a circuit assembly and a lens assembly. The circuit assembly includes a circuit substrate, a sensor holder, and an image sensing component, wherein the circuit

substrate has a plurality of circuit contacts thereon. The image sensing component has a first surface and a second surface, wherein the first surface is connected to the circuit substrate. The second surface has a sensing surface and a plurality of image contacts. Each of the image contacts is electrically connected to one of the circuit contacts on the circuit substrate via a plurality of signal transmission elements. The sensor holder is disposed on the circuit substrate and the second surface of the image sensing component, and covers the circuit contacts and the image contacts. The signal transmission elements are embedded in the sensor holder. The lens assembly includes a fixed base, a movable base, and a lens group, wherein the fixed base is made of an opaque material and has a focusing hole penetrating through two ends of the fixed base, so that the fixed base is hollow. The fixed base is disposed on the sensor holder. The movable base is disposed in the fixed base, and is located in the focusing hole to be located above the image sensing component, and is controllable to move relative to the fixed base in the focusing hole in a central axial direction of the focusing hole. The movable base has a receiving hole penetrating through two ends of the movable base, so that the movable base is hollow. The lens group includes at least two lenses having refractive power, and is disposed on the lens base and is located in the receiving hole. An image plane of the lens group is adjustable to be located on the sensing surface along with a movement of the movable base, and an optical axis of the lens group overlaps with a central normal of the sensing surface, so that a light passes through the lens group in the receiving hole and projects onto the sensing surface. The optical image capturing module further satisfies:

$$1.0 \leq f/HEP \leq 10.0; 0 \text{ deg} < HAF \leq 150 \text{ deg}; 0 \text{ mm} < PhiD \leq 18 \text{ mm}; 0 < PhiA/PhiD \leq 0.99; \text{ and} \\ 0.9 \leq 2(ARE/HEP) \leq 2.0;$$

[0035] where f is a focal length of the lens group; HEP is an entrance pupil diameter of the lens group; HAF is a half of a maximum field angle of the lens group; $PhiD$ is a maximum value of a minimum length on a periphery of the fixed base perpendicular to the optical axis of the lens group; $PhiA$ is a maximum effective diameter of an image-side surface of the at least two lenses of the lens group closest to the image plane; ARE is a profile curve length measured from a start point where the optical axis of the lens group passes through any surface of one of the at least two lenses, along a surface profile of the corresponding lens, and finally to a coordinate point of a perpendicular distance where is a half of the entrance pupil diameter away from the optical axis.

[0036] The length of the contour curve of any surface of a single lens in the range of the maximum effective radius affects the surface correction aberration and the optical path difference between the fields of view. The longer the profile curve length, the better the ability to correct the aberration, but at the same time it will increase the difficulty in manufacturing, so it is necessary to control the length of the profile curve of any surface of a single lens within the maximum effective radius, in particular to control the profile length (ARS) and the surface within the maximum effective radius of the surface. The proportional relationship (ARS/TP) between the thicknesses (TP) of the lens on the optical axis. For example, the length of the contour curve of the maximum effective radius of the side surface of the first lens object is represented by $ARS11$, and the thickness of the first

lens on the optical axis is TP1, and the ratio between the two is $ARS11/TP1$, and the maximum effective radius of the side of the first lens image side. The length of the contour curve is represented by $ARS12$, and the ratio between it and TP1 is $ARS12/TP1$. The length of the contour curve of the maximum effective radius of the side of the second lens object is represented by $ARS21$, the thickness of the second lens on the optical axis is TP2, the ratio between the two is $ARS21/TP2$, and the contour of the maximum effective radius of the side of the second lens image. The length of the curve is represented by $ARS22$, and the ratio between it and TP2 is $ARS22/TP2$. The proportional relationship between the length of the profile of the maximum effective radius of any surface of the remaining lenses in the optical imaging system and the thickness (TP) of the lens on the optical axis to which the surface belongs, and so on. The optical image capturing module of the present invention satisfies: $0.9 \leq ARS/EHD \leq 2.0$.

[0037] The optical image capturing module has a maximum image height HOI on the image plane vertical to the optical axis. A transverse aberration at 0.7 HOI in the positive direction of the tangential ray fan aberration after the longest operation wavelength passing through the edge of the entrance pupil is denoted by PLTA; a transverse aberration at 0.7 HOI in the positive direction of the tangential ray fan aberration after the shortest operation wavelength passing through the edge of the entrance pupil is denoted by PSTA; a transverse aberration at 0.7 HOI in the negative direction of the tangential ray fan aberration after the longest operation wavelength passing through the edge of the entrance pupil is denoted by NLTA; a transverse aberration at 0.7 HOI in the negative direction of the tangential ray fan aberration after the shortest operation wavelength passing through the edge of the entrance pupil is denoted by NSTA; a transverse aberration at 0.7 HOI of the sagittal ray fan aberration after the longest operation wavelength passing through the edge of the entrance pupil is denoted by SLTA; a transverse aberration at 0.7 HOI of the sagittal ray fan aberration after the shortest operation wavelength passing through the edge of the entrance pupil is denoted by SSTA. The optical image capturing module of the present invention satisfies:

[0038] $PLTA \leq 100 \mu\text{m}$; $PSTA \leq 100 \mu\text{m}$; $NLTA \leq 100 \mu\text{m}$; $NSTA \leq 100 \mu\text{m}$; $SLTA \leq 100 \mu\text{m}$; $SSTA \leq 100 \mu\text{m}$; $|TDT| < 250\%$; $0.1 \leq \ln TL/HOS \leq 0.95$; and $0.2 \leq \ln s/HOS \leq 1.1$.

[0039] For visible light spectrum, the values of MTF in the spatial frequency of 110 cycles/mm at the optical axis, 0.3 field of view, and 0.7 field of view on an image plane are respectively denoted by MTFQ0, MTFQ3, and MTFQ7. The optical image capturing module of the present invention satisfies:

[0040] $MTFQ0 \geq 0.2$; $MTFQ3 \geq 0.01$; and $MTFQ7 \geq 0.01$.

[0041] For any surface of any lens, the profile curve length within a half of the entrance pupil diameter (HEP) affects the ability of the surface to correct aberration and differences between optical paths of light in different fields of view. With longer profile curve length, the ability to correct aberration is better. However, the difficulty of manufacturing increases as well. Therefore, the profile curve length within a half of the entrance pupil diameter (HEP) of any surface of any lens has to be controlled. The ratio between the profile curve length (ARE) within a half of the entrance pupil diameter (HEP) of one surface and the thickness (TP) of the lens, which the surface belonged to, on the optical axis (i.e.,

ARE/TP) has to be particularly controlled. For example, the profile curve length of a half of the entrance pupil diameter (HEP) of the object-side surface of the first lens is denoted by ARE11, the thickness of the first lens on the optical axis is TP1, and the ratio between these two parameters is $ARE11/TP1$; the profile curve length of a half of the entrance pupil diameter (HEP) of the image-side surface of the first lens is denoted by ARE12, and the ratio between ARE12 and TP1 is $ARE12/TP1$. The profile curve length of a half of the entrance pupil diameter (HEP) of the object-side surface of the second lens is denoted by ARE21, the thickness of the second lens on the optical axis is TP2, and the ratio between these two parameters is $ARE21/TP2$; the profile curve length of a half of the entrance pupil diameter (HEP) of the image-side surface of the second lens is denoted by ARE22, and the ratio between ARE22 and TP2 is $ARE22/TP2$. For any surface of other lenses in the optical image capturing system, the ratio between the profile curve length of a half of the entrance pupil diameter (HEP) thereof and the thickness of the lens which the surface belonged to is denoted in the same manner.

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

[0042] The present invention will be best understood by referring to the following detailed description of some illustrative embodiments in conjunction with the accompanying drawings, in which

[0043] FIG. 1A is a schematic diagram of a first structural embodiment of the present invention;

[0044] FIG. 1B is a schematic diagram of a second structural embodiment of the present invention;

[0045] FIG. 1C is a schematic diagram of a third structural embodiment of the present invention;

[0046] FIG. 1D is a schematic diagram of a fourth structural embodiment of the present invention;

[0047] FIG. 1E is a schematic diagram of a fifth structural embodiment of the present invention;

[0048] FIG. 1F is a schematic diagram of a sixth structural embodiment of the present invention;

[0049] FIG. 1G is a schematic diagram of a seventh structural embodiment of the present invention;

[0050] FIG. 2A is a schematic diagram of a first optical embodiment of the present invention;

[0051] FIG. 2B shows curve diagrams of longitudinal spherical aberration, astigmatic field, and optical distortion of the optical image capturing module in the order from left to right of the first optical embodiment of the present application;

[0052] FIG. 3A is a schematic diagram of a second optical embodiment of the present invention;

[0053] FIG. 3B shows curve diagrams of longitudinal spherical aberration, astigmatic field, and optical distortion of the optical image capturing module in the order from left to right of the second optical embodiment of the present application;

[0054] FIG. 4A is a schematic diagram of a third optical embodiment of the present invention;

[0055] FIG. 4B shows curve diagrams of longitudinal spherical aberration, astigmatic field, and optical distortion of the optical image capturing module in the order from left to right of the third optical embodiment of the present application;

[0056] FIG. 5A is a schematic diagram of a fourth optical embodiment of the present invention;

[0057] FIG. 5B shows curve diagrams of longitudinal spherical aberration, astigmatic field, and optical distortion of the optical image capturing module in the order from left to right of the fourth optical embodiment of the present application;

[0058] FIG. 6A is a schematic diagram of a fifth optical embodiment of the present invention;

[0059] FIG. 6B shows curve diagrams of longitudinal spherical aberration, astigmatic field, and optical distortion of the optical image capturing module in the order from left to right of the fifth optical embodiment of the present application;

[0060] FIG. 7A is a schematic diagram of a sixth optical embodiment of the present invention;

[0061] FIG. 7B shows curve diagrams of longitudinal spherical aberration, astigmatic field, and optical distortion of the optical image capturing module in the order from left to right of the sixth optical embodiment of the present application;

[0062] FIG. 8A is a schematic diagram, showing the optical image capturing module of the present invention is applied to the mobile communication device;

[0063] FIG. 8B is a schematic diagram, showing the optical image capturing module of the present invention is applied to the mobile information device;

[0064] FIG. 8C is a schematic diagram, showing the optical image capturing module of the present invention is applied to the smart watch;

[0065] FIG. 8D is a schematic diagram, showing the optical image capturing module of the present invention is applied to the smart head-wearing device;

[0066] FIG. 8E is a schematic diagram, showing the optical image capturing module of the present invention is applied to the safety monitoring device;

[0067] FIG. 8F is a schematic diagram, showing the optical image capturing module of the present invention is applied to the vehicle image device;

[0068] FIG. 8G is a schematic diagram, showing the optical image capturing module of the present invention is applied to the unmanned aircraft device;

[0069] FIG. 8H is a schematic diagram, showing the optical image capturing module of the present invention is applied to the extreme sport image device.

DETAILED DESCRIPTION OF THE INVENTION

[0070] An optical image capturing module of the present invention includes a structural design and an optical design, wherein structural embodiments will be described first.

[0071] As shown in FIG. 1A, an optical image capturing module according to a first structural embodiment of the present invention includes mainly includes a circuit assembly and a lens assembly. The circuit assembly includes an image sensing component S, a sensor holder SB, and a circuit substrate EB. A maximum value of a minimum length of an outer periphery of the image sensing component S which is perpendicular to a plane of an optical axis of the lens assembly is denoted by LS. In the current embodiment, the image sensing component S is fixed on the circuit substrate EB in a Chip On Board (COB) package. More specifically, the circuit substrate EB has a plurality of circuit contacts EP thereon; the image sensing component S has a

first surface S1 and a second surface S2, wherein the first surface S1 is connected to the circuit substrate EB, and the second surface S2 has a sensing surface and a plurality of image contacts IP. Each of the image contacts IP is electrically connected to one of the circuit contacts EP on the circuit substrate EB via a plurality of signal transmission elements SC1. In the current embodiment, each of the signal transmission elements SC1 is a gold wire. The sensor holder SB is disposed on the circuit substrate EB and on the second surface S2 of the image sensing component S, and covers the circuit contacts EP and the image contacts IP, wherein the signal transmission elements SC1 is embedded in the sensor holder SB. In this way, when an image optical signal is sensed by the sensing surface of the image sensing component S and is transformed into an electrical signal, the electrical signal could be sent to the circuit contacts EP via the image contacts IP and the signal transmission elements SC1, so that the circuit contacts EP could transmit the electrical signal to other external components for subsequent processing.

[0072] The lens assembly includes a fixed base FB1, a movable base MB1, a lens group L, and an IR-cut filter IR1. In the current embodiment, the fixed base FB1 is made of plastic material and is opaque, and has a focusing hole penetrating through both ends of the fixed base FB1, so that the fixed base FB1 is hollow. The fixed base FB1 is disposed on the sensor holder SB, so that the focusing hole directly faces the image sensing component S. The fixed base FB1 has a predetermined thickness TH1, and a maximum value of a minimum length on a periphery of the lens holder LH1 perpendicular to the optical axis of the lens group L is denoted by PhiD. The movable base MB1 has a receiving hole penetrating through both ends of the movable base MB1, so that the movable base MB1 is hollow, wherein the receiving hole directly faces the sensing surface of the image sensing component S. More specifically, the movable base MB1 includes an inner holder LH1 and a lens barrel B1, wherein the inner holder LH1 is disposed in the fixed base FB1 and is located in the focusing hole, and is controllable to move relative to the fixed base FB1. In addition, the inner holder LH1 has an inner through hole DH1 penetrating through both ends of the inner holder LH1 to be hollow. The lens barrel B1 is disposed in the inner holder LH1 and is located in the inner through hole DH1, and is capable of being driven by the inner holder LH1 to move relative to the fixed base FB1. The lens barrel B1 has the receiving hole penetrating through both ends of the lens barrel B1, so that the lens barrel B1 is hollow. The lens barrel B1 has a predetermined thickness TH2, and a maximum value of a minimum length on a periphery of the lens barrel B1 perpendicular to the optical axis of the lens group L is denoted by PhiC. The lens group L is disposed in the lens barrel B1 to directly face the sensing surface of the image sensing component S. In the current embodiment, a glue is coated between the lens barrel B1 and the inner holder LH1, and the lens barrel B1 and the inner holder LH1 are fixed to each other via the glue, so that the lens barrel B1 is disposed in the inner holder LH1 and is fixed in the inner through hole DH1.

[0073] The lens group L includes at least two lenses with refractive power, and optical embodiments will be described in detail later. The lens group L is disposed on the lens barrel B1 of the movable base MB1 and is located in the receiving hole. In addition, an image plane of the lens group L is

adjustable to be located on the sensing surface of the image sensing component S along with a movement of the movable base MB1, wherein the optical axis of the lens group L overlaps with a central normal of the sensing surface, so that light could pass through the lens group L in the receiving hole and could be projected onto the sensing surface. Moreover, a maximum diameter of an image-side surface of a lens of the lens group L closest to the image plane is denoted by ΦB , and a maximum effective diameter of the image-side surface of the lens of the lens group L closest to the image plane (i.e., the image space) could be also called optical exit pupil, and is denoted by ΦA .

[0074] The IR-cut filter IR1 is disposed in the fixed holder FB1 and is located above the image sensing component S, thereby to filter out an excess infrared in the image light passing through the lens group L, enhancing the image quality.

[0075] It is worth mentioning that, in order to overlap the optical axis of the lens group L with the central normal of the sensing surface of the image sensing component S, an outer side of the lens barrel B1 of the optical image capturing module of the current embodiment is not completely in contact with an inner periphery of the inner holder LH1, thereby to leave a slight gap, so that a curable glue could be coated between the inner holder LH1 and the lens barrel B1 in advance, and the optical axis of the lens group L and the central normal of the image sensing component S could be adjusted to be overlapped with each other, and then the curable glue is cured to fix the lens barrel B1 to the inner holder LH1, that is, an active alignment assembly is carried out. The precision optical image capturing modules or special applications (such as the assembly of multiple lenses) require the active alignment technology, and the optical image capturing module of the present invention could meet such requirement.

[0076] In order to keep small in size and provide high imaging quality, the optical image capturing module of the current embodiment satisfies:

[0077] $0 \text{ mm} < \Phi A \leq 17.4 \text{ mm}$; $0 \text{ mm} < \Phi C \leq 17.7 \text{ mm}$; $0 \text{ mm} < \Phi D \leq 18 \text{ mm}$; $0 \text{ mm} < TH1 \leq 5 \text{ mm}$; $0 \text{ mm} < TH2 \leq 5 \text{ mm}$; $0 < \Phi A / \Phi D \leq 0.99$; $0 \text{ mm} < TH1 + TH2 \leq 1.5 \text{ mm}$; and $0 < 2 * (TH1 + TH2) / \Phi A \leq 0.95$.

[0078] Preferably, the optical image capturing module of the current embodiment satisfies:

[0079] $0 \text{ mm} < \Phi A \leq 13.5 \text{ mm}$; $0 \text{ mm} < \Phi C \leq 14 \text{ mm}$; $0 \text{ mm} < \Phi D \leq 15 \text{ mm}$; $0 \text{ mm} < TH1 \leq 0.5 \text{ mm}$; $0 \text{ mm} < TH2 \leq 0.5 \text{ mm}$; $0 < \Phi A / \Phi D \leq 0.97$; $0 \text{ mm} < TH1 + TH2 \leq 1 \text{ mm}$; and $0 < 2 * (TH1 + TH2) / \Phi A \leq 0.5$.

[0080] As shown in FIG. 1B to FIG. 1G, optical image capturing modules according to a second structural embodiment to a seventh structural embodiment are illustrated, each of which is slightly different from that of the first structural embodiment, but the effect of miniaturization and high optical quality could be achieved as well.

[0081] The optical image capturing modules according to the second structural embodiment is illustrated in FIG. 1B, which has almost the same structure with that of the first structural embodiment, except that an outer peripheral wall of a lens barrel B2 has an external thread OT2 thereon, and an inner wall of an inner through hole DH2 of an inner holder LH2 has an inner thread IT2 thereon, wherein the inner thread IT2 is adapted to be screwed with the external thread OT2, thereby to dispose the lens barrel B2 in the inner holder LH2 to be fixed in the inner through hole DH2. In

addition, an IR-cut filter IR2 is fixed in the lens barrel B2 to filter out an excess infrared light. Moreover, the optical image capturing modules according to the second structural embodiment satisfies the conditions of the first structural embodiment, which could keep small in size and provide high imaging quality as well.

[0082] The optical image capturing modules according to the third structural embodiment is illustrated in FIG. 1C, which has almost the same structure with that of the first structural embodiment, except that a movable base MB3 is integrally formed as a monolithic unit, instead of being separated to a lens barrel and an inner holder, which reduces the time required for producing components and for assembling. In addition, an IR-cut filter IR3 is capable of being disposed in a fixed base FB3 or on the sensor holder SB to be located above the image sensing component S. In the current embodiment, the IR-cut filter IR3 is disposed in the fixed base FB3.

[0083] Moreover, the optical image capturing modules according to the third structural embodiment satisfies $0 \text{ mm} < \Phi A \leq 17.4 \text{ mm}$, and a preferable range is $0 \text{ mm} < \Phi A \leq 13.5 \text{ mm}$; $0 \text{ mm} < \Phi D \leq 18 \text{ mm}$, and a preferable range is $0 \text{ mm} < \Phi D \leq 15 \text{ mm}$; $0 < \Phi A / \Phi D \leq 0.99$, and a preferable range is $0 < \Phi A / \Phi D \leq 0.97$; $0 \text{ mm} < TH1 + TH2 \leq 1.5 \text{ mm}$, and a preferable range is $0 \text{ mm} < TH1 + TH2 \leq 1 \text{ mm}$; $0 < 2 * (TH1 + TH2) / \Phi A \leq 0.95$, and a preferable range is $0 < 2 * (TH1 + TH2) / \Phi A \leq 0.5$. In other words, the optical image capturing modules according to the third structural embodiment satisfies partially of the conditions of the first structural embodiment, which could keep small in size and provide high imaging quality as well.

[0084] The optical image capturing modules according to the fourth structural embodiment is illustrated in FIG. 1D, which has almost the same structure with that of the first structural embodiment, except that an IR-cut filter IR4 is capable of being disposed on a movable base MB4, on a fixed base FB4, or on the sensor holder SB. In the current embodiment, the IR-cut filter IR4 is disposed on the sensor holder SB and is located above the image sensing component S. A lens base LB4 includes a filter holder IRH4, a lens holder LH4, and a lens barrel B4. The filter holder IRH4 has a through hole IH penetrating through both ends of the filter holder IRH4, and is disposed on the circuit substrate EB. An IR-cut filter IR4 is disposed in the filter holder IRH4 and is located in the through hole IH of the filter holder IRH4, so that the IR-cut filter IR4 is located above the image sensing component S. The lens holder LH4 is fixed on the filter holder IRH4, and the lens barrel B4 is disposed in the lens holder LH4, so that an upper through hole UH4 of the lens barrel B4, a lower through hole DH4 of the lens holder LH4, and the through hole IH of the filter holder IRH4 communicate with one another to form a receiving hole. In addition, the optical image capturing modules according to the fourth structural embodiment satisfies the conditions of the first structural embodiment, and could be fixed by a glue to carry out the active alignment assembly, which could keep small in size and provide high imaging quality as well.

[0085] The optical image capturing modules according to the fifth structural embodiment is illustrated in FIG. 1E, which has almost the same structure with that of the fourth structural embodiment, except that a fixed base FB5 includes a filter holder IRH5 and an outer holder OH5. The filter holder IRH5 is disposed on the sensor holder SB and has a through hole IRH penetrating through both ends of the

filter holder IRH5. An IR-cut filter IR5 is disposed in the filter holder IRH5 and is located in the through hole IRH of the filter holder IRH5, so that the IR-cut filter IR5 is located above the image sensing component S. The outer holder OH5 is fixed on the filter holder IRH5 and has an outer through hole UH5 penetrating through both ends of the outer holder OH5. The outer through hole UH5 and the through hole IRH of the filter holder IRH5 constitute the focusing hole. A movable base MB5 is disposed in the outer holder OH5 to be located in the outer through hole UH5, and is controllable to move relative to the outer holder OH5 in the outer through hole UH5. In the current embodiment, a distance from an outer wall of the outer holder OH5 to an inner wall of the inner through hole of the inner holder LH1 in a direction perpendicular to the optical axis of the lens group L is denoted by TH1. In addition, the optical image capturing modules according to the fifth structural embodiment satisfies the conditions of the first structural embodiment, and could be fixed by a glue to carry out the active alignment assembly, which could keep small in size and provide high imaging quality as well. Moreover, a glue is coated between the outer holder OH5 and the filter holder IRH5, and the outer holder OH5 and the filter holder IRH5 are fixed to each other via the glue, so that the outer holder OH5 is fixed on the filter holder IRH5.

[0086] The optical image capturing modules according to the sixth structural embodiment is illustrated in FIG. 1F, which has almost the same structure with that of the fifth structural embodiment, except that an outer peripheral wall of a lens barrel B6 has an external thread OT6 thereon, and an inner wall of an inner through hole DH6 of an inner holder LH6 has an inner thread IT6 thereon, wherein the inner thread IT6 is adapted to be screwed with the external thread OT6, thereby the lens barrel B6 is disposed in the inner holder LH6 and is located in the inner through hole DH6. In addition, the optical image capturing modules according to the sixth structural embodiment satisfies the conditions of the first structural embodiment, and could be fixed by a glue to carry out the active alignment assembly, which could keep small in size and provide high imaging quality as well.

[0087] The optical image capturing modules according to the seventh structural embodiment is illustrated in FIG. 1G, which has almost the same structure with that of the fifth structural embodiment, except that a movable base MB7 is integrally formed as a monolithic unit, instead of being separated to a lens barrel and an inner holder, which reduces the time required for producing components and for assembling. In addition, the optical image capturing modules according to the seventh structural embodiment satisfies the conditions of the first structural embodiment, and could be fixed by a glue to carry out the active alignment assembly, which could keep small in size and provide high imaging quality as well.

[0088] Furthermore, the optical embodiments will be described in detail as follow. The optical image capturing module could work in three wavelengths, including 486.1 nm, 587.5 nm, and 656.2 nm, wherein 587.5 nm is the main reference wavelength and is the reference wavelength for obtaining the technical characters. The optical image capturing module could also work in five wavelengths, including 470 nm, 510 nm, 555 nm, 610 nm, and 650 nm wherein 555 nm is the main reference wavelength, and is the reference wavelength for obtaining the technical characters.

[0089] The optical image capturing module of the present invention satisfies $0.5 \leq \Sigma PPR / \Sigma NPR \leq 15$, and a preferable range is $1 \leq \Sigma PPR / \Sigma NPR \leq 3.0$, where PPR is a ratio of the focal length f of the optical image capturing module to a focal length f_p of each of lenses with positive refractive power; NPR is a ratio of the focal length f of the optical image capturing module to a focal length f_n of each of lenses with negative refractive power; ΣPPR is a sum of the PPRs of each positive lens; and ΣNPR is a sum of the NPRs of each negative lens. It is helpful for control of an entire refractive power and an entire length of the optical image capturing module.

[0090] The optical image capturing module further include an image sensor provided on the image plane. The optical image capturing module of the present invention satisfies $HOS/HOI \leq 50$ and $0.5 \leq HOS/f \leq 150$, and a preferable range is $1 \leq HOS/HOI \leq 40$ and $1 \leq HOS/f \leq 140$, where HOI is a half of a diagonal of an effective sensing area of the image sensor, i.e., the maximum image height, and HOS is a height of the optical image capturing module, i.e. a distance on the optical axis between the object-side surface of the first lens and the image plane. It is helpful for reduction of the size of the optical image capturing module for used in compact cameras.

[0091] The optical image capturing module of the present invention further is provided with an aperture to increase image quality.

[0092] In the optical image capturing module of the present invention, the aperture could be a front aperture or a middle aperture, wherein the front aperture is provided between the object and the first lens, and the middle is provided between the first lens and the image plane. The front aperture provides a long distance between an exit pupil of the optical image capturing module and the image plane, which allows more elements to be installed. The middle could enlarge a view angle of view of the optical image capturing module and increase the efficiency of the image sensor. The optical image capturing module satisfies $0.1 \leq \ln S / HOS \leq 1.1$, where $\ln S$ is a distance between the aperture and the image surface. It is helpful for size reduction and wide angle.

[0093] The optical image capturing module of the present invention satisfies $0.1 \leq \Sigma TP / \ln TL \leq 0.9$, where $\ln TL$ is a distance between the object-side surface of the first lens and the image-side surface of the sixth lens, and ΣTP is a sum of central thicknesses of the lenses on the optical axis. It is helpful for the contrast of image and yield rate of manufacture and provides a suitable back focal length for installation of other elements. In addition, the optical image capturing module of the present invention satisfies $0.1 \leq \ln TL / HOS \leq 0.95$, which is helpful for reduction of the size of the optical image capturing module for used in compact cameras.

[0094] The optical image capturing system has a maximum image height HOI on the image plane vertical to the optical axis. A transverse aberration at 0.7 HOI in the positive direction of the tangential ray fan aberration after the longest operation wavelength of visible light passing through the edge of the entrance pupil is denoted by PLTA; a transverse aberration at 0.7 HOI in the positive direction of the tangential ray fan aberration after the shortest operation wavelength of visible light passing through the edge of the entrance pupil is denoted by PSTA; a transverse aberration at 0.7 HOI in the negative direction of the tangential ray fan aberration after the longest operation wavelength of

visible light passing through the edge of the entrance pupil is denoted by NLTA; a transverse aberration at 0.7 HOI in the negative direction of the tangential ray fan aberration after the shortest operation wavelength of visible light passing through the edge of the entrance pupil is denoted by NSTA; a transverse aberration at 0.7 HOI of the sagittal ray fan aberration after the longest operation wavelength of visible light passing through the edge of the entrance pupil is denoted by SLTA; a transverse aberration at 0.7 HOI of the sagittal ray fan aberration after the shortest operation wavelength of visible light passing through the edge of the entrance pupil is denoted by SSTA. In addition, the optical image capturing module has a better image performance when the optical image capturing module of the present invention satisfies $PLTA \leq 100 \mu\text{m}$; $PSTA \leq 100 \mu\text{m}$; $NLTA \leq 100 \mu\text{m}$; $NSTA \leq 100 \mu\text{m}$; $SLTA \leq 100 \mu\text{m}$; and $SSTA \leq 100 \mu\text{m}$.

[0095] The optical image capturing module of the present invention satisfies $0.001 \leq |R1/R2| \leq 25$, and a preferable range is $0.01 \leq |R1/R2| < 12$, where R1 is a radius of curvature of the object-side surface of the first lens, and R2 is a radius of curvature of the image-side surface of the first lens. It provides the first lens with a suitable positive refractive power to reduce the increase rate of the spherical aberration.

[0096] The optical image capturing module of the present invention satisfies $-7 < (R11 - R12)/(R11 + R12) < 50$, where R11 is a radius of curvature of the object-side surface of the sixth lens, and R12 is a radius of curvature of the image-side surface of the sixth lens. It may modify the astigmatic field curvature.

[0097] The optical image capturing module of the present invention satisfies $IN12/f \leq 60$, where IN12 is a distance on the optical axis between the first lens and the second lens. It may correct chromatic aberration and improve the performance.

[0098] The optical image capturing module of the present invention satisfies $IN56/f \leq 3.0$, where IN56 is a distance on the optical axis between the fifth lens and the sixth lens. It may correct chromatic aberration and improve the performance.

[0099] The optical image capturing module of the present invention satisfies $0.1 \leq (TP1 + IN12)/TP2 \leq 10$, where TP1 is a central thickness of the first lens on the optical axis, and TP2 is a central thickness of the second lens on the optical axis. It may control the sensitivity of manufacture of the optical image capturing module and improve the performance.

[0100] The optical image capturing module of the present invention satisfies $0.1 \leq (TP6 + IN56)/TP5 \leq 15$, where TP5 is a central thickness of the fifth lens on the optical axis, TP6 is a central thickness of the sixth lens on the optical axis, and IN56 is a distance between the fifth lens and the sixth lens. It may control the sensitivity of manufacture of the optical image capturing module and improve the performance.

[0101] The optical image capturing module of the present invention satisfies $0.1 \leq TP4/(IN34 + TP4 + IN45) < 1$ where TP2 is a central thickness of the second lens on the optical axis, TP3 is a central thickness of the third lens on the optical axis, TP4 is a central thickness of the fourth lens on the optical axis, IN34 is a distance on the optical axis between the third lens and the fourth lens, IN45 is a distance on the optical axis between the fourth lens and the fifth lens, and InTL is a distance between the object-side surface of the first lens and the image-side surface of the seventh lens. It may

fine tune and correct the aberration of the incident rays layer by layer, and reduce the height of the optical image capturing module.

[0102] The optical image capturing module satisfies $0 \text{ mm} \leq HVT61 \leq 3 \text{ mm}$; $0 \text{ mm} < HVT62 \leq 6 \text{ mm}$; $0 \leq HVT61/HVT62$; $0 \text{ mm} \leq |SGC61| \leq 0.5 \text{ mm}$; $0 \text{ mm} < |SGC62| \leq 2 \text{ mm}$; and $0 < |SGC62|/(|SGC62| + TP6) \leq 0.9$, where HVT61 a distance perpendicular to the optical axis between the critical point C61 on the object-side surface of the sixth lens and the optical axis; HVT62 a distance perpendicular to the optical axis between the critical point C62 on the image-side surface of the sixth lens and the optical axis; SGC61 is a distance on the optical axis between a point on the object-side surface of the sixth lens where the optical axis passes through and a point where the critical point C61 projects on the optical axis; SGC62 is a distance on the optical axis between a point on the image-side surface of the sixth lens where the optical axis passes through and a point where the critical point C62 projects on the optical axis. It is helpful to correct the off-axis view field aberration.

[0103] The optical image capturing module satisfies $0.2 \leq HVT62/HOI \leq 0.9$, and preferably satisfies $0.3 \leq HVT62/HOI \leq 0.8$. It may help to correct the peripheral aberration.

[0104] The optical image capturing module satisfies $0 \leq HVT62/HOS \leq 0.5$, and preferably satisfies $0.2 \leq HVT62/HOS \leq 0.45$. It may help to correct the peripheral aberration.

[0105] The optical image capturing module of the present invention satisfies $0 < SGI611/(SGI611 + TP6) \leq 0.9$; $0 < SGI621/(SGI621 + TP6) \leq 0.9$, and it is preferable to satisfy $0.1 \leq SGI611/(SGI611 + TP6) \leq 0.6$; $0.1 \leq SGI621/(SGI621 + TP7) \leq 0.6$, where SGI611 is a displacement on the optical axis from a point on the object-side surface of the sixth lens, through which the optical axis passes, to a point where the inflection point on the object-side surface, which is the closest to the optical axis, projects on the optical axis, and SGI621 is a displacement on the optical axis from a point on the image-side surface of the sixth lens, through which the optical axis passes, to a point where the inflection point on the image-side surface, which is the closest to the optical axis, projects on the optical axis.

[0106] The optical image capturing module of the present invention satisfies $0 < SGI612/(SGI612 + TP6) \leq 0.9$; $0 < SGI622/(SGI622 + TP6) \leq 0.9$, and it is preferable to satisfy $0.1 \leq SGI612/(SGI612 + TP6) \leq 0.6$; $0.1 \leq SGI622/(SGI622 + TP6) \leq 0.6$, where SGI612 is a displacement on the optical axis from a point on the object-side surface of the sixth lens, through which the optical axis passes, to a point where the inflection point on the object-side surface, which is the second closest to the optical axis, projects on the optical axis, and SGI622 is a displacement on the optical axis from a point on the image-side surface of the sixth lens, through which the optical axis passes, to a point where the inflection point on the object-side surface, which is the second closest to the optical axis, projects on the optical axis.

[0107] The optical image capturing module of the present invention satisfies $0.001 \text{ mm} \leq |HIF611| < 5 \text{ mm}$; $0.001 \text{ mm} \leq |HIF621| \leq 5 \text{ mm}$, and it is preferable to satisfy $0.1 \text{ mm} \leq |HIF611| \leq 3.5 \text{ mm}$; $1.5 \text{ mm} \leq |HIF621| \leq 3.5 \text{ mm}$, where HIF611 is a distance perpendicular to the optical axis between the inflection point on the object-side surface of the sixth lens, which is the closest to the optical axis, and the optical axis; HIF621 is a distance perpendicular to the

optical axis between the inflection point on the image-side surface of the sixth lens, which is the closest to the optical axis, and the optical axis.

[0108] The optical image capturing module of the present invention satisfies $0.001 \text{ mm} \leq |HIF612| \leq 5 \text{ mm}$; $0.001 \text{ mm} \leq |HIF622| \leq 5 \text{ mm}$, and it is preferable to satisfy $0.1 \text{ mm} \leq |HIF622| \leq 3.5 \text{ mm}$; $0.1 \text{ mm} \leq |HIF612| \leq 3.5 \text{ mm}$, where HIF612 is a distance perpendicular to the optical axis between the inflection point on the object-side surface of the sixth lens, which is the second closest to the optical axis, and the optical axis; HIF622 is a distance perpendicular to the optical axis between the inflection point on the image-side surface of the sixth lens, which is the second closest to the optical axis, and the optical axis.

[0109] The optical image capturing module of the present invention satisfies $0.001 \text{ mm} \leq |HIF613| \leq 5 \text{ mm}$; $0.001 \text{ mm} \leq |HIF623| \leq 5 \text{ mm}$, and it is preferable to satisfy $0.1 \text{ mm} \leq |HIF623| \leq 3.5 \text{ mm}$; $0.1 \text{ mm} \leq |HIF613| \leq 3.5 \text{ mm}$, where HIF613 is a distance perpendicular to the optical axis between the inflection point on the object-side surface of the sixth lens, which is the third closest to the optical axis, and the optical axis; HIF623 is a distance perpendicular to the optical axis between the inflection point on the image-side surface of the sixth lens, which is the third closest to the optical axis, and the optical axis.

[0110] The optical image capturing module of the present invention satisfies $0.001 \text{ mm} \leq |HIF614| \leq 5 \text{ mm}$; $0.001 \text{ mm} \leq |HIF624| \leq 5 \text{ mm}$, and it is preferable to satisfy $0.1 \text{ mm} \leq |HIF624| \leq 3.5 \text{ mm}$; $0.1 \text{ mm} \leq |HIF614| \leq 3.5 \text{ mm}$, where HIF614 is a distance perpendicular to the optical axis between the inflection point on the object-side surface of the sixth lens, which is the fourth closest to the optical axis, and the optical axis; HIF624 is a distance perpendicular to the optical axis between the inflection point on the image-side surface of the sixth lens, which is the fourth closest to the optical axis, and the optical axis.

[0111] The optical image capturing module of the present invention satisfies $0 < (TH1+TH2)/HOI \leq 0.95$; $0 < (TH1+TH2)/HOS \leq 0.95$; $0 < 2 * (TH1+TH2)/\Phi A \leq 0.95$; and it is preferable to satisfy $0 < (TH1+TH2)/HOI \leq 0.5$; $0 < (TH1+TH2)/HOS \leq 0.5$; $0 < 2 * (TH1+TH2)/\Phi A \leq 0.5$.

[0112] In an embodiment, the lenses of high Abbe number and the lenses of low Abbe number are arranged in an interlaced arrangement that could be helpful for correction of aberration of the optical image capturing module.

[0113] An equation of aspheric surface is

$$z = ch^2 / [1 + \sqrt{1 - (k+1)c^2h^2}] + A4h^4 + A6h^6 + A8h^8 + A10h^{10} + A12h^{12} + A14h^{14} + A16h^{16} + A18h^{18} + A20h^{20} + \dots \quad (1)$$

[0114] where z is a depression of the aspheric surface; k is conic constant; c is reciprocal of the radius of curvature; and A4, A6, A8, A10, A12, A14, A16, A18, and A20 are high-order aspheric coefficients.

[0115] In the optical image capturing module, the lenses could be made of plastic or glass. The plastic lenses may reduce the weight and lower the cost of the optical image capturing module, and the glass lenses may control the thermal effect and enlarge the space for arrangement of the refractive power of the optical image capturing module. In addition, the opposite surfaces (object-side surface and image-side surface) of the first to the seventh lenses could be aspheric that could obtain more control parameters to reduce aberration. The number of aspheric glass lenses could be less

than the conventional spherical glass lenses, which is helpful for reduction of the height of the optical image capturing module.

[0116] When the lens has a convex surface, which means that the surface is convex around a position, through which the optical axis passes, and when the lens has a concave surface, which means that the surface is concave around a position, through which the optical axis passes.

[0117] The optical image capturing module of the present invention could be applied in a dynamic focusing optical image capturing module. It is superior in the correction of aberration and high imaging quality so that it could be allied in lots of fields.

[0118] The optical image capturing module of the present invention could further include a driving module to meet different demands, wherein the driving module could be coupled with the movable base or the lenses to move the lenses. The driving module could be a voice coil motor (VCM), which is used to move the lens for focusing, or could be an optical image stabilization (OIS) component, which is used to lower the possibility of having the problem of image blurring which is caused by subtle movements of the lens while shooting.

[0119] To meet different requirements, at least one lens among the first lens to the seventh lens of the optical image capturing module of the present invention could be a light filter, which filters out light of wavelength shorter than 500 nm. Such effect could be achieved by coating on at least one surface of the lens, or by using materials capable of filtering out short waves to make the lens.

[0120] To meet different requirements, the image plane of the optical image capturing module in the present invention could be either flat or curved. If the image plane is curved (e.g., a sphere with a radius of curvature), the incidence angle required for focusing light on the image plane could be decreased, which is not only helpful to shorten the length of the optical image capturing module (TTL), but also helpful to increase the relative illuminance.

[0121] We provide several optical embodiments in conjunction with the accompanying drawings for the best understanding. In practice, the optical embodiments of the present invention could be applied to other structural embodiments.

First Optical Embodiment

[0122] As shown in FIG. 2A and FIG. 2B, an optical image capturing module 10 of the first optical embodiment of the present invention includes, along an optical axis from an object side to an image side, a first lens 110, an aperture 100, a second lens 120, a third lens 130, a fourth lens 140, a fifth lens 150, a sixth lens 160, an IR-cut filter 180, an image plane 190, and an image sensor 192.

[0123] The first lens 110 has negative refractive power and is made of plastic. An object-side surface 112 thereof, which faces the object side, is a concave aspheric surface, and an image-side surface 114 thereof, which faces the image side, is a concave aspheric surface. The object-side surface 112 has two inflection points. A profile curve length of the maximum effective half diameter of the object-side surface 112 of the first lens 110 is denoted by ARS11, and a profile curve length of the maximum effective half diameter of the image-side surface 114 of the first lens 110 is denoted by ARS12. A profile curve length of a half of the entrance pupil diameter (HEP) of the object-side surface 112 of the first lens 110 is denoted by ARE11, and a profile curve length of

a half of the entrance pupil diameter (HEP) of the image-side surface **114** of the first lens **110** is denoted by ARE12. A thickness of the first lens **110** on the optical axis is denoted by TP1.

[0124] The first lens satisfies $SGI111=-0.0031$ mm; $|SGI111|/(|SGI111+TP1|)=0.0016$, where a displacement on the optical axis from a point on the object-side surface **112** of the first lens **110**, through which the optical axis passes, to a point where the inflection point on the object-side surface **112**, which is the closest to the optical axis, projects on the optical axis, is denoted by SGI111, and a displacement on the optical axis from a point on the image-side surface **114** of the first lens **110**, through which the optical axis passes, to a point where the inflection point on the image-side surface **114**, which is the closest to the optical axis, projects on the optical axis is denoted by SGI121.

[0125] The first lens **110** satisfies $SGI112=1.3178$ mm; $|SGI112|/(|SGI112+TP1|)=0.4052$, where a displacement on the optical axis from a point on the object-side surface **112** of the first lens **110**, through which the optical axis passes, to a point where the inflection point on the object-side surface **112**, which is the second closest to the optical axis, projects on the optical axis, is denoted by SGI112, and a displacement on the optical axis from a point on the image-side surface **114** of the first lens **110**, through which the optical axis passes, to a point where the inflection point on the image-side surface **114**, which is the second closest to the optical axis, projects on the optical axis is denoted by SGI122.

[0126] The first lens **110** satisfies $HIF111=0.5557$ mm; $HIF111/HOI=0.1111$, where a displacement perpendicular to the optical axis from a point on the object-side surface **112** of the first lens **110**, through which the optical axis passes, to the inflection point, which is the closest to the optical axis is denoted by HIF111, and a displacement perpendicular to the optical axis from a point on the image-side surface **114** of the first lens **110**, through which the optical axis passes, to the inflection point, which is the closest to the optical axis is denoted by HIF121.

[0127] The first lens **110** satisfies $HIF112=5.3732$ mm; $HIF112/HOI=1.0746$, where a displacement perpendicular to the optical axis from a point on the object-side surface **112** of the first lens **110**, through which the optical axis passes, to the inflection point, which is the second closest to the optical axis is denoted by HIF112, and a displacement perpendicular to the optical axis from a point on the image-side surface **114** of the first lens **110**, through which the optical axis passes, to the inflection point, which is the second closest to the optical axis is denoted by HIF122.

[0128] The second lens **120** has positive refractive power and is made of plastic. An object-side surface **122** thereof, which faces the object side, is a convex aspheric surface, and an image-side surface **124** thereof, which faces the image side, is a convex aspheric surface. The object-side surface **122** has an inflection point. A profile curve length of the maximum effective half diameter of the object-side surface **122** of the second lens **120** is denoted by ARS21, and a profile curve length of the maximum effective half diameter of the image-side surface **124** of the second lens **120** is denoted by ARS22. A profile curve length of a half of the entrance pupil diameter (HEP) of the object-side surface **122** of the second lens **120** is denoted by ARE21, and a profile curve length of a half of the entrance pupil diameter (HEP) of the image-side surface **124** of the second lens **120** is

denoted by ARE22. A thickness of the second lens **120** on the optical axis is denoted by TP2.

[0129] The second lens **120** satisfies $SGI211=0.1069$ mm; $|SGI211|/(|SGI211+TP2|)=0.0412$; $SGI221=0$ mm; $|SGI221|/(|SGI221+TP2|)=0$, where a displacement on the optical axis from a point on the object-side surface **122** of the second lens **120**, through which the optical axis passes, to a point where the inflection point on the object-side surface **122**, which is the closest to the optical axis, projects on the optical axis, is denoted by SGI211, and a displacement on the optical axis from a point on the image-side surface **124** of the second lens **120**, through which the optical axis passes, to a point where the inflection point on the image-side surface **124**, which is the closest to the optical axis, projects on the optical axis is denoted by SGI221.

[0130] The second lens **120** satisfies $HIF211=1.1264$ mm; $HIF211/HOI=0.2253$; $HIF221=0$ mm; $HIF221/HOI=0$, where a displacement perpendicular to the optical axis from a point on the object-side surface **122** of the second lens **120**, through which the optical axis passes, to the inflection point, which is the closest to the optical axis is denoted by HIF211, and a displacement perpendicular to the optical axis from a point on the image-side surface **124** of the second lens **120**, through which the optical axis passes, to the inflection point, which is the closest to the optical axis is denoted by HIF221.

[0131] The third lens **130** has negative refractive power and is made of plastic. An object-side surface **132**, which faces the object side, is a concave aspheric surface, and an image-side surface **134**, which faces the image side, is a convex aspheric surface. The object-side surface **132** has an inflection point, and the image-side surface **134** has an inflection point. The object-side surface **122** has an inflection point. A profile curve length of the maximum effective half diameter of the object-side surface **132** of the third lens **130** is denoted by ARS31, and a profile curve length of the maximum effective half diameter of the image-side surface **134** of the third lens **130** is denoted by ARS32. A profile curve length of a half of the entrance pupil diameter (HEP) of the object-side surface **132** of the third lens **130** is denoted by ARE31, and a profile curve length of a half of the entrance pupil diameter (HEP) of the image-side surface **134** of the third lens **130** is denoted by ARE32. A thickness of the third lens **130** on the optical axis is denoted by TP3.

[0132] The third lens **130** satisfies $SGI311=-0.3041$ mm; $|SGI311|/(|SGI311+TP3|)=0.4445$; $SGI321=-0.1172$ mm; $|SGI321|/(|SGI321+TP3|)=0.2357$, where SGI311 is a displacement on the optical axis from a point on the object-side surface **132** of the third lens **130**, through which the optical axis passes, to a point where the inflection point on the object-side surface **132**, which is the closest to the optical axis, projects on the optical axis, and SGI321 is a displacement on the optical axis from a point on the image-side surface **134** of the third lens **130**, through which the optical axis passes, to a point where the inflection point on the image-side surface **134**, which is the closest to the optical axis, projects on the optical axis.

[0133] The third lens **130** satisfies $HIF311=1.5907$ mm; $HIF311/HOI=0.3181$; $HIF321=1.3380$ mm; $HIF321/HOI=0.2676$, where HIF311 is a distance perpendicular to the optical axis between the inflection point on the object-side surface **132** of the third lens **130**, which is the closest to the optical axis, and the optical axis; HIF321 is a distance perpendicular to the optical axis between the inflection point

on the image-side surface **134** of the third lens **130**, which is the closest to the optical axis, and the optical axis.

[0134] The fourth lens **140** has positive refractive power and is made of plastic. An object-side surface **142**, which faces the object side, is a convex aspheric surface, and an image-side surface **144**, which faces the image side, is a concave aspheric surface. The object-side surface **142** has two inflection points, and the image-side surface **144** has an inflection point. A profile curve length of the maximum effective half diameter of the object-side surface **142** of the fourth lens **140** is denoted by ARS41, and a profile curve length of the maximum effective half diameter of the image-side surface **144** of the fourth lens **140** is denoted by ARS42. A profile curve length of a half of the entrance pupil diameter (HEP) of the object-side surface **142** of the fourth lens **140** is denoted by ARE41, and a profile curve length of a half of the entrance pupil diameter (HEP) of the image-side surface **144** of the fourth lens **140** is denoted by ARE42. A thickness of the fourth lens **140** on the optical axis is TP4.

[0135] The fourth lens **140** satisfies $SGI411=0.0070$ mm; $|SGI411|/(|SGI411|+TP4)=0.0056$; $SGI421=0.0006$ mm; $|SGI421|/(|SGI421|+TP4)=0.0005$, where SGI411 is a displacement on the optical axis from a point on the object-side surface **142** of the fourth lens **140**, through which the optical axis passes, to a point where the inflection point on the object-side surface **142**, which is the closest to the optical axis, projects on the optical axis, and SGI421 is a displacement on the optical axis from a point on the image-side surface **144** of the fourth lens **140**, through which the optical axis passes, to a point where the inflection point on the image-side surface **144**, which is the closest to the optical axis, projects on the optical axis.

[0136] The fourth lens **140** satisfies $SGI412=-0.2078$ mm; $|SGI412|/(|SGI412|+TP4)=0.1439$, where SGI412 is a displacement on the optical axis from a point on the object-side surface **142** of the fourth lens **140**, through which the optical axis passes, to a point where the inflection point on the object-side surface **142**, which is the second closest to the optical axis, projects on the optical axis, and SGI422 is a displacement on the optical axis from a point on the image-side surface **144** of the fourth lens **140**, through which the optical axis passes, to a point where the inflection point on the image-side surface **144**, which is the second closest to the optical axis, projects on the optical axis.

[0137] The fourth lens **140** further satisfies $HIF411=0.4706$ mm; $HIF411/HOI=0.0941$; $HIF421=0.1721$ mm; $HIF421/HOI=0.0344$, where HIF411 is a distance perpendicular to the optical axis between the inflection point on the object-side surface **142** of the fourth lens **140**, which is the closest to the optical axis, and the optical axis; HIF421 is a distance perpendicular to the optical axis between the inflection point on the image-side surface **144** of the fourth lens **140**, which is the closest to the optical axis, and the optical axis.

[0138] The fourth lens **140** satisfies $HIF412=2.0421$ mm; $HIF412/HOI=0.4084$, where HIF412 is a distance perpendicular to the optical axis between the inflection point on the object-side surface **142** of the fourth lens **140**, which is the second closest to the optical axis, and the optical axis; HIF422 is a distance perpendicular to the optical axis between the inflection point on the image-side surface **144** of the fourth lens **140**, which is the second closest to the optical axis, and the optical axis.

[0139] The fifth lens **150** has positive refractive power and is made of plastic. An object-side surface **152**, which faces the object side, is a convex aspheric surface, and an image-side surface **154**, which faces the image side, is a convex aspheric surface. The object-side surface **152** has two inflection points, and the image-side surface **154** has an inflection point. A profile curve length of the maximum effective half diameter of the object-side surface **152** of the fifth lens **150** is denoted by ARS51, and a profile curve length of the maximum effective half diameter of the image-side surface **154** of the fifth lens **150** is denoted by ARS52. A profile curve length of a half of the entrance pupil diameter (HEP) of the object-side surface **152** of the fifth lens **150** is denoted by ARE51, and a profile curve length of a half of the entrance pupil diameter (HEP) of the image-side surface **154** of the fifth lens **150** is denoted by ARE52. A thickness of the fifth lens **150** on the optical axis is denoted by TP5.

[0140] The fifth lens **150** satisfies $SGI511=0.00364$ mm; $SGI521=-0.63365$ mm; $|SGI511|/(|SGI511|+TP5)=0.00338$; $|SGI521|/(|SGI521|+TP5)=0.37154$, where SGI511 is a displacement on the optical axis from a point on the object-side surface **152** of the fifth lens **150**, through which the optical axis passes, to a point where the inflection point on the object-side surface **152**, which is the closest to the optical axis, projects on the optical axis, and SGI521 is a displacement on the optical axis from a point on the image-side surface **154** of the fifth lens **150**, through which the optical axis passes, to a point where the inflection point on the image-side surface **154**, which is the closest to the optical axis, projects on the optical axis.

[0141] The fifth lens **150** satisfies $SGI512=-0.32032$ mm; $|SGI512|/(|SGI512|+TP5)=0.23009$, where SGI512 is a displacement on the optical axis from a point on the object-side surface **152** of the fifth lens **150**, through which the optical axis passes, to a point where the inflection point on the object-side surface **152**, which is the second closest to the optical axis, projects on the optical axis, and SGI522 is a displacement on the optical axis from a point on the image-side surface **154** of the fifth lens **150**, through which the optical axis passes, to a point where the inflection point on the image-side surface **154**, which is the second closest to the optical axis, projects on the optical axis.

[0142] The fifth lens **150** satisfies $SGI513=0$ mm; $SGI523=0$ mm; $|SGI513|/(|SGI513|+TP5)=0$; $|SGI523|/(|SGI523|+TP5)=0$, where SGI513 is a displacement on the optical axis from a point on the object-side surface **152** of the fifth lens **150**, through which the optical axis passes, to a point where the inflection point on the object-side surface **152**, which is the third closest to the optical axis, projects on the optical axis, and SGI523 is a displacement on the optical axis from a point on the image-side surface **154** of the fifth lens **150**, through which the optical axis passes, to a point where the inflection point on the image-side surface **154**, which is the third closest to the optical axis, projects on the optical axis.

[0143] The fifth lens **150** satisfies $SGI514=0$ mm; $SGI524=0$ mm; $|SGI514|/(|SGI514|+TP5)=0$; $|SGI524|/(|SGI524|+TP5)=0$, where SGI514 is a displacement on the optical axis from a point on the object-side surface **152** of the fifth lens **150**, through which the optical axis passes, to a point where the inflection point on the object-side surface **152**, which is the fourth closest to the optical axis, projects on the optical axis, and SGI524 is a displacement on the optical axis from a point on the image-side surface **154** of

the fifth lens **150**, through which the optical axis passes, to a point where the inflection point on the image-side surface **154**, which is the fourth closest to the optical axis, projects on the optical axis.

[0144] The fifth lens **150** further satisfies $HIF511=0.28212$ mm; $HIF521=2.13850$ mm; $HIF511/HOI=0.05642$; $HIF521/HOI=0.42770$, where $HIF511$ is a distance perpendicular to the optical axis between the inflection point on the object-side surface **152** of the fifth lens **150**, which is the closest to the optical axis, and the optical axis; $HIF521$ is a distance perpendicular to the optical axis between the inflection point on the image-side surface **154** of the fifth lens **150**, which is the closest to the optical axis, and the optical axis.

[0145] The fifth lens **150** further satisfies $HIF512=2.51384$ mm; $HIF512/HOI=0.50277$, where $HIF512$ is a distance perpendicular to the optical axis between the inflection point on the object-side surface **152** of the fifth lens **150**, which is the second closest to the optical axis, and the optical axis; $HIF522$ is a distance perpendicular to the optical axis between the inflection point on the image-side surface **154** of the fifth lens **150**, which is the second closest to the optical axis, and the optical axis.

[0146] The fifth lens **150** further satisfies $HIF513=0$ mm; $HIF513/HOI=0$; $HIF523=0$ mm; $HIF523/HOI=0$, where $HIF513$ is a distance perpendicular to the optical axis between the inflection point on the object-side surface **152** of the fifth lens **150**, which is the third closest to the optical axis, and the optical axis; $HIF523$ is a distance perpendicular to the optical axis between the inflection point on the image-side surface **154** of the fifth lens **150**, which is the third closest to the optical axis, and the optical axis.

[0147] The fifth lens **150** further satisfies $HIF514=0$ mm; $HIF514/HOI=0$; $HIF524=0$ mm; $HIF524/HOI=0$, where $HIF514$ is a distance perpendicular to the optical axis between the inflection point on the object-side surface **152** of the fifth lens **150**, which is the fourth closest to the optical axis, and the optical axis; $HIF524$ is a distance perpendicular to the optical axis between the inflection point on the image-side surface **154** of the fifth lens **150**, which is the fourth closest to the optical axis, and the optical axis.

[0148] The sixth lens **160** has negative refractive power and is made of plastic. An object-side surface **162**, which faces the object side, is a concave surface, and an image-side surface **164**, which faces the image side, is a concave surface. The object-side surface **162** has two inflection points, and the image-side surface **164** has an inflection point. Whereby, the incident angle of each view field entering the sixth lens **160** could be effectively adjusted to improve aberration. A profile curve length of the maximum effective half diameter of the object-side surface **162** of the sixth lens **160** is denoted by $ARS61$, and a profile curve length of the maximum effective half diameter of the image-side surface **164** of the sixth lens **160** is denoted by $ARS62$. A profile curve length of a half of the entrance pupil diameter (HEP) of the object-side surface **162** of the sixth lens **160** is denoted by $ARE61$, and a profile curve length of a half of the entrance pupil diameter (HEP) of the image-side surface **164** of the sixth lens **160** is denoted by $ARE62$. A thickness of the sixth lens **160** on the optical axis is denoted by $TP6$.

[0149] The sixth lens **160** satisfies $SGI611=-0.38558$ mm; $SGI621=0.12386$ mm; $|SGI611|/(|SGI611|+TP6)=0.27212$; $|SGI621|/(|SGI621|+TP6)=0.10722$, where $SGI611$ is a displacement on the optical axis from a point on the object-side

surface **162** of the sixth lens **160**, through which the optical axis passes, to a point where the inflection point on the object-side surface **162**, which is the closest to the optical axis, projects on the optical axis, and $SGI621$ is a displacement on the optical axis from a point on the image-side surface **164** of the sixth lens **160**, through which the optical axis passes, to a point where the inflection point on the image-side surface **164**, which is the closest to the optical axis, projects on the optical axis.

[0150] The sixth lens **160** satisfies $SGI612=-0.47400$ mm; $|SGI612|/(|SGI612|+TP6)=0.31488$; $SGI622=0$ mm; $|SGI622|/(|SGI622|+TP6)=0$, where $SGI612$ is a displacement on the optical axis from a point on the object-side surface **162** of the sixth lens **160**, through which the optical axis passes, to a point where the inflection point on the object-side surface **162**, which is the second closest to the optical axis, projects on the optical axis, and $SGI622$ is a displacement on the optical axis from a point on the image-side surface **164** of the sixth lens **160**, through which the optical axis passes, to a point where the inflection point on the image-side surface **164**, which is the second closest to the optical axis, projects on the optical axis.

[0151] The sixth lens **160** further satisfies $HIF611=2.24283$ mm; $HIF621=1.07376$ mm; $HIF611/HOI=0.44857$; $HIF621/HOI=0.21475$, where $HIF611$ is a distance perpendicular to the optical axis between the inflection point on the object-side surface **162** of the sixth lens **160**, which is the closest to the optical axis, and the optical axis; $HIF621$ is a distance perpendicular to the optical axis between the inflection point on the image-side surface **164** of the sixth lens **160**, which is the closest to the optical axis, and the optical axis.

[0152] The sixth lens **160** further satisfies $HIF612=2.48895$ mm; $HIF612/HOI=0.49779$, where $HIF612$ is a distance perpendicular to the optical axis between the inflection point on the object-side surface **162** of the sixth lens **160**, which is the second closest to the optical axis, and the optical axis; $HIF622$ is a distance perpendicular to the optical axis between the inflection point on the image-side surface **164** of the sixth lens **160**, which is the second closest to the optical axis, and the optical axis.

[0153] The sixth lens **160** further satisfies $HIF613=0$ mm; $HIF613/HOI=0$; $HIF623=0$ mm; $HIF623/HOI=0$, where $HIF613$ is a distance perpendicular to the optical axis between the inflection point on the object-side surface **162** of the sixth lens **160**, which is the third closest to the optical axis, and the optical axis; $HIF623$ is a distance perpendicular to the optical axis between the inflection point on the image-side surface **164** of the sixth lens **160**, which is the third closest to the optical axis, and the optical axis.

[0154] The sixth lens **160** further satisfies $HIF614=0$ mm; $HIF614/HOI=0$; $HIF624=0$ mm; $HIF624/HOI=0$, where $HIF614$ is a distance perpendicular to the optical axis between the inflection point on the object-side surface **162** of the sixth lens **160**, which is the fourth closest to the optical axis, and the optical axis; $HIF624$ is a distance perpendicular to the optical axis between the inflection point on the image-side surface **164** of the sixth lens **160**, which is the fourth closest to the optical axis, and the optical axis.

[0155] The IR-cut filter **180** is made of glass and is disposed between the sixth lens **160** and the image plane **190**. The IR-cut filter **180** gives no contribution to the focal length of the optical image capturing module.

[0156] The optical image capturing module 10 of the first optical embodiment has the following parameters, which are $f=4.075$ mm; $f/HEP=1.4$; $HAF=50.001$ degrees; and $\tan(HAF)=1.1918$, where f is a focal length of the lens group; HAF is a half of the maximum field angle; and HEP is an entrance pupil diameter.

[0157] The parameters of the lenses of the first optical embodiment are $f1=-7.828$ mm; $|f/f1|=0.52060$; $f6=-4.886$; and $f1>f6$, where $f1$ is a focal length of the first lens 110; and $f6$ is a focal length of the sixth lens 160.

[0158] The first optical embodiment further satisfies $f21+f31+f4+f5=95.50815$; $|f1|+|f6|=12.71352$ and $f2+|f3|+|f4|+f5>|f1|+|f6|$, where $f2$ is a focal length of the second lens 120, $f3$ is a focal length of the third lens 130, $f4$ is a focal length of the fourth lens 140, $f5$ is a focal length of the fifth lens 150, and $f6$ is a focal length of the sixth lens 160.

[0159] The optical image capturing module 10 of the first optical embodiment further satisfies $\Sigma PPR=f/f2+f/f4+f/f5=1.63290$; $\Sigma NPR=|f/f1|+|f/f3|+|f/f6|=1.51305$; $\Sigma PPR/\Sigma NPR=1.07921$; $|f/f2|=0.69101$; $|f/f3|=0.15834$; $|f/f4|=0.06883$; $|f/f5|=0.87305$; and $|f/f6|=0.83412$, where PPR is a ratio of a focal length f of the optical image capturing module to a focal length f_p of each of the lenses with positive refractive power; and NPR is a ratio of a focal length f of the optical image capturing module to a focal length f_n of each of lenses with negative refractive power.

[0160] The optical image capturing module 10 of the first optical embodiment further satisfies $InTL+BFL=HOS$; $HOS=19.54120$ mm; $HOI=5.0$ mm; $HOS/HOI=3.90824$; $HOS/f=4.7952$; $InS=11.685$ mm; $InTL/HOS=0.9171$; and $InS/HOS=0.59794$, where $InTL$ is a distance between the object-side surface 112 of the first lens 110 and the image-side surface 164 of the sixth lens 160; HOS is a height of the image capturing system, i.e. a distance between the object-side surface 112 of the first lens 110 and the image plane 190; InS is a distance between the aperture 100 and the image plane 190; HOI is a half of a diagonal of an effective sensing area of the image sensor 192, i.e., the maximum image height; and BFL is a distance between the image-side surface 164 of the sixth lens 160 and the image plane 190.

[0161] The optical image capturing module 10 of the first optical embodiment further satisfies $\Sigma TP=8.13899$ mm; and $\Sigma TP/InTL=0.52477$, where ΣTP is a sum of the thicknesses of the lenses 110-160 with refractive power. It is helpful for the contrast of image and yield rate of manufacture and provides a suitable back focal length for installation of other elements.

[0162] The optical image capturing module 10 of the first optical embodiment further satisfies $|R1/R2|=129.9952$, where $R1$ is a radius of curvature of the object-side surface 112 of the first lens 110, and $R2$ is a radius of curvature of the image-side surface 114 of the first lens 110. It provides the first lens 110 with a suitable positive refractive power to reduce the increase rate of the spherical aberration.

[0163] The optical image capturing module 10 of the first optical embodiment further satisfies $(R11-R12)/(R11+R12)=1.27780$, where $R11$ is a radius of curvature of the object-side surface 162 of the sixth lens 160, and $R12$ is a radius of curvature of the image-side surface 164 of the sixth lens 160. It may modify the astigmatic field curvature.

[0164] The optical image capturing module 10 of the first optical embodiment further satisfies $\Sigma PP=f2+f4+f5=69.770$ mm; and $f5/(f2+f4+f5)=0.067$, where ΣPP is a sum of the focal lengths f_p of each lens with positive refractive power.

It is helpful to share the positive refractive power of a single lens to other positive lenses to avoid the significant aberration caused by the incident rays.

[0165] The optical image capturing module 10 of the first optical embodiment further satisfies $\Sigma NP=f1+f3+f6=-38.451$ mm; and $f6/(f1+f3+f6)=0.127$, where ΣNP is a sum of the focal lengths f_n of each lens with negative refractive power. It is helpful to share the negative refractive power of the sixth lens 160 to the other negative lens, which avoid the significant aberration caused by the incident rays.

[0166] The optical image capturing module 10 of the first optical embodiment further satisfies $IN12=6.418$ mm; $IN12/f=1.57491$, where $IN12$ is a distance on the optical axis between the first lens 110 and the second lens 120. It may correct chromatic aberration and improve the performance.

[0167] The optical image capturing module 10 of the first optical embodiment further satisfies $IN56=0.025$ mm; $IN56/f=0.00613$, where $IN56$ is a distance on the optical axis between the fifth lens 150 and the sixth lens 160. It may correct chromatic aberration and improve the performance.

[0168] The optical image capturing module 10 of the first optical embodiment further satisfies $TP1=1.934$ mm; $TP2=2.486$ mm; and $(TP1+IN12)/TP2=3.36005$, where $TP1$ is a central thickness of the first lens 110 on the optical axis, and $TP2$ is a central thickness of the second lens 120 on the optical axis. It may control the sensitivity of manufacture of the optical image capturing module and improve the performance.

[0169] The optical image capturing module 10 of the first optical embodiment further satisfies $TP5=1.072$ mm; $TP6=1.031$ mm; and $(TP6+IN56)/TP5=0.98555$, where $TP5$ is a central thickness of the fifth lens 150 on the optical axis, $TP6$ is a central thickness of the sixth lens 160 on the optical axis, and $IN56$ is a distance on the optical axis between the fifth lens 150 and the sixth lens 160. It may control the sensitivity of manufacture of the optical image capturing module and lower the total height of the optical image capturing module.

[0170] The optical image capturing module 10 of the first optical embodiment further satisfies $IN34=0.401$ mm; $IN45=0.025$ mm; and $TP4/(IN34+TP4+IN45)=0.74376$, where $TP4$ is a central thickness of the fourth lens 140 on the optical axis; $IN34$ is a distance on the optical axis between the third lens 130 and the fourth lens 140; $IN45$ is a distance on the optical axis between the fourth lens 140 and the fifth lens 150. It may help to slightly correct the aberration caused by the incident rays and lower the total height of the optical image capturing module.

[0171] The optical image capturing module 10 of the first optical embodiment further satisfies $InRS51=-0.34789$ mm; $InRS52=-0.88185$ mm; $|InRS51|/TP5=0.32458$; and $|InRS52|/TP5=0.82276$, where $InRS51$ is a displacement from a point on the object-side surface 152 of the fifth lens 150 passed through by the optical axis to a point on the optical axis where a projection of the maximum effective semi diameter of the object-side surface 152 of the fifth lens 150 ends; $InRS52$ is a displacement from a point on the image-side surface 154 of the fifth lens 150 passed through by the optical axis to a point on the optical axis where a projection of the maximum effective semi diameter of the image-side surface 154 of the fifth lens 150 ends; and $TP5$ is a central thickness of the fifth lens 150 on the optical axis. It is helpful for manufacturing and shaping of the lenses and is helpful to reduce the size.

[0172] The optical image capturing module 10 of the first optical embodiment further satisfies $HVT51=0.515349$ mm; and $HVT52=0$ mm, where $HVT51$ is a distance perpendicular to the optical axis between the critical point on the object-side surface 152 of the fifth lens 150 and the optical axis; and $HVT52$ is a distance perpendicular to the optical axis between the critical point on the image-side surface 154 of the fifth lens 150 and the optical axis.

[0173] The optical image capturing module 10 of the first optical embodiment further satisfies $InRS61=-0.58390$ mm; $InRS62=0.41976$ mm; $|InRS61|/TP6=0.56616$; and $|InRS62|/TP6=0.40700$, where $InRS61$ is a displacement from a point on the object-side surface 162 of the sixth lens 160 passed through by the optical axis to a point on the optical axis where a projection of the maximum effective semi diameter of the object-side surface 162 of the sixth lens 160 ends; $InRS62$ is a displacement from a point on the image-side surface 164 of the sixth lens 160 passed through by the optical axis to a point on the optical axis where a projection of the maximum effective semi diameter of the image-side surface 164 of the sixth lens 160 ends; and $TP6$ is a central thickness of the sixth lens 160 on the optical axis. It is helpful for manufacturing and shaping of the lenses and is helpful to reduce the size.

[0174] The optical image capturing module 10 of the first optical embodiment satisfies $HVT61=0$ mm; and $HVT62=0$ mm, where $HVT61$ is a distance perpendicular to the optical axis between the critical point on the object-side surface 162 of the sixth lens 160 and the optical axis; and $HVT62$ is a distance perpendicular to the optical axis between the critical point on the image-side surface 164 of the sixth lens 160 and the optical axis.

[0175] The optical image capturing module 10 of the first optical embodiment satisfies $HVT51/HOI=0.1031$. It is helpful for correction of the aberration of the peripheral view field of the optical image capturing module.

[0176] The optical image capturing module 10 of the first optical embodiment satisfies $HVT51/HOS=0.02634$. It is helpful for correction of the aberration of the peripheral view field of the optical image capturing module.

[0177] The second lens 120, the third lens 130, and the sixth lens 160 have negative refractive power. The optical image capturing module 10 of the first optical embodiment further satisfies $NA6/NA2 \leq 1$, where $NA2$ is an Abbe number of the second lens 120; $NA3$ is an Abbe number of the third lens 130; and $NA6$ is an Abbe number of the sixth lens 160. It may correct the aberration of the optical image capturing module.

[0178] The optical image capturing module 10 of the first optical embodiment further satisfies $|TDT|=2.124\%$; $|ODT|=5.076\%$, where TDT is TV distortion; and ODT is optical distortion.

[0179] The optical image capturing module 10 of the first optical embodiment further satisfies $LS=12$ mm; $\Phi A=2^*$ ($EHD62$)= 6.726 mm; $\Phi C=\Phi A+2^*TH2=7.026$ mm; $\Phi D=\Phi C+2^*(TH1+TH2)=7.426$ mm; $TH1=0.2$ mm; $TH2=0.15$ mm; $\Phi A/\Phi D=0.9057$; $TH1+TH2=0.35$ mm; $(TH1+TH2)/HOI=0.035$; $(TH1+TH2)/HOS=0.0179$; $2(TH1+TH2)/\Phi A=0.1041$; $(TH1+TH2)/LS=0.0292$, where $EHD62$ is a maximum effective half diameter of the image-side surface 164 of the sixth lens 160.

[0180] The parameters of the lenses of the first optical embodiment are listed in Table 1 and Table 2.

TABLE 1

f = 4.075 mm; f/HEP = 1.4; HAF = 50.000 deg							
Surface	Radius of curvature (mm)	Thickness (mm)	Material	Refractive index	Abbe number	Focal length (mm)	
0	Object	plane	plane				
1	1 st lens	-40.99625704	1.934	plastic	1.515	56.55	-7.828
2		4.555209289	5.923				
3	Aperture	plane	0.495				
4	2 nd lens	5.333427366	2.486	plastic	1.544	55.96	5.897
5		-6.781659971	0.502				
6	3 rd lens	-5.697794287	0.380	plastic	1.642	22.46	-25.738
7		-8.883957518	0.401				
8	4 th lens	13.19225664	1.236	plastic	1.544	55.96	59.205
9		21.55681832	0.025				
10	5 th lens	8.987806345	1.072	plastic	1.515	56.55	4.668
11		-3.158875374	0.025				
12	6 th lens	-29.46491425	1.031	plastic	1.642	22.46	-4.886
13		3.593484273	2.412				
14	Infrared rays filter	plane	0.200		1.517	64.13	
15		plane	1.420				
16	Image plane	plane					

Reference wavelength (d-line): 555 nm;

the position of blocking light: the effective half diameter of the clear aperture of the first surface is 5.800 mm;

the effective diameter of the clear aperture of the third surface is 1.570 mm;

the effective diameter of the clear aperture of the fifth surface is 1.950 mm.

TABLE 2

Coefficients of the aspheric surfaces							
	Surface						
	1	2	3	4	5	6	8
k	4.310876E+01	-4.707622E+00	2.616025E+00	2.445397E+00	5.645686E+00	-2.117147E+01	-5.287220E+00
A4	7.054243E-03	1.714312E-02	-8.377541E-03	-1.789549E-02	-3.379055E-03	-1.370959E-02	-2.937377E-02
A6	-5.233264E-04	-1.502232E-04	-1.838068E-03	-3.657520E-03	-1.225453E-03	6.250200E-03	2.743532E-03
A8	3.077890E-05	-1.359611E-04	1.233332E-03	-1.131622E-03	-5.979572E-03	-5.854426E-03	-2.457574E-03
A10	-1.260650E-06	2.680747E-05	-2.390895E-03	1.390351E-03	4.556449E-03	4.049451E-03	1.874319E-03
A12	3.319093E-08	-2.017491E-06	1.998555E-03	-4.152857E-04	-1.177175E-03	-1.314592E-03	-6.013661E-04
A14	-5.051600E-10	6.604615E-08	-9.734019E-04	5.487286E-05	1.370522E-04	2.143097E-04	8.792480E-05
A16	3.380000E-12	-1.301630E-09	2.478373E-04	-2.919339E-06	-5.974015E-06	-1.399894E-05	-4.770527E-06

	Surface				
	9	10	11	12	13
k	6.200000E+01	-2.114008E+01	-7.699904E+00	-6.155476E+01	-3.120467E-01
A4	-1.359965E-01	-1.263831E-01	-1.927804E-02	-2.492467E-02	-3.521844E-02
A6	6.628518E-02	6.965399E-02	2.478376E-03	-1.835360E-03	5.629654E-03
A8	-2.129167E-02	-2.116027E-02	1.438785E-03	3.201343E-03	-5.466925E-04
A10	4.396344E-03	3.819371E-03	-7.013749E-04	-8.990757E-04	2.231154E-05
A12	-5.542899E-04	-4.040283E-04	1.253214E-04	1.245343E-04	5.548990E-07
A14	3.768879E-05	2.280473E-05	-9.943196E-06	-8.788363E-06	-9.396920E-08
A16	-1.052467E-06	-5.165452E-07	2.898397E-07	2.494302E-07	2.728360E-09

[0181] The figures related to the profile curve lengths obtained based on Table 1 and Table 2 are listed in the following table:

First optical embodiment (Reference wavelength (d-line): 555 nm)						
ARE	1/2(HEP)	ARE value	ARE - 1/2(HEP)	2(ARE/HEP) %	TP	ARE/TP (%)
11	1.455	1.455	-0.00033	99.98%	1.934	75.23%
12	1.455	1.495	0.03957	102.72%	1.934	77.29%
21	1.455	1.465	0.00940	100.65%	2.486	58.93%
22	1.455	1.495	0.03950	102.71%	2.486	60.14%
31	1.455	1.486	0.03045	102.09%	0.380	391.02%
32	1.455	1.464	0.00830	100.57%	0.380	385.19%
41	1.455	1.458	0.00237	100.16%	1.236	117.95%
42	1.455	1.484	0.02825	101.94%	1.236	120.04%
51	1.455	1.462	0.00672	100.46%	1.072	136.42%
52	1.455	1.499	0.04335	102.98%	1.072	139.83%
61	1.455	1.465	0.00964	100.66%	1.031	142.06%
62	1.455	1.469	0.01374	100.94%	1.031	142.45%

ARS						
ARS	EHD	ARS value	ARS - EHD	(ARS/EHD) %	TP	ARS/TP (%)
11	5.800	6.141	0.341	105.88%	1.934	317.51%
12	3.299	4.423	1.125	134.10%	1.934	228.70%
21	1.664	1.674	0.010	100.61%	2.486	67.35%
22	1.950	2.119	0.169	108.65%	2.486	85.23%
31	1.980	2.048	0.069	103.47%	0.380	539.05%
32	2.084	2.101	0.017	100.83%	0.380	552.87%
41	2.247	2.287	0.040	101.80%	1.236	185.05%
42	2.530	2.813	0.284	111.22%	1.236	227.63%
51	2.655	2.690	0.035	101.32%	1.072	250.99%
52	2.764	2.930	0.166	106.00%	1.072	273.40%
61	2.816	2.905	0.089	103.16%	1.031	281.64%
62	3.363	3.391	0.029	100.86%	1.031	328.83%

[0182] The detail parameters of the first optical embodiment are listed in Table 1, in which the unit of the radius of curvature, thickness, and focal length are millimeter, and surface 0-16 indicates the surfaces of all elements in the system in sequence from the object side to the image side. Table 2 is the list of coefficients of the aspheric surfaces, in

which k indicates the taper coefficient in the aspheric curve equation, and A1-A20 indicate the coefficients of aspheric surfaces from the first order to the twentieth order of each aspheric surface. The following optical embodiments have the similar diagrams and tables, which are the same as those of the first optical embodiment, so we do not describe it again. The definitions of the mechanism component parameters of the following optical embodiments are the same as those of the first optical embodiment.

Second Optical Embodiment

[0183] As shown in FIG. 3A and FIG. 3B, an optical image capturing module 20 of the second optical embodiment of the present invention includes, along an optical axis from an object side to an image side, a first lens 210, a second lens 220, a third lens 230, an aperture 200, a fourth lens 240, a fifth lens 250, a sixth lens 260, a seventh lens 270, an IR-cut filter 280, an image plane 290, and an image sensor 292.

[0184] The first lens 210 has negative refractive power and is made of glass. An object-side surface 212 thereof, which faces the object side, is a convex spherical surface, and an image-side surface 214 thereof, which faces the image side, is a concave spherical surface.

[0185] The second lens 220 has negative refractive power and is made of glass. An object-side surface 222 thereof, which faces the object side, is a concave spherical surface, and an image-side surface 224 thereof, which faces the image side, is a convex spherical surface.

[0186] The third lens 230 has positive refractive power and is made of glass. An object-side surface 232, which faces the object side, is a convex spherical surface, and an image-side surface 234, which faces the image side, is a convex spherical surface.

[0187] The fourth lens 240 has positive refractive power and is made of glass. An object-side surface 242, which

[0193] An equation of the aspheric surfaces of the second optical embodiment is the same as that of the first optical embodiment, and the definitions are the same as well.

[0194] The exact parameters of the second optical embodiment based on Table 3 and Table 4 are listed in the following table:

Second optical embodiment (Reference wavelength: 555 nm)					
f/f1	f/f2	f/f3	f/f4	f/f5	f/f6
0.3764	0.0478	0.1081	0.2458	0.2354	0.6208
f/f7	Σ PPR	Σ NPR	Σ PPR/Σ NPR	IN12/f	IN67/f
0.3495	1.3510	0.6327	2.1352	2.8858	0.0451
f1/f2	f2/f3	(TP1 + IN12)/TP2		(TP7 + IN67)/TP6	
0.1271	2.2599	3.7428		1.0296	
HOS	InTL	HOS/HOI	InS/HOS	ODT %	TDT %
81.6178	70.9539	13.6030	0.3451	-113.2790	84.4806
HVT11	HVT12	HVT21	HVT22	HVT31	HVT32
0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
HVT61	HVT62	HVT71	HVT72	HVT72/HOI	HVT72/HOS
0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
PhiA	PhiC	PhiD	TH1	TH2	HOI
11.962 mm	12.362 mm	12.862 mm	0.25 mm	0.2 mm	6 mm
		(TH1 + TH2)/	(TH1 + TH2)/	2(TH1 + TH2)/	
PhiA/PhiD	TH1 + TH2	HOI	HOS	PhiA	InTL/HOS
0.9676	0.45 mm	0.075	0.0055	0.0752	0.8693
PSTA	PLTA	NSTA	NLTA	SSTA	SLTA
0.060 mm	-0.005 mm	0.016 mm	0.006 mm	0.020 mm	-0.008 mm

[0195] The figures related to the profile curve lengths obtained based on Table 3 and Table 4 are listed in the following table:

Second optical embodiment (Reference wavelength: 555 nm)						
ARE	1/2(HEP)	ARE value	ARE - 1/2(HEP)	2(ARE/HEP) %	TP	ARE/TP (%)
11	1.082	1.081	-0.00075	99.93%	4.977	21.72%
12	1.082	1.083	0.00149	100.14%	4.977	21.77%
21	1.082	1.082	0.00011	100.01%	5.000	21.64%
22	1.082	1.082	-0.00034	99.97%	5.000	21.63%
31	1.082	1.081	-0.00084	99.92%	5.000	21.62%
32	1.082	1.081	-0.00075	99.93%	5.000	21.62%
41	1.082	1.081	-0.00059	99.95%	4.095	26.41%
42	1.082	1.081	-0.00067	99.94%	4.095	26.40%
51	1.082	1.082	-0.00021	99.98%	1.539	70.28%
52	1.082	1.081	-0.00069	99.94%	1.539	70.25%
61	1.082	1.082	-0.00021	99.98%	5.000	21.63%
62	1.082	1.082	0.00005	100.00%	5.000	21.64%
71	1.082	1.082	-0.00003	100.00%	4.933	21.93%
72	1.082	1.083	0.00083	100.08%	4.933	21.95%

ARS	EHD	ARS value	ARS - EHD	(ARS/EHD) %	TP	ARS/TP (%)
11	20.767	21.486	0.719	103.46%	4.977	431.68%
12	9.412	13.474	4.062	143.16%	4.977	270.71%
21	8.636	9.212	0.577	106.68%	5.000	184.25%
22	9.838	10.264	0.426	104.33%	5.000	205.27%
31	8.770	8.772	0.003	100.03%	5.000	175.45%
32	8.511	8.558	0.047	100.55%	5.000	171.16%
41	4.600	4.619	0.019	100.42%	4.095	112.80%
42	4.965	4.981	0.016	100.32%	4.095	121.64%
51	5.075	5.143	0.067	101.33%	1.539	334.15%
52	5.047	5.062	0.015	100.30%	1.539	328.89%
61	5.011	5.075	0.064	101.28%	5.000	101.50%
62	5.373	5.489	0.116	102.16%	5.000	109.79%
71	5.513	5.625	0.112	102.04%	4.933	114.03%
72	5.981	6.307	0.326	105.44%	4.933	127.84%

[0196] The results of the equations of the second optical embodiment based on Table 3 and Table 4 are listed in the following table:

Values related to the inflection points of the second optical embodiment (Reference wavelength: 555 nm)							
HIF111	0	HIF111/HOI	0	SGI111	0	SGI111 /(SGI111 + TP1)	0

Third Optical Embodiment

[0197] As shown in FIG. 4A and FIG. 4B, an optical image capturing module of the third optical embodiment of the present invention includes, along an optical axis from an object side to an image side, a first lens 310, a second lens 320, a third lens 330, an aperture 300, a fourth lens 340, a fifth lens 350, a sixth lens 360, a seventh lens 370, an IR-cut filter 380, an image plane 390, and an image sensor 392.

[0198] The first lens 310 has negative refractive power and is made of glass. An object-side surface 312 thereof, which faces the object side, is a convex spherical surface, and an image-side surface 314 thereof, which faces the image side, is a concave spherical surface.

[0199] The second lens 320 has negative refractive power and is made of glass. An object-side surface 322 thereof, which faces the object side, is a concave spherical surface, and an image-side surface 324 thereof, which faces the image side, is a convex spherical surface.

[0200] The third lens 330 has positive refractive power and is made of plastic. An object-side surface 332 thereof, which faces the object side, is a convex aspheric surface, and an image-side surface 334 thereof, which faces the image side, is a convex aspheric surface. The image-side surface 334 has an inflection point.

[0201] The fourth lens 340 has negative refractive power and is made of plastic. An object-side surface 342, which faces the object side, is a concave aspheric surface, and an image-side surface 344, which faces the image side, is a concave aspheric surface. The image-side surface 344 has an inflection point.

[0202] The fifth lens 350 has positive refractive power and is made of plastic. An object-side surface 352, which faces the object side, is a convex aspheric surface, and an image-side surface 354, which faces the image side, is a convex aspheric surface.

[0203] The sixth lens 360 has negative refractive power and is made of plastic. An object-side surface 362, which faces the object side, is a convex aspheric surface, and an image-side surface 364, which faces the image side, is a concave aspheric surface. The object-side surface 362 has an inflection point, and the image-side surface 364 has an inflection point. It may help to shorten the back focal length to keep small in size. Whereby, the incident angle of each

view field entering the sixth lens 360 could be effectively adjusted to improve aberration.

[0204] The IR-cut filter 380 is made of glass and is disposed between the sixth lens 360 and the image plane 390. The IR-cut filter 390 gives no contribution to the focal length of the optical image capturing module.

[0205] The parameters of the lenses of the third optical embodiment are listed in Table 5 and Table 6.

TABLE 5

f = 2.808 mm; f/HEP = 1.6; HAF = 100 deg							
Surface		Radius of curvature (mm)	Thickness (mm)	Material	Refractive index	Abbe number	Focal length (mm)
0	Object	1E+18	1E+18				
1	1 st lens	71.398124	7.214	glass	1.702	41.15	-11.765
2		7.117272355	5.788				
3	2 nd lens	-13.29213699	10.000	glass	2.003	19.32	-4537.460
4		-18.37509887	7.005				
5	3 rd lens	5.039114804	1.398	plastic	1.514	56.80	7.553
6		-15.53136631	-0.140				
7	Aperture	1E+18	2.378				
8	4 th lens	-18.68613609	0.577	plastic	1.661	20.40	-4.978
9		4.086545927	0.141				
10	5 th lens	4.927609282	2.974	plastic	1.565	58.00	4.709
11		-4.551946605	1.389				
12	6 th lens	9.184876531	1.916	plastic	1.514	56.80	-23.405
13		4.845500046	0.800				
14	Infrared rays filter	1E+18	0.500	BK_7	1.517	64.13	
15		1E+18	0.371				
16	Image plane	1E+18	0.005				

Reference wavelength (d-line): 555 nm; the position of blocking light: none.

TABLE 6

Coefficients of the aspheric surfaces							
	Surface						
	1	2	3	4	5	6	8
k	0.000000E+00	0.000000E+00	0.000000E+00	0.000000E+00	1.318519E-01	3.120384E+00	-1.494442E+01
A4	0.000000E+00	0.000000E+00	0.000000E+00	0.000000E+00	6.405246E-05	2.103942E-03	-1.598286E-03
A6	0.000000E+00	0.000000E+00	0.000000E+00	0.000000E+00	2.278341E-05	-1.050629E-04	-9.177115E-04
A8	0.000000E+00	0.000000E+00	0.000000E+00	0.000000E+00	-3.672908E-06	6.168906E-06	1.011405E-04
A10	0.000000E+00	0.000000E+00	0.000000E+00	0.000000E+00	3.748457E-07	-1.224682E-07	-4.919835E-06
	Surface						
	9	10	11	12	13		
k	2.744228E-02	-7.864013E+00	-2.263702E+00	-4.206923E+01	-7.030803E+00		
A4	-7.291825E-03	1.405243E-04	-3.919567E-03	-1.679499E-03	-2.640099E-03		
A6	9.730714E-05	1.837602E-04	2.683449E-04	-3.518520E-04	-4.507651E-05		
A8	1.101816E-06	-2.173368E-05	-1.229452E-05	5.047353E-05	-2.600391E-05		
A10	-6.849076E-07	7.328496E-07	4.222621E-07	-3.851055E-06	1.161811E-06		

[0206] An equation of the aspheric surfaces of the third optical embodiment is the same as that of the first optical embodiment, and the definitions are the same as well.

[0207] The exact parameters of the third optical embodiment based on Table 5 and Table 6 are listed in the following table:

Third optical embodiment (Reference wavelength: 555 nm)					
f/f1	f/f2	f/f3	f/f4	f/f5	f/f6
0.23865	0.00062	0.37172	0.56396	0.59621	0.11996
		Σ PPR/Σ			TP4/
Σ PPR	Σ NPR	NPR	IN12/f	IN56/f	(IN34 + TP4 + IN45)
1.77054	0.12058	14.68400	2.06169	0.49464	0.19512
f1/f2	f2/f3	(TP1 + IN12)/TP2		(TP6 + IN56)/TP5	
0.00259	600.74778	1.30023		1.11131	
HOS	InTL	HOS/HOI	InS/HOS	ODT %	TDT %
42.31580	40.63970	10.57895	0.26115	-122.32700	93.33510
HVT51	HVT52	HVT61	HVT62	HVT62/HOI	HVT62/HOS
0	0	2.22299	2.60561	0.65140	0.06158
TP2/TP3	TP3/TP4	InRS61	InRS62	InRS61 /TP6	InRS62 /TP6
7.15374	2.42321	-0.20807	-0.24978	0.10861	0.13038
PhiA	PhiC	PhiD	TH1	TH2	HOI
6.150 mm	6.41 mm	6.71 mm	0.15 mm	0.13 mm	4 mm
PhiA/		(TH1 + TH2)/	(TH1 + TH2)/	2(TH1 + TH2)/	
PhiD	TH1 + TH2	HOI	HOS	PhiA	InTL/HOS
0.9165	0.28 mm	0.07	0.0066	0.0911	0.9604
PSTA	PLTA	NSTA	NLTA	SSTA	SLTA
0.014 mm	0.002 mm	-0.003 mm	-0.002 mm	0.011 mm	-0.001 mm

[0208] The figures related to the profile curve lengths obtained based on Table 5 and Table 6 are listed in the following table:

Third optical embodiment (Reference wavelength: 555 nm)						
ARE	1/2(HEP)	ARE value	ARE - 1/2(HEP)	2(ARE/HEP) %	TP	ARE/TP (%)
11	0.877	0.877	-0.00036	99.96%	7.214	12.16%
12	0.877	0.879	0.00186	100.21%	7.214	12.19%
21	0.877	0.878	0.00026	100.03%	10.000	8.78%
22	0.877	0.877	-0.00004	100.00%	10.000	8.77%
31	0.877	0.882	0.00413	100.47%	1.398	63.06%
32	0.877	0.877	0.00004	100.00%	1.398	62.77%
41	0.877	0.877	-0.00001	100.00%	0.577	152.09%
42	0.877	0.883	0.00579	100.66%	0.577	153.10%
51	0.877	0.881	0.00373	100.43%	2.974	29.63%
52	0.877	0.883	0.00521	100.59%	2.974	29.68%
61	0.877	0.878	0.00064	100.07%	1.916	45.83%
62	0.877	0.881	0.00368	100.42%	1.916	45.99%

-continued

Third optical embodiment (Reference wavelength: 555 nm)						
ARS	EHD	ARS value	ARS - EHD	(ARS/EHD) %	TP	ARS/TP (%)
11	17.443	17.620	0.178	101.02%	7.214	244.25%
12	6.428	8.019	1.592	124.76%	7.214	111.16%
21	6.318	6.584	0.266	104.20%	10.000	65.84%
22	6.340	6.472	0.132	102.08%	10.000	64.72%
31	2.699	2.857	0.158	105.84%	1.398	204.38%
32	2.476	2.481	0.005	100.18%	1.398	177.46%
41	2.601	2.652	0.051	101.96%	0.577	459.78%
42	3.006	3.119	0.113	103.75%	0.577	540.61%
51	3.075	3.171	0.096	103.13%	2.974	106.65%
52	3.317	3.624	0.307	109.24%	2.974	121.88%
61	3.331	3.427	0.095	102.86%	1.916	178.88%
62	3.944	4.160	0.215	105.46%	1.916	217.14%

[0209] The results of the equations of the third optical embodiment based on Table 5 and Table 6 are listed in the following table:

Values related to the inflection points of the third optical embodiment (Reference wavelength: 555 nm)							
HIF321	2.0367	HIF321/HOI	0.5092	SGI321	-0.1056	SGI321 /(SGI321 + TP3)	0.0702
HIF421	2.4635	HIF421/HOI	0.6159	SGI421	0.5780	SGI421 /(SGI421 + TP4)	0.5005
HIF611	1.2364	HIF611/HOI	0.3091	SGI611	0.0668	SGI611 /(SGI611 + TP6)	0.0337
HIF621	1.5488	HIF621/HOI	0.3872	SGI621	0.2014	SGI621 /(SGI621 + TP6)	0.0951

TABLE 8-continued

Coefficients of the aspheric surfaces			
	Surface		
	9	10	11
k	-0.18604	-6.17195	27.541383
A4	4.33629E-03	1.58379E-03	7.56932E-03
A6	-2.91588E-04	-1.81549E-04	-7.83858E-04
A8	9.11419E-06	-1.18213E-05	4.79120E-05
A10	1.28365E-07	1.92716E-06	-1.73591E-06
A12	0.000000E+00	0.000000E+00	0.000000E+00

[0218] An equation of the aspheric surfaces of the fourth optical embodiment is the same as that of the first optical embodiment, and the definitions are the same as well.

[0219] The exact parameters of the fourth optical embodiment based on Table 7 and Table 8 are listed in the following table:

Fourth optical embodiment (Reference wavelength: 555 nm)					
f/f1	f/f2	f/f3	f/f4	f/f5	f1/f2
0.08902	0.32019	0.28029	0.53121	0.56045	3.59674
Σ PPR	Σ NPR	Σ PPR/Σ NPR	IN12/f	IN45/f	f2/f3
1.4118	0.3693	3.8229	2.1247	0.0181	0.8754
TP3/(IN23 + TP3 + IN34)	(TP1 + IN12)/TP2		(TP5 + IN45)/TP4		
0.73422	3.51091		0.53309		
HOS	InTL	HOS/HOI	InS/HOS	ODT %	TDT %
46.12590	41.77110	11.53148	0.23936	-125.266	99.1671
HVT41	HVT42	HVT51	HVT52	HVT52/HOI	HVT52/HOS
0.00000	0.00000	0.00000	0.00000	0.00000	0.00000
TP2/TP3	TP3/TP4	InRS51	InRS52	InRS51 /TP5	InRS52 /TP5
0.23184	3.68765	-0.679265	0.5369	0.32528	0.25710
PhiA	PhiC	PhiD	TH1	TH2	HOI
5.598 mm	5.858 mm	6.118 mm	0.13 mm	0.13 mm	4 mm
PhiA/PhiD	TH1 + TH2	HOI	(TH1 + TH2)/HOS	PhiA	InTL/HOS
0.9150	0.26 mm	0.065	0.0056	0.0929	0.9056
PSTA	PLTA	NSTA	NLTA	SSTA	SLTA
-0.011 mm	0.005 mm	-0.010 mm	-0.003 mm	0.005 mm	-0.00026 mm

[0220] The figures related to the profile curve lengths obtained based on Table 7 and Table 8 are listed in the following table:

Fourth optical embodiment (Reference wavelength: 555 nm)						
ARE	1/2 (HEP)	ARE value	ARE - 1/2(HEP)	2(ARE/HEP) %	TP	ARE/TP (%)
11	0.775	0.774	-0.00052	99.93%	6.117	12.65%
12	0.775	0.774	-0.00005	99.99%	6.117	12.66%
21	0.775	0.774	-0.00048	99.94%	3.430	22.57%
22	0.775	0.776	0.00168	100.22%	3.430	22.63%
31	0.775	0.774	-0.00031	99.96%	14.794	5.23%
32	0.775	0.776	0.00177	100.23%	14.794	5.25%
41	0.775	0.775	0.00059	100.08%	4.012	19.32%
42	0.775	0.779	0.00453	100.59%	4.012	19.42%
51	0.775	0.778	0.00311	100.40%	2.088	37.24%
52	0.775	0.774	-0.00014	99.98%	2.088	37.08%

-continued

Fourth optical embodiment (Reference wavelength: 555 nm)						
ARS	EHD	ARS value	ARS - EHD	(ARS/EHD)%	TP	ARS/TP (%)
11	23.038	23.397	0.359	101.56%	6.117	382.46%
12	10.140	11.772	1.632	116.10%	6.117	192.44%
21	10.138	10.178	0.039	100.39%	3.430	296.74%
22	5.537	6.337	0.800	114.44%	3.430	184.76%
31	4.490	4.502	0.012	100.27%	14.794	30.43%
32	2.544	2.620	0.076	102.97%	14.794	17.71%
41	2.735	2.759	0.024	100.89%	4.012	68.77%
42	3.123	3.449	0.326	110.43%	4.012	85.97%
51	2.934	3.023	0.089	103.04%	2.088	144.74%
52	2.799	2.883	0.084	103.00%	2.088	138.08%

[0221] The results of the equations of the fourth optical embodiment based on Table 7 and Table 8 are listed in the following table:

Values related to the inflection points of the fourth optical embodiment (Reference wavelength: 555 nm)

HIF211	6.3902	HIF211/HOI	1.5976	SGI211	-0.4793	SGI211 /(SGI211 + TP2)	0.1226
HIF311	2.1324	HIF311/HOI	0.5331	SGI311	0.1069	SGI311 /(SGI311 + TP3)	0.0072
HIF411	2.0278	HIF411/HOI	0.5070	SGI411	0.2287	SGI411 /(SGI411 + TP4)	0.0539
HIF511	2.6253	HIF511/HOI	0.6563	SGI511	-0.5681	SGI511 /(SGI511 + TP5)	0.2139
HIF512	2.1521	HIF512/HOI	0.5380	SGI512	-0.8314	SGI512 /(SGI512 + TP5)	0.2848

Fifth Optical Embodiment

[0222] As shown in FIG. 6A and FIG. 6B, an optical image capturing module of the fifth optical embodiment of the present invention includes, along an optical axis from an object side to an image side, an aperture 500, a first lens 510, a second lens 520, a third lens 530, a fourth lens 540, an IR-cut filter 570, an image plane 580, and an image sensor 590.

[0223] The first lens 510 has positive refractive power and is made of plastic. An object-side surface 512, which faces the object side, is a convex aspheric surface, and an image-side surface 514, which faces the image side, is a convex aspheric surface. The object-side surface 512 has an inflection point.

[0224] The second lens 520 has negative refractive power and is made of plastic. An object-side surface 522 thereof, which faces the object side, is a convex aspheric surface, and an image-side surface 524 thereof, which faces the image side, is a concave aspheric surface. The object-side surface 522 has two inflection points, and the image-side surface 524 has an inflection point.

[0225] The third lens 530 has positive refractive power and is made of plastic. An object-side surface 532, which faces the object side, is a concave aspheric surface, and an image-side surface 534, which faces the image side, is a convex aspheric surface. The object-side surface 532 has three inflection points, and the image-side surface 534 has an inflection point.

[0226] The fourth lens 540 has negative refractive power and is made of plastic. An object-side surface 542, which faces the object side, is a concave aspheric surface, and an image-side surface 544, which faces the image side, is a concave aspheric surface. The object-side surface 542 has two inflection points, and the image-side surface 544 has an inflection point.

[0227] The IR-cut filter 570 is made of glass and is disposed between the fourth lens 540 and the image plane 580. The IR-cut filter 570 gives no contribution to the focal length of the optical image capturing module.

[0228] The parameters of the lenses of the fifth optical embodiment are listed in Table 9 and Table 10.

TABLE 9

f = 1.04102 mm; f/HEP = 1.4; HAF = 44.0346 deg

Surface		Radius of curvature (mm)	Thickness (mm)	Material	Refractive index	Abbe number	Focal length (mm)
0	Object	1E+18	600				
1	Aperture	1E+18	-0.020				
2	1 st lens	0.890166851	0.210	plastic	1.545	55.96	1.587
3		-29.11040115	-0.010				
4		1E+18	0.116				
5	2 nd lens	10.67765398	0.170	plastic	1.642	22.46	-14.569
6		4.977771922	0.049				
7	3 rd lens	-1.191436932	0.349	plastic	1.545	55.96	0.510
8		-0.248990674	0.030				
9	4 th lens	-38.08537212	0.176	plastic	1.642	22.46	-0.569
10		0.372574476	0.152				
11	1E+18	0.210	BK_7	1.517	64.13		1E+18
12	1E+18	0.185					1E+18
13	1E+18	0.005					1E+18

Reference wavelength (d-line): 555 nm; the position of blocking light: the effective half diameter of the clear aperture of the fourth surface is 0.360 mm.

TABLE 10

Coefficients of the aspheric surfaces

	Surface					
	2	3	5	6	7	8
k	-1.106629E+00	2.994179E-07	-7.788754E+01	-3.440335E+01	-8.522097E-01	-4.735945E+00
A4	8.291155E-01	-6.401113E-01	-4.958114E+00	-1.875957E+00	-4.878227E-01	-2.490377E+00
A6	-2.398799E+01	-1.265726E+01	1.299769E+02	8.568480E+01	1.291242E+02	1.524149E+02
A8	1.825378E+02	8.457286E+01	-2.736977E+03	-1.279044E+03	-1.979689E+03	-4.841033E+03
A10	-6.211133E+02	-2.157875E+02	2.908537E+04	8.661312E+03	1.456076E+04	8.053747E+04

TABLE 10-continued

Coefficients of the aspheric surfaces						
A12	-4.719066E+02	-6.203600E+02	-1.499597E+05	-2.875274E+04	-5.975920E+04	-7.936887E+05
A14	0.000000E+00	0.000000E+00	2.992026E+05	3.764871E+04	1.351676E+05	4.811528E+06
A16	0.000000E+00	0.000000E+00	0.000000E+00	0.000000E+00	-1.329001E+05	-1.762293E+07
A18	0.000000E+00	0.000000E+00	0.000000E+00	0.000000E+00	0.000000E+00	3.579891E+07
A20	0.000000E+00	0.000000E+00	0.000000E+00	0.000000E+00	0.000000E+00	-3.094006E+07

	Surface	
	9	10
k	-2.277155E+01	-8.039778E-01
A4	1.672704E+01	-7.613206E+00
A6	-3.260722E+02	3.374046E+01
A8	3.373231E+03	-1.368453E+02
A10	-2.177676E+04	4.049486E+02
A12	8.951687E+04	-9.711797E+02
A14	-2.363737E+05	1.942574E+03
A16	3.983151E+05	-2.876356E+03
A18	-4.090689E+05	2.562386E+03
A20	2.056724E+05	-9.943657E+02

[0229] An equation of the aspheric surfaces of the fifth optical embodiment is the same as that of the first optical embodiment, and the definitions are the same as well.

[0230] The exact parameters of the fifth optical embodiment based on Table 9 and Table 10 are listed in the following table:

Fifth optical embodiment (Reference wavelength: 555 nm)						
InRS41	InRS42	HVT41	HVT42	ODT %	TDT %	
-0.07431	0.00475	0.00000	0.53450	2.09403	0.84704	
f/f1	f/f2	f/f3	f/f4	f1/f2	f2/f3	
0.65616	0.07145	2.04129	1.83056	0.10890	28.56826	
Σ PPR	Σ NPR	Σ PPR/Σ NPR	Σ PP	Σ NP	f1/Σ PP	
2.11274	2.48672	0.84961	-14.05932	1.01785	1.03627	
f4/Σ NP	IN12/f	IN23/f	IN34/f	TP3/f	TP4/f	
1.55872	0.10215	0.04697	0.02882	0.33567	0.16952	
InTL	HOS	HOS/HOI	InS/HOS	InTL/HOS	Σ TP/InTL	
1.09131	1.64329	1.59853	0.98783	0.66410	0.83025	
(TP1 + IN12)/TP2	(TP4 + IN34)/TP3	TP1/TP2	TP3/TP4	IN23/(TP2 + IN23 + TP3)		
1.86168	0.59088	1.23615	1.98009	0.08604		
InRS41 /TP4	InRS42 /TP4	HVT42/HOI	HVT42/HOS	InTL/HOS		
0.4211	0.0269	0.5199	0.3253	0.6641		
PhiA	PhiC	PhiD	TH1	TH2	HOI	
1.596 mm	1.996 mm	2.396 mm	0.2 mm	0.2 mm	1.028 mm	
PhiA/PhiD	TH1 + TH2	HOI	HOS	PhiA		
0.7996	0.4 mm	0.3891	0.2434	0.5013		
PSTA	PLTA	NSTA	NLTA	SSTA	SLTA	
-0.029 mm	-0.023 mm	-0.011 mm	-0.024 mm	0.010 mm	0.011 mm	

[0231] The results of the equations of the fifth optical embodiment based on Table 9 and Table 10 are listed in the following table:

Values related to the inflection points of the fifth optical embodiment (Reference wavelength: 555 nm)							
HIF111	0.28454	HIF111/HOI	0.27679	SGI111	0.04361	SGI111 /(SGI111 + TP1)	0.17184
HIF211	0.04198	HIF211/HOI	0.04083	SGI211	0.00007	SGI211 /(SGI211 + TP2)	0.00040
HIF212	0.37903	HIF212/HOI	0.36871	SGI212	-0.03682	SGI212 /(SGI212 + TP2)	0.17801
HIF221	0.25058	HIF221/HOI	0.24376	SGI221	0.00695	SGI221 /(SGI221 + TP2)	0.03927
HIF311	0.14881	HIF311/HOI	0.14476	SGI311	-0.00854	SGI311 /(SGI311 + TP3)	0.02386
HIF312	0.31992	HIF312/HOI	0.31120	SGI312	-0.01783	SGI312 /(SGI312 + TP3)	0.04855
HIF313	0.32956	HIF313/HOI	0.32058	SGI313	-0.01801	SGI313 /(SGI313 + TP3)	0.04902
HIF321	0.36943	HIF321/HOI	0.35937	SGI321	-0.14878	SGI321 /(SGI321 + TP3)	0.29862
HIF411	0.01147	HIF411/HOI	0.01116	SGI411	-0.00000	SGI411 /(SGI411 + TP4)	0.00001
HIF412	0.22405	HIF412/HOI	0.21795	SGI412	0.01598	SGI412 /(SGI412 + TP4)	0.08304
HIF421	0.24105	HIF421/HOI	0.23448	SGI421	0.05924	SGI421 /(SGI421 + TP4)	0.25131

[0232] The figures related to the profile curve lengths obtained based on Table 9 and Table 10 are listed in the following table:

Fifth optical embodiment (Reference wavelength: 555 nm)						
ARE	1/2(HEP)	ARE value	ARE - 1/2(HEP)	2(ARE/HEP) %	TP	ARE/TP (%)
11	0.368	0.374	0.00578	101.57%	0.210	178.10%
12	0.366	0.368	0.00240	100.66%	0.210	175.11%
21	0.372	0.375	0.00267	100.72%	0.170	220.31%
22	0.372	0.371	-0.00060	99.84%	0.170	218.39%
31	0.372	0.372	-0.00023	99.94%	0.349	106.35%
32	0.372	0.404	0.03219	108.66%	0.349	115.63%
41	0.372	0.373	0.00112	100.30%	0.176	211.35%
42	0.372	0.387	0.01533	104.12%	0.176	219.40%

ARS	EHD	ARS value	ARS - EHD	(ARS/EHD) %	TP	ARS/TP (%)
11	0.368	0.374	0.00578	101.57%	0.210	178.10%
12	0.366	0.368	0.00240	100.66%	0.210	175.11%
21	0.387	0.391	0.00383	100.99%	0.170	229.73%
22	0.458	0.460	0.00202	100.44%	0.170	270.73%
31	0.476	0.478	0.00161	100.34%	0.349	136.76%
32	0.494	0.538	0.04435	108.98%	0.349	154.02%
41	0.585	0.624	0.03890	106.65%	0.176	353.34%
42	0.798	0.866	0.06775	108.49%	0.176	490.68%

Sixth Optical Embodiment

[0233] As shown in FIG. 7A and FIG. 7B, an optical image capturing module of the sixth optical embodiment of

the present invention includes, along an optical axis from an object side to an image side, a first lens 610, an aperture 600, a second lens 620, a third lens 630, an IR-cut filter 670, an image plane 680, and an image sensor 690.

[0234] The first lens 610 has positive refractive power and is made of plastic. An object-side surface 612, which faces the object side, is a convex aspheric surface, and an image-side surface 614, which faces the image side, is a concave aspheric surface.

[0235] The second lens 620 has negative refractive power and is made of plastic. An object-side surface 622 thereof, which faces the object side, is a concave aspheric surface, and an image-side surface 624 thereof, which faces the image side, is a convex aspheric surface. The image-side surface 624 has an inflection point.

[0236] The third lens 630 has positive refractive power and is made of plastic. An object-side surface 632, which faces the object side, is a convex aspheric surface, and an image-side surface 634, which faces the image side, is a concave aspheric surface. The object-side surface 632 has two inflection points, and the image-side surface 634 has an inflection point.

[0237] The IR-cut filter 670 is made of glass and is disposed between the third lens 630 and the image plane 680. The IR-cut filter 670 gives no contribution to the focal length of the optical image capturing module.

[0238] The parameters of the lenses of the sixth optical embodiment are listed in Table 11 and Table 12.

TABLE 11

f = 2.41135 mm; f/HEP = 2.22; HAF = 36 deg						
Surface	Radius of curvature (mm)	Thickness (mm)	Material	Refractive index	Abbe number	Focal length (mm)
0	Object	1E+18	600			
1	1 st lens	0.840352226	0.468	plastic	1.535	56.27
2		2.271975602	0.148			
3	Aperture	1E+18	0.277			
4	2 nd lens	-1.157324239	0.349	plastic	1.642	22.46
5		-1.968404008	0.221			
6	3 rd lens	1.151874235	0.559	plastic	1.544	56.09
7		1.338105159	0.123			
8	Infrared rays filter	1E+18	0.210	BK7	1.517	64.13
9		1E+18	0.547			
10	Image plane	1E+18	0.000			

Reference wavelength (d-line): 555 nm; the position of blocking light: the effective half diameter of the clear aperture of the first surface is 0.640 mm.

TABLE 12

Coefficients of the aspheric surfaces						
	Surface					
	1	2	4	5	6	7
k	-2.019203E-01	1.528275E+01	3.743939E+00	-1.207814E+01	-1.276860E+01	-3.034004E+00
A4	3.944883E-02	-1.670490E-01	-4.266331E-01	-1.696843E+00	-7.396546E-01	-5.308488E-01
A6	4.774062E-01	3.857435E+00	-1.423859E+00	5.164775E+00	4.449101E-01	4.374142E-01
A8	-1.528780E+00	-7.091408E+01	4.119587E+01	-1.445541E+01	2.622372E-01	-3.111192E-01
A10	5.133947E+00	6.365801E+02	-3.456462E+02	2.876958E+01	-2.510946E-01	1.354257E-01

TABLE 12-continued

Coefficients of the aspheric surfaces						
Surface						
	1	2	4	5	6	7
A12	-6.250496E+00	-3.141002E+03	1.495452E+03	-2.662400E+01	-1.048030E-01	-2.652902E-02
A14	1.068803E+00	7.962834E+03	-2.747802E+03	1.661634E+01	1.462137E-01	-1.203306E-03
A16	7.995491E+00	-8.268637E+03	1.443133E+03	-1.327827E+01	-3.676651E-02	7.805611E-04

[0239] An equation of the aspheric surfaces of the sixth optical embodiment is the same as that of the first optical embodiment, and the definitions are the same as well.

[0240] The exact parameters of the sixth optical embodiment based on Table 11 and Table 12 are listed in the following table:

Sixth optical embodiment (Reference wavelength: 555 nm)					
f1/f1	f2/f2	f3/f3	f1/f2	f2/f3	TP1/TP2
1.08042	0.46186	0.32763	2.33928	1.40968	1.33921
Σ PPR	Σ NPR	Σ PPR/Σ NPR	IN12/f	IN23/f	TP2/TP3
1.40805	0.46186	3.04866	0.17636	0.09155	0.62498
TP2/ (IN12 + TP2 + IN23)		(TP1 + IN12)/TP2		(TP3 + IN23)/TP2	
0.35102		2.23183		2.23183	
HOS	InTL	HOS/HOI	InS/HOS	ODT %	TDT %
2.90175	2.02243	1.61928	0.78770	1.50000	0.71008
HVT21	HVT22	HVT31	HVT32	HVT32/HOI	HVT32/ HOS
0.00000	0.00000	0.46887	0.67544	0.37692	0.23277
PhiA	PhiC	PhiD	TH1	TH2	HOI
2.716 mm	3.116 mm	3.616 mm	0.25 mm	0.2 mm	1.792 mm
PhiA/ PhiD	TH1 + TH2	HOI	HOS	2(TH1 + TH2)/PhiA	InTL/HOS
0.7511	0.45 mm	0.2511	0.1551	0.3314	0.6970
PLTA	PSTA	NLTA	NSTA	SLTA	SSTA
-0.002 mm	0.008 mm	0.006 mm	-0.008 mm	-0.007 mm	0.006 mm

[0241] The results of the equations of the sixth optical embodiment based on Table 11 and Table 12 are listed in the following table:

Values related to the inflection points of the sixth optical embodiment (Reference wavelength: 555 nm)						
HIF221	0.5599	HIF221/HOI	0.3125	SGI221	-0.1487 SGI221 /(SGI221 + TP2)	0.2412
HIF311	0.2405	HIF311/HOI	0.1342	SGI311	0.0201 SGI311 /(SGI311 + TP3)	0.0413
HIF312	0.8255	HIF312/HOI	0.4607	SGI312	-0.0234 SGI312 /(SGI312 + TP3)	0.0476
HIF321	0.3505	HIF321/HOI	0.1956	SGI321	0.0371 SGI321 /(SGI321 + TP3)	0.0735

[0242] The figures related to the profile curve lengths obtained based on Table 11 and Table 12 are listed in the following table:

Sixth optical embodiment (Reference wavelength: 555 nm)						
ARE	1/2(HEP)	ARE value	ARE - 1/2(HEP)	2(ARE/HEP) %	TP	ARE/TP (%)
11	0.546	0.598	0.052	109.49%	0.468	127.80%
12	0.500	0.506	0.005	101.06%	0.468	108.03%
21	0.492	0.528	0.036	107.37%	0.349	151.10%
22	0.546	0.572	0.026	104.78%	0.349	163.78%
31	0.546	0.548	0.002	100.36%	0.559	98.04%
32	0.546	0.550	0.004	100.80%	0.559	98.47%

-continued

Sixth optical embodiment (Reference wavelength: 555 nm)						
ARS	EHD	ARS value	ARS - EHD	(ARS/EHD) %	TP	ARS/TP (%)
11	0.640	0.739	0.099	115.54%	0.468	158.03%
12	0.500	0.506	0.005	101.06%	0.468	108.03%
21	0.492	0.528	0.036	107.37%	0.349	151.10%
22	0.706	0.750	0.044	106.28%	0.349	214.72%
31	1.118	1.135	0.017	101.49%	0.559	203.04%
32	1.358	1.489	0.131	109.69%	0.559	266.34%

[0243] The optical image capturing module of the present invention could be one of a group consisting of an electronic portable device, an electronic wearable device, an electronic monitoring device, an electronic information device, an electronic communication device, a machine vision device, and a vehicle electronic device. In addition, the optical image capturing module of the present invention could reduce the required mechanism space and increase the visible area of the screen by using different lens groups with different number of lens.

[0244] As shown in FIG. 8A, an optical image capturing module 712 and an optical image capturing module 714 (front lens) of the present invention are applied to a mobile communication device 71 (e.g. a smart phone). As shown in FIG. 8B, an optical image capturing module 722 of the present invention is applied to a mobile information device 72 (e.g. a notebook). As shown in FIG. 8C, an optical image capturing module 732 of the present invention is applied to a smart watch 73. As shown in FIG. 8D, an optical image capturing module 742 of the present invention is applied to a smart head-wearing device 74 (e.g. a smart hat). As shown in FIG. 8E, an optical image capturing module 752 of the present invention is applied to a safety monitoring device 75 (e.g. an IP cam). As shown in FIG. 8F, an optical image capturing module 762 of the present invention is applied to a vehicle image device 76. As shown in FIG. 8G, an optical image capturing module 772 of the present invention is applied to an unmanned aircraft device 77. As shown in FIG. 8H, an optical image capturing module 782 of the present invention is applied to an extreme sport image device 78.

[0245] It must be pointed out that the embodiments described above are only some embodiments of the present invention. All equivalent structures which employ the concepts disclosed in this specification and the appended claims should fall within the scope of the present invention.

What is claimed is:

1. An optical image capturing module, comprising:

a circuit assembly, which comprises a circuit substrate, a sensor holder, and an image sensing component, wherein the circuit substrate has a plurality of circuit contacts thereon; the image sensing component has a first surface and a second surface, wherein the first surface is connected to the circuit substrate; the second surface has a sensing surface and a plurality of image contacts; each of the image contacts is electrically connected to one of the circuit contacts on the circuit substrate via a plurality of signal transmission elements; the sensor holder is disposed on the circuit substrate and the second surface of the image sensing component, and covers the circuit contacts and the image contacts; the signal transmission elements are embedded in the sensor holder; and

a lens assembly, which comprises a fixed base, a movable base, and a lens group, wherein the fixed base is made of an opaque material and has a focusing hole penetrating through two ends of the fixed base, so that the fixed base is hollow; the fixed base is disposed on the sensor holder; the movable base is disposed in the fixed base, and is located in the focusing hole to be located above the image sensing component, and is controllable to move relative to the fixed base in the focusing hole in a central axial direction of the focusing hole; the movable base has a receiving hole penetrating through two ends of the movable base, so that the movable base

is hollow; the lens group comprises at least two lenses having refractive power, and is disposed on the lens base and is located in the receiving hole; moreover, an image plane of the lens group is adjustable to be located on the sensing surface along with a movement of the movable base, and an optical axis of the lens group overlaps with a central normal of the sensing surface, so that a light passes through the lens group in the receiving hole and projects onto the sensing surface; wherein the optical image capturing module satisfies:

$$1.0 \leq f/HEP < 10.0;$$

$$0 \text{ deg} < HAF \leq 150 \text{ deg};$$

$$0 \text{ mm} \leq \Phi HiD \leq 18 \text{ mm};$$

$$0 < \Phi HiA / \Phi HiD \leq 0.99; \text{ and}$$

$$0.9 \leq 2(ARS/HEP) \leq 2.0;$$

where f is a focal length of the lens group; HEP is an entrance pupil diameter of the lens group; HAF is a half of a maximum field angle of the lens group; ΦHiD is a maximum value of a minimum length on a periphery of the fixed base perpendicular to the optical axis of the lens group; ΦHiA is a maximum effective diameter of an image-side surface of the at least two lenses of the lens group closest to the image plane; ARS is a profile curve length measured from a start point where the optical axis of the lens group passes through any surface of one of the at least two lenses, along a surface profile of the corresponding lens, and finally to a coordinate point of a perpendicular distance where is a half of the entrance pupil diameter away from the optical axis.

2. The optical image capturing module of claim 1, wherein the optical image capturing module further satisfies:

$$0.9 \leq ARS/EHD \leq 2.0;$$

where for any surface of any lens, ARS is a profile curve length measured from a start point where the optical axis passes therethrough, along a surface profile thereof, and finally to an end point of the maximum effective half diameter thereof; EHD is a maximum effective half diameter thereof.

3. The optical image capturing module of claim 1, wherein the optical image capturing module further satisfies:

$$PLTA \leq 100 \mu\text{m};$$

$$PSTA \leq 100 \mu\text{m};$$

$$NLTA \leq 100 \mu\text{m};$$

$$NSTA \leq 100 \mu\text{m};$$

$$SLTA \leq 100 \mu\text{m};$$

$$SSTA \leq 100 \mu\text{m}; \text{ and}$$

$$|TDT| < 250\%$$

where HOI is a maximum height for image formation perpendicular to the optical axis on the image plane; PLTA is a transverse aberration at 0.7 HOI in a positive direction of a tangential ray fan aberration after the longest operation wavelength passing through an edge of the entrance pupil; PSTA is a transverse aberration at 0.7 HOI in the positive direction of the tangential ray fan aberration after the shortest operation wavelength passing through the edge of the entrance pupil; NLTA is a transverse aberration at 0.7 HOI in a negative direction of the tangential ray fan aberration after the longest operation wavelength passing through the edge

of the entrance pupil; NSTA is a transverse aberration at 0.7 HOI in the negative direction of the tangential ray fan aberration after the shortest operation wavelength passing through the edge of the entrance pupil; SLTA is a transverse aberration at 0.7 HOI of a sagittal ray fan aberration after the longest operation wavelength passing through the edge of the entrance pupil; SSTA is a transverse aberration at 0.7 HOI of the sagittal ray fan aberration after the shortest operation wavelength passing through the edge of the entrance pupil; TDT is a TV distortion for image formation in the optical image capturing module.

4. The optical image capturing module of claim 1, wherein the lens group comprises four lenses having refractive power, which are constituted by a first lens, a second lens, a third lens, and a fourth lens in order along an optical axis from an object side to an image side; the lens group satisfies:

$$0.1 \leq \text{InTL}/\text{HOS} \leq 0.95;$$

where HOS is a distance in parallel with the optical axis between an object-side surface of the first lens and the image plane; InTL is a distance in parallel with the optical axis from the object-side surface of the first lens to an image-side surface of the fourth lens.

5. The optical image capturing module of claim 1, wherein the lens group comprises five lenses having refractive power, which are constituted by a first lens, a second lens, a third lens, a fourth lens, and a fifth lens in order along an optical axis from an object side to an image side; the lens group satisfies:

$$0.1 \leq \text{InTL}/\text{HOS} \leq 0.95;$$

where HOS is a distance in parallel with the optical axis between an object-side surface of the first lens and the image plane; InTL is a distance in parallel with the optical axis from the object-side surface of the first lens to an image-side surface of the fifth lens.

6. The optical image capturing module of claim 1, wherein the lens group comprises six lenses having refractive power, which are constituted by a first lens, a second lens, a third lens, a fourth lens, a fifth lens, and a sixth lens in order along an optical axis from an object side to an image side; the lens group satisfies:

$$0.1 \leq \text{InTL}/\text{HOS} \leq 0.95;$$

where HOS is a distance in parallel with the optical axis between an object-side surface of the first lens and the image plane; InTL is a distance in parallel with the optical axis from the object-side surface of the first lens to an image-side surface of the sixth lens.

7. The optical image capturing module of claim 1, wherein the lens group comprises seven lenses having refractive power, which are constituted by a first lens, a second lens, a third lens, a fourth lens, a fifth lens, a sixth lens, and a seventh lens in order along an optical axis from an object side to an image side; the lens group satisfies:

$$0.1 \leq \text{InTL}/\text{HOS} \leq 0.95;$$

where HOS is a distance in parallel with the optical axis between an object-side surface of the first lens and the image plane; InTL is a distance in parallel with the optical axis from the object-side surface of the first lens to an image-side surface of the seventh lens.

8. The optical image capturing module of claim 1, wherein the optical image capturing module further satisfies:

$$\begin{aligned} \text{MTFQ0} &\geq 0.2; \\ \text{MTFQ3} &\geq 0.01; \text{ and} \\ \text{MTFQ7} &\geq 0.01; \end{aligned}$$

where HOI is a maximum height for image formation perpendicular to the optical axis on the image plane; MTFQ0, MTFQ3, and MTFQ7 are respectively a value of modulation transfer function of visible light in a spatial frequency of 110 cycles/mm at the optical axis, 0.3 HOI, and 0.7 HOI on an image plane for visible light.

9. The optical image capturing module of claim 1, further comprising an aperture, wherein the optical image capturing module further satisfies:

$$0.2 \leq \text{InS}/\text{HOS} \leq 1.1;$$

where InS is a distance on the optical axis between the aperture and the image plane; HOS is a distance in parallel with the optical axis between an object-side surface of one of the at least two lenses of the lens group furthest from the image plane and the image plane.

10. The optical image capturing module of claim 1, wherein the movable base further comprises a lens barrel and an inner holder; the inner holder is disposed in the fixed base, and is located in the focusing hole, and is controllable to move relative to the fixed base; the inner holder has an inner through hole penetrating through two ends of the inner holder, so that the inner holder is hollow; the lens barrel is disposed in the inner holder and is located in the inner through hole, and is driven by the inner holder to move relative to the fixed base, and has the receiving hole penetrating through two ends of the lens barrel, so that the lens barrel is hollow; the lens group is disposed in the lens barrel to directly face the image sensing component.

11. The optical image capturing module of claim 10, wherein the optical image capturing module further satisfies:

$$0 \text{ mm} \leq \text{TH1} + \text{TH2} \leq 1.5 \text{ mm};$$

where TH1 is a distance from an outer wall of the fixed base to an inner wall of the inner through hole of the inner holder in a direction perpendicular to the optical axis of the lens group; TH2 is a minimum thickness of the lens barrel.

12. The optical image capturing module of claim 10, wherein the optical image capturing module further satisfies:

$$0 < (\text{TH1} + \text{TH2})/\text{HOI} \leq 0.95;$$

where TH1 is a distance from an outer wall of the fixed base to an inner wall of the inner through hole of the inner holder in a direction perpendicular to the optical axis of the lens group; TH2 is a minimum thickness of the lens barrel; HOI is a maximum height for image formation perpendicular to the optical axis on the image plane.

13. The optical image capturing module of claim 10, wherein an outer peripheral wall of the lens barrel has an external thread thereon, and an inner wall of the inner through hole of the inner holder has an inner thread thereon, wherein the inner thread is screwed with the external thread, so that the lens barrel is disposed in the inner holder to be fixed in the inner through hole.

14. The optical image capturing module of claim 10, wherein a glue is coated between the lens barrel and the

inner holder, and the lens barrel and the inner holder are fixed to each other via the glue, so that the lens barrel is disposed in the inner holder and is fixed in the inner through hole.

15. The optical image capturing module of claim **1**, wherein the movable base is integrally formed as a monolithic unit.

16. The optical image capturing module of claim **1**, wherein the optical image capturing module further comprises an IR-cut filter which is disposed on the movable base or on the sensor holder and is located above the image sensing component.

17. The optical image capturing module of claim **1**, wherein the optical image capturing module further comprises an IR-cut filter which is disposed in the fixed base and is located above the image sensing component.

18. The optical image capturing module of claim **17**, wherein the fixed base comprises a filter holder; the filter holder has a through hole penetrating through two ends of the filter holder; the IR-cut filter is disposed in the filter holder and is located in the through hole of the filter holder; the filter holder is disposed on the sensor holder, so that the IR-cut filter is located above the image sensing component.

19. The optical image capturing module of claim **18**, wherein the fixed base further comprises an outer holder; the outer holder is fixed on the filter holder and has an outer through hole penetrating through two ends of the outer holder, so that the outer holder is hollow; the outer through hole and the through hole of the filter holder constitute the focusing hole; in addition, the movable base is disposed in the outer holder to be located in the outer through hole, and is controllable to move relative to the outer holder in the outer through hole.

20. The optical image capturing module of claim **19**, wherein the movable base comprises an inner holder and a lens barrel; the inner holder is disposed in the outer holder, and is located in the outer through hole, and is controllable to move relative to the outer holder, and has an inner through hole penetrating through two ends of the inner holder, so that the inner holder is hollow; the lens barrel is disposed in the inner holder and is located in the inner through hole, and is driven by the inner holder to move relative to the fixed base, and has the receiving hole penetrating through two ends of the lens barrel, so that the lens barrel is hollow; the lens group is disposed in the lens barrel to directly face the image sensing component.

21. The optical image capturing module of claim **20**, wherein the optical image capturing module further satisfies:

$$0 \text{ mm} < TH1 + TH2 \leq 1.5 \text{ mm};$$

where TH1 is a distance from an outer wall of the outer holder to an inner wall of the inner through hole of the inner holder in a direction perpendicular to the optical axis of the lens group; TH2 is a minimum thickness of the lens barrel.

22. The optical image capturing module of claim **20**, wherein the optical image capturing module further satisfies:

$$0 < (TH1 + TH2) / HOI \leq 0.95;$$

where TH1 is a distance from an outer wall of the outer holder to an inner wall of the inner through hole of the inner holder in a direction perpendicular to the optical axis of the lens group; TH2 is a minimum thickness of the lens barrel; HOI is a maximum height for image formation perpendicular to the optical axis on the image plane.

23. The optical image capturing module of claim **20**, wherein an outer peripheral wall of the lens barrel has an external thread thereon, and an inner wall of the inner through hole of the inner holder has an inner thread thereon, wherein the inner thread is screwed with the external thread, so that the lens barrel is disposed in the inner holder and is located in the inner through hole; in addition, a glue is coated between the outer holder and the filter holder, and the outer holder and the filter holder are fixed to each other via the glue, so that the outer holder is fixed on the filter holder.

24. The optical image capturing module of claim **20**, wherein a glue is coated between the lens barrel and the inner holder, and the lens barrel and the inner holder are fixed to each other via the glue, so that the lens barrel is disposed in the inner holder and is located in the inner through hole; in addition, a glue is coated between the outer holder and the filter holder, and the outer holder and the filter holder are fixed to each other via the glue, so that the outer holder is fixed on the filter holder.

25. The optical image capturing module of claim **1**, wherein the movable base is integrally formed as a monolithic unit; a glue is coated between the outer holder and the filter holder, and the outer holder and the filter holder are fixed to each other via the glue, so that the outer holder is fixed on the filter holder.

26. The optical image capturing module of claim **1**, wherein the optical image capturing module is applied to one of a group consisting of an electronic portable device, an electronic wearable device, an electronic monitoring device, an electronic information device, an electronic communication device, a machine vision device, and a vehicle electronic device.

* * * * *