



US 20180085033A1

(19) **United States**

(12) **Patent Application Publication**
SULZER et al.

(10) **Pub. No.: US 2018/0085033 A1**

(43) **Pub. Date: Mar. 29, 2018**

(54) **MECHANICAL AUDIO AND HAPTIC
FEEDBACK DEFLECTION BEAM**

Related U.S. Application Data

(60) Provisional application No. 62/150,957, filed on Apr. 22, 2015.

(71) Applicants: **BOARD OF REGENTS, THE
UNIVERSITY OF TEXAS SYSTEM,**
Austin, TX (US); **SETON
HEALTHCARE FAMILY,** Austin, TX
(US)

Publication Classification

(51) **Int. Cl.**
A61B 5/11 (2006.01)
A61B 5/00 (2006.01)

(52) **U.S. Cl.**
CPC *A61B 5/1126* (2013.01); *A61B 5/4576*
(2013.01); *A61B 5/4566* (2013.01); *A61B*
5/7455 (2013.01); *A61B 5/6822* (2013.01);
A61B 5/7405 (2013.01); *A61B 5/6833*
(2013.01)

(72) Inventors: **James S. SULZER,** Austin, TX (US);
Jose J. MENDEZ, Jr., Austin, TX
(US); **Nicholas D. PHILLIPS,** Austin,
TX (US); **Lisa STEVENS,** Austin, TX
(US); **Curtis MERRING,** Austin, TX
(US)

(21) Appl. No.: **15/568,109**

(57) **ABSTRACT**


(22) PCT Filed: **Apr. 22, 2016**

Devices and methods for detecting joint motion of a user. In particular embodiments, devices may comprise a deflectable beam coupled to a user via adhesive pads located between the neck and shoulder of the user. Audio and haptic feedback can be provided to the user when the deflectable beam deflects due to motion of the joint.

(86) PCT No.: **PCT/US2016/028749**

§ 371 (c)(1),

(2) Date: **Oct. 20, 2017**






FIG. 1




FIG. 2




FIG. 3

MECHANICAL AUDIO AND HAPTIC FEEDBACK DEFLECTION BEAM

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This applications claims priority to U.S. Provisional Patent Application Ser. No. 62/150,957 filed Apr. 22, 2015, the entire contents of which are incorporated herein by reference.

BACKGROUND INFORMATION

[0002] Existing methods for monitoring joint movement include shortcomings that have not been adequately addressed. For example, currently the traditional method in therapy for “shoulder hiking” is to undergo a set of exercises in front of a mirror or with the guidance of a clinician or assistant. This traditional method requires many hours of observation of the patient for corrections that could be used for other purposes. This method also does not allow the patient to work independently to improve their condition for better results.

[0003] There is presently a shortage of devices and methods that provide independence to the patient. Exemplary embodiments of the device and methods disclosed herein promote patient independence by providing audio and haptic feedback of excessive shoulder hiking to the user. Exemplary embodiments not only meet the desired criteria, but can also be applied for other uses around joints, the torso, or neck.

SUMMARY

[0004] Exemplary embodiments of the present disclosure address the issues described above. As explained more fully below, in one exemplary embodiment the device comprises a deflectable beam configured to provide audio and haptic feedback to the user when the deflectable beam is deflected due to joint movement. In specific embodiments the deflectable beam comprises a first end and a second end, and the device comprises a first support coupled to the deflectable beam proximal to the first end and a second support coupled to the deflectable beam proximal to the second end. In particular embodiments, the device also includes a first adhesive pad coupled to the first support; and a second adhesive pad coupled to the second support. Exemplary embodiments also include method of using devices as described herein.

[0005] Exemplary embodiments of the present disclosure provide numerous benefits over existing technologies. For example, exemplary embodiments are mechanical in nature and do not require expensive or complicated electronics for operation. In addition, exemplary embodiments provide audio and haptic feedback upon deflection. Dimensions of the deflectable beam can be altered for different applications (e.g. to monitor different joints).

[0006] Exemplary embodiments are also user friendly, inexpensive to produce, and can be easily attached and removed from the user. Such benefits allow for independent operation by the patient/user, and can promote time efficiency for clinicians and tech assistants. This can allow for a safe and comfortable interaction with the patient.

[0007] Embodiments of the devices and methods disclosed herein address the issue of detecting joint movement (e.g. the elevation of the shoulder on the user) while under-

going therapy without needing the constant observation of technicians and promotes independence through each therapy session. Exemplary embodiments use can be expanded to other applications that require detection of excessive joint movement.

[0008] Exemplary embodiments are also advantageous by providing purely mechanical feedback, as opposed to other devices and methods that use electronics. Exemplary embodiments are also easy to use and fabricate.

[0009] In the present disclosure, the term “coupled” is defined as connected, although not necessarily directly, and not necessarily mechanically.

[0010] The use of the word “a” or “an” when used in conjunction with the term “comprising” in the claims and/or the specification may mean “one,” but it is also consistent with the meaning of “one or more” or “at least one.” The terms “approximately,” “about” or “substantially” mean, in general, the stated value plus or minus 5%. The use of the term “or” in the claims is used to mean “and/or” unless explicitly indicated to refer to alternatives only or the alternative are mutually exclusive, although the disclosure supports a definition that refers to only alternatives and “and/or.”

[0011] The terms “comprise” (and any form of comprise, such as “comprises” and “comprising”), “have” (and any form of have, such as “has” and “having”), “include” (and any form of include, such as “includes” and “including”) and “contain” (and any form of contain, such as “contains” and “containing”) are open-ended linking verbs. As a result, a method or device that “comprises,” “has,” “includes” or “contains” one or more steps or elements, possesses those one or more steps or elements, but is not limited to possessing only those one or more elements. Likewise, a step of a method or an element of a device that “comprises,” “has,” “includes” or “contains” one or more features, possesses those one or more features, but is not limited to possessing only those one or more features. Furthermore, a device or structure that is configured in a certain way is configured in at least that way, but may also be configured in ways that are not listed.

[0012] Other objects, features and advantages of the present invention will become apparent from the following detailed description. It should be understood, however, that the detailed description and the specific examples, while indicating specific embodiments of the invention, are given by way of illustration only, since various changes and modifications within the spirit and scope of the invention will be apparent to those skilled in the art from this detailed description.

BRIEF DESCRIPTION OF THE FIGURES

[0013] FIG. 1 illustrates an exploded view of one portion an exemplary embodiment of device according to the present disclosure.

[0014] FIG. 2 illustrates a perspective view of the embodiment of FIG. 1 during use.

[0015] FIG. 3 illustrates a perspective view of a component of the embodiment of FIG. 1.

DETAILED DESCRIPTION OF ILLUSTRATIVE EMBODIMENTS

[0016] Referring now to FIGS. 1-3, a device 100 for detecting joint motion of a user is illustrated. FIG. 1 illus-

trates an exploded view of one half of device **100**. It is understood the other half of device **100** not shown in FIG. **1** is equivalent to the portion shown in FIG. **1**. FIG. **2** illustrates a perspective view of device **100** during use, while FIG. **3** illustrates a perspective view of a deflectable beam **10** of device **100**.

[0017] In this embodiment, device **100** comprises deflectable beam **10** comprising a first end **15** and a second end **115**. The illustrated embodiment further comprises a first support **20** coupled to deflectable beam **10** proximal to first end **15**, and a second support **120** coupled to deflectable beam **10** proximal to second end **115**. In specific embodiments first support **20** and second support **120** may be configured as U-shaped brackets such that ends **15** and **115** can be inserted into the brackets. In particular embodiments, first support **20** and second support **120** can be coupled to first and second adhesive pads **50** and **150**, respectively. In specific embodiments, first and second adhesive pads **50** and **150** may be components that are also configured for use in electrocardiograms, and in particular, as electrocardiogram electrodes.

[0018] Adhesive pads **50** and **150** can be used to couple device **100** to a user **210** (e.g. by adhering to the skin of user **210** in an area proximal to the joint in which it is desired to detect motion). In the embodiment shown in FIG. **2**, device **100** has been coupled to user **210** in an area between shoulder **220** and neck **230**. In this location, device **100** can detect motion of shoulder **220** to provide audio and haptic feedback to user **210** when shoulder **220** has extended past a particular range of motion.

[0019] For example, as shoulder **220** is raised, adhesive pad **50** will move because it is coupled to user **210** in an area proximal to should **220**. Adhesive pad **150**, which is distal to shoulder **220** (relative to adhesive pad **50**), will not move an amount equivalent to that of adhesive pad **50**. Accordingly, the distance between adhesive pads **50** and **150** will decrease as shoulder **220** is raised. This decrease in distance between adhesive pads **50** and **150** will lead to a corresponding decrease in the distance between supports **40** and **140**, which are coupled to ends **15** and **115** of deflectable beam **10**. Accordingly, supports **40** and **140** will exert a compressive force on beam **10** in the direction of arrows A and B. When shoulder **220** is raised a sufficient amount, a deflection **60** will form in deflectable beam **10** and an audio feedback (e.g. an audible noise) **70** will be emitted as a result of the deflection. In addition, deflection **60** will result in a decreased stiffness in deflectable beam. The reduction in stiffness can provide haptic feedback to user **210** in addition to the audio feedback from audible noise **70**. This feedback can alert user **210** that shoulder **220** has been raised to a particular threshold in the range of motion.

[0020] Referring specifically now to FIG. **1**, in certain embodiments, first support **20** can be coupled to deflectable beam **10** via a threaded fastener **40** and a snap member **30**. It is understood that other embodiments may comprise different coupling mechanisms, including for example combinations of rivets, hook-and-loop fasteners, etc. In the embodiment shown, threaded fastener **40** may be inserted through an orifice **25** in first support **20** and an orifice **17** in deflectable beam. In certain embodiments, threaded fastener **40** can be threaded into first support **20** and/or deflectable beam **10**. In some embodiments, threaded fastener **40** may be threaded into snap member **30**. Snap member **30** can be inserted into a cavity **27** in first support **20**, and snap member **30** can then be coupled to adhesive pad **50** (which also

comprises a snap member **55**). In this manner, first support **20** can be coupled to deflectable beam **10** and adhesive pad **50**. It is understood that the second support **120** can be coupled to deflectable beam **10** and adhesive pad **150** via threaded fastener **140** in an equivalent manner. As shown in FIG. **3**, deflectable beam **10** also comprises an orifice **117** proximal to end **115** through which threaded fastener **140** may be inserted.

[0021] In the embodiment illustrated in FIG. **3**, deflectable beam **10** comprises a length L and width W. In particular embodiments, L may range from two inches to five inches, or more particularly from three inches to four inches, or more particularly approximately 3.5 inches. In certain embodiments, W may range from 0.15 inches to 0.35 inches, or more particularly from 0.2 inches to 0.3 inches, or more particularly approximately 0.25 inches. In particular embodiments, deflectable beam **10** can have a thickness (e.g. the dimension orthogonal to width W and length L) of less than 0.010 inches. In specific embodiments, deflectable beam **10** may have a thickness of less than 0.005 inches.

[0022] In the embodiment shown, deflectable beam **10** comprises a curved profile **12** across width W. In some embodiments, deflectable beam **10** is a metal beam, and particular embodiments a steel beam. In certain embodiments, deflectable beam **10** may be formed from crinkle material, including for example, material used in children's toys. The mechanical properties and shape of deflectable beam **10** (including for example, the material, length, width, and the curved profile) can provide for particular audio feedback upon beam deflection. In exemplary embodiments, deflectable beam **10** is excited to its natural frequency which is in the audible range for humans, and the emitted amplitude of the frequency is high enough to be heard by user **210**. Accordingly, device **100** can provide audio and haptic feedback when shoulder **220** elevates so as to detect excessive joint range of motion for therapeutic use in a clinic and possibly outside the clinic.

[0023] All of the devices, systems and/or methods disclosed and claimed herein can be made and executed without undue experimentation in light of the present disclosure. While the devices, systems and methods of this invention have been described in terms of particular embodiments, it will be apparent to those of skill in the art that variations may be applied to the devices, systems and/or methods in the steps or in the sequence of steps of the method described herein without departing from the concept, spirit and scope of the invention. All such similar substitutes and modifications apparent to those skilled in the art are deemed to be within the spirit, scope and concept of the invention as defined by the appended claims.

REFERENCES

- [0024] The contents of the following references are incorporated by reference herein:
- [0025] U.S. Pat. No. 2,064,603
 - [0026] U.S. Pat. No. 2,809,042
 - [0027] U.S. Pat. No. 3,350,100
 - [0028] U.S. Pat. No. 4,800,897
 - [0029] U.S. Pat. No. 4,895,372
 - [0030] U.S. Pat. No. 5,146,929
 - [0031] U.S. Pat. No. 5,522,401
 - [0032] U.S. Pat. No. 5,743,806
 - [0033] U.S. Pat. No. 5,876,292
 - [0034] U.S. Pat. No. 6,032,530

[0035] U.S. Pat. No. 6,119,516

[0036] U.S. Pat. No. 6,447,425

[0037] U.S. Pat. No. 7,980,141

[0038] U.S. Patent Publication 2014/0128689

1. A device for detecting joint motion of a user, the device comprising:

a deflectable beam comprising a first end and a second end;

a first support coupled to the deflectable beam proximal to the first end;

a second support coupled to the deflectable beam proximal to the second end;

a first adhesive pad coupled to the first support; and

a second adhesive pad coupled to the second support, wherein:

the deflectable beam is configured to provide audio and haptic feedback to the user when the deflectable beam is deflected.

2. The device of claim 1 wherein the device is configured to be coupled to a user in an area proximal to a joint.

3. The device of claim 2 wherein the deflectable beam is configured to deflect when the joint is moved by the user.

4. The device of claim 2 wherein the joint is a shoulder joint.

5. The device of claim 2 wherein the joint is a neck joint.

6. The device of claim 1 wherein the deflectable beam is a metal beam.

7. The device of claim 1 wherein:

the first adhesive pad is coupled to the first support via a first snap member and a second snap member; and

the second adhesive pad is coupled to the second support via a third snap member and a fourth snap member.

8. The device of claim 7 wherein:

the first snap member is inserted into a first cavity in the first support;

the second snap member is coupled to the first adhesive pad;

the third snap member is inserted into a second cavity in the second support; and

the fourth snap member is coupled to the second adhesive pad.

9. The device of claim 1 wherein the haptic feedback results from a decreased stiffness of the deflectable beam.

10. The device of claim 1 wherein the audio feedback is in the audible range for a human.

11. The device of claim 1 wherein the deflectable beam is configured to provide secondary audio feedback when the deflectable beam moves from a deflected position to a straight position.

12. The device of claim 1 wherein the deflectable beam: has a length between two inches and five inches; has a width between 0.15 inches and 0.35 inches; and has a thickness less than 0.010 inches.

13. The device of claim 1 wherein the deflectable beam has a curved profile.

14. A method of detecting movement of a joint of a user, the method comprising:

coupling a device comprising a deflectable beam to an area proximal to the joint; and

moving the joint an amount sufficient to cause a deflection of the deflectable beam, wherein:

the deflection of the deflectable beam produces an audio and haptic feedback to the user.

15. The method of claim 14 wherein coupling the device comprising the deflectable beam to the area proximal to the joint comprises coupling adhesive pads to the user.

16. The method of claim 14 wherein the joint is a shoulder joint.

17. The method of claim 14 wherein the joint is a neck joint.

18. The method of claim 14 wherein the deflectable beam is a metal beam.

19. The method of claim 14 wherein the haptic feedback results from a decreased stiffness of the deflectable beam.

20. The method of claim 14 wherein the audio feedback is in the audible range for a human.

21. The method of claim 14 wherein the deflectable beam is configured to provide secondary audio feedback when the deflectable beam moves from a deflected position to a straight position.

22. The method of claim 14 wherein the deflectable beam: has a length between two inches and five inches; has a width between 0.15 inches and 0.35 inches; and has a thickness less than 0.010 inches.

* * * * *