



US 20190129902A1

(19) **United States**

(12) **Patent Application Publication**
Barday et al.

(10) **Pub. No.: US 2019/0129902 A1**

(43) **Pub. Date: May 2, 2019**

(54) **DATA PROCESSING SYSTEMS FOR GENERATING AND POPULATING A DATA INVENTORY**

on Jun. 23, 2016, provisional application No. 62/348,695, filed on Jun. 10, 2016, provisional application No. 62/541,613, filed on Aug. 4, 2017, provisional application No. 62/537,839, filed on Jul. 27, 2017.

(71) Applicant: **OneTrust, LLC**, Atlanta, GA (US)

Publication Classification

(72) Inventors: **Kabir A. Barday**, Atlanta, GA (US); **Mihir S. Karanjkar**, Marietta, GA (US); **Steven W. Finch**, Kennesaw, GA (US); **Ken A. Browne**, Johns Creek, GA (US); **Nathan W. Heard**, Marietta, GA (US); **Aakash H. Patel**, Norcross, GA (US); **Jason L. Sabourin**, Brookhaven, GA (US); **Richard L. Daniel**, Atlanta, GA (US); **Dylan D. Patton-Kuhl**, Atlanta, GA (US); **Jonathan Blake Brannon**, Smyrna, GA (US)

(51) **Int. Cl.**
G06F 16/28 (2006.01)
G06F 17/24 (2006.01)
H04L 29/06 (2006.01)
G06F 21/55 (2006.01)
G06N 20/00 (2006.01)
G06F 15/76 (2006.01)
G06F 16/25 (2006.01)
(52) **U.S. Cl.**
CPC *G06F 16/288* (2019.01); *G06F 17/248* (2013.01); *H04L 63/101* (2013.01); *G06F 16/254* (2019.01); *G06N 20/00* (2019.01); *G06F 15/76* (2013.01); *G06F 21/552* (2013.01)

(21) Appl. No.: **16/226,272**

(22) Filed: **Dec. 19, 2018**


Related U.S. Application Data

(63) Continuation of application No. 16/041,545, filed on Jul. 20, 2018, now Pat. No. 10,204,154, which is a continuation-in-part of application No. 15/996,208, filed on Jun. 1, 2018, now Pat. No. 10,181,051, which is a continuation-in-part of application No. 15/853,674, filed on Dec. 22, 2017, now Pat. No. 10,019,597, which is a continuation-in-part of application No. 15/619,455, filed on Jun. 10, 2017, now Pat. No. 9,851,966, which is a continuation-in-part of application No. 15/254,901, filed on Sep. 1, 2016, now Pat. No. 9,729,583.

(60) Provisional application No. 62/360,123, filed on Jul. 8, 2016, provisional application No. 62/353,802, filed

(57) **ABSTRACT**

In particular embodiments, a data processing data inventory generation system is configured to: (1) generate a data model (e.g., a data inventory) for one or more data assets utilized by a particular organization; (2) generate a respective data inventory for each of the one or more data assets; and (3) map one or more relationships between one or more aspects of the data inventory, the one or more data assets, etc. within the data model. In particular embodiments, a data asset (e.g., data system, software application, etc.) may include, for example, any entity that collects, processes, contains, and/or transfers personal data (e.g., such as a software application, “internet of things” computerized device, database, website, data-center, server, etc.). For example, a first data asset may include any software or device (e.g., server or servers) utilized by a particular entity for such data collection, processing, transfer, storage, etc.






FIG. 1




FIG. 2




FIG. 3

MODEL WITHOUT PROCESSING ACTIVITIES




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8

900

The screenshot shows a web application interface for 'OneTrust'. At the top, there is a navigation bar with the URL 'https://dev3.onetrust.com/app/#/data/asset/inventory/20' and the user name 'Hello Jason SITEADMIN79'. Below the navigation bar is a sidebar menu with options: Data Mapping, Dashboard, Asset Template, Processing Template, Assessments, Assets, Processing Activities, Data Elements, Asset Map, and Scan Results. The main content area is titled 'Data Mapping > Assets' and contains a table of assets. The table has columns for Assets, Managing Organi..., Hosting Location, Type, Processing Activi..., and Status. Below the table, there is a '+ New Assets' button and a pagination indicator 'Showing 1-6 of 6'. The interface is labeled '900' in the top right corner.

Assets	Managing Organi...	Hosting Location	Type	Processing Activi...	Status
4th Asset	Sabourin DM79	Tunisia	Database	****	New
5th Asset	Sabourin DM79	United Arab Emira..	****	****	In Discovery
7th Asset	Sabourin DM79	Algeria	****	****	In Discovery
Asset 1	Sabourin DM79	Afghanistan	Application	****	In Discovery
Asset 2	Sabourin DM79	United Arab Emira...	Database	****	In Discovery
ThirdAsset	Sabourin DM79	United Kingdom	****	****	In Discovery

+ New Assets

Showing 1-6 of 6

FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13

1400




FIG. 14

1500

OneTrust

Secure | <https://dev3.onetrust.com/app/#/p/a/datamap/templateb-4a996cd-2d8e-481e-9a14-67b43152a3bb/?templateType=30> | Hello Jason SITEADMIN79

Template > Processing Activity Questionnaire [V2] DRAFT Show Versions Publish Template

1420

1510

1500

Template Builder

Drag and drop question to template.

- Textbox
- MultiChoice
- Asset Attributes
- Data Subjects

Section 1 Welcome

Section 2 Business Process Information

Section 3 Personal Data

Section 4 Source

Section 5 Storage

Section 6 Destinations

Section 7 Access and Use

+ Add Section

FIG. 15

1600

The screenshot shows a web application interface for 'OneTrust'. At the top, the user is logged in as 'Sabourin DM79' with the role 'Hello Jason SITEADMIN7'. The page title is 'Data Mapping > Assets'. The main content area displays a table of assets with columns for 'Managing Organi...', 'Hosting Location', 'Type', 'Processing Activi...', and 'Status'. A selected asset is shown in a detailed view below the table, including fields for 'Asset Attributes', 'Asset', 'New Asset', 'Processing Activities', 'Internal or 3rd Party Storage', 'Other Security Measures', 'Storage Format', 'Volume of Data Subjects', 'Data Retention', 'IT Owner', 'Technical Security Measures', and 'Organizational Security Measures'. The interface includes a navigation menu on the left with items like 'Dashboard', 'Asset Template', 'Processing Template', 'Assessments', 'Assets', 'Processing Activities', 'Data Elements', 'Asset Map', and 'Scan Results'. A search bar and a 'Delete(0)' button are also visible at the top right of the main content area.

1610

1615

FIG. 16




FIG. 17

1800

The screenshot displays a web application interface for 'OneTrust'. At the top left, there is a navigation menu with the following items: Data Mapping, Dashboard, Asset Template, Processing Template, Assessments, Assets, Processing Activities, Data Elements, Asset Map, and Scan Results. The main header area shows the user 'Sabourin DM79' and the text 'Hello Jason SITEADMIN79'. The main content area is titled '7th Asset' and includes a 'NOT STARTED' status indicator. Below this, there is a table of asset information:

ORGANIZATION	CREATOR	RESPONDENT	APPROVER	DEADLINE
Sabourin DM79	Jason SITEADMIN70	Jason Testing	Jason SITEADMIN79	Jun 29, 2017

Below the table, there is a section for 'Asset Information' with a circular icon. The main content area is divided into two sections: 'Description' and 'IT Owner'. The 'Description' section contains the text 'Provide a short description of the asset' and a text input field labeled '1820' with the placeholder text 'Enter Your answer here.'. The 'IT Owner' section contains the text 'Which Person is the IT Owner for this Asset?'.

FIG. 18




FIG. 19

2000

OneTrust | Secure | https://dev3.onetrust.com/app/#/pi/data/inventory/20 | Sabourin DM79 | Hello Jason SITEADMIN7

2010 | 2020 | Send Assessments(0) | Delete(0)

Data Mapping > Assets

Asset	Managing Organi...	Hosting Location	Type	Processing Activi...	Status
<input type="checkbox"/> 7th Asset	Managing Organization Group Sabourin DM79	Algeria	Hosting Location
<input checked="" type="checkbox"/> Asset Attributes	Status In Discovery	Description Value_1	2025	Technical Security Measures	Organizational Security Measures
<input type="checkbox"/> Internal or 3rd Party Storage	Storage Format	IT Owner
<input type="checkbox"/> Other Security Measures	Volume of Data Subjects	Data Retention
<input type="checkbox"/> Additional Asset	Sabourin DM79	Argentina	New
<input type="checkbox"/> Asset1	Ssabourin DM79	Afghanistan	Application	...	In Discovery
<input type="checkbox"/> Asset2	Ssabourin DM79	United Arab Emira...	Database	...	In Discovery

Navigation: Dashboard, Asset Template, Processing Template, Assessments, Assets, Processing Activities, Data Elements, Asset Map, Scan Results

FIG. 20

2100

OneTrust

OneTrust | Hello Payam Vaghefi

Project / Payam-Vaghefi-Initiate OnePIA-10-30-2017

PROJECT APPROVER
Payam Vaghefi

INITIATE ONEPIA

Welcome

General

Data Elements

Additional Information

1

Is this a new processing activity or an existing processing activity with changes?

Click here to establish Processing Activities inventory [here](#)

New Processing Activity

Existing activity undergoing a change

Not Sure

Comments Attachments History

2

Is your organisation conducting this activity on behalf of another organisation?

If so, please list the organisation(s) and their contact details.

Yes No Not Sure

Justify your answer below.

Enter justification here.

Comments Attachments History

Previous Section Next Section Submit

2110

2120

FIG. 21

2200

OneTrust

Project / Payam-Vaghefi-Initiate OneP/A-10-30-2017

VI | IN PROGRESS

2

2220

2

Describe the activity you're pursuing.

After making a selection, please elaborate in the notes field below.

For example:

- What are you planning to do?
- What is the activity assigned to achieve/address?
- Why are you doing it?
- What is the context?

2225

See including and updates to SIG notes

Payroll Processing	Sales
Market Research	Finance
Travel Planning	Recruiting Activities
Benefits	Compensation
Background Checks	Customer Engagement
Directed Marketing	Customer Service
Public Health and Safety	Customer Relationship Management
Retirement Planning	Insurance Processing
Health Related Initiatives	New Product Development
Online Learning Initiatives	E-Commerce Activities
Contractual Obligations	Other
Not Sure	

2200

OneTrust | Hello Payam Vaghefi

Previous Section | Next Section | Sign Out

FIG. 22

2300

OneTrust

Project / Payam Vaghefi-Initiate OnePIA-10-30-2017

PROJECT APPROVER
Payam Vaghefi

INITIATE ONEPIA

Welcome

General

Data Elements

Additional Information

8

What data is involved in the activity?

Note: This includes data collected from sources other than the individual and by means other than the product itself.

8.1 Background Checks

Which data elements are processed by Background Checks?

Credit checks	Criminal History
Details of gifts events and other hospitality received	Driving Citations
Drug Test Results	Outside directorships & external business interests
Reference or Background checks	References or referee details
Other	

8.2 Education

Which data elements are processed by Education?

Academic Transcripts	Education & training history
Educational Degrees	Grades
Languages	Professional Memberships
Qualifications / certifications	Other

OneTrust | Hello Payam Vaghefi

OneTrust

Previous Section

Next Section

Submit

FIG. 28

2400

OneTrust

Project / Payam Vaghefi-Initiate OnePIA-10-30-2017

VT IN PROGRESS

2

Medical Diagnosis

Prescription Number

Other

Health Plan Account Number

Medical Hobby

Smoking Habits

8.8 Workplace Wellfare

Which data elements are processed by Workplace Wellfare?

Grievances and complaints

Other

8.9 Personal Attributes

Which data elements are processed by Personal Attributes?

Height

Weight

Other

Marital Status

Location / tracking data

8.10 Personal Directory

Which data elements are processed by Personal Directory?

Contact details

Personal Email

Previous Residence Address

Home Address

Phone Numbers

Other

8.11 Personal Identification

Which data elements are processed by Personal Identification?

INITIATE ONEPIA

Welcome

General

Data Elements

Additional Information

Previous Section

Next Section

Submit

FIG. 24

2500




FIG. 25




FIG. 26




FIG. 27




FIG. 28




FIG. 29

3000

Secure | <https://onetrust.com/privacy-policy/>

AGMTE
CORPORATION

Products Services Pricing Company Partners Resources Blog Contact RFP Template Free Trial Request Demo

Privacy Policy

Effective Date: 17 April 2017

Policy Pages
 Privacy Policy
 Cookie Policy

We at OneTrust LLC and OneTrust Technology Limited (collectively, "OneTrust", "we" and "us") know you care about how your personal information is used and shared, and we take your privacy seriously. Please read the following to learn more about how we collect, store, use and disclose information about you when you interact or use any of the following websites: www.onetrust.com, www.cookiecslaw.org, www.optanon.com, www.governor.co.uk, and <https://cookiepedia.co.uk/> (collectively the "Websites") or any related events, trade shows, sales or marketing, and/or if you use any of our products, services or applications (including any trial) (collectively the "Services") in any manner.

Submit a Privacy Related Request

What does this Privacy Policy cover?
 This Privacy Policy covers our treatment of information that we gather when you are accessing or

3005

FIG. 30

ACME CORPORATION

I am a(n): Customer Employee Other

My request involves: Requesting info Opting Out Deleting Data Updating Data Filing a Complaint Other

Select One

First Name*: Joe

Last Name*: Lopez

Email Address*: lopez123456789@gmail.com

Telephone: 123.456.7890

Addr Line 1: 123 Main St

City: Madrid

Country of Residence: Spain

Details of my request:

Send me my Data

ACME Privacy
123 Main St
Capital City, ST, USA 20019

+1 800-123-4578
email: aboutus@ACME.com
Link to Privacy Policy

ACME CORPORATION

I am a(n): Customer Employee Other

My request involves: Requesting info Opting Out Deleting Data Updating Data Filing a Complaint Other

Select One

First Name*:

Last Name*:

Email Address*:

Telephone:

Addr Line 1:

City:

Country of Residence: Afghanistan (Dropdown)

Details of my request:

Ex: Please delete my personal information

I'm not a robot

ACME Privacy
123 Main St
Capital City, ST, USA 20219

+1 800-123-4578
email: aboutus@ACME.com
Link to Privacy Policy

FIG. 31

OneTrust
Helic Payam Vagheli

Project / Marketing Trade Show Process
UNDER REVIEW

58 **Does the activity involve the use of evaluation or scoring?**

For example:

- a bank that screens its customers against a credit reference database;
- a biotechnology company offering genetic tests directly to consumers in order to assess and predict the disease/health risks; or
- a company building behavioural or marketing profiles based on usage or navigation on its website.

Yes
 No
 Not Sure

Justify your answer below:

[Comments](#)
[Attachments](#)
[History](#)

7 **Flag Risks**
[Reacts More Info](#)

59 **Does the activity involve the use of automated decision-making?**

For example:

- an individual applies for a personal loan online and the website provides an immediate decision based on algorithms and a credit search; or
- a worker's pay being automatically adjusted according to automated monitoring of his productivity

This does not include processing that has little or no effect on individuals.

Yes
 No
 Not Sure

7 **Flag Risks**
[Reacts More Info](#)

< Previous Section
Next Section >
Continue to Risk Tracking

REVIEW NOTES

Approval Notes / Internal Notes

APPROVAL NOTES

APPROVED

This project has been approved, based on information, changes, and documentation provided to the Privacy team.
 The approval is based on the following assumptions:
 1. Legal approvals for updated notices
 2. Ongoing maintenance of privacy related self certification
 3. No-impact of this questionnaire should any process/materials change in the future

FIG. 32

OneTrust
OverTrust | Hello Payam Vagheli

Project / Marketing Trade Show Process

INITIATE ONEPIA 4

Welcome

General

Data Elements

Privacy Analysis

EUIEIA - GDPR Considerations

Article 29 Working Party "High-Risk" Criteria

GDPR Article 35 DPIA

Additional Information

UNDER REVIEW

Justify your answer:

Likelihood Severity

Risk Description

Please enter risk description here.

Recommendation

Please enter Recommendation here.

Deadline

Enter Deadline Date

Submit

Flag Risks

You have indicated that you would like to flag this question with risks. Please add a description of the risks and a Recommendation for mitigation below.

Likelihood Severity

Risk Description

Please enter risk description here.

Recommendation

Please enter Recommendation here.

Deadline

Enter Deadline Date

Submit

REVIEW NOTES

Approval Notes Internal Notes

B / U / S / E / D

APPROVAL NOTES

APPROVED

This project has been approved based on information, changes, and documentation provided to the Privacy team. The approval is based on the following assumptions:
 1. Legal approval for updated notices self certification
 2. Ongoing maintenance of privacy shield process/contracts change in the future.

Flag Risks

? Needs More Info

59 Does the activity involve systematic monitoring of publicly accessible area?

For example:
 • an individual app algorithms and a worker's pay by
 This does not include
 Yes No Not Sure

Justify your answer below.

Comments Attachments History

Flag Risks

? Needs More Info

60 Does the activity involve systematic monitoring of publicly accessible area?

For example:
 • an individual app algorithms and a worker's pay by
 This does not include
 Yes No Not Sure

Justify your answer below.

Comments Attachments History

Flag Risks

? Needs More Info

Previous Section

Next Section

Continue to Risk Tracking

2:41 PM 09/26/2017

OneTrust | About | Privacy | Terms of Use | Help | Contact Us

FIG. 33

OneTrust | Hello Payam Vaghefi

Project / Payam-Vaghefi-Initiate OnePIA-10-30-2017

PROJECT APPROVER
Payam Vaghefi

INITIATE ONEPIA

Welcome

General

Data Elements

Privacy Analysis

EU/EEA - GDPR Considerations

Article 29 Working Party High-Risk Ontario

GDPR Article 35 DPIA

Additional Information

58

Does

For example:

- a big data processing activity
- a big data processing activity
- a tool

Yes No Not Sure

Justify

59

Does the activity involve the use of automated decision-making?

For example:

- an individual applies for a personal loan online and the website provides an immediate decision based on algorithms and a credit search; or
- a worker's pay being automatically adjusted according to automated monitoring of his productivity.

This does not include processing that has little or no effect on individuals.

Yes No Not Sure

Flag Risks ? Needs More Info

Flag Risks ? Needs More Info

REVIEW NOTES

Approval Notes

Internal Notes

APPROVAL NOTES

B / U / S

APPROVED

This project has been approved, based on information, changes, and documentation provided to the Privacy team. The approval is based on the following assurances:

1. Legal approvals for updated notices
2. Ongoing maintenance of privacy related notification
3. Revising of this questionnaire should any process/risks change in the future.

FIG. 34

OneTrust | Hello Payam Vaghefi

Project / Payam-Vaghefi-Initiate OnePIA-10-30-2017

INITIATE ONEPIA

Welcome

General

Data Elements

Privacy Analysis

EUEEA - GDPR Considerations

Article 29 Working Party "High-Risk" Criteria

GDPR Article 36 DPIA

Additional Information

Examples of large scale processing of personal data for purposes by a processor:

- processing of personal data for marketing purposes by a processor
- processing of personal data for recruitment purposes by a processor
- processing of personal data for research purposes by a processor
- processing of personal data for security purposes by a processor

Does the activity involve processing of personal data for purposes that are likely to result in a high risk to the rights and freedoms of natural persons, and in particular because of the nature, scope, context, purposes or effects of the processing?

Yes / No

Justify your answer:

Comments

63

Does the activity involve processing of personal data for purposes that are likely to result in a high risk to the rights and freedoms of natural persons, and in particular because of the nature, scope, context, purposes or effects of the processing?

Yes / No

Justify your answer:

Flag Risks

You have indicated that you would like to flag this question with risks. Please add a description of the risks and a Recommendation for mitigation.

Severity: High

Likelihood: Medium

Calculated Risk: High

Very High	High	Medium	Low
Very High	High	Medium	Low
Very High	High	Medium	Low
Very High	High	Medium	Low

Risk Description: A DPIA may be mandatory under Article 35 of the GDPR, as the processing activity may be likely to result in a high risk to the rights and freedoms of natural persons.

Recommendation: Complete all Article 35 based DPIA requirements.

APPROVED

This subject has been approved, based on information, checks, and documentation provided to the Privacy team.

The approval is based on the following assumptions:

- Legal approvals for updated notices
- Ongoing maintenance of privacy shield self-certification
- No major or significant changes to any processes/activities in the future.

REVIEW NOTES

Approval Notes

Internal Notes

B / U

? Needs More Info

R Flag Risks

? Needs More Info

Continue to Risk Tracking

Previous Section

Next Section

FIG. 35

**DATA PROCESSING SYSTEMS FOR
GENERATING AND POPULATING A DATA
INVENTORY**

**CROSS-REFERENCE TO RELATED
APPLICATIONS**

[0001] This application is a continuation of U.S. patent application Ser. No. 16/041,545, filed Jul. 20, 2018, which is a continuation-in-part of U.S. patent application Ser. No. 15/996,208, filed Jun. 1, 2018, which claims priority from U.S. Provisional Patent Application Ser. No. 62/537,839 filed Jul. 27, 2017, and which is also a continuation-in-part of U.S. patent application Ser. No. 15/853,674, filed Dec. 22, 2017, now U.S. Pat. No. 10,019,597, issued Jul. 10, 2018, which claims priority from U.S. Provisional Patent Application Ser. No. 62/541,613, filed Aug. 4, 2017, and which is also a continuation-in-part of U.S. patent application Ser. No. 15/619,455, filed Jun. 10, 2017, now U.S. Pat. No. 9,851,966, issued Dec. 26, 2017, which is a continuation-in-part of Ser. No. 15/254,901, filed Sep. 1, 2016, now U.S. Pat. No. 9,729,583, issued Aug. 8, 2017, which claims priority from: (1) U.S. Provisional Patent Application Ser. No. 62/360,123, filed Jul. 8, 2016; (2) U.S. Provisional Patent Application Ser. No. 62/353,802, filed Jun. 23, 2016; and (3) U.S. Provisional Patent Application Ser. No. 62/348,695, filed Jun. 10, 2016, the entire disclosures of which are hereby incorporated by reference in their entirety.

BACKGROUND

[0002] Over the past years, privacy and security policies, and related operations have become increasingly important. Breaches in security, leading to the unauthorized access of personal data (which may include sensitive personal data) have become more frequent among companies and other organizations of all sizes. Such personal data may include, but is not limited to, personally identifiable information (PII), which may be information that directly (or indirectly) identifies an individual or entity. Examples of PII include names, addresses, dates of birth, social security numbers, and biometric identifiers such as a person's fingerprints or picture. Other personal data may include, for example, customers' Internet browsing habits, purchase history, or even their preferences (e.g., likes and dislikes, as provided or obtained through social media).

[0003] Many organizations that obtain, use, and transfer personal data, including sensitive personal data, have begun to address these privacy and security issues. To manage personal data, many companies have attempted to implement operational policies and processes that comply with legal and industry requirements. However, there is an increasing need for improved systems and methods to manage personal data in a manner that complies with such policies.

SUMMARY

[0004] A data processing data inventory generation system, according to various embodiments, comprises: (1) one or more processors; (2) computer memory; and (3) a computer-readable medium storing computer-executable instructions. In various embodiments, the computer-executable instructions, when executed by the one or more processors, cause the one or more processors to perform operations comprising: (1) identifying a primary data asset that

collects or stores personal data of one or more data subjects; and (2) generating a data inventory for the primary data asset, the data inventory storing one or more primary data asset inventory attributes. In particular embodiments, the one or more primary data asset inventory attributes comprise: (1) a type of personal data collected or stored by the primary data asset; and (2) primary transfer data associated with the personal data and the primary data asset. In particular embodiments, the computer-executable instructions, when executed by the one or more processors, further cause the one or more processors to perform operations comprising: (1) identifying a transfer data asset based at least in part on the primary transfer data; (2) modifying the data inventory to include the transfer data asset, the transfer data asset storing one or more transfer data asset inventory attributes comprising the primary transfer data; (3) digitally storing the data inventory in the computer memory; and (4) electronically linking the primary data asset to the transfer data asset in the data inventory.

[0005] A computer-implemented data processing method of generating a data inventory for a plurality of inter-related data assets utilized in the processing of one or more pieces of personal data, according to various embodiments, comprises: (1) identifying, by one or more processors, from the plurality of inter-related data assets, a storage asset, the storage asset storing the one or more pieces of personal data collected from one or more data subjects; (2) identifying, by one or more processors, from the plurality of inter-related data assets, a collection asset that transfers the one or more pieces of personal data to the storage asset; (3) identifying, by one or more processors, from the plurality of inter-related data assets, a transfer asset to which the storage asset transfers the one or more pieces personal data; (4) digitally storing, by one or more processors, in computer memory, one or more storage asset inventory attributes comprising a type of personal data stored by the storage asset; (5) digitally storing, by one or more processors, in computer memory, one or more collection asset inventory attributes comprising the one or more pieces of personal data that the collection asset transfers to the storage asset; (6) digitally storing, by one or more processors, in computer memory, one or more transfer asset inventory attributes comprising the one or more pieces of personal data that the storage asset transfers to the transfer asset; and (7) generating the data inventory.

[0006] In particular embodiments, generating the data inventory comprises: (1) associating the storage asset with the one or more storage asset inventory attributes in computer memory; (2) associating the collection asset with the one or more collection asset inventory attributes in computer memory; (3) associating the transfer asset with the one or more transfer asset inventory attributes in computer memory; (4) electronically linking the collection asset to the storage asset in computer memory; (5) electronically linking the storage asset to the transfer asset; and (6) electronically mapping the one or more pieces of personal data to the collection asset, the storage asset, and the transfer asset.

[0007] A computer-implemented data processing method for generating a data model of personal data processing activities, according to particular embodiments, comprises: (1) generating a data model for one or more data assets used in the collection or storage of personal data; (2) digitally storing the data model in computer memory; (3) identifying a first data asset of the one or more data assets; (4) modifying the data model to include the first data asset; (5) generating

a data inventory for the first data asset in the data model; (6) associating the data inventory with the first data asset in computer memory; and (7) mapping the first data asset to at least one of the one or more data assets in the data model. In various embodiments, the data inventory comprises one or more inventory attributes such as, for example: (1) one or more processing activities associated with the first data asset; (2) transfer data associated with the first data asset; and (3) one or more pieces of personal data associated with the first asset.

BRIEF DESCRIPTION OF THE DRAWINGS

[0008] Various embodiments of a data model generation and population system are described below. In the course of this description, reference will be made to the accompanying drawings, which are not necessarily drawn to scale, and wherein:

[0009] FIG. 1 depicts a data model generation and population system according to particular embodiments.

[0010] FIG. 2 is a schematic diagram of a computer (such as the data model generation server 110, or data model population server 120) that is suitable for use in various embodiments of the data model generation and population system shown in FIG. 1.

[0011] FIG. 3 is a flowchart showing an example of steps performed by a Data Model Generation Module according to particular embodiments.

[0012] FIGS. 4-10 depict various exemplary visual representations of data models according to particular embodiments.

[0013] FIG. 11 is a flowchart showing an example of steps performed by a Data Model Population Module.

[0014] FIG. 12 is a flowchart showing an example of steps performed by a Data Population Questionnaire Generation Module.

[0015] FIG. 13 is a process flow for populating a data inventory according to a particular embodiment using one or more data mapping techniques.

[0016] FIGS. 14-25 depict exemplary screen displays and graphical user interfaces (GUIs) according to various embodiments of the system, which may display information associated with the system or enable access to, or interaction with, the system by one or more users (e.g., to configure a questionnaire for populating one or more inventory attributes for one or more data models, complete one or more assessments, etc.).

[0017] FIG. 26 is a flowchart showing an example of steps performed by an Intelligent Identity Scanning Module.

[0018] FIG. 27 is schematic diagram of network architecture for an intelligent identity scanning system 2700 according to a particular embodiment.

[0019] FIG. 28 is a schematic diagram of an asset access methodology utilized by an intelligent identity scanning system 2700 in various embodiments of the system.

[0020] FIG. 29 is a flowchart showing an example of a processes performed by a Data Subject Access Request Fulfillment Module 2100 according to various embodiments.

[0021] FIGS. 30-31 depict exemplary screen displays and graphical user interfaces (GUIs) according to various embodiments of the system, which may display information associated with the system or enable access to, or interaction

with, the system by one or more users (e.g., for the purpose of submitting a data subject access request or other suitable request).

[0022] FIGS. 32-35 depict exemplary screen displays and graphical user interfaces (GUIs) according to various embodiments of the system, which may display information associated with the system or enable access to, or interaction with, the system by one or more users (e.g., for the purpose of flagging one or more risks associated with one or more particular questionnaire questions).

DETAILED DESCRIPTION

[0023] Various embodiments now will be described more fully hereinafter with reference to the accompanying drawings. It should be understood that the invention may be embodied in many different forms and should not be construed as limited to the embodiments set forth herein. Rather, these embodiments are provided so that this disclosure will be thorough and complete, and will fully convey the scope of the invention to those skilled in the art. Like numbers refer to like elements throughout.

[0024] Overview

[0025] A data model generation and population system, according to particular embodiments, is configured to generate a data model (e.g., one or more data models) that maps one or more relationships between and/or among a plurality of data assets utilized by a corporation or other entity (e.g., individual, organization, etc.) in the context, for example, of one or more business processes. In particular embodiments, each of the plurality of data assets (e.g., data systems) may include, for example, any entity that collects, processes, contains, and/or transfers data (e.g., such as a software application, “internet of things” computerized device, database, website, data-center, server, etc.). For example, a first data asset may include any software or device (e.g., server or servers) utilized by a particular entity for such data collection, processing, transfer, storage, etc.

[0026] As shown in FIGS. 4 and 5, in various embodiments, the data model may store the following information: (1) the organization that owns and/or uses a particular data asset (a primary data asset, which is shown in the center of the data model in FIG. 4); (2) one or more departments within the organization that are responsible for the data asset; (3) one or more software applications that collect data (e.g., personal data) for storage in and/or use by the data asset (e.g., or one or more other suitable collection assets from which the personal data that is collected, processed, stored, etc. by the primary data asset is sourced); (4) one or more particular data subjects (or categories of data subjects) that information is collected from for use by the data asset; (5) one or more particular types of data that are collected by each of the particular applications for storage in and/or use by the data asset; (6) one or more individuals (e.g., particular individuals or types of individuals) that are permitted to access and/or use the data stored in, or used by, the data asset; (7) which particular types of data each of those individuals are allowed to access and use; and (8) one or more data assets (destination assets) that the data is transferred to for other use, and which particular data is transferred to each of those data assets. As shown in FIGS. 6 and 7, the system may also optionally store information regarding, for example, which business processes and processing activities utilize the data asset.

[0027] In particular embodiments, the data model stores this information for each of a plurality of different data assets and may include links between, for example, a portion of the model that provides information for a first particular data asset and a second portion of the model that provides information for a second particular data asset.

[0028] In various embodiments, the data model generation and population system may be implemented in the context of any suitable privacy management system that is configured to ensure compliance with one or more legal or industry standards related to the collection and/or storage of private information. In various embodiments, a particular organization, sub-group, or other entity may initiate a privacy campaign or other activity (e.g., processing activity) as part of its business activities. In such embodiments, the privacy campaign may include any undertaking by a particular organization (e.g., such as a project or other activity) that includes the collection, entry, and/or storage (e.g., in memory) of any personal data associated with one or more individuals. In particular embodiments, a privacy campaign may include any project undertaken by an organization that includes the use of personal data, or any other activity that could have an impact on the privacy of one or more individuals.

[0029] In any embodiment described herein, personal data may include, for example: (1) the name of a particular data subject (which may be a particular individual); (2) the data subject's address; (3) the data subject's telephone number; (4) the data subject's e-mail address; (5) the data subject's social security number; (6) information associated with one or more of the data subject's credit accounts (e.g., credit card numbers); (7) banking information for the data subject; (8) location data for the data subject (e.g., their present or past location); (9) internet search history for the data subject; and/or (10) any other suitable personal information, such as other personal information discussed herein. In particular embodiments, such personal data may include one or more cookies (e.g., where the individual is directly identifiable or may be identifiable based at least in part on information stored in the one or more cookies).

[0030] In particular embodiments, when generating a data model, the system may, for example: (1) identify one or more data assets associated with a particular organization; (2) generate a data inventory for each of the one or more data assets, where the data inventory comprises information such as: (a) one or more processing activities associated with each of the one or more data assets, (b) transfer data associated with each of the one or more data assets (data regarding which data is transferred to/from each of the data assets, and which data assets, or individuals, the data is received from and/or transferred to, (c) personal data associated with each of the one or more data assets (e.g., particular types of data collected, stored, processed, etc. by the one or more data assets), and/or (d) any other suitable information; and (3) populate the data model using one or more suitable techniques.

[0031] In particular embodiments, the one or more techniques for populating the data model may include, for example: (1) obtaining information for the data model by using one or more questionnaires associated with a particular privacy campaign, processing activity, etc.; (2) using one or more intelligent identity scanning techniques discussed herein to identify personal data stored by the system and map such data to a suitable data model, data asset within a

data model, etc.; (3) obtaining information for the data model from a third-party application (or other application) using one or more application programming interfaces (API); and/or (4) using any other suitable technique.

[0032] In particular embodiments, the system is configured to generate and populate a data model substantially on the fly (e.g., as the system receives new data associated with particular processing activities). In still other embodiments, the system is configured to generate and populate a data model based at least in part on existing information stored by the system (e.g., in one or more data assets), for example, using one or more suitable scanning techniques described herein.

[0033] As may be understood in light of this disclosure, a particular organization may undertake a plurality of different privacy campaigns, processing activities, etc. that involve the collection and storage of personal data. In some embodiments, each of the plurality of different processing activities may collect redundant data (e.g., may collect the same personal data for a particular individual more than once), and may store data and/or redundant data in one or more particular locations (e.g., on one or more different servers, in one or more different databases, etc.). In this way, a particular organization may store personal data in a plurality of different locations which may include one or more known and/or unknown locations. By generating and populating a data model of one or more data assets that are involved in the collection, storage and processing of such personal data, the system may be configured to create a data model that facilitates a straightforward retrieval of information stored by the organization as desired. For example, in various embodiments, the system may be configured to use a data model in substantially automatically responding to one or more data access requests by an individual (e.g., or other organization). In still other embodiments, such data model generation and population may improve the functionality of an entity's computing systems by enabling a more streamlined retrieval of data from the system and eliminating redundant storage of identical data. Various embodiments of a system for generating and populating a data model are described more fully below.

[0034] Exemplary Technical Platforms

[0035] As will be appreciated by one skilled in the relevant field, the present invention may be, for example, embodied as a computer system, a method, or a computer program product. Accordingly, various embodiments may take the form of an entirely hardware embodiment, an entirely software embodiment, or an embodiment combining software and hardware aspects. Furthermore, particular embodiments may take the form of a computer program product stored on a computer-readable storage medium having computer-readable instructions (e.g., software) embodied in the storage medium. Various embodiments may take the form of web-implemented computer software. Any suitable computer-readable storage medium may be utilized including, for example, hard disks, compact disks, DVDs, optical storage devices, and/or magnetic storage devices.

[0036] Various embodiments are described below with reference to block diagrams and flowchart illustrations of methods, apparatuses (e.g., systems), and computer program products. It should be understood that each block of the block diagrams and flowchart illustrations, and combinations of blocks in the block diagrams and flowchart illustrations, respectively, can be implemented by a computer

executing computer program instructions. These computer program instructions may be loaded onto a general purpose computer, special purpose computer, or other programmable data processing apparatus to produce a machine, such that the instructions which execute on the computer or other programmable data processing apparatus to create means for implementing the functions specified in the flowchart block or blocks.

[0037] These computer program instructions may also be stored in a computer-readable memory that can direct a computer or other programmable data processing apparatus to function in a particular manner such that the instructions stored in the computer-readable memory produce an article of manufacture that is configured for implementing the function specified in the flowchart block or blocks. The computer program instructions may also be loaded onto a computer or other programmable data processing apparatus to cause a series of operational steps to be performed on the computer or other programmable apparatus to produce a computer implemented process such that the instructions that execute on the computer or other programmable apparatus provide steps for implementing the functions specified in the flowchart block or blocks.

[0038] Accordingly, blocks of the block diagrams and flowchart illustrations support combinations of mechanisms for performing the specified functions, combinations of steps for performing the specified functions, and program instructions for performing the specified functions. It should also be understood that each block of the block diagrams and flowchart illustrations, and combinations of blocks in the block diagrams and flowchart illustrations, can be implemented by special purpose hardware-based computer systems that perform the specified functions or steps, or combinations of special purpose hardware and other hardware executing appropriate computer instructions.

[0039] Example System Architecture

[0040] FIG. 1 is a block diagram of a Data Model Generation and Population System 100 according to a particular embodiment. In various embodiments, the Data Model Generation and Population System 100 is part of a privacy compliance system (also referred to as a privacy management system), or other system, which may, for example, be associated with a particular organization and be configured to aid in compliance with one or more legal or industry regulations related to the collection and storage of personal data. In some embodiments, the Data Model Generation and Population System 100 is configured to: (1) generate a data model based on one or more identified data assets, where the data model includes a data inventory associated with each of the one or more identified data assets; (2) identify populated and unpopulated aspects of each data inventory; and (3) populate the unpopulated aspects of each data inventory using one or more techniques such as intelligent identity scanning, questionnaire response mapping, APIs, etc.

[0041] As may be understood from FIG. 1, the Data Model Generation and Population System 100 includes one or more computer networks 115, a Data Model Generation Server 110, a Data Model Population Server 120, an Intelligent Identity Scanning Server 130, One or More Databases 140 or other data structures, one or more remote computing devices 150 (e.g., a desktop computer, laptop computer, tablet computer, smartphone, etc.), and One or More Third Party Servers 160. In particular embodiments, the one or more computer networks 115 facilitate communication

between the Data Model Generation Server 110, Data Model Population Server 120, Intelligent Identity Scanning Server 130, One or More Databases 140, one or more remote computing devices 150 (e.g., a desktop computer, laptop computer, tablet computer, smartphone, etc.), and One or More Third Party Servers 160. Although in the embodiment shown in FIG. 1, the Data Model Generation Server 110, Data Model Population Server 120, Intelligent Identity Scanning Server 130, One or More Databases 140, one or more remote computing devices 150 (e.g., a desktop computer, laptop computer, tablet computer, smartphone, etc.), and One or More Third Party Servers 160 are shown as separate servers, it should be understood that in other embodiments, one or more of these servers and/or computing devices may comprise a single server, a plurality of servers, one or more cloud-based servers, or any other suitable configuration.

[0042] The one or more computer networks 115 may include any of a variety of types of wired or wireless computer networks such as the Internet, a private intranet, a public switch telephone network (PSTN), or any other type of network. The communication link between The Intelligent Identity Scanning Server 130 and the One or More Third Party Servers 160 may be, for example, implemented via a Local Area Network (LAN) or via the Internet. In other embodiments, the One or More Databases 140 may be stored either fully or partially on any suitable server or combination of servers described herein.

[0043] FIG. 2 illustrates a diagrammatic representation of a computer 200 that can be used within the Data Model Generation and Population System 100, for example, as a client computer (e.g., one or more remote computing devices 130 shown in FIG. 1), or as a server computer (e.g., Data Model Generation Server 110 shown in FIG. 1). In particular embodiments, the computer 200 may be suitable for use as a computer within the context of the Data Model Generation and Population System 100 that is configured to generate a data model and map one or more relationships between one or more pieces of data that make up the model.

[0044] In particular embodiments, the computer 200 may be connected (e.g., networked) to other computers in a LAN, an intranet, an extranet, and/or the Internet. As noted above, the computer 200 may operate in the capacity of a server or a client computer in a client-server network environment, or as a peer computer in a peer-to-peer (or distributed) network environment. The Computer 200 may be a personal computer (PC), a tablet PC, a set-top box (STB), a Personal Digital Assistant (PDA), a cellular telephone, a web appliance, a server, a network router, a switch or bridge, or any other computer capable of executing a set of instructions (sequential or otherwise) that specify actions to be taken by that computer. Further, while only a single computer is illustrated, the term “computer” shall also be taken to include any collection of computers that individually or jointly execute a set (or multiple sets) of instructions to perform any one or more of the methodologies discussed herein.

[0045] An exemplary computer 200 includes a processing device 202, a main memory 204 (e.g., read-only memory (ROM), flash memory, dynamic random access memory (DRAM) such as synchronous DRAM (SDRAM) or Rambus DRAM (RDRAM), etc.), static memory 206 (e.g., flash

memory, static random access memory (SRAM), etc.), and a data storage device **218**, which communicate with each other via a bus **232**.

[0046] The processing device **202** represents one or more general-purpose processing devices such as a microprocessor, a central processing unit, or the like. More particularly, the processing device **202** may be a complex instruction set computing (CISC) microprocessor, reduced instruction set computing (RISC) microprocessor, very long instruction word (VLIW) microprocessor, or processor implementing other instruction sets, or processors implementing a combination of instruction sets. The processing device **202** may also be one or more special-purpose processing devices such as an application specific integrated circuit (ASIC), a field programmable gate array (FPGA), a digital signal processor (DSP), network processor, or the like. The processing device **202** may be configured to execute processing logic **226** for performing various operations and steps discussed herein.

[0047] The computer **120** may further include a network interface device **208**. The computer **200** also may include a video display unit **210** (e.g., a liquid crystal display (LCD) or a cathode ray tube (CRT)), an alphanumeric input device **212** (e.g., a keyboard), a cursor control device **214** (e.g., a mouse), and a signal generation device **216** (e.g., a speaker).

[0048] The data storage device **218** may include a non-transitory computer-accessible storage medium **230** (also known as a non-transitory computer-readable storage medium or a non-transitory computer-readable medium) on which is stored one or more sets of instructions (e.g., software instructions **222**) embodying any one or more of the methodologies or functions described herein. The software instructions **222** may also reside, completely or at least partially, within main memory **204** and/or within processing device **202** during execution thereof by computer **200**—main memory **204** and processing device **202** also constituting computer-accessible storage media. The software instructions **222** may further be transmitted or received over a network **115** via network interface device **208**.

[0049] While the computer-accessible storage medium **230** is shown in an exemplary embodiment to be a single medium, the term “computer-accessible storage medium” should be understood to include a single medium or multiple media (e.g., a centralized or distributed database, and/or associated caches and servers) that store the one or more sets of instructions. The term “computer-accessible storage medium” should also be understood to include any medium that is capable of storing, encoding or carrying a set of instructions for execution by the computer and that cause the computer to perform any one or more of the methodologies of the present invention. The term “computer-accessible storage medium” should accordingly be understood to include, but not be limited to, solid-state memories, optical and magnetic media, etc.

[0050] Exemplary System Platform

[0051] Various embodiments of a Data Model Generation and Population System **100** may be implemented in the context of any suitable system (e.g., a privacy compliance system). For example, the Data Model Generation and Population System **100** may be implemented to analyze a particular company or other organization’s data assets to generate a data model for one or more processing activities, privacy campaigns, etc. undertaken by the organization. In particular embodiments, the system may implement one or more modules in order to at least partially ensure compli-

ance with one or more regulations (e.g., legal requirements) related to the collection and/or storage of personal data. Various aspects of the system’s functionality may be executed by certain system modules, including a Data Model Generation Module **300**, Data Model Population Module **1100**, Data Population Questionnaire Generation Module **1200**, Intelligent Identity Scanning Module **2600**, and Data Subject Access Request Fulfillment Module **2900**. These modules are discussed in greater detail below.

[0052] Although these modules are presented as a series of steps, it should be understood in light of this disclosure that various embodiments of the Data Model Generation Module **300**, Data Model Population Module **1100**, Data Population Questionnaire Generation Module **1200**, Intelligent Identity Scanning Module **2600**, and Data Subject Access Request Fulfillment Module **2900** described herein may perform the steps described below in an order other than in which they are presented. In still other embodiments, the Data Model Generation Module **300**, Data Model Population Module **1100**, Data Population Questionnaire Generation Module **1200**, Intelligent Identity Scanning Module **2600**, and Data Subject Access Request Fulfillment Module **2900** may omit certain steps described below. In various other embodiments, the Data Model Generation Module **300**, Data Model Population Module **1100**, Data Population Questionnaire Generation Module **1200**, Intelligent Identity Scanning Module **2600**, and Data Subject Access Request Fulfillment Module **2900** may perform steps in addition to those described (e.g., such as one or more steps described with respect to one or more other modules, etc.).

[0053] Data Model Generation Module

[0054] In particular embodiments, a Data Model Generation Module **300** is configured to: (1) generate a data model (e.g., a data inventory) for one or more data assets utilized by a particular organization; (2) generate a respective data inventory for each of the one or more data assets; and (3) map one or more relationships between one or more aspects of the data inventory, the one or more data assets, etc. within the data model. In particular embodiments, a data asset (e.g., data system, software application, etc.) may include, for example, any entity that collects, processes, contains, and/or transfers data (e.g., such as a software application, “internet of things” computerized device, database, website, data-center, server, etc.). For example, a first data asset may include any software or device (e.g., server or servers) utilized by a particular entity for such data collection, processing, transfer, storage, etc.

[0055] In particular embodiments, a particular data asset, or collection of data assets, may be utilized as part of a particular data processing activity (e.g., direct deposit generation for payroll purposes). In various embodiments, a data model generation system may, on behalf of a particular organization (e.g., entity), generate a data model that encompasses a plurality of processing activities. In other embodiments, the system may be configured to generate a discrete data model for each of a plurality of processing activities undertaken by an organization.

[0056] Turning to FIG. 3, in particular embodiments, when executing the Data Model Generation Module **300**, the system begins, at Step **310**, by generating a data model for one or more data assets and digitally storing the data model in computer memory. The system may, for example, store the data model in the One or More Databases **140** described above (or any other suitable data structure). In various

embodiments, generating the data model comprises generating a data structure that comprises information regarding one or more data assets, attributes and other elements that make up the data model. As may be understood in light of this disclosure, the one or more data assets may include any data assets that may be related to one another. In particular embodiments, the one or more data assets may be related by virtue of being associated with a particular entity (e.g., organization). For example, the one or more data assets may include one or more computer servers owned, operated, or utilized by the entity that at least temporarily store data sent, received, or otherwise processed by the particular entity.

[0057] In still other embodiments, the one or more data assets may comprise one or more third party assets which may, for example, send, receive and/or process personal data on behalf of the particular entity. These one or more data assets may include, for example, one or more software applications (e.g., such as Expensify to collect expense information, QuickBooks to maintain and store salary information, etc.).

[0058] Continuing to step 320, the system is configured to identify a first data asset of the one or more data assets. In particular embodiments, the first data asset may include, for example, any entity (e.g., system) that collects, processes, contains, and/or transfers data (e.g., such as a software application, “internet of things” computerized device, database, website, data-center, server, etc.). For example, the first data asset may include any software or device utilized by a particular organization for such data collection, processing, transfer, etc. In various embodiments, the first data asset may be associated with a particular processing activity (e.g., the first data asset may make up at least a part of a data flow that relates to the collection, storage, transfer, access, use, etc. of a particular piece of data (e.g., personal data)). Information regarding the first data asset may clarify, for example, one or more relationships between and/or among one or more other data assets within a particular organization. In a particular example, the first data asset may include a software application provided by a third party (e.g., a third party vendor) with which the particular entity interfaces for the purpose of collecting, storing, or otherwise processing personal data (e.g., personal data regarding customers, employees, potential customers, etc.).

[0059] In particular embodiments, the first data asset is a storage asset that may, for example: (1) receive one or more pieces of personal data form one or more collection assets; (2) transfer one or more pieces of personal data to one or more transfer assets; and/or (3) provide access to one or more pieces of personal data to one or more authorized individuals (e.g., one or more employees, managers, or other authorized individuals within a particular entity or organization). In a particular embodiment, the first data asset is a primary data asset associated with a particular processing activity around which the system is configured to build a data model associated with the particular processing activity.

[0060] In particular embodiments, the system is configured to identify the first data asset by scanning a plurality of computer systems associated with a particular entity (e.g., owned, operated, utilized, etc. by the particular entity). In various embodiments, the system is configured to identify the first data asset from a plurality of data assets identified in response to completion, by one or more users, of one or more questionnaires.

[0061] Advancing to Step 330, the system generates a first data inventory of the first data asset. The data inventory may comprise, for example, one or more inventory attributes associated with the first data asset such as, for example: (1) one or more processing activities associated with the first data asset; (2) transfer data associated with the first data asset (e.g., how and where the data is being transferred to and/or from); (3) personal data associated with the first data asset (e.g., what type of personal data is collected and/or stored by the first data asset; how, and from where, the data is collected, etc.); (4) storage data associated with the personal data (e.g., whether the data is being stored, protected and deleted); and (5) any other suitable attribute related to the collection, use, and transfer of personal data. In other embodiments, the one or more inventory attributes may comprise one or more other pieces of information such as, for example: (1) the type of data being stored by the first data asset; (2) an amount of data stored by the first data asset; (3) whether the data is encrypted; (4) a location of the stored data (e.g., a physical location of one or more computer servers on which the data is stored); etc. In particular other embodiments, the one or more inventory attributes may comprise one or more pieces of information technology data related to the first data asset (e.g., such as one or more pieces of network and/or infrastructure information, IP address, MAC address, etc.).

[0062] In various embodiments, the system may generate the data inventory based at least in part on the type of first data asset. For example, particular types of data assets may have particular default inventory attributes. In such embodiments, the system is configured to generate the data inventory for the first data asset, which may, for example, include one or more placeholder fields to be populated by the system at a later time. In this way, the system may, for example, identify particular inventory attributes for a particular data asset for which information and/or population of data is required as the system builds the data model.

[0063] As may be understood in light of this disclosure, the system may, when generating the data inventory for the first data asset, generate one or more placeholder fields that may include, for example: (1) the organization (e.g., entity) that owns and/or uses the first data asset (a primary data asset, which is shown in the center of the data model in FIG. 4); (2) one or more departments within the organization that are responsible for the first data asset; (3) one or more software applications that collect data (e.g., personal data) for storage in and/or use by the first data asset (e.g., or one or more other suitable collection assets from which the personal data that is collected, processed, stored, etc. by the first data asset is sourced); (4) one or more particular data subjects (or categories of data subjects) that information is collected from for use by the first data asset; (5) one or more particular types of data that are collected by each of the particular applications for storage in and/or use by the first data asset; (6) one or more individuals (e.g., particular individuals or types of individuals) that are permitted to access and/or use the data stored in, or used by, the first data asset; (7) which particular types of data each of those individuals are allowed to access and use; and (8) one or more data assets (destination assets) that the data is transferred to from the first data asset, and which particular data is transferred to each of those data assets.

[0064] As may be understood in light of this disclosure, the system may be configured to generate the one or more

placeholder fields based at least in part on, for example: (1) the type of the first data asset; (2) one or more third party vendors utilized by the particular organization; (3) a number of collection or storage assets typically associated with the type of the first data asset; and/or (4) any other suitable factor related to the first data asset, its one or more inventory attributes, etc. In other embodiments, the system may substantially automatically generate the one or more placeholders based at least in part on a hierarchy and/or organization of the entity for which the data model is being built. For example, a particular entity may have a marketing division, legal department, human resources department, engineering division, or other suitable combination of departments that make up an overall organization. Other particular entities may have further subdivisions within the organization. When generating the data inventory for the first data asset, the system may identify that the first data asset will have both an associated organization and subdivision within the organization to which it is assigned. In this example, the system may be configured to store an indication in computer memory that the first data asset is associated with an organization and a department within the organization.

[0065] Next, at Step 340, the system modifies the data model to include the first data inventory and electronically links the first data inventory to the first data asset within the data model. In various embodiments, modifying the data model may include configuring the data model to store the data inventory in computer memory, and to digitally associate the data inventory with the first data asset in memory.

[0066] FIGS. 4 and 5 show a data model according to a particular embodiment. As shown in these figures, the data model may store the following information for the first data asset: (1) the organization that owns and/or uses the first data asset; (2) one or more departments within the organization that are responsible for the first data asset; (3) one or more applications that collect data (e.g., personal data) for storage in and/or use by the first data asset; (4) one or more particular data subjects that information is collected from for use by the first data asset; (5) one or more collection assets from which the first asset receives data (e.g., personal data); (6) one or more particular types of data that are collected by each of the particular applications (e.g., collection assets) for storage in and/or use by the first data asset; (7) one or more individuals (e.g., particular individuals, types of individuals, or other parties) that are permitted to access and/or use the data stored in or used by the first data asset; (8) which particular types of data each of those individuals are allowed to access and use; and (9) one or more data assets (destination assets) the data is transferred to for other use, and which particular data is transferred to each of those data assets. As shown in FIGS. 6 and 7, the system may also optionally store information regarding, for example, which business processes and processing activities utilize the first data asset.

[0067] As noted above, in particular embodiments, the data model stores this information for each of a plurality of different data assets and may include one or more links between, for example, a portion of the model that provides information for a first particular data asset and a second portion of the model that provides information for a second particular data asset.

[0068] Advancing to Step 350, the system next identifies a second data asset from the one or more data assets. In various embodiments, the second data asset may include one

of the one or more inventory attributes associated with the first data asset (e.g., the second data asset may include a collection asset associated with the first data asset, a destination asset or transfer asset associated with the first data asset, etc.). In various embodiments, as may be understood in light of the exemplary data models described below, a second data asset may be a primary data asset for a second processing activity, while the first data asset is the primary data asset for a first processing activity. In such embodiments, the second data asset may be a destination asset for the first data asset as part of the first processing activity. The second data asset may then be associated with one or more second destination assets to which the second data asset transfers data. In this way, particular data assets that make up the data model may define one or more connections that the data model is configured to map and store in memory.

[0069] Returning to Step 360, the system is configured to identify one or more attributes associated with the second data asset, modify the data model to include the one or more attributes, and map the one or more attributes of the second data asset within the data model. The system may, for example, generate a second data inventory for the second data asset that comprises any suitable attribute described with respect to the first data asset above. The system may then modify the data model to include the one or more attributes and store the modified data model in memory. The system may further, in various embodiments, associate the first and second data assets in memory as part of the data model. In such embodiments, the system may be configured to electronically link the first data asset with the second data asset. In various embodiments, such association may indicate a relationship between the first and second data assets in the context of the overall data model (e.g., because the first data asset may serve as a collection asset for the second data asset, etc.).

[0070] Next, at Step 370, the system may be further configured to generate a visual representation of the data model. In particular embodiments, the visual representation of the data model comprises a data map. The visual representation may, for example, include the one or more data assets, one or more connections between the one or more data assets, the one or more inventory attributes, etc.

[0071] In particular embodiments, generating the visual representation (e.g., visual data map) of a particular data model (e.g., data inventory) may include, for example, generating a visual representation that includes: (1) a visual indication of a first data asset (e.g., a storage asset), a second data asset (e.g., a collection asset), and a third data asset (e.g., a transfer asset); (2) a visual indication of a flow of data (e.g., personal data) from the second data asset to the first data asset (e.g., from the collection asset to the storage asset); (3) a visual indication of a flow of data (e.g., personal data) from the first data asset to the third data asset (e.g., from the storage asset to the transfer asset); (4) one or more visual indications of a risk level associated with the transfer of personal data; and/or (5) any other suitable information related to the one or more data assets, the transfer of data between/among the one or more data assets, access to data stored or collected by the one or more data assets, etc.

[0072] In particular embodiments, the visual indication of a particular asset may comprise a box, symbol, shape, or other suitable visual indicator. In particular embodiments, the visual indication may comprise one or more labels (e.g., a name of each particular data asset, a type of the asset, etc.).

In still other embodiments, the visual indication of a flow of data may comprise one or more arrows. In particular embodiments, the visual representation of the data model may comprise a data flow, flowchart, or other suitable visual representation.

[0073] In various embodiments, the system is configured to display (e.g., to a user) the generated visual representation of the data model on a suitable display device.

[0074] Exemplary Data Models and Visual Representations of Data Models (e.g., Data Maps)

[0075] FIGS. 4-10 depict exemplary data models according to various embodiments of the system described herein. FIG. 4, for example, depicts an exemplary data model that does not include a particular processing activity (e.g., that is not associated with a particular processing activity). As may be understood from the data model shown in this figure, a particular data asset (e.g., a primary data asset) may be associated with a particular company (e.g., organization), or organization within a particular company, sub-organization of a particular organization, etc. In still other embodiments, the particular asset may be associated with one or more collection assets (e.g., one or more data subjects from whom personal data is collected for storage by the particular asset), one or more parties that have access to data stored by the particular asset, one or more transfer assets (e.g., one or more assets to which data stored by the particular asset may be transferred), etc.

[0076] As may be understood from FIG. 4, a particular data model for a particular asset may include a plurality of data elements. When generating the data model for the particular asset, a system may be configured to substantially automatically identify one or more types of data elements for inclusion in the data model, and automatically generate a data model that includes those identified data elements (e.g., even if one or more of those data elements must remain unpopulated because the system may not initially have access to a value for the particular data element). In such cases, the system may be configured to store a placeholder for a particular data element until the system is able to populate the particular data element with accurate data.

[0077] As may be further understood from FIG. 4, the data model shown in FIG. 4 may represent a portion of an overall data model. For example, in the embodiment shown in this figure, the transfer asset depicted may serve as a storage asset for another portion of the data model. In such embodiments, the transfer asset may be associated with a respective one or more of the types of data elements described above. In this way, the system may generate a data model that may build upon itself to comprise a plurality of layers as the system adds one or more new data assets, attributes, etc.

[0078] As may be further understood from FIG. 4, a particular data model may indicate one or more parties that have access to and/or use of the primary asset (e.g., storage asset). In such embodiments, the system may be configured to enable the one or more parties to access one or more pieces of data (e.g., personal data) stored by the storage asset.

[0079] As shown in FIG. 4, the data model may further comprise one or more collection assets (e.g., one or more data assets or individuals from which the storage asset receives data such as personal data). In the exemplary data model (e.g., visual data map) shown in this figure, the collection assets comprise a data subject (e.g., an individual that may provide data to the system for storage in the storage

asset) and a collection asset (e.g., which may transfer one or more pieces of data that the collection asset has collected to the storage asset).

[0080] FIG. 5 depicts a portion of an exemplary data model that is populated for the primary data asset Gusto. Gusto is a software application that, in the example shown in FIG. 5, may serve as a human resources service that contains financial, expense, review, time and attendance, background, and salary information for one or more employees of a particular organization (e.g., GeneriTech). In the example of FIG. 5, the primary asset (e.g., Gusto) may be utilized by the HR (e.g., Human Resources) department of the particular organization (e.g., GeneriTech). Furthermore, the primary asset, Gusto, may collect financial information from one or more data subjects (e.g., employees of the particular organization), receive expense information transferred from Expensify (e.g., expensing software), and receive time and attendance data transferred from Kronos (e.g., timekeeping software). In the example shown in FIG. 5, access to the information collected and/or stored by Gusto may include, for example: (1) an ability to view and administer salary and background information by HR employees, and (2) an ability to view and administer employee review information by one or more service managers. In the example shown in this figure, personal and other data collected and stored by Gusto (e.g., salary information, etc.) may be transferred to a company banking system, to QuickBooks, and/or to an HR file cabinet.

[0081] As may be understood from the example shown in FIG. 5, the system may be configured to generate a data model based around Gusto that illustrates a flow of personal data utilized by Gusto. The data model in this example illustrates, for example, a source of personal data collected, stored and/or processed by Gusto, a destination of such data, an indication of who has access to such data within Gusto, and an organization and department responsible for the information collected by Gusto. In particular embodiments, the data model and accompanying visual representation (e.g., data map) generated by the system as described in any embodiment herein may be utilized in the context of compliance with one or more record keeping requirements related to the collection, storage, and processing of personal data.

[0082] FIGS. 6 and 7 depict an exemplary data model and related example that is similar, in some respects, to the data model and example of FIGS. 4 and 5. In the example shown in FIGS. 6 and 7, the exemplary data model and related example include a specific business process and processing activity that is associated with the primary asset (Gusto). In this example, the business process is compensation and the specific processing activity is direct deposit generation in Gusto. As may be understood from this figure, the collection and transfer of data related to the storage asset of Gusto is based on a need to generate direct deposits through Gusto in order to compensate employees. Gusto generates the information needed to conduct a direct deposit (e.g., financial and salary information) and then transmits this information to: (1) a company bank system for execution of the direct deposit; (2) Quickbooks for use in documenting the direct deposit payment; and (3) HR File cabinet for use in documenting the salary info and other financial information.

[0083] As may be understood in light of this disclosure, when generating such a data model, particular pieces of data (e.g., data attributes, data elements) may not be readily

available to the system. In such embodiment, the system is configured to identify a particular type of data, create a placeholder for such data in memory, and seek out (e.g., scan for and populate) an appropriate piece of data to further populate the data model. For example, in particular embodiments, the system may identify Gusto as a primary asset and recognize that Gusto stores expense information. The system may then be configured to identify a source of the expense information (e.g., Expensify).

[0084] FIG. 8 depicts an exemplary screen display 800 that illustrates a visual representation (e.g., visual data map) of a data model (e.g., a data inventory). In the example shown in FIG. 8, the data map provides a visual indication of a flow of data collected from particular data subjects (e.g., employees 801). As may be understood from this figure, the data map illustrates that three separate data assets receive data (e.g., which may include personal data) directly from the employees 801. In this example, these three data assets include Kronos 803 (e.g., a human resources software application), Workday 805 (e.g., a human resources software application), and ADP 807 (e.g., a human resources software application and payment processor). As shown in FIG. 8, the transfer of data from the employees 801 to these assets is indicated by respective arrows.

[0085] As further illustrated in FIG. 8, the data map indicates a transfer of data from Workday 805 to ADP 807 as well as to a Recovery Datacenter 809 and a London HR File Center 811. As may be understood in light of this disclosure, the Recovery Datacenter 809 and London HR File Center 811 may comprise additional data assets in the context of the data model illustrated by the data map shown in FIG. 8. The Recover Datacenter 809 may include, for example, one or more computer servers (e.g., backup servers). The London HR File Center 811 may include, for example, one or more databases (e.g., such as the One or More Databases 140 shown in FIG. 1). AS shown in FIG. 8, each particular data asset depicted in the data map may be shown along with a visual indication of the type of data asset. For example, Kronos 803, Workday 805, and ADP 807 are depicted adjacent a first icon type (e.g., a computer monitor), while Recover Datacenter 809 and London HR File Center 811 are depicted adjacent a second and third icon type respectively (e.g., a server cluster and a file folder). In this way, the system may be configured to visually indicate, via the data model, particular information related to the data model in a relatively minimal manner.

[0086] FIG. 9 depicts an exemplary screen display 900 that illustrates a data map of a plurality of assets 905 in tabular form (e.g., table form). As may be understood from this figure, a table that includes one or more inventory attributes of each particular asset 905 in the table may indicate, for example: (1) a managing organization 910 of each respective asset 905; (2) a hosting location 915 of each respective asset 905 (e.g., a physical storage location of each asset 905); (3) a type 920 of each respective asset 905, if known (e.g., a database, software application, server, etc.); (4) a processing activity 925 associated with each respective asset 905; and/or (5) a status 930 of each particular data asset 905. In various embodiments, the status 930 of each particular asset 905 may indicate a status of the asset 905 in the discovery process. This may include, for example: (1) a “new” status for a particular asset that has recently been discovered as an asset that processes, stores, or collects personal data on behalf of an organization (e.g., discovered

via one or more suitable techniques described herein); (2) an “in discovery” status for a particular asset for which the system is populating or seeking to populate one or more inventory attributes, etc.

[0087] FIG. 10 depicts an exemplary data map 1000 that includes an asset map of a plurality of data assets 1005A-F, which may, for example, be utilized by a particular entity in the collection, storage, and/or processing of personal data. As may be understood in light of this disclosure, the plurality of data assets 1005A-F may have been discovered using any suitable technique described herein (e.g., one or more intelligent identity scanning techniques, one or more questionnaires, one or more application programming interfaces, etc.). In various embodiments, a data inventory for each of the plurality of data assets 1005A-F may define, for each of the plurality of data assets 1005A-F a respective inventory attribute related to a storage location of the data asset.

[0088] As may be understood from this figure, the system may be configured to generate a map that indicates a location of the plurality of data assets 1005A-F for a particular entity. In the embodiment shown in this figure, locations that contain a data asset are indicated by circular indicia that contain the number of assets present at that location. In the embodiment shown in this figure, the locations are broken down by country. In particular embodiments, the asset map may distinguish between internal assets (e.g., first party servers, etc.) and external/third party assets (e.g., third party owned servers or software applications that the entity utilizes for data storage, transfer, etc.).

[0089] In some embodiments, the system is configured to indicate, via the visual representation, whether one or more assets have an unknown location (e.g., because the data model described above may be incomplete with regard to the location). In such embodiments, the system may be configured to: (1) identify the asset with the unknown location; (2) use one or more data modeling techniques described herein to determine the location (e.g., such as pinging the asset, generating one or more questionnaires for completion by a suitable individual, etc.); and (3) update a data model associated with the asset to include the location.

[0090] Data Model Population Module

[0091] In particular embodiments, a Data Model Population Module 1100 is configured to: (1) determine one or more unpopulated inventory attributes in a data model; (2) determine one or more attribute values for the one or more unpopulated inventory attributes; and (3) modify the data model to include the one or more attribute values.

[0092] Turning to FIG. 11, in particular embodiments, when executing the Data Model Population Module 1100, the system begins, at Step 1110, by analyzing one or more data inventories for each of the one or more data assets in the data model. The system may, for example, identify one or more particular data elements (e.g., inventory attributes) that make up the one or more data inventories. The system may, in various embodiments, scan one or more data structures associated with the data model to identify the one or more data inventories. In various embodiments, the system is configured to build an inventory of existing (e.g., known) data assets and identify inventory attributes for each of the known data assets.

[0093] Continuing to Step 1120, the system is configured to determine, for each of the one or more data inventories, one or more populated inventory attributes and one or more

unpopulated inventory attributes (e.g., and/or one or more unpopulated data assets within the data model). As a particular example related to an unpopulated data asset, when generating and populating a data model, the system may determine that, for a particular asset, there is a destination asset. In various embodiments, the destination asset may be known (e.g., and already stored by the system as part of the data model). In other embodiments, the destination asset may be unknown (e.g., a data element that comprises the destination asset may comprise a placeholder or other indication in memory for the system to populate the unpopulated inventory attribute (e.g., data element).

[0094] As another particular example, a particular storage asset may be associated with a plurality of inventory assets (e.g., stored in a data inventory associated with the storage asset). In this example, the plurality of inventory assets may include an unpopulated inventory attribute related to a type of personal data stored in the storage asset. The system may, for example, determine that the type of personal data is an unpopulated inventory asset for the particular storage asset.

[0095] Returning to Step 1130, the system is configured to determine, for each of the one or more unpopulated inventory attributes, one or more attribute values. In particular embodiments, the system may determine the one or more attribute values using any suitable technique (e.g., any suitable technique for populating the data model). In particular embodiments, the one or more techniques for populating the data model may include, for example: (1) obtaining data for the data model by using one or more questionnaires associated with a particular privacy campaign, processing activity, etc.; (2) using one or more intelligent identity scanning techniques discussed herein to identify personal data stored by the system and then map such data to a suitable data model; (3) using one or more application programming interfaces (API) to obtain data for the data model from another software application; and/or (4) using any other suitable technique. Exemplary techniques for determining the one or more attribute values are described more fully below. In other embodiments, the system may be configured to use such techniques or other suitable techniques to populate one or more unpopulated data assets within the data model.

[0096] Next, at Step 1140, the system modifies the data model to include the one or more attribute values for each of the one or more unpopulated inventory attributes. The system may, for example, store the one or more attribute values in computer memory, associate the one or more attribute values with the one or more unpopulated inventory attributes, etc. In still other embodiments, the system may modify the data model to include the one or more data assets identified as filling one or more vacancies left within the data model by the unpopulated one or more data assets.

[0097] Continuing to Step 1150, the system is configured to store the modified data model in memory. In various embodiments, the system is configured to store the modified data model in the One or More Databases 140, or in any other suitable location. In particular embodiments, the system is configured to store the data model for later use by the system in the processing of one or more data subject access requests. In other embodiments, the system is configured to store the data model for use in one or more privacy impact assessments performed by the system.

[0098] Data Model Population Questionnaire Generation Module

[0099] In particular embodiments, a Data Population Questionnaire Generation Module 1200 is configured to generate a questionnaire (e.g., one or more questionnaires) comprising one or more questions associated with one or more particular unpopulated data attributes, and populate the unpopulated data attributes based at least in part on one or more responses to the questionnaire. In other embodiments, the system may be configured to populate the unpopulated data attributes based on one or more responses to existing questionnaires.

[0100] In various embodiments, the one or more questionnaires may comprise one or more processing activity questionnaires (e.g., privacy impact assessments, data privacy impact assessments, etc.) configured to elicit one or more pieces of data related to one or more undertakings by an organization related to the collection, storage, and/or processing of personal data (e.g., processing activities). In particular embodiments, the system is configured to generate the questionnaire (e.g., a questionnaire template) based at least in part on one or more processing activity attributes, data asset attributes (e.g., inventory attributes), or other suitable attributes discussed herein.

[0101] Turning to FIG. 12, in particular embodiments, when executing the Data Population Questionnaire Generation Module 1200, the system begins, at Step 1210, by identifying one or more unpopulated data attributes from a data model. The system may, for example, identify the one or more unpopulated data attributes using any suitable technique described above. In particular embodiments, the one or more unpopulated data attributes may relate to, for example, one or more processing activity or asset attributes such as: (1) one or more processing activities associated with a particular data asset; (2) transfer data associated with the particular data asset (e.g., how and where the data stored and/or collected by the particular data asset is being transferred to and/or from); (3) personal data associated with the particular data assets asset (e.g., what type of personal data is collected and/or stored by the particular data asset; how, and from where, the data is collected, etc.); (4) storage data associated with the personal data (e.g., whether the data is being stored, protected and deleted); and (5) any other suitable attribute related to the collection, use, and transfer of personal data by one or more data assets or via one or more processing activities. In other embodiments, the one or more unpopulated inventory attributes may comprise one or more other pieces of information such as, for example: (1) the type of data being stored by the particular data asset; (2) an amount of data stored by the particular data asset; (3) whether the data is encrypted by the particular data asset; (4) a location of the stored data (e.g., a physical location of one or more computer servers on which the data is stored by the particular data asset); etc.

[0102] Continuing to Step 1220, the system generates a questionnaire (e.g., a questionnaire template) comprising one or more questions associated with one or more particular unpopulated data attributes. As may be understood in light of the above, the one or more particulate unpopulated data attributes may relate to, for example, a particular processing activity or a particular data asset (e.g., a particular data asset utilized as part of a particular processing activity). In various embodiments, the one or more questionnaires comprise one or more questions associated with the unpopulated data

attribute. For example, if the data model includes an unpopulated data attribute related to a location of a server on which a particular asset stores personal data, the system may generate a questionnaire associated with a processing activity that utilizes the asset (e.g., or a questionnaire associated with the asset). The system may generate the questionnaire to include one or more questions regarding the location of the server.

[0103] Returning to Step **1230**, the system maps one or more responses to the one or more questions to the associated one or more particular unpopulated data attributes. The system may, for example, when generating the questionnaire, associate a particular question with a particular unpopulated data attribute in computer memory. In various embodiments, the questionnaire may comprise a plurality of question/answer pairings, where the answer in the question/answer pairings maps to a particular inventory attribute for a particular data asset or processing activity.

[0104] In this way, the system may, upon receiving a response to the particular question, substantially automatically populate the particular unpopulated data attribute. Accordingly, at Step **1240**, the system modifies the data model to populate the one or more responses as one or more data elements for the one or more particular unpopulated data attributes. In particular embodiments, the system is configured to modify the data model such that the one or more responses are stored in association with the particular data element (e.g., unpopulated data attribute) to which the system mapped it at Step **1230**. In various embodiments, the system is configured to store the modified data model in the One or More Databases **140**, or in any other suitable location. In particular embodiments, the system is configured to store the data model for later use by the system in the processing of one or more data subject access requests. In other embodiments, the system is configured to store the data model for use in one or more privacy impact assessments performed by the system.

[0105] Continuing to optional Step **1250**, the system may be configured to modify the questionnaire based at least in part on the one or more responses. The system may, for example, substantially dynamically add and/or remove one or more questions to/from the questionnaire based at least in part on the one or more responses (e.g., one or more response received by a user completing the questionnaire). For example, the system may, in response to the user providing a particular inventory attribute or new asset, generate additional questions that relate to that particular inventory attribute or asset. The system may, as the system adds additional questions, substantially automatically map one or more responses to one or more other inventory attributes or assets. For example, in response to the user indicating that personal data for a particular asset is stored in a particular location, the system may substantially automatically generate one or more additional questions related to, for example, an encryption level of the storage, who has access to the storage location, etc.

[0106] In still other embodiments, the system may modify the data model to include one or more additional assets, data attributes, inventory attributes, etc. in response to one or more questionnaire responses. For example, the system may modify a data inventory for a particular asset to include a storage encryption data element (which specifies whether the particular asset stores particular data in an encrypted format) in response to receiving such data from a question-

naire. Modification of a questionnaire is discussed more fully below with respect to FIG. **13**.

[0107] Data Model Population Via Questionnaire Process Flow

[0108] FIG. **13** depicts an exemplary process flow **1300** for populating a data model (e.g., modifying a data model to include a newly discovered data asset, populating one or more inventory attributes for a particular processing activity or data asset, etc.). In particular, FIG. **13** depicts one or more exemplary data relationships between one or more particular data attributes (e.g., processing activity attributes and/or asset attributes), a questionnaire template (e.g., a processing activity template and/or a data asset template), a completed questionnaire (e.g., a processing activity assessment and/or a data asset assessment), and a data inventory (e.g., a processing activity inventory and/or an asset inventory). As may be understood from this figure the system is configured to: (1) identify new data assets; (2) generate an asset inventory for identified new data assets; and (3) populate the generated asset inventories. Systems and methods for populating the generated inventories are described more fully below.

[0109] As may be understood from FIG. **13**, a system may be configured to map particular processing activity attributes **1320A** to each of: (1) a processing activity template **1330A**; and (2) a processing activity data inventory **1310A**. As may be understood in light of this disclosure, the processing activity template **1330A** may comprise a plurality of questions (e.g., as part of a questionnaire), which may, for example, be configured to elicit discovery of one or more new data assets. The plurality of questions may each correspond to one or more fields in the processing activity inventory **1310A**, which may, for example, define one or more inventory attributes of the processing activity.

[0110] In particular embodiments, the system is configured to provide a processing activity assessment **1340A** to one or more individuals for completion. As may be understood from FIG. **13**, the system is configured to launch the processing activity assessment **1340A** from the processing activity inventory **1310A** and further configured to create the processing activity assessment **1340A** from the processing activity template **1330**. The processing activity assessment **1340A** may comprise, for example, one or more questions related to the processing activity. The system may, in various embodiments, be configured to map one or more responses provided in the processing activity assessment **1340A** to one or more corresponding fields in the processing activity inventory **1310A**. The system may then be configured to modify the processing activity inventory **1310A** to include the one or more responses, and store the modified inventory in computer memory. In various embodiments, the system may be configured to approve a processing activity assessment **1340A** (e.g., receive approval of the assessment) prior to feeding the processing activity inventory attribute values into one or more fields and/or cells of the inventory.

[0111] As may be further understood from FIG. **13**, in response to creating a new asset record (e.g., which the system may create, for example, in response to a new asset discovery via the processing activity assessment **1340A** described immediately above, or in any other suitable manner), the system may generate an asset inventory **1310B** (e.g., a data asset inventory) that defines a plurality of inventory attributes for the new asset (e.g., new data asset).

[0112] As may be understood from FIG. 13, a system may be configured to map particular asset attributes 1320B to each of: (1) an asset template 1330BA; and (2) an asset inventory 1310A. As may be understood in light of this disclosure, the asset template 1330B may comprise a plurality of questions (e.g., as part of a questionnaire), which may, for example, be configured to elicit discovery of one or more processing activities associated with the asset and/or one or more inventory attributes of the asset. The plurality of questions may each correspond to one or more fields in the asset inventory 1310B, which may, for example, define one or more inventory attributes of the asset.

[0113] In particular embodiments, the system is configured to provide an asset assessment 1340B to one or more individuals for completion. As may be understood from FIG. 13, the system is configured to launch the asset assessment 1340B from the asset inventory 1310B and further configured to create the asset assessment 1340B from the asset template 1330B. The asset assessment 1340B may comprise, for example, one or more questions related to the data asset. The system may, in various embodiments, be configured to map one or more responses provided in the asset assessment 1340B to one or more corresponding fields in the asset inventory 1310B. The system may then be configured to modify the asset inventory 1310B (e.g., and/or a related processing activity inventory 1310A) to include the one or more responses, and store the modified inventory in computer memory. In various embodiments, the system may be configured to approve an asset assessment 1340B (e.g., receive approval of the assessment) prior to feeding the asset inventory attribute values into one or more fields and/or cells of the inventory.

[0114] FIG. 13 further includes a detail view 1350 of a relationship between particular data attributes 1320C with an exemplary data inventory 1310C and a questionnaire template 1330C. As may be understood from this detail view 1350, a particular attribute name may map to a particular question title in a template 1330C as well as to a field name in an exemplary data inventory 1310C. In this way, the system may be configured to populate (e.g., automatically populate) a field name for a particular inventory 1310C in response to a user providing a question title as part of a questionnaire template 1330C. Similarly, a particular attribute description may map to a particular question description in a template 1330C as well as to a tooltip on a fieldname in an exemplary data inventory 1310C. In this way, the system may be configured to provide the tooltip for a particular inventory 1310C that includes the question description provided by a user as part of a questionnaire template 1330C.

[0115] As may be further understood from the detail view 1350 of FIG. 13, a particular response type may map to a particular question type in a template 1330C as well as to a field type in an exemplary data inventory 1310C. A particular question type may include, for example, a multiple choice question (e.g., A, B, C, etc.), a freeform response, an integer value, a drop down selection, etc. A particular field type may include, for example, a memo field type, a numeric field type, an integer field type, a logical field type, or any other suitable field type. A particular data attribute may require a response type of, for example: (1) a name of an organization responsible for a data asset (e.g., a free form

response); (2) a number of days that data is stored by the data asset (e.g., an integer value); and/or (3) any other suitable response type.

[0116] In still other embodiments, the system may be configured to map a one or more attribute values to one or more answer choices in a template 1330C as well as to one or more lists and/or responses in a data inventory 1310C. The system may then be configured to populate a field in the data inventory 1310C with the one or more answer choices provided in a response to a question template 1330C with one or more attribute values.

[0117] Exemplary Questionnaire Generation and Completion User Experience

[0118] FIGS. 14-25 depict exemplary screen displays that a user may encounter when generating a questionnaire (e.g., one or more questionnaires and/or templates) for populating one or more data elements (e.g., inventory attributes) of a data model for a data asset and/or processing activity. FIG. 14, for example, depicts an exemplary asset based questionnaire template builder 1400. As may be understood from FIG. 14, the template builder may enable a user to generate an asset based questionnaire template that includes one or more sections 1420 related to the asset (e.g., asset information, security, disposal, processing activities, etc.). As may be understood in light of this disclosure, the system may be configured to substantially automatically generate an asset based questionnaire template based at least in part on the one or more unpopulated inventory attributes discussed above. The system may, for example, be configured to generate a template that is configured to populate the one or more unpopulated attributes (e.g., by eliciting responses, via a questionnaire to one or more questions that are mapped to the attributes within the data inventory).

[0119] In various embodiments, the system is configured to enable a user to modify a default template (e.g., or a system-created template) by, for example, adding additional sections, adding one or more additional questions to a particular section, etc. In various embodiments, the system may provide one or more tools for modifying the template. For example, in the embodiment shown in FIG. 14, the system may provide a user with a draft and drop question template 1410, from which the user may select a question type (e.g., textbox, multiple choice, etc.).

[0120] A template for an asset may include, for example: (1) one or more questions requesting general information about the asset; (2) one or more security-related questions about the asset; (3) one or more questions regarding how the data asset disposes of data that it uses; and/or (4) one or more questions regarding processing activities that involve the data asset. In various embodiments, each of these one or more sections may comprise one or more specific questions that may map to particular portions of a data model (e.g., a data map).

[0121] FIG. 15 depicts an exemplary screen display of a processing activity questionnaire template builder 1500. The screen display shown in FIG. 15 is similar to the template builder shown in FIG. 14 with respect to the data asset based template builder. As may be understood from FIG. 15, the template builder may enable a user to generate a processing activity based questionnaire template that includes one or more sections 1520 related to the processing activity (e.g., business process information, personal data, source, storage, destinations, access and use, etc.). As may be understood in light of this disclosure, the system may be configured to

substantially automatically generate a processing activity based questionnaire template based at least in part on the one or more unpopulated inventory attributes related to the processing activity (e.g., as discussed above). The system may, for example, be configured to generate a template that is configured to populate the one or more unpopulated attributes (e.g., by eliciting responses, via a questionnaire to one or more questions that are mapped to the attributes within the data inventory).

[0122] In various embodiments, the system is configured to enable a user to modify a default template (e.g., or a system-created template) by, for example, adding additional sections, adding one or more additional questions to a particular section, etc. In various embodiments, the system may provide one or more tools for modifying the template. For example, in the embodiment shown in FIG. 15, the system may provide a user with a draft and drop question template 1510, from which the user may select a question type (e.g., textbox, multiple choice, asset attributes, data subjects, etc.). The system may be further configured to enable a user to publish a completed template (e.g., for use in a particular assessment). In other embodiments, the system may be configured to substantially automatically publish the template.

[0123] In various embodiments, a template for a processing activity may include, for example: (1) one or more questions related to the type of business process that involves a particular data asset; (2) one or more questions regarding what type of personal data is acquired from data subjects for use by a particular data asset; (3) one or more questions related to a source of the acquired personal data; (4) one or more questions related to how and/or where the personal data will be stored and/or for how long; (5) one or more questions related to one or more other data assets that the personal data will be transferred to; and/or (6) one or more questions related to who will have the ability to access and/or use the personal data.

[0124] Continuing to FIG. 16, an exemplary screen display 1600 depicts a listing of assets 1610 for a particular entity. These may, for example, have been identified as part of the data model generation system described above. As may be understood from this figure, a user may select a drop down indicator 1615 to view more information about a particular asset. In the exemplary embodiment shown in FIG. 16, the system stores the managing organization group for the “New Asset”, but is missing some additional information (e.g., such as a description 1625 of the asset). In order to fill out the missing inventory attributes for the “New Asset”, the system, in particular embodiments, is configured to enable a user to select a Send Assessment indicia 1620 in order to transmit an assessment related to the selected asset to an individual tasked with providing one or more pieces of information related to the asset (e.g., a manager, or other individual with knowledge of the one or more inventory attributes).

[0125] In response to the user selecting the Send Assessment indicia 1620, the system may create the assessment based at least in part on a template associated with the asset, and transmit the assessment to a suitable individual for completion (e.g., and/or transmit a request to the individual to complete the assessment).

[0126] FIG. 17 depicts an exemplary assessment transmission interface 1700 via which a user can transmit one or more assessments for completion. As shown in this figure,

the user may assign a respondent, provide a deadline, indicate a reminder time, and provide one or more comments using an assessment request interface 1710. The user may then select a Send Assessment(s) indicia 1720 in order to transmit the assessment.

[0127] FIG. 18 depicts an exemplary assessment 1800 which a user may encounter in response to receiving a request to complete the assessment as described above with respect to FIGS. 16 and 17. As shown in FIG. 18, the assessment 1800 may include one or more questions that map to the one or more unpopulated attributes for the asset shown in FIG. 16. For example, the one or more questions may include a question related to a description of the asset, which may include a free form text box 1820 for providing a description of the asset. FIG. 19 depicts an exemplary screen display 1900 with the text box 1920 completed, where the description includes a value of “Value_1”. As shown in FIGS. 18 and 19, the user may have renamed “New Asset” (e.g., which may have included a default or placeholder name) shown in FIGS. 16 and 17 to “7th Asset.”

[0128] Continuing to FIG. 20, the exemplary screen display 2000 depicts the listing of assets 2010 from FIG. 16 with some additional attributes populated. For example, the Description 2025 (e.g., “Value_1”) provided in FIG. 19 has been added to the inventory. As may be understood in light of this disclosure, in response to a user providing the description via the assessment shown in FIGS. 18 and 19, the system may be configured to map the provided description to the attribute value associated with the description of the asset in the data inventory. The system may have then modified the data inventory for the asset to include the description attribute. In various embodiments, the system is configured to store the modified data inventory as part of a data model (e.g., in computer memory).

[0129] FIGS. 21-24 depict exemplary screen displays showing exemplary questions that make up part of a processing activity questionnaire (e.g., assessment). FIG. 21 depicts an exemplary interface 2100 for responding to a first question 2110 and a second question 2120. As shown in FIG. 21, the first question 2110 relates to whether the processing activity is a new or existing processing activity. The first question 2110 shown in FIG. 21 is a multiple choice question. The second question 2120 relates to whether the organization is conducting the activity on behalf of another organization. As shown in this figure, the second question 2120 includes both a multiple choice portion and a free-form response portion.

[0130] As discussed above, in various embodiments, the system may be configured to modify a questionnaire in response to (e.g., based on) one or more responses provided by a user completing the questionnaire. In particular embodiments, the system is configured to modify the questionnaire substantially on-the-fly (e.g., as the user provides each particular answer). FIG. 22 depicts an interface 2200 that includes a second question 2220 that differs from the second question 2120 shown in FIG. 21. As may be understood in light of this disclosure, in response to the user providing a response to the first question 2110 in FIG. 21 that indicates that the processing activity is a new processing activity, the system may substantially automatically modify the second question 2120 from FIG. 21 to the second question 2220 from FIG. 22 (e.g., such that the second question 2220 includes one or more follow up questions or

requests for additional information based on the response to the first question **2110** in FIG. **21**).

[0131] As shown in FIG. **22**, the second question **2220** requests a description of the activity that is being pursued. In various embodiments (e.g., such as if the user had selected that the processing activity was an existing one), the system may not modify the questionnaire to include the second question **2220** from FIG. **22**, because the system may already store information related to a description of the processing activity at issue. In various embodiments, any suitable question described herein may include a tooltip **2225** on a field name (e.g., which may provide one or more additional pieces of information to guide a user's response to the questionnaire and/or assessment).

[0132] FIGS. **23** and **24** depict additional exemplary assessment questions. The questions shown in these figures relate to, for example, particular data elements processed by various aspects of a processing activity.

[0133] FIG. **25** depicts a dashboard **2500** that includes an accounting of one or more assessments that have been completed, are in progress, or require completion by a particular organization. The dashboard **2500** shown in this figure is configured to provide information relate to the status of one or more outstanding assessments. As may be understood in light of this disclosure, because of the volume of assessment requests, it may be necessary to utilize one or more third party organizations to facilitate a timely completion of one or more assessment requests. In various embodiments, the dashboard may indicate that, based on a fact that a number of assessments are still in progress or incomplete, that a particular data model for an entity, data asset, processing activity, etc. remains incomplete. In such embodiments, an incomplete nature of a data model may raise one or more flags or indicate a risk that an entity may not be in compliance with one or more legal or industry requirements related to the collection, storage, and/or processing of personal data.

[0134] Intelligent Identity Scanning Module

[0135] Turning to FIG. **26**, in particular embodiments, the Intelligent Identity Scanning Module **2600** is configured to scan one or more data sources to identify personal data stored on one or more network devices for a particular organization, analyze the identified personal data, and classify the personal data (e.g., in a data model) based at least in part on a confidence score derived using one or more machine learning techniques. The confidence score may be and/or comprise, for example, an indication of the probability that the personal data is actually associated with a particular data subject (e.g., that there is at least an 80% confidence level that a particular phone number is associated with a particular individual.)

[0136] When executing the Intelligent Identity Scanning Module **2600**, the system begins, at Step **2610**, by connecting to one or more databases or other data structures, and scanning the one or more databases to generate a catalog of one or more individuals and one or more pieces of personal information associated with the one or more individuals. The system may, for example, be configured to connect to one or more databases associated with a particular organization (e.g., one or more databases that may serve as a storage location for any personal or other data collected, processed, etc. by the particular organization, for example, as part of a suitable processing activity. As may be understood in light of this disclosure, a particular organization may use a

plurality of one or more databases (e.g., the One or More Databases **140** shown in FIG. **1**), a plurality of servers (e.g., the One or More Third Party Servers **160** shown in FIG. **1**), or any other suitable data storage location in order to store personal data and other data collected as part of any suitable privacy campaign, privacy impact assessment, processing activity, etc.

[0137] In particular embodiments, the system is configured to scan the one or more databases by searching for particular data fields comprising one or more pieces of information that may include personal data. The system may, for example, be configured to scan and identify one of more pieces of personal data such as: (1) name; (2) address; (3) telephone number; (4) e-mail address; (5) social security number; (6) information associated with one or more credit accounts (e.g., credit card numbers); (7) banking information; (8) location data; (9) internet search history; (10) non-credit account data; and/or (11) any other suitable personal information discussed herein. In particular embodiments, the system is configured to scan for a particular type of personal data (e.g., or one or more particular types of personal data).

[0138] The system may, in various embodiments, be further configured to generate a catalog of one or more individuals that also includes one or more pieces of personal information (e.g., personal data) identified for the individuals during the scan. The system may, for example, in response to discovering one or more pieces of personal data in a particular storage location, identify one or more associations between the discovered pieces of personal data. For example, a particular database may store a plurality of individuals' names in association with their respective telephone numbers. One or more other databases may include any other suitable information.

[0139] The system may, for example, generate the catalog to include any information associated with the one or more individuals identified in the scan. The system may, for example, maintain the catalog in any suitable format (e.g., a data table, etc.).

[0140] In still other embodiments, in addition to connecting to a database, the system may be configured to: (1) access an application through one or more application programming interfaces (APIs); (2) use one or more screen scraping techniques on an end user page to identify and analyze each field on the page; and/or (3) connect to any other suitable data structure in order to generate the catalog of individuals and personal information associated with each of the individuals. In some embodiments, the system may be configured to analyze one or more access logs and applications set up through a system active directory or SSO portal for which one or more applications might contain certain data for user groups. The system may then be configured to analyze an email environment to identify one or more links to particular business applications, which may, for example, be in use by an entity and contain certain data. In still other embodiments, the system may be configured to analyze one or more system log files (Syslog) from a security environment to capture which particular applications an entity may be using in order to discover such applications.

[0141] Continuing to Step **2620**, the system is configured to scan one or more structured and/or unstructured data repositories based at least in part on the generated catalog to identify one or more attributes of data associated with the one or more individuals. The system may, for example, be

configured to utilize information discovered during the initial scan at Step 2610 to identify the one or more attributes of data associated with the one or more individuals.

[0142] For example, the catalog generated at Step 2610 may include a name, address, and phone number for a particular individual. The system may be configured, at Step 2620, to scan the one or more structured and/or unstructured data repositories to identify one or more attributes that are associated with one or more of the particular individual's name, address and/or phone number. For example, a particular data repository may store banking information (e.g., a bank account number and routing number for the bank) in association with the particular individual's address. In various embodiments, the system may be configured to identify the banking information as an attribute of data associated with the particular individual. In this way, the system may be configured to identify particular data attributes (e.g., one or more pieces of personal data) stored for a particular individual by identifying the particular data attributes using information other than the individual's name.

[0143] Returning to Step 2630, the system is configured to analyze and correlate the one or more attributes and metadata for the scanned one or more structured and/or unstructured data repositories. In particular embodiments, the system is configured to correlate the one or more attributes with metadata for the associated data repositories from which the system identified the one or more attributes. In this way, the system may be configured to store data regarding particular data repositories that store particular data attributes.

[0144] In particular embodiments, the system may be configured to cross-reference the data repositories that are discovered to store one or more attributes of personal data associated with the one or more individuals with a database of known data assets. In particular embodiments, the system is configured to analyze the data repositories to determine whether each data repository is part of an existing data model of data assets that collect, store, and/or process personal data. In response to determining that a particular data repository is not associated with an existing data model, the system may be configured to identify the data repository as a new data asset (e.g., via asset discovery), and take one or more actions (e.g., such as any suitable actions described herein) to generate and populate a data model of the newly discovered data asset. This may include, for example: (1) generating a data inventory for the new data asset; (2) populating the data inventory with any known attributes associated with the new data asset; (3) identifying one or more unpopulated (e.g., unknown) attributes of the data asset; and (4) taking any suitable action described herein to populate the unpopulated data attributes.

[0145] In particular embodiments, the system may, for example: (1) identify a source of the personal data stored in the data repository that led to the new asset discovery; (2) identify one or more relationships between the newly discovered asset and one or more known assets; and/or (3) etc.

[0146] Continuing to Step 2640, the system is configured to use one or more machine learning techniques to categorize one or more data elements from the generated catalog, analyze a flow of the data among the one or more data repositories, and/or classify the one or more data elements based on a confidence score as discussed below.

[0147] Continuing to Step 2650, the system, in various embodiments, is configured to receive input from a user confirming or denying a categorization of the one or more

data elements, and, in response, modify the confidence score. In various embodiments, the system is configured to iteratively repeat Steps 2640 and 2650. In this way, the system is configured to modify the confidence score in response to a user confirming or denying the accuracy of a categorization of the one or more data elements. For example, in particular embodiments, the system is configured to prompt a user (e.g., a system administrator, privacy officer, etc.) to confirm that a particular data element is, in fact, associated with a particular individual from the catalog. The system may, in various embodiments, be configured to prompt a user to confirm that a data element or attribute discovered during one or more of the scans above were properly categorized at Step 2640.

[0148] In particular embodiments, the system is configured to modify the confidence score based at least in part on receiving one or more confirmations that one or more particular data elements or attributes discovered in a particular location during a scan are associated with particular individuals from the catalog. As may be understood in light of this disclosure, the system may be configured to increase the confidence score in response to receiving confirmation that particular types of data elements or attributes discovered in a particular storage location are typically confirmed as being associated with particular individuals based on one or more attributes for which the system was scanning.

[0149] Exemplary Intelligent Identity Scanning Technical Platforms

[0150] FIG. 27 depicts an exemplary technical platform via which the system may perform one or more of the steps described above with respect to the Intelligent Identity Scanning Module 2600. As shown in the embodiment in this figure, an Intelligent Identity Scanning System 2600 comprises an Intelligent Identity Scanning Server 130, such as the Intelligent Identity Scanning Server 130 described above with respect to FIG. 1. The Intelligent Identity Scanning Server 130 may, for example, comprise a processing engine (e.g., one or more computer processors). In some embodiments, the Intelligent Identity Scanning Server 130 may include any suitable cloud hosted processing engine (e.g., one or more cloud-based computer servers). In particular embodiments, the Intelligent Identity Scanning Server 130 is hosted in a Microsoft Azure cloud.

[0151] In particular embodiments, the Intelligent Identity Scanning Server 130 is configured to sit outside one or more firewalls (e.g., such as the firewall 195 shown in FIG. 26). In such embodiments, the Intelligent Identity Scanning Server 130 is configured to access One or More Remote Computing Devices 150 through the Firewall 195 (e.g., one or more firewalls) via One or More Networks 115 (e.g., such as any of the One or More Networks 115 described above with respect to FIG. 1).

[0152] In particular embodiments, the One or More Remote Computing Devices 150 include one or more computing devices that make up at least a portion of one or more computer networks associated with a particular organization. In particular embodiments, the one or more computer networks associated with the particular organization comprise one or more suitable servers, one or more suitable databases, one or more privileged networks, and/or any other suitable device and/or network segment that may store and/or provide for the storage of personal data. In the embodiment shown in FIG. 27, the one or more computer networks associated with the particular organization may

comprise One or More Third Party Servers **160**, One or More Databases **140**, etc. In particular embodiments, the One or More Remote Computing Devices **150** are configured to access one or more segments of the one or more computer networks associated with the particular organization. In some embodiments, the one or more computer networks associated with the particular organization comprise One or More Privileged Networks **165**. In still other embodiments, the one or more computer networks comprise one or more network segments connected via one or more suitable routers, one or more suitable network hubs, one or more suitable network switches, etc.

[0153] As shown in FIG. **27**, various components that make up one or more parts of the one or more computer networks associated with the particular organization may store personal data (e.g., such as personal data stored on the One or More Third Party Servers **160**, the One or More Databases **140**, etc.). In various embodiments, the system is configured to perform one or more steps related to the Intelligent Identity Scanning Server **2600** in order to identify the personal data for the purpose of generating the catalog of individuals described above (e.g., and/or identify one or more data assets within the organization's network that store personal data)

[0154] As further shown in FIG. **27**, in various embodiments, the One or More Remote Computing Devices **150** may store a software application (e.g., the Intelligent Identity Scanning Module). In such embodiments, the system may be configured to provide the software application for installation on the One or More Remote Computing Devices **150**. In particular embodiments, the software application may comprise one or more virtual machines. In particular embodiments, the one or more virtual machines may be configured to perform one or more of the steps described above with respect to the Intelligent Identity Scanning Module **2600** (e.g., perform the one or more steps locally on the One or More Remote Computing Devices **150**).

[0155] In various embodiments, the one or more virtual machines may have the following specifications: (1) any suitable number of cores (e.g., 4, 6, 8, etc.); (2) any suitable amount of memory (e.g., 4 GB, 8 GB, 16 GB etc.); (3) any suitable operating system (e.g., CentOS 7.2); and/or (4) any other suitable specification. In particular embodiments, the one or more virtual machines may, for example, be used for one or more suitable purposes related to the Intelligent Identity Scanning System **2700**. These one or more suitable purposes may include, for example, running any of the one or more modules described herein, storing hashed and/or non-hashed information (e.g., personal data, personally identifiable data, catalog of individuals, etc.), storing and running one or more searching and/or scanning engines (e.g., Elasticsearch), etc.

[0156] In various embodiments, the Intelligent Identity Scanning System **2700** may be configured to distribute one or more processes that make up part of the Intelligent Identity Scanning Process (e.g., described above with respect to the Intelligent Identity Scanning Module **1800**). The one or more software applications installed on the One or More Remote Computing Devices **150** may, for example, be configured to provide access to the one or more computer networks associated with the particular organization to the Intelligent Identity Scanning Server **130**. The system may then be configured to receive, from the One or more Remote Computing Devices **150** at the Intelligent Identity Scanning

Server **130**, via the Firewall **195** and One or More Networks **115**, scanned data for analysis.

[0157] In particular embodiments, the Intelligent Identity Scanning System **2700** is configured to reduce an impact on a performance of the One or More Remote Computing Devices **150**, One or More Third Party Servers **160** and other components that make up one or more segments of the one or more computer networks associated with the particular organization. For example, in particular embodiments, the Intelligent Identity Scanning System **2700** may be configured to utilize one or more suitable bandwidth throttling techniques. In other embodiments, the Intelligent Identity Scanning System **2700** is configured to limit scanning (e.g., any of the one or more scanning steps described above with respect to the Intelligent Identity Scanning Module **2600**) and other processing steps (e.g., one or more steps that utilize one or more processing resources) to non-peak times (e.g., during the evening, overnight, on weekends and/or holidays, etc.). In other embodiments, the system is configured to limit performance of such processing steps to backup applications and data storage locations. The system may, for example, use one or more sampling techniques to decrease a number of records required to scan during the personal data discovery process.

[0158] FIG. **28** depicts an exemplary asset access methodology that the system may utilize in order to access one or more network devices that may store personal data (e.g., or other personally identifiable information). As may be understood from this figure, the system may be configured to access the one or more network devices using a locally deployed software application (e.g., such as the software application described immediately above). In various embodiments, the software application is configured to route identity scanning traffic through one or more gateways, configure one or more ports to accept one or more identity scanning connections, etc.

[0159] As may be understood from this figure, the system may be configured to utilize one or more credential management techniques to access one or more privileged network portions. The system may, in response to identifying particular assets or personally identifiable information via a scan, be configured to retrieve schema details such as, for example, an asset ID, Schema ID, connection string, credential reference URL, etc. In this way, the system may be configured to identify and store a location of any discovered assets or personal data during a scan.

[0160] Data Subject Access Request Fulfillment Module

[0161] Turning to FIG. **29**, in particular embodiments, a Data Subject Access Request Fulfillment Module **2900** is configured to receive a data subject access request, process the request, and fulfill the request based at least in part on one or more request parameters. In various embodiments, an organization, corporation, etc. may be required to provide information requested by an individual for whom the organization stores personal data within a certain time period (e.g., 30 days). As a particular example, an organization may be required to provide an individual with a listing of, for example: (1) any personal data that the organization is processing for an individual, (2) an explanation of the categories of data being processed and the purpose of such processing; and/or (3) categories of third parties to whom the data may be disclosed.

[0162] Various privacy and security policies (e.g., such as the European Union's General Data Protection Regulation,

and other such policies) may provide data subjects (e.g., individuals, organizations, or other entities) with certain rights related to the data subject's personal data that is collected, stored, or otherwise processed by an organization. These rights may include, for example: (1) a right to obtain confirmation of whether a particular organization is processing their personal data; (2) a right to obtain information about the purpose of the processing (e.g., one or more reasons for which the personal data was collected); (3) a right to obtain information about one or more categories of data being processed (e.g., what type of personal data is being collected, stored, etc.); (4) a right to obtain information about one or more categories of recipients with whom their personal data may be shared (e.g., both internally within the organization or externally); (5) a right to obtain information about a time period for which their personal data will be stored (e.g., or one or more criteria used to determine that time period); (6) a right to obtain a copy of any personal data being processed (e.g., a right to receive a copy of their personal data in a commonly used, machine-readable format); (7) a right to request erasure (e.g., the right to be forgotten), rectification (e.g., correction or deletion of inaccurate data), or restriction of processing of their personal data; and (8) any other suitable rights related to the collection, storage, and/or processing of their personal data (e.g., which may be provided by law, policy, industry or organizational practice, etc.).

[0163] As may be understood in light of this disclosure, a particular organization may undertake a plurality of different privacy campaigns, processing activities, etc. that involve the collection and storage of personal data. In some embodiments, each of the plurality of different processing activities may collect redundant data (e.g., may collect the same personal data for a particular individual more than once), and may store data and/or redundant data in one or more particular locations (e.g., on one or more different servers, in one or more different databases, etc.). In this way, a particular organization may store personal data in a plurality of different locations which may include one or more known and/or unknown locations. As such, complying with particular privacy and security policies related to personal data (e.g., such as responding to one or more requests by data subjects related to their personal data) may be particularly difficult (e.g., in terms of cost, time, etc.). In particular embodiments, a data subject access request fulfillment system may utilize one or more data model generation and population techniques (e.g., such as any suitable technique described herein) to create a centralized data map with which the system can identify personal data stored, collected, or processed for a particular data subject, a reason for the processing, and any other information related to the processing.

[0164] Turning to FIG. 21, when executing the Data Subject Access Request Module 2100, the system begins, at Step 2110, by receiving a data subject access request. In various embodiments, the system receives the request via a suitable web form. In certain embodiments, the request comprises a particular request to perform one or more actions with any personal data stored by a particular organization regarding the requestor. For example, in some embodiments, the request may include a request to view one or more pieces of personal data stored by the system regarding the requestor. In other embodiments, the request may include a request to delete one or more pieces of

personal data stored by the system regarding the requestor. In still other embodiments, the request may include a request to update one or more pieces of personal data stored by the system regarding the requestor. In still other embodiments, the request may include a request based on any suitable right afforded to a data subject, such as those discussed above.

[0165] Continuing to Step 2120, the system is configured to process the request by identifying and retrieving one or more pieces of personal data associated with the requestor that are being processed by the system. For example, in various embodiments, the system is configured to identify any personal data stored in any database, server, or other data repository associated with a particular organization. In various embodiments, the system is configured to use one or more data models, such as those described above, to identify this personal data and suitable related information (e.g., where the personal data is stored, who has access to the personal data, etc.). In various embodiments, the system is configured to use intelligent identity scanning (e.g., as described above) to identify the requestor's personal data and related information that is to be used to fulfill the request.

[0166] In still other embodiments, the system is configured to use one or more machine learning techniques to identify such personal data. For example, the system may identify particular stored personal data based on, for example, a country in which a website that the data subject request was submitted is based, or any other suitable information.

[0167] In particular embodiments, the system is configured to scan and/or search one or more existing data models (e.g., one or more current data models) in response to receiving the request in order to identify the one or more pieces of personal data associated with the requestor. The system may, for example, identify, based on one or more data inventories (e.g., one or more inventory attributes) a plurality of storage locations that store personal data associated with the requestor. In other embodiments, the system may be configured to generate a data model or perform one or more scanning techniques in response to receiving the request (e.g., in order to automatically fulfill the request).

[0168] Returning to Step 2130, the system is configured to take one or more actions based at least in part on the request. In some embodiments, the system is configured to take one or more actions for which the request was submitted (e.g., display the personal data, delete the personal data, correct the personal data, etc.). In particular embodiments, the system is configured to take the one or more actions substantially automatically. In particular embodiments, in response a data subject submitting a request to delete their personal data from an organization's systems, the system may: (1) automatically determine where the data subject's personal data is stored; and (2) in response to determining the location of the data (which may be on multiple computing systems), automatically facilitate the deletion of the data subject's personal data from the various systems (e.g., by automatically assigning a plurality of tasks to delete data across multiple business systems to effectively delete the data subject's personal data from the systems). In particular embodiments, the step of facilitating the deletion may comprise, for example: (1) overwriting the data in memory; (2) marking the data for overwrite; (2) marking the data as free (e.g., and deleting a directory entry associated with the data); and/or (3) any other suitable technique for deleting the

personal data. In particular embodiments, as part of this process, the system uses an appropriate data model (see discussion above) to efficiently determine where all of the data subject's personal data is stored.

[0169] Data Subject Access Request User Experience

[0170] FIGS. 30-31 depict exemplary screen displays that a user may view when submitting a data subject access request. As shown in FIG. 30, a website 30000 associated with a particular organization may include a user-selectable indicia 3005 for submitting a privacy-related request. A user desiring to make such a request may select the indicia 3005 in order to initiate the data subject access request process.

[0171] FIG. 31 depicts an exemplary data subject access request form in both an unfilled and filled out state. As shown in this figure, the system may prompt a user to provide information such as, for example: (1) what type of requestor the user is (e.g., employee, customer, etc.); (2) what the request involves (e.g., requesting info, opting out, deleting data, updating data, etc.); (3) first name; (4) last name; (5) email address; (6) telephone number; (7) home address; and/or (8) one or more details associated with the request.

[0172] As discussed in more detail above, a data subject may submit a subject access request, for example, to request a listing of any personal information that a particular organization is currently storing regarding the data subject, to request that the personal data be deleted, to opt out of allowing the organization to process the personal data, etc.

Alternative Embodiment

[0173] In particular embodiments, a data modeling or other system described herein may include one or more features in addition to those described. Various such alternative embodiments are described below.

[0174] Processing Activity and Data Asset Assessment Risk Flagging

[0175] In particular embodiments, the questionnaire template generation system and assessment system described herein may incorporate one or more risk flagging systems. FIGS. 32-35 depict exemplary user interfaces that include risk flagging of particular questions within a processing activity assessment. As may be understood from these figures, a user may select a flag risk indicia to provide input related to a description of risks and mitigation of a risk posed by one or more inventory attributes associated with the question. As shown in these figures, the system may be configured to substantially automatically assign a risk to a particular response to a question in a questionnaire. In various embodiments, the assigned risk is determined based at least in part on the template from which the assessment was generated.

[0176] In particular embodiments, the system may utilize the risk level assigned to particular questionnaire responses as part of a risk analysis of a particular processing activity or data asset. Various techniques for assessing the risk of various privacy campaigns are described in U.S. patent application Ser. No. 15/256,419, filed Sep. 2, 2016, entitled "Data processing systems and methods for operationalizing privacy compliance and assessing the risk of various respective privacy campaigns," which is hereby incorporated herein in its entirety.

CONCLUSION

[0177] Although embodiments above are described in reference to various privacy compliance monitoring systems, it should be understood that various aspects of the system described above may be applicable to other privacy-related systems, or to other types of systems, in general.

[0178] While this specification contains many specific embodiment details, these should not be construed as limitations on the scope of any invention or of what may be claimed, but rather as descriptions of features that may be specific to particular embodiments of particular inventions. Certain features that are described in this specification in the context of separate embodiments may also be implemented in combination in a single embodiment. Conversely, various features that are described in the context of a single embodiment may also be implemented in multiple embodiments separately or in any suitable sub-combination. Moreover, although features may be described above as acting in certain combinations and even initially claimed as such, one or more features from a claimed combination may in some cases be excised from the combination, and the claimed combination may be directed to a sub-combination or variation of a sub-combination.

[0179] Similarly, while operations are depicted in the drawings in a particular order, this should not be understood as requiring that such operations be performed in the particular order shown or in sequential order, or that all illustrated operations be performed, to achieve desirable results. In certain circumstances, multitasking and parallel processing may be advantageous. Moreover, the separation of various system components in the embodiments described above should not be understood as requiring such separation in all embodiments, and it should be understood that the described program components and systems may generally be integrated together in a single software product or packaged into multiple software products.

[0180] Many modifications and other embodiments of the invention will come to mind to one skilled in the art to which this invention pertains having the benefit of the teachings presented in the foregoing descriptions and the associated drawings. Therefore, it is to be understood that the invention is not to be limited to the specific embodiments disclosed and that modifications and other embodiments are intended to be included within the scope of the appended claims. Although specific terms are employed herein, they are used in a generic and descriptive sense only and not for the purposes of limitation.

What is claimed is:

1. A computer-implemented data processing method of feeding a data inventory with one or more data attribute values, the method comprising:

generating, by one or more processors, a data inventory for one or more data assets used in the collection or storage of personal data;

storing, by the one or more processors, the data inventory in computer memory;

modifying, by the one or more processors, the data inventory to include one or more data fields that each define a respective data inventory attribute of a plurality of data inventory attributes;

determining, by the one or more processors, which of the one or more data fields of the data inventory are unpopulated data fields;

- determining, by the one or more processors, a respective data inventory attribute value for each of the unpopulated data fields;
- in response to determining the respective data inventory attribute value for each of the unpopulated data fields, modifying each of the unpopulated data fields to include the respective data inventory attribute value; and
- storing the modified data inventory in the computer memory.
2. The computer-implemented data processing method of claim 1, further comprising:
- using an application programming interface to access a third-party information technology system;
 - receiving one or more pieces of data from the third-party information technology system; and
 - filling, by one or more processors, the unpopulated data fields based at least in part on the one or more pieces of data.
3. The computer-implemented data processing method of claim 1, wherein determining the respective data inventory attribute value for each of the unpopulated data fields comprises:
- providing a software application for installation on a computing device that is networked with one or more data repositories associated with an organization; and
 - providing a communication channel between one or more remote scanning servers and the software application, wherein:
 - the software application is configured to communicate with the one or more remote scanning servers; and
 - the software application is configured to scan the one or more data repositories to identify each respective data inventory attribute value stored in the one or more data repositories and transmit each respective data inventory attribute value to the one or more remote scanning servers via the communication channel.
4. The computer-implemented data processing method of claim 1, the method further comprising:
- scanning one or more data repositories on one or more remote computing devices to identify one or more data attributes; and
 - identifying each respective data inventory attribute value for each of the unpopulated data fields from the one or more data attributes.
5. The computer-implemented data processing method of claim 4, the method further comprising:
- analyzing the one or more data attributes and correlating metadata for the scanned one or more data repositories with particular attributes of the one or more data attributes discovered in the one or more data repositories; and
 - using one or more machine learning techniques to categorize the one or more data attributes based at least in part on a confidence score.
6. The computer-implemented data processing method of claim 5, the method further comprising:
- receiving input from a user confirming or denying a categorization of the one or more data elements; and
 - in response to receiving the input, modifying the confidence score.
7. The computer-implemented data processing method of claim 6, wherein identifying each respective data inventory attribute value for each of the unpopulated data fields from the one or more data attributes comprises identifying each respective data inventory attribute value for each of the unpopulated data fields based on the confidence score.
8. The computer-implemented data processing method of claim 1, wherein generating the data inventory for the one or more data assets used in the collection or storage of personal data comprises generating the data inventory for a plurality of inter-related data assets utilized in the processing of one or more pieces of personal data, and further comprises:
- identifying, by one or more processors, from the plurality of inter-related data assets, a storage asset, the storage asset storing the one or more pieces of personal data collected from one or more data subjects;
 - identifying, by one or more processors, from the plurality of inter-related data assets, a collection asset that transfers the one or more pieces of personal data to the storage asset;
 - identifying, by one or more processors, from the plurality of inter-related data assets, a transfer asset to which the storage asset transfers the one or more pieces personal data;
 - digitally storing, by one or more processors, in computer memory, one or more storage asset inventory attributes comprising a type of personal data stored by the storage asset;
 - digitally storing, by one or more processors, in computer memory, one or more collection asset inventory attributes comprising the one or more pieces of personal data that the collection asset transfers to the storage asset;
 - digitally storing, by one or more processors, in computer memory, one or more transfer asset inventory attributes comprising the one or more pieces of personal data that the storage asset transfers to the transfer asset; and
- generating the data inventory by:
- associating the storage asset with the one or more storage asset inventory attributes in computer memory;
 - associating the collection asset with the one or more collection asset inventory attributes in computer memory;
 - associating the transfer asset with the one or more transfer asset inventory attributes in computer memory;
 - electronically linking the collection asset to the storage asset in computer memory;
 - electronically linking the storage asset to the transfer asset; and
 - electronically mapping the one or more pieces of personal data to the collection asset, the storage asset, and the transfer asset.
9. The computer-implemented data processing method of claim 8, wherein determining the respective data inventory attribute value for each of the unpopulated data fields comprises determining at least one data inventory attribute selected from a group consisting of:
- the one or more storage asset inventory attributes;
 - the one or more collection asset inventory attributes; and
 - the one or more transfer asset inventory attributes.
10. A data processing data inventory population system comprising:
- one or more processors;
 - computer memory; and

- a computer-readable medium storing computer-executable instructions that, when executed by the one or more processors, cause the one or more processors to perform operations comprising:
- accessing a data model of a plurality of data assets used in the collection or storage of personal data, the data model defining one or more electronic links between the plurality of data assets and storing a plurality of data inventories that define a plurality of inventory attributes for each of the plurality of data assets;
 - identifying a first data inventory from the plurality of data inventories, each of the plurality of data inventories being associated with a respective data asset, wherein the first data inventory comprises a plurality of fields that each define a respective inventory attribute of a first data asset associated with the first data inventory;
 - determining, for each respective one of the plurality of fields of the first data inventory, whether the respective field is a populated inventory attribute field containing an attribute value for one of the plurality of inventory attributes, or an unpopulated inventory attribute field not containing an attribute value for one of the plurality of inventory attributes;
 - determining, for each respective one of the one or more unpopulated inventory attributes fields, one or more attribute values for use in populating the respective unpopulated inventory attribute field;
 - in response to determining the one or more attribute values for each of the one or more unpopulated inventory attribute fields, modifying the first data inventory to include the one or more attribute values for each of the one or more unpopulated inventory attributes fields by populating each of the plurality of unpopulated inventory attribute fields with a respective one of the determined attribute values; and
 - storing the modified first data inventory in computer memory.
- 11.** The data processing data inventory population system of claim **10**, wherein:
- the one or more attribute values comprise a second data asset;
 - the plurality of data assets do not comprise the second data asset; and
 - the computer-readable medium further stores computer-executable instructions that, when executed by the one or more processors, cause the one or more processors to perform operations comprising:
 - generating a second data inventory for the second data asset, the second data inventory storing one or more second data asset inventory attributes comprising:
 - the first data asset; and
 - a type of personal data collected or stored by the second data asset; and
 - modifying the data model to include the second data asset and the second data inventory;
 - digitally storing the modified data model in the computer memory; and
 - electronically linking the first data asset to the second data asset in the data model.
- 12.** The data processing data inventory population system of claim **10**, wherein determining the one or more attribute values comprises determining the one or more attribute values using one or more intelligent identity scanning means.
- 13.** The data processing data inventory population system of claim **10**, wherein:
- the computer-readable medium further stores computer-executable instructions that, when executed by the one or more processors, cause the one or more processors to perform operations comprising:
 - using an application programming interface to access a third-party information technology system; and
 - integrating the data processing data inventory population system with the third-party information technology system via the application programming interface; and
 - determining the one or more attribute values comprises determining the one or more attribute values by retrieving the one or more attribute values from the third-party information technology system.
- 14.** The data processing data inventory population system of claim **10**, wherein the computer-readable medium further stores computer-executable instructions that, when executed by the one or more processors, cause the one or more processors to perform operations comprising:
- scanning one or more data repositories to identify one or more data attributes;
 - analyzing the one or more data attributes and correlating metadata for the scanned one or more data repositories with particular attributes of the one or more data attributes discovered in the one or more data repositories; and
 - determining the one or more attribute values based on the one or more data elements.
- 15.** The data processing data inventory population system of claim **14**, wherein analyzing the one or more data attributes and correlating metadata for the scanned one or more data repositories with the particular attributes of the one or more data attributes discovered in the one or more data repositories comprises retrieving schema details for each of the one or more data attributes from the scanned one or more data repositories.
- 16.** The data processing data inventory population system of claim **15**, wherein the schema details comprise one or more schema details selected from a group consisting of:
- an asset ID;
 - a Schema ID; and
 - a connection string.
- 17.** The data processing data inventory population system of claim **15**, wherein the computer-readable medium further stores computer-executable instructions that, when executed by the one or more processors, cause the one or more processors to perform operations comprising analyzing the one or more data repositories to determine whether each particular data repository is part of an existing data model of data assets
- 18.** The data processing data inventory population system of claim **10**, wherein each populated inventory attribute field comprises one or more known attributes.
- 19.** The data processing data inventory population system of claim **10**, wherein the computer-readable medium further stores computer-executable instructions that, when executed by the one or more processors, cause the one or more processors to perform operations comprising analyzing the

one or more data repositories to determine whether each particular data repository is part of an existing data model of data assets

20. The data processing data inventory population system of claim 10, wherein determining the one or more attribute values comprises determining the one or more attribute values using a combination of an application programming interface and a data repository scanning system.

* * * * *