



(19) **United States**

(12) **Patent Application Publication**  
Post et al.

(10) **Pub. No.: US 2022/0299964 A1**

(43) **Pub. Date: Sep. 22, 2022**

(54) **ADAPTERS FOR COMMUNICATION BETWEEN POWER TOOLS**

(60) Provisional application No. 62/528,631, filed on Jul. 5, 2017.

(71) Applicant: **MILWAUKEE ELECTRIC TOOL CORPORATION**, Brookfield, WI (US)

**Publication Classification**

(72) Inventors: **Matthew Post**, Brookfield, WI (US); **Kellen Carey**, Brookfield, WI (US); **Gareth Mueckl**, Milwaukee, WI (US); **Jeremy R. Ebner**, Milwaukee, WI (US); **Tauhira Hoossainy**, Milwaukee, WI (US)

(51) **Int. Cl.**  
**G05B 19/042** (2006.01)  
(52) **U.S. Cl.**  
CPC ..... **G05B 19/0423** (2013.01); **G05B 2219/25274** (2013.01); **B23Q 11/0046** (2013.01)

(21) Appl. No.: **17/837,580**


(57) **ABSTRACT**

(22) Filed: **Jun. 10, 2022**

Methods and systems are provided for a power tool in control of a vacuum. In response to activation input, the power tool controls a motor for driving power tool operation and wirelessly transmits a control signal to a vacuum. In response to receiving the control signal, the vacuum controls a motor for driving operation of the vacuum. The power tool, the vacuum, or both include a wireless communication pairing butting for paring the power tool and the vacuum. The power tool and/or the vacuum may be cordless and powered by a battery pack.

**Related U.S. Application Data**

(63) Continuation of application No. 16/584,411, filed on Sep. 26, 2019, now Pat. No. 11,360,450, which is a continuation of application No. 15/955,915, filed on Apr. 18, 2018, now Pat. No. 10,444,720.








FIG. 1






FIG. 3




FIG. 4A




FIG. 4B




FIG. 5





FIG. 6

700 ↗



**FIG. 7**



800 ↗




FIG. 8

## ADAPTERS FOR COMMUNICATION BETWEEN POWER TOOLS

### RELATED APPLICATIONS

**[0001]** This application is a continuation of U.S. patent application Ser. No. 16/584,411, filed Sep. 26, 2019, which is a continuation of U.S. patent application Ser. No. 15/955,915, filed on Apr. 18, 2018, which claims the benefit of U.S. Provisional Patent Application No. 62/528,631, filed on Jul. 5, 2017, the entire content of each of which is herein incorporated by reference.

### TECHNICAL FIELD

**[0002]** Embodiments described herein relate to power tools. More specifically, embodiments described herein relate to a power tool in communication with a vacuum.

### SUMMARY

**[0003]** The ability to activate or deactivate a tool in response to the activation or deactivation of another tool can hold several potential benefits for a user. For example, a vacuum activating automatically in response to an activation of a saw or drill motor can improve dust removal in a working environment and reduce user fatigue and effort to manually enable the vacuum. Some embodiments enable detection of activation of a first tool, wireless communication of signals indicating the activation of the first tool, and responsive activation of a second tool. Some embodiments enable detection of deactivation of a first tool, wireless communication of signals indicating the deactivation of the first tool, and responsive deactivation of a second tool. Some embodiments include the use of one or more removably coupled communication adapters to enable the detection, wireless communication, and activation/deactivation, which enables user customization of tool-to-tool interactions across a variety of tools.

**[0004]** In some embodiments, a system is provided for a power tool in control of a vacuum operation. The system includes a power tool having a power tool activation input, a first power interface, a first motor for driving operation of the power tool, a first wireless communication hardware, and a first pairing button. A first electronic controller includes a first electronic processor that is communicatively coupled to a first memory, the power tool activation input, the first motor, and the first wireless communication hardware. The system also has a vacuum that includes a vacuum power enable input, a second power interface, a second motor for driving operation of the vacuum, a second wireless communication hardware, and a second pairing button for wirelessly pairing the vacuum and the power tool for wireless communication. The vacuum also has a second electronic controller including a second electronic processor that is communicatively coupled to a second memory, the vacuum enable input, the second motor, the second wireless communication hardware, and the pairing button. The vacuum further includes a suction inlet connectable to the power tool. The first memory of the power tool includes instructions that when executed by the first electronic processor cause the first electronic processor to, in response to input received via the power tool activation input, control the first motor for driving operation of the power tool and transmit a control signal via the first wireless communication hardware to the vacuum. The second memory of the

vacuum includes instructions that when executed by the second electronic processor cause the second electronic processor to, in response to receiving the control signal via the second wireless communication hardware of the vacuum, control the second motor.

**[0005]** In some embodiments, a method is provided for a power tool in control of a vacuum operation. The method includes, in response to actuation of a pairing button of a vacuum, broadcasting, by the vacuum, a pairing identification signal; detecting, by the power tool, the pairing identification signal; and pairing, by the vacuum and the power tool, based on detecting the pairing identification signal. In response to receiving input via a power tool activation input, a first electronic processor of the power tool controls a first motor for driving operation of the power tool, and transmits a control signal via a first wireless communication hardware to a vacuum, wherein the first electronic processor is communicatively coupled to a first memory. In response to receiving the control signal via a second wireless communication hardware of the vacuum, a second electronic processor of the vacuum controls a second motor for driving operation of the vacuum, wherein the second electronic processor is communicatively coupled to a second memory.

**[0006]** In some embodiments, a system is provided for controlling operation of a second electronic tool in response to communication from a first electronic tool. The system includes a first electronic tool that includes a user input, a first motor for driving operation of the first electronic tool, first wireless communication hardware, and a first electronic controller. The first electronic controller includes a first electronic processor that is communicatively coupled to a first memory, the first tool activation input, the first motor, and the first wireless communication hardware. The system further includes a second electronic tool that includes a second electronic tool power enable input, a second motor for driving operation of the second electronic tool, a second wireless communication hardware, a pairing button for wirelessly pairing the second electronic tool and the first electronic tool for wireless communication. The second electronic tool further includes a second electronic controller including a second electronic processor that is communicatively coupled to a second memory, the second tool power enable input, the second motor, the second wireless communication hardware, and the pairing button. In response to input received via the first user input, the first electronic processor controls the first motor for driving operation of the first electronic tool and transmits a signal to the second electronic tool. In response to receiving the signal via the second wireless communication hardware of the second electronic tool, the second electronic processor controls the second motor for driving operation of the second electronic tool.

**[0007]** In some embodiments, a first method for tool-to-tool communication is provided that includes detecting, by a first controller of a first communication adapter, operation of a first electronic tool. In response to the detection, the controller broadcasts an activation signal. A second controller of a second communication adapter detects the activation signal broadcast by the first controller. In response to the detection of the activation signal, the second communication adapter controls a second electronic tool.

**[0008]** In some embodiments, a second method for tool-to-tool communication is provided that includes detecting, by a first controller of a first communication adapter, deac-

tivation of a first electronic tool. In response to the detection, the controller broadcasts a deactivation signal. A second controller of a second communication adapter detects the deactivation signal broadcast by the first controller. In response to the detection of the deactivation signal, the second communication adapter controls a second electronic tool.

**[0009]** In some embodiments, the second method is executed following the first method, such that the step of detecting, by the first controller, deactivation of the first electronic tool occurs subsequent to the step of controlling, by the second communication adapter, the second electronic tool in response to detection of the activation signal.

**[0010]** In some embodiments, a first tool-to-tool communication system is provided that includes a first electronic tool system having a first electronic tool and a first communication adapter removably coupled to a power interface of the first electronic tool, and a second electronic tool system having a second electronic tool and a second communication adapter. A first controller of the first communication adapter is configured to detect operation of the first electronic tool and, in response to the detection, broadcast an activation signal. A second controller of the second communication adapter is configured to detect the activation signal broadcast by the first controller. In response to the detection of the activation signal, the second communication adapter controls the second electronic tool.

**[0011]** In some embodiments, the first controller of the first communication adapter is configured to detect deactivation of the first electronic tool and, in response to the detection, broadcast a deactivation signal. Additionally, the second controller of the second communication adapter is configured to detect the deactivation signal broadcast by the first controller. In response to the detection of the deactivation signal, the second communication adapter controls the second electronic tool.

**[0012]** In some embodiments, a second tool-to-tool communication system is provided that includes a first electronic tool system having a first electronic tool and a first communication adapter removably coupled to a power interface of the first electronic tool, and a second electronic tool system having a second electronic tool and a second communication adapter. A first controller of the first communication adapter is configured to detect deactivation of the first electronic tool and, in response to the detection, broadcast a deactivation signal. A second controller of the second communication adapter is configured to detect the deactivation signal broadcast by the first controller. In response to the detection of the deactivation signal, the second communication adapter controls the second electronic tool.

**[0013]** In some embodiments of the above systems, the second communication adapter is removably coupled to a power interface of the second electronic tool, such as a battery pack interface or an alternating current (AC) power cord. In some embodiments, the second communication adapter is integrated into the second electronic tool, for example, electrically between a power interface of the second electronic tool and a load of the second electronic tool.

**[0014]** Other aspects of the invention will become apparent by consideration of the detailed description and accompanying drawings.

#### BRIEF DESCRIPTION OF THE DRAWINGS

**[0015]** FIG. 1 illustrates a tool-to-tool communication system.

**[0016]** FIG. 2A illustrates an example first electronic tool of the system of FIG. 1.

**[0017]** FIG. 2B illustrates a block diagram of an example first electronic tool of the system of FIG. 1.

**[0018]** FIG. 3 illustrates another example first electronic tool of the system of FIG. 1.

**[0019]** FIGS. 4A and 4B illustrate examples of a second electronic tool system of the system of FIG. 1.

**[0020]** FIG. 5 illustrates a first tool-to-tool communication adapter of the system of FIG. 1.

**[0021]** FIG. 6 illustrates a second tool-to-tool communication adapter of the second electronic tool system of the system of FIG. 1.

**[0022]** FIG. 7 illustrates a method of tool-to-tool communication.

**[0023]** FIG. 8 illustrates another method of tool-to-tool communication.

#### DETAILED DESCRIPTION

**[0024]** One or more embodiments are described and illustrated in the following description and accompanying drawings. These embodiments are not limited to the specific details provided herein and may be modified in various ways. Furthermore, other embodiments may exist that are not described herein. Also, the functionality described herein as being performed by one component may be performed by multiple components in a distributed manner. Likewise, functionality performed by multiple components may be consolidated and performed by a single component. Similarly, a component described as performing particular functionality may also perform additional functionality not described herein. For example, a device or structure that is “configured” in a certain way is configured in at least that way, but may also be configured in ways that are not listed. Furthermore, some embodiments described herein may include one or more electronic processors configured to perform the described functionality by executing instructions stored in non-transitory, computer-readable medium. Similarly, embodiments described herein may be implemented as non-transitory, computer-readable medium storing instructions executable by one or more electronic processors to perform the described functionality. As used in the present application, “non-transitory computer-readable medium” comprises all computer-readable media but does not consist of a transitory, propagating signal. Accordingly, non-transitory computer-readable medium may include, for example, a hard disk, a CD-ROM, an optical storage device, a magnetic storage device, a ROM (Read Only Memory), a RAM (Random Access Memory), register memory, a processor cache, or any combination thereof.

**[0025]** In addition, the phraseology and terminology used herein is for the purpose of description and should not be regarded as limiting. For example, the use of “including,” “containing,” “comprising,” “having,” and variations thereof herein is meant to encompass the items listed thereafter and equivalents thereof as well as additional items. The terms “connected” and “coupled” are used broadly and encompass both direct and indirect connecting and coupling. Further, “connected” and “coupled” are not restricted to physical or mechanical connections or couplings and can

include electrical connections or couplings, whether direct or indirect. In addition, electronic communications and notifications may be performed using wired connections, wireless connections, or a combination thereof and may be transmitted directly or through one or more intermediary devices over various types of networks, communication channels, and connections. Moreover, relational terms such as first and second, top and bottom, and the like may be used herein solely to distinguish one entity or action from another entity or action without necessarily requiring or implying any actual such relationship or order between such entities or actions.

**[0026]** FIG. 1 illustrates a tool-to-tool communication system 100. The system 100 includes a first electronic tool system 105 and a second electronic tool system 110. The first electronic tool system 105 includes a first electronic tool 115, a first tool-to-tool communication adapter 120 (also referred to as the first adapter or the first communication adapter 120), and a first power source 125. In some embodiments, the system 100 further includes a personal mobile device 128. The first adapter 120 is configured to be removably coupled to the first electronic tool 115 and to the first power source 125. The first adapter 120 is configured to wirelessly communicate with the second electronic tool system 110 via a wireless communication link 130. Although illustrated as a bi-directional communication link, in some embodiments, the wireless communication link 130 is unidirectional either from the first adapter 120 to the second electronic tool system 110 or from the second electronic tool system 110 to the first adapter 120. Additionally, in some embodiments, first adapter 120 and the second electronic tool system 110 are configured to wirelessly communicate, unidirectionally or bidirectionally, with the personal mobile device 128.

**[0027]** The first electronic tool 115 is, for example, a power tool, fluid flow control devices, an electronic test and measurement device, a work site radio, or work flood light. Power tools can include drills, circular saws, jig saws, band saws, table saws, chop saws, miter saws, reciprocating saws, angle grinders, straight grinders, hammers, multi-tools, impact wrenches, rotary hammers, drill-drivers, hammer drill-drivers, impact drivers, angle drills, belt sanders, orbital sanders, planers, pipe cutters, grease guns, vacuum cleaners, outdoor power equipment (such as blowers, chain saws, edgers, hedge trimmers, lawn mowers, or trimmers), and the like. Electronic test and measurement devices can include digital multimeters, clamp meters, fork meters, wall scanners, IR thermometers, laser distance meters, laser levels, remote displays, insulation testers, moisture meters, thermal imagers, inspection cameras, and the like. Vacuum cleaners can include wet/dry vacuums, dust removal vacuums connectable to power tools (e.g., saws or sanders), stick vacuums, hand vacuums, upright vacuums, carpet cleaners, hard surface cleaners, canister vacuums, broom vacuums, and the like. Fluid flow control devices can include motorized water pumps, electronically controllable water flow valves, and the like.

**[0028]** In some embodiments, the first power source 125 is a removable and rechargeable power tool battery pack operable with a suite of two or more of power tools, fluid flow control devices, test and measurement devices, work site radios, and work lights. The power tool battery pack includes a housing within which are one or more battery cells, which may be lithium ion (“Li-ion”) cells, Nickel-

Cadmium (“Ni-Cad”) cells, or cells of another chemistry type. The cells, collectively, may provide nominal voltages of different values, depending on the pack. For example, the power tool battery pack may have a nominal output voltage of 4V, 12V, 18V, 28V, 36V, 40V, or other levels. In some embodiments, the first power source 125 is an alternating current (AC) power source, such as a standard AC outlet coupled to an AC power grid or AC generator. For instance, the AC source may include an approximately 120 V, 60 Hz power signal or an approximately 240 V, 50 Hz power signal.

**[0029]** FIG. 2A illustrates an example of the first electronic tool system 105 of FIG. 1. In this example, the first electronic tool 115 is a brushless hammer drill 115a having a housing 150, an output unit 165, a trigger 175, and a battery interface 180 (also referred to as a power interface). The battery interface 180 is configured to receive and electrically couple to a power tool battery pack, such as some embodiments of the first power source 125 of FIG. 1. However, in the embodiment of FIG. 2A, the first adapter 120 has an interface that mimics a power tool battery pack and is coupled to the battery interface 180, and has another interface that mimics the battery interface 180 and is coupled to the first power source 125 (in the form of a power battery pack). As illustrated, the adapter 120 including an adapter housing 185, which engages the battery interface 180, and the first power source 125 includes a pack housing 190, which engages the adapter housing 185.

**[0030]** FIG. 2B illustrates a block diagram 200 of the first electronic tool 115a, which includes the power interface 180, field effect transistors (FETs) 205, a motor 210, output unit 212, Hall sensors 215, a motor control unit 220, user input 225, and other components 230 (battery pack fuel gauge, work lights (LEDs), current/voltage sensors, etc.). The Hall sensors 215 provide motor information feedback, such as motor rotational position information, which can be used by the motor control unit 220 to determine motor position, velocity, and/or acceleration. The motor control unit 220 receives user controls from user input 225, such as by depressing the trigger 175 or shifting a forward/reverse selector of the first electronic tool 115. In response to the motor information feedback and user controls, the motor control unit 220 transmits control signals to accurately control the FETs 205 to drive the motor 210. By selectively enabling and disabling the FETs 205, power from the power interface 180 is selectively applied to the motor 210 to cause rotation of a rotor of the motor 210. The rotating rotor of the motor 210 drives the output unit 165. Although not shown, the motor control unit 220 and other components of the first electronic tool 115 are electrically coupled to and receive power from the power interface 180. The FETs 205, motor 210, Hall sensors 215, motor control unit 220, and output unit 165 may be referred to as electromechanical components 235 of the first electronic tool 115.

**[0031]** Although described with respect to the example of the hammer drill-driver 115a of FIG. 2A, the block diagram 200 generally applies to other embodiments of the first electronic tool 115. For example, the output unit 165 in the case of a power saw is a saw blade holder (for example, an arbor); the output unit 165 in the case of a vacuum is an impeller providing suction force; and the output unit 165 in the case of a water pump is a pumping mechanism. Further, in some embodiments of the first electronic tool 115, a brushed motor is provided as the motor 210 to drive the

output unit **165**. Additionally, some embodiments of the first electronic tool **115**, such as electronic test and measurement devices, work flood light embodiments, and water flow control valves, do not include a motor for driving an output device. The block diagram **200** is modified for such embodiments. For example, the electromechanical components **235** are substituted with the appropriate electronics hardware for the relevant tool, such as a controller and lighting circuitry controlled by the controller (for a work flood light); a controller, sensing circuitry providing sensed data to the controller, and a display circuitry controlled by the controller to display the sensed data (for an electronic test and measurement device); or a controller, and a valve controlled by the controller (e.g., for a water flow control valve or pump).

[0032] FIG. 3 illustrates another example of the first electronic tool system **105** of FIG. 1. In this example, the first electronic tool **115** is a vacuum **115b**, or dust removal vacuum, having a housing **300**, a power switch **305** for turning on and off the vacuum, a suction inlet **310**, a collection container **315**, and a power cord **320** (also referred to as a power interface). The power cord **320** is coupled to the first adapter **120** which, in this embodiment, includes a plug **325** extending from the adapter housing **185** and for interfacing with the first power source **125**. In this embodiment, the first power source **125** is an AC source. The diagram **200** of FIG. 2 described above similarly applies to the vacuum **115b**. However, the power interface **180**, in this example, is an AC power interface, such as the power cord **320**.

[0033] FIGS. 4A and 4B illustrate embodiments of the second electronic tool system **110**, identified as a second electronic tool system **110a** and a second electronic tool system **110b**. The second electronic tool system **110a** of FIG. 4A includes a second electronic tool **400**, a second tool-to-tool communication adapter **405** (also referred to as the second adapter or second communication adapter **405**), and a second power source **410**. Similar to the first adapter **120**, the second adapter **405** in FIG. 4A includes a housing (similar to the housing **185**) and is configured to be removably coupled to the second electronic tool **400** and to the second power source **410**. The above description of the first adapter **120** and its engagement with the power tool **115a** and the power source **125**, including as illustrated and described with respect to FIGS. 2A and 3, similarly apply to the second adapter **405** with respect to the second electronic tool **400** and the second power source **410**. The second adapter **405** is also configured to wirelessly communicate with the first adapter **120** via the wireless communication link **130** (see FIG. 1).

[0034] The second electronic tool **400** is, for example (and like the first electronic tool **115**), a power tool, a fluid flow control device, an electronic test and measurement device, a work site radio, or work flood light. The above description of the first electronic tool **115**, including the examples listed above and the examples illustrated and described with respect to FIGS. 2A, 2B, and 3, similarly apply to the second electronic tool **400**.

[0035] Similar to the first power source **125**, in some embodiments, the second power source **410** is a removable and rechargeable power tool battery pack operable with a suite of two or more of power tools, fluid flow control devices, electronic test and measurement devices, work site radios, and work lights. Additionally, in some embodiments,

the second power source **410** is an alternating current (AC) power source, such as a standard AC outlet coupled to an AC power grid or AC generator.

[0036] The second electronic tool system **110b** of FIG. 4B is similar to the second electronic tool system **110a** of FIG. 4A, but for the second adapter **405** being integrated into the second electronic tool **400** rather than removably coupled thereto. For example, the second adapter **405** is installed within a housing (similar to, for example, the housing **150** of FIG. 2A or the housing **300** of FIG. 3) of the second electronic tool **400**, preventing simple attachment and detachment of the second adapter **405** by a user.

[0037] In some embodiments, the first electronic tool system **105** of FIG. 1 is similar to the second electronic tool system **110b** of FIG. 4B, with the first adapter **120** integrated into the first electronic tool **115** rather than removably coupled thereto. For example, in contrast to FIG. 2A, the first adapter **120** is installed within the housing **150** of the first electronic tool **115,115a**, preventing simple attachment and detachment of the first adapter **120** by a user.

[0038] FIG. 5 illustrates the first adapter **120** according to some embodiments. The first adapter **120** includes a power input **505** and a power output **510**. The power input **505** includes, for example, electrical terminals for interfacing with a power source, such as the first power source **125** in the case of the first adapter **120**. In other words, in some embodiments, the power input **505** receives AC power from an AC power source and, in other embodiments, the power input **505** receives DC power from a power tool battery pack.

[0039] The first adapter **120** further includes a power switching element **515**, such as a FET or relay, and an operational sensor **520**, such as a current or voltage sensor. The operational sensor **520** includes one or more sensors for detecting various operating conditions of a tool coupled to the power output **510**, such as current drawn by the tool, as described in further detail below. In some instances, the operational sensor **520** includes a global positioning satellite (GPS) module to provide a location of the first adapter **120** or a strength-of-signal sensor in wireless communication with another wireless device, such as the first electronic tool **115** or the second electronic tool **400** described above, at a known position, to determine a relative location of the first adapter **120** with respect to the other wireless device. The power switching element **515** and the operational sensor **520** are coupled to a controller **525**.

[0040] The controller **525** includes an electronic processor and is further coupled to wireless hardware **530**, a memory **535**, user input **540**, and user output **545**. The wireless hardware **530** is used for wireless communications, such as via the wireless communication link **130** or with the personal mobile device **128**. The wireless hardware **530** may include an antenna and a transceiver for transmitting and receiving wireless communications via the antenna.

[0041] The memory **535** includes, among other elements, software that is executed by the electronic processor of the controller **525** to control the functions of the first adapter **120** described herein. The user input **540**, which may include one or more of an actuating device (e.g., button, etc.), one or more selectors (e.g., pairing/command selector, light control, etc.), and other input elements (power toggle) to provide user commands to the controller **525** to indicate how the user desires the first adapter **120** to operate. The user output **545** includes one or more of LEDs, a speaker, a vibrating

element, etc. to inform the user of the status of the first adapter 120. For instance, if an error occurs, such as low battery power, first adapter 120 may output an audible alert, an LED may flash, and/or the vibrating element may provide tactile feedback to the user.

[0042] In some embodiments, the first adapter 120 further includes power regulating and conversion circuitry (not shown) to ensure that the power provided to various components of the first adapter 120, the power output 510, or both, are at the appropriate levels.

[0043] In some embodiments, the first adapter 120 includes the operational sensor 520 in addition to the other components illustrated in FIG. 5, but not the power switching element 515. In some embodiments, the first adapter 120 includes the power switching element 515 in addition to the other components illustrated in FIG. 5, but not the operational sensor 520.

[0044] FIG. 6 illustrates the second adapter 405 according to some embodiments. The second adapter 405 includes components similar to the first adapter 120 and, accordingly, are provided with like names and labels plus 100 in FIG. 6, and the above described functions and arrangement of the components of the first adapter 120 in FIG. 5 similarly applies to the similarly named components of the second adapter 405 in FIG. 6. Similar to the first adapter 120, in some embodiments, the second adapter 405 includes the operational sensor 620 in addition to the other components illustrated in FIG. 6, but not the power switching element 615. In some embodiments, the second adapter 405 includes the power switching element 615 in addition to the other illustrated in FIG. 6, but not the operational sensor 620. Thus, in some embodiments, the first adapter 120 includes the operational sensor 520, but not the power switching element 515, while the second adapter 405 includes the power switching element 615, but not the operational sensor 620. Additionally, in some embodiments, the second adapter 405 includes the operational sensor 620, but not the power switching element 615, while the first adapter 120 includes the power switching element 515, but not the operational sensor 520.

[0045] In some embodiments, when the second adapter 405 is integrated into the second electronic tool 400, the adapter is inserted between a power interface at which power is received from an external power source (e.g., the second power source 410) and a motor or other load (e.g., lights, displays, sensing devices, radios). For example, with respect to the diagram 200 of FIG. 2, the second adapter 405 may be inserted between the power interface 180 and the FETS 205 such that the power input 605 is coupled to the power interface 180 and the power output 610 is coupled to the FETS 205.

[0046] FIG. 7 illustrates a method 700 of tool-to-tool communication. In some embodiments, the method 700 is implemented with one of the embodiments of the system 100 of FIG. 1 and, accordingly, the method 700 will be described with respect to the system 100. However, in some embodiments, the method 700 is implemented with other systems. In block 705, the controller 525 of the first adapter 120 (also referred to as a sensing adapter) detects operation of the first electronic tool 115. For example, in some embodiments, the operational sensor 520 of the first adapter 120 is a current sensor that detects current drawn from the first power source 125 by the first electronic tool 115 when the first electronic tool 115 is activated. For example, in

response to activation of the first electronic tool 115 (e.g., via a trigger such as the trigger 175 of FIG. 2 or a power switch such as the power switch 305 of FIG. 3), the first electronic tool 115 draws current through the first adapter 120 (via the power input 505 and the power output 510), which is sensed by the operational sensor 520 and thereby detected by the controller 525 of the first adapter 120. The operational state (i.e., operating or not operating) of the first electronic tool 115 detected in block 705 may be referred to as an operational parameter of the first electronic tool 115.

[0047] In block 710, the controller 525 of the first adapter 120 broadcasts an activation signal. For example, the controller 525 broadcasts the activation signal wirelessly via the wireless hardware 530. The activation signal may include one or more of an indication of the operational state of first electronic tool 115 (e.g., indicating activation occurred) and a source identifier (e.g., an identity of the first adapter 120, an identity of the first electronic tool 115, or both). In some embodiments, the activation signal is broadcast by the first adapter 120 generally without a particular destination identifier. In some embodiments, the activation signal is broadcast by the first adapter 120 with a destination identifier, such as an identity of the second electronic tool system 110, which may be an identity of the second adapter 405 or the second electronic tool 410. In some embodiments, the activation signal broadcast by the first adapter 120 is transmitted via an existing communication link between the first adapter 120 and the second adapter 405 (e.g., a Bluetooth or Wi-Fi connection previously established).

[0048] In block 715, the controller 625 of the second adapter 405 (also referred to as a switching adapter) detects the activation signal broadcast by the first adapter 120. For example, the activation signal may be received by the wireless hardware 630 of the second adapter 405 (over the wireless link 130) and forwarded to the controller 625 of the second adapter 405. The controller 625, in turn, determines that the activation signal is from the first electronic tool system 105, for example, based on a match of the source identifier of the activation signal with an identifier stored in the memory 635. In the event that an activation signal is received in block 715 that is from another device having a source identifier that does not match with an identifier stored in the memory 635, the controller 625 may exit the method 700 (i.e., bypass block 720) or loop back to block 715 to await detection of another activation signal. Accordingly, activation signals from unassociated devices received by the second adapter 405 may be dismissed.

[0049] In block 720, the controller 625 of the second adapter 405 controls the second electronic tool 400 based on the activation signal detected in block 715. In some embodiments, controlling the second electronic tool 400 in block 720 includes the second adapter 405 activating the second electronic tool 400. For example, the controller 625 controls the power switching element 615 to an enabled (i.e., closed) state that permits power to flow from the power input 605 to the power output 610. As an example, when a power switch, such as the power switch 305 (FIG. 3), of the second electronic tool 400 is placed in an on/enabled state in advance of block 720 (e.g., by a user in a setup stage), enabling the power switching element 615 in block 720 activates the second electronic tool 400 because power is supplied to a load of the second electronic tool 400 when the power switching element 615 is enabled. In other examples, the controller 625 communicates an activation command to

the second electronic tool **400** to activate the second electronic tool **400**. The activation command may be sent by the controller **625** over the power output **610**, via a separate data line between the controller **625** and a controller of the second electronic tool **400** (e.g., the motor control unit **220**), or via the wireless hardware **630** over a wireless connection with the controller of the second electronic tool **400**.

[0050] As a first example, the first electronic tool **115** is a power tool (e.g., a saw or sander) that generates dust during operation, and the second electronic tool **400** may be a dust collecting vacuum, such as the vacuum **115b** (FIG. 3). In this example, the method **700** results in automatic activation of the dust-collecting vacuum in response to activation of the dust-generating power tool. As a second example, the first electronic tool **115** is also power tool (e.g., a rotary hammer or concrete saw) that generates dust during operation, and the second electronic tool **400** may be an electronically controllable water valve or pump providing a dust suppressing water flow. In this example, the method **700** results in automatic activation of the valve or pump providing a dust suppressing water flow (e.g., aimed at or near the output unit of the first electronic tool **115**) in response to activation of the dust-generating power tool.

[0051] In some embodiments, controlling the second electronic tool **400** in block **720** includes other control actions. Other control actions may include transmitting a parameter update to the second electronic tool **400** that adjusts an operational parameter of the second electronic tool **400**. The parameter may be transmitted by the controller **625** over the power output **610**, via a separate data line between the controller **625** and a controller of the second electronic tool **400** (e.g., the motor control unit **220**), or via the wireless hardware **630** over a wireless connection with the controller of the second electronic tool **400**. Example operation parameters that are controlled in block **720** include motor speed, light level, volume level, wireless communication. In a third example, the parameter update may cause a change in a volume parameter of a radio embodiment of the second electronic tool **400**. In this example, the volume parameter may be increased in block **720** such that the method **700** results in an increased volume of the radio (the second electronic tool **400**) in response to activating the first electronic tool **115**. The increased volume enables a user to more easily hear the audio of the radio despite operation of the first electronic tool **115**. In other examples, motor speed of the second electronic tool **400** is increased or decreased; light level of the second electronic tool **400** is increased or decreased; and wireless communications by the second electronic tool **400** are requested (for example, causing the transmission of operational data from the second electronic tool **400** to the first electronic tool system **105**, to the personal mobile device **128**, or to another electronic device).

[0052] In some embodiments, the memory **635** of the second adapter **405** stores instructions for executing various control actions to be executed in block **720**, where the instructions for particular control actions are associated with particular activation signals. Thus, different activation signals received (e.g., from different source devices) may result in different control actions by the second adapter **405**.

[0053] FIG. 8 illustrates a method **800** of tool-to-tool communication. In some embodiments, the method **800** is implemented with one of the embodiments of the system **100** of FIG. 1 and, accordingly, the method **800** will be described with respect to the system **100**. However, in some

embodiments, the method **800** is implemented with other systems. In some embodiments, the method **700** and the method **800** are performed sequentially such that the method **800** begins after block **720** of the method **700**. In other embodiments, the method **800** is performed independently of the method **700**.

[0054] In block **805**, the controller **525** of the first adapter **120** detects deactivation of the first electronic tool **115**. For example, in some embodiments, the operational sensor **520** of the first adapter **120** is a current sensor that detects a ceasing of current drawn from the first power source **125** by the first electronic tool **115** when the first electronic tool **115** is deactivated. For example, in response to deactivation of the first electronic tool **115** (e.g., via a trigger such as the trigger **175** of FIG. 2 or a power switch such as the power switch **305** of FIG. 3), the first electronic tool **115** ceases drawing current through the first adapter **120** (via the power input **505** and the power output **510**), which is sensed by the operational sensor **520** and thereby detected by the controller **525** of the first adapter **120**.

[0055] In block **810**, the controller **525** of the first adapter **120** broadcasts a deactivation signal. For example, the controller **525** broadcasts the deactivation signal wirelessly via the wireless hardware **530**. The deactivation signal may include one or more of an indication that tool deactivation occurred and a source identifier (e.g., an identity of the first adapter **120**, an identity of the first electronic tool **115**, or both). In some embodiments, the deactivation signal is broadcast by the first adapter **120** generally without a particular destination identifier. In some embodiments, the deactivation signal is broadcast by the first adapter **120** with a destination identifier, such as an identity of the second electronic tool system **110**, which may be an identity of the second adapter **405** or the second electronic tool **410**. In some embodiments, the deactivation signal broadcast by the first adapter **120** is transmitted via an existing communication link between the first adapter **120** and the second adapter **405** (e.g., a Bluetooth or Wi-Fi connection previously established).

[0056] In block **815**, the controller **625** of the second adapter **405** receives the deactivation signal broadcast by the first adapter **120**. For example, the deactivation signal may be received by the wireless hardware **630** of the second adapter **405** (over the wireless link **130**) and forwarded to the controller **625** of the second adapter **405**. The controller **625**, in turn, determines that the deactivation signal is from the first electronic tool system **105**, for example, based on a match of the source identifier of the deactivation signal with an identifier stored in the memory **635**. In the event that a deactivation signal is received in block **815** that is from another device having a source identifier that does not match with an identifier stored in the memory **635**, the controller **625** may exit the method **800** (i.e., bypass block **820**) or loop back to block **815** to await detection of another deactivation signal. Accordingly, the second adapter **405** may dismiss deactivation signals received from unassociated devices.

[0057] In block **820**, the controller **625** of the second adapter **405** controls the second electronic tool **400** based on the deactivation signal received. In some embodiments, controlling the second electronic tool **400** in block **820** includes the second adapter **405** deactivating the second electronic tool **400**. For example, the controller **625** controls the power switching element **615** to a disabled (i.e., open) state that prevents power from flowing from the power input

605 to the power output 610. In other examples, the controller 625 communicates a deactivation command to the second electronic tool 400 to deactivate the second electronic tool 400. The deactivation command may be sent by the controller 625 over the power output 610, via a separate data line between the controller 625 and a controller of the second electronic tool 400 (e.g., the motor control unit 220), or via the wireless hardware 630 over a wireless connection with the controller of the second electronic tool 400.

[0058] Returning to the first example, the method 800 results in automatic deactivation of the dust-collecting vacuum in response to deactivation of the dust-generating power tool (e.g., a saw or sander). Additionally, when the method 700 and 800 are executed sequentially, the methods result in the automatic activation and deactivation of the dust-collecting vacuum in response to the activation and deactivation, respectively, of the dust-generating power tool. Returning to the second example, the method 800 results in automatic deactivation of the valve or pump providing a dust suppressing water flow (e.g., aimed at or near the output unit of the first electronic tool 115) in response to deactivation of the dust-generating power tool. Additionally, when the method 700 and 800 are executed sequentially, the methods result in the automatic activation and deactivation of the valve or pump providing a dust suppressing waterflow in response to the activation and deactivation, respectively, of the dust-generating power tool.

[0059] In some embodiments, controlling the second electronic tool 400 in block 820 includes other control actions. Other control actions may include transmitting a parameter update to the second electronic tool 400 that adjusts an operational parameter of the second electronic tool 400. The parameter may be transmitted by the controller 625 over the power output 610, via a separate data line between the controller 625 and a controller of the second electronic tool 400 (e.g., the motor control unit 220), or via the wireless hardware 630 over a wireless connection with the controller of the second electronic tool 400. Example operation parameters that are controlled in block 720 include motor speed, light level, volume level, wireless communication. For example, the parameter update may cause a change in a volume parameter of a radio embodiment of the second electronic tool 400. Returning to the third example, the volume parameter may be decreased in block 820 such that the method 800 results in a decreased volume of the radio (the second electronic tool 400) in response to deactivating the first electronic tool 115. Additionally, when the method 700 and 800 are executed sequentially, the methods result in the automatic increase and decrease of the radio volume in response to the activation and deactivation, respectively, of the second electronic tool 400.

[0060] In some embodiments, the memory 635 of the second adapter 405 stores instructions for executing various control actions to be executed in block 820, where the instructions for particular control actions are associated with particular deactivation signals. Thus, different deactivation signals received (e.g., from different source devices) may result in different control actions by the second adapter 405.

[0061] In some embodiments, other operational parameters controlled in blocks 720 and 820 include an intensity of a light (e.g., of a work flood light) or a flow rate of water (e.g., for the valve or pump examples).

[0062] In some embodiments, in addition or instead of the operational state being detected and transmitted in blocks

705 and 710, respectively, of the method 700, one or more other operational parameters are detected and transmitted in method 700. Examples of such other operational parameters that are detected in block 705 include one or more of motor speed, current draw, battery level, runtime, light level, user input on tool, wireless communication of tool, and the like. In turn, an indication for each of these one or more other detected operational parameters is broadcast in block 710 as at least a part of the activation signal. In some embodiments, the indication is a particular measured or calculated amount for the detected operational parameter in block 705 (e.g., amps drawn or lumens emitted), and, in other embodiments the indication categorizes the detected operational parameter. Example categorizations include the operational parameter being above a certain threshold, below a certain threshold, within a certain range, and the like. In such embodiments of the method 700 using one or more other operational parameters in addition or instead of the operational state, in block 715, the indication of the one or more operational parameters is detected by the controller 625 as part of the activation signal; and, in block 720, the control action is further based on the one or more other operational parameters.

[0063] To illustrate some embodiments of the method 700 using one or more other operational parameters in addition or instead of the operational state, modified versions of earlier examples are described below. Returning to the first example, in some embodiments, the activation signal (broadcast block 710) is configured to indicate an intensity of operation of the first electronic tool 115 that is detected in block 705. When the first electronic tool 115 is indicated to be operating at high intensity (e.g., based on current draw being above a threshold or a selected mode), the dust collecting vacuum is controlled (block 720) to operate with a higher suction force than when the activation signal indicates that the first electronic tool 115 is operating at a lower intensity. Returning to the second example, in some embodiments, when the activation signal indicates that the first electronic tool 115 is operating at high intensity (e.g., based on current draw being above a threshold or a selected mode), the valve or pump is controlled to provide a greater water flow than when the activation signal indicates that the first electronic tool 115 is operating at a lower intensity. Returning to the third example, when the activation signal indicates that the first electronic tool 115 is operating at high intensity (e.g., based on current draw being above a threshold or a selected mode), the volume is controlled to increase more than when the activation signal indicates that the first electronic tool 115 is operating at a lower intensity. In these embodiments, the method 700 may loop back to block 705 after block 720 (for example, until deactivation of the first electronic tool 115) such that the controller 625 continuously updates controls of the second electronic tool 400 based on changing operational parameters of the first electronic tool 115 sensed by the first adapter 120.

[0064] Accordingly, in some embodiments of the method 700, block 705 may be described as the first adapter detecting an operational parameter of the first electronic tool; block 710 may be referred to as the first adapter broadcasting an activation signal indicating the operational parameter; block 715 may be referred to as the second adapter detecting the activation signal indicating the operational parameter; and block 720 may be referred to as the second adapter



controlling the second electronic tool based on the activation signal (or, more particularly, based on the operational parameter).

[0065] As noted with respect to block 715 and 815, potential source identifiers may be stored in the memory 635 of the second adapter 405 for authorizing received activation and deactivation signals based on their included source identifiers. In some embodiments, the first adapter 120 and the second adapter 405 are paired at the time of manufacture such that the identity of the first adapter 120 is stored in the memory 635 of the second adapter for this authorization.

[0066] In some embodiments, the first adapter 120 and the second adapter 405 are paired after the point of manufacture by a user in the field. For example, the first adapter 120 broadcasts a pairing identification signal (e.g., in response to receiving user actuation of a pairing button that is part of the user input 540). The second adapter 405 detects the pairing identification signal. The second adapter pairs to the first adapter (e.g., by storing an identity of the second adapter 405 in the memory 635 for matching purposes in block 715 and 815). The second adapter 405 may also send an acknowledgement signal.

[0067] In another example, the personal mobile device 128 pairs the first adapter 120 and the second adapter 405. The personal mobile device 128 and the first adapter 120 form a wireless communication link. The first adapter 120 broadcasts a pairing identification signal over the wireless communication link, which is detected by the personal mobile device 128. The pairing identification signal may be sent in response to a request from the personal mobile device 128. The personal mobile device 128 and the second adapter 405 then form a wireless communication link. The personal mobile device 128 then sends pairing instructions to the second adapter 405 over the wireless communication link. In response, the second adapter 405 pairs to the first adapter (e.g., by storing an identity of the first adapter 120 in the memory 635 for matching purposes in block 715 and 815).

[0068] The personal mobile device 128, in some embodiments, is further configured to set and adjust the control actions to be executed in blocks 720 and 820 by the second adapter 405. For example, in addition to the pairing instructions sent by the personal mobile device 128 to the second adapter 405, the personal mobile device 128 sends configuration data that adjusts the control actions stored in the memory 635. The personal mobile device 128 may provide a graphical user interface enabling receipt of user input that selects the particular configuration data (and, thereby, the control actions).

[0069] Additionally, the personal mobile device 128 may unpair the first adapter 120 and the second adapter 405, and pair the first adapter 120 with a different adapter (another instance of the second adapter 405 associated with another instance of the second electronic tool 400).

[0070] Additionally, in some embodiments, the broadcast activation and deactivation signals of the methods 700 and 800 may be detected by multiple second adapters 405, each associated with a respective second electronic tool 400, in block 715 and 815. In response, in blocks 720 and 820, each respective second adapter 405 controls the associated second electronic tool 400.

[0071] In some embodiments, the first and second adapters switch roles in the methods 700 and 800 (and the various alternative embodiments discussed in relation to the methods 700 and 800). For example, the second adapter 405

performs the detection of the second electronic tool 400 and broadcasting in blocks 705, 710, 805, and 810, and the first adapter 102 performs the detecting and controlling of the first electronic tool 115 in blocks 715, 720, 815, and 820. Additionally, in such embodiments, the source identifier(s) and control action(s) are stored in the memory 535 of the first adapter 120.

[0072] As noted above, the first adapter 120 is removably coupled to the first electronic tool (see, e.g., FIGS. 1, 2A, and 3) and, in some embodiments, the second adapter 405 is removably coupled to the second electronic tool 400 (see, e.g., FIG. 4A). The removable nature of these adapters enables connection to various types of electronic tools. Thus, a user is able to pair electronic tools by coupling paired adapters to these electronic tools, respectively (or coupling and then pairing the adapters, as described above). This pairing ability, which can occur after purchase and multiple times throughout the life of the adapters in the field, provides flexibility to a user.

What is claimed is:

1. A system for tool communication, the system comprising:
  - a first electronic tool that includes:
    - a first power interface configured to receive power from a first power source;
    - a first wireless communication adapter that includes:
      - a first power input configured to interface with the first power source,
      - a first power output configured to interface with the first power interface,
      - an operational sensor, and
      - a first controller including a first electronic processor that is communicatively coupled to a first memory and the operational sensor, wherein the first memory of the first wireless communication adapter includes instructions that, when executed by the first electronic processor, cause the first electronic controller to:
        - detect operation of the first electronic tool based on a parameter sensed by the operational sensor, and
        - broadcast an activation signal in response to detecting operation of the first electronic tool; and
  - a second electronic tool that includes:
    - a first motor,
    - a power switching element,
    - a second power interface configured to receive power from a second power source; and
    - a second wireless communication adapter that includes:
      - a second controller including a second electronic processor that is communicatively coupled to a second memory, wherein the second memory of the second electronic tool includes instructions that, when executed by the second electronic processor, cause the second electronic controller to:
        - detect the activation signal broadcast by the first controller, and
        - enable the power switching element to provide power from second power interface to the first motor.

2. The system of claim 1, wherein the first electronic tool is a saw or sander and the second electronic tool is a dust collecting vacuum.

3. The system of claim 1, wherein the second controller is further configured to:

receive a parameter update; and

adjust an operational parameter of the second electronic tool based on the parameter update.

4. The system of claim 3, wherein, to adjust the operational parameter of the second electronic tool, the second controller is further configured to at least one of adjust motor speed, adjust an illumination level of a light coupled to the second electronic tool, or adjust a volume level of a radio of the second electronic tool.

5. The system of claim 4, wherein the volume level of the radio of the second electronic power tool is increased in response to detecting the activation signal broadcast by the first controller.

6. The system of claim 1, wherein the first wireless communication adapter is removably coupled to the first electronic tool.

7. The system of claim 6, wherein the first power output includes a mechanical interface that is the same as an output interface of the first power source.

8. The system of claim 1, wherein:

the first controller is further configured to:

broadcast a pairing identification signal, and

determine that the first wireless communication adapter is paired with the second wireless communication adapter; and

the second controller is further configured to:

receive the pairing identification signal, and

determine that the second wireless communication adapter is paired with the first wireless communication adapter.

9. The system of claim 8, wherein the first wireless communication adapter is configured to pair with the second wireless communication adapter prior to the first wireless communication adapter being coupled to the first electronic tool.

10. The system of claim 8, wherein:

the first controller broadcasts the pairing identification signal to a mobile device; and

the second controller receives pairing instructions from the mobile device.

11. A method for controlling a second electronic tool operation by a first electronic tool, the method comprising:

detecting, by a first electronic controller of a first wireless communication adapter, operation of the first electronic tool based on a parameter sensed by an operational sensor, the operational sensor being coupled to the first wireless communication adapter, the first wireless communication adapter including a power output configured to interface with the first electronic tool;

broadcasting, by the first electronic controller of the first wireless communication adapter, an activation signal in response to detecting operation of the first electronic tool;

detecting, by a second electronic controller of a second wireless communication adapter, the activation signal broadcast by the first electronic controller; and

enabling, by the second electronic controller of the second wireless communication adapter, a power switching element of the second electronic tool to provide power

from a second power interface to a first motor, the second power interface receiving power from a power source, and the first motor being housed within the second electronic tool.

12. The method of claim 11, wherein the first wireless communication adapter includes a first power input that includes electrical terminals for interfacing with a first power source and a first power output that is electrically coupled to a first power interface of the first electronic tool.

13. The method of claim 11, further comprising:

receiving, by the second electronic controller of the second wireless communication adapter, a parameter update; and

adjusting, by the second electronic controller of the second wireless communication adapter, an operational parameter of the second electronic tool.

14. The method of claim 13, wherein adjusting, by the second electronic controller of the second wireless communication adapter, the operational parameter of the second electronic tool includes at least one of adjusting a motor speed, adjusting an illumination level of a light coupled to the second electronic tool, and adjusting a volume level of a radio of the second electronic tool.

15. The method of claim 14, further comprising:

increasing, by the second electronic controller of the second wireless communication adapter, the volume level of the radio of the second electronic power tool in response to detecting the activation signal broadcast by the first controller of the first wireless communication adapter.

16. A system for tool communication, the system comprising:

a first power tool that includes:

a first power interface,

an operational sensor,

a first wireless communication adapter configured to be removably coupled to the first electronic tool, the first wireless communication adapter including:

a first power input that includes electrical terminals configured to interface with a first power source, and

a first controller including a first electronic processor that is communicatively coupled to a first memory, the first memory of the first wireless communication adapter including instructions that, when executed by the first electronic processor, cause the first controller to:

detect operation of the first power tool based on a parameter sensed by the operational sensor, and broadcast an activation signal in response to detecting operation of the first power tool; and

a second electronic tool that includes:

a first motor,

a second power interface configured to receive power from a second power source,

a power switching element that selectively provides power to the first motor, and

a second wireless communication adapter that includes:

- a second controller including a second electronic processor that is communicatively coupled to a second memory, the second memory of the second electronic tool including instructions that, when executed by the second electronic processor, cause the second controller to:
  - detect the activation signal broadcast by the first controller, and
  - enable the power switching element to provide power from the second power interface to the first motor.

**17.** The system of claim **16**, wherein the second wireless communication adapter is removably coupled to the second electronic tool.

**18.** The system of claim **16**, wherein:

- the first wireless communication adapter includes a first power output that is electrically coupled to the first power interface; and
- the first power output includes a mechanical interface that is the same as an output interface of the first power source.

**19.** The system of claim **16**, wherein the second wireless communication adapter is provided between the second power source and the first motor within the second electronic power tool.

**20.** The system of claim **16**, wherein the first power tool is a rotary hammer or a concrete saw and the second electronic tool is a water flow device.

\* \* \* \* \*