



US011910139B2

(12) **United States Patent**
Chen et al.

(10) **Patent No.:** **US 11,910,139 B2**

(45) **Date of Patent:** **Feb. 20, 2024**

(54) **ACOUSTIC DEVICE AND ELECTRONIC APPARATUS**

(58) **Field of Classification Search**

CPC H04R 1/021; H04R 1/023; H04R 1/025;
H04R 1/086; H04R 1/2811; H04R
1/2834;

(71) Applicant: **GOERTEK INC.**, Shandong (CN)

(Continued)

(72) Inventors: **Aliang Chen**, Shandong (CN);
Guoqiang Chen, Shandong (CN);
Zhaopeng Li, Shandong (CN)

(56) **References Cited**

U.S. PATENT DOCUMENTS

(73) Assignee: **GOERTEK INC.**, Weifang (CN)

6,932,187 B2 8/2005 Banter et al.
7,974,431 B2 7/2011 Saiki

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 158 days.

(Continued)

FOREIGN PATENT DOCUMENTS

(21) Appl. No.: **17/636,249**

CN 1883242 A 12/2006
CN 101023703 A 8/2007

(22) PCT Filed: **Dec. 24, 2019**

(Continued)

(86) PCT No.: **PCT/CN2019/127842**

OTHER PUBLICATIONS

§ 371 (c)(1),
(2) Date: **Feb. 17, 2022**

International Search Report from International Application No. PCT/CN2019/127842 dated May 21, 2020.

(87) PCT Pub. No.: **WO2021/031486**

Primary Examiner — Huyen D Le

PCT Pub. Date: **Feb. 25, 2021**

(74) *Attorney, Agent, or Firm* — Shih IP Law Group, PLLC

(65) **Prior Publication Data**

US 2022/0295162 A1 Sep. 15, 2022

(57) **ABSTRACT**

(30) **Foreign Application Priority Data**



Aug. 20, 2019 (CN) 201910770427.2

Disclosed is an acoustic device, comprising a sound generating unit, a sound wave at a front side of the vibrating diaphragm radiates to outside through the sound outlet, a first sealed cavity is formed at a rear side of the vibrating diaphragm, a cavity wall of the first sealed cavity is provided with a mounting hole, a flexible deformation part is provided at the mounting hole, the second sealed cavity encloses a sound wave, in the second sealed cavity, a protective cover plate located at outside of the flexible deformation part is further provided on the mounting hole, and an escape space used for avoiding vibration of the flexible deformation part is formed between the protective cover plate and the flexible deformation part; air permeable micropores are provided on

(Continued)

(51) **Int. Cl.**
H04R 1/02 (2006.01)
H04R 1/28 (2006.01)
H04R 9/06 (2006.01)

(52) **U.S. Cl.**
CPC **H04R 1/021** (2013.01); **H04R 1/025** (2013.01); **H04R 1/2811** (2013.01);
(Continued)



the protective cover plate, the air permeable micropores have an area less than or equal to 0.2 mm².

16 Claims, 5 Drawing Sheets

(52) **U.S. Cl.**

CPC **H04R 1/2834** (2013.01); **H04R 1/2849** (2013.01); **H04R 9/06** (2013.01); **H04R 2499/11** (2013.01)

(58) **Field of Classification Search**

CPC H04R 1/2849; H04R 1/2888; H04R 9/06; H04R 1/44; H04R 2499/11
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

10,390,128 B2* 8/2019 Fathollahi H04R 1/023
2005/0077102 A1 4/2005 Banter et al.
2007/0201712 A1 8/2007 Saiki
2017/0171664 A1* 6/2017 Shao H04R 7/127
2019/0222925 A1 7/2019 Ha et al.
2021/0120343 A1* 4/2021 Zhang H04R 9/02

FOREIGN PATENT DOCUMENTS

CN 101023703 B 9/2011
CN 204157049 U 2/2015
CN 204157050 U 2/2015

CN	107396256	A	11/2017
CN	206629252	U	11/2017
CN	207075085	U	3/2018
CN	207543282	U	6/2018
CN	109246563	A	1/2019
CN	109803215	A	5/2019
CN	208902682	U	5/2019
CN	109874094	A	6/2019
CN	110446139	A	11/2019
CN	110572755	A	12/2019
CN	111343547	A	6/2020
CN	109246563	B	11/2020
CN	109803215	B	1/2021
CN	110572755	B	11/2021
EP	1685740	A2	8/2006
EP	1791389	A1	5/2007
EP	1685740	A4	7/2009
EP	1791389	A4	10/2012
EP	2741522	A1	6/2014
EP	1685740	B1	12/2014
EP	1791389	B1	11/2016
JP	2007510326	A	4/2007
JP	4861825	B2	1/2012
KR	20060085958	A	7/2006
KR	100841508	B1	6/2008
KR	20210103530	A	8/2021
WO	2005039234	A2	4/2005
WO	2006030760	A1	3/2006
WO	2005039234	A3	7/2006
WO	2019136740	A1	7/2019
WO	2020103301	A1	5/2020
WO	2020125632	A1	6/2020
WO	2020125634	A1	6/2020
WO	2021031486	A1	2/2021

* cited by examiner

Prior Art




Fig 1

Prior Art




Fig 2




Fig 3A




Fig 3B




Fig 3C




Fig 4




Fig 5




Fig 6




Fig 7

1

ACOUSTIC DEVICE AND ELECTRONIC APPARATUS

TECHNICAL FIELD

The present invention relates to the acoustics technical field, in particular, relates to an acoustic device and an electronic apparatus in which the acoustic device is mounted.

BACKGROUND ART

Generally, an acoustic system with a traditional structure (Prior Art 1) comprises a closed housing and a sound generating unit provided on the closed housing, and a cavity is formed between the closed housing and the sound generating unit. Due to the volume limitation of the cavity in the acoustic system, it is difficult for the acoustic system, especially the small acoustic system, to achieve the effect of satisfactorily reproducing the bass. Conventionally, in order to achieve satisfactory bass reproduction in the acoustic system, two methods are often used, one of them is to provide a sound-absorbing material (such as activated carbon, zeolite, etc.) in the housing of the acoustic system to adsorb or desorb the gas in the housing, so as to increase the volume and thereby reduce the low-frequency resonance frequency; the other one is to provide a passive radiator on the housing of the acoustic system (prior art 2), for example, as shown in FIG. 1, wherein 10 is the sound generating unit, 20 is the housing of the acoustic system, 30 is the passive radiator, the sound generating unit and the passive radiator radiate sound to outside at the same time, and the sound waves of the sound generating unit and the passive radiator are communicated and superimposed based on the principle that the passive radiator and the housing form strong resonance at a specific frequency point f_p (resonant frequency point), so as to enhance the local sensitivity near the resonant frequency point f_p (for example, see patent CN1939086A). However, the above two methods have problems, the first method of adding the sound-absorbing material in the housing needs to realize good sealing and packaging of the sound-absorbing material, otherwise if the sound-absorbing material enters the speaker unit, it will damage the acoustic performance of the speaker unit and affect the usage life of the speaker unit; in the second method of adopting passive radiator, near the resonance frequency point f_p , the passive radiator radiates strongly and the sound generating unit almost stops, therefore, the local sensitivity enhancement of the acoustic system can be realized in the frequency band near f_p through the high sensitivity design of the passive radiator, however, in the frequency band below f_p , the phase of the sound wave of the passive radiator is opposite to the phase of the sound wave of the sound generating unit, and the sound waves offset with each other, and thus the passive radiator has a negative effect on the sensitivity of the acoustic system. In short, the passive radiator can only improve the sensitivity of the frequency band near the resonance point, but cannot improve all the low frequency bands. As shown in FIG. 2, FIG. 2 shows the test curves of loudness (SPL curves) at different frequencies for the prior art 2 and the prior art 1. Therefore, it is necessary to further improve the defects of the prior art.

SUMMARY

An object of the present invention is to provide an acoustic device which can effectively reduce the resonant frequency and greatly improve the low-frequency sensitivity of the product as a whole.

2

In order to solve the above technical problems, the technical solution provided by the present invention is an acoustic device, comprising:

a sound generating unit comprising a vibrating diaphragm, wherein the acoustic device is provided with a sound outlet, and a sound wave at a front side of the vibrating diaphragm radiates to outside through the sound outlet,

wherein a first sealed cavity is formed at a rear side of the vibrating diaphragm, a cavity wall of the first sealed cavity is provided with a mounting hole, a flexible deformation part is provided at the mounting hole, a second sealed cavity is provided at outside the first sealed cavity, the flexible deformation part is located between the first sealed cavity and the second sealed cavity, and the second sealed cavity encloses a sound wave, which is generated by the flexible deformation part during deformation, in the second sealed cavity;

a protective cover plate located at outside of the flexible deformation part is further provided on the mounting hole, and an escape space for avoiding vibration of the flexible deformation part is formed between the protective cover plate and the flexible deformation part; and

wherein a plurality of air permeable micropores are provided on the protective cover plate, and each of the air permeable micropores has an area less than or equal to 0.2 mm^2 .

Preferably, thickness of the protective cover plate is less than or equal to 0.2 mm, the air permeable micropores are circular holes, and apertures of the air permeable micropores are less than or equal to 0.5 mm.

Preferably, the apertures of the air permeable micropores are less than or equal to 0.3 mm.

Preferably, a distance from one side to other side on a line connecting the centers of two adjacent air permeable micropores is greater than or equal to 0.3 mm and less than or equal to 1 mm.

Preferably, the protective cover plate is made of one of steel sheet, FR-4 sheet, PET sheet, PEN sheet, carbon fiber sheet and ceramic sheet.

Preferably, a top surface of the protective cover plate is not higher than a top surface of the cavity wall.

Preferably, the protective cover plate comprises a fixing surface, a protective surface and a connecting wall, the fixing surface and the protective surface are located on different planes, the fixing surface are connected with the protective surface by the connecting wall, the fixing surface is fixed on the cavity wall, and the air permeable micropores are provided on the protective surface and/or the connecting wall.

Preferably, a pallet formed by recessing towards the first sealed cavity is provided on a wall of the mounting hole, and the fixing surface is fixed on the pallet.

Preferably, the edge portion of the flexible deformation part is connected to the fixing surface of the protective cover plate at first, and then the assembled member is fixed to the pallet as a whole.

Preferably, the protective cover plate is fixed on the cavity wall at first, and the flexible deformation part is fixed to the cavity wall from the inner side of the cavity wall; and

the protective cover plate is fixed on the cavity wall by bonding, alternatively the protective cover plate is fixed on the cavity wall by injection molding.

Preferably, an airflow channel is formed between the connecting wall and side wall of the pallet.

Preferably, the cavity wall comprises a first wall and a second wall connected with the first wall, the mounting hole is located on the first wall, a through groove formed by recessing towards the first sealed cavity is further provided at the first wall, and the through groove penetrates through the mounting hole and an outer surface of the second wall.

Preferably, the flexible deformation part comprises a body part, and the body part has a flat plate structure; or at least an edge portion of the body part is provided with a protrusion; or at least the edge portion of the body part has a wavy structure;

the flexible deformation part further comprises a composite sheet combined with the body part at a central position of the body part, and the body part has a sheet-like overall structure or the central position of the body part is hollowed out.

Preferably, at least a portion of a housing of an electronic apparatus for mounting the acoustic device is used to form the first sealed cavity and/or the second sealed cavity.

Preferably, the acoustic device comprises a first housing, the sound generating unit is mounted on the first housing to form a sound generating assembly, the first sealed cavity is formed between the vibrating diaphragm of the sound generating unit and the first housing, the first housing is provided with the mounting hole thereon, and the flexible deformation part is provided at the mounting hole.

The acoustic device comprises a second housing, the sound generating assembly is mounted in the second housing, the second sealed cavity is formed between the second housing and the first housing, and the second housing is the housing of the electronic apparatus.

Another object of the present invention is to provide an electronic apparatus, which comprises the housing of the acoustic device mounted in the housing. The acoustic device can effectively reduce the resonant frequency and greatly improve the low-frequency sensitivity of the product as a whole.

In the technical solution provided by the present invention, the first sealed cavity is formed at the rear side of the vibrating diaphragm in the acoustic device, the flexible deformation part is covered and provided on the mounting hole of the cavity wall of the first sealed cavity, and the second sealed cavity for enclosing the sound wave generated by the flexible deformation part during deformation is further provided at outside of the first sealed cavity. By providing the flexible deformation part, the flexible deformation part deforms with the sound pressure, and the volume of the first sealed cavity is adjustable, so that the equivalent acoustic compliance of the first sealed cavity increases, the resonance frequency of the acoustic device is effectively reduced, and the low-frequency sensitivity is improved. Through the isolation design of the sound generating unit and the flexible deformation part, the radiated sound wave of the flexible deformation part is enclosed in the acoustic device, to avoid the offset effect on the forward radiated sound wave of the sound generating unit due to the anti-phase radiated sound wave of the flexible deformation part, and thus the low-frequency sensitivity of the product is greatly improved as a whole.

Moreover, in the technical solution of the present invention, a protective cover plate is provided at outside of the flexible deformation part, and the protective cover plate has high strength and can be formed very thin, so as not to occupy too much space of the product in Z-axis, and can

prevent the flexible deformation part from being damaged or broken by the external environment during the process of transportation or assembly.

Further, a plurality of air permeable micropores are provided on the protective cover plate. The protective cover plate does not isolate the outer space of the flexible deformation part from the second sealed cavity, and the air permeable micropores can realize the pressure balance during the vibration of the flexible deformation part.

Further, each of the air permeable micropores has an area less than or equal to 0.2 mm^2 . First, it has no influence on the strength of the protective cover plate. Secondly, if the air permeable micropores is provided with too large area, liquid and impurities in the external environment, that is, the second sealed cavity will continuously adhere to the flexible deformation part and affect the performance and the usage lifespan of the flexible deformation part. This is usually solved by the method of attaching a dustproof mesh cloth onto the protective cover plate, but this method may increase material costs and assembly process, and the arrangement of the dustproof mesh cloth may increase the space of the product in Z-axis. In the technical solution of the present invention, the area of each of the air permeable micropores is reduced to less than or equal to 0.2 mm^2 , and in the case that only the protective cover plate is provided, not only the pressure balance can be achieved, but also the problem of liquid and impurities invasion can be solved, and the material cost and assembly process can be reduced, and the space of the product in Z-axis can be saved.

Through the following detailed description of the exemplary embodiments of the present invention with reference to the accompanying drawings, other features and advantages of the present invention will become clear.

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings incorporated into and constituting a part of the specification show embodiments of the present invention and are used to explain the principle of the present invention together with its description.

FIG. 1 is a schematic diagram of the structure of the acoustic device provided with a passive radiator in the prior art 2.

FIG. 2 shows the test curves of loudness (SPL curves) at different frequencies for the acoustic device provided with the passive radiator in the prior art 2 and the acoustic device with a traditional structure in the prior art 1.

FIG. 3A is a schematic diagram of the structure of an acoustic device according to an embodiment of the present invention.

FIG. 3B is an enlarged schematic diagram of part of the structure in FIG. 3A.

FIG. 3C is an enlarged schematic diagram of the structure of the flexible deformation part in FIG. 3A.

FIG. 4 is an exploded schematic diagram of the structure of the first housing, the flexible deformation part, and the protective cover plate in FIG. 3A.

FIG. 5 shows the test curves of loudness (SPL curves) at different frequencies for the acoustic device according to one embodiment of the present invention and the acoustic device with the traditional structure in the prior art 1.

FIG. 6 shows the test curves of loudness (SPL curves) at different frequencies for the acoustic device according to an embodiment of the present invention and the acoustic device provided with the passive radiator in the prior art 2.

FIG. 7 is a schematic diagram of the structure of the electronic apparatus using the acoustic device in accordance with the present invention.

DESCRIPTION OF REFERENCE NUMERALS

100: acoustic device; **1:** sound generating unit; **11:** vibrating diaphragm; **2:** first housing; **21:** first sealed cavity; **22:** flexible deformation part; **221:** body part; **222:** protrusion; **223:** composite sheet; **23:** pressure equalizing hole; **24:** pallet; **25:** through groove; **261:** first wall; **262:** second wall; **27:** protective cover plate; **271:** protective surface; **272:** connecting wall; **273:** fixing surface; **274:** air permeable micropore; **3:** second housing; **31:** second sealed cavity; **4:** sound outlet **5:** electronic apparatus.

DETAILED DESCRIPTION OF EMBODIMENTS

Various exemplary embodiments of the present invention will now be described in detail with reference to the accompanying drawings. It should be noted that the relative arrangement, numerical expressions and values of the parts and steps described in these embodiments do not limit the scope of the present invention unless otherwise specified.

The following description of at least one exemplary embodiment is actually only illustrative and in no way serves as any limitation on the present invention and its application or use.

The technologies, methods and devices known to those skilled in the art may not be discussed in detail, but in appropriate circumstance, the technologies, methods and devices shall be regarded as a part of the specification.

In all of the examples shown and discussed here, any specific value should be interpreted as merely exemplary and not as a limitation. Therefore, other examples of exemplary embodiments may have different values.

It should be noted that similar reference numerals represent similar items in the following drawings. Therefore, once an item is defined in a drawing, it does not need to be further discussed in subsequent drawings.

Embodiment 1

As shown in FIGS. 3A-4, an acoustic device comprises a sound generating unit **1**. In this embodiment, the sound generating unit **1** is a micro sound generating unit, and more specifically, the sound generating unit **1** is a micro moving coil speaker. The sound generating unit **1** generally comprises a housing, and a vibrating system and a magnetic circuit system accommodated and fixed in the housing. The vibrating system comprises a vibrating diaphragm **11** fixed on the housing and a voice coil combined with the vibrating diaphragm **11**. A magnetic gap is formed in the magnetic circuit system. The voice coil is provided in the magnetic gap. After alternating current is supplied to the voice coil, the voice coil moves up and down in the magnetic field, thus driving the vibrating diaphragm **11** to vibrate and generate sound.

The acoustic device is provided with a sound outlet **4**, the sound wave at the front side of the vibrating diaphragm **11** radiates to the outside through the sound outlet **4**, and the sound wave at the rear side of the vibrating diaphragm **11** is retained in the acoustic device. A cavity is formed between the vibrating diaphragm **11**, the housing and the magnetic circuit system. Generally, a rear sound hole is provided on the housing or the magnetic circuit system or between the

housing and the magnetic circuit system, and the sound wave at the rear side of the vibrating diaphragm **11** will enter the interior of the acoustic device through the rear sound hole. In this embodiment, the vibration direction of the vibrating diaphragm **11** of the sound generating unit **1** is parallel to the thickness direction of the acoustic device, which is beneficial to the thin design of the acoustic device.

Further, in this embodiment, a closed first sealed cavity **21** is formed at the rear side of the vibrating diaphragm **11**, the cavity wall of the first sealed cavity **21** is provided with a mounting hole, a flexible deformation part **22** is provided at the mounting hole, a second sealed cavity **31** is provided at outside of the first sealed cavity **21**, and the flexible deformation part **22** is located between the first sealed cavity **21** and the second sealed cavity **31**.

When the vibrating diaphragm **11** vibrates, the internal sound pressure of the first sealed cavity **21** changes, and the flexible deformation part **22** deforms as the sound pressure in the first sealed cavity **21** changes, so as to flexibly adjust the volume of the first sealed cavity; and the second sealed cavity **31** encloses the sound wave generated by the flexible deformation part **22** during deformation in the second sealed cavity **31**.

In this embodiment, at least a part of the housing of the electronic apparatus for mounting the acoustic device is used to form the first sealed cavity **21** and/or the second sealed cavity **31**. Wherein, the electronic apparatus **5** may be a mobile phone, a tablet computer, a notebook computer, etc. That is, part or entire of the cavity walls of the first sealed cavity **21** are composed of the housing of the electronic apparatus, or part or entire of the cavity walls of the second sealed cavity **31** are composed of the housing of the electronic apparatus, or part or entire of the cavity walls of the first sealed cavity **21** and the second sealed cavity **31** are composed of the housing of the electronic apparatus. In the present invention, the housing of the electronic apparatus is also used as the cavity wall of the first sealed cavity and/or the second sealed cavity, which can make full use of the internal space of the electronic apparatus, and meanwhile save a part of the space occupied by the cavity wall, and is more beneficial to the thin design of the electronic apparatus.

It should be noted that the term “closed” or “sealed” described in this embodiment and the present invention may be a completely closed or sealed state or a relatively closed or sealed state in physical structure. For example, according to the use requirements for the product, the first sealed cavity may comprise a pressure equalizing hole **23** provided to balance the internal and external air pressure and have no significant impact on the rapid change of the sound pressure, or other opening structures, and this first sealed cavity is also considered as a sealed cavity. For another example, the second sealed cavity may comprise a gap and the like generated when combined with the first sealed cavity, a gap of its own structure, etc. They can effectively isolate the sound wave generated by the flexible deformation part and have no obvious impact on the sound wave generated by the sound generating unit, therefore, they are also considered as sealed cavities. Generally, the total area of the above opening or gap shall not exceed 20 mm².

Further, a protective cover plate **27** located at outside of the flexible deformation part **22** is further provided on the mounting hole, and an escape space for avoiding vibration of the flexible deformation part **22** is formed between the protective cover plate **27** and the flexible deformation part **22**. The protective cover plate specifically may be made of steel sheet, FR-4 sheet, PET sheet, PEN sheet, carbon fiber sheet, ceramic sheet and so on, and the protective cover plate

itself has a certain hardness and strength, so that it can act to protect the flexible deformation part on the inner side. As a specific embodiment, the protective cover plate 27 is specifically made of stainless-steel material which has high strength and is not easily corroded. The protective cover plate 27 has high strength and can be formed very thin. For example, the thickness of the protective cover plate 27 is less than or equal to 0.2 mm, or even less than or equal to 0.1 mm, thus the protective cover plate 27 does not occupy too much space of the product in Z-axis, and can prevent the flexible deformation part 22 from being damaged or broken by the external environment during the process of transportation or assembly.

In a specific embodiment, the top surface of the protective cover plate 27 is not higher than the top surface of the cavity wall, and the protective cover plate 27 itself is not easily to contact with other components, and thus a better protective effect can be achieved.

In addition, a plurality of air permeable micropores 274 are provided on the protective cover plate 27. Specifically, the air permeable micropores 274 may be formed by means of punching or laser drilling. The air permeable micropores 274 does not isolate the outer space of the flexible deformation part 22 from the external environment, i.e., the second sealed cavity, and the air permeable micropores 274 can realize the pressure balance during the vibration of the flexible deformation part 22.

Specifically, in the present invention, each of the air permeable micropores 274 is required to have an area less than or equal to 0.2 mm², so that the air permeable micropores 274 is capable to prevent liquid and impurities from invading the space between the protective cover plate 27 and the flexible deformation part 22, to avoid the effect on the performance and usage lifespan of the flexible deformation part 22, under the condition of having no effect on the strength of the protective cover plate 27, and therefore, it is no necessary of attaching a dustproof mesh cloth onto the protective cover plate 27, the material costs and the assembly process can be reduced, and the space of the product in the Z-axis can be saved.

The shape of the air permeable micropores 274 is not limited, and may be designed in any shape such as circle, square, and ellipse, etc. In this specific embodiment, the air permeable micropores 274 are circular holes, and the aperture of each of the air permeable micropores 274 is less than or equal to 0.5 mm so that the area of each of the micropores is less than or equal to 0.2 mm². Preferably, the aperture of each of the air permeable micropores 274 is less than or equal to 0.3 mm, for example, the aperture is 0.3 mm, which can have a better dustproof and waterproof effect, and the difficulty and cost of manufacturing micropores are relatively low.

Further, the distance from one side to other side on the line connecting the centers of two adjacent air permeable micropores 274 is greater than or equal to 0.3 mm and less than or equal to 1 mm. Specifically, the distance may be 0.4 mm, 0.5 mm, 0.6 mm, 0.7 mm, etc., taking into account of both the strength of the protective cover plate and the convenience of processing.

The above-described protective cover plate 27 may have the following specific structure. The protective cover plate 27 comprises a fixing surface 273, a protective surface 271 and a connecting wall 272; the fixing surface 273 is disposed on the outer side of the protective surface 271, the fixing surface 273 and the protective surface 271 are located on different planes, the fixing surface 273 are connected with the protective surface 271 by the connecting wall 272, the

fixing surface 273 is fixed on the cavity wall, and the protective surface 271 and/or the connecting wall 272 are provided with the air permeable micropores 274 thereon, wherein an escape space is formed between the protective surface 271 and the flexible deformation part 22. As a preferred solution, the air permeable micropores 274 are provided on both the fixing surface 273 and the protective surface 271.

In order to facilitate mounting, a pallet 24 formed by recessing towards the first sealed cavity 21 may be disposed on the wall of the mounting hole, and the fixing surface 273 is to be fixed on the pallet 24, and specifically the fixing surface 273 may be fixed by applying glue or double-sided tape.

As a specific embodiment, the edge portion of the flexible deformation part 22 is connected to the fixing surface 273 of the protective cover plate 27 at first, and then the assembled member is fixed to the pallet 24 as a whole. The flexible deformation part 22 is combined with the protective cover plate 27 at first, the flexible deformation part 22 has a relatively soft material, the protective cover plate 27 acts to support and fix the flexible deformation part 22, so that it is capable to avoid the abnormal size and deteriorated performance of the flexible deformation part 22 due to deformation, furthermore to optimize the assembly process, and it is capable to realize automatic feeding and improve production efficiency.

On the basis of the above structural design, the sound generating unit 1 may be mounted on the cavity wall of the first sealed cavity 21 at first, and after the cavity wall of the first sealed cavity 21 is assembled, the flexible deformation part 22 and the protective cover plate 27 are then assembled on the cavity wall, thereby the damage to the flexible deformation part 22 due to the apparatus, tooling and environment during the assembly process can be effectively prevented.

As another embodiment, the protective cover plate 27 is fixed on the cavity wall at first, and the flexible deformation part 22 is fixed to the cavity wall from the inner side of the cavity wall. Specifically, the protective cover plate 27 may be fixed on the cavity wall by bonding, or the protective cover plate 27 may be fixed on the cavity wall by injection molding, so that they are integrated and combined, thereby the firmness of the combination can be improved, the automatic assembly can be achieved, and the efficiency can be increased.

As an example, an airflow channel is formed between the connecting wall 272 of the protective cover plate 27 and the side wall of the pallet 24, and the air permeable micropores 274 on the protective cover plate 27 can be communicated with the second sealed cavity by the airflow channel, so as to prevent the phenomenon that the air pressure balance cannot be functioned due to the air permeable micropores 274 being blocked by other components.

Furthermore, the cavity wall of the first sealed cavity 21 comprises a first wall 261 and a second wall 262 connected with the first wall 261, and the mounting hole is located on the first wall 261. The first wall 261 is further provided with a through groove 25 formed by recessing towards the first sealed cavity 21, and the through groove 25 penetrates through the mounting hole and the outer surface of the second wall 262. The above design allows the acoustic waves generated by the vibration of the flexible deformation part 22 to pass through the air permeable micropores 274 on the protective cover plate 27 and furthermore pass through the through groove 25 to be transferred into the second sealed cavity 31, or allows the acoustic waves generated by

the vibration of the flexible deformation part 22 to pass through the air permeable micropores 274 on the protective cover plate 27, the above-described air flow channel and furthermore pass through the through groove 25 to be transferred into the second sealed cavity 31. Therefore, the above structure can avoid the problem that, a good air permeable effect cannot be achieved because the surface of the protective cover plate 27 facing the second sealed cavity 31 is blocked by other components located in the second sealed cavity 31 during assembly, as a result, the sensitivity at low-frequency bands is increased in a relatively low level or the sensitivity cannot normally function.

As a specific embodiment, the acoustic device comprises a first housing 2, the sound generating unit 1 is mounted on the first housing 2 to form a sound generating assembly, the first sealed cavity 21 is formed between the vibrating diaphragm 11 of the sound generating unit 1 and the first housing 2, the mounting hole is provided on the first housing 2, the flexible deformation part 22 is provided at the mounting hole, the number of mounting holes and flexible deformation parts 22 are not limited to one group, and a plurality of groups of mounting holes and flexible deformation parts may be provided at different positions of the first housing 2. The acoustic device comprises a second housing 3, the sound generating assembly is mounted in the second housing 3, and the second sealed cavity 31 is formed between the second housing 3 and the first housing 1. Wherein, in the case that there are other components in the second housing 3, the second sealed cavity 31 is actually composed of a gap between the other components, the second housing 3 and the first housing 2.

In this embodiment, the sound generating unit 1 is provided inside the first housing 2, and the sound generating unit 1 and the first housing 2 form an integral structure, this integral structure is then assembled with the second housing 3. The first housing 2 is provided with an opening, the front space of the diaphragm is communicated with the opening, and the sound radiates to the sound outlet 4 of the acoustic device through the opening.

In one embodiment, the acoustic device is mounted in the electronic apparatus such as a mobile phone, and the housing of the electronic apparatus also serves as the second housing 3 of the acoustic device. The space between the housing of the electronic apparatus and the internal components as well as the space between the housing of the electronic apparatus and the first housing 2 of the acoustic device form the second sealed cavity 31, so that the second housing of the acoustic device itself is omitted, and the gap space between the housing of the electronic apparatus and the components is fully utilized, therefore, the maximum design of the second sealed cavity 31 can be realized.

As shown in FIG. 4, in one specific embodiment, the first housing 2 comprises a top wall, a bottom wall and a side wall connected between the top wall and the bottom wall, wherein the top wall or the bottom wall is the first wall 261, and the side wall is the second wall 262. In this specific embodiment, the top wall is the first wall 261, the mounting hole is located at the top wall, a pallet 24 formed by recessing towards the first sealed cavity 21 is provided at the top wall around the mounting hole, the flexible deformation part 22 is fixed at the groove bottom of the pallet 24, a through groove 25 formed by recessing towards the first sealed cavity 21 is further provided at the top wall, the through groove 25 passes through the pallet 24 and the outer surface of the side wall. In other embodiments, the side wall may be the first wall, the top wall or the bottom wall may be the second wall, the mounting hole, the groove and the

through groove are provided at the side wall, and the through groove passes through the pallet 24 and the outer surface of the top wall/bottom wall.

In the state that the acoustic device is in operation, when the vibrating diaphragm 11 vibrates downward to compress the volume at the rear side of the vibrating diaphragm 11, the sound pressure will be transmitted to the flexible deformation part 22 through the first sealed cavity 21, and the flexible deformation part 22 will expand and deform towards the outside of the first sealed cavity 21; on the contrary, when the diaphragm vibrates upward, the flexible deformation part 22 will shrink and deform inward, to adjust the volume of the first sealed cavity 21 so as to increase the equivalent acoustic compliance of the first sealed cavity 21, effectively reduce the resonance frequency of the acoustic device and improve the low-frequency sensitivity. Through the isolation design of the sound generating unit 1 and the flexible deformation part 22, the radiated sound wave of the flexible deformation part 22 is enclosed in the acoustic device, to avoid the offset effect on the forward radiated sound wave of the sound generating unit 1 due to the anti-phase radiated sound wave of the flexible deformation part 22, and thus the low-frequency sensitivity of the product is greatly improved as a whole.

Specifically, the flexible deformation part 22 comprises a body part 221, and the body part 221 may have a single-layer structure made of one of polymer plastic, thermoplastic elastomer and silicone rubber, alternatively, the body part 221 may have a multi-layer structure, and at least one layer in the multi-layer structure is made of one of polymer plastic, thermoplastic elastomer and silicone rubber.

The body part 221 may have a flat plate structure, which is beneficial to reducing the height of the flexible deformation part 22 and reducing the space occupied by the flexible deformation part 22. The body part 221 may also have a partially convex or concave structure, for example, a structure with a convex center portion, a convex edge portion, or a combination of a convex center portion and a convex edge portion; alternatively, at least the edge portion of the body part 221 has a wavy structure. In one specific embodiment, as shown in FIG. 3B, the edge portion of the body part 221 is provided with a protrusion 222, and the protrusion 222 protrudes from the first sealed cavity 21 towards the second sealed cavity 31; alternatively, the protrusion 222 protrudes from the second sealed cavity 31 towards the first sealed cavity 21. The protrusion structure can provide greater elastic deformation, increase the vibration displacement of the flexible deformation part 22, and improve the volume adjustment effect on the first sealed cavity 21. Further, in order to improve the vibration effect, a composite sheet 223 may be superimposed at the central position of the body part 221 of the flexible deformation part 22, the strength of the composite sheet 223 is higher than that of the body part 221, and the composite sheet 223 may be consists of metal, plastic, carbon fiber or may be a composite structure thereof, etc. In addition, the body part 221 of the flexible deformation part 22 may have a sheet-like overall structure, or the central position of the body part 221 may be hollowed out, and the portion hollowed out is enclosed through the composite sheet 223. In the case that the center hollowed-out structure of the body part 221 of the flexible deformation part 22 only retains the edge portion, the edge portion may have a flat plate shape, a shape convex towards one side, or a wavy shape.

As a specific embodiment, the flexible deformation part 22 may be integrated with other parts of the first housing 2. The flexible deformation part 22 may be manufactured at

11

first, and then the flexible deformation part 22 may be integrally injected and molded as an insert member into the other parts of the housing. Alternatively, the flexible deformation part 22 is fixedly connected with the portion of the first housing around the mounting hole by bonding, welding or hot melting.

In this embodiment, the main body of the first sealed cavity 21 and the main body of the second sealed cavity 31 extend along a horizontal direction defined by the length and width of the acoustic device, and the horizontal direction may also be defined as a direction perpendicular to the thickness direction of the acoustic device. The horizontal direction generally refers to the direction parallel to a horizontal plane when the acoustic device is placed on the horizontal plane, and the two cavities are provided along the horizontal direction, such that not occupy the space in the height direction of the acoustic device as much as possible, which is beneficial to the thin design of the product.

The second housing 3 has a top wall, a bottom wall and a side wall connecting the top wall and the bottom wall, and the sound outlet 4 of the acoustic device is provided at the top wall, the bottom wall or the side wall of the second housing. As shown in FIG. 3, in this embodiment, the sound outlet 4 is provided at the top wall of the second housing, and the pressure equalizing hole 23 is provided on the first sealed cavity 21.

In the technical solution of this embodiment, in the acoustic device, by providing the flexible deformation part 22, the flexible deformation part 22 deforms with the sound pressure, and the volume of the first sealed cavity 21 is adjustable, to increase the equivalent acoustic compliance of the first sealed cavity 21, effectively reduce the resonance frequency of the acoustic device, and improve the low-frequency sensitivity; and the sound radiation generated by the flexible deformation part 22 during the deformation is isolated by the second sealed cavity 31, and the radiated sound wave of the flexible deformation part 22 is enclosed in the acoustic device, so as to avoid the offset effect on the forward radiated sound wave of the sound generating unit 1 due to the anti-phase radiated sound wave of the flexible deformation part 22, and thus the low-frequency sensitivity of the product is greatly improved as a whole.

Moreover, in this embodiment, the volume of the second sealed cavity 31 is greater than that of the first sealed cavity 21, which can make the deformation of the flexible deformation part 22 easier, and is more beneficial to increasing the equivalent acoustic compliance of the first sealed cavity 21, effectively reducing the resonance frequency of the acoustic device, and improving the low-frequency sensitivity.

In the prior art 1, the compliance of the acoustic device is composed of the compliance of the sound generating unit and the compliance of the sealed cavity in the housing in parallel. The formula f_s in the prior art 1 is as follows:

$$f_s = \frac{1}{2 * \pi} \sqrt{\frac{C_{as} + C_{ab}}{C_{as} * C_{ab} * M_{ac}}}$$

wherein f_s : the resonance frequency of the acoustic device; C_{as} : the equivalent acoustic compliance of the sound generating unit; C_{ab} : the equivalent acoustic compliance of the air in the housing; M_{ac} : the equivalent sound quality of the vibrating system of the sound generating unit.

12

In the prior art 2 and this embodiment, as shown in FIG. 2 and FIG. 5, FIG. 2 shows the test curves of loudness (SPL curves) at different frequencies for the acoustic device provided with the passive radiator in the prior art 2 and the acoustic device with a traditional structure in the prior art 1, FIG. 5 shows the test curves of loudness (SPL curves) at different frequencies for the acoustic device according to this embodiment and the acoustic device in the prior art 1, and the final equivalent compliance increases because the sound generating unit is further connected with the compliance of a passive radiator/flexible deformation part 22 in parallel, therefore F_0 decreases. The formula f_s in the prior art 2 and this embodiment is as follows:

$$f_s = \frac{1}{2 * \pi} \sqrt{\frac{C_{as} + C_{ab} + C_{ap}}{C_{as} * C_{ab} * C_{ap} * M_{ac}}}$$

wherein f_s : the resonance frequency of the acoustic device; C_{as} : the equivalent acoustic compliance of the sound generating unit; C_{ab} : the equivalent acoustic compliance of the air in the first sealed cavity; M_{ac} : the equivalent sound quality of the vibrating system of the sound generating unit; C_{ap} : the equivalent acoustic compliance of the passive radiator/flexible deformation part.

Moreover, in the prior art 2, the sound generating unit and the passive radiator radiate sound at the same time, the phases of the sound waves of the sound generating unit and the passive radiator are opposite to each other at the frequency below the resonance point f_p , and the sound pressures of the sound generating unit and the passive radiator offset with each other, the passive radiator has a negative effect on the sensitivity of the acoustic system.

Further, in this embodiment, as shown in FIG. 6, FIG. 6 shows the test curves of loudness (SPL curves) at different frequencies for the acoustic device according to this embodiment and the acoustic device provided with the passive radiator in the prior art 2. By providing the closed second sealed cavity 31, the second sealed cavity 31 retains the sound wave generated at the rear side of the diaphragm sheet of the acoustic device in the interior of the acoustic device. Specifically, the sound pressure generated by the flexible deformation part 22 is isolated by the second sealed cavity 31, so as to avoid the offset effect on the forward radiated sound wave of the sound generating unit due to the anti-phase radiated sound wave generated by the deformation of the flexible deformation part 22, and thus the low-frequency sensitivity of the product is greatly improved as a whole.

Embodiment 2

The main difference between this embodiment and the above embodiment is that: in this embodiment, a plurality of sound generating units 1 and a plurality of first sealed cavities 21 are provided in a one-to-one correspondence, one second sealed cavity 31 is provided, and the cavity wall of each of the first sealed cavities 21 is provided with one flexible deformation part 22 and one protective cover plate 27. Specifically, the acoustic device in this embodiment comprises two sound generating units 1, in the meanwhile, two first sealed cavities 21 are provided and designed correspondingly, one second sealed cavity 31 is provided, and the cavity wall of each of the two first sealed cavities 21 is provided and designed with a flexible deformation part 22 and a protective cover plate 27. This design can facilitate the

13

application in the case of acoustic devices or systems requiring a plurality of sound generating units 1, for example, the design requirements of stereo or array form.

In another embodiment, at least two groups of flexible deformation parts 22 and protective cover plates 27 may be provided on the same side wall or on different side walls of the cavity wall of the first sealed cavity 21 by one-to-one correspondence relationship.

Embodiment 3

This embodiment discloses an electronic apparatus 5, as shown in FIG. 7, the acoustic device 100 in the above embodiments is mounted on the electronic apparatus 5. The electronic apparatus 5 may be a mobile phone, tablet computer, notebook computer, etc.

The electronic apparatus 5 specifically comprises a housing of the electronic apparatus, and at least a part of the housing of the electronic apparatus is used to form the first sealed cavity 21 and/or the second sealed cavity 31 of the acoustic device. That is, part or entire of the cavity walls of the first sealed cavity 21 are composed of the housing of the electronic apparatus, or part or entire of the cavity walls of the second sealed cavity 31 are composed of the housing of the electronic apparatus, or part or entire of the cavity walls of the first sealed cavity 21 and the second sealed cavity 31 are composed of the housing of the electronic apparatus. In the present invention, the housing of the electronic apparatus is also used as the cavity wall of the first sealed cavity 21 and/or the second sealed cavity 31, which can make full use of the space inside the electronic apparatus, save a part of the space occupied by the cavity wall, and is more beneficial to the thin design of the electronic apparatus.

In this specific embodiment, the acoustic device comprises a first housing 2, the sound generating unit 1 is mounted on the first housing 2 to form a sound generating assembly, the first sealed cavity 21 is formed between the vibrating diaphragm 11 of the sound generating unit 1 and the first housing 2, the mounting hole is provided on the first housing 2, and the flexible deformation part 22 and the protective cover plate 27 are provided at the mounting hole, the number of mounting holes, flexible deformation parts 22 and protective cover plate are not limited to one group, and a plurality of groups of mounting holes and flexible deformation parts may be provided at different positions of the first housing 2. The acoustic device further comprises a second housing 3, the sound generating assembly is mounted in the second housing 3, and the second sealed cavity 31 is formed between the second housing 3 and the first housing 1. Here, the second housing 3 is the housing of the electronic apparatus. In fact, the space between the housing of the electronic apparatus and the internal components as well as the space between the housing of the electronic apparatus and the first housing 2 of the acoustic device form the second sealed cavity 31. The housing of the electronic apparatus also serves as the second housing 3 of the acoustic device, so that the second housing of the acoustic device itself is omitted, and the gap space between the housing of the electronic apparatus and the components is fully utilized, therefore the maximum design of the second sealed cavity 31 can be realized, which is beneficial to the thin design of electronic apparatus.

Although some specific embodiments of the present invention have been described in detail by examples, those skilled in the art should understand that the above examples are only for illustration, not to limit the scope of the present invention. Those skilled in the art should understand that the

14

above embodiments may be modified without departing from the scope and spirit of the present invention. The scope of the present invention is defined by the appended claims.

What is claimed is:

1. An acoustic device, comprising a sound generating unit, the sound generating unit comprises a vibrating diaphragm, the acoustic device is provided with a sound outlet, and a sound wave at a front side of the vibrating diaphragm radiates to outside through the sound outlet,

wherein a first sealed cavity is formed at a rear side of the vibrating diaphragm, a cavity wall of the first sealed cavity is provided with a mounting hole, a flexible deformation part is provided at the mounting hole, a second sealed cavity is provided at outside of the first sealed cavity, the flexible deformation part is located between the first sealed cavity and the second sealed cavity, and the second sealed cavity seals a sound wave, which is generated by the flexible deformation part during deformation, in the second sealed cavity,

wherein a protective cover plate located at outside of the flexible deformation part is further provided on the mounting hole, and an escape space used for avoiding vibration of the flexible deformation part is formed between the protective cover plate and the flexible deformation part; and

wherein a plurality of air permeable micropores are provided on the protective cover plate, and each of the air permeable micropores has an area less than or equal to 0.2 mm².

2. The acoustic device according to claim 1, wherein thickness of the protective cover is less than or equal to 0.2 mm, the air permeable micropores are circular holes, and apertures of the air permeable micropores are less than or equal to 0.5 mm.

3. The acoustic device according to claim 2, wherein the apertures of the air permeable micropores are less than or equal to 0.3 mm.

4. The acoustic device according to claim 1, wherein a distance from one side to another side on a line connecting centers of two adjacent air permeable micropores is greater than or equal to 0.3 mm and less than or equal to 1 mm.

5. The acoustic device according to claim 1, wherein the protective cover plate is made of one of steel sheet, FR-4 sheet, PET sheet, PEN sheet, carbon fiber sheet and ceramic sheet.

6. The acoustic device according to claim 1, wherein a top surface of the protective cover plate is not higher than a top surface of the cavity wall.

7. The acoustic device according to claim 1, wherein the protective cover plate comprises a fixing surface, a protective surface and a connecting wall, the fixing surface and the protective surface are located on different planes, the fixing surface are connected with the protective surface by the connecting wall, the fixing surface is fixed on the cavity wall, and the air permeable micropores are provided on the protective surface and/or the connecting wall.

8. The acoustic device according to claim 7, wherein a pallet formed by recessing towards the first sealed cavity is provided on a wall of the mounting hole, and the fixing surface is fixed on the pallet.

9. The acoustic device according to claim 8, wherein an edge portion of the flexible deformation part and the fixing surface of the protective cover plate are connected, and then the edge portion of the flexible deformation part and the fixing surface of the protective cover plate as a whole are fixed to the pallet.

15

10. The acoustic device according to claim 1, wherein the protective cover plate is fixed on the cavity wall, and then the flexible deformation part is fixed to the cavity wall from an inner side of the cavity wall, and

wherein the protective cover plate is fixed on the cavity wall by bonding, or the protective cover plate is fixed on the cavity wall by injection molding.

11. The acoustic device according to claim 8, wherein an airflow channel is formed between the connecting wall and a side wall of the pallet.

12. The acoustic device according to claim 1, wherein the cavity wall comprises a first wall and a second wall connected with the first wall, the mounting hole is located at the first wall, a through groove formed by recessing towards the first sealed cavity is further provided at the first wall, and the through groove penetrates through the mounting hole and an outer surface of the second wall.

13. The acoustic device according to claim 1, wherein the flexible deformation part comprises a body part, the body part has a flat plate structure, or at least an edge portion of the body part is provided with a protrusion, or at least an edge portion of the body part has a wavy structure, and wherein the flexible deformation part further comprises a composite sheet combined with the body part at a

16

central position of the body part, and the body part has a sheet overall structure or the central position of the body part is hollowed out.

14. The acoustic device according to claim 1, wherein at least a portion of a housing of an electronic apparatus for mounting the acoustic device is used to form the first sealed cavity and/or the second sealed cavity.

15. The acoustic device according to claim 14, wherein the acoustic device comprises a first housing, the sound generating unit is mounted on the first housing to form a sound generating assembly, the first sealed cavity is formed between the vibrating diaphragm of the sound generating unit and the first housing, the first housing is provided with the mounting hole, and the flexible deformation part is provided at the mounting hole, and

wherein the acoustic device comprises a second housing, the sound generating assembly is mounted in the second housing, the second sealed cavity is formed between the second housing and the first housing, and the second housing is a housing of an electronic apparatus.

16. An electronic apparatus, comprising a housing of the electronic apparatus and the acoustic device according to claim 1 mounted in the housing.

* * * * *