

(19)



(11)

EP 3 678 389 B1

(12)

EUROPEAN PATENT SPECIFICATION

(45) Date of publication and mention of the grant of the patent:
08.11.2023 Bulletin 2023/45

(51) International Patent Classification (IPC):
H04W 68/02^(2009.01) H04W 4/08^(2009.01)

(21) Application number: **17923618.7**

(52) Cooperative Patent Classification (CPC):
H04W 4/08; H04W 68/02

(22) Date of filing: **30.08.2017**

(86) International application number:
PCT/CN2017/099566

(87) International publication number:
WO 2019/041152 (07.03.2019 Gazette 2019/10)

(54) PAGING MESSAGE SENDING METHOD AND APPARATUS

VERFAHREN UND VORRICHTUNG ZUM SENDEN VON FUNKRUFNACHRICHTEN

APPAREIL ET PROCÉDÉ D'ENVOI DE MESSAGES DE RADIOMESSAGERIE

(84) Designated Contracting States:
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

(74) Representative: **dompatent von Kreisler Selting Werner - Partnerschaft von Patent- und Rechtsanwälten mbB Deichmannhaus am Dom Bahnhofsvorplatz 1 50667 Köln (DE)**

(43) Date of publication of application:
08.07.2020 Bulletin 2020/28

(73) Proprietor: **Beijing Xiaomi Mobile Software Co., Ltd. Beijing 100085 (CN)**

(56) References cited:
**EP-A1- 2 369 883 CN-A- 102 761 826
CN-A- 102 857 869 CN-A- 105 792 141**

(72) Inventor: **LIU, Yang Haidian District Beijing 100085 (CN)**

EP 3 678 389 B1

Note: Within nine months of the publication of the mention of the grant of the European patent in the European Patent Bulletin, any person may give notice to the European Patent Office of opposition to that patent, in accordance with the Implementing Regulations. Notice of opposition shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

Description

TECHNICAL FIELD

[0001] The present disclosure relates to the field of communication technologies, and in particular, to a method and device for sending and receiving a paging and a base station.

BACKGROUND

[0002] With the rapid development of wireless communication technologies, 5th generation mobile communication technology (5G) systems have appeared. The 5G systems will be targeted at high-frequency applications, that is, applications at above 6 GHz. In a high-frequency band, because a propagation characteristic of a radio wave is not ideal, traditional omnidirectional transmission will no longer be applicable, and beam scanning and beam management need to be introduced for communications.

[0003] There are different types of UEs in the 5G system. One important type is low-latency UEs. Such UEs have high requirements on latency and shall not consume too much power. A main function of paging is to notify the user equipment (UE) in an idle state of a connection request, and to notify the UE in the idle and connected state of that a system message has changed. A paging message is mapped to a physical downlink shared channel (PDSCH), and the UE may obtain the paging message by monitoring a physical downlink control channel (PDCCH) of the PDSCH. When the UE monitors that the PDCCH has paging scheduling, it receives the PDSCH according to the PDCCH information, thereby obtaining paging information.

[0004] In the 5G system, when the paging message are sent on multiple beams, it is a waste of resources. In the related art, a paging indication (PI) is sent to notify one or more groups of a paging arrival, and the notified one or more groups of UEs monitor corresponding PDCCH and PDSCH to obtain the paging message. However, generally, most groups have at least one UE that has paging, that is, most groups need to monitor the paging message, which is still a waste of resources.

[0005] Related art can be found in EP Patent Application EP2369883A1 in which it is disclosed that for addressing different groups of MTCs, each MTC is provided with two IDs: its IMSI and a pseudo IMSI.

SUMMARY

[0006] The invention is set out in the appended set of claims. Additional features of the invention are provided in the dependent claims.

[0007] According to a first aspect, there is provided a method for sending a paging message, which is applied to a base station, including: determining that a current user equipment UE belongs to a first service group or a

second service group, if there is a paging request for the current UE, the first service group including a first large service group or a first small service group, the second service group including a second large service group or a second small service group, the first large service group including at least one of the first small service group, and the second large service group including at least one of the second small service group; sending a first paging message to all UEs in the first small service group to which the current UE belongs through one of a plurality of first paging occasions POs according to first configuration information which is pre-generated, if the current UE belongs to the first service group; and carrying a paging indication through one of the plurality of first POs and sending a second paging message to the UE indicated by the paging indication through one second PO according to second configuration information which is pre-generated, if the current UE belongs to the second service group, wherein the paging indication is configured to indicate an identification of all the UEs in the second small service group to which the current UE belongs.

[0008] In an embodiment, the method further includes, before the determining that a current user equipment UE belongs to a first service group or a second service group: receiving a first service request sent by the UE, and sending the first service request to a core network; and receiving the identification of the UE belonging to the first large service group returned by the core network according to the first service request, and classifying the identification of the UE not belonging to the first large service group to the second large service group.

[0009] In an embodiment, the method further includes, after the classifying the identification of the UE not belonging to the first large service group to the second large service group: dividing the first large service group into at least one of the first small service group, and dividing the second large service group into at least one of the second small service group.

[0010] In an embodiment, the method further includes, before the sending a first paging message to all UEs of the first small service group to which the current UE belongs through one of a plurality of first paging occasions POs according to first configuration information which is pre-generated: generating the first configuration information and the second configuration information, and sending the first configuration information and the second configuration information to the UE. The first configuration information includes one of the plurality of first POs allocated to the UE belonging to the first service group, and a physical downlink control channel PDCCH and a physical downlink shared channel PDSCH corresponding to an allocated first PO and being configured to transmit the first paging message. The second configuration information includes the identification of the first PO for carrying the paging indication, the second PO allocated to the UE belonging to the second service group, and the PDCCH and the PDSCH corresponding to the second PO and being configured to transmit the second paging message.

[0011] According to a second aspect, there is provided a method for receiving a paging message, which is applied to a user equipment UE, including: determining that a current user equipment UE belongs to a first service group or a second service group, the first service group including a first large service group or a first small service group, and the second service group including a second large service group or a second small service group; analyzing one of a plurality of first paging occasions POs according to first configuration information which is pre-received to obtain a first paging message, if the current UE belongs to the first service group; and analyzing second configuration information which is pre-received to obtain a paging indication, and analyzing a second PO to obtain a second paging message when an identification of the current UE is located in the identifications of the UE indicated by the paging indication, if the current UE belongs to the second service group.

[0012] In an embodiment, the method further includes: receiving the first configuration information and the second configuration information sent by a base station. The first configuration information includes one of the plurality of first POs allocated to the UE belonging to the first service group, and a physical downlink control channel PDCCH and a physical downlink shared channel PDSCH corresponding to an allocated first PO and being configured to transmit the first paging message. The second configuration information includes the identification of the first PO for carrying the paging indication, the second PO allocated to the UE belonging to the second service group, and the PDCCH and the PDSCH corresponding to the second PO and being configured to transmit the second paging message.

[0013] In an embodiment, the analyzing one of a plurality of first paging occasions PO according to first configuration information which is pre-received to obtain a first paging message includes: analyzing the PDCCH, corresponding to the first PO configured by the first configuration information and being configured to transmit the first paging message, to obtain paging control information; and analyzing the PDSCH, corresponding to the first PO configured by the first configuration information and being configured to transmit the first paging message, according to the paging control information to obtain the first paging message.

[0014] In an embodiment, the analyzing a second PO to obtain a second paging message includes: analyzing the PDCCH, corresponding to the second PO and being configured to transmit the second paging message, to obtain paging control information; and analyzing the PDSCH, corresponding to the second PO and being configured to transmit the second paging message, according to the paging control information to obtain the second paging message.

[0015] According to a third aspect of embodiments, there is provided a base station, including: a processor; and a memory having instructions stored thereon, which are executable by the processor. The processor is con-

figured to: determine that a current UE belongs to a first service group or a second service group, if there is a paging request for the current UE, the first service group including a first large service group or a first small service group, the second service group including a second large service group or a second small service group, the first large service group including at least one of the first small service group, and the second large service group including at least one of the second small service group; send a first paging message to all UEs in the first small service group to which the current UE belongs through one of a plurality of first paging occasions POs according to first configuration information which is pre-generated, if the current UE belongs to the first service group; and carry a paging indication through one of the plurality of first POs and send a second paging message to the UE indicated by the paging indication through one second PO according to second configuration information which is pre-generated, if the current UE belongs to the second service group, wherein the paging indication is configured to indicate an identification of all the UEs in the second small service group to which the current UE belongs.

[0016] According to a fourth aspect, there is provided a user equipment, including: a processor; and a memory having instructions stored thereon, which are executable by the processor. The processor is configured to: determine that a current UE belongs to a first service group or a second service group, the first service group including a first large service group or a first small service group, and the second service group including a second large service group or a second small service group; analyze one of a plurality of first paging occasions POs according to first configuration information which is pre-received to obtain a first paging message, if the current UE belongs to the first service group; and analyze second configuration information which is pre-received to obtain a paging indication, and analyze a second PO to obtain a second paging message when an identification of the current UE is located in the identifications of the UE indicated by the paging indication, if the current UE belongs to the second service group.

[0017] The technical solutions provided by the embodiments of the present disclosure may include the following beneficial effects.

[0018] By sending a first paging message to all UEs in a first small service group to which a current UE belongs through one of a plurality of first paging occasions POs according to first configuration information which is pre-generated, and carrying a paging indication through one of the plurality of first POs and sending a second paging message to the UE indicated by the paging indication through one second PO according to second configuration information which is pre-generated, both a low low-latency paging requirement of a low-latency UE and a paging requirement of a non-low-latency UE can be satisfied, and resources can be saved effectively.

[0019] When the current UE belongs to a first service group, one of a plurality of first paging occasions POs is

analyzed according to first configuration information which is pre-received to obtain a first paging message; and when the current UE does not belong to the first service group, second configuration information which is pre-received is analyzed to obtain a paging indication and a second PO is analyzed to obtain a second paging message when an identification of the current UE is located in the identifications of the UE indicated by the paging indication, which can save resources effectively.

[0020] It is to be understood that both the foregoing general description and the following detailed description are exemplary and explanatory only and are not restrictive of the present disclosure.

BRIEF DESCRIPTION OF THE DRAWINGS

[0021] The accompanying drawings herein which are incorporated into and constitute part of the description.

FIG. 1 is a flowchart of a method for sending a paging message;

FIG. 2 is a schematic diagram illustrating a plurality of first POs allocated to a UE belonging to a first service group and a second PO allocated to the UE belonging to a second service group;

FIG. 3A is a flowchart of another method for sending a paging message;

FIG. 3B is a flowchart of another method for sending a paging message;

FIG. 3C is a flowchart of another method for sending a paging message;

FIG. 4 is a flowchart of a method for receiving a paging message;

FIG. 5 is a flowchart of another method for receiving a paging message;

FIG. 6 is a signaling flowchart of a method for receiving a paging message;

FIG. 7 is a block diagram of a device for sending a paging message;

FIG. 8A is a block diagram of another device for sending a paging message;

FIG. 8B is a block diagram of another device for sending a paging message;

FIG. 8C is a block diagram of another device for sending a paging message;

FIG. 9 is a block diagram of a device for receiving a

paging message;

FIG. 10A is a block diagram of another device for receiving a paging message;

FIG. 10B is a block diagram of another device for receiving a paging message;

FIG. 10C is a block diagram of another device for receiving a paging message;

FIG. 11 is a block diagram illustrating a device suitable for sending a paging message; and

Fig. 12 is a block diagram illustrating a device suitable for receiving a paging message.

DETAILED DESCRIPTION

[0022] Exemplary embodiments will be described in detail herein, examples of which are illustrated in the accompanying drawings. When the following description refers to the accompanying drawings, the same reference numerals in different drawings represent the same or similar elements unless otherwise indicated. The implementations described in the following exemplary embodiments do not represent all implementations consistent with the present disclosure. Rather, they are merely examples of devices and methods consistent with some aspects of the present disclosure as detailed in the appended claims. The invention corresponds to the disclosure of fig. 1, 11 and the related text. The remaining part of the figures and the description is only intended to better understand the claimed invention.

[0023] FIG. 1 is a flowchart of a method for sending a paging message according to an exemplary embodiment of the present application. This embodiment is described from a base station side. As shown in FIG. 1, the method for sending a paging message includes the following steps.

[0024] In step S101, if there is a paging request for a current UE, it is determined that the current UE belongs to a first service group or a second service group. If the current UE belongs to the first service group, step S 102 is performed; and if the current UE belongs to the second service group, step S 103 is performed.

[0025] The first service group includes a first large service group or a first small service group, and the second service group includes a second large service group or a second small service group.

[0026] In the embodiment, a first service refers to a low-latency service. A UE belonging to a low-latency large or small service group may include, but is not limited to, the UE requesting service such as ultra-reliable low-latency communication (URLLC), augmented reality (AR), or virtual reality (VR), and may also include the UE with a subscriber identification module (SIM) card. A second service refers to a non-low-latency service.

[0027] In step S102, a first paging message is sent to all UEs in the first small service group to which the current UE belongs through one of a plurality of first POs according to first configuration information which is pre-generated.

[0028] In order to reduce waste of resources and at the same time to reduce effect on the low-latency service, in the embodiment, a plurality of first POs may be provided for the low-latency UE in each cycle, and one second PO is provided for the non-low-latency UE. For example, as shown in FIG. 2, two first POs are provided for the low-latency UE in each cycle, and the two first POs are referred to as a first PO 21 and a first PO 22 respectively for distinction, and one second PO 23 is provided for the non-low-latency UE.

[0029] The first configuration information includes one of the plurality of first POs allocated to the UE belonging to the first service group, and a PDCCH and a PDSCH corresponding to an allocated first PO and being configured to transmit the first paging message. For example, as shown in FIG. 2, the one first PO allocated to a UE1 assumed as the UE of the first service group is a first PO 21, the PDCCH corresponding to the first PO 21 and being configured to transmit the first paging message is PDCCH 24, and the PDSCH corresponding to the first PO 21 and being configured to transmit the first paging message is PDSCH 25.

[0030] In the embodiment, when the first service group is the first large service group, the base station may reduce resource consumption by sending the first paging message to all UEs of the first small service group to which the current UE belongs. When the first service group is the first small service group, the base station may reduce the resource consumption by sending the first paging message to all the UEs of the first small service group to which the current UE belongs. For example, if the first large service group includes 10 first small service groups, and each of the first small service groups includes 3 UEs, the base station only needs to send the first paging message to the 3 UEs in the first small service group where the current UE is located, and needs not to send the first paging message to all the UEs (i.e., the 30 UEs) in the first large service group, thereby reducing the resource consumption.

[0031] In step S103, according to second configuration information which is pre-generated, a paging indication is carried through one of the plurality of first POs and a second paging message is sent to the UE indicated by the paging indication through one second PO. The paging indication is configured to indicate an identification of all the UEs in the second small service group to which the current UE belongs.

[0032] The second configuration information includes the identification of the first PO for carrying the paging indication, the second PO allocated to the UE belonging to the second service group, and the PDCCH and the PDSCH corresponding to the second PO and being configured to transmit the second paging message. For ex-

ample, as shown in FIG. 2, the first PO for carrying the paging indication 26 is the first PO 22, the second PO allocated to a UE 3 assumed as the UE belonging to the second service group is the second PO 23, the PDCCH corresponding to the second PO 23 and being configured to transmit the second paging message is PDCCH 27, and the PDSCH corresponding to the second PO 23 and being configured to transmit the second paging message is PDSCH 28.

[0033] In the embodiment, when the second service group is the second large service group, the paging indication may be used to indicate the identification of all the UEs in the second small service group to which the current UE belongs. When the second service group is the second small service group, the paging indication may be used to indicate the identification of all the UEs in the second small service group to which the current UE belongs, that is, the paging indication is used to notify all the UEs in the second small service group to which the current UE belongs to analyze the second PO, instead of notifying all the UEs belonging to the second large service group to analyze the second PO, which can effectively save resources.

[0034] It should be noted that the first PO for carrying the paging indication and the first PO for sending the first paging message in step S102 are not necessarily the same.

[0035] In the above embodiment, by sending a first paging message to all UEs in a first small service group to which a current UE belongs through one of a plurality of first paging occasions POs according to first configuration information which is pre-generated, and carrying a paging indication through one of the plurality of first POs and sending a second paging message to the UE indicated by the paging indication through one second PO according to second configuration information which is pre-generated, both a low low-latency paging requirement of a low-latency UE and a paging requirement of a non-low-latency UE can be satisfied, and resources can be saved effectively.

[0036] FIG. 3A is a flowchart illustrating another method for sending a paging message according to an exemplary embodiment of the present application. As shown in FIG. 3A, before the above step S101, the method for sending a paging message may further include the following steps.

[0037] In step S301, a first service request sent by the UE is received, and the first service request is sent to a core network.

[0038] In the embodiment, the base station may receive the first service request sent by the UE and send the first service request to the core network. The first service may include, but is not limited to, services such as URLLC, AR, or VR.

[0039] In step S302, the identification of the UE belonging to the first large service group returned by the core network according to the first service request is received, and the identification of the UE not belonging to

the first large service group is classified to the second large service group.

[0040] After receiving the first service request from a plurality of UEs, the core network may classify all the UEs requesting the first service to a first large service group, and return the identification of the UEs belonging to the first large service group to the base station. At the same time, the identification of the UEs not belonging to the first large service group may be classified to the second large service group.

[0041] In the above embodiment, by receiving the first service request sent by the UE, and sending the first service request to the core network, and then receiving the identification of the UE belonging to the first large service group returned by the core network according to the first service request, and classifying the identification of the UE not belonging to the first large service group to the second large service group, a condition under which a paging message is sent subsequently according to the first large service group or the second large service group is provided.

[0042] FIG. 3B is a flowchart of another method for sending a paging message according to an exemplary embodiment of the present application. As shown in FIG. 3B, after the above step S302, the method for sending a paging message may further include the following steps.

[0043] In step S303, the first large service group is divided into at least one first small service group, and the second large service group is divided into at least one second small service group.

[0044] In the above embodiment, the first large service group is divided into at least one first small service group, and the second large service group is divided into at least one second small service group, such that the number of UEs included in the first or second small service group is smaller, thereby providing a condition for subsequently sending a paging messages according to the first or second small service group to which the UE belongs.

[0045] FIG. 3C is a flowchart of another method for sending a paging message according to an exemplary embodiment of the present application. As shown in FIG. 3C, before the above step S101, the method for sending a paging message may further include the followings steps.

[0046] In step S100, the first configuration information and the second configuration information are generated, and the first configuration information and the second configuration information are sent to the UE.

[0047] In the embodiment, the base station may generate the first configuration information and the second configuration information, thereby providing a condition for subsequently sending the first paging message according to the first configuration information and sending the second paging message according to the second configuration information.

[0048] In the above embodiment, by generating the first and second configuration information, a condition for subsequently sending the first paging message accord-

ing to the first configuration information and sending the second paging message according to the second configuration information is provided.

[0049] FIG. 4 is a flowchart illustrating a method for receiving a paging message according to an exemplary embodiment of the present application. This embodiment is described from a UE side. As shown in FIG. 4, the method for receiving a paging message includes the following steps.

[0050] In step S401, it is determined that a current UE belongs to a first service group or a second service group. If the current UE belongs to the first service group, step S402 is performed, and if the current UE does not belong to the first service group, step S403 is performed.

[0051] The first service group includes a first large service group or a first small service group, and the second service group includes a second large service group or a second small service group.

[0052] In the embodiment, a first service refers to a low-latency service. The UE belonging to the first service group may include, but is not limited to, the UE requesting services such as URLLC, AR, or VR, and may also include the UE with a subscriber identification module (SIM) card. A second service refers to a non-low-latency service.

[0053] In step S402, one of a plurality of first paging occasions POs is analyzed according to first configuration information which is pre-received to obtain a first paging message.

[0054] In the embodiment, the analyzing one of a plurality of first paging occasions PO according to first configuration information which is pre-received to obtain a first paging message includes: analyzing the PDCCH, corresponding to the first PO configured by the first configuration information and being configured to transmit the first paging message, to obtain paging control information; and analyzing the PDSCH, corresponding to the first PO configured by the first configuration information and being configured to transmit the first paging message, according to the paging control information to obtain the first paging message.

[0055] For example, the UE may analyze the PDCCH 24 corresponding to the first PO21 in FIG. 2 to obtain the paging control information, and then analyze the PDSCH 25, corresponding to the first PO 21 in FIG. 2 and being configured to transmit the first paging message, according to the paging control information to obtain the first paging message.

[0056] It can be seen that the implementation of obtaining the first paging message through the above analyzing is relatively simple.

[0057] In step S403, second configuration information which is pre-received is analyzed to obtain a paging indication, and a second PO is analyzed to obtain a second paging message when an identification of the current UE is located in the identifications of the UE indicated by the paging indication.

[0058] In the embodiment, the analyzing a second PO

to obtain a second paging message may include: analyzing the PDCCH, corresponding to the second PO and being configured to transmit the second paging message, to obtain paging control information; and then analyzing the PDSCH, corresponding to the second PO and being configured to transmit the second paging message, according to the paging control information to obtain the second paging message.

[0059] For example, the PDCCH 27 corresponding to the second PO 23 in FIG. 2 and being configured to transmit the second paging message is analyzed to obtain the paging control information, and then the PDSCH 28 corresponding to the second PO 23 and being configured to transmit the second paging message is analyzed according to the paging control information to obtain the second paging message.

[0060] It can be seen that the implementation of obtaining the second paging message by the above analyzing is relatively simple.

[0061] In the above embodiment, when the current UE belongs to a first service group, one of a plurality of first paging occasions POs is analyzed according to first configuration information which is pre-received to obtain a first paging message; and when the current UE does not belong to the first service group, second configuration information which is pre-received is analyzed to obtain a paging indication and a second PO is analyzed to obtain a second paging message when an identification of the current UE is located in the identifications of the UE indicated by the paging indication, which can save resources effectively.

[0062] FIG. 5 is a flowchart illustrating another method for receiving a paging message according to an exemplary embodiment of the present application. As shown in FIG. 5, before the above step S402, the method for receiving a paging message may further include the following steps.

[0063] In step S400, the first configuration information and the second configuration information sent by a base station are received.

[0064] In order to obtain the paging message, the UE may receive the first configuration information and the second configuration information sent by the base station.

[0065] The first configuration information includes one of the plurality of first POs allocated to the UE belonging to the first service group, and a PDCCH and PDSCH corresponding to an allocated first PO and being configured to transmit the first paging message. The second configuration information includes the identification of the first PO for carrying the paging indication, the second PO allocated to the UE belonging to the second service group, and the PDCCH and the PDSCH corresponding to the second PO and being configured to transmit the second paging message.

[0066] In the above embodiment, by receiving the first configuration information and the second configuration information sent by the base station, a condition for sub-

sequently obtaining the first paging message according to the first configuration information and obtaining the second paging message according to the second configuration information is provided.

[0067] FIG. 6 is a signaling flowchart of a method for sending and receiving a paging message according to an exemplary embodiment of the present application. This embodiment is described from the perspective of interaction between a UE and a base station. As shown in FIG. 6, the method for sending and receiving a paging method includes the following steps.

[0068] In step S601, the base station generates first configuration information and second configuration information, and sends the first configuration information and the second configuration information to the UE.

[0069] In step S602, the UE receives the first configuration information and the second configuration information sent by the base station.

[0070] In step S603, if there is a paging request for the UE and the UE belongs to the first small service group, the base station sends a first paging message to all UEs in the first small service group to which the current UE belongs through one of a plurality of first POs according to the first configuration information.

[0071] In step S604, the UE analyzes one of a plurality of first POs according to the first configuration information received to obtain the first paging message.

[0072] In step S605, if there is the paging request from the UE and the UE belongs to the second small service group, the base station carries a paging indication through one of the plurality of first POs and sends a second paging message to the UE indicated by the paging indication through one second PO, according to the second configuration information. The paging indication is configured to indicate an identification of all the UEs in the second small service group to which the current UE belongs.

[0073] In step S606, the UE analyzes the second configuration information received to obtain the paging indication, and analyzes the second PO to obtain the second paging message when the identification of the UE is located in the identifications of the UE indicated by the paging indication.

[0074] In the above embodiment, through the interaction between the base station and the UE, the base station may send a first paging message to all UEs in a first small service group to which a current UE belongs through one of a plurality of first POs according to first configuration information which is pre-generated, and carry a paging indication through one of the plurality of first POs and send a second paging message to the UE indicated by the paging indication through one second PO according to second configuration information which is pre-generated, and at the same time, the UE may also analyze one of the plurality of first POs according to the first configuration information to obtain the first paging message, analyze the second configuration information which is pre-received to obtain the paging indication and

analyze the second PO to obtain the second paging message when the identification of the current UE is located in the identifications of the UE indicated by the paging indication, so that the sending and receiving of the paging message is implemented and the resources may be saved.

[0075] FIG. 7 is a block diagram of a device for sending a paging message according to an exemplary embodiment. This device may be located in a base station, and as shown in FIG. 7, the device for sending a paging message includes a determining module 71, a first sending module 72 and a second sending module 73.

[0076] The determining module 71 is configured to determine that a current UE belongs to a first service group or a second service group, if there is a paging request for the current UE. The first service group includes a first large service group or a first small service group, and the second service group includes a second large service group or a second small service group.

[0077] In the embodiment, a first service refers to a low-latency service. The UE belonging to the first service group may include, but is not limited to, the UE requesting service such as URLLC, AR, or VR, and may also include the UE with a subscriber identification module (SIM) card. A second service refers to a non-low-latency service.

[0078] The first sending module 72 is configured to send a first paging message to all UEs in the first small service group to which the current UE belongs through one of a plurality of first paging occasions POs according to first configuration information which is pre-generated, if the determining module 71 determines that the current UE belongs to the first service group.

[0079] In order to reduce waste of resources and at the same time to reduce effect on the low-latency service, in the embodiment, a plurality of first POs may be provided for the low-latency UE in each cycle, and one second PO is provided for the non-low-latency UE. For example, as shown in FIG. 2, two first POs are provided for the low-latency UE in each cycle, and the two first POs are referred to as a first PO 21 and a first PO 22 respectively for distinction, and one second PO 23 is provided for the non-low-latency UE.

[0080] The first configuration information includes one of the plurality of first POs allocated to the UE belonging to the first service group, and a PDCCH and PDSCH corresponding to an allocated first PO and being configured to transmit the first paging message. For example, as shown in FIG. 2, the one first PO allocated to a UE1 assumed as the UE of the first service group is a first PO 21, the PDCCH corresponding to the first PO 21 and being configured to transmit the first paging message is PDCCH 24, and the PDSCH corresponding to the first PO 21 and being configured to transmit the first paging message is PDSCH 25.

[0081] Preferably, in the embodiment, the resource consumption may be reduced by sending the first paging message to all UEs of the first small service group to which the current UE belongs.

[0082] For example, if the first large service group includes 10 first small service groups, and each of the first small service groups includes 3 UEs, the base station only needs to send the first paging message to the 3 UEs in the first small service group where the current UE is located, and needs not to send the first paging message to all the UEs (i.e., the 30 UEs) in the first large service group, thereby reducing the resource consumption.

[0083] The second sending module 73 is configured to carry a paging indication through one of the plurality of first POs and send a second paging message to the UE indicated by the paging indication through one second PO according to second configuration information which is pre-generated, if the determining module 71 determines that the current UE belongs to the second service group. The paging indication is configured to indicate an identification of all the UEs in the second small service group to which the current UE belongs.

[0084] The second configuration information includes the identification of the first PO for carrying the paging indication, the second PO allocated to the UE belonging to the second service group, and the PDCCH and the PDSCH corresponding to the second PO and being configured to transmit the second paging message. For example, as shown in FIG. 2, the first PO for carrying the paging indication 26 is the first PO 22, the second PO allocated to a UE 3 assumed as the UE belonging to the second service group is the second PO 23, the PDCCH corresponding to the second PO 23 and being configured to transmit the second paging message is PDCCH 27, and the PDSCH corresponding to the second PO 23 and being configured to transmit the second paging message is PDSCH 28.

[0085] In the embodiment, when the second service group is the second large service group, the paging indication may be used to indicate the identification of one or more UEs in the second large service group. When the second service group is the second small service group, the paging indication may be used to indicate the identification of all the UEs in the second small service group to which the current UE belongs, that is, the paging indication is used to notify all the UEs in the second service group to which the current UE belongs to analyze the second PO, instead of notifying all the UEs belonging to the second large service group to analyze the second PO, which can effectively save resources.

[0086] It should be noted that the first PO for carrying the paging indication and the first PO for sending the first paging message in step S102 are not necessarily the same.

[0087] In the above embodiment, by sending a first paging message to all UEs in a first small service group to which a current UE belongs through one of a plurality of first paging occasions POs according to first configuration information which is pre-generated, and carrying a paging indication through one of the plurality of first POs and sending a second paging message to the UE indicated by the paging indication through one second

PO according to second configuration information which is pre-generated, both a low low-latency paging requirement of a low-latency UE and a paging requirement of a non-low-latency UE can be satisfied, and resources can be saved effectively.

[0088] FIG. 8A is a block diagram of another device for sending a paging message according to an exemplary embodiment. As shown in FIG. 8A, on the basis of the above embodiment shown in FIG. 7, the device may further include a forwarding module 74 and a receiving and classifying module 75.

[0089] The forwarding module 74 is configured to receive a first service request sent by the UE, and send the first service request to a core network, before the determining module 71 determines that the current UE belongs to the first service group or the second service group.

[0090] In the embodiment, the base station may receive the first service request sent by the UE and send the first service request to the core network. The first service may include, but is not limited to, services such as URLLC, AR, or VR.

[0091] The receiving and classifying module 75 is configured to receive the identification of the UE belonging to the first large service group returned by the core network according to the first service request, and classify the identification of the UE not belonging to the first large service group to the second large service group.

[0092] After receiving the first service request from a plurality of UEs, the core network may classify all the UEs requesting the first service to a first large service group, and return the identification of the UEs belonging to the first large service group to the base station. At the same time, the identification of the UEs not belonging to the first large service group may be classified to the second large service group.

[0093] In the above embodiment, by receiving the first service request sent by the UE, and sending the first service request to the core network, and then receiving the identification of the UE belonging to the first large service group returned by the core network according to the first service request, and classifying the identification of the UE not belonging to the first large service group to the second large service group, a condition under which a paging message is sent subsequently according to the first large service group or the second large service group is provided.

[0094] FIG. 8B is a block diagram of another device for sending a paging message according to an exemplary embodiment. As shown in FIG. 8B, on the basis of the above embodiment shown in FIG. 8A, the device may further include a dividing module 76.

[0095] The dividing module 76 is configured to divide the first large service group into at least one first small service group, and divide the second large service group into at least one of the second small service group, after the receiving and classifying module 75 classifies the identification of the UE not belonging to the first large

service group to the second large service group.

[0096] In the above embodiment, the first large service group is divided into at least one first small service group, and the second large service group is divided into at least one second small service group, such that the number of UEs included in the first or second small service group is smaller, thereby providing a condition for subsequently sending a paging messages according to the first or second small service group to which the UE belongs.

[0097] FIG. 8C is a block diagram of another device for sending a paging message according to an exemplary embodiment. As shown in FIG. 8C, on the basis of the above embodiment shown in FIG. 7, the device may further include a generating and sending module 77.

[0098] The generating and sending module 77 is configured to generate the first configuration information and the second configuration information, and send the first configuration information and the second configuration information to the UE, before the first sending module 72 sends the first paging message to all the UEs of the first small service group to which the current UE belongs through one of the plurality of first paging occasions POs according to the first configuration information which is pre-generated.

[0099] The first configuration information includes one of the plurality of first POs allocated to the UE belonging to the first service group, and a physical downlink control channel PDCCH and a physical downlink shared channel PDSCH corresponding to an allocated first PO and being configured to transmit the first paging message. The second configuration information includes the identification of the first PO for carrying the paging indication, the second PO allocated to the UE belonging to the second service group, and the PDCCH and the PDSCH corresponding to the second PO and being configured to transmit the second paging message.

[0100] In the embodiment, the base station may generate the first and second configuration information, to provide a condition for subsequently sending the first paging message according to the first configuration information and sending the second paging message according to the second configuration information.

[0101] In the above embodiment, by generating the first and second configuration information, a condition for subsequently sending the first paging message according to the first configuration information and sending the second paging message according to the second configuration information is provided.

[0102] FIG. 9 is a block diagram of a device for receiving a paging message according to an exemplary embodiment. The device may be located in a UE, and as shown in FIG. 9, the device for receiving a paging message include a service group determining module 91, a first analyzing module 92 and a second analyzing module 93.

[0103] The service group determining module 91 is configured to determine that a current UE belongs to a first service group or a second service group. The first

service group includes a first large service group or a first small service group, and the second service group includes a second large service group or a second small service group.

[0104] The first service group includes a first large service group or a first small service group, and the second service group includes a second large service group or a second small service group.

[0105] In the embodiment, a first service refers to a low-latency service. The UE belonging to the first service group may include, but is not limited to, the UE requesting services such as URLLC, AR, or VR, and may also include the UE with a subscriber identification module (SIM) card. A second service refers to a non-low-latency service.

[0106] The first analyzing module 92 is configured to analyze one of a plurality of first paging occasions POs according to first configuration information which is pre-received to obtain a first paging message, if the service group determining module 91 determines that the current UE belongs to the first service group.

[0107] The second analyzing module 93 is configured to analyze second configuration information which is pre-received to obtain a paging indication, and analyze a second PO to obtain a second paging message when an identification of the current UE is located in the identifications of the UE indicated by the paging indication, if the service group determining module 91 determines that the current UE belongs to the second service group.

[0108] In the above embodiment, when the current UE belongs to a first service group, one of a plurality of first paging occasions POs is analyzed according to first configuration information which is pre-received to obtain a first paging message; and when the current UE does not belong to the first service group, second configuration information which is pre-received is analyzed to obtain a paging indication and a second PO is analyzed to obtain a second paging message when an identification of the current UE is located in the identifications of the UE indicated by the paging indication, which can save resources effectively.

[0109] FIG. 10A is a block diagram of another device for receiving a paging message according to an exemplary embodiment. As shown in FIG. 10A, on the basis of the above embodiment shown in FIG. 9, the device may further include a receiving module 90.

[0110] The receiving module 90 is configured to receive the first configuration information and the second configuration information sent by a base station, before the first analyzing module 92 obtains the first paging message through analyzing or the second analyzing module obtains the second paging message through analyzing.

[0111] In order to obtain the paging message, the UE may receive the first configuration information and the second configuration information sent by the base station.

[0112] The first configuration information includes one of the plurality of first POs allocated to the UE belonging

to the first service group, and a PDCCH and PDSCH corresponding to an allocated first PO and being configured to transmit the first paging message. The second configuration information includes the identification of the first PO for carrying the paging indication, the second PO allocated to the UE belonging to the second service group, and the PDCCH and the PDSCH corresponding to the second PO and being configured to transmit the second paging message.

[0113] In the above embodiment, by receiving the first configuration information and the second configuration information sent by the base station, a condition for subsequently obtaining the first paging message according to the first configuration information and obtaining the second paging message according to the second configuration information is provided.

[0114] FIG. 10B is a block diagram of another device for receiving a paging message according to an exemplary embodiment. As shown in FIG. 10B, on the basis of the above embodiment shown in FIG. 10A, the first analyzing module 90 may include a first analyzing sub-module 921 and a second analyzing sub-module 922.

[0115] The first analyzing sub-module 921 is configured to analyze the PDCCH, corresponding to the first PO configured by the first configuration information and being configured to transmit the first paging message, to obtain paging control information.

[0116] The second analyzing sub-module 922 is configured to analyze the PDSCH, corresponding to the first PO configured by the first configuration information and being configured to transmit the first paging message, according to the paging control information obtained by the first analyzing sub-module 921 to obtain the first paging message.

[0117] In the embodiment, the PDCCH corresponding to the first PO configured by the first configuration information and being configured to transmit the first paging message may be analyzed to obtain paging control information; and the PDSCH corresponding to the first PO configured by the first configuration information and being configured to transmit the first paging message may be analyzed according to the paging control information to obtain the first paging message.

[0118] For example, the UE may analyze the PDCCH 24 corresponding to the first PO 21 in FIG. 2 to obtain the paging control information, and then analyze the PDSCH 25, corresponding to the first PO 21 in FIG. 2 and being configured to transmit the first paging message, according to the paging control information to obtain the first paging message.

[0119] In the above embodiment, by analyzing the PDCCH, corresponding to the first PO configured by the first configuration information and being configured to transmit the first paging message, to obtain paging control information, and then analyzing the PDSCH, corresponding to the first PO configured by the first configuration information and being configured to transmit the first paging message, according to the paging control information

to obtain the first paging message, the implementation is relatively simple.

[0120] FIG. 10C is a block diagram of another device for receiving a paging message according to an exemplary embodiment. As shown in FIG. 10C, on the basis of the above embodiment shown in FIG. 10A, the second analyzing module 93 may include a third analyzing sub-module 931 and a fourth analyzing sub-module 932.

[0121] The third analyzing sub-module 931 is configured to analyze the PDCCH, corresponding to the second PO and being configured to transmit the second paging message, to obtain paging control information.

[0122] The fourth analyzing sub-module 932 is configured to analyze the PDSCH, corresponding to the second PO and being configured to transmit the second paging message, according to the paging control information obtained by the third analyzing sub-module 931 to obtain the second paging message.

[0123] In the embodiment, the PDCCH corresponding to the second PO and being configured to transmit the second paging message may be analyzed to obtain paging control information; and then the PDSCH corresponding to the second PO and being configured to transmit the second paging message may be analyzed according to the paging control information to obtain the second paging message.

[0124] For example, the PDCCH 27 corresponding to the second PO 23 in FIG. 2 and being configured to transmit the second paging message is analyzed to obtain the paging control information, and then the PDSCH 28 corresponding to the second PO 23 and being configured to transmit the second paging message is analyzed according to the paging control information to obtain the second paging message.

[0125] In the above embodiment, by analyzing the PDCCH, corresponding to the second PO and being configured to transmit the second paging message, to obtain paging control information, and then analyzing the PDSCH, corresponding to the second PO and being configured to transmit the second paging message, according to the paging control information to obtain the second paging message, the implementation is relatively simple.

[0126] FIG. 11 is a block diagram illustrating another device suitable for sending a paging message according to an exemplary embodiment. The device 1100 may be provided as a base station. Referring to FIG. 11, the device 1100 includes a processing component 1122, a wireless transmitting/receiving component 1124, an antenna component 1126, and a signal processing portion unique to a wireless interface. The processing component 1122 may further include one or more processors.

[0127] One of the processors in the processing component 1122 is configured to:

determine that a current UE belongs to a first service group or a second service group, if there is a paging request for the current UE, the first service group including a first large service group or a first small

service group, and the second service group comprising a second large service group or a second small service group;

send a first paging message to all UEs in the first small service group to which the current UE belongs through one of a plurality of first paging occasions POs according to first configuration information which is pre-generated, if the current UE belongs to the first service group; and

carry a paging indication through one of the plurality of first POs and send a second paging message to the UE indicated by the paging indication through one second PO according to second configuration information which is pre-generated, if the current UE belongs to the second service group, wherein the paging indication is configured to indicate an identification of all the UEs in the second small service group to which the current UE belongs.

[0128] In an exemplary embodiment, there is further provided a non-transitory computer-readable storage medium including instructions, and the foregoing instructions may be executed by the processing component 1122 of the device 1100 to implement the foregoing method for sending a paging message. For example, the non-transitory computer-readable storage medium may be a ROM, a random access memory (RAM), a CD-ROM, a magnetic tape, a floppy disk, an optical data storage device, and the like.

[0129] Fig. 12 is a block diagram illustrating a device suitable for receiving a paging message according to an exemplary embodiment. For example, the device 1200 may be a user equipment such as a mobile phone, a computer, a digital broadcasting terminal, a messaging device, a game console, a tablet device, a medical device, a fitness device, a personal digital assistant, and the like.

[0130] Referring to FIG. 12, the device 1200 may include one or more of the following components: a processing component 1202, a memory 1204, a power component 1206, a multimedia component 1208, an audio component 1210, an input/output (I/O) interface 1212, a sensor component 1214, and a communication component 1216.

[0131] The processing component 1202 generally controls overall operations of the device 1200, such as operations associated with display, telephone calls, data communications, camera operations, and recording operations. The processing component 1202 may include one or more processors 1220 to execute instructions to implement all or part of the steps of the foregoing method for receiving a paging message. In addition, the processing component 1202 may include one or more modules to facilitate interaction between the processing component 1202 and other components. For example, the processing component 1202 may include a multimedia module to facilitate the interaction between the multimedia component 1208 and the processing component

1202.

[0132] One of the processors 1220 in the processing component 1202 may be configured to:

determine that a current UE belongs to a first service group or a second service group, the first service group including a first large service group or a first small service group, and the second service group including a second large service group or a second small service group;

analyze one of a plurality of first paging occasions POs according to first configuration information which is pre-received to obtain a first paging message, if the current UE belongs to the first service group; and

analyze second configuration information which is pre-received to obtain a paging indication, and analyze a second PO to obtain a second paging message when an identification of the current UE is located in the identifications of the UE indicated by the paging indication, if the current UE belongs to the second service group.

[0133] The memory 1204 is configured to store various types of data to support operation of the device 1200. Examples of such data include instructions for any application or method operating on the device 1200, contact data, phone book data, messages, pictures, videos, and the like. The memory 1204 may be implemented by any type of volatile or non-volatile storage device or a combination thereof, such as static random access memory (SRAM), electrically erasable programmable read-only memory (EEPROM), erasable programmable read-only memory (EPROM), programmable read-only memory (PROM), read-only memory (ROM), magnetic memory, flash memory, magnetic disk or optical disk.

[0134] The power supply assembly 1206 provides power to various components of the device 1200. The power component 1206 may include a power management system, one or more power sources, and other components associated with generating, managing, and distributing power for the device 1200.

[0135] The multimedia component 1208 includes a screen that provides an output interface between the device 1200 and a user. In some embodiments, the screen may include a liquid crystal display (LCD) and a touch panel (TP). If the screen includes a touch panel, the screen may be implemented as a touch screen to receive an input signal from a user. The touch panel includes one or more touch sensors to sense touch, swipe, and gestures on the touch panel. The touch sensor can not only sense the boundary of a touch or slide action, but also detect duration and pressure related to the touch or slide operation. In some embodiments, the multimedia component 1208 includes a front camera and / or a rear camera. When the device 1200 is in an operation mode, such as a shooting mode or a video mode, the front camera and/or the rear camera may receive external multimedia

data. Each front camera and rear camera may be a fixed optical lens system or have focal length and optical zoom capabilities.

[0136] The audio component 1210 is configured to output and/or input audio signals. For example, the audio component 1210 includes a microphone (MIC). When the device 1200 is in an operation mode, such as a call mode, a recording mode, and a voice recognition mode, the microphone is configured to receive an external audio signal. The received audio signal may be further stored in the memory 1204 or transmitted via the communication component 1216. In some embodiments, the audio component 1210 further includes a speaker for outputting audio signals.

[0137] The I/O interface 1212 provides an interface between the processing component 1202 and a peripheral interface module. The peripheral interface module may be a keyboard, a click wheel, a button, or the like. These buttons may include, but are not limited to: a home button, a volume button, a start button, and a lock button.

[0138] The sensor assembly 1214 includes one or more sensors for providing status evaluation of various aspects of the device 1200. For example, the sensor component 1214 may detect an on/off state of the device 1200, relative positioning of the components (for example, the components are a display and keypad of the device 1200), the sensor component 1214 may also detect the change in the position of the device 1200 or a component of the device 1200, presence or absence of contact of the user with the device 1200, orientation or acceleration/deceleration of the device 1200, and temperature change of the device 1200. The sensor assembly 1214 may include a proximity sensor configured to detect the presence of nearby objects without any physical contact. The sensor component 1214 may also include a light sensor, such as a CMOS or CCD image sensor, for use in imaging applications. In some embodiments, the sensor component 1214 may further include an acceleration sensor, a gyroscope sensor, a magnetic sensor, a pressure sensor, or a temperature sensor.

[0139] The communication component 1216 is configured to facilitate wired or wireless communication between the device 1200 and other devices. The device 1200 may access a wireless network based on a communication standard, such as WiFi, 2G, or 3G, or a combination thereof. In an exemplary embodiment, the communication component 1216 receives a broadcast signal or broadcast-related information from an external broadcast management system via a broadcast channel. In an exemplary embodiment, the communication component 1216 further includes a near field communication (NFC) module to facilitate short-range communication. For example, the NFC module may be implemented based on radio frequency identification (RFID) technology, infrared data association (IrDA) technology, ultra wideband (UWB) technology, Bluetooth (BT) technology and other technologies.

[0140] In an exemplary embodiment, the device 1200

may be implemented by one or more application-specific integrated circuits (ASICs), a digital signal processor (DSP), a digital signal processing device (DSPD), a programmable logic device (PLD), a field programmable gate array (FPGA), a controller, a microcontroller, a microprocessor, or other electronic components, and is configured to perform the foregoing method for receiving a paging message.

[0141] In an exemplary embodiment, there is further provided a non-transitory computer-readable storage medium including instructions, such as a memory 1204 including the instructions, and the instructions may be executed by the processor 1220 of the device 1200 to implement the foregoing method. For example, the non-transitory computer-readable storage medium may be a ROM, a random access memory (RAM), a CD-ROM, a magnetic tape, a floppy disk, an optical data storage device, and the like.

[0142] As for the device embodiment, since it basically corresponds to the method embodiment, the relevant parts thereof may refer to the description of the method embodiment. The device embodiments described above are only schematic, wherein the units described as separate components may be or may not be physically separated, and the components shown as units may be or may not be physical units, that is, may be located in one place, or may be distributed across multiple network elements. Some or all of the modules may be selected according to actual needs to achieve the solution of this embodiment. Those of ordinary skill in the art can understand and implement without creative efforts.

[0143] It should be noted that in this text, relational terms such as first and second are only used to distinguish one entity or operation from another entity or operation, and do not necessarily require or imply that these entities or operations have any such actual relationship or order. The term "comprising", "including" or any other variation thereof is intended to encompass non-exclusive inclusion, such that a process, method, article, or device that includes a series of elements includes not only those elements, but also other elements, or elements that are inherent to such process, method, article, or device. Without more restrictions, the elements defined by the sentence "including a ..." do not exclude the existence of other identical elements in the process, method, article, or equipment including the elements.

Claims

1. A method for sending a paging message, which is applied to a base station, comprising:

determining (S101) that a current user equipment, UE, belongs to a first service group or a second service group, if there is a paging request for the current UE, wherein the first service group comprises a first larger service group or

a first smaller service group, the second service group comprises a second larger service group or a second smaller service group, the first larger service group comprises at least one of the first smaller service group, and the second larger service group comprises at least one of the second smaller service group;

sending (S102) a first paging message to all UEs in the first smaller service group to which the current UE belongs through one of a plurality of first paging occasions, Pos, according to first configuration information which is pre-generated, if the current UE belongs to the first service group; and

carrying (S103) a paging indication through one of the plurality of the first POs and sending a second paging message to the UE indicated by the paging indication through one second PO according to second configuration information which is pre-generated, if the current UE belongs to the second service group, wherein the paging indication is configured to indicate an identification of all the UEs in the second smaller service group to which the current UE belongs.

2. The method according to claim 1, further comprising, before the determining (S101) that a current user equipment UE belongs to a first service group or a second service group:

receiving (S301) a first service request sent by the UE, and sending the first service request to a core network; and

receiving (S302) the identification of the UE belonging to the first larger service group returned by the core network according to the first service request, and classifying the identification of the UE not belonging to the first larger service group to the second larger service group.

3. The method according to claim 2, further comprising, after the classifying the identification of the UE not belonging to the first larger service group to the second larger service group (S302):

dividing (S303) the first larger service group into at least one of the first smaller service group, and dividing the second larger service group into at least one of the second smaller service group.

4. The method according to claim 1, further comprising, before the sending (S102) a first paging message to all UEs of the first smaller service group to which the current UE belongs through one of a plurality of first paging occasions POs according to first configuration information which is pre-generated:

generating (S100) the first configuration information and the second configuration informa-

tion, and sending the first configuration information and the second configuration information to the UE,

wherein the first configuration information comprises one of the plurality of the first POs allocated to the UE belonging to the first service group, and a physical downlink control channel PDCCH and a physical downlink shared channel, PDSCH, corresponding to an allocated first PO and being configured to transmit the first paging message, and

the second configuration information comprises the identification of the first PO for carrying the paging indication, the second PO allocated to the UE belonging to the second service group, and the PDCCH and the PDSCH corresponding to the second PO and being configured to transmit the second paging message.

5. A base station (1100), comprising:

a processor (1122); and
a memory having instructions stored thereon, which are executable by the processor,
characterized in that the processor is configured to:

determine that a current UE belongs to a first service group or a second service group, if there is a paging request for the current UE, wherein the first service group comprises a first larger service group or a first smaller service group, and the second service group comprises a second larger service group or a second smaller service group;

send a first paging message to all UEs in the first smaller service group to which the current UE belongs through one of a plurality of first paging occasions, Pos, according to first configuration information which is pre-generated, if the current UE belongs to the first service group; and

carry a paging indication through one of the plurality of the first POs and send a second paging message to the UE indicated by the paging indication through one second PO according to second configuration information which is pre-generated, if the current UE belongs to the second service group, wherein the paging indication is configured to indicate an identification of all the UEs in the second smaller service group to which the current UE belongs.

6. The base station according to claim 5, wherein the processor is further configured to, before determining that the current user equipment, UE, belongs to

the first service group or the second service group:

receive a first service request sent by the UE, and send the first service request to a core network; and

receive the identification of the UE belonging to the first larger service group returned by the core network according to the first service request, and classify the identification of the UE not belonging to the first larger service group to the second larger service group.

7. The base station according to claim 6, wherein the processor is further configured to, after classifying the identification of the UE not belonging to the first larger service group to the second larger service group:

divide the first larger service group into at least one of the first smaller service group, and divide the second larger service group into at least one of the second smaller service group.

8. The base station according to claim 5, wherein the processor is configured to, before sending the first paging message to all UEs of the first smaller service group to which the current UE belongs through one of the plurality of first paging occasions POs according to the first configuration information which is pre-generated:

generate the first configuration information and the second configuration information, and send the first configuration information and the second configuration information to the UE, wherein the first configuration information comprises one of the plurality of the first POs allocated to the UE belonging to the first service group, and a physical downlink control channel, PDCCH, and a physical downlink shared channel, PDSCH, corresponding to an allocated first PO and being configured to transmit the first paging message, and
the second configuration information comprises the identification of the first PO for carrying the paging indication, the second PO allocated to the UE belonging to the second service group, and the PDCCH and the PDSCH corresponding to the second PO and being configured to transmit the second paging message.

Patentansprüche

1. Verfahren zum Senden einer Paging-Nachricht, das bei einer Basisstation angewendet wird, wobei das Verfahren umfasst:

Bestimmen (S101), dass ein aktuelles Benutze-

rendgerät, UE, zu einer ersten Servicegruppe oder einer zweiten Servicegruppe gehört, wenn eine Paging-Anfrage für das aktuelle UE vorliegt, wobei die erste Servicegruppe eine erste größere Servicegruppe oder eine erste kleinere Servicegruppe umfasst, wobei die zweite Servicegruppe eine zweite größere Servicegruppe oder eine zweite kleinere Servicegruppe umfasst, wobei die erste größere Servicegruppe mindestens eine der ersten kleineren Servicegruppe umfasst, und wobei die zweite größere Servicegruppe mindestens eine der zweiten kleineren Servicegruppe umfasst;
 Senden (S102) einer ersten Paging-Nachricht an alle UEs in der ersten kleineren Servicegruppe, zu der das aktuelle UE gehört, durch einen aus einer Vielzahl von ersten Paging-Anlässe, POs, entsprechend vorgenerierten ersten Konfigurationsinformationen, wenn das aktuelle UE zu der ersten Servicegruppe gehört; und
 Tragen (S103) einer Paging-Anzeige durch einen der Vielzahl von ersten POs und Senden einer zweiten Paging-Nachricht an das UE, das von der Paging-Anzeige angezeigt wird, durch einen zweiten PO entsprechend den vorgenerierten zweiten Konfigurationsinformationen, wenn das aktuelle UE zu der zweiten Servicegruppe gehört, wobei die Paging-Anzeige dazu ausgebildet ist, eine Identifikation aller UEs in der zweiten kleineren Servicegruppe anzuzeigen, zu der das UE gehört.

2. Verfahren nach Anspruch 1, das ferner vor dem Bestimmen (S101), dass das aktuelle Benutzerendgerät, UE, zu einer ersten Servicegruppe oder einer zweiten Servicegruppe gehört, umfasst:

Empfangen (S301) einer von dem UE gesendeten ersten Serviceanfrage, und Senden der ersten Serviceanfrage an ein Kernnetzwerk; und
 Empfangen (S302) der Identifikation des UEs, das zu der ersten größeren Servicegruppe gehört, die von dem Kernnetzwerk entsprechend der ersten Serviceanfrage zurückgegeben wird, und
 Klassifizieren der Identifikation des UEs, das nicht zu der ersten größeren Servicegruppe gehört, in die zweite größere Servicegruppe.

3. Verfahren nach Anspruch 2, das ferner umfasst, nach dem Klassifizieren der Identifikation des UEs, das nicht zu der ersten größeren Servicegruppe gehört, in die zweite größere Servicegruppe (S302):
 Teilen (S303) der ersten größeren Servicegruppe in mindestens eine der ersten kleineren Servicegruppe, und Teilen der zweiten größeren Servicegruppe in mindestens eine der zweiten kleineren Servicegruppe.

4. Verfahren nach Anspruch 1, das ferner umfasst, vor dem Senden (S102) einer ersten Paging-Nachricht an alle UEs der ersten kleineren Servicegruppe, zu der das aktuelle UE gehört, durch einen aus einer Vielzahl von ersten Paging-Anlässen, POs, entsprechend vorgenerierten ersten Konfigurationsinformationen:

Generieren (S100) der ersten Konfigurationsinformationen und der zweiten Konfigurationsinformationen, und Senden der ersten Konfigurationsinformationen und der zweiten Konfigurationsinformationen an das UE, wobei die ersten Konfigurationsinformationen einen der Vielzahl von ersten POs, der dem zu der ersten Servicegruppe gehörenden UE zugewiesen ist, und einen Physical Downlink Control Channel, PDCCH, und einen Physical Downlink Shared Channel, PDSCH umfassen, die einem zugewiesenen ersten PO entsprechen und dazu ausgebildet sind, die erste Paging-Nachricht zu übertragen, und die zweiten Konfigurationsinformationen die Identifikation des ersten PO zum Tragen der Paging-Anzeige, den zweiten PO, der dem zu der zweiten Servicegruppe gehörenden UE zugewiesen ist, und den PDCCH und den PDSCH umfassen, die dem zweiten PO entsprechen und dazu ausgebildet sind, die zweite Paging-Nachricht zu übertragen.

5. Basisstation (1100), die aufweist:

einen Prozessor (1122); und
 einen Speicher mit darauf gespeicherten Anweisungen, die von dem Prozessor ausgeführt werden können,
dadurch gekennzeichnet, dass der Prozessor für Folgendes ausgebildet ist:

Bestimmen, dass ein aktuelles UE zu einer ersten Servicegruppe oder einer zweiten Servicegruppe gehört, wenn eine Paging-Anfrage für das aktuelle UE vorliegt, wobei die erste Servicegruppe eine erste größere Servicegruppe oder eine erste kleine Servicegruppe umfasst, und die zweite Servicegruppe eine zweite größere Servicegruppe oder eine zweite kleinere Servicegruppe umfasst;
 Senden einer ersten Paging-Nachricht an alle UEs in der ersten kleineren Servicegruppe, zu der das aktuelle UE gehört, durch einen aus einer Vielzahl von ersten Paging-Anlässen, POs, entsprechend ersten vorgenerierten Konfigurationsinformationen, wenn das aktuelle UE zu der ersten Servicegruppe gehört; und

Tragen einer Paging-Anzeige durch einen der Vielzahl von ersten POs und Senden einer zweiten Paging-Nachricht an das UE, das von der Paging-Anzeige angezeigt wird, durch einen zweiten PO entsprechend den vorgenerierten zweiten Konfigurationsinformationen, wenn das aktuelle UE zu der zweiten Servicegruppe gehört, wobei die Paging-Anzeige dazu ausgebildet ist, eine Identifikation aller UEs in der zweiten kleineren Servicegruppe anzuzeigen, zu der das UE gehört.

6. Basisstation nach Anspruch 5, wobei der Prozessor vor dem Bestimmen, dass das aktuelle Benutzergerät, UE, zu der ersten Servicegruppe oder der zweiten Servicegruppe gehört, ferner für Folgendes ausgebildet ist:

Empfangen einer von dem UE gesendeten ersten Serviceanfrage, und Senden der ersten Serviceanfrage an ein Kernnetzwerk; und Empfangen der Identifikation des UEs, das zu der ersten größeren Servicegruppe gehört, die von dem Kernnetzwerk entsprechend der ersten Serviceanfrage zurückgegeben wird, und Klassifizieren der Identifikation des UEs, das nicht zu der ersten größeren Servicegruppe gehört, in die zweite größere Servicegruppe.

7. Basisstation nach Anspruch 6, wobei der Prozessor nach dem Klassifizieren der Identifikation des UEs, das nicht zu der ersten größeren Servicegruppe gehört, in die zweite größere Servicegruppe, ferner für Folgendes ausgebildet ist:

Teilen der ersten größeren Servicegruppe in mindestens eine der ersten kleineren Servicegruppe, und Teilen der zweiten größeren Servicegruppe in mindestens eine der zweiten kleineren Servicegruppe.

8. Basisstation nach Anspruch 5, wobei der Prozessor vor dem Senden der ersten Paging-Nachricht an alle UEs der ersten kleineren Servicegruppe, zu der das aktuelle UE gehört, durch einen der Vielzahl von ersten Paging-Anlässen, POs, entsprechend den vorgenerierten ersten Konfigurationsinformationen ferner für Folgendes ausgebildet ist:

Generieren der ersten Konfigurationsinformationen und der zweiten Konfigurationsinformationen, und Senden der ersten Konfigurationsinformationen und der zweiten Konfigurationsinformationen an das UE, wobei die ersten Konfigurationsinformationen einen der Vielzahl von ersten POs, der dem zu der ersten Servicegruppe gehörenden UE zugewiesen ist, und einen Physical Downlink Con-

trol Channel, PDCCH, und einen Physical Downlink Shared Channel, PDSCH umfassen, die einem zugewiesenen ersten PO entsprechen und dazu ausgebildet sind, die erste Paging-Nachricht zu übertragen, und die zweiten Konfigurationsinformationen die Identifikation des ersten POs zum Tragen der Paging-Anzeige, den zweiten PO, der dem zu der zweiten Servicegruppe gehörenden UE zugewiesen ist, und den PDCCH und den PDSCH umfassen, die dem zweiten PO entsprechen und dazu ausgebildet sind, die zweite Paging-Nachricht zu übertragen.

Revendications

1. Procédé permettant d'envoyer un message de radiomessagerie, qui est appliqué à une station de base, comprenant :

le fait de déterminer (S101) qu'un équipement utilisateur, UE, actuel appartient à un premier groupe de services ou à un second groupe de services, s'il y a une demande de radiomessagerie pour l'UE actuel, le premier groupe de services comprenant un premier groupe de services plus grand ou un premier groupe de services plus petit, le second groupe de services comprenant un second groupe de services plus grand ou un second groupe de services plus petit, le premier groupe de services plus grand comprenant au moins l'un du premier groupe de services plus petit, et le second groupe de services plus grand comprenant au moins l'un du second groupe de services plus petit ;

l'envoi (S102) d'un premier message de radiomessagerie à tous les UE dans le premier groupe de services plus petit auquel l'UE actuel appartient par l'intermédiaire de l'une parmi une pluralité de premières occasions de radiomessagerie, Po, selon des premières informations de configuration qui sont pré-générées, si l'UE actuel appartient au premier groupe de services ; et

le transport (S103) d'une indication de radiomessagerie par l'intermédiaire de l'une parmi la pluralité des premières PO et l'envoi d'un second message de radiomessagerie à l'UE indiqué par l'indication de radiomessagerie par l'intermédiaire d'une seconde PO selon des secondes informations de configuration qui sont pré-générées, si l'UE actuel appartient au second groupe de services, l'indication de radiomessagerie étant configurée pour indiquer une identification de tous les UE dans le second groupe de services plus petit auquel appartient l'UE actuel.

2. Procédé selon la revendication 1, comprenant en outre, avant la détermination (S101) que l'équipement utilisateur UE actuel appartient à un premier groupe de services ou à un second groupe de services :

la réception (S301) d'une première demande de service envoyée par l'UE, et l'envoi de la première demande de service à un réseau central ; et
 la réception (S302) de l'identification de l'UE appartenant au premier groupe de services plus grand renvoyée par le réseau central selon la première demande de service, et la classification de l'identification de l'UE n'appartenant pas au premier groupe de services plus grand dans le second groupe de services plus grand.

3. Procédé selon la revendication 2, comprenant en outre, après la classification de l'identification de l'UE n'appartenant pas au premier groupe de services plus grand dans le second groupe de services plus grand (S302) :

la division (S303) du premier groupe de services plus grand en au moins l'un du premier groupe de services plus petit, et la division du second groupe de services plus grand en au moins l'un du second groupe de services plus petit.

4. Procédé selon la revendication 1, comprenant en outre, avant l'envoi (S102) d'un premier message de radiomessagerie à tous les UE du premier groupe de services plus petit auquel appartient l'UE actuel par l'intermédiaire d'une parmi une pluralité de premières occasions de radiomessagerie PO selon des premières informations de configuration qui sont pré-générées :

la génération (S100) des premières informations de configuration et des secondes informations de configuration, et l'envoi des premières informations de configuration et des secondes informations de configuration à l'UE,
 les premières informations de configuration comprenant l'une parmi la pluralité des première PO allouées à l'UE appartenant au premier groupe de services, et un canal de commande de liaison descendante physique PDCCH et un canal partagé de liaison descendante physique, PDSCH, correspondant à une première PO allouée et étant configurés pour transmettre le premier message de radiomessagerie, et
 les secondes informations de configuration comprenant l'identification de la première PO pour transporter l'indication de radiomessagerie, la seconde PO allouée à l'UE appartenant au second groupe de services, et le PDCCH et le PDSCH correspondant à la seconde PO et

étant configurés pour transmettre le second message de radiomessagerie.

5. Station de base (1100), comprenant :

un processeur (1122) ; et
 une mémoire sur laquelle sont stockées des instructions, qui sont exécutables par le processeur,
caractérisée en ce que le processeur est configuré pour :

déterminer qu'un UE actuel appartient à un premier groupe de services ou à un second groupe de services, s'il y a une demande de radiomessagerie pour l'UE actuel, le premier groupe de services comprenant un premier groupe de services plus grand ou un premier groupe de services plus petit, et le second groupe de services comprenant un second groupe de services plus grand ou un second groupe de services plus petit ;
 envoyer un premier message de radiomessagerie à tous les UE dans le premier groupe de services plus petit auquel l'UE actuel appartient par l'intermédiaire de l'une parmi une pluralité de premières occasions de radiomessagerie, Po, selon des premières informations de configuration qui sont pré-générées, si l'UE actuel appartient au premier groupe de services ; et
 transporter une indication de radiomessagerie par l'intermédiaire de l'une parmi la pluralité des premières PO et envoyer un second message de radiomessagerie à l'UE indiqué par l'indication de radiomessagerie par l'intermédiaire d'une seconde PO selon des secondes informations de configuration qui sont pré-générées, si l'UE actuel appartient au second groupe de services, l'indication de radiomessagerie étant configurée pour indiquer une identification de tous les UE dans le second groupe de services plus petit auquel appartient l'UE actuel.

6. Station de base selon la revendication 5, dans laquelle le processeur est configuré en outre pour, avant le fait de déterminer que l'équipement utilisateur, UE, actuel appartient au premier groupe de services ou au second groupe de services :

recevoir une première demande de service envoyée par l'UE, et envoyer la première demande de service à un réseau central ; et
 recevoir l'identification de l'UE appartenant au premier groupe de services plus grand renvoyée par le réseau central selon la première demande

de service, et classer l'identification de l'UE n'appartenant pas au premier groupe de services plus grand dans le second groupe de services plus grand.

5

7. Station de base selon la revendication 6, dans laquelle le processeur est configuré en outre pour, après classification de l'identification de l'UE n'appartenant pas au premier groupe de services plus grand dans le second groupe de services plus grand :

10

diviser le premier groupe de services plus grand en au moins l'un du premier groupe de services plus petit, et diviser le second groupe de services plus grand en au moins l'un du second groupe de services plus petit.

15

8. Station de base selon la revendication 5, dans laquelle le processeur est configuré pour, avant envoi du premier message de radiomessagerie à tous les UE du premier groupe de services plus petit auquel appartient l'UE actuel par l'intermédiaire d'une parmi la pluralité de premières occasions de radiomessagerie PO selon les premières informations de configuration qui sont pré-générées :

20

25

générer les premières informations de configuration et les secondes informations de configuration, et envoyer les premières informations de configuration et les secondes informations de configuration à l'UE,

30

les premières informations de configuration comprenant l'une parmi la pluralité des premières PO allouées à l'UE appartenant au premier groupe de services, et un canal de commande de liaison descendante physique, PDCCH, et un canal partagé de liaison descendante physique, PDSCH, correspondant à une première PO allouée et étant configurés pour transmettre le premier message de radiomessagerie, et

35

40

les secondes informations de configuration comprenant l'identification de la première PO pour transporter l'indication de radiomessagerie, la seconde PO allouée à l'UE appartenant au second groupe de services, et le PDCCH et le PDSCH correspondant à la seconde PO et étant configurés pour transmettre le second message de radiomessagerie.

45

50

55




FIG. 1




FIG. 2




FIG. 3A




FIG. 3B




FIG. 3C




FIG. 4




FIG. 5




FIG.6




FIG. 7




FIG. 8A




FIG. 8B




FIG. 8C




FIG. 9




FIG. 10A




FIG. 10B




FIG. 10C




FIG. 11




FIG. 12

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- EP 2369883 A1 [0005]