



US 20220012439A1

(19) **United States**

(12) **Patent Application Publication**
DUCKETT et al.

(10) **Pub. No.: US 2022/0012439 A1**

(43) **Pub. Date: Jan. 13, 2022**

(54) **INDUSTRIAL PRINTER**

(71) Applicant: **Avery Dennison Retail Information Services, LLC**, Mentor, OH (US)

(72) Inventors: **Jeanne F. DUCKETT**, Franklin, OH (US); **Richard D. WIRRIG**, Centerville, OH (US); **Lance D. NEUHARD**, New Carlisle, OH (US); **David J. WIMMERS**, Hamilton, OH (US); **Larri B. WILLIAMS**, Dayton, OH (US); **James A. MAKLEY**, Springboro, OH (US); **Jan M. WATSON**, Miamisburg, OH (US); **Andrew R. EVANS**, Centerville, OH (US)

(21) Appl. No.: **17/322,099**

(22) Filed: **May 17, 2021**

G06K 5/00 (2006.01)
B41J 3/407 (2006.01)
B41J 3/50 (2006.01)
G06K 17/00 (2006.01)
B41J 29/13 (2006.01)
G06K 1/00 (2006.01)
G06K 7/00 (2006.01)
G06K 19/07 (2006.01)
B41J 2/335 (2006.01)

(52) **U.S. Cl.**
CPC **G06K 7/10198** (2013.01); **A63F 2003/066** (2013.01); **G06K 5/00** (2013.01); **G06K 7/10316** (2013.01); **B41J 3/4075** (2013.01); **B41J 3/50** (2013.01); **G06K 17/0025** (2013.01); **B41J 29/13** (2013.01); **G06K 1/00** (2013.01); **G06K 7/00** (2013.01); **G06K 19/0725** (2013.01); **G06K 7/10366** (2013.01); **G06K 19/0723** (2013.01); **B41J 2/335** (2013.01); **G06K 7/10227** (2013.01); **G06K 1/20** (2013.01)

Related U.S. Application Data

(60) Continuation of application No. 16/816,792, filed on Mar. 12, 2020, now Pat. No. 11,010,571, which is a division of application No. 14/882,194, filed on Oct. 13, 2015, now Pat. No. 10,592,794.


(60) Provisional application No. 62/063,258, filed on Oct. 13, 2014, provisional application No. 62/063,213, filed on Oct. 13, 2014, provisional application No. 62/063,238, filed on Oct. 13, 2014, provisional application No. 62/063,227, filed on Oct. 13, 2014, provisional application No. 62/063,249, filed on Oct. 13, 2014.

Publication Classification

(51) **Int. Cl.**
G06K 7/10 (2006.01)
G06K 1/20 (2006.01)

(57) **ABSTRACT**

A high speed tabletop and industrial printer is disclosed with integrated high speed RFID encoding and verification at the same time. The industrial printer simultaneously prints on and electronically encodes/verifies RFID labels, tags, and/or stickers attached to a continuous web. The industrial printer comprises a lighted sensor array for indexing the printing to the RFID tags; and a cutter powered from the industrial printer for cutting the web that the RFID tags are disposed on. The industrial printer comprises two RFID reader/writers that are individually controlled. Specifically, one of the RFID reader/writers comprises the ability to electronically encode the RFID tags while the web is moving; and the second RFID reader/writer uses an additional RFID module and antenna on the printer for verifying the data encoded to the RFID tags.






FIG. 1





FIG. 2



SCALE 0.500

FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8A




FIG. 8B




FIG. 9A




FIG. 9B




FIG. 10A

COMMUNICATION PROCESS WITH FORE KNOWLEDGE OF THE COMMUNICATION SEQUENCE




FIG. 10B




FIG. 11




FIG. 12A




FIG. 12B




FIG. 13




FIG. 14




FIG. 15

APERTURE SENSOR CALIBRATION




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20A




FIG. 20B




FIG. 20C




FIG. 20D




FIG. 20E




FIG. 21

INDUSTRIAL PRINTER

CROSS-REFERENCE TO RELATED APPLICATION(S)

[0001] The present application is a continuation of U.S. patent application Ser. No. 16/816,792 filed Mar. 27, 2020, which is a division of U.S. patent application Ser. No. 14/882,194 filed Oct. 13, 2015, now U.S. Pat. No. 10/592,794, which claims the benefit of U.S. Provisional Patent Application Nos. 62/063,258 filed Oct. 13, 2014, 62/063,213 filed Oct. 13, 2014, 62/063,249 filed Oct. 13, 2014, 62/063,238 filed Oct. 13, 2014, and 62/063,227 filed Oct. 13, 2014, all of which are incorporated herein by reference in their entireties.

BACKGROUND

[0002] The present invention relates generally to thermal tabletop and industrial printers with radio frequency identification (RFID) read/write capabilities. More particularly, the present disclosure relates to a high speed tabletop and industrial printer with integrated high speed RFID encoding and verification at the same time. The present disclosure includes a passive NFC I²C inlay for the purpose of communication with the Printer's processor when using a NFC reader/encoder and a passive UHF, read by the embedded RFID Reader/Encoder, temperature inlay for the purpose of inputting the printer's temperature with the intention of using the temperature to improve printer operation.

[0003] Radio frequency identification (RFID) tags are electronic devices that may be affixed to items whose presence is to be detected and/or monitored. The presence of an RFID tag, and therefore the presence of the item to which the RFID tag is affixed, may be checked and monitored by devices known as "readers" or "reader panels." Readers typically transmit radio frequency signals to which the RFID tags respond. Each RFID tag can store a unique identification number. The RFID tags respond to reader-transmitted signals by providing their identification number and additional information stored on the RFID tag based on a reader command to enable the reader to determine identification and characteristics of an item.

[0004] Current RFID tags and labels are produced through the construction of an inlay which includes a chip connected to an antenna applied to a substrate. The inlay is then inserted into a single tag or label. These labels or tags are then printed by either conventional printing processes, such as flexographic processes, and then variable information may be printed either with the static information or singularity. The chips are then encoded in a printer which has a read/encoding device or separately by a reader/encoding device normally in a stop to encode process. This method is slow and costly due to multiple steps that are involved in the manufacture of the product. In addition, such a method can only be accomplished typically one tag or label at a time per lane of manufacturing capability. This can result in higher cost, limited output, and limited product variation in terms of size, color, and complexity.

[0005] Thus, there exists a need for an RFID printer that is capable of both printing on record members, such as labels, tags, etc., and capable of encoding, or writing to and/or reading from an RFID transponder contained on the record member, as well as verifying the data encoded to the RFID tags.

[0006] The present invention discloses a high speed tabletop and industrial printer with integrated high speed RFID encoding and verification at the same time. The industrial printer comprises two RFID reader/writers that are individually controlled, such that the industrial printer can encode and verify at the same time. Specifically, one of the RFID reader/writers encodes RFID tags while the web is moving; and the second RFID reader/writer verifies the data encoded to the RFID tags.

[0007] The present invention discloses a high speed tabletop and industrial printer with an integrated NFC I²C connected to the main processor of the printer. This chip enables an NFC transmitter to communicate with the printer's main processor to impact the operation of the printer.

[0008] The present invention discloses a RFID printer encoder that includes a UHF temperature inlay for the purpose of using the operating temperature of the printer to improve the performance of the printer read by the embedded RFID printer/encoder.

SUMMARY

[0009] The following presents a simplified summary in order to provide a basic understanding of some aspects of the disclosed innovation. This summary is not an extensive overview, and it is not intended to identify key/critical elements or to delineate the scope thereof. Its sole purpose is to present some concepts in a simplified form as a prelude to the more detailed description that is presented later.

[0010] The subject matter disclosed and claimed herein, in one aspect thereof, comprises a high speed tabletop and industrial printer with integrated high speed RFID encoding and verification at the same time. Specifically, the industrial printer simultaneously prints on and electronically encodes/verifies RFID labels, tags, and/or stickers attached to a continuous web. The industrial printer comprises a lighted sensor array for indexing the printing to the RFID tags; and an optional cutter powered from the industrial printer for cutting the web that the RFID tags are disposed on.

[0011] In a preferred embodiment, the industrial printer comprises two RFID reader/writers that are individually controlled, such that the industrial printer can encode and verify at the same time. Specifically, one of the RFID reader/writers comprises the ability to electronically encode the RFID tags while the web is moving; and the second RFID reader/writer uses an additional RFID module and antenna on the printer for verifying the data encoded to the RFID tags.

[0012] To the accomplishment of the foregoing and related ends, certain illustrative aspects of the disclosed innovation are described herein in connection with the following description and the annexed drawings. These aspects are indicative, however, of but a few of the various ways in which the principles disclosed herein can be employed and is intended to include all such aspects and their equivalents. Other advantages and novel features will become apparent from the following detailed description when considered in conjunction with the drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

[0013] FIG. 1 illustrates a front, perspective view of a thermal tabletop and industrial printer opened to reveal internal components in accordance with the disclosed architecture.

[0014] FIG. 2 illustrates a top, perspective view of the thermal tabletop and industrial printer in accordance with the disclosed architecture.

[0015] FIG. 3 illustrates a back, perspective view of the thermal tabletop and industrial printer with a cover on in accordance with the disclosed architecture.

[0016] FIG. 4 illustrates a back, perspective view of the thermal tabletop and industrial printer without the cover in accordance with the disclosed architecture.

[0017] FIG. 5 illustrates a right, perspective view of the thermal tabletop and industrial printer in accordance with the disclosed architecture.

[0018] FIG. 6 illustrates a left, perspective view of the thermal tabletop and industrial printer in accordance with the disclosed architecture.

[0019] FIG. 7 illustrates a top, perspective view of the thermal tabletop and industrial printer further identifying the I²C NFC inlay, Passive UHF Temperature sensor, an RFID verifier and an RFID encoder in accordance with the disclosed architecture.

[0020] FIG. 8A and 8B illustrate a flowchart disclosing an RFID read/write operation and a print operation of the thermal tabletop and industrial printer in accordance with the disclosed architecture.

[0021] FIG. 9A illustrates a line diagram of a traditional communication operation of an RFID printer in accordance with the disclosed architecture.

[0022] FIG. 9B illustrates a line diagram of a high level command optimization operation of an RFID printer in accordance with the disclosed architecture.

[0023] FIG. 10A illustrates a communication process without foreknowledge of a communication sequence of an RFID interrogator in accordance with the disclosed architecture.

[0024] FIG. 10B illustrates a communication process with foreknowledge of a communication sequence of an RFID interrogator in accordance with the disclosed architecture.

[0025] FIG. 11 illustrates a printer cover of the thermal tabletop and industrial printer comprising thumb screws in accordance with the disclosed architecture.

[0026] FIG. 12A illustrates a flowchart disclosing an RFID read/write and verify operation of the thermal tabletop and industrial printer in accordance with the disclosed architecture.

[0027] FIG. 12B illustrates a flowchart disclosing adaptive RFID power settings for the thermal tabletop and industrial printer in accordance with the disclosed architecture.

[0028] FIG. 13 illustrates a roll of tag supplies aperture mark holes for use with the thermal tabletop and industrial printer in accordance with the disclosed architecture.

[0029] FIG. 14 illustrates an array sensor of the thermal tabletop and industrial printer in accordance with the disclosed architecture.

[0030] FIG. 15 illustrates a close up view of a tag from the roll of tag supplies in accordance with the disclosed architecture.

[0031] FIG. 16 illustrates a flow chart of calibration in accordance with the disclosed architecture.

[0032] FIG. 17 illustrates a flow chart of tag sensing in accordance with the disclosed architecture.

[0033] FIG. 18 illustrates a cut away of the thermal tabletop and industrial printer comprising a sensor array in accordance with the disclosed architecture.

[0034] FIG. 19 illustrates a flow chart for setting backlight for a display of the thermal tabletop and industrial printer in accordance with the disclosed architecture.

[0035] FIG. 20A-20E outlines a process flow of RSSI improved singulation in accordance with the disclosed architecture.

[0036] FIG. 21 illustrates a transponder of the thermal tabletop and industrial printer in an ideal encode location over the RFID encoder antenna in accordance with the disclosed architecture.

DETAILED DESCRIPTION

[0037] The innovation is now described with reference to the drawings, wherein like reference numerals are used to refer to like elements throughout. In the following description, for purposes of explanation, numerous specific details are set forth in order to provide a thorough understanding thereof. It may be evident, however, that the innovation can be practiced without these specific details. In other instances, well-known structures and devices are shown in block diagram form in order to facilitate a description thereof.

[0038] The present invention discloses a high speed tabletop and industrial printer with integrated high speed RFID encoding and verification at the same time. The industrial printer is capable of both printing on record members, such as labels, tags, etc., and capable of encoding from an RFID transponder contained on the record member, as well as verifying the data encoded to the RFID tags. The industrial printer comprises two RFID reader/writers that are individually controlled, such that the industrial printer can encode and verify at the same time. Specifically, one of the RFID reader/writers encodes RFID tags while the web is moving; and the second RFID reader/writer verifies the data encoded to the RFID tags.

[0039] Referring initially to the drawings, FIG. 1 illustrates a thermal tabletop and/or industrial printer device 100 with integrated high speed RFID encoding and verification. The thermal tabletop and/or industrial printer 100, comprises a reader and/or encoding device, as well as a verification device. The reader and/or encoding device can read and program an RFID device, such as a RFID chip, that is contained in an inlay which may or may not be incorporated into a label, tag, or any other desired product, and which can also print onto the product without damaging or otherwise undesirably affecting the RFID device. The inlay may also be affixed directly to the product without necessarily being incorporated into a label or tag, such as through use of an adhesive to affix the inlay to the product.

[0040] In some exemplary embodiments, the products can be arranged into sheets or rolls, and multiple products can be printed, encoded, or verified at one time, in a sequential manner, simultaneously or substantially simultaneously. In some exemplary embodiments, reader and chip/antenna configurations can allow the encoding and verification to occur in line, so that printing, encoding, variable data imaging, verifying, and finishing can all be completed in one continuous process. As used herein a continuous process includes both a roll to roll configuration, and a sheet fed process in which there is no stopping of the process. Continuous may also include a slight incremental stopping, indexing, advancing or the like which does not last longer than a couple of seconds.

[0041] Furthermore, a cutter (not shown) can also be included in the printer 100. The cutter would be used to cut the web being printed on and the RFID tags disposed thereon. Typically, the cutter would be powered from the printer 100, or can be powered by any suitable means as is known in the art.

[0042] Printing as provided herein may be accomplished by using any number of processes, including impact and non-impact printers, flexographic, gravure, ink jet, electrostatic and the like just to provide some representative examples. Static printing may include company logos, manufacturers' information, size, color and other product attributes. Variable printing may include identification numbers, bar codes, pricings, store location and such other information as a retailer may decide is required.

[0043] Exemplary RFID devices, e.g. inlays, tags, labels and the like are available from Avery Dennison RFID Company and Avery Dennison Retail Information Services of Clinton, S.C. and Framingham, Mass., respectively. Such devices may be provided in any number of antenna and size configurations depending on the needs or end-use applications for which the product is intended. FIGS. 1-7 disclose multiple views of the industrial printer 100, and are described below. The printer 100 can be any suitable size, shape, and configuration as is known in the art without affecting the overall concept of the invention. One of ordinary skill in the art will appreciate that the interior and/or exterior shape of the printer 100 as shown in FIGS. 1-7 is for illustrative purposes only and many other shapes of the printer 100 are well within the scope of the present disclosure. Although dimensions of the printer 100 (i.e., length, width, and height) are important design parameters for good performance, the printer 100 may be any shape that ensures optimal high speed encoding and verification.

[0044] Generally referring to FIG. 1, the thermal tabletop and industrial printer 100 has a generally rectangular shape with a printer cover 101. However, tabletop printer covers can be cumbersome to remove when standard screws are used to fasten the cover down. Thus, in a preferred embodiment, the standard screws are replaced with thumb screws 103 (as shown in FIG. 11). The thumb screws 103 can be any suitable thumb screw 103 as is known in the art, and allow a user to easily remove the printer cover 101 whenever necessary without need of a screwdriver or other such tool. Further, the printer 100 comprises a front door 12 and handle 1. The front door 12 can be actuated via the handle 1 to provide access to the front of the printer 100 and to load supplies. Once the front door 12 is opened, the user installs the supply roll 3 on the supply roll holder 4.

[0045] The present invention contemplates that communication to the printers main processor can use Near Field Communication (HF RFID) for both forward and reverse data (not related to encoding, e.g. error display data, print jobs, printer settings) shown in FIG. 6 (23).

[0046] The supply roll 3 contains supplies for the printer 100 to print on. One configuration for the supplies is a pressure sensitive label comprising of a face sheet, adhesive layer and liner paper. After dispensing the labels, the liner take-up 5 acts as a rewind holder for spent liner from adhesive backed labels.

[0047] Furthermore, the printer 100 comprises a supply damper 6 that helps to remove vibration from the supply roll 3 to improve print quality. And, an out of stock switch 7 provides an on/off indication if supplies are loaded in the

printer 100, or if the printer 100 is in need of supplies. A supply guide or frame 8 holds and centers supplies. Further, an array sensor (shown in FIG. 2 as 35) is attached to the supply guide 8 to detect and accommodate minor variations in aperture location. An upper guide 11 guides supplies within the printer 100, and a loading label 18 (see FIG. 2) is a label indicating the supply path for users to load supplies into the printer 100. In one embodiment, the upper guide 11 includes a lighted paper path to illuminate the supplies for the user. The printer further comprises a print head 14. The print head 14 is a thermal print head such that the printer 100 automatically detects dot density and the location of failed heating elements. Additionally, the printer comprises a print head holder 15 which is a cast aluminum piece that the print head 14 is installed on to secure the print head 14 in place. Further a release handle 10 opens the printhead 14 and the printhead release tabs 36 (see FIG. 2) release printhead 14 from holder 15 when needed for servicing. The printer 100 also comprises a ribbon spindle 16 and a ribbon take-up 17. The ribbon spindle 16 is a DC motor-controlled supply for ribbon, and the ribbon take-up 17 is a DC motor-controlled takeup for ribbon. Further, a wireless antenna 2 is also included within the printer 100. The wireless antenna 2 is an 802.11 b/g/n dual band antenna for communicating with a router or other device. Additionally, the printer comprises two other intention transmitting antennas and 2 passive RFID antennas. An RFID antenna 9 to allow for the RFID encoding of supplies, and an RFID verifier 13, which is an external antenna for reading RFID supplies. It is noted that the power used to on the second RFID module controlling the verify antenna can be either the read power from the first RFID module, the write power from the RFID encode module or another optimum value. I²C NFC 1356 MHz antenna is attached to the main processor contained on 29. Underneath the supply guides 8 is a UHF Temperature Sensor 37 whereas RFID Encoder Antenna 34 can be used to read the operating temperature of the printer.

[0048] Generally referring to FIG. 2, the printer 100 comprises an overhead LED (light emitting diode) door 19 which covers the overhead LED board 20 which is a reflective supply sensor LED. Further, the printer includes an LED cap 21 which is a reflective supply sensor reflector, and an index sensor 35 which is a unique array sensor that automatically detects aperture sense marks. The index sensor 35 comprises a sensor cap 19. Print head release tabs indicated by reference numeral 36 are illustrated in FIG. 2 to aid in easy release of the print head 14. Specifically, the lighted sensor array 35 provides a lighted supply path 22 that automatically senses the position of holes disposed through the web which are used for sense marking, and correctly indexes the printing to the RFID tags. By using the sensor array 35, the printer 100 can determine which of the individual sensors within the array should be used for the indexing to account for manufacturing variations in the placement of the aperture.

[0049] Generally referring to FIG. 3, the back of the printer 100 comprises a back cover 26 that covers the electronics panel (shown in FIG. 4). A display panel 25 displays a user interface, and the wireless antenna 2 (as shown in FIG. 1) can also be seen on the back of the printer 100. Generally referring to FIG. 4, the back of the printer 100 is shown without the cover 26. A CPU board 29 or main PC board is shown, as well as an RFID I/O board 27 which is a module that contains both the encoding and verification

modules. A power supply **28** which is the main supply for power in the printer **100** is also shown at the back of the printer **100**. Furthermore, the display panel **25** (as shown in FIG. 3), and the wireless antenna **2** (as shown in FIG. 1) can both be seen in FIG. 4 as well.

[0050] Generally referring to FIG. 5, the right side of the printer **100** is shown. The right side of the printer **100** shows the access door **32**, as well as the wireless antenna **2** (as shown in FIG. 1). Further, the CPU board **29** (as shown in FIG. 4) is shown, as well as an I/O switch **30** and an I/O outlet **31**. Generally referring to FIG. 6, the left side of the printer **100** is shown. The left side of the printer **100** shows the wireless antenna **2** (as shown in FIG. 1), as well as a supply exit door **22** that secures and allows access to the supply roll **3**. Further, a NFC I2C chip **23** is also disclosed which provides unique capability to the printer **100** and allows the printer **100** to communicate directly with the main processor through a bridge. Finally, the printer **100** comprises a display panel **25** which includes a keypad **24**.

[0051] In a preferred embodiment, the printer **100** includes a plurality of keys including the keypad **24** and a trigger key (not shown). The keypad **24** may be utilized to enter alpha-numeric data to the printer **100**. Alternatively, the keypad **24** may have only a limited number of keys that are actuable in accordance with information depicted on the display **25** for selecting a number of operations of the printer, for example, feeding a web of record members through the printer **100**, displaying status information, etc. The trigger key may be actuable by a user in various modes of the printer **100** to actuate the printing system and/or a RFID read/write module **34**. Alternatively, one or more of these devices can be actuated automatically by a controller of the printer **100** in accordance with a stored application program. In addition to displaying status information or data entered via the keypad **24**, the display **25** may also be controlled to provide prompts to the user to actuate the trigger key and/or other keys so as to control various operations of the printer **100**.

[0052] Generally referring to FIG. 7, the top, perspective view of the printer **100** discloses the RFID verifier **33** and the RFID encoder **34** (as shown in FIG. 1 as antennas **9** and **13** respectively), as well as UHF Temperature RFID Tag **37**. Specifically, the RFID encoder **34** encodes RFID tags while the web is moving, and the RFID verifier **33** verifies the data encoded to the RFID tags. Also disclosed on FIG. 7 is the UHF temperature passive tag used to acquire the operating temperature of the printer.

[0053] Specifically, the industrial printer **100** comprises two RFID reader/writers (**33** and **34**) that are individually controlled, allowing the industrial printer **100** to encode and verify at the same time. Thus, the industrial printer **100** comprises both an RFID writer or encoder **34** module and an RFID verifier **33** module that operate independently encoding and verifying RFID transponders within the label, tag, or other construction media. The two RFID modules cooperate with each other and with the processor of the industrial printer **100**. The RFID encoder module **34** encodes the desired information to the RFID transponder when the transponder reaches the encoding location. The RFID verifier module **33** reads the transponders and compares it with information provided by the printer controller. Then, any stock that contains a failed RFID may optionally be marked by the print mechanism, so as to designate it as defective

with a visual indication for the user, and the failed verification will be sent to a host for data logging purposes.

[0054] Furthermore, typically RFID output power is set to what is necessary to encode the transponder that is electrically singulated in the RF field. There is no other singulation for the transponders therefore it is expected that there is only one transponder present in the RF field at a time. However, the transponder positioned over the antenna may be defective or less sensitive to the set power level such that an adjacent transponder is acquired by the antenna and therefore encoded. Thus, to prevent misreads or other errors such as duplicate tags with the same encoded data, the printer **100** may use adaptive RFID power settings.

[0055] Specifically, two power levels are employed to assist in the electrical singulation by software. As reading the contents of a transponder requires less power than encoding it, a sufficiently low power level is used to create an RF field small enough in strength so that the only transponder acted upon is the one positioned immediately over the antenna. At this read power level, the serialized tag identification (TID) field of the RFID transponder would be read and saved. Next, the power level would be increased to the level necessary to write the tag. The TID serial number would be included in the encode command to singulate on the particular tag containing the serial number and ignore any adjacent tags that may accidentally be in the RF field. Finally, the RF power level is reduced back down to the selected read level, such that the RFID verifier can read and compare the encoded data of the tag with the data originally sent in the write command to confirm the tag is accurately encoded.

[0056] Furthermore, it is known that there is variation within a supply roll from RFID transponder to RFID transponder. The disclosed printer **100** utilizes an adaptive algorithm that will allow for a variation in transponders without generation of an error. This algorithm will start at a read power low enough not to detect a transponder and then will increment up in steps until a transponder is seen. For the next transponder, the previous detection point will be used as a starting point and then will increment up if needed. If more than one transponder is detected the read power will be reduced. If no transponders are detected, then the read power will be increased until a transponder is detected. The selected power will then be used as a starting point for the next transponder and so forth.

[0057] Generally referring to FIGS. 8A-B, the microprocessor controls the printer **100** of the embodiments of the present invention to encode, write to and/or read an RFID transponder in a label and to print on that same label. When the processor decides that the label must be stopped to be encoded at block **800**, the processor then controls the printer motor to feed a label into position at which point the movement of the label web is stopped. Once the label is in position, the RFID transponder will be generally aligned with the antenna. At block **802**, the microprocessor retrieves data from the memory that has been sent from the host for writing to the RFID transponder. This data may be for example electronic product code (EPC) information or other data. Thereafter, at block **804**, the microprocessor generates a program command. The program command is a packet of control information to be sent to the RFID interrogator or module. From block **804**, the microprocessor proceeds to block **806** to send the generated packet to the RFID module i.e. interrogator.

[0058] It is noted that in a preferred embodiment, the RFID module or interrogator includes its own microprocessor. The RFID module performs a number of functions. For example, the module determines whether an RFID transponder is within its field by reading the RFID transponder's identification code. The RFID module as instructed by the controller erases the data stored in the RFID transponder, verifies the erasure and then programs the RFID data received from the microprocessor into the RFID transponder. The RFID module also verifies that the data has been programmed into the RFID transponder by reading the data stored in the transponder after a programming operation to verify that the data was correctly written into the RFID transponder. Upon completing the verification process, the RFID module generates a response packet that is transmitted back to the microprocessor.

[0059] The microprocessor, at block **808**, receives the response packet from the RFID module and at block **810**, the microprocessor extracts data from the response packet. The data in the response packet may include a code representing the successful programming of the RFID transponder or the data may include a code representing a particular error. For example, the response data may include an error code indicating that the RFID module could not read an RFID tag, or a code indicating that the tag could not be erased or a code indicating that the tag was not accurately programmed. At block **812**, the microprocessor decodes the data in the response packet to determine at block **814** whether the programming of the RFID transponder was successful or whether the response packet from the RFID module included an error code. If the programming of the RFID transponder was determined to be successful, that is, without error, at block **814**, the microprocessor proceeds to block **816** to control the feeding or movement of the web and the printing of data on the label via the print head. It is noted, that while the RFID transponder is being read from or programmed, the web is stationary. However, during the printing of information on a record member at block **816**, the microprocessor moves the web past the print head during the printing operation. If the microprocessor determines at block **814** that the response packet received from the RFID module indicated an error condition, the microprocessor proceeds to block **818** to display an error message on a liquid crystal display of the printer. From block **818**, the microprocessor proceeds to block **820** to feed the label with the defective RFID transponder past the print head and controls the print head to print an overstrike image, such as evenly spaced longitudinally extending bars, on the record member RM. This indicates that the RFID transponder is defective. From blocks **816** or **820**, the microprocessor proceeds to block **800** to feed the next label into position as discussed above.

[0060] Furthermore, in a preferred embodiment, the thermal printer **100** also provides for optimized RFID encoding by reducing the time required to complete a user defined command sequence. A user sequence may include the following command sequence that will select a tag, write the words (6-15 words) of the EPC memory, write the access password in the reserved memory and set the lock memory to password lock and then read the banks of the EPC memory. In a RFID printer with a RFID writer (interrogator) there are two opportunities for optimization. The RFID printer communicates across a communication channel for example serial, USB or other method to a RFID writer that contains an independent processor. This communication

involves a handshake and necessary error processing. If it is already known that a sequence of commands will be sent to the RFID writer, the implementation of a command stack sent in one sequence will eliminate unnecessary overhead between the RFID printer and the RFID writer. Generally referring to FIG. **9A**, traditional communication operation **900** would involve the RFID printer **901** issuing individual commands for Write EPC **902**, Write Access **904**, Password Lock **906**, and Read EPC **908**, then the RFID interrogator **903** would process each command (**902**, **904**, **906**, and **908**) and respond **910** after each command creating unnecessary overhead between the RFID printer **901** and the RFID interrogator **903**. Generally referring to FIG. **9B**, the RFID printer **901** creates a high level command optimization operation **907**, wherein the RFID printer **901** issues the individual commands of Write EPC, Write Access, Password Lock, and Read EPC as one command **912**, allowing the RFID interrogator **903** to process all the commands **912** at once and then respond **914**, saving time and eliminating the unnecessary overhead between the RFID printer **901** and the RFID interrogator **903**.

[0061] In addition, between the RFID writer and the RFID tag there is a handshake that can be optimized if there is pre-knowledge that a set of high level commands will be sent. The handshake process can be optimized if there is no reason to power down the RFID tag. However, one reason the RFID tag may need to be powered down is to change the power level to a different power. For instance, if the RFID tag EPC memory was written at one power and the RFID tag EPC memory was read at a different power, then a power down is necessary.

[0062] Furthermore, EPC RFID access commands must follow an inventory to obtain the tag handle REQ_RN. For each access (Read, Write, Kill, Lock) command that is done this sequence must be followed. For a thermal barcode printer with an RFID writer this sequence contains redundant steps if more than one access command is executed after the tag has been acquired since the REQ_RN handle must be reacquired for the same tag for each access command. The EPC Gen 2 protocol specifies that as long as the tag is powered on it must retain the REQ_RN handle. Thus, in order to optimize the command sequence, the select and inventory commands issued for each access command have been optimized out as long as the tag is powered on.

[0063] Generally referring to FIG. **10A**, the traditional communication process of a high level command sequence, for illustrative purposes the following commands: Write EPC, Write Access Code, Lock Tag, ReadEPC; without foreknowledge of communication requires the RFID Interrogator **1053** for to issue the command sequence for encoding the 96 bit EPC, a query command **1058** and the RFID tag **1059** will respond RN_16 ,**1060**, then the RFID Interrogator **1053** issues Ack (RN16) **1058** and the RFID tag **1059** responds with PC, EPC & CRC-16 **1060** to identify the command stream. Then the RFID Interrogator **1053** issues REQ_RN **1058** and the RFID tag **1059** issues the handle (New RN16) **1060**, then the RFID Interrogator **1053** issues the Write Command **1058** and the RFID tag **1059** responds with the Status—Success, Error Failure **1060**. At this point the RFID Interrogator **1053** issues Read PC bits and Req RN **1058** to which tag **1059** responds with the EPC. Since the RFID Interrogator had not preprocessed the command sequence in Encode Access Password the chip must be powered on and transitioned to the Open state. **1062**. RFID

Interrogator **1053** reissues the Query, ACK, Req RN, Req RN before writing the Access Password in **1062**. The tag **1059** will respond appropriately in **1064** to these commands. Next the RFID Interrogator **1053** will issue the command sequence required to lock the tag **1059**. Since the tag **1059** was not kept in the open state the RFID Interrogator **1053** will need to reissue Query, ACK, Req RN **1066**, Req RN before locking tag **1059**. Tag **1059** will respond appropriately **1068**. A final read is shown in **1074** that could be used for validation purposes to ensure accuracy. The tag **1059** is starting from power on the Query, ACK and Query Rep need to be issued from RFID Interrogator **1053** to which tag **1059** responds in **1072**. However, if the RFID Interrogator **1053** already has knowledge of a command stream as illustrated in FIG. **1013** then the select and query commands become redundant, and the interrogator **1053** and the chip (or tag **1059**) only need to issue the Req-RN **1020** before receiving the next access command **1022**. Thus, as illustrated in FIG. **1013**, the communication process with foreknowledge of the communication sequence discloses the RFID Interrogator **1059** issuing the next access commands **1016** and **1022** to encode the Access Password the Query and ACK are eliminated to increase the encoding throughput. Req_RN command at **1022** followed by the 32-bit write to the access password. RFID tag **1009** at **1024** issuing the handle (New RN **16**) **1024** and the RFID Interrogator **1003** responding with the Access Command **1026** and the RFID tag **1009** responding with the Status Success, Error Failure **1028**. This process is continued to be followed in **1026** for the lock command. In **1028** the tag **1009** responds appropriately. If it is desired to do a final read to ensure encoding accuracy if the read is at the same power the process between **1003** and **1009** is shown streamlined in **1030** and **1032**. Thus, with knowledge of a command stream, the communication sequence between the interrogator **1003** and the chip (or tag **1009**) can be optimized via removal of the query and Ack commands between the access commands. This optimization reduces the overall cycle time. Further, a composite RFID Interrogator Host Write memory command which provides for successive writes to various memory blocks in a RFID Gen 2 Tag device before returning the results of the command to the host can be utilized to optimize system throughput. This command accepts memory block identification for each memory block to be written and data to be written into each memory block. The RFID Interrogator executes the necessary Gen 2 RFID tag device commands to place the tag into the Open State and then proceeds to execute to Gen 2 the successive Write commands to the various memory blocks, defined in the host command.

[0064] When all memory blocks have been written, the RFID Interrogator returns the tag device to the ready state and returns the status of the results to the host.

[0065] Furthermore, optimization of the thermal printer occurs with successive write and verify commands. Specifically, a composite RFID interrogator host write/verify command which provides for multiple writes to various memory areas in an RFID Gen 2 tag device where the tag device is left in the Open state for the duration of the entire set of command write/verification operations is utilized. The command is executed in two stages. In the first stage, the command is defined as a record with a unique ID, followed by a flag that specifies whether an optional tag identification (TID) is to be used for identifying the tag to be written to. This is followed by one or more write directives, where each

directive is comprised of the memory bank to write to, the word offset into the memory bank to begin writing, the number of words to write, and a flag that indicates whether the write is to be verified.

[0066] In the second stage, the data to be encoded for each tag is sent as a record beginning with a unique ID that matches the ID defined in the first stage, followed by an optional TID used to identify the tag in the RF field, followed by one or more write directives that match the write directives defined in stage 1. In this record each write directive contains the actual data to be written to the memory areas specified in stage 1. After writing, the specified memory banks optional verification read could occur in the same state where allowed by the chip architecture. Upon completion of the write and verification phases the Interrogator powers the tag device down and returns the results of the command to the host.

[0067] Thus, this composite RFID Interrogator Host Write memory command would be used in the RFID enabled thermal barcode printer **100** reducing the amount of time required to complete a user defined command sequence increasing the overall throughput of the RFID encode sequence which would allow a user to increase the throughput and encode at higher web speeds. As a result, more RFID tags per minute can be produced thus increasing printer productivity. This higher productivity would increase printing capacity to meet demand.

[0068] Generally referring to FIGS. **1-7**, an exemplary embodiment of a system which may include at least a printer **100** and encoder/verifier is shown. Printer **100** can print through ink jet, flexographic, offset, gravure, digital offset or xerographic digital processes, or any other desired print process. Printer **100** can accept input information in any format, for example Portable Document Format (PDF), Personalized Print Markup Language (PPML), Java Script Object Notation (JSON) or any other desired format. The information is typically provided from a computer which may either be co-located with the printer **100** or may be provided in a remote location. The printer **100** may be connected to the computer via an intranet or over the Internet, depending on the requirements of the manufacturing operation. Printer **100** can also include one or more RFID readers and RFID encoders **34** (as shown in FIGS. **1-7**, such as for example FIG. **7**) which can be arranged in any configuration, for example in a configuration that allows RFID encoding to occur in line, either before or after printing.

[0069] In exemplary embodiments, printer **100** can contain multiple RFID readers and RFID encoders **34**, arranged in such a way that allows multiple products, for example in sheet or roll form, to be printed and encoded as part of a continuous process. It should be understood that the reader and encoder can be combined in a single unit or provided in a two separate components. Printer **100** can also comprise an RFID verifier **33** that verifies the data encoded by the RFID encoder **34**. The RFID encoder **34** and RFID verifier **33** are individually controlled such that encoding and verifying can occur at the same time. Printer **100** can also isolate adjacent products from radio-frequency cross-coupling and interference using physical screening, for example with a moving shutter, electrical screening, for example using infrared light or an interfering carrier signal, or by any other desired method for providing electrical shielding.

[0070] Still referring to FIGS. 1-7, printer 100 can also have a quality control system (not shown), such as a vision inspection system, RFID test system or other device to ensure adequate quality in the unit. Quality control system can be located in line with the printer 100, or it can be located off line, such as with a remote RFID test station. Quality control system can include one or more RFID readers and RFID encoders 34, which can allow quality control system to check products for errors in RFID encoding. Quality control system can also include optical readers or scanners in any desired configuration, which can allow quality control system to check products for errors in printing. Quality control system can further include a die cutter, which can allow the system to separate improper or defective products so that they can be discarded or reprocessed. RFID products that are detected as being defective can be marked or otherwise identified so that they can be removed from the web or sheet during manufacturing or inspection or can be easily recognized by the customer so that the end user does not use the defective tag as part of RFID tag or label.

[0071] Referring generally to the FIG., printer/encoder 100 can encode RFID devices using full encoding or it can encode RFID devices or products using partial encoding with the remainder of the coding to be completed by the end user such as a retail or brand owner. When using full encoding, printer/encoder 100 may fully program each RFID device or product individually. This programming can occur all at once (e.g. substantially simultaneously) or in stages, in an incremental fashion or as desired. When using partial encoding, printer/encoder 100 can program each RFID device or product with only a portion of the information that is to be stored on the products. This programming can occur all at once or in stages, as desired. For example, when using EPCs and partial encoding, printer/encoder 100 can receive a sheet of RFID products that have already been programmed with the portion of the EPCs that are common to all RFID products in the sheet, batch of sheets or roll. This can allow printer/encoder 100 to save time by only encoding each RFID device or product with variable information that is different for each product in the sheet or roll. In some embodiments, fixed data fields can be encoded and the unique chip identification number can be used as the serialization.

[0072] In another embodiment, the printer 100 includes a microprocessor and a memory (not shown). The memory includes non-volatile memory such as flash memory and/or a ROM such as the EEPROM. The memory also includes a RAM for storing and manipulating data. In accordance with a preferred embodiment of the present invention, the microprocessor controls the operations of the printer 100 in accordance with an application program that is stored in the flash memory. The microprocessor may operate directly in accordance with the application program. Alternatively, the microprocessor can operate indirectly in accordance with the application program as interpreted by an interpreter program stored in the memory or another area of the flash memory.

[0073] The microprocessor is operable to select an input device to receive data therefrom and to manipulate the receive data and/or combine it with data received from a different input source in accordance with a stored application program. The microprocessor couples the selected, combined and/or manipulated data to the printing system for printing on a record member. The microprocessor may select

the same or different data to be written to an external RFID chip. The microprocessor couples the data selected for writing to the RFID read/write module wherein the data is written in encoded form to the external RFID chip. Similarly, the microprocessor can select the same or different data for storage in a transaction record in the RAM and for uploading via the communication interface to a host. The processor is operable to select data to be coupled to the printing system independently of the data that the processor selects to be coupled to the RFID read/write module to provide greater flexibility than has heretofore been possible.

[0074] Generally referring to FIG. 12A, the industrial printer 100 comprises two RFID reader/writers (33 and 34) that are individually controlled, allowing the industrial printer 100 to encode and verify at the same time. Thus, the industrial printer 100 comprises both an RFID writer or encoder 34 module and an RFID verifier 33 module that operate independently encoding and verifying RFID transponders within the label, tag, or other construction media. The two RFID modules cooperate with each other and with the processor of the industrial printer 100. At 200, a label is fed into position, and then at 202 the RFID encoder module 34 encodes the desired information to the RFID transponder when the transponder reaches the encoding location. At 204, the RFID verifier module 33 reads the transponders and at 206 compares it with information provided by the printer controller. Thus, the two RFID reader/writers (33 and 34) are operated independently (see 208), allowing the industrial printer 100 to simultaneously encode and verify the RFID transponders within the RFID labels (see 210). At 212, it is determined whether the RFID tag contains a failed RFID. Then, at 214 any stock that contains a failed RFID may optionally be marked by the print mechanism, so as to designate it as defective with a visual indication for the user, and the failed verification will be sent to a host for data logging purposes (see 216). It may be advantageous to place a shield between the two RFID reader/writers 33 and 34 as shown in 1820 FIG. 18 to minimize the cross talk between the two RFID reader/writers 33 and 34.

[0075] Furthermore, typically RFID output power is set to what is necessary to encode the transponder that is electrically singulated in the RF field. There is no other singulation for the transponders therefore it is expected that there is only one transponder present in the RF field at a time. However, the transponder positioned over the antenna may be defective or less sensitive to the set power level such that an adjacent transponder is acquired by the antenna and therefore encoded. Thus, to prevent misreads or other errors such as duplicate tags with the same encoded data, the printer 100 utilizes adaptive RFID power settings.

[0076] Specifically, two power levels are employed to assist in the electrical singulation by software. As reading the contents of a transponder requires less power than encoding it, a sufficiently low power level is used to create an RF field small enough in strength so that the only transponder acted upon is the one positioned immediately over the antenna. At this write adjust power level, the serialized tag identification (TID) field of the RFID transponder would be read and saved. Next, the power level would be increased to the level necessary to write the tag. The TID serial number would be included in the encode command to singulate on the particular tag containing the serial number and ignore any adjacent tags that may accidentally be in the RF field. Finally, the RF power level is

reduced back down to the selected write adjust level, such that the RFID verifier can read and compare the encoded data of the tag with the data originally sent in the write command to confirm the tag is accurately encoded.

[0077] Furthermore, it is known that there is variation within a supply roll from RFID transponder to RFID transponder. The disclosed printer **100** utilizes an adaptive algorithm that will allow for a variation in transponders without generation of an error. This algorithm will start at a write adjust low enough not to detect a transponder and then will increment up in steps until a transponder is seen. For the next transponder, the previous detection point will be used as a starting point and then will increment up if needed. If more than one transponder is detected the write adjust owner will be reduced. If no transponders are detected, then the write adjust power will be increased until a transponder is detected. The selected power will then be used as a starting point for the next transponder and so forth. If this is not sufficient to uniquely identify the transponder the singulation process will be enhanced as follows.

[0078] Generally referring to FIG. **12B**, two power levels are employed to assist in the electrical singulation by software. As reading the contents of a transponder requires less power than encoding it, a sufficiently low power level is used to create an RF field small enough in strength so that the only transponder acted upon is the one positioned immediately over the antenna (see FIG. **12b**, **300**). At this writer adjust power level, the serialized tag identification (TID) field of the RFID transponder would be read and saved (see **302**). At **304**, the power level is increased to the level necessary to write the tag. At **306**, the TID serial number would be included in the encode command (see **312**) to singulate on the particular tag containing the serial number and ignore any adjacent tags that may accidentally be in the RF field. At **308**, the RF power level is reduced back down to the selected read level, and at **310** the RFID verifier can read and compare the encoded data of the tag with the data originally sent in the write command to confirm the tag is accurately encoded.

[0079] Furthermore, it is known that there is variation within a supply roll from RFID transponder to RFID transponder. The disclosed printer utilizes an adaptive algorithm that will allow for a variation in transponders without generation of an error. At **314**, this algorithm will start at a writer adjust power low enough not to detect a transponder and then at **316** will increment up in steps until a transponder is seen. For the next transponder, the previous detection point will be used as a starting point and then will increment up if needed (see **318**). If more than one transponder is detected the writer adjust power will be reduced. If no transponders are detected, then the writer adjust power will be increased until a transponder is detected. The selected power will then be used as a starting point for the next transponder and so forth.

[0080] In FIG. **13**, **1310**, shows a representation of a web of tag supply with aperture holes. Reference numeral **1540** (see FIG. **15**) indicates one embodiment of the aperture on the tag located on roll **1310** that be pushed past sensor **1410** (see FIG. **14**) retained in supply guide **8**. In one embodiment the aperture hole enables light to pass from the emitter to the detector as it moves by the sensor array indicated by **1810** on FIG. **18** which obtains the reference voltage by using the controller logic retained on CPU board **29**. The aperture or break in the supply **1310** will normally exceed the focal

point of one of the sensors **1410**. The aperture or break in supply **1310** can be aligned anywhere along sensor **1410**.

[0081] Prior to running supplies **1310** through printer **100** it would be expected that the calibration processes initiated in process **1610** depicted on FIG. **16** would be completed. The flow of calibration is to prompt the user if they would like to calibrate aperture supply, **1620**, if not the process exits in **1630**. If the user wishes to continue and the aperture supply is calibrated, the user is prompted to align the aperture in sensor **1410** installed in printer **100** for the calibration process. The diameter of the aperture shown by reference numeral **1510** in FIG. **15** must be placed in sensor **1410** prior to moving to decision point **1660**. The user is prompted verify that the supplies are properly aligned in **1660** prior to moving the **1670** to acquire the actual voltage. The read voltage is compared to the desired reference voltage if the read voltage in **1670** meets or exceeds the reference voltage the process is completes and exits in **1680**. If the read voltage is less than the reference voltage the power is increased to the sensor in **1640** and the read voltage is acquired again.

[0082] When printer **100** prepares to move web **1310** showing a feed direction in **1530** in FIG. **15**, the selected media sensor enters the process of checking which sensor is being used, **1710** on FIG. **17**. Prior to testing the sensors there is a test to determine if the web is moving in **1750**. If there is no movement the process exits in **1730**. If the aperture sensor is selected **1720** the process continues to **1740** or else the process exits in **1730**. In **1740** the voltage determined in **1670** is applied to sensor **1410**. The voltage is acquired from sensor **1410** in **1760**. A test is completed in **1770** to determine if the reference voltage matches or exceeds the reference voltage. If not the process returns to **1720**. If the reference voltage does exceed reference voltage in **1780** it is recorded that a mark is seen and the process terminates in **1790**. This process represents one example of control logic for sensor **1410**. In other examples is presumed that hysteresis would be added to the control logic depicted in FIG. **17** to prevent false readings of a mark.

[0083] In FIG. **19**, **1910** shows checking the status of the printer in order to set the backlight for the display shown in **25** on printer **100**. When the status of the printer is determined one of four paths are followed: **1920** is if the status of the printer is idle a backlight will be set to white. In **1930** if the status of the printer is offline the backlight is set to white. In **1940** if the status of the printer is active the backlight is set to green. In **1950** if the status of the printer is an operator intervention required the backlight is set to read. Finally, the process enters the sub process **1960** to count down the system flag status check. If **1970** when the count reaches zero, we reenter **1905** to reset the interval counter and then check the current status of the industrial printer in **1910**.

[0084] RSSI singulation process begins with **2010** in FIG. **20A**. Printer **100** either back feeds or forward feeds in order to center the metal of the first candidate inlay over the centerline of the coupler depending on the value of tag save as indicated by **2020**. The amount of distance to overfeed, **2040**, or back feed, **2030**, as determined by the user in identifying the ideal couple point which will be referred to as first TID position.

[0085] In step **2050** the power is set to a write adjust power and (in **2060**) attempt to read a 96-bit TID. In **2070** it is determined if we successfully read a **96** bit tag is success-

fully read. If yes, the method continues on to **2100**, where the web can be encoded while moving; if the web is not encoded while moving, in step **2090** the process stops encoding. If the web is encoded while moving the inventory command tag population is taken at step **2140**. If we fail to read a 96 bit transponder at **2070**, the process continues to step **2080**. On step **2080** the system attempts to read a 64 bit transponder in **2120**. If we fail, we will record the error as **739** and go to **2130**. If successful, else we go to step **2100**. In **2100** we determine if we are encoding while the web is moving. If this is a stop to encode case we go to **2190**.

[0086] In the case of encoding while the web is moving we will do a tag inventory with the tag population set to 4. If from the tag inventory we receive 0 tags, we will record error **741** and go to error processing **2130**. If we find 4 or more transponders, we will record error **727** and go to error processing **2130**. If there is only one transponder we will determine if we are going to move forward or reverse in step **2190**. If there are 2 or 3 tags the RSSI values will be compared in step **2160**. If there is not a transponder with a count return signal strength indicator of **100** or more at **2170**, we will record error **740** and proceed to error processing **2130**. If there is a candidate transponder indicated by the RSSI we will processed to step **2190** to determine motion direction.

[0087] In step **2190** depending on the user selection of the Tag Saver value we determine the motion. If the value is yes, we processed to the tag saver function in **2210** if the value is no we processed to encoding the transponder in **2200**.

[0088] For encoding the transponder in **2200** we will proceed to **2270** to determine the number of transponders located as illustrated in FIG. 20B. If there was one transponder located, we encode it in **2260** and proceed to the finish encode in **2250**. If the number of transponders in **2270** is greater than 1 we go to **2280** to advance the encode zone into the RFID encode antenna. If **2290** we perform another inventory with a transponder population set to 2. In **2300** we determine the number of transponders that responded. If the number is less than 1 or greater than 2 we record the error as **740** and proceed to error process **2130**. If there was one tag responding in **2320** we determine if we have already seen this transponder. If we have, we record the error as **740** and proceed to error process **2130**. Is this the first time we have seen this transponder we proceed to encoding in **2340**. Backing up to step **2300** if two tags responded we processed to **2310** where we decide if one of the tags has been seen before. If not, we record the error as **740** and proceed to error process **2130**. If we have seen on of the transponders before we proceed to select new transponder in **2330** and proceed to **2340** to encode transponder.

[0089] In **2340** we encode the transponder with the new data setting **S3** and proceed to finish encoding in **2250**.

[0090] If after **2190** it was determined that the tag saver was desired by the user in **2210** we proceed to **2220** to reverse motion the transponder over the RFID encoding antenna show in FIG. 21 **22000**. The tag inventory with the transponder population set to 1 in **2230** is performed. If only 1 transponder responds we proceed to **2340** to encode the required data into the transponder. If there is any other response error **736** is recorded and we proceed to error processing **2130**.

[0091] After **2130**, the method proceeds to finish encode in **2250**. A decision point is reached if we have more inlays to process as required by the user in **2350** as illustrated in

FIG. 20C. If there is no decision point, then in step **2400** a done state is reached. If there are more inlays to process, we increment the step count **2360** for the RFID process and then look to see if the step count is equal to the next inlay position in **2370**. If no, return to increment the step count. If yes, we do an inventory with a transponder population set to 1 setting **S2** in step **2380**. If there do a check in **2390** if we located 1 transponder. If we did in **2410** we encode the transponder with the required data and proceed to **2350** decision. If there is any other response, we set the error code to **741** or **736** and proceed to error processing **2130**.

[0092] If at decision **2100** we took the stop to encode path this is the process as illustrated in FIG. 20D. In **2090** we proceed to determining if the motion is stopped in **2420**. If no, we return wait. If yes, we proceed to **2430** and do a tag inventory with the population set to 4. If we received 0 or more than 4 tags responding in **2440** we mark the error code and proceed to error process **2130**. If there was 1 tag, we proceed to **2470**. If we received 2 or 3 tags, we compare the RSSI value at **2450**. In **2480** we check to see if we have an RSSI value of on tag that is at **100** count greater than the other tags. If no, we mark the error code **740** and proceed to error process **2130**. If yes, we proceed to **2470** and encode with the required data.

[0093] In **2480** we determine if there are more transponders to encode if yes we return to decision point **2420**. If no, we proceed to a done state at **2400**.

[0094] The error process as illustrated in FIG. 20E is brief; at **2130** we enter the error process. On **2490** we stop motion of printer **100** and inform the user there is an error then proceed to the done state **2400**.

[0095] What has been described above includes examples of the claimed subject matter. It is, of course, not possible to describe every conceivable combination of components or methodologies for purposes of describing the claimed subject matter, but one of ordinary skill in the art may recognize that many further combinations and permutations of the claimed subject matter are possible. Accordingly, the claimed subject matter is intended to embrace all such alterations, modifications and variations that fall within the spirit and scope of the appended claims. Furthermore, to the extent that the term “includes” is used in either the detailed description or the claims, such term is intended to be inclusive in a manner similar to the term “comprising” as “comprising” is interpreted when employed as a transitional word in a claim.

1. A commercial printer device for printing on and electronically encoding and verifying one or more radio frequency identification (RFID) labels, tags, or stickers attached to a continuous web, comprising:

a print head capable of printing on the continuous web; and

an RFID reader/writer configured to electronically encodes the RFID label, tag, or sticker with data while the continuous web is moving;

wherein the printer device can read and encode and print on the RFID label, tag, or sticker without damaging the RFID tag; and

wherein the printer is configured to send as one command: write EPC, write access, and read EPC.

2. The printer device of claim 1, wherein encoding and printing occurs substantially simultaneously.

3. The printer device of claim 2, further comprising a second RFID reader/writer module that verifies the data encoded to the RFID label, tag, or sticker.

4. The printer device of claim 3, wherein the second RFID reader/writer module is individually controlled from the RFID reader/writer module that electronically encodes the RFID label, tag, or sticker, such that the printer device can encode and verify simultaneously.

5. The printed device of claim 4, further comprising a lighted sensor array that automatically detects aperture sense marks on the continuous web to correctly index printing to the RFID label, tag, or sticker.

6. The printer device of claim 1, further comprising a main processor and an NFC I²C inlay for the purposes of communicating with the main processor.

7. (canceled).

8. The printer device of claim 1, wherein the print head automatically detects dot density.

9. The printer of claim 1, further comprising supply guides and a UHF temperature inlay contained under the supply guides for the purpose of reading the printer's temperature and using the temperature for optimizing printer performance.

10. The printer device of claim 1, wherein the print head can accept input information from Portable Document Format (PDF) or Personalized Print Markup Language (PPML).

11. The printer device of claim 1, wherein the continuous web is arranged in a sheet or roll form so that the RFID tags can be printed or encoded as part of a continuous process without stopping the web motion.

12. (canceled)

13. (canceled)

14. (canceled)

15. (canceled)

16. (canceled)

17. (canceled)

18. (canceled)

19. (canceled)

20. (canceled)

21. A method, comprising:

providing a commercial printer device configured for printing on and electronically encoding and verifying a radio frequency identification (RFID) label, tag, or sticker attached to a continuous web, the commercial printer device comprising

a print head capable of printing on the continuous web, and

an RFID reader/writer;

using the commercial printer device, sending as one command, write EPC, write access, and read EPC,

wherein the RFID reader/writer electronically encodes the RFID label, tag, or sticker with data while the continuous web is moving, and

wherein the commercial printer device reads, encodes, and prints on the RFID label, tag, or sticker without damaging the RFID label, tag, or sticker.

22. The method of claim 21, further comprising:

using the commercial printer device, encoding and verifying in a sequential manner, substantially simultaneously or simultaneously, and

using the commercial printer device, reading, encoding, and printing on the RFID label, tag, or sticker without damaging the RFID label, tag, or sticker;

23. The method of claim 21, further comprising:

using a second RFID reader/writer of the commercial printer device, verifying the data encoded to the RFID label, tag, or sticker, wherein the second RFID reader/writer is individually controlled from the RFID reader/writer that electronically encodes the RFID label, tag, or sticker.

24. The method of claim 21, further comprising:

feeding a label in position;

fetching EPC data from memory;

generating a program command with an EPC data packet;

sending a packet to an RFID module;

receiving an RFID module response packet;

extracting response data from the packet; and

decoding the response data.

25. The method of claim 21, wherein the printer device further comprises a lighted sensor array, the method further comprising:

Using the lighted sensor array, automatically detecting aperture sense marks on the continuous web to correctly index printing to the RFID label, tag, or sticker.

26. The method of claim 21, wherein the printer device further comprises a NFC I²C inlay for the purposes of communicating with a main processor.

27. The method of claim 21, wherein the print head is a thermal print head that automatically detects dot density.

28. The method of claim 21, wherein the printer device further comprises a UHF temperature inlay contained under supply guides for the purpose of reading the printer's temperature and using the temperature for optimizing printer performance.

29. The method of claim 21, wherein, the print head can accept input information from Portable Document Format (PDF) Personalized Print Markup Language (PPML) or JSON (Java Script Object Notation).

30. The method of claim 21, wherein the continuous web is arranged in a sheet or roll form so that the RFID tags can be printed or encoded as part of a continuous process without stopping the web motion.

31. The method of claim 21, further comprising determining whether the RFID reader/writer responded with an error.

32. The method of claim 31, wherein when the RFID reader/writer did respond with an error, then the process further comprises:

decoding and displaying error message on an LCD screen; and

feeding and printing overstrike image on label.

33. The method of claim 31, wherein the RFID reader/writer did not respond with an error, then the process further comprises: feeding and printing image defined by format and batch data on label.

34. The method of claim 21, wherein after the image is fed and printed, the process reverts to a prior operation and a label is fed into position.

35. The method of claim 21, further comprising, using the RFID reader/writer, determining whether an RFID transponder is within its field by reading the RFID transponder's identification code.

36. The method of claim **21**, further comprising, using the RFID reader/writer, encoding at least one RFID label, tag, or sticker with data while the web is moving.

37. The method of claim **21**, further comprising, using a second RFID reader/writer, verifying that the data has been programmed into the RFID transponder and that the data was correctly written into the RFID transponder.

* * * * *