

FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5A




FIG. 5B




FIG. 5C




FIG. 6




FIG. 7

1

METHODS AND APPARATUS FOR HARMONIC SOURCE ENHANCEMENT

CROSS-REFERENCE TO RELATED APPLICATION

The present application is a continuation of U.S. patent application Ser. No. 16/850,855 filed on Apr. 16, 2020, the entire contents of which is incorporated herein by reference.

FIELD OF THE DISCLOSURE

This disclosure relates generally to audio processing and, more particularly, to methods and apparatus for harmonic source enhancement.

BACKGROUND

Audio information (e.g., sounds, speech, music, etc.) can be represented as digital data (e.g., electronic, optical, etc.). Captured audio (e.g., via a microphone) can be digitized, stored electronically, processed and/or cataloged. One way of cataloging audio information is by generating an audio fingerprint. Audio fingerprints are digital summaries of audio information created by sampling a portion of the audio signal. Audio fingerprints have historically been used to identify audio and/or verify audio authenticity. In some examples, it is beneficial to separate an audio signal into harmonic and percussive components to help improve identifying audio and/or verifying audio authenticity.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is an illustration of an example system including and audio source and an example meter to enhance a harmonic source present in a media signal.

FIG. 2 is a block diagram of an example audio analyzer and an example audio determiner of FIG. 1.

FIG. 3 is a flowchart representative of example machine readable instructions that may be executed to implement the example audio analyzer of FIGS. 1 and 2 to enhance a harmonic source present in a media signal.

FIG. 4 is a flowchart representative of example machine readable instructions that may be executed to implement the example audio determiner of FIGS. 1 and 2 to characterize audio and/or identify media based on a harmonic source.

FIGS. 5A-5C illustrate an example magnitude spectrogram, an example time-frequency mask, and an example enhanced magnitude spectrogram in accordance with the teachings of this disclosure.

FIG. 6 is a block diagram of a processor platform structured to execute the example machine readable instructions of FIG. 3 to implement the example audio analyzer of FIGS. 1 and 2.

FIG. 7 is a block diagram of a processor platform structured to execute the example machine readable instructions of FIG. 4 to implement the example audio determiner of FIGS. 1 and 2.

The figures are not to scale. Wherever possible, the same reference numbers will be used throughout the drawing(s) and accompanying written description to refer to the same or like parts.

DETAILED DESCRIPTION

Audio signals are commonly a sinusoid (or sine wave) or combinations of sinusoids. A sinusoid is a mathematical

2

curve having features including 1) an amplitude which corresponds to the peak deviation of the curve from zero, 2) a repeating pattern having a frequency corresponding to the number of complete cycles of the curve per unit time, and 3) a phase which corresponds to where in its cycle the curve begins. Audio signals are typically combinations of various sinusoids with different amplitudes, frequencies and phases. Audio signals can broadly be categorized into two types of sources. For example, audio signals can be categorized into harmonic sources and percussive sources.

Harmonic sources correspond to pitched sound such as melodies and chords. In some examples, a violin can have a strong harmonic source, as well as a percussive source.

Percussive sources are noise-like and can correspond to instrument onsets (e.g., a hit on a drum, consonants in speech, etc.). In some examples, percussive sources may be the result of two colliding objects (e.g., a drum and drum-stick). Percussive sources typically do not have a pitch, but correspond to a localization in time.

Many audio signals are a combination of harmonic and percussive sources. For example, a note played on a piano has a percussive source (e.g., the hammer hitting the piano strings) which results in a harmonic source (e.g., the vibrating piano string).

Harmonic source enhancement of audio signals focuses on enhancing harmonic (pitched) sources over percussive sources. In particular, harmonic source enhancement focuses on decomposing an input audio signal into a signal consisting of harmonic sources and a signal consisting of percussive sources, and/or enhancing harmonic sources present in the audio signal.

Harmonic source enhancement has numerous applications including remixing audio signals and audio identification and/or authentication. Harmonic source enhancement can also be utilized as a preprocessing tool for other tasks including automatic music transcription, chord estimation, and key signature detection. In these examples, the elimination and/or reduction of the percussive sources and emphasis on the harmonic sources allows improved estimation of pitched content.

As explained above, the enhanced harmonic source may be used to classify media and/or identify media and/or may be used as part of a signaturing algorithm. For example, the characteristic audio may be used to adjust audio settings of a media output device to provide a better audio experience for a user. For example, some audio equalizer settings may be better suited for audio from a particular instrument and/or genre. Accordingly, examples disclosed herein may adjust the audio equalizer settings of a media output device based on an identified instrument/genre corresponding to an enhanced harmonic source. In another example, harmonic source may be used to identify a media being output by a media presentation device (e.g., a television, computer, radio, smartphone, tablet, etc.) by comparing the enhanced harmonic source to reference harmonic sources in a database. In this manner, the enhanced harmonic source may be used to provide an audience measurement entity with more detailed media exposure information than conventional techniques.

In some examples, the enhanced harmonic source may be used to improve audio fingerprinting. For example, the enhanced harmonic source may be utilized to generate an audio fingerprint to help identify the audio signal in subsequent processing. For example, enhancing the harmonic source of an audio signal can mitigate background noise, thereby improving the audio signal. In some examples,

enhancement of harmonic source of an audio signal can increase the efficiency and accuracy of audio identification systems and processes.

FIG. 1 illustrates an example audio analyzer 100 to enhance harmonic source present in a media signal. FIG. 1 includes the example audio analyzer 100, an example media output device 102, example speakers 104a, 104b, an example media signal 106, an example audio determiner 108, and an example audio equalizer 110.

The example audio analyzer 100 of FIG. 1 receives media signals from a device (e.g., the example media output device 102 and/or the example speakers 104a, 104b) and processes the media signal to determine a harmonic source. In some examples, the audio analyzer 100 may include, or otherwise be connected to, a microphone to receive the example media signal 106 by sensing ambient audio. In such examples, the audio analyzer 100 may be implemented in a meter or other computing device utilizing a microphone (e.g., a computer, a tablet, a smartphone, a smart watch, etc.). In some examples, the audio analyzer 100 includes an interface to receive the example media signal 106 directly (e.g., via a wired or wireless connection) from the example media output device 102 and/or a media presentation device presenting the media to the media output device 102. For example, the audio analyzer 100 may receive the media signal 106 directly from a set-top-box, a mobile phone, a gaming device, an audio receiver, a DVD player, a blue-ray player, a tablet, and/or any other devices that provides media to be output by the media output device 102 and/or the example speakers 104a, 104b.

As further described below in conjunction with FIG. 2, the example audio analyzer 100 enhances the harmonic source present in the media signal 106. If the media signal 106 is a video signal with an audio component, the audio analyzer 100 extracts the audio component from the media signal 106 prior to enhancing the harmonic source.

The example media output device 102 of FIG. 1 is a device that outputs media in the form of audio and/or video. Although the media output device 102 of FIG. 1 is illustrated as a television, the media output device 102 may be a radio, an MP3 player, a video game console, a stereo system, a mobile device, a tablet, a computing device, a laptop, a projector, a DVD player, a set-top-box, an over-the-top device, and/or any device capable of outputting media (e.g., video and/or audio).

The example media output device 102 may include speakers 104a and/or may be coupled, or otherwise connected to portable speakers 104b via a wired or wireless connection. The example speakers 104a, 104b output the audio portion of the media output by the media output device 102. The media output device 102 may include a display through which visual media may be presented, or the media output device 102 may not include a display. In the illustrated example of FIG. 1, the media signal 106 represents audio that is output by the speakers 104a, 104b. Additionally or alternatively, the media signal 106 may be an audio signal and/or a video signal that is transmitted to the media output device 102 and/or the speakers 104a, 104b to be output by the media output device 102 and/or the speakers 104a, 104b. For example, the media signal 106 may be a signal from a gaming console that is transmitted to the media output device 102 and/or the speakers 104a, 104b to output audio and video of a video game. The example audio analyzer 100 may receive the media signal 106 directly from the media presentation device (e.g., the gaming console) and/or from the ambient audio. In this manner, the audio analyzer 100

may classify and/or identify audio from a media signal even when the speakers 104a, 104b are off, not working, or have audio that is turned down.

The example audio determiner 108 of FIG. 1 is in communication with the audio analyzer 100 and characterizes audio and/or identifies media based on a harmonic source measurement from the audio analyzer 100. For example, as described in further detail in connection with FIG. 2, the audio determiner 108 may include a database of reference harmonic sources corresponding to classifications and/or identifications. In this manner, the audio determiner 108 may compare received harmonic source(s) with the reference harmonic source to identify a match. If the audio determiner 108 identifies a match, the audio determiner 108 classifies the audio and/or identifies the media on information corresponding to the matched reference harmonic source. For example, if a received harmonic source matches a reference harmonic source corresponding to a particular audio signal (e.g., a song, a show, etc.), the audio determiner 108 classifies the audio corresponding to the received harmonic source as the particular audio signal, and/or increases a count associated with measuring media exposure (e.g., increases a count associated with how many times the audio signal has been listened to). In such an example, if the audio analyzer 100 is part of a mobile phone, the audio analyzer 100 may receive the audio signal for the song (e.g., via an interface receiving the audio/video signal or via a microphone of the mobile phone receiving the audio signal). In this manner, the audio determiner 108 may identify that the received audio corresponds to the user (e.g., using a user interface of the mobile device). In another example, if a received harmonic source matches a reference harmonic source corresponding to a particular video game, the audio determiner 108 may identify the audio as being from the particular video game.

In some examples, the audio determiner 108 may include a database of reference audio signals (e.g., signatures) having enhanced harmonic sources (e.g., enhanced based on methods disclosed herein, enhanced based on other known methods) corresponding to classifications and/or identifications. In this manner, the audio determiner 108 may compare an audio signal with an enhanced harmonic source(s) with the reference audio signals with enhanced harmonic sources to identify a match. If the audio determiner 108 identifies a match, the audio determiner 108 classifies the audio and/or identifies the media on information corresponding to the matched reference audio signal with the enhanced harmonic source. For example, if a received audio signals with enhanced harmonic source matches a reference audio signal with an enhanced harmonic source corresponding to a particular audio signal (e.g., a song, a show, etc.), the audio determiner 108 classifies the audio corresponding to the received audio signal as the particular audio signal, and/or increases a count associated with measuring media exposure (e.g., increases a count associated with how many times the audio signal has been listened to). In some examples, the audio determiner 108 may include a database of reference audio signals (e.g., signatures) that do not have enhanced harmonic sources corresponding to classifications and/or identifications. In this manner, the audio determiner 108 may compare an audio signal with an enhanced harmonic source (s) with the reference audio signals without enhanced harmonic sources to identify a match.

If the example audio determiner 108 identifies a match, the audio determiner 108 classifies the audio and/or identifies the media on information corresponding to the matched reference audio signal with the enhanced harmonic source.

As such, the examples disclosed herein enhance the harmonic source of an audio signal to improve the accuracy and efficiency of audio identification systems and processes. For example, the examples disclosed herein enhance the harmonic source of a query audio signal to improve the accuracy of identifying a reference audio signal in an audio signal reference database. The audio determiner 108 may generate a report to identify the audio. In this manner, an audience measurement entity may credit exposure to the video game based on the report.

In some examples, the audio determiner 108 receives the enhanced harmonic source directly from the audio analyzer 100 (e.g., both the audio analyzer 100 and the audio determiner 108 are located in the same device). In some examples, the audio determiner 108 is located in a different location and receives the enhanced harmonic source from the audio analyzer 100 via a wireless communication.

In some examples, the audio determiner 108 transmits instructions to the audio media output device 102 and/or the audio analyzer 100 (e.g., when the audio analyzer 100 is implemented in the media output device 102) to adjust the audio equalizer settings of the audio equalizer 110 based on the audio classification. For example, if the audio determiner 108 classifies audio being output by the media output device 102 as being from a “Rock” genre, the audio determiner 108 may transmit instructions to adjust the audio equalizer settings of the audio equalizer 110 to settings that correspond to “Rock” audio. The audio determiner 108 is further described below in conjunction with FIG. 2.

FIG. 2 includes block diagrams of example implementations of the example audio analyzer 100 and the example audio determiner 108 of FIG. 1. The audio analyzer 100 of FIG. 2 includes an example media interface 200, an example audio extractor 202, an example harmonic source enhancer 204, and an example device interface 206. The audio determiner 108 of FIG. 2 includes an example device interface 210, an example harmonic processor 212, an example harmonic database 214, and an example audio settings adjuster 216. In some examples, elements of the audio analyzer 100 may be implemented in the audio determiner 108 and/or elements of the audio determiner 108 may be implemented in the audio analyzer 100.

The example media interface 200 of FIG. 2 receives (e.g., samples) the media signal 106 of FIG. 1. In some examples, the media interface 200 may be a microphone used to obtain the media signal 106 as audio by gathering the media signal 106 through the sensing of ambient audio. In some examples, the media interface 200 may be an interface to directly receive an audio and/or video signal (e.g., a digital representation of a media signal) that is to be output by the media output device 102. In some examples, the media interface 200 may include two interfaces: a microphone for detecting and sampling ambient audio and an interface to directly receive and/or sample an audio and/or video signal.

The example audio extractor 202 of FIG. 2 extracts audio from the received/sampled media signal 106. For example, the audio extractor 202 determines if a received media signal 106 corresponds to an audio signal or a video signal with an audio component. If the media signal corresponds to a video signal with an audio component, the audio extractor 202 extracts the audio component to generate the audio signal/samples for further processing.

The example harmonic source enhancer 204 of FIG. 2 processes the audio signal/samples to enhance a harmonic source of the audio signal/samples. For example, the harmonic source enhancer 204 determines a magnitude spectrogram for the audio signal. In some examples, the har-

monic source enhancer 204 determines the magnitude spectrogram for the audio signal based on a band-pass filter, a Fourier transform, or a wavelet transform. In the illustrated example, the harmonic source enhancer 204 converts the audio signal into a time-frequency representation using a transform algorithm (e.g., Fourier transform, Constant Q transform, etc.), where each column of the time-frequency representation represents a spectrum at a particular instant in time. In some examples, the harmonic source enhancer 204 determines the magnitude spectrogram 500 of FIG. 5A.

The harmonic source enhancer 204 of the illustrated example then determines the magnitude of the complex time-frequency representation of the time-frequency spectrum. In some examples, the harmonic source enhancer 204 of the illustrated example determines a Fourier transform of the magnitude spectrogram. For example, the harmonic source enhancer 204 determines the magnitude of every column of the time frequency representation. In this example, the harmonic source enhancer 204 determines the magnitude of every column 502 of the magnitude spectrogram 500 of FIG. 5A. The example harmonic source enhancer 204 of the illustrated example divides the Fourier transform by the absolute value of the Fourier transform. In some examples, the harmonic source enhancer 204 determines a Fourier transform of every column (e.g., each column 502 of the magnitude spectrogram 500 of FIG. 5A). The harmonic source enhancer 204 of the illustrated example then divides each column by the magnitude of that column. For example, the harmonic source enhancer 204 divides each column 502 of the magnitude spectrogram of FIG. 5A by the magnitude of the respective columns 502. The harmonic source enhancer 204 then generates the inverse Fourier transform for each column.

The harmonic source enhancer 204 of the illustrated example utilizes the output of the inverse Fourier transform to enhance the harmonic source. In some examples, the harmonic source enhancer 204 may generate a time-frequency mask and apply the time-frequency mask to a complex spectrogram of the audio signal to enhance the harmonic source of the audio signal. For example, the harmonic source enhancer 204 may generate the time frequency mask 504 illustrated in FIG. 5B. In this example, the output of the inverse Fourier transform may correspond to a violin. In some examples, the harmonic source enhancer 204 may apply the time-frequency mask 504 to the magnitude spectrogram 500 to determine the enhanced magnitude spectrogram 506 of FIG. 5C. In some examples, the enhanced magnitude spectrogram 506 of FIG. 5C represents the enhanced harmonic source. In some examples, the harmonic source enhancer 204 processes the enhanced magnitude spectrogram 506 of FIG. 5C to generate an audio signal representative of the enhanced harmonic source. The enhanced harmonic source may be utilized to identify the audio signal in subsequent processing. For example, the enhanced harmonic source corresponds to a particular piece of media (e.g., a song, a show, a movie, etc.). In some examples, the enhanced harmonic source may be stored in the harmonic database 214 to be used as a reference audio signature to identify subsequent audio signals. As used herein, “enhanced harmonic source” refers to an audio signal that has been processed in accordance with the teachings of this disclosure to emphasize the harmonics of the audio signal. For example, enhanced harmonic source refers to an audio signal that has emphasized harmonics to improve accuracy and efficiency of audio identification systems and processes.

In some examples, the harmonic source enhancer **204** may compute a magnitude spectrogram for the audio signal, determine a Fourier transform for each of the columns of the magnitude spectrogram, divide the resulting output by their respective magnitudes, and determine the inverse Fourier transform. In some examples, the harmonic source enhancer **204** generates a time-frequency mask which is applied to the audio signal to enhance the harmonic source. In such an example, the harmonic source enhancer **204** may utilize the time-frequency mask and apply the time-frequency mask to a complex spectrogram of the audio signal to enhance the harmonic source present in the audio signal.

In some examples, if the harmonic source enhancer **204** of FIG. 2 determines that resulting enhanced harmonic source is not satisfactory, the harmonic source enhancer **204** filters the results to improve the decomposition. For example, the harmonic source enhancer **204** may filter the results by emphasizing particular harmonics or by forcing a single peak/line and updating other components of the result. The example harmonic source enhancer **204** may filter once or may perform an iterative algorithm while updating the enhanced harmonic source at each iteration, thereby ensuring that the overall enhanced harmonic source result in the original audio. The harmonic source enhancer **204** may determine that the results are unsatisfactory based on user and/or manufacturer preferences.

The example device interface **206** of the audio analyzer **100** of FIG. 2 interfaces with the example audio determiner **108** and/or other devices (e.g., user interfaces, processing device, etc.). For example, when the harmonic source enhancer **204** determines the enhanced harmonic source, the example device interface **206** may transmit the enhanced harmonic source to the audio determiner **108** to classify the audio and/or identify media. In response, the device interface **206** may receive a classification and/or identification (e.g., an identifier corresponding to the source of the media signal **106**) from the audio determiner **108** (e.g., in a signal or report). In such an example, the device interface **206** may transmit the classification and/or identification to other devices (e.g., a user interface) to display the classification and/or identification to a user. For example, if the audio analyzer **100** is being used in conjunction with a smart phone, the device interface **206** may output the results of the classification and/or identification to a user of the smart-phone via an interface (e.g., screen) of the smart-phone.

The example device interface **210** of the audio determiner **108** of FIG. 2 receives enhanced harmonic sources from the audio analyzer **100**. Additionally, the device interface **210** outputs a signal/report representative of the classification and/or identification determined by the audio determiner **108**. The report may be a signal that corresponds to the classification and/or identification based on the received enhanced harmonic source. In some examples, the device interface **210** transmits the report (e.g., including an identification of media corresponding to the harmonic source) to a processor (e.g., such as a processor of an audience measurement entity) for further processing. For example, the processor of the receiving device may process the report to generate media exposure metrics, audience measurement metrics, etc. In some examples, the device interface **210** transmits the report to the audio analyzer **100**.

The example harmonic processor **212** of FIG. 2 processes the received enhanced harmonic source of the audio analyzer **100** to characterize the audio and/or identify the source of the audio. For example, the harmonic processor **212** may compare the received enhanced harmonic source to reference enhanced harmonic sources and/or reference audio

signals that do not have enhanced harmonic sources in the example harmonic database **214**. In this manner, if the harmonic processor **212** determines that the received enhanced harmonic source matches a reference harmonic source and/or reference audio signal, the harmonic processor **212** classifies and/or identifies a source of the audio based on data corresponding to the matched reference harmonic source and/or audio signal. For example, if the harmonic processor **212** determines that a received enhanced harmonic source matches a reference harmonic source that corresponds to a particular commercial, the harmonic processor **212** identifies the source of the audio to be the particular commercial. In some examples, the classification may include a genre classification. For example, if the harmonic processor **212** determines a number of instruments based on the enhanced harmonic source, the harmonic processor **212** may identify a genre of audio (e.g., classical, rock, hip hop, etc.) based on the identified instruments and/or based on the enhanced harmonic source itself. In some examples, when the harmonic processor **212** does not find a match, the harmonic processor **212** stores the received enhanced harmonic source in the harmonic database **214** to become a new reference harmonic source. If the harmonic processor **212** stores a new reference harmonic source in the harmonic database **214**, the device interface **210** transmits instructions to the audio analyzer **100** to prompt a user for identification information (e.g., what is the classification of the audio, what is the source of the media, etc.). In this manner, if the audio analyzer **100** responds with additional information, the harmonic database **214** may store the additional information in conjunction with the new reference harmonic source. In some examples, a technician analyzes the new reference harmonic source to determine the additional information. The harmonic processor **212** generates a report based on the classification and/or identification.

The example audio settings adjuster **216** of FIG. 2 determines audio equalizer settings based on the classified audio for utilization by the audio equalizer **110**. For example, if the classified audio corresponds to one or more instruments and/or a genre, the audio settings adjuster **216** may determine an audio equalizer setting corresponding to the one or more instruments and/or the genre and send instructions to the audio equalizer **110**. In some examples, if the audio is classified as classical music, the audio setting adjuster **216** may select a classical audio equalizer setting (e.g., based on a level of bass, a level of tremble, etc.) corresponding to classical music and send instructions to the audio equalizer **110** in accordance with the classical music equalizer settings. In this manner, the device interface **210** may transmit the audio equalizer setting to the audio equalizer **110** to adjust the audio equalizer settings of the media output device **102**.

While an example manner of implementing the example audio analyzer **100** and the example audio determiner **108** of FIG. 1 is illustrated in FIG. 2, one or more of the elements, processes and/or devices illustrated in FIG. 2 may be combined, divided, re-arranged, omitted, eliminated and/or implemented in any other way. Further, the example media interface **200**, the example audio extractor **202**, the example harmonic source enhancer **204**, the example device interface **206**, the example audio settings adjuster **216**, and/or, more generally, the example audio analyzer **100** of FIG. 2 and/or the example device interface **210**, the example harmonic processor **212**, the example harmonic database **214**, the example audio settings adjuster **216**, and/or, more generally, the example audio determiner **108** of FIG. 2 may be implemented by hardware, software, firmware and/or any combi-

nation of hardware, software and/or firmware. Thus, for example, any of the example media interface **200**, the example audio extractor **202**, the example harmonic source enhancer **204**, the example device interface **206**, and/or, more generally, the example audio analyzer **100** of FIG. **2** and/or the example device interface **210**, the example harmonic processor **212**, the example harmonic database **214**, the example audio settings adjuster **216**, and/or, more generally, the example audio determiner **108** of FIG. **2** could be implemented by one or more analog or digital circuit(s), logic circuits, programmable processor(s), programmable controller(s), graphics processing unit(s) (GPU(s)), digital signal processor(s) (DSP(s)), application specific integrated circuit(s) (ASIC(s)), programmable logic device(s) (PLD(s)) and/or field programmable logic device(s) (FPLD(s)). When reading any of the apparatus or system claims of this patent to cover a purely software and/or firmware implementation, at least one of the example media interface **200**, the example audio extractor **202**, the example harmonic source enhancer **204**, the example device interface **206**, and/or, more generally, the example audio analyzer **100** of FIG. **2** and/or the example device interface **210**, the example harmonic processor **212**, the example harmonic database **214**, the example audio settings adjuster **216**, and/or, more generally, the example audio determiner **108** of FIG. **2** is/are hereby expressly defined to include a non-transitory computer readable storage device or storage disk such as a memory, a digital versatile disk (DVD), a compact disk (CD), a Blu-ray disk, etc. including the software and/or firmware. Further still, the example audio analyzer **100** and/or the example audio determiner **108** of FIG. **1** may include one or more elements, processes and/or devices in addition to, or instead of, those illustrated in FIG. **2**, and/or may include more than one of any or all of the illustrated elements, processes and devices. As used herein, the phrase “in communication,” including variations thereof, encompasses direct communication and/or indirect communication through one or more intermediary components, and does not require direct physical (e.g., wired) communication and/or constant communication, but rather additionally includes selective communication at periodic intervals, scheduled intervals, aperiodic intervals, and/or one-time events.

A flowchart representative of example hardware logic or machine readable instructions for implementing the audio analyzer **100** of FIG. **2** is shown in FIG. **3** and a flowchart representative of example hardware logic or machine readable instructions for implementing the audio determiner **108** of FIG. **2** is shown in FIG. **4**. The machine readable instructions may be a program or portion of a program for execution by a processor such as the processor **612**, **712** shown in the example processor platform **600**, **700** discussed below in connection with FIGS. **6** and/or **7**. The program may be embodied in software stored on a non-transitory computer readable storage medium such as a CD-ROM, a floppy disk, a hard drive, a DVD, a Blu-ray disk, or a memory associated with the processor **612**, **712**, but the entire program and/or parts thereof could alternatively be executed by a device other than the processor **612**, **712** and/or embodied in firmware or dedicated hardware. Further, although the example program is described with reference to the flowcharts illustrated in FIGS. **3-4**, many other methods of implementing the example audio analyzer **100** and/or the example audio determiner **108** may alternatively be used. For example, the order of execution of the blocks may be changed, and/or some of the blocks described may be changed, eliminated, or combined. Additionally or alternatively, any or all of the blocks may be implemented by one

or more hardware circuits (e.g., discrete and/or integrated analog and/or digital circuitry, an FPGA, an ASIC, a comparator, an operational-amplifier (op-amp), a logic circuit, etc.) structured to perform the corresponding operation without executing software or firmware.

As mentioned above, the example processes of FIGS. **3-4** may be implemented using executable instructions (e.g., computer and/or machine readable instructions) stored on a non-transitory computer and/or machine readable medium such as a hard disk drive, a flash memory, a read-only memory, a compact disk, a digital versatile disk, a cache, a random-access memory and/or any other storage device or storage disk in which information is stored for any duration (e.g., for extended time periods, permanently, for brief instances, for temporarily buffering, and/or for caching of the information). As used herein, the term non-transitory computer readable medium is expressly defined to include any type of computer readable storage device and/or storage disk and to exclude propagating signals and to exclude transmission media.

“Including” and “comprising” (and all forms and tenses thereof) are used herein to be open ended terms. Thus, whenever a claim employs any form of “include” or “comprise” (e.g., comprises, includes, comprising, including, having, etc.) as a preamble or within a claim recitation of any kind, it is to be understood that additional elements, terms, etc. may be present without falling outside the scope of the corresponding claim or recitation. As used herein, when the phrase “at least” is used as the transition term in, for example, a preamble of a claim, it is open-ended in the same manner as the term “comprising” and “including” are open ended. The term “and/or” when used, for example, in a form such as A, B, and/or C refers to any combination or subset of A, B, C such as (1) A alone, (2) B alone, (3) C alone, (4) A with B, (5) A with C, and (6) B with C.

FIG. **3** is an example flowchart **300** representative of example machine readable instructions that may be executed by the example audio analyzer **100** of FIGS. **1** and **2** to cause the audio analyzer **100** to enhance harmonic source present in a media signal (e.g., an audio signal of a media signal). Although the instructions of FIG. **3** are described in conjunction with the example audio analyzer **100** of FIG. **1**, the example instructions may be used by an audio analyzer in any environment.

At block **302**, the example media interface **200** receives one or more media signals or samples of media signals (e.g., the example media signal **106**). As described above, the example media interface **200** may receive the media signal **106** directly (e.g., as a signal to/from the media output device **102**) or indirectly (e.g., as a microphone detecting the media signal by sensing ambient audio). At block **304**, the example audio extractor **202** determines if the media signal correspond to video or audio. For example, if the media signal was received using a microphone, the audio extractor **202** determines that the media corresponds to audio. However, if the media signal is received signal, the audio extractor **202** processes the received media signal to determine if the media signal corresponds to audio or video with an audio component. If the example audio extractor **202** determines that the media signal corresponds to audio (block **304**: AUDIO), the process continues to block **308**. If the example audio extractor **202** determines that the media signal corresponds to video (block **306**: VIDEO), the example audio extractor **202** extracts the audio component from the media signal (block **306**).

At block **308**, the example harmonic source enhancer **204** determines the magnitude spectrogram of the audio signal.

For example, the harmonic source enhancer **204** may determine the magnitude spectrogram (e.g., magnitude spectrogram **500** of FIG. 5A) of the audio signal by performing a known magnitude spectrogram technique. At block **310**, the example harmonic source enhancer **204** determines the Fourier transform (FT) of the magnitude spectrogram. For example, the harmonic source enhancer **204** performs a FT to the magnitude spectrogram. At block **312**, the example harmonic source enhancer **204** divides the Fourier transform by the absolute value of the Fourier transform. At block **314**, the example harmonic source enhancer **204** determines the inverse Fourier transform. For example, the audio analyzer determines the inverse of the Fourier transform from block **312**. At block **316**, the example harmonic source enhancer **204** enhances the harmonic source from the inverse Fourier transform. For example, the harmonic source enhancer **204** may generate a time-frequency mask (e.g., time-frequency mask **504** of FIG. 5B) and apply it to the audio signal and/or the magnitude spectrogram to enhance the harmonic source present in the audio signal.

At block **318**, the example harmonic source enhancer **204** determines if the result(s) (e.g., the determined harmonic source) is satisfactory. As described above in conjunction with FIG. 2, the example harmonic source enhancer **204** determines that the result(s) are satisfactory based on user and/or manufacturer result preferences. If the example harmonic source enhancer **204** determines that the results are satisfactory (block **318**: YES), the process continues to block **322**. If the example harmonic source enhancer **204** determines that the results are satisfactory (block **318**: NO), the example harmonic source enhancer **204** filters the results (block **320**). As described above in conjunction with FIG. 2, the example harmonic source enhancer **204** may filter the results by emphasizing harmonics or forcing a single peak/line (e.g., once or iteratively).

At block **322**, the example device interface **206** transmits the results to the example audio determiner **108**. At block **324**, the example harmonic source enhancer **204** receives a classification and/or identification data corresponding to the audio signal. Alternatively, if the audio determiner **108** was not able to match the enhanced harmonic source of the audio signal to a reference, the device interface **206** may transmit instructions for additional data corresponding to the audio signal. In such examples, the device interface **206** may transmit prompt to a user interface for a user to provide the additional data. Accordingly, the example device interface **206** may provide the additional data to the example audio determiner **108** to generate a new reference harmonic source. At block **326**, the example harmonic source enhancer **204** transmits the classification and/or identification to other connected devices. For example, the harmonic source enhancer **204** may transmit a classification to a user interface to provide the classification to a user.

FIG. 4 is an example flowchart **400** representative of example machine readable instructions that may be executed by the example audio determiner **108** of FIGS. 1 and 2 to cause the audio determiner **108** classify audio and/or identify media based on harmonic source of audio. Although the instructions of FIG. 4 are described in conjunction with the example audio determiner **108** of FIG. 1, the example instructions may be used by an audio determiner in any environment.

At block **402**, the example device interface **210** receives a measured (e.g., determined or enhanced) harmonic source from the example audio analyzer **100**. At block **404**, the example harmonic processor **212** compares the measured enhanced harmonic source to the reference harmonic

sources in the example harmonic database **214**. At block **406**, the example harmonic processor **212** determines if a match is found between the received enhanced harmonic source and the reference harmonic sources. If the example harmonic processor **212** determines that a match is determined (block **406**: YES), the example harmonic processor **212** classifies the audio (e.g., identifying instruments and/or genres) and/or identifies media corresponding to the audio based on the match (block **408**) using additional data stored in the example harmonic database **214** corresponding to the matched reference harmonic source.

At block **410**, the example audio settings adjuster **216** determines whether the audio settings of the media output device **102** can be adjusted. For example, there may be an enabled setting to allow the audio settings of the media output device **102** to be adjusted based on a classification of the audio being output by the example media output device **102**. If the example audio settings adjuster **216** determines that the audio settings of the media output device **102** are not to be adjusted (block **410**: NO), the process continues to block **414**. If the example audio settings adjuster **216** determines that the audio settings of the media output device **102** are to be adjusted (block **410**: YES), the example audio settings adjuster **216** determines a media output device setting adjustment based on the classified audio. For example, the example audio settings adjuster **216** may select an audio equalizer setting based on one or more identified instruments and/or an identified genre (e.g., from the harmonic source or based on the identified instruments) (block **412**). At block **414**, the example device interface **210** outputs a report corresponding to the classification, identification, and/or media output device setting adjustment. In some examples the device interface **210** outputs the report to another device for further processing/analysis. In some examples, the device interface **210** outputs the report to the example audio analyzer **100** to display the results to a user via a user interface. In some examples, the device interface **210** outputs the report to the example audio equalizer **110** to adjust the audio settings of the media output device **102**.

If the example harmonic processor **212** determines that a match is not determined (block **406**: NO), the example device interface **210** prompts for additional information corresponding to the audio signal (block **416**). For example, the device interface **210** may transmit instructions to the example audio analyzer **100** to (A) prompt a user to provide information corresponding to the audio or (B) prompt the audio analyzer **100** to reply with the full audio signal. At block **418**, the example harmonic database **214** stores the measured harmonic source in conjunction with corresponding data that may have been received.

FIGS. 5A-5C illustrate the example magnitude spectrogram **500**, the example time-frequency mask **504**, and the example enhanced magnitude spectrogram **506**. FIG. 5A illustrates the example magnitude spectrogram **500** including columns **502** that may be generated by the harmonic source enhancer **204** in accordance with the methods disclosed in connection with FIG. 2. FIG. 5B illustrates the example time-frequency mask **504** that may be generated by the harmonic source enhancer **204** in accordance with the methods disclosed in connection with FIG. 2. FIG. 5C illustrates the example enhanced magnitude spectrogram **506** that may be generated by the harmonic source enhancer **204** in accordance with the methods disclosed in connection with FIG. 2. The enhanced magnitude spectrogram **506** is the result of applying the time-frequency mask **504** to the magnitude spectrogram **500**. As shown in the illustrated enhanced magnitude spectrogram **506** of FIG. 5C, various

portions of the magnitude spectrogram **500** have been masked by the time-frequency mask **504**, thereby enhancing the harmonics of the magnitude spectrogram **500** and generating an enhanced harmonic source.

FIG. **6** is a block diagram of an example processor platform **600** structured to execute the instructions of FIG. **3** to implement the audio analyzer **100** of FIG. **2**. The processor platform **600** can be, for example, a server, a personal computer, a workstation, a self-learning machine (e.g., a neural network), a mobile device (e.g., a cell phone, a smart phone, a tablet such as an iPad™), a personal digital assistant (PDA), an Internet appliance, a DVD player, a CD player, a digital video recorder, a Blu-ray player, a gaming console, a personal video recorder, a set top box, a headset or other wearable device, or any other type of computing device.

The processor platform **600** of the illustrated example includes a processor **612**. The processor **612** of the illustrated example is hardware. For example, the processor **612** can be implemented by one or more integrated circuits, logic circuits, microprocessors, GPUs, DSPs, or controllers from any desired family or manufacturer. The hardware processor may be a semiconductor based (e.g., silicon based) device. In this example, the processor implements the example media interface **200**, the example audio extractor **202**, the example harmonic source enhancer **204**, and/or the example device interface of FIG. **2**.

The processor **612** of the illustrated example includes a local memory **613** (e.g., a cache). The processor **612** of the illustrated example is in communication with a main memory including a volatile memory **614** and a non-volatile memory **616** via a bus **618**. The volatile memory **614** may be implemented by Synchronous Dynamic Random Access Memory (SDRAM), Dynamic Random Access Memory (DRAM), RAIVIBUS® Dynamic Random Access Memory (RDRAM®) and/or any other type of random access memory device. The non-volatile memory **616** may be implemented by flash memory and/or any other desired type of memory device. Access to the main memory **614**, **616** is controlled by a memory controller.

The processor platform **600** of the illustrated example also includes an interface circuit **620**. The interface circuit **620** may be implemented by any type of interface standard, such as an Ethernet interface, a universal serial bus (USB), a Bluetooth® interface, a near field communication (NFC) interface, and/or a PCI express interface.

In the illustrated example, one or more input devices **622** are connected to the interface circuit **620**. The input device (s) **622** permit(s) a user to enter data and/or commands into the processor **612**. The input device(s) can be implemented by, for example, an audio sensor, a microphone, a camera (still or video), a keyboard, a button, a mouse, a touchscreen, a track-pad, a trackball, isopoint and/or a voice recognition system.

One or more output devices **624** are also connected to the interface circuit **620** of the illustrated example. The output devices **624** can be implemented, for example, by display devices (e.g., a light emitting diode (LED), an organic light emitting diode (OLED), a liquid crystal display (LCD), a cathode ray tube display (CRT), an in-place switching (IPS) display, a touchscreen, etc.), a tactile output device, a printer and/or speaker. The interface circuit **620** of the illustrated example, thus, typically includes a graphics driver card, a graphics driver chip and/or a graphics driver processor.

The interface circuit **620** of the illustrated example also includes a communication device such as a transmitter, a receiver, a transceiver, a modem, a residential gateway, a

wireless access point, and/or a network interface to facilitate exchange of data with external machines (e.g., computing devices of any kind) via a network **626**. The communication can be via, for example, an Ethernet connection, a digital subscriber line (DSL) connection, a telephone line connection, a coaxial cable system, a satellite system, a line-of-site wireless system, a cellular telephone system, etc.

The processor platform **600** of the illustrated example also includes one or more mass storage devices **628** for storing software and/or data. Examples of such mass storage devices **628** include floppy disk drives, hard drive disks, compact disk drives, Blu-ray disk drives, redundant array of independent disks (RAID) systems, and digital versatile disk (DVD) drives.

The machine executable instructions **632** of FIG. **3** may be stored in the mass storage device **628**, in the volatile memory **614**, in the non-volatile memory **616**, and/or on a removable non-transitory computer readable storage medium such as a CD or DVD.

FIG. **7** is a block diagram of an example processor platform **700** structured to execute the instructions of FIG. **4** to implement the audio determiner **108** of FIG. **2**. The processor platform **700** can be, for example, a server, a personal computer, a workstation, a self-learning machine (e.g., a neural network), a mobile device (e.g., a cell phone, a smart phone, a tablet such as an iPad™), a personal digital assistant (PDA), an Internet appliance, a DVD player, a CD player, a digital video recorder, a Blu-ray player, a gaming console, a personal video recorder, a set top box, a headset or other wearable device, or any other type of computing device.

The processor platform **700** of the illustrated example includes a processor **712**. The processor **712** of the illustrated example is hardware. For example, the processor **712** can be implemented by one or more integrated circuits, logic circuits, microprocessors, GPUs, DSPs, or controllers from any desired family or manufacturer. The hardware processor may be a semiconductor based (e.g., silicon based) device. In this example, the processor implements the example device interface **210**, the example harmonic processor **212**, the example harmonic database **214**, and/or the example audio settings adjuster **216**.

The processor **712** of the illustrated example includes a local memory **713** (e.g., a cache). The processor **712** of the illustrated example is in communication with a main memory including a volatile memory **714** and a non-volatile memory **716** via a bus **718**. The volatile memory **714** may be implemented by Synchronous Dynamic Random Access Memory (SDRAM), Dynamic Random Access Memory (DRAM), RAMBUS® Dynamic Random Access Memory (RDRAM®) and/or any other type of random access memory device. The non-volatile memory **716** may be implemented by flash memory and/or any other desired type of memory device. Access to the main memory **714**, **716** is controlled by a memory controller.

The processor platform **700** of the illustrated example also includes an interface circuit **720**. The interface circuit **720** may be implemented by any type of interface standard, such as an Ethernet interface, a universal serial bus (USB), a Bluetooth® interface, a near field communication (NFC) interface, and/or a PCI express interface.

In the illustrated example, one or more input devices **722** are connected to the interface circuit **720**. The input device (s) **722** permit(s) a user to enter data and/or commands into the processor **712**. The input device(s) can be implemented by, for example, an audio sensor, a microphone, a camera

(still or video), a keyboard, a button, a mouse, a touchscreen, a track-pad, a trackball, isopoint and/or a voice recognition system.

One or more output devices **724** are also connected to the interface circuit **720** of the illustrated example. The output devices **724** can be implemented, for example, by display devices (e.g., a light emitting diode (LED), an organic light emitting diode (OLED), a liquid crystal display (LCD), a cathode ray tube display (CRT), an in-place switching (IPS) display, a touchscreen, etc.), a tactile output device, a printer and/or speaker. The interface circuit **720** of the illustrated example, thus, typically includes a graphics driver card, a graphics driver chip and/or a graphics driver processor.

The interface circuit **720** of the illustrated example also includes a communication device such as a transmitter, a receiver, a transceiver, a modem, a residential gateway, a wireless access point, and/or a network interface to facilitate exchange of data with external machines (e.g., computing devices of any kind) via a network **726**. The communication can be via, for example, an Ethernet connection, a digital subscriber line (DSL) connection, a telephone line connection, a coaxial cable system, a satellite system, a line-of-site wireless system, a cellular telephone system, etc.

The processor platform **700** of the illustrated example also includes one or more mass storage devices **728** for storing software and/or data. Examples of such mass storage devices **728** include floppy disk drives, hard drive disks, compact disk drives, Blu-ray disk drives, redundant array of independent disks (RAID) systems, and digital versatile disk (DVD) drives.

The machine executable instructions **732** of FIG. **4** may be stored in the mass storage device **728**, in the volatile memory **714**, in the non-volatile memory **716**, and/or on a removable non-transitory computer readable storage medium such as a CD or DVD.

From the foregoing, it would be appreciated that the above disclosed method, apparatus, and articles of manufacture enhance harmonic source present in a media signal. Examples disclosed herein determine a harmonic source based on audio received directly or indirectly from a media output device. Example disclosed herein further include classifying the audio based on the enhanced harmonic source and/or identifying a media source (e.g., a song, a video game, an advertisement, etc.) of the audio based on the enhanced harmonic source. Using examples disclosed herein, enhanced harmonic source can be used to classify and/or identify audio with significantly less resources than conventional techniques. Additionally, examples disclosed herein can be used to identify a pitch, separate out an instrument from audio, and/or improve fingerprinting audio. Accordingly, examples disclosed herein are directed to improvements in a computing device and to improvements to the field of audio processing (e.g., fingerprinting, audio identification, etc.).

Although certain example methods, apparatus and articles of manufacture have been described herein, other implementations are possible. The scope of coverage of this patent is not limited thereto. On the contrary, this patent covers all methods, apparatus and articles of manufacture fairly falling within the scope of the claims of this patent.

What is claimed is:

1. A system comprising:
at least one memory;
instructions; and

one or more processors to execute the instructions to:
determine a magnitude spectrogram of audio corresponding to a media signal;

based on the determined magnitude spectrogram, enhance a harmonic source of the media signal;
compare the media signal having the enhanced harmonic source with reference media signals to determine an audio characteristic corresponding to the enhanced harmonic source;

identify an audio classification corresponding to the media signal based on the determined audio characteristic; and

identify at least one of a song, an advertisement, a show, or a video game based on the determined audio characteristic.

2. The system of claim **1**, wherein the determined magnitude spectrogram of audio comprises transforming the audio into a time-frequency representation using at least one of a Fourier transform, or a Constant Q transform.

3. The system of claim **2**, wherein the time-frequency representation includes respective columns corresponding to a spectrum at a particular instant.

4. The system of claim **1**, wherein the audio characteristic comprises an instrument corresponding to the enhanced harmonic source.

5. The system of claim **1**, wherein the audio characteristic comprises a reference harmonic source that corresponds to the enhanced harmonic source.

6. The system of claim **1**, wherein the audio characteristic comprises a genre corresponding to the enhanced harmonic source.

7. The system of claim **1**, wherein the audio classification comprises a genre of the media signal.

8. The system of claim **1**, wherein the instructions further comprise instructions to:

transmit the enhanced harmonic source; and

obtain at least one of an additional classification of the audio or an identifier corresponding to the media signal.

9. A non-transitory computer readable medium comprising instructions that, when executed, cause one or more processors to at least:

determine a magnitude spectrogram of audio corresponding to a media signal;

based on the determined magnitude spectrogram, enhance a harmonic source of the media signal;

compare the media signal having the enhanced harmonic source with reference media signals to determine an audio characteristic corresponding to the enhanced harmonic source;

identify an audio classification corresponding to the media signal based on the determined audio characteristic; and

identify at least one of a song, an advertisement, a show, or a video game based on the determined audio characteristic.

10. The non-transitory computer readable medium of claim **9**, wherein the determined magnitude spectrogram of audio comprises transforming the audio into a time-frequency representation using at least one of a Fourier transform, or a Constant Q transform.

11. The non-transitory computer readable medium of claim **10**, wherein the time-frequency representation includes respective columns corresponding to a spectrum at a particular instant.

12. The non-transitory computer readable medium of claim **11**, wherein the audio characteristic comprises an instrument corresponding to the enhanced harmonic source.

17

13. The non-transitory computer readable medium of claim 9, wherein the audio characteristic comprises a reference harmonic source that corresponds to the enhanced harmonic source.

14. The non-transitory computer readable medium of claim 9, wherein the audio characteristic comprises a genre corresponding to the enhanced harmonic source.

15. The non-transitory computer readable medium of claim 9, wherein the audio classification comprises a genre of the media signal.

16. The non-transitory computer readable medium of claim 9, wherein the instructions further comprise instructions to:

transmit the enhanced harmonic source; and

obtain at least one of an additional classification of the audio or an identifier corresponding to the media signal.

17. A method comprising:

determining, by executing an instruction with one or more processors, a magnitude spectrogram of audio corresponding to a media signal;

18

based on the determined magnitude spectrogram, enhancing, by executing an instruction with one or more processors, an enhanced harmonic source of the media signal;

comparing, by executing an instruction with one or more processors, the media signal having the enhanced harmonic source with reference media signals to determine an audio characteristic corresponding to the enhanced harmonic source;

identifying, by executing an instruction with one or more processors, an audio classification corresponding to the media signal based on the determined audio characteristic and

identify at least one of a song, an advertisement, a show, or a video game based on the determined audio characteristic.

18. The method of claim 17, wherein the audio characteristic comprises an instrument corresponding to the enhanced harmonic source.

19. The method of claim 17, wherein the audio characteristic comprises a reference harmonic source that corresponds to the enhanced harmonic source.

* * * * *