



(19) **United States**
(12) **Patent Application Publication**
Curtis et al.

(10) **Pub. No.: US 2014/0256466 A1**
(43) **Pub. Date: Sep. 11, 2014**

(54) **GOLF CLUB HEAD WITH IMPROVED PERFORMANCE**

continuation of application No. 12/643,203, filed on Dec. 21, 2009, now Pat. No. 8,262,501.

(71) Applicant: **Acushnet Company**, Fairhaven, MA (US)

Publication Classification

(72) Inventors: **Andrew J. Curtis**, Carlsbad, CA (US);
Charles E. Golden, Encinitas, CA (US);
Scott A. Rice, San Diego, CA (US);
Douglas E. Roberts, Carlsbad, CA (US);
Thomas W. Preece, San Diego, CA (US)

(51) **Int. Cl.**
A63B 53/04 (2006.01)
(52) **U.S. Cl.**
CPC *A63B 53/0466* (2013.01); *A63B 2053/0408* (2013.01); *A63B 2053/0458* (2013.01)
USPC **473/345**

(73) Assignee: **Acushnet Company**, Fairhaven, MA (US)

(57) **ABSTRACT**

(21) Appl. No.: **14/282,124**


A golf club head with an improved sweet spot, defined as a portion of the striking face that has at least 99.7% of the maximum ballspeed is disclosed herein. More specifically, the present invention discloses a golf club head with a significantly circular sweet spot that encompasses at least about 1.5% of the total striking face. A golf club head in accordance with the present invention may generally have a improved face geometry with an elliptical factor of greater than about 0.5, a beveled transition portion around the striking face of the golf club head, a variable face thickness region with decreases thickness, or even a tilted bulge and roll radius all helping improve the performance of the golf club head.

(22) Filed: **May 20, 2014**

Related U.S. Application Data

(63) Continuation of application No. 13/953,498, filed on Jul. 29, 2013, now Pat. No. 8,758,160, which is a continuation of application No. 13/600,291, filed on Aug. 31, 2012, now Pat. No. 8,500,572, which is a

800






FIG. 1




FIG. 2




FIG. 3





FIG. 4



(Prior Art)
FIG. 5




FIG. 6




FIG. 7




FIG. 8a




FIG. 8b




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13

GOLF CLUB HEAD WITH IMPROVED PERFORMANCE

CROSS REFERENCE TO RELATED APPLICATION

[0001] The present application is a Continuation of co-pending U.S. patent application Ser. No. 13/953,498, filed on Jul. 29, 2013, which is a Continuation of U.S. patent application Ser. No. 13/600,291, filed on Aug. 31, 2012, now U.S. Pat. No. 8,500,572, which is a Continuation of U.S. patent application Ser. No. 12/643,203, filed Dec. 21, 2009, now U.S. Pat. No. 8,262,501, the disclosure of which are all incorporated by reference in their entirety.

FIELD OF THE INVENTION

[0002] The present invention relates generally to a golf club head that is capable of achieving an improved sweet spot, defined as a portion of the striking face that has at least 99.7% of the maximum ballspeed. More specifically, the present invention relates to a golf club head wherein the sweet spot covers at least 1.5% of the entire total striking face of the golf club head. Even more specifically, the present invention relates to a golf club head with a significantly elliptical shaped striking face with an elliptical factor of greater than about 0.50 to achieve an improved sweet spot, wherein the elliptical factor is defined as the length of the minor axis divided by the length of the major axis. The present invention may also relate to a golf club head with a tilted bulge and roll radius to further improve the performance of the golf club head.

BACKGROUND OF THE INVENTION

[0003] In the competitive industry of golf club design, distance and accuracy are two of the most important performance factors that help define the desirability of a metal wood type golf club. Although some may argue that the look, feel, and sound of a golf club may influence their opinion of a golf club; there is no arguing that the performance factors play a major role in determining the desirability of a golf club. The performance factors of maximizing distance while maintaining accuracy becomes even more prevalent in a metal wood type golf club head. Unlike iron type golf club heads where accuracy of a golf shot clearly trumps the distance benefits gained by any individual golf club, metal wood type golf club heads are designed to allow a golfer to hit the golf ball as far as possible in and as straight as possible.

[0004] In order to maximize distance while maintaining accuracy of a metal wood type golf club head, metal wood type golf clubs have been designed with the objective of maximizing the distance of a golf ball struck by a golf club head close to the geometric center of the golf club head. This geometric center of the golf club head, due to the inherent laws of physics, may generally produce a golf shot that maximizes the distance by reducing the energy loss between the golf ball and the golf club head. In order to quantify this value, the United States Golf Association (USGA), in conjunction with the golfing industry, have come up with various methods such as the calculation the Coefficient of Restitution (COR) or the calculation of the Characteristic Time (CT) as ways to quantify the rebounding characteristic of a golf ball after it impacts a golf club head.

[0005] U.S. Pat. No. 6,390,933 to Galloway et al. ('933 Patent) discusses one of the methods to increase the COR of a golf club head by disclosing a golf club head having a

coefficient of restitution greater than 0.845 and a durability to withstand 2000 impacts with a golf ball at 110 miles per hour, wherein the club head may be composed of three pieces, a face, a sole, and a crown. More specifically, the '933 Patent discloses a golf club head that may be composed of a titanium material, having a volume in the range of 175 cubic centimeters to 400 cubic centimeters, a weight in the range of 165 grams to 300 grams, and a striking plate surface area in the range of 4.00 square inches to 7.50 square inches.

[0006] Focusing on accuracy instead of distance, U.S. Patent Publication No. 2004/0116202 to Lin ('02 Patent Publication), discusses a method to increase the accuracy of a golf club head by disclosing a golf club head having a plurality of holes around the periphery of the club head, so that when the club head hits the golf ball, most of the vibration waves and sound waves generated are dispersed out of these holes thus improving accuracy of the direction of the striking golf ball.

[0007] However, upon closer examination, we can see that developments in maximizing distance while maintaining accuracy of a metal wood type golf club head are premised upon the fact that the golfer be capable of hitting the golf ball at the sweet spot. The sweet spot, generally coinciding with the geometric center of the golf club, may cover such a small area of the striking face of the golf club head, it may be difficult for the average golfer to consistently strike a golf ball in the sweet spot. Hence, in addition to the performance factors mentioned above, it may also be desirable to increase the size of this sweet spot, so an average golfer may obtain the design benefits of maximizing the distance and accuracy of the golf club head without having to strike the golf ball perfectly every time.

[0008] In order to address the issue that the golfer may not always strike a golf ball at the center of the striking face, the industry has attempted to experiment striking faces having different variable face thickness. In fact, different golf club heads may even have multiple zones with different thicknesses to improve the size of the sweet spot to allow the average golfer to achieve maximum results even when they do not hit the golf ball at the center of the striking face. Despite the fact that these methodologies may improve the size of the club head, they do not take into consideration the performance benefits that may be achieved by adjusting the actual geometry of the striking face of the golf club head.

[0009] It can be seen from above there is a need in the field for a golf club head that is capable of utilizing the geometry of the striking face of the golf club head itself to increase the size of the sweet spot of the golf club head. More specifically, there is a need in the field for a golf club head that allows the average golfer to achieve performance benefits similar to those achievable by the skilled professional golfer even when they do not strike the golf ball directly at the center of the golf club head.

BRIEF SUMMARY OF THE INVENTION

[0010] One aspect of the present invention is a golf club head comprising a striking face, a posterior body portion, and a beveled transition portion. The striking face may have a frontal surface area of greater than 3600 mm². The posterior body portion may further comprise a crown portion coupled to an upper portion of the striking face and a sole portion coupled to a lower portion of the striking face. The beveled transition portion is at least partially surrounding the perimeter of the striking face, connecting the striking face with the

posterior body. The golf club head may have a sweet spot, defined as the area of the frontal surface of the striking face having at least 99.7% of the maximum ballspeed achievable by a golf club head, that encompasses greater than about 1.5% of the frontal surface area of the striking face.

[0011] In another aspect of the present invention is a golf club head comprising a striking face, a posterior body portion, and a beveled transition portion. The striking face may have a frontal surface area of greater than 3600 mm². The posterior body portion may further comprise a crown portion coupled to an upper portion of the striking face and a sole portion coupled to a lower portion of the striking face. The beveled transition portion is at least partially surrounding the perimeter of the striking face, connecting the striking face with the posterior body, wherein the beveled transition portion further comprises of at least a toe beveled transition portion and a heel beveled transition portion. The toe beveled transition portion may have a radius of curvature of greater than about 30 mm and the heel beveled transition portion may have a radius of curvature greater than about 25 mm.

[0012] In a further aspect of the present invention is a golf club head comprising a striking face and a posterior body portion. The striking face may have a frontal surface area of greater than 3600 mm². The posterior body portion may further comprise a crown portion coupled to an upper portion of the striking face and a sole portion coupled to a lower portion of the striking face. The frontal surface area of the striking face may further comprise a bulge radius spanning in an approximately horizontal direction across the frontal surface area of the striking face from a heel portion to a toe portion and a roll radius spanning in an approximately vertical direction across the frontal surface area of the striking face from a crown portion to a sole portion; wherein the bulge and roll radius are tilted in a direction of high toe to low heel.

[0013] These and other features, aspects, and advantages of the present invention will become better understood with references to the following drawings, description and claims.

BRIEF DESCRIPTION OF THE DRAWINGS

[0014] The foregoing and other features and advantages of the invention will be apparent from the following description of the invention as illustrated in the accompanying drawings. The accompanying drawings, which are incorporated herein and form a part of the specification, further serve to explain the principles of the invention and to enable a person skilled in the pertinent art to make and use the invention.

[0015] FIG. 1 is a frontal elevated view of a golf club head in accordance with an exemplary embodiment of the present invention;

[0016] FIG. 2 is a frontal view of a golf club head in accordance with an exemplary embodiment of the present invention;

[0017] FIG. 3 is a graphical representation of a typical impact pattern between a golf club and a golf ball;

[0018] FIG. 4 is a frontal view of a golf club head showing the relative size, shape, and location of a sweet spot in accordance with an exemplary embodiment of the present invention;

[0019] FIG. 5 is a graphical representation of an enlarged view of a prior art sweet spot associated with a prior art golf club head;

[0020] FIG. 6 is a graphical representation of an enlarged view of an improved sweet spot in accordance with an exemplary embodiment of the present invention;

[0021] FIG. 7 is a top view of a golf club head in accordance with an exemplary embodiment of the present invention;

[0022] FIG. 8a is a cross-sectional view of a golf club head in accordance with an exemplary embodiment of the present invention taken along cross-sectional line A-A' as shown in FIG. 7;

[0023] FIG. 8b is a frontal view of the golf club head in accordance with an exemplary embodiment of the present invention showing the geometry behind the striking face;

[0024] FIG. 9 is a graphical representation of an enlarged view of an improved sweet spot in accordance with an exemplary embodiment of the present invention;

[0025] FIG. 10 is a toe biased perspective view of a golf club head in accordance with an exemplary embodiment of the present invention;

[0026] FIG. 11 is a heel biased perspective view of a golf club head in accordance with an exemplary embodiment of the present invention;

[0027] FIG. 12 is a graphical representation of an enlarged view of an improved sweet spot in accordance with an exemplary embodiment of the present invention; and

[0028] FIG. 13 is a frontal view of a golf club head showing a tilted bulge and roll radius in accordance with an exemplary embodiment of the present invention.

DETAILED DESCRIPTION OF THE INVENTION

[0029] The following detailed description is of the best currently contemplated modes of carrying out the invention. The description is not to be taken in a limiting sense, but is made merely for the purpose of illustrating the general principles of the invention, since the scope of the invention is best defined by the appended claims.

[0030] Various inventive features are described below that can each be used independently of one another or in combination with other features. However, any single inventive feature may not address any or all of the problems discussed above or may only address one of the problems discussed above. Further, one or more of the problems discussed above may not be fully addressed by any of the features described below.

[0031] FIG. 1 shows an elevated view of a golf club head 100 in accordance with an exemplary embodiment of the present invention. Golf club head 100 shown here in FIG. 1 may generally have a striking face 102, a posterior body portion 104 and a hosel 105. The posterior body portion 104 may generally be further comprised of a crown portion 106, a sole portion (not shown), and a skirt portion 110. The crown portion 106 may generally be connected to the upper portion of the striking face 102 while the sole portion (not shown) may generally be connected to the bottom portion of the striking face 102. The skirt portion 110, as shown in the current exemplary embodiment, may generally be juxtaposed between the crown portion 106 and the sole portion (not shown) to complete the posterior body portion 104. Golf club head 100, as shown in the current exemplary embodiment depicted by FIG. 1, may generally have a beveled transition portion 112 at least partially surrounding the perimeter of the striking face 102. More specifically, as we can see in FIG. 1, the beveled transition portion 112 may be further comprised of a toe beveled transition portion 114 and a heel beveled transition portion 116 surrounding the striking face 102 near the toe and heel portion of the striking face 102 respectively. It should be noted that although the current exemplary embodiment shown in FIG. 1 only shows the beveled transi-

tion portion **112** covering the toe and heel portion of the golf club head **100**, the beveled transition portion **112** could completely surround the perimeter of the striking face **102** without departing from the scope and content of the present invention.

[0032] It should be noted in FIG. 1 that the striking face **102** may generally have a surface area of greater than about 3600 mm², more preferably greater than about 3700 mm², and most preferably greater than about 3750 mm². Additionally, the beveled transition portion **112** may generally have a surface area of less than about 850 mm², more preferably less than about 825 mm², and most preferably less than about 810 mm². Finally, the entire golf club head **100** may generally have a surface area of between about 32,000 mm² and about 35,000 mm². With the surface area value above, it is important to determine the ratio of the surface area of the striking face **102** relative to the total area of the entire golf club head **100**. This striking face surface area ratio may generally be greater than about 9%, more preferably greater than about 10%, and most preferably greater than about 11%. Alternatively, the above surface areas may also yield a beveled transition portion surface area ratio. This beveled transition portion surface area ratio may generally be less than about 3.0%, more preferably less than about 2.75%, and most preferably less than about 2.5%.

[0033] FIG. 2 shows a frontal view of a golf club head **200** in accordance with an exemplary embodiment of the present invention. This frontal view of the golf club head **200** allows a more direct view of the striking face **202** showing the striking face **202** being of a significantly elliptical shape; with a major axis **220** running in a significantly heel to toe direction and a minor axis **222** running in a significantly crown to sole direction. The striking face **202** of the golf club head **200** in accordance with an exemplary embodiment of the present invention may generally have an elliptical factor greater than about 0.33, more preferably greater than about 0.41, and most preferably greater than about 0.50. The elliptical factor discussed above may be defined by Equation 1 below:

$$\text{Elliptical Factor} = \frac{\text{Length of Minor Axis 222}}{\text{Length of Major Axis 220}} \quad \text{Eq. (1)}$$

The length of the major axis **220** may generally be defined as the distance of the longest line that can be drawn on the striking face **202**. Here, in this current exemplary embodiment shown in FIG. 2, the major axis **220** spans in a direction that is significantly heel to toe; however the major axis **220** could be orientated in any other direction that deviates from the current orientation so long it represents the longest line that can be drawn on the striking face **202** all without departing from the scope and content of the present invention. Minor axis **222**, as shown in the current exemplary embodiment, may generally be defined as a line across the striking face **202** that runs perpendicular to the major axis **220**, while passing through the geometric center **201** of the striking face **202**.

[0034] The length of the major axis **220**, as shown in the current exemplary embodiment, may generally be less than about 120 mm, more preferably less than about 110 mm, and most preferably less than about 100 mm. The length of the minor axis **222** on the other hand, as shown in the current exemplary embodiment, may generally be greater than about 40 mm, more preferably greater than about 45 mm, and most preferably greater than about 50 mm. Hence, it can be seen

that when the length of the minor axis **222** is divided by the length of the major axis **220**, the resulting elliptical factor may generally be within the range discussed above.

[0035] The frontal view of golf club head **200** shown in FIG. 2 may also help illustrate how the striking face **202** of the golf club head **200** is tilted in a more upright position while keeping the golf club head **200** in a relatively flat position. Alternatively speaking, the vertical minor axis **222** of the striking face **202** may generally be tilted at an angle θ when compared to a vertical line **223** that is vertical to the ground **225**. The angle θ , as shown in the current exemplary embodiment, may generally be greater than about 3.0 degrees and less than about 16.0 degrees, more preferably greater than about 3.0 degrees and less than about 12.0 degrees, and most preferably greater than about 3.0 degrees and less than about 8.0 degrees. As it can be seen from FIG. 2, the tilting of the striking face **202** of the golf club head **200** relative to the ground **225** will also cause the major axis **220** and minor axis **222** to tilt to the same extent and in the same direction. Viewed in another way, the tilt of the striking face **202** may also be defined as having the major axis **220** and the minor axis **222** both tilted in a direction of high toe to low heel by an angle of greater than about 3.0 degrees and less than about 16.0 degrees, more preferably greater than about 3.0 degrees and less than about 12.0 degrees, and most preferably greater than about 3.0 degrees and less than about 8.0 degrees.

[0036] To understand the rationale behind the tilting of the striking face **202** of the golf club head **200**, it may be beneficial to view FIG. 3 showing the typical impact pattern of a golfer relative to the striking face **202**; with each of the dots on the graph representing a typical hit location when a golfer hits a golf ball with a golf club. As it has been reported in F. Werner and R. Greig, How Golf Clubs Really Work and How to Optimize Their Designs, Ch. 4, pp. 17-21 (2000), a typical distribution of golf ball hits on the face of a driver clubs follows an elliptical pattern with its major axis orientating in a direction from high toe to low heel, corresponding with the elliptical pattern shown in FIG. 3. Examining more closely the impact pattern shown in FIG. 3, we can determine that the major axis **320** of the impact pattern may form an angle α with the horizontal axis **323**. This angle α may generally coincide with the tilt angle θ of the striking face **202** of the golf club head **200** shown in FIG. 2. More specifically, α may generally be greater than about 3.0 degrees and less than about 16.0 degrees, more preferably greater than about 3.0 degrees and less than about 12.0 degrees, and most preferably greater than about 3.0 degrees and less than about 8.0 degrees.

[0037] Returning to FIG. 2, we can see from the hit pattern shown in FIG. 3 that it may be desirable to tilt the striking face **202** of the golf club head **200** at an angle θ that corresponds to the tilt angle α of the impact pattern. More important than the tilting of the striking face **202** of the golf club head **200** results in the tilting of the major axis **220** and the minor axis **222**, as tilting the afore mentioned axes will allow the striking face **202** to be more in alignment with the typical hit pattern shown in FIG. 3.

[0038] Turning now to FIG. 4, showing another frontal view of a golf club head in accordance with an embodiment of the present invention, we can see that the golf club head **400** is shown with a sweet spot **430** located near the geometric center **401** of the striking face **402** of the golf club head **400**. More specifically, the sweet spot **430** may generally be concentric with the geometric center **401** of the striking face **402** of the golf club head **400**. One of the major advantage of a golf

club head **400** designed in accordance with the present invention is that it may offer an improved sweet spot that is significantly larger than previously achievable. More specifically, a golf club head **400** in accordance with an exemplary embodiment of the present invention may have a sweet spot **430** that encompasses greater than about 1.5% of the total surface area of the striking face **402**, more preferably greater than about 1.75% of the striking face **402**, and most preferably greater than about 2.0% of the striking face **402**. The sweet spot **430**, within the context of the current application, may generally be defined as the area of the entire striking face **402** that is capable of achieving at least 99.7% of the maximum ballspeed achievable by the golf club head **400**. The 99.7% value utilized in determining the size of the sweet spot **430** may be relevant, because a golf ball that is capable of achieving 99.7% of the maximum ballspeed only loses about ½ a mile per hour of ballspeed when compared to a direct central hit achieving 100% of the maximum ballspeed capable by the golf club head **400**. The maximum ballspeed achievable by the golf club head **400**, as shown in the current exemplary embodiment, may generally relate to the highest ballspeed that can be achieved by the golf club head regardless of where the golf club head **400** strikes a golf ball.

[0039] Here, shown in FIG. 4, the area of the striking face **402** of a golf club head **400** in accordance with an exemplary embodiment of the present invention may generally be greater than about 3600 mm², more preferably greater than about 3700 mm², and most preferably greater than about 3750 mm². The area of the sweet spot **430** on the other hand, may generally have an area greater than about 75 mm², more preferably greater than about 110 mm², and most preferably greater than about 120 mm². An better view of the sweet spot **430**, showing its improved geometric profile may be shown later in FIGS. 6, 9, and 12; wherein it can focus on an enlarged ballspeed grid showing an enlarged view of the sweet spot **430**. Considering the areas of the striking face **402** and the sweet spot **430** above, we can see that the sweet spot **430** encompasses greater than about 1.5% of the striking face **402**, more preferably greater than about 1.75% of the striking face **402**, and more preferably greater than about 2.0% of the striking face **402**.

[0040] In order to properly explain the size of this improved sweet spot **430** in accordance with an exemplary embodiment of the present invention, it may be worth while to examine the sweet spot size that is generally attributed to the striking face portion of a prior art golf club head. FIG. 5 shows the sweet spot **530** of a prior art golf club head that has at least 99.7% of the maximum ballspeed within a ballspeed grid **531** located on the striking face of a prior art golf club head. The ballspeed grid **531**, as defined in this context, may generally be rectangular area located on the striking face of a golf club head with a dimension of 40 mm in width by 20 mm in height. The sweet spot **530** of a normal prior art golf club head may generally have an area of about 45 mm², which is significantly smaller than the sweet spot area **430** achievable by a golf club head **400** in accordance with an exemplary embodiment of the present invention.

[0041] It is also worth noting that this prior art sweet spot **530** shown in FIG. 5, in addition to being significantly small in size, also suffers from a less than optimal shape. More specifically, this prior art sweet spot **530** has a significantly elliptical shape, with a major axis **532** spanning in a significantly horizontal direction and a minor axis **534** spanning in a significantly vertical direction. A closer examination of this

prior art sweet spot **530** within this prior art golf club head may show that the major axis is significantly longer than the minor axis of the sweet spot, wherein the circumference of the sweet spot at the horizontal ends along the major axis may be a significantly further distance away from the circumference of the sweet spot at the vertical end. This elliptical sweet spot **530** may be undesirable because it fails to capture the extremities of a typical impact pattern shown in FIG. 3, especially when the misses are at a location that is high toe or low heel.

[0042] FIG. 6 shows the sweet spot **630** of a golf club head in accordance with an exemplary embodiment of the present invention within a ballspeed grid **631** of the same size. First and foremost, as it can be seen from FIG. 6, the size of the sweet spot **630** is significantly bigger than the size of the prior art sweet spot **530** shown in FIG. 5. More specifically, the sweet spot **630** shown in this current exemplary embodiment may generally have an area of about 75 mm², which may be the result of the enhanced face geometry shown before in FIG. 2. In addition to the larger sweet spot **630**, the improved sweet spot **630** may also have an improved shape that is more circular, allowing the sweet spot **630** to capture more of the impact region shown in FIG. 3. More specifically, the sweet spot **630**, as shown in the current exemplary embodiment in FIG. 6, may generally be of a more circular shape, with a major axis **632** and a minor axis **634** being approximately the same length. Alternatively speaking, no point along the circumference of the sweet spot **630** may be more than about 5.0 mm away from the geometric center of the sweet spot **630** while maintaining a sweet spot **630** area of about 75 mm².

[0043] Although the enhanced face geometry shown in FIG. 2 may improve the size and shape of the sweet spot **630** shown in FIG. 6, a further exemplary embodiment of a golf club head shown in FIG. 7 and FIG. 8 may provide additional features and benefits that could further enhance the performance of a golf club head **200** shown in FIG. 2. Turning now to FIG. 7 which shows a top view of a golf club head **700** in accordance with a further exemplary embodiment of the present invention having a striking face **702** with a variable face thickness. Although the variable face thickness can not be seen from FIG. 7, FIG. 7 provides a cross sectional line A-A' across the center of the golf club head **700**, allowing a cross sectional profile of golf club head **700** to be shown in FIG. 8a with a variable face thickness profile.

[0044] FIG. 8a shows a cross sectional view of the golf club head **700** taken along cross sectional line A-A' shown in FIG. 7. Golf club head **800**, as shown in this current exemplary embodiment in FIG. 8a, may have a striking face **802** with a variable face thickness profile **840** behind the striking face **802**. More specifically, the variable face thickness profile **840**, as shown in the current exemplary embodiment, may generally be comprised of a thick central portion **842** surrounded by a transition portion **843**, which is then surrounded by a thin perimeter portion **844**. Because the striking face **802** of a golf club head **800** deforms like a trampoline when striking a golf ball, having a variable face thickness profile **840** allows the thin perimeter portion **844** of the striking face **802** to be thin enough to provide a trampoline effect while the thick central portion **842** of the variable face thickness profile **840** provides sufficient thickness to endure the stresses associated with a golf ball impact. Because the beveled transition portion **112** (shown in FIG. 1) may provide additional structural stiffness to the striking face **802** of the golf club head **800**, the striking face **802** of the golf club head may be made

thinner to create an even bigger sweet spot. More specifically, the increased structural stiffness may allow the thickness of the thin perimeter portion **844** to be less than about 3.0 mm thick, more preferably less than about 2.9 mm thick, and most preferably less than about 2.8 mm thick. More detailed disclosure regarding using variable face thickness to improve the performance of a golf club head may be found in U.S. Pat. No. 7,029,403 to Rice et. al., the disclosure of which is incorporated by reference in its entirety.

[0045] FIG. **8b** shows a frontal view of the internal geometry of a golf club head **800** with a variable face thickness profile **840**. More specifically, FIG. **8b** shows the relative size and position of the central portion **842**, the transition portion **843**, and the thin perimeter portion **844**. Although not specifically labeled in FIG. **8b**, because the striking face **802** of the golf club head **800** is tilted in a direction that is high heel to low toe, the variable face thickness profile **840** may be tilted in a direction of high toe to low heel by an angle θ . The angle θ , as previously discussed in FIG. **2**, may generally be greater than about 3.0 degrees and less than about 16.0 degrees, more preferably greater than about 3.0 degrees and less than about 12.0 degrees, and most preferably greater than about 3.0 degrees and less than about 8.0 degrees.

[0046] It is also worth noting here in FIG. **8b** that the central portion **842** may generally have an elliptical profile shape with a major axis **820** running substantially in a direction of heel to toe and a minor axis **822** running substantially in a direction of crown to sole. The shape and proportion of the central portion **842**, defined by the relative length of the major axis **820** and the minor axis **822**, may generally correlate with the Elliptical Factor as previously discussed in FIG. **2**. The central portion **842** of the striking face **902** in accordance with an exemplary embodiment of the present invention may generally have an elliptical factor greater than about 0.33, more preferably greater than about 0.41, and most preferably greater than about 0.50, calculated based on Eq. (1) above.

[0047] This enlarged view of the variable face thickness profile **840** also shows an interesting relationship of the different widths of the perimeter of the transition portion **843** relative to the central portion **842**. More specifically, as we can see from FIG. **8b**, the transition portion **843** may have a variable transition width C1, C2, C3, or C4 depending on where the width measurement is taken. The transition width C1, C2, C3, and C4 may have different values resulting in a shift in the placement of the central portion **842** within the transition portion **843** without departing from the scope and content of the present invention. "Transition width", as used herein, may generally refer to the distances C1, C2, C3, and C4, signifying the distance between the perimeter of the central portion **842** and the perimeter of the transition portion **843** measured from a point that is normal to a tangent line taken at that point across the perimeter of the central portion **842**.

[0048] Alternatively speaking, the geometric center of the central portion **842** shown in FIG. **8b** may be offset from the geometric center of the transition portion **843** within the two dimensional plane shown in FIG. **8b**. In one exemplary embodiment of the present invention, the transition width C1 near the top of the transition portion **843** may generally be greater than the transition width C2 near the bottom of the transition portion **843**. More specifically, transition width C2 may generally equal to about 80% of the transition width C1 to improve the performance of the variable face thickness profile **840**. This ratio of a wider transition width C1 com-

pared a narrower transition width C2, may yield a central portion **842** that sits closer to the bottom or sole of the striking face **802** with a placement that is sole biased. In the current exemplary embodiment of the present invention, the transition width C1 may generally be greater than about 8.0 mm, while the width C2 may generally be about less than about 7.0 mm. More specifically, transition width C1 may generally be about 8.5 mm, while transition width C2 may generally be about 6.8 mm. However, in other alternative embodiment of the present invention, the transition width C2, may be wider than transition width C1 to create a central portion **842** that sits closer to the top or crown of the striking face **802** without departing from the scope and content of the present invention.

[0049] Other than changing the transition width C1, and C2 of the transition portion **843** along the minor axis **822**, it should be noted that the transition width C3 and C4 along the major axis **820** may adjusted to further adjust the size and placement of the central portion **842** within the transition portion **843** without departing from the scope and content of the present invention. In fact, the current invention could involve the adjustment of all of the transition widths C1, C2, C3, and C4 simultaneously all without departing from the scope and content of the present invention. In an exemplary embodiment of the present invention, transition width C3 and C4 may be about the same width as transition width C1 to yield a more centralized placement of the central portion **842** within the transition portion **843**. In an alternative embodiment of the present invention, transition widths C3 or C4 may be greater than transition width C1 to further adjust the size or placement of the central portion **842** also without departing from the scope and content of the present invention. In a further alternative embodiment of the present invention, transition widths C3 and C4 may generally be greater than about 8.0 mm, more preferably greater than about 8.2 mm, and most preferably greater than about 8.3 mm.

[0050] FIG. **9** shows a sweet spot **930** in accordance with a further exemplary embodiment of the present invention utilizing both the enhanced face geometry shown in FIG. **2** and the variable face thickness profile shown in FIG. **8**. As it can be seen from FIG. **9** utilizing a ballspeed grid **931** of the same size as previously shown, the size of the sweet spot **930** is significantly larger than any of the previous plots. More specifically, the size of the sweet spot **930**, corresponding to a golf club head **900** incorporating the enhanced face geometry as well as the variable face thickness profile, may generally have an area that is about 110 mm². In addition to the larger sweet spot **930**, the sweet spot **930** may also have a shape that is more circular, allowing the sweet spot **930** to encompass more of the impact region shown in FIG. **3**. Similar to what is already described in FIG. **6**, the sweet spot **930** may generally be of a more circular shape wherein no point along the circumference of the sweet spot **930** may be more than about 6.0 mm away from the geometric center of the sweet spot **930** while maintaining a sweet spot **930** area of about 110 mm².

[0051] FIGS. **10**, **11**, and **12** show further alternative embodiments of the present invention wherein the beveled transition portion that at least partially surrounds the striking face could further improve the performance of a golf club by further enlarging the size of the sweet spot. More specifically, because the beveled transition portion at least partially surrounds the striking face, the beveled transition portion could provide additional structural stiffness, allowing the striking face to be made thinner. A golf club head with a thinner striking face could be beneficial to the performance charac-

teristics because it allows for more discretionary weight that could be distributed around the striking face of a golf club head to create a larger sweet spot by adjusting the thickness of the various portions all without departing from the scope and content of the present invention.

[0052] In addition to the above, the beveled transition portion could also improve the confidence factor of a golfer when the golfer attempts to hit a golf ball using the golf club head. Because golfers are accustomed to a golf club having a specific shape and geometry, dramatic deviation of the shape and geometry of a golf club from the traditional shape and size could cause a golfer to be distracted by an abnormal shape and geometry; causing him to lose confidence. Because the elliptical factor above that improves the performance of a golf club head causes the striking face portion of the golf club head to deviate from the conventional shape and size, some may consider a golf club head with such a shape, size, and geometry to be unconventional. The beveled transition portion helps address this issue by taking away extraneous material from the perimeter of the striking face bringing the golf club back into a more traditional shape. More specifically, the beveled transition portion may have a higher radius of curvature around the toe and heel portion to recapture the traditional shape and geometry of a golf club head to inspire confidence to a golfer.

[0053] FIG. 10 shows a perspective of an inventive golf club head **1000** in accordance with an exemplary embodiment of the present invention viewed from the toe portion of the golf club head **1000**. This toe biased perspective view of the golf club head **1000** shows the beveled transition portion **1012** around the toe portion of the golf club head. More specifically, FIG. 10 illustrates the various radius of curvature around the striking face **1002** that can be used to create the beveled transition portion **1012**. The radius of curvature for the crown transition portion **1015** of the golf club head **1000**, between the striking face **1002** and the crown **1006**, may generally be less than about 5 mm, more preferably less than about 3 mm, and most preferably less than about 2 mm. The radius of curvature for the toe beveled transition portion **1014** on the other hand, may generally be variable in order to create a proper transition between the crown transition portion **1015** and the sole transition portion **1017**. More specifically, the radius of curvature for the toe beveled transition portion **1014** may generally be greater than about 25 mm at its flattest point, more preferably greater than about 30 mm at its flattest point, and most preferably greater than about 35 mm at its flattest point. Hence, it can be seen from FIG. 10 that although the crown transition portion **1015** may generally have a constant radius of curvature, the toe beveled transition portion **1014** may have a varying radius of curvature from about 2 mm to about 35 mm to ensure a smooth transition between the two transition portions. It is worth noting here that although the toe transition portion **1014** may generally refer to the toe portion of the perimeter of the striking face **1002**, it may extend into the crown transition portion **1015** or even the sole transition portion **1017** to smooth out the transition between the varying radius of curvature without departing from the scope and content of the present invention.

[0054] FIG. 11 shows a perspective of an inventive golf club head **1100** in accordance with an exemplary embodiment of the present invention viewed from the heel portion of the golf club head **1100**. Similar to FIG. 10, the golf club head **1100** has a crown transition portion with the same radius of curvature as discussed earlier in FIG. 10. FIG. 11, however,

shows a heel beveled transition portion **1116** having a radius of curvature of greater than about 20 mm at its flattest point, more preferably greater than about 25 mm at its flattest point, and most preferably greater than about 27.5 mm at its flattest point. Similar to the toe beveled transition portion **1014** (shown in FIG. 10), the heel beveled transition portion **1116** may also have a variable radius of curvature from about 2 mm to about 27.5 mm to ensure a smooth transition between the two transition portions. The heel beveled transition portion **1116** may extend into the crown transition portion **1115** or even the sole transition portion **1117** to smooth out the transition between the varying radius of curvature also without departing from the scope and content of the present invention.

[0055] FIG. 12 shows a sweet spot **1230** of a golf club head in accordance with the further exemplary embodiment of the present invention utilizing the enhanced face geometry shown in FIG. 2, the variable face thickness profile shown in FIG. 8, and the beveled transition portion shown in FIGS. 10 and 11. As it can be seen from FIG. 12, utilizing a ballspeed grid **1231** of the same size as previously shown, the size of the sweet spot **1231** is significantly larger than any of the previous plots. More specifically, the size of the sweet spot **1230**, corresponding to a golf club head **1200** incorporating all of the above mentioned features, may generally have an area that is about 120 mm². In addition to the larger sweet spot **1230**, the sweet spot may also be more of a circular shape, with no point along the circumference of the sweet spot **1230** being more than 7.0 mm away from the geometric center of the sweet spot **1230** while maintaining a sweet spot **1230** area of about 120 mm².

[0056] FIG. 13 shows a further alternative embodiment of the present invention wherein the striking face **1302** may have a tilted bulge radius **1350** as well as a tilted roll radius **1352** to help improve the performance of a golf club head. Bulge radius **1350** may refer to the curvature of the striking face **1302** spanning in an approximately horizontal direction across the striking face **1302** from a heel portion to a toe portion. Roll radius **1352**, on the other hand, may generally refer to the curvature of the striking face **1302** spanning in an approximately vertical direction across the striking face **1302** from a crown portion to a toe portion. Although the tilted bulge radius **1350** and the tilted roll radius **1352** may not further enlarge the size of the sweet spot of a golf club head, it could help correct for mis-struck shots by imparting corrective spin on a golf ball. More detailed discussion of the effect of having a striking face **1302** with a bulge radius **1350** and a roll radius **1352** may be found in U.S. Pat. No. 6,595,869 to McCabe et al., the disclosure of which is incorporated by reference in its entirety.

[0057] It should be worth noting that in this current exemplary embodiment shown in FIG. 13, the striking face **1302** of the golf club head **1300** is tilted more upright by an angle θ , as already shown in FIG. 2. As mentioned earlier, this angle θ may align the majority of the striking face **1302** with the impact pattern of a normal golfer shown in FIG. 3. However, without any adjustment to the bulge radius **1350** and the roll radius **1352**, the compensation of the bulge and roll in terms of spinning the golf ball back into the central portion may no longer be correctly matched. Hence, it may be desirable to tilt the bulge radius **1350** and the roll radius **1352** more upright by an angle Φ of greater than about 1 degree and less than about 16 degrees, more preferably greater than about 1 degree and less than about 12 degrees, and most preferably greater than about 1 degree and less than about 8 degrees. Alternatively

speaking, the bulge radius **1350** and the roll radius **1352** may be tilted in a direction of high toe to low heel by an angle that is greater than about 1 degree and less than about 16 degrees, more preferably greater than about 1 degree and less than about 12 degrees, and most preferably greater than about 1 degree and less than about 8 degrees. It should be noted that although the current tilt angle Φ may generally match the tilt angle θ of the golf club head **1300**, the tilt angle Φ of the bulge and roll radius, **1350** and **1352** respectively, can be determined independent of the tilt angle θ of the golf club head **1300** itself without departing from the scope and content of the present invention.

[0058] Other than in the operating example, or unless otherwise expressly specified, all of the numerical ranges, amounts, values and percentages such as those for amounts of materials, moment of inertias, center of gravity locations, loft, draft angles, various performance ratios, and others in the foregoing portions of the specification may be read as if prefaced by the word “about” even though the term “about” may not expressly appear in the value, amount, or range. Accordingly, unless indicated to the contrary, the numerical parameters set forth in the following specification and attached claims are approximations that may vary depending upon the desirable properties sought to be obtained by the present invention. At the very least, and not as an attempt to limit the application of the doctrine of equivalents to the scope of the claims, each numerical parameter should at least be construed in light of the number of reported significant digits and by applying ordinary rounding techniques.

[0059] Notwithstanding that the numerical ranges and parameters setting forth the broad scope of the invention are approximations, the numerical values set forth in the specific examples are reported as precisely as possible. Any numerical value, however, inherently contains certain errors necessarily resulting from the standard deviation found in their respective testing measurements. Furthermore, when numerical ranges of varying scope are set forth herein, it is contemplated that any combination of these values inclusive of the recited values may be used.

[0060] It should be understood, of course, that the foregoing relates to exemplary embodiments of the present invention and that modifications may be made without departing from the spirit and scope of the invention as set forth in the following claims.

What is claimed is:

1. A golf club head comprising:

a striking face with a frontal surface area of greater than about 3,600 mm²;

a posterior body portion further comprising a crown portion and a sole portion, and

a beveled transition portion at least partially surrounding a perimeter of said striking face, connecting said striking face with said posterior body portion;

wherein said crown portion is coupled to an upper portion of said striking face and said sole portion is coupled to a lower portion of said striking face;

wherein said striking face has an elliptical geometry having a major axis less than about 120 mm and a minor axis greater than about 40 mm, and

wherein said beveled transition portion further comprises a toe beveled transition portion and a heel beveled transition portion, and a radius of curvature of said toe beveled transition portion is different from a radius of curvature of said heel beveled transition portion.

2. The golf club head of claim **1**, wherein said radius of curvature of said toe beveled transition portion is greater than about 25 mm.

3. The golf club head of claim **2**, wherein said radius of curvature of said toe beveled transition portion is greater than about 30 mm.

4. The golf club head of claim **3**, wherein said radius of curvature of said toe beveled transition portion is greater than about 35 mm.

5. The golf club head of claim **1**, wherein said radius of curvature of said heel beveled transition portion is greater than about 20 mm.

6. The golf club head of claim **5**, wherein said radius of curvature of said heel beveled transition portion is greater than about 25 mm.

7. The golf club head of claim **6**, wherein said radius of curvature of said heel beveled transition portion is greater than about 27.5 mm.

8. The golf club head of claim **1**, wherein said striking face further comprises;

a thickened portion located near a center of a rear of said striking face portion; and

a thin perimeter portion around said thickened portion; wherein said thin perimeter portion has a thickness of less than about 3.0 mm.

9. The golf club head of claim **8**, wherein said thin perimeter portion has a thickness of less than about 2.9 mm.

10. The golf club head of claim **9**, wherein said thin perimeter portion has a thickness of less than about 2.9 mm.

11. A golf club head comprising:

a striking face with a frontal surface area of greater than about 3,600 mm²;

a posterior body portion further comprising a crown portion and a sole portion, and

a beveled transition portion at least partially surrounding a perimeter of said striking face, connecting said striking face with said posterior body portion;

wherein said crown portion is coupled to an upper portion of said striking face and said sole portion is coupled to a lower portion of said striking face;

wherein said beveled transition portion further comprises a toe beveled transition portion and a heel beveled transition portion, and a radius of curvature of said toe beveled transition portion is different from a radius of curvature of said heel beveled transition portion, and

wherein said striking face further comprises;

a thickened portion located near a center of a rear of said striking face portion; and

a thin perimeter portion around said thickened portion; wherein said thin perimeter portion has a thickness of less than about 3.0 mm.

12. The golf club head of claim **11**, wherein said thin perimeter portion has a thickness of less than about 2.9 mm.

13. The golf club head of claim **12**, wherein said thin perimeter portion has a thickness of less than about 2.9 mm.

14. The golf club head of claim **11**, wherein said striking face has an elliptical factor of greater than about 0.33;

said elliptical factor defined as a length of a minor axis divided by a length of a major axis.

15. The golf club head of claim **14**, wherein said striking face has an elliptical factor of greater than about 0.41.

16. The golf club head of claim **15**, wherein said striking face has an elliptical factor of greater than about 0.50.

17. The golf club head of claim **16**, wherein said major axis is less than about 120 mm and said minor axis is greater than about 40 mm.

18. The golf club head of claim **17**, wherein said major axis is less than about 110 mm and said minor axis is greater than about 45 mm.

19. The golf club head of claim **18**, wherein said major axis is less than about 100 mm and said minor axis is greater than about 50 mm.

* * * * *