



US011865291B2

(12) **United States Patent**
Merritt et al.

(10) **Patent No.:** **US 11,865,291 B2**

(45) **Date of Patent:** **Jan. 9, 2024**

(54) **HEMOSTASIS VALVES AND METHODS OF USE**

(71) Applicant: **Inari Medical, Inc.**, Irvine, CA (US)

(72) Inventors: **Benjamin E. Merritt**, San Clemente, CA (US); **John C. Thress**, Capistrano Beach, CA (US); **Paul Lubock**, Monarch Beach, CA (US)

(73) Assignee: **Inari Medical, Inc.**, Irvine, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **18/142,518**

(22) Filed: **May 2, 2023**

(65) **Prior Publication Data**

US 2023/0270991 A1 Aug. 31, 2023

Related U.S. Application Data

(60) Division of application No. 17/705,189, filed on Mar. 25, 2022, now Pat. No. 11,697,011, which is a (Continued)

(51) **Int. Cl.**

A61M 39/06 (2006.01)

A61B 17/3207 (2006.01)

(52) **U.S. Cl.**

CPC **A61M 39/0613** (2013.01); **A61B 17/3207** (2013.01); **A61M 2039/062** (2013.01); **A61M 2039/0673** (2013.01)

(58) **Field of Classification Search**

CPC **A61M 2039/062**; **A61M 39/06**; **A61M 2039/0626**; **A61M 2039/0673**;
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,101,890 A 6/1914 Tunstead
2,784,717 A 3/1957 Thompson

(Continued)

FOREIGN PATENT DOCUMENTS

AU 2015210338 8/2015
CN 102186427 9/2011

(Continued)

OTHER PUBLICATIONS

European Patent Application No. 13838945.7, Extended European Search Report, 9 pages, dated Apr. 15, 2016.

(Continued)


Primary Examiner — Quynh-Nhu H. Vu

(74) *Attorney, Agent, or Firm* — Perkins Coie LLP

(57) **ABSTRACT**

Devices, systems, and methods for sealing medical devices, particularly during intravascular access, are disclosed herein. Some aspects relate to a hemostatic valve for sealing a wide range of medical devices, such as catheters, wires, embolectomy systems. The valve can include an elongate member having a first end, a second end, and a central lumen extending therebetween. A reinforcement structure extends along at least a portion of the elongate member and is coupled to the elongate member. A shell defining a first aperture and a second aperture may be included, which first and second apertures can be fluidly coupled by the elongate member. A tensioning mechanism is coupled to the shell and to the elongate member, the tensioning mechanism can be moveable between a first configuration wherein the tensioning mechanism is collapsed and the central lumen is sealed and a second configuration wherein the central lumen is open.

20 Claims, 10 Drawing Sheets



Related U.S. Application Data

continuation of application No. 17/226,318, filed on Apr. 9, 2021, which is a continuation of application No. 16/117,519, filed on Aug. 30, 2018, now Pat. No. 11,000,682.

(60) Provisional application No. 62/554,931, filed on Sep. 6, 2017.

(58) **Field of Classification Search**

CPC A61M 39/0613; F16K 7/06; F16K 7/04; F16K 7/08; F16K 7/02
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,846,179	A	8/1958	Monckton
2,955,592	A	10/1960	Maclean
3,088,363	A	5/1963	Sparks
3,197,173	A	7/1965	Taubenheim
3,416,531	A	12/1968	Edwards
3,435,826	A	4/1969	Fogarty
3,438,607	A	4/1969	Williams et al.
3,515,137	A	6/1970	Santomieri
3,675,657	A *	7/1972	Gauthier A61B 17/132 606/203
3,860,006	A	1/1975	Patel
3,892,161	A	7/1975	Sokol
3,923,065	A	12/1975	Nozick et al.
4,030,503	A	6/1977	Clark, III
4,034,642	A	7/1977	Tannucci et al.
4,222,380	A	9/1980	Terayama
4,243,040	A	1/1981	Beecher
4,287,808	A	9/1981	Leonard et al.
4,324,262	A	4/1982	Hall
4,393,872	A	7/1983	Reznik et al.
4,401,107	A	8/1983	Harber et al.
4,469,100	A	9/1984	Hardwick
4,523,738	A	6/1985	Raftis et al.
4,551,862	A *	11/1985	Haber A61F 2/0036 600/491
4,604,094	A	8/1986	Shook
4,611,594	A	9/1986	Grayhack et al.
4,634,421	A	1/1987	Hegemann
4,643,184	A	2/1987	Mobin-Uddin
4,646,736	A	3/1987	Auth et al.
4,650,466	A	3/1987	Luther
4,776,337	A	10/1988	Palmaz
4,790,812	A	12/1988	Hawkins, Jr. et al.
4,863,440	A	9/1989	Chin et al.
4,870,953	A	10/1989	DonMichael et al.
4,883,458	A	11/1989	Shiber
4,886,062	A	12/1989	Wiktor
4,890,611	A	1/1990	Monfort et al.
4,898,575	A	2/1990	Fischell et al.
4,946,440	A	8/1990	Hall
4,960,259	A	10/1990	Sunnanvader et al.
4,978,341	A	12/1990	Niederhauser
4,981,478	A	1/1991	Evard et al.
5,030,201	A	7/1991	Palestrant
5,059,178	A	10/1991	Ya
5,100,423	A	3/1992	Fearnot
5,127,626	A	7/1992	Hilal et al.
5,129,910	A	7/1992	Phan et al.
5,135,484	A	8/1992	Wright
5,154,724	A	10/1992	Andrews
5,158,533	A	10/1992	Strauss et al.
5,158,564	A	10/1992	Schnepp-Pesch et al.
5,192,274	A	3/1993	Bierman
5,192,286	A	3/1993	Phan et al.
5,192,290	A	3/1993	Hilal
5,197,485	A	3/1993	Grooters
5,234,403	A	8/1993	Yoda et al.
5,242,461	A	9/1993	Kortenbach et al.
5,244,619	A	9/1993	Burnham

5,329,923	A	7/1994	Lundquist
5,360,417	A	11/1994	Gravener et al.
5,364,345	A	11/1994	Lowery et al.
5,376,101	A	12/1994	Green et al.
5,383,887	A	1/1995	Nadal
5,389,100	A	2/1995	Bacich et al.
5,391,152	A	2/1995	Patterson et al.
5,419,774	A	5/1995	Willard et al.
5,421,824	A	6/1995	Clement et al.
5,443,443	A	8/1995	Shiber
5,456,667	A	10/1995	Ham et al.
5,476,450	A	12/1995	Ruggio
5,484,418	A	1/1996	Quiachon et al.
5,490,859	A	2/1996	Mische et al.
5,496,365	A	3/1996	Sgro
5,527,326	A	6/1996	Hermann et al.
5,549,626	A	8/1996	Miller et al.
5,591,137	A	1/1997	Stevens
5,639,276	A	6/1997	Weinstock et al.
5,653,684	A	8/1997	Laptewicz et al.
5,662,703	A	9/1997	Yurek et al.
5,746,758	A	5/1998	Nordgren et al.
5,749,858	A	5/1998	Cramer
5,769,816	A	6/1998	Barbut et al.
5,782,817	A	7/1998	Franzel et al.
5,800,457	A	9/1998	Gelbfish
5,827,229	A	10/1998	Auth et al.
5,846,251	A	12/1998	Hart
5,860,938	A	1/1999	Lafontaine et al.
5,873,866	A	2/1999	Kondo et al.
5,873,882	A	2/1999	Straub et al.
5,876,414	A	3/1999	Straub
5,895,406	A	4/1999	Gray et al.
5,908,435	A	6/1999	Samuels
5,911,710	A	6/1999	Barry et al.
5,911,733	A	6/1999	Parodi
5,911,754	A	6/1999	Kanesaka et al.
5,941,869	A	8/1999	Patterson et al.
5,947,985	A	9/1999	Imram
5,954,737	A	9/1999	Lee
5,971,938	A	10/1999	Hart et al.
5,971,958	A	10/1999	Zhang
5,972,019	A	10/1999	Engelson et al.
5,974,938	A	11/1999	Lloyd
5,989,233	A	11/1999	Yoon
5,993,483	A	11/1999	Gianotti
6,017,335	A	1/2000	Burnham
6,030,397	A	2/2000	Moneti et al.
6,059,814	A	5/2000	Ladd
6,066,158	A	5/2000	Engelson et al.
6,068,645	A	5/2000	Tu
6,126,635	A	10/2000	Simpson et al.
6,142,987	A	11/2000	Tsugita
6,146,396	A	11/2000	Konya et al.
6,146,403	A	11/2000	St. Germain
6,152,144	A	11/2000	Lesh et al.
6,152,946	A	11/2000	Broome et al.
6,156,055	A	12/2000	Ravenscroft
6,159,230	A	12/2000	Samuels
6,165,196	A	12/2000	Stack et al.
6,168,579	B1	1/2001	Tsugita
6,179,859	B1	1/2001	Bates et al.
6,221,006	B1	4/2001	Dubrul et al.
6,228,060	B1	5/2001	Howell
6,238,412	B1	5/2001	Dubrul et al.
6,245,078	B1	6/2001	Ouchi
6,245,089	B1	6/2001	Daniel et al.
6,254,571	B1	7/2001	Hart
6,258,115	B1	7/2001	Dubrul
6,264,663	B1	7/2001	Cano
6,306,163	B1	10/2001	Fitz
6,322,572	B1	11/2001	Lee
6,350,271	B1	2/2002	Kurz et al.
6,361,545	B1	3/2002	Macoviak et al.
6,364,895	B1	4/2002	Greenhalgh
6,368,339	B1	4/2002	Amplatz
6,383,205	B1	5/2002	Samson et al.
6,402,771	B1	6/2002	Palmer et al.
6,413,235	B1	7/2002	Parodi

(56)

References Cited

U.S. PATENT DOCUMENTS

6,423,032 B2	7/2002	Parodi	7,331,980 B2	2/2008	Dubrul et al.
6,432,122 B1	8/2002	Gilson et al.	7,481,805 B2	1/2009	Magnusson
6,451,036 B1	9/2002	Heitzmann et al.	7,534,234 B2	5/2009	Fotjik
6,458,103 B1	10/2002	Albert et al.	7,578,830 B2	8/2009	Kusleika et al.
6,475,236 B1	11/2002	Roubin et al.	7,621,870 B2	11/2009	Berrada et al.
6,485,502 B2	11/2002	Don Michael	7,674,247 B2	3/2010	Fotjik
6,508,782 B1	1/2003	Evans et al.	7,678,131 B2	3/2010	Muller
6,511,492 B1	1/2003	Rosenbluth et al.	7,691,121 B2	4/2010	Rosenbluth et al.
6,514,273 B1	2/2003	Voss et al.	7,695,458 B2	4/2010	Belley et al.
6,530,923 B1	3/2003	Dubrul et al.	7,713,282 B2	5/2010	Frazier et al.
6,530,935 B2	3/2003	Wensel et al.	7,722,641 B2	5/2010	van der Burg et al.
6,540,722 B1	4/2003	Boyle et al.	7,763,010 B2	7/2010	Evans et al.
6,544,276 B1	4/2003	Azizi	7,766,934 B2	8/2010	Pal et al.
6,544,278 B1	4/2003	Vrba et al.	7,775,501 B2*	8/2010	Kees F16K 7/065
6,544,279 B1	4/2003	Hopkins et al.			251/5
6,551,342 B1	4/2003	Shen et al.	7,780,696 B2	8/2010	Daniel et al.
6,564,828 B1	5/2003	Ishida	7,815,608 B2	10/2010	Schafersman et al.
6,569,181 B1	5/2003	Burns	7,905,877 B1	3/2011	Oscar et al.
6,575,995 B1	6/2003	Huter et al.	7,905,896 B2	3/2011	Straub
6,589,263 B1	7/2003	Hopkins et al.	7,938,809 B2	5/2011	Lampropoulos et al.
6,596,011 B2	7/2003	Johnson et al.	7,938,820 B2	5/2011	Webster et al.
6,602,271 B2	8/2003	Adams et al.	7,967,790 B2	6/2011	Whiting et al.
6,605,074 B2	8/2003	Zadno-azizi et al.	7,976,511 B2	7/2011	Fotjik
6,605,102 B1	8/2003	Mazzocchi et al.	7,993,302 B2	8/2011	Hebert et al.
6,610,077 B1	8/2003	Hancock et al.	7,993,363 B2	8/2011	Demond et al.
6,620,148 B1	9/2003	Tsugita	8,021,351 B2	9/2011	Boldenow et al.
6,620,179 B2	9/2003	Brook et al.	8,043,313 B2	10/2011	Krolik et al.
6,620,182 B1	9/2003	Khosravi et al.	8,052,640 B2	11/2011	Fiorella et al.
6,623,460 B1	9/2003	Heck	8,057,496 B2	11/2011	Fischer, Jr.
6,635,068 B1	10/2003	Dubrul et al.	8,057,497 B1	11/2011	Raju et al.
6,645,222 B1	11/2003	Parodi et al.	8,066,757 B2	11/2011	Ferrera et al.
6,660,013 B2	12/2003	Rabiner et al.	8,070,694 B2	12/2011	Galdonik et al.
6,660,014 B2	12/2003	Demarais et al.	8,070,769 B2	12/2011	Broome
6,663,650 B2	12/2003	Sepetka et al.	8,070,791 B2	12/2011	Ferrera et al.
6,692,504 B2	2/2004	Kurz et al.	8,075,510 B2	12/2011	Aklog et al.
6,699,260 B2	3/2004	Dubrul et al.	8,080,032 B2	12/2011	van der Burg et al.
6,702,830 B1	3/2004	Demarais et al.	8,088,140 B2	1/2012	Ferrera et al.
6,719,717 B1	4/2004	Johnson et al.	8,092,486 B2	1/2012	Berrada et al.
6,755,847 B2	6/2004	Eskuri	8,100,935 B2	1/2012	Rosenbluth et al.
6,767,353 B1	7/2004	Shiber	8,109,962 B2	2/2012	Pal
6,790,204 B2	9/2004	Zadno-Azizi et al.	8,118,829 B2	2/2012	Carrison et al.
6,800,080 B1	10/2004	Bates	8,197,493 B2	6/2012	Ferrera et al.
6,818,006 B2	11/2004	Douk et al.	8,246,641 B2	8/2012	Osborne et al.
6,824,545 B2	11/2004	Sepetka et al.	8,261,648 B1	9/2012	Marchand et al.
6,824,550 B1	11/2004	Noriega et al.	8,267,897 B2	9/2012	Wells
6,824,553 B1	11/2004	Gene et al.	8,298,257 B2	10/2012	Sepetka et al.
6,830,561 B2	12/2004	Jansen et al.	8,317,748 B2	11/2012	Fiorella et al.
6,846,029 B1	1/2005	Ragner et al.	8,337,450 B2	12/2012	Fotjik
6,902,540 B2	6/2005	Dorros et al.	RE43,902 E	1/2013	Hopkins et al.
6,939,361 B1	9/2005	Kleshinski	8,343,167 B2	1/2013	Henson
6,942,682 B2	9/2005	Vrba et al.	8,357,178 B2	1/2013	Grandfield et al.
6,945,977 B2	9/2005	Demarais et al.	8,361,104 B2	1/2013	Jones et al.
6,960,189 B2	11/2005	Bates et al.	8,409,215 B2	4/2013	Sepetka et al.
6,960,222 B2	11/2005	Vo et al.	8,480,708 B2	7/2013	Kassab et al.
7,004,931 B2	2/2006	Hogendijk	8,486,105 B2	7/2013	Demond et al.
7,004,954 B1	2/2006	Voss et al.	8,491,539 B2	7/2013	Fotjik
7,036,707 B2	5/2006	Aota et al.	8,512,352 B2	8/2013	Martin
7,041,084 B2	5/2006	Fotjik	8,523,897 B2	9/2013	van der Burg et al.
7,052,500 B2	5/2006	Bashiri et al.	8,535,283 B2	9/2013	Heaton et al.
7,056,328 B2	6/2006	Arnott	8,535,334 B2	9/2013	Martin
7,063,707 B2	6/2006	Bose et al.	8,535,343 B2	9/2013	van der Burg et al.
7,069,835 B2	7/2006	Nishri et al.	8,545,526 B2	10/2013	Martin et al.
7,094,249 B1	8/2006	Thomas et al.	8,568,432 B2	10/2013	Straub
7,122,034 B2	10/2006	Belhe et al.	8,568,465 B2	10/2013	Freudenthal et al.
7,128,073 B1	10/2006	van der Burg et al.	8,574,262 B2	11/2013	Ferrera et al.
7,152,605 B2	12/2006	Khairkhahan et al.	8,579,915 B2	11/2013	French et al.
7,179,273 B1	2/2007	Palmer et al.	8,585,713 B2	11/2013	Ferrera et al.
7,223,253 B2	5/2007	Hogendijk	8,608,754 B2	12/2013	Wensel et al.
7,232,432 B2	6/2007	Fulton, III et al.	8,647,367 B2	2/2014	Kassab et al.
7,244,243 B2	7/2007	Lary	8,657,867 B2	2/2014	Dorn et al.
7,285,126 B2	10/2007	Sepetka et al.	8,696,622 B2	4/2014	Fiorella et al.
7,300,458 B2	11/2007	Henkes et al.	8,715,314 B1	5/2014	Janardhan et al.
7,306,618 B2	12/2007	Demond et al.	8,721,714 B2	5/2014	Kelley
7,320,698 B2	1/2008	Eskuri	8,753,322 B2	6/2014	Hu et al.
7,323,002 B2	1/2008	Johnson et al.	8,771,289 B2	7/2014	Mohiuddin et al.
			8,777,893 B2	7/2014	Malewicz
			8,784,441 B2	7/2014	Rosenbluth et al.
			8,784,442 B2	7/2014	Jones et al.
			8,784,469 B2	7/2014	Kassab

(56)

References Cited

U.S. PATENT DOCUMENTS

8,795,305 B2	8/2014	Martin et al.	10,058,339 B2	8/2018	Galdonik et al.
8,795,345 B2	8/2014	Grandfield et al.	10,098,651 B2	10/2018	Marchand et al.
8,801,748 B2	8/2014	Martin	10,130,385 B2	11/2018	Farhangnia et al.
8,808,259 B2	8/2014	Walton et al.	10,183,159 B2*	1/2019	Nobles A61M 39/22
8,814,927 B2	8/2014	Shin et al.	10,226,263 B2	3/2019	Look et al.
8,820,207 B2	9/2014	Marchand et al.	10,238,406 B2	3/2019	Cox et al.
8,826,791 B2	9/2014	Thompson et al.	10,271,864 B2	4/2019	Greenhalgh et al.
8,828,044 B2	9/2014	Aggerholm et al.	10,327,883 B2	6/2019	Yachia
8,833,224 B2	9/2014	Thompson et al.	10,335,186 B2	7/2019	Rosenbluth et al.
8,834,519 B2	9/2014	van der Burg et al.	10,342,571 B2	7/2019	Marchand et al.
8,845,621 B2	9/2014	Fotjik	10,349,960 B2	7/2019	Quick
8,852,226 B2	10/2014	Gilson et al.	10,383,644 B2	8/2019	Molaei et al.
8,939,991 B2	1/2015	Krolik et al.	10,384,034 B2	8/2019	Carrison et al.
8,945,143 B2	2/2015	Ferrera et al.	10,456,555 B2	10/2019	Carrison et al.
8,945,172 B2	2/2015	Ferrera et al.	10,478,535 B2	11/2019	Ogle
8,956,384 B2	2/2015	Berrada et al.	10,485,952 B2	11/2019	Carrison et al.
8,992,504 B2	3/2015	Castella et al.	10,524,811 B2	1/2020	Marchand et al.
9,005,172 B2	4/2015	Chung	10,531,883 B1	1/2020	Deville et al.
9,011,551 B2	4/2015	Oral et al.	10,588,655 B2	3/2020	Rosenbluth et al.
9,028,401 B1	5/2015	Bacich et al.	10,648,268 B2	5/2020	Jaffrey et al.
9,078,682 B2	7/2015	Lenker et al.	10,695,159 B2	6/2020	Hauser
9,101,382 B2	8/2015	Krolik et al.	10,709,471 B2	7/2020	Rosenbluth et al.
9,125,683 B2	9/2015	Farhangnia et al.	10,772,636 B2	9/2020	Kassab et al.
9,126,016 B2	9/2015	Fulton	10,799,331 B2	10/2020	Hauser
9,149,609 B2	10/2015	Ansel et al.	10,912,577 B2	2/2021	Marchand et al.
9,155,552 B2	10/2015	Ulm, III	10,926,060 B2	2/2021	Stern et al.
9,161,766 B2	10/2015	Slee et al.	10,953,195 B2	3/2021	Jalgaonkar et al.
9,168,043 B2	10/2015	van der Burg et al.	10,960,114 B2	3/2021	Goisis
9,173,668 B2	11/2015	Ulm, III	11,000,682 B2	5/2021	Merritt et al.
9,186,487 B2	11/2015	Dubrul et al.	11,013,523 B2	5/2021	Arad Hadar
9,204,887 B2	12/2015	Cully et al.	11,058,445 B2	7/2021	Cox et al.
9,216,277 B2	12/2015	Myers	11,058,451 B2	7/2021	Marchand et al.
9,241,669 B2	1/2016	Pugh et al.	11,065,019 B1	7/2021	Chou et al.
9,358,037 B2	1/2016	Farhangnia et al.	11,147,571 B2	10/2021	Cox et al.
9,259,237 B2	2/2016	Quick et al.	11,154,314 B2	10/2021	Quick
9,265,512 B2	2/2016	Carrison et al.	11,166,703 B2	11/2021	Kassab et al.
9,283,066 B2	3/2016	Hopkins et al.	11,185,664 B2	11/2021	Carrison et al.
9,301,769 B2	4/2016	Brady et al.	11,224,450 B2	1/2022	Chou et al.
9,351,747 B2	5/2016	Kugler et al.	11,224,721 B2	1/2022	Carrison et al.
9,439,664 B2	9/2016	Sos	11,259,821 B2	3/2022	Buck et al.
9,439,751 B2	9/2016	White et al.	11,305,094 B2	4/2022	Carrison et al.
9,456,834 B2	10/2016	Folk	11,383,064 B2	7/2022	Carrison et al.
9,463,035 B1	10/2016	Greenhalgh et al.	11,395,903 B2	7/2022	Carrison et al.
9,463,036 B2	10/2016	Brady et al.	11,433,218 B2	9/2022	Quick et al.
9,526,864 B2	12/2016	Quick	11,439,799 B2	9/2022	Buck et al.
9,526,865 B2	12/2016	Quick	11,457,936 B2	10/2022	Buck et al.
9,532,792 B2	1/2017	Galdonik et al.	11,529,158 B2	12/2022	Hauser
9,566,073 B2	2/2017	Kassab et al.	11,554,005 B2	1/2023	Merritt et al.
9,566,424 B2	2/2017	Pessin	11,559,382 B2	1/2023	Merritt et al.
9,579,116 B1	2/2017	Nguyen et al.	11,576,691 B2	2/2023	Chou et al.
9,581,942 B1	2/2017	Shippert	11,596,768 B2	3/2023	Stern et al.
9,616,213 B2	4/2017	Furnish et al.	11,642,209 B2	5/2023	Merritt et al.
9,636,206 B2	5/2017	Nguyen et al.	11,648,028 B2	5/2023	Rosenbluth et al.
9,643,035 B2	5/2017	Mastenbroek	11,697,011 B2	7/2023	Merritt et al.
9,662,129 B2	5/2017	Galdonik et al.	11,697,012 B2	7/2023	Merritt et al.
9,700,332 B2	7/2017	Marchand et al.	11,744,691 B2	9/2023	Merritt et al.
9,717,488 B2	8/2017	Kassab et al.	11,806,033 B2	11/2023	Marchand et al.
9,717,514 B2	8/2017	Martin et al.	2001/0004699 A1	6/2001	Gittings et al.
9,717,519 B2	8/2017	Rosenbluth et al.	2001/0031981 A1	10/2001	Evans et al.
9,744,024 B2	8/2017	Nguyen et al.	2001/0041909 A1	11/2001	Tsugita et al.
9,757,137 B2	9/2017	Krolik et al.	2001/0049486 A1	12/2001	Evans et al.
9,827,084 B2	11/2017	Bonnette et al.	2001/0051810 A1	12/2001	Dubrul et al.
9,844,386 B2	12/2017	Nguyen et al.	2002/0022858 A1	2/2002	Demond et al.
9,844,387 B2	12/2017	Marchand et al.	2002/0022859 A1	2/2002	Hogendijk
9,848,975 B2	12/2017	Hauser	2002/0026211 A1	2/2002	Khosravi et al.
9,849,014 B2	12/2017	Kusleika	2002/0032455 A1	3/2002	Book et al.
9,884,387 B2	2/2018	Plha	2002/0049452 A1	4/2002	Kurz et al.
9,962,178 B2	5/2018	Greenhalgh et al.	2002/0095161 A1	7/2002	Dhindsa
9,980,813 B2*	5/2018	Eller F16K 7/06	2002/0095171 A1	7/2002	Belef
9,999,493 B2	6/2018	Nguyen et al.	2002/0111648 A1	8/2002	Kusleika et al.
10,004,531 B2	6/2018	Rosenbluth et al.	2002/0120277 A1	8/2002	Hauschild et al.
10,010,335 B2	7/2018	Greenhalgh et al.	2002/0147458 A1	10/2002	Hiblar et al.
10,016,266 B2	7/2018	Hauser	2002/0151918 A1	10/2002	Lafontaine et al.
10,028,759 B2	7/2018	Wallace et al.	2002/0156457 A1	10/2002	Fisher
10,045,790 B2	8/2018	Cox et al.	2002/0161392 A1	10/2002	Dubrul
			2002/0169474 A1	11/2002	Kusleika
			2002/0173819 A1	11/2002	Leeflang et al.
			2002/0188276 A1	12/2002	Evans et al.
			2003/0023263 A1	1/2003	Krolik et al.

(56)		References Cited					
		U.S. PATENT DOCUMENTS					
2003/0083693	A1	5/2003	Daniel et al.	2007/0179513	A1	8/2007	Deutsch
2003/0100919	A1	5/2003	Hopkins et al.	2007/0191866	A1	8/2007	Palmer et al.
2003/0114875	A1	6/2003	Sjostrom	2007/0198028	A1	8/2007	Miloslavski et al.
2003/0116731	A1	6/2003	Hartley	2007/0208361	A1	9/2007	Okushi et al.
2003/0125663	A1*	7/2003	Coleman	2007/0208367	A1	9/2007	Fiorella et al.
			A61M 25/0136	2007/0213753	A1	9/2007	Waller
			604/95.04	2007/0213765	A1	9/2007	Adams et al.
2003/0135151	A1	7/2003	Deng	2007/0233043	A1	10/2007	Dayton et al.
2003/0135230	A1	7/2003	Massey et al.	2007/0255252	A1	11/2007	Mehta
2003/0135258	A1	7/2003	Andreas et al.	2007/0288054	A1	12/2007	Tanaka et al.
2003/0153873	A1	8/2003	Luther et al.	2008/0015541	A1	1/2008	Rosenbluth et al.
2003/0153973	A1	8/2003	Soun et al.	2008/0087853	A1	4/2008	Kees
2003/0168068	A1	9/2003	Poole et al.	2008/0088055	A1	4/2008	Ross
2003/0176884	A1	9/2003	Berrada et al.	2008/0157017	A1	7/2008	Macatangay et al.
2003/0191516	A1	10/2003	Weldon et al.	2008/0167678	A1	7/2008	Morsi
2003/0208224	A1	11/2003	Broome	2008/0183136	A1	7/2008	Lenker et al.
2003/0216774	A1	11/2003	Larson	2008/0228209	A1	9/2008	DeMello et al.
2004/0019310	A1	1/2004	Hogendijk	2008/0234715	A1	9/2008	Pesce et al.
2004/0039351	A1	2/2004	Barrett	2008/0234722	A1	9/2008	Bonnette et al.
2004/0039412	A1	2/2004	Isshiki et al.	2008/0262528	A1	10/2008	Martin
2004/0068288	A1	4/2004	Palmer et al.	2008/0269798	A1	10/2008	Ramzipoor et al.
2004/0073243	A1	4/2004	Sepetka et al.	2008/0300466	A1	12/2008	Gresham
2004/0098033	A1	5/2004	Leefflang et al.	2008/0312681	A1	12/2008	Ansel et al.
2004/0102807	A1	5/2004	Kusleika et al.	2009/0018566	A1	1/2009	Escudero et al.
2004/0122359	A1	6/2004	Wenz et al.	2009/0054918	A1	2/2009	Henson
2004/0127936	A1	7/2004	Salahieh et al.	2009/0062841	A1	3/2009	Amplatz et al.
2004/0133232	A1	7/2004	Rosenbluth et al.	2009/0069828	A1	3/2009	Martin et al.
2004/0138525	A1	7/2004	Saadat et al.	2009/0076417	A1	3/2009	Jones
2004/0138692	A1	7/2004	Phung et al.	2009/0160112	A1	6/2009	Ostrovsky
2004/0167567	A1	8/2004	Cano et al.	2009/0163846	A1	6/2009	Aklog et al.
2004/0199201	A1	10/2004	Kellett et al.	2009/0182362	A1	7/2009	Thompson et al.
2004/0199202	A1	10/2004	Dubrul et al.	2009/0192495	A1	7/2009	Ostrovsky et al.
2004/0260344	A1	12/2004	Lyons et al.	2009/0281525	A1	11/2009	Harding et al.
2004/0267272	A1	12/2004	Henniges et al.	2009/0292307	A1	11/2009	Razack
2005/0004534	A1	1/2005	Lockwood et al.	2009/0299393	A1	12/2009	Martin et al.
2005/0033172	A1	2/2005	Dubrul et al.	2010/0016837	A1	1/2010	Howat
2005/0038468	A1	2/2005	Panetta et al.	2010/0030256	A1	2/2010	Dubrul et al.
2005/0054995	A1	3/2005	Barzell et al.	2010/0042136	A1	2/2010	Berrada et al.
2005/0055047	A1	3/2005	Greenhalgh	2010/0087844	A1	4/2010	Fischer, Jr.
2005/0085769	A1	4/2005	MacMahon et al.	2010/0087850	A1	4/2010	Razack
2005/0085826	A1	4/2005	Nair et al.	2010/0094201	A1	4/2010	Mallaby
2005/0085846	A1	4/2005	Carrison et al.	2010/0106081	A1	4/2010	Brandeis
2005/0085849	A1	4/2005	Sepetka et al.	2010/0114017	A1	5/2010	Lenker et al.
2005/0119668	A1	6/2005	Teague et al.	2010/0114113	A1	5/2010	Dubrul et al.
2005/0177132	A1	8/2005	Lentz et al.	2010/0121312	A1	5/2010	Gielenz et al.
2005/0187570	A1	8/2005	Nguyen et al.	2010/0137846	A1	6/2010	Desai et al.
2005/0203605	A1	9/2005	Dolan	2010/0190156	A1	7/2010	Van Wordragen et al.
2005/0283165	A1	12/2005	Gadberry	2010/0204712	A1	8/2010	Mallaby
2005/0283166	A1	12/2005	Greenhalgh et al.	2010/0217276	A1	8/2010	Garrison et al.
2005/0283186	A1	12/2005	Berrada et al.	2010/0249815	A1	9/2010	Jantzen et al.
2006/0020286	A1	1/2006	Niermann	2010/0268264	A1	10/2010	Bonnette et al.
2006/0042786	A1	3/2006	West	2010/0318178	A1	12/2010	Rapaport et al.
2006/0047286	A1	3/2006	West	2011/0034986	A1	2/2011	Chou et al.
2006/0074401	A1	4/2006	Ross	2011/0034987	A1	2/2011	Kennedy
2006/0089533	A1	4/2006	Ziegler et al.	2011/0054405	A1	3/2011	Whiting et al.
2006/0100662	A1	5/2006	Daniel et al.	2011/0060212	A1	3/2011	Slee et al.
2006/0155305	A1	7/2006	Freudenthal et al.	2011/0071503	A1	3/2011	Takagi et al.
2006/0173525	A1	8/2006	Behl et al.	2011/0118817	A1	5/2011	Gunderson et al.
2006/0195137	A1	8/2006	Sepetka et al.	2011/0125181	A1	5/2011	Brady et al.
2006/0200221	A1	9/2006	Malewicz	2011/0144592	A1*	6/2011	Wong
2006/0217664	A1	9/2006	Hattler et al.				A61M 39/0613
2006/0224177	A1	10/2006	Finitis	2011/0152823	A1	6/2011	Mohiuddin et al.
2006/0229645	A1	10/2006	Bonnette et al.	2011/0152889	A1	6/2011	Ashland
2006/0247500	A1	11/2006	Voegele et al.	2011/0152993	A1	6/2011	Marchand et al.
2006/0253145	A1	11/2006	Lucas	2011/0160742	A1	6/2011	Ferrera et al.
2006/0264905	A1	11/2006	Eskridge et al.	2011/0160763	A1	6/2011	Ferrera et al.
2006/0276874	A1	12/2006	Wilson et al.	2011/0190806	A1	8/2011	Wittens
2006/0282111	A1	12/2006	Morsi	2011/0196309	A1	8/2011	Wells
2006/0293696	A1	12/2006	Fahey et al.	2011/0196414	A1	8/2011	Porter et al.
2007/0010787	A1	1/2007	Hackett et al.	2011/0213290	A1	9/2011	Chin et al.
2007/0038225	A1	2/2007	Osborne	2011/0213403	A1	9/2011	Aboytes
2007/0093744	A1	4/2007	Elmaleh	2011/0224707	A1	9/2011	Miloslavski et al.
2007/0112374	A1	5/2007	Paul, Jr. et al.	2011/0245807	A1	10/2011	Sakata et al.
2007/0118165	A1	5/2007	DeMello et al.	2011/0251629	A1	10/2011	Galdonik et al.
2007/0149996	A1	6/2007	Coughlin	2011/0264133	A1	10/2011	Hanlon et al.
2007/0161963	A1	7/2007	Smalling	2011/0265681	A1	11/2011	Allen et al.
				2011/0288529	A1	11/2011	Fulton
				2011/0288572	A1	11/2011	Martin
				2011/0319917	A1	12/2011	Ferrera et al.

(56)	References Cited							
	U.S. PATENT DOCUMENTS							
2012/0059309	A1	3/2012	di Palma et al.	2015/0005792	A1	1/2015	Ahn	
2012/0059356	A1	3/2012	di Palma et al.	2015/0018859	A1	1/2015	Quick	
2012/0083824	A1	4/2012	Berrada et al.	2015/0018860	A1	1/2015	Quick	
2012/0083868	A1	4/2012	Shrivastava	2015/0018929	A1	1/2015	Martin et al.	
2012/0089216	A1	4/2012	Rapaport et al.	2015/0025555	A1	1/2015	Sos	
2012/0101480	A1	4/2012	Ingle et al.	2015/0032144	A1	1/2015	Holloway	
2012/0101510	A1	4/2012	Lenker et al.	2015/0059908	A1	3/2015	Mollen	
2012/0109109	A1	5/2012	Kajii	2015/0088190	A1	3/2015	Jensen	
2012/0138832	A1	6/2012	Townsend	2015/0127035	A1	5/2015	Trapp et al.	
2012/0143239	A1	6/2012	Aklog et al.	2015/0133990	A1	5/2015	Davidson	
2012/0165919	A1	6/2012	Cox et al.	2015/0150672	A1	6/2015	Ma	
2012/0172918	A1	7/2012	Fifer et al.	2015/0164523	A1	6/2015	Brady et al.	
2012/0179181	A1	7/2012	Straub et al.	2015/0164666	A1	6/2015	Johnson et al.	
2012/0197277	A1	8/2012	Stinis	2015/0173782	A1	6/2015	Garrison et al.	
2012/0232655	A1	9/2012	Lorrison et al.	2015/0190155	A1	7/2015	Ulm, III	
2012/0271105	A1	10/2012	Nakamura et al.	2015/0190156	A1	7/2015	Ulm, III	
2012/0271231	A1	10/2012	Agrawal	2015/0196380	A1	7/2015	Berrada et al.	
2012/0277788	A1	11/2012	Cattaneo	2015/0196744	A1	7/2015	Aboytes	
2012/0310166	A1	12/2012	Huff	2015/0209058	A1	7/2015	Ferrera et al.	
2013/0030460	A1	1/2013	Marks et al.	2015/0209165	A1	7/2015	Grandfield et al.	
2013/0035628	A1	2/2013	Garrison et al.	2015/0238207	A1	8/2015	Cox et al.	
2013/0046332	A1	2/2013	Jones et al.	2015/0250578	A1	9/2015	Cook et al.	
2013/0066348	A1	3/2013	Fiorella et al.	2015/0265299	A1	9/2015	Cooper et al.	
2013/0092012	A1	4/2013	Marchand et al.	2015/0305756	A1	10/2015	Rosenbluth	
2013/0096571	A1	4/2013	Massicotte et al.	2015/0305859	A1*	10/2015	Eller	A61F 2/2469 623/1.24
2013/0102996	A1	4/2013	Strauss	2015/0352325	A1	12/2015	Quick	
2013/0116708	A1	5/2013	Ziniti et al.	2015/0360001	A1	12/2015	Quick	
2013/0116721	A1	5/2013	Takagi et al.	2015/0374391	A1	12/2015	Quick	
2013/0126559	A1	5/2013	Cowan et al.	2016/0022293	A1	1/2016	Dubrul et al.	
2013/0144326	A1	6/2013	Brady et al.	2016/0030708	A1	2/2016	Casiello et al.	
2013/0150793	A1	6/2013	Beissel et al.	2016/0038267	A1	2/2016	Allen et al.	
2013/0165871	A1	6/2013	Fiorella et al.	2016/0058540	A1	3/2016	Don Michael	
2013/0184703	A1	7/2013	Shireman et al.	2016/0074627	A1	3/2016	Cottone	
2013/0197454	A1	8/2013	Shibata et al.	2016/0106353	A1	4/2016	Schuetz et al.	
2013/0197567	A1	8/2013	Brady et al.	2016/0106448	A1	4/2016	Brady et al.	
2013/0204297	A1	8/2013	Melsheimer et al.	2016/0106449	A1	4/2016	Brady et al.	
2013/0226196	A1	8/2013	Smith	2016/0113663	A1	4/2016	Brady et al.	
2013/0281788	A1	10/2013	Garrison	2016/0113664	A1	4/2016	Brady et al.	
2013/0289608	A1	10/2013	Tanaka et al.	2016/0113665	A1	4/2016	Brady et al.	
2013/0317589	A1	11/2013	Martin et al.	2016/0113666	A1	4/2016	Quick	
2013/0345739	A1	12/2013	Brady et al.	2016/0135829	A1	5/2016	Holochwost et al.	
2014/0005712	A1	1/2014	Martin	2016/0143721	A1	5/2016	Rosenbluth	
2014/0005713	A1	1/2014	Bowman	2016/0151605	A1	6/2016	Welch et al.	
2014/0005715	A1	1/2014	Castella et al.	2016/0192912	A1	7/2016	Kassab et al.	
2014/0005717	A1	1/2014	Martin et al.	2016/0206344	A1	7/2016	Bruzzi et al.	
2014/0025048	A1	1/2014	Ward	2016/0008014	A1	8/2016	Rosenbluth	
2014/0031856	A1	1/2014	Martin	2016/0220741	A1	8/2016	Garrison et al.	
2014/0046133	A1	2/2014	Nakamura et al.	2016/0228134	A1	8/2016	Martin et al.	
2014/0046243	A1	2/2014	Ray et al.	2016/0262774	A1	9/2016	Honda	
2014/0052161	A1	2/2014	Cully et al.	2016/0262790	A1	9/2016	Rosenbluth et al.	
2014/0074144	A1	3/2014	Shrivastava et al.	2016/0287276	A1	10/2016	Cox et al.	
2014/0121672	A1	5/2014	Folk	2016/0367285	A1	12/2016	Sos	
2014/0155830	A1	6/2014	Bonnette et al.	2017/0014560	A1	1/2017	Minskoff et al.	
2014/0155980	A1	6/2014	Turjman	2017/0021130	A1	1/2017	Dye	
2014/0180055	A1	6/2014	Glynn et al.	2017/0037548	A1	2/2017	Lee	
2014/0180397	A1	6/2014	Gerberding et al.	2017/0042571	A1	2/2017	Levi	
2014/0155908	A1	7/2014	Rosenbluth et al.	2017/0049942	A1	2/2017	Conlan et al.	
2014/0188127	A1	7/2014	Dubrul et al.	2017/0056032	A1	3/2017	Look et al.	
2014/0188143	A1	7/2014	Martin et al.	2017/0058623	A1	3/2017	Jaffrey et al.	
2014/0222070	A1	8/2014	Belson et al.	2017/0079672	A1	3/2017	Quick	
2014/0236219	A1	8/2014	Dubrul et al.	2017/0086864	A1	3/2017	Greenhalgh et al.	
2014/0243882	A1	8/2014	Ma	2017/0100142	A1	4/2017	Look et al.	
2014/0257253	A1	9/2014	Jemison	2017/0105743	A1	4/2017	Vale et al.	
2014/0257363	A1	9/2014	Lippert	2017/0105745	A1	4/2017	Rosenbluth et al.	
2014/0276403	A1	9/2014	Follmer et al.	2017/0112514	A1	4/2017	Marchand et al.	
2014/0296868	A1	10/2014	Garrison et al.	2017/0143359	A1	5/2017	Nguyen et al.	
2014/0303658	A1	10/2014	Bonnette et al.	2017/0143938	A1	5/2017	Ogle et al.	
2014/0318354	A1	10/2014	Thompson et al.	2017/0112513	A1	7/2017	Marchand et al.	
2014/0324091	A1	10/2014	Rosenbluth	2017/0189041	A1	7/2017	Cox et al.	
2014/0330286	A1	11/2014	Wallace et al.	2017/0196576	A1	7/2017	Long et al.	
2014/0336691	A1	11/2014	Jones et al.	2017/0233908	A1	8/2017	Kroczyński et al.	
2014/0343593	A1	11/2014	Chin et al.	2017/0252057	A1	9/2017	Bonnette et al.	
2014/0364896	A1	12/2014	Consigny	2017/0265878	A1	9/2017	Marchand et al.	
2014/0371779	A1	12/2014	Vale et al.	2017/0281204	A1	10/2017	Garrison et al.	
2015/0005781	A1	1/2015	Lund-Clausen et al.	2017/0303939	A1	10/2017	Greenhalgh et al.	
				2017/0303942	A1	10/2017	Greenhalgh et al.	
				2017/0303947	A1	10/2017	Greenhalgh et al.	
				2017/0303948	A1	10/2017	Wallace et al.	

(56)

References Cited

FOREIGN PATENT DOCUMENTS

WO	WO2009086482	7/2009
WO	WO2009155571	12/2009
WO	WO2010002549	1/2010
WO	WO2010010545	1/2010
WO	WO2010023671	3/2010
WO	WO2010049121	5/2010
WO	WO2010102307	9/2010
WO	WO2011032712	3/2011
WO	WO2011054531	5/2011
WO	WO2011073176	6/2011
WO	WO2012009675	1/2012
WO	WO2012011097	1/2012
WO	WO2012049652	4/2012
WO	WO2012065748	5/2012
WO	WO2012120490	9/2012
WO	WO2012126237	11/2012
WO	WO2014047650	3/2014
WO	WO2014081892	5/2014
WO	WO2015006782	1/2015
WO	WO2015061365	4/2015
WO	WO2015121424	8/2015
WO	WO2015179329	11/2015
WO	WO2015189354	12/2015
WO	WO2015191646	12/2015
WO	WO2016014955	1/2016
WO	WO2017024258	2/2017
WO	WO2017058280	4/2017
WO	WO2017070702	4/2017
WO	WO2017106877	6/2017
WO	WO2017189535	11/2017
WO	WO2017189550	11/2017
WO	WO2017189591	11/2017
WO	WO2017189615	11/2017
WO	WO2017210487	12/2017
WO	WO2018049317	3/2018
WO	WO2018065092	4/2018
WO	WO2018080590	5/2018
WO	WO2018148174	8/2018
WO	WO2019010318	1/2019
WO	WO2019050765	3/2019
WO	WO2019075444	4/2019
WO	WO2019094456	5/2019
WO	WO2019173475	9/2019
WO	WO2019222117	11/2019
WO	WO2019246240	12/2019
WO	WO2020036809	2/2020
WO	WO2021067134	4/2021
WO	WO2021076954	4/2021
WO	WO2021127202	6/2021
WO	WO2021248042	12/2021
WO	WO2022032173	2/2022
WO	WO2022103848	5/2022
WO	WO2022109021	5/2022
WO	WO2022109034	5/2022
WO	WO2023137341	7/2023
WO	WO2023147353	8/2023
WO	WO2023154612	8/2023
WO	WO2023192925	10/2023

OTHER PUBLICATIONS

Gibbs, et al., "Temporary Stent as a bail-out device during percutaneous transluminal coronary angioplasty: preliminary clinical experience," *British Heart Journal*, 1994, 71:372-377, Oct. 12, 1993 6 pgs.

Gupta, S. et al., "Acute Pulmonary Embolism Advances in Treatment", JAPI, Association of Physicians India, Mar. 2008, vol. 56, 185-191.

International Search Report and Written Opinion for International App. No. PCT/US13/61470, dated Jan. 17, 2014, 7 pages.

International Search Report and Written Opinion for International App. No. PCT/US2014/046567, dated Nov. 3, 2014, 13 pages.

International Search Report and Written Opinion for International App. No. PCT/US2014/061645, dated Jan. 23, 2015, 15 pages.

International Search Report for International App. No. PCT/US13/71101, dated Mar. 31, 2014, 4 pages.

Konstantinides, S. et al., "Pulmonary embolism hotline 2012—Recent and expected trials", *Thrombosis and Haemostasis*, Jan. 9, 2013:33; 43-50.

Konstantinides, S. et al., "Pulmonary embolism: risk assessment and management", *European Society of Cardiology; European Heart Journal*, Sep. 7, 2012:33, 3014-3022.

Kucher, N. et al., "Percutaneous Catheter Thrombectomy Device for Acute Pulmonary Embolism: In Vitro and in Vivo Testing", *Circulation*, Sep. 2005:112:e28-e32.

Kucher, N., "Catheter Interventions in Massive Pulmonary Embolism", *Cardiology Rounds*, Mar. 2006 vol. 10, Issue 3, 6 pages.

Kucher, N. et al., "Management of Massive Pulmonary Embolism", *Radiology*, Sep. 2005:236:3 852-858.

Kucher, N. et al., "Randomized, Controlled Trial of Ultrasound-Assisted Catheter-Directed Thrombolysis for Acute Intermediate-Risk Pulmonary Embolism." *Circulation*, 2014, 129, pp. 9 pages.

Kuo, W. et al., "Catheter-directed Therapy for the Treatment of Massive Pulmonary Embolism: Systematic Review and Meta-analysis of Modern Techniques", *Journal of Vascular and Interventional Radiology*, Nov. 2009:20:1431-1440.

Kuo, W. et al., "Catheter-Directed Embolectomy, Fragmentation, and Thrombolysis for the Treatment of Massive Pulmonary Embolism After Failure of Systemic Thrombolysis", *American College of CHEST Physicians* 2008: 134:250-254.

Kuo, W. MD, "Endovascular Therapy for Acute Pulmonary Embolism", *Continuing Medical Education Society of Interventional Radiology ("CME")*; *Journal of Vascular and Interventional Radiology*, Feb. 2012: 23:167-179.

Lee, L. et al., "Massive pulmonary embolism: review of management strategies with a focus on catheter-based techniques", *Expert Rev. Cardiovasc. Ther.* 8(6), 863-873 (2010).

Liu, S. et al., "Massive Pulmonary Embolism: Treatment with the Rotarex Thrombectomy System", *Cardiovascular Interventional Radiology*; 2011: 34:106-113.

Muller-Hulsbeck, S. et al. "Mechanical Thrombectomy of Major and Massive Pulmonary Embolism with Use of the Amplatz Thrombectomy Device", *Investigative Radiology*, Jun. 2001:36:6:317-322.

Reekers, J. et al., "Mechanical Thrombectomy for Early Treatment of Massive Pulmonary Embolism", *Cardiovascular and Interventional Radiology*, 2003: 26:246-250.

Schmitz-Rode et al., "New Mesh Basket for Percutaneous Removal of Wall-Adherent Thrombi in Dialysis Shunts," *Cardiovasc Intervent Radiol* 16:7-10 1993 4 pgs.

Schmitz-Rode et al., "Temporary Pulmonary Stent Placement as Emergency Treatment of Pulmonary Embolism," *Journal of the American College of Cardiology*, vol. 48, No. 4, 2006 (5 pgs.).

Schmitz-Rode, T. et al., "Massive Pulmonary Embolism: Percutaneous Emergency Treatment by Pigtail Rotation Catheter", *JACC Journal of the American College of Cardiology*, Aug. 2000:36:2:375-380.

Spiotta, A et al., "Evolution of thrombectomy approaches and devices for acute stroke: a technical review." *J NeuroIntervent Surg* 2015, 7, pp. 7 pages.

Svilaaas, T. et al., "Thrombus Aspiration During Primary Percutaneous Coronary Intervention." *The New England Journal of Medicine*, 2008, vol. 358, No. 6, 11 pages.

Tapson, V., "Acute Pulmonary Embolism", *The New England Journal of Medicine*, Mar. 6, 2008:358:2037-52.

The Penumbra Pivotal Stroke Trial Investigators, "The Penumbra Pivotal Stroke Trial: Safety and Effectiveness of a New Generation of Mechanical Devices for Clot Removal in Intracranial Large Vessel Occlusive Disease." *Stroke*, 2009, 40: p. 9 pages.

Truong et al., "Mechanical Thrombectomy of Iliocaval Thrombosis Using a Protective Expandable Sheath," *Cardiovasc Intervent Radiol* 27:254-258, 2004, 5 pgs.

Turk et al., "ADAPT FAST study: a direct aspiration first pass technique for acute stroke thrombectomy." *J NeuroIntervent Surg*, vol. 6, 2014, 6 pages.

(56)

References Cited

OTHER PUBLICATIONS

Uflacker, R., "Interventional Therapy for Pulmonary Embolism", *Journal of Vascular and Interventional Radiology*, Feb. 2001: 12:147-164.

Verma, R., MD et al. "Evaluation of a Newly Developed Percutaneous Thrombectomy Basket Device in Sheep With Central Pulmonary Embolisms", *Investigative Radiology*, Oct. 2006, 41, 729-734. International Search Report and Written Opinion for International App. No. PCT/US2015/034987 filed Jun. 9, 2015, Applicant: Inceptus Medical, LLC, dated Sep. 17, 2015, 12 pages.

English translation of Japanese Office Action received for JP Application No. 2016-564210, Applicant: Inceptus Medical, LLC, dated Sep. 4, 2017, 4 pages.

Australian Exam Report received for AU Application No. 2015274704, Applicant: Inceptus Medical, LLC, dated Sep. 7, 2017, 3 pages.

European Search Report received for EP Application No. 15805810.7, Applicant: Inceptus Medical, LLC, dated Sep. 4, 2017, 6 pages. International Search Report and Written Opinion for International App. No. PCT/US2016/067628 filed Dec. 19, 2016, Applicant: Inari Medical, Inc., dated Apr. 10, 2017, 11 pages.

Goldhaber, S. et al. "Percutaneous Mechanical Thrombectomy for Acute Pulmonary Embolism—A Double-Edged Sword," *American College of CHEST Physicians*, Aug. 2007, 132:2, 363-372.

Goldhaber, S., "Advanced treatment strategies for acute pulmonary embolism, including thrombolysis and embolectomy," *Journal of Thrombosis and Haemostasis*, 2009: 7 (Suppl. 1): 322-327.

International Search Report and Written Opinion for International App. No. PCT/US2017/029696, Date of Filing: Apr. 26, 2017, Applicant: Inari Medical, Inc., dated Sep. 15, 2017, 19 pages.

International Search Report and Written Opinion for International App. No. PCT/US2016/058536, Date of Filing: Oct. 24, 2016, Applicant: Inari Medical, Inc., dated Mar. 13, 2017, 14 pages.

European First Office Action received for EP Application No. 13838945.7, Applicant: Inari Medical, Inc., dated Oct. 26, 2018, 7 pages.

International Search Report and Written Opinion for International App. No. PCT/US2018/048786, Date of Filing: Aug. 30, 2018, Applicant: Inari Medical, Inc., dated Dec. 13, 2018, 12 pages.

International Search Report and Written Opinion for International App. No. PCT/US2018/055780, Date of Filing: Oct. 13, 2018, Applicant: Inceptus Medical LLC., dated Jan. 22, 2019, 8 pages.

European Search Report for European Application No. 16876941.2, Date of Filing: Dec. 19, 2016, Applicant: Inari Medical, Inc., dated Jul. 18, 2019, 7 pages.

Extended European Search Report for European Application No. 16858462.1, Date of Filing: Oct. 24, 2016, Applicant: Inari Medical, Inc., dated Jun. 3, 2019, 10 pages.

International Search Report and Written Opinion for International App. No. PCT/US2019/045794, Date of Filing: Aug. 8, 2019, Applicant: Inari Medical, Inc., dated Nov. 1, 2019, 17 pages.

Partial Supplementary European Search Report for European Application No. 17864818.4, Date of Filing: May 21, 2019, Applicant: Inari Medical, Inc., dated Apr. 24, 2020, 11 pages.

International Search Report and Written Opinion for International App. No. PCT/US2020/056067, Date of Filing: Oct. 16, 2020; Applicant: Inari Medical, Inc., dated Jan. 22, 2021, 8 pages.

Extended European Search Report for European Application No. 20191581.6, Applicant: Inari Medical, Inc., dated Mar. 31, 2021, 11 pages.

International Search Report and Written Opinion for International App. No. PCT/US2020/055645, Date of Filing: Dec. 17, 2020; Applicant: Inari Medical, Inc., dated Apr. 14, 2021, 12 pages.

Extended European Search Report for European Application No. 18853465.5, Applicant: Inari Medical, Inc., dated May 7, 2021, 2021, 7 pages.

Vorwerk, D. MD, et al., "Use of a Temporary Caval Filter to Assist Percutaneous Iliocaval Thrombectomy: Experimental Results." *SCVIR*, 1995, 4 pages.

PCT International Search Report and Written Opinion for International Appln. No. PCT/US2020/014854, dated Oct. 5, 2020 (13 pages).

PCT International Search Report and Written Opinion for International Appln. No. PCT/US2020/018655, dated Dec. 16, 2020 (22 pages).

PCT International Search Report and Written Opinion for International Appln. No. PCT/US2020/017684, dated Nov. 30, 2020 (19 pages).

Extended European Search Report for EP Patent Appln. No. 20185092.2 dated Sep. 11, 2020, 6 pages.

EP Examination Report for EP Patent Appln. No. 18745794.0 dated Jul. 20, 2020, 4 pages.

Wikipedia; Embolectomy; retrieved from the internet: <https://en.wikipedia.org/wiki/Embolectomy>; 4 pgs.; retrieved/printed: Mar. 24, 2016.

O'Sullivan; Thrombolysis versus thrombectomy in acute deep vein thrombosis; *Interventional Cardiology*; 3(5); pp. 589-596; Oct. 2011.

Capture Vascular Systems; (company website); retrieved <http://www.capturevascular.com>; 3 pgs.; retrieved/printed: Mar. 24, 2016.

Edwards Lifesciences; Fogarty® Occlusion Catheters (product brochure); retrieved from the internet: <http://web.archive.org/web/20150228193218/http://www.edwards.com/products/vascular/atraumaticocclusion/pages/occlusioncatheter.aspx>; © 2011; 2 pgs.; retrieved/printed: Mar. 24, 2011.

Boston Scientific; Fetch(TM) 2 Aspiration Catheter (product information); retrieved from the internet: <http://www.bostonscientific.com/en-us/products/thrombectomy-systems/fetch2-aspiration-catheter.html>; 2 pgs.; retrieved/printed: Mar. 24, 2016.

Penumbra, Inc.; Indigo® System (product information); retrieved from the internet: <http://www.penumbrainc.com/peripheralpercutaneous-thromboembolectomy/indigo-system>; 7 pgs.; retrieved/printed: Mar. 24, 2016.

Youtube; Merci Retrieval System X Series Animation; uploaded Mar. 16, 2009 (product information); posted on May 7, 2009 by SSMDePAUL, time 1:09, retrieved from the internet: <https://www.youtube.com/watch?v=MGX7deuFkhc>; 3 pgs.; retrieved/printed: Mar. 24, 2016.

Covidien; Solitaire(TM) AS Neurovascular Remodeling Device (product information); retrieved from the internet: <http://www.ev3.net/neuro/intl/remodeling-devices/solitaire-ab.htm>; © 2015; 2 pgs.; retrieved/printed: Mar. 24, 2016.

PCT International Search Report and Written Opinion for International Patent Appln. No. PCT/US2019/050467, Applicant Stryker Corporation, dated Dec. 18, 2019 (17 pages).

PCT International Search Report and Written Opinion for International Appln. No. PCT/US2017/029440, Applicant Stryker Corporation, dated Jul. 7, 2017.

PCT International Search Report and Written Opinion for International Appln. No. PCT/US2017/029472, Applicant Stryker Corporation, dated Jul. 7, 2017.

PCT International Search Report and Written Opinion for International Appln. No. PCT/US2017/035543, Applicant Stryker Corporation, dated Aug. 14, 2017.

PCT International Search Report and Written Opinion for International Appln. No. PCT/US2017/029366, Applicant Stryker Corporation, dated Aug. 29, 2017.

PCT International Search Report and Written Opinion for International Appln. No. PCT/US2017/050933, Applicant Stryker Corporation, forms PCT/ISA/210, 220, and 237, dated Nov. 10, 2017 (16 pages).

International search report and written opinion dated Feb. 28, 2018 for PCT/US2017/029345, Applicant Stryker Corporation 26 pages. Extended European Search Report dated Aug. 22, 2018 for European patent appln No. 16852212.6, 6 pages.

Extended European Search Report dated Oct. 5, 2018 for European patent appln No. 18174891.4, 6 pages.

International search report and written opinion dated Nov. 14, 2018 for PCT/US2018/040937, Applicant Stryker Corporation 16 pages. International Search Report and Written Opinion dated Mar. 28, 2019 for International Appln. No. PCT/US2018/059607.

(56)

References Cited

OTHER PUBLICATIONS

International Search Report and Written Opinion dated May 6, 2016 for PCT/US2016/017982.

PCT International Search Report and Written Opinion for International Patent Appln. No. PCT/US2019/032601, Applicant Stryker Corporation, dated Jul. 23, 2019 (12 pages).

Extended European Search Report dated Oct. 8, 2019 for European Patent Application No. 19191925.7.

International Search Report and Written Opinion for International Patent Appln. No. PCT/US2019/050410 dated Oct. 25, 2019.

International Search Report and Written Opinion for International App. No. PCT/US21/35965, Date of Filing: Jun. 4, 2021, Applicant: Inari Medical, Inc., dated Sep. 28, 2021, 12 pages.

International Search Report and Written Opinion for International App. No. PCT/US21/45072 Date of Filing: Aug. 6, 2021, Applicant: Inari Medical, Inc., dated Jan. 20, 2022, 10 pages.

International Search Report and Written Opinion for International App. No. PCT/US21/58793; Date of Filing: Nov. 10, 2021, Applicant: Inari Medical, Inc., dated Mar. 16, 2022, 13 pages.

International Search Report and Written Opinion for International App. No. PCT/US21/59718; Date of Filing: Nov. 17, 2021, Applicant: Inari Medical, Inc., dated Mar. 22, 2022, 13 pages.

International Search Report and Written Opinion for International App. No. PCT/US21/59735; Date of Filing: Nov. 17, 2021, Applicant: Inari Medical, Inc., Date of Mailing: Mar. 22, 2022, 11 pages.

International Search Report and Written Opinion for International App. No. PCT/US23/60502; Date of Filing: Jan. 11, 2023, Applicant: Inari Medical, Inc., dated May 25, 2023, 9 pages.

International Search Report and Written Opinion for International App. No. PCT/US23/61256; Date of Filing: Jan. 25, 2023, Applicant: Inari Medical, Inc., dated Jun. 7, 2023, 8 pages.

Gross et al., "Dump the pump: manual aspiration thrombectomy (MAT) with a syringe is technically effective, expeditious, and cost-efficient," J NeuroIntervent Surg, 2018, 4 pages.

International Search Report and Written Opinion for International App. No. PCT/US23/60927; Date of Filing: Jan. 19, 2023, Applicant: Inari Medical, Inc., dated Jul. 20, 2023, 12 pages.

Extended European Search Report issued for EP Application No. 20877370.5, dated Oct. 17, 2023, 11 pages.

* cited by examiner




FIG. 1




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12

HEMOSTASIS VALVES AND METHODS OF USE

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a divisional of U.S. patent application Ser. No. 17/705,189, filed on Mar. 25, 2022, and titled “HEMOSTASIS VALVES AND METHODS OF USE,” which is a continuation of U.S. patent application Ser. No. 17/226,318, filed on Apr. 9, 2021, and titled “HEMOSTASIS VALVES AND METHODS OF USE,” which is a continuation of U.S. patent application Ser. No. 16/117,519, filed on Aug. 30, 2018, now issued as U.S. Pat. No. 11,000,682, and titled “HEMOSTASIS VALVES AND METHODS OF USE,” which claims the benefit of U.S. Provisional Patent Application No. 62/554,931, filed on Sep. 6, 2017, and titled “HEMOSTASIS VALVES AND METHODS OF USE,” each of which is herein incorporated by reference herein in its entirety.

BACKGROUND

During a surgical procedure, a portion of a patient’s body (e.g., vasculature) is accessed to allow for performance of a desired intervention or treatment. During such surgical procedures, it is desired to minimize patient blood loss, prevent delivery of air into the vasculature, and to maintain the sterility of the accessed portions or sites of the patient’s body so as to prevent issues such as infection. Further, the desire for improved patient outcomes has led to the development of hemostasis valves that facilitate minimally invasive surgery.

In minimally invasive surgery, small incisions are created through a blood vessel which one or several catheters are inserted. Each of these one or several catheters can define a lumen extending longitudinally through that catheter. These catheters are moved to a position proximate to tissue, nerves, or other body structures targeted by the surgery, and then tools for performing the procedure are inserted through the lumens of some or all of these catheters.

To minimize blood loss, prevent delivery of air into the vasculature, and to facilitate maintenance of sterility within the patient’s body (e.g., blood vessel), these catheters are equipped with hemostasis valves. These valves seal or selectively seal the lumens of the catheters. In many instances, these valves can seal the lumen of the catheter when a tool extends through the catheter, and specifically through the valve. Additionally the valves can seal the lumen when a tool is removed or does not extend through the catheter.

While such traditional hemostasis valves are greatly beneficial for intravascular access, they have some drawbacks. For example, some valves may not seal adequately for all interventional applications or tools, and/or the operation of some valves may be complicated for operator use. The drawbacks of such valve designs may in turn increase the complexity of any surgery performed therewith and/or reduce patient safety (e.g., bleeding, infection, and/or other detrimental complications). Accordingly, new and improved hemostasis valves and methods of use are desired.

SUMMARY

The following relates to valves, medical systems incorporating valves, and methods of using the same. The valve can include a tubular member that can be constricted, collapsed, and/or sealed by one or several tensioning mecha-

nisms. The tensioning mechanism can include at least one filament that extends around at least a portion of the tubular member. The filament can interact with the tubular member to constrict, collapse, and/or seal the tubular member via manipulation of the tensioning mechanism(s). A tool can be inserted through the valve to gain access to a patient’s body and specifically to gain access to a blood vessel. Through the use of the tensioning mechanism and filament to constrict, collapse, and/or seal the tubular member, the valve can seal around a wide range of tool sizes and shapes, as well as multiple tools of differing sizes simultaneously. Additionally, such a valve creates a robust seal that maintains its seal when a vacuum is applied such as occurs during aspiration.

Aspects of the present disclosure relate to a hemostatic valve for sealing a medical device. The hemostatic valve includes an elongate member having a first end, a second end, and a central lumen extending therebetween. In some embodiments, the elongate member is pliable. The hemostatic valve can include a reinforcement structure extending along at least a portion of the elongate member, such that the reinforcement structure is coupled to the elongate member. The hemostatic valve includes an active tensioning mechanism coupled to the elongate member. In some embodiments, the tensioning mechanism is moveable between a first configuration in which the central lumen is constricted and sealed and a second configuration in which the central lumen is open. Optionally, the valve may be manually adjusted by the user to intermediate positions between fully open and fully closed. Additionally, an instrument (e.g. catheter) may provide an intermediate position where the valve creates hemostasis without user adjustment.

In some embodiments, the elongate member can be a compliant polymer tube. In some embodiments, the tensioning mechanism can include at least one filament extending at least partially around the elongate member. In some embodiments, the reinforcement structure is positioned between the at least one filament and the elongate member. In some embodiments, the reinforcement structure can be a braided mesh. In some embodiments, the reinforcement structure is coupled to the elongate member at a position proximate to the first end of the elongate member and at a position proximate to the second end of the elongate member. In some embodiments, the reinforcement structure is not coupled to the elongate member at a position between the first end of the elongate member and the second end of the elongate member. In some embodiments, the central portion of the compliant polymer tube that is constrained or collapsed by the tensioning mechanism, and at least one filament, is not coupled to the reinforcement structure.

In some embodiments, the tensioning mechanism can include an actuator coupled to the at least one filament. In some embodiments there are two tensioning mechanisms coupled to the at least one filament that operate in opposite directions. In some embodiments the two tensioning mechanisms are attached to the same filament. In some embodiments the two tensioning mechanisms are attached to opposing filaments. In some embodiments, the actuator can be moveable to control movement of the at least one filament from a first position in which the central lumen is constricted and sealed to a second position in which the central lumen is open. In some embodiments, the at least one filament is in the first position when the tensioning mechanism is in the first configuration. In some embodiments, the actuator is biased towards the first position. In some embodiments, the actuator is biased toward the second position. In some embodiments, the actuator can be a manual actuator.

3

In some embodiments, the at least one filament forms a loop around the elongate member. In some embodiments, the at least one filament forms a bight around a portion of the elongate member. In some embodiments, the at least one filament can include a first filament and a second filament. In some embodiments, each of the first filament and the second filament are coupled to the same actuator. In some embodiments, each of the first filament and the second filament are coupled to different actuators. In some embodiments, the first filament and the second filament are moveable from the first position to the second position. In some embodiments, each of the first filament and the second filament form a loop around the elongate member. In some embodiments, the first filament forms a first bight around a first portion of the elongate member, and the second filament forms a second bight around a second portion of the elongate member. In some embodiments, the first bight extends through the second bight.

In some embodiments, the hemostatic valve can include a shell defining a first aperture and a second aperture. In some embodiments, the elongate member extends from the first aperture to the second aperture and fluidly couples the first aperture and the second aperture. In some embodiments, the tensioning mechanism is self-adjustable to seal around tools of different sizes extending through the hemostatic valve. In some embodiments, the central lumen can comprise a single lumen, and in some embodiments, the central lumen can comprise a plurality of lumens.

One aspect of the present disclosure relates to a delivery system for intravascular access of a blood vessel within a patient's body. The delivery system includes a catheter having a first end, a second end, and a catheter lumen extending therebetween and a hemostatic valve coupled to the first end of the catheter. The hemostatic valve includes a tubular member having a first end, a second end, and a central lumen extending therebetween. In some embodiments, the central lumen of the tubular member is fluidly coupled with the catheter lumen. The hemostatic valve includes an active tensioning mechanism coupled to the tubular member, the tensioning mechanism can be moveable between a first configuration in which the tensioning mechanism constricts on the central lumen and the central lumen is sealed and a second configuration in which the central lumen is open.

In some embodiments, the hemostatic valve further includes a reinforcement structure extending along at least a portion of the tubular member. In some embodiments, the reinforcement structure is located between the tensioning mechanism and the tubular member. In some embodiments, the reinforcement structure can be a braided mesh. In some embodiments, the reinforcement structure is coupled to the tubular member at a position proximate to the first end of the tubular member and at a position proximate to the second end of the tubular member. In some embodiments, the reinforcement structure is adhered to the tubular member at the first end of the tubular member and at the second end of the tubular member. In some embodiments, the reinforcement structure is uncoupled to the tubular member between the first end of the tubular member and the second end of the tubular member.

In some embodiments, the tensioning mechanism can include at least one filament extending at least partially around the tubular member. In some embodiments, the tensioning mechanism can include an actuator coupled to the at least one filament. In some embodiments, moving the tensioning mechanism from the first configuration to the second configuration can include moving the actuator and

4

the thereto coupled at least one filament from a first position to a second position. In some embodiments, the filament constricts and seals the central lumen of the tubular member when the filament is in the first position.

In some embodiments, the actuator can be a manual actuator. In some embodiments, the actuator can include a pair of opposing and depressable buttons, which buttons can be biased towards an undepressed position. In some embodiments, the central lumen is sealed when the buttons are in the undepressed position. In some embodiments, the filament can be a monofilament. In some embodiments, the filament can be at least one of: a polymer filament; or a metallic filament. In some embodiments, the catheter can include a thrombus extraction device.

One aspect of the present disclosure relates to a method of sealing a delivery device accessing a blood vessel of a patient. The method includes inserting the delivery device including a catheter and a hemostatic valve into the blood vessel of the patient. In some embodiments, the catheter can have a first end, a second end, and a catheter lumen extending therethrough. In some embodiments, the hemostatic valve can be coupled to the first end and can have a tubular member defining a central lumen fluidly coupled with the catheter lumen and a tensioning mechanism coupled with the tubular member. In some embodiments, the tensioning mechanism collapses and seals the central lumen in a first configuration and thereby seals access to the blood vessel. The method can include moving the tensioning mechanism of the hemostatic valve to a second configuration. In some embodiments, the central lumen is open and access to the blood vessel is unsealed when the tensioning mechanism is in the second configuration. The method can include advancing a shaft of a tool through the delivery device until a first end of the tool reaches a desired position within the blood vessel of the patient and a portion of the shaft is positioned within the central lumen of the tubular member. The method can include returning the tensioning mechanism of the hemostatic valve to the first configuration such that the tubular member collapses on the shaft of the tool and seals around the shaft of the tool.

In some embodiments, the method includes retracting the shaft of the tool from the delivery device. In some embodiments, the tensioning mechanism is maintained in the first configuration during and after the retracting of the shaft of the tool from the delivery device. In some embodiments, the tensioning mechanism is moved to the second configuration during the retracting of the shaft of the tool from the delivery device, and the tensioning mechanism is returned to the first configuration after the shaft of the tool is retracted from the delivery device.

In some embodiments, the tensioning mechanism can include at least one filament extending at least partially around the tubular member. In some embodiments, the at least one filament collapses the tubular member when the tensioning mechanism is in the first configuration. In some embodiments, the at least one filament circumferentially constricts the tubular member to collapse the tubular member when the tensioning mechanism is in the first configuration. In some embodiments, the hemostatic valve can include a reinforcement structure located between the at least one filament and the tubular member.

In some embodiments, the at least one filament forms a loop around the elongate member, and moving the tensioning mechanism from the second configuration to the first configuration reduces a size of the loop to thereby constrict the tubular member within the loop. In some embodiments, the filament forms at least one bight around a portion of the

5

elongate member. In some embodiments, the filament can include a first filament and a second filament. In some embodiments, the at least one bight can include a first bight oriented in a first direction and formed by the first filament and a second bight oriented in a second direction and formed by the second filament. In some embodiments, the first and second bights overlap to encircle a portion of the tubular member within a constricting area.

In some embodiments, moving the tensioning mechanism from the second configuration to the first configuration can include moving the first bight in the first direction and the second bight in the direction to reduce the size of the constricting area and collapse and seal the central lumen of the tubular member. In some embodiments, the tensioning mechanism can include an actuator. In some embodiments, moving the tensioning mechanism to the second configuration can include manipulating the actuator. In some embodiments, the method includes applying a vacuum to the delivery device and/or delivery system to aspirate material through the catheter. In some embodiments, the central lumen remains sealed during the aspiration. In some embodiments, the tool can include a thrombus extraction device.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view of one embodiment of a delivery device.

FIG. 2 is a side-section view of one embodiment of a hemostasis valve in a first configuration.

FIG. 3 is a side-section view of one embodiment of the valve in a second configuration.

FIG. 4 is a side-section view of one embodiment of the valve in the first configuration and with a tool extending through the valve.

FIG. 5 is a side-section view of one embodiment of a single-button hemostasis valve in a first configuration.

FIG. 6 is a perspective view of a filament of a valve forming a loop.

FIG. 7 is a perspective view of two filaments of a valve, each of the filaments forming a loop.

FIG. 8 is a perspective view of two overlapping and interlocked bights in an open configuration.

FIG. 9 is a perspective view of two overlapping and interlocked bights in a closed configuration.

FIG. 10 is a flowchart illustrating one embodiment of a method for sealing a valve and/or catheter.

FIG. 11 is a side view of one embodiment of a thrombectomy system including the delivery device.

FIG. 12 is a side-section view of another embodiment of a hemostasis valve having two-piece caps.

DETAILED DESCRIPTION

The present disclosure relates to a valve that can be used as a hemostasis valve. This valve, also referred to herein as a garrote valve can seal with or without a tool extending through the valve. The garrote valve provides convenient, single-handed operation for a wide range of medical devices including catheters, wires, embolectomy systems, or the like. This single-handed operation of the garrote valve allows the user to easily and quickly swap different tools being used through the valve without compromising hemostasis and therefore simplifying the procedure. Combined with single-handed operation, the garrote valve provides robust sealing either with or without a tool extending through the valve. This robust sealing minimizes leakage in

6

applications with a pressure differential on different sides of the valve. This pressure differential can arise, for example, during the application of vacuum aspiration in a procedure. Even under such conditions, as well as under other conditions, the garrote valve maintains seal integrity and prevents leakage in one or both directions.

The garrote valve includes a tubular member. The tubular member is a flexible member that defines a central lumen, which can, in some embodiments, define a single lumen, and in some embodiments, defines a plurality of lumens. In some embodiments, each of the plurality of lumens can comprise the same size and shape, and in some embodiments, some or all of the plurality of lumens can comprise different sizes and shapes. In some embodiments, for example, the plurality of lumens can comprise a lumen sized and/or shaped to receive a guide wire and a lumen sized and/or shaped to receive a tool. The tubular member extends at least partially through a constricting mechanism. The constricting mechanism can be moved from a first configuration to a second configuration, and the constricting mechanism can collapse and/or seal the central lumen of the tubular member when the constricting mechanism is in the first configuration. The constricting mechanism creates the above-discussed robust seal of the tubular member and thus of the valve.

With reference now to FIG. 1, a perspective view of one embodiment of a delivery system 100, also referred to herein as a delivery device 100, is shown. The delivery system 100 can include a catheter 102 and a garrote valve 104, also referred to herein as valve 104. The catheter 102 can comprise a shaft 106, also referred to herein as an elongate sheath 106, having a proximal end 108, also referred to herein as a first end 108, that can connect to the valve 104 and a distal end 110, also referred to herein as a second end 110. The shaft 106 can define a catheter lumen 112 extending from the proximal end 108 of the shaft 106 to the distal end 110 of the shaft 106. The catheter 102 and specifically the shaft 106 can comprise a variety of shapes and sizes and can be made from a variety of materials. In some embodiments, the catheter 102 can be flexible and/or can be made from a biocompatible material. The elongate sheath 106 can have an outer diameter of at least 4 French, at least 6 French, at least 8 French, at least 10 French, at least 12 French, at least 14 French, at least 18 French, at least 20 French, at least 22 French, between 4 French and 30 French, between 8 French and 24 French, between 12 French and 20 French, and/or any other or intermediate size.

The valve 104 can include an outer shell 114. The outer shell 114 can comprise a variety of shapes and sizes and can be made from a variety of materials. In some embodiments, the outer shell 114 can be made from one or several polymers or composites. The outer shell 114 can include features that allow interaction with and/or control of the valve 104 to move the valve 104 between the first configuration and the second configuration.

The outer shell 114 can include a proximal cap 116 located at a proximal end 118 of the outer shell 114 and a distal cap 120 located at a distal end 122 of the shell 114. The proximal cap 116 can include and/or house a proximal aperture 124, also referred to herein as a proximal channel 124, a first channel 124, or a first aperture 124, that extends through the proximal cap 116, and the distal cap 120 can include and/or house a distal aperture 126, also referred to herein as a distal channel 126, a second channel 126, or second aperture 126, that extends through the distal cap 120. As seen in FIG. 1, the distal cap 120 connects to the shaft 106 of the catheter 102 at the distal end 122 of the valve 104.

The proximal cap 116 and the distal cap 120 are connected via a housing 128. The housing 128 can be a one-piece housing 128 or a multi-piece housing 128. In the embodiment depicted in FIG. 1, the housing comprises a two-piece housing 128. The housing 128 can be configured to receive and couple with each of the proximal cap 116 and the distal cap 120, and as seen in FIG. 1, the housing 128 is coupled with each of the proximal cap 116 and the distal cap 120 to secure the relative position of the proximal cap 116 and the distal cap 120 with respect to each other.

The housing 128 can define an interior channel 130 through which an elongate member 132, also referred to herein as a tubular member 132, a septum 132, or a tubular septum 132, can extend and connect the proximal cap 116 and the distal cap 120. The elongate member 132 can comprise a variety of shapes and sizes and can be made from a variety of materials. In some embodiments, the elongate member 132 can comprise a compliant tubular structure that can be, for example, a thin-walled compliant tubular structure. The thin-walled structure of the elongate member 132 can facilitate the collapse, and specifically the uniform collapse of the elongate member 132 and the sealing of the elongate member 132. In some embodiments, the elongate member 132 is an elastic, resilient material that may comprise a polymer including either a natural or synthetic polymer. In some embodiments, the elongate member can comprise an elastic, resilient material that may comprise silicone, urethane, ethylene-vinyl acetate, natural or synthetic rubber or other elastomers known in the art. In some embodiments, the elongate member 132 can comprise a silicone tube.

The elongate member 132 can comprise a proximal end 134, also referred to herein as a first end 134, that can couple to the proximal cap 116, and a distal end 136, also referred to herein as a second end 136, that can couple to the distal cap 120. The elongate member 132 can define a central lumen 138 that can extend from the first end 134 to the second end 136 of the elongate member 132. The elongate member 132 can be coupled to the proximal cap 116 such that the central lumen 138 is fluidly coupled with the proximal aperture 124 of the proximal cap 116, and the elongate member 132 can be coupled to the distal cap 120 such that the central lumen 138, as seen in FIG. 2 and in FIG. 3, is fluidly coupled with the distal aperture 126 of the distal cap 120.

The central lumen 138 of the elongate member 132 can be defined by a wall of the elongate member 132 that can have a thickness that is uniform along the length of the elongate member 132 between the first end 134 and the second end 136, or that is non-uniform along the length of the elongate member 132 between the first end 134 and the second end 136. In some embodiments, the wall can have a thickness that is approximately between 0.005 inches and 0.05 inches, and/or approximately between 0.010 inches and 0.030 inches. As used anywhere herein, "approximately" refers to a range of +/-10% of the value and/or range of values for which "approximately" is used.

In some embodiments, the elongate member 132 can be cylindrically shaped, and specifically can be circular-cylindrically shaped. In some embodiments, the elongate member 132 can be dog-bone shaped to facilitate, for example, connection to each of the proximal cap 116 and the distal cap 120. In some embodiments, the elongate member 132 can include one or several outward-extending protuberances that engage with all or portions of a constricting mechanism 141, also referred to herein as a tensioning mechanism 141, of the valve 104 to secure a position of all or portions of the

constricting mechanism 141 with respect to the elongate member 132. In some embodiments, the constricting mechanism 141 can be self-adjusting to seal around tools of different sizes extending through the valve 104.

The constricting mechanism 141 can, in some embodiments, collapse and seal the elongate member 132 via compression and/or constriction, and specifically via constriction with at least one filament 150. The constricting mechanism 141 can comprise: an actuator 142 which can be a manual actuator such as one or several buttons 144; and the at least one filament 150 that can extend at least partially around the elongate member 132. In some embodiments, the use of the constricting mechanism 141 can facilitate sealing of the valve around tools or instruments of a wide range of sizes and/or diameters, and particularly around tools or instruments that fit through the elongate member 132.

The housing 128 can further include one or several retention features 140. The one or several retention features 140 of the housing can engage with and retain all or portions of the constricting mechanism 141 of the valve 104. In some embodiments, the one or several retention features 140 of the housing 128 can retain the actuator 142 and/or can couple the actuator 142 to the housing 128. The actuator 142 can comprise any desired type of actuator including, for example, a manual actuator and/or an automated actuator such as, for example, an electromechanical actuator including a solenoid-based actuator. In some embodiments, the actuator can comprise one or several buttons 144, and specifically, as depicted in FIG. 1, the actuator 142 can comprise a first button 144-A and a second button 144-B. Alternatively, and as depicted in FIG. 5, the actuator 142 can comprise a single button 144. In such an embodiment, the filament 150 can be coupled to the single button 144 and to a portion of the housing 128 such as, for example, to grip portion 500 of the housing 128 such that the movement of the single button 144 causes the sealing and/or opening of the elongate member 132 and of the valve 104.

The actuator 142 can be biased towards a configuration such as, for example, biased towards the first configuration or biased towards the second configuration. As depicted in FIG. 2, which shows the constricting mechanism 141 in the first configuration, the actuator 142 can be biased towards the first configuration wherein the elongate member 132 is collapsed and/or sealed by a bias feature 146. In this first configuration, the buttons 144 can be in a first position, also referred to herein as an undepressed position. This bias feature 146 can, as shown in FIG. 2, include a first spring 148-A configured to bias the first button 144-A towards the first position corresponding to the first configuration of the constricting mechanism 141, and a second spring 148-B configured to bias the second button 144-B towards a first position corresponding to the first configuration of the constricting mechanism 141. One or both of the first spring 148-A and the second spring 148-B can comprise a tension spring, compression spring, a torsion spring, a coil spring, or any other desired type of spring.

In some embodiments, one or both of the first spring 148-A and the second spring 148-B can generate sufficient force so as to allow actuation of the actuator 142 with a single hand and so as to collapse and seal the elongate member 132 when the constricting mechanism 141 is in the first configuration. In some embodiments, one or both of the first spring 148-A and the second spring 148-B can generate a force of: at least 0.1 pounds, at least 0.2 pounds, at least 0.3 pounds, at least 0.4 pounds, at least 0.5 pounds, at least 0.6 pounds, at least 0.7 pounds, at least 0.8 pounds, at least 0.9 pounds, at least 1 pound, at least 1.5 pounds, at least 2

pounds, at least 3 pounds, at least 5 pounds, and/or at least 10 pounds and in some embodiments one or both of the first spring 148-A and the second spring 148-B can generate a force approximately between: 0.1 and 10 pounds, 0.1 and 5 pounds, 0.1 and 1.5 pounds, 0.2 and 1 pounds, and/or 0.4 and 0.8 pounds.

The constricting mechanism 141 can include at least one filament 150 that extends at least partially around the elongate member 132. In some embodiments, the at least one filament 150 can circumferentially constrict the elongate member 132 to collapse and seal the elongate member 132 when the constricting mechanism 141 is in the first configuration. The filament can be made from a variety of materials including, for example, a polymer, a synthetic, and/or a metal. In some embodiments, the filament 150 can be nylon, stainless steel, nitinol, silicone, or the like. In some embodiments, the filament can comprise a single strand such as, for example, a monofilament, and in some embodiments, the filament can comprise a plurality of strands that can be, for example, twisted, woven, grouped, and/or fused to form the filament. In some embodiments, the filament 150 can comprise one or several threads, lines, cords, rope, ribbon, flat wire, sheet, or tape.

The filament 150 can be coupled to the actuator 142 such that the filament 150 selectively constricts, collapses, and/or seals the elongate member 132, and specifically the central lumen 138 of the elongate member 132 based on the movement and/or position of the actuator 142. In some embodiments, the filament 150 can be connected to one or both of the buttons 144-A, 144-B such that the filament 150 collapses, constricts, and/or seals the elongate member 132 and specifically the central lumen 138 of the elongate member 132 when the buttons 144-A, 144-B are in the first position, and the filament 150 can be connected to one or both of the buttons 144-A, 144-B such that the elongate member 132 and specifically the central lumen 138 of the elongate member 132 is open and uncollapsed when the buttons 144-A, 144-B are in the second position. In some embodiments in which the actuator 142 comprises a single button 144, as depicted in FIG. 5, the filament 150 can be connected to the button 144 and to the housing 128 such that the filament 150 is tightened when the button 144 moves to the first position.

In some embodiments, the at least one filament 150 can extend along an axis 152 that can be perpendicular to a central axis 154 of the elongate member 132 and/or of the apertures 124, 126. In some embodiments, the axis 152 of the at least one filament 150 can intersect and be perpendicular to the central axis 154 of the elongate member 132 and/or of the apertures 124, 126. In some embodiments, the actuator 142, and specifically the buttons 144-A, 144-B can move along this axis 152 when moved from the first position to the second position.

In FIG. 3, an embodiment of the valve 104 with the constricting mechanism 141 in the second configuration is shown. As specifically shown, both of the first and second buttons 144-A, 144-B are in the second position, depressed into the retention features 140 of the housing 128. In this second position, the filament 150 is loosened, thereby allowing the expansion of the elongate member 132 and the unsealing of the central lumen 138 of the elongate member 132.

As further seen in FIG. 3, the proximal cap 116 has a proximal end 300 and a distal end 302. The proximal cap 116 can include a funnel portion 301 of the proximal aperture 124, which funnel portion 301 can facilitate insertion of a tool into the proximal aperture 124. The distal end 302 of the

proximal cap 116 can partially extend into the interior channel 130 of the housing 128. The proximal cap 116 can include a mating feature 304 that can mate with the proximal end 134 of the elongate member 132. In some embodiments, the proximal end 134 of the elongate member 132 can fit over the mating feature 304 of the proximal cap 116. The proximal end 134 of the elongate member 132 can be compressed between the mating feature 304 of the elongate member 132 and a portion of the interior channel 130 of the housing 128 into which the mating feature 304 is inserted to thereby secure the proximal end 134 of the elongate member 132 on the mating feature 304. In some embodiments, the proximal end 134 of the elongate member 132 can be further secured on the mating feature 304 by a proximal O-ring 306 that can be compressed between the housing 128 and the mating feature 304 of the proximal cap 116 to sealingly couple the elongate member 132 to the proximal cap 116.

The distal cap 120 has a proximal end 308 and a distal end 310. The distal cap can include a mating feature 312 located on the proximal end 308 of the distal cap 120, which mating feature 312 can mate with the distal end 136 of the elongate member 132. In some embodiments, the distal end 136 of the elongate member 132 can fit over the mating feature 312 of the distal cap 123. The distal end 136 of the elongate member 132 can be compressed between the mating feature 312 of the elongate member 132 and a portion of the interior channel 130 of the housing 128 into which the mating feature 312 is inserted to thereby secure the distal end 136 of the elongate member 132 on the mating feature 312. In some embodiments, the distal end 136 of the elongate member 132 can be further secured on the mating feature 312 by a distal O-ring 314 that can be compressed between the housing 128 and the mating feature 312 of the proximal cap 116 to sealingly couple the elongate member 132 to the distal cap 120.

The distal cap 120 can, in some embodiments, further include a side port barb 314 that can extend laterally away from the distal cap 120 and specifically away from the distal aperture 126 of the distal cap 120. The side port barb 314 can define a side port channel 316 that can extend through the side port barb 314 and fluidly connect to the distal aperture 126. In some embodiments, the side port barb 314 can include a securement feature 318 such as a barb that can secure coupling of a hose or tube to the side port barb 314.

In some embodiments, the side barb 314 can be used to apply a vacuum to the portions of the delivery device 100, and particularly to portions of the delivery device 100 that are distal of the axis 152 along which the elongate member 132 seals. This vacuum can be applied to aspirate a material through the delivery device 100, and specifically through the catheter 102 of the delivery device. This aspirated material can be a biological material including, for example, bodily fluids, multi-phase bodily materials that can include, for example, a fluidic portion and at least one solid portion, or the like.

In some embodiments, due to the narrowing shape of the elongate member 132 when the constricting mechanism 141 is in the first configuration, a vacuum applied to the portions of the delivery device 100 distal to the axis 152 draws the elongate member 132 towards the first configuration and can, in some embodiments, increase the strength, robustness, and/or strength of the seal of the valve 104. This attribute of the valve 104 can provide benefits over other valve designs in which a vacuum can compromise the seal of the valve, and thus the ability to draw a vacuum and aspirate can be limited.

In some embodiments, the valve **104** can further include a reinforcement structure **320** that can extend along all or portions of the elongate member **132**. The reinforcement structure **320** can facilitate the uniform collapse of the elongate member **132**, can prevent the at least one filament **150** from cutting through and/or tearing the elongate member **132**, and can assist in guiding one or several tools through the elongate member **132**. The reinforcement structure **320** can be tubular, can extend along and around the elongate member **132**, and can be positioned so as to be between the elongate member **132** and the at least one filament **150**.

The reinforcement structure **320** can include a proximal end **322** and a distal end **324**. In some embodiments, the reinforcement structure **320** extends along and around the elongate member **132**, and is positioned such that the proximal end **322** of the reinforcement structure **320** is proximate to the first end **134** of the elongate member **132** and the distal end **324** of the reinforcement structure **320** is proximate to the second end **136** of the elongate member **132**.

The reinforcement structure **320** can be coupled to the elongate member **132**. In some embodiments, the reinforcement structure **320** is coupled to the elongate member **132** along the length of the reinforcement structure **320**, and in some embodiments, the reinforcement structure **320** is coupled to the elongate member **132** and distinct positions along the length of the elongate member **132** and/or the reinforcement structure **320**. In one embodiment, for example, the reinforcement structure **320** can be coupled to the elongate member **132** at one or both of the proximal end **322** of the reinforcement structure **320** and the distal end **324** of the reinforcement structure **320** and/or at one or both of the first end **134** and the second end **136** of the elongate member **132**. In some embodiments, the reinforcement structure **320** can be coupled to the elongate member **132** via one or several other components of the valve **104**. In some embodiments, the reinforcement structure **320** can be coupled to the elongate member **132** via the compression of the reinforcement structure **320** and the elongate member **132** between the housing **128** and one or both of the proximal **116** and the distal **120**.

In some embodiments, the reinforcement structure **320** can be adhered to the elongate member **132** via, for example, an adhesive such as silicone adhesive. In some embodiments, the adhesive can be circumferentially applied to the reinforcement structure **320** and/or the elongate member **132** in an adhesive ring that can, for example, have a length approximately between: 0.010 inches and 0.5 inches; 0.02 and 0.4 inches; 0.050 inches and 0.0250 inches, or any other or intermediate range.

In one embodiment, each of the proximal end **322** and the distal end **324** of the reinforcement structure **320** can be adhered via an adhesive to the elongate member **132**. In such an embodiment, the reinforcement structure **320** may be uncoupled to the elongate member **132** at positions other than the coupling at one or both of the proximal end **322** and the distal end **324** of the reinforcement structure **320**, and thus the reinforcement structure **320** is uncoupled to the elongate member **132** at a position between the first end **134** and the second end **136** of the elongate member **132** and/or between the proximal end **322** and the distal end **324** of the reinforcement structure **320**.

The lack of coupling of the reinforcement structure **320** to the elongate member **132** can facilitate and improve the collapse of the elongate member **132** around a tool **400**, also referred to herein as instrument **400** or device **400**, inserted

through the valve **104** as shown in FIG. 4. The tool **400** can be any device inserted through the valve **104** including, for example, one or several additional catheters, lines, wires, grippers, punches, cutters, or the like. As seen in FIG. 4, the tool **400** is inserted through the valve **104** and specifically through the elongate member **132** of the valve. As shown, the constricting mechanism **141** is in the first configuration and the elongate member **132** and the central lumen **138** of the elongate member **132** is collapsed around the tool **400**, and specifically around a shaft **402** of the tool **400** to thereby seal the valve **104** around the tool **400** and specifically around the shaft **402** of the tool **400**. The constricting mechanism **141** can seal around tools **400** that fit through the elongate member **132**, regardless of the size of the tool **400**. Thus, the valve can be used with a wide variety of tools.

The reinforcement structure **320** can comprise a variety of designs, shapes, sizes, and materials. In some embodiments, the reinforcement structure **320** can be sized and shaped so as to receive elongate member **132** and to be positioned between the elongate member **132** and the at least one filament **150**. In some embodiments, the reinforcement structure **320** can be made from a material sufficiently strong to prevent the cutting of the at least one filament **150** through the elongate member **132**.

In some embodiments, the reinforcement structure can comprise a coil or a mesh sheath. The mesh sheath can, in some embodiments, comprise a braided mesh. The braided mesh can be made from any desired number of wires in any desired configuration. In some embodiments, the braided mesh can comprise a 4 wire braided mesh, an 8 wire braided mesh, a 12 wire braided mesh, a 16 wire braided mesh, a 20 wire braided mesh, a 24 wire braided mesh, a 32 wire braided mesh, a 48 wire braided mesh, a 64 wire braided mesh, a 72 wire braided mesh, an 80 wire braided mesh, a 96 wire braided mesh, or any other or intermediate braided mesh. In some embodiments, the braided mesh can comprise: a 1x1 configuration. In some embodiments, the wire in the braided mesh can be any desired material including, for example, a metal wire such as a nitinol wire or a stainless steel wire, a polymer wire, or a natural wire. In one embodiment, the braided mesh can comprise a 48 wire mesh in a 1x1 configuration made with a nitinol wire having a diameter of 0.003 inches.

With reference now to FIGS. 6 through 9, different embodiments and/or configurations of the filament **150** are shown. The filament **150** can comprise a single filament **150** having a first end **600** and a second end **602** as shown in FIG. 6. The filament **150**, and specifically which first and second ends **600**, **602** can be coupled to the actuator **142** to move the filament **150** between the first and second configurations or positions and/or from the first configuration or position to the second configuration or position. In some embodiments, both of the first end **600** and the second end **602** can be coupled to a single button **144**, in some embodiments, each of the first end **600** and the second end **602** can be coupled to different buttons **144**, and in some embodiments, one of the first end **600** and the second end **602** can be coupled to a button **144** and the other of the first end **600** and the second end **602** can be coupled to the housing **128** or other portion of the valve **104**.

In some embodiments, the filament **150** can comprise multiple filaments, and specifically, as shown in FIGS. 7 through 9, the filament **150** can comprise a first filament **150-A** and a second filament **150-B**. In embodiments in which the filament **150** comprises multiple filaments, each of the multiple filaments can have a first end **700** and a second end **702**. The first and second filaments **150-A**,

150-B can be coupled to the actuator 142. In such embodiments, the first and second ends 700, 702 can be coupled to the actuator 142 to move the filaments 150-A, 150-B between the first and second configurations and/or from the first configuration to the second configuration. In some 5
embodiments, both of the first end 700 and the second end 702 of one or more of the multiple filaments 150 can be coupled to a single button 144, in some embodiments, each of the first end 700 and the second end 702 of one or more of the multiple filaments 150 can be coupled to different 10
buttons 144, and in some embodiments, one of the first end 700 and the second end 702 of one or more of the multiple filaments 150 can be coupled to one button 144 and the other of the first end 700 and the second end 702 of those one or more filaments 150 can be coupled to the housing 128 or 15
other portion of the valve 104.

The filament 150 can be arranged in a variety of configurations. In some embodiments, the filament 150 can be configured to form a single loop 604 that can extend around the elongate member 132 and/or through which the elongate 20
member 132 can be received as shown in FIG. 6, and in some embodiments, the filament 150 can be configured to form multiple loops, and specifically a first loop 704 and a second loop 706 as shown in FIG. 7. The first and second loops 704, 706 can each receive the elongate member 132. 25
In some embodiments, a diameter or size of the loop 604, or of the loops 704, 706 can decrease when the constricting mechanism 141 is moved from the second configuration to the first configuration.

In some embodiments, the filament 150 can be configured 30
to form a bight 800, which bight 800 can be a single bight or multiple bights. As used herein, a “bight” refers to a U-shaped section between the two ends of the filament 150. As depicted in FIGS. 8 and 9, the bight 800 can comprise multiple bights, and specifically a first bight 800-A and a 35
second bight 800-B. In some embodiments, the first bight 800-A can extend through the second bight 800-B such that the first and second bights 800-A, 800-B interlock, whereas in other embodiments, the first and second bights 800-A, 800-B can be non-interlocking. Similarly, in embodiments 40
containing the filament 150 having multiple loops, one or several of the multiple loops can be interlocking.

In some embodiments, the bight 800, and specifically one or both of the first bight 800-A and the second bight 800-B can be formed around a portion of the elongate member 132 45
and/or can extend around a portion of the elongate member 132. Each bight 800 can define a partially enclosed receiving area 808 wherein the elongate member 132 can be received. Thus, the first bight 800-A can define a first receiving area 808-A and the second bight 800-B can define a second 50
receiving area 808-B.

As seen in FIGS. 8 and 9, multiple bights, and specifically the first and the second bights 800-A, 800-B can be positioned and oriented such that the first bight 800-A has a first orientation or first direction as indicated by arrow 810, and 55
the second bight has a second orientation or second direction as indicated by the arrow 812. In some embodiments, the first orientation is different from the second orientation such that the first and second receiving areas 808-A, 808-B overlap and define an encircled area 814, also referred to 60
herein as a constricting area 814. The elongate member 132 can be received within the encircled area 814. In embodiments in which bights 800-A, 800-B overlap to define the encircled area 814, the movement of the constricting mechanism 141 to the first configuration can result in and/or 65
include the first bight 800-A moving in the direction indicated by the arrow 810 and/or the second bight 800-B

moving in the direction indicated by the arrow 812, which movement of the bights 800-A, 800-B decreases the size of the encircled area 814 and constricts, collapses, and/or seals the elongate member 132 extending through the encircled 5
area 814.

The filament(s) 150 forming the bights 800 can each apply an arcuate line or narrow longitudinal zone of pressure to the elongate member 132. If the filament(s) are circular in cross-section, the zone of pressure can be very small, and can, in some embodiments, be less than the diameter or 10
thickness of the filament. In some embodiments, the filaments have a diameter or width less than about 2.5 mm, less than about 2 mm, less than about 1.5 mm, less than about 1.25 mm, less than about 1 mm, less than about 0.75 mm, less than about 0.5 mm, and/or less than about 0.25 mm. In some embodiments, the filaments can have a diameter or width of between about 0.01 mm and 2.5 mm, between about 0.05 mm and 2 mm, between about 0.1 mm and 1 mm, and/or between about 0.125 mm and 0.70 mm. In some 15
embodiments, the arcuate line or zone of pressure may form two opposing arcs and in other embodiments, the arcuate line of pressure may be a singular substantially circular line or zone that encircles the elongate member at least once. The longitudinal length of the of the line or zone of pressure may be very short compared to other valves known in the art. In some embodiments, the longitudinal length of the zone of pressure applied to the elongate member 132 by the filament(s) 150 may be less than about 2.0 mm and in some 20
embodiments less than about 0.5 mm. In some embodiments, the filament(s) 150 can have any desired cross-sectional shape including, for example, a circular cross-section, a rectangular cross-section, an oval cross-section, a square cross-section, a polygonal cross-section, a triangular cross-section, or any other desired shape of cross-section.

With reference now to FIG. 10, a flowchart illustrating one embodiment of a process 1000 for sealing a valve 104 and/or catheter 102 accessing a body of a patient is shown. The process 1000 can be performed using the valve 104 and/or the delivery system 100. The process 1000 begins at block 1002, wherein the delivery device 100, and specifically the catheter 102 of the delivery device 100 is inserted into the body of the patient. In some embodiments, this can include inserting the catheter 102 into a portion of the circulator system of the patient such as, for example, a blood vessel including an artery or a venous vessel. In some 25
embodiments, the delivery device 100 can be inserted into the body of the patient directly through an aperture or incision in the patient, and in some embodiments, the delivery device 100 can be inserted into the body of the patient via another catheter or device. In some embodiments, the constricting mechanism 141 can be in the first configuration while the delivery device 100 and/or the catheter 102 is inserted into the patient’s body.

After the delivery device 100 is inserted into the body of the patient, the process 1000 proceeds to block 1004, wherein the constricting mechanism 141 is moved from the first configuration to the second configuration. As described above, the central lumen 138 of the elongate member 132 is unsealed when the constricting mechanism 141 is in the second configuration. In some embodiments, the moving of the constricting mechanism 141 from the first configuration to the second configuration can include the manipulation of the actuator 142 and/or the control of the actuator 142, and specifically the depressing of the one or several buttons 144 30
to move the filament 150 from the first position to the second position to allow the expansion and opening of the central lumen 138 of the elongate member 132.

15

After the constricting mechanism **141** is moved from the first configuration to the second configuration, the process **1000** proceeds to block **1006**, wherein the tool **400**, and specifically the shaft **402** of the tool **400** is advanced through the delivery device **100** and specifically through the valve **104** until a first end of the tool reaches a desired position within the body of the patient. In some embodiments, a portion of the shaft **402** can be positioned within the central lumen **138** of the elongate member **132** after the advancing of the tool **400** through the delivery device **100**. In some embodiments, after the tool **400** is advanced through the delivery device **100**, the desired procedure can be performed with the tool.

After the tool **400** is advanced through the delivery device **100**, or while the tool **400** is being advanced through the delivery device **100**, the process **1000** proceeds to block **1008**, wherein the constricting mechanism **141** is returned to the first configuration. In some embodiments, the returning of the constricting mechanism **141** to the first configuration can include the release of the one or several buttons **144** and/or the control of the actuator **142** to reconfigure the constricting mechanism **141** to the first configuration. In some embodiments, the return of the constricting mechanism **141** to the first configuration can result in the collapse and/or sealing of the elongate member **132** and specifically the central lumen **138** of the elongate member **132** around the tool **400** and specifically around the shaft **402** of the tool **400**. The return of the constricting mechanism **141** to the first configuration, or the movement of the constricting mechanism **141** to the first configuration can include the decreasing of the size and/or diameter of one or several loops formed by the filament **150** and/or the movement of one or several bights **800** such as, for example, the movement of the first bight **800-A** in the first direction indicated by arrow **810** and the movement of the second bight **800-B** in the second direction indicated by arrow **812** to reduce the size of the constricting area **814**. In some embodiments, after the constricting mechanism is returned to the first configuration, the desired procedure can be performed with the tool.

After the constricting mechanism is returned to the first configuration, the process **1000** proceeds to block **1010**, wherein the tool **400**, and specifically the shaft **402** of the tool **400** is retracted from the delivery device **100**, and more specifically from the valve **104**. In some embodiments, the valve **104** can remain sealed during the retracting of the tool **400** and/or the shaft **402** of the tool. In some embodiments, the valve **104** remains sealed during the retracting of the tool **400** and/or the retracting of the shaft **402** of the tool **400** as the constricting mechanism **141** can remain in the first configuration during the retracting of the tool **400** and/or the shaft **402** of the tool **400**.

In some embodiments, the constricting mechanism **141** can be moved to the second configuration to allow the retraction of the tool **400** and/or the shaft **402** of the tool **400** from the valve **104**, and the constricting mechanism **141** can be returned to the first configuration when the tool **400** and/or the shaft **402** of the tool **400** is removed from the valve **104**. In some embodiments, the retraction of the tool **400** and/or shaft **402** of the tool **400** from the valve **104** can be performed with the constricting mechanism **141** left in the first configuration. In some embodiments, the constricting mechanism **141** can be moved to the second configuration, and then returned to the first configuration via the manipulation and/or control of the actuator **142**, which manipulation and/or control of the actuator **142** can include the depressing of the one or several buttons **144** to move the constricting mechanism **141** to the second configuration, and

16

the release of the one or several buttons **144** to return the constricting mechanism **141** to the first configuration. In some embodiments, if the procedure is complete, the delivery device **100** can then be removed from the body of the patient, and any incision created for the procedure can be closed.

With reference now to FIG. **11**, a side view of one embodiment of a thrombectomy system **1100** including the delivery device **100** and a thrombus extraction device **1102** is shown. In some embodiments, the thrombectomy system **1100** can be used to access a blood vessel **1104** to treat and/or extract a thrombus **1106** from the blood vessel **1104**. The thrombus extraction device **1102** can include a self-expanding coring element **206** and expandable cylindrical portion **208**. In some embodiments, and as shown in FIG. **11**, the thrombus extraction device **1102** can be the tool **400** that can extend through the valve **104**, and in some embodiments, the valve **104** can be a part of the thrombus extraction device **1102**. Further details of thrombectomy systems, thrombus extraction devices, and methods of using the same are disclosed in: U.S. application Ser. No. 15/268,296, filed Sep. 16, 2016, and entitled "INTRAVASCULAR TREATMENT OF VASCULAR OCCLUSION AND ASSOCIATED DEVICES, SYSTEMS, AND METHODS"; U.S. application Ser. No. 15/498,320, filed Apr. 26, 2017, and entitled "DEVICES AND METHODS FOR TREATING VASCULAR OCCLUSION"; and U.S. application Ser. No. 15/466,740, filed on Mar. 22, 2017, and entitled "DEVICE AND METHOD FOR TREATING VASCULAR OCCLUSION", the entirety of each of which is hereby incorporated by reference herein.

With reference now to FIG. **12**, a side-section view of another embodiment of the hemostasis valve **104** having two piece caps **116**, **120** is shown. The valve **104** can include a housing **128** defining an interior channel **130** through which the tubular member **132** can extend. The valve **104** can include the proximal cap **116** and the distal cap **120**. In some embodiments, the proximal cap **116** can comprise a two piece cap and can include a proximal exterior member **1200** and a proximal channel member **1202**. In some embodiments, the distal cap **120** can comprise a two-piece cap and can include a distal exterior member **1204** and a distal channel member **1206**. In some embodiments, this coupling between the proximal exterior member **1200** and the proximal channel member **1202** and/or the coupling between the distal exterior member **1204** and the distal channel member **1206** can be a sealed coupling so as to prevent the leakage of material including fluid or gas between the respective ones of the proximal exterior member **1200** and the proximal channel member **1202** and/or the distal exterior member **1204** and the distal channel member **1206**. In some embodiments, this sealing coupling can be achieved and/or maintained via a seal such as an O-ring **1208** that can be positioned between the proximal exterior member **1200** and the proximal channel member **1202** and/or between the distal exterior member **1204** and the distal channel member **1206**.

In some embodiments, the proximal exterior member **1200** can be coupled, and in some embodiments, rotatably coupled to the proximal channel member **1202** in a manner to allow the rotation of the proximal exterior member **1200** without rotating the proximal channel member **1202**. Similarly, in some embodiments, the distal exterior member **1204** can be rotatably coupled to the distal channel member **1206** in a manner to allow the rotation of the distal exterior member **1204** without the rotating of the distal channel member **1206**. In some such embodiments, the channel

members **1202**, **1206** can be non-rotatable with respect to the housing **128** and/or the tubular member **132**, and one or both of the exterior members **1200**, **1204** can be rotatable with respect to the housing **128** and/or the tubular member **132**. In such an embodiment, the maintaining of the rotational position of the channel members **1202**, **1206** with respect to the housing **128** and/or the tubular member **132** can prevent the twisting of the tubular member **132** which can result in the sealing of the tubular member **132** regardless of the configuration of the constructing mechanism **141**.

The exterior members **1200**, **1204** can comprise a variety of shapes and sizes and can include a variety of features. In some embodiments, one or both of the exterior members **1200**, **1204** can be coupled to, for example, a shaft similar to the shaft **106** shown in FIG. 1. In some embodiments, for example, the distal exterior member **1204** can be coupled to a shaft **106**, including, for example, can be non-detachably coupled to the shaft **106**. In some embodiments, one or both of the exterior members can include one or several features configured to facilitate coupling with the valve **104**. These one or several features can include, for example, one or several male or female: connectors; couplers; attachment mechanisms; or the like. In some embodiments, these one or several features can facilitate use of the valve with other existing components, instruments, tools, or the like. In some embodiments, for example, one or both of the exterior members **1200**, **1204** can comprise either a male or female luer fitting, and specifically as shown in FIG. 12, the distal exterior member **1204** can comprise a male luer fitting **1210**.

Several aspects of the present technology are set forth in the following examples.

1. A hemostatic valve for sealing a medical device, the hemostatic valve comprising:
an elongate member having a first end, a second end, and a central lumen extending therebetween, wherein the elongate member is pliable;
a reinforcement structure extending along at least a portion of the elongate member, wherein the reinforcement structure is coupled to the elongate member; and
an active tensioning mechanism coupled to the elongate member, wherein the tensioning mechanism is moveable between a first configuration wherein the central lumen is constricted and sealed and a second configuration wherein the central lumen is open.
2. The hemostatic valve of example 1, wherein the elongate member comprises a compliant polymer tube.
3. The hemostatic valve of example 1 or 2, wherein the tensioning mechanism comprises at least one filament extending at least partially around the elongate member.
4. The hemostatic valve of example 3, wherein the reinforcement structure is positioned between the at least one filament and the elongate member.
5. The hemostatic valve of example 4, wherein the reinforcement structure comprises a braided mesh.
6. The hemostatic valve of example 4 or 5, wherein the reinforcement structure is coupled to the elongate member at a position proximate to the first end of the elongate member and at a position proximate to the second end of the elongate member.
7. The hemostatic valve of example 6, wherein the reinforcement structure is not coupled to the elongate member at a position between the first end of the elongate member and the second end of the elongate member.
8. The hemostatic valve of any one of examples 3-7, wherein the tensioning mechanism comprises an actua-

- tor coupled to the at least one filament, wherein the actuator is moveable to control movement of the at least one filament from a first position wherein the central lumen is constricted and sealed to a second position wherein the central lumen is open, wherein the at least one filament is in the first position when the tensioning mechanism is in the first configuration.
9. The hemostatic valve of example 8, wherein the actuator is biased towards the first position.
 10. The hemostatic valve of example 8 or 9, wherein the actuator is biased toward the second position.
 11. The hemostatic valve of any one of examples 8-10, wherein the actuator comprises a manual actuator.
 12. The hemostatic valve of any one of examples 8-11, wherein the at least one filament forms a loop around the elongate member.
 13. The hemostatic valve of any one of examples 8-12, wherein the at least one filament forms a bight around a portion of the elongate member.
 14. The hemostatic valve of any one of examples 8-13, wherein the at least one filament comprises a first filament and a second filament, wherein each of the first filament and the second filament are coupled to the actuator, and wherein the first filament and the second filament are moveable from the first position to the second position.
 15. The hemostatic valve of example 14, wherein each of the first filament and the second filament form a loop around the elongate member.
 16. The hemostatic valve of example 14 or 15, wherein the first filament forms a first bight around a first portion of the elongate member, and wherein the second filament forms a second bight around a second portion of the elongate member.
 17. The hemostatic valve of example 16, wherein the first bight extends through the second bight.
 18. The hemostatic valve of any one of examples 1-17, further comprising a shell defining a first aperture and a second aperture, wherein the elongate member extends from the first aperture to the second aperture and fluidly couples the first aperture and the second aperture.
 19. The hemostatic valve of any one of examples 1-18, wherein the tensioning mechanism is self-adjustable to seal around tools of different sizes extending through the hemostatic valve.
 20. The hemostatic valve of any one of examples 1-19, wherein the central lumen comprises a single lumen.
 21. The hemostatic valve of any one of examples 1-20, wherein the central lumen comprises a plurality of lumens.
 22. A delivery system for intravascular access of a blood vessel within a patient's body, the delivery system comprising:
a catheter having a first end, a second end, and a catheter lumen extending therebetween;
a hemostatic valve coupled to the first end of the catheter, the hemostatic valve comprising:
a tubular member having a first end, a second end, and a central lumen extending therebetween, wherein the central lumen of the tubular member is fluidly coupled with the catheter lumen; and
an active tensioning mechanism coupled to the tubular member, the tensioning mechanism moveable between a first configuration wherein the tensioning mechanism constricts on the central lumen and the

- central lumen is sealed and a second configuration wherein the central lumen is open.
23. The delivery system of example 22, wherein the hemostatic valve further comprises a reinforcement structure extending along at least a portion of the tubular member. 5
 24. The delivery system of example 22 or 23, wherein the reinforcement structure is located between the tensioning mechanism and the tubular member.
 25. The delivery system of example 24, wherein the reinforcement structure comprises a braided mesh. 10
 26. The delivery system of example 24 or 25, wherein the reinforcement structure is coupled to the tubular member at a position proximate to the first end of the tubular member and at a position proximate to the second end of the tubular member. 15
 27. The delivery system of example 26, wherein the reinforcement structure is adhered to the tubular member at the first end of the tubular member and at the second end of the tubular member. 20
 28. The delivery system of example 27, wherein the reinforcement structure is uncoupled to the tubular member between the first end of the tubular member and the second end of the tubular member.
 29. The delivery system of any one of examples 22-28, wherein the tensioning mechanism comprises at least one filament extending at least partially around the tubular member. 25
 30. The delivery system of example 29, wherein the tensioning mechanism comprises an actuator coupled to the at least one filament, wherein moving the tensioning mechanism from the first configuration to the second configuration comprises moving the actuator and the thereto coupled at least one filament from a first position to a second position, wherein the filament constricts and seals the central lumen of the tubular member when the filament is in the first position. 35
 31. The delivery system of example 30, wherein the actuator comprises a manual actuator.
 32. The delivery system of example 31, wherein the actuator comprises a pair of opposing and depressable buttons, wherein the buttons are biased towards an undepressed position. 40
 33. The delivery system of example 31 or 32, wherein the central lumen is sealed when the buttons are in the undepressed position. 45
 34. The delivery system of any one of examples 30-33, wherein the filament comprises a monofilament.
 35. The delivery system of any one of examples 30-34, wherein the filament comprises at least one of: a polymer filament; or a metallic filament. 50
 36. The delivery system of any one of examples 22-35, wherein the catheter comprises a thrombus extraction device.
 37. A method of sealing a delivery device accessing a blood vessel of a patient, the method comprising: inserting the delivery device comprising a catheter and a hemostatic valve into the blood vessel of the patient, the catheter having a first end, a second end, and a catheter lumen extending therethrough, and the hemostatic valve coupled to the first end and having a tubular member defining a central lumen fluidly coupled with the catheter lumen and a tensioning mechanism coupled with the tubular member, wherein the tensioning mechanism collapses and seals the central lumen in a first configuration and thereby seals access to the blood vessel; 55

- moving the tensioning mechanism of the hemostatic valve to a second configuration, wherein the central lumen is open and access to the blood vessel is unsealed when the tensioning mechanism is in the second configuration;
- advancing a shaft of a tool through the delivery device until a first end of the tool reaches a desired position within the blood vessel of the patient and a portion of the shaft is positioned within the central lumen of the tubular member; and
- returning the tensioning mechanism of the hemostatic valve to the first configuration such that the tubular member collapses on the shaft of the tool and seals around the shaft of the tool.
38. The method of example 37, further comprising retracting the shaft of the tool from the delivery device.
39. The method of example 38, wherein the tensioning mechanism is maintained in the first configuration during and after the retracting of the shaft of the tool from the delivery device.
40. The method of example 38 or 39, wherein the tensioning mechanism is moved to the second configuration during the retracting of the shaft of the tool from the delivery device, and wherein the tensioning mechanism is returned to the first configuration after the shaft of the tool is retracted from the delivery device.
41. The method of any one of examples 37-40, wherein the tensioning mechanism comprises at least one filament extending at least partially around the tubular member, wherein the at least one filament collapses the tubular member when the tensioning mechanism is in the first configuration.
42. The method of example 41, wherein the at least one filament circumferentially constricts the tubular member to collapse the tubular member when the tensioning mechanism is in the first configuration.
43. The method of example 41 or 42, wherein the hemostatic valve comprises a reinforcement structure located between the at least one filament and the tubular member.
44. The method of any one of examples 41-43, wherein the at least one filament forms a loop around the elongate member, and wherein moving the tensioning mechanism from the second configuration to the first configuration reduces a size of the loop to thereby constrict the tubular member within the loop.
45. The method of any one of examples 41-44, wherein the filament forms at least one bight around a portion of the elongate member.
46. The method of example 45, wherein the filament comprises a first filament and a second filament, and wherein the at least one bight comprises a first bight oriented in a first direction and formed by the first filament and a second bight oriented in a second direction and formed by the second filament, wherein the first and second bights overlap to encircle a portion of the tubular member within an constricting area.
47. The method of example 46, wherein moving the tensioning mechanism from the second configuration to the first configuration comprises moving the first bight in the first direction and the second bight in the direction to reduce the size of the constricting area and collapse and seal the central lumen of the tubular member.
48. The method of any one of examples 37-47, wherein the tensioning mechanism comprises an actuator, and

wherein moving the tensioning mechanism to the second configuration comprises manipulating the actuator.

49. The method of any one of examples 37-48, further comprising applying a vacuum to the delivery device to aspirate material through the catheter, wherein the central lumen remains sealed during the aspiration.

50. The method of any one of examples 37-49, wherein the tool comprises a thrombus extraction device.

51. A hemostatic valve for sealing a medical device, the hemostatic valve comprising:

an elongate member having a first end, a second end, and a central lumen comprising a plurality of lumens extending therebetween, wherein the elongate member is pliable; and

an active tensioning mechanism coupled to the elongate member, wherein the tensioning mechanism is moveable between a first configuration wherein the central lumen is constricted and sealed and a second configuration wherein the central lumen is open.

Other variations are within the spirit of the present invention. Thus, while the invention is susceptible to various modifications and alternative constructions, certain illustrated embodiments thereof are shown in the drawings and have been described above in detail. It should be understood, however, that there is no intention to limit the invention to the specific form or forms disclosed, but on the contrary, the intention is to cover all modifications, alternative constructions, and equivalents falling within the spirit and scope of the invention, as defined in the appended claims.

In the previous description, various embodiments of the present invention are described. For purposes of explanation, specific configurations and details are set forth in order to provide a thorough understanding of the embodiments. However, it will also be apparent to one skilled in the art that the present invention may be practiced without the specific details. Furthermore, well-known features may be omitted or simplified in order not to obscure the embodiment being described.

The use of the terms “a” and “an” and “the” and similar referents in the context of describing the invention (especially in the context of the following claims) are to be construed to cover both the singular and the plural, unless otherwise indicated herein or clearly contradicted by context. The terms “comprising,” “having,” “including,” and “containing” are to be construed as open-ended terms (i.e., meaning “including, but not limited to,”) unless otherwise noted. The term “connected” is to be construed as partly or wholly contained within, attached to, or joined together, even if there is something intervening. Recitation of ranges of values herein are merely intended to serve as a shorthand method of referring individually to each separate value falling within the range, unless otherwise indicated herein, and each separate value is incorporated into the specification as if it were individually recited herein. All methods described herein can be performed in any suitable order unless otherwise indicated herein or otherwise clearly contradicted by context. The use of any and all examples, or exemplary language (e.g., “such as”) provided herein, is intended merely to better illuminate embodiments of the invention and does not pose a limitation on the scope of the invention unless otherwise claimed. No language in the specification should be construed as indicating any non-claimed element as essential to the practice of the invention.

Preferred embodiments of this invention are described herein, including the best mode known to the inventors for carrying out the invention. Variations of those preferred embodiments may become apparent to those of ordinary

skill in the art upon reading the foregoing description. The inventors expect skilled artisans to employ such variations as appropriate, and the inventors intend for the invention to be practiced otherwise than as specifically described herein. Accordingly, this invention includes all modifications and equivalents of the subject matter recited in the claims appended hereto as permitted by applicable law. Moreover, any combination of the above-described elements in all possible variations thereof is encompassed by the invention unless otherwise indicated herein or otherwise clearly contradicted by context.

All references, including publications, patent applications, and patents, cited herein are hereby incorporated by reference to the same extent as if each reference were individually and specifically indicated to be incorporated by reference and were set forth in its entirety herein.

The invention claimed is:

1. A hemostasis valve, comprising:

a support;

an actuator having at least a first member movably coupled to the support;

a collapsible tubular sidewall defining a lumen carried by the support;

a filament formed in a loop around the tubular sidewall, the filament having at least a first end portion extending away from the loop to the first member; and

a spring configured to move the first member in a direction that pulls the first end portion away from the tubular sidewall, reducing a diameter of the lumen in response to reducing a diameter of the loop.

2. The hemostasis valve of claim 1, further comprising a second member movably coupled to the support.

3. The hemostasis valve of claim 2 wherein the filament further comprises a second end portion extending away from the loop to the second member.

4. The hemostasis valve of claim 3 wherein the first end portion, the loop, and the second end portion are one continuous filament.

5. The hemostasis valve of claim 3 wherein first member and the second member are biased in a direction that places the first end portion and the second end portion under sufficient tension to reduce the diameter of the lumen and provide a seal around a device extending through the lumen.

6. The hemostasis valve of claim 3 wherein the first member and the second member are biased in a direction that places the first end portion and the second end portion under sufficient tension to close the lumen.

7. The hemostasis valve of claim 1 wherein the lumen extends along a longitudinal axis, and wherein the direction is a direction away from the longitudinal axis.

8. The hemostasis valve of claim 1 wherein the lumen extends along a longitudinal axis, and wherein the direction is a direction orthogonal to the longitudinal axis.

9. The hemostasis valve of claim 1 wherein the spring is positioned between the first member and the support.

10. The hemostasis valve of claim 1 wherein the first member is a button.

11. The hemostasis valve of claim 10 wherein the direction is a first direction, and wherein the button is depressible in a second direction to move the first end portion toward the tubular sidewall to increase the diameter of the lumen in response to increasing the diameter of the loop.

12. The hemostasis valve of claim 1 wherein the direction is a first direction, and wherein the first member is actuatable in a second direction to move the first end portion toward the tubular sidewall to increase the diameter of the lumen in response to increasing the diameter of the loop.

23

13. The hemostasis valve of claim 12 wherein the first direction is opposite the second direction.

14. The hemostasis valve of claim 13 wherein the lumen extends along a longitudinal axis, and wherein the first direction and the second direction are orthogonal to the longitudinal axis.

15. The hemostasis valve of claim 1 wherein the actuator further comprises a second member movably coupled to the support, wherein the filament further comprises a second end portion extending away from the loop to the second member, wherein the spring is a first spring, wherein the direction is a first direction, and further comprising a second spring configured to move the second member in a second direction that pulls the second end portion away from the tubular sidewall, reducing the diameter of the lumen in response to reducing the diameter of the loop.

16. The hemostasis valve of claim 15 wherein the first direction is opposite to the second direction.

17. The hemostasis valve of claim 15 wherein the first member is actuatable in the second direction and/or the second member is actuatable in the first direction to move the first end portion toward the tubular sidewall to increase the diameter of the lumen in response to increasing the diameter of the loop.

18. An aspiration catheter system, comprising:
an aspiration catheter defining a lumen and having a proximal end portion; and
a hemostasis valve comprising—
a support;
an actuator having at least a first member movably coupled to the support;
a collapsible tubular sidewall defining a lumen carried by the support, wherein the lumen of the tubular sidewall is selectively fluidly coupleable to the lumen of the aspiration catheter;

24

a filament formed in a loop around the tubular sidewall, the filament having at least a first end portion extending away from the loop to the first member; and

a spring configured to move the first member in a direction that pulls the first end portion away from the tubular sidewall, reducing a diameter of the lumen in response to reducing a diameter of the loop to fluidly decouple the lumen of the tubular sidewall from the lumen of the aspiration catheter.

19. The aspiration catheter system of claim 1 wherein the direction is a first direction, and wherein the first member is actuatable in a second direction to move the first end portion toward the tubular sidewall to increase the diameter of the lumen in response to increasing the diameter of the loop to fluidly couple the lumen of the tubular sidewall to the lumen of the aspiration catheter.

20. A hemostasis valve, comprising:

- a support;
- a button movably coupled to the support;
- a collapsible tubular sidewall carried by the support and defining a lumen;
- a filament formed in a loop around the tubular sidewall, the filament having at least a first end portion extending away from the loop to the button; and
- a biasing member positioned between the support and the button, wherein the biasing member is configured to bias the button in a direction that pulls the first end portion away from the tubular sidewall to reduce a diameter of the loop to thereby reduce a diameter of the lumen.

* * * * *