



US 20160209885A1

(19) **United States**

(12) **Patent Application Publication**  
**ELLIS**

(10) **Pub. No.: US 2016/0209885 A1**

(43) **Pub. Date: Jul. 21, 2016**

(54) **POWER ADAPTER UNIT WITH  
INTEGRATED INPUT/OUTPUT INTERFACE,  
AND PORTABLE ELECTRONIC DEVICE  
WITH STORAGE RECESS FOR  
MULTIFUNCTION POWER ADAPTER**

(30) **Foreign Application Priority Data**

Oct. 4, 2013 (GB) ..... 1317624.3

**Publication Classification**

(71) Applicant: **AQUATERRA LIMITED**, Tetbury  
Gloucestershire (GB)

(51) **Int. Cl.**  
**G06F 1/16** (2006.01)  
**G06F 1/18** (2006.01)

(72) Inventor: **Julian Richard ELLIS**, Tetbury,  
Gloucestershire (UK)

(52) **U.S. Cl.**  
CPC ..... **G06F 1/1684** (2013.01); **G06F 1/189**  
(2013.01)

(73) Assignee: **AQUATERRA LIMITED**, Tetbury,  
Gloucestershire (GB)

(57) **ABSTRACT**


(21) Appl. No.: **15/025,338**





A multifunctional adapter or interface unit for a portable electronic device, the adapter unit being stored or stowable within the portable electronic device and being operable as a power adaptor, user input/output device, and/or data transfer unit. The power adaptor includes a plug body with a retractable tray for storing a user input/output device, e.g. a peripheral device such as earphones.

(22) PCT Filed: **Oct. 1, 2014**

(86) PCT No.: **PCT/GB2014/052968**

§ 371 (c)(1),  
(2) Date: **Mar. 28, 2016**








Fig. 2C




Fig. 3A




Fig. 3B








Fig. 3C






Fig. 5




Fig. 6




Fig. 7A




Fig. 7B




Fig. 7C




Fig. 8A

Fig. 8B

Fig. 8C




Fig. 9






Fig. 10A




Fig. 10B

**POWER ADAPTER UNIT WITH  
INTEGRATED INPUT/OUTPUT INTERFACE,  
AND PORTABLE ELECTRONIC DEVICE  
WITH STORAGE RECESS FOR  
MULTIFUNCTION POWER ADAPTER**

TECHNICAL FIELD

**[0001]** The invention relates to devices (e.g. power adapters, data ports and data plugs, audio ports and audio jacks, etc.) which provide a connection between portable electronic devices (e.g. smartphone, MP3 player, etc.) and associated peripheral devices (e.g. earphones, USB ports, etc.) and/or external power supplies.

BACKGROUND TO THE INVENTION

**[0002]** Portable electronic devices providing a plurality of functions such as telephone and internet connectivity, music and video playback are well known. Such devices usually require a power adapter for recharging a battery from a mains power supply or via a USB connection and a set of earphones for a user to listen to an audio output signal. When travelling for extended periods, it is often necessary to transport the power adapter and the set of earphones in addition to the portable electronic device itself. In some cases the power adapter and earphones can take up more space than the portable electronic device itself.

**[0003]** Space saving designs for power adapters, earphones and the like to increase their portability are already known. For example, WO 2006/016119 discloses a design for a 3-pin plug with foldable pins and CN 2396594 discloses a telephone handset with a inbuilt cavity for storing earphones and associated wiring. Devices with retractable USB plugs are also known.

SUMMARY OF THE INVENTION

**[0004]** At its most general, the present invention provides a multifunctional adapter or interface unit for a portable electronic device, the adapter unit being stored or stowable within the portable electronic device and preferably being capable of providing a plurality of different connection functions for the portable electronic device depending on its physical configuration.

**[0005]** According to a first aspect of the invention, there is provided a portable electronic device comprising a main body, and a multifunction interface unit communicably connectable to the main body via a cable, wherein the main body includes a recess for storing the interface unit, and wherein the multifunction interface unit is selectively operable as a power adapter and a user input/output device.

**[0006]** Herein the term “power adapter” may mean a unit for transferring and, optionally, transforming power from an external power source (e.g. mains power) to the portable electronic device, e.g. for purpose of recharging a battery. For example, the power adapter may be an AC/DC adapter, having a transformer or rectifier integrated therewith. Alternatively or additionally, the power adapter may function to transfer power from an external supply (either DC or AC) into a portable electronic device, with or without transforming that power. For example, the power adapter may function to connect the portable electronic device to a laptop or desktop computer, from which a DC power signal is available.

**[0007]** The term “user input/output device” may mean a unit that operate to transfer and, optionally, transform signals

to and/or from the portable electronic device for use by a user. For example, the user input/output device may be a pair of earphones, which act to transfer an audio signal to a user. Alternatively, the user input/output device may comprise a USB adapter plug and cable for conveying data into or out of the portable electronic device. In principle the user input/output device may be any unit suitable for transferring audio, video or data traffic between a user (or other external device) and the portable electronic device.

**[0008]** The main body is the housing of the portable electronic device which contains the functional components thereof, e.g. processor, memory, display, etc. Incorporating a multifunction interface unit into the main body provides a complete self-contained portable entity, i.e. it is not necessary for the user to remember to carry additional components in order to use all of the functions of the device.

**[0009]** The device may include a mode selector arranged to configure the circuitry of the device according to a selected function of the multifunction interface unit. The mode selector may be mounted on or part of the main body. The mode selector may communicate, electronically and/or physically, with the multifunction interface unit. The plurality of selectable functions may permit the portable electronic device to interface or interact with other entities. For example, the multifunction interface unit may enable the portable electronic device to connect to an external power supply (e.g. mains power) or to other computing devices (via a USB connection or the like). Furthermore, the multifunction interface unit may provide additional peripheral user input/output means, such as audio (e.g. via earphones), or a computer mouse or the like. According to the invention, the interface to these additional functions can be inbuilt, i.e. stowable in the device when not need. Moreover, the device can be easily configurable to adapt to the selected function.

**[0010]** The portable electronic device may be a laptop computer, tablet computer, smartphone, MP3 player, cell phone, or any other portable electronic device. The main body may be a conventional handset or casing, save for the recess to house the multifunction interface unit and the mode selector.

**[0011]** The mode selector may be a physical switch or dial operable by the user. Alternatively, the mode selector may operate automatically, e.g. via software instructions running in the portable electronic device, based on a detected configuration of the multifunction interface unit.

**[0012]** The main body may include a battery. As mentioned above, the multifunction unit may be operable as a power adapter, whereby it performs a battery recharge function.

**[0013]** In order to execute the battery recharge function, the multifunction interface unit may include a power adapter plug portion that is receivable in a mains power socket. For example, the power adapter plug portion may include a body having a pair of terminal pins protruding therefrom, wherein the pair of terminal pins are shaped and spaced to be receivable in a mains power socket (e.g. a two-pin or three-pin mains power socket). The power adapter plug portion may be connected to the device via a cable containing wiring suitable for conveying a power signal for recharging the battery. The power adapter plug portion may include a transformer for converting an AC mains signal into a DC power signal. The mode selector may be arranged to configure the circuitry of the device to pass the power signal from the power adapter plug portion to the battery.

**[0014]** If the multifunction interface unit operates as a user input/output device, it may execute a peripheral communica-

tion function, i.e. it may control or facilitate communication between the portable electronic device and an external peripheral device. Herein the term "peripheral device" may have its conventional meaning, i.e. any device that is used to send or receive information from a computing device. According to the invention, the multifunction interface unit may comprise one or more peripheral devices. For example, the multifunction interface unit may comprise a pair of earphones or a USB plug adapter. Each peripheral device may be communicably connectable, e.g. via a cable and suitable adapter plug (e.g. USB adapter or jack), to the power adapter plug portion when the power adapter plug portion is stowed in the recess of the portable electronic device.

**[0015]** The multifunction interface unit may include a peripheral storage portion in which the peripheral device is stowable when not in use. The peripheral storage portion may be part of the power adapter plug portion. For example, the body of the power adapter plug portion may have a retractable tray slidably or pivotably mounted therein. The tray may be arranged to receive one or more peripheral components, such as a pair of earphones. The peripheral component may be communicably connected to the handset wirelessly (e.g. using the Bluetooth® protocol) or via a cable.

**[0016]** Alternatively or additionally, the peripheral storage portion may be separate or separable from the multifunction interface unit. For example, the peripheral storage portion may include a data transfer component for inserting into a data communication port on another computing device to enable data communication between the portable electronic device and the other computing device. The data transfer component may be or may be capable of insertion into a port on another computing device. For example, the data transfer component may be a USB plug (e.g. a USB type A connector).

**[0017]** The multifunction interface unit may comprise a power adapter plug body (e.g. containing a peripheral device storage portion as discussed above), a data transfer connector, e.g. USB plug, and a cable connected between the power adapter plug body and data transfer connector. The recess in the main body of the portable electronic device may be arranged to receive all of the power adapter plug body, cable and data transfer component. Preferably, the recess includes terminal connectors arranged so that the plug adapter body and the data transfer connector and operably connected to the portable electronic device when the multifunction interface unit is stowed in the recess. In this way, the device may automatically select the relevant function for the multifunction interface unit depending on which connections in the recess are detected to be present. Thus, if the data transfer connector is detached but the power adapter plug remains connected, the multifunction interface unit operates as a data transfer unit. If the data transfer component is connected and the power adapter unit detached, the multifunction interface unit operates as a power adapter. In this arrangement, the capable thus has a dual functionality, depending on the operation mode of the multifunction interface unit.

**[0018]** If the power adapter plug body includes a peripheral device storage portion, e.g. retractable tray, this is preferably accessible while the power adapter plug body is secured in the recess. The peripheral device may thus be accessed independently of the power adapter plug. Again, the portable electronic device may detect the configuration in which the peripheral device is detached but the power adapter plug and

data transfer connector remain connected. In this configuration, the multifunction interface unit thus operates as a user input/output device.

**[0019]** The multifunction interface unit may include a controller portion for sending user instructions to the main body of the portable electronic device (sometimes referred to herein as the handset). For example, the controller portion may include volume control push buttons and/or a locking switch. The controller portion may be located on an outer side of the handset when the multifunction interface unit is stowed therein so that the controller portion are accessible in use. The peripheral storage portion may be part of the controller portion. For example, the controller portion may include a retractable tray as mentioned above. In one embodiment, the controller portion may comprise a retractable data transfer component, e.g. a retractable plug, such as a USB plug or the like.

**[0020]** The controller portion may be separate from the power adapter plug portion. The controller portion may be connected to the handset by a first length of cable, and the power adapter plug portion (and its associated peripheral component) may be connected to the controller portion by a second length of cable. The cable may be configured to carry the necessary signals to or from a handset depending on the selected mode of operation.

**[0021]** The main body may include a recessed channel around its side surfaces to store the cable. The cable may comprise a flat sheath that encapsulates the wiring, wherein the flat sheath is shaped to fit snugly in the recessed channel. This may facilitate alignment of the cable in the channel and can improve the appearance of the main body (e.g. mobile phone handset). In one embodiment, the cable may be magnetically retainable in the recessed channel, e.g. using one or more magnets in the main body, which attract corresponding magnets mounted in the cable itself.

**[0022]** Alternatively, the cable may comprise a plurality of rigid portions that are retainable in a folded stack configuration for storage in a corresponding recess in the portable electronic device.

**[0023]** The cable itself may include a split portion comprising a pair of separable cable strands, e.g. for delivering audio signals to a respective earphone. The pair of separable cable strands may be connected together so that the split portion resembles a single cable. The connection may be physical, but preferably the pair of separable cable strands are arranged to be magnetically attracted together.

**[0024]** The power adapter plug portion itself may be an independent aspect of the invention. According to this aspect, there may be provided a power adapter unit for a portable electronic device, the power adapter unit comprising: a plug body having a plurality of terminal pins shaped as spaced to be receivable in a mains power socket; a cable connected to the plug body for conveying an electrical signal received through the plurality of terminal pins; a user input/output device; and a retractable storage tray in the plug body for holding the user input/output device. The user input/output device may be a peripheral device as described above, e.g. a pair of earphones or the like. The retractable tray may include a recess shaped to receive the earphones. The pair earphones may be separable from the plug body, when in use.

**[0025]** The cable connected to the plug body may also be connected to the user input/output device. For example, the cable may comprise a pair of cable strands, each cable strand being of a respective one of the pair of earphones. The cable

may thus be arranged to convey a power signal from the plurality of terminal pins when the user input/output device is stored in the storage tray, and to convey a communication signal to the user input/output device when the user input/output device is removed from the storage tray. For example, the cable may convey an audio signal to the earphones. To achieve this, the storage tray may include one or more electric terminals that physically contact and electrically connect to corresponding electric connections on the user input/output device when mounted in the storage tray. The recess in the storage tray may be arranged to ensure safe and repeatable contact. For example, when the user input/output device is a pair of earphones, the one or more electric terminals may be provided on a collar in the recess that receives the neck of the earphone. An electric connection may thus be provided on the neck of the earphone to convey the power signal to the cable. The electric connection on the neck of the earphone may be isolated or shielded from the audio components in the earphone. Alternatively, the electric connection may be switched based on the output from a control device, e.g. a microchip mounted in the earphones that is controllable via the main body.

**[0026]** The connector portion discussed above may also be understood as an independent concept presented herein. According to this concept, there may be provided a peripheral cable interface for a portable electronic device, the peripheral cable interface comprising a body connectable between a peripheral component and the portable electronic device by a first cable and a second cable respectively, the body including a first body portion having a first cable port for receiving the first cable and a second body portion having a second cable port for receiving the second cable, wherein the first body portion and second body portion are rotatable relative to each other between a storage configuration in which the first cable port and second cable port are at the same end of the body and a use configuration in which the first cable port and second cable port are at different ends of the body. The peripheral cable interface may be mountable in a recess in the portable electronic device when in the storage configuration.

**[0027]** The peripheral cable interface may include a user interface arranged to communicate user instructions to the portable electronic device. The user interface may be used to control audio volume, etc.

**[0028]** The peripheral cable interface may include a data transfer component (e.g. USB connector) for inserting into a USB port on another computing device to enable data communication between the portable electronic device and the other computing device.

#### BRIEF DESCRIPTION OF THE DRAWINGS

**[0029]** Embodiments of the invention are described in detail below with reference to the accompanying drawings, in which:

**[0030]** FIG. 1A is a front perspective view of a smartphone that incorporates a multifunction interface unit that is an embodiment of the invention;

**[0031]** FIG. 1B is a rear perspective view of the smartphone shown in FIG. 1A;

**[0032]** FIG. 2A shows a power adapter plug portion of the multifunction interface unit when removed from the smartphone of FIG. 1A;

**[0033]** FIG. 2B shows the power adapter plug portion of FIG. 2A with a peripheral storage tray pivoted outward therefrom;

**[0034]** FIG. 2C shows the power adapter plug portion of FIG. 2B with a pair of earphones removed from the peripheral storage tray;

**[0035]** FIG. 3A shows a rear perspective view of the smartphone with the power adapter plug portion removed;

**[0036]** FIG. 3B shows a rotatable selector dial on the back of the smartphone of FIG. 3A;

**[0037]** FIG. 3C shows a close-up view of the rotatable selector dial;

**[0038]** FIG. 4A shows a controller portion of the multifunction interface unit in a storage configuration when removed from the smartphone of FIG. 1A;

**[0039]** FIG. 4B shows the controller portion of FIG. 4A in a data transfer plug deployed configuration;

**[0040]** FIG. 4C shows a transition of the controller portion of FIG. 4A from the storage configuration towards an earphone deployed configuration;

**[0041]** FIG. 4D shows the controller portion of FIG. 4A in the earphone/power adapter plug deployed configuration;

**[0042]** FIG. 5 shows the relatively rotatable components of the controller portion of FIG. 4A;

**[0043]** FIG. 6 shows an exploded view of the controller portion of FIG. 4A;

**[0044]** FIG. 7A shows a multifunction power adapter plug that is another embodiment of the invention;

**[0045]** FIG. 7B shows the multifunction power adapter plug of FIG. 7A with its hinged cover in an open position;

**[0046]** FIG. 7C shows the multifunction power adapter plug of FIG. 7A with a slidable peripheral storage tray partially extracted therefrom;

**[0047]** FIGS. 8A and 8B show left and right side views respectively of a multifunction power adapter plug that is another embodiment of the invention;

**[0048]** FIG. 8C is a perspective view of a smartphone having the multifunction power adapter plug of FIGS. 8A and 8B mounted in a side edge recess thereof;

**[0049]** FIG. 9 is a right side view of a multifunction power adapter plug that is another embodiment of the invention;

**[0050]** FIG. 10A is a perspective view of a multifunction power adapter plug that is another embodiment of the invention; and

**[0051]** FIG. 10B is a perspective view of a smartphone having the multifunction power adapter plug of FIG. 10A mounted in a back surface recess thereof.

#### DETAILED DESCRIPTION; FURTHER OPTIONS AND PREFERENCES

**[0052]** FIG. 1A shows a smartphone **100** having a multifunction interface unit that is an embodiment of the invention. Although the invention is illustrated herein with reference to a smartphone, it can be appreciated that it is applicable to any consumer electronic device, especially portable electronic devices such as laptop computers, tablet computers, etc.

**[0053]** The smartphone **100** may be operable in a conventional manner, e.g. by a touch screen **102** and button **104**. The multifunction interface unit is housed within the smartphone body. As described below, in this embodiment the multifunction interface unit has two parts. The first part is a power adapter plug portion **200** (shown in FIGS. 2A to 2C) and the second part is a controller portion **300**. The smartphone **100** is connected to the controller portion **300** by a first length of cable (not shown in FIGS. 1A and 1B). The controller portion **300** is connected to the power adapter plug portion **200** by a second length of cable (also not shown). The body of the

smartphone **100** includes a recessed channel **106** around its sides for receiving the first and second lengths of cable. The cable is connected, either permanently or removably, to the smartphone **100** at the end of the recessed channel **106**.

[0054] In a preferred embodiment, the first and second lengths of cable comprises a flat sheath made of a suitable flexible material (e.g. silicone rubber) in which the conductive wire elements are embedded. The cable may be retained in the channel **106**. In a preferred embodiment, the cable may be retained in the channel **106** using magnets, which facilitate alignment.

[0055] As shown in FIG. 1B, the multifunction interface unit is mounted along the bottom side of the smartphone **100**. The controller portion **300** is mounted at the edge of the smartphone so that it presents an outer surface at the edge of the smartphone. This outer surface may have control buttons, e.g. for volume, or a phone lock switch, which operate in a conventional manner.

[0056] The smartphone **100** includes a stand **400** that pivots out of a recess **108** in the back surface of the body of the smartphone **100**. The stand **400** also functions as the handle of a rotatable selector dial discussed below with reference to FIGS. 3A to 3C.

[0057] FIG. 2A illustrates the power adapter plug portion **200** after it is removed from the body of the smartphone **100**. The power adapter plug portion **200** comprises a body **201** having two pins **202** projecting from one end thereof. The pins **202** may be shaped and spaced in a manner to fit a conventional two-pin plug socket. As shown in FIG. 3A, the body of the smartphone includes a pair of slots **110** for receiving the pins **202** when the power adapter plug portion **200** is stored therein.

[0058] The body **201** of the power adapter plug portion **200** stores the necessary circuitry to transmit a power signal from the pins **202** to the cable **206**. In this embodiment, the body **201** also houses a peripheral storage tray **208**, which is pivotable in and out of the body **201** on a hinge **204**. FIG. 2B shows the peripheral storage tray **208** partly rotated out of the body **201**. In this embodiment, a pair of earphones **210** are stored in the peripheral storage tray **208**. FIG. 2C shows the peripheral storage tray **208** fully rotated out of the body **201** and the earphones **210** removed. The peripheral storage tray **208** includes a recessed pocket **212** for receiving the earphones **210**.

[0059] The cable **206** comprises two separate strands. Each strand is attached to a respective earphone **210**. One or both cable strands are capable of transmitting the power signal from the power adapter plug portion **200** to the smartphone and conveying an audio signal from the smartphone to the earphones **210**. The function performed by the cable **206** may depend of the position of the rotatable selector dial, as discussed below. To make electrical contact between the pins **202** and the wiring in the cable **206**, the recessed pocket **212** in the peripheral storage tray **208** may include an electric terminal **214** at a position where it contacts a corresponding terminal **216** on the collar of one or both earphones **210**. The circuitry may be arranged to shield or isolate the earphones **210** from the power signal. Each cable may carry four or more separate conductive wires. Each wire can be used to carry a power signal, data signal or an audio signal. The signals can be shared across the wires, or a cable may carry two signals, e.g. an audio signal and a control signal on different pairs of wires in the cable.

[0060] FIGS. 3A to 3C illustrate the configuration and function of the rotatable selector dial **402**, which is operated using the handle **400**. The handle **400** is pivotable about the rotatable selector dial **402** between a protruding position (as shown in FIGS. 3A to 3C) and a stored position, in which it is seated in recess **108**. The position of the rotatable selector dial **402** sets the internal circuitry of the smartphone **100** to ensure that it is correctly configured to send and/or receive an appropriate signal along the cable from the multifunction interface unit.

[0061] The circled section in FIG. 3B is shown in close up in FIG. 3C. In this embodiment, the rotatable selector dial **402** is movable between three positions, which represent respective functions of the multifunction interface unit. The first function **404** is for charging the battery of the smartphone. Here the internal circuitry of the smartphone is configured to convey a power signal received from the power adapter plug portion to recharge the battery. The second function **406** is for USB functionality. Here the internal circuitry of the smartphone is configured to send and receive data communication signals from a USB plug on the controller portion **300** (discussed below). The third function **408** is for earphone operation. Here the internal circuitry of the smartphone is configured to send an audio signal to the earphones **210**.

[0062] The rotatable selector dial **402** may include one or more actuating protrusions which interface with the body **201** in different ways depending on the position of the dial. For example, when the rotatable selector dial **402** selects third function **408**, an actuating protrusion may extend into the body **201** to release the tray **208** without disturbing the position of the body **201** in the smartphone **100**. For the first and second functions, the rotatable selector dial **402** may include actuating protrusions which act to push or lever the body **201** or controller portion **300** out of the recess in the smartphone **100**. The handle **400** may be further pivotable when in these positions to cause the actuating protrusions to extend further into the recess. There may be a restrictive collar around the rotatable selector dial **402** which inhibits further such pivoting of the handle **200** unless it is properly aligned in the position of the relevant function.

[0063] FIGS. 4A to 4D shows the controller portion **300** of the multifunction interface unit after it has been removed from the smartphone **100**. FIG. 4A shows the controller portion **300** in a storage configuration, in which it can be stowed in the smartphone **100**. In this configuration, the controller portion **300** receives two lengths of cable **206**, **306** into the same end thereof. The first length of cable **306** connected the controller portion **300** to the smartphone. The second length of cable **206** connects the controller portion **300** to the power adapter plug portion **200**.

[0064] The controller portion **300** itself comprises a cuboidal body **301** made from two triangular prisms **303**, **305** which can be twisted relative to one another about a central pivot point as shown in FIG. 4C. The first length of cable **306** connects to a first triangular prism **303**, and the second length of cable **206** connects to a second triangular prism **305**. Twisting the two triangular prisms **303**, **305** about 180° relative to each other therefore causes the lengths of cable **206**, **306** to extend from opposite ends of the controller portion **300** as shown in FIG. 4D. In this configuration, the controller portion **300** can be used as a quasi-remote volume control on a cable that extends from the smartphone **100** to the earphones **210**.

[0065] The controller portion **300** includes a slider **308** on the first triangular prism **303**. The slider **308** is operable to

extend and retract a data transfer plug **310** from the body **301**. FIG. **4B** shows the data transfer plug **310** in an extended position ready for use. The data transfer plug may be capable of insertion into a USB port.

[0066] The second triangular prism **305** includes a data transfer port **312**, e.g. a USB port. When the slider **308** is retracted, electrical contacts **314** on the bottom surface of the data transfer plug **310** align with and electrically connect to corresponding contact on the second triangular prism **305**, whereby data communication signals received in the data transfer port **312** can be conveyed to the smartphone using the same circuitry as the data transfer plug **310**.

[0067] FIG. **5** shows a view of the controller portion **300** in which the first and second triangular prisms **303**, **305** are separated. The first triangular prism **303** includes a projecting post **316** which is received in a corresponding recess in second triangular prism **305**. The first and second triangular prisms **303**, **305** are relatively rotatable about the post **316**.

[0068] Electrical connection between the first and second triangular prisms **303**, **305** is achieved using a pair of electrical terminals **318** on the first triangular prism **303**, which overlie and electrically connect to corresponding electrical terminals on the second triangular prism **305**, and a male coaxial connector **320** on the first triangular prism **303**, which is rotatably mounted in a corresponding female connector (not shown) on the second triangular prism **305**. The coaxial connector forms a permanent electrical connection through the controller portion **300**, whereas the electrical terminals **318** form a connection only when the triangular prisms are aligned.

[0069] FIG. **6** shows an exploded view of the connector portion **300**, which illustrates how the data transfer plug **310** can be formed in one piece with the slider **308** to move relative to the first and second triangular prisms **303**, **305**.

[0070] FIGS. **7A**, **7B** and **7C** show a multifunction plug adapter **500** that is another embodiment of the invention. The plug adaptor **500** comprises a cuboidal body **501** having a pair of terminal pins **502** projecting from a front edge thereof. The body **501** is hollow, and has a slidable tray **504** mounted therein (see FIG. **7C**). The rear edge of the body **501** comprises a cover **506** that is connected to a corner of the housing at a living hinge **508** which permits the cover **506** to pivot between a closed position (shown in FIG. **7A**) and an open position (shown in FIG. **7B**).

[0071] The cover **506** has a slidable button **510** on its outer surface which operates a catch **512** on the inside surface thereof. The catch **512** cooperates with a recess of the slidable tray to secure the cover **506** to the tray when in the closed position. The catch **512** may be biased into engagement with the recess.

[0072] As shown in FIGS. **7B** and **7C**, the slidable tray **504** is connected to the underside of the cover **506** by an arm **514**. A first end of the arm **514** is pivotably attached to the underside of the cover **506** at a first living hinge **516**, and a second end of the arm **514** opposite to the first end is pivotably attached to the slidable tray **504** at a second living hinge **518**. In operation, the arm **514** permits a limited sliding range for the tray **504**, whereby the tray is prevented from leaving the body **501**. There is a recess **520** in the top surface of the slidable tray **504** shaped to receive the arm **514** when the cover **506** is in the closed position.

[0073] Similarly to the arrangement discussed with reference to FIGS. **2A**, **2B** and **2C** above, the slidable tray **504** includes a shaped pocket **522** for receiving a pair of earphones

**524**. A cable **526** (e.g. a pair of cables magnetically retained together as discussed above) for the earphones extend through an opening formed by gaps in the corners of the slidable tray **504** and body **501** respectively.

[0074] The other end of the cable **526** is connected or connectable to a portable electronic device (e.g. smartphone, tablet, laptop, MP3 player, etc.). The cable **526** may terminate at a USB plug. The cable is capable of performing two functions: (i) audio data signal delivery to the earphones (e.g. from the portable electronic device), and (ii) power (recharging) signal delivery from the power adapter plug (e.g. to the portable electronic device). The slidable tray **504** may include a collar **530** at the gap in its corner for engaging the cable **526**, e.g. in an interference fit. The collar **530** may have power connector portions (e.g. operating inductively or conductively) for transferring power into the cable **526**.

[0075] The multifunction plug adapter **500** shown in FIGS. **7A**, **7B** and **7C** may be mountable in a recess formed in the side edge surface of a portable electronic device (e.g. smartphone **600**) as shown in FIGS. **8A**, **8B** and **8C**. The cable **526** may be arranged to adopt a folded stack configuration. The folded stack configuration may be formed from a plurality of rigid cable sub-portions, which retained one on top of another e.g. used magnets or the like. Each rigid cable sub-portion is separated from its nearest neighbour by a flexible joint, whereby the cable forms a repeating "S" pattern up the folded stack.

[0076] A USB plug **532** is attached at the end of the cable opposite to the body **501**.

[0077] The smartphone **600** may include a recess (not shown) similar to that discussed above with reference to FIG. **3A** for receiving the body **501** of the plug adapter **500**. The body **501** may be retained in the recess by means of a mechanical catch, which is releasable by operation of slider **602**.

[0078] The smartphone **600** may further include a narrow recessed channel shaped to receive the cable **526** in the folded stack configuration. The recessed channel may have a depth selected to ensure that the cable formed part of the side edge of the smartphone when stored therein. This configuration also means that the cover **506** of the body is directly accessible on the side edge of the smartphone **600**. The button **510** on the cover can thus be operated independently of the slider **502**, whereby the earphones can be extracted without removing the body **501** from the smartphone.

[0079] The recessed channel may have a USB port at its base for receiving the USB plug **532**. Thus, when the multifunction plug adapter is stored in the smartphone **600**, the USB plug **532** is operatively connected to the smartphone **600**. This configuration enables the multifunction plug adaptor to be ready for use with either the earphones or the power adapter. If the earphones are extracted from the body, the USB port acts as an output unit, whereby audio signals are sent from the smartphone through the USB plug. Alternatively, if the power plug adapter is extracted, the USB port acts as an input unit, for deliver a power (recharge) signal into the smartphone. In a further development, the USB plug **532** may be detached from the smartphone **600** while the plug adapter body **501** and earphones are stowed. In this arrangement the multifunction unit may operate as a data transfer unit, to permit the smartphone to be connected to another computing device, whereby data signals can be sent through the cable into and out of the smartphone. In this arrangement, the recess for receiving the plug adapter body **501** may be provided with

suitable electrical connections to enable data signals to be transferred to and from the cable 526.

**[0080]** FIG. 9 shows the multifunction plug adapter 500 of FIGS. 7A, 7B and 7C with an alternative folded stack configuration for the cable 526. In this arrangement, the rigid cable sub-portions are arranged vertically rather than horizontally. This allows them to be longer, which may improve the speed with which the cable can be stored.

**[0081]** FIGS. 10A and 10B shows the multifunction plug adapter 500 of FIGS. 7A, 7B and 7C with yet another cable storage configuration. In this embodiment, the body 501 of the plug adapter is receivable in a recess formed in the top edge surface of the smartphone 600. The cover 506 and button 510 are directly accessible as explained above. The slider 602 for releasing the plug adapter body 501 is located on the side edge of the smartphone 600.

**[0082]** The cable 526 in this embodiment is stored in a planar configuration which can lie against (and be secured, e.g. magnetically, to) the rear surface of the smartphone 600.

**[0083]** Aspects of the disclosure presented herein may be summarised by the following statements:

**[0084]** A portable electronic device comprising: a main body, and a multifunction interface unit communicably connected to the main body via a cable, the multifunction interface unit providing a plurality of selectable functions, wherein the main body includes a recess for storing the interface unit.

**[0085]** A portable electronic device as described above including a mode selector arranged to configure the circuitry of the device according to a selected function of the multifunction interface unit.

**[0086]** A portable electronic device as described above, wherein the mode selector is a physical switch or dial.

**[0087]** A portable electronic device as described above, wherein the main body houses: a user input/output interface; a processor; a memory; software instructions stored on the memory and executable by the processor, wherein the software instructions include instructions for configuring operation of the portable electronic device according to a setting of the mode selector.

**[0088]** A portable electronic device as described above, wherein the main body includes a battery, and the plurality of selectable functions includes a battery recharge function and a peripheral communication function.

**[0089]** A portable electronic device as described above, wherein the multifunction interface unit includes a power adapter plug portion that is receivable in a mains power socket.

**[0090]** A portable electronic device as described above, wherein the power adapter plug portion includes a body having a plurality of terminal pins protruding therefrom, wherein the plurality of terminal pins are shaped and spaced to be receivable in a mains power socket.

**[0091]** A portable electronic device as described above, wherein the power adapter plug portion includes a peripheral storage portion.

**[0092]** A portable electronic device as described above, wherein the peripheral storage portion a retractable tray slidably or pivotably mounted in the power adapter plug portion, the retractable tray being arranged to receive one or more peripheral components.

**[0093]** A portable electronic device as described above, wherein the one or more peripheral components is a pair of earphones.

**[0094]** A portable electronic device as described above, wherein the cable is arranged to convey an audio signal from the portable electronic device or a power signal to the portable electronic device.

**[0095]** A portable electronic device as described above, wherein the multifunction interface unit is permanently connected to the main body via the cable.

**[0096]** A portable electronic device as described above including a peripheral storage portion that is separate or separable from the multifunction interface unit.

**[0097]** A portable electronic device as described above, wherein the peripheral storage portion includes a data transfer component for inserting into a data communication port on another computing device to enable data communication between the portable electronic device and the other computing device.

**[0098]** A portable electronic device as described above including a controller portion for sending user instructions to the handset.

**[0099]** A portable electronic device as described above, wherein the main body includes a recessed channel around its side surfaces to store the cable.

**[0100]** A portable electronic device comprising: a main body, and a multifunction interface unit communicably connected to the main body via a cable, the multifunction interface unit providing a plurality of selectable functions, wherein the main body includes a recessed channel around its side surfaces to store the cable.

**[0101]** A portable electronic device as described above, wherein the cable is magnetically retainable in the recessed channel.

**[0102]** A portable electronic device as described above, wherein the cable includes a split portion comprising a pair of separable cable strands, wherein the pair of separable cable strands are arranged to be magnetically attracted together.

**[0103]** A portable electronic device as described above, wherein the cable comprises a flat sheath that encapsulates electrically conductive wiring.

**[0104]** A power adapter unit for a portable electronic device, the power adapter unit comprising: a plug body having a plurality of terminal pins shaped as spaced to be receivable in a mains power socket; a cable connected to the plug body for conveying an electrical signal received through the plurality of terminal pins; and a peripheral storage portion in the plug body, the peripheral storage portion being arranged to hold a peripheral component.

**[0105]** A power adapter unit as described above, wherein the peripheral component is a pair of earphones, whereby the peripheral storage portion includes a recess shaped to receive the earphones.

**[0106]** A power adapter unit as described above, wherein the peripheral storage portion includes one or more electric terminals that physical contact and electrically connect to corresponding electric connections on the peripheral component when mounted in the peripheral storage portion.

**[0107]** A peripheral cable interface for a portable electronic device, the peripheral cable interface comprising a body connectable between a peripheral component and the portable electronic device by a first cable and a second cable respectively, the body including: a first body portion having a first cable port for receiving the first cable, and a second body portion having a second cable port for receiving the second cable, wherein the first body portion and second body portion are rotatable relative to each one between a storage configura-

ration in which the first cable port and second cable port are at the same end of the body and a use configuration in which the first cable port and second cable port are at different ends of the body.

**[0108]** A peripheral cable interface as described above including a user interface arranged to communicate user instructions to the portable electronic device.

**[0109]** A peripheral control interface as described above including a data transfer component for inserting into a port on another computing device to enable data communication between the portable electronic device and the other computing device.

**[0110]** A peripheral control interface as described above, wherein the data transfer component is a retractable plug on the first or second body portion.

1. A portable electronic device comprising a main body, and a multifunction interface unit communicably connectable to the main body via a cable, wherein the main body includes a recess for storing the interface unit, and wherein the multifunction interface unit is selectively operable as a power adapter and a user input/output device.

2. A portable electronic device according to claim 1 including a mode selector arranged to configure the circuitry of the device according to a selected function of the multifunction interface unit.

3. A portable electronic device according to claim 2, wherein the main body includes:

a user interface;

a processor;

a memory;

software instructions stored on the memory and executable by the processor, wherein the software instructions include instructions for configuring operation of the portable electronic device according to a setting of the mode selector.

4. A portable electronic device according to claim 2, wherein the mode selector is arranged to operate automatically based on a detected configuration of the multifunction interface unit.

5. A portable electronic device according to claim 1, wherein the main body includes a battery, and wherein the multifunction unit is operable as a power adapter to perform a battery recharge function.

6. A portable electronic device according to claim 1, wherein the multifunction interface unit includes a power adapter plug portion securable to one end of the cable, the power adapter plug portion being receivable in a mains power socket.

7. A portable electronic device according to claim 6, wherein the multifunction interface unit comprises a peripheral device connected to the cable, the peripheral device being stowable in the power adapter plug portion.

8. A portable electronic device according to claim 7, wherein the power adapter plug portion includes a retractable storage tray mounted therein, wherein the peripheral device is securable in the storage tray.

9. A portable electronic device according to claim 7, wherein the peripheral device is a pair of earphones.

10. A portable electronic device according to claim 9, wherein the cable is arranged to convey an audio signal from the portable electronic device or a power signal to the portable electronic device.

11. A portable electronic device according to claim 6, wherein the multifunction interface unit comprises a data transfer connector connected to the cable at an end thereof opposite to the power adapter plug portion, wherein the recess in the main body of the portable electronic device is arranged to receive all of the power adapter plug portion, the cable and the data transfer component, and wherein the recess includes terminal connectors arranged so that the power adapter plug portion and the data transfer connector are operably connected to the portable electronic device when the multifunction interface unit is stowed in the recess.

12. A portable electronic device according to claim 1, further comprising a controller portion for sending user instructions to the main body of the portable electronic device.

13. A portable electronic device according to claim 1, wherein the cable is magnetically retainable in or on the main body.

14. A portable electronic device according to claim 13, wherein the cable comprises a flat sheath that encapsulates electrically conductive wiring and magnetic retention elements.

15. A portable electronic device according to claim 14, wherein the cable comprises a plurality of rigid portions that are retainable in a folded stack configuration for storage in a corresponding recess in the portable electronic device.

16. A power adapter unit for a portable electronic device, the power adapter unit comprising:

a plug body having a plurality of terminal pins shaped and spaced to be connectable to an external power source;

a cable connectable to the plug body for conveying electrical power received through the plurality of terminal pins; and

a user input/output device connected to the cable to send or receive an electrical signal,

wherein the user input/output device is stowable in the plug body, and

the power adapter unit is selectively operable as a power adapter and the user input/output device.

17. A power adapter unit according to claim 16, wherein the plug body comprises a retractable storage tray for holding the user input/output device.

18. A power adapter unit according to claim 17, wherein the retractable storage tray is slidably or pivotably mounted in the plug body.

19. A power adapter unit according to claim 16, wherein the user input/output device is a pair of earphones, and the plug body includes a recess shaped to receive the earphones.

20. A power adapter unit according to claim 16, wherein the plug body includes one or more electric terminals that physical contact and electrically connect to corresponding electric connections on the user input/output device when mounted in the plug body.

21. A power adapter unit according to claim 16, wherein the multifunction interface unit comprises a data transfer connector connected to the cable at an end thereof opposite to the plug body.

22. A power adapter unit according to claim 21, wherein the data transfer connector is a USB connector.

\* \* \* \* \*