



(19) **United States**

(12) **Patent Application Publication**

Karaoguz et al.

(10) **Pub. No.: US 2004/0114630 A1**

(43) **Pub. Date: Jun. 17, 2004**

(54) **MEDIA PROCESSING SYSTEM BASED ON SATELLITE SET TOP BOX PLATFORM WITH TELEPHONY DOWNSTREAM AND UPSTREAM DATA PATHS**

filed on Mar. 25, 2003. Provisional application No. 60/432,472, filed on Dec. 11, 2002. Provisional application No. 60/443,894, filed on Jan. 30, 2003.

Publication Classification

(76) Inventors: **Jeyhan Karaoguz**, Irvine, CA (US);
James D. Bennett, Laguna Beach, CA (US)

(51) **Int. Cl.⁷** **H04J 1/00**
(52) **U.S. Cl.** **370/486**

Correspondence Address:
MCANDREWS HELD & MALLOY, LTD
500 WEST MADISON STREET
SUITE 3400
CHICAGO, IL 60661

(57) **ABSTRACT**


(21) Appl. No.: **10/674,671**

(22) Filed: **Sep. 30, 2003**

Related U.S. Application Data

(60) Provisional application No. 60/467,097, filed on Apr. 30, 2003. Provisional application No. 60/457,179,

Systems and methods that provide satellite-based media processing are described. In one embodiment, a system that exchanges media may include, for example, a communications device that may be coupled to a network and to an antenna. The communications device may provide two-way communications with the network and may provide one-way communications with the antenna. The communications may receive media content from the antenna and/or the network. The communications device may send the media content to the network



- device IP address registration
- device ID registration
- channel/program setup/mgmt
- proxy for anonymity

Fig. 1





Fig. 2A

200



210




Fig. 2B




Fig. 2C




Fig. 3




Fig. 4




Fig. 5




Fig. 6

700 →




Fig. 7

800 →

CHANNEL LINE UP	HOUR, DAY			
	<<1PM	2PM	...	6PM 7PM>>
FAMILY VACATIONS				
KID'S SPORTS				
:				
VACATION in ALASKA VIDEO				Showing All Day (48 Min), Earliest Order Time: 4:00PM MPEG-2 1.5 Mbps
VACATION in ALASKA VIDEO				Showing All Day (48 Min), Earliest Order Time: 4:00PM MPEG-2 4 Mbps
VACATION in ALASKA VIDEO				Showing All Day (48 Min), Earliest Order Time: 4:00PM MPEG-2 19 Mbps

801 {

Fig. 8





Fig. 9A

Fig. 9B






Fig. 10




Fig. 11

**MEDIA PROCESSING SYSTEM BASED ON
SATELLITE SET TOP BOX PLATFORM WITH
TELEPHONY DOWNSTREAM AND UPSTREAM
DATA PATHS**

**CROSS-REFERENCE TO RELATED
APPLICATIONS/INCORPORATION BY
REFERENCE**

[0001] This application makes reference to, claims priority to and claims benefit from U.S. Patent Application Serial No. 60/467,097 (Attorney Docket No. 14827US01), entitled "Media Processing System Based on Satellite Set Top Box Platform with Telephony Downstream and Upstream Data Paths" and filed on Apr. 30, 2003; U.S. Patent Application Serial No. 60/457,179 (Attorney Docket No. 14825US01), entitled "Server Architecture Supporting a Personal Media Exchange Network" and filed on Mar. 25, 2003; U.S. Patent Application Serial No. 60/432,472 (Attorney Docket No. 14185US01), entitled "Personal Inter-Home Media Exchange Network" and filed on Dec. 11, 2002; and U.S. Patent Application Serial No. 60/443,894 (Attorney Docket No. 14274US01), entitled "Access and Control of Media Peripherals Via a Media Processing System" and filed on Jan. 30, 2003. The complete subject matter of the above-identified applications are hereby incorporated herein by reference in their entirety.

[0002] In addition, this application makes reference to U.S. patent application Ser. No. _____ (Attorney Docket No. 14185US02), entitled "Personal Inter-Home Media Exchange Network" and filed on Sep. 8, 2003; and U.S. patent application Ser. No. _____ (Attorney Docket No. 14274US02), entitled "Personal Access and Control of Media Peripherals on a Media Exchange Network" and filed on Sep. 11, 2003. The complete subject matter of the above-identified applications are hereby incorporated herein by reference in their entirety.

**FEDERALLY SPONSORED RESEARCH OR
DEVELOPMENT**

[0003] [Not Applicable]

SEQUENCE LISTING

[0004] [Not Applicable]

MICROFICHE/COPYRIGHT REFERENCE

[0005] [Not Applicable]

BACKGROUND OF THE INVENTION

[0006] The ways in which digital media are shared today are somewhat limited. Today, there are two primary ways that people exchange digital media. A first way is a fairly interactive way using a personal computer (PC) having an upstream and downstream connection to, for example, the Internet.

[0007] An Internet service provider (ISP) may provide temporary Internet protocol (IP) addresses to PC's connected to the Internet using, for example, dynamic host configuration protocol (DHCP). The PC's may then access web pages on the Internet using a web browser and send and receive email with or without file attachments to exchange media, data, and services between PC's. Files may also be

transferred over the Internet using a file transfer protocol (FTP). FTP allows PC's connected to the Internet to exchange files, independently of the PC platform.

[0008] A user of a PC may connect a device, for example, a digital camera or an MP3 player to his PC and download digital files from the device to the PC. Such a device may interface to a PC through a Universal Serial Bus (USB) interface to exchange digital media between a PC and the device. Again, the digital files may be attached to emails and shared with others in such a manner.

[0009] A user may have access to digital broadcast media through a set-top box providing predominantly one-way communication (i.e., broadcast media is sent from a broadcast media provider to the set-top box). A user of a set-top box may also be able to order pay per view (PPV) broadcast channels via the set-top box, but interaction between the user and the set-top box is, otherwise, very limited. A set-top box may interface to a cable infrastructure, a satellite infrastructure or a digital subscriber line (DSL) infrastructure to receive broadcast media and to exchange access information between the infrastructure and the set-top box.

[0010] Further limitations and disadvantages of conventional and traditional approaches will become apparent to one of skill in the art, through comparison of such systems with aspects of the present invention as set forth in the remainder of the present application with reference to the drawings.

BRIEF SUMMARY OF THE INVENTION

[0011] Aspects of the present invention may be found in, for example, systems and methods that provide satellite-based media processing with telephony. In one embodiment, the present invention may provide a system that exchanges media content. The system may include, for example, a communications device that may be coupled to a network and to an antenna. The communications device may provide two-way communications with the network and may provide one-way communications with the antenna. The communications may receive media content from the antenna and/or the network. The communications device may send the media content to the network.

[0012] In another embodiment, aspects of the present invention may provide a method that exchanges media content. The method may include, for example, one or more of the following: adapting a communications device to provide two-way communications with a network; adapting the communications device to provide one-way communications with an antenna; receiving, by the communications device, media content from the antenna; receiving, by the communications device, the media content from the network; and sending, by the communications device, the media content to the network.

[0013] These and other advantages, aspects and novel features of the present invention, as well as details of illustrated embodiments thereof, will be more fully understood from the following description and drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

[0014] **FIG. 1** is a diagram illustrating an embodiment of a media exchange network supporting a media processing

system based on a satellite set-top box platform with telephony according to the present invention.

[0015] FIG. 2A is a flowchart illustrating an embodiment of a method supporting a media processing system of a media exchange network according to the present invention.

[0016] FIG. 2B is a flowchart illustrating an embodiment of a method that generates a unified media guide in the media processing system according to the present invention.

[0017] FIG. 2C is a flowchart illustrating an embodiment of a method that generates a unified media guide according to the present invention.

[0018] FIG. 3 is a schematic block diagram illustrating an embodiment of a media exchange network according to the present invention.

[0019] FIG. 4 is a schematic block diagram illustrating an exchange of personal media over a media exchange network according to an embodiment of the present invention.

[0020] FIG. 5 is a schematic block diagram illustrating an exchange of third-party media over a media exchange network according to an embodiment of the present invention.

[0021] FIG. 6 illustrates an embodiment of a television (TV) guide channel user interface according to the present invention.

[0022] FIG. 7 illustrates an embodiment of a TV guide channel user interface according to the present invention.

[0023] FIG. 8 illustrates an embodiment of a TV guide channel user interface showing several options of a pushed media according to present invention.

[0024] FIG. 9A is a schematic block diagram illustrating an embodiment of a media processing system (MPS) interfacing to media capture peripherals according to the present invention.

[0025] FIG. 9B illustrates an embodiment of an MPS according to the present invention.

[0026] FIG. 10 is a schematic block diagram illustrating an embodiment of a personal computer (PC) and an MPS interfacing to a server on a media exchange network according to the present invention.

[0027] FIG. 11 is a schematic block diagram illustrating an embodiment of a PC interfacing to personal media capture devices and remote media storage on a media exchange network according to the present invention.

DETAILED DESCRIPTION OF THE INVENTION

[0028] Some embodiments of the present invention may relate to providing a network for media exchange. Some embodiments of the present invention may relate to providing a media exchange network supporting a media processing system based on a satellite set-top box platform with telephony downstream and upstream data paths.

[0029] FIG. 1 is a diagram illustrating an embodiment of a media exchange network 100 supporting a media processing system (MPS) 101 based on a satellite set-top box platform with telephony downstream and upstream data paths according to the present invention.

[0030] In accordance with various embodiments of the present invention, an MPS may comprise, for example, at least one of a set-top box, a personal computer (PC) and a television (TV) with a media management system (MMS). An MMS is also known herein as a media exchange software (MES) platform.

[0031] In accordance with various embodiments of the present invention, an MMS may comprise a software platform operating on at least one processor to provide certain functionality including, for example, user interface functionality, distributed storage functionality and networking functionality. For example, an MMS may provide control of media peripheral devices, status monitoring of media peripheral devices and inter-home MPS routing selection in accordance with an embodiment of the present invention.

[0032] The media exchange network 100 may include a communication network comprising, for example, a satellite MPS 101, a PC 104, a media peripheral (MP) 105, and a digital subscriber line (DSL) modem 103 at a 1st home 102. The DSL modem 103 interfaces to the satellite MPS 101 and the PC 104. The MP 105 interfaces to the satellite MPS 101 and the PC 104 via, for example, universal serial bus (USB) connections or other types of wire connections (e.g., cable connections). Optionally, the MP 105 may interface to the PC 104 and/or the MPS 101 via a wireless link. The media exchange network 100 may also comprise a satellite dish antenna 106 interfacing to the satellite MPS 101 at the 1st home 102.

[0033] The media exchange network 100 may further comprise, for example, an Internet infrastructure 109, a media exchange server 110, a DSL infrastructure 107, a DSL headend 113, and a satellite headend 108. The media exchange network 100 may also comprise a media storage server 111 and a 3rd party media server 112. The DSL headend 113 and the satellite headend 108 may interface to the Internet infrastructure 109 via the DSL infrastructure 107. The media storage server 111, the media exchange server 110, and the 3rd party media server 112 each may interface to the Internet infrastructure 109. The DSL infrastructure 107 may interface to the DSL modem 103 at the 1st home 102. The satellite headend 108 and the DSL headend 113 may interface to the DSL infrastructure 107. In some embodiments according to the present invention, the media storage server 111 may interface with the media exchange network 110. In various embodiments according to the present invention, the PC 104, MPS 101, and/or the MP 105 may include an internal DSL modem to communicate with the DSL infrastructure 107.

[0034] The media exchange network 100 may further comprise, for example, a headend 114 and a 2nd home 115. The headend 114 may comprise, for example, a satellite headend, a cable headend, or a DSL headend. The 2nd home 115 may include, for example, an MPS, a PC, an MP, and modems in accordance with various embodiments of the present invention. A device (e.g., a cable modem or a DSL modem) at the 2nd home 115 may interface to the Internet infrastructure 109 via the headend 114.

[0035] The architecture of FIG. 1, for example, may provide communication between a device (e.g., an MPS, a PC, an MP) at one home and a satellite provider over the media exchange network 100. The media exchange server 110 provides functionality on the media exchange network

100 including, for example, device registration, channel/program setup and management, and security.

[**0036**] In accordance with an embodiment of the present invention, the satellite headend **108**, the DSL headend **113** and/or the headend **114** may be upgraded to media exchange headends by adding functionality to facilitate the exchange of media on the media exchange network **100** in conjunction with the media exchange server **110**. Such functionality may include, for example, distributed networking capability, archival functionality (e.g., long term media storage), temporary storage (e.g., to aid in the distribution and routing of media), storage management, and digital rights management.

[**0037**] Some elements of the media exchange network **100** may include, for example, storage locations for digital media and data in accordance with various embodiments of the present invention. The storage locations may comprise, for example, hard disk drives, a DVD player, a CD player, floppy disk drives, a RAM, or any combination of these. The storage locations may also include, for example, memory sticks, PCMCIA cards, compact flash cards, or any combination of these.

[**0038**] The PC **104** may comprise, for example, a desktop PC, a notebook PC, a personal digital assistant (PDA), or any computing device. The media peripheral **105** may include, for example, a digital camera, a digital camcorder, an MP3 player, a home juke-box system, a PDA, and a multi-media gateway device.

[**0039**] In accordance with some embodiments of the present invention, the satellite MPS **101** may comprise an enhanced satellite set-top box. The MPS **101** may include, for example, a TV screen that can be used for viewing and interacting with various user interfaces, media, data, and services that are available on the media exchange network **100** using, for example, a remote control. The PC **104** may include, for example, a PC monitor for viewing and interacting with various user interfaces, media, data, and services that are available on the media exchange network **100** using, for example, a keyboard and a mouse. The MPS **101**, the PC **104**, and/or the MP **105** may include, for example, functional software to support interaction with the headends **108** and **113** and the media exchange server **110** on the media exchange network **100** in accordance with various embodiments of the present invention.

[**0040**] The MPS **101** may support a satellite downstream communication link for legacy network programming via the dish antenna **106**. The pushing and pulling of digital media and data are supported through the use of the DSL modem **103** in accordance with an embodiment of the present invention. In some embodiments of the present invention, the telephony network **107** may comprise a dial-up network and the modem **103** may comprise a dial-up modem.

[**0041**] The satellite headend **108** may comprise, for example, a high-end DSL modem with supporting infrastructure (e.g., upconverters/modulators, a router/firewall, an intranet infrastructure, etc.) and may be operated by a satellite provider company. The satellite headend **108** may be able to communicate to users via the DSL infrastructure **107** which may comprise a telephony network to transmit information along twisted pairs of copper wires according to

some embodiments of the present invention. A user at the 1st home **102** may receive broadcast media transmitted from a satellite in space to the dish antenna **106**. The dish antenna **106** may receive the satellite signal and may make it available to the satellite MPS **101**. Bi-directional communications (e.g., command data) between the 1st home **102** and the satellite headend **108** takes place via, for example, the DSL infrastructure **107**.

[**0042**] The DSL headend **113** may comprise, for example, a high-end DSL modem with supporting infrastructure (e.g., upconverters/modulators, a router/firewall, an intranet infrastructure, etc.) and may be operated by a DSL provider company. Command and control data, for example, may be communicated bi-directionally between the 1st home **102** and the DSL headend **113**.

[**0043**] In accordance with an embodiment of the present invention, some or all of the functionality of the media exchange server **110** may be distributed throughout the various elements of the media exchange network **100**. For example, referring to **FIG. 1**, the functionality of the media exchange server **110** may be distributed into any combination of devices on the media exchange network **100** including, for example, the PC **104**, the satellite MPS **101**, the satellite headend **108**, the DSL headend **113**, the headend **114**, and/or devices within the 2nd home **115**.

[**0044**] The media exchange server **110** in the media exchange network **100** may be jointly managed and accessed by the operators of the satellite headend **108** and the DSL headend **113** for program content, device registration, user authentication, billing, etc., in accordance with an embodiment of the present invention.

[**0045**] Other embodiments of the present invention may comprise various combinations and/or multiple instantiations of the elements of **FIG. 1**, in accordance with the present invention.

[**0046**] In accordance with some embodiments of the present invention, the DSL modem **103** may provide an upstream path and a downstream path through the telephony network **107** within the media exchange network **100** combined with a digital satellite downstream path from a satellite in space to the dish antenna **106**. Some or all of the functions of the media exchange network **100** may be performed using the satellite MPS **101**. The media content (e.g., personal media content) and 3rd party media content may be communicated between the satellite MPS **101** and other elements of the media exchange network **100** via the DSL infrastructure.

[**0047**] 3rd party media content may be ordered through the DSL infrastructure **107** from the satellite headend **108**. The satellite headend **108** may then command that the 3rd party media be piped from a satellite in space to the dish antenna **106**. The satellite in space may provide an MPEG transport stream via a downstream path to the dish antenna **106**. In accordance with an embodiment of the present invention, the MPEG transport stream may include, for example, broadcast video channels, interleaved data streams, interleaved 3rd party media content, and an interleaved media guide. The satellite MPS **101** may process the various content within the MPEG transport stream.

[**0048**] In accordance with some embodiments of the present invention, the functionality that a cable MPS, in

conjunction with a cable modem, may perform with respect to the media exchange network may also be performed by a satellite MPS in conjunction with a DSL modem as described in, for example, U.S. Patent Application Serial No. 60/457,179 (Attorney Docket No. 14825US01), entitled "Server Architecture Supporting a Personal Media Exchange Network" and filed on Mar. 25, 2003, which has been incorporated herein by reference in its entirety.

[0049] FIG. 2A is a flowchart illustrating an embodiment of a method 200 supporting the media processing system 101 of the media exchange network 100 of FIG. 1, in accordance with various aspects of the present invention. In step 201, a satellite MPS at a first home sends a request to receive 3rd party media content to a satellite headend via a DSL infrastructure on a media exchange network. In step 202, the satellite headend responds to the request by sending acknowledge information to the satellite MPS via the DSL infrastructure. In step 203, the satellite MPS receives the 3rd party media content from a satellite provider via a satellite dish antenna and consumes or stores the 3rd party media content either locally or at a network storage location.

[0050] As an example, referring to FIG. 1, the satellite MPS 101 at the first home 102 sends a request to receive a particular 3rd party media content (e.g., a car commercial) to the satellite headend 108. The request is transmitted from the satellite MPS 101, to the DSL modem 103, to the DSL infrastructure 107, and finally to the satellite headend 108. The satellite headend 108 processes the request and pushes acknowledge information (e.g., request received, request approved, etc.) to the satellite MPS 101. The acknowledge information is transmitted along the reverse path of the original request.

[0051] The satellite headend 108 may bill an account of the user of the satellite MPS 101 for access to the 3rd party media content. The account may be managed in, for example, the satellite headend 108, the DSL headend 113, or the media exchange server 110, in accordance with various embodiments of the present invention.

[0052] The satellite MPS 101 receives the 3rd party media content via the satellite dish antenna 106. The satellite MPS 101 records the 3rd party media content in digital form on the MP 105 which may comprise, for example, a disk storage device.

[0053] Other examples of access and media exchange are possible as well, in accordance with various embodiments of the present invention.

[0054] FIG. 2B is a flowchart illustrating an embodiment of a method 210 to generate a unified media guide in the media processing system 101 of FIG. 1, in accordance with various embodiments of the present invention. In step 211, a satellite headend pushes a broadcast media guide to a satellite MPS on a media exchange network. In step 212, a DSL headend pushes an updated personal media guide to the satellite MPS on the media exchange network. In step 213, the satellite MPS generates a unified media guide comprising, for example, programming content from the broadcast media guide and the updated personal media guide.

[0055] In accordance with an embodiment of the present invention, a broadcast programming guide may comprise a legacy programming guide listing scheduled broadcast programs provided by the satellite provider. A personal media

guide may comprise scheduled personal media content in the form of channels such as, for example, a user's personal media channels, a friend's media channels, a family member's media channels, and/or a 3rd party provider's media channels.

[0056] As an example, referring to FIG. 1, the satellite headend 108 pushes a broadcast media guide, corresponding to that day's programming schedule of the satellite provider, to the satellite MPS 101 via the DSL infrastructure 107. The DSL headend 113 pushes an updated personal media guide to the satellite MPS 101 via the DSL infrastructure 107. The DSL headend may have just updated the personal media guide with channels from a family member on the media exchange network 100, for example.

[0057] The satellite MPS 101 processes the broadcast media guide and the personal media guide to generate a unified media guide comprising the program content and channels from both media guides. In other words, the unified media guide comprises both broadcast program content and personal media content in a scheduled format. A user of the satellite MPS 101 may use a remote control to view the unified media guide and select from a variety of personal and broadcast media channels.

[0058] FIG. 2C is a flowchart illustrating an embodiment of a method 215 to generate a unified media guide in a DSL headend 113 of the media exchange network 100 of FIG. 1, in accordance with various embodiments of the present invention. In step 216, a satellite headend pushes a broadcast media guide to a DSL headend on a media exchange network. In step 217, a satellite MPS pushes a personal media guide to the DSL headend on the media exchange network. In step 218, the DSL headend generates a unified media guide comprising programming content from the broadcast media guide and the personal media guide. In step 219, the DSL headend pushes the unified media guide to the satellite MPS on the media exchange network.

[0059] As an example, referring to FIG. 1, the satellite headend 108 pushes a broadcast media guide containing that day's scheduled satellite programming content to the DSL headend 113 via the DSL infrastructure 107. The satellite MPS 101 pushes its personal media guide to the DSL headend 113 via the DSL infrastructure 107. The DSL headend processes the two media guides and generates a unified media guide comprising the program content and channels from both media guides. In other words, the unified media guide comprises both broadcast program content and personal media content in a scheduled format.

[0060] The DSL headend 113 then pushes the unified media guide to the satellite MPS 101 on the media exchange network 100 via the DSL infrastructure 107. A user of the satellite MPS 101 may use a remote control to view the unified media guide and select from a variety of personal and broadcast media channels.

[0061] Other examples of media guide exchange and generation are possible as well, in accordance with various embodiments of the present invention. For example, in one embodiment according to the present invention, the satellite MPS 101 may generate a unified media guide by processing a broadcast media guide received from the satellite headend 108 and a personal media guide residing in the satellite MPS 101. In another embodiment according to the present inven-

tion, the DSL headend **113** may generate a unified media guide by processing a broadcast media guide received from the satellite headend **108** and a personal media guide residing in the DSL headend **113**. The unified media guide may then be pushed to the satellite MPS **101**.

[**0062**] Some embodiments according to the present invention can transfer and share many different types of digital media, data, and services between one device/location and another with ease while being able to index, manage, and store the digital media and data.

[**0063**] For example, it may be desirable to be able to distribute and to store many types of digital media in a PC and/or a television environment in a user-friendly manner without using many different types of software applications and/or unique and dedicated interfaces. Any networking issues or other technical issues may be transparent to the users. It may also be desirable to use existing hardware infrastructure, as much as possible, when providing such capability.

[**0064**] In an embodiment of the present invention, a media exchange network is provided that enables many types of digital media, data, and/or services to be stored, indexed, viewed, searched for, pushed from one user to another, and requested by users, via a TV channel guide look-and-feel user interface. The media exchange network also allows a user to construct personal media channels that comprise personal digital media (e.g., captured digital pictures, digital video, digital audio, etc.), request that third-party media channels be constructed from third-party digital media, and access the media channels pushed to the user by other users on the media exchange network.

[**0065**] PC's may be used, but are not required, to interface to the media exchange network for the purpose of exchanging digital media, data, and services. Set-top boxes or integrated MPS's may be used with the media exchange network to perform some or all of the previously described media exchange functions using, for example, a remote control with a television screen.

[**0066**] Set-top boxes may be software enhanced to create an MPS that provides full media exchange network interfacing and functionality via a TV screen with a TV guide look-and-feel. PC's may be software enhanced and may provide the same TV guide look-and-feel. Therefore, the media exchange network may support both PC's and MPS's in a similar manner. In accordance with an embodiment of the present invention, a fully integrated MPS may be designed from the ground up, having full MPS capability.

[**0067**] In the case of an MPS configuration, the user may use a remote control and a TV screen to access the media exchange network. In the case of a PC configuration, the user may use a keyboard and/or a mouse to access the media exchange network.

[**0068**] An MPS or an enhanced PC may provide, for example, a storage and distribution platform for the exchange of personal and third party digital media, data, and services as well as for bringing the conventional television channels to a user's home. An MPS and/or a PC may connect to the media exchange network via an existing communication infrastructure which may include, for example, a cable infrastructure, a DSL infrastructure, a satellite infra-

structure, etc. The connection to the communication infrastructure may be hard-wired or wireless.

[**0069**] The media exchange network may allow users to effectively become their own broadcasters from their own homes by creating their own media channels and pushing those media channels to other authorized users on the media exchange network, such as friends and family members.

[**0070**] FIG. 3 illustrates a media exchange network **300** for exchanging and sharing digital media, data, and services in accordance with an embodiment of the present invention. The media exchange network **300** may comprise, for example, a secure, closed network environment that is only accessible to pre-defined users and service providers. The media exchange network of FIG. 3 comprises a first PC **301** and a first MPS **302** at a user's home **303**, a communication infrastructure **304**, an external processing hardware support **305**, a remote media storage **306**, a second PC **307** at a remote location **308** such as an office, and a second MPS **309** at a parent's home **310**.

[**0071**] The PC's **301** and **307** and the MPS's **302** and **309** may each include a media exchange software (MES) platform **311** and a networking component **312** for connectivity. The MES platform **311** provides multiple capabilities including, for example, media "push" capability, media "access" capability, media channel construction/selection, image sequence selection, text and voice overlay, channel and program naming, inter-home routing selection, authorship and media rights management, shared inter-home media experience, billing service, and an integrated TV channel guide look-and-feel.

[**0072**] The external processing hardware support **305** may comprise, for example, at least one server such as a centralized Internet server, a peer-to-peer server, or a cable head end. The server may alternatively be distributed over various hosts or remote PC's. The MES platform **311** may reside on the external processing hardware support server **305**. The remote media storage **306** may comprise, for example, user media storage and distribution systems **313** and/or third party media storage and distribution systems **314**.

[**0073**] The communication infrastructure **304** may comprise, for example, at least one of an Internet infrastructure, a satellite infrastructure, a cable infrastructure, a dial-up infrastructure, a cellular infrastructure, an xDSL infrastructure, an optical infrastructure, or some other infrastructure. The communication infrastructure **304** may link the user's home **303**, the parent's home **310**, the remote media storage **306**, and the remote location office **308** to each other (e.g., the communication infrastructure **304** may link all users and service providers of the media exchange network **300**).

[**0074**] The various functions **315** of the media exchange network **300** may comprise, for example, generating personal network associations, personal storage management, media capture device support, security/authentication/authorization support, authorship tracking and billing and address registration and maintenance. These media exchange management functions **315** may be distributed over various parts of the media exchange network **300**. For example, the personal network associations and personal storage management functions may be integrated into the PC **301** at the user's home **303**.

[**0075**] FIG. 4 illustrates an example of a personal media exchange over a media exchange network **400** in accordance

with an embodiment of the present invention. In step 1, the media exchange software (MES) platform 401 is used to construct personal media channels on a PC 402 by a user at "my house" 403. For example, with various media stored on the PC 402 such as digital pictures 404, videos 405, and music 406, the MES platform 401 allows the digital media to be organized by a user into several channels having a TV channel guide look-and-feel user interface 407 on the PC 402.

[0076] In step 2, the user at "my house" 403 pushes a media channel 408 (e.g., "Joe's Music") to "brother's house" 409 and pushes two media channels 410 and 411 (e.g., "Vacation Video" and "Kid's Pictures") to "Mom's house" 412 via a peer-to-peer server 413 over the Internet-based media exchange network 400. "Brother's house" 409 includes a first MPS 414 connected to the media exchange network 400. "Mom's house" 412 includes a second MPS 415 connected to the media exchange network 400. The MPS's 414 and 415 also provide a TV channel guide look-and-feel user interface 407.

[0077] In step 3, brother and/or Mom access the pushed media channels via their respective media processing systems (MPS's) 414 and 415 using their respective MPS TV screens and remote controls.

[0078] FIG. 5 illustrates an example of a third-party media exchange over a media exchange network 500 in accordance with an embodiment of the present invention. In step 1, a PC-initiated third-party request is made by a first party 501 via an Internet-based media exchange network 500 using a TV channel guide look-and-feel user interface 502 on a PC 503. In step 2, an anonymous delivery of the requested third-party channel 504 is made to a second party 505 via the Internet-based media exchange network 500. In step 3, the second party 505 accesses the third-party channel 504 using a TV channel guide look-and-feel user interface 506 on a TV screen 507 that is integrated into an MPS 508.

[0079] Similarly, in step A, an MPS-initiated third-party request is made by a second party 505 via an Internet-based media exchange network 500 using a TV channel guide look-and-feel user interface 506 on a TV screen 507 using a remote control 509. The second party 505 may key in a code, using the remote control 509, that is correlated to a commercial or some other third party broadcast media. In step B, an anonymous delivery of the requested third-party channel 504 is made to a first party 501 via the Internet-based media exchange network 500. In step C, the first party 501 accesses the third-party channel 504 using a TV channel guide look-and-feel user interface 502 on a PC 503.

[0080] FIG. 6 illustrates a TV channel guide user interface 600 in accordance with an embodiment of the present invention. The TV channel guide user interface 600 may be displayed on a TV screen 608 and controlled by a remote control device 609. Also, the TV channel guide user interface 600 may be displayed on a PC monitor and controlled by a keyboard or a mouse.

[0081] The TV channel guide user interface 600 may be configured not only for conventional TV channels, but also for personal media channels 601 that are constructed by a user of a media exchange network, friend's and family's media channels 602 constructed by friends and family, and third party channels 603 that are constructed by third parties

either upon request by a user of a media exchange network or based on a profile of a user.

[0082] The personal media channels 601 may include, for example, a "family vacations channel", a "kid's sports channel", a "my life channel", a "son's life channel", a "my music channel", and a "kid's music channel". The friends and family media channels 602 may include, for example, a "brother's channel", a "Mom's channel", and a "friend's channel". The third party media channels 603 may include, for example, a "Sears Fall sale channel" and a "car commercials channel".

[0083] Each media channel may correspond to a schedule 604 showing, for example, a week 605 and a year 606. For example, under the "kid's sports channel", Ty's soccer game could be scheduled to be viewed on Tuesday of the current week 605 and current year 606. For each media channel, a sub-menu 607 allows for selection of certain control and access functions such as, for example, "play", "send to list", "send to archive", "confirm receipt", "view", "purchase", and "profile".

[0084] FIG. 7 illustrates possible multiple instantiations of a TV channel guide user interface 700 in accordance with an embodiment of the present invention. The TV channel guide user interface 700 may be viewed with a schedule having formats of, for example, "month, year", "week#, year", "day, week#", or "hour, day".

[0085] Referring to FIG. 8, a user of a media exchange network may push a media channel (e.g., "Vacation in Alaska Video") to a friend who is on the same media exchange network. The TV channel guide user interface 800 may give the friend several options 801 for accepting and downloading the pushed media in accordance with an embodiment of the present invention.

[0086] For example, a first, most expensive option 803 may be "Express Delivery" which would deliver the pushed media to the friend in 18 minutes using queuing and cost \$1.20, for example. The pushed media may be stored in a file in an MPEG 2 format that was recorded at a rate of 4 Mbps, for example. Queuing may comprise, for example, buffering and delivering a previous part of the media and then buffering and delivering a next part of the media. For example, a first six minutes of the "Vacation in Alaska Video" may be buffered and delivered first, then a second six minutes may be buffered and delivered next, and so on until the entire media is delivered.

[0087] A second, less expensive option 802 may be "Normal Delivery" which would deliver the pushed media in 2 hours and 13 minutes without queuing and cost \$0.59, for example. The pushed media may be stored in a file in an MPEG 2 format that was recorded at a rate of 1.5 Mbps, for example.

[0088] A third, least expensive option 804 may be "Over-night Delivery" which would deliver the pushed media by the next morning and cost only \$0.05, for example. The pushed media may be stored in a file in an MPEG 2 format that was recorded at a rate of 19 Mbps and stored on a server, for example.

[0089] FIG. 9A illustrates some elements of a media processing system (MPS) 900 and media capture devices 901 in accordance with an embodiment of the present

invention. The media capture devices **901** may comprise, for example, audio, video, and image players, such as digital cameras, digital camcorders, and MP3 players, that each may include, for example, a temporary storage area **902** and a communication interface **903** such as, for example, a wired interface (e.g., a USB interface) or a wireless interface. The media capture devices **901** may interface to an MPS and a PC.

[**0090**] The MPS **900** may comprise, for example, a media processing unit (MPU) **904**, remote user interface(s) **905**, and a TV screen **918** to provide integrated media processing capability and indirect user interface capability. The remote user interfaces **905** may comprise, for example, a voice or keyed remote control **906**, keyboards and pads **907**, a remote PC access interface **908**, and a remote media system access interface **909** (e.g., providing access from another MPS).

[**0091**] The media processing unit (MPU) **904** may comprise, for example, TV and radio tuners **910** for image and audio consumption, communications interfaces **911**, channel processing **912** (e.g., creating, storing, indexing, and viewing), storage **913**, media players **914** (e.g., CD players, DVD players, tape players, PVRs, and MP3 players), an integrated user interface **915** (e.g., to provide a TV channel guide look-and-feel), networking components **916** to provide client functions such as, for example, consumption (e.g., billing), authorization (e.g., using digital certificates and digital ID's), registration, security, and connectivity. In accordance with an embodiment of the present invention, the networking components **916** may include a distributed server element **917** that is part of a distributed server.

[**0092**] FIG. 9B illustrates an embodiment of a media processing system (MPS) **920** in accordance with various aspects of the present invention. The MPS **920** may comprise, for example, an enhanced set-top box for viewing and interacting with various user interfaces, media, data and services that are available on the media exchange network using, for example, a remote control. The MPS **920** may comprise, for example, a media peripheral **921**, a media management system (MMS) **922** and a broadband communication interface **923**.

[**0093**] The media peripheral **921** may include, for example, a TV, a PC and media players (e.g., a CD player, a DVD player, a tape player and an MP3 player) for video, image and audio consumption of broadcast channels and/or personal channels. The broadband communication interface **923** may include, for example, internal modems (e.g., a cable modem or a DSL modem) or other interface devices to communicate with, for example, a cable or satellite headend.

[**0094**] The MMS **922** may include a software platform to provide functionality including, for example, media "push" capability, media "access" capability, media channel construction/selection, image sequence selection, text and voice overlay, channel and program naming, inter-home routing selection, authorship and media rights management, shared inter-home media experience, billing service and a media guide user interface providing an integrated TV channel guide look-and-feel.

[**0095**] FIG. 10 illustrates connectivity between a PC **1000**, an MPS **1001**, and an external processing hardware **1002** (e.g., a server) in accordance with an embodiment of the present invention. The PC **1000** and the MPS **1001** may

include networking components **1003** to provide client functions such as, for example, consumption (e.g., billing), authorization, registration, security, and connectivity. In accordance with various embodiments of the present invention, the PC **1000** and the MPS **1001** may include a distributed server element **1004** that is part of a distributed server.

[**0096**] The PC **1000** and the MPS **1001** may connect to the external processing hardware **1002** via wired connections or wireless connections in accordance with various embodiments of the present invention. The external processing hardware **1002** may comprise, for example, a distributed server or a peer-to-peer server. The external processing hardware **1002** also may comprise communication interfaces **1005** (e.g., cable interfaces, optical interfaces, etc.) and a media exchange software (MES) platform **1006**. The MES platform **1006** in the external processing hardware **1002** may allow for communication with the PC **1000** and the MPS **1001** which may also use the same MES platform **1006**. The external processing hardware **1002** may also include networking server components **1007** to provide the similar client functions such as, for example, consumption (e.g., billing), authorization, registration, security, and connectivity at the server side.

[**0097**] FIG. 11 illustrates connectivity between a PC **1100**, a remote media storage **1101**, and personal media capture devices **1102** when the PC **1100** is used as the primary distributor of digital media such as in the case of a PC-to-PC operation, in accordance with an embodiment of the present invention. The personal media capture devices **1102** and the remote media storage **1101** may connect to the PC **1100** via a wireless connection or a wired connection. The remote media storage **1101** may provide user media storage and distribution **1103** as well as third party media storage and distribution **1104**. The personal media capture devices **1102** may provide temporary storage **1114** and communication interfaces **1115**.

[**0098**] Viewing may be done using a PC monitor **1105** instead of a television screen in accordance with various embodiments of the present invention. The PC **1100** may include, for example, storage **1106**, TV/radio tuners **1107** for media consumption, media players **1108**, and communication interfaces **1109** and user interfaces **1110** similar to those for the MPS of FIG. 9. The PC **1100** may include a media exchange software (MES) platform **1111** that provides channel construction capability **1112** and networking capability **1113**. The channel construction capability **1112** may provide, for example, third party and personal media access, sequencing, editing, media overlays and inserts, billing, scheduling, and addressing.

[**0099**] In summary, some embodiments of the present invention may relate to systems and methods that support a media processing system based on a satellite set-top box platform. The media processing system may provide telephony downstream and upstream data paths on a media exchange network.

[**0100**] While the present invention has been described with reference to certain embodiments, it will be understood by those skilled in the art that various changes may be made and equivalents may be substituted without departing from the scope of the present invention. In addition, many modifications may be made to adapt a particular situation or

material to the teachings of the present invention without departing from its scope. Therefore, it is intended that the present invention not be limited to the particular embodiments disclosed, but that the present invention will include all embodiments falling within the scope of the appended claims.

What is claimed is:

1. A system for exchanging media content, comprising:
 - a communications device operatively coupled to a network and to an antenna, the communications device providing two-way communications with the network and providing one-way communications with the antenna,
 - wherein the communications device can receive media content from the antenna,
 - wherein the communications device can send the media content to the network, and
 - wherein the communications device can receive the media content from the network.
2. The system according to claim 1, wherein the antenna comprises a dish antenna.
3. The system according to claim 1, wherein the communications device comprises a software platform that can provide at least one of a user-interface functionality, a distributed storage functionality and a networking functionality.
4. The system according to claim 1, wherein the communications device comprises a software platform that can provide at least one of device registration, channel setup, program setup, management and security.
5. The system according to claim 1, wherein the communications device is adapted to provide at least one of distributed a networking capability, an archival functionality, a temporary storage capability, a storage manager and a digital rights manager.
6. The system according to claim 1, wherein the network comprises a telephony network.
7. The system according to claim 1, wherein the network comprises an Internet infrastructure.
8. The system according to claim 7,
 - wherein the Internet infrastructure is coupled to a telephony network, and
 - wherein the communications device provides two-way communications with telephony network.
9. The system according to claim 1,
 - wherein the network comprises a telephony network, a telephony network headend and a satellite system headend,
 - wherein the communications device provides two-way communications with the telephony network headend via the telephony network, and
 - wherein the communications device provides two-way communications with the satellite system headend via the telephony network.
10. The system according to claim 9,
 - wherein the communications device can request the media content from the satellite system headend via the telephony network, and
 - wherein the communications device receives the requested media content via the antenna.
11. The system according to claim 10, wherein the communications device receives acknowledge information relating to the media content request from the satellite system headend via the telephony network.
12. The system according to claim 9, wherein at least one of the telephony network headend and the satellite system headend comprises a modem that supports at least one of an upconverter, a modulator, a router, a firewall and an intranet infrastructure.
13. The system according to claim 9,
 - wherein the communications device receives a broadcast media guide from the satellite system headend,
 - wherein the communications device receives a personal media guide from the telephony network headend, and
 - wherein the communications device generates a unified media guide by processing the received broadcast media guide and the received personal media guide.
14. The system according to claim 9,
 - wherein telephony network headend receives a broadcast media guide from the satellite system headend,
 - wherein telephony network headend receives a personal media guide from the communications device, and
 - wherein telephony network headend generates a unified media guide by processing the received broadcast media guide and the received personal media guide.
15. The system according to claim 14, wherein the telephony network headend sends the unified media guide to the communications device.
16. The system according to claim 9, wherein the telephony network headend is a digital subscriber line (DSL) headend.
17. The system according to claim 16,
 - wherein the telephony network comprises a DSL infrastructure, and
 - wherein the communications device provides two-way communications with the DSL headend via a DSL modem and the DSL infrastructure.
18. The system according to claim 1, further comprising:
 - a second communications device coupled to the network, the second communications device providing two-way communications with the network,
 - wherein the second communications device can send the media content to the communications device via the network, and
 - wherein the second communications can receive the media content from communications device via the network.
19. The system according to claim 18,
 - wherein the communications device is disposed at a first location, and
 - wherein the second communications device is disposed in a second location.
20. The system according to claim 18,
 - wherein the communications device is disposed in a first home environment, and

wherein the second communications device is disposed in a second home environment.

21. The system according to claim 18, wherein the second communications device is coupled to the network via a headend.

22. The system according to claim 1, further comprising:
a media server coupled to the network,

wherein the communications device can receive the media content from the media server via the network.

23. A method for exchanging media content, comprising:
adapting a communications device to provide two-way communications with a network;

adapting the communications device to provide one-way communications with an antenna;

receiving, by the communications device, media content from the antenna;

receiving, by the communications device, the media content from the network; and

sending, by the communications device, the media content to the network.

24. The method according to claim 23, further comprising:

requesting, by the communications device, the media content from a satellite headend that is part of the network;

receiving, by the communications device, acknowledge information relating to the requested media content from the satellite headend; and

receiving, by the communications device, the requested media content from the antenna.

25. The method according to claim 23, further comprising:

receiving, by the communications device, a personal media guide from a telephony network headend that is part of the network;

receiving, by the communications device, a broadcast media guide from a satellite headend that is part of the network; and

generating, by the communications device, a unified media guide based on at least the received personal media guide and the received broadcast media guide.

26. The method according to claim 23, further comprising:

receiving, by a telephony network headend that is part of the network, a personal media guide from the communications device;

receiving, by the telephony network headend, a broadcast media guide from a satellite headend that is part of the network; and

generating, by the telephony network headend, a unified media guide based on at least the received personal media guide and the received broadcast media guide.

27. The method according to claim 26, further comprising:

sending the unified media guide to the communications device.

28. The method according to claim 23, further comprising:

sending, by the communications device, the received media content to another communications device coupled to the network.

29. The method according to claim 23, further comprising:

receiving, by the communications device, the media content from another communications device coupled to the network.

* * * * *