



US011975424B2

(12) **United States Patent**
Irwin et al.

(10) **Patent No.:** **US 11,975,424 B2**

(45) **Date of Patent:** **May 7, 2024**

(54) **MULTIPLE ENTRY ANGLE ADAPTOR WITH LOCATOR FOR FASTENER INSTALLATION TOOL**

(71) Applicant: **OMG, Inc.**, Agawam, MA (US)

(72) Inventors: **R. Timothy Irwin**, Lenox, MA (US); **Mark A. Dicaire**, Northborough, MA (US); **Christopher C. Will**, Big Lake, MN (US); **David L. Mathieu**, Colchester, CT (US); **Timothy F. Gillis**, Florence, MA (US); **Arun Srinivasan Venkatesan**, Feeding Hills, MA (US); **Jonathan W. Dezielle**, Agawam, MA (US)

(73) Assignee: **OMG, Inc.**, Agawam, MA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 401 days.

(21) Appl. No.: **16/738,523**

(22) Filed: **Jan. 9, 2020**

(65) **Prior Publication Data**

US 2020/0147765 A1 May 14, 2020

Related U.S. Application Data

(63) Continuation-in-part of application No. 16/168,090, filed on Oct. 23, 2018, now Pat. No. 11,433,511, (Continued)

(51) **Int. Cl.**
B25B 23/00 (2006.01)
B25B 21/00 (2006.01)
B25B 23/12 (2006.01)

(52) **U.S. Cl.**
CPC **B25B 21/002** (2013.01); **B25B 23/0021** (2013.01); **B25B 23/005** (2013.01); **B25B 23/12** (2013.01); **B25B 23/0078** (2013.01)

(58) **Field of Classification Search**
CPC . B25B 21/002; B25B 21/007; B25B 23/0021; B25B 23/0028; B25B 23/005; (Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

975,285 A 11/1910 Robertson
1,631,501 A 6/1927 Payzant
(Continued)

FOREIGN PATENT DOCUMENTS

CN 203553488 U 4/2014
DE 3104460 A1 6/1982
(Continued)

OTHER PUBLICATIONS


Search Report and Written Opinion dated Nov. 9, 2017.
(Continued)

Primary Examiner — Lee D Wilson

(74) *Attorney, Agent, or Firm* — Alix, Yale & Ristas, LLP

(57) **ABSTRACT**

An adaptor for a fastener driver assembly employs a bi-positionable angle guide assembly mounted to a head having an entry reference surface defining an opening for a fastener. The adaptor provides a proper location and entry angle for the fastener for implementing various structural connections. A pivotal angle guide has a pair of reference engagement edges functionally configured to engage either an upper horizontal member or a lower horizontal member. A locator having a location reference is mounted to the guide assembly. In one mode, the reference edges, together with the location reference, define a proper entry location and normal angle for connecting a horizontal member, which may be either an upper plate or a lower plate, to a rim board or other structural member. The selected adaptor position is achieved by securing the adaptor in one of two stable (Continued)



angular positions relative to the drive axis of the fastener driver assembly. In a second mode, the implemented entry angle is oblique to the horizontal member. The adaptor also includes at least one flush indicator to indicate that the proper flush position of a reference surface is achieved. The locator is removably mounted to the pivotal angle guide and mounts a variably positionable position detector with a measurement scale.

19 Claims, 85 Drawing Sheets

Related U.S. Application Data

which is a continuation-in-part of application No. 15/239,047, filed on Aug. 17, 2016, now Pat. No. 10,124,470, which is a continuation-in-part of application No. 14/211,685, filed on Mar. 14, 2014, now Pat. No. 9,452,514.

- (60) Provisional application No. 61/890,905, filed on Oct. 15, 2013, provisional application No. 61/787,170, filed on Mar. 15, 2013.
- (58) **Field of Classification Search**
CPC B25B 23/12; B25B 23/0078; B25F 3/00; B25F 5/021; B25F 5/023
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,651,796	A	12/1927	Arenz	
1,764,053	A	6/1930	Reed et al.	
3,207,023	A	9/1965	Knohl	
3,357,295	A	12/1967	Smith	
3,670,941	A	6/1972	Grinnell et al.	
3,960,191	A	6/1976	Murray	
3,965,950	A	6/1976	MacDonald	
4,295,394	A	10/1981	DeCaro	
4,510,826	A	4/1985	Marks	
4,572,715	A *	2/1986	Wolff	B23B 47/287 408/112
4,689,881	A	9/1987	Fall	
4,890,968	A	1/1990	Beach et al.	
4,900,208	A	2/1990	Kaiser et al.	
5,100,274	A	3/1992	Hasan et al.	
5,447,401	A	9/1995	Jones et al.	
5,540,531	A	7/1996	Choiniere	
5,584,221	A	12/1996	Petrantoni	
5,667,126	A	9/1997	Boucek	
5,740,705	A	4/1998	Graham	
5,791,207	A	8/1998	Ahdoot	
5,827,031	A	10/1998	Swallow	
5,865,584	A	2/1999	Onofrio	
5,921,454	A	7/1999	Larson et al.	
5,947,670	A	9/1999	Larson	
6,050,765	A	4/2000	McGovern et al.	
6,074,149	A	6/2000	Habermehl et al.	
6,109,145	A	8/2000	Habermehl	
6,296,064	B1	10/2001	Janusz et al.	
6,322,307	B1	11/2001	Glover	
6,363,818	B1	4/2002	Habermehl	
6,425,306	B1	7/2002	Habermehl	
6,439,085	B1	8/2002	Habermehl et al.	
6,481,613	B1	11/2002	Tebo	
6,494,322	B1	12/2002	Habermehl et al.	
6,647,836	B1	11/2003	Habermehl	
6,729,522	B2	5/2004	Hempfling et al.	
6,789,991	B2	9/2004	Hsu	

6,862,963	B2	3/2005	Habermehl et al.	
6,915,724	B2 *	7/2005	Kigel	B21J 15/323 81/433
6,945,140	B2	9/2005	Gibbons et al.	
6,990,731	B2	1/2006	Haytayan	
7,029,220	B2	4/2006	Fujiyama et al.	
7,134,367	B2 *	11/2006	Gehring	B25B 23/045 81/57.37
7,287,681	B1	10/2007	Wen	
7,341,146	B2 *	3/2008	Habermehl	F16B 27/00 206/820
7,743,683	B2	6/2010	Dayton et al.	
7,874,232	B2	1/2011	Gauthreaux et al.	
7,900,420	B2	3/2011	Pope	
8,202,032	B2	6/2012	Gillis et al.	
8,220,367	B2	7/2012	Hsu	
8,375,541	B1 *	2/2013	Beachy	B23B 47/287 408/110
8,376,203	B2	2/2013	Martel et al.	
8,403,194	B2	3/2013	Tebo	
8,733,609	B2	5/2014	Weigmann et al.	
8,955,210	B2	2/2015	Vandenberg	
9,144,896	B2	9/2015	Vandenberg	
9,452,514	B2	9/2016	Guthrie et al.	
9,587,662	B2	3/2017	Glass	
9,751,197	B2	9/2017	Vandenberg	
9,802,300	B2	10/2017	Vandenberg	
9,969,068	B2	5/2018	Walters et al.	
10,018,215	B2	7/2018	Walters et al.	
10,603,768	B2	3/2020	Irwin et al.	
2003/0024962	A1	2/2003	Sims et al.	
2003/0031528	A1	2/2003	Kram et al.	
2004/0081535	A1	4/2004	Birkelbach et al.	
2004/0093997	A1 *	5/2004	Huang	B25B 15/001 81/125
2006/0207204	A1	9/2006	Wasitis et al.	
2006/0269380	A1	11/2006	Yin-Feng	
2007/0065255	A1	3/2007	Liu	
2007/0258794	A1	11/2007	Litzinger	
2007/0271761	A1	11/2007	Haytayan	
2008/0260495	A1	10/2008	Gong et al.	
2009/0014495	A1	1/2009	Lin et al.	
2009/0194954	A1 *	8/2009	Hsu	B23B 51/126 279/144
2010/0270352	A1	10/2010	Popovich et al.	
2011/0089218	A1	4/2011	Santamarina et al.	
2011/0110745	A1	5/2011	Shih	
2012/0096701	A1	4/2012	Schachner	
2012/0183371	A1	7/2012	Druschel et al.	
2013/0175314	A1	7/2013	Francis et al.	
2014/0161561	A1	6/2014	Tebo	
2014/0304973	A1	10/2014	Guthrie et al.	
2016/0354904	A1	12/2016	Dicaire et al.	
2017/0320197	A1	11/2017	Dicaire et al.	
2019/0366518	A1 *	12/2019	Tillinghast	B25B 23/0035

FOREIGN PATENT DOCUMENTS

DE	4132504	4/1992
EP	0195851 B1	1/1992
EP	1226901	7/2002
GB	2250559 B	3/1995

OTHER PUBLICATIONS

European Search Report.
Search Report dated Jul. 29, 2014.
"Acutrak Headless Compression Screw System," Acumed, Jun. 2014, retrieved from www.acumed.net/products/screw-pin/acutrak-headless-compression-screw-system/.
"Plywood Design and Application Guide," TECO, p. 5, Jul. 20, 2006.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4A

FIG. 4

FIG. 4B




FIG. 5




FIG. 6




FIG. 8





FIG. 7






FIG. 10




FIG. 11




FIG. 12A




FIG. 12B




FIG. 12C




FIG. 13




FIG. 14




FIG. 15A




FIG. 15B




FIG. 15C




FIG. 15D




FIG. 16A




FIG. 16B




FIG. 17




FIG. 18




FIG. 19A




FIG. 19B




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 25




FIG. 26






FIG. 27






FIG. 29




FIG. 33




FIG. 30




FIG. 31A




FIG. 31B




FIG. 32A




FIG. 32B




FIG. 34A




FIG. 34C






FIG. 35E

FIG. 35D

FIG. 35C

FIG. 35B

FIG. 35A




FIG. 36A




FIG. 36B



FIG. 36C




FIG. 37B




FIG. 37A




FIG. 37C




FIG. 38A




FIG. 38B




FIG. 38C




FIG. 39C




FIG. 39B




FIG. 39E




FIG. 39D




FIG. 39A




FIG. 40B




FIG. 40A




FIG. 41B




FIG. 41D




FIG. 41A




FIG. 41C




FIG. 42




FIG. 43




Fig. 44A




Fig. 44B

Fig. 44




Fig. 45




Fig. 46




Fig. 47




Fig. 48




Fig. 49




Fig. 50





Fig. 51






Fig. 53




Fig. 54




Fig. 55




Fig. 56




Fig. 57A




Fig. 57B




Fig. 58A




Fig. 58B




Fig. 59A




Fig. 59B





Fig. 61A






Fig. 61B

Fig. 62A





Fig. 62B

Fig. 63A





Fig. 63B

Fig. 64A





Fig. 64B




Fig. 65




Fig. 66

Fig. 67




Fig. 68A




Fig. 68B




Fig. 69A




Fig. 69B

Fig. 70A





Fig. 70B

Fig. 71A




Fig. 71B

Fig. 72A




Fig. 72B




Fig. 73A

Fig. 73B




Fig. 74




Fig. 75A




Fig. 75B




Fig. 76




Fig. 77




Fig. 78




Fig. 79




Fig. 80




Fig. 81




Fig. 82




Fig. 83




Fig. 84




Fig. 85A




Fig. 85B




Fig. 86A




Fig. 86B




Fig. 87A

Fig. 87B




Fig. 88A




Fig. 88B




Fig. 89A




Fig. 89B




Fig. 90




Fig. 91




Fig. 92




Fig. 93




Fig. 94




Fig. 95




Fig. 96




Fig. 97




Fig. 98




Fig. 99

MULTIPLE ENTRY ANGLE ADAPTOR WITH LOCATOR FOR FASTENER INSTALLATION TOOL

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a continuation-in-part of U.S. patent application Ser. No. 16/168,090 filed on Oct. 23, 2018, which is a continuation-in-part of U.S. patent application Ser. No. 15/239,047 filed on Aug. 17, 2016, which is a continuation-in-part of U.S. patent application Ser. No. 14/211,685 filed on Mar. 14, 2014, which application claims the priority of U.S. Provisional Patent Application No. 61/787,170 filed on Mar. 15, 2013 and U.S. Provisional Patent Application No. 61/890,905 filed on Oct. 15, 2013, the disclosures of which applications are incorporated herein in their entirety.

BACKGROUND

The present disclosure relates to generally fastening systems employed to connect wood structural members to comply with construction codes. The present disclosure relates generally to tools and methods for installing a fastener to secure wood framing components. More particularly, this disclosure relates to tools and techniques to precisely install fasteners to secure the top plate to roof trusses or rafters.

Local and state building codes, which are typically based on universal codes such as the International Residential Code and the International Building Code, set forth various requirements for securing wooden framing components. Provisions are made in such codes to require that the top plate and the rafters, or roof trusses, must be connected to comply with pre-established connection force standards calculated to resist substantial uplift forces that may be experienced throughout the lifetime of the structure. For locations which are susceptible to high wind uplift and/or seismic activity, typically, a stronger force-resistant connection between the top plate and rafters or trusses is required.

To satisfy building code requirements, the use of metal brackets and a large number of nails are commonly installed using pneumatic nail guns. Many of the structural locations requiring these robust connections are at the top corners of walls and where walls meet roof trusses and the like. These locations typically require workers to stand on ladders and employ a hammer or pneumatic nail guns to nail brackets to roof rafters, roof trusses and the like. A common complaint is that the ladders are not a stable platform and maneuvering bulky nail guns into cramped locations while standing on a ladder is both difficult and dangerous.

The concept of a continuous load path (CLP) from the peak of the roof to the foundation is one that is gaining some popularity in the construction industry. Various devices of straps, brackets, cables, threaded rods and bolts are currently employed to tie various building components together and create an integrated unit where stress on any one structural component is transferred to other components for additional durability.

There are a number of techniques, fasteners and hardware items that are conventionally employed to provide the required connection between the top plate and the rafters or roof trusses. Hurricane clips or other forms of metal straps or clips are traditionally used and secured by multiple nails or threaded fasteners. There is commonly a trade-off between connection integrity and construction efficiency.

For example, hurricane clips, which are effective and widely used in many locations, may require eight or more nails or threaded fasteners to meet the requisite code connection standard.

It is possible to employ threaded fasteners such as elongated screws to replace some of the metal brackets and nails currently employed to meet building codes. However, such screws need to be installed at a particular angle and position to ensure penetration through several wood members to engage, for example, a roof truss or rafter. There is a need for a construction system that would facilitate the use of threaded fasteners to connect building components in a manner that meets building codes and allows building inspectors to visually confirm correct installation of such threaded fasteners.

A highly secure and efficient connection between the top plate and rafters or roof trusses can be implemented by employing multiple specialty six-inch threaded fasteners, such as TimberLOK® wood screws manufactured and marketed by OMG, Inc., of Agawam, Massachusetts. To secure the framing components with the sufficient retentive force, each threaded fastener is driven through the top plate and into the rafters or roof trusses at a $22.5 \pm \text{°}$ optimum angle with respect to the vertical. Although securing multiple threaded fasteners is typically more efficient than attaching a hurricane clip or other strap-type connector, it is difficult to consistently implement a 22.5° angle within a reasonable range of precision. The usage of protractors, levels and other similar-type tools to obtain the optimum angle for the threaded fastener has proven to be clumsy, difficult, time consuming and, at best, only marginally advantageous over more conventional securement methods.

The present disclosure addresses the need for a tool and method for complementing various structural connections by efficiently installing multiple threaded fasteners having a consistently precise optimum connection angle.

SUMMARY

Briefly stated, a multiple entry angle adaptor with a variably positionable locator for a fastener installation tool mounts to a driver assembly to precisely provide a location and entry angle for driving a fastener to achieve an optimum connection for various wood structural components.

In one preferred embodiment, a bi-positionable adaptor for a fastener driver assembly comprises a head which mounts a fastener receiver assembly and has a reference surface with a fastener opening. A connector is configured to mount the head to the driver assembly so that a fastener received in the receiver assembly is drivable through the opening.

An angle guide assembly pivotally mounted to the head comprises a pair of spaced panels with coplanar engagement edges and an orthogonal reference surface. When the guide assembly is at a first angular position and each reference edge engages an upper horizontal member and the reference surface engages a vertical member, a fastener is drivable by the fastener drive assembly through the fastener opening at a first oblique entry angle into the horizontal member. When the guide assembly is at a second angular position and each reference edge engages a horizontal member, a fastener is drivable through the fastener opening at a normal or 90° entry angle into the horizontal member.

The first entry angle relative to a vertical member is preferably approximately 12° . In one application, the vertical member is a stud, the horizontal member is a top plate,

header, a multi-ply beam or a bottom plate. The guide/head assembly has an indicator indicating a flush position of the reference surface.

The angle guide assembly is securably positionable at one of two angularly spaced positions. A fastener receiver assembly of the adaptor further forms a fastener channel leading to the fastener opening and further comprises a magnet assembly for retaining the fastener in the channel.

A fastener installation tool comprises a fastener driver assembly having a distal tube. The head has an entry reference surface and defines a fastener opening in the entry reference surface. A connector is configured to mount the head to the driver assembly at a fixed angular position so that a fastener is drivable through the fastener opening. A guide assembly is pivotally mounted to the head and comprises a pair of spaced members having opposed faces. Each member has an engagement edge perpendicular to the faces. The engagement edges are substantially coplanar and function as a guide for defining the fastener entry angle.

In one embodiment, an adaptor for a fastener driver assembly comprises a head. The head defines a fastener opening and communicates with a fastener receiver assembly. A connector is configured to mount the head to the driver assembly so that a fastener received in the assembly is drivable through the opening. A guide module is pivotally mounted to the head and comprises a pair of laterally spaced panels and defines a reference engagement structure. When the guide module is at a first pivot position and the reference engagement structure engages a member and a fastener is drivable by the fastener drive assembly through the fastener opening at an oblique entry angle and when the guide module is at a second pivot position and the reference engagement structure engages the member, the fastener is drivable through the fastener opening at a normal entry angle into the member.

The first entry angle relative to a vertical axis is approximately 12°. The head defines two lateral openings and the guide module mounts a depressible interlock assembly comprising a pawl engageable into one lateral opening to define a first or second pivot position. The head defines a drive axis and the guide module is pivotal about an axis orthogonal to the drive axis.

In one embodiment, the guide module mounts a variably positionable locator securable in a fixed position. The locator comprises a pair of laterally spaced arms which extend from the guide module and mount a variably positionable elongated position detector. A knob secures the locator in a fixed position. Each of the arms is parallel to the reference engagement structure.

At least one flush indicator indicates a flush position of the reference engagement structure. The flush indicator comprises a spring biased lever having a flag which is withdrawable into an enclosure.

A fastener installation tool assembly comprises a fastener driver assembly. A head has an entry reference engagement surface and defines a fastener opening. A connector is configured to mount the head to the driver assembly at a secured angular position so that a fastener is drivable through the fastener opening. An angled guide assembly is pivotally mounted to the head and has a guide reference. A locator has a locating reference surface and is slidably mounted to the assembly. When the guide assembly is at a first angular position relative to the driver assembly and the locating reference surface engages a vertical edge of the structural member and the guide reference engages a horizontal surface of the structural member. A fastener is drivable by the fastener driver assembly through the fastener

opening at a normal entry angle into the structural member and when the guide is a second angular position relative to the head and the guide reference engages a horizontal surface of the structural member, the fastener is drivable through the fastener opening at an oblique angle into said structural member.

The oblique angle entry is approximately 12° from a vertical line. The fastener is driven into a rim board to connect the structural member and the rim board and the structural member is a top plate, a header, a beam or a bottom plate. The guide reference comprises laterally spaced coplanar edges of a pair of laterally spaced panels. The guide assembly is securable at one of two pivotal positions by a depressible spring loaded member having a pawl.

The locator preferably comprises a pair of elongated arms mounting a platform defining a locator reference surface. The platform defines an elongated slot receiving a position detector. The guide assembly has a pair of bores for slidably receiving the locator arms. Each locator arm is fixedly secured by a knob threadably engaging the guide assembly. The position detector has a variably positionably graduated scale.

A fastener installation assembly comprises a head having an entry reference surface and defining a fastener opening in the entry reference surface. A connector is configured head to the tubular member at a fixed angular position so that a fastener is drivable through the opening. A guide assembly is pivotally mounted to the head and comprises a pair of spaced panels having coplanar reference edges. A locator is removably mounted to the guide assembly and has a movable position locator. When the guide assembly is at a first angular position relative the head and the locator engages a vertical surface and the reference edges engage a horizontal member, a fastener is drivable through the passenger opening into the horizontal member at a first entry angle. When the guide assembly is a second angular position relative to the head and the reference edges engage the horizontal member, the fastener is drivable through the fastener opening at a second entry angle into the horizontal member.

A locator is mounted to the guide assembly and is slidably relative to the guide assembly for positioning at either a frontal location adjacent the guide assembly or a rear location adjacent the rear of the head. The locator comprises a frame. The locator frame has a surface which functions as a position guide.

The arms each have a rounded end. The panels of the guide assembly form a ledge which defines a cam track for the rounded ends of the arms so that the rounded ends ride along the cam track when the position of the locator is changed from a frontal to a rearward position. The arms also have a serrated surface which engages a serrated surface at the end of the cam track of the panels to further prevent transverse movement of the locator when it is disposed in a rearward position. A knob is tightenable against one of the arms to secure the locator in a selected fixed position.

A fastener receiver assembly is mounted to the guide head and defines a fastener channel leading to the opening wherein a fastener is retainable in the channel by means of a magnet assembly. The connector connects the adaptor with an end portion of the distal tube of the driver assembly.

When the guide assembly is secured at a first angular position relative to the head, a locator reference surface engages a vertical member and each engagement edge engages a horizontal member, a fastener is drivable by the fastener driver assembly through the fastener opening at an oblique entry angle into the horizontal member. When the guide assembly is secured at a second angular position

relative to the head, a frontal guide reference surface engages the vertical member and each engagement edge engages a lower horizontal member, a fastener is drivable through the fastener opening at an oblique entry angle into the lower horizontal member.

Preferably, the oblique entry angle is approximately 12° to a vertical line, and the vertical member is a stud with the horizontal member being a top plate, header or multi-ply beam or a bottom plate. In one configuration, the horizontal member is adjacent an external rim board, and the fastener is driven through the horizontal member into the rim board.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a side view, partly broken away, of a fastener installation tool for securing a top plate to a roof support member;

FIG. 2 is a fragmentary top plan view of the installation tool of FIG. 1;

FIG. 3 is a fragmentary partially disassembled side view of the installation tool of FIG. 1;

FIG. 4 is a representative perspective view, partly in schematic, of a structure during its construction phase and illustrating the usage of a fastener to connect a top plate to a roof support member;

FIG. 4A is a fragmentary side sectional view of the structure of FIG. 4, illustrating a fastener connecting a top plate to a roof support member at a location adjacent a vertical stud;

FIG. 4B is a fragmentary side sectional view of the structure of FIG. 4, illustrating a fastener connecting a top plate to a roof support member at a location between vertical studs;

FIG. 5 is a side elevational view, portions broken away to show detail and partly in diagram form, of the installation tool of FIG. 1;

FIG. 6 is a side elevational view, portions broken away to show detail and partly in diagram form, of a modified embodiment of the fastener installation tool of FIG. 1;

FIG. 7 is a perspective view, partly in diagram form, of a guide portion of the installation tool of FIG. 1;

FIG. 8 is a perspective view of the guide portion of FIG. 7, portions being shown in phantom and portions being shown to reveal internal detail;

FIG. 9 is an annotated composite schematic view illustrating the sequential operation of the installation tool of FIG. 1;

FIG. 10 is a side elevational view, partly broken away, of a second embodiment of a fastener installation tool for connecting a top plate with a roof support member;

FIG. 11 is a fragmentary top plan view of the installation tool of FIG. 10;

FIGS. 12A-12C are side elevational views, partly in schematic, illustrating the sequential operation of the installation tool of FIG. 10;

FIG. 13 is a side elevational view, partly broken away, of a third embodiment of a fastener installation tool for connecting a top plate with a roof support member;

FIG. 14 is a fragmentary top plan view of the installation tool of FIG. 13;

FIGS. 15A-15D are annotated representative side elevational views, partly in schematic, illustrating the sequential operation of the installation tool of FIG. 13;

FIGS. 16A-16B are schematic diagrams illustrating the usage and versatility of a representative fastener installation tool for different structural heights and wherein the installers have different heights;

FIG. 17 is a perspective view of a fourth embodiment of an installation tool without the power driver assembly wherein certain external portions are shown as transparent to reveal internal components;

FIG. 18 is an enlarged perspective view of a portion of the installation tool of FIG. 17 wherein certain external components are shown as transparent to reveal internal components;

FIGS. 19A and 19B are top sectional views of portions of the installation tool of FIG. 17;

FIG. 20 is an enlarged end sectional view of the installation tool of FIG. 17 and further illustrating a fastener received in the installation tool;

FIG. 21 is an enlarged generally top plan view of the guide head portion of the installation tool of FIG. 17;

FIG. 22 is an enlarged generally bottom perspective view of a guide head portion of FIG. 21;

FIG. 23 is an enlarged generally opposite side elevational view, portions removed, of a handle assembly for the installation tool of FIG. 17;

FIG. 24 is an enlarged side elevational view, portions in section and portions removed, of the handle assembly of FIG. 23;

FIG. 25 is an enlarged generally right side view of a portion of the handle portion of FIG. 24, taken from the right thereof and partially broken away to show detail

FIG. 26 is an annotated side elevational view, partly in schematic, of an installation tool;

FIG. 27 is a side elevational view, partly in schematic and partly annotated, of an installation tool;

FIGS. 28A and 28B are annotated side views of an installation tool together with an enlarged top plan view of a portion of the tool, respectively;

FIG. 29 is an annotated side elevational view of an installation tool;

FIG. 30 is a schematic view of an installer illustrating a belt holster and a representative installation tool for reception by said holster;

FIGS. 31A and 31B are respectively a schematic view illustrating a bandolier holder for fasteners and a representative installation tool and an enlarged fragmentary front view of the bandolier holder and fasteners;

FIGS. 32A and 32B are respectively a schematic side view of a thigh-mounted fastener holder and a representative installation tool and an enlarged fragmentary front view of the thigh-mounted fastener holder and fasteners;

FIG. 33 is a perspective view of a representative fastener that may be employed in the installation tools;

FIGS. 34A-34D are respectively a side view of a fastener employed in an installation tool, an enlarged top plan view of the fastener and a side elevational view of a fastener with a different tint together with an enlarged top plan view of the fastener with the different tint;

FIGS. 35A-35E schematically illustrate an installer using an installation tool for fastening respectively a truss to a top plate, a stud to a top plate, a stud to a bottom plate, a bottom plate to a rim, and a top plate to a rim;

FIGS. 36A-36C are respectively a perspective view, a diagrammatic side view and an end view of a fastener which may be employed for an installation tool;

FIGS. 37A-37C are respectively a diagrammatic view of a fastener which may be employed for an installation tool, a perspective view of the fastener and a top plan view of the head of the fastener;

FIGS. 38A-38C are respectively fragmentary portions of a perspective view of a representative construction illustrat-

ing the use of a bracket assembly, an exploded view of the brackets, and a side sectional view illustrating the mounting of the brackets;

FIGS. 39A-39E respectively illustrate another bracket for construction in connection with a portion of a truss, a schematic view of a fastener in connection with a second truss assembly portion together with the brackets, a third side end view of the bracket together with a fastener in a truss assembly, a perspective view of the bracket and a side elevational view of the bracket;

FIGS. 40A-40B respectively illustrate a perspective view of another bracket as mounted in place and a top view in a preassembled stage for the bracket;

FIGS. 41A-41D respectively illustrate a first step and tool which may be employed in installing the bracket of FIGS. 40A and 40B, a second step in the installation process, a third step in the installation process, and an installed view of the bracket

FIG. 42 is a representative perspective view of a structure during its constructive phase and illustrating another embodiment of an installation tool guide head;

FIG. 43 is a representative perspective view, partly in schematic, of a structure during its construction phase and illustrating a further embodiment of an installation tool guide head;

FIG. 44 is an annotated schematic view illustrating a fastener installation tool adaptor as used in connection with fastening a wall stud to a top plate and as used in fastening a wall stud to a bottom plate;

FIG. 44A is an enlarged schematic view of the adaptor and wall stud/top plate portion of FIG. 44;

FIG. 44B is an enlarged schematic view of the adaptor and wall stud/bottom plate portion of FIG. 44;

FIG. 45 is a perspective view of the adaptor of FIG. 44;

FIG. 46 is a perspective view of the adaptor of FIG. 45 from a different perspective;

FIG. 47 is a side view, portions in phantom, of the adaptor of FIG. 45;

FIG. 48 is a diagrammatic bottom plan view, portions in phantom, of the adaptor of FIG. 47;

FIG. 49 is a right side view, portions in phantom, of the adaptor of FIG. 47;

FIG. 50 is a side view, portions in phantom, of a modified adaptor;

FIG. 51 is a bottom plan view, portions in phantom, of the modified adaptor of FIG. 50;

FIG. 52 is an annotated schematic view illustrating the usage of another embodiment of a fastener installation tool adaptor to fasten a top plate to lateral blocking, to fasten a plate to a rim board/lateral blocking from an upper installation position and to fasten a top plate to a rim board/lateral blocking from a lower position;

FIG. 52A is an enlarged schematic view of the adaptor and plate/lateral blocking of FIG. 52;

FIG. 52B is an enlarged schematic view of the adaptor and bottom plate/rim board/lateral blocking from a mid-position of FIG. 52;

FIG. 52C is an enlarged schematic view illustrating the adaptor and top plate/rim board/lateral blocking from a lower position;

FIG. 53 is a frontal view of the fastener installation tool adaptor of FIG. 52;

FIG. 54 is an enlarged view of the adaptor of FIG. 53 in a top pivot position;

FIG. 55 is a side view of the adaptor of FIG. 53 in a bottom pivot position;

FIG. 56 is a side elevational view of the adaptor of FIG. 53 in a top pivot position;

FIGS. 57A and 57B are respectively side views of a dual positionable adaptor and a fastener driver assembly in a dismounted and mounted disposition for a first installation position;

FIGS. 58A and 58B are respectively enlarged side views of the adaptor and a portion of the driver assembly of FIG. 57A in a dismounted and mounted disposition for the first position;

FIGS. 59A and 59B are respectively side views of the adaptor and driver assembly of FIG. 57A in a mounted and a dismounted disposition for a second installation position;

FIGS. 60A and 60B are respectively enlarged side views of the adaptor and driver assembly of FIG. 59A in a mounted and a dismounted position illustrating the second installation position;

FIGS. 61A and 61B are perspective views of the dual positionable adaptor respectively illustrating a flush indicator in a non-flush mode and a flush mode;

FIGS. 62A and 62B are generally bottom and left end perspective views, respectively, of the dual positionable adaptor;

FIGS. 63A and 63B are respectively a side view and a bottom plan view of the dual positionable adaptor;

FIGS. 64A and 64B are central sectional views of the dual positionable adaptor illustrating a non-flush mode and a flush mode for the adaptor for a first and a second flush indicator, respectively;

FIG. 65 is a central sectional view of the dual positionable adaptor with a received fastener with indicators in a flush mode;

FIG. 66 is a fragmentary enlarged sectional view of the adaptor and fastener of FIG. 65;

FIG. 67 is an exploded perspective view of portions of the dual positionable adaptor;

FIGS. 68A and 68B are perspective views of the adaptor and a portion of the drive assembly illustrating an unsecured and secured position, respectively, for the adaptor and driver assembly at a first installation position;

FIGS. 69A and 69B are side views of the adaptor and driver assembly portion of FIGS. 68A and 68B, respectively;

FIGS. 70A and 70B are perspective views of the adaptor showing the pivoting transformation of a wing from a tandem wing relationship to a pivoted position, respectively;

FIGS. 71A and 71B are side views of the adaptor illustrating the wing positions of FIGS. 70A and 70B, respectively;

FIGS. 72A and 72B are perspective views illustrating the adaptor transformation of a wing from a tandem relationship to a pivoted position, respectively;

FIGS. 73A and 73B are side views of the adaptor positions illustrating the wing portions of FIGS. 72A and 72B, respectively;

FIG. 74 is a fragmentary side perspective view illustrating how the wing pivoting is achieved and secured;

FIGS. 75A and 75B are fragmentary side views of the adaptor illustrating an adaptor installation position for a stud to bottom plate configuration from a side and a rear view, respectively;

FIG. 76 is a perspective view of a multiple entry angle adaptor with a locator for a fastener installation tool;

FIG. 77 is a second perspective view of the adaptor of FIG. 76;

FIG. 78 is a third perspective view of the adaptor of FIG. 76;

FIG. 79 is a fourth perspective view of the adaptor of FIG. 76;

FIG. 80 is a sectional view taken of the adaptor as shown in FIG. 79;

FIG. 81 is a side elevational view of the adaptor of FIG. 76;

FIG. 82 is a central sectional view of the adaptor as shown in FIG. 81;

FIG. 83 is an opposite side elevational view of the adaptor as shown in FIG. 81;

FIG. 84 is a front elevational view of the adaptor as shown in FIG. 81;

FIGS. 85A and 85B are side elevational views of the adaptor of FIG. 76 illustrating a fastener installation shown in section in a representative application for an overhead external rim board connection;

FIGS. 86A and 86B are side elevational views of the adaptor of FIG. 76 in a second entry angle mode and further illustrating a fastener installation shown in section connecting a header to an overhead member;

FIGS. 87A and 87B are side elevational views of the adaptor of FIG. 76 in a second entry angle mode and further illustrating a fastener connector shown in section connecting a header to another overhead member;

FIGS. 88A and 88B are side elevational views of the adaptor of FIG. 76 illustrating a fastener installation shown in section connecting a member to a lower external rim board;

FIGS. 89A and 89B are side elevational views of the adaptor of FIG. 76 in a second entry angle mode and illustrating a fastener installation shown in section connecting a stud with an underlying member;

FIG. 90 is a perspective view of a multiple entry angle adaptor with a locator;

FIG. 91 is a perspective view of the multiple entry angle adaptor of FIG. 90 with the locator in a second position;

FIG. 92 is a side view, portions removed, of the multiple entry angle adaptor of FIG. 90;

FIG. 93 is a side sectional view of the multiple entry angle adaptor of FIG. 92;

FIG. 94 is a perspective view of the multiple entry angle adaptor of FIG. 90 with a portion of the locator removed;

FIG. 95 is an enlarged fragmentary perspective view of the multiple entry angle adaptor of FIG. 94;

FIG. 96 is a side view, portions removed, of the multiple entry angle adaptor of FIG. 90 with the adaptor being configured in a second entry angle mode;

FIG. 97 is a side sectional view of the multiple entry angle adaptor of FIG. 96 at the second entry angle mode thereof;

FIG. 98 is a side elevational view of the multiple entry angle adaptor of FIG. 90 in the first entry angle mode and illustrating a fastener installation shown in a section connecting a header to a rim board; and

FIG. 99 is a side elevational view of the multiple entry angle adaptor in the second entry angle mode of FIG. 96 and further illustrating a fastener installation shown in connecting a header to another rim board.

DETAILED DESCRIPTION

With reference to the drawings wherein like numerals represent like parts throughout the several figures, a fastener installation tool is generally designated by the numeral 10. The fastener installation tool 10 is a heavy-duty hand tool adapted for installing threaded fasteners 12 at a consistent angle of approximately $22\frac{1}{2}^\circ$ (to the vertical) into a top plate for connection with a roof support member.

As best illustrated in FIGS. 4, 4A and 4B, for a representative structure 20 for which the installation tool 10 is particularly adapted, a top plate 22, which may include a single 2x4 or a double 2x4, is mounted at the top of spaced vertical studs 24. Roof support members 26 of roof trusses 28 are mounted and supported on the top plate 22. Threaded fasteners 12 are driven into the top plate at a $22\frac{1}{2}^\circ$ angle for engagement with the roof support member 26. Multiple spaced threaded fasteners 12 are sequentially driven at pre-established spacings to provide the proper uplift resistance.

FIG. 4A illustrates the fastener driven at the upper location of the stud 24. FIG. 4B illustrates the fastener as driven at the location along the top plate between the vertical studs 24. The fasteners 12 are each preferably a six-inch fastener having a continuous threaded portion with a pointed tip and a head defining a socket or a six-inch TimberLOK® fastener manufactured and marketed by OMG, Inc., of Agawam, Massachusetts. The TimberLOK® fastener 12 has a hex head 14 and a drill tip 16. Alternative configurations for head 14 are also possible.

As will be further described below, the installation tool 10 is preferably dimensioned, principally by means of the length of a telescopic tube assembly 30, to provide an installation tool which may be effectively used by installers having a wide range of height and reach for a wide range of commonly vertically dimensioned structures. The principal function of the telescopic tube assembly 30 is to exert positive forward or upward pressure against the top plate/roof support interface.

With reference to FIGS. 5 and 6, representative tube assembly lengths are designated by L and l and representative fastener lengths are designated by D and d which also represents the travel distance to drive the screws. For one example in FIG. 5, $L=36.14"$ and $D=8"$. In FIG. 6, $l=27.4"$ and $d=6"$. The telescopic tube assembly 30 preferably has a maximum length of between 27.4 inches and 36.14 inches to accommodate the height and reach of the installer. For a six-inch fastener 12, the telescopic assembly 30 must retract 6 inches to drive the fastener, as will be described below.

The installation tool 10 dimensions allow for the tool to be effectively and efficiently used for connecting the top plates 22 to the roof support members 26 without requiring the use of a ladder, platforms or other means for providing the proper effective height relationship for driving the fasteners 12. Moreover, the proper fastener angle may be sequentially implemented from location to location along the top plate 22 to ensure a proper consistent angle for each of the multiple fasteners and to provide an integrated composite connection having an uplift resistance of high integrity.

The installation tool 10 preferably comprises a driver assembly 40 which includes a power driver 42. The driver 42 may be a conventional drill gun such as DeWalt™ model or an impact driver. The elongated telescopic tube assembly 30, which may have a rounded, rectangular or other profile, is mounted over and attaches to the forward torque end 44 of the driver 42. The telescopic tube assembly 30 comprises a proximal tube 32 which receives and mounts the driver 42 and a longer tube 34 secured to the tube 32. During fastener driving, tube 32 slides relative to tube 34 which essentially remains stationary in relation to the components to be connected by the fastener. Tube 34 terminates in a distal end 36.

A fastener guide assembly 50 is mounted at the distal tip 36 of the tube assembly. The guide assembly 50 provides the proper alignment structure for implementing the preferred

22½° entry angle for the fastener. The assembly **50** also engages the support member for stabilizing the installation tool during the driving process. The guide assembly **50** is dimensioned in accordance with the dimensions of a given fastener. The guide assembly has a fastener channel **52** which functions to receive and load the fastener in a muzzle-loading fashion. The fastener drill tip **16** is positioned proximate the channel opening **53**. The fastener is inserted head **14** first into the fastener channel **52** of the guide assembly. The fastener head **14** is engaged by a complementary torque coupler **43**, such as a socket, for a hex thread fastener or a projecting coupler for a fastening head socket at the applicator end of the torque drive assembly train **45**. The drive train **45**, which may include multiple components, extends through and is housed within the tube assembly **30** and is driven by the torque driver **42**.

With reference to FIGS. **7** and **8**, guide assembly **50** is preferably a cast or molded member of a lightweight rigid form which is mounted at the distal end **36** of the tube assembly. The guide assembly **50** has a frame **60** with a planar locating or engagement surface **62** disposed at an acute angle with respect to lower planar mounting surface **64**. Mounting surface **64** preferably engages against the end of the tube assembly and transversely extends across the end of the tube **34**. A planar end plate **66** is preferably perpendicular to surface **62** and is positioned and configured to closely approach or even contact the underside of the roof support member **26** (as will be explained below). The acute angle is preferably 22½°, although other angles may be provided depending on the intended application of the installation tool **10**.

The fastener channel **52**, which may be formed by a cylinder, has a central axis which is perpendicular to the surface **64**. The fastener channel axis is disposed at an acute angle of preferably 22½° to the surface **62**. Surface **62** defines the channel opening **53**. The channel **52** receives the fastener **12** so that the head **14** is proximate and readily engageable with the torque coupler **43**.

A transverse slot **65** receives an alignment bracket **68** having a T-shaped section which protrudes transversely at opposed sides of the engagement surface **62** and also projects outwardly from the surface **62**. The alignment bracket **68** is positioned and configured to fit or ride below the 2x4 of the top plate **22** to ensure proper perpendicular alignment with the top plate **22**. The alignment bracket **68** may be secured in the frame by a friction or interference fit or may be secured by a fastener (not illustrated) to the frame and can be transversely moved. In one embodiment, the bracket **68** is located approximately 1⅞ inches below the end plate **66**.

The upper portion of the frame is traversed by a slot **69** which receives a metal stabilizer plate **70**. The stabilizer plate is secured in place by a threaded adjustment knob **72**. The knob **72** connects with a threaded rod **74**. The rod extends through an opening in the plate **70** and threads into a central threaded opening **75**. The stabilizer plate **70** preferably has a square configuration with four vertices which form edges **76**. The edges **76** are sharpened. When the plate **70** is mounted in position, one edge **76** or vertex projects upwardly from the end surface **66** of the frame. Openings **78** are provided in the plate to provide a height adjustment for vaulted ceilings and other configurations. Alternatively, the projecting structure is in the form of a barb.

The function of the stabilizer plate **70** is to provide a stabbing point to engage into the wood proximate the interface of the top plate **22** and the roof support member **26** to thereby stabilize the tool and prevent movement while the

fastener is being torqued by the installation tool. The stabilization is especially important at the initial stages of driving the fastener.

In addition, the stabilizer plate functions to present a stabbing point so that upon inspection, an inspector will readily perceive that the fastener is at the proper angle.

The guide assembly **50** is positioned by the installer at the intersection of the top plate **22** and the roof support member **26** with the projecting stabilizer plate edge **76** engaging into the wood and the engagement surface **62** engaging in surface-to-surface relationship against the vertical side of the top plate **22**. The end surface **66** is typically positioned proximate the underside of the roof support member **26**, but is slightly offset due to the less than complete penetration of the stabilizer edge, and the alignment bracket **68** engages the lower edge portion of the top plate **22**.

Prior to engagement of the guide assembly with the top plate/roof support structure (as previously described), a fastener **12** is dropped into the fastener channel **52** with the fastener head **14** proximate to or engaging with the complementary coupler **43**. A portion of the fastener **12** is typically initially received in a chamber of tube **34** adjacent the distal end **36**. The fastener drill tip **16** is proximate the channel opening **53** in the engagement plate **62**. It will be appreciated that the guide assembly **50** as properly positioned provides the proper entry point and entry angle for the fastener **12** as the fastener is driven through the top plate **22** into the roof support member **26**.

With reference to FIGS. **42** and **43**, alternative embodiments of the guide assembly that mount to the end of the telescopic tube assembly of an installation tool are generally designated as guide head **150A** and guide head **150B**, respectively. These guide heads include additional features both for providing the proper alignment and positioning for the screw and for enhancing the ability of the operator and/or an inspector to verify that a proper connection has been made. Each of the guide heads has a frame **160** with a planar locating surface **162** disposed at an acute angle with respect to a tube assembly. Locating surface **162** defines a channel opening for the fastener channel access of the tube assembly. A planar end plate **166** is configured to engage or closely approach the underside of the roof support member **26**.

An L-shaped bracket preferably extends transversely at opposed sides of the engagement surface and projects outwardly from the surface to provide an alignment bracket **168** to engage the vertical support **24**. Bracket **168** may be adjustable. A pair of arms **180** and **182** is pivotally mounted at the top of the frame. One or more of the arms **180** and **182** may be pivoted upwardly to engage a vertical side of member **26** and provide a proper positioning relative to the roof support member **26**.

A stabber point **170** projects through the end plate **166**. In addition, the upper portion of the frame mounts a linear ink pad **190**. In the embodiment position illustrated in FIGS. **42** and **43**, the guide heads **160A** and **160B** have not been positioned against the roof support member **26**. Upon proper positioning, the pivotal arms **180** and **182** would engage against the sides of the support member **26**, and the ink pad would make a linear mark indicated at **191** on the bottom of the roof support member **26**. In addition, the stabber **170** would stab into the wood and leave a mark **171** as indicated. It should be appreciated that either the ink mark **191** or the stab mark **171** could be used to identify both the proper fastener as well as the proper entry angle of the fastener and accordingly indicate that a proper connection has been completed.

The guide head **150B** illustrated in FIG. **43** has a pair of barbs **176** projecting from the end plate **166**. When properly engaged under the roof support member **26**, the pair of barbs would provide two marks **177** which would again provide a unique marking for indicating the proper connection. Of course, the barbs **176** also enhance the stability of the installation tool and the fastener during the installation process.

The installation tool preferably includes an auxiliary handle (in addition to the handle on the driver **40**) to facilitate two-handed positioning and stability during the driving process. Various auxiliary handle configurations can be employed.

With reference to FIGS. **2** and **9**, an auxiliary handle **80** is slidably mounted to the tube and is longitudinally adjustable to provide an auxiliary handle for the installer. The handle **80** includes a rear grip **82** which radially projects radially or quasi-radially relative to the longitudinal axis of the tube assembly. A forward rod **84** extends from the grip generally parallel to the tube assembly. The rod **84** connects to a forward yoke **86** which envelopes the outer surface of the tube assembly and is slidable along the tube assembly. The intermediate portion of the rod is received in a cam lock **88** carried by the fixed proximal tube **32** that mounts to the forward portion of the driver **42**. The rod locks in place with the cam lock **88**.

The tube **34** telescopes with the proximal tube **32** and is slidably receivable throughout the driving of the fastener **12** in the installation process as the fastener is driven to complete the connection. The changing dynamic relationships of the fastener **12**, the guide assembly **50**, the telescopic tube assembly **30** and the handle **80** at the various stages of installation are illustrated in FIG. **9**.

The auxiliary handle **80** is selectively adjustable by the installer to provide maximum stability and comfort to the installer. The handle locks in place with a pin **85**. The handle **80** is initially adjustable. A button **87** is pressed to release the telescoping tube **34** from its fixed relationship with the proximal tube **32** and drive the threaded fastener. The handle **80** essentially remains stationary as the driver moves during the installation progress, as best illustrated in FIG. **9**. The tube **32** retracts relative to tube **34** to accommodate the progressive expelling of the fastener **12** from the fastener chamber **52**. The telescoping tubes **32** and **34** only lock when in the fully driven position, at which point, the fastener **12** is fully driven.

It should be appreciated that approximately six-inch driving link is required for driving a six-inch fastener.

With reference to FIGS. **10**, **11** and **12A-C**, an automatic locking handle is generally designated by the numeral **90**. The handle **90** is generally configured to radially extend from the proximal tube **32** and slide along the tube **32** during the driving process until it automatically locks at the full drive position. The handle has an orthogonally projecting grip **92** which connects with a yoke **94**. The yoke **94** wraps around the tube **32** and is exteriorly slidable therealong.

The automatic locking handle **90** is automatically locked by the use of balls **96** which are entrapped in a bearing **98**. The driving rod **49** has a varying diameter along a longitudinal portion. As best illustrated in the sequence of FIGS. **12A-C**, as the fastener **12** is driven, the geometry of the driving rod has reduced diametric surfaces allowing the balls to slip by and the outer distal tube **34** to fully telescope. The external handle can be placed anywhere along the proximal tube **32**. It will be appreciated that as the fastener **12** is

driven, the handle is rearwardly displaced toward the driver **42** until a fully locked position is obtained and the telescoping tube **34** is retracted.

With reference to FIGS. **13**, **14** and **15A-D**, another handle which may be employed for a third embodiment of a fastener installation tool is generally designated by the numeral **110**. The handle **110** includes a circumferential grip **112** which extends around the proximal tube **132**. The grip **112** may be easily moved along the base tube **32** and tightened in position or loosened by means of a twisting motion on the grip about the longitudinal axis of the tube assembly **30**.

A protrusion **114** rides within an internal slot **116** which is attached in fixed relationship to the driver **42**. The proximal tube **132** forms the internal slot **116**, and the sliding tube **134** includes an external rib **147**. The internal slot **116** is not aligned with the rib **147** in the dormant/non-drive state (FIG. **15A**). As the driver starts to drive, the protrusion **114** starts to ride in the internal slot **116** until it changes geometry and twists, thereby causing the handle to twist (FIGS. **15B-C**). The foregoing continues until the second slot is aligned with the external rib, thereby allowing the tube **134** to fully telescope inwardly (FIG. **15D**). When the installer feels the handle **110** rotate slightly, the installer knows that the fastener **12** has been sufficiently initially driven, and the installer can release the grip **112** on the handle and place both hands on the driver **42**.

Naturally, other handles are possible. In some embodiments, an auxiliary handle as such is not required. In such embodiments, the installer merely grips along the tube assembly at a location that appears to be most advantageous.

The installation tool **10** is preferably battery powered and includes a chargeable battery power pack. However, in some embodiments, the power driver (not illustrated) may be directly electrically powered and include a cord which connects with the power line.

With reference to FIGS. **16A** and **16B**, two different structural heights of the top plane **22** and two appropriately dimensioned installation tools for relatively tall and short installers (shown in silhouette) are illustrated, it should be appreciated that the dimensioning of the telescopic tube assembly **30**, in terms of longitudinal length, is established to accommodate the preferred application in connection with connecting a top plate **22** to a roof support member **26** without the installer needing a ladder or a platform to obtain the correct reach for driving the fastener. In addition, because the height and reach of an installer may significantly vary, the length of the telescopic tube assembly **30** is preferably selected to accommodate a wide range of installers' physical dimensions.

For applications wherein a fastener greater than 6 inches or even less than 6 inches may be applicable, an alternative guide assembly may be employed. For such a guide assembly, the effective depth of the fastener channel is altered. In addition, the telescopic extremes of the telescopic tubes **32** and **34** are adjusted to accommodate for the driving length for the fastener. Naturally, the coupler of the installation tool is adapted to complement the head of the fastener.

It should also be appreciated that for applications in which an angle other than $22\frac{1}{2}^\circ$ is desired, the guide assembly may also be configured so that the fastener channel is at an acute angle relative to the engagement surface at the prescribed optimum angle. Naturally, the position of the alignment bracket **68** may also be varied in accordance with a specific project. Multiple guide assemblies for various installation angles may be provided and attached to the telescopic tube assembly as desired.

For some embodiments, the power driver **40** is easily dismounted from the telescopic tube assembly **30**. The telescopic tube assembly may employ a receiver configured to receive and functionally attach to a wide range of dismountable drill guns without the torque driver being fully integrated with the telescopic tube assembly.

With reference to FIGS. **17-25**, another embodiment of an installation tool (which does not show the power driver assembly) is generally designated by the numeral **200** (FIG. **17**). Installation tool **200** includes a receiver **202** for the power driver assembly (not illustrated), a telescopic tube assembly **230** comprising telescopic tubes **232** and **234**, and a fastener guide head assembly **250** which is mounted at the end **236** of tube **234**.

A handle assembly **210** is disposed in longitudinally fixed relationship to tube **234** and includes a trigger **212** which is depressible into one of essentially two positions. One partially depressed position of the trigger **212** allows for the handle assembly to be angularly adjusted about the longitudinal axis of the distal tube **234** at a preset defined angular position. The full depressed position of the trigger **212** allows for the proximal tube **232** to be retracted relative to the distal tube **234** when the fastener **12** is driven. The handle assembly **210** also provides for two-handed support of the tool so that the stabilizing edge **276** can be effectively stabbed into the support member. It should be appreciated that the tubes **232** and **234** do not rotate relative to each other with the non-rotatable position being ensured by a longitudinal flat **236** which engages through the handle assembly.

With reference to FIGS. **19A-B** and **23-25**, the handle **210** has a grip portion **214** which carries the trigger **212**. The handle assembly **210** is attached to the distal tube **234** by a yoke **240** which is longitudinally fixed between a pair of collars **241** and **243**. The trigger **212** moves a ramp **216** which engages complementary ramp **218** of a plunger **220**. The plunger **220** has a radially acting detent **222** which is biased inwardly into the tube **234**.

A plurality of (preferably five) recesses **225** are angularly spaced in fixed relationship to the outer tube **234**. The projectable detent **222** is longitudinally aligned with the recesses **225** and receivable in a selected recess for retention under the plunger bias. Upon depressing the trigger **212**, the detent **222** is retracted from a recess **225**. Angularly rotating the grip **214** relative to the distal tube **234** allows detent **222** to be angularly engageable into a selected recess **225** to fix the angular position of the handle assembly **210** as desired by the installer. That angular position is further secured by a thumb screw **246** at the top which is tightened to secure the desired angular position.

A pair of internal collar mounts **245** and **247** are respectively fixedly mounted interiorly of the tubes **232** and **234**. The mounts allow rotational and axial movement of the drive train. A spring **248** bears against the mounts and essentially biases the tubes **232** and **234** to a maximum extended position which is limited by a stop **249**. The spring **248** may be optional. Stop **249** allows for replacement of the driver bit **282** to complement the fastener head. The plunger detent **222** also extends through an opening **223** to prevent movement between the distal tube **234** and the proximal tube **232** and thus fix the effective tool length. When the trigger **212** is fully depressed, the plunger is retracted from the opening **223** to allow the proximal tube to move relative to the distal tube against the bias of the spring **248** until the fastener is fully driven.

With additional reference to FIGS. **5**, **17** and **20-22**, a dual floating alignment bushing or receiver guide **280** is mounted at the interior of the distal tube **234** and has a central opening

which receives the output coupler **284** of the drive train **282**. The guide **280** ensures a concentric alignment between the fastener and the driver. The dual receiver guide **280** has a double conical or funnel-like constriction **286** which receives the head **14** of the fastener **12** and centers it for engagement by the coupler **284** as illustrated.

A fastener guide head assembly **250** is mounted at the distal tip **236** of the tube assembly. The guide head assembly **250** has a generally cylindrical base **251** which is retained to the distal tube **234** by means of one or more set screws **239** (FIG. **17**). A sleeve **252** extends through the base **251** to form a channel which receives and guides the fastener **12**. Surface **262** defines the sleeve input opening **253** to sleeve **252** for the fastener as correspondingly described with respect to guide assembly **50**. The sleeve **252** receives the fastener so that the head **14** is properly positioned to be readily engageable by the torque coupler **282**. The major thread diameters of the fastener **12** and the interior diameter of the sleeve **252** are configured so that the interior diameter of the sleeve is only slightly larger than the major thread diameters of the fastener. Preferably, the maximum diameter of the head **14** is approximately equal to the major diameter of the threads. It will be appreciated that as the fastener **12** is loaded into the guide head assembly **250**, the head **14** moves through the sleeve or channel **252** and is convergently directed via the funnel-like constriction **286** (FIG. **20**) toward engagement with the torque coupler **284** of the drive train. The coupler **284** is also axially centered by the dual receiver guide **280**. The dual receiver guide **280** can axially move or float within the tube. The movement is inwardly limited by a dimple **281**.

The guide head assembly **250** is preferably a cast or molded member of lightweight rigid form which includes a frame extending from the base with a planar engagement surface **262** disposed at an acute angle with respect to the lower planar mounting surface **264**. Mounting surface **264** preferably engages against the end of the tube assembly and transversely extends across the distal end **236** of the tube **234**. A planar end plate **266** is parallel to surface **264** and positioned to engage the underside of the roof support member **26**. The acute angle is preferably $22\frac{1}{2}^\circ$, although other angles may be provided depending on the intended application of the installation tool. The specific angle can be provided with a guide head assembly having the required angle of the sleeve or guide channel relative to the engagement surface **262**.

A transverse slot **265** receives an L-shaped alignment bracket **268** which protrudes transversely at opposed sides of the engagement surface **262** and also projects outwardly from the surface **262**. A set screw **271** secures the bracket **268** and allows the bracket **268** to be adjusted laterally, for example, when required at corners. The alignment bracket **268** is positioned and configured to fit below the 2×4 at the top plate **22** to ensure proper perpendicular alignment with the top plate. For corner configurations, the alignment bracket **268** may be moved to an extreme lateral position, either left or right of the position as shown in FIG. **21**.

The upper portion of the frame is traversed by a slot **269** which receives a metal stabilizer plate **270**. The stabilizer plate is secured by an adjustment knob **272** which connects with a threaded rod **274**. The rod extends through an opening in the plate and threads into separate threaded opening **275**. The stabilizer plate **270** preferably has a square configuration with four vertices which form edges **276**. The edges **276** are sharpened. When the guide head assembly **250** is properly positioned a sharp edge **276** projects upwardly from the edge surface **266** of the frame. The function of the stabilizer plate **270** with edge **276** is to provide a stabbing structure to

17

engage into the wood proximate the interface of the top plate 22 and the roof support member 26 to thereby stabilize the tool 200 and prevent movement or walking while the fastener 12 is being torqued by the installation tool. The stabilization is important at the initial stages of driving the fastener.

FIGS. 26-29 illustrate installation tools 300, 400, 500 and 600 which incorporate various adaptors for coupling with the conventional rotary driver tools.

FIG. 26 illustrates an installation tool 300 which an adaptor 302 for attachment to the type of rotary driver tool which includes a collar mounted auxiliary handle. Such handles are frequently found on hammer type drills to provide additional leverage for the user. In this case, the disclosed adaptor 302 replaces the auxiliary handle of the driver tool 340 with a collar attachment to secure the adaptor to the rotary driver behind the chuck. The chuck is used to secure the extended length drive shaft to the rotary driver and a grip 310 permits the user to securely grasp and maneuver the tool 300 and adaptor 302. The grip 310 of the tube assembly 330 receives a manually fed plunger front portion. The plunger front portion is configured to telescope inside the grip of the adaptor during screw installation. The manual feed plunger incorporates a screw guide 353 which surrounds and guides the screw during installation. The guide head 350 is configured to permit the user to accurately place the screw in the center of a wood structural member so that the screw will be installed centered on the truss and parallel to truss orientation, and preferably at a 22.5° angle with respect to a vertical direction. This 22.5° angle is selected to ensure that the installed screw passes through the lower building components and accurately penetrates an upper building component, for example a roof truss. It will be apparent to those skilled in the art that other angles may be suitable for other applications and that alternative plunger tip configurations will be desirable for other screw installations.

The rotary tool adaptor illustrated in FIG. 26 includes a cylindrical screw magazine 390 disposed about the grip 310 of the tube assembly 330. In this embodiment, screws 392 are removed from the magazine 390 and manually inserted into the screw guide 353 located in the plunger front end of the tube assembly 330. The screw guide is configured to closely receive a screw without excess radial space around the screw. The screw guide is configured to accurately start and deliver the screw 392 through the wood structural members. The length of the screw and the intended structural purpose of the installation require precise guidance and delivery of the screw through the associated wood members.

FIG. 27 illustrates an installation tool 400 with a second embodiment of a tool adaptor for use with the disclosed construction system. The embodiment of FIG. 27 illustrates a pistol grip adaptor 402 configured to engage a rotary driver tool 440. The pistol grip permits the user to maintain control over the adaptor and rotary tool during screw installation. This embodiment also includes a grip 412 forward of the pistol grip 410 and a plunger/screw guide 453 at the forward end of the tube assembly 430. The tip of the plunger/screw guide is configured to assist the operator to drive screws at the 22.5° angle (FIG. 27, lower right), though other tip configurations and angles are compatible with the disclosed construction system. The embodiment of FIG. 27 shows an arrangement where the position of the pistol grip 410 is adjustable on the rear portion of the tube assembly 430. This arrangement permits the user to customize the ergonomics of the adaptor to the task and an operator. A lever actuated cam lock system 414 allows the user to disengage the pistol

18

grip 410 from a tubular rear portion and to fix the pistol grip in a selected alternative position. FIG. 27 illustrates a view of a guide head 450 for the screw guide plunger which includes a sight line enhancing an operator's ability to center the screw on a structural member during installation.

FIGS. 28A and 28B illustrate an installation tool 500 with an alternative embodiment of a tool adaptor 502. The embodiment of FIGS. 28A and 28B includes a pair of flexible arms 504 configured to elastically deform and grip the sides of a rotary driver tool 540. Thermoplastic resin pads 506 enhance frictional engagement between the arms and the sides of the rotary tool. The adaptor 502 of FIGS. 28A and 28B also includes an extended grip area 510 for use by the operator. The screw guide/plunger front end of the adaptor is shown with one of several contemplated plastic guide heads 550. The illustrated head 550 is configured to aid the operator in installing a screw at a 22.5° angle relative to the vertical as previously described. A plurality of plastic tips for mounting on the end of the screw guide can be swapped out for different screw installation purposes.

In installation tool 600 with a further alternative tool adaptor 602 is disclosed in FIG. 29. In this embodiment, the adaptor is secured to the rotary tool by a ratchet type strap 604 extending from the sides of the adaptor around a rear portion of the rotary tool 640. This configuration permits the adaptor to be securely integrated with the rotary tool. Various means may be provided to tighten the ratchet strap in a manner similar to arrangements used on snow sport bindings for example. In the embodiment of FIG. 29, the rear grip portion 610 has an ergonomic shape and a textured grip area to enhance operator ease of use and safety. The embodiment of FIG. 29 shows a molded plastic plunger guide head 650 with an integrated molded 6" screw clip 690. The grip portion 610 is configured to permit the forward plunger portion to recede into the grip portion during screw delivery. A pump action screw feeder is illustrated where screws are moved from a clip to a screw guide by manual cycling of the manual pump grip 695. Once the first screw is manually fed into the screw guide, further screws may be delivered with the longitudinal cycling of the screw guide during subsequent screw installation. A sight line 691 on top of a clip 690 enhances the user's ability to center the screw guide on a structural member for accurate delivery of screws.

Accessories can also aid in efficient use of the disclosed installation tools and the construction system. Various ways of maintaining a supply of fasteners on the person of an operator are disclosed. Such accessories minimize the necessity to interrupt installation to renew a supply of fasteners. For example, FIG. 30 illustrates a belt holster 700 holding several screws from which the operator efficiently retrieves a screw and manually installs each screw in a screw guide.

FIGS. 31A-31B and 32A-32B respectively illustrate a bandolier 700A and leg mounted screw holster 700B as alternatives for maintaining a number of screws 702 on the person of the operator. The screw holding systems illustrated in FIGS. 31A-31B and 32A-32B may include magnets arranged to maintain screws in the disclosed holders while the worker is moving about the construction site. This reduces the chance that screws may fall out of the disclosed holders and enhance ease of use. The fastener holders of FIGS. 30-32B may include tapered plastic tubes 704 for each fastener. The tubes can be configured to cover the sharp points of the fasteners to avoid inadvertent injury to the operator. For example, the bottom end of the tapered tubes 704 may be closed.

The disclosed installation tools may be adapted for use in driving a wide range of fasteners to implement various connections of wood components in a wood structure. A preferred fastener **900** which has particular applicability for providing a connection between a top plate and a truss frame is illustrated in FIG. **33**. Fastener **900** is a six-inch fastener which has an uninterrupted thread **910** extending from a gimlet point **912** toward a head **914**. The thread **910** is approximately five inches. In one embodiment, the gimlet point has a 30° angle. The head **914** has a socket which may be a T25 Autosert drive or other socket configuration with a fixed diameter that preferably ranges from 0.260 to 0.290 inches, which is approximately the major diameter of the thread **910**.

Depending upon the application, a number of other fasteners are possible depending upon the connection to be implemented as well as the specific structural components.

FIGS. **34A-34D** illustrate representative fasteners compatible with the disclosed construction system. The disclosed fasteners **920A** and **920B** are double-threaded, having a self-drilling tip **922** and approximately 2" bottom thread **924** paired with a threadless center shank portion **926** and 1½"-2" top thread. The top thread **928** (under the head **930A** and **930B**) is for increasing head pull-through performance. The top thread **928** in one configuration has a higher pitch, e.g., a greater number of threads per inch, to reduce the rate of penetration of the fastener as the top thread enters the wood during installation. This configuration will reduce the likelihood of board jacking and enhance clamping during installation. The top thread **928** may be of the same major and minor diameter as the bottom thread or may have a larger major and/or minor diameter to enhance pull-through resistance. The axial length of the top thread **928** may be as short as ½" depending upon the configuration of the upper thread and the desired pull-through resistance. The threadless center portion of the screw is arranged to permit maximum penetration of the bottom thread **924** into the various structural members prior to engagement of the top thread. The screws are illustrated with a Torx type drive socket **932** configured to facilitate automated or mechanized screw installation in the disclosed screw guides.

Different bright colors or tints are applied to the screws **920A** and **920B** to readily identify the fastener for both proper connection and inspection purposes. Currently, building inspectors can easily identify metal brackets applied to structural members. The alternative use of threaded fasteners potentially makes inspections more problematic. Threaded fasteners are not as easily seen by building inspectors. Even if the inspector can see the ends of the fasteners, the inspector would not necessarily know what type of fastener is installed. The disclosed construction system addresses this issue by applying bright colors to the fastener or at least the head of each fastener. Brightly colored fastener heads **930A** and **930B** provide a clear visual indication of the type of fastener installed in a given location. Bright colors can also help builders and workers to identify the correct fastener for a particular purpose.

FIGS. **35A-35E** illustrate an embodiment of the representative installation tool and construction system being used to install the disclosed threaded fasteners to connect various structural components. Note that the construction worker standing on the floor has clear sight lines to the installed fasteners whether the installation is overhead or at floor level. The worker is neither climbing a ladder nor squatting down at floor level. The disclosed construction system should enhance workers' safety and productivity while reducing the possibility of injury or worker discomfort.

FIGS. **36A-36C** illustrate a proposed embodiment of a fastener **940** compatible with the disclosed construction system. A Torx drive socket **942** in the screw head **944** is shown but other socket-type drive heads, such as square drive, Torx T-Tap, Torx Plus, Phillips, etc. are possible. The head **944** of the fastener employs an internal (socket) type drive, is compact and relatively small in diameter to reduce the likelihood of interference with other building components such as sheathing on the outside and sheetrock on the inside of a structure. The relatively small head can reduce the fastener resistance to pulling through wood structural members when subjected to forces along the axis of the fastener.

In the disclosed fastener **940** shown in FIGS. **36A-36C**, it can be seen that the top thread **946** has a higher pitch than the bottom thread **948**. This thread pitch differential between top and bottom threads for some applications to reduces board jacking and enhances building component clamping during installation of the disclosed screws. The top threads of the disclosed fasteners are configured to enhance pull-through resistance of the disclosed fasteners. It will be noted that the major diameter of the top thread **946** is larger than the major diameter of the bottom thread **948**. The disclosed fastener employs a single diameter shank which is formed to result in the disclosed thread patterns. Multi-diameter blanks are also contemplated where the diameter of the shank at the top of the fastener may be larger to provide more material for the top thread resulting in enhanced pull-through resistance. The disclosed threaded fasteners are contemplated between 5.25"-6" in length but length will vary depending on the intended purpose of the fastener. The illustrated fastener **940** has a 2" bottom thread **948** and a 1.75" top thread **946**. The length of the top thread and the length of the unthreaded center portion of the screw shank can be varied to tune screw performance.

While the fastener **940** employs a thread configuration where the top thread **946** has a higher thread count (TPI) than the bottom thread **948**, fasteners with the same thread count or a bottom thread having a higher thread count than the top thread may be useful for some purposes.

FIGS. **37A-37C** illustrate an alternative screw configuration **960** contemplated as useful for certain locations in a structure. This fastener is a single thread fastener with a fin **962** or wing type boring feature adjacent to the tip. Fastener **960** may be suitable for a bottom plate to rim joist applications for example. The flared head **964** of this fastener provides enhanced pull-through resistance in locations where interference with sheathing or sheetrock is not a concern. The boring feature reduces the possibility of cracking the wood structural member during screw installation. This fastener has a large diameter main thread **966** to reduce strip out of the fastener when tightening multiple plies of laminated veneer lumber beams together. Alternatively, the boring feature may be configured as more of a fin type wing that can appear as a spiral and may be applied by a threading machine, eliminating the need for a secondary pointing operation. There may be two, three or four fins **962** that are equi-angularly distributed about the circumference of the screw tip. Each of the fasteners illustrated in FIGS. **36A-36C** and **37A-37C** are configured so that the head penetrates slightly into a structural member or sits flat against the member to prevent interference with other building components such as sheathing or brackets, straps and joist hangers that may need to be installed.

FIGS. **38A-38C** illustrate various metal brackets and straps that may be employed in conjunction with the disclosed construction system. FIGS. **38A-38C** illustrates the

junction of a roof truss with the top plate of a structure. This is a location where many building codes require that the truss be strapped or tied to the top plate using a hurricane tie or the like. Metal plates **802** are typically used to hold truss components together. Such truss plates **802** are installed in a factory setting and include perforations that provide metal penetrating barbs to hold the plate to the truss components, thereby securing the truss components to each other. The resulting perforated configuration may provide an opportunity to attach L-shaped brackets **804** to tie the roof truss to the top plate of the wall as shown in FIGS. **38A-38C**. Screws or bolts **806** may pass through the roof truss plates **802** and L-shaped brackets **804**. Threaded fasteners **808** may be used to attach the lower portion of the L-shaped bracket to the top plate. FIG. **38C** illustrates an L-shaped bracket **804** with perforations and wood penetrating barbs arranged to match the perforations in the truss plates. The L-shaped bracket **804** could be installed by pressing or hammering into the truss plates and threaded fasteners **808** can be employed to tie the L-shaped bracket **804** to the top plate.

FIGS. **391A-39E** illustrates a possible alternative configuration for a truss plate. The disclosed truss plate **810** is U-shaped with the vertical portions of the U including perforations and wood penetrating points configured to secure the truss plate to the truss components. The bottom portion of the U-shape includes wood penetrating barbs **812** directed away from the truss and intended to penetrate the top plate of the wall. Threaded fasteners **814** contemplated in the disclosed construction system are then installed to tie the truss to the top plate and wall. The downward extending barbs **812** from the proposed U-shaped truss plate grip the top plate and enhance a secure connection of the truss to the wall. Further, the metal bottom panel **818** of the proposed truss plate **810** enhance pull-through resistance of the fastener relative to the truss.

FIGS. **40A-40B** illustrates an alternative metal construction bracket system. Flexible metal brackets **820** are arranged in elongated strips with score marks **822** or indentations between the segments. The elongated strips may be cut or broken between segments to provide metal brackets of different length. FIG. **40A** illustrates a five-segment bracket placed to tie a vertical stud to a top plate and a roof truss. The disclosed metal brackets **820** include metal perforations which can be pressed into the wood to provide a secure bracket to wood connection.

FIGS. **41A-41D** illustrates a tool **830** complementary to the disclosed flexible metal brackets **820**. The tool **830** is configured to bend and clamp the proposed bracket in place, pushing the perforated metal barbs into the wood. A tool adaptor **832** provides clamping force on the disclosed brackets. A rotary drive tool adaptor is disclosed, though a hydraulic tool is also suitable for this purpose. The jaws of the tool include protrusions configured to mate with perforations on the brackets and push portions of the brackets into the wood, thereby attaching the brackets to the wood.

With reference to FIGS. **44-49**, an adaptor **1000** is adapted for use in mounting to the end of an installation tool, such as tools **10**, **200**, **300**, **400**, **500** and **600** (without guide assemblies or adaptors) to provide a reference guide to reliably implement a proper entry angle and location of a fastener **1012** connecting through a support stud into a top plate and also into a bottom plate. The same adaptor **1000** may be used for both the illustrated top plate fastener installation and the bottom plate fastener installation as illustrated in FIG. **44**. The stud is designated by the letter S, the top plate by TP and the bottom plate by BP in FIGS. **44**, **44A** and **44B**.

The adaptor **1000** comprises an adaptor head **1010** which mounts via coupling tube **1020** to the distal tube of a telescopic tube assembly. The head defines a reference entry surface **1030** which is at an angle to the fastener opening **1032** and fastener channel **1034** aligned with the drive axis of the tube. A pair of irregularly shaped polygon arms **1040**, which are identical in shape, connect at opposite sides of the head and define spacing distance D which is substantially equal to the width of the stud S (FIG. **48**). The arms **1040** each have a first reference edge **1042** and a second reference edge **1044** that intersect and are at angles to each other. The reference edges **1042** are co-planar, and the reference edges **1044** are co-planar.

The arms have substantially parallel inner faces **1046**. The inner faces **1046** of the arms receive and essentially capture the upper portion of the stud S. The entry surface **1030** engages against the edge of the stud and the first reference edges **1042** of the arms engage the underside of the top plate TP, as best illustrated in FIGS. **44** and **44A**. The concurrent engagement of the entry surface **1030** and the first reference edge **1042** properly fixes the position and the entry angle of the fastener **1012** into the stud S (from the edge) and ultimately the top plate TP to provide an optimum connection. In the preferred embodiment, the entry angle α (relative to the vertical) is approximately 35° .

When it is desired to use the installation tool to provide a connection between the lower portion of the wall stud S and the bottom plate BP, the installation tool with the fixed adaptor is merely repositioned so that the entry surface **1030** of the head engages the lower portion of the edge of the stud and the second reference edge **1044** engages the top portion of the bottom plate BP to provide an optimal position and entry angle for driving a fastener **1012** into the stud S and the bottom plate BP as illustrated in FIG. **44B**. In the preferred embodiment, the entry angle α relative to vertical is approximately 35° .

With reference to FIGS. **50** and **51**, a modified version of adaptor **1000** is designated as adaptor **1050**. This adaptor **1050** is substantially identical to adaptor **1000** except that the arms **1040** are pivotally mounted to the adaptor head by a pivot pin **1060**. The arms may be independently pivotal, but for most fastener installations, generally align as illustrated for adaptor **1000**. This adaptor **1050** thus allows for one arm to be pivoted in the event that there is a headroom constraint or obstacle which prevents both of the arms from engaging opposing sides of a vertical stud S.

With reference to FIGS. **52-56**, a fastener installation tool adaptor **1100** is configured to mount to the end of a fastener installation tool and provide a proper entry for a fastener **1012** for a plate to a rim board or blocking B as illustrated in FIGS. **52-52C**. The fasteners are installed to resist uplift and/or lateral forces in the structure. For adaptor **1100**, there are two pivotal positions. Each pivot position defines a different entry angle into a horizontally disposed member.

The head **1110** mounts to a connector or coupling tube **1120** and provides an opening for the fastener so that the fastener is driven at an optimum location and angle. Two substantially identical irregular four sided arms **1140** are pivotally mounted to the head by a pivot pin **1112**. A transverse bridge **1150** connects the arms **1040**. The arms **1140** pivot in tandem. The arms define first reference edges **1142** and second reference edges **1144** that are at substantially right angles or orthogonal to each other. The first reference edges **1142** are coplanar and the second reference edges **1144** are coplanar.

In the upper or TOP position, as best illustrated in FIG. **52A**, reference edges **1142** engage the underside of the top

plate TP and reference edges **1144** engage against a sheathing SH. This fixes the proper location and entry angle β (relative to the vertical) for the fastener which connects the top plate to the lateral blocking LB. This position is also illustrated in FIG. **52C**.

The arms **1140** may also be pivoted in tandem to a second BOTTOM position wherein the first reference edges **1144** engage the upper surface of a lower plate and the second reference edges **1142** engage the sheathing SH to provide the proper location and entry angle γ (relative to the vertical) into the rim board/lateral blocking LB, as best illustrated in FIG. **52B**.

With reference to FIG. **54**, the bridge **1150** preferably includes an arrow **1152** and the head has indicia **1114** and **1116**, respectively, indicating TOP and BOTTOM pivot position. Selectively pivoting positioning the arrow **1152** relative to the head **1110** indicates the proper pivotal position of the adaptor **1100** for a desired fastener connection. The entry angles are preferably approximately 20° for the entry angle β of the top plate TP to the lateral blocking LB (FIG. **52C**) and approximately 12° for the entry angle γ of the bottom plate BP to the lateral blocking LB (FIG. **52B**).

With reference to FIGS. **57A** to **75**, a dual positionable fastener installation tool adaptor is generally designated by the numeral **2000**. The adaptor **2000** functions to provide the proper entry angle and location for driving a fastener to connect a vertical member, such as a stud, with a horizontal member. Adaptor **2000** mounts to the end of a fastener driver assembly **2010** having a telescopic tube assembly with a distal tube **2020**. The adaptor **2000** and distal tube **2020** of the driver assembly are configured so that the adaptor may be mounted to the tube at one of two angular positions about the central axis of the distal tube **2020** at essentially 180° spaced angular positions.

A first mounted position is illustrated in FIGS. **57A** and **57B**. The adaptor engages a vertical member and a horizontal member in a stable, fixed position to provide a proper angle for driving a fastener, for example, through a vertical stud into a bottom plate. In a second mounted position illustrated in FIG. **59B**, the adaptor **2000** is configured to engage the stud in a stable, fixed and properly aligned relationship and drive a fastener into a top plate. The adaptor **2000** thus provides an optimal location and entry angle for connecting an upper top plate and an optimal location and entry angle for driving a fastener for connecting a lower bottom plate.

The key to obtaining the dual positions is unclamping the adaptor **2000** at a first defined angular position relative to the tool, slightly axially displacing the adaptor, rotating the adaptor 180° to a second angular position, slightly axially displacing the adaptor, and reclamping the adaptor **2000** in position.

The adaptor **2000** includes a base **2100** which has a generally planar first reference surface **2110** and a generally opposite second generally planar reference surface **2120**. Surfaces **2110** and **2120** are not parallel. The reference surface **2120** of the base defines a fastener opening **2122** (FIG. **63B**). A fastener receiver assembly **2300** (FIG. **65**) is received by the base **2100** and is disposed at an acute angle relative to the reference surface **2120**. The forward distal portion of the base **2100** forms a planar nose **2130** (FIG. **62A**). The base also mounts a flush indicator **2140** which is pivotal relative to the reference surface **2120** to provide an indicator that the reference surface **2120** is flush with the appropriate member as desired for driving the fastener.

The surface **2110** of the base defines a recess **2112** which receives a second pivotal flush indicator **2150** which, when

the reference surface **2120** is flush against upper vertical reference surface, the indicator **2150** pivots to indicate a flush position (FIG. **61B**). The indicator is spring biased to extend outwardly from the reference surface when a component is not engaged in surface-to-surface relationship with the reference surface **2120**.

Transversely spaced wings **2200**, which are preferably substantially identical in shape, function in tandem as guides to properly position and stabilize the adaptor. The wings pivotally mount to the base about a pivot **2210** at a location generally adjacent the nose **2130** of the base. The wings preferably have a quasi-triangular shape with a restricted access opening **2212** (FIG. **72B**) and a second restricted access opening **2214** at quasi-opposed vertex positions. Openings **2212** and **2214** are equidistantly spaced from pivot **2210**. A threaded pin **2230** with a knob **2232** threads into the base and extends through one of the openings to secure the wing **2200** at a given pivotal position (see FIG. **74**). In that position, the other access opening is temporarily non-functional.

With additional reference to FIG. **62B**, a wing has a reference engagement edge **2240**. A metal plate **2250** is preferably mounted in a recess of an inner surface **2245**. The plate **2250** is integrally affixed with a pair of spaced claws **2252** and **2254**. The claws preferably have a claw configuration wherein the claws essentially traverse in three directions. The claws **2252**, **2254** project from the reference engagement edges **2240**. The claws are adapted to bite into the structural members to provide a stable fixed position for the fastener installation tool. As described herein, engagement by edges **2240** encompasses direct edges **2240** and/or claws **2252**, **2254**.

It will be appreciated that the wings **2200** are transversely spaced so that they receive between surfaces **2245** opposite sides of a stud so that the opening **2122**—and hence the fastener—can be driven through the medial center line of the stud. The reference surface **2120**, of course, also functions to engage against the stud surface-to-surface relationship to provide an optimum angle entry for the fastener.

With reference to FIGS. **64A-67**, the base mounts a fastener receiver assembly **2300** that employs a multifunction tube **2410** which defines a fastener channel **2310** for a received fastener F (FIGS. **65**, **66**). The channel is disposed at a pre-established angle relative to the reference surface **2120**, e.g., the entry angle. A conical or quasi-conical funnel-like guide **2320** is mounted at an upper portion of the receiver assembly to center the received fastener F so that the driver bit or coupler (not illustrated) from the driver tool will properly engage the fastener head H. The lower portion of the tube assembly also includes a guide sleeve **2340** so that the driver will be unidirectionally driven into the member without wobble. A pair of wraparound magnets **2350** is secured by cooperative engaged pronged plugs **2360** at the driver coupling end of the tube. The magnets **2350** function so that the fastener is retained within the adaptor and does not slide out through the opening **2122** prior to drive engagement with the driver coupler.

A connector assembly **2400** extends from the base **2100**. The assembly functions to receive the distal end of the telescopic tube assembly of the installation tool. The connector assembly employs the tube **2410** which defines and extends coaxially with the channel **2310**. A pair of cooperative arcuate brackets **2450** surrounds a lower portion of the tube to form an arcuate receiving slot **2454**. A lug **2460** (FIG. **68A**) projects from the tube **2410**. A second lug **2460** also projects at a diametrically opposed location.

25

The fastener driver assembly **2010** has a distal tube portion **2020** with two notches **2030** at diametrically opposed positions at its terminus. A lever clamp **2040** is spaced from the distal end. The clamp **2040** is pivotally actuated to govern the radial position of a lock member. The distal tube portion **2030** slides over tube **2410** into slot **2454**. The adaptor tube **2410** and distal tube **2020** align so that each circumferential lug **2460** is received in a distal notch **2030** (FIG. **68A**). The handle of clamp **2040** is forced inwardly to secure the adaptor to the tool by the lock member engaging a detent **2470** on the tube **2410**.

It will be appreciated that the adaptor is positioned at the selected angular position on the telescopic end of the installation tool, the lugs are captured in the notches and the clamp is locked to axially secure the adaptor to the driver assembly at the desired angular position. A fastener is then loaded in the channel **2310**. The adaptor **2000** may be, for example, positioned, as indicated in FIG. **75A** (the fastener driver assembly **2010** is omitted for purposes of clarity) where the claws engage the bottom rim or plate H and the wings capture the opposite sides of the vertical stud V. The reference surface **2120** of the base is moved against the edge of the stud V and the engagement edges **2240** and/or claws **2252**, **2254** engage the surface of plate H. The flush indicator **2140** indicates the flush position, as best illustrated in FIGS. **75A** and **75B**. The installation tool with the mounted adaptor **2000** may then drive the fastener at the properly located entry position and angle to fasten the stud V to the bottom plate H.

For some applications, there is an obstruction which prevents the tandem usage of the wings **2200** in positioning the adaptor for properly driving the fastener. The wings **2020** may be independently pivoted out of the way by loosening the knob **2032**, pivoting the wing **2020** and then securing the previously unused access opening **2214** against the threaded pin **2230** of the knob **2232** and tightening the knob **2232**, such as illustrated in and in FIGS. **70B** and **71B**. For this application, only a single wing is employed to install the fastener. Likewise, the opposed wing may also be pivoted out of position and secured by the opposing knob, as best illustrated in FIGS. **72B** and **73B**. It should be appreciated that FIGS. **70A** and **70B** together illustrate pivoting the wing out of the way from the normal tandem wing position of FIG. **70A**. FIGS. **72A** and **72B** illustrate pivoting the opposed wing from the normal tandem wing position to the pivoted position for a second adaptor/driver assembly position. Accordingly, it will be appreciated that either wing **2200** may be independently pivoted, if required, to accommodate a structural obstacle.

It will thus be appreciated that the adaptor **2000** has a novel claw feature to lock the adaptor in place. The adaptor **2000** also provides two flush indicators to readily indicate that the proper flush position for the adaptor has been achieved. The adaptor **2000** functions to angularly pivot and be secured in position on the distal tube portion of the driver assembly to provide the optimal driving position and angle for both the top plate and the bottom plate fastener connection. The adaptor **2000** also functions to provide a feature for retaining a loaded fastener within the adaptor by means of a pair of magnets. In addition, the adaptor **2000** is highly versatile in that, if required, either wing **2200** may be independently pivotally retracted and secured to accommodate obstacles wherein the tandem wing arrangement cannot be employed.

With reference to FIGS. **76-89B**, a convertible multiple entry angle adaptor with a position locator for a fastener installation tool is generally designated by the numeral

26

3000. The adaptor **3000** functions to provide the proper entry angle and location for driving a fastener for various structural connections, for example, to connect a horizontal member, such as a top plate or a bottom plate with an external rim board A, as illustrated in FIGS. **85A** and **88A**, or to provide a vertical connection through a horizontal member to an adjacent support member, truss or stud B or C, as illustrated in FIGS. **86A** and **89A**.

The adaptor **3000** principally comprises a head **3100**, a pivotally mounted convertible angle guide **3500** and a pivotally mounted and transformable locator **3900**. The adaptor **3000** mounts to the end of a fastener/driver assembly **2010** having a telescopic tube assembly with a distal tube **2020**. The adaptor and distal tube are configured so that the adaptor **3000** is mounted to the tube assembly at a fixed angular position about the central drive axis of the tube assembly. The multiple angle feature is accomplished by a manual position adjustment of a pivotal angle guide **3500**, as will be described below. An optimum fastener entry location for certain structural configurations is provided by a variably positionable locator **3900** mounted to the guide **3500**, as will be described below.

The head **3100** has a planar reference surface **3110** (top depicted in FIG. **76**) which defines a fastener opening **3120**. The fastener opening **3120** preferably functions both as a fastener receiver opening and a fastener discharge opening. The head has a generally multifaceted structure defined by a front **3130** and laterally opposed parallel sides **3140** and **3150** and a rear **3160**.

With additional reference to FIGS. **80** and **82**, the head **3100** connects with a fastener receiver assembly **3300** that has a segmented tubular structure which at least partially defines a fastener channel **3310** for a received fastener F. The channel extends to opening **3120** and is disposed orthogonally with respect to reference surface **3110** of the head. A conical or quasi-conical funnel-like guide **3320** is mounted at a lower portion of the receiver assembly to center the received fastener F so that the driver bit or coupler from the driver tool properly engages the fastener head H. The upper portion of the tube assembly also includes a segmented guide sleeve **3340** so that the fastener will be uni-directionally driven without wobble into the member or members.

A pair of wraparound magnets **3350** is secured by cooperative engaged prong plugs **3360** at the driver coupling end of the tube. The magnets **3350** function so that a received fastener is initially retained within the adaptor **3000** and does not slide out through the opening **3120** prior to being driven by the driver.

A connector assembly **3400** extends from a tubular portion to receive and/or connect with the distal end of the telescopic tube assembly of the installation tool. The connector assembly preferably employs the tube **3410** which encloses a portion of the receiver assembly **3300** and extends coaxially with the channel **3310**, and one or more screws and/or a circumferential clamp. In the illustrated connector, a connector screw **3420** extends through the connector portion to connect the adaptor at a fixed angular position relative to the end of the telescopic tube assembly. Other connection configurations are possible.

An angle guide **3500**, which ultimately defines the fastener entry angle, is pivotally mounted to the head by a pivot pin **3510**. Pin **3510** extends through a lateral opening **3170** of the head at opposed sides of the angle guide **3500**. The guide has a three-sided rectilinear form, including a frontal end reference panel **3600** and perpendicular laterally opposed panels **3700** and **3800**. The panels **3600**, **3700** and **3800** form a pivotal shield-like enclosure which surrounds

the head in a quasi-complementary fashion, but allows for pivoting relative to the head and specifically reference surface **3110**, as will be described below. The outer and inner surfaces of panels **3700** and **3800** are configured to facilitate pivoting relative to the head **3100** and selective positioning of the locator **3900**, as described below.

The respective edges **3610**, **3710** and **3810** (upper edges in the orientation of FIGS. **76-84**) of the panels form coplanar surfaces for the adaptor which together constitutes an entry angle reference structure. For some embodiments, the entry angle reference is formed by coplanar edges **3710** and **3810** only. The top of the head **3110**, which surrounds the opening **3120**, is generally planar, and in one pivotal position mode (which defines a 90° or normal entry angle), is preferably substantially coplanar with the edges **3710** and **3810**. The outer side portions of panels **3700** and **3800**, respectively, form a contoured cam-like abutment **3790**, **3890** rearwardly terminating a serrated segment **3792**, **3892** which interact with locator **3900**, as further described below. Forward edges **3720** and **3820** of panels **3700** and **3800** define orthogonal coplanar reference strips which provide a vertical frontal position guide, as described below.

In a first pivotal position mode of the guide relative to the head **3100**, as best illustrated in FIGS. **76**, **77** and **82**, a pin **3175** extends through an opening **3770** of the panel **3700** and through an opening **3170** (FIG. **80**) in the head to fix the angle of the angle guide relative to the head and the drive axis of the adaptor. The central drive axis **D** is preferably approximately 12° from the normal **N** to the reference edges. The head includes a second opening **3180**. In the illustrated preferred embodiment, when the pin **3175** is received in opening **3180**, the reference surface **3110** and the reference edges **3710**, **3810** are parallel or coplanar and the entry angle is 90° or normal **N** to the member upon engagement against the member. See FIGS. **85A-89B**. The pin **3175** has a ring **3185** to facilitate removal and insertion.

Alternatively, additional openings may be located in the head to provide for additional entry angles. It should also be appreciated that a single opening may be provided in the head and multiple aligned openings in the panels **3700** and **3800** to pivotally fix the guide assembly relative to the head and specifically reference surface **3110** and thereby define multiple entry angles.

A slidably and pivotally positionable bracket-like locator **3900** is selectively positionable to ensure the proper fastener entry location for certain structural configurations. Locator bracket **3550** has a frontal frame **3950** with a central window **3952**. The obverse surface **3955** of the frame functions as a reference position guide and stabilizer. A pair of laterally spaced arms **3970** and **3980** project rearwardly. The arms **3970** and **3980** are perpendicular relative to the medial portion of the frame **3960**. The arms **3970** and **3980** have rounded ends **3975** and **3985**. The ends **3975** and **3985** are somewhat complementary to portions of abutments **3790** and **3890** which interact in cam-like fashion when the locator is repositioned, as described below.

The arms **3970** and **3980** each have an elongated slot **3972** and **3982**, respectively, which functions as a guide for positioning and pivoting the locator **3900**. Pins **3715** and **3815** project at opposing sides of the panels **3700** and **3800**. Each pin is received in a corresponding slot so that the locator may slide along the pin and axially may pivot upwardly and rearwardly during the transformation of the locator **3900** from a frontal (FIG. **85A**) to a rearward position. A knob **3990** is threaded to the panel through the slot and is tightenable against arm **3570** to secure the locator

3900 in a fixedly locked position. The knob **3990** may contain recesses and serrations to facilitate tightening the knob.

The upper edge of each bracket arm has a series of serrations **3976**, **3986**. The side panels **3700** and **3800** each include a protruding portion forming the abutments or cams **3790** and **3890**. Each cam is contoured and positioned to engage the rounded ends **3975**, **3985** of the arms. The protruding portion at its opposite terminus has a plurality of serrations **3792** and **3892** which are respectively engageable by the serrations **3976** and **3986** of the locator to fixedly engage the locator in a stable fixed transverse position when the frame **3950**/reference surface **3955** is positioned at the rear of the head (see FIGS. **86B**, **87B**).

The panels **3700** and **3800** include recess portions **3750** and **3850** adjacent the reference edges **3710** and **3810**. Plates **3760** and **3860**, which mount a pair of claws **3770** and **3870**, are secured at opposed sides of the panels by screws **3772** and **3872**. The claws project upwardly from the reference edges and provide a secure engagement into the structure (horizontal member in preferred applications) to provide a stable positioning of the adaptor **3000** as the fastener is driven.

With reference to FIGS. **85A-89B**, the adaptor **3000** may be configured and positioned to drive a fastener **F** at a proper entry angle and location for various structural configurations. For FIGS. **85B**, **86B**, **87B**, **88B** and **89B**, the knob **3990** has been removed so that the position of the pin **3715** in the slot **3972** and the serrations **3792**/serrations **3976** engagement can be illustrated. For FIGS. **85A**, **85B**, **87A**, **88A** and **88B**, the angle guide **3500** is in the first angular mode which essentially functions to define an acute entry angle of 12° to the normal for the preferred embodiment. The locator **3900** is at a first position in FIGS. **85A** and **85B** for connecting with an overhead external rim board and at a second position illustrated in FIGS. **88A** and **88B** for providing a lower external rim board connection.

For the installations illustrated in FIGS. **86A**, **86B**, **87A**, **87B**, **89A** and **89B**, the angle guide is in a second pivotal position (the pin **3175** is withdrawn from slot **3170** and reinserted into slot **3180**) so that the reference edges **3710**, **3810** are coplanar with the top surface **3110** of the head. In this configuration, a normal or vertical connection is provided with the proper entry angle and location. For the overhead installation, the locator **3900** has been repositioned so that the reference surface **3955** engages a vertical edge of the top plate to provide the proper location and also to stabilize the fastener/driver assembly. It should be noted that the angle surfaces **3720** and **3820** function as a guide reference surface for the connection of FIGS. **88A** and **88B**.

The locator **3900** is transformable from the position illustrated in FIGS. **85A** and **85B** for providing the proper entry angle for an external rim board **A** to the bracket position of FIGS. **86A** and **86B** which engages the edge of a top plate or header for providing a normal entry angle into a medial board **B** to a third lateral position as illustrated in FIGS. **87A** and **87B** wherein the proper entry angle for an entry into a third board **C** is positioned at the medial location. The position of pin **3715** in slot **3972** is different for FIGS. **86B** and **87B**.

With reference to FIGS. **88A** and **88B**, the locator **3900** is positioned in a location against the rear of the head and surfaces **3720** and **3820** engage a vertical member and the guide is positioned at the first entry angle position so that a proper entry angle into a lower rim board may be obtained. The front of the guide functions as a reference positioner.

As best illustrated in FIGS. 89A and 89B, the normal angle for lower board at a proper location is illustrated. The position of the locator 3900 is transformable to a rear position, but does not function to provide a guide and stabilizer for the fastener installation and the illustrated structural configuration.

With reference to FIGS. 90-99, a convertible multiple entry angle adaptor with a position locator for a fastener installation tool is generally designated by the numeral 4000. The adaptor 4000 functions to provide the proper entry angle and location for driving a fastener F for various structural connections preferably, for example, to connect a horizontal member, such as a horizontal beam HB with an overhead rim board R1, R2, as illustrated in FIGS. 98 and 99. Upon mounting to the installation tool, the adaptor 4000 provides an overhead beam/rim board fastening system which can be precisely implemented without a ladder and also facilitates numerous other structural connections.

The adaptor 4000 principally comprises a head 4100, a pivotally mounted convertible angle guide module 4500 and a removably mounted and transformable position locator 4900. The adaptor 4000 mounts to the end of a fastener/driver assembly 2010 having a telescopic tube assembly with a distal tube 2020. The adaptor and distal tube are configured so that the adaptor 4000 is mounted to the tube assembly at a fixed angular position about the central drive axis of the tube assembly. The multiple entry angle feature is accomplished by a manual adjustment of the pivotal angle guide module 4500, as will be described below. An optimum fastener entry location for certain structural configurations is facilitated by the variably positionable locator 4900 mounted to the guide 4500, as will be described below.

The head 4100 has a planar reference surface 4110 (top depicted in FIGS. 90-95) which defines a fastener opening 4120. The fastener opening 4120 preferably functions both as a fastener receiver opening and a fastener discharge opening. The head has a generally multifaceted structure including a rear 4130 and laterally opposed parallel sides 4140 and 4150 and a front 4160. It will be appreciated that the terms "top", "bottom", "front", "rear" and "side" are arbitrary and are employed for descriptive and explanatory purposes.

With additional reference to FIGS. 92 and 93, the head 4100 connects at the bottom with a fastener receiver assembly 4300 that has a segmented tubular structure which at least partially defines a fastener channel 4310 for a received fastener F. The channel 4310 extends to opening 4120 and is disposed orthogonally with respect to reference surface 4110 of the head. A conical or quasi-conical funnel-like guide 4320 is mounted at a lower portion of the receiver assembly to center the received fastener F so that the driver bit or coupler from the driver tool properly engages the fastener head H. The upper portion of the tube assembly also includes a segmented guide sleeve 4340 so that the fastener will be uni-directionally driven without wobble into the member or members.

A pair of wraparound magnets 4350 is secured by cooperative engaged prong plugs 4360 at the driver coupling end of the tube. The magnets 4350 function so that a received fastener is initially retained within the adaptor 4000 and does not slide out through the opening 4120 prior to being driven by the driver.

A connector assembly 4400 extends from a tubular portion to receive and/or connect with the distal end of the telescopic tube assembly of the installation tool. The connector assembly preferably employs the tube 4410 which encloses a portion of the receiver assembly 4300 and

extends coaxially with the channel 4310, and one or more screws and/or a circumferential clamp. In the illustrated connector, a connector screw 4420 extends through the connector portion to connect the adaptor at a fixed angular position relative to the end of the telescopic tube assembly. Other connection configurations are possible.

An angle guide module 4500, which ultimately defines the fastener entry angle, is pivotally mounted to the head by a pivot pin 4510. Pin 4510 extends through a lateral opening 4170 of the head at opposed sides of the angle guide 4500. The guide generally has a three-sided rectilinear form, including a rear end reference panel 4600 and perpendicular laterally opposed panels 4700 and 4800. The three panels may be formed from two opposed sections each partially forming panel 4600. The panels 4600, 4700 and 4800 form a pivotal shield-like enclosure which surrounds the head in a quasi-complementary fashion, but allows for pivoting relative to the head and specifically reference surface 4110, as will be described below. The outer and inner surfaces of panels 4700 and 4800 are configured to facilitate pivoting relative to the head 4100 and selective positioning of the locator 4900, as described below. The outer surfaces of panels 4700 and 4800 form opposed substantially identical outer protrusions 4785.

The respective edges 4610, 4710 and 4810 (upper edges in the orientation of FIGS. 94 and 95) of the panels form coplanar surfaces for the adaptor which together constitutes an entry angle reference structure. For some embodiments, the entry angle reference is formed by coplanar edges 4710 and 4810 only. The top of the head 4110, which surrounds the opening 4120, is generally planar, and in one pivotal position mode (which defines a 0° or normal entry angle), is preferably substantially coplanar with the edges 4710 and 4810.

The pivotal position of the guide module 4500 relative to the head 4100 about the pivot pin 4510 is fixed at one of two pivot positions, e.g., normal or 0° (FIG. 93) and 12° (FIG. 99), by a depressible interlock assembly carried by the angle guide module 4500 and designated generally by the numeral 4520. The interlock assembly 4520 includes an elongated lever 4530 depressible at an accessible location which protrudes below the guide module/head assembly. The lever 4530 is mounted at an intermediate location via a pivot pin 4532 fixed to the angle guide module 4500.

The lever 4530 includes a protruding pawl 4534. The pawl 4534 is receivable in one of two detents 4180 and 4182 of the head. The detents are angularly spaced about the pivot axis of pivot pin 4510 so that the upper surface of the head are disposed at either 0° (normal) (FIG. 93) or 12° (FIG. 95) relative to the edges 4610, 4710 and 4810. A guide pin 4590 extends between the panels 4700 and 4800 through an arcuate slot 4090 of the head to limit the angular pivoting of the head relative to the guide module 4500.

The lever 4530 is spring loaded by a spring 4092 so that the pawl 4534 is urged to engage in either detent 4180 or 4182 at the angular positions generally limited by the guide pin 4590. When it is desired to change the angular position of the angle guide 4500, the lever 4530 is depressed toward the tube 4410 of the connector assembly 4400, which extends from the head. The angle guide module 4500 is then pivoted relative to the pivot pin 4510 for securing the angle guide at the proper angular position of either 0° (FIG. 93) or 12° (FIG. 97) relative the head 4100.

With reference to FIGS. 90 to 97, the side panels 4700 and 4800 each have opposed substantially identical flush indicators 4750 and 4850, respectively. The flush indicators are configured to indicate that the reference surfaces 4610, 4710

and **4810** are flush against a member through which a fastener is to be initially driven. The flush position is illustrated in FIGS. **98** and **99**.

A skirt **4760** and **4860** integrally projects outwardly (laterally) from the upper side of the panels. Each skirt respectively mounts a pivotal lever indicator **4762** and **4862** mounted at an intermediate location to a pivot pin **4764** and **4864**. A torsion spring **4666** (see FIGS. **93** and **97**) biases each lever indicator so that one end projects above the reference surface **4710** and **4810** and an indicator flag **4768** and **4868** at each opposite end is respectively pivoted downwardly. The flag indicator **4768** and **4868** of each indicator lever projects downwardly through an opening or window **4769** of the skirt to indicate that the reference surfaces **4710** and **4810** are not flush against a structure to be connected. When the reference surfaces **4710** and **4810** are flush against a planar surface, the flush indicators pivot so that the indicator flags **4768** are upwardly withdrawn into the skirt to indicate that the proper flush position has been obtained by the angle guide module **4500**, as illustrated in FIGS. **98** and **99**.

In addition, the panels **4700** and **4800** forwardly extend to cooperatively form a nose-like skirt defined by extensions **4790** and **4890**. A flush indicator assembly **4650** includes an indicator lever **4660** which is mounted at an intermediate position to a pivot pin **4662** and biased by a torsion spring **4666** (FIG. **93**) to pivot upwardly. When the flush position of the reference surfaces **4710** or **4810** is obtained, the lever pivots, and the indicator flag **4668** is upwardly withdrawn into the skirt and enclosure to further indicate that the proper flush position of the angle guide module **4500** has been obtained, as illustrated in FIGS. **98** and **99**.

The indicator flags **4668** and **4768** preferably have a luminescent surface or a strikingly visible surface such as yellow, orange or red in contrast to the tints of the other adaptor components so that they are readily visible.

A locator assembly **4900** is employable to accurately position the adaptor **4000** and specifically the fastener opening **4120** along a horizontal beam or member to selectively implement an optimum positioning for driving the fastener into an adjacent rim board or structure. The panels **4700** and **4800** have axial bores which extend parallel to the reference edges **4710** and **4810** and open frontally at the end of the panels. A pair of laterally spaced arms **4910** have a generally L-shape and upwardly mount a receiving platform **4920**. The platform **4920** has a front reference surface **4922** perpendicular to edges **4710** and **4810**. The reference surface **4922** is engageable against a side edge of a horizontal beam as illustrated in FIG. **98**.

The arms **4910** are slidably receivable in the bores and are secured by knobs **4950** tightenable to secure the arms at fixed positions relative to the panels. In some embodiments, the arms **4910** are manufactured from stamped sheet metal. The knobs **4950** preferably contain recesses and serrations to facilitate tightening the knob. The arms **4910** are positionably adjustable at various selected distances from the front end of the angle guide module **4500**. See, for example, the contrast in spacing of FIGS. **98** and **99**.

The platform **4920** mounts an L-shaped bracket **4930** which has a slot **4940**. The slot receives an elongated locator guide **4960** (FIGS. **90** and **91**). The locator guide **4960** is variably slidably longitudinally positionable in the slot **4940**. The bracket **4930** has at least one window **4935** in alignment with the slot. The locator guide **4960** has an abutment end **4962** engageable against a potentially blindly locatable structural member, such as a rim board disposed above a horizontal beam. The locator guide **4960** also

preferably has a linear measurement scale **4970** to precisely indicate a spacing measurement in the window **4935** of a structural member from an underside reference edge of a beam. The locator guide **4960** may be manually pushed forwardly so that the abutment end **4962** engages the side of a rim board which ultimately receives a driven fastener. The scale indicates the measured location of the rim board so that the opening (fastener entry) may be accurately positioned relative to the rim board. The locator assembly **4900** may be fully or partially removed from the angle guide module so that the fastener F may be driven at the appropriate location and angle.

With reference to FIGS. **98** and **99**, the adaptor **4000** may be configured and positioned to drive a fastener F at a proper entry angle and location for various representative structural configurations.

In FIG. **98**, the angle guide **4500** is in the first angular mode (FIGS. **92-93**) which essentially functions to define an acute entry angle of 0° to the normal for the preferred embodiment. The locator **4900**, with the locator guide **4960** removed, is at a first position for connecting with an overhead medially positioned rim board. The beam edge reference **4922** engages the edge of the beam to secure the adaptor at the proper fastening location for the rim board R1 connection. The reference **4922** also stabilizes the adaptor/installation tool. The flush indicator **4750** and **4950** indicate that the reference edge **4710** and **4810** are flush against the underside surface of the beam.

For the installation illustrated in FIG. **99**, the angle guide is at a second pivotal position so that the reference edges **4710**, **4810** are at approximately 12° with the top surface **4110** of the head. In this configuration, a connection is provided with the proper entry angle and location for an external rim board R2. The latter entry angle is at $12^\circ \pm 2^\circ$ relative to a vertical line. For the overhead installation, the platform **4910** of the locator **4900** has been repositioned the front panel surface **4960** engages a vertical stud to provide the proper location and also to stabilize the fastener/driver assembly. It should be noted that the angle surfaces **4710** and **4810** function as a guide reference surface for the connection of FIG. **99**. The flush indicator **4650**, **4750** and **4850** indicate the adaptor flush position in FIG. **99**.

The adaptor **4000** may be employed at the first and second pivotal positions of the angle guide **4500** to implement numerous board connections. For example, at the second pivotal position, the adaptor **4000** may be employed to connect through headboards into a third board of a tall wall configuration (not illustrated) as well as to implement other board and structural connections.

The locator **4900** is transformable from the position or mode illustrated in FIGS. **90** and **91** for providing the proper entry angle location for rim board which by engaging the side so that the distance of the board to the reference **4720** can be measured on the scale **4970**.

While preferred embodiments of the foregoing have been set for purposes of illustration, the foregoing descriptions should not be deemed a limitation of the invention herein. Accordingly, various modifications, adaptations and alternatives may occur to one skilled in the art without departing from the spirit and the scope of the present invention.

The invention claimed is:

1. An adaptor for a fastener driver assembly comprising: a head defining a fastener opening, the opening communicating with a fastener receiver assembly;
- a connector configured to mount said head to the driver assembly so that a fastener received in said receiver assembly is drivable through said opening;

a guide module pivotally mounted to said head comprising a pair of laterally spaced panels and defining a reference engagement structure; and
 a variably positionable locator mounted to the guide module, wherein
 when said guide module is at a first pivot position and said reference engagement structure engages a member, a fastener is drivable by said fastener drive assembly through said fastener opening at an oblique entry angle into said member and when said guide module is at a second pivot position and said reference engagement structure engages said member, a fastener is drivable through said fastener opening at a normal entry angle into said member, and
 the locator is positionable in a first fixed position on a frontal longitudinal side of the guide module and positionable in a second fixed position on a rearward longitudinal side of the guide module opposite the frontal longitudinal side.

2. The adaptor of claim 1 wherein said first entry angle relative to a vertical axis is approximately 12°.

3. The adaptor of claim 1, comprising a depressible interlock assembly comprising a pawl, wherein said head defines two spaced openings and said guide module mounts the depressible interlock assembly and said pawl is engageable into one opening of the two spaced openings to define a first or second pivot position.

4. The adaptor of claim 1 wherein said head defines a drive axis and said guide module is pivotal about an axis orthogonal to said drive axis.

5. The adaptor of claim 1 wherein said locator comprises a pair of laterally spaced arms and a variably positionable elongated position detector mounted from the laterally spaced arms, and wherein the laterally spaced arms extending from said guide module.

6. The adaptor of claim 5 further comprising a knob which secures the locator in a fixed position to said guide module.

7. The adaptor of claim 6 wherein each of said arms is parallel to said reference engagement structure.

8. The adaptor of claim 1 wherein said receiver assembly further forms a fastener channel and further comprising a magnet assembly for retaining said fastener in said channel.

9. The adaptor of claim 1 further comprising at least one flush indicator which indicates a flush position of said reference engagement structure.

10. The adaptor of claim 9 wherein said at least one flush indicator comprises a spring biased lever having a flag and which is withdrawable into an enclosure.

11. A fastener installation tool assembly comprising:
 a fastener driver assembly defining a longitudinal axis;
 a head having an entry reference engagement surface and defining a fastener opening;
 a connector configured to engage the driver assembly to mount said head to the driver assembly in a first locked position about said longitudinal axis at a secured angular position so that a fastener is longitudinally drivable through said fastener opening;
 an angle guide assembly pivotally mounted to said head about a lateral axis and having a guide reference;
 a locator having a locating reference surface slidably mounted to said guide assembly; wherein
 when said guide assembly is at a first angular position about said lateral axis relative to said head and said locating reference surface engages a vertical edge of an upper structural member, and said guide reference

engages a horizontal surface of said upper structural member, a fastener is drivable by said fastener driver assembly longitudinally through said fastener opening at a normal entry angle into said upper structural member and said guide reference,
 when said guide assembly is at a second angular position about said lateral axis relative to said head and the guide reference engages a horizontal surface of said upper structural member, a fastener is drivable through said fastener opening at an oblique entry angle relative to said guide reference and into said upper structural member, and
 said connector is configured to be selectively disengaged from the drive assembly and re-engaged in a second locked position about the axis that is different from the first locked position, thereby allowing driving of a fastener longitudinally into a lower structural member.

12. The installation tool of claim 11 wherein said oblique entry angle is approximately 12° from a vertical line.

13. The installation tool of claim 11 wherein said fastener is driven into a rim board to connect said structural member and said rim board, and said structural member is a top plate, a header, a beam or a bottom plate.

14. The installation tool of claim 11 wherein said guide reference comprises laterally spaced coplanar edges of a pair of laterally spaced panels.

15. The installation tool of claim 11, comprising a depressible spring loaded member configured to secure said guide angle assembly at one of the first and second angular positions.

16. The fastener installation assembly of claim 11, comprising a position detector, wherein said locator comprises a pair of elongated arms mounting a platform defining said locator reference surface and an elongated slot, the slot receiving the position detector and said guide assembly has a pair of bores for slidably receiving said locator arms.

17. The fastener installation assembly of claim 16 wherein each said locator arm is fixedly secured by a knob threadably engaging said guide assembly.

18. The fastener installation assembly of claim 16 wherein said position detector has a variably positionable graduated scale.

19. A fastener installation assembly comprising:
 a head having an entry surface and defining a fastener opening in said entry surface;
 a connector configured to mount said head to the tubular member at a fixed angular position so that a fastener is drivable through said opening;
 a guide assembly pivotally mounted to said head comprising a pair of spaced panels having coplanar reference edges; and
 a locator removably mounted to said guide assembly and having a movable position locator;
 so that when said guide assembly is at a first angular position relative to said head and said locator engages a vertical surface, and said reference edges engage a horizontal member, a fastener is drivable through said fastener opening into said horizontal member at a first entry angle, and when said guide assembly is at a second angular position relative to said driver assembly and said reference edges engage the horizontal member, a fastener is drivable through said fastener opening at a second entry angle into said horizontal member.