



Europäisches  
Patentamt  
European  
Patent Office  
Office européen  
des brevets



(11)

**EP 1 873 413 B1**

(12)

## **EUROPEAN PATENT SPECIFICATION**

(45) Date of publication and mention  
of the grant of the patent:  
**28.10.2009 Bulletin 2009/44**

(51) Int Cl.:  
**F16D 3/38 (2006.01)**

(21) Application number: **07011591.0**

(22) Date of filing: **13.06.2007**

**(54) Yoke for universal joint and universal joint**

Gabel für Kardangelenk und Kardangelenk

Fourchette pour joint universel et un joint universel

(84) Designated Contracting States:  
**DE FR**

(72) Inventor: **Tokioka, Ryouichi**  
**Osaka-shi**  
**Osaka 542-8502 (JP)**

(30) Priority: **19.06.2006 JP 2006169140**

(74) Representative: **Steil, Christian et al**  
**Witte, Weller & Partner**  
**Postfach 10 54 62**  
**70047 Stuttgart (DE)**

(43) Date of publication of application:

**02.01.2008 Bulletin 2008/01**

(73) Proprietor: **JTEKT Corporation**  
**Osaka-shi**  
**Osaka 542-8502 (JP)**

(56) References cited:  
**FR-A- 1 254 364    JP-A- 2000 097 246**  
**US-A- 5 916 026**

Note: Within nine months of the publication of the mention of the grant of the European patent in the European Patent Bulletin, any person may give notice to the European Patent Office of opposition to that patent, in accordance with the Implementing Regulations. Notice of opposition shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

**Description****BACKGROUND OF THE INVENTION****Field of the Invention**

**[0001]** The present invention relates to a yoke for universal joint according to the preamble of claim 1 and to a universal joint.

**Description of Related Art**

**[0002]** In an automotive steering system, for example, an intermediate shaft for connecting a steering shaft and a steering gear such as a rack and pinion mechanism has a function to contract following the retraction of the steering gear when a vehicle collides against a front object (at primary collision). This prevents an impact of the primary collision from being transferred to a steering member such as a steering wheel.

**[0003]** When the intermediate shaft is contracted at the primary collision, a universal joint connecting the intermediate shaft with the steering gear and the steering shaft assumes a greater bend angle (e.g., a bend angle on the order of 60°) than a bend angle thereof while the vehicle is moving.

**[0004]** Since the steering member may be turned at any steering angle at the primary collision, the universal joint is required to secure the above bend angle with respect to the overall range of rotational angle of the steering member.

**[0005]** On the other hand, a yoke for universal joint has been proposed which is formed by punching out a sheet metal and press forming the resultant sheet metal (see, for example, Japanese Unexamined Patent Publication No. 2005-163866).

**[0006]** In an electronic power steering device having an electric motor for power assist disposed at a steering column, on the other hand, the intermediate shaft is designed to bear a greater load and hence, higher rigidity is required for the yoke for universal joint.

**[0007]** In a case where the press molded yoke is used as the yoke for universal joint, the yoke may suffer poor rigidity if the yoke is decreased in thickness in order to provide for the increase of the bend angle.

**[0008]** A yoke according to the preamble of claim 1 is known from JP-2000-097246 A.

**[0009]** It is an object of the invention to provide a yoke for universal joint and a universal joint which feature a high rigidity and can secure a greater bend angle.

**SUMMARY OF THE INVENTION**

**[0010]** In order to achieve foregoing object, a preferred embodiment of the present invention provides a yoke for universal joint formed by punching out a sheet metal and press forming the resultant sheet metal according to claim 1. The yoke for universal joint comprising a cylind-

rical base for fixing a shaft; and a pair of arms extending from an end of the base in parallel to a center axis of the base and swingably connected with a counterpart yoke via a cross shaft. Each of the arms is formed with a support hole for supporting a corresponding trunnion of the cross shaft via a bearing. The support hole of each of the arms has a center axis extending in a direction orthogonal to the center axis of the base. The end of the base is formed with a relief portion including a concave curved surface.

The concave curved surface of the relief portion at the end of the base has a center of curvature located at place offset from a center of the joint toward a distal end of the arm.

**[0011]** In order to avoid interference between the end of the base of the yoke for universal joint and a distal end of a counterpart yoke, it may be possible to provide the relief portion at the end of the base, shaped in a concave spherical surface and having a concentric relation with the center of the joint, and to define a radius of the concave spherical surface to be greater than a radius of the swing motion of the counterpart yoke. In this case, however, the relief portion intersects with the base at an acute angle, so that the end of the base is decreased in thickness. Therefore, the yoke has a drawback of low rigidity.

**[0012]** According to the embodiment, on the other hand, the relief portion formed at the end of the base and including the concave curved surface has the center of curvature located at place offset from the center of the joint toward the distal end of the arm. That is, the embodiment adopts a layout wherein the concave curved surface of the relief portion is in a non-concentric relation with the center of the joint. Thus, the embodiment is adapted to overcome the above drawback and to attain an advantage to increase the bend angle while increasing rigidity.

**[0013]** It should be noted that the concave curved surface of the relief portion may have the center of curvature located at place on the center axis of the base and otherwise. In a case where the concave curved surface of the relief portion does not have the center of curvature located at place on the center axis of the base, a normal line of the concave curved surface of the relief portion only need to have a point closest to the center axis of the base offset from the center of the joint toward the distal end of the arm.

**[0014]** FIG.1 is a front view of a universal joint for showing a state where the universal joint including a yoke according to one embodiment of the invention is connected with shafts;

FIG.2 is a schematic perspective view of the yoke;

FIG.3 is a partly cut-away front view of the yoke;

FIG.4 is a vertical sectional view of the yoke;

FIG.5 is a sectional view showing a principal part of

an arm of the yoke;

FIG.6 is a sectional view taken on the line VI-VI in FIG.4;

FIG.7A, FIG.7B, FIG.7C and FIG.7D are a group of schematic perspective views showing the steps of forming the yoke from a sheet metal, in this order; FIG.8 is a schematic perspective view of an intermediary body for yoke manufacture;

FIG.9 is a schematic perspective view showing the universal joint at the maximum bend angle; and

FIG. 10 is a schematic diagram showing a principal part of corresponding arms of the yokes at the maximum bend angle.

#### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

**[0015]** A preferred embodiment of the invention will be described with reference to the accompanying drawings.

**[0016]** FIG. 1 is a schematic side view showing a universal joint employing a yoke for universal joint according to one embodiment of the invention. Referring to FIG.1, a universal joint 1 connects a first shaft 2 and a second shaft 3. The first shaft 2 comprises, for example, a steering shaft of an automotive vehicle, whereas the second shaft 3 comprises, for example, an intermediate shaft for connecting the steering shaft and a steering mechanism such as a rack and pinion mechanism.

**[0017]** The universal joint 1 includes: a first yoke 4 as a yoke for universal joint connected with the first shaft 2; a second yoke 5 as another yoke (counterpart yoke) connected with the second shaft 3; and a cross shaft 6 interconnecting the first yoke 4 and the second yoke 5.

**[0018]** The first and second yokes 4, 5 have the same constitution and each support each corresponding pair of trunnions 7 via a bearing 8 such as a needle roller bearing.

**[0019]** The following description is made with reference to the first yoke 4. FIG.2 is a perspective view of the first yoke 4. FIG.3 is a partly cut-away front view of the first yoke 4, and FIG. 4 is a vertical sectional view of the first yoke 4.

**[0020]** Referring to FIG.1 and FIG.3, the first yoke 4 is formed by punching out a sheet metal having a thickness of 6 to 9mm, for example, and by press molding the resultant the sheet metal. The first yoke 4 includes: a cylindrical base 9 for fixing the yoke to the shaft; and a pair of arms 11 provided to extend from a first end 9a of the base 9 in parallel to a center axis 10 of the base 9, and to oppose each other.

**[0021]** Each of the arms 11 is formed with a support hole 12 for supporting a corresponding trunnion 7 of the cross shaft 6 via the bearing 8. Each of the support holes 12 has a center axis 13 extending in a direction orthogonal to the center axis 10 of the base 9.

**[0022]** Referring to FIG.2 and FIG.4, the first end 9a of the cylindrical base 9 is formed with a first relief portion 14 including a concave curved surface. Specifically, the

first relief portion 14 defines a concave spherical surface. For instance, a part of or the all of the first relief portion 14 is defined by a sphere (curvature radius R1) in a non-concentric relation with a center C1 of the joint 1.

**[0023]** The concave spherical surface defined by the first relief portion 14 has a center of curvature A1 located between the center C1 of the joint 1 and a distal end of the arm 11 on the center axis 10 of the base 9. In other words, the concave spherical surface (concave curved surface) constituting the first relief portion 14 has the center of curvature A1 thereof offset from the center C1 of the joint 1 toward the distal end of the arm 11.

**[0024]** Each of the arms 11 includes: an outside surface 15; an inside surface 16; and an edge portion 17 having an inverted-U shape. The edge portion 17 of each arm 11 includes a pair of side edges 17a substantially extending in parallel to the center axis 10 of the base 9. The inside surface 16 is formed with a gutter-like concave groove 16a extending in parallel to the center axis 10 of the base 9. Each side edge 17a is formed with a second relief portion 18 including a flat plane defining a parallelogram.

**[0025]** The flat plane of the second relief portion 18 and the corresponding side edge 17a of the corresponding arm 11 intersect each other on first and second intersections 19, 20 extending in parallel to the center axis 10 of the base 9. These intersections 19, 20 constitute two opposite sides of the parallelogram. The first intersection 19 is relatively closer to the center axis 10 of the base 9, whereas the second intersection 20 is relatively farther from the center axis 10 of the base 9. With respect to a direction parallel to the center axis 10 of the base 9, the first intersection 19 is relatively farther from the center C1 of the joint 1, whereas the second intersection 20 is relatively closer to the center C1 of the joint 1. In this manner, the arm 11 is provided with relief at only necessary areas for avoiding interference with the counterpart yoke 5. Thus, the joint 1 can achieve a great bend angle (e.g., 60°) while securing high rigidity of the arms 11.

**[0026]** As shown in FIG.5, a chamfer 22 for relief is formed on the overall length of a ridge 21 between the edge portion 17 having the inverted-U shape and the outside surface 15 of each arm 11 such that stress concentration on the arm 11 may be alleviated. The chamfer 22 is continuous to the first relief portion 14 at the first end 9a of the base 9 so that stress concentration generated on a root of the arm 11 may be alleviated to increase rigidity and durability.

**[0027]** The distance L1 from the center C1 of the joint 1 to the first end 9a of the base 9 is designed not to exceed the maximum radius of rotation R2 of the base 9 (namely,  $L1 \leq R2$ ). In this manner, the arm 11 is designed to have a short length thereby securing the rigidity.

**[0028]** The maximum thickness T1 (see FIG.6) of the arm 11 is defined to be at least 15% of the maximum diameter of rotation D1 ( $D1=2 \times R2$ ) of the base 9 (namely,  $T1 \geq 0.15 \times D1$ ). Thus, the arm 11 can secure a determined rigidity so that controllability may be secured.

**[0029]** With respect to a direction parallel to a direction K1 orthogonal to the center axis 10 of the base 9 and the center axis 13 of the support hole 12, the second relief portions 18 of the pair of the side edges 17a of the arm 11 have a width W1 (or the width W1 between the relief portions 18 of the pair of side edges 17a) progressively decreased toward the center axis 10 of the base 9, as shown in FIG. 6 showing a section taken on the line VI-VI in FIG. 4. Accordingly, the interference between the corresponding side edges 17a of the yokes 4, 5 can be effectively prevented, so that the yokes are adapted to achieve the great bend angle (e.g., 60°).

**[0030]** Next, an exemplary procedure of forming the first yoke 4 by punching out and by press forming is described with reference to FIG. 7A to 7D and FIG. 8. First, a lower hole 32 drilled through an elongate sheet metal 31 is expanded by burring, as shown in FIG. 7A. A periphery of the lower hole 32 is extruded in one direction, whereby a cylindrical portion 33 is formed. The burring process may be replaced by drawing.

**[0031]** Subsequently, as shown in FIG. 7B, a blank as an intermediate member 34 having a predetermined outside shape is formed by a trimming process. The blank as an intermediate member 34 includes: a first portion 35 to form the base formed around the cylindrical portion 33 and designed; and a pair of second portions 36 to form the arms sandwiching the first portion 35 therebetween and extending in mutually opposite directions.

**[0032]** Next, as shown in FIG. 7C, a coining process is performed to form portions 16a', 14', 18' and 22' on each of the second portions 36 such that these portions 16a', 14', 18' and 22' constitute the concave groove 16a, the first relief portion 14, the second relief portion 18 and the chamfer 22, respectively.

**[0033]** As shown in FIG. 7D, the cylindrical portion 33 is subjected to drawing a process into a shaped portion 9' approximate to the base 9. While the pair of second portions 36 are bent to form portions 11' approximate to the pair of arms 11 by a bending process.

**[0034]** Subsequently, by shaping and coining processes the base 9 and the pair of arms 11 are formed as shown in FIG. 8.

**[0035]** Next, an inner periphery of the base 9 is subjected to serration, while each of the arms 11 is machined to form the support hole 12 therethrough, whereby the first yoke 4 is obtained as shown in FIG. 2.

**[0036]** FIG. 9 schematically shows a state where the universal joint 1 achieves the maximum bend angle of 60°. FIG. 9 omits the cross shaft.

**[0037]** A first axis P is an axis of the paired trunnions 7 connected with the first yoke 4 (equivalent to the center axis 13 of the support holes 12 of the first yoke 4). A second axis Q is an axis orthogonal to both the above first axis P and a rotation axis 4a of the first yoke 4.

**[0038]** In a state where the second yoke 5 is rotationally shifted from an unbent state about the first axis P in a first rotational direction P1 through a rotational angle  $\alpha$  ( $\alpha=45^\circ$ ) and as rotated about the second axis Q in a sec-

ond direction Q1 through a rotational angle  $\beta$  ( $\beta=45^\circ$ ), both the yokes 4, 5 encounter the severest conditions for the interference between the corresponding arms 11 thereof. The first rotational direction P1 and the second rotational direction Q1 are directed opposite to each other.

**[0039]** As schematically shown in FIG. 10, the embodiment is designed such that the flat plane as the second relief portion 18 of the arm 11 of the first yoke 4 and the flat plane as the second relief portion 18 of the corresponding arm 11 of the second yoke 5 are positioned in a parallel relation via a predetermined gap therebetween when these yokes are subjected to the severest conditions for the interference between these arms. Accordingly, the interference between the corresponding arms 11 of these yokes 4, 5 can be avoided by reducing a bare minimum amount of thickness of the arms 11. As a result, the universal joint 1 is adapted to secure the great bend angle while securing the secure strength thereof.

**[0040]** According to the embodiment, an advantage can be obtained to increase the bend angle and the rigidity of the joint 1 because the first relief portion 14 formed at the first end 9a of the base 9 and defined by the concave curved surface has the center of curvature A1 located at place offset from the center C1 of the joint 1 toward the distal end of the arm 11.

**[0041]** It should be noted that the center of curvature A1 of the first relief portion 14 need not necessarily be located on the center axis 10 of the base 9. In a case where the center of curvature A1 of the first relief portion 14 is not located on the center axis 10 of the base 9, a normal line of the first relief portion 14 having a position closest to the center axis 10 of the base 9 may be offset from the center C1 of the joint 1 toward the distal end of the arm 11.

**[0042]** In the second relief portion 18 provided at each of the side edges 17a of each arm 11, the width W1 of the arm 11 with respect to the direction parallel to the direction K1 orthogonal to the center axis 10 of the base 9 and the center axis 13 of the support hole 12 is progressively decreased toward the center axis 10 of the base 9, as shown in FIG. 6. Therefore, the interference between the corresponding side edges 17a of the yokes 4, 5 may be effectively avoided. Hence, the yokes can achieve the great bend angle (e.g., 60°).

**[0043]** The second relief portion 18 of each side edge 17a includes the flat plane defining the parallelogram. The flat plane intersects with the corresponding side edge 17a of the corresponding arm 11 on the first intersection 19 and the second intersection 20 extending in parallel to the center axis 10 of the base 9. The first intersection 19 is relatively closer to the center axis 10 of the base 9, whereas the second intersection 20 is relatively farther from the center axis 10 of the base 9. With respect to the direction parallel to the center axis 10 of the base 9, the first intersection 19 is relatively farther from the center C1 of the joint 1, whereas the second intersection 20 is relatively closer to the center C1 of the

joint 1. Thus, the relief is only provided at the necessary areas of the arms 11 such as to avoid the interference with the counterpart yoke 5. Hence, the joint 1 can achieve the great bend angle (e.g., 60°) while securing the strength of the arms 11.

**[0044]** In the present invention, the chamfer 22 for relief is formed on the overall length of the ridge 21 between the outside surface 15 of each arm 11 and the edge portion 17 having the inverted-U shape. Hence, the stress concentration on the arm 11 may be effectively alleviated.

**[0045]** What is more, the above chamfer 22 is formed continuous to the first relief portion 14 at the first end 9a of the base 9. Therefore, the yoke 4 may decrease in the stress concentration generated on the root of the arm 11, thereby achieving to increase strength and durability.

**[0046]** The length of the arm 11 is shortened such that the distance L1 from the center C1 of the joint 1 to the first end 9a of the base 9 does not exceed the maximum radius of rotation R2 of the base 9, thereby securing the rigidity of the arm 11.

**[0047]** Since the maximum thickness T1 of the arm 11 is defined to be at least 15% of the maximum diameter of rotation D1 of the base 9, the arm 11 can secure the determined rigidity so that the controllability may be secured.

**[0048]** While the invention has been described in greater details with reference to the specific embodiments thereof, it is to be understood that changes, modifications and equivalents will occur to those skilled in the art who have understood the above contents. The scope of the invention, therefore, is defined by the appended claims.

## Claims

1. A yoke (4) for universal joint (1) formed by punching out a sheet metal and press forming the sheet metal, comprising:

a cylindrical base (9) for fixing a shaft; and a pair of arms (11) extending from an end (9a) of the base (9) in parallel to a center axis (10) of the base (9) and swingably connectable with a counterpart yoke (5) via a cross shaft (6),

wherein each of the arms (11) is formed with a support hole (12) for supporting a corresponding trunnion (7) of the cross shaft (6) via a bearing (8), the support hole (12) of each of the arms (11) has a center axis (13) extending in a direction orthogonal to the center axis (10) of the base (9),  
**characterized in that**

the end (9a) of the base (9) is formed with a relief portion (14) including a concave curved surface, and the concave curved surface of the relief portion (14) at the end (9a) of the base (9) has a center of curvature (A1) located at place offset from a center (C1)

of the joint (1) toward a distal end of the arm (11).

2. The yoke of Claim 1, wherein each of the arms (11) includes an edge portion (17) having an inverted-U shape, the edge portion (17) of each of the arms (11) includes a pair of side edges (17a) extending in parallel to the center axis (10) of the base (9), the pair of each side edge (17a) of each of the arms (11) is each provided with a relief portion (18), and with respect to a direction parallel to a direction (K1) orthogonal to the center axis (10) of the base (9) and to the center axis (13) of the support hole (12), a width (W1) of the relief portions (18) of the pair of side edges (17a) of each of the arms (11) is progressively decreased toward the center axis (10) of the base (9).
3. The yoke of Claim 2, wherein the relief portion (18), of each of the side edges (17a) includes a flat plane defining a parallelogram, the flat plane intersects with the corresponding side edge (17a) of the corresponding arm (11) on first and second intersections (19, 20) extending in parallel to the center axis (10) of the base (9), the first intersection (19) is relatively closer to the center axis (10) of the base (9), whereas the second intersection (20) is relatively farther from the center axis (10) of the base (9), and with respect to a direction parallel to the center axis (10) of the base (9), the first intersection (19) is relatively farther from the center (C1) of the joint (1), whereas the second intersection (20) is relatively closer to the center (C1) of the joint (1).
4. The yoke of any of Claims 1 to 3, wherein a chamfer (22) for relief is formed on the overall length of a ridge (21) between an outside surface (15) of each of the arms (11) and the edge portion (17) having the inverted-U shape.
5. The yoke of Claim 4, wherein the chamfer (22) for relief is continuous to the relief portion (14) formed at the end (9a) of the base (9) and including the concave curved surface.
6. The yoke of any of Claims 1 to 5, wherein a distance (L1), from the center C1 of the joint (1) to the end (9a) of the base (9) is defined not to exceed the maximum radius of rotation (R2) of the base (9).
7. The yoke of any of Claims 1 to 6, wherein the maximum thickness (T1) of each of the arms (11) is at least 15% of the maximum diameter of rotation (D1) of the base (9).
8. A universal joint, comprising first and second yokes (4, 5) connected with each other via a cross shaft (6)

including four trunnions (7), and the universal joint using the yoke for universal joint according to any one of Claims 1 to 7 as each of the first and second yokes (4, 5), wherein in a state where the second yoke (5) is rotationally shifted from an unbent position about a first axis (P) through a rotation angle of 45° and about a second axis (Q) through a rotation angle of 45°, the flat plane as the relief portion (18) of each side edge (17a) of each of the arms (11) of the first yoke (4), and the flat plane as the relief portion (18) of the corresponding side edge (17a) of the corresponding arm (11) of the second yoke (5) are positioned in a parallel relation via a predetermined gap therebetween, where the first axis (P) is an axis of a pair of trunnions (7) connected with the first yoke (4), and the second axis (Q) is an axis orthogonal to both the first axis (P) and a rotation axis (4a) of the first yoke (4).

### Patentansprüche

1. Gabelkopf (4) für eine Gelenkkupplung (1), der durch Ausstanzen eines Blechs und Formpressen des Blechs ausgebildet ist, mit:

einer zylindrischen Basis (9) zum Anbringen einer Welle; und einem Paar von Armen (11), die sich von einem Ende (9a) der Basis (9) parallel zu einer Mittennachse (10) der Basis (9) erstrecken und schwenkbar mit einem Gegengabelkopf (5) mittels einer Querwelle (6) verbindbar sind,

wobei jeder der Arme (11) mit einem Stützloch (12) zum Stützen eines entsprechenden Zapfens (7) der Querwelle (6) mittels eines Lagers (8) ausgebildet ist,

wobei das Stützloch (12) von jedem der Arme (11) eine Mittennachse (13) aufweist, die sich in einer Richtung orthogonal zu der Mittennachse (10) der Basis (9) erstreckt,

**dadurch gekennzeichnet, dass**

das Ende (9a) der Basis (9) mit einem Aussparungsabschnitt (14) ausgebildet ist, der eine konkav gekrümmte Fläche aufweist, und

die konkav gekrümmte Fläche des Aussparungsabschnitts (14) an dem Ende (9a) der Basis (9) einen Krümmungsmittelpunkt (A1) aufweist, der an einem Ort versetzt von einer Mitte (C1) der Gelenkkupplung (1) in Richtung eines Distalendes des Arms (11) angeordnet ist.

2. Gelenkkupplung nach Anspruch 1, wobei jeder der Arme (11) einen Kantenabschnitt (17) aufweist, der die Form eines umgedrehten U aufweist, wobei der Kantenabschnitt (17) von jedem der Arme

(11) ein Paar von Seitenkanten (17a) aufweist, die sich parallel zu der Mittennachse (10) der Basis (9) erstrecken, wobei das Paar von jeder Seitenkante (17a) von jedem der Arme (11) jeweils mit einem Aussparungsabschnitt (18) versehen ist, und in Bezug auf eine Richtung parallel zu einer Richtung (K1), die orthogonal zu der Mittennachse (10) der Basis (9) und zu der Mittennachse (13) des Stützlochs (12) ist, eine Breite (W1) des Aussparungsabschnitts (18) des Paares von Seitenkanten (17a) von jedem der Arme (11) progressiv zu der Mittennachse (10) der Basis (9) hin abnimmt.

15 3. Gabelkopf nach Anspruch 2, wobei der Aussparungsabschnitt (18) von jeder der Seitenkanten (17a) eine flache Ebene aufweist, die ein Parallelogramm definieren,

wobei die flache Ebene sich mit der entsprechenden Seitenkante (17a) des entsprechenden Arms (11) an einem ersten und einem zweiten Schnittpunkt (19, 20) schneidet, die sich parallel zu der Mittennachse (10) der Basis (9) erstrecken,

wobei der erste Schnittpunkt (19) relativ näher an der Mittennachse (10) der Basis (9) ist, wohingegen der zweite Schnittpunkt (20) relativ weiter von der Mittennachse (10) der Basis (9) weg ist, und wobei in Bezug auf eine Richtung parallel zu der Mittennachse (10) der Basis (9) der erste Schnittpunkt (19) relativ weiter von der Mitte (C1) der Gelenkkupplung (1) weg ist, wohingegen der zweite Schnittpunkt (20) relativ näher zu der Mitte (C1) der Gelenkkupplung (1) ist.

35 4. Gabelkopf nach einem der Ansprüche 1 bis 3, wobei eine Abkantung (22) zur Entlastung über die gesamte Länge einer Kante (21) zwischen einer Außenfläche (15) von jedem der Arme (11) und dem Kantenabschnitt (17) ausgebildet ist, der die Form des umgedrehten U aufweist.

5 5. Gabelkopf nach Anspruch 4, wobei die Abkantung (22) zur Entlastung sich durchgängig zu dem Aussparungsabschnitt (14) erstreckt, der an dem Ende (9a) der Basis (9) ausgebildet ist und die konkav gekrümmte Fläche aufweist.

6. Gabelkopf nach einem der Ansprüche 1 bis 5, wobei eine Entfernung (L1) von der Mitte C1 der Gelenkkupplung (1) zu dem Ende (9a) der Basis (9) derart definiert ist, dass sie nicht den maximalen Rotationsradius (R2) der Basis (9) überschreitet.

7. Gabelkopf nach einem der Ansprüche 1 bis 6, wobei die maximale Dicke (T1) von jedem der Arme (11) mindestens 15 % des maximalen Rotationsdurchmessers (D1) der Basis (9) beträgt.

8. Gelenkkupplung, mit einem ersten und einem zweiten Gabelkopf (4, 5), die miteinander mittels einer Querwelle (6) verbunden sind, die vier Zapfen (7) aufweist, und der Gelenkkupplung, die den Gabelkopf für eine Gelenkkupplung nach einem der Ansprüche 1 bis 7 sowohl als ersten als auch als zweiten Gabelkopf (4, 5) verwendet, wobei in einem Zustand, in dem der zweite Gabelkopf (5) rotatorisch aus einer unverdrehten Position um eine erste Achse (P) um einen Rotationswinkel von 45° und um eine zweite Achse (Q) um einen Rotationswinkel von 45° versetzt ist, die flache Ebene als der Aussparungsabschnitt (18) von jeder Seitenkante (17a) von jedem der Arme (11) des ersten Gabelkopfs (4) und die flache Ebene als der Aussparungsabschnitt (18) der entsprechenden Seitenkante (17a) des entsprechenden Arms (11) des zweiten Gabelkopfs (5) in parallelem Verhältnis mit einer bestimmten Lücke zwischen sich angeordnet sind, wobei die erste Achse (P) eine Achse von einem Paar von Zapfen (7) ist, die mit dem ersten Gabelkopf (4) verbunden sind, und die zweite Achse (Q) eine Achse ist, die orthogonal zu sowohl der ersten Achse (P) und einer Rotationsachse (4a) des ersten Gabelkopfs (4) ist.

#### Revendications

1. Chape (4) pour un joint universel (1) formée par poinçonnage d'une tôle et formage à la presse de la tôle, comportant :

une base cylindrique (9) pour la fixation d'un arbre ; et une paire de bras (11) s'étendant depuis une extrémité (9a) de la base (9) parallèlement à un axe central (10) de la base (9) et pouvant être reliés de façon oscillante à une chape correspondante (5) par l'intermédiaire d'un croisillon (6), chacun des bras (11) étant formé avec un trou de support (12) destiné à supporter un tourillon (7) correspondant du croisillon (6) par l'intermédiaire d'un palier (8), le trou de support (12) de chacun des bras (11) ayant un axe central (13) s'étendant dans une direction perpendiculaire à l'axe central (10) de la base (9),

#### caractérisée en ce que

l'extrémité (9a) de la base (9) est formée avec une partie de dégagement (14) comprenant une surface courbe concave, et la surface courbe concave de la partie de dégagement (14) au niveau de l'extrémité (9a) de la base

(9) a un centre de courbure (A1) situé dans un emplacement décalé par rapport à un centre (C1) du joint (1) vers une extrémité distale du bras (11).

- 5 2. Chape selon la revendication 1, dans laquelle chacun des bras (11) comprend une partie de bord (17) ayant une forme de U inversé, la partie de bord (17) de chacun des bras (11) comprend une paire de bords latéraux (17a) s'étendant parallèlement à l'axe central (10) de la base (9), la paire de chaque bord latéral (17a) de chacun des bras (11) est pourvue chacune d'une partie de dégagement (18), et par rapport à une direction parallèle à une direction (K1) perpendiculaire à l'axe central (10) de la base (9) et à l'axe central (13) du trou de support (12), une largeur (W1) des parties de dégagement (18) de la paire de bords latéraux (17a) de chacun des bras (11) est progressivement diminuée vers l'axe central (10) de la base (9).
- 10 3. Chape selon la revendication 2, dans laquelle la partie de dégagement (18) de chacun des bords latéraux (17a) comprend un plan plat définissant un parallélogramme, le plan plat se coupe avec le bord latéral (17a) correspondant du bras (11) correspondant sur des première et deuxième intersections (19, 20) s'étendant parallèlement à l'axe central (10) de la base (9), la première intersection (19) est relativement plus près de l'axe central (10) de la base (9), alors que la deuxième intersection (20) est relativement plus loin de l'axe central (10) de la base (9), et par rapport à une direction parallèle à l'axe central (10) de la base (9), la première intersection (19) est relativement plus loin du centre (C1) du joint (1), alors que la deuxième intersection (20) est relativement plus près du centre (C1) du joint (1).
- 15 4. Chape selon l'une quelconque des revendications 1 à 3, dans laquelle un chanfrein (22) pour un dégagement est formé sur une longueur totale d'une arête (21) entre une surface extérieure (15) de chacun des bras (11) et la partie de bord (17) ayant la forme de U inversé.
- 20 5. Chape selon la revendication 4, dans laquelle le chanfrein (22) pour un dégagement est dans la continuité de la partie de dégagement (14) formée au niveau de l'extrémité (9a) de la base (9) et comprenant la surface courbe concave.
- 25 6. Chape selon l'une quelconque des revendications 1 à 5, dans laquelle une distance (L1) depuis le centre C1 du joint (1) jusqu'à l'extrémité (9a) de la base (9) est définie pour ne pas dépasser le rayon de rotation maximum (R2) de la base (9).

7. Chape selon l'une quelconque des revendications 1 à 6, dans laquelle l'épaisseur maximum (T1) de chacun des bras (11) est d'au moins 15% du diamètre de rotation maximum (D1) de la base (9).

5

8. Joint universel, comportant des première et deuxième chapes (4, 5) reliées l'une à l'autre par l'intermédiaire d'un croisillon (6) comprenant quatre tourillons (7), et

le joint universel utilisant la chape pour un joint universel selon l'une quelconque des revendications 1 à 7 comme première et deuxième chapes (4, 5), dans lequel, dans un état où la deuxième chape (5) est déplacée en rotation depuis une position non fléchie autour d'un premier axe (P) sur un angle de rotation de 45° et autour d'un deuxième axe (Q) sur un angle de rotation de 45°, le plan plat servant de partie de dégagement (18) de chaque bord latéral (17a) de chacun des bras (11) de la première chape (4), et le plan plat servant de partie de dégagement (18) du bord latéral (17a) correspondant du bras (11) correspondant de la deuxième chape (5) sont positionnés en relation parallèle avec un espace préterminé entre eux,

où le premier axe (P) est un axe d'une paire de tourillons (7) reliés à la première chape (4), et le deuxième axe (Q) est un axe perpendiculaire à la fois au premier axe (P) et à un axe de rotation (4a) de la première chape (4).

10

15

20

25

30

35

40

45

50

55

FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7A




FIG. 7B




FIG. 7C




FIG. 7D




FIG. 8




FIG. 9





FIG. 10



**REFERENCES CITED IN THE DESCRIPTION**

*This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.*

**Patent documents cited in the description**

- JP 2005163866 A [0005]
- JP 2000097246 A [0008]