



US 20200227008A1

(19) **United States**

(12) **Patent Application Publication**  
**Silvanto et al.**

(10) **Pub. No.: US 2020/0227008 A1**

(43) **Pub. Date: Jul. 16, 2020**

(54) **ELECTRONIC DEVICE DISPLAY WITH EXTENDED ACTIVE AREA**

**Publication Classification**

(71) Applicant: **Apple Inc.**, Cupertino, CA (US)

(51) **Int. Cl.**  
**G09G 5/14** (2006.01)  
**G06F 1/16** (2006.01)

(72) Inventors: **Mikael M. Silvanto**, San Francisco, CA (US); **Dinesh C. Mathew**, San Francisco, CA (US); **Victor H. Yin**, Cupertino, CA (US)

(52) **U.S. Cl.**  
CPC ..... **G09G 5/14** (2013.01); **G06F 1/1686** (2013.01); **G09G 3/3208** (2013.01); **G06F 1/1688** (2013.01); **G06F 1/1605** (2013.01)

(21) Appl. No.: **16/831,577**

(57) **ABSTRACT**


(22) Filed: **Mar. 26, 2020**

An electronic device may be provided with a display. The display may be formed from liquid crystal display pixels, organic light-emitting diode pixels, or other pixels. The display may have an active area that is bordered along at least one edge by an inactive area. The active area contains pixels and displays images. The inactive area does not contain any pixels and does not display images. The inactive area may have a layer of black ink or other masking material to block internal components from view. The active area may have an opening that contains an isolated portion of the inactive area or may contain a recess into which a portion of the inactive area protrudes. An electrical component such as a speaker, camera, light-emitting diode, light sensor, or other electrical device may be mounted in the inactive area in the recess or opening of the active area.

**Related U.S. Application Data**

(63) Continuation of application No. 15/759,054, filed on Mar. 9, 2018, now Pat. No. 10,607,573, filed as application No. PCT/US2016/048754 on Aug. 25, 2016.

(60) Provisional application No. 62/233,923, filed on Sep. 28, 2015.






FIG. 1




FIG. 2




FIG. 3





FIG. 4



**PRIOR ART**  
**FIG. 5**






FIG. 7




FIG. 8






FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14

## ELECTRONIC DEVICE DISPLAY WITH EXTENDED ACTIVE AREA

[0001] This application is a continuation of U.S. patent application Ser. No. 15/759,054, filed Mar. 9, 2018, which is a national stage application filed under 35 U.S.C. § 371 of international patent application No. PCT/2016/048754, filed Aug. 25, 2016, which claims priority to U.S. provisional patent application No. 62/233,923, filed Sep. 28, 2015, all of which are hereby incorporated by reference herein in their entireties.

### FIELD

[0002] This relates generally to electronic devices, and more particularly, to electronic devices with displays.

### BACKGROUND

[0003] Electronic devices often include displays. For example, cellular telephones, tablet computers, and laptop computers include displays for presenting information to users.

[0004] The active area of a display contains pixels that display images. Display driver circuits, buttons, cameras, and other components that do not emit light are located in an inactive border region that surrounds the active area.

[0005] If care is not taken, the size of the border of a display may be larger than desired. For example, when a component such as a camera or button is located along the border of a display, the border may need to be enlarged to accommodate the camera or button. This can restrict the amount of display area that is available for presenting visual information to a user.

### SUMMARY

[0006] An electronic device may be provided with a display. The display may be formed from liquid crystal display pixels, organic light-emitting diode pixels, or other pixels. The display may have an active area that is bordered by an inactive area. The active area contains pixels and displays images. The inactive area does not contain any pixels and does not display images.

[0007] The inactive area may have a layer of black ink or other masking material to block internal components from view. The active area may have an opening that contains an isolated inactive area region or may contain a notch or other recess into which a portion of the inactive area protrudes. An electrical component such as a speaker, camera, light-emitting diode, light sensor, proximity sensor, strain gauge, magnetic sensor, pressure sensor, force sensor, temperature sensor, or other sensor, button, touch-sensitive component, microphone or other audio component, or other electrical device that produces output and/or gathers input, may be mounted in a portion of the inactive area that protrudes into the recess or that is located in the opening of the active area.

[0008] The inactive area may have a main region such as a rectangular region that displays images and may have one or more extended regions that extend from the main region. The extended regions may, for example, include first and second elongated rectangular extended regions that lie between the main rectangular region and the inactive border. The first and second extended regions may be located on opposing sides of a camera or other electrical component in a protruding portion or island-shaped portion of the inactive

region. Icons or other information may be displayed on a black background in the extended regions, giving the display a continuous unbroken appearance.

[0009] Further features will be more apparent from the accompanying drawings and the following detailed description.

### BRIEF DESCRIPTION OF THE DRAWINGS

[0010] FIG. 1 is a perspective view of an illustrative electronic device such as a laptop computer with a display in accordance with an embodiment.

[0011] FIG. 2 is a perspective view of an illustrative electronic device such as a handheld electronic device with a display in accordance with an embodiment.

[0012] FIG. 3 is a perspective view of an illustrative electronic device such as a tablet computer, watch, or other portable device with a display in accordance with an embodiment.

[0013] FIG. 4 is a perspective view of an illustrative electronic device such as a computer display with display structures in accordance with an embodiment.

[0014] FIG. 5 is a diagram of a conventional display.

[0015] FIG. 6 is a diagram of an illustrative display in accordance with an embodiment.

[0016] FIG. 7 is a diagram of a portion of an illustrative display in accordance with an embodiment.

[0017] FIG. 8 is a diagram showing how an inactive area of a display may have the shape of an island surrounded by active area in accordance with an embodiment.

[0018] FIG. 9 is a diagram of an illustrative display in which an edge region of the display contains an inactive area protrusion that extends into a notch in an active area and contains a pair of extended active area regions on opposing sides of the inactive area protrusion in which icons and other information may be displayed in accordance with an embodiment.

[0019] FIGS. 10, 11, 12, 13, and 14 are front views of displays having illustrative active area and inactive area patterns in accordance with embodiments.

### DETAILED DESCRIPTION

[0020] Electronic devices may include displays. The displays may be used to display images for a user. Illustrative electronic devices that may be provided with displays are shown in FIGS. 1, 2, 3, and 4.

[0021] FIG. 1 shows how electronic device 10 may have the shape of a laptop computer having upper housing 12A and lower housing 12B with components such as keyboard 16 and touchpad 18. Device 10 may have hinge structures 20 that allow upper housing 12A to rotate in directions 22 about rotational axis 24 relative to lower housing 12B. Display 14 may be mounted in upper housing 12A. Upper housing 12A, which may sometimes referred to as a display housing or lid, may be placed in a closed position by rotating upper housing 12A towards lower housing 12B about rotational axis 24.

[0022] FIG. 2 shows how electronic device 10 may be a handheld device such as a cellular telephone, music player, gaming device, navigation unit, or other compact device. In this type of configuration for device 10, housing 12 may have opposing front and rear surfaces. Display 14 may be mounted on a front face of housing 12. Display 14 may, if desired, have openings for components such as button 26.

Openings may also be formed in display 14 to accommodate a speaker port (see, e.g., speaker port 28 of FIG. 2).

[0023] FIG. 3 shows how electronic device 10 may be a tablet computer, watch, or other portable device. In electronic device 10 of FIG. 3, housing 12 may have opposing planar front and rear surfaces. Display 14 may be mounted on the front surface of housing 12. As shown in FIG. 3, display 14 may have an opening to accommodate button 26. If desired, button 26 may be omitted.

[0024] FIG. 4 shows how electronic device 10 may be a display such as a display with an embedded computer, a display without an embedded computer, or other suitable equipment for displaying images. With this type of arrangement, housing 12 for device 10 may be mounted on a support structure such as stand 30 or stand 30 may be omitted (e.g., to mount device 10 on a wall). Display 14 may be mounted on a front face of housing 12.

[0025] The illustrative configurations for device 10 that are shown in FIGS. 1, 2, 3, and 4 are merely illustrative. The outline of display 14 may be rectangular, oval, circular, or other suitable shape. In general, electronic device 10 may be a laptop computer, a computer monitor or other display containing an embedded computer, a tablet computer, a cellular telephone, a media player, or other handheld or portable electronic device, a smaller device such as a wrist-watch device, a pendant device, a headphone or earpiece device, or other wearable or miniature device, a computer display or other monitor that does not contain an embedded computer, a gaming device, a navigation device, an embedded system such as a system in which electronic equipment with a display is mounted in a kiosk or automobile, equipment that implements the functionality of two or more of these devices, or other electronic equipment.

[0026] Housing 12 of device 10, which is sometimes referred to as a case, may be formed of materials such as plastic, glass, ceramics, carbon-fiber composites and other fiber-based composites, metal (e.g., machined aluminum, stainless steel, or other metals), other materials, or a combination of these materials. Device 10 may be formed using a unibody construction in which most or all of housing 12 is formed from a single structural element (e.g., a piece of machined metal or a piece of molded plastic) or may be formed from multiple housing structures (e.g., outer housing structures that have been mounted to internal frame elements or other internal housing structures).

[0027] Display 14 may be a touch sensitive display that includes a touch sensor or may be insensitive to touch. Touch sensors for display 14 may be formed from an array of capacitive touch sensor electrodes, a resistive touch array, touch sensor structures based on acoustic touch, optical touch, or force-based touch technologies, or other suitable touch sensor components.

[0028] Display 14 for device 10 may be a liquid crystal display, an organic light-emitting diode display, a plasma display, an electrophoretic display, an electrowetting display, a display formed from an array of crystalline semiconductor light-emitting diode dies, or a display formed from other types of pixels. A display cover layer may cover the surface of display 14 or a display layer such as a color filter layer or other portion of a display may be used as the outermost (or nearly outermost) layer in display 14. The outermost display layer may be formed from a transparent glass sheet, a clear plastic layer, or other transparent member.

[0029] The layers of material that make up display 14 may be mounted in chassis structures such as a plastic chassis structure and/or a metal chassis structure to form a display module for mounting in housing 12 and/or the layers of display 14 may be mounted directly in housing 12 (e.g., by stacking display layers into a recessed portion of housing 12).

[0030] Display 14 may have a rectangular shape (i.e., display 14 may have a rectangular footprint and a rectangular peripheral edge that runs around the rectangular footprint), may have an oval or circular footprint, or may have other shapes with curved and/or straight edges. Display 14 may be planar or may have a curved profile. To help accommodate electrical components along the edges of display 14 without overly reducing the size of the footprint of display 14, the edges of active area of display 14 may be provided with locally recessed portions such as notches and/or display 14 may be provided with isolated inactive areas in which electrical components can be mounted.

[0031] A top view of a conventional display is shown in FIG. 5. Display 200 of FIG. 5 has a rectangular active area AA with four straight edges 202. A rectangular ring-shaped inactive area IA surrounds active area AA. The width W of the upper strip of inactive area IA is sufficiently wide to accommodate camera 202. However, the width W of this upper strip of inactive area IA is larger than necessary in regions such as regions 206 of the upper strip of inactive area that do not contain camera 202. This leads to wasted space.

[0032] A top view of an illustrative display with a recessed portion along one of the edges of its active area is shown in FIG. 6. As shown in FIG. 6, display 14 may have an array of pixels 122 formed from layers of material on a substrate such as substrate 36. Substrates such as substrate 36 may be formed from glass, metal, plastic, ceramic, or other suitable materials. Pixels 122 may receive data signals over signal paths such as data lines D and may receive one or more control signals over control signal paths such as horizontal control lines G (sometimes referred to as gate lines, scan lines, emission control lines, etc.). There may be any suitable number of rows and columns of pixels 122 in display 14 (e.g., tens or more, hundreds or more, or thousands or more).

[0033] Display 14 may be formed from an array of discrete light-emitting diodes, from electrowetting pixel structures, from electrophoretic pixel structures, or from other suitable display structures. In organic light-emitting diode displays, pixels 122 contain respective organic light-emitting diodes and pixel circuits that control the application of current to the light-emitting diodes. In liquid crystal displays, pixels 122 contain pixel circuits that control the application of signals to pixel electrodes that are used for applying controlled amounts of electric field to pixel-sized portions of a liquid crystal layer. The pixel circuits in pixels 122 may contain transistors having gates that are controlled by control signals such as gate line signals on gate lines G.

[0034] Display driver circuitry 120 may be used to control the operation of pixels 122. Display driver circuitry 120 may be formed from integrated circuits, thin-film transistor circuits, or other suitable circuitry. Thin-film transistor circuitry may be formed from polysilicon thin-film transistors, semiconducting-oxide thin-film transistors such as indium gallium zinc oxide transistors, or thin-film transistors formed from other semiconductors. Pixels 122 may have color filter elements or other colored structures of different

colors (e.g., red, green, and blue) to provide display 14 with the ability to display color images.

**[0035]** Display driver circuitry 120 may include display driver circuits such as display driver circuitry 120A and gate driver circuitry 120B. Display driver circuitry 120A may be formed from one or more display driver integrated circuits and/or thin-film transistor circuitry (e.g., timing controller integrated circuits). Gate driver circuitry 120B may be formed from gate driver integrated circuits or may be thin-film “gate-on-array” circuitry. Display driver circuitry 120A of FIG. 6 may contain communications circuitry for communicating with system control circuitry in device 10. This control circuitry may include microprocessors, application-specific integrated circuits, memory, and other storage and processing circuitry for generating images to display on display 14. The control circuitry of device 10 may communicate with display driver circuitry 120A over path 32. Path 32 may be formed from traces on a flexible printed circuit or other conductive lines. During operation, the control circuitry of device 10 may supply circuitry 120A with information on images to be displayed on pixels 122 of active area AA of display 14.

**[0036]** To display the images on display pixels 122, display driver circuitry 120A may supply image data to data lines D while issuing control signals to supporting display driver circuitry such as gate driver circuitry 120B over paths such as paths 38. Path 38 may, for example, include lines for carrying power signals, control signals such as output enable signals, clock signals, etc. Circuitry 120A may supply these signals to gate driver circuitry 120B. Circuitry 120B may be located on one edge of display 14, on opposing left and right edges of display 14, or elsewhere in display 14.

**[0037]** Gate driver circuitry 120B (sometimes referred to as horizontal control line control circuitry) may control horizontal control lines (gate lines) G using the signals received from path 38 (e.g., power signals, output enable signals, clock signals, etc.). Gate lines G in display 14 may each carry a gate line signal or other signal or signals for controlling the pixels 122 of a respective row (e.g., to turn on transistors in pixels 122 when loading data from the data lines into pixel storage capacitors in those pixels from data lines D). During operation, frames of image data may be displayed by asserting a gate signal on each gate line G in the display in sequence. Shift register circuitry (e.g., a chain of registers) in gate driver circuitry 120B may be used in controlling the gate line signals.

**[0038]** Display 14 has an active area AA that contains pixels 122 and that displays images. Display 14 may also have an inactive area IA (sometimes referred to as a border region) that contains display driver circuitry 120 and other components that do not produce images. In some configurations, the underside of a display cover layer for display 14 or other layer of display 14 may contain opaque masking material (e.g., a layer of black or white ink, etc.) to hide display driver circuitry and other components in inactive area IA from view from the exterior of device 10. Windows may also be formed in the inactive area of display 14 (e.g., to accommodate image sensors, to accommodate ambient light sensors, proximity sensors, etc.).

**[0039]** In display 14 of FIG. 6, active area AA has a generally rectangular shape with upper and lower edges and left and right edges. Inactive area IA may have four generally strip-shaped edge regions (e.g., display 14 may have a rectangular ring-shaped inactive border made up of upper

and lower inactive area strips and left and right inactive area strips). To accommodate components in inactive area IA without overly enlarging inactive area IA (and thereby overly reducing the size of active area AA), active area AA may be provided with one or more recesses or isolated openings into which part of inactive area IA may extend. For example, a notch may be formed in active area AA and a portion of inactive area IA may protrude into the notch. This protruding portion of the inactive area may be used to accommodate a component such as a button, fingerprint reader, light-emitting diode status indicator, ambient light sensor, proximity sensor, touch sensor, camera (i.e., a digital image sensor), strain gauge, magnetic sensor, pressure sensor, force sensor, temperature sensor, or other sensor, button, touch-sensitive component, microphone or other audio component, or other electrical component(s) that produces output and/or receives input.

**[0040]** In the configuration of FIG. 6, for example, active area AA of display 14 may have an upper edge such as edge 132. A recess such as recessed portion 130 may be formed in edge 132. Recessed portion 130 creates an associated enlarged inwardly protruding region 134 of inactive area IA. Extended inactive areas such as inactive area IA in region 134 may be contiguous with other portions of inactive area IA or may be formed as isolated islands of inactive area IA that are surrounded by active area AA. In the example of FIG. 6, inactive area IA in inwardly protruding area 134 is contiguous with the horizontal upper strip of inactive area IA that forms the top border region of display 14.

**[0041]** Due to the presence of inactive area protrusion 134, there is room in display 14 for a component such as component 136. Component 136 may be a sensor, a light detecting device, an output device, a button, a fingerprint reader, an image sensor, or other suitable device. As an example, component 136 may be an image sensor (camera) that is mounted behind a camera window. The camera window may include an opening in a black ink layer and/or unpolarized regions of otherwise polarized layer(s) in the layers of material forming display 14. Other light-based components (e.g., light sensors, light-emitting devices such as one or more discrete visible-light or infrared light-emitting diodes, light-based proximity sensors, etc.) may also be mounted under a window in region 134 of inactive area IA. The use of a camera in region 134 is merely illustrative.

**[0042]** Because region 134 protrudes inwardly into active area AA, the gate lines G (or other horizontal control lines) that would otherwise traverse region 134 may be truncated, as shown in FIG. 6. In general, data lines D, control lines such as gate lines G, and/or both data lines and control lines may be routed in a way that accommodates extended inactive area 134. In the example of FIG. 6, shortened gate lines G allow extended portions of active area AA to be present on the left and right sides of inactive region 134. It is therefore not necessary to eliminate entire rows of pixels 122 along the upper edge of active area AA to accommodate component 136. This maximizes the area consumed by active area AA.

**[0043]** In the example of FIG. 6, gate lines G include regular length lines that extend from gate driver circuitry 120B at the left and right edge of display 14 to the middle of display 14. Gate lines G also include shortened lines. The shortened lines extend from gate driver circuitry 120B at the left and right edges of display 14 towards the middle of

display **14** as with the regular length lines, but terminate at the edge of inactive area protrusion **134** so as not to intrude into protrusion **134**. Data lines **D** likewise include regular length lines that extend the full vertical extent of display **14** and shortened data lines such as data line **D'** that terminate at the edge of protrusion **134**.

**[0044]** If desired, other data line and gate line layouts may be used to route signals to pixels **122** without intruding on inactive areas such as protrusion **134**. For example, the illustrative arrangement of FIG. **7** shows how gate line signals may be routed vertically to horizontal gate lines **G** using vertical gate line extensions **G'**. Gate line extensions **G'** may each be coupled to gate driver circuitry located along the lower edge of display **14** (as an example). This layout, which reduces or eliminates the need for gate driver circuitry along the left and right edges of display **14**, allows borders such as the left-hand border region (inactive area **IA**) for display **14** to be reduced in size. In the illustrative configuration of FIG. **8**, data lines **D** have folded over end portions **DF** that allow data lines **D** to load data into pixels **122** that would otherwise be blocked due to the presence of an island of inactive area **IA** such as island **1341** or other isolated inactive area. If desired, display driver circuitry may be located in blocks both above and below islands such as island **1341** (in which case data lines can extend directly to pixels **122** from the respective blocks without folding). Other arrangements for routing control line signals, data line signals, and power signals may be used to accommodate inward protrusions of inactive area (i.e., active area notches or other recesses) and/or islands of inactive area surrounded by active area (i.e., inactive area formed in isolated openings in the active area). The configurations of FIGS. **6**, **7**, and **8** are merely illustrative.

**[0045]** The extended inactive area regions of display **14** may make it difficult or impossible to display a perfect rectangle of image content on display **14**. Nevertheless, the enhanced amount of active area that is present in display **14** can be put to use in displaying other information for a user.

**[0046]** With one illustrative approach, which is illustrated in FIG. **9**, a portion of active area **AA** (i.e., a main rectangular portion of active area **AA** such as main portion **AA-M**) may be used in displaying a rectangular portion of content for the user. Rectangular main portion **AA-M** of display **14** may, for example, be used to display a rectangular picture, a rectangular video, a rectangular document containing text and/or graphics, or other rectangular content. Due to the presence of inactive area protrusion **134**, horizontal upper edge **140** of portion **AA-M** cannot be extended farther upward without altering its shape. Nevertheless, extended active area regions **AA-EL** and **AA-ER** are available to the left and right of region **134**. Regions **AA-EL** and **AA-ER** may be elongated rectangular regions (i.e., strip-shaped regions that extend horizontally). Region **AA-EL** lies between edge **140** of active area region **AA-M** and inner edge **142** of the portion of inactive area **IA** that extends along the upper edge of display **14**. Region **AA-ER** lies between edge **140** of active area region **AA-M** and inner edge **142**.

**[0047]** Regions such as extended regions **AA-EL** and **AA-ER** may be used to display content such as text, graphics, video, pictures, etc. For example, regions **AA-EL** and **AA-ER** may be used to display information such as time and data information **144** and icons **146**. This information may relate to the general status of device **10** and/or may be related to the content being displayed in area **AA-M**. For

example, information in regions **AA-EL** and **AA-ER** may contain status bar information such as battery charge level, wireless local area network signal strength information, network connectivity information, time information, date information, message status information, display brightness information, media playback status information, etc. If desired, information in regions **AA-EL** and **AA-ER** may relate to a document being displayed in region **AA-M**. For example, page count information, word count information, document magnification status, line spacing settings, and other status information on a document may be presented. In situations in which region **AA-M** is displaying a video, regions **AA-EL** and **AA-ER** may display running time information, time remaining information, playback volume information, media title information, etc.

**[0048]** Information **144** and **146** may be presented on a background such as background **148**. Background **148** may have any suitable color and/or pattern. If desired, inactive area **IA** may include a layer of black ink or other opaque masking material to hide internal components under the outermost layer(s) of display **14** from view. In this type of arrangement, background **148** may be black to match the black color of the inactive area masking material. Region **134** may also be black (e.g., the underside of the display layer(s) in region **134** may be coated with black ink) or region **134** may have a contrasting appearance (e.g., region **134** may be shiny, may be white, may be colored red or other suitable color, etc.). In configurations in which region background **148** is black to match the black color of region **134**, regions **AA-EL** and **AA-ER** will have the appearance of being part of an integral strip of active area (and thereby an integral extensions of active area **AA-M**). The visual interruption from protrusion **134** will not be visually prominent because the black of region **134** will blend with the black of background **148**.

**[0049]** If desired, the active area **AA** of display **14** may have other shapes with islands of inactive area **IA** (i.e., openings in which inactive area **IA** has the shape of an isolated region surrounded by active area **AA**) and/or rectangular notches or other recesses. In the example of FIG. **10**, active area **AA** of display **14** has a rectangular shape with a relatively shallow rectangular recess **130**. FIG. **11** shows how there may be multiple recesses (e.g., recesses such as rectangular recesses **130-1** and **130-2**) in active area **AA**. In the FIG. **12** configuration, there are recesses in each of the four corners of active area **AA** (i.e., recesses **130-1**, **130-2**, **130-3**, and **130-4**). In FIG. **13**, active area **AA** has a circular outline into which a smooth mousehole-shaped recess **130** has been formed. Rectangular active areas such as rectangular active area **AA** of FIG. **14** may also be provided with curved recesses. Recess **130** of FIG. **14** may, as an example, accommodate button **26**. Openings in active area **AA** such as illustrative opening **1301** of FIG. **14** may be used to accommodate speakers and/or other electrical components.

**[0050]** Inactive area portions such as protrusions **134** may extend into each of the openings and other recesses of FIGS. **10**, **11**, **12**, **13**, and **14**. Moreover, other shapes and layouts for the active area **AA** and inactive area **IA** of display **14** may be used. The examples of FIGS. **10**, **11**, **12**, **13**, and **14** are merely illustrative.

**[0051]** In accordance with an embodiment, a display is provided that includes an active area containing pixels that displays images, and an inactive area without pixels that extends along at least a portion of one edge of the active

area, a protruding portion of the inactive area extends into the active area along the portion of the edge.

**[0052]** In accordance with another embodiment, the active area includes a rectangular portion and two rectangular extended regions on opposing sides of the inactive area.

**[0053]** In accordance with another embodiment, the pixels in the active area are configured to display icons in the rectangular extended regions.

**[0054]** In accordance with another embodiment, the display includes a camera in the protruding portion.

**[0055]** In accordance with another embodiment, the display includes an electrical component in the protruding portion of the inactive area.

**[0056]** In accordance with another embodiment, the electrical component includes an image sensor.

**[0057]** In accordance with another embodiment, the protruding portion includes a rectangular portion of the inactive area.

**[0058]** In accordance with another embodiment, the protruding portion of the inactive area has a black masking layer and the active area includes at least one portion that is adjacent to the protruding portion that displays information on a black background.

**[0059]** In accordance with another embodiment, the active area has a rectangular shape and the protruding portion includes a rectangular portion of the inactive area.

**[0060]** In accordance with another embodiment, the active area has a circular shape.

**[0061]** In accordance with another embodiment, the active area has a rectangular shape and the protruding portion protrudes into at least one corner of the rectangular shape.

**[0062]** In accordance with an embodiment, a display is provided that includes an active area containing pixels that displays images, and an isolated inactive area without pixels that is formed in an opening in the active area and that does not display images.

**[0063]** In accordance with another embodiment, the display includes an electrical component in the isolated inactive area.

**[0064]** In accordance with another embodiment, the electrical component includes a component selected from the group consisting of a speaker, a camera, a light sensor, a discrete light-emitting diode, a proximity sensor, a strain gauge, a force sensor, a temperature sensor, a fingerprint sensor, a button, and a microphone.

**[0065]** In accordance with another embodiment, the pixels include liquid crystal display pixels.

**[0066]** In accordance with another embodiment, the pixels include organic light-emitting diode pixels.

**[0067]** In accordance with another embodiment, the active area includes data lines and at least some of the data lines have folded ends adjacent to the isolated inactive area.

**[0068]** In accordance with another embodiment, the active area has a recessed portion into which a protruding inactive area extends.

**[0069]** In accordance with an embodiment, a laptop computer is provided that includes a housing having a base and a lid that rotates relative to the base, a display supported by the lid, the display has an active area containing pixels that displays images and has an inactive area that runs along at least one edge of the active area and the active area has a recess and the inactive area has a protruding portion that extends into the recess, and a camera mounted in the protruding portion of the inactive area.

**[0070]** In accordance with another embodiment, the active area has a main rectangular region that displays images and has first and second rectangular extended regions between the main rectangular region and the inactive border and the first and second rectangular extended regions are on opposing sides of the camera.

**[0071]** In accordance with another embodiment, the first and second rectangular extended regions display icons on a black background while the main rectangular region displays a rectangular picture.

**[0072]** The foregoing is merely illustrative and various modifications can be made by those skilled in the art without departing from the scope and spirit of the described embodiments. The foregoing embodiments may be implemented individually or in any combination.

What is claimed is:

1. An electronic device, comprising:
  - an array of pixels that form an active area, wherein the array of pixels includes first and second groups of pixels;
  - an opaque masking material that forms an inactive area between the first and second groups of pixels; and
  - a light sensor and light emitter located in the inactive area between the first and second groups of pixels.
2. The electronic device defined in claim 1 wherein the opaque masking material forms a border around the array of pixels.
3. The electronic device defined in claim 1 wherein the light emitter emits infrared light.
4. The electronic device defined in claim 3 wherein the light sensor detects infrared light.
5. The electronic device defined in claim 1 wherein the opaque masking layer has an opening that is located between the first and second groups of pixels and that is aligned with the light sensor.
6. The electronic device defined in claim 1 further comprising signal lines that extend across rows of the pixels in the array, wherein the signal lines include first and second signal lines and wherein the first signal line is shorter than the second signal line.
7. The electronic device defined in claim 6 wherein the signal lines comprise gate lines and wherein the first signal line extends across the first group of pixels.
8. The electronic device defined in claim 1 wherein the second group of pixels is configured to display a battery charge level and signal strength information.
9. The electronic device defined in claim 1 wherein the opaque masking layer comprises an opening located between the first and second groups of pixels.
10. The electronic device defined in claim 1 further comprising a display cover layer that overlaps the array of pixels and that has a speaker port located between the first and second groups of pixels.
11. An electronic device, comprising:
  - an active display area including an array of pixels, wherein the array of pixels includes first and second rows of pixels and wherein the first row has fewer pixels than the second row;
  - first and second signal lines that respectively extend across the first and second rows of pixels, wherein the first signal line is shorter than the second signal line;
  - an inactive display area having a protruding portion that protrudes into the active display area and interrupts the first row of pixels; and



input-output components in the protruding portion of the inactive display area.

**12.** The electronic device defined in claim **11** wherein the input-output components comprise at least one component selected from the group consisting of: a speaker, a camera, a light sensor, a discrete light-emitting diode, a proximity sensor, a strain gauge, a force sensor, a temperature sensor, a fingerprint sensor, a button, and a microphone.

**13.** The electronic device defined in claim **11** wherein the first and second signal lines comprise gate lines.

**14.** The electronic device defined in claim **11** further comprising opaque masking material in the protruding portion of the inactive display area.

**15.** The electronic device defined in claim **14** wherein the opaque masking material has an opening in the inactive display area that is aligned with one of the input-output components.

**16.** An electronic device, comprising:

an array of pixels including first and second rows of pixels, wherein the first row has fewer pixels than the second row;

an infrared light-emitting component interposed between first and second pixels in the first row of pixels; and an opaque masking material interposed between the first and second pixels in the first row of pixels.

**17.** The electronic device defined in claim **16** wherein the opaque masking material has an opening aligned with the infrared light-emitting component.

**18.** The electronic device defined in claim **16** wherein the opaque masking material interrupts the first row of pixels without interrupting the second row of pixels.

**19.** The electronic device defined in claim **16** further comprising a first gate line that extends across the first row of pixels and a second gate line that extends across the second row of pixels, wherein the first gate line is shorter than the second gate line.

**20.** The electronic device defined in claim **16** further comprising a display cover layer that overlaps the array of pixels and that has an opening between the first and second pixels.

\* \* \* \* \*