




(86) Date de dépôt PCT/PCT Filing Date: 2017/07/20  
 (87) Date publication PCT/PCT Publication Date: 2018/01/25  
 (45) Date de délivrance/Issue Date: 2021/04/13  
 (85) Entrée phase nationale/National Entry: 2019/01/21  
 (86) N° demande PCT/PCT Application No.: US 2017/043162  
 (87) N° publication PCT/PCT Publication No.: 2018/017886  
 (30) Priorités/Priorities: 2016/07/21 (US62/365,070);  
 2017/03/14 (US62/471,213); 2017/07/18 (US15/653,390)

(51) Cl.Int./Int.Cl. *A61F 2/24* (2006.01)  
 (72) Inventeurs/Inventors:  
 PETERSON, MATTHEW A., US;  
 YI, SEUNG-BEOM, US;  
 VAD, SIDDHARTH, US;  
 OBA, TRAVIS ZENYO, US;  
 FRESCHAUF, LAUREN R., US;  
 FRENCH, AMANDA, US;  
 KEIDAR, YARON, IL;  
 ...  
 (73) Propriétaire/Owner:  
 EDWARDS LIFESCIENCES CORPORATION, US  
 (74) Agent: STIKEMAN ELLIOTT S.E.N.C.R.L.,SRL/LLP

(54) Titre : PROTHESE DE VALVULE CARDIAQUE DE REMPLACEMENT  
 (54) Title: REPLACEMENT HEART VALVE PROSTHESIS



(57) **Abrégé/Abstract:**

A prosthesis can be configured to grasp intraluminal tissue when deployed within a body cavity and prevent axial flow of fluid around an exterior of the prosthesis. The prosthesis can include an expandable frame configured to radially expand and contract

(72) **Inventeurs(suite)/Inventors(continued)**: DU, YUANLONG, US; BAK-BOYCHUK, GREGORY, US;  
GOLEMO, KEVIN M., US

(57) **Abrégé(suite)/Abstract(continued)**:

for deployment within the body cavity and a valve body. The expandable frame can include a frame body and a supplemental frame. The valve body can include a plurality of leaflets and one or more intermediate components. The one or more intermediate components can couple at least a portion of the leaflets to the expandable frame. The prosthesis can include an annular flap positioned around an exterior of the expandable frame.

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization  
International Bureau

(43) International Publication Date  
25 January 2018 (25.01.2018)



(10) International Publication Number  
**WO 2018/017886 A1**

- (51) International Patent Classification:  
*A61F 2/24* (2006.01)
- (21) International Application Number:  
PCT/US2017/043162
- (22) International Filing Date:  
20 July 2017 (20.07.2017)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
 

62/365,070	21 July 2016 (21.07.2016)	US
62/471,213	14 March 2017 (14.03.2017)	US
15/653,390	18 July 2017 (18.07.2017)	US
- (71) Applicant: EDWARDS LIFESCIENCES CORPORATION [US/US]; One Edwards Way, Irvine, CA 92614 (US).

- (72) Inventors: PETERSON, Matthew, A.; Edwards Lifesciences, One Edwards Way, Legal Department, Irvine, CA 92614 (US). YI, Seung-Beom; Edwards Lifesciences, One Edwards Way, Legal Department, Irvine, CA 92614 (US). VAD, Siddharth; Edwards Lifesciences, One Edwards Way, Legal Department, Irvine, CA 92614 (US). OBA, Travis, Zenyo; Edwards Lifesciences, One Edwards Way, Legal Department, Irvine, CA 92614 (US). FRESCHAUF, Lauren, R.; Edwards Lifesciences, One Edwards Way, Legal Department, Irvine, CA 92614 (US). FRENCH, Amanda; 1885 Hayes Street, San Francisco, CA 94117 (US). KEIDAR, Yaron; 2 Kashtan Street, 34984 Haifa (IL). DU, Yuanlong; Edwards Lifesciences, One Edwards Way, Legal Department, Irvine, CA 92614 (US). BAK-BOY-CHUK, Gregory; Edwards Lifesciences, One Edwards Way, Legal Department, Irvine, CA 92614 (US). GOLEMO, Kevin, M.; One Edwards Way, Legal Department, Irvine, CA 92614 (US).

(54) Title: REPLACEMENT HEART VALVE PROSTHESIS




FIG. 120

(57) Abstract: A prosthesis can be configured to grasp intraluminal tissue when deployed within a body cavity and prevent axial flow of fluid around an exterior of the prosthesis. The prosthesis can include an expandable frame configured to radially expand and contract for deployment within the body cavity and a valve body. The expandable frame can include a frame body and a supplemental frame. The valve body can include a plurality of leaflets and one or more intermediate components. The one or more intermediate components can couple at least a portion of the leaflets to the expandable frame. The prosthesis can include an annular flap positioned around an exterior of the expandable frame.



WO 2018/017886 A1

**WO 2018/017886 A1** 

(74) **Agent:** CRAPENHOFT, Michael et al.; Edwards Life-sciences, One Edwards Way, Irvine, CA 92614 (US).

(81) **Designated States** (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DJ, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JO, JP, KE, KG, KH, KN, KP, KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) **Designated States** (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

**Published:**

- with international search report (*Art. 21(3)*)
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments (*Rule 48.2(h)*)

## REPLACEMENT HEART VALVE PROSTHESIS

### BACKGROUND

#### Field

[0001] Embodiments disclosed herein relate generally to prostheses for implantation within a lumen or body cavity. In particular, certain embodiments relate to expandable prostheses such as replacement heart valves, such as for the mitral valve, that are configured to be secured to intralumenal tissue and prevent paravalvular leakage.

#### Background

[0002] Human heart valves, which include the aortic, pulmonary, mitral and tricuspid valves, function essentially as one-way valves operating in synchronization with the pumping heart. The valves allow blood to flow downstream, but block blood from flowing upstream. Diseased heart valves exhibit impairments such as narrowing of the valve or regurgitation, which inhibit the valves' ability to control blood flow. Such impairments reduce the heart's blood-pumping efficiency and can be a debilitating and life threatening condition. For example, valve insufficiency can lead to conditions such as heart hypertrophy and dilation of the ventricle. Thus, extensive efforts have been made to develop methods and apparatuses to repair or replace impaired heart valves.

[0003] Prostheses exist to correct problems associated with impaired heart valves. For example, mechanical and tissue-based heart valve prostheses can be used to replace impaired native heart valves. More recently, substantial effort has been dedicated to developing replacement heart valves, particularly tissue-based replacement heart valves that can be delivered with less trauma to the patient than through open heart surgery. Replacement valves are being designed to be delivered through minimally invasive procedures and even percutaneous procedures. Such replacement valves often include a tissue-based valve body that is connected to an expandable frame that is then delivered to the native valve's annulus.

[0004] These replacement valves are often intended to at least partially block blood flow. However, a problem occurs when blood flows around the valve on the outside of the prosthesis. For example, in the context of replacement heart valves, paravalvular leakage has proven particularly challenging. An additional challenge relates

to the ability of such prostheses to be secured relative to intraluminal tissue, e.g., tissue within any body lumen or cavity, in an atraumatic manner. Yet another challenge arises when trying to reduce the likelihood of thrombosis within parts of the replacement valves and increasing the longevity of the replacement valve. Further challenges arise when trying to replace an already existing replacement valve with a new replacement valve.

#### SUMMARY

**[0005]** Embodiments of the present disclosure are directed to a prosthesis, such as but not limited to a replacement heart valve. According to some embodiments, a prosthesis can be configured to be deployed within a body cavity and prevent axial flow of fluid around an exterior of the prosthesis. The prosthesis can include an expandable frame configured to radially expand and contract for deployment within the body cavity, and an annular skirt positioned around an exterior of the expandable frame. The prosthesis can further include a valve body configured to provide one-way flow through the prosthesis. The prosthesis can further include a plurality of anchors for securing the prosthesis to intraluminal tissue such as the native valve anatomy. Further embodiments are directed to methods of delivering a prosthesis, e.g. a replacement heart valve, and methods of using a prosthesis to create a barrier to fluid flow exterior to the prosthesis (e.g., to prevent paravalvular leakage).

**[0006]** In some embodiments, a prosthesis can include an expandable frame having a proximal end and a distal end and a longitudinal axis extending therethrough. The expandable frame can be configured to radially expand and contract for deployment within a native heart valve. The prosthesis can include a valve body positioned within an interior of the expandable frame. The valve body can include a plurality of leaflets each having an arcuate proximal edge and a free distal edge, the plurality of leaflets being joined at commissures. The plurality of leaflets can be configured to allow flow in a proximal-to-distal direction and prevent flow in a distal-to-proximal direction. The valve body can include one or more intermediate components connecting the leaflets to the expandable frame, wherein at least a portion of the arcuate proximal edge of each leaflet and/or the commissures are indirectly coupled to the expandable frame via the one or more intermediate components such that when the frame is in an expanded configuration, the one or more intermediate components position at least a portion of the arcuate

proximal edge of each leaflet and/or the commissures radially inward from an inner surface of the frame.

**[0007]** In some embodiments, at least a portion of the arcuate proximal edge of each leaflet can be directly coupled to the expandable frame. In some embodiments, the one or more intermediate components can be formed from a material having a stiffness greater than that of the plurality of leaflets and less than that of the expandable frame. In some embodiments, the one or more intermediate components can be formed from a sheet of material. In some embodiments, the one or more intermediate components can be formed from a sheet of at least one of fabric, polyurethane, and polyethylene terephthalate (PET).

**[0008]** In some embodiments, the one or more intermediate components can include a first intermediate component and a second intermediate component. The first intermediate component can be tensioned in a first direction and the second intermediate component can be tensioned in a second direction when the frame is in an expanded configuration. In some embodiments, the first direction can be oriented generally radially outwardly. In some embodiments, the second direction can be oriented generally axially. In some embodiments, the second direction can be oriented generally in a circumferential direction. In some embodiments, the one or more intermediate components can include a third intermediate component. The first intermediate component, the second intermediate component, and the third intermediate component can form a pocket at or proximate a commissure of the valve body.

**[0009]** In some embodiments, the one or more intermediate components can include a cylindrical conduit. In some embodiments, at least one of the one or more intermediate components can extend in a radial direction between the expandable frame and the plurality of leaflets. In some embodiments, at least one of the one or more intermediate components can extend tangentially to the plurality of leaflets. In some embodiments, at least one of the one or more intermediate components extends in a direction generally aligned with the longitudinal axis of the frame. In some embodiments, at least one of the one or more intermediate components extends in circumferential direction. In some embodiments, the prosthesis can include an annular skirt extending around the exterior of the expandable frame. In some embodiments, a

proximal end of the annular skirt is attached to a proximal region of the expandable frame and a distal end of the annular skirt is attached to a distal region of the expandable frame. In some embodiments, an intermediate region of the frame can have a diameter greater than a diameter of the proximal region and/or a diameter of the distal region.

**[0010]** In some embodiments, a prosthesis can include an expandable frame configured to radially expand and contract for deployment within a native heart valve. The expandable frame can include a proximal end and a distal end and a longitudinal axis extending therethrough. The expandable frame can include a supplemental prosthesis retention structure. The prosthesis can include a valve body positioned within an interior of the expandable frame. The valve body can include a plurality of leaflets configured to allow flow in a first direction and prevent flow in a second opposite direction.

**[0011]** In some embodiments, the supplemental prosthesis retention structure can include an interfacing structure. The interfacing structure can include a plurality of V-shaped apices extending radially inward towards the longitudinal axis. The plurality of V-shaped apices can be configured to couple with a frame of a supplemental prosthesis. In some embodiments, the supplemental prosthesis retention structure can include an interfacing structure. The interfacing structure can include a plurality of protrusions extending radially inwardly from distal portions of cells of the expandable frame. In some embodiments, the supplemental prosthesis retention structure can include an internal expandable cage which can be configured to receive a supplemental prosthesis. In some embodiments, the internal expandable cage can include a plurality of circumferentially-expandable struts.

**[0012]** In some embodiments, a prosthesis can include an expandable frame which can be configured to radially expand and contract for deployment within a native heart valve. The expandable frame can include a frame body which can include a proximal region, a distal region, an intermediate region extending between the proximal and distal regions, and a longitudinal axis extending between proximal and distal ends of the frame body. The frame body can include a plurality of struts forming one or more rows of cells. The proximal region can include a first bend adjacent the intermediate region. A proximally extending portion of the first bend can be inclined or curved



towards the longitudinal axis. The distal region can include a second bend adjacent the intermediate region. A distally extending portion of the second bend can be inclined or curved towards the longitudinal axis. The intermediate region can have a generally cylindrical shape. A diameter of the intermediate region can be greater than a diameter of the proximal region and a diameter of the distal region. A height of the intermediate region can be greater than a height of the proximal region and a height of the distal region.

**[0013]** The prosthesis can include a proximal anchoring feature attached to the frame body. The proximal anchoring feature can be sized to be positioned on a first side of an annulus of the native heart valve. The prosthesis can include a distal anchoring feature attached to the frame body. The distal anchoring feature can be sized to be positioned on a second side of an annulus of the native heart valve. The prosthesis can include a valve body positioned within an interior of the expandable frame, the valve body comprising a plurality of leaflets configured to allow flow in a first direction and prevent flow in a second opposite direction.

**[0014]** In some embodiments, when the expandable frame is in an expanded configuration, the height of the distal region can be greater than the height of the proximal region. In some embodiments, when the expandable frame is in an expanded configuration, a ratio of a largest diameter of the frame body to the height of the frame body can be between about 3:1 to about 1:1. In some embodiments, when the expandable frame is in an expanded configuration, a ratio of a largest diameter of the frame body to the height of the frame body can be between about 2:1 to about 3:2. In some embodiments, when the expandable frame is in an expanded configuration, a ratio of the height of the intermediate region to the combined heights of the proximal region and the distal region can be between about 2:1 to about 1:2. In some embodiments, when the expandable frame is in an expanded configuration, a ratio of the height of the intermediate region to the combined heights of the proximal region and the distal region can be between about 3:2 to about 1:1. In some embodiments, when the expandable frame is in an expanded configuration, a ratio of a largest diameter of the frame body to a smallest diameter of the frame body can be between about 2:1 to about 4:3.

**[0015]** In some embodiments, when the expandable frame is in an expanded configuration, the first bend can orient a portion of the proximal region, positioned proximally of the beginning of the first bend, such that the portion forms an angle of between about 30 degrees to about 60 degrees with a plane orthogonal to the longitudinal axis. In some embodiments, when the expandable frame is in an expanded configuration, the first bend can orient a portion of the proximal region, positioned proximally of the beginning of the first bend, such that the portion forms an angle of between about 40 degrees to about 50 degrees with a plane orthogonal to the longitudinal axis. In some embodiments, when the expandable frame is in an expanded configuration, the second bend can orient a portion of the distal region, positioned distally of the beginning of the second bend, such that the portion forms an angle of between about 30 degrees to about 60 degrees with a plane orthogonal to the longitudinal axis. In some embodiments, when the expandable frame is in an expanded configuration, the second bend can orient a portion of the distal region, positioned distally of the beginning of the second bend, such that the portion forms an angle of between about 40 degrees to about 50 degrees with a plane orthogonal to the longitudinal axis.

**[0016]** In some embodiments, the proximal anchoring feature can be attached to the proximal region of the frame body. In some embodiments, the proximal anchoring feature can include a plurality of anchors. In some embodiments, at least one of the anchors can include one or more eyelets. In some embodiments, at least one of the anchors can include two or more eyelets. In some embodiments, the distal anchoring feature can be attached to the distal region of the frame body. In some embodiments, the distal anchoring feature can include a plurality of distal anchors. In some embodiments, when the expandable frame is in an expanded configuration, at least one of the distal anchors can include ends extending radially outwardly away from the longitudinal axis. In some embodiments, when the expandable frame is in an expanded configuration, at least one of the distal anchors can include ends extending radially outwardly away from the longitudinal axis in a direction generally perpendicular to the longitudinal axis. In some embodiments, when the expandable frame is in an expanded configuration, all of the distal anchors can include ends extending radially outwardly away from the

longitudinal axis. In some embodiments, when the expandable frame is in an expanded configuration, at least one of the distal anchors can include ends extending radially inwardly towards the longitudinal axis. In some embodiments, when the expandable frame is in an expanded configuration, at least one of the distal anchors can include ends extending radially inwardly towards the longitudinal axis in a direction generally perpendicular to the longitudinal axis. In some embodiments, when the expandable frame is in an expanded configuration, all of the distal anchors can include ends extending radially inwardly towards the longitudinal axis.

**[0017]** In some embodiments, the expandable frame further can include a plurality of locking tabs. In some embodiments, the locking tabs can include a bend in a direction opposite the first bend.

**[0018]** In some embodiments, the valve body further can include one or more intermediate components. At least a portion of each leaflet can be indirectly coupled to the expandable frame via the one or more intermediate components such that at least a portion of each leaflet is positioned radially inward from an inner surface of the frame body. In some embodiments, commissures of the valve body can be indirectly coupled to the expandable frame via the one or more intermediate components such that the commissures are positioned radially inward from the inner surface of the frame body. In some embodiments, at least a portion of an arcuate proximal edge of each leaflet can be indirectly coupled to the frame via the one or more intermediate components such that the arcuate proximal edge is positioned radially inward from the inner surface of the frame body. In some embodiments, at least a portion of an arcuate proximal edge of each leaflet can be directly coupled to the expandable frame.

**[0019]** In some embodiments, the one or more intermediate components can be formed from a material having a stiffness greater than that of the plurality of leaflets and less than that of the expandable frame. In some embodiments, the one or more intermediate components can include a first intermediate component and a second intermediate component. The first intermediate component can be tensioned in a first direction and the second intermediate component can be tensioned in a second direction when the frame is in an expanded configuration. In some embodiments, the first direction can be oriented generally radially outward. In some embodiments, the second

direction can be oriented generally axially. In some embodiments, the second direction can be oriented generally in a circumferential direction.

**[0020]** In some embodiments, the one or more intermediate components can include a third intermediate component. The first intermediate component, the second intermediate component, and the third intermediate component can form a pocket at or proximate a commissure of the valve body. In some embodiments, the one or more intermediate components can include a cylindrical conduit. In some embodiments, at least one of the one or more intermediate components can extend in a radial direction between the expandable frame and the plurality of leaflets. In some embodiments, at least one of the one or more intermediate components can extend tangentially to the plurality of leaflets. In some embodiments, at least one of the one or more intermediate components can extend in a direction generally aligned with the longitudinal axis of the frame. In some embodiments, at least one of the one or more intermediate components can extend in circumferential direction.

**[0021]** In some embodiments, the prosthesis can include an annular skirt extending around the exterior of the expandable frame. In some embodiments, a proximal end of the annular skirt is attached to the proximal region of the frame body and a distal end of the annular skirt is attached to the distal region of the frame body.

**[0022]** In some embodiments, the prosthesis can include an expandable frame having a proximal end and a distal end and a longitudinal axis extending therethrough. The frame can be configured to radially expand and contract for deployment within a native heart valve. The prosthesis can include a valve body positioned within an interior of the expandable frame. The valve body can include a plurality of leaflets which can be configured to allow flow in a first direction and prevent flow in a second opposite direction. The prosthesis can include an annular skirt extending around the exterior of the expandable frame.

**[0023]** In some embodiments, the valve body can include one or more intermediate components. In some embodiments, at least one of the valve body and the annular skirt can include one or more openings which can be configured to allow at least one of: fluid ingress into a space between the valve leaflets and the annular skirt, and fluid egress out of the space between the valve leaflets and the annular skirt. In some

embodiments, the one or more openings can be configured to allow fluid ingress into the space between the valve leaflets and the annular skirt when fluid flow is in the first direction. In some embodiments, the one or more openings can be configured to allow fluid egress out of the space between the valve leaflets and the annular skirt when fluid flow is in the second direction. In some embodiments, at least one of the one or more openings can be positioned within an area of the annular skirt between a first edge of a valve leaflet and the annular skirt.

**[0024]** In some embodiments, the prosthesis can include one or more conduits extending into the one or more openings. In some embodiments, the expandable frame can include an anchoring member sized and shaped to be positioned on an inflow side of a native valve annulus. In some embodiments, the one or more conduits can be configured to extend proximal of the anchoring member. In some embodiments, the anchoring member can be positioned along a proximal portion of the expandable frame.

**[0025]** In some embodiments, the inflow side of the native valve annulus is an atrial side of the native mitral valve annulus.

**[0026]** In some embodiments, when the annular skirt is in an expanded configuration, the annular skirt comprises a supplemental rib extending from a portion of the annular skirt. In some embodiments, when the annular skirt is in an expanded configuration, a proximal portion of the annular skirt bulges radially outward relative to the distal portion of the annular skirt. In some embodiments, when the annular skirt is in an expanded configuration, a distal portion of the annular skirt bulges radially outward relative to the proximal portion of the annular skirt. In some embodiments, when the annular skirt is in an expanded configuration, the annular skirt extends around the entire circumferential periphery of the frame to a generally equivalent radial dimension. In some embodiments, the annular skirt extends to different radial dimensions with a first peripheral region extending to a first radial dimension and a second peripheral region extending to a second radial dimension greater than the first radial dimension.

**[0027]** In some embodiments, the prosthesis can include one or more biasing members which can be configured to bias the skirt into an expanded configuration. In

some embodiments, the one or more biasing members can include a radial spring. In some embodiments, the one or more biasing members can include a cantilever.

**[0028]** In some embodiments, the annular skirt can be configured to transition into an expanded configuration via blood flow into the annular skirt. In some embodiments, the prosthesis can include a one-way valve configured to allow blood flow into the annular skirt and inhibit blood flow out of the annular skirt. In some embodiments, the one-way valve can be positioned on a valve skirt, the valve skirt being positioned between the plurality of leaflets and the annular skirt. In some embodiments, the one-way valve can include a flap positioned on an exterior of the valve skirt. In some embodiments, the one-way valve can include a duckbill valve. In some embodiments, the one-way valve can be configured to allow blood flow into the annular skirt during systole and inhibit blood flow out of the annular skirt during diastole.

**[0029]** In some embodiments, the prosthesis can be a replacement mitral valve prosthesis, the expandable frame being configured for deployment within a native mitral valve.

**[0030]** In some embodiments, the prosthesis can include six distal anchors. In some embodiments, the prosthesis can include twelve distal anchors.

**[0031]** In some embodiments, the prosthesis can include an expandable frame which can be configured to radially expand and contract for deployment within a native heart valve. The expandable frame can include a frame body having a proximal region, a distal region, and an intermediate region extending between the proximal and distal regions. The frame body can include a first row of struts and a second row of struts. The expandable frame can include a supplemental frame having a first row of struts. The first row of struts can be configured to be generally aligned along the first row of struts of the frame body. The first row of struts of the supplemental frame can have a size and/or shape which generally matches the size and/or shape of the first row of struts of the frame body.

**[0032]** The expandable frame can include a distal anchoring feature. The distal anchoring feature can be sized to be positioned on a first side of an annulus of the native heart valve. For example, the distal anchoring feature can be positioned on a ventricular side of a native mitral valve annulus. The expandable frame can include a

valve body positioned within an interior of the expandable frame. The valve body can include a plurality of leaflets which can be configured to allow flow in a first direction and prevent flow in a second opposite direction.

**[0033]** In some embodiments, the supplemental frame can be formed separately from the frame body. In some embodiments, the first row of struts of the supplemental frame can be configured to be attached to at least a portion of the first row of struts of the frame body. In some embodiments, the first row of struts of the supplemental frame can be attached to the first row of struts of the frame body via sutures. In some embodiments, the first row of struts of the supplemental frame and the first row of struts of the frame body can have an undulating shape.

**[0034]** In some embodiments, the first row of struts of the supplemental frame can be configured to be positioned radially inwardly of the first row of struts of the frame body. In some embodiments, the first row of struts of the supplemental frame can be configured to be positioned radially outwardly of the first row of struts of the frame body. In some embodiments, the distal anchoring feature can extend from the frame body. In some embodiments, the distal anchoring feature can extend distally from the frame body. In some embodiments, the distal anchoring feature can extend from the supplemental frame.

**[0035]** In some embodiments, the supplemental frame can include a second row of struts. The first and second rows of struts of the supplemental frame can form cells. In some embodiments, the second row of struts of the supplemental frame can have an undulating shape. In some embodiments, the second row of struts of the supplemental frame can be configured to extend distally of the frame body.

**[0036]** In some embodiments, the expandable frame can include a proximal anchoring feature. The proximal anchoring feature can be sized to be positioned on a second side of the annulus of the native heart valve. For example, the proximal anchoring feature can be positioned on an atrial side of a native mitral valve annulus. In some embodiments, the proximal anchoring feature can include a first row of struts. The first row of struts can be configured to be generally aligned along the second row of struts of the frame body. The first row of struts of the proximal anchoring feature can have a size and/or shape which generally matches the size and/or shape of the second

row of struts of the frame body. In some embodiments, the proximal anchoring feature can be formed separately from the frame body. In some embodiments, the first row of struts of the proximal anchoring feature can be configured to be attached to at least a portion of the second row of struts of the frame body. In some embodiments, the first row of struts of the proximal anchoring feature can be attached to the second row of struts of the frame body via sutures. In some embodiments, the first row of struts of the proximal anchoring feature and the second row struts of cells of the frame body can have an undulating shape.

**[0037]** In some embodiments, the first row of struts of the proximal anchoring feature can be configured to be positioned radially outwardly of the second row of struts of the frame body. In some embodiments, the first row of struts of the proximal anchoring feature can be configured to be positioned radially inwardly of the second row of struts of the frame body. In some embodiments, the proximal anchoring feature can include a second row of struts. The first and second rows of struts of the proximal anchoring feature can form cells. In some embodiments, the second row of struts of the proximal anchoring feature can have an undulating shape. In some embodiments, the second row of struts of the proximal anchoring feature can be configured to be generally aligned along a third row of struts of the frame body. The second row of struts of the proximal anchoring feature can have a size and/or shape which generally matches the size and/or shape of the third row of struts of the frame body.

**[0038]** In some embodiments, the prosthesis can include a plurality of locking tabs. In some embodiments, at least some of the locking tabs can extend from the frame body. In some embodiments, at least some of the locking tabs can extend from the frame body. In some embodiments, at least some of the locking tabs can extend from the frame body and at least some of the locking tabs can extend from the proximal anchoring feature. The locking tabs of the proximal anchoring feature can be configured to be generally aligned along the locking tabs of the frame body. The locking tabs of the proximal anchoring feature can have a size and/or shape which generally matches the size and/or shape of the locking tabs of the frame body.



**[0039]** In some embodiments, the distal anchoring feature can include a plurality of distal anchors, at least one of the distal anchors can include two or more prongs. In some embodiments, the two or more prongs can be movable in a lateral direction relative to each other. In some embodiments, a lateral dimension of the distal anchor having two or more prongs can increase when the expandable frame transitions to an expanded configuration. In some embodiments, the two or more prongs can be movable in a radial direction relative to each other. In some embodiments, a radial offset of the two or more prongs can increase when the expandable frame transitions to an expanded configuration.

**[0040]** In some embodiments, the distal anchoring feature includes one or more anchors configured to be movable in an axial direction relative to the frame body. In some embodiments, the distal anchoring feature includes one or more anchors having an insert. In some embodiments, the insert can be configured to extend radially outwardly relative to the frame body when the expandable frame is in an expanded configuration. In some embodiments, the insert can include a platform. The platform can be configured to extend radially and/or laterally outwardly relative to the distal anchor when the expandable frame is in an expanded configuration.

**[0041]** In some embodiments, at least one of the distal anchors can include a strut which bifurcates into two or more struts proximate a base of the distal anchor.

**[0042]** In some embodiments, the plurality of leaflets can each have an arcuate proximal edge and a free distal edge. The plurality of leaflets can be joined at commissures. The plurality of leaflets can be configured to allow flow in a proximal-to-distal direction and prevent flow in a distal-to-proximal direction.

**[0043]** In some embodiments, the valve body can include one or more intermediate components connecting the leaflets to the expandable frame. The one or more intermediate components can connect the leaflets to the expandable frame. At least a portion of the arcuate proximal edge of each leaflet and/or the commissures can be indirectly coupled to the expandable frame via the one or more intermediate components such that when the frame is in an expanded configuration, the one or more intermediate components position at least a portion of the arcuate proximal edge of each leaflet and/or the commissures radially inward from an inner surface of the expandable frame

**[0044]** In some embodiments, the one or more intermediate components can form a generally tangent surface with the expandable frame when the valve body is closed to prevent flow in the second direction. In some embodiments, the one or more intermediate components can form an angle between about 120° to about 195° with the expandable frame when the valve body is closed to prevent flow in the second direction. In some embodiments, the one or more intermediate components can form an angle between about 140° to about 190° with the expandable frame when the valve body is closed to prevent flow in the second direction. In some embodiments, the one or more intermediate components form an angle between about 160° to about 185° with the expandable frame when the valve body is closed to prevent flow in the second direction. In some embodiments, the one or more intermediate components can form an angle of about 180° with the expandable frame when the valve body is closed to prevent flow in the second direction.

**[0045]** In some embodiments, the prosthesis can include an annular skirt. The annular skirt can be at least partially formed from a material which can allow blood to flow therethrough. In some embodiments, the material can be a partially porous cloth. In some embodiments, the material can include one or more holes formed therethrough. In some embodiments, the material can be configured such that, after deployment at the native heart valve, a rate of blood flow through the material decreases. In some embodiments, the skirt can include a hydrogel which can reduce the rate of blood flow through the material.

#### BRIEF DESCRIPTION OF THE DRAWINGS

**[0046]** These and other features, aspects and advantages are described below with reference to the drawings, which are intended to illustrate embodiments of prostheses including embodiments of various components of these prostheses.

**[0047]** FIGURE 1 is a side-oriented cross-sectional schematic view of an embodiment of a frame, a plurality of anchors, an annular skirt, and a floating valve.

**[0048]** FIGURE 2 is a top-oriented perspective view of another embodiment of a frame, a plurality of anchors, an annular skirt, and a valve body.

**[0049]** FIGURE 3 is a side view of the prosthesis of FIGURE 2.

[0050] FIGURE 4 is a bottom-oriented perspective view of the prosthesis of FIGURE 2.

[0051] FIGURE 5A is a side view of the front-half of an embodiment of a frame.

[0052] FIGURE 5B is a side view of the front-half of another embodiment of a frame.

[0053] FIGURE 6 is a side view of another embodiment of a frame.

[0054] FIGURE 7 is a flat, cutting pattern for the frame of FIGURE 6.

[0055] FIGURE 8 is a flat, cutting pattern for another embodiment of a frame.

[0056] FIGURE 9 is a side view of another embodiment of a frame.

[0057] FIGURE 10 is a side-oriented schematic view of an embodiment of a ventricular anchor.

[0058] FIGURE 11 is a top-oriented schematic view of the ventricular anchor of FIGURE 10.

[0059] FIGURE 12 is a side-oriented schematic view of another embodiment of a ventricular anchor.

[0060] FIGURE 13 is a top-oriented schematic view of the ventricular anchor of FIGURE 12.

[0061] FIGURE 14 is a side-oriented schematic view of an embodiment of a floating valve.

[0062] FIGURE 15 is a cross-sectional schematic view of another embodiment of a floating valve.

[0063] FIGURE 16 is a perspective schematic view of an embodiment of a portion of a frame.

[0064] FIGURE 17 is a cross-sectional schematic view of the frame of FIGURE 16 with a floating valve attached.

[0065] FIGURE 18 is a top-oriented perspective view of an embodiment of a frame and floating valve.

[0066] FIGURE 19A is a flat, cutting pattern for various components of another embodiment of a floating valve.

[0067] FIGURE 19B is a bottom-oriented perspective view of an embodiment of a frame with the floating valve of FIGURE 19A.

[0068] FIGURE 19C is a cross-sectional schematic of the floating valve of FIGURE 19A.

[0069] FIGURE 20 is a side-oriented cross-sectional schematic view of another embodiment of a frame and floating valve.

[0070] FIGURE 21 is a top-oriented cross-sectional schematic view of the frame and floating valve of FIGURE 20.

[0071] FIGURE 22 is a side-oriented cross-sectional schematic view of another embodiment of a frame and floating valve.

[0072] FIGURE 23 is a top-oriented cross-sectional schematic view of the frame and floating valve of FIGURE 22.

[0073] FIGURE 24 is a side-oriented cross-sectional schematic view of another embodiment of a frame and floating valve.

[0074] FIGURE 25 is a side-oriented cross-sectional schematic view of another embodiment of a frame and floating valve.

[0075] FIGURE 26 is a top-oriented cross-sectional schematic view of another embodiment of a frame and floating valve.

[0076] FIGURE 27 is a top-oriented cross-sectional schematic view of another embodiment of a frame and floating valve.

[0077] FIGURE 28 is a top-oriented cross-sectional schematic view of another embodiment of a frame and floating valve.

[0078] FIGURE 29 is a top-oriented cross-sectional schematic view of another embodiment of a frame and floating valve.

[0079] FIGURE 30 is a side-oriented cross-sectional schematic view of another embodiment of a frame and floating valve.

[0080] FIGURE 31 is a schematic view of an embodiment of a portion of a frame.

[0081] FIGURE 32 is a side-oriented cross-sectional schematic view of another embodiment of a frame and floating valve.

**[0082]** FIGURE 33 is a side-oriented schematic view of an embodiment of a frame in which a supplemental prosthesis has been attached.

**[0083]** FIGURE 34 is a side-oriented schematic view of another embodiment of a frame.

**[0084]** FIGURE 35 is a side-oriented schematic view of another embodiment of a frame.

**[0085]** FIGURE 36 is a side-oriented schematic view of another embodiment of a frame.

**[0086]** FIGURE 37 is a side-oriented schematic view of another embodiment of a frame.

**[0087]** FIGURE 38 is a cross-sectional schematic view of an embodiment of a frame, a plurality of anchors, an annular skirt, and a floating valve.

**[0088]** FIGURE 39 is a cross-sectional schematic view of another embodiment of a frame, a plurality of anchors, an annular skirt, and a floating valve.

**[0089]** FIGURE 40 is a cross-sectional schematic view of another embodiment of a frame, a plurality of anchors, an annular skirt, and a floating valve.

**[0090]** FIGURE 41A-43 illustrate schematic representations of the prosthesis of Figure 3 positioned within a heart, with FIGURES 41A-41C illustrating the prosthesis in situ with distal anchors contacting the ventricular side of a mitral valve annulus, FIGURES 42A-42B illustrating the prosthesis in situ with distal anchors not contacting the ventricular side of the mitral valve annulus, and FIGURE 43 illustrating the prosthesis in situ with distal anchors not extending between the chordae tendineae.

**[0091]** FIGURE 44 is an atrial-oriented, view of an embodiment of a frame, a plurality of anchors, an annular skirt, and a floating valve implanted within a native mitral valve.

**[0092]** FIGURE 45 is a ventricular-oriented, view of the frame, a plurality of anchors, an annular skirt, and a floating valve of FIGURE 44 implanted within a native mitral valve.

**[0093]** FIGURE 46 is a cross-sectional view of a distal end of an embodiment of a delivery system loaded with an embodiment of a prosthesis.

**[0094]** FIGURE 47 is a cross-sectional view of a distal end of another embodiment of a delivery system loaded with another embodiment of a prosthesis.

**[0095]** FIGURES 48 and 49 illustrate schematic representations of an embodiment of a prosthesis positioned within a heart.

**[0096]** FIGURE 50 illustrates a schematic representation of the valve body of the prosthesis of FIGURES 48 and 49.

**[0097]** FIGURES 51-53 illustrate schematics of embodiments of shapes of openings in skirts.

**[0098]** FIGURES 54 and 55 illustrate schematic representations of another embodiment of a prosthesis positioned within a heart.

**[0099]** FIGURE 56 illustrates a front view of an embodiment of a prosthesis, the prosthesis having a skirt with an opening.

**[0100]** FIGURE 57 illustrates a side view of the prosthesis of FIGURE 56.

**[0101]** FIGURE 58 illustrates a side-oriented cross-sectional schematic view of an embodiment of a frame and skirt.

**[0102]** FIGURE 59 illustrates a perspective-oriented, exploded schematic of the annular skirt of FIGURE 58.

**[0103]** FIGURE 60 illustrates a side-oriented cross-sectional schematic view of the frame and skirt of FIGURE 58 in a first configuration.

**[0104]** FIGURE 61 illustrates a side-oriented cross-sectional schematic view of the frame and skirt of FIGURE 58 in a second configuration.

**[0105]** FIGURE 62 illustrates a side-oriented cross-sectional schematic view of another embodiment of a frame and skirt.

**[0106]** FIGURE 63 illustrates a perspective-oriented, exploded schematic of the annular skirt of FIGURE 62.

**[0107]** FIGURE 64 illustrates a side-oriented cross-sectional schematic view of the frame and skirt of FIGURE 62 in a first configuration.

**[0108]** FIGURE 65 illustrates a side-oriented cross-sectional schematic view of the frame and skirt of FIGURE 62 in a second configuration.

**[0109]** FIGURE 66 illustrates a side-oriented cross-sectional schematic view of another embodiment of a frame and skirt.

**[0110]** FIGURE 67 illustrates a side-oriented cross-sectional schematic view of another embodiment of a frame and skirt.

**[0111]** FIGURE 68 illustrates a side-oriented cross-sectional schematic view of another embodiment of a frame and skirt.

**[0112]** FIGURE 69 illustrates a side-oriented cross-sectional schematic view of another embodiment of a frame and skirt.

**[0113]** FIGURE 70 illustrates a perspective view of an embodiment of a frame, a plurality of anchors, and a skirt.

**[0114]** FIGURE 71 illustrates a top-oriented cross-sectional schematic view of another embodiment of a frame and skirt.

**[0115]** FIGURE 72 illustrates a top-oriented cross-sectional schematic view of another embodiment of a frame and skirt.

**[0116]** FIGURE 73 illustrates a top-oriented cross-sectional schematic view of another embodiment of a frame and skirt.

**[0117]** FIGURE 74 illustrates a side-oriented cross-sectional schematic view of another embodiment of a frame, skirt, and a valve body.

**[0118]** FIGURE 75 illustrates a perspective-oriented schematic view of another embodiment of a skirt having one-way valves.

**[0119]** FIGURE 76 illustrates a perspective-oriented schematic view of the skirt of FIGURE 75 with a one-way valve in an open configuration.

**[0120]** FIGURE 77 illustrates a perspective-oriented schematic view of the skirt of FIGURE 75 with a one-way valve in a closed configuration.

**[0121]** FIGURE 78 illustrates a side-oriented cross-sectional schematic view of an embodiment of a frame, a skirt, and a biasing member.

**[0122]** FIGURE 79 illustrates a top-oriented cross-sectional schematic view of the frame, skirt, and biasing member of FIGURE 78.

**[0123]** FIGURE 80 illustrates a side-oriented cross-sectional schematic view of another embodiment of a frame, a skirt, and a biasing member.

**[0124]** FIGURE 81 illustrates a side-oriented cross-sectional schematic view of another embodiment of a frame, a skirt, and a biasing member.

**[0125]** FIGURE 82 illustrates a top-oriented cross-sectional schematic view of the frame, skirt, and biasing member of FIGURE 80.

**[0126]** FIGURE 83 illustrates a front view of an embodiment of an anchoring feature.

**[0127]** FIGURE 84 illustrates a side view of the anchoring feature of FIGURE 83.

**[0128]** FIGURE 85 illustrates a side view of another embodiment of an anchoring feature.

**[0129]** FIGURE 86 illustrates a top view of an embodiment of an anchoring feature, the anchoring feature being in a first configuration.

**[0130]** FIGURE 87 illustrates a front view of the anchoring feature of FIGURE 86, the anchoring feature being in a first configuration.

**[0131]** FIGURE 88 illustrates a top view of the anchoring feature of FIGURE 86, the anchoring feature being in a second configuration.

**[0132]** FIGURE 89 illustrates a front view of the anchoring feature of FIGURE 86, the anchoring feature being in a second configuration.

**[0133]** FIGURE 90 illustrates a side view of the anchoring feature of FIGURE 86, the anchoring feature being in a second configuration.

**[0134]** FIGURE 91 illustrates a front view of another embodiment of an anchoring feature, the anchoring feature being in a first configuration.

**[0135]** FIGURE 92 illustrates a front view of the anchoring feature of FIGURE 91, the anchoring feature being in a second configuration.

**[0136]** FIGURE 93 illustrates a front view of another embodiment of an anchoring feature, the anchoring feature being in a first configuration.

**[0137]** FIGURE 94 illustrates a front view of the anchoring feature of FIGURE 93, the anchoring feature being in a second configuration.

**[0138]** FIGURE 95 illustrates a top view of another embodiment of an anchoring feature, the anchoring feature being in a first configuration.

**[0139]** FIGURE 96 illustrates a front view of the anchoring feature of FIGURE 95, the anchoring feature being in a first configuration.



**[0140]** FIGURE 97 illustrates a top view of the anchoring feature of FIGURE 95, the anchoring feature being in a second configuration.

**[0141]** FIGURE 98 illustrates a front view of the anchoring feature of FIGURE 95, the anchoring feature being in a second configuration.

**[0142]** FIGURE 99 illustrates a side view of the anchoring feature of FIGURE 95, the anchoring feature being in a second configuration.

**[0143]** FIGURE 100 illustrates a perspective view of an embodiment of a combined anchoring feature having a base anchor and an insert.

**[0144]** FIGURE 101 illustrates a top view of the combined anchoring feature of FIGURE 100.

**[0145]** FIGURE 102 illustrates a front view of the combined anchoring feature of FIGURE 100.

**[0146]** FIGURE 103 illustrates a side view of the combined anchoring feature of FIGURE 100.

**[0147]** FIGURE 104 illustrates a top view of the insert of the combined anchoring feature of FIGURE 100.

**[0148]** FIGURE 105 illustrates a front view of the insert of the combined anchoring feature of FIGURE 100.

**[0149]** FIGURE 106 illustrates a side view of the insert of the combined anchoring feature of FIGURE 100.

**[0150]** FIGURE 107 illustrates a cross-sectional schematic of a delivery system having anchoring features positioned therein.

**[0151]** FIGURE 108 illustrates a flat pattern of an embodiment of a frame.

**[0152]** FIGURE 109A illustrates a flat pattern of another embodiment of a frame.

**[0153]** FIGURE 109B illustrates a schematic of a native mitral valve.

**[0154]** FIGURE 110 illustrates a perspective view of an embodiment of a frame having an adjustable anchoring feature.

**[0155]** FIGURE 111 illustrates a perspective view of a portion of the frame of FIGURE 110.

**[0156]** FIGURE 112 illustrates a side-oriented cross-sectional schematic view of an embodiment of a frame.

**[0157]** FIGURE 113 illustrates a front-oriented schematic view of the frame of FIGURE 112.

**[0158]** FIGURE 114 illustrates a top-oriented schematic view of the frame of FIGURE 112.

**[0159]** FIGURE 115 illustrates a side-oriented cross-sectional schematic view of another embodiment of a frame.

**[0160]** FIGURE 116 illustrates a front-oriented schematic view of the frame of FIGURE 115.

**[0161]** FIGURE 117 illustrates a top-oriented schematic view of the frame of FIGURE 115.

**[0162]** FIGURE 118 is a side-oriented cross-sectional schematic view of an embodiment of a frame, a plurality of anchors, an annular skirt, and a floating valve, the components being a first configuration.

**[0163]** FIGURE 119 is a side-oriented cross-sectional schematic view of the components of FIGURE 118, the components being in a second configuration.

**[0164]** FIGURE 120 is a top-oriented perspective view of another embodiment of a frame, a plurality of anchors, an annular skirt, and a valve body.

**[0165]** FIGURE 121 is a bottom-oriented perspective view of the components of FIGURE 120.

**[0166]** FIGURE 122 is a side view of a front-half of another embodiment of a frame and a plurality of anchors.

**[0167]** FIGURE 123 is a close-up view of the components of FIGURE 122.

**[0168]** FIGURE 124 is a flat pattern of an embodiment of a frame having multiple frame components.

**[0169]** FIGURE 125 is a flat, cutting pattern for the frame components of FIGURE 124.

**[0170]** FIGURE 126 is a flat pattern of another embodiment of a frame having multiple frame components.

[0171] FIGURE 127 is a flat, cutting pattern for the frame components of FIGURE 126.

[0172] FIGURE 128 is a flat pattern of another embodiment of a frame having multiple frame components.

[0173] FIGURE 129 is a flat, cutting pattern for the frame components of FIGURE 128.

[0174] FIGURE 130 is a side view of a front-half of another embodiment of a frame having multiple frame components.

[0175] FIGURE 131 is a top-oriented perspective view of the frame components of FIGURE 130.

#### DETAILED DESCRIPTION

[0176] The present specification and drawings provide aspects and features of the disclosure in the context of several embodiments of prostheses, replacement heart valves, and methods that are configured for use in the vasculature of a patient, such as for replacement of natural heart valves in a patient. These embodiments may be discussed in connection with replacing specific valves such as the patient's mitral valve. However, it is to be understood that the features and concepts discussed herein can be applied to replacing other types of valves including, but not limited to, the aortic valve, the pulmonary valve, and the tricuspid valve. Moreover, it is to be understood that the features and concepts discussed herein can be applied to products other than heart valve implants. For example, the controlled positioning, deployment, and/or securing features described herein can be applied to medical implants, for example other types of expandable prostheses, for use elsewhere in the body, such as within a vein, or the like. In addition, particular features of a prosthesis should not be taken as limiting, and features of any one embodiment discussed herein can be combined with features of other embodiments as desired and when appropriate.

[0177] Certain terminology may be used in the following description for the purpose of reference only, and thus are not intended to be limiting. For example, terms such as "upper", "lower", "upward", "downward", "above", "below", "top", "bottom" and similar terms refer to directions in the drawings to which reference is made. Terms

such as “proximal”, “distal”, “radially outward”, “radially inward,” and “side” describe the orientation and/or location of portions of the components or elements within a consistent but arbitrary frame of reference which is made clear by reference to the text and the associated drawings describing the components or elements under discussion. Such terminology may include the words specifically mentioned above, derivatives thereof, and words of similar import. Similarly, the terms “first”, “second”, and other such numerical terms referring to structures neither imply a sequence or order unless clearly indicated by the context.

[0178] In some embodiments, the term “proximal” may refer to the parts of the prostheses, or components thereof, which are located closer to the operator of the device and system (e.g., the clinician implanting the prosthesis). The term “distal” may refer to the parts of the prostheses, or components thereof, which are located further from the operator of the device and system (e.g., the clinician implanting the prosthesis). However, it is to be understood that this terminology may be reversed depending on the delivery technique utilized (e.g., a transapical approach as compared to a transseptal approach).

#### Overview of Replacement Valves

[0179] With reference to **Figures 1-4**, embodiments of prostheses **100**, **200** are illustrated. The illustrated prostheses **100**, **200** may include components which are self-expanding or balloon expandable. The prostheses **100**, **200**, as well as other prostheses described herein, may be replacement valves that can be designed to replace a damaged or diseased native heart valve such as a mitral valve, as discussed above. It should be understood that the prostheses **100**, **200**, as well as other prostheses described herein, are not limited to being a replacement valve.

[0180] With reference first to the prosthesis **100** illustrated in **Figure 1**, the prosthesis **100** includes a frame **120**, a valve body **140**, and a skirt **160**. The frame **120** can be self-expanding or balloon expandable. The frame **120** provides a structure to which various components of the prosthesis **100** can be attached. As shown in the illustrated embodiment, the frame **120** includes a frame body **122**, a first anchoring feature **124**, and a second anchoring feature **126**. As shown in the illustrated

embodiment, the frame body **122** includes an upper region **127**, an intermediate region **128**, and a lower region **129**. The intermediate region **128** can have a larger diameter than the upper region **127** and/or the lower region **129**. In some embodiments, the frame **120** is oriented such that the upper region **127** is a proximal portion and the lower region **129** is a distal portion. The frame **120** can be formed from many different materials, including metals, such as Nitinol. The frame **120** is preferably formed from a plurality of struts forming open cells. As will be discussed in further detail below, components of the frame **120**, such as the frame body **122**, the first anchoring feature **124**, and/or the second anchoring feature **126**, can be used to attach or secure the prosthesis **100** to a native valve. For example, the frame body **122** and the second anchoring feature **126** can be used to attach or secure the prosthesis **100** to a native valve, such as a native mitral valve. In some embodiments, the frame **120** is sized to allow a supplemental prosthesis to be positioned within the frame **120**. The frame **120** can include structural elements to secure the supplemental prosthesis to the frame **120**. In some situations, this can allow for the use of a prosthesis designed for a different body cavity, such as a replacement aortic valve, to be positioned within the frame **120** when the frame **120** is positioned in another body cavity, such as a native mitral valve. However, it is to be understood that a prosthesis designed for the same body cavity can also be used. For example, in some situations, a supplemental prosthesis intended for the mitral valve can be used with the frame **120** when the frame **120** is positioned within the native mitral valve.

**[0181]** It is to be understood that the frame **120** can incorporate features and concepts which are the same as, or at least similar to, those of other frames described herein such as, but not limited to, frames **220, 300, 400, 500, 600, 700, 750, 810, 910, 1010, 1210, 1310, 1410, 1510, 1610, 1710, 1810, 1910, 2010, 2110, 2210, 2300, 2400, 2500, 2600, 2710, 2810, 2910, 3002, 3420, 3520, 3620, 3820, 3920, 4020, 4120, 4220, 4320, 4420, 4520, 4620, 4720, 4820, 4920, 5020, 5120, 5220, 6000, 6100, 6200, 6300, 6400, 6520, 6620, 6700, 6800, 6900, 7000, 7100** discussed below in connection with **Figures 2-18, 20-43, 48-53, 58, 60-62, 64-80, 108-131**. The frame **120**, and any other frame described herein, may include features and concepts similar to those disclosed in U.S. Patent Nos. 8,403,983, 8,414,644, and 8,652,203 and U.S. Publication Nos. 2010/0298931, 2011/0313515, 2014/0277390, 2014/0277427, 2014/0277422, and

2015/0328000. This is inclusive of the entire disclosure and is not in any way limited to the disclosure of the associated frames. Moreover, although the frame **120** has been described as including a frame body **122**, a first anchoring feature **124**, and a second anchoring feature **126**, it is to be understood that the frame **120** need not include all components. For example, in some embodiments, the frame **120** can include the frame body **122** and the second anchoring feature **126** while omitting the first anchoring feature **124**. Moreover, although the frame body **122**, the first anchoring feature **124**, and the second anchoring feature **126** have been illustrated as being unitarily or monolithically formed, it is to be understood that in some embodiments one or more of the frame body **122**, the first anchoring feature **124**, and the second anchoring feature **126** can be formed separately. In such embodiments, the separate components can be attached using any of the fasteners and techniques described herein, such as via sutures as shown, for example, in **Figures 120-123**. For example, the first anchoring feature **124** and/or the second anchoring feature **126** can be formed separately from the frame body **122**. The first anchoring feature **124** and/or the second anchoring feature **126** can be attached to the frame body **122** via sutures.

[0182] With continued reference to the prosthesis **100** illustrated in **Figure 1**, the valve body **140** is attached to the frame **120** within an interior of the frame **120**. The valve body **140** functions as a one-way valve to allow blood flow in a first direction through the valve body **140** and inhibit blood flow in a second direction through the valve body **140**. For example, in embodiments where the upper region **127** is a proximal portion and the lower region **129** is a distal portion, the valve body **140** can allow blood flow in a proximal-to-distal direction and inhibit blood flow in a distal-to-proximal direction. The valve body **140** preferably includes a plurality of valve leaflets **142**, for example three leaflets **142**, which are joined at commissures. As will be discussed in further detail below in connection with additional figures, the valve body **140** can include one or more intermediate components **144**. The intermediate components **144** can be positioned between a portion of, or the entirety of, the leaflets **142** and the frame **120** such that at least a portion of the leaflets **142** are coupled to the frame **120** via the intermediate component **144**. In this manner, a portion of, or the entirety of, the portion of the valve leaflets **142** at the commissures and/or an arcuate edge of the valve leaflets

**142** are not directly coupled or attached to the frame **120** and are indirectly coupled or “float” within the frame **120**. For example, a portion of, or the entirety of, the portion of the valve leaflets **142** proximate the commissures and/or the arcuate edge of the valve leaflets **142** can be spaced radially inward from an inner surface of the frame **120**. This can beneficially allow valve leaflets **142** having various shapes and sizes to be incorporated into a frame **120** having a shape and size which does not correspond to the shape and size of the valve leaflets **142**. For example, the valve leaflets **142** can be sized and shaped to form a generally cylindrical shape having a diameter. By using one or more intermediate components **144**, the valve leaflets **142** can be attached to non-cylindrical frames **120** and/or frames **120** having a diameter larger than that of the diameter of the valve leaflets **142**. Use of one or more intermediate components **144** can also beneficially reduce stress concentrations on valve leaflets **142**. This can advantageously increase the effective lifespan of the valve leaflets **142**. For example, the one or more intermediate components **144** can be formed from a material having a stiffness greater than that of the valve leaflet **142** yet less than that of the frame **120**.

[0183] It is to be understood that the valve body **140** can incorporate features and concepts similar to, or the same as, those of other valve bodies described herein such as, but not limited to, valve bodies **240, 820, 920, 1020, 1110, 1220, 1320, 1420, 1520, 1620, 1720, 1820, 1920, 2020, 2120, 2220, 2720, 2820, 2920, 3440, 3540, 3640, 4830, 6540, 6640**, discussed below in connection with **Figures 2-4, 14-33, 38-40, 48-53, 57, 74, 118, 120, and 121**. Moreover, although the valve body **140** has been described as including a plurality of leaflets **142** and one or more intermediate components **144**, it is to be understood that the valve body **140** need not include all features. For example, the valve body **140** can include the plurality of valve leaflets **142** while omitting the intermediate components **144**. In some embodiments, the valve leaflets **142** can be directly attached to the frame **120**.

[0184] With continued reference the prosthesis **100** illustrated in **Figure 1**, the skirt **160** can be attached to the frame **120**. The skirt **160** can be positioned around and secured to an exterior of the frame **120**. The skirt **160** can be annular and can extend entirely circumferentially around the frame **120**. The skirt **160** can prevent or inhibit backflow of fluids, such as blood, around the prosthesis **100**. For example, with the skirt

**160** positioned annularly around an exterior of the frame **120**, the skirt **160** can create an axial barrier to fluid flow exterior to the frame **120** when deployed within a body cavity such as a native valve annulus. The skirt **160** can encourage tissue in-growth between the skirt **160** and the natural tissue of the body cavity. This may further help to prevent leakage of blood flow around the prosthesis **100** and can provide further securement of the prosthesis **100** to the body cavity. In some embodiments, the skirt **160** can be loosely attached to the exterior of the frame **120**. In some embodiments, the skirt **160** can be tautly secured around the frame **120**.

[0185] It is to be understood that the skirt **160** can incorporate features and concepts similar to, or the same as, those of other skirts described herein such as, but not limited to, skirts **260**, **2730**, **2830**, **2930**, **3030**, **3460**, **3560**, **3660**, **3860**, **3960**, **4060**, **4160**, **4260**, **4360**, **4460**, **4560**, **4660**, **4760**, **4860**, **4960**, **5060**, **5160**, **6560**, **6660** discussed below in connection with **Figures 2-4**, **38-43**, **48-53**, **58-79**, **118**, **120**, and **121**. Although the prosthesis **100** has been described as including a frame **120**, a valve body **140**, and a skirt **160**, it is to be understood that the prosthesis **100** need not include all components. For example, in some embodiments, the prosthesis **100** can include only the frame **120** and the valve body **140** while omitting the skirt **160**.

[0186] With reference next to the prosthesis **200** illustrated in **Figures 2-4**, the prosthesis **200** can include a frame **220**, a valve body **240**, and a skirt **260**. The frame **220** can be self-expanding or balloon expandable. As shown in the illustrated embodiment, the frame **220** can include a frame body **222** formed from a plurality of struts defining a plurality of cells **224** (as shown in **Figure 4**). One or more of the cells **224** can allow the frame **220** to longitudinally foreshorten when the frame **220** radially expands.

[0187] The frame **220** includes a first anchoring feature **226** and a second anchoring feature **228**. As shown, the first anchoring feature **226** can be formed from a plurality of individual anchors extending from the frame body **222** in a direction radially outward from a longitudinal axis of the frame **220** and/or in a direction generally toward a lower end of the frame **220**. The individual anchors of the first anchoring feature **226** can include tips or ends **230** having one or more eyelets. The eyelets can be used to facilitate attachment of a skirt, cover, and/or cushion to the first anchoring feature **226**.



As shown in the illustrated embodiment, the first anchoring feature **226** can include twelve individual anchors; however, it is to be understood that a greater number or lesser number of individual anchors can be used. For example, the number of individual anchors can be chosen as a multiple of the number of commissures for the valve body **240**. As such, for a prosthesis **200** with a valve body **240** having three commissures, the first anchoring feature **226** can have three individual anchors, six individual anchors, nine individual anchors, twelve individual anchors, fifteen individual anchors, or any other multiple of three. It is to be understood that the number of individual anchors need not correspond to the number of commissures of the valve body **240**.

**[0188]** As shown, the second anchoring feature **228** can be formed from a plurality of individual anchors extending from the frame body **222** in a direction radially toward the longitudinal axis of the frame **220** and bent to extend in a direction radially outward from the longitudinal axis of the frame **220**. A portion of the individual anchors, such as tips or ends **230**, can extend in a direction generally toward an upper end of the frame **220**. The individual anchors of the second anchoring feature **228** can include tips or ends **230** having covers and/or cushions as shown. In some embodiments, the tips or ends **230** can be enlarged relative to the preceding portion of the second anchoring feature **228**, such as a strut. The covers and/or cushions can reduce pressure applied to tissue of the body cavity, such as the native valve annulus, when the tips or ends **230** contact the native valve annulus. As shown in the illustrated embodiment, the second anchoring feature **228** can include twelve individual anchors; however, it is to be understood that a greater number or lesser number of individual anchors can be used. For example, the number of individual anchors can be chosen as a multiple of the number of commissures for the valve body **240**. As such, for a prosthesis **200** with a valve body **240** having three commissures, the second anchoring feature **228** can have three individual anchors, six individual anchors, nine individual anchors, twelve individual anchors, fifteen individual anchors, or any other multiple of three. It is to be understood that the number of individual anchors need not correspond to the number of commissures of the valve body **240**.

**[0189]** The frame **220** preferably includes a set of locking tabs **234** extending from the frame body **222** at its upper end. As shown, the frame **220** includes twelve

locking tabs **234**, however, it is to be understood that a greater number or lesser number of locking tabs can be used. The locking tabs **234** can extend generally upwardly from the frame body **222** in a direction generally aligned with the longitudinal axis of the frame **220**. The locking tab **234** can include an enlarged head or end **236**. As shown, the enlarged head or end **236** has a semi-circular or semi-elliptical shape forming a “mushroom” shape with the remaining portion of the locking tab **234**. The locking tab **234** can include an eyelet which can be positioned through the enlarged head **236**. It is to be understood that the locking tab **234** can include an eyelet at other locations, or can include more than a single eyelet. The locking tab **234** can be advantageously used with multiple types of delivery systems such as a “slot-based” delivery system and/or a “tether-based” delivery system.

[0190] With continued reference to the prosthesis **200** illustrated in **Figures 2-4**, the valve body **240** preferably includes a plurality of valve leaflets **242** each having a first edge **244**, a second edge **246**, and one or more tabs **248**. The first edge **244**, which may be considered a proximal edge, may be arcuate in shape. The tabs **248** can form part of the valve leaflets **242** positioned at the commissures of the valve body **240**. The second edge **246** can be a freely moving edge which can allow the valve body **240** to open and close. The valve leaflet **242** can be similar to leaflet **1110** illustrated in **Figure 19A** which includes a first edge **1112**, a second edge **1114**, and tabs **1116**. The plurality of valve leaflets **242** can function in a manner similar to the native mitral valve, or to any other valves in the vascular system as desired.

[0191] As shown in the illustrated embodiment, the valve body **240** can include one or more first intermediate components **250a** (as shown in **Figure 2**) and one or more second intermediate component **250b** (as shown in **Figure 4**). The one or more first intermediate components **250a** and the one or more second intermediate components **250b** can be used to attach one or more of the valve leaflets **242**, or a portion thereof, to the frame **220** such that the valve leaflet **242** is indirectly coupled to the frame **220** or “floats” within the frame **220**. For example, as shown in the illustrated embodiment, at least a portion of the first edge **244** and the tabs **248** can be indirectly coupled to the frame **220** via the one or more intermediate components **250a**, **250b** with a portion of the first edge **244** directly coupled to the frame **220**. The one or more first intermediate

components **250a** and/or one or more second intermediate components **250b** can be formed from a combination of units, such as a combination of two, three, or more units. It is contemplated that the one or more intermediate components **250a**, **250b** can be formed from fewer units. As will be described in further detail, the intermediate components **250a**, **250b** can be attached to one or more third intermediate components to form a partially sealed or fully sealed pocket. The intermediate components **250** may be formed from a slightly porous material which allows fluid, such as blood, to enter into the pocket. In some instances, the blood can form a clot within the pocket.

[0192] With continued reference to the prosthesis **200** illustrated in **Figures 2-4**, the skirt **260** can be loosely attached to the exterior of the frame **220**. The skirt **260** can be formed from multiple components such as an upper component **262**, a middle component **264**, and a lower component **266**. The upper component **262** can be attached to an upper portion of the frame **220**. As shown, the upper component **262** can be attached at or proximate the uppermost cusp or first edge **244** of the valve leaflet **242**. The upper component **262** can extend downwardly and be attached to the middle component **264**. The middle component **264** can extend downwardly towards a lower portion of the frame **220**. As shown, the middle component **264** can be attached at or proximate the commissures of the valve body **240** and/or the base of the anchors of the second anchoring feature **228**. The lower component **266** can be attached to the middle component **264** and can extend downwardly. As shown, the lower edge of the lower component **266** can follow the undulations of the struts of the frame **220**. However, it is contemplated that the lower component **266** can have a lower edge with a different shape, such as a straight edge. Moreover, it is to be understood that the skirt **260** can be formed from a greater number or lesser number of components. For example, one or more of the upper component **262**, the middle component **264**, and/or the lower component **266** can be combined into a single component. The skirt **260** can be formed from a variety of materials, such as a knit polyester (e.g., polyethylene terephthalate (PET)) or any other biocompatible material.

[0193] As shown in the illustrated embodiment, the skirt **260** can be attached at or proximate the upper end of the frame **220** and at or proximate the lower end of the frame **220**. The skirt **260** can be formed with sufficient material such that a portion of

the skirt **260** positioned around a middle portion of the frame **220** is loose relative to an exterior of the frame **220**.

#### Embodiments of Replacement Mitral Valve Frames and Anchoring Features

[0194] With reference to **Figures 5A-13 and 83-117**, embodiments of frames **300, 400, 500, 600, 700, and 750, 6000, 6100, 6200, 6300, 6400** and anchoring features **340, 350, 440, 450, 540, 550, 650, 710, 760, 5200, 5300, 5400, 5500, 5600, 5700, 5800, 5920, 5930, 6020, 6120, 6220, 6320, 6420** are illustrated. With reference first to the frame **300** illustrated in **Figure 5A**, the frame **300** is shown in an expanded configuration. The frame **300** can include a frame body **302** having an upper region **310**, an intermediate region **320**, and a lower region **330**. A longitudinal axis of the frame **300** may be defined as the central axis that extends through the center of the frame **300** between the upper and lower ends of the frame **300**. In some embodiments, the frame **300** may be oriented such that the upper region **310** is a proximal portion and the lower region **330** is a distal portion. The frame **300** can include a first anchoring feature **340** and a second anchoring feature **350**. In some embodiments, the frame **300** may be oriented such that the first anchoring feature **340** is a proximal anchoring feature and the second anchoring feature **350** is a distal anchoring feature.

[0195] One or both anchoring features **340, 350** can contact or engage a native valve annulus, such as the native mitral valve annulus, tissue beyond the native valve annulus, native leaflets, and/or other tissue at or around the implantation location during one or more phases of the cardiac cycle, such as systole and/or diastole. In some embodiments, one or both anchoring features **340, 350** do not contact or engage, or only partially contact or engage, a native valve annulus, such as the native mitral valve annulus, tissue beyond the native valve annulus, native leaflets, and/or other tissue at or around the implantation location during one or more phases of the cardiac cycle, such as systole and/or diastole. For example, when the frame **300** is used for a replacement mitral valve prosthesis, during at least systole, in some embodiments the second anchoring feature **350** is sized to contact or engage the native mitral valve annulus whereas the first anchoring feature **340** is sized to be spaced from the native mitral valve annulus. It is to be understood that in some embodiments, when the frame **300** is used

for a replacement mitral valve prosthesis, during diastole and/or systole, in some embodiments both the first anchoring feature **340** and the second anchoring feature **350** are sized to contact or engage the native mitral valve annulus. In some instances, the first anchoring feature **340** may contact a portion of a skirt, such as skirts **160**, **260**, which can contact or engage the native mitral valve annulus. For example, the first anchoring feature **340** can be connected to a portion of a skirt. While the anchoring features **340**, **350** have been illustrated as extending from the upper and lower regions **310**, **330** of the frame **300** respectively, it is to be understood that the anchoring features **340**, **350** can be positioned along any other portion of the frame **300** as desired. Moreover, while two anchoring features **340**, **350** have been included in the illustrated embodiment, it is to be understood that a greater number or lesser number of sets of anchoring features can be utilized.

[0196] As shown, the frame body **302**, when in an expanded configuration such as in a fully expanded configuration, has a bulbous or slightly bulbous shape, with an intermediate region **320** being larger than the upper region **310** and the lower region **330**. The bulbous shape of the frame body **302** can advantageously allow the frame body **302** to engage a native valve annulus or other body cavity, while spacing the inlet and outlet from the heart or vessel wall. This can advantageously reduce undesired contact between the prosthesis and the heart or vessel, such as the atrial and ventricular walls of the heart.

[0197] As shown in the illustrated embodiment, the intermediate region **320** is preferably cylindrical or generally cylindrical in shape such that a diameter of an upper end of the intermediate region **320** and/or a diameter of a lower end of the intermediate region **320** is equal or generally equal to the diameter of a middle portion of the intermediate region **320**. The general uniformity of the diameter of the intermediate region **320** from the upper end to the lower end, in conjunction with the axial dimension between the upper end and the lower end (i.e., the “height” of the intermediate region **320**), provides for a significantly large circumferential area upon which a native valve annulus, or other body cavity, can be engaged. This can beneficially improve securement of the frame **300** to the native valve annulus or other body cavity. This can also improve sealing between the frame **300** and the native valve annulus, or other body

cavity, thereby reducing paravalvular leakage. Although the frame body **302**, such as the intermediate portion **302**, has been described and illustrated as being cylindrical, it is to be understood that all or a portion of the frame body **302** can be have a non-circular cross-section such as, but not limited to, a D-shape, an oval or an otherwise ovoid cross-sectional shape.

[0198] In some embodiments, the diameter of the upper end of the intermediate region **320** and the lower end of the intermediate region **320** can be about the same. However, it is to be understood that the diameter of the upper end of the intermediate region **320** and the lower end of the intermediate region **320** can differ. In some embodiments, the frame body **302** in an expanded configuration can have a diameter at its widest portion of between about 30mm to about 60mm, between about 35mm to about 55mm, about 40mm, any sub-range within these ranges, or any other diameter as desired. In some embodiments, the frame body **302** in an expanded configuration has a diameter at its narrowest portion between about 20mm to about 40mm, any sub-range within these ranges, or any other diameter as desired. In an expanded configuration, the ratio of the diameter of the frame body **302** at its widest portion to the diameter of the frame body **302** at its narrowest portion can be about 3:1, about 5:2, about 2:1, about 3:2, about 4:3, any ratio within these ratios, or any other ratio as desired. In the expanded configuration, the frame body **302** preferably has an axial dimension between the upper and lower ends of the frame body **302** (i.e., the “height” of the frame body **302**) of between about 10mm to about 40mm, between about 18mm to about 30mm, about 20mm, any sub-range within these ranges, or any other height as desired.

[0199] The frame body **302** can have an axially compact configuration relative to the radial dimension. For example, the ratio of the diameter of the largest portion of the frame body **302** to the height of the frame body **302** when the frame is in its expanded configuration can be about 3:1, about 5:2, about 2:1, about 3:2, about 4:3, about 13:10, about 5:4, or about 1:1. Thus, in some embodiments the width at the largest portion of the frame body **302** can be greater than the height of the frame body **302**.

[0200] As shown in the illustrated embodiment, the height of the intermediate region **320** can be larger than the axial dimension between the upper and lower ends of

the upper region **310** (i.e., the “height” of the upper region **310**) and/or the axial dimension between the upper and lower ends of the lower region **330** (i.e., the “height” of the lower region **330**). The height of the upper region **310** is preferably between about 3mm to about 10mm. In some embodiments, the height of the intermediate region **320** can be between about 6mm to about 15mm. In some embodiments, the height of the lower region **330** can be between about 3mm to about 15mm. The ratio of the height of the intermediate region **320** to the combined heights of the upper region **310** and lower region **330** can be about 1:2, about 2:3, about 3:5, about 1:1, about 5:3, about 3:2, about 2:1, any ratio within these ratios, or any other ratio as desired. The height of the intermediate region **320** can be greater than the height of the lower region **330** and the height of the lower region **330** can be greater than the height of the upper region **310**.

[0201] With continued reference to the frame **300** illustrated in **Figure 5A**, at the juncture between the intermediate region **320** and the upper region **310**, the frame body **302** can include a bend **312**. The bend **312** can be a radially inward bend towards the longitudinal axis of the frame **300** such that a portion of the upper region **310**, extending upwardly from the beginning of bend **312** adjacent the intermediate region **320**, is inclined or curved towards the longitudinal axis of the frame **300**. The radially inward inclination of the upper region **310** can allow for a substantial decrease in radial dimension over a relatively small axial dimension. The greater the degree of inclination, the greater the decrease in radial dimension per increase in axial dimension. This can beneficially provide a relatively compact or “squat” form factor for the frame body **302**. Moreover, as will be discussed in further detail, the inclined or curved portion of the upper region **310** can facilitate the securement of a supplemental prosthesis within frame **300**.

[0202] In some embodiments, the bend **312** can orient the portion of the upper region **310**, positioned upward of the beginning of bend **312**, such that it forms an angle of between about 20 degrees to about 70 degrees with a plane orthogonal to the longitudinal axis of the frame **300**, an angle of between about 30 degrees to about 60 degrees with a plane orthogonal to the longitudinal axis of the frame **300**, an angle of between about 40 degrees to about 50 degrees with a plane orthogonal to the longitudinal axis of the frame **300**, an angle of about 45 degrees with a plane orthogonal to the

longitudinal axis of the frame **300**, any subrange within these ranges, or any other angle as desired. An angle of about 40 degrees to about 50 degrees can allow for a significant reduction in radial dimension per increase in axial dimension while still reducing strain when the frame **300** is in a crimped configuration. In some embodiments, the bend **312** can orient the portion of the upper region **310**, positioned upward of the beginning of bend **312**, such that it forms an angle of less than 70 degrees with a plane orthogonal to the longitudinal axis of the frame **300**, an angle of less than 55 degrees with a plane orthogonal to the longitudinal axis of the frame **300**, an angle of less than 40 degrees with a plane orthogonal to the longitudinal axis of the frame **300**, an angle of less than 25 degrees with a plane orthogonal to the longitudinal axis of the frame **300**, or less than any other angle as desired.

[0203] The bend **312** can generally form an arc with an angle between about 20 degrees to about 90 degrees. For example, as shown in the illustrated embodiment, the arc can have an angle of about 45 degrees. In other embodiments, the bend **312** can form an arc with an angle between about 30 degrees to about 60 degrees. The radius of curvature of the arc may be constant such that the bend **312** forms a circular arc or may differ along the length of the bend **312**.

[0204] With continued reference to the frame **300** illustrated in **Figure 5A**, at the juncture between the intermediate region **320** and the lower region **330**, the frame body **302** can include a bend **332** toward the longitudinal axis of the frame **300**. The bend **332** can be a radially inward bend towards the longitudinal axis of the frame **300** such that a portion of the lower region **330**, extending downwardly from the beginning of bend **332** adjacent the intermediate region **320**, is inclined or curved towards the longitudinal axis of the frame **300**. The radially inward inclination of the lower region **330** can allow for a substantial decrease in radial dimension over a relatively small axial dimension. The greater the degree of inclination, the greater the decrease in radial dimension per increase in axial dimension. This can beneficially provide a relatively compact or “squat” form factor for the frame body **302**. Moreover, when used at a native mitral valve, this can beneficially enhance the atraumatic nature of the device by allowing chordae tendineae to take a more natural trajectory, thereby relieving stress on the chordae and leaflets. Additionally, as will be discussed in further detail below, the



inclined or curved portion of the lower region **330** can facilitate the securement of a supplemental prosthesis within frame **300**.

[0205] The bend **332** can orient the portion of the lower region **330**, positioned below the beginning of bend **332**, such that it forms an angle of between about 20 degrees to about 70 degrees with a plane orthogonal to the longitudinal axis, an angle of between about 30 degrees to about 60 degrees with a plane orthogonal to the longitudinal axis, an angle of between about 40 degrees to about 50 degrees with a plane orthogonal to the longitudinal axis, an angle of about 45 degrees with a plane orthogonal to the longitudinal axis, any subrange within these ranges, or any other angle as desired. An angle of about 40 degrees to about 50 degrees can allow for a significant reduction in radial dimension per increase in axial dimension while still reducing strain when the frame **300** is in a crimped configuration. In some embodiments, the bend **332** can orient the portion of the lower region **330**, positioned below of the beginning of bend **332**, such that it forms an angle of less than 70 degrees with a plane orthogonal to the longitudinal axis, an angle of less than 55 degrees with a plane orthogonal to the longitudinal axis, an angle of less than 40 degrees with a plane orthogonal to the longitudinal axis, an angle of less than 25 degrees with a plane orthogonal to the longitudinal axis, or less than any other angle as desired.

[0206] The bend **332** can generally form an arc with an angle between about 20 degrees to about 90 degrees. For example, as shown in the illustrated embodiment, the arc can have an angle of about 45 degrees. In some embodiments, the bend **332** can form an arc with an angle between about 30 degrees to about 60 degrees. The radius of curvature of the arc may be constant such that the bend **332** forms a circular arc or may differ along the length of the bend **332**.

[0207] The lower region **330** can include a bend **334** below the bend **332**. The bend **334** can be oriented opposite that of the bend **332** such that a portion of the lower region **330**, extending downwardly from the beginning of the bend **334**, is inclined or curved at less of an angle towards the longitudinal axis of the frame **300** than the portion above the beginning of bend **334**, is generally parallel to the longitudinal axis, or is inclined or curved at an angle away from the longitudinal axis of the frame **300**. This

can beneficially reduce the rate of decrease in radial dimension over the remainder of the axial dimension of the lower region **330**.

[0208] The bend **334** can orient the portion of the lower region **330**, positioned below the beginning of bend **334**, such that it forms an angle of between about 30 degrees to about 90 degrees with a plane orthogonal to the longitudinal axis, an angle of between about 45 degrees to about 85 degrees with a plane orthogonal to the longitudinal axis, an angle of between about 60 degrees to about 80 degrees with a plane orthogonal to the longitudinal axis, an angle of about 80 degrees with a plane orthogonal to the longitudinal axis, any subrange within these ranges, or any other angle as desired. In some embodiments, the bend **334** can orient the portion of the lower region **330**, positioned below the beginning of bend **334**, such that it forms an angle of greater than 25 degrees with a plane orthogonal to the longitudinal axis, an angle of greater than 40 degrees with a plane orthogonal to the longitudinal axis, an angle of greater than 55 degrees with a plane orthogonal to the longitudinal axis, an angle of greater than 70 degrees with a plane orthogonal to the longitudinal axis, or greater than any other angle as desired.

[0209] The diameter of the upper end of the upper region **310** and the lower end of the lower region **330** can be about the same. However, it should be understood that the diameter of the upper end of the upper region **310** and the lower end of the lower region **330** can differ. Moreover, in some embodiments, the frame body **302** may not have a bulbous portion, and can have substantially the same outer dimension along its entire length (e.g., cylindrical), or it may have one end larger than the other end. For example, the intermediate region **320** and the lower region **330** can have the same, or substantially the same, diameter.

[0210] With continued reference to the frame **300** illustrated in **Figure 5A**, the frame body **302** can include a plurality of struts with at least some of the struts forming cells **360a**, **360b**, **360c**. Any number of configurations of struts can be used, such as rings of undulating struts shown forming ellipses, ovals, rounded polygons, and teardrops, but also chevrons, diamonds, curves, and various other shapes. As shown in the illustrated embodiment, the frame body **302** can include three rows of cells **360a**, **360b**, **360c**.

[0211] The upper row of cells **360a** can have a hexagonal or generally hexagonal shape. The cell **360a** can be formed via a combination of struts. As shown in the illustrated embodiment, the upper portion of cells **360a** can be formed from a set of circumferentially-expandable struts **365** having a zig-zag or undulating shape forming a repeating “V” shape. The circumferentially-expandable struts **365** can be inclined or curved towards a longitudinal axis of the frame **300** such that an upper portion of the struts **365** are positioned closer to the longitudinal axis of the frame **300** than the lower portion of the struts **365**.

[0212] The middle portion of cells **360a** can be formed from a set of struts **370** extending downwardly from bottom ends of each of the “V” shapes. The struts **370** can extend generally longitudinally in a distal direction. As shown in the illustrated embodiment, the struts **370** can incorporate the bend **312** such that an upper portion of the struts **370** are inclined or curved towards the longitudinal axis of the frame **300** and the lower portion of the struts **370** extend in a direction generally parallel to the longitudinal axis of the frame **300**.

[0213] The lower portion of cells **360a** can be formed from a set of circumferentially-expandable struts **375** having a zig-zag or undulating shape forming a repeating “V” shape. As shown in the illustrated embodiment, circumferentially-expandable struts **375** can form a generally cylindrical portion of the frame **300** with the upper portion of the struts **375** having a radial dimension which is about the same as the radial dimension as the lower portion of the struts **375**. The portion of the cells **360a** extending upwardly from the bottom end of struts **370** may be considered to be a substantially non-foreshortening portion of the frame **300**. As will be discussed in further detail below, foreshortening refers to the ability of the frame to longitudinally shorten as the frame radially expands.

[0214] As shown in the illustrated embodiment, the cells **360a** can have an irregular hexagon shape. For example, hexagonal cells **360a** can be symmetrical about a vertical axis extending from upper to lower ends of the cell **360a**. In some embodiments, two of the sides of the hexagonal cells **360a** can be one length, while the other four sides of the cells **360a** can be a greater length. In some embodiments, the two sides with the same length can be generally parallel to one another.

[0215] As shown in the illustrated embodiment, the middle and/or lower rows of cells **360b**, **360c** can have a different shape from the cells **360a** of the first row. The middle and lower row of cells **360b**, **360c** can have a diamond or generally diamond shape. The cells **360b**, **360c** may be considered to be a substantially foreshortening portion of the frame **300**. The diamond or generally diamond shape can be formed via a combination of struts. The upper portion of cells **360b** can be formed from the set of circumferentially-expansible struts **375** such that cells **360b** share struts with cells **360a**. The lower portion of cells **360b** can be formed from a set of circumferentially-expansible struts **380**. As shown in the illustrated embodiment, circumferentially-expansible struts **380** can extend generally in a downward direction. The circumferentially-expansible struts **380** can incorporate the bend **332** such that an upper portion of the struts **380** form a generally cylindrical portion of the frame **300** and the lower portion of the struts **380** can be inclined or curved towards the longitudinal axis of the frame **300**.

[0216] The upper portion of cells **360c** can be formed from the set of circumferentially-expansible struts **380** such that cells **360c** share struts with cells **360b**. The lower portion of cells **360c** can be formed from a set of circumferentially-expansible struts **385**. Circumferentially-expansible struts **385** can extend generally in a downward direction. The circumferentially-expansible struts **385** can be inclined or curved towards the longitudinal axis of the frame **300**. As shown in the illustrated embodiment, the angle of inclination of the circumferentially-expansible struts **385** can be different from the angle of inclination of the lower portion of circumferentially-expansible struts **380**. For example, the circumferentially-expansible struts **385** can be less inclined or curved towards the longitudinal axis of the frame **300** than the lower portion of circumferentially-expansible struts **380**. As will be discussed in further detail, the angle of inclination of circumferentially-expansible struts **385** can be chosen based on the supplemental prosthesis the frame **300** is designed to receive.

[0217] While the cells **360a**, **360b**, **360c** were described as generally hexagonal-shaped and generally diamond-shaped, it is to be understood that some or all of the struts **365**, **370**, **375**, **380**, **385** may not form entirely straight segments. As shown in the illustrated embodiments, the struts **365**, **370**, **375**, **380**, **385** can include some curvature such that the upper and/or lower apices are curved. For example, the struts

**375, 380** forming apices of cells **360b** can incorporate curvature such that the apices are generally “onion” shaped.

[0218] As shown in the illustrated embodiment, there can be a row of twelve cells **360a**, a row of twelve cells **360b**, and a row of twelve cells **360c**. While each of the cells **360a, 360b, 360c** are shown as having the same shape as other cells **360a, 360b, 360c** of the same row, it is to be understood that the shapes of cells **360a, 360b, 360c** within a row can differ. Moreover, it is to be understood that any number of rows of cells can be used and any number of cells may be contained in the rows. In some embodiments, the number of cells can correspond to the number of anchors or anchor tips forming the first anchoring feature and/or the number of anchors or anchor tips forming the second anchoring feature. As shown, the number of cells in each row of cells **360a, 360b, 360c** have a 1:1 correspondence with the number of anchors in both the first anchoring feature **340** and the second anchoring feature **350** (i.e., twelve cells in each row of cells **360a, 360b, 360c** and twelve anchors for the anchoring features **340, 350**). It is to be understood that other ratios of numbers of cells per row to number of anchors per anchoring feature can be used such as, but not limited to, 2:1, 3:1, 4:1, 5:1, 6:1, and other ratios as desired. For example, as shown in the embodiment of frame **300** illustrated in **Figure 5B**, the number of cells in some rows may be increased to a 2:1 ratio with anchors of one or both of the anchoring features, such as anchoring feature **350'**. Although the anchors of anchoring feature **350'** illustrated in **Figure 5B** are equally spaced with two cells between each anchor, it is to be understood that the anchors can be unequally spaced. In some implementations, two anchors may be spaced apart by one cell whereas the remaining anchors are spaced apart by two or more cells. As another example, as shown in the embodiment of frame **600** illustrated in **Figure 9**, the number of cells in some rows may be increased to a 2:1 ratio.

[0219] With continued reference to the frame **300** illustrated in **Figure 5A**, the geometry of cells **360a, 360b, 360c** can allow the cells **360a, 360b, 360c** to foreshorten as the frame **300** is expanded. As such, one or more of cells **360a, 360b, 360c** can allow the frame **300** to foreshorten as the frame **300** is expanded. Foreshortening of the frame **300** can be used to secure the prosthesis to intraluminal tissue in a body cavity, for example tissue at or adjacent a native valve, such as a native

valve annulus and/or leaflets. The anchoring features **340**, **350** and anchor tips **344**, **358** are preferably located along the frame **300** with at least part of the foreshortening portion positioned between the anchoring features **340**, **350** so that a portion of the anchoring features **340**, **350** will move closer together with expansion of the frame **300**.

[0220] As one example, this can allow the anchoring features **340**, **350** to close in on opposite sides of the native mitral annulus to thereby secure the prosthesis at the mitral valve. In some embodiments, the anchoring features **340**, **350** can be positioned such that the anchoring features **340**, **350** do not contact opposing portions of the native mitral annulus at the same time. For example, in some situations, the anchoring feature **350** may contact the native mitral annulus while the anchoring feature **340** does not contact the native mitral annulus. This can be beneficial when anchoring feature **340** are used to provide stabilization and help align the prosthesis. In some embodiments, the anchoring features **340**, **350** can be positioned such that the anchoring features **340**, **350** grasp opposite side of the native mitral annulus.

[0221] With continued reference to the frame **300** illustrated in **Figure 5A**, anchoring feature **340** can include one or more anchors. For example, as shown in the illustrated embodiment, the anchoring feature **340** can include twelve anchors. Each anchor can include one or more struts **342** extending from an upper region **310** of the frame body **302**. As shown, struts **342** extend into the cells **360a**. The struts **342** extend from an upper intersection of two segments of the cell **360a**, for example, from the uppermost corner of the cells **360a** between struts **365**. However, it is to be understood that the struts **342** can extend from other portions of the frame body **302**, such as other portions of the cell **360a**. As shown, the struts **342** extend generally downwardly into the cells **360a** while curving outwards away from the frame body **302**. Thus, the anchoring feature **340** extends radially outwardly from the frame body **302** as it extends generally downwardly towards a tip **344**. The tips **344** of the anchoring feature **340** can end after extending approximately between about one-third to about two-thirds of the height of hexagonal cells **360a** when the frame **300** is expanded. Further, the tips **344** can extend farther outwards than the frame body **302**.

[0222] As shown in the illustrated embodiment, the anchoring feature **340** can include one or more eyelets such as the two eyelets illustrated per strut **342**. The one

or more eyelets can form a portion of the tip **344** of the anchoring feature **340**. The one or more eyelets can be used to attach other components of the prosthesis in which the frame **300** is used, such as a skirt. The shape of the one or more eyelets beneficially reduce the potential for trauma should the tips **344** contact tissue such as that of the native valve annulus or other body cavity.

[0223] Anchoring feature **350** can include one or more anchors. For example, as shown in the illustrated embodiment, the anchoring feature **350** can include twelve anchors. However, it is to be understood that the anchoring feature **350'** can include a fewer or greater number of anchors. For example, as shown in **Figure 5B**, the anchoring feature **350** can include six anchors. Each anchor can include one or more struts **352** extending from a lower region **330** of the frame **300**. As shown, struts **352** extend from a lower intersection of two segments of the cell **360b**, for example, from the lowermost corner of the cells **360b** between struts **380**. However, it is to be understood that the struts **352** can extend from other portions of the frame **300**, such as other portions of the cell **360b** and/or other portions of the cells **360c**. For example, the struts **352** can extend from a lower intersection of two segments of the cell **360c**, for example, from the lowermost corner of the cells **360c** between struts **385**.

[0224] As shown, the struts **352** extend generally downwardly while curving inwardly towards the longitudinal axis from the frame **300**. Thus, the narrowest portion of the anchoring feature **340** can have a diameter which is about the same as, or less than, a diameter of the lower region **330** of the frame body **302**. The struts **352** can incorporate a bend **354** to orient the strut **352** such that it extends radially outward away from the longitudinal axis of the frame **300**. As shown in the illustrated embodiment, the bend can be generally semi-circular or semi-elliptical which can provide a space for the distal ends of the native valve leaflets to be stored. The anchors may then extend in a linear segment radially outwardly and upwardly. The struts **352** can include a second bend **356** along the linear segment. As shown in the illustrated embodiment, the bend **356** can orient the strut **352** such that it extends generally parallel to the longitudinal axis of the frame **300**. For example, the tip **358** of anchoring feature **350** can extend generally parallel to the longitudinal axis of the frame **300**. The tips **358** of the anchoring feature **350** can end after extending approximately above the base or connection point of the

anchoring feature **350** to the frame body **302**. In some embodiments, the tips **358** of the anchoring feature **350** can end after extending up to, or slightly past, the lower end of the intermediate region **320** of the frame body **302**.

[0225] While the bend **356** orients the tip **358** such that it extends generally parallel to a longitudinal axis of the frame **300**, it is to be understood that the bend **356** can orient the struts **352**, such as the tips **358**, in other directions. For example, the bend **356** can orient the struts **352**, such as the tips **358**, such that they extend radially outward away from the longitudinal axis of the frame **300**, such that struts **352** extends radially inward towards the longitudinal axis of the frame **300**, or such that a portion of struts **352** extends radially outward away from the longitudinal axis of the frame **300** and another portion of struts **352**. In some embodiments, the bend **356** can orient the struts **352**, such as the tips **358**, such that they extend generally perpendicular to a longitudinal axis of the frame **302** such as is shown with frame **400** illustrated in **Figure 6**.

[0226] The tips or ends **344**, **358** as described above can advantageously provide atraumatic surfaces that may be used to contact or engage intraluminal tissue without causing unnecessary or undesired trauma to tissue. For example, the tips or ends **344**, **358** can form flat, substantially flat, curved or other non-sharp surfaces to allow the tips to engage and/or grasp tissue, without necessarily piercing or puncturing through tissue. A looped end or looped anchor may assist the frame in not getting caught up on structures at or near the treatment location. For example, each loop can be configured so that when the frame **300** is deployed in-situ and the anchoring features **340**, **350** expand away from the frame body **302**, the movement of each loop from a delivered position to a deployed position avoids getting caught on the papillary muscles. As shown in the illustrated embodiment, the first anchoring feature **340** includes rounded eyelets at a tip or end **344** of the anchoring feature **340**. The second anchoring feature **350** includes anchors tips or ends **358** having looped ends with a flattened or rounded top surface.

[0227] With continued reference to the frame **300** illustrated in **Figure 5A**, the anchors of the first anchoring feature **340** can be circumferentially staggered with respect to the anchors of the second anchoring feature **350** meaning that the tips or ends **344** of the first anchoring feature **340** are not aligned, circumferentially, with the tips or ends **358** of the second anchoring feature **350**. In other embodiments (not shown), the



anchors of the first anchoring feature **340** and the anchors of the second anchoring feature **358** can be circumferentially aligned.

[0228] Preferably, each of the anchoring features **340**, **350** are positioned or extend generally radially outwardly from the frame **300** so that the anchor tips **344**, **358** are generally spaced away or radially outward from the rest of the frame body **302** and from where the base of the anchors connect to the frame body **302**. For example, the anchor tips **344**, **358** may be located radially outward from the intermediate region **320** of the frame body **302**, with the tips **344**, **358** being axially spaced from one another. In some embodiments, at least some of the anchoring features, such as anchoring features **340**, **350**, can extend to a radial distance from an exterior surface of the intermediate region **320** of the frame body **302** that is about 110% or more of the expanded diameter of the intermediate region **320** of the body **302** at the plane of tips **344**, **358**. In some embodiments, all of the anchors of the first anchoring feature **340** and/or all of the anchors of the second anchoring feature **350** extend at least to this radial distance. In other embodiments, fewer than all of the anchors of the first anchoring feature **340** and/or all of the anchors of the second anchoring feature **350** extend to this radial distance. The outermost diameter of the first anchoring feature **340** and/or the second anchoring feature **350** may be greater than the diameter of frame the body **302** as described above and may be in the range of about 35mm to about 70mm when expanded, in the range of about 35mm to about 60mm when expanded, in the range of about 40mm to about 60mm when expanded, in the range of about 45mm to about 50mm when expanded, any sub-range within these ranges when expanded, or any other diameter as desired.

[0229] The first anchoring feature **340** and the second anchoring feature **350** can extend radially outward from the longitudinal axis of the frame **300** to about the same radial dimension. However, it is to be understood that in other embodiments (not shown), the first anchoring feature **340** can be positioned to be not as far radially outward as the second anchoring feature **350** or the second anchoring feature **350** can be positioned to be not as far radially outward as the first anchoring feature **340**. Such configurations may be advantageous in positioning and securing the prosthesis in a native valve annulus or other body location.

[0230] With continued reference to the frame **300** illustrated in **Figure 5A**, it should be understood that the anchoring features **340**, **350** can have various other configurations. For example, while the frame **300** includes anchoring features **340**, **350** with twelve anchors each, it is to be understood that a greater number of anchors or a lesser number of anchors can be used. The number of anchors can correspond to the number of commissures of the internal valve used with the frame **300**. For example, for a prosthesis with a valve having three commissures, the number of anchors can be chosen in multiples of three such as three anchors, six anchors, twelve anchors, fifteen anchors, and any other multiple of three. In some embodiments, instead of a 1:1 correspondence between the number of anchors in the first anchoring feature **340** and the second anchoring feature **350** (i.e., twelve anchors each), other ratios can be used. For example, a 1:2 or a 1:3 correspondence between the anchors, are possible such that the first anchoring feature **340** or the second anchoring feature **350** have fewer anchors than the other anchoring feature.

[0231] Individual anchors may extend radially outwardly from the frame at an anchor base and terminate at an anchor tip. The individual anchors can be connected to the frame at one of many different locations including apices, junctions, other parts of struts, etc. Moreover, the anchors forming the anchoring features **340**, **350** can comprise first, second, third, or more spaced apart bending stages along the length of each anchor. Further details that may be incorporated and/or interchanged with the features described herein are disclosed in U.S. Publication Nos. 2014/0277422, 2014/0277427, 2014/0277390, and 2015/0328000, which have been incorporated by reference herein.

[0232] Covers and/or cushions (see, for example, covers and/or cushions **720**, **770** illustrated in Figures **10-13**) may be used to surround or partially surround at least a portion of the first anchoring feature **340** and/or the second anchoring feature **350**, such as the tips or ends **344** of the first anchoring feature **340** and/or the tips or ends **358** of the second anchoring feature **350** and/or the struts to which the tips or ends **344**, **458** are attached. The covers and/or cushions can be similar to those described in U.S. Publication No. 2015/0328000. For example, the covers and/or cushions can be formed from one or more pieces of material. In some embodiments, an inner portion can be positioned within a covering such that the covering forms a layer surrounding the inner

portion. The inner portion can be formed of a foam material, such as a polymer foam, such that the inner portion is at least somewhat compliant. The covering can be formed of a biocompatible, fabric material such as a polymer woven or knitted cloth or sheet. In some embodiments, the cushions can be formed as a polymer molded insert. In some embodiments, the covers and/or cushions can be taut. In some embodiments, the covers and/or cushions can be loosely coupled to the anchoring feature. For example, a loosely coupled cover can be positioned along a side of a strut intended to be positioned against tissue.

[0233] In some embodiments, the covers and/or cushions can either fit snugly around the tips **358** or can have extra padding so that the covers extend radially away from the frame **300**. In some embodiments, all of the anchors of the second anchoring feature **350** can have the covers and/or cushions with some of the anchors having less cushioning than others. In some embodiments, all of the anchors of the second anchoring feature **350** can have the padded covers. In some embodiments, all of the anchors of the second anchoring feature **350** can have the snugly fitting cushions. In some embodiments, not all of all of the anchors of the second anchoring feature **350** can have covers.

[0234] With continued reference to the frame **300** illustrated in **Figure 5A**, the frame **300** can include a set of locking tabs **390** extending from the upper region **310** of the frame **300**. As shown, the frame **300** includes twelve locking tabs **390**, however, it is to be understood that a greater number or lesser number of locking tabs can be used. The locking tabs **390** can extend generally upwardly from the upper region **310** in a direction generally aligned with the longitudinal axis of the frame **300**. As shown in the illustrated embodiment, the locking tabs **390** include a strut **392** which can include a bend **394** such that a portion of the strut **392**, positioned upwards of the beginning of the bend **394**, is inclined or curved at less of an angle towards the longitudinal axis of the frame **300** than the portion below the beginning of the bend **394**, is generally parallel to the longitudinal axis, or is inclined or curved at an angle away from the longitudinal axis of the frame **300**.

[0235] In some embodiments, the bend **394** can orient the portion of the strut **392**, positioned upward of the beginning of bend **394**, such that it forms an angle of

between about 30 degrees to about 90 degrees with a plane orthogonal to the longitudinal axis, an angle of between about 45 degrees to about 85 degrees with a plane orthogonal to the longitudinal axis, an angle of between about 60 degrees to about 80 degrees with a plane orthogonal to the longitudinal axis, an angle of about 80 degrees with a plane orthogonal to the longitudinal axis, any subrange within these ranges, or any other angle as desired. In some embodiments, the bend **394** can orient the portion of the strut **392**, positioned upward of the beginning of bend **394**, such that it forms an angle of greater than 25 degrees with a plane orthogonal to the longitudinal axis, an angle of greater than 40 degrees with a plane orthogonal to the longitudinal axis, an angle of greater than 55 degrees with a plane orthogonal to the longitudinal axis, an angle of greater than 70 degrees with a plane orthogonal to the longitudinal axis, or greater than any other angle as desired.

[0236] At an upper end of the strut **392**, the locking tab **390** can include an enlarged head **394**. As shown, the enlarged head **394** has a semi-circular or semi-elliptical shape forming a “mushroom” shape with the strut **396**. The locking tab **390** can include an eyelet **396** which can be positioned through the enlarged head **394**. It is to be understood that the locking tab **234** can include an eyelet at other locations, or can include more than a single eyelet. The locking tab **390** can be advantageously used with multiple types of delivery systems. For example, the shape of the struts **392** and the enlarged head **394** can be used to secure the frame **300** to a “slot” based delivery system. The eyelets **396** can be used to secure the frame **300** to a “tether” based delivery system such as those which utilize sutures, wires, or fingers to control delivery of the frame **300**. This can advantageously facilitate recapture and repositioning of the frame **300** in situ. In some embodiments, the frame **300** can be used with the delivery systems described in U.S. Patent Nos. 8,414,644 and 8,652,203 and U.S. Publication Nos. 2015/0238315.

[0237] With reference next to the frame **400** illustrated in **Figure 6**, the frame **400** is shown in an expanded configuration. The frame **400** can include a frame body **402** having an upper region **410**, an intermediate region **420**, and a lower region **430**. A longitudinal axis of the frame **400** may be defined as the central axis that extends through the center of the frame **400** between the upper and lower ends of the frame **400**. In some embodiments, the frame **400** may be oriented such that the upper region **410** is a

proximal portion and the lower region **430** is a distal portion. The frame **400** can include a first anchoring feature **440** and a second anchoring feature **450**. In some embodiments, the frame **400** may be oriented such that the first anchoring feature **440** is a proximal anchoring feature and the second anchoring feature **450** is a distal anchoring feature.

[0238] As shown in the illustrated embodiment, the height of the intermediate region **420** can be larger relative to the heights of the upper region **410** and lower region **430** as compared to the height of the intermediate region **320** relative to the heights of the upper region **310** and lower region **330**. This can advantageously provide a larger circumferential area upon which a native valve annulus can be engaged. This can also beneficially enhance securement of the frame **400** to the native valve annulus or other body cavity. Moreover, this can beneficially reduce the overall height of the frame **400**.

[0239] At the juncture between the intermediate region **420** and the lower region **430**, the frame **400** can include a bend **432** toward the longitudinal axis of the frame **400**. The bend **432** can be a radially inward bend towards the longitudinal axis of the frame **400** such that a portion of the lower region **430**, extending downwardly from the beginning of bend **432**, is inclined or curved towards the longitudinal axis of the frame **400**. The lower region **430** can include a second bend **434** below the bend **432**. The bend **434** can be oriented opposite that of the bend **432** such that a portion of the lower region **430**, extending downwardly from the beginning of the bend **434**, is inclined or curved at an angle away from the longitudinal axis of the frame **400**. This can beneficially allow at least a portion of the lower region **430** to form part of the second anchoring feature **450**.

[0240] The frame **400** can include a first row of cells **460a**, a second row of cells **460b**, and a third row of cells **460c** (as shown in **Figure 7**) which can share some similarities to cells **360a**, **360b**, **360c** of frame **300**. As shown in the illustrated embodiment, the upper portion of cells **460c** can be formed from the set of circumferentially-expandable struts **480** such that cells **460c** share struts with the cells of the row above. The lower portion of cells **460c** can be formed from a set of circumferentially-expandable struts **485**. Circumferentially-expandable struts **485** can extend generally in a downward direction. The circumferentially-expandable struts **485** can be inclined or curved away from the longitudinal axis of the frame **400** such that the

upper portion of struts **485** are positioned closer to the longitudinal axis of the frame **400** than the lower portion of struts **485**. As shown in the illustrated embodiment, the bend **434** can be formed by struts **485** and can be shaped similarly to the bend **354** discussed in connection with struts **352** of the second anchoring feature **350** of frame **300**.

[0241] Anchoring feature **450** can include one or more anchors. For example, as shown in the illustrated embodiment, the anchoring feature **450** can include twelve anchors. Each anchor can include one or more struts **452** extending from a lower region **430** of the frame **400**. As shown, struts **452** extend from a lower intersection of two segments of the cell **360c**, for example, from the lowermost corner of the cells **460c** between struts **485**. However, it is to be understood that the struts **452** can extend from other portions of the frame **400**, such as other portions of the cell **460b** and/or other portions of the cells **460c**. For example, the struts **452** can extend from a lower intersection of two segments of the cell **460b**, for example, from the lowermost corner of the cells **460c** between struts **480**.

[0242] As shown, the struts **452** extend generally radially outward. The struts **452** can incorporate a bend **454** to orient the strut **452** such that it extends radially outward away from the longitudinal axis of the frame **400** and upwards. The anchors may then extend in a linear segment radially outwardly and upwardly. The struts **452** can include a second bend **456** along the linear segment. As shown in the illustrated embodiment, the bend **456** can orient the strut **452** such that it extends generally radially outward from the longitudinal axis of the frame **400** and generally perpendicular to the longitudinal axis of the frame **400**. For example, the tip **458** of anchoring feature **450** can extend generally perpendicular to the longitudinal axis of the frame **400**. This can beneficially increase the tissue contact area of the tip **458** of the anchor as compared to an anchor which does not incorporate such a bend. This increased tissue contact area can beneficially reduce the stress applied by the tip **458** to tissue thereby reducing the amount of pressure and potential for trauma to the tissue. In some embodiments, the uppermost portions of the anchoring feature **450** can extend up to, or slightly past, the lower end of the intermediate region **420** of the frame body **402**.

[0243] With continued reference to the frame **400** illustrated in **Figure 6**, the frame **400** can include locking tabs **490**. These locking tabs **490** are similar to locking

tabs **390** of frame **300**; however, the locking tabs **490** have a lower axial dimension thereby providing for a more compact form factor. Although the locking tabs **490** do not include eyelets, it is to be understood that the locking tabs **490** can include eyelets.

[0244] With reference next to the frame **400** illustrated in **Figure 7**, the frame **400** is shown as a flat pattern. Any of the frames described herein such as, but not limited to, frames **300**, **400** can be made of many different materials, but is preferably made from metal. In some embodiments, the frames can be made from a shape memory material, such as nitinol. A wire frame or a metal tube can be used to make the frame. The wire frame of a metal tube can be cut or etched to remove all but the desired metal skeleton. In some embodiments a metal tube is laser cut in a repeating pattern to form the frame. The flat pattern can be cut from a metal tube and then the tube can be bent and expanded to the expanded configurations shown herein. The frames can further be expanded and/or compressed and/or otherwise worked to have the desired shape or shapes, such as for introduction and implantation.

[0245] With reference next to the frame **500** illustrated in **Figure 8**, the frame **500** is shown as a flat pattern. As shown in the illustrated embodiment, the frame **500** can include first anchoring feature **540**, second anchoring feature **550**, a first row of cells **560a**, a second row of cells **560b**, a third row of cells **560c**, and a plurality of locking tabs **590**. The second anchoring feature **550** can include anchors with tips **558** having one or more eyelets. As shown, each anchor can include two eyelets. The eyelets can beneficially facilitate attachment of other components, such as covers and/or cushions, to the tips **558**.

[0246] With reference next to the frame **600** illustrated in **Figure 9**, the frame **600** is shown in an expanded configuration. The frame **600** can include a frame portion **602** having an upper region **610**, an intermediate region **620**, and a lower region **630**. A longitudinal axis of the frame **600** may be defined as the central axis that extends through the center of the frame **600** between the upper and lower ends of the frame **600**. In some embodiments, the frame **600** may be oriented such that the upper region **610** is a proximal portion and the lower region **630** is a distal portion. The frame **600** can include an anchoring feature **650**. In some embodiments, the frame **600** may be oriented such that the anchoring feature **650** is a distal anchoring feature.

[0247] As shown in the illustrated embodiment, anchoring feature **650** can include one or more anchors. For example, as shown in the illustrated embodiment, the anchoring feature **650** can include nine anchors each including a strut **652** extending from a lower region **630** of the frame body **602**. The diameter of the frame body **602** at the widest portion is approximately the same as those of frames **300**, **400**, **500** are their widest portions. Moreover, when crimped into a collapsed configuration for delivery via a transcatheter delivery system, the overall length of the frame **600** can be similar to those of frames **300**, **400**, **500** when in a collapsed configuration for delivery. As shown in the illustrated embodiment, this can be achieved via strut and cell geometry.

[0248] As shown in the illustrated embodiment, there can be a first row of nine cells **660a**, a second row of eighteen cells **660b**, a third row of eighteen cells **660c**, and a row of nine cells **660d**. Cells **660b** share similarities to cells **360a**, **460a**, **560a**. For example, cells **660b** can have a hexagonal or generally hexagonal shape. Cells **660** have generally longitudinally extending struts **670** which can extend generally parallel to the longitudinal axis of the frame **600**. Cells **660a**, **660c** share similarities to cells **360b**, **460b**, **560b**. For example, cells **660a**, **660c** can have a diamond or generally diamond shape. Cells **660d** have an irregular polygonal shape. As shown, the number of cells in the first row of cells **660a** and fourth row of cells **660d** correspond to the number of anchors of the anchoring portion **650**. The number of cells in the second row of cells **660b** and the third row of cells **660c** are twice that of the number of anchors. This can beneficially allow the frame to reach a desired width while maintaining a relatively axially compact profile when crimped into a collapsed configuration. Other ratios of the number of cells to the number of anchors can be chosen including 3:1, 4:1, 5:1, or any other ratio as desired.

[0249] With reference next to the frame **700** illustrated in **Figures 10** and **11**, the frame **700** includes anchoring feature **710** having covers and/or cushions **720**. As shown in the illustrated embodiment, the anchoring feature **710** can have a similar profile to those of anchoring feature **350**. The anchoring feature **710** can include a cover and/or cushion **720** extending over a tip **712** of the anchors. In some embodiments, the cover and/or cushion **720** can be positioned such that it extends over the top of the tip **712**. In some embodiments, the cover and/or cushion **720** can also be positioned such that it



extends circumferentially around the tip **712**. The cover and/or cushion **720** can be formed from a deformable material such as a foam. When the top portion of the cover and/or cushion **720** is subject to pressure due to a downwardly directed force, the cover and/or cushion **720** can compress and expand laterally outward. Such a force may be exerted upon the cover and/or cushion **720** when the cover and/or cushion **720**, for example, when the cover and/or cushion **720** contacts a ventricular side of the mitral valve annulus during systole. The compression and lateral expansion of cover and/or cushion **720** can increase the surface area of the cover and/or cushion **720** in contact with the tissue, thereby exerting less pressure on the tissue and reducing the potential for trauma.

[0250] With reference next to the frame **750** illustrated in **Figures 12 and 13**, the frame **750** includes anchoring feature **760** having covers and/or cushions **770**. As shown in the illustrated embodiment, the anchoring feature **760** can have a tip profile similar to that of anchoring feature **450**. The anchoring feature **760** can include a cover and/or cushion **770** extending over a tip **762** of the anchors. In some embodiments, the cover and/or cushion **770** can be positioned such that it extends over the top of the tip **762**. In some embodiments, the cover and/or cushion **770** can also be positioned such that it extends circumferentially around the tip **762**. The cover and/or cushion **770** can be formed from a deformable material such as a foam. When the top portion of the cover and/or cushion **770** is subject to pressure due to a downwardly directed force, the cover and/or cushion **770** can compress and expand laterally outward. Such a force may be exerted upon the cover and/or cushion **770** when the cover and/or cushion **770**, for example, when the cover and/or cushion **770** contacts a ventricular side of the mitral valve annulus during systole. The compression and lateral expansion of cover and/or cushion **770** can increase the surface area of the cover and/or cushion **770** in contact with the tissue, thereby exerting less pressure on the tissue and reducing the potential for trauma.

[0251] With reference next to **Figures 83-85**, embodiments of anchoring features **5200, 5300** are illustrated. In the expanded configuration, the anchoring features **5200, 5300** can include one or more prongs which are at least radially offset relative to each other. In this manner, tips of the one or more prongs can be at different radial

positions relative to a longitudinal axis of a frame (not shown) to which the anchoring features **5200**, **5300** are attached. This can beneficially increase the tissue contact area of the tips of the anchoring features **5200**, **5300**. This increased tissue contact area can beneficially reduce the stress applied by the anchoring features **5200**, **5300** to tissue thereby reducing the amount of pressure and potential for trauma to the tissue. In some embodiments, the radial distance between the prongs of the anchoring features **5200**, **5300** can be reduced or eliminated when in a collapsed configuration. This can beneficially reduce the crimp profile of the anchoring features **5200**, **5300** such that a smaller delivery system can be utilized.

[0252] With reference first to **Figures 83 and 84**, anchoring feature **5200** is illustrated. The anchoring feature **5200** can be attached to a frame body (not shown) via one or more struts **5210**. The anchoring feature **5200** can include one or more prongs **5220**, **5230** having tips **5222**, **5232**. As shown in the illustrated embodiment, the first prong **5220** can form a loop similar to other anchoring features described herein. The second prong **5230** can be positioned within the first prong **5220**. Positioning the second prong **5230** within the first prong **5220** can advantageously make use of an existing space within the first prong **5220**.

[0253] The first prong **5220** and the second prong **5230** can be radially offset. As shown, the first prong **5220** can include a bend **5224** which directs the first prong **5220** radially outward relative to the second prong **5230** such that the tips **5222**, **5232** are at different radial positions relative to each other. One or more coverings and/or cushions (not shown) can be attached to the anchoring feature **5200** which covers the tips **5222**, **5232**. The one or more coverings and/or cushions can span the gap between the tips **5222**, **5232** to further increase the tissue contact area of the tips. The coverings and/or cushions can include the same or similar structure to those described herein. For example, the coverings and/or cushions can be formed from a foam material, woven or knitted cloth or sheet, and/or an insert. As shown in the illustrated embodiment, the tip **5222** of prong **5220** can be extend in a direction generally parallel to tip **5232** of prong **5230**. While the tips **5222**, **5232** are shown at or around the same axial position, it is to be understood that the tips **5222**, **5232** can be axially offset. The prong **5230** can include an eyelet **5234**.

[0254] With reference next to **Figure 85**, anchoring feature **5300** is illustrated. The anchoring feature **5300** can be attached to a frame body (not shown) via one or more struts **5310**. The anchoring feature **5300** can include one or more prongs **5320, 5330, 5340** having tips **5222, 5232, 5342**.

[0255] The first prong **5320**, the second prong **5320**, and/or the third prong **5340** can be radially offset. As shown, the first prong **5320** can include a bend **5224** which directs the first prong **5320** radially outward relative to the second prong **5330** such that the tips **5322, 5332** are at different radial positions relative to each other. The third prong **5340** can include a bend **5344** which directs the third prong **5340** radially inward relative to the second prong **5330** such that the tips **5342, 5332** are at different radial positions relative to each other. One or more coverings and/or cushions (not shown) can be attached to the anchoring feature **5300** which covers the tips **5322, 5332, 5342**. The one or more coverings and/or cushions can span the gap between the tips **5222, 5232, 5342** to further increase the tissue contact area of the tips. The coverings and/or cushions can include the same or similar structure to those described herein. For example, the coverings and/or cushions can be formed from a foam material, woven or knitted cloth or sheet, and/or an insert. While the tips **5322, 5332, 5342** are shown at or around the same axial position, it is to be understood that the tips **5322, 5332, 5342** can be axially offset.

[0256] With reference next to **Figures 86-99**, embodiments of anchoring features **5400, 5500, 5600, 5700** are illustrated. The anchoring features **5400, 5500, 5600, 5700** can transition between a crimped or collapsed configuration and an expanded configuration. In the collapsed configuration, the anchoring features **5400, 5500, 5600, 5700** can have a reduced crimp profile to facilitate delivery to a target location. In the expanded configuration, the anchoring features **5400, 5500, 5600, 5700** can increase in size which can advantageously increase the tissue contact area of the anchoring features **5400, 5500, 5600, 5700**. This increased tissue contact area can beneficially reduce the stress applied by the anchoring features **5400, 5500, 5600, 5700** to tissue thereby reducing the amount of pressure and potential for trauma to the tissue.

[0257] With reference first to **Figures 86-90**, anchoring feature **5400** is illustrated. The anchoring feature **5400** can transition between a collapsed configuration

(as shown in **Figures 86 and 87**) and an expanded configuration (as shown in **Figures 88-90**). In transitioning from the collapsed configuration to the expanded configuration, the lateral dimension (or width) of the anchoring feature **5400** can increase.

[0258] The anchoring feature **5400** can be attached to a frame body (not shown) via one or more struts **5410**. The anchoring feature **5400** can include one or more prongs **5420, 5430** having tips **5422, 5432**. As shown in the illustrated embodiment, the anchoring feature **5400** can have a looped profile similar to other anchoring features described herein. The first prong **5420** and the second prong **5430** can be radially offset such that the tip **5422** of first prong **5420** is radially outward relative to the tip **5432** of the second prong **5430**. This can allow the tips **5422, 5432** to slide relative to each other when transitioning between the collapsed configuration and the expanded configuration. As shown, the tips **5422, 5432** can form a relatively flat surface of the anchoring feature **5400**; however, it is to be understood that the tips **5422, 5432** can take on a more rounded shape similar to other anchoring features described herein. Moreover, while the tips **5422, 5432** are shown at or around the same axial position, it is to be understood that the tips **5422, 5432** can be axially offset. One or more cushions (not shown) can be attached to the anchoring feature **5400** which cover the tips **5422, 5432**.

[0259] With reference next to **Figures 91 and 92**, anchoring feature **5500** is illustrated. The anchoring feature **5500** can transition between a collapsed configuration (as shown in **Figure 91**) and an expanded configuration (as shown in **Figure 92**). In transitioning from the collapsed configuration to the expanded configuration, the lateral dimension (or width) of the anchoring feature **5500** can increase.

[0260] The anchoring feature **5500** can be attached to a frame body (not shown) via one or more struts **5510**. The anchoring feature **5500** can include one or more prongs **5520, 5530** having tips **5522, 5532**. In the expanded configuration, the first prong **5520** and the second prong **5530** can be laterally offset such that a gap exists between tips **5522, 5532** of the prongs **5520, 5530**. One or more coverings and/or cushions (not shown) can be attached to the anchoring feature **5500** which cover the tips **5522, 5532**. The one or more coverings and/or cushions can span the gap between the tips **5522, 5532** to further increase the tissue contact area of the tips. The coverings

and/or cushions can include the same or similar structure to those described herein. For example, the coverings and/or cushions can be formed from a foam material, woven or knitted cloth or sheet, and/or an insert. While the tips **5522**, **5532** are shown at or around the same axial position, it is to be understood that the tips **5522**, **5532** can be axially offset.

[0261] With reference next to **Figures 93 and 94**, anchoring feature **5600** is illustrated. The anchoring feature **5600** can transition between a collapsed configuration (as shown in **Figure 93**) and an expanded configuration (as shown in **Figure 94**). In transitioning from the collapsed configuration to the expanded configuration, the lateral dimension (or width) of the anchoring feature **5600** can increase.

[0262] The anchoring feature **5600** can be attached to a frame body (not shown) via one or more struts **5610**. The anchoring feature **5600** can include one or more prongs **5620**, **5630** having tips **5622**, **5632**. As shown in the illustrated embodiment, the anchoring feature **5600** can have a generally looped profile similar to other anchoring features described herein. The first prong **5620** and the second prong **5630** can be axially offset such that the tip **5622** of first prong **5620** is positioned above tip **5632** of the second prong **5630**. This can allow the tips **5622**, **5632** to slide relative to each other when transitioning between the collapsed configuration and the expanded configuration. The tips **5622**, **5632** can be at or around the same radial position. One or more coverings and/or cushions (not shown) can be attached to the anchoring feature **5600** which cover the tips **5622**, **5632**. The one or more coverings and/or cushions can span the axial offset between the tips **5622**, **5632** to further increase the tissue contact area of the anchoring feature **5600**. The coverings and/or cushions can include the same or similar structure to those described herein. For example, the coverings and/or cushions can be formed from a foam material, woven or knitted cloth or sheet, and/or an insert.

[0263] With reference next to **Figures 95-99**, anchoring feature **5700** is illustrated. The anchoring feature **5700** can transition between a collapsed configuration (as shown in **Figures 95 and 96**) and an expanded configuration (as shown in **Figures 97-99**). In transitioning from the collapsed configuration to the expanded configuration,

the lateral dimension (or width) and/or a radial offset of the anchoring feature **5700** can increase.

[0264] The anchoring feature **5700** can be attached to a frame body (not shown) via one or more struts **5710**. The anchoring feature **5700** can include one or more prongs **5720**, **5730** having tips **5722**, **5732**. As shown in the illustrated embodiment, the tips **5722**, **5732** can form an enlarged, looped shape. By increasing the area of contact between the tips **5722**, **5732**, the enlarged looped shape can reduce the likelihood that the tips **5722**, **5732** are improperly aligned prior to crimping. For example, the enlarged loop shape can reduce the likelihood that the tips **5722**, **5732** are in the same radial plane prior to crimping. It is to be understood that the tips **5722**, **5732** can form other shapes such as those described in connection with other anchoring features described herein.

[0265] The first prong **5720** and the second prong **5730** can be radially offset such that the tip **5722** of first prong **5720** is radially outward relative to the tip **5732** of the second prong **5730**. This can allow the tips **5722**, **5732** to slide relative to each other when transitioning between the collapsed configuration and the expanded configuration. As shown, the tips **5722**, **5732** can form a relatively flat surface of the anchoring feature **5700**; however, it is to be understood that the tips **5722**, **5732** can take on a more rounded shape similar to other anchoring features described herein. Moreover, while the tips **5722**, **5732** are shown at or around the same axial position, it is to be understood that the tips **5722**, **5732** can be axially offset. One or more coverings and/or cushions (not shown) can be attached to the anchoring feature **5700** which cover the tips **5722**, **5732**. The one or more coverings and/or cushions can span the radial offset and/or lateral offset between the tips **5722**, **5732** to further increase the tissue contact area of the anchoring feature **5700**. The coverings and/or cushions can include the same or similar structure to those described herein. For example, the coverings and/or cushions can be formed from a foam material, woven or knitted cloth or sheet, and/or an insert.

[0266] With reference next to **Figures 100-106**, anchoring feature **5800** is illustrated. The anchoring feature **5800** can include a base anchor **5810** to which one or more additional components, such as inserts **5820**, can be attached. As shown in the illustrated embodiment, the insert **5820** can extend radially outward relative to the base

anchor **5810** when the frame (not shown) is in an expanded configuration; however, it is to be understood that the insert **5820** can extend in other directions relative to the base anchor **5810**. For example, the insert **5820** can extend in directions including, but not limited to, radially inward, laterally, and/or axially relative to the base anchor **5810**.

[0267] In some embodiments, the base anchor **5810** can be attached to a frame body (not shown) of the replacement valve. For example, the base anchor **5810** can be unitarily formed with the frame body similar to other anchoring features described herein. In some instances, the base anchor **5810** can be unitarily formed with the frame body via laser-cutting a single tube. The insert **5820** can be formed separately from the base anchor **5810** and attached using any of the fasteners and techniques described herein, such as via sutures, welding, adhesives, and/or a snap-fit, such as via connectors **5826**, **5828** described below. As will be described in further detail below, the insert **5820** can increase the tissue contact area of the anchoring feature **5800**.

[0268] The anchoring feature **5800** can be attached to a frame body via one or more struts **5812** of the base anchor **5810**. The base anchor **5810** can include a strut forming a portion of the tip **5830** of the anchoring feature **5800**. As shown, the tip **5830** can have a looped shape which forms a hole or aperture **5816**. In some implementations, the insert **5820** can be positioned at least partially within the hole or aperture **5816**.

[0269] The insert **5820** can include a rib **5822** and a platform **5824**. The insert **5820** may also include one or more connectors **5826**, **5828**. The rib **5822** can extend generally axially and radially when the insert **5820** is attached to the base anchor **5810**. The rib **5822** can beneficially support other portions of the insert **5820** at least when the insert **5820** is subject to an axial load. As shown, the rib **5822** can have an arcuate shape when viewed from a side profile. The arcuate shape can reduce the likelihood of the rib **5822** catching onto to native anatomy, such as chordae tendineae when the anchoring feature **5800** is positioned at a target location.

[0270] The platform **5824** can form a contact surface for native anatomy, such as a ventricular side of the native mitral valve annulus. As shown, the platform **5824** can extend laterally outward relative to the base anchor **5810** and/or the rib **5822**. The platform **5824** can form a generally planar surface. By increasing the lateral extent of the platform **5824**, the tissue contact area of the anchoring feature **5800** can be

significantly increased. This increased tissue contact area can beneficially reduce the stress applied by the anchoring feature **5800** to tissue thereby reducing the amount of pressure and potential for trauma to the tissue.

[0271] In some embodiments, the insert **5820** can include one or more connectors **5826**, **5828**. The connectors **5826**, **5828** can be used to facilitate coupling of the insert **5820** to the base anchor **5810**. In some embodiments, the one or more connectors **5826**, **5828** can snap fit into openings of the base anchor **5810**. For example, one or more complementary openings (not shown) can be formed along the strut within the hole or aperture **5816** of the base anchor **5810**. In some embodiments, the one or more connectors **5826**, **5828** can extend across the hole or aperture **5816** and clamp onto an opposite side of the base anchor **5810**. However, it is to be understood that the one or more connectors **5826**, **5828** can be omitted.

[0272] Use of separate components can beneficially allow for localized control over performance characteristics of the anchoring feature **5800**. In some embodiments, the base anchor **5810** can be formed from a relatively rigid material and the insert **5820** can be formed from another material which may be more compliant than the material used for the base anchor **5810**. This can increase the strength of the base anchor **5810** to allow the base anchor **5810** to resist loads imposed on the anchoring feature **5800** while in use. The compliancy of the insert **5820** can better conform to the native anatomy to enhance the tissue contact area and reduce the potential for trauma to tissue of the native anatomy. In some embodiments, the base anchor **5810** can be formed from a metal, such as nitinol, and the insert **5820** can be formed from a softer metal or plastic. The insert **5820** can have a cushion-like structure similar to other cushions described herein. For example, the insert **5820** can be formed at least partially from a foam material. This can beneficially enhance the compliancy of the insert **5820** and allow the insert **5820** to better conform to native anatomy. In some embodiments, at least the platform **5824** is formed from a foam material. As another example, at least the insert **5820** can be formed from a material that facilitates tissue ingrowth or formation. This can further enhance securement of the anchoring feature **5800** to tissue of the native anatomy.



[0273] It is to be understood that the base anchor **5810** and the insert **5820** can be formed from the same material. Use of separate components can facilitate manufacture of the anchoring feature **5800**. As noted above, the base anchor **5810** can be unitarily formed with the frame body via laser-cutting a single tube. In such an embodiment, it may be difficult or impossible to form the geometry of the insert **5820**. As such, the insert **5820** can be manufactured via an alternative manufacturing method.

[0274] With reference next to **Figure 107**, a cross-sectional schematic of an embodiment of a delivery system **5900** is illustrated. The delivery system **5900** can include an outer sheath **5910** and an inner sheath or rail **5912**. Two anchoring features **5920**, **5930** are illustrated within the outer sheath **5910** in a crimped or collapsed configuration. Although two anchoring features **5920**, **5930** are shown, it is to be understood that a fewer or greater number of anchoring features can be used. Moreover, although two different anchoring features **5920**, **5930** are illustrated, it is to be understood that the anchoring features can be the same.

[0275] Anchoring feature **5920** can share structures similar to anchoring feature **5800** described above. For example, the anchoring feature **5920** can include a base anchor **5922** and an insert **5924**. In the illustrated embodiment, the insert **5924** of the anchoring feature **5920** extends radially inward relative to the base anchor **5922**. This can more efficiently utilize the available space between the outer sheath **5910** and the inner sheath **5912**. In some embodiments, when the replacement valve is released and transitioned into the expanded configuration, the anchoring feature **5920** can flip around in a manner similar to other anchoring features described herein. In so doing, the insert **5924** can be positioned radially outward relative to the base anchor **5920** similar to anchoring feature **5800**.

[0276] Anchoring feature **5930** can share structures similar to anchoring features **5400**, **5700** described above. For example, the anchoring feature **5930** can include a first prong **5932** and a second prong **5934** which are radially offset relative to each other. In the illustrated embodiment, the first prong **5932** of the anchoring feature **5930** is positioned radially outward of the second prong **5934** and is wider than the second prong **5934**. This can more efficiently utilize the available space between the outer sheath **5910** and the inner sheath **5912**.

[0277] With reference next to **Figure 108**, a portion of an embodiment of a frame **6000** is illustrated. The frame **6000** can include a frame body **6010** having one or more struts forming cells **6012**. The frame **6000** can include an anchoring feature **6020** having a strut **6022** and a tip **6024**. As shown in the illustrated embodiment, the tip **6024** can form a looped shape; however, it is to be understood that the tip **6024** can incorporate any other tip configuration described herein. The strut **6022** can split into two or more struts **6026a**, **6026b** proximate a base or pivot location **6028** between the frame body **6010** and the anchoring feature **6020**. As shown, the strut **6022** can bifurcate into two struts **6026a**, **6026b** which are each connected to struts **6014a**, **6014b** forming part of cells **6012**. The struts **6014a**, **6026a** can be disconnected from struts **6014b**, **6026b** such that the struts **6014a**, **6026a** are movable relative to struts **6014b**, **6026b**.

[0278] This configuration can beneficially reduce strains imposed on the struts **6014a**, **6014b**, **6026a**, **6026b** when the frame **6000** is in a collapsed or crimped configuration and/or when the frame **6000** is subject to fatigue loading. The struts can effectively widen the outflow struts to allow for a greater distribution of strain during crimping and/or during fatigue loading since the struts are separated into two individual members. Moreover, as shown in the illustrated embodiment, the aspect ratio of the anchoring feature **6020** proximate the base or pivot location **6028** is larger than the aspect ratio of the anchoring feature **6020** further distal of the base or pivot location **6028**. This can beneficially reduce resistance to side-loading and/or out-of-plane loading.

[0279] Moreover, in some implementations, localized stresses at the pivot location **6028** can be sufficient to effect at least a partial phase transformation of the material at the pivot location **6028**. For example, in embodiments utilizing nitinol, localized stresses can be sufficient to cause at least partial “martensitic transformation” of nitinol at the pivot location **6028**. This “martensitic transformation” can transform nitinol into the martensite phase from the austenite phase which has different material properties than the austenite phase. For example, nitinol in the austenite phase is less malleable and does not exhibit the same level of elastic deformation characteristics as nitinol in the martensite phase.

[0280] With respect to the geometry illustrated in **Figure 108**, further crimping of the cells **6012** can cause the slot between struts **6026a**, **6026b** to increase in size. In implementations where the nitinol anchor flips from the collapsed configuration to the expanded configuration, this can be particularly advantageous. In such an implementation, when the nitinol anchor is released and allowed to expand while the cells **6012** remain in a compressed configuration, the nitinol anchor can flip to a lesser degree to facilitate positioning of the nitinol anchor between chordae tendineae and/or native leaflets. When such localized stresses at the pivot location **6028** are released, such as by allowing the cells **6012** to expand, material at the pivot location **6028** can revert back to the austenite phase.

[0281] With reference next to **Figures 109-111**, portions of embodiments of frames **6100**, **6200** are illustrated. The frames **6100**, **6200** can include anchoring features **6120**, **6220** with anchors having different lengths. This can allow the anchors to have different heights when the frames **6100**, **6200** are in an expanded configuration. This can be particularly advantageous in situations where the native anatomy is non-planar. For example, the native mitral valve typically has a non-planar, saddle-shape. By better matching the length of the anchoring features **6120**, **6220** with the shape of the native anatomy, the load distribution on frames **6100**, **6200** as well as the native anatomy can be improved.

[0282] With reference first to **Figure 109A**, frame **6100** is illustrated. The frame **6100** can include a frame body **6110** having one or more struts **6012** forming cells (not shown). The frame **6100** can include an anchoring feature **6120** in the form of multiple individual anchors **6122a-e**. As shown in the illustrated embodiment, the individual anchors **6122a-e** can have different lengths. The lengths can be chosen based on the contemplated position of the individual anchors **6122a-e** on the native valve anatomy. For example, short anchors such as anchor **6122b** can be positioned at an anterior or posterior location of the native mitral valve (e.g., the A2 and P2 lobes as shown in **Figure 109B**) whereas longer anchors such as anchor **6122e** can be positioned at or proximate commissures of the native mitral valve (e.g., the A1, A3, P1, or P3 lobes as shown in **Figure 109B**).

[0283] Since certain regions of annular tissue may have greater stiffness than other regions of annular tissue, certain regions of annular tissue may be better suited for anchoring and load transfer. In some embodiments, the strength and/or compliancy of individual anchors **6122a-e** can differ. For example, primary, load-bearing anchors can be stiffer than other anchors. These primary, load-bearing anchors can be designed to engage stiffer tissue at anterior or posterior locations of the native mitral valve. In some implementations, two primary anchors can be positioned behind the native anterior leaflet. Two or three primary anchors can be positioned behind the native posterior leaflet. This can beneficially enhance securement to the native annulus. For example, primary anchors can be positioned at the A1 and A3 lobes of the native anterior leaflet **6130** and/or the P1, P2, and P3 lobes of the native posterior leaflet **6140** (as shown in **Figure 109B**). Moreover, this can beneficially increase the likelihood that at least one anchor extends behind the leaflets. Although four to five primary anchors have been described, it is to be understood that a fewer or greater number of primary anchors can be used. For example, in some embodiments, two to six primary anchors can be utilized.

[0284] Secondary anchors can be more compliant than other anchors. These secondary anchors can interact with more compliant tissue. In some implementations, these secondary anchors can be sized and shaped to isolate and/or immobilize the free edge of a native leaflet. This can beneficially reduce movement of the native leaflet during the cardiac cycle which can, in some instances, advantageously improve tissue ingrowth and/or reduction of paravalvular leakage. In some implementations, secondary anchors can be positioned at the A2 lobe of the native anterior leaflet **6130** and/or the commissures of the native mitral valve. The number of secondary anchors can be chosen to obtain a total number of desired anchors. For example, in embodiments having twelve anchors, the frame **6100** can have five primary anchors and seven secondary anchors. It is to be understood that a fewer or greater number of total anchors may be used as described above (e.g., nine total anchors).

[0285] With reference next to **Figures 110 and 111**, frame **6200** is illustrated. The frame **6200** can include a frame body **6210** having one or more struts forming cells **6212**. The frame **6200** can include an anchoring feature **6220** having one or more anchors **6222a, 6222b**. As shown in the illustrated embodiment, the individual anchors

**6222a**, **6222b** can be adjustable to different heights. The heights can be changed based on the positioning of the individual anchors **6222a**, **6222b** relative to the native valve anatomy such as the native mitral valve annulus **6230**. Individual placement of anchors can advantageously provide the user more controlled deployment of individual anchors. In some embodiments, a slight tug by the operator can be applied after each individual anchor is placed to verify that the anchor is well placed before moving onto the next anchor. In this manner, individual anchors can be more suitably positioned relative to the native valve anatomy. This can advantageously reduce the likelihood that the frame **6200** tilts or rocks during the various cardiac cycles of the patient's heart. Among other benefits, this can reduce the likelihood of paravalvular leakage which may be caused by tilting or rocking of the frame **6200**.

[0286] With reference to **Figure 111**, one or more of the anchors, such as anchor **6222b**, can be attached to the frame body **6210** via one or more connector tabs **6214**, **6216**, **6218**. The connector tabs **6214**, **6216**, **6218** can include apertures through which a strut **6224b** of the anchor **6222b** can be passed. As shown, a first connector tab **6214** can be positioned along a bottom region of a cell **6212**. For example, the first connector tab **6214** can be positioned at or proximate a bottom apex of the cell **6212**. A second connector tab **6216** can be positioned along a top region of a cell **6212**. For example, the second connector tab **6216** can be positioned at or proximate a top apex of the cell **6212**. A third connector tab **6218** can be positioned between the first and second connector tabs **6214**, **6216**.

[0287] In some embodiments, the connector tabs **6214**, **6216**, **6218** can be sized and shaped to retain the anchor **6222b** in position. For example, as shown in the illustrated embodiment, the connector tabs **6216**, **6218** can be biased in a direction which is non-perpendicular to a longitudinal axis of the frame body **6210**. As such, the connector tabs **6216**, **6218** can impose a frictional force on the strut **6224b** which can resist translation of the strut **6224b** relative to the connector tabs **6216**, **6218**. This frictional force is preferably sufficient to resist axially directed forces exerted on the anchor **6222b**. In some embodiments, the connector tabs **6216**, **6218** can allow the anchor **6222b** to move axially in one direction (e.g., proximally) while inhibiting or preventing movement in the opposite direction (e.g., distally). For example, this can

allow the operator to pull on the anchor **6222b** in a proximal direction to shorten the anchor **6222b** while inhibiting the anchor **6222b** from moving distally and elongating during operation in the patient's heart. In some embodiments, the connector tabs **6216**, **6218** can be pinched or squeezed towards each other to reduce this frictional force thereby facilitating adjustment of the length of the anchor **6222b**.

[0288] While the frame **6200** includes connector tabs **6214**, **6216**, **6218**, it is to be understood that other types of connection mechanisms can be used in conjunction with, or in lieu of, connector tabs **6214**, **6216**, **6218**. For example, the frame **6200** can include a ratcheting mechanism which allows the length of the anchors to be reduced while inhibiting or preventing the length of the anchors to be increased. It is to be understood that the tips of the anchoring features **6220** can include any of the features and structures described herein with respect to other anchoring features.

[0289] With reference next to **Figures 112-117**, portions of embodiments of frames **6300**, **6400** are illustrated. The frames **6300**, **6400** can include anchoring features **6320**, **6420** with anchors having struts attached to the frame **6300**, **6400** at two or more locations. This can beneficially enhance the strength of the anchors of the anchoring features **6320**, **6420**.

[0290] With reference first to **Figures 112-114**, a portion of an embodiment of a frame **6300** is illustrated. The frame **6300** can include a frame body **6310** having one or more struts forming cells **6312**. The frame **6300** can include an anchoring feature **6320** having one or more combined anchors **6322**. As shown in the illustrated embodiment, the combined anchors **6322** can be formed from a first strut **6324a** and a second strut **6324b** which can extend from different portions of the frame body **6310**. For example, the first strut **6324a** and the second strut **6324b** can extend from different cells of the frame body **6310**. While the struts **6324a**, **6324b** are spaced apart about one cell length, it is to be understood that this distance can be increased or decreased.

[0291] In the expanded configuration, the tip **6326a** of the first strut **6324a** and the tip **6326b** of the second strut **6324b** can overlap. The overlap between the tips **6326a**, **6326b** can allow forces imposed on the tips **6326a**, **6326b** to be distributed between the two struts **6324a**, **6324b**. This can allow the struts **6324a**, **6324b** to be thinner which can facilitate delivery. For example, the use of thinner struts can facilitate

crimping of the struts for positioning within a delivery system. As another example, the user of thinner struts can allow the struts to more easily pass between chordae tendineae when the frame **6300** is utilized in the native mitral valve and the anchoring feature **6320** is positioned within the left ventricle. As shown, the tips **6326a**, **6326b** overlap such that the tips are generally aligned along a plane passing through a longitudinal axis of the frame **6300**. Moreover, the struts **6324a**, **6324b** can extend towards each other such that the lateral width of the combined anchor **6322** can be reduced. The reduced lateral width of the anchors can allow the combined anchor **6322** to more easily pass between chordae tendineae when the frame **6300** is utilized in the native mitral valve and the anchoring feature **6320** is positioned within the left ventricle.

[0292] In some embodiments, struts **6324a**, **6324b** can be positioned in a non-overlapping manner when the frame **6300** is in a collapsed or crimped configuration. As the frame **6300** transitions to the expanded configuration, the struts **6324a**, **6324b** can shift in position such that the struts overlap. This can beneficially allow the struts **6324a**, **6324b** to extend around chordae tendineae. It is to be understood that the struts **6324a**, **6324b** can be positioned in an overlapping manner when the frame **6300** is in a collapsed or crimped configuration.

[0293] With reference next to **Figures 115-117**, a portion of an embodiment of a frame **6400** is illustrated. The frame **6400** can include a frame body **6410** having one or more struts forming cells **6412**. The frame **6400** can include an anchoring feature **6420** having one or more anchors **6422**. As shown in the illustrated embodiment, the anchors **6422** can be formed from a first strut portion **6424a** and a second strut portion **6424b** which can extend from different portions of the frame body **6410**. For example, the first strut portion **6424a** and the second strut portion **6424b** can extend from different cells of the frame body **6410**. While the struts **6424a**, **6424b** are spaced apart about one cell length, it is to be understood that this distance can be increased or decreased.

[0294] Forces applied to the tip **6426** can be beneficially distributed between the two struts **6424a**, **6424b**. This can allow the struts **6424a**, **6424b** to be thinner which can facilitate delivery. For example, the use of thinner struts can facilitate crimping of the struts for positioning within a delivery system. The strut portions **6424a**, **6424b** can extend towards each other such that the lateral width of the anchor **6422** can be reduced.

The reduced lateral width of the anchors can allow the anchor **6422** to more easily pass between chordae tendineae when the frame **6400** is utilized in the native mitral valve and the anchoring feature **6420** is positioned within the left ventricle.

#### Embodiments of Replacement Valves with Multi-Part Frames

[0295] With reference next to **Figures 118-131**, embodiments of prostheses **6500**, **6600** and frames **6520**, **6620**, **6700**, **6800**, **6900**, **7000**, **7100** are illustrated. The illustrated prostheses **6500**, **6600** and frames **6520**, **6620**, **6700**, **6800**, **6900**, **7000**, **7100** may include components which are self-expanding or balloon expandable. As will be discussed in further detail below, the illustrated prostheses **6500**, **6600** and frames **6520**, **6620**, **6700**, **6800**, **6900**, **7000**, **7100** can include one or more components which are separately formed and subsequently attached. The components can be attached using any of the fasteners and techniques described herein, such as via sutures, welding, and/or adhesives. In some embodiments, the components can be attached in a similar manner to that described in U.S. Publication No. 2016/0310268, published October 27, 2016. The prostheses **6500**, **6600** and frames **6520**, **6620**, **6700**, **6800**, **6900**, **7000**, **7100** as well as other prostheses described herein, may be replacement valves that can be designed to replace a damaged or diseased native heart valve such as a mitral valve, as discussed above. It should be understood that the prostheses **6500**, **6600** and frames **6520**, **6620**, **6700**, **6800**, **6900**, **7000**, **7100** as well as other prostheses described herein, are not limited to being a replacement valve.

[0296] With reference first to **Figures 118 and 119**, the prosthesis **6500** can include a frame **6520**, a valve body **6540**, and a skirt **6560**. The prosthesis **6500** can transition between an expanded configuration (shown in **Figure 118**) and a collapsed or crimped configuration (shown in **Figure 119**). The prosthesis **6500** can incorporate features and concepts which are the same as, or at least similar to, those of other frames described herein such as, but not limited to, prosthesis **100** described above in connection with **Figure 1**. It is to be understood that structures, features, and/or functionality of the components described in connection with prosthesis **100** may be applicable to those described in connection with prosthesis **6500**.



[0297] As shown in the illustrated embodiment, the frame **6520** can include a frame body **6522a**, a first anchoring feature **6524**, and a second anchoring feature **6526**. As shown in the illustrated embodiment, the frame body **6522a** includes an upper region **6527**, an intermediate region **6528**, and a lower region **6529**. The intermediate region **6528** can have a larger diameter than the upper region **6527** and/or the lower region **6529**. In some embodiments, the frame **6520** can be oriented such that the upper region **6527** is a proximal or inflow portion and the lower region **6529** is a distal or outflow portion. The frame **6520** can be formed from many different materials, including metals, such as Nitinol.

[0298] The frame **6520** is preferably formed from a plurality of struts forming open cells. As will be discussed in further detail below, components of the frame **6520**, such as the frame body **6522a**, the first anchoring feature **6524**, and/or the second anchoring feature **6526**, can be used to attach or secure the prosthesis **6500** to a native valve. For example, the frame body **6522a** and the second anchoring feature **6526** can be used to attach or secure the prosthesis **6500** to a native valve, such as a native mitral valve. Although the frame **6520** has been described as including a frame body **6522a**, a first anchoring feature **6524**, and a second anchoring feature **6526**, it is to be understood that the frame **6520** need not include all components. For example, in some embodiments, the frame **6520** can include the frame body **6522a** and the second anchoring feature **6526** while omitting the first anchoring feature **6524**.

[0299] With continued reference to **Figures 118 and 119**, one or more components of the frame **6520** can be formed separately from each other. This can beneficially allow the performance of the frame **6520** to be more precisely tuned for desired characteristics and uses. As shown in the illustrated embodiment, the frame body **6522a**, the first anchoring feature **6524**, and/or a supplemental frame **6522b** can be formed separately from each other and subsequently attached. The frame body **6522a**, the first anchoring feature **6524**, and/or the supplemental frame **6522b** can be attached using any of the fasteners and techniques described herein, such as via sutures, welding, and/or adhesives. In some embodiments, the frame body **6522a**, the first anchoring feature **6524**, and/or a supplemental frame **6522b** can be delivered to the native valve separately from the frame **6520**.

[0300] Use of separate components can beneficially allow for localized control over performance characteristics of the frame **6520**. For example, the supplemental frame **6522b** can locally reinforce a portion of the frame body **6522a** by effectively increasing the wall thickness of the frame body **6522a**. As shown, the supplemental frame **6522b** can be positioned proximate a lower region **6529** of the frame **6520**. In some implementations, such as those in which the replacement valve **6500** is used in a native mitral valve, the lower region **6529** of the frame **6520** can be subject to more stresses than the upper region **6527** of the frame **6520**. By locally reinforcing portions of the frame body **6522a** subject to greater stresses, the wall thickness in other portions of the frame **6520** which are subject to lower stresses can be remain thinner. This can allow other desirable characteristics, such as crimp diameter, to be generally maintained.

[0301] Moreover, as will be discussed in further detail below, use of separate components can allow different geometries to exist along different “layers” of the frame **6520**. As shown in **Figure 119**, the frame **6520** can have a multi-layer construction with supplemental frame **6522b** forming an inner layer, frame body **6522a** forming an intermediate layer, and/or first anchoring feature **6524** forming an outer layer. In this manner, supplemental frame **6522b**, frame body **6522a**, and/or first anchoring feature **6524** can be located in different circumferential planes. This can beneficially disassociate at least some impact of the various components on each other when the frame **6520** is in a crimped or collapsed configuration. This can advantageously reduce the crimp diameter of the frame **6520** since the components of frame **6520** crimp “in parallel” (i.e., along different planes) as compared to “in series” (i.e., within the same plane). Moreover, this can advantageously reduce the crimp length of the frame **6520** since the frame **6520** need not be designed to accommodate “in series” crimping of the anchoring features thereby allowing the frame **6520** to be made more compact.

[0302] As noted above, the frame components can be attached to each other using any of the fasteners and techniques described herein, such as via sutures, welding, and/or adhesives. In some implementations, the frame components can be attached in such a manner that some degree of movement may occur between the frame components. For example, in embodiments where the frame components are sutured together, the

frame components may be capable of sliding relative to other frame components. This can beneficially reduce the effects each frame component has on each other during crimping. For example, this can allow the frame components to crimp together at the same or similar rate such that the frame components have about the same or similar strains.

[0303] With continued reference to the prosthesis **6500** illustrated in **Figures 118 and 119**, the valve body **6540** is attached to the frame **6520** within an interior of the frame **6520**. The valve body **6540** functions as a one-way valve to allow blood flow in a first direction through the valve body **6540** and inhibit blood flow in a second direction through the valve body **6540**. For example, in embodiments where the upper region **6527** is a proximal portion and the lower region **6529** is a distal portion, the valve body **6540** can allow blood flow in a proximal-to-distal direction and inhibit blood flow in a distal-to-proximal direction. The valve body **6540** preferably includes a plurality of valve leaflets **6542**, for example three leaflets **6542**, which are joined at commissures. As will be discussed in further detail below in connection with additional figures, the valve body **6540** can include one or more intermediate components **6544**. The intermediate components **6544** can be positioned between a portion of, or the entirety of, the leaflets **6542** and the frame **6520** such that at least a portion of the leaflets **6542** are coupled to the frame **6520** via the intermediate component **6544**. In this manner, a portion of, or the entirety of, the portion of the valve leaflets **6542** at the commissures and/or an arcuate edge of the valve leaflets **6542** are not directly coupled or attached to the frame **6520** and are indirectly coupled or “float” within the frame **6520**.

[0304] Although the valve body **6540** has been described as including a plurality of leaflets **6542** and one or more intermediate components **6544**, it is to be understood that the valve body **6540** need not include all features. For example, the valve body **6540** can include the plurality of valve leaflets **6542** while omitting the intermediate components **6544**. In some embodiments, the valve leaflets **6542** can be directly attached to the frame **6520**.

[0305] With continued reference the prosthesis **6500** illustrated in **Figures 118 and 119**, the skirt **6560** can be attached to the frame **6520**. The skirt **6560** can be positioned around and secured to an exterior of the frame **6520**. The skirt **6560** can be

annular and can extend entirely circumferentially around the frame **6520**. The skirt **6560** can prevent or inhibit backflow of fluids, such as blood, around the prosthesis **6500**. For example, with the skirt **6560** positioned annularly around an exterior of the frame **6520**, the skirt **6560** can create an axial barrier to fluid flow exterior to the frame **6520** when deployed within a body cavity such as a native valve annulus. The skirt **6560** can encourage tissue in-growth between the skirt **6560** and the natural tissue of the body cavity. This may further help to prevent leakage of blood flow around the prosthesis **6500** and can provide further securement of the prosthesis **6500** to the body cavity. In some embodiments, the skirt **6560** can be loosely attached to the exterior of the frame **6520**. In some embodiments, the skirt **6560** can be tautly secured around the frame **6520**. As shown in the illustrated embodiment, the skirt **6560** can extend along at least a portion of the second anchoring feature **6526**. In some implementations, this can allow the skirt **6560** to form a flange along a lower region **6529** of the frame **6520** when the frame **6500** is in an expanded configuration. This can beneficially enhance sealing along the lower region **6529** of the frame **6520**.

[0306] As shown, the shape of the frame **6520**, in conjunction with the shape of the leaflets **6542** and intermediate components **6544**, can beneficially enhance hemodynamic performance. For example, the shape of the frame **6520** with a larger intermediate region **6520** can allow for increased motion of the leaflets **6542** when transitioning between systole and diastole. This increased motion can help push or pull blood into and out of the region between the leaflets **6542** and the frame **6520** thereby increasing flow in the region. Moreover, the shape of the frame **6520**, in conjunction with the shape of the leaflets **6542** and intermediate components **6544**, can allow for significant washout on an underside of the valve body **6540**. That is, the shape of the frame **6520**, in conjunction with the shape of the leaflets **6542** and intermediate components **6544**, can enhance the exchange of blood from a prior cardiac cycle – which may have stagnated and accumulated in crevices, pockets, and/or surfaces of the frame **6520**, valve **6540**, and/or skirt **6560** – with fresh blood from a current cardiac cycle.

[0307] As shown, the connection between the frame **6520** and the intermediate component **6544** can be greater than 90°. Preferably, the connection between the frame **6520** and the intermediate component **6544** can be generally aligned

when the leaflets **6542** such that the intermediate component **6544** forms a tangent surface with the frame **6520**. That is, the connection between the frame **6520** and the intermediate component **6544** can be about  $180^\circ$  when the leaflets are in a closed position (e.g., during systole). In some implementations, the angle  $\theta$  of the connection between the frame **6520** and the intermediate component **6544** can be between about  $160^\circ$  to about  $185^\circ$ , between about  $140^\circ$  to about  $190^\circ$ , between about  $120^\circ$  to about  $195^\circ$ , any sub-ranges within these ranges, or other angles as desired, when the leaflets **6542** are in a closed position. This tangent surface can enhance flow over the underside of the leaflets **6542** and/or intermediate components **6544** during systole. Moreover, the increased radius of curvature can reduce flow resistance and regions where flow could stagnate and initiate thrombus formation. In some embodiments, the radius of curvature can be about 15mm, between about 12mm to about 20mm, between about 8mm to about 25mm, between about 5mm to about 30mm, any sub-ranges within these ranges, or other radii as desired, when the leaflets **6542** are in a closed position.

[0308] Although the prosthesis **6500** has been described as including a frame **6520**, a valve body **6540**, and a skirt **6560**, it is to be understood that the prosthesis **6500** need not include all components. For example, in some embodiments, the prosthesis **6500** can include only the frame **6520** and the valve body **6540** while omitting the skirt **6560**.

[0309] With reference next to the prosthesis **6600** illustrated in **Figures 120 and 121**, the prosthesis **6600** can include a frame **6620**, a valve body **6640**, and a skirt **6660**. The frame **6620** can be self-expanding or balloon expandable. As shown in the illustrated embodiment, the frame **6620** can include a frame body **6622a** formed from a plurality of struts defining a plurality of cells **6624**. One or more of the cells **6624** can allow the frame **6620** to longitudinally foreshorten when the frame **6620** radially expands.

[0310] The frame **6620** can include a first anchoring feature **6626** and a second anchoring feature **6628**. As shown, the first anchoring feature **6626** can be formed from a plurality of individual anchors extending from the frame body **6622a** in a direction radially outward from a longitudinal axis of the frame **6620** and/or in a direction generally toward a lower end of the frame **6620**. As shown in the illustrated

embodiment, the first anchoring feature **6626** can include twelve individual anchors; however, it is to be understood that a greater number or lesser number of individual anchors can be used. For example, the number of individual anchors can be chosen as a multiple of the number of commissures for the valve body **6640**. As such, for a prosthesis **6600** with a valve body **6640** having three commissures, the first anchoring feature **6626** can have three individual anchors, six individual anchors, nine individual anchors, twelve individual anchors, fifteen individual anchors, or any other multiple of three. It is to be understood that the number of individual anchors need not correspond to the number of commissures of the valve body **6640**.

[0311] As shown in the illustrated embodiment, the first anchoring feature **6626** can be formed separately from the frame body **6622a**. The first anchoring feature **6626** can include structures which generally match that of the frame body **6622a**. For example, the first anchoring feature **6626** can include a plurality of struts **6627** forming cells which generally match the shape of the struts **6623a** and/or cells of the frame body **6622a**. This can allow at least some of the struts **6627** of the first anchoring feature **6626** to be aligned with struts **6623a** of the frame body **6622a**. This can beneficially facilitate attachment of the first anchoring feature **6626** to the frame body **6622a**. The first anchoring feature **6626** can also include one or more struts **6628** which include tips **6629** in the form of eyelets. The one or more struts **6628** can extend radially outwardly and/or downwardly. As shown, sutures **6630** can wrap around struts **6627** of the first anchoring feature **6626** and struts **6623a** of the frame body **6622a** to couple the first anchoring feature **6626** and the frame body **6622a** together; however, it is to be understood that other attachment mechanisms can be used such as those described herein including, but not limited to, welding and adhesives.

[0312] As shown, the second anchoring feature **6632** can be formed from a plurality of individual anchors extending from the frame body **6622a** in a direction radially toward the longitudinal axis of the frame **6620** and bent to extend in a direction radially outward from the longitudinal axis of the frame **6620**. A portion of the individual anchors, such as tips or ends **6633**, can extend in a direction generally toward an upper end of the frame **6320**. The individual anchors of the second anchoring feature **6632** can include tips or ends **6633** having covers and/or cushions as shown. In some

embodiments, the tips or ends **6633** can be enlarged relative to the preceding portion of the second anchoring feature **6632**, such as a strut. The covers and/or cushions can reduce pressure applied to tissue of the body cavity, such as the native valve annulus, when the tips or ends **6633** contact the native valve annulus. As shown in the illustrated embodiment, the second anchoring feature **6632** can include twelve individual anchors; however, it is to be understood that a greater number or lesser number of individual anchors can be used. For example, the number of individual anchors can be chosen as a multiple of the number of commissures for the valve body **6640**. As such, for a prosthesis **6600** with a valve body **6640** having three commissures, the second anchoring feature **6632** can have three individual anchors, six individual anchors, nine individual anchors, twelve individual anchors, fifteen individual anchors, or any other multiple of three. It is to be understood that the number of individual anchors need not correspond to the number of commissures of the valve body **6640**.

[0313] The frame **6620** preferably includes a set of locking tabs **6634** extending from the frame body **6622a** at its upper end. As shown, the frame **6620** includes twelve locking tabs **6634**, however, it is to be understood that a greater number or lesser number of locking tabs can be used. The locking tabs **6634** can extend generally upwardly from the frame body **6622a** in a direction generally aligned with the longitudinal axis of the frame **6620**. The locking tab **6634** can include an enlarged head or end **6635**. As shown, the enlarged head or end **6636** has a semi-circular or semi-elliptical shape forming a “mushroom” shape with the remaining portion of the locking tab **6634**. The locking tab **6634** can include an eyelet which can be positioned through the enlarged head **6635**. It is to be understood that the locking tab **6635** can include an eyelet at other locations, or can include more than a single eyelet. The locking tab **6634** can be advantageously used with multiple types of delivery systems such as a “slot-based” delivery system and/or a “tether-based” delivery system.

[0314] As shown in **Figure 121**, the frame **6620** can include a supplemental frame **6622b** which can be used to reinforce portions of the frame body **6622a**. The supplemental frame **6622b** can be formed separately from the frame body **6622a**. The supplemental frame **6622b** can include structures which generally match that of the frame body **6622a**. For example, the supplemental frame **6622b** can include a plurality

of struts **6623b** forming cells which generally match the shape of the struts **6623a** and/or cells of the frame body **6622a**. This can allow at least some of the struts **6623b** of the supplemental frame **6622b** to be aligned with struts **6623a** of the frame body **6622a**. This can beneficially facilitate attachment of the supplemental frame **6622b** to the frame body **6622a**. As shown, the supplemental frame **6622b** can extend along the entire circumferential periphery of the frame body **6622a** (e.g., a loop); however, it is to be understood that the supplemental frame **6622b** can extend along only a portion of the circumferential periphery of the frame body (e.g., an arc segment).

[0315] The supplemental frame **6622b** can include struts which extend further below struts forming the frame body **6622a**. This can beneficially increase the area to which the valve body **6640** can be attached to the frame **6620**. For example, the valve body **6640** can be attached to portions of the supplemental frame **6622b** extending below the frame body **6622a**. In some implementations, the size of the supplemental frame **6622b** can be chosen based on the type of valve body **6640** being used. For example, in some embodiments, the supplemental frame **6622b** may not extend below the frame body **6622a**. As shown, sutures **6631** can wrap around struts **6623b** of the supplemental frame **6622b** and struts **6623a** of the frame body **6622a** to couple the first supplemental frame **6622b** and the frame body **6622a** together; however, it is to be understood that other attachment mechanisms can be used such as those described herein including, but not limited to, welding and adhesives.

[0316] With continued reference to the prosthesis **6600** illustrated in **Figures 120 and 121**, the valve body **6640** preferably includes a plurality of valve leaflets **6642**. The valve body **6640** can include one or more intermediate components such as first intermediate component **6644** and second intermediate component **6646**. The valve leaflet **6642** can be similar to leaflet **1110** illustrated in **Figure 19A** which includes a first edge **1112**, a second edge **1114**, and tabs **1116**. The plurality of valve leaflets **6642** can function in a manner similar to the native mitral valve, or to any other valves in the vascular system as desired. As shown in the illustrated embodiment, a portion of the valve body is attached to the supplemental frame **6622b**.

[0317] The skirt **6660** can be loosely attached to the exterior of the frame **6620**. The skirt **6660** can be formed from one or more components. As shown, the skirt



**6660** can extend from an upper region of the frame **6620** towards a lower region of the frame **6620**. An upper portion of the skirt **6660** can extend between the frame body **6622a** and the first anchoring feature **6626**. The lower portion of the skirt **6660** can extend distally towards the second anchoring feature **6632**. As shown, the lower portion of the skirt **6660** can extend around anchors of the second anchoring feature **6632** can form a flange **6662**. This can beneficially enhance sealing along the lower region of the frame **6600**. The skirt **260** can be formed from a variety of materials, such as a knit polyester (e.g., polyethylene terephthalate (PET)) or any other biocompatible material.

[0318] As shown in the illustrated embodiment, the skirt **6660** can be attached at or proximate the upper end of the frame **6620** and at or proximate the lower end of the frame **6620**. The skirt **6660** can be formed with sufficient material such that a portion of the skirt **6660** positioned around a middle portion of the frame **6620** is loose relative to an exterior of the frame **6620**.

[0319] With reference next to the frame **6700** illustrated in **Figures 122 and 123**, the frame **6700** is shown in an expanded configuration. The frame **6700** can include a frame body **6702a** and a supplemental frame **6702b**. The frame **6700** can have an upper region **6710**, an intermediate region **6720**, and a lower region **6730**. A longitudinal axis of the frame **6700** may be defined as the central axis that extends through the center of the frame **6700** between the upper and lower ends of the frame **6700**. In some embodiments, the frame **6700** may be oriented such that the upper region **6710** is a proximal portion and the lower region **6730** is a distal portion. The frame **6700** can include an anchoring feature **6740** positioned at the intermediate region **6720** and/or lower region **6730**. In some embodiments, the frame **6700** may be oriented such that the anchoring feature **6740** is a distal anchoring feature. It is to be understood that the frame **6700** can include other anchoring features. For example, the frame **6700** can include an anchoring feature positioned above the anchoring feature **6740** which can be a proximal anchoring feature.

[0320] Anchoring feature **6740** can contact or engage a native valve annulus, such as the native mitral valve annulus, tissue beyond the native valve annulus, native leaflets, and/or other tissue at or around the implantation location during one or more phases of the cardiac cycle, such as systole and/or diastole. For example, when the frame

**6700** is used for a replacement mitral valve prosthesis, during at least systole, in some embodiments the anchoring feature **6740** is sized to contact or engage the native mitral valve annulus. While the anchoring feature **6740** has been illustrated as extending from between the intermediate and lower regions **6730** of the frame **6700**, it is to be understood that the anchoring feature **6740** can be positioned along any other portion of the frame **6700** as desired.

[0321] As shown, the frame body **6702a** and/or the supplemental frame **6702b**, when in an expanded configuration such as in a fully expanded configuration, has a bulbous or slightly bulbous shape, with an intermediate region **6720** being larger than the upper region **6710** and the lower region **6730**. The bulbous shape of the frame body **6702** can advantageously allow the frame body **6702** to engage a native valve annulus or other body cavity, while spacing the inlet and outlet from the heart or vessel wall. This can advantageously reduce undesired contact between the prosthesis and the heart or vessel, such as the atrial and ventricular walls of the heart.

[0322] As shown in the illustrated embodiment, the intermediate region **6720** is preferably cylindrical or generally cylindrical in shape such that a diameter of an upper end of the intermediate region **6720** and/or a diameter of a lower end of the intermediate region **6720** is equal or generally equal to the diameter of a middle portion of the intermediate region **6720**. The general uniformity of the diameter of the intermediate region **6720** from the upper end to the lower end, in conjunction with the axial dimension between the upper end and the lower end (i.e., the “height” of the intermediate region **6720**), provides for a significantly large circumferential area upon which a native valve annulus, or other body cavity, can be engaged. Although the frame body **6702**, such as the intermediate portion **6702**, has been described and illustrated as being cylindrical, it is to be understood that all or a portion of the frame body **6702** can be have a non-circular cross-section such as, but not limited to, a D-shape, an oval or an otherwise ovoid cross-sectional shape.

[0323] In some embodiments, the diameter of the upper end of the intermediate region **6720** and the lower end of the intermediate region **6720** can be about the same. However, it is to be understood that the diameter of the upper end of the intermediate region **6720** and the lower end of the intermediate region **6720** can differ.

[0324] With continued reference to the frame **6700** illustrated in **Figures 122 and 123**, at the juncture between the intermediate region **6720** and the upper region **6710**, the frame body **6702a** can include a bend **6712**. The bend **6712** can be a radially inward bend towards the longitudinal axis of the frame **6700** such that a portion of the upper region **6710**, extending upwardly from the beginning of bend **6712** adjacent the intermediate region **6720**, is inclined or curved towards the longitudinal axis of the frame **6700**. The radially inward inclination of the upper region **6710** can allow for a substantial decrease in radial dimension over a relatively small axial dimension. The greater the degree of inclination, the greater the decrease in radial dimension per increase in axial dimension. This can beneficially provide a relatively compact form factor for the frame **6700**.

[0325] As shown in the illustrated embodiment, the diameter of the upper end of the upper region **6710** can be less than the diameter of the lower end of the lower region **6730**. However, it should be understood that the diameter of the upper end of the upper region **6710** can be the same as, or greater than, the diameter of the lower end of the lower region **6730**. Moreover, in some embodiments, the frame **6700** may not have a bulbous portion, and can have substantially the same outer dimension along its entire length (e.g., cylindrical).

[0326] With continued reference to the frame **6700** illustrated in **Figures 122 and 123**, the frame body **6702a** can include a plurality of struts with at least some of the struts forming cells **6750a**, **6750b**, **6750c**. The supplemental frame **6702b** can include a plurality of struts with at least some of the struts forming cells **6750d**. Any number of configurations of struts can be used, such as rings of undulating struts shown forming ellipses, ovals, rounded polygons, and teardrops, but also chevrons, diamonds, curves, and various other shapes. As shown in the illustrated embodiment, the frame body **6702a** and the supplemental frame **6702b** such that the frame **6700** can include four rows of cells **6750a**, **6750b**, **6750c**, **6750d**. However, it is to be understood that the frame body **6702a** and/or supplemental frame **6702b** can include a fewer or greater number of rows of cells. Moreover, it is to be understood that the frame body **6702a** and supplemental frame **6702b** can be arranged with cells overlapping each other such that

the frame **6700** has fewer rows of cells. For example, cells **6750c** and cells **6750d** can overlap such that the frame **6700** has three rows of cells.

[0327] The cell **6750a** can be formed via a combination of struts. As shown in the illustrated embodiment, the upper portion of cells **6750a** can be formed from a set of circumferentially-expansive struts **6752** having a zig-zag or undulating shape forming a repeating “V” shape. The circumferentially-expansive struts **6752** can be inclined or curved towards a longitudinal axis of the frame **6700** such that an upper portion of the struts **6752** are positioned closer to the longitudinal axis of the frame **6700** than the lower portion of the struts **6752**.

[0328] The lower portion of cells **6750a** can be formed from a set of circumferentially-expansive struts **6754** having a zig-zag or undulating shape forming a repeating “V” shape. As shown in the illustrated embodiment, the struts **6754** can incorporate the bend **6712** such that an upper portion of the struts **6754** are inclined or curved towards the longitudinal axis of the frame **6700** and the lower portion of the struts **6754** extend in a direction generally parallel to the longitudinal axis of the frame **6700**.

[0329] The upper portion of cells **6750b** can be formed from the set of circumferentially-expansive struts **6754** such that cells **6750b** share struts with cells **6750a**. The lower portion of cells **6750b** can be formed from a set of circumferentially-expansive struts **6756**. Circumferentially-expansive struts **6756** can extend generally in a downward direction. As shown in the illustrated embodiment, circumferentially-expansive struts **6756** can form a generally cylindrical portion of the frame **6700** with the upper portion of the struts **6756** having a radial dimension which is about the same as the radial dimension as the lower portion of the struts **6756**.

[0330] The upper portion of cells **6750c** can be formed from the set of circumferentially-expansive struts **6756** such that cells **6750c** share struts with cells **6750b**. The lower portion of cells **6750c** can be formed from a set of circumferentially-expansive struts **6758** having a zig-zag or undulating shape forming a repeating “V” shape. Circumferentially-expansive struts **6758** can extend generally in a downward direction. As shown in the illustrated embodiment, circumferentially-expansive struts **6758** can be slightly inclined or curved towards the longitudinal axis of the frame **6700**.

[0331] The upper portion of cells **6750d** can be formed from the set of circumferentially-expansible struts **6760** having a zig-zag or undulating shape forming a repeating “V” shape. The lower portion of cells **6750d** can be formed from a set of circumferentially-expansible struts **6762** having a zig-zag or undulating shape forming a repeating “V” shape. Circumferentially-expansible struts **6762** can extend generally in a downward direction. As shown in the illustrated embodiment, circumferentially-expansible struts **6762** can be slightly inclined or curved towards the longitudinal axis of the frame **6700**.

[0332] As shown in the illustrated embodiment, struts **6752**, **6754**, **6756**, **6758** can be monolithically or unitarily formed and define at least a portion of the frame body **6702a**. Struts **6760**, **6762** can be monolithically or unitarily formed and define at least a portion of the supplemental frame **6702b**. The struts **6758** of the frame body **6702a** and the struts **6760** of the supplemental frame **6702b** can have the same general size and shape. Accordingly, when aligned together, the struts **6758**, **6760** can form a “combined” strut with the combined wall thicknesses of the struts **6758**, **6760**. This can beneficially enhance the structural rigidity of the frame **6700** along the combined strut formed by struts **6758**, **6760**. The struts **6758**, **6760** can be attached using sutures **6764** as shown; however, it is to be understood that the struts **6758**, **6760** can be attached using any of the fasteners and techniques described herein, such as via welding and/or adhesives.

[0333] While the cells **6750a**, **6750b**, **6750c**, **6750d** are generally diamond-shaped, it is to be understood that some or all of the struts **6752**, **6754**, **6756**, **6758**, **6760**, **6762** may not form entirely straight segments. The struts **6752**, **6754**, **6756**, **6758**, **6760**, **6762** can include some curvature such that the upper and/or lower apices are curved. For example, one or more struts can incorporate curvature such that the apices are generally “onion” shaped.

[0334] As shown in the illustrated embodiment, there can be a row of twelve cells **6750a**, a row of twelve cells **6750b**, a row of twelve cells **6750c**, and a row of twelve cells **6750d**. While each of the cells **6750a**, **6750b**, **6750c**, **6750d** are shown as having the same shape as other cells **6750a**, **6750b**, **6750c**, **6750d** of the same row, it is to be understood that the shapes of cells **6750a**, **6750b**, **6750c**, **6750d** within a row can

differ. Moreover, it is to be understood that any number of rows of cells can be used and any number of cells may be contained in the rows. In some embodiments, the number of cells can correspond to the number of anchors or anchor tips forming the first anchoring feature and/or the number of anchors or anchor tips forming the second anchoring feature. As shown, the number of cells in each row of cells **6750a**, **6750b**, **6750c**, **6750d** have a 4:3 correspondence with the number of anchors in the anchoring feature **6740** (i.e., twelve cells in each row of cells **6750a**, **6750b**, **6750c**, **6750d** and nine anchors for the anchoring feature **6740**). It is to be understood that other ratios of numbers of cells per row to number of anchors per anchoring feature can be used such as, but not limited to, 1:1, 2:1, 3:1, 4:1, 5:1, 6:1, and other ratios as desired.

[0335] With continued reference to the frame **6700** illustrated in **Figures 122 and 123**, the geometry of cells **6750a**, **6750b**, **6750c**, **6750d** can allow the cells **6750a**, **6750b**, **6750c**, **6750d** to foreshorten as the frame **6700** is expanded. As such, one or more of cells **6750a**, **6750b**, **6750c**, **6750d** can allow the frame **6700** to foreshorten as the frame **6700** is expanded. Foreshortening of the frame **6700** can be used to secure the prosthesis to intraluminal tissue in a body cavity, for example tissue at or adjacent a native valve, such as a native valve annulus and/or leaflets.

[0336] Anchoring feature **6740** can include one or more anchors. For example, as shown in the illustrated embodiment, the anchoring feature **6740** can include nine anchors. In some implementations, the use of fewer anchors on anchoring feature **6740** can provide multiple advantages. Use of fewer anchors can enhance imaging of the frame **6700** during the delivery process which can beneficially facilitate implantation of the frame **6700**. For example, this can reduce the amount of material, such as metal, and potential interference when used with echocardiography or other types of imaging techniques. Moreover, implantation can be facilitated since fewer anchors are to be positioned. In some implementations, the use of fewer anchors can reduce the amount of force applied on the delivery system. For example, in embodiments where the anchors expand radially outward when the frame **6700** transitions from a collapsed configuration to an expanded configuration, fewer anchors would impart a radially outward force on a component (e.g., a sheath) of the delivery system.

[0337] Each anchor can include one or more struts **6742** extending from an intermediate region **6720** and/or lower region **6730** of the frame **6700**. As shown, struts **6752** extend from a lower intersection of two segments of the cell **6750c**, for example, from the lowermost corner of the cells **6750c** at the apex formed by struts **6758**. However, it is to be understood that the struts **6752** can extend from other portions of the frame **6700**, such as other portions of the cell **6750c** and/or other portions of the cells **6750d**. As shown in the illustrated embodiment, the anchoring feature **6740** can be monolithically or unitarily formed with the frame body **6702a**. This can beneficially enhance structural stability of the anchoring feature **6740** as the anchoring feature **6740** is formed on a primary portion of the frame **6700**.

[0338] As shown, the struts **6742** extend generally downwardly from the frame **6700**. The struts **6742** can incorporate a bend **6744** to orient the strut **6742** such that it extends radially outward away from the longitudinal axis of the frame **300** and/or generally upwardly. As shown in the illustrated embodiment, the bend **6744** can be generally semi-circular or semi-elliptical which can provide a space for the distal ends of the native valve leaflets to be stored. The anchors may then extend in a linear segment radially outwardly and upwardly. As shown in the illustrated embodiment, the bend **6744** can orient the strut **6742** such that it extends generally parallel to the longitudinal axis of the frame **6700**. For example, the tip **6746** of anchoring feature **6740** can extend generally parallel to the longitudinal axis of the frame **6700**. The tips **6746** of the anchoring feature **6740** can end after extending approximately above the base or connection point of the anchoring feature **6740** to the frame body **6702a**. In some embodiments, the tips **6746** of the anchoring feature **6740** can end after extending up to, or slightly past, the lower end of the intermediate region **6720** of the frame **6700**. As shown in the illustrated embodiment, the tips **6746** can include multiple prongs which can be movable relative to each other. For example, the geometry of tips **6746** can be similar to that of anchoring feature **5600** discussed in connection with **Figures 93 and 94**.

[0339] While the bend **6744** orients the tip **6746** such that it extends generally parallel to a longitudinal axis of the frame **6700**, it is to be understood that the bend **6744** can orient the struts **6742**, such as the tips **6746**, in other directions. For example, the

bend **6746** can orient the struts **6742**, such as the tips **6746**, such that they extend radially outward away from the longitudinal axis of the frame **6700**, such that struts **6742** extends radially inward towards the longitudinal axis of the frame **6700**, or such that a portion of struts **6742** extends radially outward away from the longitudinal axis of the frame **6700** and another portion of struts **6742**. In some embodiments, the bend **6744** can orient the struts **6742**, such as the tips **6746**, such that they extend generally perpendicular to a longitudinal axis of the frame **6700** such as is shown with frame **400** illustrated in **Figure 6**.

[0340] As shown in the illustrated embodiment, struts **6742** of the anchoring feature **6740** are positioned further radially outward from a longitudinal axis of the frame **6700** as compared to struts **6762** of the supplement frame **6702b**. In other words, the struts **6742** and the struts **6762** are in different circumferential planes. When the frame **6700** transitions from the expanded configuration to a collapsed or crimped configuration for delivery, interference between the struts **6742** and the struts **6762** is reduced or eliminated. The removal or “un-nesting” of struts **6742** from the circumferential plane of struts **6762** effectively reduces the contribution to the circumference of material that does not circumferentially expand or crimp (e.g., the struts **6742**). This can beneficially reduce stresses and strains imposed on the struts **6742**, **6762** as compared to implementations in which the struts **6742**, **6762** are within the same circumferential plane. In many instances, this can allow for the struts **6762** to compress further thereby allowing the frame **6700** to take on a smaller crimp profile when in the collapsed or crimped configuration.

[0341] Preferably, the anchoring feature **6740** is positioned or extend generally radially outwardly from the frame **300** so that the anchor tips **6746** are generally spaced away or radially outward from the rest of the frame body **6702a** and from where the base of the anchors connect to the frame body **302**. For example, the anchor tips **6746** may be located radially outward from the intermediate region **67720** of the frame **6700**. Individual anchors may extend radially outwardly from the frame at an anchor base and terminate at an anchor tip. The individual anchors can be connected to the frame at one of many different locations including apices, junctions, other parts of struts, etc. Moreover, the anchors forming the anchoring feature **670** can comprise first,



second, third, or more spaced apart bending stages along the length of each anchor. Further details that may be incorporated and/or interchanged with the features described herein are disclosed in U.S. Publication Nos. 2014/0277422, 2014/0277427, 2014/0277390, and 2015/0328000.

**[0342]** Covers and/or cushions (see, for example, covers and/or cushions **720**, **770** illustrated in Figures **10-13**) may be used to surround or partially surround at least a portion of the anchoring feature **6740**, such as the tips or ends **6746** and/or the struts to which the tips or ends **6746** are attached. The covers and/or cushions can be similar to those described in U.S. Publication No. 2015/032800. In some embodiments, the covers and/or cushions can either fit snugly around the tips **6746** or can have extra padding so that the covers extend radially away from the frame **6700**. In some embodiments, all of the anchors of the anchoring feature **6740** can have the covers and/or cushions with some of the anchors having less cushioning than others. In some embodiments, all of the anchors of the anchoring feature **6740** can have the padded covers. In some embodiments, all of the anchors of the anchoring feature **6740** can have the snugly fitting cushions. In some embodiments, not all of all of the anchors of the second anchoring feature **6740** can have covers.

**[0343]** With continued reference to the frame **6700** illustrated in **Figures 122 and 123**, the frame **6700** can include a set of locking tabs **6770** extending from the upper region **6710** of the frame **6700**. As shown, the frame **6700** includes twelve locking tabs **6770**, however, it is to be understood that a greater number or lesser number of locking tabs can be used. The locking tabs **6770** can extend generally upwardly from the upper region **6710** in a direction generally aligned with the longitudinal axis of the frame **6700**.

**[0344]** At an upper end of the strut **6772**, the locking tab **6770** can include an enlarged head **6774**. As shown, the enlarged head **6774** has a semi-circular or semi-elliptical shape forming a “mushroom” shape with the strut **6772**. The locking tab **6770** can be advantageously used with multiple types of delivery systems. For example, the shape of the struts **6772** and the enlarged head **6774** can be used to secure the frame **6700** to a “slot” based delivery system. It is to be understood that the locking tab **6770** can include an eyelet at other locations, or can include more than a single eyelet. The eyelets can be used to secure the frame **6700** to a “tether” based delivery system such as those

which utilize sutures, wires, or fingers to control delivery of the frame **6700**. This can advantageously facilitate recapture and repositioning of the frame **6700** in situ. In some embodiments, the frame **6700** can be used with the delivery systems described in U.S. Patent Nos. 8,414,644 and 8,652,203 and U.S. Publication Nos. 2015/0238315.

**[0345]** The frame **6700** can include one or more posts **6780**. The posts **6780** can facilitate attachment of a valve body to the frame **6700**. In some implementations, commissures of the valve body can be attached to the posts **6780**. The commissures of the valve body can be attached to the posts **6780** via sutures and/or an intermediate component such as those described herein. For example, the commissures of the leaflets of the valve body can be indirectly coupled to the posts **6780** via an intermediate component which is sutured to and/or extends around the posts **6780**.

**[0346]** As shown in the illustrated embodiment, the posts **6780** can extend distally from a lower portion of the frame body **6702a**, such as the apices of cells **6750c**. Extension of the posts **6780** from the frame body **6702a** can reduce relative movement between the posts **6780** and the overall frame **6700**. This can beneficially enhance the stability of a valve body positioned within the frame **6700**. Moreover, distal extension of the posts **6780** can allow a longer valve body to be utilized within the frame **6700**.

**[0347]** The number of posts **6780** can match the number of commissures of the valve body. For example, in implementations where a valve body having three leaflets is used, the frame **6700** can include three posts **6780** to which each commissure of the valve body can be attached. The posts **6780** can be generally equally spaced around the periphery of the frame **6700**. Although the posts **6780** are positioned on the frame body **6702a**, it is to be understood that the posts **6780** can extend from the supplemental frame **6702b**. The posts **6780** can extend between the cells **6750d** and/or can extend from a distal portion of cells **6750d** (e.g., distal apices). In some embodiments, the posts **6780** can be positioned radially inwardly relative to the struts **6762** of the supplemental frame **6702b**. For example, the posts **6780** can extend from an inner surface of the supplemental frame **6702b**. In some embodiments, the posts **6780** can be positioned radially outwardly relative to the struts **6758** of the frame body **6702a**. For example, the posts **6780** can extend from an outer surface of the frame body **6702a**.

[0348] With reference next to the frame **6800** illustrated in **Figures 124 and 125**, the frame **6800** is shown as a flat pattern. The frame **6800** is shown in an assembled configuration in **Figure 124** and a disassembled configuration in **Figure 125**. As shown in the illustrated embodiment, the frame **6800** can include a frame body **6810a**, a supplemental frame **6810b**, first anchoring feature **6820**, and/or a second anchoring feature **6830**. In the assembled configuration, the frame **6800** can include a first row of cells **6840a**, **6840b**, a second row of cells **6840c**, a third row of cells **6840d**, and/or a fourth row of cells **6840e**. In some embodiments, in the assembled configuration, the frame **6800** can include a plurality of locking tabs **6850a**, **6850b**. The first anchoring feature **6820** can include anchors with tips **6822** having one or more eyelets. The second anchoring feature **6830** can include anchors with tips **6832**. As shown in the illustrated embodiment, the tips **6832** can include multiple prongs which can be movable relative to each other. For example, the geometry of tips **6832** can be similar to that of anchoring feature **5700** discussed in connection with **Figures 95-99** when shapaset.

[0349] One or more components of the frame **6800** can be formed separately from each other. As shown in the illustrated embodiment, the frame body **6810a**, the supplemental frame **6810b**, and/or the first anchoring feature **6820** can be formed separately from each other and subsequently attached. The first anchoring feature **6820** can be positioned in front of the frame body **6810a**. The supplemental frame **6810b** can be positioned behind the frame body **6810a**. The frame body **6810a**, the supplemental frame **6810b**, and/or the first anchoring feature **6820** can be attached using any of the fasteners and techniques described herein, such as via sutures, welding, and/or adhesives.

[0350] With reference to **Figure 125**, the frame body **6810a** include one or more struts forming cells **6840b**, **6840c**, **6840d** as shown in three separate rows. The one or more struts can be monolithically or unitarily formed to enhance the structural integrity of the frame body **6810a**. The anchoring feature **6830** can be monolithically or unitarily formed with the frame body **6810a**. The locking tabs **6850b** can be monolithically or unitarily formed with the frame body **6810a**.

[0351] The supplemental frame **6810b** can include one or more struts forming cells **6840e** as shown in a single row. The struts forming the lower portion of the lower row of cells **6840d** and the struts forming the upper portion of the cells **6840e**

can have the same general size and shape. Accordingly, when aligned together, these struts can form a “combined” strut with the combined wall thicknesses of the struts. This can beneficially enhance the structural rigidity of the frame **6800** along the lower portion of the frame **6800**. This can be advantageous since the second anchoring feature **6830**, which can be subject to significant loading during operation, can be attached to at least a portion of this combined strut.

[0352] The first anchoring feature **6820** can include one or more struts forming cells **6840a** as shown in a single row. The struts forming the upper portion of the upper row of cells **6840b** and the struts forming the upper portion of the cells **6840a** can have the same general size and shape. Accordingly, when aligned together, these struts can form a “combined” strut with the combined wall thicknesses of the struts. This can beneficially enhance the structural rigidity of the frame **6800** along the lower portion of the frame **6800**. This can be advantageous since the tips **6822** of first anchoring feature **6820**, which can be subject to loading during operation, can be attached to at least a portion of this combined strut.

[0353] The first anchoring feature **6820** can include a locking tab **6850a**. The locking tabs **6850a** of the frame body **6810a** and the locking tabs **6850b** of the first anchoring feature **6810b** can have the same general size and shape. Accordingly, when aligned together, “combined” locking tabs **6850a**, **6850b** can have a larger wall thickness. This can beneficially enhance the structural rigidity of the locking tabs **6850a**, **6850b**. This can be advantageous since the tips **6850a**, **6850b** can be subject to loading during delivery.

[0354] While the cells **6840a**, **6840b**, **6840c**, **6840d**, **6840e** are generally diamond-shaped, it is to be understood that some or all of the struts forming cells **6840a**, **6840b**, **6840c**, **6840d**, **6840e** may not be entirely straight segments. The struts forming cells **6840a**, **6840b**, **6840c**, **6840d**, **6840e** can include some curvature such that the upper and/or lower apices are curved. For example, one or more struts can incorporate curvature such that the apices are generally “onion” shaped.

[0355] As shown in the illustrated embodiment, each row of cells **6840a**, **6840b**, **6840c**, **6840d**, **6840e** can include twelve cells. While each of the cells **6840a**, **6840b**, **6840c**, **6840d**, **6840e** are shown as having the same shape as other cells **6840a**,

**6840b**, **6840c**, **6840d**, **6840e** of the same row, it is to be understood that the shapes of cells **6840a**, **6840b**, **6840c**, **6840d**, **6840e** within a row can differ. Moreover, it is to be understood that any number of rows of cells can be used and any number of cells may be contained in the rows. For example, some rows of cells may have twelve cells whereas other rows of cells may have six cells.

[0356] With reference next to the frame **6900** illustrated in **Figures 126 and 127**, the frame **6900** is shown as a flat pattern. The frame **6900** is shown in an assembled configuration in **Figure 126** and a disassembled configuration in **Figure 127**. As shown in the illustrated embodiment, the frame **6900** can include a frame body **6910a**, a supplemental frame **6910b**, first anchoring feature **6920**, and/or a second anchoring feature **6930**. In the assembled configuration, the frame **6900** can include a first row of cells **6940a**, a second row of cells **6940b**, and/or a third row of cells **6940c**. In some embodiments, in the assembled configuration, the frame **6900** can include a plurality of locking tabs **6950a**, **6950b**. The first anchoring feature **6920** can include anchors with tips **6922** having one or more eyelets. The second anchoring feature **6930** can include anchors with tips **6932**.

[0357] As shown in the illustrated embodiment, the frame body **6910a**, the supplemental frame **6910b**, and/or the first anchoring feature **6920** can be formed separately from each other and subsequently attached. The first anchoring feature **6920** can be positioned in front of the frame body **6910a**. The supplemental frame **6910b** can be positioned behind the frame body **6910a**. The frame body **6910a**, the supplemental frame **6910b**, and/or the first anchoring feature **6920** can be attached using any of the fasteners and techniques described herein, such as via sutures, welding, and/or adhesives.

[0358] With reference to **Figure 127**, the frame body **6910a** include one or more struts forming cells **6940a**, **6940b** as shown in two separate rows. The one or more struts can be monolithically or unitarily formed to enhance the structural integrity of the frame body **6910a**. The anchoring feature **6930** can be monolithically or unitarily formed with the frame body **6910a**. The frame body **6910a** can include one or more eyelets **6912**. The eyelets **6912** can be utilized to attach components of the replacement valve, such as a valve skirt, to the frame body **6910a**. In some embodiments, the eyelets **6912** can be used to attach the first anchoring feature **6920** to the frame body **6910a**.

[0359] The supplemental frame **6910b** can include one or more struts forming cells **6940c** as shown in a single row. The struts forming the lower portion of the lower row of cells **6940c** and the struts forming the upper portion of the cells **6940b** can have the same general size and shape. Accordingly, when aligned together, these struts can form a “combined” strut with the combined wall thicknesses of the struts.

[0360] The first anchoring feature **6920** can include one or more struts **6942**. The struts **6942** and the struts forming the upper portion of the cells **6940a** can have the same general size and shape. Accordingly, when aligned together, these struts can form a “combined” strut with the combined wall thicknesses of the struts. The first anchoring feature **6920** can include locking tabs **6950**. As shown in the illustrated embodiment, the first anchoring feature **6920** can include one or more eyelets **6944**. The eyelets **6944** of the first anchoring feature **6920** can be aligned with the eyelets **6912** of the frame body **6910a** to facilitate securement of the first anchoring feature **6920** to the frame body **6910a** by allowing sutures to be passed therethrough. Use of two eyelets **6912**, **6944** on each of the frame body **6910a** and the first anchoring feature **6920** can enhance securement. For example, a cloth or another intermediate, buffer material can be positioned between the eyelets **6912**, **6944**. A suture can be passed through both sets of eyelets using a “Figure 8” suture technique. In some embodiments, the eyelets **6912**, **6944** and/or the space between the eyelets **6912**, **6944** can be wrapped with a suture or a sleeve to further enhance securement.

[0361] While the cells **6940a**, **6940b**, **6940c** are generally diamond-shaped, it is to be understood that some or all of the struts forming cells **6940a**, **6940b**, **6940c** may not be entirely straight segments. The struts forming cells **6940a**, **6940b**, **6940c** can include some curvature such that the upper and/or lower apices are curved. For example, one or more struts can incorporate curvature such that the apices are generally “onion” shaped.

[0362] As shown in the illustrated embodiment, each row of cells **6940a**, **6940b**, **6940c** can include twelve cells. While each of the cells **6940a**, **6940b**, **6940c** are shown as having the same shape as other cells **6940a**, **6940b**, **6940c** of the same row, it is to be understood that the shapes of cells **6940a**, **6940b**, **6940c** within a row can differ. Moreover, it is to be understood that any number of rows of cells can be used and any

number of cells may be contained in the rows. For example, some rows of cells may have twelve cells whereas other rows of cells may have six cells.

[0363] With reference next to the frame **7000** illustrated in **Figures 128 and 129**, the frame **7000** is shown as a flat pattern. The frame **7000** is shown in an assembled configuration in **Figure 128** and a disassembled configuration in **Figure 129**. As shown in the illustrated embodiment, the frame **7000** can include a frame body **7010a**, a supplemental frame **7010b**, a first anchoring feature **7020**, and/or a second anchoring feature **7030**. In the assembled configuration, the frame **7000** can include a first row of cells **7040a**, a second row of cells **7040b**, a third row of cells **7040c**, and/or a fourth row of cells **7040d**. In some embodiments, in the assembled configuration, the frame **7000** can include a plurality of locking tabs **7050**. The first anchoring feature **7020** can include anchors with tips **7022** having one or more eyelets. The second anchoring feature **7030** can include anchors with tips **7032**.

[0364] As shown in the illustrated embodiment, the frame body **7010a**, the supplemental frame **7010b**, and/or the first anchoring feature **7020** can be formed separately from each other and subsequently attached. The first anchoring feature **7020** can be positioned in front of the frame body **7010a**. The supplemental frame **7010b** can be positioned behind the frame body **7010a**. The frame body **7010a**, the supplemental frame **7010b**, and/or the first anchoring feature **7020** can be attached using any of the fasteners and techniques described herein, such as via sutures, welding, and/or adhesives.

[0365] With reference to **Figure 129**, the frame body **7010a** include one or more struts forming cells **7040a**, **7040b**, **7040c** as shown in three separate rows. The one or more struts can be monolithically or unitarily formed to enhance the structural integrity of the frame body **7010a**. The anchoring feature **7030** can be monolithically or unitarily formed with the frame body **7010a**. The locking tabs **7050** can be monolithically or unitarily formed with the frame body **7010a**.

[0366] The supplemental frame **7010b** can include one or more struts forming cells **7040d** as shown in a single row. The struts forming the lower portion of the lower row of cells **7040c** and the struts forming the upper portion of the cells **7040d** can have the same general size and shape. Accordingly, when aligned together, these struts can form a “combined” strut with the combined wall thicknesses of the struts.

[0367] The first anchoring feature **7020** can include one or more struts **7042**. The struts forming the lower portion of the upper row of cells **7040a** and the struts **7042** can have the same general size and shape. The struts **7042** can be attached to the frame body **7010a** along the upper portion, such as the upper apices, of the struts **7042**.

[0368] While the cells **7040a**, **7040b**, **7040c**, **7040d** are generally diamond-shaped, it is to be understood that some or all of the struts forming cells **7040a**, **7040b**, **7040c**, **7040d** may not be entirely straight segments. The struts forming cells **7040a**, **7040b**, **7040c**, **7040d** can include some curvature such that the upper and/or lower apices are curved. For example, one or more struts can incorporate curvature such that the apices are generally “onion” shaped.

[0369] As shown in the illustrated embodiment, each row of cells **7040a**, **7040b**, **7040c**, **7040d** can include twelve cells. While each of the cells **7040a**, **7040b**, **7040c**, **7040d** are shown as having the same shape as other cells **7040a**, **7040b**, **7040c**, **7040d** of the same row, it is to be understood that the shapes of cells **7040a**, **7040b**, **7040c**, **7040d** within a row can differ. Moreover, it is to be understood that any number of rows of cells can be used and any number of cells may be contained in the rows. For example, some rows of cells may have twelve cells whereas other rows of cells may have six cells.

[0370] While the embodiments described above have an anchoring feature monolithically or unitarily formed with the frame body, it is to be understood that the frame body can be formed without anchoring features. For example, with reference next to the frame **7100** illustrated in **Figures 130 and 131**, the frame **7100** is shown in an assembled configuration in **Figure 130** and a disassembled configuration in **Figure 131**. As shown in the illustrated embodiment, the frame **7100** can include a frame body **7110a**, a supplemental frame **7110b**, and/or an anchoring feature **7120**. The anchoring feature **7120** can be monolithically or unitarily formed with the supplemental frame **7110b**. The supplemental frame **7110b** can be attached to struts which are positioned further proximal than the distalmost struts of the frame body **7110a**. As shown, the supplemental frame **7110b** is positioned in front of, or radially outward of, the frame body **7110a**.



Embodiments of Floating Valves

[0371] With reference to **Figures 14-32**, embodiments of prostheses **800**, **900**, **1000**, **1200**, **1300**, **1400**, **1500**, **1600**, **1700**, **1800**, **1900**, **2000**, **2100**, or components thereof such as frames **810**, **910**, **1010**, **1210**, **1310**, **1410**, **1510**, **1610**, **1710**, **1810**, **1910**, **2010**, **2110** and/or valve bodies **820**, **920**, **1020**, **1100**, **1220**, **1320**, **1420**, **1520**, **1620**, **1720**, **1820**, **1920**, **2020**, **2120**, are illustrated. With reference first to the prosthesis **800** illustrated in **Figures 14** and **15**, the prosthesis **800** can include a frame **810** and a valve body **820**. The valve body **820** can be positioned within the frame **810** and can be a replacement heart valve which includes a plurality of valve leaflets **830**.

[0372] The valve leaflets **830** can include a first edge **832**, second edge **834**, and one or more tabs **836** for attaching the valve leaflets **830** to struts of the frame **810**. The tabs **836** can form part of the valve leaflet **830** at the commissures of the valve body **820**. The second edge **834** can be a freely moving edge which can allow the valve body **820** to open and close. The plurality of valve leaflets **830** can function in a manner similar to the native mitral valve, or to any other valves in the vascular system as desired. The plurality of valve leaflets **830** can open in a first position and then engage one another to close the valve in a second position. The plurality of valve leaflets **830** can be made to function as a one way valve such that flow in one direction opens the valve and flow in a second direction opposite the first direction closes the valve. For example, as shown in the illustrated embodiment, the valve body **820** can open allow blood to flow through the valve body **820** in a direction from the upper end of the frame **810** to the lower end of the frame **810**. The valve body **820** can close to inhibit blood flow through the valve body **820** in a direction from the lower end of the frame **810** to the upper end of the frame **810**. The valve body **820** can be constructed so as to open naturally with the beating of the heart. For example, the plurality of valve leaflets **830** can open during diastole and close during systole. The valve body **820** can replace a damaged or diseased native heart valve such as a diseased native mitral valve.

[0373] As shown in the illustrated embodiment, the valve body **820** can include one or more intermediate components **840**. The one or more intermediate components **840** can be used to attach one or more of the valve leaflets **830**, or a portion thereof, to the frame **810** such that the valve leaflet **830** is indirectly coupled to the frame

**810** or “floats” within the frame **810**. For example, as shown in **Figure 15**, a first end of a first intermediate component **842** can be attached to the tabs **836** of the valve leaflet **830** and a second end of the first intermediate component **842** can be attached to the frame **810**. In this manner, the tabs **836** of the valve leaflet **830** are not directly attached to the frame **810**. As shown in the illustrated embodiment, the tabs **836** and/or the commissures of the valve body **820** can be spaced from an inner surface of the frame **810**. In some embodiments, a first end of a second intermediate component **844** can be attached to other portions of the valve leaflet **830** such as a portion of, or the entirety of, the first edge **832** of the valve leaflet **830**. A second end of the second intermediate component **844** can be attached to the frame **810**. In this manner, at least a portion of, or the entirety of, the first edge **832** of the valve leaflet **830** is not directly attached to the frame **810**. As shown in the illustrated embodiment, a portion of, or the entirety of, the first edge **832** of the valve leaflet **830** can be spaced from an inner surface of the frame **810**. Although the two intermediate components **842**, **844** were described herein for the tabs **836** and the first edge **832** respectively, it is to be understood that these two intermediate components **842**, **844** can be formed as a single component or can be formed from more than two components.

[0374] The valve leaflet **830** can be attached to the intermediate component **840** using any mechanism or technique as desired such as, but not limited to, mechanical fasteners, such as sutures, staples, screws, rivets, and any other type of mechanical fastener as desired, chemical fasteners such as adhesives and any other type of chemical fastener as desired, fastening techniques such as welding, sintering, and any other type of fastening technique as desired, and/or a combination of such fasteners and techniques. In some embodiments, the valve leaflet **830** can be attached to the intermediate component **840** via an intermediate post or wireframe positioned between the leaflet **830** and the intermediate component **840**. The intermediate post or wireframe can be formed from a generally rigid structure. This can beneficially enhance stability of valve leaflet **830** by serving as a generally rigid support structure for the valve leaflet **830**. In some embodiments, the intermediate component **840** can be attached to the frame **810** using any mechanism or technique described above.

[0375] The intermediate component **840** can be formed from a material having a stiffness between that of the valve leaflets **830**, which are relatively flexible, and the frame **810** which is generally rigid. The intermediate component **840** can serve as a dampener between the valve leaflet **830** and the frame **810** and transmit stresses from the leaflet **830** to the frame **810**. For example, the intermediate component **840** can be formed from a flexible or semi-flexible material having a stiffness greater than the valve leaflet **830**. In some embodiments, the intermediate component **840** can be formed from a biocompatible material such as, but not limited to, fabrics such as cloth, flexible or rigid polymers such as polyurethane and polyethylene terephthalate (PET), metals such as stainless steel, titanium, Nitinol, composites, and any other biocompatible material such as those which are wholly or substantially fluid impermeable, flexible, semi-flexible, stretchable, deformable, and/or resilient. When formed from a stiff material, such as metals or polymers, the intermediate component **840** can have a geometry which allows for less effective stiffness in certain direction than others. For example, the intermediate component **840** can be formed to have tapering cross-section and/or shapes to flex in certain directions and not in others. In some embodiments, the intermediate component **840** can be formed from a material that facilitates tissue ingrowth or formation. In this embodiment, the valve leaflets **830** can be formed from a tissue-based media such as bovine, equine and/or porcine pericardium. Vascular tissue, as well as other natural and manmade materials that are flexible and durable, may also be employed for the valve leaflets **830**.

[0376] By isolating portions of the valve leaflets **830**, such as the portions at the commissures or tabs **836** and/or the cusp or first edge **832**, from the frame **810** with an intermediate component **840** of lesser stiffness than the frame, the stress concentrations on the valve leaflets **830** during operation of the valve body **820** can be reduced or eliminated. Such stresses can occur, for example, due to changes in blood flow during the cardiac cycle. For example, when the prosthesis **800** is positioned within a native mitral valve, such stresses can occur during systole when the valve leaflets **830** close to inhibit to restrict blood flow from the left ventricle to the left atrium. These stresses can be particularly elevated at portions of the leaflet connected to the frame **810**

such as the portions at the commissures or tabs **836**. This reduction of stress concentrations can beneficially increase the functional lifespan of the valve leaflet **830**.

[0377] Moreover, the intermediate component **840** can beneficially allow the design of the valve leaflets **830** to be independent from the design of the frame **810** and allow for a single design of valve leaflets **830** to be applied to a wide variety of frames of different shapes and sizes. In this manner, the frame **810** can be designed in a manner that enhances anchoring or securement to a body cavity, such as a native valve annulus, and the valve leaflets **830** can be designed in a manner that enhances hemodynamic performance.

[0378] For example, valve leaflets **830** can be designed to have a small diameter to increase blood flow velocity through the valve leaflets **830**. The increase in blood flow velocity, due to the reduction in diameter of the valve leaflets **830**, can beneficially increase leaflet **830** activity and reduce the risk of thrombosis. The frame **810** can be designed with a large diameter to enhance anchoring or securement to a body cavity, such as a native valve annulus. The smaller diameter valve leaflets **830** can also be used to throttle flow through the prosthesis **800**. Moreover, valve leaflets **830** having a smaller diameter relative beneficially allow for the frame **810** to be crimped to a smaller diameter with a reduced risk of damaging the valve leaflets **830**.

[0379] With reference next to the prosthesis **900** illustrated in **Figures 16** and **17**, the prosthesis **900** can include a frame **910** and a valve body **920**. As shown in the illustrated embodiment, the frame **910** can include a projection **912** which extends radially inwards. The valve body **920** can include a leaflet **930** and an intermediate component **940**. The intermediate component **940** can be attached to at least a portion of leaflet **930** at a first end of the intermediate component **940**. The intermediate component **940** can be attached to at least a portion of the frame **910**, such as projection **912**. The combination of the intermediate component **940** and the generally rigid projection **912** can be used to achieve a variable stiffness such as in the radial direction.

[0380] With reference next to the prosthesis **1000** illustrated in **Figure 18**, the prosthesis **1000** can include a frame **1010** and a valve body **1020**. As shown in the illustrated embodiment, the valve body **1020** can include a plurality of leaflets **1030** and one or more intermediate components **1040**. The one or more intermediate components

**1040** extend across most of, if not the entirety of, the first edge **1032** of the leaflets **1030** and is attached to the first edge **1032** via sutures. The one or more intermediate components **1040** can also be attached to the frame **1010** via sutures along one or more struts of the frame **1010** via sutures. As shown in the illustrated embodiment, a portion of the first edge **1032** of the leaflet **1030** is positioned proximate a strut of the frame **1010**. This can beneficially enhance stability of the leaflet **1030**. In some embodiments, a portion of edge **1032** of the leaflet **1030**, such as the positioned proximate a strut of the frame **1010**, can be directly attached to the frame **1010**.

[0381] With reference next to the portion of valve body **1100** illustrated in **Figure 19A**, a flat pattern of various components are shown. The portion of valve body **1100** can include a valve leaflet **1110**, a first intermediate component **1120**, a second intermediate component **1130**, and a third intermediate component **1140**. The valve leaflet **1110** can include a first edge **1112**, a second edge **1114**, and one or more tabs **1116**. The first edge **1112** can form a cusp of the leaflet **1110**. The second edge **1114** can be a freely moving edge which can allow the valve body **1100** to open and close. The tabs **1116** can be used to attach valve leaflets **1110** together at commissures of the valve body **1100**.

[0382] The first intermediate component **1120** can include an edge **1122**. The edge **1122** can generally match the general curvature of the first edge **1112** of the valve leaflet **1110**. In some embodiments, the first intermediate component **1120** can be attached to the valve leaflet **1110** at or proximate the edges **1112**, **1122**. As shown, the valve leaflet **1110** and the first intermediate component **1120** can include suturing holes to facilitate attachment of the valve leaflet **1110** and the second intermediate component **1130** via sutures. The first intermediate component **1120** can be attached along an inflow surface and/or outflow surface of the valve leaflet **1110**. The first intermediate component **1120** can include one or more tabs **1124** on lateral sides of the first intermediate component **1120**. The one or more tabs **1124** can generally correspond to the tabs **1116** of the valve leaflet **1110**. The one or more tabs **1124** can be used at the commissures of the valve body **1100**. In some embodiments, a plurality of first intermediate components **1120** can be attached along the edges **1126**. This can form a generally cylindrical portion of a valve body **1100** along an inflow or upstream end of

the valve body **1100**. The first intermediate component **1120** can be similar to intermediate component **250a** illustrated in **Figure 2**.

[0383] The second intermediate component **1130** can include an inner edge **1132** and an outer edge **1134**. The inner edge **1132** can generally match the general curvature of the first edge **1112** of the valve leaflet **1110**. In some embodiments, the second intermediate component **1130** can be attached to the valve leaflet **1110** at or proximate the edges **1112**, **1132**. As shown, the valve leaflet **1110** and the second intermediate component **1130** can include suturing holes to facilitate attachment of the valve leaflet **1110** and the second intermediate component **1130** via sutures. The second intermediate component **1130** can be attached along an outflow surface and/or inflow surface of the valve leaflet **1110**. The second intermediate component **1130** can be attached to struts of a frame along the inner edge **1132** and/or the outer edge **1134**. To facilitate attachment of the second intermediate component **1130** to the frame, the second intermediate component **1130** can include a plurality of slits **1136**. The second intermediate component **1130** can be similar to intermediate components **250b** and **1040** illustrated in **Figures 4** and **18** respectively.

[0384] The third intermediate component **1140** can include a first portion **1142** and a second portion **1144**. The third intermediate component **1140** can be used to attach the valve leaflet **1110** to the frame at or proximate the portions of the valve leaflet **1110** at the commissures of the valve body **1100**. The third intermediate component **1140** can be attached to a frame along a portion, or the entirety of, the edges defining the first portion **1142** and/or second portion **1144**. In some embodiments, the third intermediate component **1140** can be positioned along portions of the frame near the valve body **1100** commissures. This can beneficially provide a seal between the first intermediate component **1120** and the second intermediate component **1130** as shown in **Figure 19C**.

[0385] With reference next to the valve body **1100** and frame **1150** illustrated in **Figure 19B**, the valve body **1100** is shown attached to the frame **1140**. With reference next to the valve body **1100** and frame **1150** illustrated in **Figure 19C**, a schematic cross-section of the valve body **1100** and frame **1150**. As shown, the first intermediate component **1120** can form a generally vertically oriented structure around

the frame **1150** and be attached to the frame **1150** at an upper end and to an inflow surface of a valve leaflet **1110** at a lower end. The second intermediate component **1120** can be attached to the valve leaflet **1110** at an upper end and to the frame **1150** at a lower end. The third intermediate component **1140** can be attached to the frame **1150** as well as the first and second intermediate components **1120**, **1130**. This can form an enclosed pocket **1146**. In some embodiments, one or more of the intermediate components **1120**, **1130**, **1140** may be formed from a slightly porous material which allows fluid, such as blood, to enter into the pocket **1146**. In some instances, the blood can form a clot within the pocket **1146**.

[0386] With reference next to the prosthesis **1200** illustrated in **Figures 20** and **21**, the prosthesis **1200** can include a frame **1210** and a valve body **1220**. As shown in the illustrated embodiment, the valve body **1220** can include a plurality of valve leaflets **1230** and a plurality of intermediate components **1240**. For example, the valve body **1220** can include three valve leaflets **1230** and three intermediate components **1240**. The number of intermediate components **1240** can match the number of commissures for the valve body **1220** having three valve leaflets **1230**. However, it is to be understood that any number of valve leaflets **1230** and/or intermediate components **1240** can be used. The intermediate components **1240** can be attached to at least the commissures of the valve leaflets **1230** at a first end of the intermediate components **1240**. The intermediate components **1240** can be attached to the frame **1210** at a second end of the intermediate components **1240**. As shown in the illustrated embodiment, an entirety of, or at least a portion of, the intermediate components **1240** can be generally flat. For example, at least a portion of the intermediate components **1240** proximate commissures of the valve body **1220** can be flat. The flat portion of the intermediate components **1240** can be generally aligned with a plane parallel to the longitudinal axis. In some embodiments, the flat portion of the intermediate components **1240** can be aligned with a plane which is parallel with, and extends through, the longitudinal axis. In some embodiments, the valve body **1220** can include an intermediate component **1250** in the form of a conduit which can extend circumferentially around the plurality of valve leaflets **1230**. This can beneficially provide support for the valve leaflets **1230**. As

shown in the illustrated embodiment, the conduit **1250** can be generally cylindrical although other geometries can be used.

[0387] As noted above, the “floating” valve design can beneficially allow the design of the valve leaflets to be independent from the design of the frame. As shown in the illustrated embodiment, the diameter **1260** of the valve leaflets **1230** and/or conduit **1250** can be smaller than the widest diameter **1270** of the frame **1210**. Moreover, the diameter **1260** of the valve leaflets **1230** and/or conduit **1250** can be smaller than the diameter **1280** of an upper or inflow end of the frame **1210**. In some embodiments, the ratio of the diameter **1260** of the valve leaflets **1230** and/or conduit **1250** to the widest diameter **1270** of the frame **1210** can be about 1:3, about 2:5, about 1:2, about 3:5, about 4:5 or any other ratio as desired. In some embodiments, the diameter **1260** of the valve leaflets **1230** and/or conduit **1250** can be between about 20mm to about 35mm, any sub-range within these ranges, or any other diameter as desired.

[0388] With reference next to the prosthesis **1300** illustrated in **Figures 22** and **23**, the prosthesis **1300** can include a frame **1310** and a valve body **1320**. As shown in the illustrated embodiment, the valve body **1320** can include a plurality of valve leaflets **1330**, a plurality of first or commissural intermediate components **1340**, and one or more second intermediate components **1350**. For example, the valve body **1320** can include three valve leaflets **1330** and three commissural intermediate components **1340**. The number of commissural intermediate components **1340** can match the number of commissures for the valve body **1320** having three valve leaflets **1330**. However, it is to be understood that any number of valve leaflets **1330** and/or intermediate components **1340** can be used. The commissural intermediate components **1340** can be attached to at least the portions of the valve leaflets **1330** at commissures of the valve body **1320** at a first end of the commissural intermediate components **1340**. The commissural intermediate components **1340** can be attached to the frame **1310** at a second end of the commissural intermediate components **1340**. As shown in the illustrated embodiment, an entirety of, or at least a portion of, the intermediate components **1340** can be generally flat. For example, at least a portion of the intermediate components **1340** proximate commissures of the valve body **1320** can be flat. The flat portion of the intermediate components **1340** can be generally aligned with a plane parallel to the longitudinal axis.



In some embodiments, the flat portion of the intermediate components **1240** can be aligned with a plane which is parallel with, and extends through, the longitudinal axis.

[0389] The second intermediate component **1350** can extend at least around a portion of the cusps of the leaflets **1320**. The second intermediate component **1350** can be attached to at least the cusps of the valve leaflets **1330** at a first end of the second intermediate component **1350**. The second intermediate components **1350** can be attached to the frame **1310** at a second end of the second intermediate component **1350**. In some embodiments, the first intermediate components **1340** and the second intermediate component **1350** can “tent” the valve leaflet **1330**. That is, the first intermediate components **1340** can be tensioned in a first direction, such as a direction generally radially outward away from the longitudinal axis of the frame **1310**. The second intermediate component **1350** can be tensioned in a second direction different from the first direction. For example, the second intermediate component **1350** can be tensioned in an axial direction generally aligned with a longitudinal axis of the frame **1310** and/or in a circumferential direction about the longitudinal axis of the frame **1310**. The application of tension in different directions (i.e., “tenting”) can beneficially provide enhanced structural support for the valve leaflets **1320** such that the valve leaflets **1320** retain their shape.

[0390] The second intermediate component **1350** can be used to assist with fluid flow through and/or around the prosthesis **1300**. As shown, the second intermediate component **1350** can be positioned within the interior of the frame **1310** and can form a wall of the prosthesis **1300** along the inflow path from the upper end towards the lower end of the frame **1310**. The second intermediate component **1350** can be positioned such that the second intermediate component **1350** is radially inward, relative to the longitudinal axis of the frame **1310**, from struts of the frame **1310**. In this manner, fluid can be directed towards the valve leaflets **1330** of the valve body **1310** along the inflow path.

[0391] As shown in the illustrated embodiment, the diameter **1360** of the valve leaflets **1330** and/or second intermediate component **1350** can be smaller than the widest diameter **1370** of the frame **1310**. Moreover, the diameter **1360** of the valve leaflets **1330** can be smaller than the diameter **1380** of an upper or inflow end of the

frame **1310**. In some embodiments, the ratio of the diameter **1360** of the valve leaflets **1330** and/or conduit **1350** to the widest diameter **1370** of the frame **1310** can be about 1:3, about 2:5, about 1:2, about 3:5, about 4:5 or any other ratio as desired. In some embodiments, the diameter **1360** of the valve leaflets **1330** can be between about 20mm to about 25mm, any sub-range within these ranges, or any other diameter as desired. In some embodiments, the diameter **1380** of the second intermediate component **1350** can be the same, or about the same, as the diameter **1380** of the upper or inflow end of the frame **1310**. In some embodiments, the diameter **1380** of the upper or inflow end of the frame **1310** can be between about 20mm to about 40mm, between about 25mm to about 35mm, between about 27mm to about 33mm, about 27mm, any sub-range within these ranges, or any other diameter as desired.

[0392] With reference next to the prostheses **1400**, **1500** illustrated in **Figures 24** and **25**, the prostheses **1400**, **1500** can each include a frame **1410**, **1510** and a valve body **1420**, **1520**. With reference to prosthesis **1400**, the valve body **1420** can include a plurality of valve leaflets **1430** and a plurality of intermediate components **1440**. As shown, the valve body **1420** can have a generally frustoconical shape with a diameter of the upper or inflow end of the valve body **1420** being larger than a diameter of the lower or outflow end of the valve body **1420**. With reference to prosthesis **1500**, the valve body **1520** can include a plurality of valve leaflets **1530** and a plurality of intermediate components **1540**. As shown, the valve body **1520** can have a generally frustoconical shape with a diameter of the upper or inflow end of the valve body **1520** being smaller than a diameter of the lower or outflow end of the valve body **1520**.

[0393] With reference next to the prostheses **1600**, **1700**, **1800**, **1900** illustrated in **Figures 26-29**, the prostheses **1600**, **1700**, **1800**, **1900** can each include a frame **1610**, **1710**, **1810**, **1910** and a valve body **1620**, **1720**, **1820**, **1920** which can each include valve leaflets schematically represented as structures **1630**, **1730**, **1830**, **1930** and various configurations of intermediate components.

[0394] With reference first to prosthesis **1600** illustrated in **Figure 26**, the valve body **1620** can include a plurality of intermediate components **1640** extending radially between the frame **1620** and the valve leaflets **1630**. As shown in the illustrated embodiment, the valve body **1620** can include twelve intermediate components **1640**. It

is to be understood that a greater number or a lesser number of intermediate components **1640** can be used.

[0395] With reference next to prosthesis **1700** illustrated in **Figure 27**, the valve body **1720** can include a plurality of intermediate components **1740** oriented tangentially to the valve leaflets **1730**. The intermediate components **1740** can be coupled at a first and second end to the frame **1710** and be coupled to the valve leaflets **1730** along a portion of the intermediate components **1740** between the first and second ends. As shown in the illustrated embodiment, the valve body **1720** can include six intermediate components **1740**. It is to be understood that a greater number or a lesser number of intermediate components **1740** can be used.

[0396] With reference next to prosthesis **1800** illustrated in **Figure 28**, the valve body **1820** can include a plurality of first intermediate components **1840** oriented tangentially to the valve leaflets **1830**. The first intermediate components **1840** can be coupled at a first and second end to the frame **1810** and be coupled to the valve leaflets **1830** along a portion of the first intermediate components **1840** between the first and second ends. As shown in the illustrated embodiment, the ends of the first intermediate components **1840** can be attached to the frame **1810** at or proximate the same location. The valve body **1820** can include a second intermediate component **1850** extending or wrapping around at least a portion of the valve leaflets **1830**. As shown in the illustrated embodiment, the valve body **1820** can include three first intermediate components **1840** and one second intermediate component **1850**. It is to be understood that a greater number or a lesser number of intermediate components **1840**, **1850** can be used.

[0397] With reference next to prosthesis **1900** illustrated in **Figure 29**, the valve body **1920** can include a plurality of first intermediate components **1940**, similar to intermediate components **1840**, which are oriented tangentially to the valve leaflets **1930**. The first intermediate components **1940** can be coupled at a first and second end to the frame **1910** and be coupled to the valve leaflets **1930** along a portion of the first intermediate components **1940** between the first and second ends. As shown in the illustrated embodiment, the ends of the first intermediate components **1940** can be attached to the frame **1910** at or proximate the same location. The valve body **1920** can include second intermediate components **1950**, similar to intermediate components **1640**,

extending radially between the frame **1920** and the valve leaflets **1930**. As shown in the illustrated embodiment, the valve body **1920** can include three first intermediate components **1940** and three second intermediate components **1950**. It is to be understood that a greater number or a lesser number of intermediate components **1940**, **1950** can be used.

[0398] With reference next to the prostheses **2000** illustrated in **Figures 30** and **31**, the prostheses **2000** can include a frame **2010** and a valve body **2020** which can each include valve leaflets schematically represented as structures **2030**. As shown in the illustrated embodiment, the frame **2010** can include projections **2012** extending inwardly towards an interior volume of the frame **2010**. As shown in the illustrated embodiment, the projections **2012** can be formed from a first strut **2014** and a second strut **2016** to form a “V” shaped configuration. The projections **2012** can provide a mounting location for valve body **2020**. For example, at least a portion of the valve body **2020** can be attached directly to the projections **2012** or can be attached via an intermediate component. This can beneficially allow a valve body **2020** having a different shape from frame **2010** to be attached to frame **2010**.

[0399] With reference next to the prostheses **2100** illustrated in **Figures 32**, the prostheses **2100** can include a frame **2110** and a valve body **2120** which can each include valve leaflets schematically represented as structures **2130**. As shown in the illustrated embodiment, the frame **2110** can include projections **2112** extending inwardly towards an interior volume of the frame **2110**. The projections **2112** can provide a mounting location for valve body **2120**. For example, at least a portion of the valve body **2120** can be attached directly to the projections **2112** or can be attached via an intermediate component. This can beneficially allow a valve body **2020** having a different shape from frame **2010** to be attached to frame **2010**. A lower region **2114** of frame **2110** can be sized and shaped to generally correspond to the shape of the valve body **2120** to facilitate mounting along the lower region **2114**. This can beneficially enhance stability of the valve body **2120** when mounted to the frame **2110**.

#### Embodiments of Valve-In-Valve Mechanisms

[0400] With reference to **Figures 33-37**, embodiments of prostheses **2200**, or components thereof such as frames **2210**, **2300**, **2400**, **2500**, **2600** and/or valve bodies **2220**, are illustrated. With reference first to the prosthesis **2200** illustrated in **Figure 33**, the prosthesis **2200** include a frame **2210** and a valve body **2220**. The valve body **2220** can include a plurality of leaflets **2222**. The valve body **2220** can be designed to be used for an extended period of time. However, in some instances, it may be beneficial to utilize a supplemental prosthesis **2250** in order to prolong use of the prosthesis **2200**. As shown in the illustrated embodiment, the prosthesis **2200** can be sized and shaped to receive a supplemental prosthesis **2250** such as, but not limited to, Edwards Lifesciences' Sapien 3 valve, replacement aortic valves, replacement mitral valves, and replacement valves described in U.S. Publication Nos. 2012/0123529, 2013/0030519, and 2013/0030520. The supplemental prosthesis **2250** can include a frame **2260** which can be self-expanding or balloon expandable. The supplemental prosthesis **2250** can also include a plurality of valve leaflets **2270**. While the valve body **2220** has been described as being used for an extended period of time, it is to be understood that the valve body **2220** can be designed to be used temporarily. For example, the prosthesis **2200** and supplemental prosthesis **2250** can be delivered during the same surgical procedure. In such instances, the valve body **2220** can be used to ensure functioning of the heart when the prosthesis **2200** is implanted but before the supplemental prosthesis **2250** is mounted to the prosthesis **2200**. Due to the lower expected period of use for valve body **2220**, the valve body **2220** can be designed to utilize less materials which can allow the valve body **2220** to take on a more compact form factor.

[0401] As shown in the illustrated embodiment, the upper region **2230** of the frame **2210** can serve as a backstop for an upper end of the frame **2260** of the supplemental prosthesis **2250**. For example, in the expanded configuration, the diameter **2222** of the upper or inflow end of the frame **2210** can be less than the diameter **2262** of the upper or inflow end of the frame **2260**. This can beneficially inhibit the frame **2260** of supplemental prosthesis **2250** from moving axially upward past frame **2210** during the cardiac cycle. This can be particularly beneficial during periods of the cardiac cycle in which an upwardly directed force is applied to the prostheses **2200**, **2250**. For example, this upwardly directed force could be applied during systole in cases where the

prostheses **2200**, **2250** are positioned within a native mitral valve. In some embodiments, the diameter **2222** of the upper or inflow end of the frame **2210** can be between about 20mm to about 40mm, between about 25mm to about 35mm, between about 27mm to about 33mm, about 27mm, any sub-range within these ranges, or any other diameter as desired. In some embodiments, the diameter **2222** of the upper or inflow end of the frame **2210** can be between about 20mm to about 45mm, between about 25mm to about 40mm, between about 28mm to about 33mm, about 29mm, any sub-range within these ranges, or any other diameter as desired.

[0402] As shown in the illustrated embodiment, the lower region **2240** of the frame **2210** can have a diameter about the same, or less than, the diameter of the supplemental prosthesis **2250** such that the supplemental prosthesis **2250** is maintained within the lower region **2240** in a press fit, a friction fit, and/or an interference fit. As shown in the illustrated embodiment, the valve body **2220** of the prosthesis **2200**, such as leaflets **2222**, can beneficially enhance stability of the supplemental prosthesis **2250**. For example, the valve body **2220** can beneficially reduce lateral movements of the supplemental prosthesis **2250**. Moreover, in some embodiments, friction between the valve body **2220** and the supplemental prosthesis **2250** can beneficially reduce movement of the supplemental prosthesis **2250** in an axial direction.

[0403] With reference to **Figures 33-37**, embodiments of frames **2300**, **2400**, **2500**, **2600** are illustrated. With reference first to frame **2300** illustrated in **Figure 34**, the frame **2300** can have an upper region **2310** which serves as a backstop for a supplemental prosthesis and a lower region **2320** which interfaces with a portion of the supplemental prosthesis to retain the supplemental prosthesis within the frame **2300**. As shown in the illustrated embodiment, the lower region **2320** includes an interface structure **2322** formed by one or more struts extending forming a “V” shaped configuration. This configuration is similar to that shown in **Figure 5A** having struts **385**. The interface structure **2322** can be inclined or curved towards a longitudinal axis of the frame **2300** such that a lower portion of the interface structure **2322** is positioned closer to the longitudinal axis of the frame **2300** than the lower portion of the interface structure **2322**. The lower portion of the interface structure **2322**, such as the lower apices formed by struts, can beneficially engage portions of the supplemental prosthesis.

For example, in instances where the supplemental prosthesis includes a frame having a plurality of cells, the lower portion of the interface structure **2322** can extend within the cells to retain the supplemental prosthesis within the frame **2300**. While the interface structure **2322** was described as having “V” shaped apices, it is to be understood that the interface structure **2322** can have other geometries and could, for example, be formed as fingers formed from separate struts.

[0404] With reference next to frame **2400** illustrated in **Figure 35**, the frame **2400** can have an upper region **2410** which serves as a backstop for a supplemental prosthesis and an inner frame **2420** which interfaces with a portion of the supplemental prosthesis to retain the supplemental prosthesis within the frame **2400**. As shown in the illustrated embodiment, the inner frame **2420** can include one or more arms coupling the inner frame **2420** to the frame **2400**. The inner frame **2420** can be expandable. For example, the inner frame **2420** can be formed from one or more circumferentially-expandable struts **2424**. In this manner, the inner frame **2420** can be expanded to accommodate a supplemental prosthesis. In some embodiments, the inner frame **2420** can be biased to a smaller diameter than the supplemental prosthesis. This biasing force can beneficially create a friction fit with a supplemental prosthesis. In some embodiments, the frame **2420** can be positioned below the frame **2420**. For example, the frame **2420** can include one or more protrusions which extend from a lower end of the frame **2420**. The protrusions can extend radially inwardly towards a longitudinal axis of the frame **2420** to form a diameter smaller than that of the lower end of the frame **2420**.

[0405] With reference next to frame **2500** illustrated in **Figure 36**, the frame **2500** can have an upper region **2510** which serves as a backstop for a supplemental prosthesis **2550** and a lower region **2520** which can serve as an opposing backstop for the supplemental prosthesis **2550**. With reference next to frame **2600** illustrated in **Figure 37**, the frame **2600** can have an upper region **2610** which serves as a backstop for a supplemental prosthesis. The frame **2600** can include an anchoring feature **2620** having an effective inner diameter less than, or the same as, that of the supplemental prosthesis. In some embodiments, the anchoring feature **2620** can retain the supplemental prosthesis in a manner similar to interface structure **2322** such that portions of the anchoring feature **2620** interface with portions of the supplemental prosthesis, such as cells forming the

frame of the supplemental prosthesis. In some embodiments, the anchoring feature **2620** can retain the supplemental prosthesis in a manner similar to lower region **2520** such that portions of the anchoring feature **2620** serves as an opposing backstop for the supplemental prosthesis.

#### Embodiments of Annular Skirts

[0406] With reference to **Figures 38-40**, embodiments of prostheses **2700**, **2800**, **2900**, or components thereof such as frames **2710**, **2810**, **2910**, valve bodies **2720**, **2820**, **2920**, and skirts **2730**, **2830**, **2930**, are illustrated. With reference first to the prosthesis **2700** illustrated in **Figure 38**, the prosthesis **2700** can include a frame **2710**, a valve body **2720**, and a skirt **2730**. The skirt **2730** can be positioned around and secured to an exterior of the frame **2710**. The skirt **2730** can be annular and can extend entirely circumferentially around the frame **2710**. The skirt **2730** can prevent or inhibit backflow of fluids around the prosthesis **2700**. For example, with the skirt **2730** positioned annularly around an exterior of the frame **2710**, the skirt **2730** can create an axial barrier to fluid flow exterior to the frame **2710** when deployed within a body cavity. The skirt **2730** can form a flange when the skirt **2730** is positioned within a body cavity, such as a native valve, with the flange sealing against at least a portion of tissue surrounding the body cavity. In addition, the skirt **2730** can encourage tissue in-growth between the skirt **2730** and the natural tissue. This may further help to prevent leakage of blood flow around the prosthesis **2700**.

[0407] The skirt **2730** can have a first end **2732** positioned at or proximate an upper or inflow end of the frame **2710** and extend to a second end **2734** positioned at or proximate a lower or outflow end of the frame **2710**. In some embodiments, the second end **2734** can follow the shape of the struts along the lower or outflow end of the frame **2710** as shown, for example, in **Figures 3** and **4**. It is to be understood that other configurations, such as a curved edge or straight edge, can also be used as desired. The skirt **2730** can be attached to the frame **2710** and/or the valve body **2720** using any mechanism or technique as described above, such as sutures and/or adhesives.

[0408] In some embodiments, the skirt **2730** can be formed from a material such as such as knit polyester (e.g., polyethylene terephthalate (PET)) or any other



biocompatible material such as those which are wholly or substantially fluid impermeable, flexible, stretchable, deformable, and/or resilient. In some embodiments, the skirt **2730** can be formed from separate components and can be attached together using any mechanism or technique as described above, such as via sutures and/or adhesives. In other embodiments, the skirt **2730** can be a single component. The skirt **2730** can also include other structures, such as wires formed from resilient materials such as nitinol, to allow at least portions of the skirt **2730** to retain a particular shape. These structures may be positioned on an inner surface of the skirt **2730**.

[0409] As shown, the shape of the frame **2710**, in conjunction with the skirt **2730**, can beneficially enhance hemodynamic performance. For example, the shape of the frame **2710** with a larger, generally cylindrical intermediate region **2712** can allow for significant washout on an underside of the valve **2720**. That is, the shape of the frame **2710** can enhance the exchange of blood from a prior cardiac cycle – which may have stagnated and accumulated in crevices, pockets, and/or surfaces of the frame **2710**, valve **2720**, and/or skirt **2730** – with fresh blood from a current cardiac cycle. This washout can beneficially reduce the risk of thrombosis or clot formation under the valve **2720**.

[0410] With reference next to the prosthesis **2800** illustrated in **Figure 39**, the prosthesis **2800** can include a frame **2810**, a valve body **2820**, and a skirt **2830**. The skirt **2830** can be positioned around and secured to an exterior of the frame **2810**. The skirt **2830** can be annular and can extend entirely circumferentially around the frame **2810**. The skirt **2830** can prevent or inhibit backflow of fluids around the prosthesis **2800**. For example, with the skirt **2830** positioned annularly around an exterior of the frame **2810**, the skirt **2830** can create an axial barrier to fluid flow exterior to the frame **2810** when deployed within a body cavity. In addition, the skirt **2830** can encourage tissue in-growth between the skirt **2830** and the natural tissue. This may further help to prevent leakage of blood flow around the prosthesis **2800**. Unlike the skirt **2730**, the skirt **2830** can be formed such that it remains generally taut against the frame **2810**.

[0411] The skirt **2830** can have a first end **2832** positioned at or proximate an upper or inflow end of the frame **2810** and extend to a second end **2834** positioned at or proximate a lower or outflow end of the frame **2810**. In some embodiments, the second

end **2834** can follow the shape of the struts along the intermediate region **2812** of the frame **2812**. The skirt **2830** can be attached to the frame **2810** and/or the valve body **2820** using any mechanism or technique as described above, such as sutures and/or adhesives.

[0412] The skirt **2830** is preferably formed from a material, such as such as knit polyester (e.g., polyethylene terephthalate (PET)), or any other biocompatible material such as those which are wholly or substantially fluid impermeable, flexible, stretchable, deformable, and/or resilient. In some embodiments, the skirt **2830** can be formed from separate components and can be attached together using any mechanism or technique as described above, such as via sutures and/or adhesives. In other embodiments, the skirt **2830** can be a single component. The skirt **2830** can also include other structures, such as wires formed from resilient materials such as nitinol, to allow at least portions of the skirt **2830** to retain a particular shape. These structures may be positioned on an inner surface of the skirt **2830**.

[0413] As shown, the shape of the frame **2810** can beneficially enhance hemodynamic performance. For example, the shape of the frame **2810** with a larger, generally cylindrical intermediate region **2812** can allow for significant washout on an underside of the valve **2820**. This washout can beneficially reduce the risk of thrombosis or clot formation under the valve **2820**.

[0414] With reference next to the prosthesis **2900** illustrated in **Figure 40**, the prosthesis **2900** can include a frame **2910**, a valve body **2920**, and a skirt **2930**. The skirt **2830** can have a first end **2832** positioned at or proximate an upper or inflow end of the frame **2810** and extend to a second end **2834** positioned at or proximate a lower or outflow end of the frame **2810**.

[0415] Although some embodiments of skirts described herein are formed from materials which can be substantially fluid impermeable, it is to be understood that the skirts can be entirely, or at least partially, formed from materials which are permeable and/or materials with holes formed therethrough. This can allow some blood to pass through and/or around the skirt. In embodiments where the skirt expands in size (e.g., due to systolic pressure), the amount of expansion can be reduced due to blood passing through the skirt. In some implementations, the skirt may not completely contact

surrounding tissue and/or may apply a reduced amount of pressure against surrounding tissue. This can allow some blood to pass around the skirt.

**[0416]** In some embodiments, the entirety, or at least a portion, of the skirt can be formed from a partially porous cloth. The picks-per-inch (PPI) and/or the ends-per-inch (EPI) can be chosen to attain a desired porosity. In some embodiments, the cloth can have a PPI and/or EPI of between about 50 to about 500, a PPI and/or EPI of between about 100 to about 375, a PPI and/or EPI of between about 150 to about 250, any sub-range within these ranges, or any other PPI and/or EPI as desired. The cloth may be structured to incorporate pores via a specific weave pattern. In some embodiments, the skirt may be drilled to form one or more holes.

**[0417]** Use of an at least partially porous skirt and/or a skirt with holes can allow some degree of mitral regurgitation to persist, at least temporarily. This can be particularly beneficial in instances where a sudden correction in mitral regurgitation may be undesirable. For example, an immediate reduction in mitral regurgitation can place a significantly higher load on the left ventricle; however, patients who have functional mitral regurgitation may have a weak left ventricle. This immediate reduction in mitral regurgitation can result in a situation in which the patient's left ventricle is unable to expel all, or a majority, of blood through the aortic valve (e.g., volume overload). As such, it can be beneficial to allow some degree of mitral regurgitation to persist, at least temporarily, to allow the patient's heart to acclimate to an environment of reduced mitral regurgitation.

**[0418]** The amount of blood flow through and/or around the skirt can gradually reduce over time. For example, in some embodiments, the skirts can become effectively impermeable over time. In some embodiments, the skirt can incorporate a material such as, but not limited to hydrogel, which can seal or at least significantly reduce blood flow through pores and/or holes of the skirt. In some embodiments, the size of the pores and/or holes can be chosen such that a platelet response can reduce or eliminate flow through the pores and/or holes, and/or tissue healing (e.g., tissue ingrowth) can reduce or eliminate flow through the pores and/or holes.

**[0419]** The gradual reduction in size of the pores and/or holes can gradually reduce the amount of blood flow through the skirt. In embodiments where the skirt

expands in size, the amount of expansion can gradually increase due to less blood passing through the skirt. In some implementations, the skirt may begin to completely contact surrounding tissue and/or may apply an increased amount of pressure against surrounding tissue. This can reduce, or wholly eliminate, blood flow around the skirt.

**[0420]** In some embodiments, this gradual reduction of blood flow through and/or around the skirt can occur over a period of between about 12 hours to about 72 hours. This can beneficially allow the patient's heart to gradually acclimate to reducing mitral regurgitation while allowing the physician to assess whether the patient's heart is properly acclimating to the reduction in mitral regurgitation. In some embodiments, this gradual reduction of blood flow through and/or around the skirt can occur over an extended period of time. For example, this gradual reduction in blood flow can occur over a period of between about one week to about one month. This can provide the patient's heart with additional time to acclimate to reducing mitral regurgitation. It is to be understood that in some embodiments, blood flow through and/or around the skirt can decrease at a greater rate over a shorter time period (e.g., about 12 hours to about 72 hours) and continue to decrease at a reduced rate over an extended period of time (e.g., up to one month).

**[0421]** With reference to **Figures 48-57**, embodiments of prostheses **3400**, **3500**, **3600**, or components thereof such as frames **3420**, **3520**, **3620**, valve bodies **3440**, **3540**, **3640**, **3740** and skirts **3460**, **3560**, **3660**, are illustrated. These embodiments can include features, such as openings and/or conduits, which can enhance hemodynamic performance of the prostheses **3400**, **3500**, **3600**. With reference first to the prosthesis **3400** illustrated in **Figures 48** and **49**, the prosthesis **3400** can include a frame **3420**, a valve body **3440**, and a skirt **3460**. As shown in the illustrated embodiment, the prosthesis **3400** can be positioned within a native mitral valve. The frame **3420** can be self-expanding or balloon expandable. The frame **3420** can include a frame body formed from a plurality of struts defining a plurality of cells. One or more of the cells can allow the frame **3420** to longitudinally foreshorten when the frame **3420** radially expands. Although not shown, the frame **3420** can include one or more anchoring features to secure the prosthesis to a native valve, such as a native mitral valve.

[0422] The valve body **3440** preferably includes a plurality of valve leaflets **3442** each having at least a first edge **3444** and a second edge **3446**. The cusp or first edge **3444**, which may be considered a proximal edge, may be arcuate in shape. The second edge **3446** can be a freely moving edge which can allow the valve body **3440** to open and close. The valve leaflet **3442** can be similar to leaflet **1110** illustrated in **Figure 19A** which includes a first edge **1112**, a second edge **1114**, and tabs **1116**. The plurality of valve leaflets **3442** can function in a manner similar to the native mitral valve, or to any other valves in the vascular system as desired.

[0423] The skirt **3460** can be attached to the frame **3420**. The skirt **3460** can be positioned around and secured to an exterior of the frame **3420**. The skirt **3460** can be annular and can extend entirely circumferentially around the frame **3420**. The skirt **3460** can generally prevent or inhibit backflow of fluids, such as blood, around the prosthesis **3400**. For example, with the skirt **3460** positioned annularly around an exterior of the frame **3420**, the skirt **3460** can create an axial barrier to fluid flow exterior to the frame **3420** when deployed within a body cavity such as a native valve annulus. As shown in the illustrated embodiment, the skirt **3460** can be tautly secured around the frame **3420**. However, it is to be understood that the skirt **3460** can be loosely attached to the exterior of the frame **3420**. As shown in the illustrated embodiment, at least a portion of the first edge **3444** can be attached to the skirt **3460**.

[0424] The skirt **3460** can include one or more openings **3462** in the material forming the skirt **3460**. The openings **3462** can be positioned within an area of the skirt **3460** between the first edge **3444** of a valve leaflet **3442** (i.e., an area of the skirt positioned behind a valve leaflet **3442**). In some embodiments, the skirt **3460** can include at least one opening **3462** for each valve leaflet **3442**. The one or more openings **3462** can beneficially enhance hemodynamic performance of the prosthesis **3400**. For example, the one or more openings **3462** can allow for significant washout on an underside of the valve **3420**. That is, the one or more openings **3462** can enhance the exchange of blood from a prior cardiac cycle – which may have stagnated and accumulated in crevices, pockets, and/or surfaces of the frame **3420**, valve body **3440**, and/or skirt **3460** – with fresh blood from a current cardiac cycle. This washout can beneficially reduce the risk of thrombosis or clot formation under the valve body **3440**.

In some instances, since the space between the valve leaflet **3442** and the skirt **3460** is generally shielded from the primary flow field of the prosthesis **3400**, blood within this space can begin to stagnate thereby increasing the risk of thrombosis. The one or more openings **3462** can reduce, or eliminate, the amount of stagnant blood within this space. Blood flow through the one or more openings **3462** can occur due to a pressure differential across the prosthesis **3400** (e.g., pressure differential between the left atrium and left ventricle during diastole and systole) and/or momentum (e.g., momentum of blood flow during systole). The one or more openings **3462** can take on shapes such as those illustrated in **Figures 50-52** (e.g., circular, diamond-shaped, triangular, etc.). In some embodiments, the one or more openings **3462** can have different shapes.

[0425] As shown in the illustrated embodiment, the one or more openings **3462** can be positioned along the skirt **3460** at or proximate a proximal region of the space between the valve leaflet **3442** and the skirt **3460**. For example, the one or more openings **3462** can be positioned at or proximate the attachment between the cusp or first edge **3444** and the skirt **3460** near a proximal area of this attachment (as shown in **Figure 50**). By positioning the one or more openings **3462** at or proximate a proximal region of the space between the valve leaflet **3442** and the skirt **3460**, a greater degree of washout of the space between the valve leaflet **3442** and the skirt **3460** can be achieved. This can beneficially ensure that a majority, if not the entirety, of the valve leaflet **3442** is washed or flushed and reduce the likelihood of build-up of stagnant blood.

[0426] In some embodiments, the one or more openings **3462** can be positioned at least above the distalmost part of the valve leaflet **3442** (e.g., the second edges **3446**) when coapted during the systolic phase. In some embodiments, the one or more openings **3462** can be positioned at or proximate a proximalmost region of the space between the valve leaflet **3442** and the skirt **3460**. It is to be understood that the positioning, number, and size of the openings **3462** can be chosen based on numerous factors including, but not limited to, the geometry of the prosthesis **3400** (i.e., frame **3420**, valve body **3440**, and/or skirt **3460**) and the desired amount of washout.

[0427] As shown in **Figure 48**, in some embodiments the one or more openings **3462** can allow antegrade blood flow through the space between the valve leaflet **3442** and the skirt **3460** and into the ventricle during diastole. This can allow

stagnant or trapped blood on the underside of the valve leaflet **3442** and the skirt **3460**, from a prior systolic phase, to be flushed during the diastolic phase. As shown in **Figure 49**, in some embodiments the one or more openings **3462** can allow retrograde blood flow through the space between the valve leaflet **3442** and the skirt **3460** and into the atrium during systole. This can allow blood which was previously trapped on the underside of the valve leaflet **3442** and the skirt **3460**, from a prior diastolic phase, to be flushed during the systolic phase.

[0428] In some embodiments (not shown), the one or more openings **3462** can include one-way valves which allow blood to flow through the one or more openings **3462** during systole or diastole while preventing or inhibiting blood to flow through the one or more openings **3462** during the opposite phase. This can beneficially decrease undesirable retrograde flow during systole or antegrade flow during diastole through the one or more openings **3462**. In some embodiments, some of the one or more openings **3462** can include one-way valves whereas other of the one or more openings **3462** can permit flow in both directions. In this manner, the effective area of the one or more openings **3462** can differ depending on the directionality of blood flow. For example, in embodiments where the one-way valves permit antegrade flow, the effective area of the one or more openings **3462** during diastole is greater than the effective area during systole. This can be beneficial due to the difference in pressure differential between the left atrium and left ventricle during diastole as compared to the pressure differential between the left atrium and left ventricle during systole. Since this pressure differential is generally greater during systole, a greater amount of blood would flow through the one or more openings **3462** as compared to the amount of blood flow during diastole. It is to be understood that in some embodiments, at least one of the one-way valves can allow retrograde flow and at least one of the one-way valves may allow antegrade flow.

[0429] With reference next to the prosthesis **3500** illustrated in **Figures 54** and **55**, the prosthesis **3500** can include a frame **3520**, a valve body **3540**, and a skirt **3560**. As shown in the illustrated embodiment, the prosthesis **3500** can be positioned within a native mitral valve. The frame **3520** can be self-expanding or balloon expandable. The frame **3520** can include a frame body formed from a plurality of struts defining a plurality of cells. One or more of the cells can allow the frame **3520** to

longitudinally foreshorten when the frame **3520** radially expands. The frame **3520** can include one or more anchoring features **3522**, such as an annular flange, to secure the prosthesis to a native valve, such as a native mitral valve.

[0430] The valve body **3540** preferably includes a plurality of valve leaflets **3542** each having at least a first edge **3544** and a second edge **3546**. The cusp or first edge **3544**, which may be considered a proximal edge, may be arcuate in shape. The second edge **3546** can be a freely moving edge which can allow the valve body **3540** to open and close. The valve leaflet **3542** can be similar to leaflet **1110** illustrated in **Figure 19A** which includes a first edge **1112**, a second edge **1114**, and tabs **1116**. The plurality of valve leaflets **3542** can function in a manner similar to the native mitral valve, or to any other valves in the vascular system as desired.

[0431] The skirt **3560** can be attached to the frame **3520**. The skirt **3560** can be positioned around and secured to an exterior of the frame **3520**. The skirt **3560** can be annular and can extend entirely circumferentially around the frame **3520**. The skirt **3560** can generally prevent or inhibit backflow of fluids, such as blood, around the prosthesis **3500**. For example, with the skirt **3560** positioned annularly around an exterior of the frame **3520**, the skirt **3560** can create an axial barrier to fluid flow exterior to the frame **3520** when deployed within a body cavity such as a native valve annulus. As shown in the illustrated embodiment, the skirt **3560** can be tautly secured around the frame **3520** including the anchoring feature **3522**. However, it is to be understood that the skirt **3560** can be loosely attached to the exterior of the frame **3520**. As shown in the illustrated embodiment, at least a portion of the first edge **3544** of the valve leaflet **3542** can be attached to the skirt **3560**.

[0432] The prosthesis **3500** can include one or more channels or conduits **3580** which can allow fluid ingress into and egress out of the space between the valve leaflet **3442** and the skirt **3460**. For example, the prosthesis **3500** can include at least one conduit **3580** for each valve leaflet **3542**. These conduits **3580** can extend between openings in the material forming the skirt **3560**. As shown, the skirt **3560** can include an opening along a portion of the skirt **3560** proximate the valve leaflet **3542** (similar to that described above in connection with **Figures 48** and **49**) and an opening along a portion of the skirt **3560** extending along the anchoring feature **3522**. The conduit **3580** can



form a fluid pathway between these openings. In some embodiments, such as that shown, the conduits **3580** can extend past these openings. For example, the conduits **3580** can extend distally past the anchoring feature **3522** and extend into the atrium and/or the conduits **3580** can extend into a space between the skirt **3560** and the valve leaflet **3442**. Blood flow through the one or more conduits **3580** can occur due to a pressure differential across the prosthesis **3500** (e.g., pressure differential between the left atrium and left ventricle during diastole and systole) and/or momentum (e.g., momentum of blood flow during systole).

[0433] The one or more conduits **3580** can be formed as structures separate from other components of the prosthesis **3500** such as the frame **3520**, valve body **3540**, and/or the skirt **3560**. For example, the conduit **3580** can be a tube which is attached to one or more other components of the prosthesis **3500**. However, it is to be understood that the one or more conduits **3580** can form part of one of the other components of the prosthesis **3500**. For example, the one or more conduits **3580** can form part of the frame **3520**. As another example, the one or more conduits **3580** can form part of the skirt **3560**. In some embodiments, the one or more conduits **3580** can be a crease, such as a v-shaped crease, of the skirt **3560** which extends between the anchoring feature **3522** and the space between the skirt **3560** and the leaflets **3542**.

[0434] By utilizing conduits **3580**, the pathway for blood flow can be controlled. This can be beneficial in instances where the prosthesis **3500** includes structures positioned between the skirt **3560** and the left atrium such as anchoring feature **3522**. Other examples include another skirt positioned exteriorly of the skirt **3560** such that the skirt **3560** is an inner skirt. The one or more channels or conduits **3580** can beneficially enhance hemodynamic performance of the prosthesis **3500**. For example, the one or more conduits **3580** can allow for significant washout on an underside of the valve body **3540**. That is, the one or more conduits **3580** can enhance the exchange of blood from a prior cardiac cycle, which may have stagnated and accumulated in crevices, pockets, and/or surfaces of the frame **3520**, valve body **3540**, and/or skirt **3560**, with fresh blood from a current cardiac cycle. This washout can beneficially reduce the risk of thrombosis or clot formation under the valve body **3540**.

[0435] As shown in the illustrated embodiment, the one or more conduits **3580** can be positioned such that blood flows at or proximate a proximal region of the space between the valve leaflet **3542** and the skirt **3560**. For example, the one or more conduits **3580** can be positioned such that blood flows at or proximate the attachment between the first edge **3544** and the skirt **3560** near a proximal area of this attachment. By positioning the one or more conduits **3580** such that blood flows at or proximate a proximal region of the space between the valve leaflet **3542** and the skirt **3560**, a greater degree of washout of the space between the valve leaflet **3542** and the skirt **3560** can be achieved. This can beneficially ensure that a majority, if not the entirety, of the valve leaflet **3442** is washed or flushed and reduce the likelihood of build-up of stagnant blood.

[0436] In some embodiments, the one or more conduits **3580** can be positioned such that blood flows at least above the distalmost part of the valve leaflet **3542** (e.g., the second edges **3546**) when coapted during the systolic phase. In some embodiments, the one or more conduits **3580** can be positioned at or proximate a proximalmost region of the space between the valve leaflet **3442** and the skirt **3460**. It is to be understood that the positioning, number, and size of the conduits **3580** can be chosen based on numerous factors including, but not limited to, the geometry of the prosthesis **3500** (i.e., frame **3520**, valve body **3540**, and/or skirt **3560**) and the desired amount of washout.

[0437] As shown in **Figure 54**, in some embodiments the one or more conduits **3580** can allow antegrade blood flow through the space between the valve leaflet **3542** and the skirt **3560** and into the ventricle during diastole. This can allow stagnant or trapped blood on the underside of the valve leaflet **3542** and the skirt **3560**, from a prior systolic phase, to be flushed during the diastolic phase. As shown in **Figure 55**, in some embodiments the one or more conduits **3580** can allow retrograde blood flow through the space between the valve leaflet **3542** and the skirt **3560** and into the atrium during systole. This can allow blood which was previously trapped on the underside of the valve leaflet **3542** and the skirt **3560**, from a prior diastolic phase, to be flushed during the systolic phase.

[0438] In some embodiments, the one or more conduits **3580** can include one-way valves which allow blood to flow through the one or more conduits **3580** during

systole or diastole while preventing or inhibiting blood to flow through the one or more conduits **3580** during the opposite phase. This can beneficially decrease undesirable retrograde flow during systole or antegrade flow during diastole through the one or more conduits **3580**. In some embodiments, some of the one or more conduits **3580** can include one-way valves whereas other of the one or more conduits **3580** can permit flow in both directions. In this manner, the effective area of the one or more conduits **3580** can differ depending on the directionality of blood flow. It is to be understood that in some embodiments, at least one of the one-way valves can allow retrograde flow and at least one of the one-way valves may allow antegrade flow.

[0439] Although prosthesis **3500** incorporates one or more conduits **3580** extending between openings formed in the material of the skirt **3560**, it is to be understood that the valve body **3540** and/or skirt **3560** can include openings which are not connected with conduits **3580**. For example, the one or more openings can be formed along parts of the valve body, such as valve leaflets and/or intermediate components (not shown) as described above. Moreover, it is to be understood that in some embodiments, the conduits can be omitted and the skirt **3560** can simply include openings along a portion of the skirt **3560** extending along the frame. These openings can be positioned within an area of the skirt **3560** between the first edge **3544** of a valve leaflet **3542** (i.e., an area of the skirt positioned behind a valve leaflet **3442**). These openings can be positioned within a portion of the skirt **3560** extending along the frame at the anchoring feature **3522**. This can beneficially allow washout in a space between the skirt **3560** and the valve leaflet **3542** as well as in a space between the skirt **3560** and the native mitral valve leaflet (e.g., above the native mitral valve leaflet).

[0440] With reference next to the prosthesis **3600** illustrated in **Figures 56** and **57**, the prosthesis **3600** can include a frame **3620**, a valve body **3640**, and a skirt **3660**. While the embodiments of prostheses **3400**, **3500**, and **3600** have included openings within skirts, it is to be understood that other components of the prosthesis can include one or more openings. For example, components of the valve body, such as the intermediate components and/or the valve leaflets can include one or more openings.

[0441] With reference to **Figures 58-73**, embodiments of prostheses **3800**, **3900**, **4000**, **4100**, **4200**, **4300**, **4400**, **4500**, **4600**, **4700** or components thereof such as

frames **3820**, **3920**, **4020**, **4120**, **4220**, **4320**, **4420**, **4520**, **4620**, **4720** and skirts **3860**, **3960**, **4060**, **4160**, **4260**, **4360**, **4460**, **4560**, **4660**, **4760** are illustrated. These embodiments illustrate components and geometries of skirts which can beneficially reduce paravalvular leakage around the prostheses when implanted within a native valve.

[0442] With reference first to the prosthesis **3800** illustrated in **Figures 58-61**, the prosthesis **3800** can include a frame **3820**, a valve body (not shown), and a skirt **3860** which can be attached to the frame **3820**. **Figure 58** illustrates the frame **3820** with the proximal end of the skirt **3860** detached from the frame **3820**. **Figure 59** is a perspective-oriented, exploded schematic view of the skirt **3860** to illustrate the various parts forming the skirt **3860**. **Figures 60** and **61** illustrate the skirt **3860** in a first configuration and a second configuration. The frame **3820** can be self-expanding or balloon expandable. As shown in the illustrated embodiment, the frame **3820** can include a frame body formed from a plurality of struts defining a plurality of cells. One or more of the cells can allow the frame **3820** to longitudinally foreshorten when the frame **3820** radially expands.

[0443] The skirt **3860** can be positioned around and secured to an exterior of the frame **3820**. As shown in the illustrated embodiment, the skirt **3860** can be loosely attached to the exterior of the frame **3820**. The skirt **3860** can generally prevent or inhibit backflow of fluids, such as blood, around the prosthesis **3800**. For example, with the skirt **3860** positioned annularly around an exterior of the frame **3820**, the skirt **3860** can create an axial barrier to fluid flow exterior to the frame **3820** when deployed within a body cavity such as a native valve annulus. As such, the skirt **3860** can have a geometry which forms an advantageous seal over the native valve annulus, such as that of the native mitral valve annulus.

[0444] The skirt **3860** can be formed from multiple components such as an upper component **3862** and a lower component **3864**. As shown in **Figures 60** and **61**, the upper component **3862** can be attached to an upper portion of the frame **3820**, such as an upper edge or inflow end of the frame **3820**. The upper component **3862** can extend downwardly and be attached to the lower component **3864**. The lower component **3864** can be attached to the upper component **3862**. As shown in the illustrated embodiment, the lower component **3864** can extend downwardly. As shown, the lower edge of the

lower component **3864** can be attached along a lower portion of the frame **3820**, such as a lower edge or outflow end of the frame **3820**. It is contemplated that the lower component **3864** can have a lower edge with a shape that matches the lower edge of the frame **3820**. While the skirt **3860** is formed from two components – an upper component **3862** and a lower component **3864** – it is to be understood that the skirt **3860** can be formed from a fewer number of components or a greater number of components. For example, the skirt **3860** can be formed as a monolithic unit.

[0445] In embodiments where the prosthesis **3800** is designed for use in the native mitral valve, the prosthesis **3800** can include a valve body which inhibits or prevents blood flow in a retrograde direction (i.e., in a direction from the lower edge to the upper edge). As shown in **Figure 61**, blood flow can be directed from within the frame **3820** and outwardly towards the skirt **3860** to expand the skirt **3860**. In so doing, the skirt **3860** can impart a force on the native mitral valve annulus to enhance sealing and beneficially reduce paravalvular leakage. As shown, when in a radially expanded configuration, the skirt **3860** can have a shape which bulges radially outwardly closer to the upper end of the frame **3820** than the lower end of the frame **3820** due to the size of the components **3862**, **3864** and the location of the seam lines. This can be beneficial in instances where the skirt **3860** is intended to be seated generally supra-annularly. However, it is to be understood that the skirt **3860** can have a shape which bulges radially outwardly closer to the lower end of the frame **3820** than the upper end of the frame **3820** when the skirt **3860** in a radially expanded configuration. This can be achieved by modifying the position of the attachment points of the skirt **3860**. For example, the attachment point between the components **3862**, **3864** can be shifted upwards.

[0446] With reference next to the prosthesis **3900** illustrated in **Figures 62-65**, the prosthesis **3900** can include a frame **3920**, a valve body (not shown), and a skirt **3960** which can be attached to the frame **3920**. **Figure 62** illustrates the frame **3920** with components of the skirt **3960** detached from each other. **Figure 63** is a perspective-oriented, exploded schematic view of the skirt **3960** to illustrate the various parts forming the skirt **3960**. **Figures 64** and **65** illustrate the skirt **3960** in a first configuration and a second configuration. The skirt **3960** can be formed from multiple

components such as an upper component **3962**, a middle component **3964**, and a lower component **3966**. The upper component **3962** can be attached to an upper portion of the frame **3920**, such as an upper edge or inflow end of the frame **3920**. The upper component **3962** can extend downwardly and be attached to the middle component **3964**. The lower component **3966** can be attached to the middle component **3964** and can extend downwardly. As shown, the lower edge of the lower component **3966** can be attached along a lower portion of the frame **3920**, such as a lower edge or outflow end of the frame **3920**. It is contemplated that the lower component **3964** can have a lower edge with a shape that matches the lower edge of the frame **3920**. While the skirt **3960** is formed from three components, it is to be understood that the skirt **3960** can be formed from a fewer number of components or a greater number of components. For example, the skirt **3960** can be formed as a monolithic unit.

[0447] In embodiments where the prosthesis **3900** is designed for use in the native mitral valve, the prosthesis **3900** can include a valve body which inhibits or prevents blood flow in a retrograde direction (i.e., in a direction from the lower edge to the upper edge). As shown in **Figure 65**, blood flow can be directed from within the frame **3920** and outwardly towards the skirt **3960** to expand the skirt **3960**. As shown, when in a radially expanded configuration, the skirt **3960** can have a supplemental rib or extension formed by the middle component **3964**. The supplemental rib can have a partially toroidal shape, formed by the middle component **3964**, which extends further radially outward from the middle portion of the skirt **3960** which itself forms an annular ring. This shape can be achieved via sizing of the components **3962**, **3964**, **3966** and the location of the seam lines. For example, portions of the components **3962**, **3964**, **3966** can overlap prior to being sutured or attached. This partially toroidal extension can beneficially increase the volume of the skirt in a region between an upper side and a lower side of the native valve annulus (e.g., an atrial side and a ventricular side of the native mitral valve annulus). This can beneficially ensure that the skirt **3960** forms a seal within the native valve annulus without significantly increasing the amount of material for the skirt **3960**. This can beneficially allow the prosthesis **3900** to maintain a smaller form factor when in a collapsed configuration for delivery. While the partially toroidal extension is shown generally along a middle portion of the skirt **3960** when the skirt

**3960** is in an expanded configuration, it is to be understood that the partially toroidal extension can be positioned higher or lower along the skirt **3960** when the skirt **3960** is in an expanded configuration.. Moreover, while the partially toroidal extension has been described as having a greater volume within the native valve annulus to form a seal within the native valve annulus, it is to be understood that the partially toroidal extension can be positioned above or below the native valve annulus to seal above or below the native valve annulus.

[0448] With reference next to the prosthesis **4000** illustrated in **Figure 66**, the prosthesis **4000** can include a frame **4020**, a valve body (not shown), and a skirt **4060** which can be attached to the frame **4020**. In embodiments where the prosthesis **4000** is designed for use in the native mitral valve, the prosthesis **4000** can include a valve body which inhibits or prevents blood flow in a retrograde direction (i.e., in a direction from the lower edge to the upper edge). As shown, since the lower edge of the skirt **4060** is attached to the lower edge of the frame **4020**, blood flow can be directed from within the frame **4020** and outwardly towards the skirt **4060** to expand the skirt **4060**. As shown, when in an expanded configuration, the skirt **4060** can have a shape which bulges radially outwardly closer to the upper end of the frame **4020** than the lower end of the frame **4020**. The skirt **4060** can also have a generally concave shape near a lower end of the skirt **4060**. This can be beneficial in instances where the skirt **4060** is intended to be seated generally supra-annularly. However, it is to be understood that the dimensions of the skirt **4060** can be reversed.

[0449] With reference next to the prosthesis **4100** illustrated in **Figure 67**, the prosthesis **4100** can include a frame **4120**, a valve body (not shown), and a skirt **4160** which can be attached to the frame **4120**. In embodiments where the prosthesis **4100** is designed for use in the native mitral valve, the prosthesis **4100** can include a valve body which inhibits or prevents blood flow in a retrograde direction (i.e., in a direction from the lower edge to the upper edge). As shown, since the lower edge of the skirt **4160** is not attached to the lower edge of the frame **4120**, blood flow can be directed from outside the frame **4120** and into the skirt **4160**. Moreover, blood flow can be directed from within the frame **4120** and outwardly towards the skirt **4160** to expand the skirt **4160**. As shown, when in an expanded configuration, the skirt **4160** can have a shape

which is generally cylindrical. However, it is to be understood that the skirt **4160** can have a non-cylindrical shape. For example, as shown in **Figure 68**, the skirt **4260** can have a shape which bulges radially outwardly closer to the upper end of the frame **4220** than the lower end of the frame **4220**. However, it is to be understood that the dimensions of the skirt **4260** can be reversed.

[0450] With reference next to the prosthesis **4300** illustrated in **Figure 69**, the prosthesis **4300** can include a frame **4320**, a valve body (not shown), and a skirt **4360** which can be attached to the frame **4320**. In embodiments where the prosthesis **4300** is designed for use in the native mitral valve, the prosthesis **4300** can include a valve body which inhibits or prevents blood flow in a retrograde direction (i.e., in a direction from the lower edge to the upper edge). As shown, since the lower edge of the skirt **4360** is attached to the lower edge of the frame **4320**, blood flow can be directed from within the frame **4320** and outwardly towards the skirt **4360** to expand the skirt **4360**. As shown, when in an expanded configuration, the skirt **4360** can have a shape which bulges radially outwardly closer to the lower end of the frame **4320** than the upper end of the frame **4320**. In some embodiments, such as that of prosthesis **4400** of **Figure 70**, the skirt **4460** can include a bulge which can beneficially be positioned proximate a lower anchoring feature **4422** of the frame **4420**. This can enhance sealing sub-annularly by imparting a force upon the native leaflets towards a sub-annular surface of the native annulus. However, it is to be understood that the dimensions can be reversed.

[0451] **Figures 71-73** illustrate top-oriented cross-sectional schematic views of prostheses **4500**, **4600**, **4700**. The skirts **4560**, **4660**, **4700** can correspond to the skirts described above in connection with **Figures 66-69** or any other skirt as described herein. With reference first to the prosthesis **4500** illustrated in **Figure 71**, the prosthesis **4500** can include a frame **4520**, a valve body (not shown), and a skirt **4560** which can be attached to the frame **4520**. The skirt **4560** can extend around the entire periphery of the frame **4520** to a generally equivalent radial dimension when in an expanded configuration.

[0452] With reference next to the prosthesis **4600** illustrated in **Figure 72**, the prosthesis **4600** can include a frame **4620**, a valve body (not shown), and a skirt **4660** which can be attached to the frame **4620**. As shown, when in an expanded configuration,



the skirt **4660** can extend partially around the entire periphery of the frame **4620**. This can be beneficial in instances where the prosthesis **4600** is positioned within native anatomy which is non-circular in shape and/or in instances where targeted contact locations can be advantageous. Moreover, this configuration can reduce the total material usage for skirt **4660** which can advantageously reduce the overall form factor when in a compact configuration for delivery.

[0453] With reference next to the prosthesis **4700** illustrated in **Figure 73**, the prosthesis **4700** can include a frame **4720**, a valve body (not shown), and a skirt **4760** which can be attached to the frame **4720**. As shown, the skirt **4760** can extend around the entire periphery of the frame **4720**. When in an expanded configuration, the skirt **4760** can extend to different radial dimensions with a first peripheral region **4762** extending to a first radial dimension and a second peripheral region **4764** extending to a second radial dimension greater than the first radial dimension. The second region **4764** can form one or more bulges which extends further radially outward than the other portions of the skirt **4760**. This can be beneficial in instances where the prosthesis **4700** is positioned within native anatomy which is non-circular in shape and/or in instances where targeted contact locations can be advantageous. Moreover, this configuration can reduce the total material usage for skirt **4760** which can advantageously reduce the overall form factor when in a compact configuration for delivery.

[0454] Although the skirts **3860**, **3960**, **4060**, **4160**, **4260**, **4360**, **4460** described above are illustrated as extending the entire height of the frames **3820**, **3920**, **4020**, **4120**, **4220**, **4320**, **4420**, it is to be understood that the skirts can extend only a part of the height of the frames.

[0455] With reference to **Figures 74-79**, embodiments of prostheses **4800**, **4900**, **5000**, **5100**, or components thereof such as frames **4820**, **4920**, **5020**, **5120**, valve bodies **4840**, and skirts **4860**, **4960**, **5060**, **5160**, are illustrated. These embodiments illustrate methods by which skirts can extend radially outwardly and impart a force upon native tissue, such as tissue of a native valve annulus. With reference first to the prosthesis **4800** illustrated in **Figure 74**, the prosthesis **4800** can include a frame **4820**, a valve body **4840**, and a skirt **4860** which can be attached to the frame **4820**. The frame **4820** can be self-expanding or balloon expandable. As shown in the illustrated

embodiment, the frame **4820** can include a frame body formed from a plurality of struts defining a plurality of cells. One or more of the cells can allow the frame **4820** to longitudinally foreshorten when the frame **4820** radially expands.

[0456] The valve body **4840** preferably includes a plurality of valve leaflets **4842** and a valve skirt **4843**. The valve skirt **4843** can include one or more openings or windows **4844** which can allow fluid communication between an interior of the valve body **4840** and an interior of the skirt **4860**. These openings or windows **4844** can be similar to those described above in connection with **Figures 48-56**. The plurality of valve leaflets **4842** can function in a manner similar to the native mitral valve, or to any other valves in the vascular system as desired. The skirt **4860** can be positioned around and secured to an exterior of the frame **4820**. As shown in the illustrated embodiment, the skirt **4860** can be loosely attached to the exterior of the frame **4820**. The skirt **4860** can generally prevent or inhibit backflow of fluids, such as blood, around the prosthesis **4800**. For example, with the skirt **4860** positioned annularly around an exterior of the frame **4820**, the skirt **4860** can create an axial barrier to fluid flow exterior to the frame **4820** when deployed within a body cavity such as a native valve annulus. As such, the skirt **4860** can have a geometry which forms an advantageous seal over the native valve annulus, such as that of the native mitral valve annulus.

[0457] In embodiments where the prosthesis **4800** is designed for use in the native mitral valve, the prosthesis **4800** can include a valve body **4840** which inhibits or prevents blood flow in a retrograde direction (i.e., in a direction from the lower edge to the upper edge). As shown, blood flow can be directed from within the frame **4820** and outwardly towards the skirt **4860** to expand the skirt **4860**. The openings or windows **4844** of the valve skirt **4843** can beneficially direct blood flow towards particular areas of the skirt **4860**. In so doing, the skirt **4860** can impart a force on the native mitral valve annulus to enhance sealing and beneficially reduce paravalvular leakage. As shown, multiple openings or windows **4844** can be positioned along the valve skirt **4843** at various axial positions. In some embodiments, multiple openings or windows can form a row which extends a substantial portion of the height of the frame **4820**. In some embodiments, a single opening can extend a substantial portion of the height of the frame

**4820.** However, it is to be understood that the openings or windows **4844** can instead be positioned a part of the height of the frame **4820**.

[**0458**] In some embodiments, components of the prosthesis **4800**, such as the valve body **4840** and/or skirt **4860**, can include one or more one-way valves which inhibit or prevent blood from flowing out of the skirt **4860**. For example, as shown in the embodiment of valve skirt **4843'** illustrated in **Figures 75-77**, the valve skirt **4843'** can include one-way valves **4846'** in the form of flaps which cover the openings **4844'** in the valve skirt **4843'**. As shown in **Figure 75**, the one-way valves **4846'** can be positioned along an exterior of the valve skirt **4843'**. The one-way valves **4846'** can be attached to the valve skirt **4843'** via sutures along at least a portion of the periphery of the one-way valves **4846'**. For example, as shown in the illustrated embodiment, the one-way valves **4846'** can be attached to the valve skirt **4843'** along side edges **4848a'**, **4848b'** of the one-way valves **4846'**. However, it is to be understood that the one-way valves **4846'** can be attached to the valve skirt **4843'** along other portions of the periphery such as the top and/or bottom edges of the one-way valves **4846'**.

[**0459**] The one-way valves **4846'** can allow flow in a first direction and reduce or inhibit flow in a second direction opposite the first direction. For example, as shown in **Figure 76**, the one-way valves **4846'** can transition to an open configuration when subject to fluid flow in a direction from a first side of the valve skirt **4843'** to a second side of the valve skirt **4843'**. As shown in **Figure 77**, the one-way valves **4846'** can transition to a closed configuration when subject to fluid flow in a direction from a second side of the valve skirt **4843'** to a first side of the valve skirt **4843'**. In some instances, this transitioning between open and closed configurations may be caused by a pressure differential between the two sides of the valve skirt **4843'**. For example, the one-way valves **4846'** can transition into the open configuration during systole and transition into the closed configuration during diastole. However, it is to be understood that the operation of the one-way valves **4846'** may be reversed such that the one-way valves **4846'** transition into the open configuration during diastole and transition into the closed configuration during systole.

[**0460**] In some embodiments, the one or more one-way valves **4846'** can allow flow in a first direction from inside the valve body, such as valve body **4840**, and

into a skirt, such as skirt **4860**, and reduce or inhibit flow in a second direction out of the skirt into the valve body. For example, the one or more one-way valves **4846'** can allow flow into a skirt, such as skirt **4860**, during systole and reduce or inhibit flow out of the skirt during diastole. This can beneficially ensure that the skirt **4860** remains in a generally enlarged configuration throughout the various phases of the cardiac cycle and thereby reduce material fatigue. Moreover, since the skirt **4860** is maintained in the second configuration with a fluid, the skirt **4860** can better conform to the native anatomy. This can beneficially enhance tissue ingrowth along the skirt **4860** due to constant contact with surrounding body tissue.

[0461] Additionally, by ensuring that the skirt **4860** remains in a generally enlarged configuration, the amount of blood traveling into skirt **4860** during systole can be reduced since the skirt **4860** is already filled with blood. This can advantageously increase efficiency of the left ventricle since little to no blood volume is pumped into the skirt **4860** once the skirt **4860** is filled. Moreover, by relying on blood flow into the skirt **4860**, the prosthesis **4800** can advantageously take on a relatively compact form factor when initially delivered to the native heart valve. In some instances, since the skirt **4860** is maintained in the second configuration with blood, the consistency of the skirt **4860** can more closely match that of native valve tissue and allow movement of the prosthesis **4800** to be dampened during the cardiac cycle.

[0462] It is to be understood that the one-way valves **4846'** can take on other forms, such as duckbill valves and slit valves. In some embodiments, the one-way valves **4846'** can incorporate features, such as nitinol struts, which bias the one-way valves **4846'** into a closed configuration. As another example, the one-way valves **4846'** can be shaped similarly to a windsock with a larger cross-sectional area at an inlet end and a smaller cross-sectional area at an outlet end. When subject to flow in a first direction from the inlet end to the outlet end, the one-way valve **4846'** can transition to an expanded configuration in which the one-way valve **4846'** allows blood to flow through the valve **4846'**. When subject to flow in a second direction from the outlet end to the inlet end, the one-way valve **4846'** can collapse upon itself such that blood is not allowed to flow through the valve **4846'**.

[0463] With reference first to the prosthesis **4900** illustrated in **Figures 78** and **79**, the prosthesis **4900** can include a frame **4920**, a valve body (not shown), and a skirt **4960** which can be attached to the frame **4920**. The frame **4920** can be self-expanding or balloon expandable. As shown in the illustrated embodiment, the frame **4920** can include a frame body formed from a plurality of struts defining a plurality of cells. One or more of the cells can allow the frame **4920** to longitudinally foreshorten when the frame **4920** radially expands.

[0464] The skirt **4960** can be positioned around and secured to an exterior of the frame **4920**. As shown in the illustrated embodiment, the skirt **4960** can be loosely attached to the exterior of the frame **4920**. The skirt **4960** can generally prevent or inhibit backflow of fluids, such as blood, around the prosthesis **4900**. For example, with the skirt **4960** positioned annularly around an exterior of the frame **4920**, the skirt **4960** can create an axial barrier to fluid flow exterior to the frame **4920** when deployed within a body cavity such as a native valve annulus. As such, the skirt **4960** can have a geometry which forms an advantageous seal over the native valve annulus, such as that of the native mitral valve annulus.

[0465] As shown, the prosthesis **4900** can include a biasing member **4980**, such as a radial or torsion spring, which imparts a radially outward force upon the skirt **4960** to bias the skirt **4960** radially outwardly. In so doing, the skirt **4960** can impart a force on the native mitral valve annulus to enhance sealing and beneficially reduce paravalvular leakage. It is to be understood that other types of biasing members, such as coil springs, can be used. Moreover, as shown in the embodiments of prostheses **5000**, **5100** illustrated in **Figures 80-82**, other types of biasing members **5080**, **5180**, such as cantilevers or arms, can be used to bias skirts **5060**, **5160** radially outwardly of frames **5020**, **5120**. As shown in **Figures 80-82**, the biasing members **5080**, **5180** can extend from various portions of the frame such as the upper edge and/or the lower edge. Other embodiments of biasing members are described in further detail in U.S. App. No. 15/247,461, filed August 25, 2016.

[0466] In some embodiments, the biasing members **4980**, **5080**, **5180** can be used in combination with blood flow into the skirts **4060**, **5060**, **5160**, to impart a force on surrounding tissue. For example, the configuration of prostheses **4900**, **5000**, **5100**

can be used in combination with the configuration of prosthesis **4800**. This can beneficially increase the amount of force imparted on surrounding tissue. However, it is to be understood that the biasing members **4980**, **5080**, **5180** can be utilized without blood flow into the skirts to impart such forces on surrounding tissue.

#### Exemplary Placement of Replacement Valves

[0467] Reference is now made to **Figures 41A-43** which illustrate schematic representations of an embodiment of a prosthesis **3000** positioned within a native mitral valve of a heart **10**. As noted above, in some embodiments the prostheses described herein can be positioned within a native mitral valve. A portion of the native mitral valve is shown schematically and represents typical anatomy, including a left atrium **20** positioned above an annulus **40** and a left ventricle **30** positioned below the annulus **40**. The left atrium **20** and left ventricle **30** communicate with one another through a mitral annulus **40**. Also shown schematically in **Figures 41A-43** is a native mitral leaflet **50** having chordae tendineae **60** that connect a downstream end of the mitral leaflet **50** to the papillary muscle of the left ventricle **30**. The portion of the prosthesis **3000** disposed upstream of the annulus **40** (toward the left atrium) can be referred to as being positioned supra-annularly. The portion generally within the annulus **40** can be referred to as positioned intra-annularly. The portion downstream of the annulus **40** can be referred to as being positioned sub-annularly (toward the left ventricle). In the illustrated embodiment, only a part of the foreshortening portion is positioned intra-annularly or sub-annularly, and the rest of the prosthesis **3000** is supra-annular.

[0468] As shown in the situations illustrated in **Figures 22A-23B**, the prosthesis **3000** can be disposed so that the mitral annulus **40** is between the upper or atrial anchoring feature **3010** and the lower or ventricular anchoring feature **3020**. In some situations, the prosthesis **3000** can be positioned such that ends or tips **3022** of the lower anchoring feature **3020** can contact the ventricular side of the annulus **40** as shown, for example, in **Figures 41A-C**. In some situations, the prosthesis **3000** can be positioned such that ends or tips **3022** of the lower anchoring feature **3020** do not contact the annulus **40** as shown, for example, in **Figures 42A-B**, and may just contact a downstream side of the leaflet **50**. In some situations, the prosthesis **3000** can be

positioned such that the lower anchoring feature **3020** do not extend around the leaflet **50** as illustrated, but rather are positioned radially inward of the leaflet **50** as shown, for example, in **Figure 43**. While **Figures 41A-43** are described separately below, it should be understood that one or more of the situations illustrated in **Figures 41A-43** may be present when the prosthesis **3000** is positioned at the implantation location, such as a native mitral valve. For example, in some situations the prosthesis **3000** may be positioned such that some portion of the anchoring feature **3020** may contact the annulus **40** while another portion of the lower anchoring feature **3020** may not. Moreover, it may be contemplated some in some situations, some portion of the anchoring feature **3020** may be positioned

[0469] With reference first to the situations illustrated in **Figures 41A-42B**, the prosthesis **3000** can be positioned so that the ends or tips **3022** of the lower anchoring feature **3020** are on a ventricular side of the mitral annulus **40** and the ends or tips **3012** of the upper anchoring feature **3010** are on an atrial side of the mitral annulus **40**. The lower anchoring feature **3020** can be positioned such that the ends or tips **3022** of the lower anchoring feature **3020** are on a ventricular side of the native leaflets radially outwardly beyond a location where chordae tendineae **60** connect to free ends of the native leaflets **50**. The lower anchoring feature **3020** may extend between at least some of the chordae tendineae **60** and, in some situations such as those shown in **Figures 41A-C**, can contact or engage a ventricular side of the annulus **40**. It is also contemplated that in some situations, such as those shown in **Figures 42A-B**, the lower anchoring feature **3020** may not contact the annulus **40**, though the lower anchoring feature **3020** may still contact the native leaflet **50**. In some situations, the lower anchoring feature **3020** can contact tissue of the left ventricle **30** beyond the annulus **40** and/or a ventricular side of the leaflets **50**.

[0470] During delivery, the lower anchoring feature **3020** (along with the frame **3002**) can be moved toward the ventricular side of the annulus **40** with the lower anchoring feature **3020** extending between at least some of the chordae tendineae **60** to provide tension on the chordae tendineae **60** after the prosthesis **3000** is finally delivered. The degree of tension provided on the chordae tendineae **60** can differ. For example, little to no tension may be present in the chordae tendineae **60** as shown in **Figure 41C**

where the leaflet **50** is shorter than or similar in size to the lower anchoring feature **3020**. A greater degree of tension may be present in the chordae tendineae **60** as shown in **Figure 41A** and **42B** where the leaflet **50** is longer than the lower anchoring feature **3020** and, as such, takes on a compacted form and is pulled proximally. An even greater degree of tension may be present in the chordae tendineae **60** as shown in **Figures 42A-B** where the leaflets **50** are even longer relative to the lower anchoring feature **3020**. As shown in **Figures 42A-B**, the leaflet **50** is sufficiently long such that the lower anchoring feature **3020** do not contact the annulus **40**.

[0471] The upper anchoring feature **3010** can be positioned such that the ends or tips **3012** of the upper anchoring feature **3010** are on or adjacent the atrial side of the annulus **40** and/or tissue of the left atrium **20** beyond the annulus **40**. In some situations, some portion or all of the upper anchoring feature **3010** may only occasionally contact or engage atrial side of the annulus **40** and/or tissue of the left atrium **20** beyond the annulus **40**. For example, as shown in **Figures 41A-B**, the upper anchoring feature **3010** may be spaced from the atrial side of the annulus **40** and/or tissue of the left atrium **20** beyond the annulus **40**. The upper anchoring feature **3010** may be utilized to provide axial stability for the prosthesis **3000** and prevent off-axis orientation. Further, the upper anchoring feature **3010** can act as a safety feature without utilizing them for axial stability and off-axis orientation. For example, if the prosthesis **3000** is improperly deployed so that the prosthesis **3000** is deployed too low toward the left ventricle **30**, the upper anchoring feature **3010** can prevent the prosthesis **3000** from falling into the left ventricle **30**. In some situations such as those shown in **Figures 41A** and **42A**, some or all of the upper anchoring feature **3010** may not contact the annular skirt **3030**. This may occur when the skirt **3030** is in a collapsed configuration although it may also occur when the skirt **3030** is in an expanded configuration. It is also contemplated that some or all of the upper anchoring feature **3010** may contact the atrial side of the annulus **40** and/or tissue of the left atrium **20** beyond the annulus **40**. The particular curve of the upper anchoring feature **3010** discussed above can prevent trauma to tissue of the heart **10**, and can also help with stabilization of the prosthesis **3000** in the heart **10**.

[0472] With continued reference to the situations illustrated in **Figures 41A-43**, the skirt **3030** can be positioned such that a proximal portion **3032** of the annular



skirt **3030** is positioned along or adjacent an atrial side of the annulus **40**. The proximal portion **3032** can be positioned between the atrial side of the annulus **40** and the upper anchoring feature **3010**. The proximal portion **3032** can extend radially outward such that the skirt **3030** is positioned along or adjacent tissue of the left atrium **20** beyond the annulus **40**.

[0473] In some situations such as those shown in **Figure 41A** and **41A**, the skirt **3030** may not contact the wall of the heart **10**. In some situations such as those shown in **Figures 41B, 41C, 42B, 43**, the skirt **3030** may contact the wall of the heart **10**. As shown in **Figure 22A-23B**, the annular skirt **3030** can also assist in filling gaps which exist between the leaflet **50** and the frame **3002** (portions of which are illustrated in dashed lines).

[0474] In some situations such as that shown in **Figure 43**, the leaflet **50** may not be captured between the frame **3002** and a portion of the lower anchoring feature **3020**. As shown, the portion of the lower anchoring feature **3020** may be positioned along an atrial surface of the leaflet **50**. The portion of the lower anchoring feature **3020** may also be positioned along an inner surface of the annulus **40**. It is also contemplated that the portion of the lower anchoring feature **3020** may exert a force against the leaflet **50** such that the leaflet **50** is pushed radially outward, relative to the longitudinal axis of the frame **3002**, towards a wall of the heart **10**. In such situations, the skirt **3030** can create a seal intra-annularly and/or along an atrial side of the leaflet **50**. In alternative situations (not shown), the skirt **3030** can create a seal along a ventricular side of the annulus **40**. For example, the prosthesis **3000** may be disposed in the annulus **40** such that a portion of the skirt **3030** is positioned on the ventricular side of the annulus **40**.

[0475] As noted above, although the in vivo situations of **Figure 41A-43** have been described separately, it should be understood that one or more of these situations may be present when a prosthesis is positioned at the implantation location, such as a native mitral valve. For example, a portion of the lower anchoring feature **3020** may not capture the leaflet **50** whereas the remaining portion may capture the leaflet **50**. As another example, when the prosthesis **3000** is positioned within the native mitral valve, the skirt **3030** can contact the wall of the heart **10** along one or more portions of an outermost circumference of the proximal portion **3032** and may not contact the wall of

the heart **10** along other portions of the outermost circumference of the proximal portion **3032**. For example, the skirt **3030** may contact the wall of the heart **10** along an approximately 180 degree portion of the outermost circumference of the proximal portion **3032** and may not contact the wall of the heart **10** along the remaining, approximately 180 degree portion of the outermost circumference of the proximal portion **3032**.

[0476] With reference next to the prosthesis **3100** illustrated in **Figures 44** and **45**, the prosthesis **3100** is illustrated positioned within a heart **10** which has been splayed to more clearly show positioning of the prosthesis **3100** within the heart **10**. **Figure 44** illustrates the prosthesis **3100** as viewed from an atrial side of the native mitral valve annulus. As shown in the illustrated embodiment, the prosthesis **3100** includes a skirt **3110** extending over an anchoring feature positioned over an atrial side of a native mitral valve annulus. **Figure 45** illustrates the prosthesis **3100** as viewed from a ventricular side of the native mitral valve annulus.

#### Delivery of Prosthesis

[0477] The prostheses described herein can be delivered to a patient's native heart valve in various ways, such as by open surgery, minimally-invasive surgery, and percutaneous or transcatheter delivery through the patient's vasculature. In some embodiments, the prosthesis can be delivered to a patient's native mitral valve through procedure such as, but not limited to, a transapical procedure and a transseptal procedure.

[0478] As noted above, the prostheses can be used with a variety of delivery systems such as "slot"-based and/or "tether"-based systems. For purposes of the following figures, it is to be understood that the distal direction is towards the right of the drawing. With reference first to the system **3200** of **Figure 46**, the system **3200** can include a delivery device **3210** with a prosthesis **3280** contained within the delivery device **3210**. A first end **3282** of the prosthesis **3280** can be placed in a compressed state such that the first end **3282** of the prosthesis **3280** is retained between a nose cone **3220** and an inner retention member **3222** when the inner retention member **3222** is received within and covered by the nose cone **3220**. The inner retention member **3222** can include one or more slots which interface with locking tabs **3284**. The interface between

the locking tabs **3284** and slots of the inner retention member **3222** can inhibit axial movement of the prosthesis **3280** relative to the inner retention member **3222**. When the first end **3282** of the prosthesis **3280** is uncovered, such as by moving the nose cone **3220** distally relative to the inner retention member **3222** or by moving the inner retention member **3222** proximally relative to the nose cone **3220**, the first end **3282** of the prosthesis **3280** can be released. This release can be caused by the prosthesis **3280** transitioning from a collapsed configuration to an expanded configuration when the prosthesis **3280** is formed from a self-expanding material.

[0479] At least a second end **3286** of the prosthesis **3280** can be placed in a compressed state such that the second end **3286** of the prosthesis **3280** is retained within a hollow shaft member **3230**. When the second end **3286** is uncovered, such as by moving the hollow shaft member **3230** proximally relative to the prosthesis **3280** or by moving the prosthesis **3280** distally relative to the hollow shaft member **3230**, the second end **3286** of the prosthesis **3280** can be released. This release can be caused by the prosthesis **3280** transitioning from a collapsed configuration to an expanded configuration when the prosthesis **3280** is formed from a self-expanding material. In some embodiments, the delivery system **3210** can include a tether **3240** which can wrap around a portion of the prosthesis **3280**, such as an anchoring feature on the second end **3286**. The tether **3240** can be used to control expansion of a portion of the prosthesis **3280**, such as the second end **3286**, when the portion of the prosthesis **3280** is uncovered.

[0480] In some embodiments, the system **3200** can be used in connection with a transapical procedure to access a native mitral valve. During such a procedure, the system **3200** can access a mitral valve through the apex of the heart. The anchoring feature on a ventricular side of the prosthesis **3280**, such as the second end **3286**, can be released on a ventricular side of the native mitral valve annulus. During delivery, the anchoring feature on a ventricular side of the annulus (along with the prosthesis **3280**) can be moved toward the ventricular side of the annulus with the ventricular anchors extending between at least some of the chordae tendineae to provide tension on the chordae tendineae. The degree of tension provided on the chordae tendineae can differ. For example, little to no tension may be present in the chordae tendineae if the leaflet is shorter than or similar in size to the ventricular anchors. A greater degree of tension may

be present in the chordae tendineae where the leaflet is longer than the ventricular anchors and, as such, takes on a compacted form and is pulled toward the native valve annulus. An even greater degree of tension may be present in the chordae tendineae where the leaflets are even longer relative to the ventricular anchors. The leaflet can be sufficiently long such that the ventricular anchors do not contact the annulus. After the anchoring feature on a ventricular side of the annulus is positioned, the remainder of the prosthesis can be deployed from the delivery system **3210**.

[0481] With reference next to the system **3300** of **Figure 47**, the system **3300** can include a delivery device **3310** with a prosthesis **3380** contained within the delivery device **3310**. A first end **3382** of the prosthesis **3380** can be placed in a compressed state such that the first end **3382** of the prosthesis **3380** is retained between an inner retention member **3320** and another portion of the delivery device, such as an outer retention member **3322**, when the inner retention member **3320** is received within and covered by the outer retention member **3322**. The interface between the locking tabs **3384** and slots of the inner retention member **3320** can inhibit axial movement of the prosthesis **3380** relative to the inner retention member **3320**. When the first end **3382** of the prosthesis **3380** is uncovered, such as by moving the outer retention member **3322** proximally relative to the inner retention member **3320** or by moving the inner retention member **3320** distally relative to the outer retention member **3322**, the first end **3382** of the prosthesis **3380** can be released from the inner retention member **3322**. If the inner retention member **3320** is fully uncovered, the first end **3382** of the prosthesis **3380** can be released from the delivery device **3310**. This release can be caused by the prosthesis **3380** transitioning from a collapsed configuration to an expanded configuration when the prosthesis **3380** is formed from a self-expanding material.

[0482] At least a second end **3386** of the prosthesis **3380** can be placed in a compressed state such that the second end **3386** of the prosthesis **3380** is retained within an outer sheath assembly **3330**. When the second end **3386** is uncovered, such as by moving the outer sheath assembly **3330** proximally relative to the prosthesis **3380** or by moving the prosthesis **3380** distally relative to the outer shaft assembly **3330**, the second end **3386** of the prosthesis **3380** can be released. This release can be caused by the

prosthesis **3380** transitioning from a collapsed configuration to an expanded configuration when the prosthesis **3380** is formed from a self-expanding material.

[0483] In some embodiments, the system **3300** can be used in connection with a transseptal procedure to access a native mitral valve. During such a procedure, the system **3300** can access a mitral valve through a septal puncture. The anchoring feature on a ventricular side of the prosthesis **3380**, such as the second end **3386**, can be released on a ventricular side of the native mitral valve annulus. During delivery, the anchoring feature on a ventricular side of the annulus (along with the prosthesis **3380**) can be moved toward the ventricular side of the annulus with the ventricular anchors extending between at least some of the chordae tendineae to provide tension on the chordae tendineae. The degree of tension provided on the chordae tendineae can differ. For example, little to no tension may be present in the chordae tendineae if the leaflet is shorter than or similar in size to the ventricular anchors. A greater degree of tension may be present in the chordae tendineae where the leaflet is longer than the ventricular anchors and, as such, takes on a compacted form and is pulled toward the native valve annulus. An even greater degree of tension may be present in the chordae tendineae where the leaflets are even longer relative to the ventricular anchors. The leaflet can be sufficiently long such that the ventricular anchors do not contact the annulus. After the anchoring feature on a ventricular side of the annulus is positioned, the remainder of the prosthesis can be deployed from the delivery device **3310**.

#### Other Embodiments

[0484] While certain embodiments have been described, these embodiments have been presented by way of example only, and are not intended to limit the scope of the disclosure. Indeed, the novel methods and systems described herein may be embodied in a variety of other forms. Furthermore, various omissions, substitutions and changes in the systems and methods described herein may be made without departing from the spirit of the disclosure. The accompanying claims and their equivalents are intended to cover such forms or modifications as would fall within the scope of the disclosure. Accordingly, the scope of the present disclosure is defined only by reference to the claims presented herein or as presented in the future.

**[0485]** Features, materials, characteristics, or groups described in conjunction with a particular aspect, embodiment, or example are to be understood to be applicable to any other aspect, embodiment or example described in this section or elsewhere in this specification unless incompatible therewith. All of the features disclosed in this specification (including any accompanying claims, abstract and drawings), and/or all of the steps of any method or process so disclosed, may be combined in any combination, except combinations where at least some of such features and/or steps are mutually exclusive. The protection is not restricted to the details of any foregoing embodiments. The protection extends to any novel one, or any novel combination, of the features disclosed in this specification (including any accompanying claims, abstract and drawings), or to any novel one, or any novel combination, of the steps of any method or process so disclosed.

**[0486]** Furthermore, certain features that are described in this disclosure in the context of separate implementations can also be implemented in combination in a single implementation. Conversely, various features that are described in the context of a single implementation can also be implemented in multiple implementations separately or in any suitable subcombination. Moreover, although features may be described above as acting in certain combinations, one or more features from a claimed combination can, in some cases, be excised from the combination, and the combination may be claimed as a subcombination or variation of a subcombination.

**[0487]** For purposes of this disclosure, certain aspects, advantages, and novel features are described herein. Not necessarily all such advantages may be achieved in accordance with any particular embodiment. Thus, for example, those skilled in the art will recognize that the disclosure may be embodied or carried out in a manner that achieves one advantage or a group of advantages as taught herein without necessarily achieving other advantages as may be taught or suggested herein.

**[0488]** Conditional language, such as “can,” “could,” “might,” or “may,” unless specifically stated otherwise, or otherwise understood within the context as used, is generally intended to convey that certain embodiments include, while other embodiments do not include, certain features, elements, and/or steps. Thus, such conditional language is not generally intended to imply that features, elements, and/or

steps are in any way required for one or more embodiments or that one or more embodiments necessarily include logic for deciding, with or without user input or prompting, whether these features, elements, and/or steps are included or are to be performed in any particular embodiment.

**[0489]** Conjunctive language such as the phrase “at least one of X, Y, and Z,” unless specifically stated otherwise, is otherwise understood with the context as used in general to convey that an item, term, etc. may be either X, Y, or Z. Thus, such conjunctive language is not generally intended to imply that certain embodiments require the presence of at least one of X, at least one of Y, and at least one of Z.

**[0490]** Language of degree used herein, such as the terms “approximately,” “about,” “generally,” and “substantially” as used herein represent a value, amount, or characteristic close to the stated value, amount, or characteristic that still performs a desired function or achieves a desired result. For example, the terms “approximately,” “about,” “generally,” and “substantially” may refer to an amount that is within less than 10% of, within less than 5% of, within less than 1% of, within less than 0.1% of, and within less than 0.01% of the stated amount. As another example, in certain embodiments, the terms “generally parallel” and “substantially parallel” refer to a value, amount, or characteristic that departs from exactly parallel by less than or equal to 15 degrees, 10 degrees, 5 degrees, 3 degrees, 1 degree, or 0.1 degree.

**[0491]** The scope of the present disclosure is not intended to be limited by the specific disclosures of preferred embodiments in this section or elsewhere in this specification, and may be defined by claims as presented in this section or elsewhere in this specification or as presented in the future. The language of the claims is to be interpreted broadly based on the language employed in the claims and not limited to the examples described in the present specification or during the prosecution of the application, which examples are to be construed as non-exclusive.

WHAT IS CLAIMED IS:

1. A replacement heart valve prosthesis, the prosthesis comprising:
  - an expandable frame comprising a proximal end and a distal end and a longitudinal axis extending therethrough, the frame configured to radially expand and contract for deployment within a native heart valve; and
  - a valve body positioned within an interior of the expandable frame, wherein the valve body comprises:
    - a plurality of leaflets each having an arcuate proximal edge and a free distal edge, the plurality of leaflets being joined at commissures, the plurality of leaflets configured to allow flow in a proximal-to-distal direction and prevent flow in a distal-to-proximal direction; and
    - one or more intermediate components connecting the leaflets to the expandable frame, wherein at least a portion of the arcuate proximal edge of each leaflet and/or the commissures are indirectly coupled to the expandable frame via the one or more intermediate components such that when the frame is in an expanded configuration, the one or more intermediate components position at least a portion of the arcuate proximal edge of each leaflet and/or the commissures radially inward from an inner surface of the frame.
2. The prosthesis of Claim 1, wherein at least a portion of the arcuate proximal edge of each leaflet is directly coupled to the expandable frame.
3. The prosthesis of any one of Claims 1 or 2, wherein the one or more intermediate components is formed from a material having a stiffness greater than that of the plurality of leaflets and less than that of the expandable frame.
4. The prosthesis according to any one of Claims 1-3, wherein the one or more intermediate components is formed from a sheet of material.
5. The prosthesis of Claim 4, wherein the one or more intermediate components is formed from a sheet of at least one of fabric, polyurethane, and polyethylene terephthalate (PET).
6. The prosthesis according to any one of Claims 1-5, wherein the one or more intermediate components comprises a first intermediate component and a second



intermediate component, wherein the first intermediate component is tensioned in a first direction and the second intermediate component is tensioned in a second direction when the expandable frame is in an expanded configuration.

7. The prosthesis of Claim 6, wherein the first direction is oriented generally radially outwardly.

8. The prosthesis of Claim 7, wherein the second direction is oriented generally axially.

9. The prosthesis of Claim 7, wherein the second direction is oriented generally in a circumferential direction.

10. The prosthesis according to any one of Claims 6-9, wherein the one or more intermediate components comprises a third intermediate component, wherein the first intermediate component, the second intermediate component, and the third intermediate component form a pocket at or proximate a commissure of the valve body.

11. The prosthesis according to any one of Claims 1-10, wherein the one or more intermediate components comprises a cylindrical conduit.

12. The prosthesis according to any one of Claims 1-11, wherein at least one of the one or more intermediate components extends in a radial direction between the expandable frame and the plurality of leaflets.

13. The prosthesis according to any one of Claims 1-12, wherein at least one of the one or more intermediate components extends tangentially to the plurality of leaflets.

14. The prosthesis according to any one of Claims 1-13, wherein at least one of the one or more intermediate components extends in a direction generally aligned with the longitudinal axis of the frame.

15. The prosthesis according to any one of Claims 1-14, wherein at least one of the one or more intermediate components extends in circumferential direction.

16. The prosthesis according to any one of Claims 1-15, wherein the expandable frame comprises a proximal region, an intermediate region, and a distal region, the intermediate region having a diameter greater than at least one of a diameter of the proximal region and a diameter of the distal region.

17. The prosthesis according to any one of Claims 1-16, wherein the prosthesis comprises an annular skirt extending around the exterior of the expandable frame.

18. The prosthesis of Claim 17, wherein a proximal end of the annular skirt is attached to a proximal region of the expandable frame and a distal end of the annular skirt is attached to a distal region of the expandable frame.

19. A replacement heart valve prosthesis, the prosthesis comprising:

an expandable frame configured to radially expand and contract for deployment within a native heart valve, the expandable frame comprising a proximal end and a distal end and a longitudinal axis extending therethrough, the frame comprising a supplemental prosthesis retention structure; and

a valve body positioned within an interior of the expandable frame, wherein the valve body comprises a plurality of leaflets configured to allow flow in a first direction and prevent flow in a second opposite direction.

20. The prosthesis of Claim 19, wherein the supplemental prosthesis retention structure comprises an interfacing structure, the interfacing structure comprising a plurality of V-shaped apices extending radially inward towards the longitudinal axis, the plurality of V-shaped apices configured to couple with a frame of a supplemental prosthesis.

21. The prosthesis of Claim 19, wherein the supplemental prosthesis retention structure comprises an interfacing structure, the interfacing structure comprising a plurality of protrusions extending radially inwardly from distal portions of cells of the expandable frame.

22. The prosthesis of Claim 19, wherein the supplemental prosthesis retention structure comprises an internal expandable cage configured to receive a supplemental prosthesis.

23. The prosthesis of Claim 22, wherein the internal expandable cage comprises a plurality of circumferentially-expandable struts.

24. A replacement heart valve prosthesis, the prosthesis comprising:

an expandable frame configured to radially expand and contract for deployment within a native heart valve, the expandable frame comprising:

a frame body comprising a proximal region, a distal region, an intermediate region extending between the proximal and distal regions, and a longitudinal axis extending between proximal and distal ends of the frame body, the frame body comprising a plurality of struts forming one or more rows of cells, wherein, in an expanded configuration:

the proximal region comprises a first bend adjacent the intermediate region, wherein a proximally extending portion of the first bend is inclined or curved towards the longitudinal axis;

the distal region comprises a second bend adjacent the intermediate region, wherein a distally extending portion of the second bend is inclined or curved towards the longitudinal axis;

the intermediate region has a generally cylindrical shape;

a diameter of the intermediate region is greater than a diameter of the proximal region and a diameter of the distal region; and

a height of the intermediate region is greater than a height of the proximal region and a height of the distal region;

a proximal anchoring feature attached to the frame body, the proximal anchoring feature sized to be positioned on a first side of an annulus of the native heart valve;

a distal anchoring feature attached to the frame body, the distal anchoring feature sized to be positioned on a second side of an annulus of the native heart valve; and

a valve body positioned within an interior of the expandable frame, the valve body comprising a plurality of leaflets configured to allow flow in a first direction and prevent flow in a second opposite direction.

25. The prosthesis of Claim 24, wherein, when the expandable frame is in an expanded configuration, the height of the distal region is greater than the height of the proximal region.

26. The prosthesis of any one of Claims 24 or 25, wherein, when the expandable frame is in an expanded configuration, a ratio of a largest diameter of the frame body to the height of the frame body is between about 3:1 to about 1:1.

27. The prosthesis of Claim 26, wherein, when the expandable frame is in an expanded configuration, a ratio of a largest diameter of the frame body to the height of the frame body is between about 2:1 to about 3:2.

28. The prosthesis according to any one of Claims 24-27, wherein, when the expandable frame is in an expanded configuration, a ratio of the height of the intermediate region to the combined heights of the proximal region and the distal region is between about 2:1 to about 1:2.

29. The prosthesis of Claim 28, wherein, when the expandable frame is in an expanded configuration, a ratio of the height of the intermediate region to the combined heights of the proximal region and the distal region is between about 3:2 to about 1:1.

30. The prosthesis according to any one of Claims 24-29, wherein, when the expandable frame is in an expanded configuration, a ratio of a largest diameter of the frame body to a smallest diameter of the frame body is between about 2:1 to about 4:3.

31. The prosthesis according to any one of Claims 24-30, wherein, when the expandable frame is in an expanded configuration, the first bend orients a portion of the proximal region, positioned proximally of the beginning of the first bend, such that the portion forms an angle of between about 30 degrees to about 60 degrees with a plane orthogonal to the longitudinal axis.

32. The prosthesis of Claim 31, wherein, when the expandable frame is in an expanded configuration, the first bend orients a portion of the proximal region, positioned proximally of the beginning of the first bend, such that the portion forms an angle of between about 40 degrees to about 50 degrees with a plane orthogonal to the longitudinal axis.

33. The prosthesis according to any one of Claims 24-32, wherein, when the expandable frame is in an expanded configuration, the second bend orients a portion of the distal region, positioned distally of the beginning of the second bend, such that the portion forms an angle of between about 30 degrees to about 60 degrees with a plane orthogonal to the longitudinal axis.

34. The prosthesis of Claim 33, wherein, when the expandable frame is in an expanded configuration, the second bend orients a portion of the distal region, positioned distally of the beginning of the second bend, such that the portion forms an angle of between about 40 degrees to about 50 degrees with a plane orthogonal to the longitudinal axis.

35. The prosthesis according to any one of Claims 24-34, wherein the proximal anchoring feature is attached to the proximal region of the frame body.

36. The prosthesis according to any one of Claims 24-35, wherein the proximal anchoring feature comprises a plurality of anchors.

37. The prosthesis of Claim 36, wherein at least one of the anchors comprise one or more eyelets.

38. The prosthesis of Claim 37, wherein at least one of the anchors comprise two or more eyelets.

39. The prosthesis according to any one of Claims 24-38, wherein the distal anchoring feature is attached to the distal region of the frame body.

40. The prosthesis according to any one of Claims 24-39, wherein the distal anchoring feature comprises a plurality of distal anchors.

41. The prosthesis of Claim 40, wherein, when the expandable frame is in an expanded configuration, at least one of the distal anchors comprises ends extending radially outwardly away from the longitudinal axis.

42. The prosthesis of Claim 41, wherein, when the expandable frame is in an expanded configuration, at least one of the distal anchors comprises ends extending radially outwardly away from the longitudinal axis in a direction generally perpendicular to the longitudinal axis.

43. The prosthesis of Claim 41, wherein, when the expandable frame is in an expanded configuration, all of the distal anchors comprise ends extending radially outwardly away from the longitudinal axis.

44. The prosthesis of Claim 40, wherein, when the expandable frame is in an expanded configuration, at least one of the distal anchors comprises ends extending radially inwardly towards the longitudinal axis.

45. The prosthesis of Claim 44, wherein, when the expandable frame is in an expanded configuration, at least one of the distal anchors comprises ends extending radially inwardly towards the longitudinal axis in a direction generally perpendicular to the longitudinal axis.

46. The prosthesis of Claim 44, wherein, when the expandable frame is in an expanded configuration, all of the distal anchors comprise ends extending radially inwardly towards the longitudinal axis.

47. The prosthesis according to any one of Claims 24-46, wherein the expandable frame further comprises a plurality of locking tabs.

48. The prosthesis of Claim 47, wherein the locking tabs comprise a bend in a direction opposite the first bend.

49. The prosthesis according to any one of Claims 24-48, wherein the valve body further comprises one or more intermediate components and wherein at least a portion of each leaflet is indirectly coupled to the expandable frame via the one or more intermediate components such that at least a portion of each leaflet is positioned radially inward from an inner surface of the frame body.

50. The prosthesis of Claim 49, wherein commissures of the valve body are indirectly coupled to the expandable frame via the one or more intermediate components such that the commissures are positioned radially inward from the inner surface of the frame body.

51. The prosthesis of one of Claims 49 or 50, wherein at least a portion of an arcuate proximal edge of each leaflet is indirectly coupled to the frame via the one or more intermediate components such that the arcuate proximal edge is positioned radially inward from the inner surface of the frame body.

52. The prosthesis according to any one of Claims 49-51, wherein at least a portion of an arcuate proximal edge of each leaflet is directly coupled to the expandable frame.

53. The prosthesis of according to any one of Claims 49-52, wherein the one or more intermediate components is formed from a material having a stiffness greater than that of the plurality of leaflets and less than that of the expandable frame.

54. The prosthesis of according to any one of Claims 49-53, wherein the one or more intermediate components comprises a first intermediate component and a second intermediate component, wherein the first intermediate component is tensioned in a first direction and the second intermediate component is tensioned in a second direction when the expandable frame is in an expanded configuration.

55. The prosthesis of Claim 54, wherein the first direction is oriented generally radially outward.

56. The prosthesis of Claim 55, wherein the second direction is oriented generally axially.

57. The prosthesis of Claim 55, wherein the second direction is oriented generally in a circumferential direction.

58. The prosthesis according to any one of Claims 54-57, wherein the one or more intermediate components comprises a third intermediate component, wherein the first intermediate component, the second intermediate component, and the third intermediate component form a pocket at or proximate a commissure of the valve body.

59. The prosthesis according to any one of Claims 49-58, wherein the one or more intermediate components comprises a cylindrical conduit.

60. The prosthesis according to any one of Claims 49-59, wherein at least one of the one or more intermediate components extends in a radial direction between the expandable frame and the plurality of leaflets.

61. The prosthesis according to any one of Claims 49-60, wherein at least one of the one or more intermediate components extends tangentially to the plurality of leaflets.

62. The prosthesis according to any one of Claims 44-61, wherein at least one of the one or more intermediate components extends in a direction generally aligned with the longitudinal axis of the frame.

63. The prosthesis according to any one of Claims 44-62, wherein at least one of the one or more intermediate components extends in circumferential direction.

64. The prosthesis according to any one of Claims 24-63, wherein the prosthesis comprises an annular flap extending around the exterior of the expandable frame.

65. The prosthesis of Claim 64, wherein a proximal end of the annular skirt is attached to the proximal region of the frame body and a distal end of the annular skirt is attached to the distal region of the frame body.

66. A replacement heart valve prosthesis, the prosthesis comprising:

an expandable frame comprising a proximal end and a distal end and a longitudinal axis extending therethrough, the frame configured to radially expand and contract for deployment within a native heart valve;

a valve body positioned within an interior of the expandable frame, wherein the valve body comprises a plurality of leaflets configured to allow flow in a first direction and prevent flow in a second opposite direction; and

an annular skirt extending around the exterior of the expandable frame;

wherein the valve body comprises one or more intermediate components.

67. The prosthesis of Claim 66, wherein at least one of the valve body and the annular skirt comprises one or more openings configured to allow at least one of:

fluid ingress into a space between the valve leaflets and the annular skirt;

and

fluid egress out of the space between the valve leaflets and the annular skirt.

68. The prosthesis of Claim 67, wherein the one or more openings are configured to allow fluid ingress into the space between the valve leaflets and the annular skirt when fluid flow is in the first direction.

69. The prosthesis of any one of Claims 67 or 68, wherein the one or more openings are configured to allow fluid egress out of the space between the valve leaflets and the annular skirt when fluid flow is in the second direction.

70. The prosthesis according to any one of Claims 67-69, wherein at least one of the one or more openings is positioned within an area of the annular skirt between a first edge of a valve leaflet and the annular skirt.

71. The prosthesis according to any one of Claims 66-68, wherein the prosthesis comprises one or more conduits extending into the one or more openings.

72. The prosthesis of Claim 71, wherein the expandable frame comprises an anchoring member sized and shaped to be positioned on an inflow side of a native valve



annulus and wherein the one or more conduits is configured to extend proximal of the anchoring member.

73. The prosthesis of Claim 72, wherein the anchoring member is positioned along a proximal portion of the expandable frame.

74. The prosthesis of any one of Claims 72 or 73, wherein the inflow side of the native valve annulus is an atrial side of the native mitral valve annulus.

75. The prosthesis according to any one of Claims 66-74, wherein, when the annular skirt is in an expanded configuration, the annular skirt comprises a supplemental rib extending from a portion of the annular skirt.

76. The prosthesis according to any one of Claims 66-75, wherein, when the annular skirt is in an expanded configuration, a proximal portion of the annular skirt bulges radially outward relative to the distal portion of the annular skirt.

77. The prosthesis according to any one of Claims 66-75, wherein, when the annular skirt is in an expanded configuration, a distal portion of the annular skirt bulges radially outward relative to the proximal portion of the annular skirt.

78. The prosthesis according to any one of Claims 66-77, wherein, when the annular skirt is in an expanded configuration, the annular skirt extends around the entire circumferential periphery of the frame to a generally equivalent radial dimension.

79. The prosthesis according to any one of Claims 66-77, wherein the annular skirt extends to different radial dimensions with a first peripheral region extending to a first radial dimension and a second peripheral region extending to a second radial dimension greater than the first radial dimension.

80. The prosthesis according to any one of Claims 66-79, wherein the prosthesis comprises one or more biasing members configured to bias the skirt into an expanded configuration.

81. The prosthesis of Claim 80, wherein the one or more biasing members comprise a radial spring.

82. The prosthesis of any one of Claims 80 or 81, wherein the one or more biasing members comprise a cantilever.

83. The prosthesis according to any one of Claims 66-82, wherein the annular skirt is configured to transition into an expanded configuration via blood flow into the annular skirt.

84. The prosthesis of Claim 83, wherein the prosthesis comprises a one-way valve configured to allow blood flow into the annular skirt and inhibit blood flow out of the annular skirt.

85. The prosthesis of Claim 84, wherein the one-way valve is positioned on a valve skirt, the valve skirt being positioned between the plurality of leaflets and the annular skirt.

86. The prosthesis of Claim 85, wherein the one-way valve comprises a flap positioned on an exterior of the valve skirt.

87. The prosthesis according to any one of Claims 84-86, wherein the one-way valve comprises a duckbill valve.

88. The prosthesis according to any one of Claims 84-87, wherein the one-way valve is configured to allow blood flow into the annular skirt during systole and inhibit blood flow out of the annular skirt during diastole.

89. The prosthesis according to any one of claims 1-88, wherein the prosthesis is a replacement mitral valve prosthesis, the expandable frame being configured for deployment within a native mitral valve.

90. The prosthesis according to any one of claims 1-89, wherein the prosthesis comprises six distal anchors.

91. The prosthesis according to any of Claims 1-89, wherein the prosthesis comprises twelve distal anchors.

92. A replacement heart valve prosthesis for deployment at a native heart valve, the prosthesis comprising:

an expandable frame configured to radially expand and contract for deployment within a native heart valve, the expandable frame comprising:

a frame body comprising a proximal region, a distal region, and an intermediate region extending between the proximal and distal regions, the frame body comprising a first row of struts and a second row of struts;

a supplemental frame comprising a first row of struts configured to be generally aligned along the first row of struts of the frame body, the first row of struts of the supplemental frame having a shape which generally matches the shape of the first row of struts of the frame body; and

a distal anchoring feature, the distal anchoring feature sized to be positioned on a first side of an annulus of the native heart valve; and

a valve body positioned within an interior of the expandable frame, the valve body comprising a plurality of leaflets configured to allow flow in a first direction and prevent flow in a second opposite direction;

wherein the supplemental frame is formed separately from the frame body; and wherein the first row of struts of the supplemental frame is configured to be attached to at least a portion of the first row of struts of the frame body.

93. The prosthesis of Claim 92, wherein the first row of struts of the supplemental frame is attached to the first row of struts of the frame body via sutures.

94. The prosthesis according to any one of Claims 92-93, wherein the first row of struts of the supplemental frame and the first row of struts of the frame body have an undulating shape.

95. The prosthesis according to any one of Claims 92-94, wherein the first row of struts of the supplemental frame is configured to be positioned radially inwardly of the first row of struts of the frame body.

96. The prosthesis according to any one of Claims 92-94, wherein the first row of struts of the supplemental frame is configured to be positioned radially outwardly of the first row of struts of the frame body.

97. The prosthesis according to any one of Claims 92-96, wherein the distal anchoring feature extends from the frame body.

98. The prosthesis of Claim 97, wherein the distal anchoring feature extends distally from the frame body.

99. The prosthesis according to any one of Claims 92-98, wherein the distal anchoring feature extends from the supplemental frame.

100. The prosthesis according to any one of Claims 92-99, wherein the supplemental frame comprises a second row of struts, the first and second rows of struts of the supplemental frame forming cells.

101. The prosthesis of Claim 100, wherein the second row of struts of the supplemental frame has an undulating shape.

102. The prosthesis of any one of Claims 100 or 101, wherein the second row of struts of the supplemental frame is configured to extend distally of the frame body.

103. The prosthesis according to any one of Claims 92-102, wherein the expandable frame comprises a proximal anchoring feature, the proximal anchoring feature sized to be positioned on a second side of the annulus of the native heart valve.

104. The prosthesis of Claim 103, wherein the proximal anchoring feature comprises a first row of struts configured to be generally aligned along the second row of struts of the frame body, the first row of struts of the proximal anchoring feature having a shape which generally matches the shape of the second row of struts of the frame body.

105. The prosthesis of any one of Claims 103 or 104, wherein the proximal anchoring feature is formed separately from the frame body.

106. The prosthesis of Claim 105, wherein the first row of struts of the proximal anchoring feature is configured to be attached to at least a portion of the second row of struts of the frame body.

107. The prosthesis of Claim 106, wherein the first row of struts of the proximal anchoring feature is attached to the second row of struts of the frame body via sutures.

108. The prosthesis according to any one of Claims 104-107, wherein the first row of struts of the proximal anchoring feature and the second row struts of cells of the frame body have an undulating shape.

109. The prosthesis according to any one of Claims 104-108, wherein the first row of struts of the proximal anchoring feature is configured to be positioned radially outwardly of the second row of struts of the frame body.

110. The prosthesis according to any one of Claims 104-108, wherein the first row of struts of the proximal anchoring feature is configured to be positioned radially inwardly of the second row of struts of the frame body.

111. The prosthesis according to any one of Claims 104-110, wherein the proximal anchoring feature comprises a second row of struts, the first and second rows of struts of the proximal anchoring feature forming cells.

112. The prosthesis of Claim 111, wherein the second row of struts of the proximal anchoring feature has an undulating shape.

113. The prosthesis of any one of Claims 111 or 112, wherein the second row of struts of the proximal anchoring feature is configured to be generally aligned along a third row of struts of the frame body, the second row of struts of the proximal anchoring feature having a shape which generally matches the shape of the third row of struts of the frame body.

114. The prosthesis according to any one of Claims 103-113, further comprising a plurality of locking tabs.

115. The prosthesis of Claim 114, wherein at least some of the locking tabs extend from the frame body.

116. The prosthesis of any one of Claims 114 or 115, wherein at least some of the locking tabs extend from the proximal anchoring feature.

117. The prosthesis of Claim 114, wherein at least some of the locking tabs extend from the frame body and at least some of the locking tabs extend from the proximal anchoring feature, wherein the locking tabs of the proximal anchoring feature are configured to be generally aligned along the locking tabs of the frame body, the locking tabs of the proximal anchoring feature having a shape which generally matches the shape of the locking tabs of the frame body.

118. The prosthesis according to any one of Claims 92-117, wherein the distal anchoring feature comprises a plurality of distal anchors, at least one of the distal anchors comprising two or more prongs.

119. The prosthesis of Claim 118, wherein the two or more prongs are movable in a lateral direction relative to each other.

120. The prosthesis of any one of Claims 118 or 119, wherein a lateral dimension of the distal anchor comprising two or more prongs increases when the expandable frame transitions to an expanded configuration.

121. The prosthesis according to any one of Claims 118-120, wherein the two or more prongs are movable in a radial direction relative to each other.

122. The prosthesis according to any one of Claims 118-121, wherein a radial offset of the two or more prongs increases when the expandable frame transitions to an expanded configuration.

123. The prosthesis according to any one of Claims 92-122, wherein the distal anchoring feature comprises one or more anchors configured to be movable in an axial direction relative to the frame body.

124. The prosthesis according to any one of Claims 92-123, wherein the distal anchoring feature comprises one or more anchors having an insert.

125. The prosthesis of Claim 124, wherein the insert is configured to extend radially outwardly relative to the frame body when the expandable frame is in an expanded configuration.

126. The prosthesis of any one of Claims 124 or 125, wherein the insert comprises a platform, the platform configured to extend radially and laterally outwardly relative to the distal anchor when the expandable frame is in an expanded configuration.

127. The prosthesis according to any one of Claims 92-126, wherein at least one of the distal anchors comprises a strut which bifurcates into two or more struts proximate a base of the distal anchor.

128. The prosthesis according to any one of Claims 92-127, wherein the valve body comprises one or more intermediate components connecting the leaflets to the expandable frame.

129. The prosthesis of Claim 128, wherein:

the plurality of leaflets each have an arcuate proximal edge and a free distal edge, the plurality of leaflets being joined at commissures, the plurality of leaflets configured to allow flow in a proximal-to-distal direction and prevent flow in a distal-to-proximal direction; and

the one or more intermediate components connect the leaflets to the expandable frame, wherein at least a portion of the arcuate proximal edge of each leaflet and/or the commissures are indirectly coupled to the expandable frame via the one or more intermediate components such that when the frame is in an

expanded configuration, the one or more intermediate components position at least a portion of the arcuate proximal edge of each leaflet and/or the commissures radially inward from an inner surface of the expandable frame.

130. The prosthesis of any one of Claims 128 or 129, wherein the one or more intermediate components form a generally tangent surface with the expandable frame when the valve body is closed to prevent flow in the second direction.

131. The prosthesis of any one of Claims 128 or 129, wherein the one or more intermediate components form an angle between about 120° to about 195° with the expandable frame when the valve body is closed to prevent flow in the second direction.

132. The prosthesis of Claim 131, wherein the one or more intermediate components form an angle between about 140° to about 190° with the expandable frame when the valve body is closed to prevent flow in the second direction.

133. The prosthesis of Claim 132, wherein the one or more intermediate components form an angle between about 160° to about 185° with the expandable frame when the valve body is closed to prevent flow in the second direction.

134. The prosthesis of Claim 133, wherein the one or more intermediate components form an angle of about 180° with the expandable frame when the valve body is closed to prevent flow in the second direction.

135. The prosthesis according to any one of Claims 92-134, wherein the prosthesis comprises an annular skirt, the annular skirt being at least partially formed from a material configured to allow blood to flow therethrough and wherein the material is a partially porous cloth.

136. The prosthesis of Claim 135, wherein the material comprises one or more holes formed therethrough.

137. The prosthesis according to any one of Claims 135 or 136, wherein the material is configured such that, after deployment at the native heart valve, a rate of blood flow through the material decreases.

138. The prosthesis according to Claim 137, wherein the skirt comprises a hydrogel configured to reduce the rate of blood flow through the material.




FIG. 1






FIG. 2




FIG. 3




FIG. 4




FIG. 5A




FIG. 5B




FIG. 6




FIG. 7




FIG. 8






FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19A




FIG. 19B

17/71




FIG. 19C



18/71




FIG. 20




FIG. 21

19/71




FIG. 22




FIG. 23

20/71




FIG. 24




FIG. 25




FIG. 28




FIG. 29




FIG. 26




FIG. 27




FIG. 30




FIG. 31




FIG. 32

23/71




FIG. 33




FIG. 36




FIG. 37




FIG. 34




FIG. 35




FIG. 38




FIG. 39




FIG. 40

FIG. 38






FIG. 41A




FIG. 41B




FIG. 41C




FIG. 42A





FIG. 42B



32/71




FIG. 44




FIG. 45



34/71




FIG. 46

35/71




FIG. 47






FIG. 50




FIG. 51




FIG. 52




FIG. 53




FIG. 54




FIG. 55

39/71




FIG. 56




FIG. 57




FIG. 58

FIG. 59




FIG. 60

FIG. 61




FIG. 62




FIG. 63




FIG. 64




FIG. 65



42/71




FIG. 66




FIG. 67




FIG. 68




FIG. 69




FIG. 70

43/71




FIG. 73

FIG. 72

FIG. 71

44/71




FIG. 74




FIG. 75




FIG. 76




FIG. 77




FIG. 78




FIG. 79

46/71




FIG. 80




FIG. 81




FIG. 82




FIG. 83




FIG. 84




FIG. 85




FIG. 86

FIG. 88

FIG. 87

FIG. 89

FIG. 90




FIG. 91




FIG. 92




FIG. 93




FIG. 94






FIG. 95




FIG. 97




FIG. 99




FIG. 96




FIG. 98




FIG. 100




FIG. 102




FIG. 103




FIG. 104




FIG. 105




FIG. 106




FIG. 107




FIG. 108




FIG. 109A




FIG. 109B

55/71




FIG. 111




FIG. 110

56/71




FIG. 114

FIG. 113

FIG. 112

57/71




FIG. 115




FIG. 116




FIG. 117






FIG. 118

59/71




FIG. 119




FIG. 120

61/71




FIG. 121




FIG. 122




FIG. 123

64/71




FIG. 124

65/71




FIG. 125






FIG. 126

67/71




FIG. 127




FIG. 128

69/71




FIG. 129

70/71




FIG. 130

71/71




FIG. 131

