



(51) International Patent Classification:

G06F 9/451 (2018.01) H04L 29/06 (2006.01)
H03M 7/30 (2006.01) H04W 28/06 (2009.01)
H04L 29/08 (2006.01)

(21) International Application Number:

PCT/US2020/013607

(22) International Filing Date:

15 January 2020 (15.01.2020)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

16/252,809 21 January 2019 (21.01.2019) US

(71) Applicant: CITRIX SYSTEMS, INC. [US/US]; 851 W. Cypress Creek Rd., Fort Lauderdale, Florida 33309 (US).

(72) Inventors: RAMAREDDY, Shashidhar; 851 West Cypress Creek Road, Fort Lauderdale, Florida 33309 (US). MOMCHILOV, Georgy; 851 W. Cypress Creek Rd., Fort Lauderdale, Florida 33309 (US). MITTAL, Ankur; Prestige Dynasty, No. 33, Ulsoor Road, Bangalore 560 042 (IN).

(74) Agent: TAYLOR, Michael W. et al.; Allen Dyer, Doppelt & Gilchrist, P.A., 255 S. Orange Avenue, Suite 1401, Orlando, Florida 32802-3791 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DJ, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JO, JP, KE, KG, KH, KN, KP, KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, WS, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

(54) Title: COMPUTING SYSTEM WITH GATEWAY DATA TRANSFER BASED UPON DEVICE DATA FLOW CHARACTERISTICS AND RELATED METHODS




FIG. 3B

(57) Abstract: A computing system may include a server, client computing devices, a gateway device in communication between the server and the client computing devices, and a local device to be coupled to a given client computing device and to be operable in a given virtual desktop instance associated with the given client computing device, thereby generating client initialization packets. The gateway device may be configured to when the local device is coupled to the given client computing device, determine whether a client packet from a plurality of client initialization packets is within a client mapping table, replace the client packet with a client mapping ID number to define compressed client initialization packets, and send the compressed client initialization packets to the server. The server may be configured to replace the client mapping ID number with the client packet in the compressed client initialization packets based upon a server mapping table.



Published:

— *with international search report (Art. 21(3))*

COMPUTING SYSTEM WITH GATEWAY DATA TRANSFER BASED UPON DEVICE DATA FLOW CHARACTERISTICS AND RELATED METHODS

Background

[0001] In virtual desktop infrastructure systems, a typical user uses a terminal or client machine to connect to a remotely provided computing environment that provides a desktop paradigm. The remote or “virtual” desktop is typically kept or stored on a remote central server instead of on the hard-drive of the local client machine. Accordingly, the remote desktop may execute a single user operating system (e.g. Windows 10) or a multi-user operating system (e.g. Windows 10 Server), that allows multiple independent connections to separate virtual desktops. In this arrangement, the different users of the independent connections are capable of having different levels of authorization privileges. For example, some users may be permitted access to all, some or none of the applications, files, etc., of the computing environment.

[0002] Although client machines are often referred to as “dumb terminals”, client machines offer a full desktop experience when connecting in a virtual desktop infrastructure environment, offering capabilities and performance, specifically designed to best leverage and enhance the performance and functionality of the virtual desktop infrastructure. For example, client machines are often highly configurable and perform a high degree of local processing (e.g., management of local screen and keyboard, management of locally connected devices, and handling of specific keys and/or key combinations).

[0003] Because the virtual desktop infrastructure provides the perception that the client machine is merely an extension of the remote computer, if a new device is attached to the client machine, it is necessary to configure the client machine to recognize and configure the device. In short, when the user connects a local device to the client machine, the virtual desktop instance needs to recognize and use the local device as if it was the client machine. Because of this, the virtual desktop infrastructure needs to establish a communication link with the local device. Depending on the bandwidth of the local device, this new link can be burdensome on the virtual desktop instance, and may create latency issues.

Summary

[0004] Generally, a computing system may include a server, and a plurality of client computing devices. The server may be configured to provide a corresponding plurality of virtual desktop instances for the plurality of client computing devices. The computing system may include a gateway device in communication between the server and the plurality of client computing devices, and at least one local device to be coupled to a given client computing device and to be operable in a given virtual desktop instance associated with the given client computing device, thereby generating a plurality of client initialization packets. The server may be configured to generate a server mapping table comprising a plurality of known server packets associated with the at least one local device, and a plurality of server mapping ID numbers respectively associated with the plurality of known server packets. The gateway device may be configured to generate a client mapping table comprising a plurality of known client packets associated with the at least one local device, and a plurality of client mapping ID numbers respectively associated with the plurality of known client packets.

[0005] The gateway device may be configured to, when the at least one local device is coupled to the given client computing device, determine whether at least one client packet from the plurality of client initialization packets is within the client mapping table, replace the at least one client packet with at least one client mapping ID number to define a plurality of compressed client initialization packets, and send the plurality of compressed client initialization packets to the server. The server may be configured to

replace the at least one client mapping ID number with the at least one client packet in the plurality of compressed client initialization packets based upon the server mapping table.

[0006] Additionally, the server and the gateway device may be configured to synchronize the server mapping table and the client mapping table. The server may be configured to, when the at least one local device is coupled to the given client computing device, determine whether at least one server packet from a plurality of server initialization packets is within the server mapping table, replace the at least one server packet with at least one server mapping ID number to define a plurality of compressed server initialization packets, and send the plurality of compressed server initialization packets to the gateway device. Also, the server and the gateway device may be configured to, when the at least one local device is decoupled from the given client computing device, perform the determining, the replacing, and the sending.

[0007] For example, the plurality of known server packets and the plurality of known client packets each may comprise a communication standard initialization packet. The plurality of known server packets and the plurality of known client packets may each comprise at least one of a smart card initialization sequence packet, smart card authentication packet, smart card digital signing packet, and smart card certificate transmission packet.

[0008] The server mapping table and the client mapping table may each comprise a plurality of local device types associated with the plurality of client mapping ID numbers and the plurality of server mapping ID numbers. When the plurality of compressed client initialization packets generates an error, the server and the gateway device may be configured to initialize the at least one local device using the plurality of client initialization packets.

[0009] For example, the at least one local device may comprise at least one of a universal serial bus (USB) device, a TWAIN device, and a smart card device. In some embodiments, the determining may be based upon at least one of client name, smart card reader name, smart card reader state, smart card type, smart card Answer to Reset (ATR) string, smart card ID, and smart card certificate hash.

[0010] Yet another aspect is directed to a method for operating a gateway device in communication between a server and a plurality of client computing devices. The server is to provide a corresponding plurality of virtual desktop instances for the plurality of client computing devices, and at least one local device is to be coupled to a given client computing device and to be operable in a given virtual desktop instance associated with the given client computing device, thereby generating a plurality of client initialization packets. The method may comprise generating a client mapping table comprising a plurality of known client packets associated with the at least one local device, and a plurality of client mapping ID numbers respectively associated with the plurality of known client packets. The method may include when the at least one local device is coupled to the given client computing device, determining whether at least one client packet from the plurality of client initialization packets is within the client mapping table, replacing the at least one client packet with at least one client mapping ID number to define a plurality of compressed client initialization packets, and sending the plurality of compressed client initialization packets to the server.

[0011] Another aspect is directed to a method for operating a server in communication with a plurality of client computing devices via a gateway device. The server is to provide a corresponding plurality of virtual desktop instances for the plurality of client computing devices, and at least one local device is to be coupled to a given client computing device and to be operable in a given virtual desktop instance associated with the given client computing device, thereby generating a plurality of server initialization packets. The method may comprise generating a server mapping table comprising a plurality of known server packets associated with the at least one local device, and a plurality of server mapping ID numbers respectively associated with the plurality of known server packets. The method may include when the at least one local device is coupled to the given client computing device, determining whether at least one server packet from the plurality of server initialization packets is within the server mapping table, replacing the at least one server packet with at least one server mapping ID number to define a plurality of compressed server initialization packets, and sending the plurality of compressed server initialization packets to the gateway device.

Brief Description of the Drawings

[0012] FIG. 1 is a schematic block diagram of a network environment of computing devices in which various aspects of the disclosure may be implemented.

[0013] FIG. 2 is a schematic block diagram of a computing device useful for practicing an embodiment of the client machines or the remote machines illustrated in FIG. 1.

[0014] FIG. 3A is a schematic block diagram of a first embodiment of a computing system with data transfer between a server and a client computing device based upon device data flow characteristics, according to the disclosure.

[0015] FIG. 3B is a schematic block diagram of a second embodiment of the computing system with data transfer between a server and a gateway device based upon device data flow characteristics, according to the disclosure.

[0016] FIG. 4A is a flowchart of a method for operating the computing system of FIG. 3A.

[0017] FIG. 4B is a flowchart of a method for operating the client computing device in the computing system of FIG. 3A.

[0018] FIG. 4C is a flowchart of a method for operating the server in the computing system of FIG. 3A.

[0019] FIG. 5 is a diagram of a server mapping table or a client mapping table in the computing system according to the disclosure.

[0020] FIG. 6 is a diagram of communication flow between the client computing device and the server in the computing system of FIG. 3A.

[0021] FIG. 7 is a diagram of local device descriptors in the computing system according to the disclosure.

[0022] FIG. 8 is a diagram of a local device interrupt transfer sequence in the computing system according to the disclosure.

[0023] FIGS. 9A-9B are diagrams of non-optimized and optimized local device initialization data exchanges, respectively, in the computing system according to the disclosure.

[0024] FIGS. 10A-10D are diagrams of local device initialization data exchanges in the computing system according to the disclosure.

[0025] FIG. 11 is a diagram of a local device initialization sequence in the computing system according to the disclosure.

Detailed Description

[0026] The present description is made with reference to the accompanying drawings, in which example embodiments are shown. However, many different embodiments may be used, and thus the description should not be construed as limited to the particular embodiments set forth herein. Like numbers refer to like elements throughout, and base 100 reference numerals are used to indicate similar elements in alternative embodiments.

[0027] As will be appreciated by one of skill in the art upon reading the following disclosure, various aspects described herein may be embodied as a device, a method or a computer program product (e.g., a non-transitory computer-readable medium having computer executable instruction for performing the noted operations or steps). Accordingly, those aspects may take the form of an entirely hardware embodiment, an entirely software embodiment, or an embodiment combining software and hardware aspects.

[0028] Furthermore, such aspects may take the form of a computer program product stored by one or more computer-readable storage media having computer-readable program code, or instructions, embodied in or on the storage media. Any suitable computer readable storage media may be utilized, including hard disks, CD-ROMs, optical storage devices, magnetic storage devices, solid-state storage devices, and/or any combination thereof.

[0029] Referring initially to FIG. 1, a non-limiting network environment **101** (i.e. a communication system) in which various aspects of the disclosure may be implemented includes one or more client machines **102a-102n**, one or more remote machines **106a-106n**, one or more networks **104a, 104b**, and one or more appliances **108** installed within the computing environment **101**. The client machines **102a-102n** communicate with the remote machines **106a-106n** via the networks **104a, 104b**.

[0030] In some embodiments, the client machines **102a-102n** communicate with the remote machines **106a-106n** via an intermediary appliance **108**. The illustrated

appliance **108** is positioned between the networks **104a**, **104b** and may also be referred to as a network interface or gateway. In some embodiments, the appliance **108** may operate as an application delivery controller (ADC) to provide clients with access to business applications and other data deployed in a datacenter, the cloud, or delivered as Software as a Service (SaaS) across a range of client devices, and/or provide other functionality such as load balancing, etc. In some embodiments, multiple appliances **108** may be used, and the appliance(s) **108** may be deployed as part of the network **104a** and/or **104b**.

[0031] The client machines **102a-102n** may be generally referred to as client machines **102**, local machines **102**, clients **102**, client nodes **102**, client computers **102**, client devices **102**, computing devices **102**, endpoints **102**, or endpoint nodes **102**. The remote machines **106a-106n** may be generally referred to as servers **106** or a server farm **106**. In some embodiments, a client device **102** may have the capacity to function as both a client node seeking access to resources provided by a server **106** and as a server **106** providing access to hosted resources for other client devices **102a-102n**. The networks **104a**, **104b** may be generally referred to as a network. The networks **104a**, **104b** may be configured in any combination of wired and wireless networks.

[0032] A server **106** may be any server type such as, for example: a file server; an application server; a web server; a proxy server; an appliance; a network appliance; a gateway; an application gateway; a gateway server; a virtualization server; a deployment server; a Secure Sockets Layer (SSL) or Transport Layer Security (TLS) Virtual Private Network (VPN) server; a firewall; a web server; a server executing an active directory; a cloud server; or a server executing an application acceleration program that provides firewall functionality, application functionality, or load balancing functionality.

[0033] A server **106** may execute, operate or otherwise provide an application that may be any one of the following: software; a program; executable instructions; a virtual machine; a hypervisor; a web browser; a web-based client; a client-server application; a thin-client computing client; an ActiveX control; a Java applet; software related to voice over internet protocol (VoIP) communications like a soft IP telephone; an application for streaming video and/or audio; an application for facilitating real-time-data

communications; a HTTP client; a FTP client; an Oscar client; a Telnet client; or any other set of executable instructions.

[0034] In some embodiments, a server **106** may execute a remote presentation services program or other program that uses a thin-client or a remote-display protocol to capture display output generated by an application executing on a server **106** and transmit the application display output to a client device **102**. In yet other embodiments, a server **106** may execute a virtual machine providing, to a user of a client device **102**, access to a computing environment. The client device **102** may be a virtual machine. The virtual machine may be managed by, for example, a hypervisor, a virtual machine manager (VMM), or any other hardware virtualization technique within the server **106**.

[0035] In some embodiments, the network **104a, 104b** may be: a local-area network (LAN); a metropolitan area network (MAN); a wide area network (WAN); a primary public network; and a primary private network. Additional embodiments may include a network **104a, 104b** of mobile telephone networks that use various protocols to communicate among mobile devices. For short range communications within a wireless local-area network (WLAN), the protocols may include IEEE 802.11, Bluetooth, and Near Field Communication (NFC).

[0036] FIG. 2 depicts a block diagram of a computing device **100** useful for practicing an embodiment of client devices **102**, appliances **108** and/or servers **106**. The computing device **100** includes one or more processors **103**, volatile memory **122** (e.g., random access memory (RAM)), non-volatile memory **128**, user interface (UI) **123**, one or more communications interfaces **118**, and a communications bus **127**. The non-volatile memory **128** may include: one or more hard disk drives (HDDs) or other magnetic or optical storage media; one or more solid state drives (SSDs), such as a flash drive or other solid-state storage media; one or more hybrid magnetic and solid-state drives; and/or one or more virtual storage volumes, such as a cloud storage, or a combination of such physical storage volumes and virtual storage volumes or arrays thereof.

[0037] The user interface **123** may include a graphical user interface (GUI) **124** (e.g., a touchscreen, a display, etc.) and one or more input/output (I/O) devices **126** (e.g., a mouse, a keyboard, a microphone, one or more speakers, one or more cameras, one or

more biometric scanners, one or more environmental sensors, and one or more accelerometers, etc.).

[0038] The non-volatile memory **128** stores an operating system **115**, one or more applications **116**, and data **117** such that, for example, computer instructions of the operating system **115** and/or the applications **116** are executed by processor(s) **103** out of the volatile memory **122**. In some embodiments, the volatile memory **122** may include one or more types of RAM and/or a cache memory that may offer a faster response time than a main memory. Data may be entered using an input device of the GUI **124** or received from the I/O device(s) **126**. Various elements of the computer **100** may communicate via the communications bus **127**.

[0039] The illustrated computing device **100** is shown merely as an example client device or server, and may be implemented by any computing or processing environment with any type of machine or set of machines that may have suitable hardware and/or software capable of operating as described herein.

[0040] The processor(s) **103** may be implemented by one or more programmable processors to execute one or more executable instructions, such as a computer program, to perform the functions of the system. As used herein, the term “processor” describes circuitry that performs a function, an operation, or a sequence of operations. The function, operation, or sequence of operations may be hard coded into the circuitry or soft coded by way of instructions held in a memory device and executed by the circuitry. A processor may perform the function, operation, or sequence of operations using digital values and/or using analog signals.

[0041] In some embodiments, the processor can be embodied in one or more application specific integrated circuits (ASICs), microprocessors, digital signal processors (DSPs), graphics processing units (GPUs), microcontrollers, field programmable gate arrays (FPGAs), programmable logic arrays (PLAs), multi-core processors, or general-purpose computers with associated memory.

[0042] The processor **103** may be analog, digital or mixed-signal. In some embodiments, the processor **103** may be one or more physical processors, or one or more virtual (e.g., remotely located or cloud) processors. A processor including multiple processor cores and/or multiple processors may provide functionality for parallel,

simultaneous execution of instructions or for parallel, simultaneous execution of one instruction on more than one piece of data.

[0043] The communications interfaces **118** may include one or more interfaces to enable the computing device **100** to access a computer network such as a Local Area Network (LAN), a Wide Area Network (WAN), a Personal Area Network (PAN), or the Internet through a variety of wired and/or wireless connections, including cellular connections.

[0044] In described embodiments, the computing device **100** may execute an application on behalf of a user of a client device. For example, the computing device **100** may execute one or more virtual machines managed by a hypervisor. Each virtual machine may provide an execution session within which applications execute on behalf of a user or a client device, such as a hosted desktop session. The computing device **100** may also execute a terminal services session to provide a hosted desktop environment. The computing device **100** may provide access to a remote computing environment including one or more applications, one or more desktop applications, and one or more desktop sessions in which one or more applications may execute.

[0045] Additional descriptions of a computing device **100** configured as a client device **102** or as a server **106**, or as an appliance intermediary to a client device **102** and a server **106**, and operations thereof, may be found in U.S. Patent Nos. 9,176,744 and 9,538,345, which are incorporated herein by reference in their entirety. The '744 and '345 patents are both assigned to the current assignee of the present disclosure.

[0046] Referring now to FIG. 3A, a computing system **201** (FIG. 3A) according to the disclosure is now described. Also, with reference to a flowchart **940** (FIG. 4A), a method for operating the computing system **201** is also described. The computing system **201** illustratively includes a server **206**, and a plurality of client computing devices **202a-202b** in communication with the server. The server **206** is configured to provide a corresponding plurality of virtual desktop instances **230a-230b** for the plurality of client computing devices **202a-202b**.

[0047] The computing system **201** includes a plurality of local devices **235a-235b** to be coupled respectively to the plurality of client computing devices **202a-202b**. The local device **235a** is coupled to a given client computing device **202a** and to be operable in a

given virtual desktop instance **230a** associated with the given client computing device, thereby generating a plurality of client initialization packets. The server **206** is configured to generate a server mapping table **245** comprising a plurality of known server packets **242** associated with the local device **235a**, and a plurality of server mapping ID numbers **243** respectively associated with the plurality of known server packets.

[0048] The given client computing device **202a** is configured to generate a client mapping table **244** comprising a plurality of known client packets **238** associated with the local device **235a**, and a plurality of client mapping ID numbers **239** respectively associated with the plurality of known client packets. The given client computing device **202a** is configured to, when the local device **235a** is coupled to the given client computing device, determine whether at least one client packet from the plurality of client initialization packets is within the client mapping table **244**, replace the at least one client packet with at least one client mapping ID number **239** to define a plurality of compressed client initialization packets, and send the plurality of compressed client initialization packets to the server **206**. The server **206** is configured to replace the at least one client mapping ID number **239** with the at least one client packet in the plurality of compressed client initialization packets based upon the server mapping table **245**.

[0049] Referring now to FIG. 4A, the method for operating the computing system **201** is now described with reference to the flowchart **940**. (Block **941**). The method includes generating the server mapping table **245** at the server **206** (Block **943**), and generating the client mapping table **244** at the given client computing device **202a**. (Block **945**). The method illustratively includes determining when the local device **235a** is coupled to the given client computing device **202a** (Block **947**), and then generating the plurality of compressed client initialization packets (Block **949**), and sending the plurality of compressed client initialization packets to the server **206**. (Blocks **951**, **953**).

[0050] Referring now again to FIG. 3A, the computing system **201** according to the disclosure is now described in more detail. Also, with reference to flowcharts **960**, **980** (FIGS. 4B-4C), the method for operating the computing system **201** is also described in

more detail. The computing system **201** illustratively includes a server **206**, and a plurality of client computing devices **202a-202b** in communication with the server.

[0051] The server **206** is configured to provide a corresponding plurality of virtual desktop instances **230a-230b** for the plurality of client computing devices **202a-202b**. The server **206** illustratively comprises a memory **231**, and a processor **232** cooperating with the memory. Each of the plurality of client computing devices **202a-202b** illustratively comprises a memory **233**, and a processor **234** cooperating with the memory.

[0052] The computing system **201** illustratively comprises a plurality of local devices **235a-235b** to be coupled respectively to the plurality of client computing devices **202a-202b** and to be operable in a given virtual desktop instance **230a** associated with the given client computing device, thereby generating a plurality of client initialization packets. Each local device **235a-235b** may comprise one or more of a USB device, a TWAIN device, and a smart card device. Of course, this coupling may comprise a wired connection, or a wireless connection (e.g. Bluetooth, infrared, or some other local wireless standard).

[0053] As will be appreciated, when the user of the given client computing device **202a** couples the local device **235a** to the respective device providing the given virtual desktop instance **230a**, the user expects the local device to be operable similarly to the local desktop environment. In particular, the user expects the resources of the local device **235a** to be fully accessible in the given virtual desktop instance **230a**.

[0054] In typical local desktop environments, when the local device **235a** is coupled or decoupled, the local device and the local desktop environment (i.e. the local operating system) exchange local device initialization/deinitialization communications. Given that these local device communications standards were developed with local connections in mind (i.e. typically wired, high bandwidth, low latency, low packet loss), these local device communications standards are data heavy in nature.

[0055] Moreover, in the virtual desktop infrastructure space, these same local device communications standards must now be implemented over the network (e.g. the Internet) between the server **206** and the given client computing device **202a**. The computing system **201** provides an approach to this issue by compressing these local

device initialization/deinitialization communications at the server **206** and the given client computing device **202a**.

[0056] The server **206** is configured to generate a server mapping table **245** comprising a plurality of known server packets **242** associated with the at least one local device, and a plurality of server mapping ID numbers **243** respectively associated with the plurality of known server packets. The given client computing device **202a** is also configured to generate a client mapping table **244** comprising a plurality of known client packets **238** associated with the at least one local device, and a plurality of client mapping ID numbers **239** respectively associated with the plurality of known client packets.

[0057] The plurality of known server packets **242** and the plurality of known client packets **238** may each comprise a communication standard initialization packet (e.g. USB initialization/deinitialization packet). The plurality of known server packets **242** and the plurality of known client packets **238** each may comprise at least one of a smart card initialization sequence packet, smart card authentication packet, smart card digital signing packet, and smart card certificate transmission packet. In other words, the plurality of known server packets **242** and the plurality of known client packets **238** each comprise commonly exchanged packets.

[0058] The given client computing device **202a** is configured to, when the local device **235a** is either coupled or decoupled to the given client computing device, determine whether at least one client packet from the plurality of client initialization packets is within the client mapping table **244**. In other words, this determining step is performed when the local device **235a** initialization/deinitialization communications are about to be exchanged between the given client computing device **202a** and the server **206**. The determining may be based upon at least one of client name, smart card reader name, smart card reader state, smart card type, smart card ATR string, smart card ID, and smart card certificate hash.

[0059] If the at least one client packet is within the client mapping table **244**, the given client computing device **202a** is configured to replace the at least one client packet with at least one client mapping ID number **239** to define a plurality of compressed client initialization packets. If the at least one client packet is not within the client mapping

table **244**, then the given client computing device **202a** is configured to move on to a next packet, and repeat the analysis.

[0060] In some embodiments, the given client computing device **202a** is configured to examine each and every packet in the plurality of client initialization packets. In other embodiments, the given client computing device **202a** is configured to selectively review only portions of the plurality of client initialization packets (e.g. portions more likely to have repeating packets). In other words, with a generated sequence of packets, the recognized packets are swapped out with respective client mapping ID numbers **239**, which reduces the size of the payload.

[0061] In some embodiments, the respective client mapping ID numbers **239** may each represent a common sequence for initialization and/or deinitialization. For example, instead of receiving a sequence of initialization packets from the given client computing device **202a**, the server **206** would receive a single mapping ID number mapped to the same sequence, i.e. an effective instruction to playback the sequence of packets rather than sending the sequence of packets (See, e.g., FIG. 11). Also, in some embodiments where the local device **235a** experiences a communication port change, the plurality of compressed client initialization packets would include that new port information.

[0062] Then, the given client computing device **202a** is configured to send the plurality of compressed client initialization packets to the server **206**. The server **206** is configured to receive the plurality of compressed client initialization packets.

Subsequent to their receipt, the server **206** is configured to reconstitute the original initialization packets by replacing the at least one client mapping ID number **239** with the at least one client packet in the plurality of compressed client initialization packets based upon the server mapping table **245**. To this end, the server **206** and the given client computing device **202a** are configured to synchronize the server mapping table **245** and the client mapping table **244**. As the server **206** and the given client computing device **202a** build their respective mapping tables, they need to reconcile changes/additions so that the plurality of compressed client initialization packets can be properly processed.

[0063] Also, in some embodiments, the server **206** is configured to perform the same compression features with the server mapping table **245**. In particular, the server **206** is

configured to, when the local device **235a** is coupled to the given client computing device **202a**, determine whether at least one server packet from a plurality of server initialization packets is within the server mapping table **245**, replace the at least one server packet with at least one server mapping ID number **243** to define a plurality of compressed server initialization packets, and send the plurality of compressed server initialization packets to the given client computing device. As will be appreciated, the plurality of server initialization packets are exchanged in response to the plurality of client initialization packets from the given client computing device **202a**.

[0064] Moreover, the server **206** and the given client computing device **202a** are configured to, when the local device **235a** is decoupled from the given client computing device **202a**, perform the determining, the replacing, and the sending. Indeed, as will be appreciated, the server **206** and the given client computing device **202a** are configured to perform compression of local device deinitialization communications, and is not limited to local device initialization communications. As will be appreciated, the teachings of this disclosure could be expanded to any communications with reoccurring packets.

[0065] As depicted in the exemplary embodiment, it should be appreciated that the other client computing device **202b** also has a local device **235b** coupled thereto. Also, the server **206** may be configured to monitor packets exchanged between the plurality of client computing devices **202a-202b** and respective local devices **235a-235b** to generate the server mapping table **245**. In other words, the server **206** is configured to learn reoccurring packet sequences from global communications in the computing system **201** and add them to the server mapping table **245** and the client mapping table **244**. Indeed, in some embodiments, the server **206** may utilize machine learning techniques to predict packet sequences in communications between the server **206** and the plurality of client computing devices **202a-202b** and respective local devices **235a-235b**.

[0066] As will be appreciated, the computing system **201** illustratively includes only two client computing devices **202a-202b** for drawing clarity. It should be appreciated that the computing system **201** could accommodate a large number of client computing

devices. In fact, the server **206** may be configured to use big data analytics to further build the server mapping table **245** and the client mapping table **244**.

[0067] Referring briefly to FIG. 5 and a diagram **905** therein, an exemplary embodiment of either the server mapping table **245** or the client mapping table **244** is shown. The server mapping table **245** and the client mapping table **244** each may comprise a plurality of local device types (device column) associated with the plurality of client mapping ID numbers **239** (identifier column) and the plurality of server mapping ID numbers **243** (identifier column).

[0068] Helpfully, when the plurality of compressed client initialization packets generates an error, the server **206** and the given client computing device **202a** may be configured to initialize the at least one local device **235a-235b** using the plurality of client initialization packets. In other words, if the plurality of compressed initialization packets causes an error, the server **206** and the given client computing device **202a** revert to the uncompressed sequences to remedy the error (e.g. the USB connection would be reset, i.e. local USB device ejected, and then a reinitialization is performed).

[0069] Also, if the connection to the local device **235a-235b** is lost, the server **206** and the given client computing device **202a** are configured to reinitialize the connection automatically. If the local device **235a-235b** is decoupled during the initialization, the given client computing device **202a** is configured to send an abort message to the server **206** so that the server does not play out the initialization packets on its end.

[0070] As shown in the exemplary use application in FIG. 6, when the local device **235a** (e.g., the illustrated web camera) is coupled to the client computing device **202a**, the local device initialization is optimized. Indeed, in the illustrated step 4, no data is exchanged since these packets are standardized and stored in respective mapping tables. Here, the packets typically received at the server **206** from the client computing device **202a** are played back or recreated from the server mapping table **245**. The client computing device **202a** does the same using the client mapping table **244**.

[0071] In some embodiments, the computing system further may include a bridge device **241** coupled between the client computing device **202b** and the server **206** and configured to generate a bridge mapping table comprising a plurality of known bridge packets associated with the at least one local device, and a corresponding plurality of

bridge mapping ID numbers. In FIG. 3A, the bridge device **241** is depicted with dashed lines, and may be omitted. The bridge device **241** may comprise one or more of a Citrix Software-Defined Wide Area Network (SD-WAN) and a Citrix Gateway (NetScaler).

[0072] Referring now to FIG. 4B and the flowchart **960** therein, a method for operating a given client computing device **202a** in communication with a server **206** is now described. (Block **961**). The server **206** is to provide a given virtual desktop instance **230a** for the given client computing device **202a**, and at least one local device **235a** is to be coupled to the given client computing device and to be operable in the given virtual desktop instance **230a** associated with the given client computing device. The method comprises generating a client mapping table **244** comprising a plurality of known client packets associated with the at least one local device **235a**, and a plurality of client mapping ID numbers respectively associated with the plurality of known client packets. (Block **963**). The method includes when the at least one local device **235a** is coupled to the given client computing device **202a** (Block **965**), generating a plurality of client initialization packets, determining whether at least one client packet from the plurality of client initialization packets is within the client mapping table **244** (Block **967**), replacing the at least one client packet with at least one client mapping ID number to define a plurality of compressed client initialization packets (Block **969**), and sending the plurality of compressed client initialization packets to the server **206**. (Blocks **971, 973**).

[0073] Referring now to FIG. 4C and the flowchart **980** therein, a method for operating the server **206** is now described. (Block **981**). The server **206** is in communication with at least one client computing device **202a** to provide a corresponding at least one virtual desktop instance **230a-230b** for the at least one client computing device. At least one local device **235a** is to be coupled to a given client computing device **202a** and to be operable in a given virtual desktop instance **230a** associated with the given client computing device, thereby generating a plurality of server initialization packets. The method includes generating a server mapping table **245** comprising a plurality of known server packets associated with the at least one local device **235a**, and a plurality of server mapping ID numbers respectively associated with the plurality of known server packets. (Block **982**). The method comprises when the at least one local device **235a** is coupled to the given client computing device **202a** (Block **983**), determining whether

at least one server packet from the plurality of server initialization packets is within the server mapping table **245** (Block **984**), replacing the at least one server packet with at least one server mapping ID number to define a plurality of compressed server initialization packets (Block **985**), and sending the plurality of compressed server initialization packets to the given client computing device. (Blocks **986**, **987**).

[0074] It should be appreciated that the above methods could be defined as a computer executable instruction. From this computer executable instruction, a non-transitory computer-readable medium having the computer executable instruction for performing the noted operations or steps of these methods could be provided.

[0075] Referring now additionally to FIG. 3B, another embodiment of the computing system **301** is now described. In this embodiment of the computing system **301**, those elements already discussed above with respect to FIG. 3A are incremented by 300 and most require no further discussion herein. The computing system **301** illustratively includes a server **306**, and a plurality of client computing devices **302a-302b**. The server **306** is configured to provide a corresponding plurality of virtual desktop instances **330a-330b** for the plurality of client computing devices **302a-302b**. The server **306** illustratively comprises a memory **331**, and a processor **332** cooperating with the memory. This embodiment differs from the previous embodiment in that this computing system **301** illustratively comprises a gateway device **336** in communication between the server **306** and the plurality of client computing devices **302a-302b**, and a local device **335a** to be coupled to a given client computing device **302a** and to be operable in a given virtual desktop instance **330a** associated with the given client computing device **302a**, thereby generating a plurality of client initialization packets. In other words, the communications between the plurality of client computing devices **302a-302b** and the server **306** are routed through the gateway device **336**. The gateway device **336** illustratively comprises a memory **337**, and a processor **340** cooperating with the memory.

[0076] The server **306** is configured to generate a server mapping table **345** comprising a plurality of known server packets **342** associated with the local device **335a**, and a plurality of server mapping ID numbers **343** respectively associated with the plurality of known server packets. The gateway device **336** is configured to generate a client

mapping table **344** comprising a plurality of known client packets **338** associated with the local device **335a**, and a plurality of client mapping ID numbers **339** respectively associated with the plurality of known client packets.

[0077] As packets from the plurality of client computing devices **302a-302b** are sent through the gateway device **336**, the gateway device **336** is configured to, when the local device **335a** is either coupled or decoupled to the given client computing device **302a**, determine whether at least one client packet from the plurality of client initialization packets is within the client mapping table **344**, replace the at least one client packet with at least one client mapping ID number **339** to define a plurality of compressed client initialization packets, and send the plurality of compressed client initialization packets to the server **306**. The server **306** is configured to replace the at least one client mapping ID number **339** with the at least one client packet in the plurality of compressed client initialization packets based upon the server mapping table **345**.

[0078] Referring now additionally to FIGS. 7, 8, 10A-10D, several diagrams **910, 915, 920, 925, 930, 935** relating to embodiments of the computing systems **201, 301** where the local device **235a-235b, 335a** comprises a USB device are now described. Of course, this discussion regarding USB devices is exemplary, and is equally applicable to other types of the local device **235a-235b, 335a**.

[0079] With reference to FIG. 7, the diagram **910** includes a table showing the type of data associated with different USB device descriptors. USB initialization goes through standard set of USB request blocks (URB) exchanges of device descriptor, interface descriptor, pipe details etc. For a given local device (or type of device), these packets and sequence remains mostly the same with minor changes in certain fields. Because of this, these exchanges may benefit from the teachings of this disclosure.

[0080] In particular, descriptors used in local device **235a-235b, 335a** initialization are shown. The descriptors are typically used for device enumeration in known order for each kind of device. For example, this sequence is translated to uniformity in the Independent Computing Architecture (ICA) protocol (USB Redirection Virtual Channel) between the client computing device **202a-202b, 302a-302b** and the server **206, 306**. Hence, with small exceptions of address, the data transfer will be predictable, and by

using cached data with variable fields, the computing system **201, 301** could achieve packet replay at client computing device **202a-202b, 302a-302b** and the server **206, 306**.

[0081] With reference to FIG. 8, the diagram **915** aids in discussing USB interrupt pipe control flow and interrupt transfers. In the USB standard, if the local device **235a-235b, 335a** requires the attention of the host, it must wait until the host polls it. Interrupt transfers are typically non-periodic, small device “initiated” communication requiring bounded latency. An interrupt request is queued by the local device **235a-235b, 335a** until the host polls the USB device asking for data. According to the teachings of this disclosure, the polling mechanism will be a cached operation on the client computing device **202a-202b, 302a-302b**, which may avoid chattiness of connection from the server **206, 306** to client computing device.

[0082] Also, in embodiments of the computing systems **201, 301** where the local device **235a-235b, 335a** comprises a smart card device, the teachings of the disclosure may be used to optimize smart card logon operations. For example, for redirected smart card authentication, the server **206, 306** is configured to create a smart card resource manager context. The host re-enumerates smart card readers, gets smart card status (e.g., empty, present, etc.), establishes smart card communication context, obtains the CARD ATR, which maps to card type, finds the Cryptographic Service Provider (CSP), retrieves the certificate from the card, and initiates a challenge-response mechanism, which normally involves the user entering a PIN to unlock the private key on the card, etc. In this case, the initialization sequence and, in particular, the retrieval of the certificate are very expensive operations involving multiple round-trips, which could be optimized. Some certificates may be several kilobytes in size. In addition, some smart cards may only support 1-byte addressing thus limiting transactions to 256 bytes. An optimization is possible, for example, by detecting repetitive logon patterns with endpoint device/client name, reader name, reader state, card type, card ID, or certificate hash, and mapping them to a mapping ID number. If no match is found on the server, the normal processes could be performed.

[0083] Referring now to FIG. 9A and a diagram **916** therein, the following steps provide an example illustration of a non-optimized smart card authentication sequence. A

similar sequence exists for other smart card scenarios, such as digitally signing documents, e-mails, etc., in a Virtual Delivery Agent (VDA) session. The execution of this sequence serves as a learning phase of the method to optimize smart card operations. The client device has a smart card reader attached to it. In some embodiments, the reader may be combined with a smart card into a single device, for example, into a USB dongle containing the smart card, while a virtual smart card reader is simulated by the client operating system (OS). Of course, this is an exemplary listing, and other variants could be used.

[0084] Smart Card Authentication Sequence

- The client enumerates readers and their state (smart card empty, present, etc.).
 - A user inserts their card into the reader, the reader state changes.
 - The VDA Logon Process establishes Smart Card Resource Manager Context.
 - The request is forwarded to the client's OS Smart Card Resource Manager (RM).
- Note: The VDA Logon Process may involve multiple components or services, e.g. Logon UI, WinLogon, Local Security Authority Subsystem Service (LSASS), etc. It may also involve Smart Card/Personal Computer (SC/PC) application programming interface (API) hooking and redirection components. For purposes of this description, they are collectively referred to as VDA Logon Process.
- The client creates a RM Context and returns it to the server VDA Logon Process.
 - Using the RM context, the VDA Logon Process enumerates readers and their state. The request is forwarded to the client.
 - The client returns to the VDA Logon Process the list of readers and their state.
 - Using the RM context, if there is a card present in at least one reader, the VDA Logon Process establishes smart card Communication Context. The request is forwarded to the client's OS smart card RM.
 - The client creates a smart card Communication Context and returns it to the server VDA Logon Process.
 - Using the smart card Communication Context, the VDA Logon Process retrieves the card ATR string. Likewise, the request is forwarded to the client's smart card. Note: The ATR string uniquely identifies the smart card type.
 - The client returns to the VDA Logon Process the card ATR string. Note: The following

request is a modification of the normal sequence to facilitate the present disclosure, i.e. to uniquely identify the card.

- The card ID string uniquely identifies the card. This is required, since an endpoint client device may be shared between multiple users (Kiosk mode).
- The VDA Logon Process requests the card ID string.
- The client returns to the VDA Logon Process the card ID string.
- The VDA Logon Process looks up and loads the CSP, for example, based on the card ATR string. A CSP may perform crypto operations specific to a card type.
- VDA Logon Process retrieves the smart card certificate over a series of transactions, which are redirected to the client's smart card, and involve multiple roundtrips.
- The VDA Logon Process parses the certificate and extracts the User Principal Name (UPN), the public key, etc.
- The VDA Logon Process then prompts the user for PIN, e.g. via a Logon UI. The PIN prompt becomes visible at the client device via server-to-client graphics redirection.
- The user enters their PIN at the client, which is transferred to the server and into the VDA Logon Process, e.g. Logon UI.
- The VDA Logon Process initiates a challenge required to determine if the user is the true owner of the smart card. The challenge may involve creating a (random) nonce sent to the card. The VDA Logon Process also sends the PIN to the card.
- The client device communicates both the PIN and the nonce to the card. The PIN is used to unlock the use of the smart card's private key, which never leaves the card.
- The card uses the private key to sign the nonce and answer the challenge by sending it to the server.
- The VDA Logon Process verifies the signature of the signed nonce using the public key from certificate.
- The VDA Logon Process proceeds to log the user on.

[0085] Referring to FIG. 9B and a diagram **917** therein, the following steps provide an example illustration of an optimized smart card authentication sequence. A similar sequence exists for other smart card scenarios, such as digitally signing documents, e-mails, etc. in a VDA session.

[0086] The execution of this sequence illustrates another example of the use of the previously discussed method of “Map ID” pointing to observed, cached and shared client and server protocol sequences. In particular, a Map ID is used to identify and look up previously communicated smart card initialization and certificate data. Light-weight differential data is also exchanged for purposes of efficient contextualization and precise look up.

[0087] Optimized Smart Card Authentication Sequence

- The client enumerates readers and their state (smart card empty, present, etc.).
- A user inserts their card into the reader, the reader state changes.
- The client establishes Smart Card RM Context for the server.
- The client establishes smart card Communication Context for the server, based on the RM context.
- Using the smart card Communication Context, the client retrieves the card ATR string, ID string and certificate. Note: The ID string uniquely identifies the card. However, some cards may hold more than one certificate, so the certificate may also be required for further contextualization. The client computes a hash of the certificate.
- The client looks up the table with Map IDs based on at least one of ATR string, ID string and certificate hash.
- The client sends to the server the matching Map ID and, if an exact match is not found, also differential data, e.g. at least one of: RM context; Readers and their state; smart card Context; and at least one of card ATR string, ID string, certificate hash.
- The server looks up its table of Map IDs based on at least one of Map ID and differential data.
- If a match is not found, the VDA Logon Process proceeds as normal.
- If a match is found, the VDA Logon Process advantageously proceeds to short-circuit all of the following operations by servicing them from the server's table with cached protocol exchanges and the received contextual differential data, rather than using transactions requiring round-trips to the client: establish Smart Card RM Context; using the RM context, enumerate readers and their state; using the RM context, if there is a card present in at least one reader, establish smart card Communication Context; using the smart card Communication Context, retrieve the card ATR string; request the card

ID string (for consistency with the learning phase); look up and load the CSP, e.g. based on the card ATR string; a CSP may perform crypto operations specific to a card type. (Note: This operation does not have to go to the client anyway, even during the learning phase.); and retrieve the smart card certificate.

[0088] For security reasons and due to the random nature of the challenge-response mechanism, the rest of the logon process proceeds as normal:

-The VDA Logon Process parses the certificate and extracts the UPN, the public key, etc. The VDA Logon Process then prompts the user for PIN, e.g. via a Logon UI. The PIN prompt becomes visible at the client device via server-to-client graphics redirection.

-The user enters their PIN at the client, which is transferred to the server and into the VDA Logon Process, e.g. Logon UI.

-The VDA Logon Process initiates a challenge required to determine if the user is the true owner of the smart card. The challenge may involve creating a (random) nonce sent to the card.

-The VDA Logon Process also sends the PIN to the card.

-The client device communicates both the PIN and the nonce to the card. The PIN is used to unlock the use of the smart card's private key, which never leaves the card.

-The card uses the private key to sign the nonce and answer the challenge by sending it to the server.

-The VDA Logon Process verifies the signature of the signed nonce using the public key from certificate.

-The VDA Logon Process proceeds to log the user on.

[0089] Referring now to FIGS. 10A-10D, USB-specific standard initialization data exchange at bus level is shown in diagrams **920, 925, 930, 935**. More specifically, the diagrams **920, 925, 930, 935** show the standard descriptors and standard responses in a USB device initialization sequence. In other words, these figures show the initialization data exchange between local devices **235a-235b, 335a** and client computing devices **202a-202b, 302a-302b** as per the USB protocol specification. For a given local device, for example, local device **235a**, and a given client computing device, for example, client computing device **202a**, the initialization data exchanges are expected to remain consistent between different initialization occurrences as previously

discussed in the disclosure. As illustrated, it can be appreciated that examples of the standard descriptors such as configuration, interface and endpoint will be consistently repeated during each initialization sequence. Minor variations are possible in special cases. For example, a connection port may change when a user plugs in the local device **235a** into a different USB port of the client computing device **202a**. In these special cases, the previously discussed technique of sending light-weight differential data along with Map IDs may be applied. If significant changes occur, or an error occurs, the previously discussed technique of reverting to sending the complete uncompressed sequences may also be applied.

[0090] Thus, as described herein, the described embodiments provide improved operation of virtual desktop infrastructure computing systems, for example by providing an approach to data transfer when either coupling or decoupling the local device **235a-235b, 335a** to the client computing devices **202a-202b, 302a-302b**. Indeed, the computing systems **201, 301** leverage the fact that data transfer, such as during local device (e.g. USB device) redirection, has packets of data which are of a predictable format and sequence during initialization, surprise removal, deinitialization (i.e. termination of the local device communications). By storing the format and sequence, mapping ID numbers could be exchanged instead of complete packet and/or packet sequences between the client computing device **202a-202b, 302a-302b** and the server **206, 306**. This mapping ID numbers could be used to play the packet or packet sequence at the server **206, 306** and the client computing device instead of complete sequence transfer as it happens in typical approaches.

[0091] Typical approaches to data transfer using compression/encoding focus on the relationship between the current frame and the next frame for compression/optimization. The computing system **201, 301** of the disclosure is unique as it leverages behavior patterns specific to the virtual channel under consideration.

[0092] By swapping out packets with mapping ID numbers, the computing systems **201, 301** reduce aggregate traffic, improving system performance. The prior knowledge of data playback sequences may be used to create optimized packet sequences and protocol optimizations by building a mapping database of ID numbers to protocol sequence playback at the server **206, 306** and the client computing device **202a-202b,**

302a-302b. In the client computing device **202a-202b, 302a-302b** and the server **206, 306**, special concise messages are used to send differential data and playback the sequence of steps. Thus, this may optimize the overall data transfer requirements.

[0093] For example, the diagram **900** (FIG. 11) comprises a sequence diagram showing an example of a client computing device **202a-202b, 302a-302b** sending a mapping ID number (id1) as an indicator for a server **206, 306** to play the initialization sequence in the virtual desktop instance **230a-230b, 330a-330b** to initialize the local device **235a-235b, 335a** and return status to client computing device. Instead of the typical back and forth for local device initialization, the client computing device **202a-202b, 302a-302b** and the server **206** may regenerate the sequence using their respective mapping tables.

[0094] Other features relating to computing systems are disclosed in co-pending application: titled "COMPUTING SYSTEM WITH DATA TRANSFER BASED UPON DEVICE DATA FLOW CHARACTERISTICS AND RELATED METHODS," Attorney Docket No. ID1984US (96109), which is incorporated herein by reference in their entirety.

[0095] Many modifications and other embodiments will come to the mind of one skilled in the art having the benefit of the teachings presented in the foregoing descriptions and the associated drawings. Therefore, it is understood that the foregoing is not to be limited to the example embodiments, and that modifications and other embodiments are intended to be included within the scope of the appended claims.

THAT WHICH IS CLAIMED IS:

1. A computing system comprising:

a server;

a plurality of client computing devices, said server configured to provide a corresponding plurality of virtual desktop instances for said plurality of client computing devices;

a gateway device in communication between said server and said plurality of client computing devices; and

at least one local device to be coupled to a given client computing device and to be operable in a given virtual desktop instance associated with said given client computing device, thereby generating a plurality of client initialization packets;

said server configured to generate a server mapping table comprising a plurality of known server packets associated with said at least one local device, and a plurality of server mapping identification (ID) numbers respectively associated with said plurality of known server packets;

said gateway device configured to generate a client mapping table comprising a plurality of known client packets associated with said at least one local device, and a plurality of client mapping ID numbers respectively associated with said plurality of known client packets;

wherein said gateway device is configured to, when said at least one local device is coupled to said given client computing device,

determine whether at least one client packet from the plurality of client initialization packets is within the client mapping table,

replace the at least one client packet with at least one client mapping ID number to define a plurality of compressed client initialization packets, and

send the plurality of compressed client initialization packets to said server,

said server configured to replace the at least one client mapping ID number with the at least one client packet in the plurality of compressed client initialization packets based upon the server mapping

table.

2. The computing system of claim 1 wherein said server and said gateway device are configured to synchronize the server mapping table and the client mapping table.

3. The computing system of claim 1 wherein said server is configured to, when said at least one local device is coupled to said given client computing device:
determine whether at least one server packet from a plurality of server initialization packets is within the server mapping table;
replace the at least one server packet with at least one server mapping ID number to define a plurality of compressed server initialization packets; and
send the plurality of compressed server initialization packets to said gateway device.

4. The computing system of claim 3 wherein said server and said gateway device are configured to, when said at least one local device is decoupled from said given client computing device, perform the determining, the replacing, and the sending.

5. The computing system of claim 1 wherein the plurality of known server packets and the plurality of known client packets each comprises a communication standard initialization packet.

6. The computing system of claim 1 wherein the plurality of known server packets and the plurality of known client packets each comprises at least one of a smart card initialization sequence packet, smart card authentication packet, smart card digital signing packet, and smart card certificate transmission packet.

7. The computing system of claim 1 wherein the server mapping table and the client mapping table each comprises a plurality of local device types associated

with the plurality of client mapping ID numbers and the plurality of server mapping ID numbers.

8. The computing system of claim 1 wherein when the plurality of compressed client initialization packets generates an error, said server and said gateway device are configured to initialize the at least one local device using the plurality of client initialization packets.

9. The computing system of claim 1 wherein said at least one local device comprises at least one of a universal serial bus (USB) device, a TWAIN device, and a smart card device.

10. The computing system of claim 1 wherein the determining is based upon at least one of client name, smart card reader name, smart card reader state, smart card type, smart card Answer to Reset (ATR) string, smart card ID, and smart card certificate hash.

11. A method for operating a gateway device in communication between a server and a plurality of client computing devices, the server to provide a corresponding plurality of virtual desktop instances for the plurality of client computing devices, at least one local device to be coupled to a given client computing device and to be operable in a given virtual desktop instance associated with the given client computing device, thereby generating a plurality of client initialization packets, the method comprising:

generating a client mapping table comprising a plurality of known client packets associated with the at least one local device, and a plurality of client mapping identification (ID) numbers respectively associated with the plurality of known client packets; and

when the at least one local device is coupled to the given client computing device,

determining whether at least one client packet from the plurality of client initialization packets is within the client mapping table, replacing the at least one client packet with at least one client mapping ID number to define a plurality of compressed client initialization packets, and sending the plurality of compressed client initialization packets to the server.

12. The method of claim 11 further comprising synchronizing a server mapping table and the client mapping table.

13. The method of claim 11 further comprising when the at least one local device is decoupled from the given client computing device, performing the determining, the replacing, and the sending.

14. The method of claim 11 wherein the plurality of known client packets each comprises a communication standard initialization packet.

15. The method of claim 11 wherein the plurality of known client packets each comprises at least one of a smart card initialization sequence packet, smart card authentication packet, smart card digital signing packet, and smart card certificate transmission packet.

16. The method of claim 11 wherein the client mapping table comprises a plurality of local device types associated with the plurality of client mapping ID numbers.

17. A method for operating a server in communication with a plurality of client computing devices via a gateway device, the server to provide a corresponding plurality of virtual desktop instances for the plurality of client computing devices, at least one local device to be coupled to a given client computing device and to be operable in

a given virtual desktop instance associated with the given client computing device, thereby generating a plurality of server initialization packets, the method comprising:

generating a server mapping table comprising a plurality of known server packets associated with the at least one local device, and a plurality of server mapping identification (ID) numbers respectively associated with the plurality of known server packets; and

when the at least one local device is coupled to the given client computing device,

determining whether at least one server packet from the plurality of server initialization packets is within the server mapping table,

replacing the at least one server packet with at least one server mapping ID number to define a plurality of compressed server initialization packets, and

sending the plurality of compressed server initialization packets to the gateway device.

18. The method of claim 17 further comprising synchronizing the server mapping table and a client mapping table.

19. The method of claim 17 further comprising when the at least one local device is decoupled from the given client computing device, performing the determining, the replacing, and the sending.

20. The method of claim 17 wherein the plurality of known server packets each comprises a communication standard initialization packet.

21. The method of claim 17 wherein the plurality of known server packets each comprises at least one of a smart card initialization sequence packet, smart card authentication packet, smart card digital signing packet, and smart card certificate transmission packet.

22. The method of claim 17 wherein the server mapping table comprises a plurality of local device types associated with the plurality of server mapping ID numbers.




FIG. 1




FIG. 2

201




FIG. 3A




FIG. 3B

940




FIG. 4A

960




FIG. 4B

980




FIG. 4C

905

IDENTIFIER	DEVICE	CLIENT SEQUENCE	SERVER SEQUENCE
D1	VID: 1234 PID: 5678 (WEBCAM)	CAPTURED REQUEST RESPONSE SEQUENCE.	CAPTURED REQUEST RESPONSE SEQUENCE.
D2	VID: 2345 BPID: 6789 (PEN)	CAPTURED REQUEST RESPONSE SEQUENCE.	CAPTURED REQUEST RESPONSE SEQUENCE.
D3	VID: 1111 PID: 2222 (SENSOR)	CAPTURED REQUEST RESPONSE SEQUENCE.	CAPTURED REQUEST RESPONSE SEQUENCE.
D4	VID: 4444 PID: 5555 (WACOM DEVICE)	CAPTURED REQUEST RESPONSE SEQUENCE.	CAPTURED REQUEST RESPONSE SEQUENCE.

FIG. 5




FIG. 6

910 ↘




FIG. 7

915




FIG. 8




FIG. 9A

917




FIG. 9B




FIG. 10A

925

TRANSACTION	F	SETUP	ADDR	ENDP	D	T	R	bREQUEST	wVALUE	wINDEX	wLENGTH	ACK	TIME
14	S	0x84	1	0	D->H	S	D	GET_DESCRIPTOR	CONFIGURATION TYPE	0x0000	255	0x48	999.750 μ S
TRANSACTION	F	IN	ADDR	ENDP	T	DATA	ACK	TIME					
15	S	0x96	1	0	1	09 02 19 00 01 01 00 80	0x48	999.750 μ S					

TRANSACTION	F	IN	ADDR	ENDP	T	DATA	ACK	TIME
16	S	0x96	1	0	0	32 09 24 00 00 01 55 00	0x48	999.750 μ S

TRANSACTION	F	IN	ADDR	ENDP	T	DATA	ACK	TIME
17	S	0x96	1	0	1	00 00 07 05 82 02 40 00	0x48	999.750 μ S

TRANSACTION	F	IN	ADDR	ENDP	T	DATA	ACK	TIME
18	S	0x96	1	0	0	00	0x48	1.999 ms

REQUEST FOR DEVICE QUALIFIER DESCRIPTOR

1st STRING DESCRIPTOR REQUEST (LANGUAGE IDs)

TRANSACTION	F	OUT	ADDR	ENDP	T	DATA	ACK	TIME
19	S	0x87	1	0	1		0x48	1.999 ms

TRANSACTION	F	SETUP	ADDR	ENDP	D	T	R	bREQUEST	wVALUE	wINDEX	wLENGTH	ACK	TIME
20	S	0x84	1	0	D->H	S	D	GET_DESCRIPTOR	DEVICE_QUALIFIER TYPE	0x0000	10	0x48	999.750 μ S

TRANSACTION	F	IN	ADDR	ENDP	STALL	TIME
21	S	0x96	1	0	0x78	2.000 ms

THIS IS A FULL SPEED ONLY DEVICE. AS RESULT. A STALL REQUEST ERROR IS ISSUED

TRANSACTION	F	SETUP	ADDR	ENDP	D	T	R	bREQUEST	wVALUE	wINDEX	wLENGTH	ACK	TIME
22	S	0x84	1	0	D->H	S	D	GET_DESCRIPTOR	STRING TYPE, LANGID CODES REQUESTED	LANGUAGE ID 0x0000	255	0x48	999.833 μ S

TRANSACTION	F	IN	ADDR	ENDP	T	DATA	ACK	TIME
23	S	0x96	1	0	1	04 03 09 04	0x48	1.999 ms

TRANSACTION	F	OUT	ADDR	ENDP	T	DATA	ACK	TIME
24	S	0x87	1	0	1		0x48	1.999 ms

TRANSACTION	F	SETUP	ADDR	ENDP	D	T	R	bREQUEST	wVALUE	wINDEX	wLENGTH	ACK	TIME
25	S	0x84	1	0	D->H	S	D	GET_DESCRIPTOR	STRING TYPE, INDEX 2	LANGUAGE ID 0x0409	255	0x48	999.750 μ S

TRANSACTION	F	IN	ADDR	ENDP	T	DATA	ACK	TIME
26	S	0x96	1	0	1	18 03 55 00 53 00 42 00	0x48	999.750 μ S

TRANSACTION	F	IN	ADDR	ENDP	T	DATA	ACK	TIME
27	S	0x96	1	0	0	20 00 15 00 79 00 51 00	0x48	999.750 μ S

TRANSACTION	F	IN	ADDR	ENDP	T	DATA	ACK	TIME
28	S	0x96	1	0	0	60 00 70 00 60 00 15 00	0x48	999.750 μ S

TRANSACTION	F	IN	ADDR	ENDP	T	DATA	ACK	TIME

FIG. 10B

930

RE-REQUEST OF DESCRIPTORS BY DRIVER

TRANSACTION	F	OUT	ADDR	ENDP	T	DATA	ACK	TIME					
30	S	0x87	1	0	1		0x48	1.999 ms					
TRANSACTION	F	SETUP	ADDR	ENDP	D	T	R	bREQUEST	wVALUE	wINDEX	wLENGTH	ACK	TIME
31	S	0x84	1	0	D->H	S	D	GET_DESCRIPTOR	STRING TYPE, LANGID CODES REQUESTED	LANGUAGE ID 0x0000	255	0x48	999.750 μ S
TRANSACTION	F	IN	ADDR	ENDP	T	DATA	ACK	TIME					
32	S	0x96	1	0	1	04 03 09 04	0x48	1.999 ms					
TRANSACTION	F	OUT	ADDR	ENDP	T	DATA	ACK	TIME					
33	S	0x87	1	0	1		0x48	1.999 ms					
TRANSACTION	F	SETUP	ADDR	ENDP	D	T	R	bREQUEST	wVALUE	wINDEX	wLENGTH	ACK	TIME
34	S	0x84	1	0	D->H	S	D	GET_DESCRIPTOR	STRING TYPE, INDEX 2	LANGUAGE ID 0x0409	255	0x48	999.750 μ S
TRANSACTION	F	IN	ADDR	ENDP	T	DATA	ACK	TIME					
35	S	0x96	1	0	1	18 03 55 00 53 50 42 00	0x48	999.833 μ S					
TRANSACTION	F	IN	ADDR	ENDP	T	DATA	ACK	TIME					
36	S	0x96	1	0	1	20 00 45 00 18 00 61 00	0x48	999.750 μ S					
TRANSACTION	F	IN	ADDR	ENDP	T	DATA	ACK	TIME					
37	S	0x96	1	0	1	60 00 70 00 60 00 69 00	0x48	999.750 μ S					
TRANSACTION	F	IN	ADDR	ENDP	T	DATA	ACK	TIME					
38	S	0x90	1	0	1		0x48	1.993 ms					
TRANSACTION	F	OUT	ADDR	ENDP	T	DATA	ACK	TIME					
39	S	0x87	1	0	1		0x48	29.993 ms					
TRANSACTION	F	SETUP	ADDR	ENDP	D	T	R	bREQUEST	wVALUE	wINDEX	wLENGTH	ACK	TIME
40	S	0x84	1	0	D->H	S	D	GET_DESCRIPTOR	DEVICE TYPE	0x0000	18	0x48	999.750 μ S
TRANSACTION	F	IN	ADDR	ENDP	T	DATA	ACK	TIME					
41	S	0x96	1	0	1	12 01 00 02 00 00 02 09	0x48	999.750 μ S					
TRANSACTION	F	IN	ADDR	ENDP	T	DATA	ACK	TIME					
42	S	0x96	1	0	0	34 04 34 12 00 00 01 02	0x48	999.750 μ S					
TRANSACTION	F	IN	ADDR	ENDP	T	DATA	ACK	TIME					
43	S	0x96	1	0	1	00 01	0x48	999.750 μ S					
TRANSACTION	F	OUT	ADDR	ENDP	T	DATA	ACK	TIME					
44	S	0x87	1	0	1		0x48	1.999 ms					
TRANSACTION	F	SETUP	ADDR	ENDP	D	T	R	bREQUEST	wVALUE	wINDEX	wLENGTH	ACK	TIME
45	S	0x84	1	0	D->H	S	D	GET_DESCRIPTOR	CONFIGURATION TYPE	0x0000	9	0x48	999.750 μ S
TRANSACTION	F	IN	ADDR	ENDP	T	DATA	ACK	TIME					
46	S	0x96	1	0	0	09 02 19 00 01 01 00 80	0x48	999.750 μ S					
TRANSACTION	F	IN	ADDR	ENDP	T	DATA	ACK	TIME					
47	S	0x96	1	0	1	12	0x48	999.833 μ S					
TRANSACTION	F	OUT	ADDR	ENDP	T	DATA	ACK	TIME					
48	S	0x87	1	0	1		0x48	1.999 ms					

FIG. 10C

935

RE-REQUEST OF DESCRIPTORS BY DRIVER (CONTINUED)

TRANSACTION	F	SETUP	ADDR	ENDP	D	T	R	bREQUEST	wVALUE	wINDEX	wLENGTH	ACK	TIME		
49	S	0x84	1	0	D->H	S	D	GET_DESCRIPTOR	CONFIGURATION TYPE	0x0000	25	0x48	999.833 μ s		
50	S	0x96	1	0	T			DATA				ACK	TIME		
					1	09	02	19	00	01	01	00	80	0x48	999.667 μ s
51	S	0x96	1	0	T			DATA				ACK	TIME		
					0	32	09	04	00	00	01	77	00	0x48	999.750 μ s
52	S	0x96	1	0	T			DATA				ACK	TIME		
					1	00	00	07	05	81	02	40	00	0x48	999.750 μ s
53	S	0x96	1	0	T			DATA				ACK	TIME		
					0	00						0x48	999.750 μ s		
54	S	0x87	1	0	T			DATA				ACK	TIME		
					1							0x48	1.999 ms		
RE-REQUEST FOR DEVICE STATUS															
55	S	0x84	1	0	D->H	S	D	GET_STATUS	0x0000	DEVICE STATUS REQUESTED	2	0x48	999.750 μ s		
56	S	0x98	1	0	T			DATA				ACK	TIME		
					1	00	00					0x48	999.750 μ s		
BIT 0 = SELF POWERED, BIT 1 = REMOTE WAKEUP. BOTH ARE SET TO ZERO SINCE DEVICE IS BUS POWERED AND REMOTE WAKEUP IS NOT SUPPORTED. BITS 15 THROUGH 2 ARE RESERVED AND SET AT ZERO															
57	S	0x87	1	0	T			DATA				ACK	TIME		
					1							0x48	1.999 ms		
CONFIGURATION IS SELECTED. CONFIGURATION 1															
58	S	0x84	1	0	D->H	S	D	SET_CONFIGURATION	NEW CONFIGURATION 1	0x0000	2	0x48	999.750 μ s		
59	S	0x96	1	0	T			DATA				ACK			
					1							0x48			

FIG. 10D

900




FIG. 11