



US 20190315151A1

(19) **United States**

(12) **Patent Application Publication**
Skinner et al.

(10) **Pub. No.: US 2019/0315151 A1**

(43) **Pub. Date: Oct. 17, 2019**

(54) **INK-BASED MARKING DEVICE HAVING A MULTI-COMPONENT NIB STRUCTURE**

(71) Applicant: **CRAYOLA LLC**, EASTON, PA (US)

(72) Inventors: **Craig Skinner**, Easton, PA (US);
Robert N. Amabile, Bangor, PA (US);
Scott Collins, Nazareth, PA (US); **Jake Towne**, Nazareth, PA (US)

(21) Appl. No.: **16/386,757**

(22) Filed: **Apr. 17, 2019**

Related U.S. Application Data


(60) Provisional application No. 62/658,699, filed on Apr. 17, 2018.




Publication Classification

(51) **Int. Cl.**
B43K 1/12 (2006.01)
B43K 1/00 (2006.01)
B43K 1/01 (2006.01)
(52) **U.S. Cl.**
CPC *B43K 1/12* (2013.01); *B43K 1/01* (2013.01); *B43K 1/006* (2013.01)

(57) **ABSTRACT**

Embodiments of the invention are directed to a multi-component nib structure and marking device for selectively generating primary marks and a secondary marks for lettering and shading. The marking device includes a multi-component nib structure, an ink source. The multi-component nib structure generally includes a first nib component, a second nib component, and optionally, a transfer component between the first nib component and the second nib component. In other aspects, the multi-component nib structure may allow lettering with different tones creating, for example, an ombre effect.








FIG. 1D.




FIG. 2.




FIG. 3.

FIG. 4A.




FIG. 4B.




FIG. 5.








FIG. 7.

FIG. 6.






FIG. 10A.




FIG. 10B.




FIG. 11A.




FIG. 11B.



FIG. 12.

INK-BASED MARKING DEVICE HAVING A MULTI-COMPONENT NIB STRUCTURE

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This Application having attorney docket No. 31046.295335, claims priority to U.S. Provisional Application No. 62/658,699 filed on Apr. 17, 2018, which is incorporated by reference in its entirety herein.

SUMMARY

[0002] Embodiments of the invention are defined by the claims below, not this summary. A high-level overview of various aspects of the invention disclosure introduces a selection of concepts that are further described below in the detailed description. This summary is not intended to identify key features or essential features of the claimed subject matter, nor is it intended to be used as an aid in isolation to determine the scope of the claimed subject matter.

[0003] In brief and at a high level, this disclosure describes, among other things, a system, method, and ink-based marking device. The ink-based marking device, in accordance with aspects herein, is configured to create markings with different shading (e.g., ombre style), or simultaneously create markings with both a primary lettering color and a secondary shading color. The ink-based marking device may comprise a multi-component nib structure. Each component of the multi-component nib structure may have a different density/porosity. Further, there may be different configurations for the multi-component nib structure.

DESCRIPTION OF THE DRAWINGS

[0004] Illustrative embodiments of the invention are described in detail below with reference to the attached drawing figures, wherein:

[0005] FIG. 1A is a perspective view of a first exemplary configuration of the multi-component nib structure in accordance with aspects of the invention;

[0006] FIG. 1B is a cut-out view of the first exemplary multi-component nib structure in accordance with aspects of the invention;

[0007] FIGS. 1C and 1D depict exemplary markings made with the first exemplary multi-component nib structure of FIGS. 1A and 1B in accordance with aspects of the invention;

[0008] FIG. 2 is a perspective view of a second exemplary configuration of the multi-component nib structure in accordance with aspects of the invention;

[0009] FIG. 3 is another perspective view of the second exemplary configuration of the multi-component nib structure in accordance with aspects of the invention;

[0010] FIG. 4A is a first perspective view of a third exemplary configuration of the multi-component nib structure in accordance with aspects of the invention;

[0011] FIG. 4B is a second perspective view of the third exemplary configuration of the multi-component nib structure in accordance with aspects of the invention;

[0012] FIG. 5 is a perspective view of a fourth exemplary configuration of the multi-component nib structure in accordance with aspects of the invention;

[0013] FIG. 6 is a cross-sectional view of the second multi-component nib structure of FIG. 3 along the line 6-6 in accordance with aspects of the invention;

[0014] FIG. 7 is a cross-sectional view of a fifth exemplary multi-component nib structure in accordance with aspects of the invention;

[0015] FIG. 8A is a cross-sectional view of a configuration of a sixth exemplary multi-component nib structure in accordance with aspects of the invention;

[0016] FIG. 8B is an exemplary marking made with the sixth exemplary multi-component nib structure of FIG. 8A in accordance with aspects of the invention;

[0017] FIG. 9A is a perspective view of a configuration of a seventh exemplary multi-component nib structure in accordance with aspects of the invention;

[0018] FIG. 9B is an exemplary marking made with the seventh exemplary multi-component nib structure in FIG. 9A in accordance with aspects of the invention;

[0019] FIG. 10A is a perspective view of a configuration of an eighth exemplary multi-component nib structure in accordance with aspects of the invention;

[0020] FIG. 10B is an exemplary marking made with the eighth exemplary multi-component nib structure in FIG. 10A in accordance with aspects of the invention;

[0021] FIG. 11A is a perspective view of a configuration of a ninth exemplary multi-component nib structure in accordance with aspects of the invention;

[0022] FIG. 11B is an exemplary marking made with the ninth exemplary multi-component nib structure in FIG. 11A in accordance with aspects of the invention; and

[0023] FIG. 12 is an exemplary marking made with a multi-component nib structure of, for example, FIGS. 2-6, 9, 10, or 11 in accordance with aspects of the invention.

DETAILED DESCRIPTION

[0024] The subject matter of embodiments of the invention is described with specificity herein to meet statutory requirements. But the description itself is not intended to necessarily limit the scope of claims. Rather, the claimed subject matter might be embodied in other ways to include different steps or combinations of steps similar to the ones described in this document, in conjunction with other present or future technologies. Terms should not be interpreted as implying any particular order among or between various steps herein disclosed unless and except when the order of individual steps is explicitly described.

[0025] In some aspects, the ink-based marking device may be configured to dispense gradient tones of markings from a common ink reservoir based on a first configuration for the multi-component nib structure. In other aspects, the ink-based marking device may be configured to make markings with a primary color and a secondary color, where the primary color may be used for lettering and the secondary color may be used for shading, or vice versa based on other configurations for the multi-component nib structure. Yet in other aspects, the ink-based marking device may be configured to make markings with at least a first color and a second color that may or may not be the in the same tonality.

[0026] In certain aspects, the multi-component nib structure may be configured as a unitary nib structure having different areas of different densities/porosities feeding from a single ink reservoir. In other aspects, the multi-component nib structure may be configured as multiple nibs having the same or different densities/porosities, being coupled

together, and feeding from separate ink reservoirs. Further, the marking device in accordance with aspects herein, may include ink flow properties that may direct ink from one or more reservoirs to one or more separate portions of the multi-component nib structure. For example, one or more ink sources, such as an ink-filled marker barrel or ink-loaded marker reservoir, may provide ink to only one component of the multi-component nib structure, while the other component of the multi-component nib structure is fed ink from a first component of the multi-component nib structure. In other aspects, a common ink source may provide ink to both primary and secondary nib components, either at the same time or sequentially by virtue of ink flow between the components of the multi-component nib structure.

[0027] In further aspects, the different areas/components of the multi-component nib structure may be separated by a non-permeable boundary that obstructs ink flow between the different areas/components of the multi-component nib structure. In other aspects, the different areas/components of the multi-component nib structure may be separated by a partially permeable boundary that permits a threshold amount of ink to flow from one area/component to another area/component of the multi-component nib structure. Depending on the specific configuration of the multi-component nib structure, different marking characteristics (i.e., primary and secondary colorant and/or shading) may be derived from a common ink reservoir or separate ink reservoirs. As such, lettering with the marking device may include both a primary lettering color and a secondary shading color depending on which portion of which multi-component nib structure is in contact with the writing surface. In other aspects, instead of a membrane, the multi-component nib structure may comprise a nib dividing component. The nib dividing component may be comprised of a chemical and/or physical boundary extending along at least a portion of the length of the multi-component nib structure to prevent or facilitate ink exchange between a particular nib portion and a marker barrel and/or ink reservoir. The nib dividing component may be a semipermeable barrier and/or a selectively permeable barrier that permits flow of ink from, for example, a first nib component to a second nib component, with the second nib component having a different porosity than the first nib component, to provide a primary marking and secondary shading device within the marking device. Since the dividing component may create a space between, for example, a first component and a second component of the multi-component nib structure, any marking output from the first component may also be spaced apart from any marking output from the second component of the multi-component nib structure.

[0028] Moving on to FIG. 1A, a perspective view 10 of a conical multi-component nib structure 100 is shown. The conical multi-component nib structure 100 comprises a shank portion 102, a conduction band 104, and a tip 108. The conical multi-component nib structure 100 may comprise an optional slit 106 that in some instances, may serve as a breather hole/tunnel, or as a fitting component that aids in the fitting of the conical multi-component nib structure 100 in a housing 114, which may comprise a lip 116 for coupling with the conduction band 104 of the multi-component nib structure 100, as shown in FIG. 1C. As shown in FIG. 1B, the conical multi-component nib structure 100 may be comprised of a first component 110 having a first density/porosity enveloped by a second component 112 having a

second density/porosity. The density/porosity of the first component 110 may be different than the second component 112 of the conical multi-component nib structure 100. In particular, the density of the first component 110 is higher than the density of the second component 112, or in other words, the porosity of the second component 112 is higher than the porosity of the first component 110. Thus, when the shank portion 102 is coupled to an ink reservoir (not shown), as will become more apparent with respect to FIGS. 3-5, the first component 110 is able to absorb more ink (i.e., an amount larger than) from the ink reservoir than the second component 112.

[0029] In the multi-component nib structure 100, as described with respect to FIG. 1B, the first component 110 is enveloped or enclosed by the second component 112, with the porosity of the second component 112 being higher than the porosity of the first component 110. FIG. 1C depicts an effect of pressure on the multi-component nib structure 100 when using a marking device equipped with the multi-component nib structure 100 in accordance with aspects herein. As shown in FIG. 1B, a volume occupied by the first component 110 is greater than a volume occupied by the second component 112 at least at the tip 108 since the second component 112 is a layer of material wrapped around a core formed by the first component 110. As such, when only light or no pressure is applied to the marking device, only the ink available to the second component 112 will be transferred to a writing surface. However, as pressure on the marking device is gradually increased by the user (the user pushes down on the marking device), ink absorbed into the second component 112 is able to be released in addition to ink absorbed into the first component 110. Therefore, as shown in FIG. 1C, depending on a gradual increase in pressure applied to the marking device, the mark 120 on made on the writing surface may gradually increase in the direction of the gradient 122 from a first side 134 toward a second side 136. As shown in FIG. 1C, on the first side 134 of the mark 120, light or no pressure is applied to the marking device so that there is minimal or low contact with the marking surface, thereby making a light mark on the first side 134. On the other hand, as also shown in FIG. 1C, when higher pressure is applied on the marking device, the contact with the writing surface is increased or maximized so that more ink is able to flow onto the writing surface and thus, a darker mark is made toward the second side 136.

[0030] FIG. 1D shows a mark 124 having an ombre effect created with the multi-component nib structure 100. When making the mark 124, a user may start by applying a high amount of pressure at portion 126 and gradually decrease the amount of pressure as the tip 108 of the multi-component nib structure 100 is moved in the direction of the arrow 128, resulting in a gradually lighter mark as in portion 130, gradually increase the amount of pressure back up as moving toward portion 132, and gradually decrease the amount of pressure back down as the tip 108 of the multi-component nib structure 100 is moved, resulting in a gradually lighter mark as in portion 133 of mark 124.

[0031] In FIG. 2, a perspective view 20 of a different conical multi-component nib structure 200, is shown. The conical multi-component nib structure 200, like the conical multi-component nib structure 100 comprises a shank portion 202, a conduction band 204, and a tip 206. The conical multi-component nib structure 200 is divided along a length 212 into a first component 208 having a first density/porosity

and a second component **210** having a second density/porosity, that are arranged in a side by side relationship. In this example, the conical multi-component nib structure **200** may provide, for example, different writing characteristics from the first component **208** and the second component **210**, respectively. As shown in the perspective view **30** of FIG. **3** the conical multi-component nib structure **200** may be coupled to an ink reservoir **300** by having at least a portion **306** of the shank portion **202** inserted inside the ink reservoir **300**. The ink reservoir **300** may be comprised of a first compartment **302** having a first ink color or shade and a second compartment **304** having a second ink color or shade (as shown), or the ink reservoir **300** may be comprised of one compartment having a single ink color (not shown). The conical multi-component nib structure **200** can be used to make multi-tonal markings based on the characteristics of the first component **208** and the second component **210**, including a primary lettering color with ink dispensed from, for example, the first compartment **302** and a secondary shading color with ink dispensed from the second compartment **304**. In one aspect, the primary lettering color and the secondary shading color may comprise a tonal difference, or in another aspect, the primary lettering color may be comprised of a first color and the secondary shading color may be comprised of a second color that is different from the first color. In the case of a single compartment ink reservoir, the difference in shade may be achieved by a difference in ink volume being dispensed from the first component **208** or the second component **210** of the multi-component nib structure **200**.

[0032] FIG. **4A** depicts a perspective view **40** of a flat tip multi-component nib structure **400** is shown. The flat tip multi-component nib structure **400**, like the conical multi-component nib structure **200** comprises a shank portion **402**, a conduction band **404**, and a tip **406**. The flat tip multi-component nib structure **400** is divided along a length **412** into a first component **408** having a first density/porosity and a second component **410** having a second density/porosity, that are arranged in a side by side relationship and directly adjacent to each other. In this example, the flat tip multi-component nib structure **400** may also provide, for example, two different writing characteristics from the first component **408** and the second component **410**, respectively. The flat tip multi-component nib structure **400** may be coupled to an ink reservoir **414** by having at least a portion **420** of the shank portion **402** inserted inside the ink reservoir **414**. The ink reservoir **414** may be comprised of a first compartment **416** having a first ink color or shade and a second compartment **418** having a second ink color or shade (as shown), or the ink reservoir **414** may be comprised of one compartment having a single ink color (not shown). The flat tip multi-component nib structure **400**, like the conical multi-component nib structure **200**, can also be used to make multi-tonal markings including a primary lettering color dispensed from, for example, the first compartment **416** and a secondary shading color dispensed from the second compartment **418**. In one aspect, the primary lettering color and the secondary shading color may comprise a tonal difference, or in another aspect, the primary lettering color may be comprised of a first color and the secondary shading color may be comprised of a second color that is different from the first color.

[0033] In accordance with other aspects, as shown in FIG. **4B**, the first component **408** and the second component **410**

of the flat tip multi-component nib structure **400** may be directly adjacent to each other at the tip **406** and gradually start separating through the conduction band **404** until they are completely separated in the shank portion **402** such that at least a portion **420a** may be coupled to and inserted to a first ink reservoir **422** and at least a portion **420b** may be coupled to and inserted to a separate second ink reservoir **424**. It is to be understood that, although this configuration is only shown with respect to the flat tip multi-component nib structure **400**, the conical multi-component nib structure **200**, and the angled tip multi-component nib structure **500** may also have the configuration shown in FIG. **4B**.

[0034] FIG. **5** depicts a perspective view **50** of an angled tip multi-component nib structure **500** is shown. The angled tip multi-component nib structure **500**, like the conical multi-component nib structure **200** and the flat tip multi-component nib structure **400** comprises a shank portion **502**, a conduction band **504**, and a tip **508**. The angled tip multi-component nib structure **500** is divided along a length **514** into a first component **510** having a first density/porosity and a second component **512** having a second density/porosity, that are arranged in a side by side relationship and directly adjacent to each other. In this example, the angled tip multi-component nib structure **500** may also provide, for example, two different writing characteristics from the first component **510** and the second component **512**, respectively. The angled tip multi-component nib structure **500** may be coupled to an ink reservoir **522** by having at least a portion **520** of the shank portion **502** inserted inside the ink reservoir **522**. The ink reservoir **522** may be comprised of a first compartment **516** having a first ink color or shade and a second compartment **518** having a second ink color or shade (as shown), or the ink reservoir **522** may be comprised of one compartment having a single ink color (not shown). The angled tip multi-component nib structure **500**, like the conical multi-component nib structure **200** and the flat tip multi-component nib structure **400**, can also be used to make multi-tonal markings including a primary lettering color dispensed from, for example, the first compartment **516** and a secondary shading color dispensed from the second compartment **518**. In one aspect, the primary lettering color and the secondary shading color may comprise a tonal difference, or in another aspect, the primary lettering color may be comprised of a first color and the secondary shading color may be comprised of a second color that is different from the first color. In the angled tip multi-component nib structure **500**, the tip portion **506a** may be shorter than the tip portion **506b** of the angled tip multi-component nib structure **500**, such that a length **524** measured on a first side of the angled tip multi-component nib structure **500** is shorter than a length **514** measured on a second side of the angled tip multi-component nib structure **500**.

[0035] Moving on to FIG. **6**, a cross-sectional view **60** of the conical multi-component nib structure **200** in FIG. **3** is shown. As described above, a first component of **208** of the multi-component nib structure **200** may be comprised of a first material having a first density/porosity, and the second component **210** of the multi-component nib structure **200** may be comprised of a second material having a second density/porosity. Thus in certain aspects, a first amount of ink may be permitted to travel from the ink reservoir **300** through the first component **208** starting from the shank portion **202** towards the tip **206** at a first flow rate, and a second amount of ink may be permitted to travel from the

ink reservoir **300** through the second component **210** starting from the shank portion **202** towards the tip **206** at a second flow rate. In other aspects, the multi-component nib structure **200** may comprise a physical barrier **600** comprised of an impermeable membrane/thin film, or a semipermeable membrane/thin film. As shown in FIG. 6, the physical barrier **600** may have a first surface **602** adjacent to the first component **208** and a second surface **604** adjacent to the second component **210**.

[0036] Further, as briefly described above, the ink reservoir **300** may be comprised of a single ink compartment containing one color (not shown), or multiple ink compartments such as, for example, the first compartment **302** and the second compartment **304**, as shown in FIG. 3, each of the first compartment **302** and the second compartment **304** having either different shades of an ink color, or different colors altogether. In either case, the physical barrier **600** when impermeable, may block ink from the first component **208** from flowing into the second component **210**. On the other hand, when the physical barrier **600** is semipermeable, some ink may be allowed to flow from the first component **208** to the second component **210**. As a result, a mark made with the multi-component nib structure **200** may include both the ink from the first compartment **302** and the ink from the second compartment **304**. In the case where the physical barrier **600** is impermeable, the mark may have a clear division between the ink from the first compartment **302** and the ink from the second compartment **304**. On the other hand, where the physical barrier **600** is semipermeable, the division between the ink from the first compartment **302** and the ink from the second compartment **304** may be fuzzy, or intermixed, such as in a tie dye. It is to be understood that the overall profile of the multi-compartment nib structure is inconsequential, or in other words, the overall profile may be rounded (as shown), slanted, ridged, pointed, angled, straight, offset at an angle, and the like.

[0037] Moving on to FIG. 7, a cross-sectional view **70** of a different configuration for the multi-component nib structure **700** having a first component **704** of a first material and a second component **706** of a second material, is shown. As shown, the multi-component nib structure **700**, like the multi-component nib structure **200**, may also have a physical barrier **702** located between a first component **704** and a second component **706**, with a surface **708** of the physical barrier **702** facing the first component **704** and a surface **710** of the physical barrier **702** facing the second component **706**. However, as shown in FIG. 7, the first component **704** or the second component **706** may have different volumes. For example, in the example shown in FIG. 7, the first component **704** may comprise a smaller volume than the second component **706**, or vice versa, which can be observed by the difference in surface areas depicted in the cross-sectional view **70**. In other words, the physical barrier **700** may be offset from a midline of the multi-component nib structure.

[0038] In further aspects, as shown in the cross-sectional view **80** of a multi-component nib structure **800** in FIG. 8A, the multi-component nib structure **800** may comprise a first component **802**, a second component **804**, and a third component **806**, where the second component **804** may be at an offset position within the third component **806**. As shown, rather than the physical barrier being a membrane or thin film as shown in FIGS. 6 and 7, for example, the second component **804** may have a thickness **812**, and may be

configured in a zig-zag configuration (as shown) or may be configured in a straight line, a curved line, or any other suitable configuration, depending on a ratio of first component **802** and third component **806** desired. In accordance with aspects herein, the first component **802** may have a first density/porosity and the third component **806** may have a third density/porosity, and the second component **804** may have an intermediate density/porosity that is between the first density/porosity and the third density/porosity. The second component **804** may serve as an overlap portion, thus when creating a marking **820** (shown in FIG. 8B) in the direction **814** that is orthogonal to a stacking direction **816** of the first component **802**, the second component **804**, and the third component **806**, the marking may have an ombre effect with a gradient **822** with the darkest portion **824** being formed by the first component **802** having the lowest density/highest porosity, followed by an intermediate portion **826** formed by the second component **804** having the intermediate density/porosity, and the lightest portion **828** formed by the third component **806** having the highest density/lowest porosity.

[0039] FIG. 9A depicts yet another exemplary multi-component nib structure **900** comprising a shank **902**, a conduction band **904**, and a tip portion **906**. As shown, the shank **902** may be continuous with only a first component **908** extending from the shank **902**, through the conduction band **904**, and through the tip portion **906**. The tip portion **906**, however, may be comprised of the first component **908** and a second component **910**. As discussed above with reference to FIGS. 6, 7, and 8, the multi-component nib structure **900** may also comprise a physical barrier **912** comprised of a semipermeable or permeable membrane/thin film. In accordance with aspects herein, the first component **908** may be comprised of a lower density material so that as the ink contained within an ink reservoir coupled to the shank **902** flows in the direction of the arrow **914** toward the tip portion **906**, some ink is allowed to flow in the direction of the arrow **916** into the second component **910** comprised of a higher density material. As such, as shown in FIG. 9B, a marking **920** formed with the multi-component nib structure **900** may comprise a darker portion **922** and a lighter portion **924**. Although the multi-component nib-structure **900** is depicted as having an angled tip, it is contemplated that the tip portion **906** may have any other profiles, such as, for example, rounded, slanted, ridged, pointed, straight, offset at an angle, and the like.

[0040] FIG. 10A depicts yet another exemplary multi-component nib structure **1000**. In the multi-component nib structure **1000**, the tip **1002** may have the first component **1008** spaced apart from the second component **1004** by spacer **1006** by a distance **1010**. It is contemplated that the spacer **1006** may be impermeable (i.e., non-porous) or permeable (i.e., porous) according to the desired effects for the multi-component nib structure **1000**. For example, if complete color or shade separation is desired, the spacer **1006** may be made to be impermeable from a solid plastic, rubber, or thermoplastic material, for example. On the other hand, if some color or shade mixing is desired, the spacer **1006** may be made permeable from a foam or fiber material that is able to serve as an ink transfer portion that facilitates a threshold quantity of ink to transfer from the first component **1008** to the second component **1004** and vice versa according to the particular density/porosity characteristics of the respective first component **1008** or the second compo-

ment **1004**. Therefore, each of the first component **1008** and the second component **1004** may comprise respective shank portions (not shown) coupled to their respective ink reservoirs or respective compartments of a single ink reservoir, as shown in FIGS. 3-5, or a single compartment ink reservoir (not shown). As well, if configured like the tip in FIG. 9A, only one of the first component **1008** or the second component **1004** may comprise a shank portion connected to an ink reservoir, and transfer ink to the other of the first component **1008** or the second component **1004** through the spacer **1006**. The spacer **1006** may comprise a width **1012** that determines the distance **1010** by which the first component **1008** and the second component **1004** are separated. This distance may be varied depending on the marking effect desired for the multi-component nib structure **1000**. For example, when both the first component **1008** and second component **1004** are simultaneously contacted with a writing surface, a marking **1020** may be formed having a first mark **1022** having a width **1028** and a second mark **1024** having a width **1030** spaced apart by a distance **1026**, as shown in FIG. 10B. The distance **1026** may substantially correspond to the distance **1010** by which the first component **1008** and the second component **1004** of the multi-component nib structure **1000** are separated, and the widths **1028** and **1030** of the first and second marks **1022** and **1024**, respectively, may substantially correspond to the width **1014** and **1016** of the first and second components **1008** and **1004**, respectively. By substantially in accordance with aspects herein, it is meant that the respective measurements of the respective compared widths and distances are at least $90\pm 0.5\%$ analogous, at least $92\pm 0.5\%$ analogous, $94\pm 0.5\%$ analogous, $96\pm 0.5\%$ analogous, or $98\pm 0.5\%$ analogous. Although the multi-component nib-structure **1000** is depicted as having an angled tip, it is contemplated that the tip of the multi-component nib structure **1000** may have any other profiles, such as, for example, rounded, slanted, ridged, pointed, straight, offset at an angle, and the like.

[0041] FIG. 11A depicts a multi-component nib structure **1100**. In the multi-component nib structure **1100**, the tip **1102** may have the first component **1108** spaced apart from the second component **1104** by spacer **1106**. Unlike the multi-component nib structure **1000**, however, the spacer **1106** may be configured to taper (i.e., become thinner) towards an end **1101** of the tip **1102** so that the distance **1110** between the first component **1108** and the second component **1104** becomes gradually smaller, thereby creating a more seamless end **1101** of the tip **1102** for contacting a writing surface. Like in the case for the multi-component nib structure **1000**, it is contemplated that the spacer **1106** may be impermeable (i.e., non-porous) or permeable (i.e., porous) according to the desired effects for the multi-component nib structure **1100**. For example, if complete color or shade separation is desired, the spacer **1106** may be made to be impermeable from a solid plastic, rubber, or thermoplastic material, for example. On the other hand, if some color or shade mixing is desired, the spacer **1106** may be made permeable from a foam or fiber material that is able to serve as an ink transfer portion that facilitates a threshold quantity of ink to transfer from the first component **1108** to the second component **1104** and vice versa according to the particular density/porosity characteristics of the respective first component **1108** or the second component **1104**. Therefore, each of the first component **1108** and the second component **1104** may comprise respective shank portions

(not shown) coupled to their respective ink reservoirs or respective compartments of a single ink reservoir, as shown in FIGS. 3-5, or a single compartment ink reservoir (not shown). As well, if configured like the tip in FIG. 9A, only one of the first component **1108** or the second component **1104** may comprise a shank portion connected to an ink reservoir, and transfer ink to the other of the first component **1108** or the second component **1104** through the spacer **1106**. The spacer **1106** may comprise a width **1112** that as mentioned above, gradually tapers so that a final width **1111** determines the distance **1110** by which the first component **1108** and the second component **1104** are separated by at the end **1101** of the tip **1102**. Of course, this distance may be varied depending on the marking effect desired for the multi-component nib structure **1100**. For example, when both the first component **1108** and second component **1104** are simultaneously contacted with a writing surface, a marking **1120** may be formed having a first mark **1122** having a width **1128** and a second mark **1124** having a width **1130** spaced apart by a distance **1126**, as shown in FIG. 11B. The distance **1126** may substantially correspond to the distance **1110** by which the first component **1108** and the second component **1104** of the multi-component nib structure **1100** are separated at the end **1101** of the tip **1102**, and the widths **1128** and **1130** of the first and second marks **1122** and **1124**, respectively, may substantially correspond to the width **1114** and **1116** of the first and second components **1108** and **1104**, respectively. Although the multi-component nib-structure **1100** is depicted as having an angled tip, it is contemplated that the tip of the multi-component nib structure **1100** may have any other profiles, such as, for example, rounded, slanted, ridged, pointed, straight, offset at an angle, and the like.

[0042] Although not shown, the components of the marking device include may include a housing and an optional cap for retaining at least the multi-component nib structure and the ink reservoir in a coupled configuration. For any of the multi-component nib structures discussed herein, it is contemplated that these may be held at different angles by a user of a marking device having any of the multi-component nib structures. The different angles of contact of the tip portion of the multi-component nib structures in accordance with aspects herein may create different effects on the ink markings released by the multi-component nib structures. For example, FIG. 12 depicts an exemplary artistic marking/lettering creation **1200** created by using a marking device having a multi-component nib structure in accordance with aspects herein. In the creation **1200**, the phrase **1210** "create WHAT YOU" may be generated with a marking device by holding/gripping the marking device at a first angle or first position where only the tip of one component of the multi-component nib structure is contacted with the writing surface. The user may manipulate or shift the orientation of the tip of the multi-component nib structure by rotating or changing his/her grip on the housing of the marking device. As such, when the writing device is gripped so that both the first component and the second component of the tip of the multi-component nib structure are in contact with the writing surface, the resulting markings may have a shaded effect with adjacent light and dark marks. For example, the line marks **1220** may be created by using downward strokes with a multi-component nib structure having an angled tip as shown, for example, in FIGS. 5, 9A, 10A, 11A, which cause both the first component and the second component to

contact the writing surface simultaneously. On the other hand, the word **1230** “love” may be formed by using upward strokes forcing the contact of only one of the first component or the second component having the primary shade or color ink, contact the writing surface to make the non-shaded marks, and continue on by using a downward stroke(s) to make the shaded marks by forcing simultaneous contact with the writing surface of both the first component and the second component of the multi-component nib structure in accordance with aspects herein.

[0043] The aspects described throughout this specification are intended in all respects to be illustrative rather than restrictive. Upon reading the present disclosure, alternative aspects will become apparent to ordinary skilled artisans that practice in areas relevant to the described aspects without departing from the scope of this disclosure. In addition, aspects of this technology are adapted to achieve certain features and possible advantages set forth throughout this disclosure, together with other advantages which are inherent. It will be understood that certain features and subcombinations are of utility and may be employed without reference to other features and subcombinations. This is contemplated by and is within the scope of the claims.

[0044] Since many different applications are available for the invention without departing from the scope thereof, it is to be understood that all matter herein set forth or shown in the accompanying drawings is to be interpreted as illustrative and not in a limiting sense.

1. A multi-component nib structure for a marking device for selectively generating marks on a receiving surface, wherein the marking device comprises:

an ink reservoir; and

a multi-component nib structure having a tip portion, a shank portion, a first component, and a second component,

wherein the first component is enveloped by the second component,

wherein the first component has a first porosity and wherein the second component has a second porosity.

2. The multi-component nib structure of claim **1**, wherein the second porosity of the second component is greater than the first porosity of the first component.

3. The multi-component nib structure of claim **1**, wherein a first density of the first component is higher than a second density of the second component.

3. (canceled)

4. The multi-component nib structure of claim **3**, wherein a first pressure exerted on the marking device causes the multi-component nib structure to release a first amount of ink, and wherein a second pressure exerted on the marking device causes the multi-component nib structure to release a second amount of ink.

5. The multi-component nib structure of claim **4**, wherein the second pressure is greater than the first pressure, and wherein the second amount of ink is greater than the first amount of ink.

6. The multi-component nib structure of claim **5**, wherein the first pressure causes an output of a first shade of ink that is lighter than an output of a second shade of ink caused by the second pressure.

7. The multi-component nib structure of claim **6**, wherein the first shade of ink and the second shade of ink create an ombre effect for the marks.

8. A marking device for creating multi-tonal lettering marks on a surface, the marking device comprising:

an ink reservoir;

a multi-component nib structure having a tip portion, a shank portion, a first component, and a second component, wherein the first component comprises a first ink transfer property and wherein the second component comprises a second ink transfer property; and

a nib boundary between the first component and the second component, wherein the nib boundary is configured to control a flow of ink between the first component and the second component.

9. The marking device of claim **8**, wherein the ink reservoir comprises a first ink compartment and a second ink compartment.

10. The marking device of claim **9**, wherein the first ink compartment comprises a first ink having a first ink color, and wherein the second ink compartment comprises a second ink having a second ink color.

11. The marking device of claim **8**, wherein the first component has a first porosity and wherein the second component has a second porosity.

12. The marking device of claim **11**, wherein the second porosity of the second component is greater than the first porosity of the first component.

13. The marking device of claim **8**, wherein a first density of the first component is higher than a second density of the second component.

14. The marking device of claim **8**, wherein a first density of the first component is equal to a second density of the second component.

15. A marking device for creating shadowed lettering, the marking device comprising:

an ink reservoir;

a multi-component nib structure coupled to the ink reservoir having a first component directly adjacent to a second component with a boundary component located between the first component and the second component; and

a housing for enclosing at least a portion of the multi-component nib structure and the ink reservoir.

16. The marking device of claim **15**, wherein the first component provides a primary marking and the second component provides a shading marking when the multi-component nib structure is in contact with a writing surface.

17. The marking device of claim **15**, wherein the first component has a first porosity and wherein the second component has a second porosity.

18. The marking device of claim **17**, wherein the second porosity of the second component is greater than the first porosity of the first component.

19. The marking device of claim **15**, wherein a first density of the first component is higher than a second density of the second component.

20. The marking device of claim **12**, wherein the first component of the multi-component nib structure comprises a first tip portion and a shank portion, wherein the shank portion of the first component is coupled to the ink reservoir, and wherein the second component comprises a second tip portion coupled to the first tip portion of the first component.