



US009125662B2

(12) **United States Patent**  
**Shelton, IV**

(10) **Patent No.:** **US 9,125,662 B2**  
(45) **Date of Patent:** **Sep. 8, 2015**

(54) **MULTI-AXIS ARTICULATING AND ROTATING SURGICAL TOOLS**

(56) **References Cited**

(75) Inventor: **Frederick E. Shelton, IV**, Hillsboro, OH (US)

(73) Assignee: **Ethicon Endo-Surgery, Inc.**, Cincinnati, OH (US)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 493 days.

(21) Appl. No.: **13/536,362**

(22) Filed: **Jun. 28, 2012**

(65) **Prior Publication Data**

US 2014/0005662 A1 Jan. 2, 2014

(51) **Int. Cl.**

**A61B 18/14** (2006.01)  
**A61B 19/00** (2006.01)  
**A61B 17/29** (2006.01)  
**A61B 17/00** (2006.01)

(52) **U.S. Cl.**

CPC ..... **A61B 18/1445** (2013.01); **A61B 19/2203** (2013.01); **A61B 2017/003** (2013.01); **A61B 2017/00309** (2013.01); **A61B 2017/00314** (2013.01); **A61B 2017/00327** (2013.01); **A61B 2017/00477** (2013.01); **A61B 2017/2903** (2013.01); **A61B 2017/2927** (2013.01); **A61B 2018/1455** (2013.01); **A61B 2019/2223** (2013.01); **A61B 2019/2238** (2013.01)

(58) **Field of Classification Search**

CPC ..... **A61B 18/1445**; **A61B 2018/1455**; **A61B 2017/2927**; **A61B 19/2203**

USPC ..... **606/41**, 48–50  
See application file for complete search history.

U.S. PATENT DOCUMENTS

66,052 A 6/1867 Smith  
662,587 A 11/1900 Blake  
670,748 A 3/1901 Weddeler  
951,393 A 3/1910 Hahn  
1,306,107 A 6/1919 Elliott  
1,314,601 A 9/1919 McCaskey  
1,677,337 A 7/1928 Grove  
2,037,727 A 4/1936 La Chapelle

(Continued)

FOREIGN PATENT DOCUMENTS

AU 2008207624 A1 3/2009  
AU 2010214687 A1 9/2010

(Continued)

OTHER PUBLICATIONS

U.S. Appl. No. 14/521,748, filed Oct. 23, 2014.  
U.S. Appl. No. 14/559,172, filed Dec. 3, 2014.  
U.S. Appl. No. 14/559,188, filed Dec. 3, 2014.  
U.S. Appl. No. 14/559,224, filed Dec. 3, 2014.  
U.S. Appl. No. 14/559,251, filed Dec. 3, 2014.  
International Search Report for PCT/US2013/046782, dated Feb. 7, 2014 (7 pages).

(Continued)


Primary Examiner — Catherine Voorhees

(57)

**ABSTRACT**

Surgical end effectors are disclosed having an end effector and a shaft assembly coupled proximal to the end effector. The end effector has a first jaw member, a second jaw member, and a closure mechanism configured to move the first jaw member relative to the second jaw member. The shaft assembly has an articulation joint and/or a head rotation joint. The articulation joint is configured to independently articulate the end effector in a vertical direction and a horizontal direction. The head rotation joint is configured to independently rotate the end effector. The surgical instrument also has at least one active electrode disposed on at least one of the first jaw member and the second jaw member, and is configured to deliver RF energy to tissue located between the first jaw member and the second jaw member when in the closed position.

**18 Claims, 128 Drawing Sheets**



(56)

## References Cited

## U.S. PATENT DOCUMENTS

2,132,295 A	10/1938	Hawkins	4,349,028 A	9/1982	Green
2,161,632 A	6/1939	Nattenheimer	4,353,371 A	10/1982	Cosman
2,211,117 A	8/1940	Hess	4,379,457 A	4/1983	Gravener et al.
2,214,870 A	9/1940	West	4,380,312 A	4/1983	Landrus
2,441,096 A	5/1948	Happe	4,382,326 A	5/1983	Rabuse
2,526,902 A	10/1950	Rublee	4,383,634 A	5/1983	Green
2,674,149 A	4/1954	Benson	4,393,728 A	7/1983	Larson et al.
2,804,848 A	9/1957	O'Farrell et al.	4,396,139 A	8/1983	Hall et al.
2,808,482 A	10/1957	Zanichkowsky et al.	4,397,311 A	8/1983	Kanshin et al.
2,853,074 A	9/1958	Olson	4,402,445 A	9/1983	Green
2,959,974 A	11/1960	Emrick	4,408,692 A	10/1983	Sigel et al.
3,032,769 A	5/1962	Palmer	4,409,057 A	10/1983	Molenda et al.
3,075,062 A	1/1963	Iaccarino	4,415,112 A	11/1983	Green
3,078,465 A	2/1963	Bobrov	4,416,276 A	11/1983	Newton et al.
3,079,606 A	3/1963	Bobrov et al.	4,428,376 A	1/1984	Mericle
3,166,072 A	1/1965	Sullivan, Jr.	4,429,695 A	2/1984	Green
3,196,869 A	7/1965	Scholl	4,434,796 A	3/1984	Karapetian et al.
3,266,494 A	8/1966	Brownrigg et al.	4,438,659 A	3/1984	Desplats
3,269,630 A	8/1966	Fleischer	4,442,964 A	4/1984	Becht
3,275,211 A	9/1966	Hirsch et al.	4,451,743 A	5/1984	Suzuki et al.
3,317,103 A	5/1967	Cullen et al.	4,454,887 A	6/1984	Kruger
3,317,105 A	5/1967	Astafjev et al.	4,467,805 A	8/1984	Fukuda
3,357,296 A	12/1967	Lefever	4,473,077 A	9/1984	Noiles et al.
3,490,675 A	1/1970	Green et al.	4,475,679 A	10/1984	Fleury, Jr.
3,494,533 A	2/1970	Green et al.	4,485,816 A	12/1984	Krumme
3,499,591 A	3/1970	Green	4,486,928 A	12/1984	Tucker et al.
3,551,987 A	1/1971	Wilkinson	4,488,523 A	12/1984	Shichman
3,572,159 A	3/1971	Tschanz	4,489,875 A	12/1984	Crawford et al.
3,598,943 A	8/1971	Barrett	4,500,024 A	2/1985	DiGiovanni et al.
3,643,851 A	2/1972	Green et al.	4,505,272 A	3/1985	Utyamyshev et al.
3,662,939 A	5/1972	Bryan	4,505,273 A	3/1985	Braun et al.
3,717,294 A	2/1973	Green	4,505,414 A	3/1985	Filipi
3,734,207 A	5/1973	Fishbein	4,506,671 A	3/1985	Green
3,740,994 A	6/1973	DeCarlo, Jr.	4,520,817 A	6/1985	Green
3,744,495 A	7/1973	Johnson	4,522,327 A	6/1985	Korthoff et al.
3,746,002 A	7/1973	Haller	4,526,174 A	7/1985	Froehlich
3,751,902 A	8/1973	Kingsbury et al.	4,527,724 A	7/1985	Chow et al.
3,819,100 A	6/1974	Noiles et al.	4,530,453 A	7/1985	Green
3,821,919 A	7/1974	Knohl	4,531,522 A	7/1985	Bedi et al.
3,841,474 A	10/1974	Maier	4,532,927 A	8/1985	Miksza, Jr.
3,851,196 A	11/1974	Hinds	4,548,202 A	10/1985	Duncan
3,885,491 A	5/1975	Curtis	4,565,109 A	1/1986	Tsay
3,892,228 A	7/1975	Mitsui	4,565,189 A	1/1986	Mabuchi
3,894,174 A	7/1975	Cartun	4,566,620 A	1/1986	Green et al.
3,940,844 A	3/1976	Colby et al.	4,571,213 A	2/1986	Ishimoto
3,955,581 A	5/1976	Spasiano et al.	4,573,468 A	3/1986	Conta et al.
RE28,932 E	8/1976	Noiles et al.	4,573,469 A	3/1986	Golden et al.
3,981,051 A	9/1976	Brumlik	4,573,622 A	3/1986	Green et al.
4,054,108 A	10/1977	Gill	4,576,167 A	3/1986	Noiles et al.
4,060,089 A	11/1977	Noiles	4,580,712 A	4/1986	Green
4,106,446 A	8/1978	Yamada et al.	4,585,153 A	4/1986	Failla et al.
4,111,206 A	9/1978	Vishnevsky et al.	4,589,416 A	5/1986	Green
4,129,059 A	12/1978	Van Eck	4,591,085 A	5/1986	Di Giovanni
4,169,990 A	10/1979	Lerdman	4,600,037 A	7/1986	Hatten
4,198,734 A	4/1980	Brumlik	4,604,786 A	8/1986	Howie, Jr.
4,198,982 A	4/1980	Fortner et al.	4,605,001 A	8/1986	Rothfuss et al.
4,207,898 A	6/1980	Becht	4,605,004 A	8/1986	Di Giovanni et al.
4,213,562 A	7/1980	Garrett et al.	4,606,343 A	8/1986	Conta et al.
4,226,242 A	10/1980	Jarvik	4,607,638 A	8/1986	Crainich
4,244,372 A	1/1981	Kapitanov et al.	4,608,981 A	9/1986	Rothfuss et al.
4,250,436 A	2/1981	Weissman	4,610,250 A	9/1986	Green
4,261,244 A	4/1981	Becht et al.	4,610,383 A	9/1986	Rothfuss et al.
4,272,002 A	6/1981	Moshofsky	4,619,262 A	10/1986	Taylor
4,272,662 A	6/1981	Simpson	4,619,391 A	10/1986	Sharkany et al.
4,274,304 A	6/1981	Curtiss	4,629,107 A	12/1986	Fedotov et al.
4,275,813 A	6/1981	Noiles	4,632,290 A	12/1986	Green et al.
4,289,133 A	9/1981	Rothfuss	4,633,874 A	1/1987	Chow et al.
4,305,539 A	12/1981	Korolkov et al.	4,634,419 A	1/1987	Kreizman et al.
4,312,685 A	1/1982	Riedl	4,641,076 A	2/1987	Linden
4,317,451 A	3/1982	Cerwin et al.	4,646,722 A	3/1987	Silverstein et al.
4,321,002 A	3/1982	Froehlich	4,655,222 A	4/1987	Florez et al.
4,328,839 A	5/1982	Lyons et al.	4,662,555 A	5/1987	Thornton
4,331,277 A	5/1982	Green	4,663,874 A	5/1987	Sano et al.
4,340,331 A	7/1982	Savino	4,664,305 A	5/1987	Blake, III et al.
4,347,450 A	8/1982	Colligan	4,665,916 A	5/1987	Green
			4,667,674 A	5/1987	Korthoff et al.
			4,669,647 A	6/1987	Storace
			4,671,445 A	6/1987	Barker et al.
			4,676,245 A	6/1987	Fukuda

(56)

## References Cited

## U.S. PATENT DOCUMENTS

4,684,051 A	8/1987	Akopov et al.	5,080,556 A	1/1992	Carreno
4,693,248 A	9/1987	Failla	5,083,695 A	1/1992	Foslien et al.
4,700,703 A	10/1987	Resnick et al.	5,084,057 A	1/1992	Green et al.
4,708,141 A	11/1987	Inoue et al.	5,088,979 A	2/1992	Filipi et al.
4,709,120 A	11/1987	Pearson	5,088,997 A	2/1992	Delahueriga et al.
4,715,520 A	12/1987	Roehr, Jr. et al.	5,094,247 A	3/1992	Hernandez et al.
4,719,917 A	1/1988	Barrows et al.	5,100,420 A	3/1992	Green et al.
4,727,308 A	2/1988	Huljak et al.	5,104,025 A	4/1992	Main et al.
4,728,020 A	3/1988	Green et al.	5,104,397 A	4/1992	Vasconcelos et al.
4,728,876 A	3/1988	Mongeon et al.	5,106,008 A	4/1992	Tompkins et al.
4,729,260 A	3/1988	Dudden	5,111,987 A	5/1992	Moeinzadeh et al.
4,730,726 A	3/1988	Holzwarth	5,116,349 A	5/1992	Aranyi
4,741,336 A	5/1988	Failla et al.	5,122,156 A	6/1992	Granger et al.
4,743,214 A	5/1988	Tai-Cheng	5,129,570 A	7/1992	Schulze et al.
4,747,820 A	5/1988	Hornlein et al.	5,137,198 A	8/1992	Nobis et al.
4,750,902 A	6/1988	Wuchinich et al.	5,139,513 A	8/1992	Segato
4,752,024 A	6/1988	Green et al.	5,141,144 A	8/1992	Foslien et al.
4,754,909 A	7/1988	Barker et al.	5,142,932 A	9/1992	Moya et al.
4,767,044 A	8/1988	Green	5,155,941 A	10/1992	Takahashi et al.
4,773,420 A	9/1988	Green	5,156,315 A	10/1992	Green et al.
4,777,780 A	10/1988	Holzwarth	5,156,609 A	10/1992	Nakao et al.
4,787,387 A	11/1988	Burbank, III et al.	5,156,614 A	10/1992	Green et al.
4,790,225 A	12/1988	Moody et al.	5,158,567 A	10/1992	Green
4,805,617 A	2/1989	Bedi et al.	D330,699 S	11/1992	Gill
4,805,823 A	2/1989	Rothfuss	5,163,598 A	11/1992	Peters et al.
4,809,695 A	3/1989	Gwathmey et al.	5,171,247 A	12/1992	Hughett et al.
4,817,847 A	4/1989	Redtenbacher et al.	5,171,249 A	12/1992	Stefanchik et al.
4,819,853 A	4/1989	Green	5,171,253 A	12/1992	Klieman
4,821,939 A	4/1989	Green	5,188,111 A	2/1993	Yates et al.
4,827,911 A	5/1989	Broadwin et al.	5,190,517 A	3/1993	Zieve et al.
4,834,720 A	5/1989	Blinkhorn	5,192,288 A	3/1993	Thompson et al.
4,844,068 A	7/1989	Arata et al.	5,195,968 A	3/1993	Lundquist et al.
4,848,637 A	7/1989	Pruitt	5,197,648 A	3/1993	Gingold
4,865,030 A	9/1989	Polyak	5,197,649 A	3/1993	Bessler et al.
4,869,414 A	9/1989	Green et al.	5,200,280 A	4/1993	Karasa
4,869,415 A	9/1989	Fox	5,205,459 A	4/1993	Brinkerhoff et al.
4,873,977 A	10/1989	Avant et al.	5,207,697 A	5/1993	Carusillo et al.
4,880,015 A	11/1989	Nierman	5,209,747 A	5/1993	Knoepfler
4,890,613 A	1/1990	Golden et al.	5,211,649 A	5/1993	Kohler et al.
4,892,244 A	1/1990	Fox et al.	5,211,655 A	5/1993	Hasson
4,893,622 A	1/1990	Green et al.	5,217,457 A	6/1993	Delahueriga et al.
4,896,678 A	1/1990	Ogawa	5,217,478 A	6/1993	Rexroth
4,903,697 A	2/1990	Resnick et al.	5,219,111 A	6/1993	Bilotti et al.
4,915,100 A	4/1990	Green	5,221,036 A	6/1993	Takase
4,930,503 A	6/1990	Pruitt	5,221,281 A	6/1993	Klicek
4,930,674 A	6/1990	Barak	5,222,963 A	6/1993	Brinkerhoff et al.
4,931,047 A	6/1990	Broadwin et al.	5,222,975 A	6/1993	Crainich
4,932,960 A	6/1990	Green et al.	5,222,976 A	6/1993	Yoon
4,938,408 A	7/1990	Bedi et al.	5,223,675 A	6/1993	Taft
4,941,623 A	7/1990	Pruitt	5,234,447 A	8/1993	Kaster et al.
4,944,443 A	7/1990	Odds et al.	5,236,440 A	8/1993	Hlavacek
4,955,959 A	9/1990	Tompkins et al.	5,239,981 A	8/1993	Anaplotis
4,965,709 A	10/1990	Ngo	5,240,163 A	8/1993	Stein et al.
4,973,274 A	11/1990	Hirukawa	5,242,457 A	9/1993	Akopov et al.
4,978,049 A	12/1990	Green	5,244,462 A	9/1993	Delahueriga et al.
4,978,333 A	12/1990	Broadwin et al.	5,246,156 A	9/1993	Rothfuss et al.
4,986,808 A	1/1991	Broadwin et al.	5,246,443 A	9/1993	Mai
4,988,334 A	1/1991	Hornlein et al.	5,253,793 A	10/1993	Green et al.
5,002,543 A	3/1991	Bradshaw et al.	5,258,009 A	11/1993	Connors
5,002,553 A	3/1991	Shiber	5,258,012 A	11/1993	Luscombe et al.
5,009,661 A	4/1991	Michelson	5,259,366 A	11/1993	Reydel et al.
5,014,899 A	5/1991	Presty et al.	5,260,637 A	11/1993	Pizzi
5,015,227 A	5/1991	Broadwin et al.	5,263,629 A	11/1993	Trumbull et al.
5,024,671 A	6/1991	Tu et al.	5,263,973 A	11/1993	Cook
5,027,834 A	7/1991	Pruitt	5,268,622 A	12/1993	Philipp
5,031,814 A	7/1991	Tompkins et al.	5,271,543 A	12/1993	Grant et al.
5,038,109 A	8/1991	Goble et al.	5,271,544 A	12/1993	Fox et al.
5,040,715 A	8/1991	Green et al.	RE34,519 E	1/1994	Fox et al.
5,042,707 A	8/1991	Taheri	5,275,323 A	1/1994	Schulze et al.
5,061,269 A	10/1991	Muller	5,275,608 A	1/1994	Forman et al.
5,062,563 A	11/1991	Green et al.	5,279,416 A	1/1994	Malec et al.
5,065,929 A	11/1991	Schulze et al.	5,281,216 A	1/1994	Klicek
5,071,052 A	12/1991	Rodak et al.	5,282,806 A	2/1994	Haber et al.
5,071,430 A	12/1991	de Salis et al.	5,282,829 A	2/1994	Hermes
5,074,454 A	12/1991	Peters	5,284,128 A	2/1994	Hart
			5,285,945 A	2/1994	Brinkerhoff et al.
			5,289,963 A	3/1994	McGarry et al.
			5,297,714 A	3/1994	Kramer
			5,304,204 A	4/1994	Bregen

(56)

## References Cited

## U.S. PATENT DOCUMENTS

5,307,976 A	5/1994	Olson et al.	5,413,267 A	5/1995	Solyntjes et al.
5,309,927 A	5/1994	Welch	5,413,268 A	5/1995	Green et al.
5,312,023 A	5/1994	Green et al.	5,413,272 A	5/1995	Green et al.
5,312,024 A	5/1994	Grant et al.	5,413,573 A	5/1995	Koivukangas
5,312,329 A	5/1994	Beaty et al.	5,415,334 A	5/1995	Williamson, IV et al.
5,314,424 A	5/1994	Nicholas	5,415,335 A	5/1995	Knodell, Jr.
5,314,445 A	5/1994	Heidmueller née Degwitz et al.	5,417,203 A	5/1995	Tovey et al.
5,318,221 A	6/1994	Green et al.	5,417,361 A	5/1995	Williamson, IV
5,330,487 A	7/1994	Thornton et al.	5,421,829 A	6/1995	Olichney et al.
5,330,502 A	7/1994	Hassler et al.	5,422,567 A	6/1995	Matsunaga
5,332,142 A	7/1994	Robinson et al.	5,423,471 A	6/1995	Mastri et al.
5,333,422 A	8/1994	Warren et al.	5,423,809 A	6/1995	Klicek
5,333,772 A	8/1994	Rothfuss et al.	5,425,745 A	6/1995	Green et al.
5,334,183 A	8/1994	Wuchinich	5,431,322 A	7/1995	Green et al.
5,336,232 A	8/1994	Green et al.	5,431,654 A	7/1995	Nic
5,339,799 A	8/1994	Kami et al.	5,431,668 A	7/1995	Burbank, III et al.
5,341,724 A	8/1994	Vatel	5,433,721 A	7/1995	Hooven et al.
5,341,810 A	8/1994	Dardel	5,437,681 A	8/1995	Meade et al.
5,342,381 A	8/1994	Tidemand	5,438,302 A	8/1995	Goble
5,342,395 A	8/1994	Jarrett et al.	5,439,155 A	8/1995	Viola
5,342,396 A	8/1994	Cook	5,439,156 A	8/1995	Grant et al.
5,344,060 A	9/1994	Gravener et al.	5,439,479 A	8/1995	Shichman et al.
5,346,504 A	9/1994	Ortiz et al.	5,441,191 A	8/1995	Linden
5,348,259 A	9/1994	Blanco et al.	5,441,193 A	8/1995	Gravener
5,350,388 A	9/1994	Epstein	5,441,483 A	8/1995	Avitall
5,350,391 A	9/1994	Iacovelli	5,441,494 A	8/1995	Ortiz
5,350,400 A	9/1994	Esposito et al.	5,445,155 A	8/1995	Sieben
5,352,229 A	10/1994	Goble et al.	5,445,304 A	8/1995	Plyley et al.
5,352,235 A	10/1994	Koros et al.	5,445,644 A	8/1995	Pietrafitta et al.
5,352,238 A	10/1994	Green et al.	5,447,417 A	9/1995	Kuhl et al.
5,354,303 A	10/1994	Spaeth et al.	5,447,513 A	9/1995	Davison et al.
5,356,006 A	10/1994	Alpern et al.	5,449,355 A	9/1995	Rhum et al.
5,358,506 A	10/1994	Green et al.	5,449,365 A	9/1995	Green et al.
5,358,510 A	10/1994	Luscombe et al.	5,449,370 A	9/1995	Vaitekunas
5,359,231 A	10/1994	Flowers et al.	5,452,836 A	9/1995	Huitema et al.
D352,780 S	11/1994	Glaeser et al.	5,452,837 A	9/1995	Williamson, IV et al.
5,360,428 A	11/1994	Hutchinson, Jr.	5,454,378 A	10/1995	Palmer et al.
5,364,001 A	11/1994	Bryan	5,454,827 A	10/1995	Aust et al.
5,364,003 A	11/1994	Williamson, IV	5,456,401 A	10/1995	Green et al.
5,366,133 A	11/1994	Geiste	5,458,579 A	10/1995	Chodorow et al.
5,366,134 A	11/1994	Green et al.	5,462,215 A	10/1995	Viola et al.
5,366,479 A	11/1994	McGarry et al.	5,464,013 A	11/1995	Lemelson
5,368,015 A	11/1994	Wilk	5,464,144 A	11/1995	Guy et al.
5,368,592 A	11/1994	Stern et al.	5,464,300 A	11/1995	Crainich
5,370,645 A	12/1994	Klicek et al.	5,465,894 A	11/1995	Clark et al.
5,372,596 A	12/1994	Klicek et al.	5,465,895 A	11/1995	Knodel et al.
5,372,602 A	12/1994	Burke	5,465,896 A	11/1995	Allen et al.
5,374,277 A	12/1994	Hassler	5,466,020 A	11/1995	Page et al.
5,376,095 A	12/1994	Ortiz	5,467,911 A	11/1995	Tsuruta et al.
5,379,933 A	1/1995	Green et al.	5,468,253 A	11/1995	Bezwada et al.
5,381,782 A	1/1995	DeLaRama et al.	5,470,006 A	11/1995	Rodak
5,382,247 A	1/1995	Cimino et al.	5,470,007 A	11/1995	Plyley et al.
5,383,880 A	1/1995	Hooven	5,470,009 A	11/1995	Rodak
5,383,881 A	1/1995	Green et al.	5,470,010 A	11/1995	Rothfuss et al.
5,383,888 A	1/1995	Zvenyatsky et al.	5,472,132 A	12/1995	Savage et al.
5,383,895 A	1/1995	Holmes et al.	5,472,442 A	12/1995	Klicek
5,389,098 A	2/1995	Tsuruta et al.	5,473,204 A	12/1995	Temple
5,389,104 A	2/1995	Hahnen et al.	5,474,057 A	12/1995	Makower et al.
5,391,180 A	2/1995	Tovey et al.	5,474,566 A	12/1995	Alesi et al.
5,392,979 A	2/1995	Green et al.	5,476,206 A	12/1995	Green et al.
5,395,030 A	3/1995	Kuramoto et al.	5,476,479 A	12/1995	Green et al.
5,395,033 A	3/1995	Byrne et al.	5,478,003 A	12/1995	Green et al.
5,395,034 A	3/1995	Allen et al.	5,478,354 A	12/1995	Tovey et al.
5,395,312 A	3/1995	Desai	5,480,089 A	1/1996	Blewett
5,395,384 A	3/1995	Duthoit	5,480,409 A	1/1996	Riza
5,397,046 A	3/1995	Savage et al.	5,482,197 A	1/1996	Green et al.
5,397,324 A	3/1995	Carroll et al.	5,484,095 A	1/1996	Green et al.
5,403,312 A	4/1995	Yates et al.	5,484,398 A	1/1996	Stoddard
5,405,072 A	4/1995	Zlock et al.	5,484,451 A	1/1996	Akopov et al.
5,405,073 A	4/1995	Porter	5,485,947 A	1/1996	Olson et al.
5,405,344 A	4/1995	Williamson et al.	5,485,952 A	1/1996	Fontayne
5,405,360 A	4/1995	Tovey	5,487,499 A	1/1996	Sorrentino et al.
5,407,293 A	4/1995	Crainich	5,487,500 A	1/1996	Knodel et al.
5,409,498 A	4/1995	Braddock et al.	5,489,058 A	2/1996	Plyley et al.
5,411,508 A	5/1995	Bessler et al.	5,489,256 A	2/1996	Adair
			5,496,312 A	3/1996	Klicek
			5,496,317 A	3/1996	Goble et al.
			5,497,933 A	3/1996	DeFonzo et al.
			5,503,320 A	4/1996	Webster et al.

(56)

## References Cited

## U.S. PATENT DOCUMENTS

5,503,635 A	4/1996	Sauer et al.	5,591,170 A	1/1997	Spievack et al.
5,503,638 A	4/1996	Cooper et al.	5,591,187 A	1/1997	Dekel
5,505,363 A	4/1996	Green et al.	5,597,107 A	1/1997	Knodel et al.
5,507,426 A	4/1996	Young et al.	5,599,151 A	2/1997	Daum et al.
5,509,596 A	4/1996	Green et al.	5,599,344 A	2/1997	Paterson
5,509,916 A	4/1996	Taylor	5,599,350 A	2/1997	Schulze et al.
5,511,564 A	4/1996	Wilk	5,599,852 A	2/1997	Scopelianos et al.
5,514,129 A	5/1996	Smith	5,601,224 A	2/1997	Bishop et al.
5,514,157 A	5/1996	Nicholas et al.	5,603,443 A	2/1997	Clark et al.
5,518,163 A	5/1996	Hooven	5,605,272 A	2/1997	Witt et al.
5,518,164 A	5/1996	Hooven	5,605,273 A	2/1997	Hamblin et al.
5,520,678 A	5/1996	Heckele et al.	5,607,094 A	3/1997	Clark et al.
5,520,700 A	5/1996	Beyar et al.	5,607,095 A	3/1997	Smith et al.
5,522,817 A	6/1996	Sander et al.	5,607,433 A	3/1997	Polla et al.
5,527,320 A	6/1996	Carruthers et al.	5,607,450 A	3/1997	Zvenyatsky et al.
5,529,235 A	6/1996	Boiarski et al.	5,609,285 A	3/1997	Grant et al.
D372,086 S	7/1996	Grasso et al.	5,609,601 A	3/1997	Kolesa et al.
5,531,305 A	7/1996	Roberts et al.	5,611,709 A	3/1997	McAnulty
5,531,744 A	7/1996	Nardella et al.	5,613,966 A	3/1997	Makower et al.
5,533,521 A	7/1996	Granger	5,615,820 A	4/1997	Viola
5,533,581 A	7/1996	Barth et al.	5,618,294 A	4/1997	Aust et al.
5,533,661 A	7/1996	Main et al.	5,618,303 A	4/1997	Marlow et al.
5,535,934 A	7/1996	Boiarski et al.	5,618,307 A	4/1997	Donlon et al.
5,535,935 A	7/1996	Vidal et al.	5,619,992 A	4/1997	Guthrie et al.
5,535,937 A	7/1996	Boiarski et al.	5,620,289 A	4/1997	Curry
5,540,375 A	7/1996	Bolanos et al.	5,620,452 A	4/1997	Yoon
5,541,376 A	7/1996	Ladtkow et al.	5,624,452 A	4/1997	Yates
5,542,594 A	8/1996	McKean et al.	5,626,587 A	5/1997	Bishop et al.
5,542,949 A	8/1996	Yoon	5,626,595 A	5/1997	Sklar et al.
5,543,119 A	8/1996	Sutter et al.	5,628,446 A	5/1997	Geiste et al.
5,547,117 A	8/1996	Hamblin et al.	5,628,743 A	5/1997	Cimino
5,549,621 A	8/1996	Bessler et al.	5,628,745 A	5/1997	Bek
5,549,628 A	8/1996	Cooper et al.	5,630,539 A	5/1997	Plyley et al.
5,549,637 A	8/1996	Crainich	5,630,540 A	5/1997	Blewett
5,551,622 A	9/1996	Yoon	5,630,541 A	5/1997	Williamson, IV et al.
5,553,675 A	9/1996	Pitzen et al.	5,630,782 A	5/1997	Adair
5,553,765 A	9/1996	Knodel et al.	5,632,432 A	5/1997	Schulze et al.
5,554,148 A	9/1996	Aebischer et al.	5,632,433 A	5/1997	Grant et al.
5,554,169 A	9/1996	Green et al.	5,634,584 A	6/1997	Okorocho et al.
5,556,416 A	9/1996	Clark et al.	5,636,779 A	6/1997	Palmer
5,558,665 A	9/1996	Kieturakis	5,636,780 A	6/1997	Green et al.
5,558,671 A	9/1996	Yates	5,639,008 A	6/1997	Gallagher et al.
5,560,530 A	10/1996	Bolanos et al.	5,643,291 A	7/1997	Pier et al.
5,560,532 A	10/1996	DeFonzo et al.	5,645,209 A	7/1997	Green et al.
5,562,239 A	10/1996	Boiarski et al.	5,647,526 A	7/1997	Green et al.
5,562,241 A	10/1996	Knodel et al.	5,647,869 A	7/1997	Goble et al.
5,562,682 A	10/1996	Oberlin et al.	5,649,937 A	7/1997	Bito et al.
5,562,690 A	10/1996	Green et al.	5,651,491 A	7/1997	Heaton et al.
5,562,701 A	10/1996	Huitema et al.	5,653,373 A	8/1997	Green et al.
5,562,702 A	10/1996	Huitema et al.	5,653,374 A	8/1997	Young et al.
5,564,615 A	10/1996	Bishop et al.	5,653,677 A	8/1997	Okada et al.
5,569,161 A	10/1996	Ebling et al.	5,653,721 A	8/1997	Knodel et al.
5,569,270 A	10/1996	Weng	5,655,698 A	8/1997	Yoon
5,569,284 A	10/1996	Young et al.	5,657,921 A	8/1997	Young et al.
5,571,090 A	11/1996	Sherts	5,658,281 A	8/1997	Heard
5,571,100 A	11/1996	Goble et al.	5,658,300 A	8/1997	Bito et al.
5,571,116 A	11/1996	Bolanos et al.	5,658,307 A	8/1997	Exconde
5,571,285 A	11/1996	Chow et al.	5,662,258 A	9/1997	Knodel et al.
5,573,543 A	11/1996	Akopov et al.	5,662,260 A	9/1997	Yoon
5,574,431 A	11/1996	McKeown et al.	5,662,662 A	9/1997	Bishop et al.
5,575,054 A	11/1996	Klinzing et al.	5,665,085 A	9/1997	Nardella
5,575,789 A	11/1996	Bell et al.	5,667,517 A	9/1997	Hooven
5,575,799 A	11/1996	Bolanos et al.	5,667,526 A	9/1997	Levin
5,575,803 A	11/1996	Cooper et al.	5,667,527 A	9/1997	Cook
5,575,805 A	11/1996	Li	5,669,544 A	9/1997	Schulze et al.
5,577,654 A	11/1996	Bishop	5,669,904 A	9/1997	Platt, Jr. et al.
5,579,978 A	12/1996	Green et al.	5,669,907 A	9/1997	Platt, Jr. et al.
5,580,067 A	12/1996	Hamblin et al.	5,669,918 A	9/1997	Balazs et al.
5,582,611 A	12/1996	Tsuruta et al.	5,673,840 A	10/1997	Schulze et al.
5,582,617 A	12/1996	Klieman et al.	5,673,841 A	10/1997	Schulze et al.
5,584,425 A	12/1996	Savage et al.	5,673,842 A	10/1997	Bittner et al.
5,586,711 A	12/1996	Plyley et al.	5,674,286 A	10/1997	D'Alessio et al.
5,588,579 A	12/1996	Schnut et al.	5,678,748 A	10/1997	Plyley et al.
5,588,580 A	12/1996	Paul et al.	5,680,981 A	10/1997	Mililli et al.
5,588,581 A	12/1996	Conlon et al.	5,680,982 A	10/1997	Schulze et al.
			5,680,983 A	10/1997	Plyley et al.
			5,683,349 A	11/1997	Makower et al.
			5,685,474 A	11/1997	Seeber
			5,686,090 A	11/1997	Schilder et al.

(56)

## References Cited

## U.S. PATENT DOCUMENTS

5,688,270 A	11/1997	Yates et al.	5,782,859 A	7/1998	Nicholas et al.
5,690,269 A	11/1997	Bolanos et al.	5,784,934 A	7/1998	Izumisawa
5,692,668 A	12/1997	Schulze et al.	5,785,232 A	7/1998	Vidal et al.
5,693,020 A	12/1997	Rauh	5,785,647 A	7/1998	Tompkins et al.
5,693,042 A	12/1997	Boiarski et al.	5,787,897 A	8/1998	Kieturakis
5,693,051 A	12/1997	Schulze et al.	5,792,135 A	8/1998	Madhani et al.
5,695,494 A	12/1997	Becker	5,792,165 A	8/1998	Klieman et al.
5,695,502 A	12/1997	Pier et al.	5,794,834 A	8/1998	Hamblin et al.
5,695,504 A	12/1997	Gifford, III et al.	5,796,188 A	8/1998	Bays
5,695,524 A	12/1997	Kelley et al.	5,797,536 A	8/1998	Smith et al.
5,697,543 A	12/1997	Burdorff	5,797,537 A	8/1998	Oberlin et al.
5,697,943 A	12/1997	Sauer et al.	5,797,538 A	8/1998	Heaton et al.
5,700,270 A	12/1997	Peysen et al.	5,797,906 A	8/1998	Rhum et al.
5,702,387 A	12/1997	Arts et al.	5,797,959 A	8/1998	Castro et al.
5,702,408 A	12/1997	Wales et al.	5,799,857 A	9/1998	Robertson et al.
5,702,409 A	12/1997	Rayburn et al.	5,800,379 A	9/1998	Edwards
5,704,087 A	1/1998	Strub	5,806,676 A	9/1998	Wasgien
5,704,534 A	1/1998	Huitema et al.	5,807,376 A	9/1998	Viola et al.
5,706,997 A	1/1998	Green et al.	5,807,378 A	9/1998	Jensen et al.
5,706,998 A	1/1998	Plyley et al.	5,807,393 A	9/1998	Williamson, IV et al.
5,707,392 A	1/1998	Kortenbach	5,809,441 A	9/1998	McKee
5,709,334 A	1/1998	Sorrentino et al.	5,810,721 A	9/1998	Mueller et al.
5,709,680 A	1/1998	Yates et al.	5,810,811 A	9/1998	Yates et al.
5,709,706 A	1/1998	Kienzle et al.	5,810,846 A	9/1998	Virnich et al.
5,711,472 A	1/1998	Bryan	5,810,855 A	9/1998	Rayburn et al.
5,713,128 A	2/1998	Schrenk et al.	5,813,813 A	9/1998	Daum et al.
5,713,505 A	2/1998	Huitema	5,814,055 A	9/1998	Knodel et al.
5,713,895 A	2/1998	Lontine et al.	5,814,057 A	9/1998	Oi et al.
5,713,896 A	2/1998	Nardella	5,816,471 A	10/1998	Plyley et al.
5,713,920 A	2/1998	Bezswana et al.	5,817,084 A	10/1998	Jensen
5,715,987 A	2/1998	Kelley et al.	5,817,091 A	10/1998	Nardella et al.
5,715,988 A	2/1998	Palmer	5,817,093 A	10/1998	Williamson, IV et al.
5,716,366 A	2/1998	Yates	5,817,109 A	10/1998	McGarry et al.
5,718,359 A	2/1998	Palmer et al.	5,817,119 A	10/1998	Klieman et al.
5,718,360 A	2/1998	Green et al.	5,820,009 A	10/1998	Melling et al.
5,718,548 A	2/1998	Cotellessa	5,823,066 A	10/1998	Huitema et al.
5,720,744 A	2/1998	Eggleston et al.	5,826,776 A	10/1998	Schulze et al.
D393,067 S	3/1998	Geary et al.	5,827,271 A	10/1998	Buyse et al.
5,725,536 A	3/1998	Oberlin et al.	5,827,298 A	10/1998	Hart et al.
5,725,554 A	3/1998	Simon et al.	5,829,662 A	11/1998	Allen et al.
5,728,110 A	3/1998	Vidal et al.	5,833,690 A	11/1998	Yates et al.
5,728,121 A	3/1998	Bimbo et al.	5,833,695 A	11/1998	Yoon
5,730,758 A	3/1998	Allgeyer	5,833,696 A	11/1998	Whitfield et al.
5,732,821 A	3/1998	Stone et al.	5,836,503 A	11/1998	Ehrenfels et al.
5,732,871 A	3/1998	Clark et al.	5,836,960 A	11/1998	Kolesa et al.
5,732,872 A	3/1998	Bolduc et al.	5,839,639 A	11/1998	Sauer et al.
5,733,308 A	3/1998	Daugherty et al.	5,843,021 A	12/1998	Edwards et al.
5,735,445 A	4/1998	Vidal et al.	5,843,096 A	12/1998	Igaki et al.
5,735,848 A	4/1998	Yates et al.	5,843,122 A	12/1998	Riza
5,735,874 A	4/1998	Measamer et al.	5,843,132 A	12/1998	Ilvento
5,738,474 A	4/1998	Blewett	5,846,254 A	12/1998	Schulze et al.
5,738,648 A	4/1998	Lands et al.	5,849,011 A	12/1998	Jones et al.
5,743,456 A	4/1998	Jones et al.	5,855,311 A	1/1999	Hamblin et al.
5,747,953 A	5/1998	Philipp	5,855,583 A	1/1999	Wang et al.
5,749,889 A	5/1998	Bacich et al.	5,860,581 A	1/1999	Robertson et al.
5,749,893 A	5/1998	Vidal et al.	5,860,975 A	1/1999	Goble et al.
5,752,644 A	5/1998	Bolanos et al.	5,865,361 A	2/1999	Milliman et al.
5,752,965 A	5/1998	Francis et al.	5,868,760 A	2/1999	McGuckin, Jr.
5,755,717 A	5/1998	Yates et al.	5,871,135 A	2/1999	Williamson, IV et al.
5,758,814 A	6/1998	Gallagher et al.	5,873,885 A	2/1999	Weidenbenner
5,762,255 A	6/1998	Chrisman et al.	5,876,401 A	3/1999	Schulze et al.
5,762,256 A	6/1998	Mastri et al.	5,878,193 A	3/1999	Wang et al.
5,766,188 A	6/1998	Igaki	5,878,937 A	3/1999	Green et al.
5,766,205 A	6/1998	Zvenyatsky et al.	5,878,938 A	3/1999	Bittner et al.
5,769,892 A	6/1998	Kingwell	5,891,160 A	4/1999	Williamson, IV et al.
5,772,379 A	6/1998	Evensen	5,893,506 A	4/1999	Powell
5,772,578 A	6/1998	Heimberger et al.	5,893,835 A	4/1999	Witt et al.
5,772,659 A	6/1998	Becker et al.	5,894,979 A	4/1999	Powell
5,776,130 A	7/1998	Buyse et al.	5,897,552 A	4/1999	Edwards et al.
5,779,130 A	7/1998	Alesi et al.	5,897,562 A	4/1999	Bolanos et al.
5,779,131 A	7/1998	Knodel et al.	5,899,914 A	5/1999	Zirps et al.
5,779,132 A	7/1998	Knodel et al.	5,901,895 A	5/1999	Heaton et al.
5,782,396 A	7/1998	Mastri et al.	5,902,312 A	5/1999	Frater et al.
5,782,397 A	7/1998	Koukline	5,904,693 A	5/1999	Dicesare et al.
5,782,749 A	7/1998	Riza	5,906,625 A	5/1999	Bitto et al.
			5,908,402 A	6/1999	Blythe
			5,908,427 A	6/1999	McKean et al.
			5,911,353 A	6/1999	Bolanos et al.
			5,915,616 A	6/1999	Viola et al.

(56)

## References Cited

## U.S. PATENT DOCUMENTS

5,918,791 A	7/1999	Sorrentino et al.	6,117,148 A	9/2000	Ravo et al.
5,919,198 A	7/1999	Graves, Jr. et al.	6,117,158 A	9/2000	Measamer et al.
5,921,956 A	7/1999	Grinberg et al.	6,119,913 A	9/2000	Adams et al.
5,928,256 A	7/1999	Riza	6,120,433 A	9/2000	Mizuno et al.
5,931,847 A	8/1999	Bittner et al.	6,123,241 A	9/2000	Walter et al.
5,931,853 A	8/1999	McEwen et al.	H1904 H	10/2000	Yates et al.
5,937,951 A	8/1999	Izuchukwu et al.	6,126,058 A	10/2000	Adams et al.
5,938,667 A	8/1999	Peysen et al.	6,126,670 A	10/2000	Walker et al.
5,941,442 A	8/1999	Geiste et al.	6,131,789 A	10/2000	Schulze et al.
5,944,172 A	8/1999	Hannula	6,131,790 A	10/2000	Piraka
5,944,715 A	8/1999	Goble et al.	6,132,368 A	10/2000	Cooper
5,947,984 A	9/1999	Whipple	6,139,546 A	10/2000	Koenig et al.
5,948,030 A	9/1999	Miller et al.	6,149,660 A	11/2000	Laufer et al.
5,951,552 A	9/1999	Long et al.	6,152,935 A	11/2000	Kammerer et al.
5,951,574 A	9/1999	Stefanchik et al.	6,155,473 A	12/2000	Tompkins et al.
5,951,581 A	9/1999	Saadat et al.	6,156,056 A	12/2000	Kearns et al.
5,954,259 A	9/1999	Viola et al.	6,159,146 A	12/2000	El Gazayerli
5,964,774 A	10/1999	McKean et al.	6,159,200 A	12/2000	Verdura et al.
5,971,916 A	10/1999	Koren	6,162,208 A	12/2000	Hipps
5,984,949 A	11/1999	Levin	6,165,175 A	12/2000	Wampler et al.
5,988,479 A	11/1999	Palmer	6,165,184 A	12/2000	Verdura et al.
5,997,528 A	12/1999	Bisch et al.	6,165,188 A	12/2000	Saadat et al.
5,997,552 A	12/1999	Person et al.	6,168,605 B1	1/2001	Measamer et al.
6,003,517 A	12/1999	Sheffield et al.	6,171,316 B1	1/2001	Kovac et al.
6,004,319 A	12/1999	Goble et al.	6,171,330 B1	1/2001	Benchtrit
6,010,054 A	1/2000	Johnson et al.	6,174,308 B1	1/2001	Goble et al.
6,010,513 A	1/2000	Törmälä et al.	6,174,309 B1	1/2001	Wrublewski et al.
6,012,494 A	1/2000	Balazs	6,179,195 B1	1/2001	Adams et al.
6,013,076 A	1/2000	Goble et al.	6,179,776 B1	1/2001	Adams et al.
6,015,406 A	1/2000	Goble et al.	6,181,105 B1	1/2001	Cutolo et al.
6,017,322 A	1/2000	Snoke et al.	6,182,673 B1	2/2001	Kindermann et al.
6,017,356 A	1/2000	Frederick et al.	6,187,003 B1	2/2001	Buysse et al.
6,022,352 A	2/2000	Vandewalle	6,190,386 B1	2/2001	Rydell
6,024,741 A	2/2000	Williamson, IV et al.	6,193,129 B1	2/2001	Bittner et al.
6,024,748 A	2/2000	Manzo et al.	6,197,042 B1	3/2001	Ginn et al.
6,027,501 A	2/2000	Goble et al.	6,200,330 B1	3/2001	Benderev et al.
6,032,849 A	3/2000	Mastri et al.	6,202,914 B1	3/2001	Geiste et al.
6,033,378 A	3/2000	Lundquist et al.	6,206,897 B1	3/2001	Jamiolkowski et al.
6,033,399 A	3/2000	Gines	6,210,403 B1	4/2001	Klicek
6,033,427 A	3/2000	Lee	6,213,999 B1	4/2001	Platt, Jr. et al.
6,039,733 A	3/2000	Buysse et al.	6,214,028 B1	4/2001	Yoon et al.
6,039,734 A	3/2000	Goble	6,220,368 B1	4/2001	Ark et al.
6,042,601 A	3/2000	Smith	6,223,835 B1	5/2001	Habedank et al.
6,045,560 A	4/2000	McKean et al.	6,224,617 B1	5/2001	Saadat et al.
6,047,861 A	4/2000	Vidal et al.	6,228,081 B1	5/2001	Goble
6,050,472 A	4/2000	Shibata	6,228,083 B1	5/2001	Lands et al.
6,050,990 A	4/2000	Tankovich et al.	6,228,084 B1	5/2001	Kirwan, Jr.
6,050,996 A	4/2000	Schmaltz et al.	6,231,565 B1	5/2001	Tovey et al.
6,053,390 A	4/2000	Green et al.	6,234,178 B1	5/2001	Goble et al.
6,053,922 A	4/2000	Krause et al.	6,241,139 B1	6/2001	Milliman et al.
RE36,720 E	5/2000	Green et al.	6,241,140 B1	6/2001	Adams et al.
6,056,735 A	5/2000	Okada et al.	6,241,723 B1	6/2001	Heim et al.
6,056,746 A	5/2000	Goble et al.	6,248,117 B1	6/2001	Blatter
6,062,360 A	5/2000	Shields	6,249,076 B1	6/2001	Madden et al.
6,063,097 A	5/2000	Oi et al.	6,250,532 B1	6/2001	Green et al.
6,063,098 A	5/2000	Houser et al.	6,258,107 B1	7/2001	Balázs et al.
6,065,919 A	5/2000	Peck	6,261,286 B1	7/2001	Goble et al.
6,066,132 A	5/2000	Chen et al.	6,264,086 B1	7/2001	McGuckin, Jr.
6,068,627 A	5/2000	Orszulak et al.	6,264,087 B1	7/2001	Whitman
6,071,233 A	6/2000	Ishikawa et al.	6,270,508 B1	8/2001	Klieman et al.
6,074,386 A	6/2000	Goble et al.	6,273,876 B1	8/2001	Klima et al.
6,074,401 A	6/2000	Gardiner et al.	6,273,897 B1	8/2001	Dalessandro et al.
6,077,286 A	6/2000	Cuschieri et al.	6,277,114 B1	8/2001	Bullivant et al.
6,079,606 A	6/2000	Milliman et al.	6,293,942 B1	9/2001	Goble et al.
6,082,577 A	7/2000	Coates et al.	6,296,640 B1	10/2001	Wampler et al.
6,083,191 A	7/2000	Rose	6,302,311 B1	10/2001	Adams et al.
6,083,234 A	7/2000	Nicholas et al.	6,305,891 B1	10/2001	Burlingame
6,083,242 A	7/2000	Cook	6,306,134 B1	10/2001	Goble et al.
6,086,600 A	7/2000	Kortenbach	6,306,149 B1	10/2001	Meade
6,090,106 A	7/2000	Goble et al.	6,309,403 B1	10/2001	Minor et al.
6,093,186 A	7/2000	Goble	6,315,184 B1	11/2001	Whitman
6,099,537 A	8/2000	Sugai et al.	6,320,123 B1	11/2001	Reimers
6,099,551 A	8/2000	Gabbay	6,322,494 B1	11/2001	Bullivant et al.
6,102,271 A	8/2000	Longo et al.	6,324,339 B1	11/2001	Hudson et al.
6,109,500 A	8/2000	Alli et al.	6,325,799 B1	12/2001	Goble
			6,325,810 B1	12/2001	Hamilton et al.
			6,330,965 B1	12/2001	Milliman et al.
			6,331,181 B1	12/2001	Tierney et al.
			6,331,761 B1	12/2001	Kumar et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

6,333,029 B1	12/2001	Vyakarnam et al.	6,551,333 B2	4/2003	Kuhns et al.
6,334,860 B1	1/2002	Dorn	6,554,861 B2	4/2003	Knox et al.
6,334,861 B1	1/2002	Chandler et al.	6,558,379 B1	5/2003	Batchelor et al.
6,336,926 B1	1/2002	Goble	6,565,560 B1	5/2003	Goble et al.
6,338,737 B1	1/2002	Toledano	6,569,085 B2	5/2003	Kortenbach et al.
6,343,731 B1	2/2002	Adams et al.	6,569,171 B2	5/2003	DeGuillebon et al.
6,346,077 B1	2/2002	Taylor et al.	6,578,751 B2	6/2003	Hartwick
6,352,503 B1	3/2002	Matsui et al.	6,582,427 B1	6/2003	Goble et al.
6,352,532 B1	3/2002	Kramer et al.	6,583,533 B2	6/2003	Pelrine et al.
6,358,224 B1	3/2002	Tims et al.	6,585,144 B2	7/2003	Adams et al.
6,364,877 B1	4/2002	Goble et al.	6,588,643 B2	7/2003	Bolduc et al.
6,364,888 B1	4/2002	Niemeyer et al.	6,589,164 B1	7/2003	Flaherty
6,370,981 B2	4/2002	Watarai	6,592,538 B1	7/2003	Hotchkiss et al.
6,373,152 B1	4/2002	Wang et al.	6,592,597 B2	7/2003	Grant et al.
6,383,201 B1	5/2002	Dong	6,596,296 B1	7/2003	Nelson et al.
6,387,113 B1	5/2002	Hawkins et al.	6,596,304 B1	7/2003	Bayon et al.
6,387,114 B2	5/2002	Adams	6,596,432 B2	7/2003	Kawakami et al.
6,391,038 B2	5/2002	Vargas et al.	D478,665 S	8/2003	Isaacs et al.
6,398,781 B1	6/2002	Goble et al.	D478,986 S	8/2003	Johnston et al.
6,398,797 B2	6/2002	Bombard et al.	6,601,749 B2	8/2003	Sullivan et al.
6,402,766 B2	6/2002	Bowman et al.	6,602,252 B2	8/2003	Mollenaer
6,406,440 B1	6/2002	Stefanchik	6,602,262 B2	8/2003	Griego et al.
6,409,724 B1	6/2002	Penny et al.	6,605,078 B2	8/2003	Adams
H2037 H	7/2002	Yates et al.	6,605,669 B2	8/2003	Awokola et al.
6,413,274 B1	7/2002	Pedros	6,607,475 B2	8/2003	Doyle et al.
6,416,486 B1	7/2002	Wampler	6,616,686 B2	9/2003	Coleman et al.
6,416,509 B1	7/2002	Goble et al.	6,619,529 B2	9/2003	Green et al.
6,419,695 B1	7/2002	Gabbay	6,620,166 B1	9/2003	Wenstrom, Jr. et al.
RE37,814 E	8/2002	Allgeyer	6,626,834 B2	9/2003	Dunne et al.
6,428,070 B1	8/2002	Takanashi et al.	6,629,630 B2	10/2003	Adams
6,429,611 B1	8/2002	Li	6,629,974 B2	10/2003	Penny et al.
6,436,097 B1	8/2002	Nardella	6,629,988 B2	10/2003	Weadock
6,436,107 B1	8/2002	Wang et al.	6,636,412 B2	10/2003	Smith
6,436,110 B2	8/2002	Bowman et al.	6,638,108 B2	10/2003	Tachi
6,436,122 B1	8/2002	Frank et al.	6,638,285 B2	10/2003	Gabbay
6,439,439 B1	8/2002	Rickard et al.	6,638,297 B1	10/2003	Huitema
6,439,446 B1	8/2002	Perry et al.	RE38,335 E	11/2003	Aust et al.
6,440,146 B2	8/2002	Nicholas et al.	6,641,528 B2	11/2003	Torii
6,443,973 B1	9/2002	Whitman	6,644,532 B2	11/2003	Green et al.
6,447,518 B1	9/2002	Krause et al.	6,645,201 B1	11/2003	Utley et al.
6,450,391 B1	9/2002	Kayan et al.	6,646,307 B1	11/2003	Yu et al.
6,450,989 B2	9/2002	Dubrul et al.	6,648,816 B2	11/2003	Irion et al.
6,454,781 B1	9/2002	Witt et al.	6,652,595 B1	11/2003	Nicolo
6,468,275 B1	10/2002	Wampler et al.	D484,243 S	12/2003	Ryan et al.
6,471,106 B1	10/2002	Reining	D484,595 S	12/2003	Ryan et al.
6,478,210 B2	11/2002	Adams et al.	D484,596 S	12/2003	Ryan et al.
6,482,200 B2	11/2002	Shippert	6,656,177 B2*	12/2003	Truckai et al. .... 606/51
6,485,490 B2	11/2002	Wampler et al.	6,656,193 B2	12/2003	Grant et al.
6,485,667 B1	11/2002	Tan	6,663,641 B1	12/2003	Kovac et al.
6,488,196 B1	12/2002	Fenton, Jr.	6,666,854 B1	12/2003	Lange
6,488,197 B1	12/2002	Whitman	6,666,875 B1	12/2003	Sakurai et al.
6,491,201 B1	12/2002	Whitman	6,667,825 B2	12/2003	Lu et al.
6,491,690 B1	12/2002	Goble et al.	6,669,073 B2	12/2003	Milliman et al.
6,491,701 B2	12/2002	Tierney et al.	6,671,185 B2	12/2003	Duval
6,492,785 B1	12/2002	Kasten et al.	D484,977 S	1/2004	Ryan et al.
6,494,896 B1	12/2002	D'Alessio et al.	6,676,660 B2	1/2004	Wampler et al.
6,500,176 B1	12/2002	Truckai et al.	6,679,269 B2	1/2004	Swanson
6,500,194 B2	12/2002	Benderev et al.	6,679,410 B2	1/2004	Würsch et al.
6,503,257 B2	1/2003	Grant et al.	6,681,978 B2	1/2004	Geiste et al.
6,503,259 B2	1/2003	Huxel et al.	6,681,979 B2	1/2004	Whitman
6,505,768 B2	1/2003	Whitman	6,682,527 B2	1/2004	Strul
6,510,854 B2	1/2003	Goble	6,682,528 B2	1/2004	Frazier et al.
6,511,468 B1	1/2003	Cragg et al.	6,685,727 B2	2/2004	Fisher et al.
6,517,528 B1	2/2003	Pantages et al.	6,689,153 B1	2/2004	Skiba
6,517,535 B2	2/2003	Edwards	6,692,507 B2	2/2004	Pugsley et al.
6,517,565 B1	2/2003	Whitman et al.	6,695,198 B2	2/2004	Adams et al.
6,517,566 B1	2/2003	Hovland et al.	6,695,199 B2	2/2004	Whitman
6,522,101 B2	2/2003	Malackowski	6,698,643 B2	3/2004	Whitman
6,533,157 B1	3/2003	Whitman	6,699,235 B2	3/2004	Wallace et al.
6,533,784 B2	3/2003	Truckai et al.	6,704,210 B1	3/2004	Myers
6,535,764 B2	3/2003	Imran et al.	6,705,503 B1	3/2004	Pedicini et al.
6,543,456 B1	4/2003	Freeman	6,709,445 B2	3/2004	Boebel et al.
6,545,384 B1	4/2003	Pelrine et al.	6,712,773 B1	3/2004	Viola
6,547,786 B1	4/2003	Goble	6,716,223 B2	4/2004	Leopold et al.
6,550,546 B2	4/2003	Thurler et al.	6,716,232 B1	4/2004	Vidal et al.
			6,716,233 B1	4/2004	Whitman
			6,722,552 B2	4/2004	Fenton, Jr.
			6,723,087 B2	4/2004	O'Neill et al.
			6,723,091 B2	4/2004	Goble et al.



(56)

## References Cited

## U.S. PATENT DOCUMENTS

6,726,697 B2	4/2004	Nicholas et al.	6,908,472 B2	6/2005	Wiener et al.
6,729,119 B2	5/2004	Schnipke et al.	6,911,033 B2	6/2005	de Guillebon et al.
6,736,825 B2	5/2004	Blatter et al.	6,913,579 B2	7/2005	Truckai et al.
6,736,854 B2	5/2004	Vadurro et al.	6,913,608 B2	7/2005	Liddicoat et al.
6,740,030 B2	5/2004	Martone et al.	6,913,613 B2	7/2005	Schwarz et al.
6,747,121 B2	6/2004	Gogolewski	6,921,397 B2	7/2005	Corcoran et al.
6,749,560 B1	6/2004	Konstorum et al.	6,921,412 B1	7/2005	Black et al.
6,752,768 B2	6/2004	Burdorff et al.	6,923,803 B2	8/2005	Goble
6,752,816 B2	6/2004	Culp et al.	6,926,716 B2	8/2005	Baker et al.
6,755,195 B1	6/2004	Lemke et al.	6,929,641 B2	8/2005	Goble et al.
6,755,338 B2	6/2004	Hahnen et al.	6,929,644 B2	8/2005	Truckai et al.
6,758,846 B2	7/2004	Goble et al.	6,931,830 B2	8/2005	Liao
6,761,685 B2	7/2004	Adams et al.	6,932,218 B2	8/2005	Kosann et al.
6,767,352 B2	7/2004	Field et al.	6,932,810 B2	8/2005	Ryan
6,767,356 B2	7/2004	Kanner et al.	6,936,042 B2	8/2005	Wallace et al.
6,769,590 B2	8/2004	Vresh et al.	6,939,358 B2	9/2005	Palacios et al.
6,769,594 B2	8/2004	Orban, III	6,942,662 B2	9/2005	Goble et al.
6,770,072 B1	8/2004	Truckai et al.	6,945,444 B2	9/2005	Gresham et al.
6,773,409 B2	8/2004	Truckai et al.	6,953,138 B1	10/2005	Dworak et al.
6,773,438 B1	8/2004	Knodel et al.	6,953,139 B2	10/2005	Milliman et al.
6,777,838 B2	8/2004	Miekka et al.	6,958,035 B2	10/2005	Friedman et al.
6,780,151 B2	8/2004	Grabover et al.	6,959,851 B2	11/2005	Heinrich
6,780,180 B1	8/2004	Goble et al.	6,959,852 B2	11/2005	Shelton, IV et al.
6,783,524 B2	8/2004	Anderson et al.	6,960,107 B1	11/2005	Schaub et al.
6,786,382 B1	9/2004	Hoffman	6,960,163 B2	11/2005	Ewers et al.
6,786,864 B2	9/2004	Matsuura et al.	6,960,220 B2	11/2005	Marino et al.
6,786,896 B1	9/2004	Madhani et al.	6,964,363 B2	11/2005	Wales et al.
6,790,173 B2	9/2004	Saadat et al.	6,966,907 B2	11/2005	Goble
6,793,652 B1	9/2004	Whitman et al.	6,966,909 B2	11/2005	Marshall et al.
6,793,661 B2	9/2004	Hamilton et al.	6,971,988 B2	12/2005	Orban, III
6,793,663 B2	9/2004	Kneifel et al.	6,972,199 B2	12/2005	Lebouitz et al.
6,802,843 B2	10/2004	Truckai et al.	6,974,462 B2	12/2005	Sater
6,805,273 B2	10/2004	Bilotti et al.	6,978,921 B2	12/2005	Shelton, IV et al.
6,806,808 B1	10/2004	Watters et al.	6,978,922 B2	12/2005	Bilotti et al.
6,808,525 B2	10/2004	Latterell et al.	6,981,628 B2	1/2006	Wales
6,814,741 B2	11/2004	Bowman et al.	6,981,941 B2	1/2006	Whitman et al.
6,817,508 B1	11/2004	Racenet et al.	6,981,978 B2	1/2006	Gannoe
6,817,509 B2	11/2004	Geiste et al.	6,984,203 B2	1/2006	Tartaglia et al.
6,817,974 B2	11/2004	Cooper et al.	6,984,231 B2	1/2006	Goble et al.
6,818,018 B1	11/2004	Sawhney	6,986,451 B1	1/2006	Mastri et al.
6,820,791 B2	11/2004	Adams	6,988,649 B2	1/2006	Shelton, IV et al.
6,821,273 B2	11/2004	Mollenauer	6,988,650 B2	1/2006	Schwemberger et al.
6,821,284 B2	11/2004	Sturtz et al.	6,990,796 B2	1/2006	Schnipke et al.
6,827,246 B2	12/2004	Sullivan et al.	6,994,708 B2	2/2006	Manzo
6,827,712 B2	12/2004	Tovey et al.	6,995,729 B2	2/2006	Govari et al.
6,827,725 B2	12/2004	Batchelor et al.	6,997,931 B2	2/2006	Sauer et al.
6,828,902 B2	12/2004	Casden	7,000,818 B2	2/2006	Shelton, IV et al.
6,830,174 B2	12/2004	Hillstead et al.	7,000,819 B2	2/2006	Swayze et al.
6,832,998 B2	12/2004	Goble	7,001,380 B2	2/2006	Goble
6,834,001 B2	12/2004	Myono	7,001,408 B2	2/2006	Knodel et al.
6,835,199 B2	12/2004	McGuckin, Jr. et al.	7,008,435 B2	3/2006	Cummins
6,835,336 B2	12/2004	Watt	7,011,657 B2	3/2006	Truckai et al.
6,837,846 B2	1/2005	Jaffe et al.	7,018,357 B2	3/2006	Emmons
6,840,423 B2	1/2005	Adams et al.	7,018,390 B2	3/2006	Turovskiy et al.
6,843,403 B2	1/2005	Whitman	7,025,743 B2	4/2006	Mann et al.
6,843,789 B2	1/2005	Goble	7,029,435 B2	4/2006	Nakao
6,846,307 B2	1/2005	Whitman et al.	7,032,798 B2	4/2006	Whitman et al.
6,846,308 B2	1/2005	Whitman et al.	7,032,799 B2	4/2006	Viola et al.
6,846,309 B2	1/2005	Whitman et al.	7,033,356 B2	4/2006	Latterell et al.
6,849,071 B2	2/2005	Whitman et al.	7,036,680 B1	5/2006	Flannery
6,858,005 B2	2/2005	Ohline et al.	7,037,344 B2	5/2006	Kagan et al.
RE38,708 E	3/2005	Bolanos et al.	7,041,102 B2	5/2006	Truckai et al.
6,861,142 B1	3/2005	Wilkie et al.	7,041,868 B2	5/2006	Greene et al.
6,863,694 B1	3/2005	Boyce et al.	7,043,852 B2	5/2006	Hayashida et al.
6,866,178 B2	3/2005	Adams et al.	7,044,352 B2	5/2006	Shelton, IV et al.
6,866,671 B2	3/2005	Tierney et al.	7,044,353 B2	5/2006	Mastri et al.
6,869,435 B2	3/2005	Blake, III	7,048,687 B1	5/2006	Reuss et al.
6,872,214 B2	3/2005	Sonnenschein et al.	7,048,745 B2	5/2006	Tierney et al.
6,874,669 B2	4/2005	Adams et al.	7,052,494 B2	5/2006	Goble et al.
6,877,647 B2	4/2005	Green et al.	7,055,730 B2	6/2006	Ehrenfels et al.
6,878,106 B1	4/2005	Herrmann	7,055,731 B2	6/2006	Shelton, IV et al.
6,889,116 B2	5/2005	Jinno	7,056,284 B2	6/2006	Martone et al.
6,893,435 B2	5/2005	Goble	7,056,330 B2	6/2006	Gayton
6,905,057 B2	6/2005	Swayze et al.	7,059,331 B2	6/2006	Adams et al.
6,905,497 B2	6/2005	Truckai et al.	7,059,508 B2	6/2006	Shelton, IV et al.
			7,063,712 B2	6/2006	Vargas et al.
			7,066,879 B2	6/2006	Fowler et al.
			7,066,944 B2	6/2006	Laufer et al.
			7,067,038 B2	6/2006	Trokhon et al.

(56)

## References Cited

## U.S. PATENT DOCUMENTS

7,070,083 B2	7/2006	Jankowski	7,207,233 B2	4/2007	Wadge
7,070,559 B2	7/2006	Adams et al.	7,207,471 B2	4/2007	Heinrich et al.
7,070,597 B2	7/2006	Truckai et al.	7,207,472 B2	4/2007	Wukusick et al.
7,071,287 B2	7/2006	Rhine et al.	7,207,556 B2	4/2007	Saitoh et al.
7,075,770 B1	7/2006	Smith	7,208,005 B2	4/2007	Frecker et al.
7,077,856 B2	7/2006	Whitman	7,210,609 B2	5/2007	Leiboff et
7,080,769 B2	7/2006	Vresh et al.	7,211,081 B2	5/2007	Goble
7,081,114 B2	7/2006	Rashidi	7,211,084 B2	5/2007	Goble et al.
7,083,073 B2	8/2006	Yoshie et al.	7,213,736 B2	5/2007	Wales et al.
7,083,075 B2	8/2006	Swayze et al.	7,214,224 B2	5/2007	Goble
7,083,571 B2	8/2006	Wang et al.	7,217,285 B2	5/2007	Vargas et al.
7,083,615 B2	8/2006	Peterson et al.	7,220,260 B2	5/2007	Fleming et al.
7,083,619 B2	8/2006	Truckai et al.	7,220,272 B2	5/2007	Weadock
7,083,620 B2	8/2006	Jahns et al.	7,225,963 B2	6/2007	Scirica
7,087,054 B2	8/2006	Truckai et al.	7,225,964 B2	6/2007	Mastri et al.
7,087,071 B2	8/2006	Nicholas et al.	7,234,624 B2	6/2007	Gresham et al.
7,090,637 B2	8/2006	Danitz et al.	7,235,089 B1	6/2007	McGuckin, Jr.
7,090,673 B2	8/2006	Dycus et al.	7,235,302 B2	6/2007	Jing et al.
7,090,683 B2	8/2006	Brock et al.	7,237,708 B1	7/2007	Guy et al.
7,090,684 B2	8/2006	McGuckin, Jr. et al.	7,238,195 B2	7/2007	Viola
7,094,202 B2	8/2006	Nobis et al.	7,241,288 B2	7/2007	Braun
7,094,247 B2	8/2006	Monassevitch et al.	7,246,734 B2	7/2007	Shelton, IV
7,097,089 B2	8/2006	Marczyk	7,247,161 B2	7/2007	Johnston et al.
7,097,644 B2	8/2006	Long	7,252,660 B2	8/2007	Kunz
7,097,650 B2	8/2006	Weller et al.	7,255,696 B2	8/2007	Goble et al.
7,098,794 B2	8/2006	Lindsay et al.	7,256,695 B2	8/2007	Hamel et al.
7,104,741 B2	9/2006	Krohn	7,258,262 B2	8/2007	Mastri et al.
7,108,695 B2	9/2006	Witt et al.	7,258,546 B2	8/2007	Beier et al.
7,108,701 B2	9/2006	Evens et al.	7,260,431 B2	8/2007	Libbus et al.
7,108,709 B2	9/2006	Cummins	7,265,374 B2	9/2007	Lee et al.
7,111,769 B2	9/2006	Wales et al.	7,267,679 B2	9/2007	McGuckin, Jr. et al.
7,112,214 B2	9/2006	Peterson et al.	7,273,483 B2	9/2007	Wiener et al.
RE39,358 E	10/2006	Goble	7,278,562 B2	10/2007	Mastri et al.
7,114,642 B2	10/2006	Whitman	7,278,563 B1	10/2007	Green
7,118,582 B1	10/2006	Wang et al.	7,278,949 B2	10/2007	Bader
7,121,446 B2	10/2006	Arad et al.	7,278,994 B2	10/2007	Goble
7,122,028 B2	10/2006	Looper et al.	7,282,048 B2	10/2007	Goble et al.
7,125,409 B2	10/2006	Truckai et al.	7,293,685 B2	11/2007	Ehrenfels et al.
7,126,303 B2	10/2006	Farritor et al.	7,295,907 B2	11/2007	Lu et al.
7,128,253 B2	10/2006	Mastri et al.	7,296,722 B2	11/2007	Ivanko
7,128,254 B2	10/2006	Shelton, IV et al.	7,296,724 B2	11/2007	Green et al.
7,128,748 B2	10/2006	Mooradian et al.	7,297,149 B2	11/2007	Vitali et al.
7,131,445 B2	11/2006	Amoah	7,300,450 B2	11/2007	Vleugels et al.
7,133,601 B2	11/2006	Phillips et al.	7,303,106 B2	12/2007	Milliman et al.
7,134,587 B2	11/2006	Schwemberger et al.	7,303,107 B2	12/2007	Milliman et al.
7,137,981 B2	11/2006	Long	7,303,108 B2	12/2007	Shelton, IV
7,140,527 B2	11/2006	Ehrenfels et al.	7,303,502 B2	12/2007	Thompson
7,140,528 B2	11/2006	Shelton, IV	7,303,556 B2	12/2007	Metzger
7,143,923 B2	12/2006	Shelton, IV et al.	7,308,998 B2	12/2007	Mastri et al.
7,143,924 B2	12/2006	Scirica et al.	7,322,975 B2	1/2008	Goble et al.
7,143,925 B2	12/2006	Shelton, IV et al.	7,322,994 B2	1/2008	Nicholas et al.
7,143,926 B2	12/2006	Shelton, IV et al.	7,324,572 B2	1/2008	Chang
7,147,138 B2	12/2006	Shelton, IV	7,326,203 B2	2/2008	Papineau et al.
7,147,139 B2	12/2006	Schwemberger et al.	7,326,213 B2	2/2008	Benderev et al.
7,147,140 B2	12/2006	Wukusick et al.	7,328,828 B2	2/2008	Ortiz et al.
7,147,637 B2	12/2006	Goble	7,328,829 B2	2/2008	Arad et al.
7,147,650 B2	12/2006	Lee	7,330,004 B2	2/2008	DeJonge et al.
7,150,748 B2	12/2006	Ebbutt et al.	7,331,340 B2	2/2008	Barney
7,153,300 B2	12/2006	Goble	7,334,717 B2	2/2008	Rethy et al.
7,156,863 B2	1/2007	Sonnenschein et al.	7,334,718 B2	2/2008	McAlister et al.
7,159,750 B2	1/2007	Racenet et al.	7,335,199 B2	2/2008	Goble et al.
7,160,299 B2	1/2007	Baily	7,336,048 B2	2/2008	Lohr
7,161,036 B2	1/2007	Oikawa et al.	7,336,184 B2	2/2008	Smith et al.
7,168,604 B2	1/2007	Milliman et al.	7,338,513 B2	3/2008	Lee et al.
7,172,104 B2	2/2007	Scirica et al.	7,341,591 B2	3/2008	Grinberg
7,179,223 B2	2/2007	Motoki et al.	7,343,920 B2	3/2008	Toby et al.
7,179,267 B2	2/2007	Nolan et al.	7,344,532 B2	3/2008	Goble et al.
7,182,239 B1	2/2007	Myers	7,348,763 B1	3/2008	Reinhart et al.
7,182,763 B2	2/2007	Nardella	RE40,237 E	4/2008	Bilotti et al.
7,183,737 B2	2/2007	Kitagawa	7,351,258 B2	4/2008	Ricotta et al.
7,188,758 B2	3/2007	Viola et al.	7,354,447 B2	4/2008	Shelton, IV et al.
7,189,207 B2	3/2007	Viola	7,354,502 B2	4/2008	Polat et al.
7,195,627 B2	3/2007	Amoah et al.	7,357,287 B2	4/2008	Shelton, IV et al.
7,199,537 B2	4/2007	Okamura et al.	7,357,806 B2	4/2008	Rivera et al.
7,204,835 B2	4/2007	Latterell et al.	7,361,195 B2	4/2008	Schwartz et al.
			7,364,060 B2	4/2008	Milliman
			7,364,061 B2	4/2008	Swayze et al.
			7,377,918 B2	5/2008	Amoah
			7,377,928 B2	5/2008	Zubik et al.

(56)

## References Cited

## U.S. PATENT DOCUMENTS

7,380,695 B2	6/2008	Doll et al.	7,507,202 B2	3/2009	Schoellhorn
7,380,696 B2	6/2008	Shelton, IV et al.	7,510,566 B2	3/2009	Jacobs et al.
7,386,730 B2	6/2008	Uchikubo	7,513,408 B2	4/2009	Shelton, IV et al.
7,388,217 B2	6/2008	Buschbeck et al.	7,517,356 B2	4/2009	Heinrich
7,391,173 B2	6/2008	Schena	7,524,320 B2	4/2009	Tierney et al.
7,396,356 B2	7/2008	Mollenauer	7,530,984 B2	5/2009	Sonnenschein et al.
7,397,364 B2	7/2008	Govari	7,530,985 B2	5/2009	Takemoto et al.
7,398,907 B2	7/2008	Racenet et al.	7,546,939 B2	6/2009	Adams et al.
7,398,908 B2	7/2008	Holsten et al.	7,546,940 B2	6/2009	Milliman et al.
7,401,721 B2	7/2008	Holsten et al.	7,547,312 B2	6/2009	Bauman et al.
7,404,508 B2	7/2008	Smith et al.	7,549,563 B2	6/2009	Mather et al.
7,404,509 B2	7/2008	Ortiz et al.	7,549,564 B2	6/2009	Boudreaux
7,404,822 B2	7/2008	Viart et al.	7,549,998 B2	6/2009	Braun
7,407,074 B2	8/2008	Ortiz et al.	7,552,854 B2	6/2009	Wixey et al.
7,407,075 B2	8/2008	Holsten et al.	7,556,185 B2	7/2009	Viola
7,407,076 B2	8/2008	Racenet et al.	7,556,186 B2	7/2009	Milliman
7,407,077 B2	8/2008	Ortiz et al.	7,556,647 B2	7/2009	Drews et al.
7,407,078 B2	8/2008	Shelton, IV et al.	7,559,449 B2	7/2009	Viola
7,410,086 B2	8/2008	Ortiz et al.	7,559,450 B2	7/2009	Wales et al.
7,413,563 B2	8/2008	Corcoran et al.	7,559,452 B2	7/2009	Wales et al.
7,416,101 B2	8/2008	Shelton, IV et al.	7,563,862 B2	7/2009	Sieg et al.
7,418,078 B2	8/2008	Blanz et al.	7,565,993 B2	7/2009	Milliman et al.
RE40,514 E	9/2008	Mastri et al.	7,566,300 B2	7/2009	Devierre et al.
7,419,080 B2	9/2008	Smith et al.	7,567,045 B2	7/2009	Fristedt
7,419,081 B2	9/2008	Ehrenfels et al.	7,568,603 B2	8/2009	Shelton, IV et al.
7,419,495 B2	9/2008	Menn et al.	7,568,604 B2	8/2009	Ehrenfels et al.
7,422,136 B1	9/2008	Marczyk	7,568,619 B2	8/2009	Todd et al.
7,422,139 B2	9/2008	Shelton, IV et al.	7,575,144 B2	8/2009	Ortiz et al.
7,424,965 B2	9/2008	Racenet et al.	7,588,174 B2	9/2009	Holsten et al.
7,427,607 B2	9/2008	Suzuki	7,588,175 B2	9/2009	Timm et al.
7,431,188 B1	10/2008	Marczyk	7,588,176 B2	9/2009	Timm et al.
7,431,189 B2	10/2008	Shelton, IV et al.	7,588,177 B2	9/2009	Racenet
7,431,694 B2	10/2008	Stefanchik et al.	7,591,783 B2	9/2009	Boulais et al.
7,431,730 B2	10/2008	Viola	7,597,229 B2	10/2009	Boudreaux et al.
7,434,715 B2	10/2008	Shelton, IV et al.	7,597,230 B2	10/2009	Racenet et al.
7,434,717 B2	10/2008	Shelton, IV et al.	7,600,663 B2	10/2009	Green
7,438,209 B1	10/2008	Hess et al.	7,604,150 B2	10/2009	Boudreaux
7,438,718 B2	10/2008	Milliman et al.	7,604,151 B2	10/2009	Hess et al.
7,439,354 B2	10/2008	Lenges et al.	7,607,557 B2	10/2009	Shelton, IV et al.
7,441,684 B2	10/2008	Shelton, IV et al.	7,611,038 B2	11/2009	Racenet et al.
7,441,685 B1	10/2008	Boudreaux	7,611,474 B2	11/2009	Hibner et al.
7,442,201 B2	10/2008	Pugsley et al.	7,615,003 B2	11/2009	Stefanchik et al.
7,448,525 B2	11/2008	Shelton, IV et al.	7,615,067 B2	11/2009	Lee et al.
7,451,904 B2	11/2008	Shelton, IV	7,624,902 B2	12/2009	Marczyk et al.
7,455,208 B2	11/2008	Wales et al.	7,624,903 B2	12/2009	Green et al.
7,455,676 B2	11/2008	Holsten et al.	7,625,370 B2	12/2009	Hart et al.
7,455,682 B2	11/2008	Viola	7,631,793 B2	12/2009	Rethy et al.
7,461,767 B2	12/2008	Viola et al.	7,631,794 B2	12/2009	Rethy et al.
7,462,187 B2	12/2008	Johnston et al.	7,635,074 B2	12/2009	Olson et al.
7,464,846 B2	12/2008	Shelton, IV et al.	7,637,409 B2	12/2009	Marczyk
7,464,847 B2	12/2008	Viola et al.	7,638,958 B2	12/2009	Philipp et al.
7,464,849 B2	12/2008	Shelton, IV et al.	7,641,091 B2	1/2010	Olson et al.
7,467,740 B2	12/2008	Shelton, IV et al.	7,641,092 B2	1/2010	Kruszynski et al.
7,467,849 B2	12/2008	Silverbrook et al.	7,641,093 B2	1/2010	Doll et al.
7,472,814 B2	1/2009	Mastri et al.	7,641,095 B2	1/2010	Viola
7,472,815 B2	1/2009	Shelton, IV et al.	7,644,783 B2	1/2010	Roberts et al.
7,472,816 B2	1/2009	Holsten et al.	7,644,848 B2	1/2010	Swayze et al.
7,473,253 B2	1/2009	Dycus et al.	7,645,230 B2	1/2010	Mikkaichi et al.
7,473,263 B2	1/2009	Johnston et al.	7,648,519 B2	1/2010	Lee et al.
7,479,608 B2	1/2009	Smith	7,651,017 B2	1/2010	Ortiz et al.
7,481,347 B2	1/2009	Roy	7,651,498 B2	1/2010	Shifrin et al.
7,481,348 B2	1/2009	Marczyk	7,654,431 B2	2/2010	Hueil et al.
7,481,349 B2	1/2009	Holsten et al.	7,656,131 B2	2/2010	Embrey et al.
7,481,824 B2	1/2009	Boudreaux et al.	7,658,311 B2	2/2010	Boudreaux
7,485,133 B2	2/2009	Cannon et al.	7,658,312 B2	2/2010	Vidal et al.
7,485,142 B2	2/2009	Milo	7,659,219 B2	2/2010	Biran et al.
7,487,899 B2	2/2009	Shelton, IV et al.	7,662,161 B2	2/2010	Briganti et al.
7,490,749 B2	2/2009	Schall et al.	7,665,646 B2	2/2010	Prommersberger
7,494,039 B2	2/2009	Racenet et al.	7,665,647 B2	2/2010	Shelton, IV et al.
7,494,499 B2	2/2009	Nagase et al.	7,669,746 B2	3/2010	Shelton, IV
7,500,979 B2	3/2009	Hueil et al.	7,669,747 B2	3/2010	Weisenburgh, II et al.
7,501,198 B2	3/2009	Barlev et al.	7,670,334 B2	3/2010	Hueil et al.
7,503,474 B2	3/2009	Hillstead et al.	7,673,780 B2	3/2010	Shelton, IV et al.
7,506,790 B2	3/2009	Shelton, IV	7,673,781 B2	3/2010	Swayze et al.
7,506,791 B2	3/2009	Omaits et al.	7,673,782 B2	3/2010	Hess et al.
			7,673,783 B2	3/2010	Morgan et al.
			7,674,253 B2	3/2010	Fisher et al.
			7,674,255 B2	3/2010	Braun
			7,674,263 B2	3/2010	Ryan

(56)

## References Cited

## U.S. PATENT DOCUMENTS

7,682,307 B2	3/2010	Danitz et al.	7,798,386 B2	9/2010	Schall et al.
7,686,201 B2	3/2010	Csiky	7,799,039 B2	9/2010	Shelton, IV et al.
7,686,826 B2	3/2010	Lee et al.	7,799,044 B2	9/2010	Johnston et al.
7,688,028 B2	3/2010	Phillips et al.	7,803,151 B2	9/2010	Whitman
7,691,098 B2	4/2010	Wallace et al.	7,806,891 B2	10/2010	Nowlin et al.
7,694,865 B2	4/2010	Scirica	7,810,690 B2	10/2010	Bilotti et al.
7,695,485 B2	4/2010	Whitman et al.	7,810,691 B2	10/2010	Boyden et al.
7,699,204 B2	4/2010	Viola	7,810,692 B2	10/2010	Hall et al.
7,699,835 B2	4/2010	Lee et al.	7,810,693 B2	10/2010	Broehl et al.
7,699,844 B2	4/2010	Utley et al.	7,815,092 B2	10/2010	Whitman et al.
7,699,846 B2	4/2010	Ryan	7,815,565 B2	10/2010	Stefanchik et al.
7,699,856 B2	4/2010	Van Wyk et al.	7,819,296 B2	10/2010	Hueil et al.
7,699,859 B2	4/2010	Bombard et al.	7,819,297 B2	10/2010	Doll et al.
7,699,860 B2	4/2010	Huitema et al.	7,819,298 B2	10/2010	Hall et al.
7,703,653 B2	4/2010	Shah et al.	7,819,299 B2	10/2010	Shelton, IV et al.
7,708,180 B2	5/2010	Murray et al.	7,819,886 B2	10/2010	Whitfield et al.
7,708,181 B2	5/2010	Cole et al.	7,823,592 B2	11/2010	Bettuchi et al.
7,708,758 B2	5/2010	Lee et al.	7,824,401 B2	11/2010	Manzo et al.
7,714,239 B2	5/2010	Smith	7,824,426 B2	11/2010	Racenet et al.
7,717,312 B2	5/2010	Beetel	7,828,189 B2	11/2010	Holsten et al.
7,717,313 B2	5/2010	Criscuolo et al.	7,828,794 B2	11/2010	Sartor
7,717,846 B2	5/2010	Zirps et al.	7,828,808 B2	11/2010	Hinman et al.
7,718,180 B2	5/2010	Karp	7,832,408 B2	11/2010	Shelton, IV et al.
7,718,556 B2	5/2010	Matsuda et al.	7,832,611 B2	11/2010	Boyden et al.
7,721,930 B2	5/2010	McKenna et al.	7,832,612 B2	11/2010	Baxter, III et al.
7,721,931 B2	5/2010	Shelton, IV et al.	7,833,234 B2	11/2010	Bailly et al.
7,721,933 B2	5/2010	Ehrenfels et al.	7,836,400 B2	11/2010	May et al.
7,721,934 B2	5/2010	Shelton, IV et al.	7,837,079 B2	11/2010	Holsten et al.
7,721,936 B2	5/2010	Shalton, IV et al.	7,837,080 B2	11/2010	Schwemberger
7,722,527 B2	5/2010	Bouchier et al.	7,837,081 B2	11/2010	Holsten et al.
7,722,607 B2	5/2010	Dumbauld et al.	7,837,694 B2	11/2010	Tethrake et al.
7,722,610 B2	5/2010	Viola et al.	7,842,025 B2	11/2010	Coleman et al.
7,726,537 B2	6/2010	Olson et al.	7,842,028 B2	11/2010	Lee
7,726,538 B2	6/2010	Holsten et al.	7,845,533 B2	12/2010	Marczyk et al.
7,726,539 B2	6/2010	Holsten et al.	7,845,534 B2	12/2010	Viola et al.
7,731,072 B2	6/2010	Timm et al.	7,845,535 B2	12/2010	Scirica
7,731,073 B2	6/2010	Wixey et al.	7,845,536 B2	12/2010	Viola et al.
7,731,724 B2	6/2010	Huitema et al.	7,845,537 B2	12/2010	Shelton, IV et al.
7,735,703 B2	6/2010	Morgan et al.	7,846,149 B2	12/2010	Jankowski
7,736,374 B2	6/2010	Vaughan et al.	7,850,642 B2	12/2010	Moll et al.
7,738,971 B2	6/2010	Swayze et al.	7,854,736 B2	12/2010	Ryan
7,740,159 B2	6/2010	Shelton, IV et al.	7,857,183 B2	12/2010	Shelton, IV
7,743,960 B2	6/2010	Whitman et al.	7,857,185 B2	12/2010	Swayze et al.
7,744,624 B2	6/2010	Bettuchi	7,857,186 B2	12/2010	Baxter, III et al.
7,744,627 B2	6/2010	Orban, III et al.	7,857,813 B2	12/2010	Schmitz et al.
7,744,628 B2	6/2010	Viola	7,861,906 B2	1/2011	Doll et al.
7,748,587 B2	7/2010	Haramiishi et al.	7,862,579 B2	1/2011	Ortiz et al.
7,749,204 B2	7/2010	Dhanaraj et al.	7,866,525 B2	1/2011	Scirica
7,751,870 B2	7/2010	Whitman	7,866,527 B2	1/2011	Hall et al.
7,753,245 B2	7/2010	Boudreaux et al.	7,866,528 B2	1/2011	Olson et al.
7,753,904 B2	7/2010	Shelton, IV et al.	7,870,989 B2	1/2011	Viola et al.
7,758,612 B2	7/2010	Shipp	7,871,418 B2	1/2011	Thompson et al.
7,766,209 B2	8/2010	Baxter, III et al.	7,879,070 B2	2/2011	Ortiz et al.
7,766,210 B2	8/2010	Shelton, IV et al.	7,883,465 B2	2/2011	Donofrio et al.
7,766,821 B2	8/2010	Brunnen et al.	7,886,951 B2	2/2011	Hessler
7,766,894 B2	8/2010	Weitzner et al.	7,886,952 B2	2/2011	Scirica et al.
7,770,773 B2	8/2010	Whitman et al.	7,887,530 B2	2/2011	Zemlok et al.
7,770,774 B2	8/2010	Mastri et al.	7,891,531 B1	2/2011	Ward
7,770,775 B2	8/2010	Shelton, IV et al.	7,891,532 B2	2/2011	Mastri et al.
7,770,776 B2	8/2010	Chen et al.	7,893,586 B2	2/2011	West et al.
7,771,396 B2	8/2010	Stefanchik et al.	7,896,214 B2	3/2011	Farascioni
7,772,720 B2	8/2010	McGee et al.	7,896,215 B2	3/2011	Adams et al.
7,776,060 B2	8/2010	Mooradian et al.	7,896,877 B2	3/2011	Hall et al.
7,778,004 B2	8/2010	Nerheim et al.	7,900,805 B2	3/2011	Shelton, IV et al.
7,780,054 B2	8/2010	Wales	7,905,380 B2	3/2011	Shelton, IV et al.
7,780,055 B2	8/2010	Scirica et al.	7,905,381 B2	3/2011	Baxter, III et al.
7,780,663 B2	8/2010	Yates et al.	7,905,889 B2	3/2011	Catanese, III et al.
7,780,685 B2	8/2010	Hunt et al.	7,905,902 B2	3/2011	Huitema et al.
7,784,662 B2	8/2010	Wales et al.	7,909,191 B2	3/2011	Baker et al.
7,784,663 B2	8/2010	Shelton, IV	7,909,220 B2	3/2011	Viola
7,789,875 B2	9/2010	Brock et al.	7,909,221 B2	3/2011	Viola et al.
7,789,883 B2	9/2010	Takashino et al.	7,913,891 B2	3/2011	Doll et al.
7,789,889 B2	9/2010	Zubik et al.	7,913,893 B2	3/2011	Mastri et al.
7,793,812 B2	9/2010	Moore et al.	7,914,543 B2	3/2011	Roth et al.
7,794,475 B2	9/2010	Hess et al.	7,914,551 B2	3/2011	Ortiz et al.
			7,918,376 B1	4/2011	Knodel et al.
			7,918,377 B2	4/2011	Measamer et al.
			7,918,848 B2	4/2011	Lau et al.
			7,922,061 B2	4/2011	Shelton, IV et al.

(56)

## References Cited

## U.S. PATENT DOCUMENTS

7,922,063 B2	4/2011	Zemlok et al.	8,057,508 B2	11/2011	Shelton, IV
7,922,743 B2	4/2011	Heinrich et al.	8,062,330 B2	11/2011	Prommersberger et al.
7,926,691 B2	4/2011	Viola et al.	8,066,167 B2	11/2011	Measamer et al.
7,927,328 B2	4/2011	Orszulak et al.	8,066,168 B2	11/2011	Vidal et al.
7,931,660 B2	4/2011	Aranyi et al.	D650,074 S	12/2011	Hunt et al.
7,931,695 B2	4/2011	Ringeisen	8,070,743 B2	12/2011	Kagan et al.
7,934,630 B2	5/2011	Shelton, IV et al.	8,075,571 B2	12/2011	Vitali et al.
7,934,631 B2	5/2011	Balbierz et al.	8,083,118 B2	12/2011	Milliman et al.
7,935,773 B2	5/2011	Hadba et al.	8,083,119 B2	12/2011	Prommersberger
7,938,307 B2	5/2011	Bettuchi	8,083,120 B2	12/2011	Shelton, IV et al.
7,941,865 B2	5/2011	Seman, Jr. et al.	8,084,001 B2	12/2011	Burns et al.
7,942,303 B2	5/2011	Shah	8,091,756 B2	1/2012	Viola
7,942,890 B2	5/2011	D'Agostino et al.	8,092,932 B2	1/2012	Phillips et al.
7,944,175 B2	5/2011	Mori et al.	8,096,458 B2	1/2012	Hessler
7,950,560 B2	5/2011	Zemlok et al.	8,097,017 B2	1/2012	Viola
7,950,561 B2	5/2011	Aranyi	8,100,310 B2	1/2012	Zemlok
7,951,071 B2	5/2011	Whitman et al.	8,105,350 B2	1/2012	Lee et al.
7,951,166 B2	5/2011	Orban et al.	8,108,072 B2	1/2012	Zhao et al.
7,954,682 B2	6/2011	Giordano et al.	8,109,426 B2	2/2012	Milliman et al.
7,954,684 B2	6/2011	Boudreaux	8,113,405 B2	2/2012	Milliman
7,954,686 B2	6/2011	Baxter, III et al.	8,113,410 B2	2/2012	Hall et al.
7,954,687 B2	6/2011	Zemlok et al.	8,114,100 B2	2/2012	Smith et al.
7,955,257 B2	6/2011	Frasier et al.	8,123,103 B2	2/2012	Milliman
7,959,050 B2	6/2011	Smith et al.	8,123,766 B2	2/2012	Bauman et al.
7,959,051 B2	6/2011	Smith et al.	8,123,767 B2	2/2012	Bauman et al.
7,963,432 B2	6/2011	Knodel et al.	8,127,975 B2	3/2012	Olson et al.
7,963,433 B2	6/2011	Whitman et al.	8,128,624 B2	3/2012	Couture et al.
7,963,963 B2	6/2011	Francischelli et al.	8,128,645 B2	3/2012	Sonnenschein et al.
7,963,964 B2	6/2011	Santilli et al.	8,132,703 B2	3/2012	Milliman et al.
7,966,799 B2	6/2011	Morgan et al.	8,132,706 B2	3/2012	Marczyk et al.
7,967,180 B2	6/2011	Scirica	8,136,712 B2	3/2012	Zingman
7,967,181 B2	6/2011	Viola et al.	8,136,713 B2	3/2012	Hathaway et al.
7,967,839 B2	6/2011	Flock et al.	8,140,417 B2	3/2012	Shibata
7,972,298 B2	7/2011	Wallace et al.	8,141,762 B2	3/2012	Bedi et al.
7,980,443 B2	7/2011	Scheib et al.	8,141,763 B2	3/2012	Milliman
7,988,026 B2	8/2011	Knodel et al.	8,146,790 B2	4/2012	Milliman
7,988,027 B2	8/2011	Olson et al.	8,152,041 B2	4/2012	Kostrzewski
7,988,028 B2	8/2011	Farascioni et al.	8,157,145 B2	4/2012	Shelton, IV et al.
7,992,757 B2	8/2011	Wheeler et al.	8,157,148 B2	4/2012	Scirica
7,997,469 B2	8/2011	Olson et al.	8,157,151 B2	4/2012	Ingmanson et al.
8,002,696 B2	8/2011	Suzuki	8,157,152 B2	4/2012	Holsten et al.
8,002,784 B2	8/2011	Jinno et al.	8,157,153 B2	4/2012	Shelton, IV et al.
8,002,785 B2	8/2011	Weiss et al.	8,161,977 B2	4/2012	Shelton, IV et al.
8,002,795 B2	8/2011	Beetel	8,162,138 B2	4/2012	Bettenhausen et al.
8,006,365 B2	8/2011	Levin et al.	8,162,197 B2	4/2012	Mastri et al.
8,006,885 B2	8/2011	Marczyk	8,167,185 B2	5/2012	Shelton, IV et al.
8,006,889 B2	8/2011	Adams et al.	8,167,895 B2	5/2012	D'Agostino et al.
8,011,550 B2	9/2011	Aranyi et al.	8,167,898 B1	5/2012	Schaller et al.
8,011,551 B2	9/2011	Marczyk et al.	8,172,120 B2	5/2012	Boyd et al.
8,011,553 B2	9/2011	Mastri et al.	8,172,122 B2	5/2012	Kasvikis et al.
8,011,555 B2	9/2011	Tarinelli et al.	8,172,124 B2	5/2012	Shelton, IV et al.
8,016,176 B2	9/2011	Kasvikis et al.	8,177,797 B2	5/2012	Shimoji et al.
8,016,177 B2	9/2011	Bettuchi et al.	8,180,458 B2	5/2012	Kane et al.
8,016,178 B2	9/2011	Olson et al.	8,181,840 B2	5/2012	Milliman
8,016,855 B2	9/2011	Whitman et al.	8,186,555 B2	5/2012	Shelton, IV et al.
8,016,858 B2	9/2011	Whitman	8,186,560 B2	5/2012	Hess et al.
8,016,881 B2	9/2011	Furst	8,191,752 B2	6/2012	Scirica
8,020,742 B2	9/2011	Marczyk	8,192,460 B2	6/2012	Orban, III et al.
8,020,743 B2	9/2011	Shelton, IV	8,196,795 B2	6/2012	Moore et al.
8,021,375 B2	9/2011	Aldrich et al.	8,196,796 B2	6/2012	Shelton, IV et al.
8,025,199 B2	9/2011	Whitman et al.	8,201,720 B2	6/2012	Hessler
8,028,883 B2	10/2011	Stopek	8,201,721 B2	6/2012	Zemlok et al.
8,028,884 B2	10/2011	Sniffin et al.	8,205,780 B2	6/2012	Sorrentino et al.
8,028,885 B2	10/2011	Smith et al.	8,205,781 B2	6/2012	Baxter, III et al.
8,034,077 B2	10/2011	Smith et al.	8,210,411 B2	7/2012	Yates et al.
8,034,363 B2	10/2011	Li et al.	8,210,414 B2	7/2012	Bettuchi et al.
8,037,591 B2	10/2011	Spivey et al.	8,210,415 B2	7/2012	Ward
8,038,045 B2	10/2011	Bettuchi et al.	8,210,416 B2	7/2012	Milliman et al.
8,038,046 B2	10/2011	Smith et al.	8,211,125 B2	7/2012	Spivey
8,038,686 B2	10/2011	Huitema et al.	8,214,019 B2	7/2012	Govari et al.
8,043,207 B2	10/2011	Adams	8,215,531 B2	7/2012	Shelton, IV et al.
8,043,328 B2	10/2011	Hahnen et al.	8,215,533 B2	7/2012	Viola et al.
8,047,236 B2	11/2011	Perry	8,220,468 B2	7/2012	Cooper et al.
8,056,787 B2	11/2011	Boudreaux et al.	8,220,688 B2	7/2012	Laurent et al.
8,056,788 B2	11/2011	Mastri et al.	8,220,690 B2	7/2012	Hess et al.
			8,221,424 B2	7/2012	Cha
			8,225,799 B2	7/2012	Bettuchi
			8,226,715 B2	7/2012	Hwang et al.
			8,231,040 B2	7/2012	Zemlok et al.

(56)

## References Cited

## U.S. PATENT DOCUMENTS

8,231,041 B2	7/2012	Marczyk et al.	8,372,094 B2	2/2013	Bettuchi et al.
8,231,042 B2	7/2012	Hessler et al.	8,376,865 B2	2/2013	Forster et al.
8,231,043 B2	7/2012	Tarinelli et al.	8,377,044 B2	2/2013	Coe et al.
8,236,010 B2	8/2012	Ortiz et al.	8,393,513 B2	3/2013	Jankowski
8,241,271 B2	8/2012	Millman et al.	8,393,514 B2	3/2013	Shelton, IV et al.
8,241,308 B2	8/2012	Kortenbach et al.	8,397,971 B2	3/2013	Yates et al.
8,241,322 B2	8/2012	Whitman et al.	8,403,138 B2	3/2013	Weisshaupt et al.
8,245,898 B2	8/2012	Smith et al.	8,403,198 B2	3/2013	Sorrentino et al.
8,245,899 B2	8/2012	Swensgard et al.	8,403,945 B2	3/2013	Whitfield et al.
8,245,900 B2	8/2012	Scirica	8,408,439 B2	4/2013	Huang et al.
8,245,901 B2	8/2012	Stopek	8,408,442 B2	4/2013	Racenet et al.
8,246,637 B2	8/2012	Viola et al.	8,409,079 B2	4/2013	Okamoto et al.
8,256,654 B2	9/2012	Bettuchi et al.	8,409,222 B2	4/2013	Whitfield et al.
8,256,655 B2	9/2012	Sniffin et al.	8,413,870 B2	4/2013	Pastorelli et al.
8,257,251 B2	9/2012	Shelton, IV et al.	8,413,871 B2	4/2013	Racenet et al.
8,257,356 B2	9/2012	Bleich et al.	8,413,872 B2	4/2013	Patel
8,257,391 B2	9/2012	Orban, III et al.	8,414,577 B2	4/2013	Boudreaux et al.
8,267,300 B2	9/2012	Boudreaux	8,424,737 B2	4/2013	Scirica
8,267,924 B2	9/2012	Zemlok et al.	8,424,739 B2	4/2013	Racenet et al.
8,267,946 B2	9/2012	Whitfield et al.	8,424,740 B2	4/2013	Shelton, IV et al.
8,267,951 B2	9/2012	Whayne et al.	8,424,741 B2	4/2013	McGuckin, Jr. et al.
8,269,121 B2	9/2012	Smith	8,430,898 B2	4/2013	Wiener et al.
8,272,553 B2	9/2012	Mastri et al.	8,439,246 B1	5/2013	Knodel
8,272,554 B2	9/2012	Whitman et al.	8,444,036 B2	5/2013	Shelton, IV
8,276,801 B2	10/2012	Zemlok et al.	8,444,549 B2	5/2013	Viola et al.
8,276,802 B2	10/2012	Kostrzewski	8,453,904 B2	6/2013	Eskaros et al.
8,281,973 B2	10/2012	Wenchell et al.	8,453,907 B2	6/2013	Laurent et al.
8,286,845 B2	10/2012	Perry et al.	8,453,908 B2	6/2013	Bedi et al.
8,287,561 B2	10/2012	Nunez et al.	8,453,912 B2	6/2013	Mastri et al.
8,292,151 B2	10/2012	Viola	8,453,914 B2	6/2013	Laurent et al.
8,292,155 B2	10/2012	Shelton, IV et al.	8,459,520 B2	6/2013	Giordano et al.
8,292,157 B2	10/2012	Smith et al.	8,459,525 B2	6/2013	Yates et al.
8,292,888 B2	10/2012	Whitman	8,464,922 B2	6/2013	Marczyk
8,298,677 B2	10/2012	Wiesner et al.	8,464,923 B2	6/2013	Shelton, IV
8,302,323 B2	11/2012	Fortier et al.	8,464,924 B2	6/2013	Gresham et al.
8,308,040 B2	11/2012	Huang et al.	8,464,925 B2	6/2013	Hull et al.
8,308,042 B2	11/2012	Aranyi	8,474,677 B2	7/2013	Woodard, Jr. et al.
8,308,046 B2	11/2012	Prommersberger	8,475,453 B2	7/2013	Marczyk et al.
8,308,659 B2	11/2012	Scheibe et al.	8,475,474 B2	7/2013	Bombard et al.
8,313,496 B2	11/2012	Sauer et al.	8,479,969 B2	7/2013	Shelton, IV
8,313,509 B2	11/2012	Kostrzewski	8,485,412 B2	7/2013	Shelton, IV et al.
8,317,070 B2	11/2012	Hueil et al.	8,490,853 B2	7/2013	Criscuolo et al.
8,317,071 B1	11/2012	Knodel	8,496,156 B2	7/2013	Sniffin et al.
8,317,074 B2	11/2012	Ortiz et al.	8,496,683 B2	7/2013	Prommersberger et al.
8,319,002 B2	11/2012	Daniels et al.	8,499,993 B2	8/2013	Shelton, IV et al.
8,322,455 B2	12/2012	Shelton, IV et al.	8,500,762 B2	8/2013	Sholev et al.
8,322,589 B2	12/2012	Boudreaux	8,506,557 B2	8/2013	Zemlok et al.
8,323,789 B2	12/2012	Rozhin et al.	8,517,239 B2	8/2013	Scheib et al.
8,328,062 B2	12/2012	Viola	8,517,241 B2	8/2013	Nicholas et al.
8,328,063 B2	12/2012	Milliman et al.	8,517,243 B2	8/2013	Giordano et al.
8,328,064 B2	12/2012	Racenet et al.	8,517,244 B2	8/2013	Shelton, IV et al.
8,328,802 B2	12/2012	Deville et al.	8,523,881 B2	9/2013	Cabiri et al.
8,328,823 B2	12/2012	Aranyi et al.	8,529,588 B2	9/2013	Ahlberg et al.
8,333,313 B2	12/2012	Boudreaux et al.	8,529,600 B2	9/2013	Woodard, Jr. et al.
8,333,764 B2	12/2012	Francischelli et al.	8,534,528 B2	9/2013	Shelton, IV
8,336,753 B2	12/2012	Olson et al.	8,535,304 B2	9/2013	Sklar et al.
8,348,123 B2	1/2013	Scirica et al.	8,540,128 B2	9/2013	Shelton, IV et al.
8,348,127 B2	1/2013	Marczyk	8,540,129 B2	9/2013	Baxter, III et al.
8,348,129 B2	1/2013	Bedi et al.	8,540,130 B2	9/2013	Moore et al.
8,348,131 B2	1/2013	Omaits et al.	8,540,131 B2	9/2013	Swayze
8,348,972 B2	1/2013	Soltz et al.	8,540,133 B2	9/2013	Bedi et al.
8,353,437 B2	1/2013	Boudreaux	8,540,733 B2	9/2013	Whitman et al.
8,353,438 B2	1/2013	Baxter, III et al.	8,556,151 B2	10/2013	Viola
8,353,439 B2	1/2013	Baxter, III et al.	8,556,918 B2	10/2013	Bauman et al.
8,357,144 B2	1/2013	Whitman et al.	8,561,870 B2	10/2013	Baxter, III et al.
8,360,296 B2	1/2013	Zingman	8,561,873 B2	10/2013	Ingmanson et al.
8,360,297 B2	1/2013	Shelton, IV et al.	8,567,656 B2	10/2013	Shelton, IV et al.
8,360,298 B2	1/2013	Farascioni et al.	8,573,461 B2	11/2013	Shelton, IV et al.
8,360,299 B2	1/2013	Zemlok et al.	8,573,465 B2	11/2013	Shelton, IV et al.
8,365,973 B1	2/2013	White et al.	8,579,176 B2	11/2013	Smith et al.
8,365,976 B2	2/2013	Hess et al.	8,579,937 B2	11/2013	Gresham
8,366,559 B2	2/2013	Papenfuss et al.	8,584,919 B2	11/2013	Hueil et al.
8,371,491 B2	2/2013	Huitema et al.	8,585,721 B2	11/2013	Kirsch
8,371,492 B2	2/2013	Aranyi et al.	8,590,762 B2	11/2013	Hess et al.
8,371,493 B2	2/2013	Aranyi et al.	8,602,287 B2	12/2013	Yates et al.
			8,602,288 B2	12/2013	Shelton, IV et al.
			8,608,044 B2	12/2013	Hueil et al.
			8,608,045 B2	12/2013	Smith et al.
			8,608,046 B2	12/2013	Laurent et al.

(56)

## References Cited

## U.S. PATENT DOCUMENTS

8,616,431 B2	12/2013	Timm et al.	8,857,693 B2	10/2014	Schuckmann et al.
8,622,274 B2	1/2014	Yates et al.	8,857,694 B2	10/2014	Shelton, IV et al.
8,622,275 B2	1/2014	Baxter, III et al.	8,858,571 B2	10/2014	Shelton, IV et al.
8,631,987 B2	1/2014	Shelton, IV et al.	8,858,590 B2	10/2014	Shelton, IV et al.
8,632,462 B2	1/2014	Yoo et al.	8,864,007 B2	10/2014	Widenhouse et al.
8,632,525 B2	1/2014	Kerr et al.	8,864,009 B2	10/2014	Shelton, IV et al.
8,632,535 B2	1/2014	Shelton, IV et al.	8,875,971 B2	11/2014	Hall et al.
8,632,563 B2	1/2014	Nagase et al.	8,875,972 B2	11/2014	Weisenburgh, II et al.
8,636,187 B2	1/2014	Hueil et al.	8,893,946 B2	11/2014	Boudreaux et al.
8,636,736 B2	1/2014	Yates et al.	8,893,949 B2	11/2014	Shelton, IV et al.
8,647,258 B2	2/2014	Aranyi et al.	8,899,463 B2	12/2014	Schall et al.
8,652,120 B2	2/2014	Giordano et al.	8,899,465 B2	12/2014	Shelton, IV et al.
8,652,151 B2	2/2014	Lehman et al.	8,899,466 B2	12/2014	Baxter, III et al.
8,657,174 B2	2/2014	Yates et al.	8,911,471 B2	12/2014	Spivey et al.
8,657,176 B2	2/2014	Shelton, IV et al.	8,925,782 B2	1/2015	Shelton, IV
8,657,178 B2	2/2014	Hueil et al.	8,925,788 B2	1/2015	Hess et al.
8,663,192 B2	3/2014	Hester et al.	8,926,598 B2	1/2015	Mollere et al.
8,668,129 B2	3/2014	Olson	8,931,682 B2	1/2015	Timm et al.
8,668,130 B2	3/2014	Hess et al.	2001/0025183 A1	9/2001	Shahidi
8,672,206 B2	3/2014	Aranyi et al.	2001/0044637 A1	11/2001	Jacobs et al.
8,672,207 B2	3/2014	Shelton, IV et al.	2002/0022836 A1	2/2002	Goble et al.
8,672,208 B2	3/2014	Hess et al.	2002/0029036 A1	3/2002	Goble et al.
8,679,137 B2	3/2014	Bauman et al.	2002/0095175 A1	7/2002	Brock et al.
8,679,454 B2	3/2014	Guire et al.	2002/0103494 A1	8/2002	Pacey
8,684,253 B2	4/2014	Giordano et al.	2002/0117534 A1	8/2002	Green et al.
8,695,866 B2	4/2014	Leimbach et al.	2002/0134811 A1	9/2002	Napier et al.
8,696,665 B2	4/2014	Hunt et al.	2002/0165541 A1	11/2002	Whitman
8,701,958 B2	4/2014	Shelton, IV et al.	2003/0023316 A1	1/2003	Brown et al.
8,701,959 B2	4/2014	Shah	2003/0078647 A1	4/2003	Vallana et al.
8,708,213 B2	4/2014	Shelton, IV et al.	2003/0084983 A1	5/2003	Rangachari et al.
8,720,766 B2	5/2014	Hess et al.	2003/0093103 A1	5/2003	Malackowski et al.
8,721,666 B2	5/2014	Schroeder et al.	2003/0096158 A1	5/2003	Takano et al.
8,727,197 B2	5/2014	Hess et al.	2003/0105478 A1	6/2003	Whitman et al.
8,733,613 B2	5/2014	Huitema et al.	2003/0130677 A1	7/2003	Whitman et al.
8,734,478 B2	5/2014	Widenhouse et al.	2003/0139741 A1	7/2003	Goble et al.
8,740,034 B2	6/2014	Morgan et al.	2003/0153908 A1	8/2003	Goble et al.
8,740,037 B2	6/2014	Shelton, IV et al.	2003/0163085 A1	8/2003	Tanner et al.
8,740,038 B2	6/2014	Shelton, IV et al.	2003/0181900 A1	9/2003	Long
8,746,529 B2	6/2014	Shelton, IV et al.	2003/0195387 A1	10/2003	Kortenbach et al.
8,746,530 B2	6/2014	Giordano et al.	2003/0205029 A1	11/2003	Chapolini et al.
8,746,535 B2	6/2014	Shelton, IV et al.	2003/0216732 A1	11/2003	Truckai et al.
8,747,238 B2	6/2014	Shelton, IV et al.	2003/0220660 A1	11/2003	Kortenbach et al.
8,752,699 B2	6/2014	Morgan et al.	2003/0236505 A1	12/2003	Bonadio et al.
8,752,747 B2	6/2014	Shelton, IV et al.	2004/0002726 A1	1/2004	Nunez et al.
8,752,749 B2	6/2014	Moore et al.	2004/0006335 A1	1/2004	Garrison
8,757,465 B2	6/2014	Woodard, Jr. et al.	2004/0006340 A1	1/2004	Latterell et al.
8,758,235 B2	6/2014	Jaworek	2004/0006372 A1	1/2004	Racenet et al.
8,758,391 B2	6/2014	Swayze et al.	2004/0006861 A1	1/2004	Haytayan
8,758,438 B2	6/2014	Boyce et al.	2004/0030333 A1	2/2004	Goble
8,763,875 B2	7/2014	Morgan et al.	2004/0034357 A1	2/2004	Beane et al.
8,763,877 B2	7/2014	Schall et al.	2004/0034369 A1	2/2004	Sauer et al.
8,763,879 B2	7/2014	Shelton, IV et al.	2004/0044364 A1	3/2004	DeVries et al.
8,777,004 B2	7/2014	Shelton, IV et al.	2004/0068161 A1	4/2004	Couvillon, Jr.
8,783,541 B2	7/2014	Shelton, IV et al.	2004/0068224 A1	4/2004	Couvillon, Jr. et al.
8,783,542 B2	7/2014	Riestenberg et al.	2004/0068307 A1	4/2004	Goble
8,783,543 B2	7/2014	Shelton, IV et al.	2004/0070369 A1	4/2004	Sakahibara
8,784,404 B2	7/2014	Doyle et al.	2004/0073222 A1	4/2004	Koseki
8,789,739 B2	7/2014	Swensgard	2004/0078037 A1	4/2004	Batchelor et al.
8,789,740 B2	7/2014	Baxter, III et al.	2004/0093024 A1	5/2004	Lousararian et al.
8,789,741 B2	7/2014	Baxter, III et al.	2004/0094597 A1	5/2004	Whitman et al.
8,794,497 B2	8/2014	Zingman	2004/0097987 A1	5/2004	Pugsley et al.
8,800,838 B2	8/2014	Shelton, IV	2004/0098040 A1	5/2004	Taniguchi et al.
8,800,841 B2	8/2014	Ellerhorst et al.	2004/0101822 A1	5/2004	Wiesner et al.
8,801,734 B2	8/2014	Shelton, IV et al.	2004/0102783 A1	5/2004	Sutterlin, III et al.
8,801,735 B2	8/2014	Shelton, IV et al.	2004/0108357 A1	6/2004	Milliman et al.
8,814,024 B2	8/2014	Woodard, Jr. et al.	2004/0111081 A1	6/2004	Whitman et al.
8,820,603 B2	9/2014	Shelton, IV et al.	2004/0115022 A1	6/2004	Albertson et al.
8,820,605 B2	9/2014	Shelton, IV	2004/0116952 A1	6/2004	Sakurai et al.
8,827,133 B2	9/2014	Shelton, IV et al.	2004/0147909 A1	7/2004	Johnston et al.
8,827,903 B2	9/2014	Shelton, IV et al.	2004/0164123 A1	8/2004	Racenet et al.
8,833,632 B2	9/2014	Swensgard	2004/0167572 A1	8/2004	Roth et al.
8,840,003 B2	9/2014	Morgan et al.	2004/0173659 A1	9/2004	Green et al.
8,840,603 B2	9/2014	Shelton, IV et al.	2004/0181219 A1	9/2004	Goble et al.
8,844,789 B2	9/2014	Shelton, IV et al.	2004/0186470 A1	9/2004	Goble et al.
8,851,354 B2	10/2014	Swensgard et al.	2004/0193189 A1	9/2004	Kortenbach et al.
			2004/0199181 A1	10/2004	Knodel et al.
			2004/0222268 A1	11/2004	Bilotti et al.
			2004/0225186 A1	11/2004	Horne, Jr. et al.
			2004/0230214 A1	11/2004	Donofrio et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2004/0232201 A1	11/2004	Wenchell et al.	2006/0015009 A1	1/2006	Jaffe et al.
2004/0236352 A1	11/2004	Wang et al.	2006/0020247 A1	1/2006	Kagan et al.
2004/0243147 A1	12/2004	Lipow	2006/0020258 A1	1/2006	Strauss et al.
2004/0243151 A1	12/2004	Demmy et al.	2006/0020336 A1	1/2006	Liddicoat
2004/0243163 A1	12/2004	Casiano et al.	2006/0025811 A1	2/2006	Shelton, IV
2004/0243176 A1	12/2004	Hahnen et al.	2006/0025812 A1	2/2006	Shelton, IV
2004/0247415 A1	12/2004	Mangone, Jr.	2006/0025813 A1	2/2006	Shelton et al.
2004/0254566 A1	12/2004	Plicchi et al.	2006/0041188 A1	2/2006	Dirusso et al.
2004/0254608 A1	12/2004	Huitema et al.	2006/0047275 A1	3/2006	Goble
2004/0260315 A1	12/2004	Dell et al.	2006/0047303 A1	3/2006	Ortiz et al.
2004/0267310 A1	12/2004	Racenet et al.	2006/0047307 A1	3/2006	Ortiz et al.
2005/0010213 A1	1/2005	Stad et al.	2006/0049229 A1	3/2006	Milliman et al.
2005/0032511 A1	2/2005	Malone et al.	2006/0052825 A1	3/2006	Ransick et al.
2005/0033357 A1	2/2005	Braun	2006/0060630 A1	3/2006	Shelton, IV et al.
2005/0054946 A1	3/2005	Krzyzanowski	2006/0064086 A1	3/2006	Odom
2005/0059997 A1	3/2005	Bauman et al.	2006/0079115 A1	4/2006	Aranyi et al.
2005/0070929 A1	3/2005	Dalessandro et al.	2006/0079735 A1	4/2006	Martone et al.
2005/0075561 A1	4/2005	Golden	2006/0085031 A1	4/2006	Bettuchi
2005/0080454 A1	4/2005	Drews et al.	2006/0085033 A1	4/2006	Criscuolo et al.
2005/0085693 A1	4/2005	Belson et al.	2006/0086032 A1	4/2006	Valencic et al.
2005/0090817 A1	4/2005	Phan	2006/0087746 A1	4/2006	Lipow
2005/0096683 A1	5/2005	Ellins et al.	2006/0089535 A1	4/2006	Raz et al.
2005/0101952 A1*	5/2005	Lands et al. .... 606/51	2006/0100643 A1	5/2006	Laufer et al.
2005/0103819 A1	5/2005	Racenet et al.	2006/0108393 A1	5/2006	Heinrich et al.
2005/0107814 A1	5/2005	Johnston et al.	2006/0111711 A1	5/2006	Goble
2005/0107824 A1	5/2005	Hillstead et al.	2006/0111723 A1	5/2006	Chapolini et al.
2005/0113820 A1	5/2005	Goble et al.	2006/0122636 A1	6/2006	Bailey et al.
2005/0119525 A1	6/2005	Takemoto	2006/0142772 A1	6/2006	Ralph et al.
2005/0119669 A1	6/2005	Demmy	2006/0149163 A1	7/2006	Hibner et al.
2005/0124855 A1	6/2005	Jaffe et al.	2006/0161185 A1	7/2006	Saadat et al.
2005/0125009 A1	6/2005	Perry et al.	2006/0167471 A1	7/2006	Phillips
2005/0125897 A1	6/2005	Wyslucha et al.	2006/0173470 A1	8/2006	Oray et al.
2005/0131173 A1	6/2005	McDaniel et al.	2006/0178556 A1	8/2006	Hasser et al.
2005/0131211 A1	6/2005	Bayley et al.	2006/0180634 A1	8/2006	Shelton, IV et al.
2005/0131390 A1	6/2005	Heinrich et al.	2006/0185682 A1	8/2006	Marczyk
2005/0131436 A1	6/2005	Johnston et al.	2006/0200123 A1	9/2006	Ryan
2005/0131437 A1	6/2005	Johnston et al.	2006/0201989 A1	9/2006	Ojeda
2005/0131457 A1	6/2005	Douglas et al.	2006/0212069 A1	9/2006	Shelton, IV
2005/0137454 A1	6/2005	Saadat et al.	2006/0217729 A1	9/2006	Eskridge et al.
2005/0137455 A1	6/2005	Ewers et al.	2006/0226196 A1	10/2006	Hueil et al.
2005/0143759 A1	6/2005	Kelly	2006/0235368 A1	10/2006	Oz
2005/0143769 A1	6/2005	White et al.	2006/0235469 A1	10/2006	Viola
2005/0145675 A1	7/2005	Hartwick et al.	2006/0241655 A1	10/2006	Viola
2005/0154258 A1	7/2005	Tartaglia et al.	2006/0241692 A1	10/2006	McGuckin, Jr. et al.
2005/0154406 A1	7/2005	Bombard et al.	2006/0244460 A1	11/2006	Weaver
2005/0165419 A1	7/2005	Sauer et al.	2006/0252993 A1	11/2006	Freed et al.
2005/0165435 A1	7/2005	Johnston et al.	2006/0253069 A1	11/2006	Li et al.
2005/0169974 A1	8/2005	Tenerz et al.	2006/0258904 A1	11/2006	Stefanchik et al.
2005/0171522 A1	8/2005	Christopherson	2006/0258910 A1	11/2006	Stefanchik et al.
2005/0177181 A1	8/2005	Kagan et al.	2006/0259073 A1	11/2006	Miyamoto et al.
2005/0182298 A1	8/2005	Ikeda et al.	2006/0264927 A1	11/2006	Ryan
2005/0187545 A1	8/2005	Hooven et al.	2006/0264929 A1	11/2006	Goble et al.
2005/0187572 A1	8/2005	Johnston et al.	2006/0271042 A1	11/2006	Latterell et al.
2005/0187576 A1	8/2005	Whitman et al.	2006/0271102 A1	11/2006	Bosshard et al.
2005/0189397 A1	9/2005	Jankowski	2006/0278680 A1	12/2006	Viola et al.
2005/0192609 A1	9/2005	Whitman et al.	2006/0278681 A1	12/2006	Viola et al.
2005/0192628 A1	9/2005	Viola	2006/0284730 A1	12/2006	Schmid et al.
2005/0203550 A1	9/2005	Laufer et al.	2006/0287576 A1	12/2006	Tsuji et al.
2005/0216055 A1	9/2005	Scirica et al.	2006/0289602 A1	12/2006	Wales et al.
2005/0228224 A1	10/2005	Okada et al.	2006/0291981 A1	12/2006	Viola et al.
2005/0240178 A1	10/2005	Morley et al.	2007/0010838 A1	1/2007	Shelton, IV et al.
2005/0240222 A1	10/2005	Shipp	2007/0023476 A1	2/2007	Whitman et al.
2005/0245965 A1	11/2005	Orban, III et al.	2007/0023477 A1	2/2007	Whitman et al.
2005/0251128 A1	11/2005	Amoah	2007/0026039 A1	2/2007	Drumheller et al.
2005/0256452 A1	11/2005	DeMarchi et al.	2007/0027468 A1	2/2007	Wales et al.
2005/0256522 A1	11/2005	Francischelli et al.	2007/0027472 A1	2/2007	Hiles et al.
2005/0261676 A1	11/2005	Hall et al.	2007/0027551 A1	2/2007	Farnsworth et al.
2005/0261677 A1	11/2005	Hall et al.	2007/0034668 A1	2/2007	Holsten et al.
2005/0263563 A1	12/2005	Racenet et al.	2007/0049966 A1	3/2007	Bonadio et al.
2005/0267455 A1	12/2005	Eggers et al.	2007/0051375 A1	3/2007	Milliman
2005/0274768 A1	12/2005	Cummins et al.	2007/0055219 A1	3/2007	Whitman et al.
2005/0283188 A1	12/2005	Loshakove et al.	2007/0066981 A1	3/2007	Meagher
2006/0004407 A1	1/2006	Hiles et al.	2007/0070574 A1	3/2007	Nerheim et al.
2006/0008787 A1	1/2006	Hayman et al.	2007/0073341 A1	3/2007	Smith
2006/0011699 A1	1/2006	Olson et al.	2007/0078484 A1	4/2007	Talarico et al.
			2007/0083193 A1	4/2007	Werneth et al.
			2007/0084897 A1	4/2007	Shelton, IV et al.
			2007/0093869 A1	4/2007	Bloom et al.
			2007/0102472 A1	5/2007	Shelton, IV



(56)

References Cited

U.S. PATENT DOCUMENTS

2007/0106113 A1	5/2007	Ravo	2008/0228029 A1	9/2008	Mikkaichi et al.
2007/0106317 A1	5/2007	Shelton, IV et al.	2008/0245841 A1	10/2008	Smith et al.
2007/0118175 A1	5/2007	Butler et al.	2008/0251568 A1	10/2008	Zemlok et al.
2007/0129605 A1	6/2007	Schaaf	2008/0251569 A1	10/2008	Smith et al.
2007/0135686 A1	6/2007	Pruitt, Jr. et al.	2008/0255413 A1	10/2008	Zemlok et al.
2007/0135803 A1	6/2007	Belson	2008/0255607 A1	10/2008	Zemlok
2007/0155010 A1	7/2007	Farnsworth et al.	2008/0262654 A1	10/2008	Omori et al.
2007/0158358 A1	7/2007	Mason, II et al.	2008/0283570 A1	11/2008	Boyden et al.
2007/0170225 A1	7/2007	Shelton, IV et al.	2008/0287944 A1	11/2008	Pearson et al.
2007/0173687 A1	7/2007	Shima et al.	2008/0290134 A1	11/2008	Bettuchi et al.
2007/0173806 A1	7/2007	Orszulak et al.	2008/0294179 A1	11/2008	Balbierz et al.
2007/0173813 A1	7/2007	Odom	2008/0296346 A1	12/2008	Shelton, IV et al.
2007/0175950 A1	8/2007	Shelton, IV et al.	2008/0297287 A1	12/2008	Shachar et al.
2007/0175951 A1	8/2007	Shelton, IV et al.	2008/0308602 A1	12/2008	Timm et al.
2007/0175955 A1	8/2007	Shelton, IV et al.	2008/0308603 A1	12/2008	Shelton, IV et al.
2007/0179528 A1	8/2007	Soltz et al.	2008/0308604 A1 *	12/2008	Timm et al. .... 227/175.1
2007/0181632 A1	8/2007	Milliman	2008/0308608 A1	12/2008	Prommersberger
2007/0194079 A1	8/2007	Hueil et al.	2008/0314960 A1	12/2008	Marczyk et al.
2007/0194082 A1	8/2007	Morgan et al.	2008/0315829 A1	12/2008	Jones et al.
2007/0203510 A1	8/2007	Bettuchi	2009/0001121 A1	1/2009	Hess et al.
2007/0213750 A1	9/2007	Weadock	2009/0001122 A1	1/2009	Prommersberger et al.
2007/0219571 A1	9/2007	Balbierz et al.	2009/0001130 A1	1/2009	Hess et al.
2007/0221700 A1	9/2007	Ortiz et al.	2009/0005807 A1	1/2009	Hess et al.
2007/0225562 A1	9/2007	Spivey et al.	2009/0005809 A1	1/2009	Hess et al.
2007/0233163 A1	10/2007	Bombard et al.	2009/0012534 A1	1/2009	Madhani et al.
2007/0239028 A1	10/2007	Houser et al.	2009/0018553 A1	1/2009	McLean et al.
2007/0243227 A1	10/2007	Gertner	2009/0020958 A1	1/2009	Soul
2007/0244471 A1	10/2007	Malackowski	2009/0048589 A1	2/2009	Takashino et al.
2007/0246505 A1	10/2007	Pace-Florida et al.	2009/0048612 A1	2/2009	Farritor et al.
2007/0249999 A1	10/2007	Sklar et al.	2009/0054908 A1	2/2009	Zand et al.
2007/0260278 A1	11/2007	Wheeler et al.	2009/0076506 A1	3/2009	Baker
2007/0270784 A1	11/2007	Smith et al.	2009/0078736 A1	3/2009	Van Lue
2007/0270884 A1	11/2007	Smith et al.	2009/0082789 A1	3/2009	Milliman et al.
2007/0276409 A1	11/2007	Ortiz et al.	2009/0088774 A1	4/2009	Swarup et al.
2007/0279011 A1	12/2007	Jones et al.	2009/0090763 A1	4/2009	Zemlok et al.
2007/0286892 A1	12/2007	Herzberg et al.	2009/0092651 A1	4/2009	Shah et al.
2007/0287993 A1	12/2007	Hinman et al.	2009/0093728 A1	4/2009	Hyde et al.
2007/0288044 A1	12/2007	Jinno et al.	2009/0099876 A1	4/2009	Whitman
2007/0299427 A1	12/2007	Yeung et al.	2009/0108048 A1	4/2009	Zemlok et al.
2008/0015598 A1	1/2008	Prommersberger	2009/0112229 A1	4/2009	Omori et al.
2008/0029570 A1	2/2008	Shelton et al.	2009/0114701 A1	5/2009	Zemlok et al.
2008/0029573 A1	2/2008	Shelton et al.	2009/0143805 A1	6/2009	Palmer et al.
2008/0029574 A1	2/2008	Shelton et al.	2009/0143855 A1	6/2009	Weber et al.
2008/0029575 A1	2/2008	Shelton et al.	2009/0149871 A9	6/2009	Kagan et al.
2008/0030170 A1	2/2008	Dacquay et al.	2009/0157067 A1	6/2009	Kane et al.
2008/0035701 A1	2/2008	Racenet et al.	2009/0157087 A1	6/2009	Wei et al.
2008/0041916 A1	2/2008	Milliman et al.	2009/0171147 A1	7/2009	Lee et al.
2008/0041917 A1	2/2008	Racenet et al.	2009/0188964 A1	7/2009	Orlov
2008/0078802 A1	4/2008	Hess et al.	2009/0198272 A1	8/2009	Kerver et al.
2008/0082114 A1	4/2008	McKenna et al.	2009/0204108 A1	8/2009	Steffen
2008/0082125 A1	4/2008	Murray et al.	2009/0206125 A1	8/2009	Huitema et al.
2008/0082126 A1	4/2008	Murray et al.	2009/0206126 A1	8/2009	Huitema et al.
2008/0083808 A1	4/2008	Scirica	2009/0206131 A1	8/2009	Weisenburgh, II et al.
2008/0083813 A1	4/2008	Zemlok et al.	2009/0206133 A1	8/2009	Morgan et al.
2008/0085296 A1	4/2008	Powell et al.	2009/0206137 A1	8/2009	Hall et al.
2008/0086078 A1	4/2008	Powell et al.	2009/0206139 A1	8/2009	Hall et al.
2008/0114315 A1	5/2008	Voegele et al.	2009/0206141 A1	8/2009	Huitema et al.
2008/0114385 A1	5/2008	Byrum et al.	2009/0206142 A1	8/2009	Huitema et al.
2008/0128469 A1	6/2008	Dalessandro et al.	2009/0213685 A1	8/2009	Mak et al.
2008/0129253 A1	6/2008	Shiue et al.	2009/0242610 A1	10/2009	Shelton, IV et al.
2008/0140115 A1	6/2008	Stopek	2009/0255974 A1	10/2009	Viola
2008/0154299 A1	6/2008	Livneh	2009/0255975 A1	10/2009	Zemlok et al.
2008/0169328 A1	7/2008	Shelton	2009/0255976 A1	10/2009	Marczyk et al.
2008/0169332 A1	7/2008	Shelton et al.	2009/0255977 A1	10/2009	Zemlok
2008/0169333 A1	7/2008	Shelton et al.	2009/0255978 A1	10/2009	Viola et al.
2008/0172087 A1	7/2008	Fuchs et al.	2009/0270895 A1	10/2009	Churchill et al.
2008/0172088 A1	7/2008	Smith et al.	2009/0277949 A1	11/2009	Viola et al.
2008/0183193 A1	7/2008	Omori et al.	2009/0292283 A1	11/2009	Odom
2008/0185419 A1	8/2008	Smith et al.	2009/0308907 A1	12/2009	Nalagatla et al.
2008/0190989 A1	8/2008	Crews et al.	2010/0010511 A1	1/2010	Harris et al.
2008/0197167 A1	8/2008	Viola et al.	2010/0012704 A1	1/2010	Tarinelli Racenet et al.
2008/0200762 A1	8/2008	Stokes et al.	2010/0023024 A1	1/2010	Zeiner et al.
2008/0200835 A1	8/2008	Monson et al.	2010/0036370 A1	2/2010	Mirel et al.
2008/0200933 A1	8/2008	Bakos et al.	2010/0049084 A1	2/2010	Nock et al.
2008/0200949 A1	8/2008	Hiles et al.	2010/0057087 A1	3/2010	Cha
			2010/0057107 A1	3/2010	Sorrentino et al.
			2010/0069942 A1	3/2010	Shelton, IV
			2010/0072254 A1	3/2010	Aranyi et al.
			2010/0076475 A1	3/2010	Yates et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2010/0076483	A1	3/2010	Imuta	2011/0253765	A1	10/2011	Nicholas et al.	
2010/0076489	A1	3/2010	Stopek et al.	2011/0275901	A1	11/2011	Shelton, IV	
2010/0087840	A1	4/2010	Ebersole et al.	2011/0276083	A1	11/2011	Shelton, IV et al.	
2010/0094091	A1 *	4/2010	Cappola ..... 600/137	2011/0278343	A1	11/2011	Knodel et al.	
2010/0094289	A1	4/2010	Taylor et al.	2011/0282339	A1 *	11/2011	Weizman et al. .... 606/33	
2010/0096431	A1	4/2010	Smith et al.	2011/0282446	A1	11/2011	Schulte et al.	
2010/0108740	A1	5/2010	Pastorelli et al.	2011/0288573	A1	11/2011	Yates et al.	
2010/0108741	A1	5/2010	Hessler et al.	2011/0290851	A1	12/2011	Shelton, IV	
2010/0133317	A1	6/2010	Shelton, IV et al.	2011/0290853	A1	12/2011	Shelton, IV et al.	
2010/0145146	A1	6/2010	Melder	2011/0290856	A1	12/2011	Shelton, IV et al.	
2010/0147921	A1	6/2010	Olson	2011/0293690	A1	12/2011	Griffin et al.	
2010/0147922	A1	6/2010	Olson	2011/0295242	A1	12/2011	Spivey et al.	
2010/0147923	A1	6/2010	D'Agostino et al.	2011/0295269	A1	12/2011	Swensgard et al.	
2010/0163598	A1	7/2010	Belzer	2011/0295295	A1	12/2011	Shelton, IV et al.	
2010/0179022	A1	7/2010	Shirokoshi	2012/0004636	A1	1/2012	Lo	
2010/0179540	A1	7/2010	Marczyk et al.	2012/0022523	A1	1/2012	Smith et al.	
2010/0186219	A1	7/2010	Smith	2012/0022630	A1	1/2012	Wübbeling	
2010/0193566	A1	8/2010	Scheib et al.	2012/0029272	A1	2/2012	Shelton, IV et al.	
2010/0193567	A1 *	8/2010	Scheib et al. .... 227/176.1	2012/0046692	A1	2/2012	Smith et al.	
2010/0200637	A1	8/2010	Beetel	2012/0071711	A1	3/2012	Shelton, IV et al.	
2010/0204717	A1	8/2010	Knodel	2012/0074200	A1	3/2012	Schmid et al.	
2010/0222901	A1	9/2010	Swayze et al.	2012/0080332	A1	4/2012	Shelton, IV et al.	
2010/0230465	A1	9/2010	Smith et al.	2012/0080336	A1	4/2012	Shelton, IV et al.	
2010/0243707	A1	9/2010	Olson et al.	2012/0080337	A1	4/2012	Shelton, IV et al.	
2010/0243708	A1	9/2010	Aranyi et al.	2012/0080338	A1	4/2012	Shelton, IV et al.	
2010/0249519	A1	9/2010	Park et al.	2012/0080340	A1	4/2012	Shelton, IV et al.	
2010/0258611	A1	10/2010	Smith et al.	2012/0080344	A1	4/2012	Shelton, IV	
2010/0268030	A1	10/2010	Viola et al.	2012/0080475	A1	4/2012	Smith et al.	
2010/0276471	A1	11/2010	Whitman	2012/0080478	A1	4/2012	Morgan et al.	
2010/0292540	A1	11/2010	Hess et al.	2012/0080484	A1	4/2012	Morgan et al.	
2010/0294827	A1	11/2010	Boyden et al.	2012/0080485	A1	4/2012	Woodard, Jr. et al.	
2010/0298636	A1	11/2010	Casto et al.	2012/0080486	A1	4/2012	Woodard, Jr. et al.	
2010/0305552	A1	12/2010	Shelton, IV et al.	2012/0080488	A1	4/2012	Shelton, IV et al.	
2010/0312261	A1	12/2010	Suzuki et al.	2012/0080491	A1	4/2012	Shelton, IV et al.	
2010/0320252	A1	12/2010	Viola et al.	2012/0080498	A1	4/2012	Shelton, IV et al.	
2010/0331856	A1	12/2010	Carlson et al.	2012/0080499	A1	4/2012	Schall et al.	
2010/0331880	A1	12/2010	Stopek	2012/0080502	A1	4/2012	Morgan et al.	
2011/0003528	A1	1/2011	Lam	2012/0083835	A1	4/2012	Shelton, IV et al.	
2011/0006099	A1	1/2011	Hall et al.	2012/0083836	A1	4/2012	Shelton, IV et al.	
2011/0006101	A1	1/2011	Hall et al.	2012/0138658	A1	6/2012	Ullrich et al.	
2011/0011916	A1	1/2011	Levine	2012/0150192	A1	6/2012	Dachs, II et al.	
2011/0017799	A1	1/2011	Whitman et al.	2012/0175398	A1	7/2012	Sandborn et al.	
2011/0017801	A1	1/2011	Zemlok et al.	2012/0187179	A1	7/2012	Gleiman	
2011/0022032	A1	1/2011	Zemlok et al.	2012/0199632	A1	8/2012	Spivey et al.	
2011/0024477	A1	2/2011	Hall	2012/0209289	A1	8/2012	Duque et al.	
2011/0024478	A1	2/2011	Shelton, IV	2012/0223123	A1	9/2012	Baxter, III et al.	
2011/0024479	A1	2/2011	Swensgard et al.	2012/0234890	A1	9/2012	Aronhalt et al.	
2011/0034918	A1	2/2011	Reschke	2012/0234891	A1	9/2012	Aronhalt et al.	
2011/0036887	A1	2/2011	Zemlok et al.	2012/0234892	A1	9/2012	Aronhalt et al.	
2011/0036890	A1	2/2011	Ma	2012/0234895	A1	9/2012	O'Connor et al.	
2011/0036891	A1	2/2011	Zemlok et al.	2012/0234897	A1	9/2012	Shelton, IV et al.	
2011/0045047	A1	2/2011	Bennett et al.	2012/0234898	A1	9/2012	Shelton, IV et al.	
2011/0060363	A1	3/2011	Hess et al.	2012/0234899	A1	9/2012	Scheib et al.	
2011/0084112	A1	4/2011	Kostrzewski	2012/0238823	A1	9/2012	Hagerty et al.	
2011/0087276	A1	4/2011	Bedi et al.	2012/0238824	A1	9/2012	Widenhouse et al.	
2011/0087279	A1	4/2011	Shah et al.	2012/0239010	A1	9/2012	Shelton, IV et al.	
2011/0095068	A1	4/2011	Patel	2012/0241491	A1	9/2012	Aldridge et al.	
2011/0101065	A1	5/2011	Milliman	2012/0241492	A1	9/2012	Shelton, IV et al.	
2011/0114697	A1	5/2011	Baxter, III et al.	2012/0241493	A1	9/2012	Baxter, III et al.	
2011/0118754	A1	5/2011	Dachs, II et al.	2012/0241496	A1	9/2012	Mandakolathur Vasudevan et al.	
2011/0118778	A1	5/2011	Burbank	2012/0241497	A1	9/2012	Mandakolathur Vasudevan et al.	
2011/0125176	A1	5/2011	Yates et al.	2012/0241498	A1	9/2012	Gonzalez et al.	
2011/0125177	A1	5/2011	Yates et al.	2012/0241499	A1	9/2012	Baxter, III et al.	
2011/0144430	A1	6/2011	Spivey et al.	2012/0241500	A1	9/2012	Timmer et al.	
2011/0144640	A1	6/2011	Heinrich et al.	2012/0241501	A1	9/2012	Swayze et al.	
2011/0147433	A1	6/2011	Shelton, IV et al.	2012/0241502	A1	9/2012	Aldridge et al.	
2011/0155786	A1	6/2011	Shelton, IV	2012/0241503	A1	9/2012	Baxter, III et al.	
2011/0155787	A1	6/2011	Baxter, III et al.	2012/0241505	A1	9/2012	Alexander, III et al.	
2011/0163146	A1	7/2011	Ortiz et al.	2012/0248169	A1	10/2012	Widenhouse et al.	
2011/0174099	A1	7/2011	Ross et al.	2012/0253298	A1	10/2012	Henderson et al.	
2011/0174861	A1	7/2011	Shelton, IV et al.	2012/0265176	A1	10/2012	Braun	
2011/0178536	A1	7/2011	Kostrzewski	2012/0273550	A1	11/2012	Scirica	
2011/0184459	A1	7/2011	Malkowski et al.	2012/0283707	A1	11/2012	Giordano et al.	
2011/0192882	A1	8/2011	Hess et al.	2012/0283748	A1	11/2012	Ortiz et al.	
2011/0210156	A1	9/2011	Smith et al.	2012/0289979	A1	11/2012	Eskaros et al.	
				2012/0292367	A1	11/2012	Morgan et al.	
				2012/0296333	A1	11/2012	Twomey	
				2012/0298719	A1	11/2012	Shelton, IV et al.	
				2012/0298722	A1	11/2012	Hess et al.	

(56)

References Cited

U.S. PATENT DOCUMENTS

2012/0310255 A1	12/2012	Brisson et al.	2013/0256369 A1	10/2013	Schmid et al.
2012/0310256 A1	12/2012	Brisson	2013/0256371 A1	10/2013	Shelton, IV et al.
2012/0312860 A1	12/2012	Ming et al.	2013/0256372 A1	10/2013	Baxter, III et al.
2012/0318842 A1	12/2012	Anim et al.	2013/0256373 A1	10/2013	Schmid et al.
2012/0318843 A1	12/2012	Henderson et al.	2013/0256374 A1	10/2013	Shelton, IV et al.
2012/0318844 A1	12/2012	Shelton, IV et al.	2013/0256375 A1	10/2013	Shelton, IV et al.
2012/0325892 A1	12/2012	Kostrzewski	2013/0256376 A1	10/2013	Barton et al.
2013/0018361 A1	1/2013	Bryant	2013/0256377 A1	10/2013	Schmid et al.
2013/0020375 A1	1/2013	Shelton, IV et al.	2013/0256378 A1	10/2013	Schmid et al.
2013/0020376 A1	1/2013	Shelton, IV et al.	2013/0256379 A1	10/2013	Schmid et al.
2013/0023861 A1	1/2013	Shelton, IV et al.	2013/0256380 A1	10/2013	Schmid et al.
2013/0023915 A1*	1/2013	Mueller ..... 606/170	2013/0256382 A1	10/2013	Swayze et al.
2013/0026208 A1	1/2013	Shelton, IV et al.	2013/0256383 A1	10/2013	Aronhalt et al.
2013/0026210 A1	1/2013	Shelton, IV et al.	2013/0261648 A1	10/2013	Laurent et al.
2013/0037596 A1	2/2013	Bear et al.	2013/0270322 A1	10/2013	Scheib et al.
2013/0048697 A1	2/2013	Shelton, IV et al.	2013/0277412 A1	10/2013	Gresham et al.
2013/0056518 A1	3/2013	Swensgard	2013/0310873 A1	11/2013	Stopek (nee Prommersberger) et al.
2013/0056521 A1	3/2013	Swensgard	2013/0313303 A1	11/2013	Shelton, IV et al.
2013/0062391 A1	3/2013	Boudreaux et al.	2013/0313304 A1	11/2013	Shelton, IV et al.
2013/0075448 A1	3/2013	Schmid et al.	2013/0313306 A1	11/2013	Shelton, IV et al.
2013/0075449 A1	3/2013	Schmid et al.	2013/0324981 A1	12/2013	Smith et al.
2013/0075450 A1	3/2013	Schmid et al.	2013/0324982 A1	12/2013	Smith et al.
2013/0079814 A1	3/2013	Hess et al.	2013/0327809 A1	12/2013	Shelton, IV et al.
2013/0087597 A1	4/2013	Shelton, IV et al.	2013/0327810 A1	12/2013	Swayze et al.
2013/0087599 A1	4/2013	Krumanaker et al.	2013/0334278 A1	12/2013	Kerr et al.
2013/0087602 A1	4/2013	Olson et al.	2013/0334283 A1	12/2013	Swayze et al.
2013/0098970 A1	4/2013	Racenet et al.	2013/0334284 A1	12/2013	Swayze et al.
2013/0103024 A1	4/2013	Monson et al.	2013/0334285 A1	12/2013	Swayze et al.
2013/0116668 A1	5/2013	Shelton, IV et al.	2013/0334286 A1	12/2013	Swayze et al.
2013/0116669 A1	5/2013	Shelton, IV et al.	2013/0334287 A1	12/2013	Shelton, IV
2013/0119108 A1	5/2013	Altman et al.	2013/0334288 A1	12/2013	Shelton, IV
2013/0123822 A1	5/2013	Wellman et al.	2013/0341374 A1	12/2013	Shelton, IV et al.
2013/0126581 A1	5/2013	Yates et al.	2014/0000411 A1	1/2014	Shelton, IV et al.
2013/0126582 A1	5/2013	Shelton, IV et al.	2014/0001231 A1	1/2014	Shelton, IV et al.
2013/0146641 A1	6/2013	Shelton, IV et al.	2014/0001234 A1	1/2014	Shelton, IV et al.
2013/0146642 A1	6/2013	Shelton, IV et al.	2014/0001235 A1	1/2014	Shelton, IV
2013/0146643 A1	6/2013	Schmid et al.	2014/0001236 A1	1/2014	Shelton, IV et al.
2013/0150832 A1	6/2013	Belson et al.	2014/0001237 A1	1/2014	Shelton, IV et al.
2013/0153633 A1	6/2013	Casasanta, Jr. et al.	2014/0001238 A1	1/2014	Shelton, IV et al.
2013/0153634 A1	6/2013	Carter et al.	2014/0001239 A1	1/2014	Shelton, IV et al.
2013/0153636 A1	6/2013	Shelton, IV et al.	2014/0001240 A1	1/2014	Shelton, IV et al.
2013/0153638 A1	6/2013	Carter et al.	2014/0005640 A1	1/2014	Shelton, IV et al.
2013/0153641 A1	6/2013	Shelton, IV et al.	2014/0005653 A1	1/2014	Shelton, IV et al.
2013/0161374 A1	6/2013	Swayze et al.	2014/0005661 A1	1/2014	Shelton, IV et al.
2013/0161375 A1	6/2013	Huitema et al.	2014/0005676 A1	1/2014	Shelton, IV et al.
2013/0168435 A1	7/2013	Huang et al.	2014/0005678 A1	1/2014	Shelton, IV et al.
2013/0172929 A1	7/2013	Hess et al.	2014/0005679 A1	1/2014	Shelton, IV et al.
2013/0175317 A1	7/2013	Yates et al.	2014/0005680 A1	1/2014	Shelton, IV et al.
2013/0175322 A1	7/2013	Yates et al.	2014/0005693 A1	1/2014	Shelton, IV et al.
2013/0181033 A1	7/2013	Shelton, IV et al.	2014/0005694 A1	1/2014	Shelton, IV et al.
2013/0181034 A1	7/2013	Shelton, IV et al.	2014/0005695 A1	1/2014	Shelton, IV
2013/0184718 A1	7/2013	Smith et al.	2014/0005702 A1	1/2014	Timm et al.
2013/0184719 A1	7/2013	Shelton, IV et al.	2014/0005708 A1	1/2014	Shelton, IV
2013/0186932 A1	7/2013	Shelton, IV et al.	2014/0005718 A1	1/2014	Shelton, IV et al.
2013/0186933 A1	7/2013	Shelton, IV et al.	2014/0008414 A1	1/2014	Shelton, IV et al.
2013/0186934 A1	7/2013	Shelton, IV et al.	2014/0014705 A1	1/2014	Baxter, III
2013/0186936 A1	7/2013	Shelton, IV	2014/0042205 A1	2/2014	Baxter, III et al.
2013/0190733 A1	7/2013	Giordano et al.	2014/0048582 A1	2/2014	Shelton, IV et al.
2013/0190757 A1	7/2013	Yates et al.	2014/0061279 A1	3/2014	Laurent et al.
2013/0193188 A1	8/2013	Shelton, IV et al.	2014/0097227 A1	4/2014	Aronhalt et al.
2013/0193189 A1	8/2013	Swensgard et al.	2014/0107640 A1	4/2014	Yates et al.
2013/0197556 A1	8/2013	Shelton, IV et al.	2014/0128850 A1	5/2014	Kerr et al.
2013/0200132 A1	8/2013	Moore et al.	2014/0151433 A1	6/2014	Shelton, IV et al.
2013/0206814 A1	8/2013	Morgan et al.	2014/0151434 A1	6/2014	Shelton, IV et al.
2013/0214030 A1	8/2013	Aronhalt et al.	2014/0166722 A1	6/2014	Hess et al.
2013/0221063 A1	8/2013	Aronhalt et al.	2014/0166724 A1	6/2014	Schellin et al.
2013/0221064 A1	8/2013	Aronhalt et al.	2014/0166725 A1	6/2014	Schellin et al.
2013/0221065 A1	8/2013	Aronhalt et al.	2014/0166726 A1	6/2014	Schellin et al.
2013/0233906 A1	9/2013	Hess et al.	2014/0171966 A1	6/2014	Giordano et al.
2013/0248576 A1	9/2013	Laurent et al.	2014/0175152 A1	6/2014	Hess et al.
2013/0248577 A1	9/2013	Leimbach et al.	2014/0175154 A1	6/2014	Shelton, IV et al.
2013/0256365 A1	10/2013	Shelton, IV et al.	2014/0175155 A1	6/2014	Shelton, IV et al.
2013/0256366 A1	10/2013	Shelton, IV et al.	2014/0191014 A1	7/2014	Shelton, IV
2013/0256367 A1	10/2013	Scheib et al.	2014/0191015 A1	7/2014	Shelton, IV
2013/0256368 A1	10/2013	Timm et al.	2014/0197223 A1	7/2014	Hess et al.
			2014/0205637 A1	7/2014	Widenhouse et al.
			2014/0207166 A1	7/2014	Shelton, IV et al.
			2014/0224686 A1	8/2014	Aronhalt et al.

(56)

## References Cited

## U.S. PATENT DOCUMENTS

2014/0224857	A1	8/2014	Schmid	CA	2639177	A1	2/2009
2014/0236184	A1	8/2014	Leimbach et al.	CN	2488482	Y	5/2002
2014/0243865	A1	8/2014	Swayze et al.	CN	1523725	A	8/2004
2014/0246471	A1	9/2014	Jaworek et al.	CN	1634601	A	7/2005
2014/0246472	A1	9/2014	Kimsey et al.	CN	1726874	A	2/2006
2014/0246473	A1	9/2014	Auld	CN	1868411	A	11/2006
2014/0246474	A1	9/2014	Hall et al.	CN	1915180	A	2/2007
2014/0246475	A1	9/2014	Hall et al.	CN	1960679	A	5/2007
2014/0246476	A1	9/2014	Hall et al.	CN	101011286	A	8/2007
2014/0246477	A1	9/2014	Koch, Jr. et al.	CN	101095621	A	1/2008
2014/0246478	A1	9/2014	Baber et al.	CN	101023879	B	3/2013
2014/0246479	A1	9/2014	Baber et al.	DE	273689	C	5/1914
2014/0249557	A1	9/2014	Koch, Jr. et al.	DE	1775926	A	1/1972
2014/0252066	A1	9/2014	Shelton, IV et al.	DE	3212828	A1	11/1982
2014/0252067	A1	9/2014	Moore et al.	DE	3709067	A1	9/1988
2014/0252068	A1	9/2014	Shelton, IV et al.	DE	9412228	U	9/1994
2014/0252069	A1	9/2014	Moore et al.	DE	19509116	A1	9/1996
2014/0252071	A1	9/2014	Moore et al.	DE	19851291	A1	1/2000
2014/0259591	A1	9/2014	Shelton, IV et al.	DE	19924311	A1	11/2000
2014/0263537	A1	9/2014	Leimbach et al.	DE	69328576	T2	1/2001
2014/0263538	A1	9/2014	Leimbach et al.	DE	10052679	A1	5/2001
2014/0263539	A1	9/2014	Leimbach et al.	DE	201112837	U1	10/2001
2014/0263541	A1	9/2014	Leimbach et al.	DE	10314072	A1	10/2004
2014/0263542	A1	9/2014	Leimbach et al.	EP	0000756	A1	2/1979
2014/0263543	A1	9/2014	Leimbach et al.	EP	0122046	A1	10/1984
2014/0263551	A1	9/2014	Hall et al.	EP	0156774	A2	10/1985
2014/0263552	A1	9/2014	Hall et al.	EP	0387980	B1	10/1985
2014/0263553	A1	9/2014	Leimbach et al.	EP	0033548	B1	5/1986
2014/0263554	A1	9/2014	Leimbach et al.	EP	0077262	B1	8/1986
2014/0263564	A1	9/2014	Leimbach et al.	EP	0129442	B1	11/1987
2014/0263565	A1	9/2014	Lytte, IV et al.	EP	0276104	A2	7/1988
2014/0263571	A1	9/2014	Morgan et al.	EP	0178940	B1	1/1991
2014/0263572	A1	9/2014	Shelton, IV et al.	EP	0178941	B1	1/1991
2014/0277017	A1	9/2014	Leimbach et al.	EP	0169044	B1	6/1991
2014/0284371	A1	9/2014	Morgan et al.	EP	0248844	B1	1/1993
2014/0284373	A1	9/2014	Shelton, IV et al.	EP	0539762	A1	5/1993
2014/0291378	A1	10/2014	Shelton, IV et al.	EP	0545029	A1	6/1993
2014/0291379	A1	10/2014	Schellin et al.	EP	0277959	B1	10/1993
2014/0291380	A1	10/2014	Weaner et al.	EP	0233940	B1	11/1993
2014/0291381	A1	10/2014	Weaner et al.	EP	0261230	B1	11/1993
2014/0291382	A1	10/2014	Lloyd et al.	EP	0639349	A2	2/1994
2014/0291383	A1	10/2014	Spivey et al.	EP	0324636	B1	3/1994
2014/0296873	A1	10/2014	Morgan et al.	EP	0593920	A1	4/1994
2014/0296874	A1	10/2014	Morgan et al.	EP	0594148	A1	4/1994
2014/0299648	A1	10/2014	Shelton, IV et al.	EP	0427949	B1	6/1994
2014/0299649	A1	10/2014	Shelton, IV et al.	EP	0523174	B1	6/1994
2014/0303645	A1	10/2014	Morgan et al.	EP	0600182	A2	6/1994
2014/0303646	A1	10/2014	Morgan et al.	EP	0310431	B1	11/1994
2014/0305986	A1	10/2014	Hall et al.	EP	0375302	B1	11/1994
2014/0305987	A1	10/2014	Parihar et al.	EP	0376562	B1	11/1994
2014/0305988	A1	10/2014	Boudreaux et al.	EP	0630612	A1	12/1994
2014/0305989	A1	10/2014	Parihar et al.	EP	0634144	A1	1/1995
2014/0305990	A1	10/2014	Shelton, IV et al.	EP	0646356	A2	4/1995
2014/0305991	A1	10/2014	Parihar et al.	EP	0646357	A1	4/1995
2014/0305992	A1	10/2014	Kimsey et al.	EP	0505036	B1	5/1995
2014/0305993	A1	10/2014	Timm et al.	EP	0653189	A2	5/1995
2014/0305994	A1	10/2014	Parihar et al.	EP	0669104	A1	8/1995
2014/0305995	A1	10/2014	Shelton, IV et al.	EP	0511470	B1	10/1995
2014/0309665	A1	10/2014	Parihar et al.	EP	0674876	A2	10/1995
2014/0309666	A1	10/2014	Shelton, IV et al.	EP	0679367	A2	11/1995
2014/0326777	A1	11/2014	Zingman	EP	0392547	B1	12/1995
2014/0330161	A1	11/2014	Swayze et al.	EP	0685204	A1	12/1995
2014/0352463	A1	12/2014	Parihar	EP	0364216	B1	1/1996
2014/0353358	A1	12/2014	Shelton, IV et al.	EP	0699418	A1	3/1996
2014/0353359	A1	12/2014	Hall et al.	EP	0702937	A1	3/1996
2014/0367447	A1	12/2014	Woodard, Jr. et al.	EP	0705571	A1	4/1996
2015/0008248	A1	1/2015	Giordano et al.	EP	0711611	A2	5/1996
				EP	0484677	B2	6/1996
				EP	0541987	B1	7/1996
				EP	0667119	B1	7/1996
				EP	0737446	A1	10/1996
				EP	0748614	A1	12/1996
				EP	0708618	B1	3/1997
				EP	0770355	A1	5/1997
				EP	0503662	B1	6/1997
				EP	0447121	B1	7/1997
AU	2012200178	B2	7/2013	EP	0621009	B1	7/1997
CA	2458946	A1	3/2003	EP	0625077	B1	7/1997
CA	2512960	A1	1/2006	EP	0633749	B1	8/1997
CA	2514274	A1	1/2006				

## FOREIGN PATENT DOCUMENTS

(56)

## References Cited

## FOREIGN PATENT DOCUMENTS

EP	0710090	B1	8/1997	EP	1459695	A1	9/2004
EP	0578425	B1	9/1997	EP	1254636	B1	10/2004
EP	0625335	B1	11/1997	EP	1473819	A1	11/2004
EP	0552423	B1	1/1998	EP	1477119	A1	11/2004
EP	0592244	B1	1/1998	EP	1479345	A1	11/2004
EP	0648476	B1	1/1998	EP	1479347	A1	11/2004
EP	0649290	B1	3/1998	EP	1479348	A1	11/2004
EP	0598618	B1	9/1998	EP	0754437	B2	12/2004
EP	0676173	B1	9/1998	EP	1025807	B1	12/2004
EP	0678007	B1	9/1998	EP	1001710	B1	1/2005
EP	0869104	A1	10/1998	EP	1520521	A1	4/2005
EP	0603472	B1	11/1998	EP	1520522	A1	4/2005
EP	0605351	B1	11/1998	EP	1520523	A1	4/2005
EP	0878169	A1	11/1998	EP	1520525	A1	4/2005
EP	0879742	A1	11/1998	EP	1522264	A1	4/2005
EP	0695144	B1	12/1998	EP	1523942	A2	4/2005
EP	0722296	B1	12/1998	EP	1550408	A1	7/2005
EP	0760230	B1	2/1999	EP	1557129	A1	7/2005
EP	0623316	B1	3/1999	EP	1064883	B1	8/2005
EP	0650701	B1	3/1999	EP	1067876	B1	8/2005
EP	0537572	B1	6/1999	EP	0870473	B1	9/2005
EP	0923907	A1	6/1999	EP	1157666	B1	9/2005
EP	0640317	A1	9/1999	EP	0880338	B1	10/2005
EP	0843906	B1	3/2000	EP	1158917	B1	11/2005
EP	0552050	B1	5/2000	EP	1344498	B1	11/2005
EP	0833592	B1	5/2000	EP	0906764	B1	12/2005
EP	0832605	B1	6/2000	EP	1330989	B1	12/2005
EP	0830094	B1	9/2000	EP	0771176	B2	1/2006
EP	1034747	A1	9/2000	EP	1621138	A2	2/2006
EP	1034748	A1	9/2000	EP	1621139	A2	2/2006
EP	0694290	B1	11/2000	EP	1621141	A2	2/2006
EP	1050278	A1	11/2000	EP	1621145	A2	2/2006
EP	1053719	A1	11/2000	EP	1621151	A2	2/2006
EP	1053720	A1	11/2000	EP	1034746	B1	3/2006
EP	1055399	A1	11/2000	EP	1201196	B1	3/2006
EP	1055400	A1	11/2000	EP	1632191	A2	3/2006
EP	1080694	A1	3/2001	EP	1647231	A1	4/2006
EP	1090592	A1	4/2001	EP	1065981	B1	5/2006
EP	1095627	A1	5/2001	EP	1082944	B1	5/2006
EP	1256318	B1	5/2001	EP	1230899	B1	5/2006
EP	0806914	B1	9/2001	EP	1652481	A2	5/2006
EP	0768840	B1	12/2001	EP	1382303	B1	6/2006
EP	0908152	B1	1/2002	EP	1253866	B1	7/2006
EP	0872213	B1	5/2002	EP	1032318	B1	8/2006
EP	0862386	B1	6/2002	EP	1045672	B1	8/2006
EP	0949886	B1	9/2002	EP	1617768	B1	8/2006
EP	1238634	A2	9/2002	EP	1693015	A2	8/2006
EP	0858295	B1	12/2002	EP	1400214	B1	9/2006
EP	0656188	B1	1/2003	EP	1702567	A2	9/2006
EP	0717960	B1	2/2003	EP	1129665	B1	11/2006
EP	1284120	A1	2/2003	EP	1400206	B1	11/2006
EP	1287788	A1	3/2003	EP	1721568	A1	11/2006
EP	0717966	B1	4/2003	EP	1256317	B1	12/2006
EP	0869742	B1	5/2003	EP	1285633	B1	12/2006
EP	0829235	B1	6/2003	EP	1728473	A1	12/2006
EP	0887046	B1	7/2003	EP	1728475	A2	12/2006
EP	0852480	B1	8/2003	EP	1736105	A1	12/2006
EP	0891154	B1	9/2003	EP	1011494	B1	1/2007
EP	0813843	B1	10/2003	EP	1479346	B1	1/2007
EP	0873089	B1	10/2003	EP	1484024	B1	1/2007
EP	0856326	B1	11/2003	EP	1749485	A1	2/2007
EP	1374788	A1	1/2004	EP	1754445	A2	2/2007
EP	0741996	B1	2/2004	EP	1759812	A1	3/2007
EP	0814712	B1	2/2004	EP	1767157	A1	3/2007
EP	1402837	A1	3/2004	EP	1767163	A1	3/2007
EP	0705570	B1	4/2004	EP	1769756	A1	4/2007
EP	0959784	B1	4/2004	EP	1769758	A1	4/2007
EP	1407719	A2	4/2004	EP	1581128	B1	5/2007
EP	1086713	B1	5/2004	EP	1780825	A1	5/2007
EP	0996378	B1	6/2004	EP	1785097	A2	5/2007
EP	1426012	A1	6/2004	EP	1790293	A2	5/2007
EP	0833593	B2	7/2004	EP	1790294	A1	5/2007
EP	1442694	A1	8/2004	EP	1563793	B1	6/2007
EP	0888749	B1	9/2004	EP	1800610	A1	6/2007
EP	0959786	B1	9/2004	EP	1300117	B1	8/2007
				EP	1813199	A1	8/2007
				EP	1813200	A2	8/2007
				EP	1813201	A1	8/2007
				EP	1813202	A1	8/2007

(56)

## References Cited

## FOREIGN PATENT DOCUMENTS

EP	1813203	A2	8/2007	EP	1878395	B1	1/2010
EP	1813207	A1	8/2007	EP	2151204	A1	2/2010
EP	1813209	A1	8/2007	EP	1813211	B1	3/2010
EP	1330991	B1	9/2007	EP	2165656	A2	3/2010
EP	1837041	A1	9/2007	EP	2165660	A2	3/2010
EP	0922435	B1	10/2007	EP	1566150	B1	4/2010
EP	1487359	B1	10/2007	EP	1813206	B1	4/2010
EP	1599146	B1	10/2007	EP	1769754	B1	6/2010
EP	1839596	A1	10/2007	EP	1854416	B1	6/2010
EP	2110083	A2	10/2007	EP	2198787	A1	6/2010
EP	1679096	B1	11/2007	EP	1647286	B1	9/2010
EP	1857057	A2	11/2007	EP	1825821	B1	9/2010
EP	1402821	B1	12/2007	EP	1535565	B1	10/2010
EP	1872727	A1	1/2008	EP	1702570	B1	10/2010
EP	1550410	B1	2/2008	EP	1785098	B1	10/2010
EP	1671593	B1	2/2008	EP	2005896	B1	10/2010
EP	1897502	A1	3/2008	EP	2030578	B1	11/2010
EP	1611856	B1	4/2008	EP	2036505	B1	11/2010
EP	1908417	A2	4/2008	EP	2245993	A2	11/2010
EP	1330201	B1	6/2008	EP	1627605	B1	12/2010
EP	1702568	B1	7/2008	EP	2027811	B1	12/2010
EP	1943955	A2	7/2008	EP	2130498	B1	12/2010
EP	1943957	A2	7/2008	EP	2263568	A2	12/2010
EP	1943959	A1	7/2008	EP	1994890	B1	1/2011
EP	1943962	A2	7/2008	EP	2005900	B1	1/2011
EP	1943964	A1	7/2008	EP	2286738	A2	2/2011
EP	1943976	A2	7/2008	EP	1690502	B1	3/2011
EP	1593337	B1	8/2008	EP	2292153	A1	3/2011
EP	1970014	A1	9/2008	EP	1769755	B1	4/2011
EP	1980213	A2	10/2008	EP	2090240	B1	4/2011
EP	1759645	B1	11/2008	EP	2305135	A1	4/2011
EP	1987780	A2	11/2008	EP	2314254	A2	4/2011
EP	1990014	A2	11/2008	EP	2316366	A2	5/2011
EP	1552795	B1	12/2008	EP	1813205	B1	6/2011
EP	1693008	B1	12/2008	EP	2090243	B1	6/2011
EP	1759640	B1	12/2008	EP	2329773	A1	6/2011
EP	1997439	A2	12/2008	EP	2353545	A1	8/2011
EP	2000102	A2	12/2008	EP	2361562	A1	8/2011
EP	2005894	A2	12/2008	EP	1836986	B1	11/2011
EP	2005901	A1	12/2008	EP	1908414	B1	11/2011
EP	2008595	A2	12/2008	EP	2153781	B1	11/2011
EP	1736104	B1	3/2009	EP	2389928	A2	11/2011
EP	1749486	B1	3/2009	EP	1847225	B1	12/2011
EP	1782743	B1	3/2009	EP	2399538	A2	12/2011
EP	2039302	A2	3/2009	EP	1785102	B1	1/2012
EP	2039308	A2	3/2009	EP	2090253	B1	3/2012
EP	2039316	A2	3/2009	EP	2430986	A2	3/2012
EP	1721576	B1	4/2009	EP	2457519	A1	5/2012
EP	1733686	B1	4/2009	EP	2462880	A2	6/2012
EP	2044890	A1	4/2009	EP	1813204	B1	7/2012
EP	1550409	B1	6/2009	EP	2189121	B1	7/2012
EP	1550413	B1	6/2009	EP	2005895	B1	8/2012
EP	1719461	B1	6/2009	EP	2090248	B1	8/2012
EP	1834594	B1	6/2009	EP	2481359	A1	8/2012
EP	1709911	B1	7/2009	EP	1935351	B1	9/2012
EP	2077093	A2	7/2009	EP	2497431	A1	9/2012
EP	1745748	B1	8/2009	EP	1616549	B1	10/2012
EP	2090231	A1	8/2009	EP	2030579	B1	10/2012
EP	2090237	A1	8/2009	EP	2090252	B1	10/2012
EP	2090241	A1	8/2009	EP	2517637	A1	10/2012
EP	2090244	A2	8/2009	EP	2517638	A1	10/2012
EP	2090245	A1	8/2009	EP	2517642	A2	10/2012
EP	2090254	A1	8/2009	EP	2517645	A2	10/2012
EP	2090256	A2	8/2009	EP	2517649	A2	10/2012
EP	2095777	A2	9/2009	EP	2517651	A2	10/2012
EP	2098170	A2	9/2009	EP	1884206	B1	3/2013
EP	2110082	A1	10/2009	EP	2090238	B1	4/2013
EP	2111803	A2	10/2009	EP	1982657	B1	7/2013
EP	1762190	B8	11/2009	EP	2090234	B1	9/2013
EP	1813208	B1	11/2009	EP	2633830	A1	9/2013
EP	1908426	B1	11/2009	EP	2644124	A1	10/2013
EP	2116195	A1	11/2009	EP	2644209	A2	10/2013
EP	1607050	B1	12/2009	EP	2700367	A1	2/2014
EP	1815804	B1	12/2009	EP	1772105	B1	5/2014
EP	1875870	B1	12/2009	ES	2396594	T3	2/2013
				FR	1112936	A	3/1956
				FR	2598905	A1	11/1987
				FR	2765794	A	1/1999
				FR	2815842		10/2000

(56)

## References Cited

FOREIGN PATENT DOCUMENTS							
GB	939929	A	10/1963	JP	2004-329624	A	11/2004
GB	1210522	A	10/1970	JP	2004-337617	A	12/2004
GB	1217159	A	12/1970	JP	2004-344663		12/2004
GB	1339394	A	12/1973	JP	2005-028147	A	2/2005
GB	2024012	A	1/1980	JP	2005-28148	A	2/2005
GB	2109241	A	6/1983	JP	2005-028149	A	2/2005
GB	2272159	A	5/1994	JP	2005-505309	A	2/2005
GB	2284242	A	5/1995	JP	2005505322	T	2/2005
GB	2286435	A	8/1995	JP	2005-103280	A	4/2005
GB	2336214	A	10/1999	JP	2005-103281	A	4/2005
GB	2425903	A	11/2006	JP	2005-511131	A	4/2005
GR	93100110	A	11/1993	JP	2005103293	A	4/2005
JP	50-33988	U	4/1975	JP	2005131163	A	5/2005
JP	S 58500053	A	1/1983	JP	2005131164	A	5/2005
JP	60-100955	A	6/1985	JP	2005131173	A	5/2005
JP	61-98249	A	5/1986	JP	2005131211	A	5/2005
JP	S 61502036	A	9/1986	JP	2005131212	A	5/2005
JP	S 63-59764	A	3/1988	JP	2005-137919	A	6/2005
JP	S 63-147449	A	6/1988	JP	2005-144183	A	6/2005
JP	63-203149		8/1988	JP	2005-516714	A	6/2005
JP	H 02-279149	A	11/1990	JP	2005137423	A	6/2005
JP	3-12126	A	1/1991	JP	2005152416	A	6/2005
JP	H 05-084252	A	4/1993	JP	2005-521109	A	7/2005
JP	5-212039	A	8/1993	JP	2005-523105	A	8/2005
JP	6007357	A	1/1994	JP	4461008	B2	8/2005
JP	H 6-30945	A	2/1994	JP	2005524474	A	8/2005
JP	H 06-26812	U	4/1994	JP	2005-296412	A	10/2005
JP	H 6-121798	A	5/1994	JP	2005-328882	A	12/2005
JP	H 06-197901	A	7/1994	JP	2005-335432	A	12/2005
JP	H 06-237937	A	8/1994	JP	2005-342267	A	12/2005
JP	7-31623	A	2/1995	JP	2006-034975	A	2/2006
JP	7051273	A	2/1995	JP	2006-34977	A	2/2006
JP	7-124166	A	5/1995	JP	2006-034978	A	2/2006
JP	H 7-163574	A	6/1995	JP	2006-034980	A	2/2006
JP	07-171163		7/1995	JP	2006-506106	A	2/2006
JP	7-255735	A	10/1995	JP	2006-187649	A	7/2006
JP	H 7-285089	A	10/1995	JP	2006-218297	A	8/2006
JP	8-33642	A	2/1996	JP	2006-223872	A	8/2006
JP	8033641	A	2/1996	JP	2006-281405	A	10/2006
JP	8-164141	A	6/1996	JP	2006-334417	A	12/2006
JP	H 08-182684	A	7/1996	JP	2006-346445	A	12/2006
JP	H 08-507708	A	8/1996	JP	2007-61628	A	3/2007
JP	8229050	A	9/1996	JP	2007-098130	A	4/2007
JP	H 09-501081	A	2/1997	JP	2007-105481	A	4/2007
JP	H 09-501577	A	2/1997	JP	3906843	B2	4/2007
JP	H 09-164144	A	6/1997	JP	2007-117725	A	5/2007
JP	H 10-11890	A	5/1998	JP	2007-130471	A	5/2007
JP	10-512469	A	12/1998	JP	2007-222615	A	6/2007
JP	2000-14632		1/2000	JP	2007-203051	A	8/2007
JP	2000033071	A	2/2000	JP	2007-203057	A	8/2007
JP	2000-112002	A	4/2000	JP	2007-524435	A	8/2007
JP	2000-166932	A	6/2000	JP	2007-229448	A	9/2007
JP	2000171730	A	6/2000	JP	4001860	B2	10/2007
JP	2000287987	A	10/2000	JP	2007-325922	A	12/2007
JP	2000325303	A	11/2000	JP	2008-68073	A	3/2008
JP	2001-046384	A	2/2001	JP	2008-206967	A	9/2008
JP	2001-87272	A	4/2001	JP	2008-212637	A	9/2008
JP	2001-514541	A	9/2001	JP	2008-212638	A	9/2008
JP	2001-517473	A	10/2001	JP	2008-259860	A	10/2008
JP	2001286477	A	10/2001	JP	2008-264535	A	11/2008
JP	2002-51974	A	2/2002	JP	2008-283459	A	11/2008
JP	2002143078	A	5/2002	JP	2009-502351	A	1/2009
JP	2002-528161	A	9/2002	JP	2009-506799	A	2/2009
JP	2002369820	A	12/2002	JP	2009-72599	A	4/2009
JP	2003-500153	A	1/2003	JP	2009-090113	A	4/2009
JP	2003-504104	A	2/2003	JP	2009-106752	A	5/2009
JP	2003-135473	A	5/2003	JP	2009-189836	A	8/2009
JP	2003-164066		6/2003	JP	2009-189838	A	8/2009
JP	2003-521301	A	7/2003	JP	2009-539420	A	11/2009
JP	2004-162035	A	6/2004	JP	2010-098844	A	4/2010
JP	2004-229976	A	8/2004	JP	4549018	B2	9/2010
JP	2004-524076	A	8/2004	JP	4783373	B2	7/2011
JP	2004-531280	A	10/2004	JP	5140421	B2	2/2013
JP	2004-532084	A	10/2004	JP	5162595	B2	3/2013
JP	2004-532676	A	10/2004	JP	2013-128791	A	7/2013
				JP	5333899	B2	11/2013
				RU	1814161	A1	5/1993
				RU	2008830	C1	3/1994
				RU	2052979	C1	1/1996

(56)

## References Cited

FOREIGN PATENT DOCUMENTS			
RU	2141279	C1	11/1999
RU	2144791	C1	1/2000
RU	2181566	C2	4/2002
RU	2187249	C2	8/2002
RU	2189091	C2	9/2002
RU	32984	U1	10/2003
RU	2225170	C2	3/2004
RU	42750	U1	12/2004
RU	61114	U1	2/2007
SU	189517	A	1/1967
SU	328636	A	9/1972
SU	674747	A1	7/1979
SU	886900	A1	12/1981
SU	1009439	A	4/1983
SU	1022703	A1	5/1983
SU	1333319	A2	8/1987
SU	1377053	A1	2/1988
SU	1561964	A1	5/1990
SU	1722476	A1	3/1992
SU	1752361	A1	8/1992
WO	WO 82/02824	A1	9/1982
WO	WO 86/02254	A1	4/1986
WO	WO 91/15157	A1	10/1991
WO	WO 92/20295	A1	11/1992
WO	WO 92/21300	A1	12/1992
WO	WO 93/08755	A1	5/1993
WO	WO 93/13718	A1	7/1993
WO	WO 93/14690	A1	8/1993
WO	WO 93/15648	A1	8/1993
WO	WO 93/15850	A1	8/1993
WO	WO 93/19681	A1	10/1993
WO	WO 94/00060	A1	1/1994
WO	WO 94/11057	A1	5/1994
WO	WO 94/12108	A1	6/1994
WO	WO 94/18893	A1	9/1994
WO	WO 94/20030	A1	9/1994
WO	WO 94/22378	A1	10/1994
WO	WO 94/23659	A1	10/1994
WO	WO 94/24943	A1	11/1994
WO	WO 94/24947	A1	11/1994
WO	WO 95/02369	A1	1/1995
WO	WO 95/03743	A1	2/1995
WO	WO 95/06817	A1	3/1995
WO	WO 95/09576	A1	4/1995
WO	WO 95/09577	A1	4/1995
WO	WO 95/14436	A1	6/1995
WO	WO 95/17855	A1	7/1995
WO	WO 95/18383	A1	7/1995
WO	WO 95/18572	A1	7/1995
WO	WO 95/19739	A1	7/1995
WO	WO 95/20360	A1	8/1995
WO	WO 95/23557	A1	9/1995
WO	WO 95/24865	A1	9/1995
WO	WO 95/25471	A3	9/1995
WO	WO 95/26562	A1	10/1995
WO	WO 95/29639	A1	11/1995
WO	WO 96/04858	A1	2/1996
WO	WO 96/18344	A2	6/1996
WO	WO 96/19151	A1	6/1996
WO	WO 96/19152	A1	6/1996
WO	WO 96/20652	A1	7/1996
WO	WO 96/21119	A1	7/1996
WO	WO 96/22055	A1	7/1996
WO	WO 96/23448	A1	8/1996
WO	WO 96/24301	A1	8/1996
WO	WO 96/27337	A1	9/1996
WO	WO 96/31155	A1	10/1996
WO	WO 96/35464	A1	11/1996
WO	WO 96/39085	A1	12/1996
WO	WO 96/39086	A1	12/1996
WO	WO 96/39087	A1	12/1996
WO	WO 96/39088	A1	12/1996
WO	WO 96/39089	A1	12/1996
WO	WO 97/00646	A1	1/1997
WO	WO 97/00647	A1	1/1997
WO	WO 97/01989	A1	1/1997
WO	WO 97/06582	A1	2/1997
WO	WO 97/10763	A1	3/1997
WO	WO 97/10764	A1	3/1997
WO	WO 97/11648	A2	4/1997
WO	WO 97/11649	A1	4/1997
WO	WO 97/15237	A1	5/1997
WO	WO 97/24073	A1	7/1997
WO	WO 97/24993	A1	7/1997
WO	WO 97/30644	A1	8/1997
WO	WO 97/34533	A1	9/1997
WO	WO 97/37598	A1	10/1997
WO	WO 97/39688	A2	10/1997
WO	WO 98/01080	A1	1/1998
WO	WO 98/17180	A1	4/1998
WO	WO 98/27880	A1	7/1998
WO	WO 98/30153	A1	7/1998
WO	WO 98/47436	A1	10/1998
WO	WO 99/03407	A1	1/1999
WO	WO 99/03408	A1	1/1999
WO	WO 99/03409	A1	1/1999
WO	WO 99/12483	A1	3/1999
WO	WO 99/12487	A1	3/1999
WO	WO 99/12488	A1	3/1999
WO	WO 99/15086	A1	4/1999
WO	WO 99/15091	A1	4/1999
WO	WO 99/23933	A2	5/1999
WO	WO 99/23959	A1	5/1999
WO	WO 99/25261	A1	5/1999
WO	WO 99/29244	A1	6/1999
WO	WO 99/34744	A1	7/1999
WO	WO 99/45849	A1	9/1999
WO	WO 99/48430	A1	9/1999
WO	WO 99/51158	A1	10/1999
WO	WO 00/24322	A1	5/2000
WO	WO 00/24330	A1	5/2000
WO	WO 00/41638	A1	7/2000
WO	WO 00/48506	A1	8/2000
WO	WO 00/53112	A2	9/2000
WO	WO 00/54653	A1	9/2000
WO	WO 00/57796	A1	10/2000
WO	WO 00/64365	A1	11/2000
WO	WO 00/72762	A1	12/2000
WO	WO 00/72765	A1	12/2000
WO	WO 01/03587	A1	1/2001
WO	WO 01/05702	A1	1/2001
WO	WO 01/10482	A1	2/2001
WO	WO 01/35845	A1	5/2001
WO	WO 01/54594	A1	8/2001
WO	WO 01/58371	A1	8/2001
WO	WO 01/62158	A2	8/2001
WO	WO 01/62161	A1	8/2001
WO	WO 01/62162	A1	8/2001
WO	WO 01/62164	A2	8/2001
WO	WO 01/62169	A2	8/2001
WO	WO 01/78605	A2	10/2001
WO	WO 01/80757	A2	11/2001
WO	WO 01/91646	A1	12/2001
WO	WO 02/00121	A1	1/2002
WO	WO 02/07608	A2	1/2002
WO	WO 02/07618	A1	1/2002
WO	WO 02/17799	A1	3/2002
WO	WO 02/19920	A1	3/2002
WO	WO 02/19932	A1	3/2002
WO	WO 02/26143	A1	4/2002
WO	WO 02/30297	A2	4/2002
WO	WO 02/32322	A2	4/2002
WO	WO 02/36028	A1	5/2002
WO	WO 02/43571	A2	6/2002
WO	WO 02/058568	A1	8/2002
WO	WO 02/060328	A1	8/2002
WO	WO 02/067785	A2	9/2002
WO	WO 02/085218	A2	10/2002
WO	WO 02/087586	A1	11/2002
WO	WO 02/098302	A1	12/2002
WO	WO 03/000138	A2	1/2003
WO	WO 03/001329	A2	1/2003
WO	WO 03/001986	A2	1/2003
WO	WO 03/013363	A1	2/2003



(56)

## References Cited

## FOREIGN PATENT DOCUMENTS

WO WO 03/013372 A2 2/2003  
 WO WO 03/015604 A2 2/2003  
 WO WO 03/020106 A2 3/2003  
 WO WO 03/020139 A2 3/2003  
 WO WO 03/024339 A1 3/2003  
 WO WO 03/079909 A3 3/2003  
 WO WO 03/030743 A2 4/2003  
 WO WO 03/037193 A1 5/2003  
 WO WO 03/047436 A3 6/2003  
 WO WO 03/055402 A1 7/2003  
 WO WO 03/057048 A1 7/2003  
 WO WO 03/057058 A1 7/2003  
 WO WO 03/063694 A1 8/2003  
 WO WO 03/077769 A1 9/2003  
 WO WO 03/079911 A1 10/2003  
 WO WO 03/082126 A1 10/2003  
 WO WO 03/086206 A1 10/2003  
 WO WO 03/088845 A2 10/2003  
 WO WO 03/090630 A2 11/2003  
 WO WO 03/094743 A1 11/2003  
 WO WO 03/094745 A1 11/2003  
 WO WO 03/094746 A1 11/2003  
 WO WO 03/094747 A1 11/2003  
 WO WO 03/101313 A1 12/2003  
 WO WO 03/105698 A2 12/2003  
 WO WO 03/105702 A2 12/2003  
 WO WO 2004/006980 A2 1/2004  
 WO WO 2004/011037 A2 2/2004  
 WO WO 2004/019769 A1 3/2004  
 WO WO 2004/019803 A1 3/2004  
 WO WO 2004/021868 A2 3/2004  
 WO WO 2004/028585 A2 4/2004  
 WO WO 2004/030554 A1 4/2004  
 WO WO 2004/032754 A2 4/2004  
 WO WO 2004/032760 A2 4/2004  
 WO WO 2004/032762 A1 4/2004  
 WO WO 2004/032763 A2 4/2004  
 WO WO 2004/032783 A1 4/2004  
 WO WO 2004/034875 A2 4/2004  
 WO WO 2004/047626 A1 6/2004  
 WO WO 2004/047653 A2 6/2004  
 WO WO 2004/049956 A2 6/2004  
 WO WO 2004/052426 A2 6/2004  
 WO WO 2004/056276 A1 7/2004  
 WO WO 2004/056277 A1 7/2004  
 WO WO 2004/062516 A1 7/2004  
 WO WO 2004/064600 A2 8/2004  
 WO WO 2004/078050 A2 9/2004  
 WO WO 2004/078051 A2 9/2004  
 WO WO 2004/078236 A2 9/2004  
 WO WO 2004/086987 A1 10/2004  
 WO WO 2004/096015 A2 11/2004  
 WO WO 2004/096057 A2 11/2004  
 WO WO 2004/103157 A2 12/2004  
 WO WO 2004/105593 A1 12/2004  
 WO WO 2004/105621 A1 12/2004  
 WO WO 2004/112618 A2 12/2004  
 WO WO 2004/112652 A2 12/2004  
 WO WO 2005/027983 A2 3/2005  
 WO WO 2005/037329 A2 4/2005  
 WO WO 2005/042041 A1 5/2005  
 WO WO 2005/044078 A2 5/2005  
 WO WO 2005/055846 A1 6/2005  
 WO WO 2005/072634 A2 8/2005  
 WO WO 2005/078892 A1 8/2005  
 WO WO 2005/079675 A2 9/2005  
 WO WO 2005/096954 A2 10/2005  
 WO WO 2005/112806 A2 12/2005  
 WO WO 2005/112808 A1 12/2005  
 WO WO 2005/115251 A1 12/2005  
 WO WO 2005/115253 A2 12/2005  
 WO WO 2005/117735 A1 12/2005  
 WO WO 2005/122936 A1 12/2005  
 WO WO 2006/023486 A1 3/2006  
 WO WO 2006/023578 A2 3/2006

WO WO 2006/027014 A1 3/2006  
 WO WO 2006/028314 A1 3/2006  
 WO WO 2006/044490 A2 4/2006  
 WO WO 2006/044581 A2 4/2006  
 WO WO 2006/044810 A2 4/2006  
 WO WO 2006/051252 A1 5/2006  
 WO WO 2006/059067 A1 6/2006  
 WO WO 2006/083748 A1 8/2006  
 WO WO 2006/092563 A1 9/2006  
 WO WO 2006/092565 A1 9/2006  
 WO WO 2006/115958 A1 11/2006  
 WO WO 2006/125940 A1 11/2006  
 WO WO 2006/132992 A2 12/2006  
 WO WO 2007/002180 A2 1/2007  
 WO WO 2007/016290 A2 2/2007  
 WO WO 2007/018898 A2 2/2007  
 WO WO 2007/089603 A2 8/2007  
 WO WO 2007/098220 A2 8/2007  
 WO WO 2007/121579 A1 11/2007  
 WO WO 2007/131110 A2 11/2007  
 WO WO 2007/137304 A2 11/2007  
 WO WO 2007/139734 A2 12/2007  
 WO WO 2007/142625 A2 12/2007  
 WO WO 2007/145825 A2 12/2007  
 WO WO 2007/146987 A2 12/2007  
 WO WO 2007/147439 A1 12/2007  
 WO WO 2008/020964 A2 2/2008  
 WO WO 2008/021969 A2 2/2008  
 WO WO 2008/039249 A1 4/2008  
 WO WO 2008/039270 A1 4/2008  
 WO WO 2008/045383 A2 4/2008  
 WO WO 2008/057281 A2 5/2008  
 WO WO 2008/070763 A1 6/2008  
 WO WO 2008/089404 A2 7/2008  
 WO WO 2008/101080 A1 8/2008  
 WO WO 2008/101228 A2 8/2008  
 WO WO 2008/109125 A1 9/2008  
 WO WO 2008/124748 A1 10/2008  
 WO WO 2009/022614 A1 2/2009  
 WO WO 2009/023851 A1 2/2009  
 WO WO 2009/033057 A2 3/2009  
 WO WO 2009/046394 A1 4/2009  
 WO WO 2009/067649 A2 5/2009  
 WO WO 2009/091497 A2 7/2009  
 WO WO 2009/137761 A2 11/2009  
 WO WO 2009/143092 A1 11/2009  
 WO WO 2009/143331 A1 11/2009  
 WO WO 2009/150650 A2 12/2009  
 WO WO 2010/028332 A2 3/2010  
 WO WO 2010/030434 A1 3/2010  
 WO WO 2010/050771 A2 5/2010  
 WO WO 2010/054404 A1 5/2010  
 WO WO 2010/063795 A1 6/2010  
 WO WO 2010/098871 A2 9/2010  
 WO WO 2011/008672 A2 1/2011  
 WO WO 2011/044343 A2 4/2011  
 WO WO 2011/060311 A2 5/2011  
 WO WO 2012/006306 A2 1/2012  
 WO WO 2012/021671 A1 2/2012  
 WO WO 2012/040438 A1 3/2012  
 WO WO 2012/044551 A1 4/2012  
 WO WO 2012/044554 A1 4/2012  
 WO WO 2012/044606 A2 4/2012  
 WO WO 2012/044820 A1 4/2012  
 WO WO 2012/044844 A2 4/2012  
 WO WO 2012/044853 A1 4/2012  
 WO WO 2012/068156 A2 5/2012  
 WO WO 2012/148667 A2 11/2012  
 WO WO 2012/148703 A2 11/2012  
 WO WO 2013/043707 A2 3/2013  
 WO WO 2013/043717 A1 3/2013

## OTHER PUBLICATIONS

Disclosed Anonymously, "Motor-Driven Surgical Stapler Improvements," Research Disclosure Database No. 526041, Published: Feb. 2008.

C.C. Thompson et al., "Peroral Endoscopic Reduction of Dilated Gastrojejunal Anastomosis After Roux-en-Y Gastric Bypass: A Possible New Option for Patients with Weight Regain," *Surg Endosc* (2006) vol. 20, pp. 1744-1748.

(56)

## References Cited

## OTHER PUBLICATIONS

B.R. Coolman, DVM, MS et al., "Comparison of Skin Staples With Sutures for Anastomosis of the Small Intestine in Dogs," Abstract; <http://www.blackwell-synergy.com/doi/abs/10.1053/jvet.2000.7539?cookieSet=1&journalCode=vsu> which redirects to <http://www3.interscience.wiley.com/journal/119040681/abstract?CRETRY=1&SRETRY=0>; [online] accessed: Sep. 22, 2008 (2 pages).

The Soderm Aseptic Battery Transfer Kit, Soderm Systems, (2000), 3 pages.

"Biomedical Coatings," Fort Wayne Metals, Research Products Corporation, obtained online at [www.fwmetals.com](http://www.fwmetals.com) on Jun. 21, 2010 (1 page).

Van Meer et al., "A Disposable Plastic Compact Wrist for Smart Minimally Invasive Surgical Tools," LAAS/CNRS (Aug. 2005).

Breedveld et al., "A New, Easily Miniaturized Sterrable Endoscope," IEEE Engineering in Medicine and Biology Magazine (Nov./Dec. 2005).

D. Tuite, Ed., "Get the Lowdown on Ultracapacitors," Nov. 15, 2007; [online] URL: <http://electronicdesign.com/Articles/Print.cfm?ArticleID=17465>, accessed Jan. 15, 2008 (5 pages).

Datasheet for Panasonic TK Relays Ultra Low Profile 2 A Polarized Relay, Copyright Matsushita Electric Works, Ltd. (Known of at least as early as Aug. 17, 2010), 5 pages.

ASTM procedure D2240-00, "Standard Test Method for Rubber Property-Durometer Hardness," (Published Aug. 2000).

ASTM procedure D2240-05, "Standard Test Method for Rubber Property-Durometer Hardness," (Published Apr. 2010).

Covidien Brochure, "Endo GIA™ Reloads with Tri-Staple™ Technology," (2010), 1 page.

Covidien Brochure, "Endo GIA™ Reloads with Tri-Staple™ Technology and Endo GIA™ Ultra Universal Staplers," (2010), 2 pages.

Covidien Brochure, "Endo GIA™ Black Reload with Tri-Staple™ Technology," (2012), 2 pages.

Covidien Brochure, "Endo GIA™ Curved Tip Reload with Tri-Staple™ Technology," (2012), 2 pages.

Covidien Brochure, "Endo GIA™ Reloads with Tri-Staple™ Technology," (2010), 2 pages.

Covidien Brochure, "Endo GIA™ Ultra Universal Stapler," (2010), 2 pages.

Miyata et al., "Biomolecule-Sensitive Hydrogels," *Advanced Drug Delivery Reviews*, 54 (2002) pp. 79-98.

Jeong et al., "Thermosensitive Sol-Gel Reversible Hydrogels," *Advanced Drug Delivery Reviews*, 54 (2002) pp. 37-51.

Byrne et al., "Molecular Imprinting Within Hydrogels," *Advanced Drug Delivery Reviews*, 54 (2002) pp. 149-161.

Qiu et al., "Environment-Sensitive Hydrogels for Drug Delivery," *Advanced Drug Delivery Reviews*, 53 (2001) pp. 321-339.

Hoffman, "Hydrogels for Biomedical Applications," *Advanced Drug Delivery Reviews*, 43 (2002) pp. 3-12.

Hoffman, "Hydrogels for Biomedical Applications," *Advanced Drug Delivery Reviews*, 54 (2002) pp. 3-12.

Peppas, "Physiologically Responsive Hydrogels," *Journal of Bioactive and Compatible Polymers*, vol. 6 (Jul. 1991) pp. 241-246.

Ebara, "Carbohydrate-Derived Hydrogels and Microgels," *Engineered Carbohydrate-Based Materials for Biomedical Applications: Polymers, Surfaces, Dendrimers, Nanoparticles, and Hydrogels*, Edited by Ravin Narain, 2011, pp. 337-345.

Peppas, Editor "Hydrogels in Medicine and Pharmacy," vol. I, *Fundamentals*, CRC Press, 1986.

Matsuda, "Thermodynamics of Formation of Porous Polymeric Membrane from Solutions," *Polymer Journal*, vol. 23, No. 5, pp. 435-444 (1991).

Young, "Microcellular foams via phase separation," *Journal of Vacuum Science & Technology A* 4(3), (May/June. 1986).

Chen et al., "Elastomeric Biomaterials for Tissue Engineering," *Progress in Polymer Science* 38 (2013), pp. 584-671.

Pitt et al., "Attachment of Hyaluronan to Metallic Surfaces," *J. Biomed. Mater. Res.* 68A: pp. 95-106, 2004.

Schellhammer et al., "Poly-Lactic-Acid for Coating of Endovascular Stents: Preliminary Results in Canine Experimental Av-Fistulae," *Mat.-wiss. u. Werkstofftech.*, 32, pp. 193-199 (2001).

Solorio et al., "Gelatin Microspheres Crosslinked with Genipin for Local Delivery of Growth Factors," *J. Tissue Eng. Regen. Med.* (2010), 4(7): pp. 514-523.

U.S. Appl. No. 12/031,573, filed Feb. 14, 2008.

U.S. Appl. No. 14/187,383, filed Feb. 24, 2014.

U.S. Appl. No. 14/187,386, filed Feb. 24, 2014.

U.S. Appl. No. 14/187,390, filed Feb. 24, 2014.

U.S. Appl. No. 14/187,385, filed Feb. 24, 2014.

U.S. Appl. No. 14/187,384, filed Feb. 24, 2014.

U.S. Appl. No. 14/187,389, filed Feb. 24, 2014.

U.S. Appl. No. 14/498,070, filed Sep. 26, 2014.

U.S. Appl. No. 14/498,087, filed Sep. 26, 2014.

U.S. Appl. No. 14/498,105, filed Sep. 26, 2014.

U.S. Appl. No. 14/498,107, filed Sep. 26, 2014.

U.S. Appl. No. 14/498,121, filed Sep. 26, 2014.

U.S. Appl. No. 14/498,145, filed Sep. 26, 2014.

U.S. Appl. No. 14/318,996, filed Jun. 30, 2014.

U.S. Appl. No. 14/319,006, filed Jun. 30, 2014.

U.S. Appl. No. 14/319,014, filed Jun. 30, 2014.

U.S. Appl. No. 14/318,991, filed Jun. 30, 2014.

U.S. Appl. No. 14/319,004, filed Jun. 30, 2014.

U.S. Appl. No. 14/319,008, filed Jun. 30, 2014.

U.S. Appl. No. 14/318,997, filed Jun. 30, 2014.

U.S. Appl. No. 14/319,002, filed Jun. 30, 2014.

U.S. Appl. No. 14/319,013, filed Jun. 30, 2014.

U.S. Appl. No. 14/319,016, filed Jun. 30, 2014.

U.S. Appl. No. 13/974,166, filed Aug. 23, 2013.

U.S. Appl. No. 14/138,481, filed Dec. 23, 2013.

U.S. Appl. No. 13/974,215, filed Aug. 23, 2013.

U.S. Appl. No. 13/974,202, filed Aug. 23, 2013.

U.S. Appl. No. 13/974,205, filed Aug. 23, 2013.

U.S. Appl. No. 13/974,224, filed Aug. 23, 2013.

U.S. Appl. No. 13/974,169, filed Aug. 23, 2013.

U.S. Appl. No. 13/974,206, filed Aug. 23, 2013.

U.S. Appl. No. 13/974,227, filed Aug. 23, 2013.

U.S. Appl. No. 13/974,174, filed Aug. 23, 2013.

U.S. Appl. No. 13/974,177, filed Aug. 23, 2013.

U.S. Appl. No. 13/974,182, filed Aug. 23, 2013.

U.S. Appl. No. 13/974,208, filed Aug. 23, 2013.

U.S. Appl. No. 13/974,209, filed Aug. 23, 2013.

U.S. Appl. No. 14/226,142, filed Mar. 26, 2014.

U.S. Appl. No. 14/226,106, filed Mar. 26, 2014.

U.S. Appl. No. 14/226,099, filed Mar. 26, 2014.

U.S. Appl. No. 14/226,094, filed Mar. 26, 2014.

U.S. Appl. No. 14/226,117, filed Mar. 26, 2014.

U.S. Appl. No. 14/226,075, filed Mar. 26, 2014.

U.S. Appl. No. 14/226,093, filed Mar. 26, 2014.

U.S. Appl. No. 14/226,116, filed Mar. 26, 2014.

U.S. Appl. No. 14/226,071, filed Mar. 26, 2014.

U.S. Appl. No. 14/226,097, filed Mar. 26, 2014.

U.S. Appl. No. 14/226,126, filed Mar. 26, 2014.

U.S. Appl. No. 14/226,133, filed Mar. 26, 2014.

U.S. Appl. No. 14/226,081, filed Mar. 26, 2014.

U.S. Appl. No. 14/226,076, filed Mar. 26, 2014.

U.S. Appl. No. 14/226,111, filed Mar. 26, 2014.

U.S. Appl. No. 14/226,125, filed Mar. 26, 2014.

U.S. Appl. No. 14/540,731, filed Nov. 13, 2014.

U.S. Appl. No. 14/540,779, filed Nov. 13, 2014.

U.S. Appl. No. 14/540,807, filed Nov. 13, 2014.

U.S. Appl. No. 14/549,098, filed Nov. 20, 2014.

U.S. Appl. No. 14/549,219, filed Nov. 20, 2014.

U.S. Appl. No. 14/518,652, filed Oct. 20, 2014.

U.S. Appl. No. 14/518,677, filed Oct. 20, 2014.

\* cited by examiner




FIG. 1





FIG. 2






FIG. 4




FIG. 5




FIG. 6






FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16






FIG. 17




FIG. 18




FIG. 20

FIG. 19




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 24A






FIG. 25

FIG. 26




FIG. 27

FIG. 28




FIG. 29






FIG. 30






FIG. 33




FIG. 33A




FIG. 33B




FIG. 34

FIG. 35






FIG. 36

FIG. 37




FIG. 38

FIG. 39




FIG. 43

FIG. 42

FIG. 41

FIG. 40




FIG. 45




FIG. 44




FIG. 46




FIG. 47




FIG. 48




FIG. 49






FIG. 50




FIG. 51




FIG. 52




FIG. 53




FIG. 54






FIG. 56




FIG. 58




FIG. 57






FIG. 59




FIG. 60




FIG. 61




FIG. 62




FIG. 63




FIG. 64




FIG. 65




FIG. 66




FIG. 67






FIG. 68




FIG. 69




FIG. 70




FIG. 71




FIG. 72




FIG. 73

FIG. 74




FIG. 75




FIG. 76




FIG. 77




FIG. 78




FIG. 79




FIG. 80






FIG. 81






FIG. 82






FIG. 85




FIG. 86




FIG. 87




FIG. 88




FIG. 89




FIG. 90




FIG. 91




FIG. 92




FIG. 93




FIG. 94




FIG. 95






FIG. 96




FIG. 98

FIG. 97




FIG. 99

FIG. 100







FIG. 101








FIG. 106




FIG. 107






FIG. 108

FIG. 109




FIG. 110




FIG. 111




FIG. 112




FIG. 113




FIG. 114




FIG. 115




FIG. 116






FIG. 117




FIG. 118




FIG. 119




FIG. 120




FIG. 121




FIG. 123




FIG. 125




FIG. 124




FIG. 128

FIG. 127

FIG. 126




FIG. 129 FIG. 130 FIG. 131






FIG. 132

FIG. 133




FIG. 134






FIG. 135






FIG. 138




FIG. 139




FIG. 140




FIG. 141






FIG. 142




FIG. 143




FIG. 144




FIG. 145




FIG. 146




FIG. 147




FIG. 148




FIG. 149






FIG. 150




FIG. 151




FIG. 152




FIG. 153




FIG. 154




FIG. 155




FIG. 156




FIG. 157




FIG. 158






FIG. 159




FIG. 160




FIG. 161




FIG. 162




FIG. 163




FIG. 164





FIG. 165









FIG. 167



1

## MULTI-AXIS ARTICULATING AND ROTATING SURGICAL TOOLS

### BACKGROUND

Over the years a variety of minimally invasive robotic (or “telesurgical”) systems have been developed to increase surgical dexterity as well as to permit a surgeon to operate on a patient in an intuitive manner. Many of such systems are disclosed in the following U.S. patents which are each herein incorporated by reference in their respective entirety: U.S. Pat. No. 5,792,135, entitled “Articulated Surgical Instrument For Performing Minimally Invasive Surgery With Enhanced Dexterity and Sensitivity”, U.S. Pat. No. 6,231,565, entitled “Robotic Arm DLUS For Performing Surgical Tasks”, U.S. Pat. No. 6,783,524, entitled “Robotic Surgical Tool With Ultrasound Cauterizing and Cutting Instrument”, U.S. Pat. No. 6,364,888, entitled “Alignment of Master and Slave In a Minimally Invasive Surgical Apparatus”, U.S. Pat. No. 7,524,320, entitled “Mechanical Actuator Interface System For Robotic Surgical Tools”, U.S. Pat. No. 7,691,098, entitled Platform Link Wrist Mechanism”, U.S. Pat. No. 7,806,891, entitled “Repositioning and Reorientation of Master/Slave Relationship in Minimally Invasive Telesurgery”, and U.S. Pat. No. 7,824,401, entitled “Surgical Tool With Writed Monopolar Electrosurgical End Effectors”. Many of such systems, however, have in the past been unable to generate the magnitude of forces required to effectively cut and fasten tissue. In addition, existing robotic surgical systems are limited in the number of different types of surgical devices that they may operate.

### BRIEF DESCRIPTION OF THE DRAWINGS

The features and advantages of this invention, and the manner of attaining them, will become more apparent and the invention itself will be better understood by reference to the following description of example embodiments of the invention taken in conjunction with the accompanying drawings, wherein:

Various example embodiments are described herein by way of example in conjunction with the following FIGS. wherein:

FIG. 1 is a perspective view of one embodiment of a robotic controller.

FIG. 2 is a perspective view of a robotic surgical arm cart/manipulator of a robotic system operably supporting a plurality of surgical tool embodiments.

FIG. 3 is a side view of one embodiment of the robotic surgical arm cart/manipulator depicted in FIG. 2.

FIG. 4 is a perspective view of a cart structure with positioning linkages for operably supporting robotic manipulators that may be used with surgical tool embodiments.

FIG. 5 is a perspective view of a surgical tool embodiment and a surgical end effector embodiment.

FIG. 6 is a perspective view of one embodiment of an electrosurgical tool in electrical communication with a generator

FIG. 7 shows a perspective view of one embodiment of the end effector of the surgical tool of FIG. 6 with the jaw members open and the distal end of an axially movable member in a retracted position.

FIG. 8 shows a perspective view of one embodiment of the end effector of the surgical tool of FIG. 6 with the jaw members closed and the distal end of an axially movable member in a partially advanced position.

2

FIG. 9 is a perspective view of one embodiment of the axially moveable member of the surgical tool of FIG. 6.

FIG. 10 is a section view of one embodiment of the electrosurgical end effector of the surgical tool of FIG. 6.

FIG. 11 is an exploded assembly view of one embodiment of an adapter and tool holder arrangement for attaching various surgical tool embodiments to a robotic system.

FIG. 12 is a side view of one embodiment of the adapter shown in FIG. 11.

FIG. 13 is a bottom view of one embodiment of the adapter shown in FIG. 11.

FIG. 14 is a top view of one embodiment of the adapter of FIGS. 11 and 12.

FIG. 15 is a partial bottom perspective view of one embodiment of a surgical tool.

FIG. 16 is a front perspective view of one embodiment of a portion of a surgical tool with some elements thereof omitted for clarity.

FIG. 17 is a rear perspective view of one embodiment of the surgical tool of FIG. 16.

FIG. 18 is a top view of one embodiment of the surgical tool of FIGS. 16 and 17.

FIG. 19 is a partial top view of one embodiment of the surgical tool of FIGS. 16-18 with the manually actuatable drive gear in an unactuated position.

FIG. 20 is another partial top view of one embodiment of the surgical tool of FIGS. 16-19 with the manually actuatable drive gear in an initially actuated position.

FIG. 21 is another partial top view of one embodiment of the surgical tool of FIGS. 16-20 with the manually actuatable drive gear in an actuated position.

FIG. 22 is a rear perspective view of another surgical tool embodiment.

FIG. 23 is a side elevational view of one embodiment of the surgical tool of FIG. 22.

FIG. 24 is a cross-sectional view of one embodiment of a portion of an articulation joint and end effector.

FIG. 24A illustrates one embodiment of the shaft assembly and articulation joint of FIG. 24 showing connections between distal cable sections and proximal cable portions.

FIG. 25 is an exploded assembly view of one embodiment of a portion of the articulation joint and end effector of FIG. 24.

FIG. 26 is a partial cross-sectional perspective view of one embodiment of the articulation joint and end effector portions depicted in FIG. 25.

FIG. 27 is a partial perspective view of an end effector and drive shaft assembly embodiment.

FIG. 28 is a partial side view of one embodiment of a drive shaft assembly.

FIG. 29 is a perspective view of one embodiment of a drive shaft assembly.

FIG. 30 is a side view of one embodiment of the drive shaft assembly of FIG. 29.

FIG. 31 is a perspective view of one embodiment of a composite drive shaft assembly.

FIG. 32 is a side view of one embodiment of the composite drive shaft assembly of FIG. 31.

FIG. 33 is another view of one embodiment of the drive shaft assembly of FIGS. 29 and 30 assuming an arcuate or “flexed” configuration.

FIG. 33A is a side view of one embodiment of a drive shaft assembly assuming an arcuate or “flexed” configuration.

FIG. 33B is a side view of one embodiment of another drive shaft assembly assuming an arcuate or “flexed” configuration.

FIG. 34 is a perspective view of a portion of another drive shaft assembly embodiment.

FIG. 35 is a top view of the drive shaft assembly embodiment of FIG. 34.

FIG. 36 is another perspective view of the drive shaft assembly embodiment of FIGS. 34 and 35 in an arcuate configuration.

FIG. 37 is a top view of the drive shaft assembly embodiment depicted in FIG. 36.

FIG. 38 is a perspective view of another drive shaft assembly embodiment.

FIG. 39 is another perspective view of the drive shaft assembly embodiment of FIG. 38 in an arcuate configuration.

FIG. 40 is a top view of the drive shaft assembly embodiment of FIGS. 38 and 39.

FIG. 41 is a cross-sectional view of the drive shaft assembly embodiment of FIG. 40.

FIG. 42 is a partial cross-sectional view of another drive shaft assembly embodiment.

FIG. 43 is another cross-sectional view of the drive shaft assembly embodiment of FIG. 42.

FIG. 44 is another cross-sectional view of a portion of another drive shaft assembly embodiment.

FIG. 45 is another cross-sectional view of one embodiment of the drive shaft assembly of FIG. 44.

FIG. 46 is a perspective view of another surgical tool embodiment.

FIG. 47 is a cross-sectional perspective view of the surgical tool embodiment of FIG. 46.

FIG. 48 is a cross-sectional perspective view of a portion of one embodiment of an articulation system.

FIG. 49 is a cross-sectional view of one embodiment of the articulation system of FIG. 48 in a neutral position.

FIG. 50 is another cross-sectional view of one embodiment of the articulation system of FIGS. 48 and 49 in an articulated position.

FIG. 51 is a side elevational view of a portion of one embodiment of the surgical tool of FIGS. 46-47 with portions thereof omitted for clarity.

FIG. 52 is a rear perspective view of a portion of one embodiment of the surgical tool of FIGS. 46-47 with portions thereof omitted for clarity.

FIG. 53 is a rear elevational view of a portion of one embodiment of the surgical tool of FIGS. 46-47 with portions thereof omitted for clarity.

FIG. 54 is a front perspective view of a portion of one embodiment of the surgical tool of FIGS. 46-47 with portions thereof omitted for clarity.

FIG. 55 is a side elevational view of a portion of the surgical tool embodiment of FIGS. 46-47 with portions thereof omitted for clarity.

FIG. 56 is an exploded assembly view of an example reversing system embodiment of the surgical tool of FIGS. 46-47.

FIG. 57 is a perspective view of a lever arm embodiment of the reversing system of FIG. 56.

FIG. 58 is a perspective view of a knife retractor button of one embodiment of the reversing system of FIG. 56.

FIG. 59 is a perspective view of a portion of the surgical tool embodiment of FIGS. 46-47 with portions thereof omitted for clarity and with the lever arm in actuatable engagement with the reversing gear.

FIG. 60 is a perspective view of a portion of the surgical tool embodiment of FIGS. 46-47 with portions thereof omitted for clarity and with the lever arm in an unactuated position.

FIG. 61 is another perspective view of a portion of the surgical tool embodiment of FIGS. 46-47 with portions thereof omitted for clarity and with the lever arm in actuatable engagement with the reversing gear.

FIG. 62 is a side elevational view of a portion of a handle assembly portion of the surgical tool embodiment of FIGS. 46-47 with a shifter button assembly moved into a position which will result in the rotation of the end effector when the drive shaft assembly is actuated.

FIG. 63 is another side elevational view of a portion of a handle assembly portion of one embodiment of the surgical tool of FIGS. 46-47 with the shifter button assembly moved into another position which will result in the firing of the firing member in the end effector when the drive shaft assembly is actuated.

FIG. 64 is a perspective view of an embodiment of a multi-axis articulating and rotating surgical tool.

FIG. 65 is an exploded perspective view of various components of one embodiment of the surgical tool shown in FIG. 64.

FIG. 66 is a partial cross-sectional perspective view of one embodiment of the surgical tool shown in FIG. 64, illustrating a rotary drive shaft engaging a rotary drive nut for actuating translation of an I-beam member and closure of a jaw assembly of an end effector.

FIG. 67 is a cross-sectional perspective view of one embodiment of the surgical tool shown in FIG. 64, illustrating a rotary drive shaft engaging a rotary drive nut for actuating translation of an I-beam member and closure of a jaw assembly of an end effector.

FIG. 68 is a partial cross-sectional perspective view of one embodiment of the surgical tool shown in FIG. 64, illustrating a rotary drive shaft engaging a shaft coupling for actuating rotation of an end effector.

FIG. 69 is a side cross-sectional view of one embodiment of the surgical tool shown in FIG. 64, illustrating the jaw assembly of an end effector in an open position, an I-beam member in a proximally retracted position, and a rotary drive shaft engaging a rotary drive nut for actuating translation of the I-beam member and closure of the jaw assembly of the end effector.

FIG. 70 is a side cross-sectional view of one embodiment of the surgical tool shown in FIG. 64, illustrating the jaw assembly of an end effector in a closed position, an I-beam member in a distally advanced position, and a rotary drive shaft engaging a rotary drive nut for actuating translation of the I-beam member and opening of the jaw assembly of the end effector.

FIG. 71 is a side cross-sectional view of one embodiment of the surgical tool shown in FIG. 64, illustrating the jaw assembly of an end effector in an open position, an I-beam member in a proximally retracted position, and a rotary drive shaft engaging a shaft coupling for actuating rotation of the end effector.

FIG. 72 is a side cross-sectional view of one embodiment of the surgical tool shown in FIG. 64, illustrating the jaw assembly of an end effector in a closed position, an I-beam member in a distally advanced position, and a rotary drive shaft engaging a shaft coupling for actuating rotation of the end effector.

FIGS. 73 and 74 are side cross-sectional detail views of one embodiment of the surgical tool shown in FIG. 64, illustrating the engagement of cam surfaces of an I-beam member with anvil surfaces of a first jaw member to move the first jaw member relative to a second jaw member between an open position and a closed position.

## 5

FIG. 75 is an exploded view of the components comprising an embodiment of a multi-axis articulating and rotating surgical tool comprising a head locking mechanism.

FIG. 76 is an exploded view of spline lock components of one embodiment of the head locking mechanism of the surgical tool illustrated in FIG. 75.

FIG. 77 is a side cross-sectional view of one embodiment of the surgical tool shown in FIG. 75, illustrating the jaw assembly of an end effector in an open position, an I-beam member in a proximally retracted position, a rotary drive shaft engaging a rotary drive nut for actuating translation of the I-beam member and closure of the jaw assembly of the end effector, and an engaged spline lock preventing rotation of the end effector.

FIG. 78 is a side cross-sectional view of one embodiment of the surgical tool shown in FIG. 75, illustrating the jaw assembly of an end effector in a closed position, an I-beam member in a distally advanced position, a rotary drive shaft engaging a rotary drive nut for actuating translation of the I-beam member and opening of the jaw assembly of the end effector, and an engaged spline lock preventing rotation of the end effector.

FIG. 79 is a side cross-sectional view of one embodiment of the surgical tool shown in FIG. 75, illustrating the jaw assembly of an end effector in an open position, an I-beam member in a proximally retracted position, a rotary drive shaft engaging a shaft coupling for actuating rotation of the end effector, and a disengaged spline lock allowing rotation of the end effector.

FIG. 80 is a side cross-sectional view of one embodiment of the surgical tool shown in FIG. 64, illustrating the jaw assembly of an end effector in a closed position, an I-beam member in a distally advanced position, a rotary drive shaft engaging a shaft coupling for actuating rotation of the end effector, and a disengaged spline lock allowing rotation of the end effector.

FIG. 81 is a side cross-sectional detail view of one embodiment of the surgical tool shown in FIG. 80.

FIG. 82 is a side cross-sectional detail view of one embodiment of the surgical tool shown in FIG. 78.

FIG. 83 is a cross sectional perspective view of a surgical tool having first and second jaw members in accordance with certain embodiments described herein.

FIG. 84 is prospective view of a closure nut of one embodiment of the surgical tool of FIG. 83.

FIG. 85 is a cross sectional elevation view of one embodiment of the surgical tool of FIG. 83 wherein the first jaw member and the second jaw member are in an at least partially open position, and wherein the rotary drive shaft is operably disengaged with the rotary drive nut.

FIG. 86 is a cross sectional elevation view of one embodiment of the surgical tool of FIG. 83 wherein the first jaw member and the second jaw member are in an at least partially open position, and wherein the rotary drive shaft is operably engaged with the rotary drive nut.

FIG. 87 is a cross sectional elevation view of one embodiment of the surgical tool of FIG. 83 wherein the first jaw member and the second jaw member are in an at least partially closed position, wherein the rotary drive shaft is operably engaged with the rotary drive nut, and wherein the closure nut is operably disengaged from the rotary drive nut.

FIG. 88 is a cross sectional elevation view of one embodiment of the surgical tool of FIG. 83 wherein the first jaw member and the second jaw member are in an at least partially closed position, wherein the rotary drive shaft is operably engaged with the rotary drive nut, and wherein the I-beam member is at least partially extended.

## 6

FIG. 89 is a cross sectional elevation view of one embodiment of the surgical tool of FIG. 83 wherein the first jaw member and the second jaw member are in an at least partially closed position, wherein the rotary drive shaft is operably engaged with the rotary drive nut, and wherein the I-beam member is at least partially retracted.

FIG. 90 is a cross sectional elevation view of one embodiment of the surgical tool of FIG. 83 wherein the first jaw member and the second jaw member are in an at least partially closed position, wherein the rotary drive shaft is operably engaged with the rotary drive nut, and wherein the I-beam member is at least partially retracted.

FIG. 91 is a cross sectional elevation view of one embodiment of the surgical tool of FIG. 83 wherein the first jaw member and the second jaw member are in an at least partially open position, wherein the rotary drive shaft is operably engaged with the rotary drive nut, and wherein the closure nut is operably engaged from the rotary drive nut.

FIG. 92 is a cross sectional perspective view of a surgical tool having first and second jaw members in accordance with certain embodiments described herein.

FIG. 93 is a cross sectional elevation view of one embodiment of the surgical tool of FIG. 92 wherein the first jaw member and the second jaw member are in an at least partially open position, and wherein the rotary drive shaft is operably engaged with spline coupling portion of the end effector drive housing.

FIG. 94 is a cross sectional elevation view of one embodiment of the surgical tool of FIG. 92 wherein the first jaw member and the second jaw member are in an at least partially closed position, and wherein the rotary drive shaft is operably engaged with spline coupling portion of the barrel cam.

FIG. 95 is a cross sectional elevation view of one embodiment of the surgical tool of FIG. 92 wherein the first jaw member and the second jaw member are in an at least partially closed position, and wherein the rotary drive shaft is not operably engaged with any of the spline coupling portions.

FIG. 96 is a cross sectional elevation view of one embodiment of the surgical tool of FIG. 92 wherein the first jaw member and the second jaw member are in an at least partially closed position, and wherein the rotary drive shaft is operably engaged with spline coupling portion of the rotary drive nut.

FIG. 97 illustrates a perspective view of an end effector and an articulation joint of a surgical instrument in accordance with at least one embodiment illustrated with portions removed for the purposes of illustration.

FIG. 98 illustrates a detail view of a drive shaft in accordance with at least one embodiment configured to be translated within the end effector and the articulation joint of FIG. 97.

FIG. 99 illustrates a perspective view of a drive shaft in accordance with at least one alternative embodiment.

FIG. 100 illustrates an elevational view of one embodiment of the drive shaft of FIG. 99.

FIG. 101 illustrates an elevational view of one embodiment of the drive shaft of FIG. 99 illustrated in an articulated condition.

FIG. 102 illustrates a perspective view of a drive shaft assembly comprising a drive tube and a thread extending around the drive tube in accordance with at least one alternative embodiment.

FIG. 103 illustrates an elevational view of one embodiment of the drive shaft assembly of FIG. 102.

FIG. 104 illustrates a perspective view of a drive shaft assembly comprising a drive tube, a thread extending around the drive tube, and an inner core extending through the drive tube in accordance with at least one embodiment.

FIG. 105 illustrates an elevational view of one embodiment of the drive shaft assembly of FIG. 104.

FIG. 106 is a perspective view of a surgical tool having first and second jaw members in accordance with certain embodiments described herein.

FIG. 107 is cross sectional view of distal portions of one embodiment of the first and second jaw members of the surgical end tool shown in FIG. 106.

FIG. 108 is a perspective view of a surgical end effector and a shaft assembly in accordance with certain embodiments described herein.

FIG. 109 is a prospective view of a jaw member of a surgical end effector in accordance with certain embodiments described herein.

FIG. 110 is a cross-sectional view of a surgical effector detached from a shaft assembly in accordance with certain embodiments described herein.

FIG. 111 is a cross-sectional view of a surgical effector attached to a shaft assembly in accordance with certain embodiments described herein.

FIG. 112 is a perspective view of multiple interchangeable surgical end effectors in accordance with certain embodiments described herein.

FIG. 113 is a perspective view of a surgical end effector including a cross sectional view of a jaw member in accordance with certain embodiments described herein.

FIG. 114 is a cross-sectional view of a surgical effector detached from a shaft assembly in accordance with certain embodiments described herein.

FIG. 115 is a cross-sectional view of a surgical effector attached to a shaft assembly in accordance with certain embodiments described herein.

FIG. 116 is a perspective view of a surgical end effector having first and second jaws in accordance with certain embodiments described herein.

FIG. 117 is another perspective view of the surgical end effector shown in FIG. 116 including a cross sectional perspective view of a jaw member in accordance with certain embodiments described herein.

FIG. 118 is cross sectional view of a first jaw member and a second jaw member of a surgical end effector in accordance with certain embodiments described herein.

FIG. 119 is cross sectional view of a first jaw member and a second jaw member of a surgical end effector in accordance with certain embodiments described herein.

FIG. 120 is a perspective view of a first jaw member and a second jaw member of a surgical end effector in accordance with certain embodiments described herein.

FIG. 121 is a prospective view of a distal portion of a jaw member of a surgical end effector in accordance with certain embodiments described herein.

FIG. 122 is a top view of a gripping portion in accordance with certain embodiments described herein.

FIG. 123 is a top view of a gripping portion in accordance with certain embodiments described herein.

FIG. 124 is a top view of a gripping portion in accordance with certain embodiments described herein.

FIG. 125 is a top view of a gripping portion in accordance with certain embodiments described herein.

FIG. 126 is a top view of a gripping portion in accordance with certain embodiments described herein.

FIG. 127 is a top view of a gripping portion in accordance with certain embodiments described herein.

FIG. 128 is a top view of a gripping portion in accordance with certain embodiments described herein.

FIG. 129 is a top view of a gripping portion in accordance with certain embodiments described herein.

FIG. 130 is a top view of a gripping portion in accordance with certain embodiments described herein.

FIG. 131 is a top view of a gripping portion in accordance with certain embodiments described herein.

FIG. 132 is a perspective view of one embodiment of an end effector having first and second jaw members in an open position and angled tissue-contacting surfaces along substantially the entire length of the jaw members.

FIG. 133 is another perspective view of one embodiment of the end effector shown in FIG. 132 with the first and second jaw members in a closed position.

FIG. 134 is a front view of one embodiment of the end effector shown in FIG. 133.

FIG. 135 is a cross-sectional view of one embodiment of the end effector shown in FIG. 134.

FIG. 136 is a side view of one embodiment of the end effector shown in FIG. 132.

FIG. 137 is a side view of one embodiment of the end effector shown in FIG. 133.

FIG. 138 is a schematic diagram showing a front view of one embodiment of an end effector having first and second jaw members, wherein each jaw member has two oppositely-angled tissue-contacting surfaces.

FIG. 139 is a perspective view of one embodiment of an end effector having first and second jaw members in an open position and angled tissue-contacting surfaces along a portion of the length of the jaw members.

FIG. 140 is another perspective view of one embodiment of the end effector shown in FIG. 139.

FIG. 141 is a perspective view of one embodiment of an end effector having first and second jaw members in an open position, angled tissue-contacting surfaces along a portion of the length of the jaw members, and electrodes positioned between the two angled tissue-contacting surfaces on the second jaw member.

FIG. 142 is a cross-sectional view of one embodiment of an end effector having first and second jaw members in a closed position clamping tissue between the jaw members, wherein the first and second jaw members have opposed angled tissue-contacting surfaces.

FIG. 143 is a cross-sectional view of one embodiment of the end effector and shaft assembly of FIGS. 64-82 illustrating an example installation of a rotary electrode assembly.

FIG. 144 is an exploded view of one embodiment of the end effector and shaft assembly of FIG. 143 showing the rotary electrode assembly both installed and exploded.

FIG. 145 is a cross-sectional view of one embodiment of the end effector and shaft assembly of FIG. 143 showing the rotary electrode assembly with a rotary drive head in a proximal position.

FIG. 146 is a cross-sectional view of one embodiment of the end effector and shaft assembly of FIG. 143 showing the rotary electrode assembly with the rotary drive head in a distal position.

FIGS. 147-148 are cross-sectional views of one embodiment of the end effector and shaft assembly of FIG. 143 where a longitudinal length of the outer contact is selected such that the rotary connector assembly alternately creates and breaks an electrical connection limited by the longitudinal position of the brush assembly.

FIGS. 149-150 illustrate one embodiment of the end effector and shaft assembly of FIG. 143 showing a configuration including lead portions and connector assembly between the end effector and the shaft assembly.

FIG. 151 illustrates a cross-sectional view one embodiment of an end effector and shaft assembly showing another context in which a rotary connector assembly may be utilized.

FIG. 152 illustrates a cross-sectional view of one embodiment of the end effector and shaft assembly of FIGS. 83-91 illustrating another example installation of a rotary electrode assembly.

FIG. 153 illustrates one embodiment of an end effector that may be utilized with various surgical tools, including those described herein.

FIG. 154 illustrates one embodiment of the end effector of FIG. 153 showing a tissue contacting portion adjacent a longitudinal channel of the second jaw member of the end effector.

FIG. 155 illustrates one embodiment of the end effector of FIG. 153 showing an axial cross-section along a midline of the first jaw member showing a tissue-contacting portion disposed adjacent to a longitudinal channel of the first jaw member.

FIG. 156 illustrates a perspective view of one embodiment of the end effector of FIG. 153 in an open position.

FIG. 157 illustrates a top view of one embodiment of a second jaw member suitable for use with the end effector of FIG. 153.

FIG. 158 illustrates a bottom view of one embodiment of a first jaw member suitable for use with the end effector of FIG. 153.

FIG. 159 illustrates a front cross-sectional view of another embodiment of the end effector of FIG. 153 in a closed position.

FIGS. 160-165 illustrates side cross-sectional views of various embodiments of the end effector of FIG. 153

FIG. 166 illustrates another embodiment of the second jaw member suitable for use with the end effector of FIG. 153. in a closed position holding a surgical implement.

FIG. 167 illustrates one embodiment of the second jaw member suitable for use with the end effector of FIG. 153.

FIG. 168 illustrates another embodiment of the second jaw member suitable for use with the end effector of FIG. 153.

#### DETAILED DESCRIPTION

Applicant of the present application also owns the following patent applications that have been filed on even date herewith and which are each herein incorporated by reference in their respective entireties:

1. U.S. patent application Ser. No. 13/536,271, entitled "Flexible Drive Member," now U.S. Patent Application Publication No. 2014-0005708 A1.

2. U.S. patent application Ser. No. 13/536,288, entitled "Multi-Functional Powered Surgical Device with External Dissection Features," now U.S. Patent Application Publication No. 2014-0005718 A1.

3. U.S. patent application Ser. No. 13/536,277, entitled "Coupling Arrangements for Attaching Surgical End Effectors to Drive Systems Therefor," now U.S. Patent Application Publication No. 2014-0001234 A1.

4. U.S. patent application Ser. No. 13/536,295, entitled "Rotary Actuable Closure Arrangement for Surgical End Effector," now U.S. Patent Application Publication No. 2014-0005676 A1.

5. U.S. patent application Ser. No. 13/536,326, entitled "Surgical End Effectors Having Angled Tissue-Contacting Surfaces," now U.S. Patent Application Publication No. 2014-0005653 A1.

6. U.S. patent application Ser. No. 13/536,303 entitled "Interchangeable End Effector Coupling Arrangement," now U.S. Patent Application Publication No. 2014-0005661 A1.

7. U.S. patent application Ser. No. 13/536,393, entitled "Surgical End Effector Jaw and Electrode Configurations," now U.S. Patent Application Publication No. 2014-0005640 A1.

8. U.S. patent application Ser. No. 13/536,284, entitled "Differential Locking Arrangements for Rotary Powered Surgical Instruments," now U.S. Patent Application Publication No. 2014-0000411 A1.

9. U.S. patent application Ser. No. 13/536,374, entitled "Interchangeable Clip Applier," now U.S. Patent Application Publication No. 2014-0005693 A1.

10. U.S. patent application Ser. No. 13/536,292, entitled "Firing System Lockout Arrangements for Surgical Instruments," now U.S. Patent Application Publication No. 2014-0001231 A1.

11. U.S. patent application Ser. No. 13/536,301, entitled "Rotary Drive Shaft Assemblies for Surgical Instruments with Articulatable End Effectors," now U.S. Pat. No. 8,747,238.

12. U.S. patent application Ser. No. 13/536,313, entitled "Rotary Drive Arrangements for Surgical Instruments," now U.S. Patent Application Publication No. 2014-0005678 A1.

13. U.S. patent application Ser. No. 13/536,323, entitled "Robotically Powered Surgical Device With Manually-Actuable Reversing System," now U.S. Patent Application Publication No. 2014-0001235 A1.

14. U.S. patent application Ser. No. 13/536,379, entitled "Replaceable Clip Cartridge for a Clip Applier," now U.S. Patent Application Publication No. 2014-0005694 A1.

15. U.S. patent application Ser. No. 13/536,386, entitled "Empty Clip Cartridge Lockout," now U.S. Patent Application Publication No. 2014-0005695 A1.

16. U.S. patent application Ser. No. 13/536,360, entitled "Surgical Instrument System Including Replaceable End Effectors," now U.S. Patent Application Publication No. 2014-0005679 A1.

17. U.S. patent application Ser. No. 13/536,335, entitled "Rotary Support Joint Assemblies for Coupling a First Portion of a Surgical Instrument to a Second Portion of a Surgical Instrument," now U.S. Patent Application Publication No. 2014-0001236 A1.

18. U.S. patent application Ser. No. 13/536,417, entitled "Electrode Connections for Rotary Driven Surgical Tools," now U.S. Patent Application Publication No. 2014-0005680 A1.

Applicant also owns the following patent applications that are each incorporated by reference in their respective entireties:

U.S. patent application Ser. No. 13/118,259, entitled "Surgical Instrument With Wireless Communication Between a Control Unit of a Robotic System and Remote Sensor", now U.S. Pat. No. 8,684,253.

U.S. patent application Ser. No. 13/118,210, entitled "Robotically-Controlled Disposable Motor Driven Loading Unit", now U.S. Pat. No. 8,752,749.

U.S. patent application Ser. No. 13/118,194, entitled "Robotically-Controlled Endoscopic Accessory Channel", now U.S. Patent Application Publication No. 2011-0295242;

U.S. patent application Ser. No. 13/118,253, entitled "Robotically-Controlled Motorized Surgical Instrument", now U.S. Patent Application Publication No. 2011-0295269 A1;

U.S. patent application Ser. No. 13/118,278, entitled "Robotically-Controlled Surgical Stapling Devices That Produce Formed Staples Having Different Lengths", now U.S. Patent Application Publication No. 2011-0290851 A1;

U.S. patent application Ser. No. 13/118,190, entitled “Robotically-Controlled Motorized Cutting and Fastening Instrument”, now U.S. Patent Application Publication No. 2011-0288573 A1

U.S. patent application Ser. No. 13/118,223, entitled “Robotically-Controlled Shaft Based Rotary Drive Systems For Surgical Instruments”, now U.S. Pat. No. 8,931,682.

U.S. patent application Ser. No. 13/118,263, entitled “Robotically-Controlled Surgical Instrument Having Recording Capabilities”, now U.S. Patent Application Publication No. 2011-0295295 A1;

U.S. patent application Ser. No. 13/118,272, entitled “Robotically-Controlled Surgical Instrument With Force Feedback Capabilities”, now U.S. Patent Application Publication No. 2011-0290856 A1;

U.S. patent application Ser. No. 13/118,246, entitled “Robotically-Driven Surgical Instrument With E-Beam Driver”, now U.S. Patent Application Publication No. 2011-0290853 A1; and

U.S. patent application Ser. No. 13/118,241, entitled “Surgical Stapling Instruments With Rotatable Staple Deployment Arrangements”, now U.S. Patent Application Publication No. 2012-0298719 A1.

Certain example embodiments will now be described to provide an overall understanding of the principles of the structure, function, manufacture, and use of the devices and methods disclosed herein. One or more examples of these example embodiments are illustrated in the accompanying drawings. Those of ordinary skill in the art will understand that the devices and methods specifically described herein and illustrated in the accompanying drawings are non-limiting example embodiments and that the scope of the various example embodiments of the present invention is defined solely by the claims. The features illustrated or described in connection with one example embodiment may be combined with the features of other example embodiments. Such modifications and variations are intended to be included within the scope of the present invention.

FIG. 1 depicts a master controller 12 that is used in connection with a robotic arm slave cart 20 of the type depicted in FIG. 2. Master controller 12 and robotic arm slave cart 20, as well as their respective components and control systems are collectively referred to herein as a robotic system 10. Examples of such systems and devices are disclosed in U.S. Pat. No. 7,524,320 which has been herein incorporated by reference. Thus, various details of such devices will not be described in detail herein beyond that which may be necessary to understand various example embodiments disclosed herein. As is known, the master controller 12 generally includes master controllers (generally represented as 14 in FIG. 1) which are grasped by the surgeon and manipulated in space while the surgeon views the procedure via a stereo display 16. The master controllers 12 generally comprise manual input devices which preferably move with multiple degrees of freedom, and which often further have an actuable handle for actuating tools (for example, for closing grasping jaws, applying an electrical potential to an electrode, or the like).

As can be seen in FIG. 2, the robotic arm cart 20 is configured to actuate a plurality of surgical tools, generally designated as 30. Various robotic surgery systems and methods employing master controller and robotic arm cart arrangements are disclosed in U.S. Pat. No. 6,132,368, entitled “Multi-Component Telepresence System and Method”, the full disclosure of which is incorporated herein by reference. As shown, the robotic arm cart 20 includes a base 22 from which, in the illustrated embodiment, three surgical tools 30

are supported. The surgical tools 30 are each supported by a series of manually articulatable linkages, generally referred to as set-up joints 32, and a robotic manipulator 34. These structures are herein illustrated with protective covers extending over much of the robotic linkage. These protective covers may be optional, and may be limited in size or entirely eliminated to minimize the inertia that is encountered by the servo mechanisms used to manipulate such devices, to limit the volume of moving components so as to avoid collisions, and to limit the overall weight of the cart 20. The cart 20 generally has dimensions suitable for transporting the cart 20 between operating rooms. The cart 20 is configured to typically fit through standard operating room doors and onto standard hospital elevators. The cart 20 would preferably have a weight and include a wheel (or other transportation) system that allows the cart 20 to be positioned adjacent an operating table by a single attendant.

Referring now to FIG. 3, robotic manipulators 34 as shown include a linkage 38 that constrains movement of the surgical tool 30. Linkage 38 includes rigid links coupled together by rotational joints in a parallelogram arrangement so that the surgical tool 30 rotates around a point in space 40, as more fully described in U.S. Pat. No. 5,817,084, the full disclosure of which is herein incorporated by reference. The parallelogram arrangement constrains rotation to pivoting about an axis 40a, sometimes called the pitch axis. The links supporting the parallelogram linkage are pivotally mounted to set-up joints 32 (FIG. 2) so that the surgical tool 30 further rotates about an axis 40b, sometimes called the yaw axis. The pitch and yaw axes 40a, 40b intersect at the remote center 42, which is aligned along a shaft 44 of the surgical tool 30. The surgical tool 30 may have further degrees of driven freedom as supported by manipulator 50, including sliding motion of the surgical tool 30 along the longitudinal tool axis “LT-LT”. As the surgical tool 30 slides along the tool axis LT-LT relative to manipulator 50 (arrow 40c), remote center 42 remains fixed relative to base 52 of manipulator 50. Hence, the entire manipulator is generally moved to re-position remote center 42. Linkage 54 of manipulator 50 is driven by a series of motors 56. These motors actively move linkage 54 in response to commands from a processor of a control system. Motors 56 are also employed to manipulate the surgical tool 30. An alternative set-up joint structure is illustrated in FIG. 4. In this embodiment, a surgical tool 30 is supported by an alternative manipulator structure 50' between two tissue manipulation tools.

Other embodiments may incorporate a wide variety of alternative robotic structures, including those described in U.S. Pat. No. 5,878,193, entitled “Automated Endoscope System For Optimal Positioning”, the full disclosure of which is incorporated herein by reference. Additionally, while the data communication between a robotic component and the processor of the robotic surgical system is described with reference to communication between the surgical tool 30 and the master controller 12, similar communication may take place between circuitry of a manipulator, a set-up joint, an endoscope or other image capture device, or the like, and the processor of the robotic surgical system for component compatibility verification, component-type identification, component calibration (such as off-set or the like) communication, confirmation of coupling of the component to the robotic surgical system, or the like.

A surgical tool 100 that is well-adapted for use with a robotic system 10 is depicted in FIGS. 5-6. FIG. 5 illustrates an additional embodiment of the surgical tool 100 and electrosurgical end effector 3000. As can be seen in FIG. 5, the surgical tool 100 includes an electrosurgical end effector



**3000.** The electro-surgical end effector **3000** may utilize electrical energy to treat and/or destroy tissue. The electro-surgical end effector **3000** generally comprises first and second jaw members **3008A**, **3008B** which may be straight, as shown in FIGS. **6-10**, or curved as shown in various other figures described herein. One or both of the jaw members **3008A**, **3008B** generally comprise various electrodes for providing electro-surgical energy to tissue. The surgical tool **100** generally includes an elongate shaft assembly **200** that is operably coupled to the manipulator **50** by a tool mounting portion, generally designated as **300**. Electro-surgical tools (e.g., surgical tools that include an electro-surgical end effector, such as the tool **100** and end effector **3000**) may be used in any suitable type of surgical environment including, for example, open, laparoscopic, endoscopic, etc.

Generally, electro-surgical tools comprise one or more electrodes for providing electric current. The electrodes may be positioned against and/or positioned relative to tissue such that electrical current can flow through the tissue. The electrical current may generate heat in the tissue that, in turn, causes one or more hemostatic seals to form within the tissue and/or between tissues. For example, tissue heating caused by the electrical current may at least partially denature proteins within the tissue. Such proteins, such as collagen, for example, may be denatured into a proteinaceous amalgam that intermixes and fuses, or “welds”, together as the proteins renature. As the treated region heals over time, this biological “weld” may be reabsorbed by the body’s wound healing process.

Electrical energy provided by electro-surgical tools may be of any suitable form including, for example, direct or alternating current. For example, the electrical energy may include high frequency alternating current such as radio frequency or “RF” energy. RF energy may include energy in the range of 300 kilohertz (kHz) to 1 megahertz (MHz). When applied to tissue, RF energy may cause ionic agitation or friction, increasing the temperature of the tissue. Also, RF energy may provide a sharp boundary between affected tissue and other tissue surrounding it, allowing surgeons to operate with a high level of precision and control. The low operating temperatures of RF energy enables surgeons to remove, shrink or sculpt soft tissue while simultaneously sealing blood vessels. RF energy works particularly well on connective tissue, which is primarily comprised of collagen and shrinks when contacted by heat.

In certain arrangements, some bi-polar (e.g., two-electrode) electro-surgical tools can comprise opposing first and second jaw members, where the face of each jaw can comprise a current path and/or electrode. In use, the tissue can be captured between the jaw faces such that electrical current can flow between the electrodes in the opposing jaw members and through the tissue positioned therebetween. Such tools may have to coagulate, seal or “weld” many types of tissues, such as anatomic structures having walls with irregular or thick fibrous content, bundles of disparate anatomic structures, substantially thick anatomic structures, and/or tissues with thick fascia layers such as large diameter blood vessels, for example. Some embodiments may include a knife or cutting edge to transect the tissue, for example, during or after the application of electro-surgical energy. With particular regard to cutting and sealing large diameter blood vessels, for example, such applications may require a high strength tissue weld immediately post-treatment.

FIG. **6** is a perspective view of one embodiment of the electro-surgical tool **100** in electrical communication with a generator **3002**. The electro-surgical tool **100** in conjunction with the generator **3002** can be configured to supply energy,

such as electrical energy, ultrasonic energy, and/or heat energy, for example, to the tissue of a patient. In the illustrated embodiment and in functionally similar embodiments, the generator **3002** is connected to electro-surgical tool **100** via a suitable transmission medium such as a cable **3010**. In one embodiment, the generator **3002** is coupled to a controller, such as a control unit **3004**, for example. In various embodiments, the control unit **3004** may be formed integrally with the generator **3002** or may be provided as a separate circuit module or device electrically coupled to the generator **3002** (shown in phantom to illustrate this option). Although in the presently disclosed embodiment, the generator **3002** is shown separate from the electro-surgical tool **100**, in one embodiment, the generator **3002** (and/or the control unit **3004**) may be formed integrally with the electro-surgical tool **100** to form a unitary electro-surgical system. For example, in some embodiments a generator or equivalent circuit may be present within the tool mounting portion **300** and/or within a handle in suitable manual embodiments (as described herein).

The generator **3002** may comprise an input device **3006** located on a front panel of the generator **3002** console. The input device **3006** may comprise any suitable device that generates signals suitable for programming the operation of the generator **3002**, such as a keyboard, or input port, for example. In one embodiment, various electrodes in the first jaw member **3008A** and the second jaw member **3008B** may be coupled to the generator **3002**. A cable **3010** connecting the tool mounting portion **300** to the generator **3002** may comprise multiple electrical conductors for the application of electrical energy to positive (+) and negative (−) electrodes of the electro-surgical tool **100**. The control unit **3004** may be used to activate the generator **3002**, which may serve as an electrical source. In various embodiments, the generator **3002** may comprise an RF source, an ultrasonic source, a direct current source, and/or any other suitable type of electrical energy source, for example.

In various embodiments, surgical tool **100** may comprise at least one supply conductor **3012** and at least one return conductor **3014**, wherein current can be supplied to electro-surgical tool **100** via the supply conductor **3012** and wherein the current can flow back to the generator **3002** via return conductor **3014**. In various embodiments, the supply conductor **3012** and the return conductor **3014** may comprise insulated wires and/or any other suitable type of conductor. In certain embodiments, as described below, the supply conductor **3012** and the return conductor **3014** may be contained within and/or may comprise the cable **3010** extending between, or at least partially between, the generator **3002** and the end effector **3000** of the electro-surgical tool **100**. In any event, the generator **3002** can be configured to apply a sufficient voltage differential between the supply conductor **3012** and the return conductor **3014** such that sufficient current can be supplied to the end effector **3000**.

The electro-surgical end effector **3000** may be adapted for capturing and transecting tissue and for the contemporaneously welding the captured tissue with controlled application of energy (e.g., RF energy). FIG. **7** illustrates one embodiment of the electro-surgical end effector **3000** with the jaw members **3008A**, **3008B** open and an axially movable member **3016** in a proximally retracted position. FIG. **8** illustrates one embodiment of the electro-surgical end effector **3000** with the jaw members **3008A**, **3008B** closed and the axially movable member **3016** in a partially advanced position.

In use, the jaw members **3008A**, **3008B** close to thereby capture or engage tissue about a longitudinal tool axis LT-LT defined by the axially moveable member **3016** (or a distal portion thereof). The first jaw member **3008A** and second jaw

member **3008B** may also apply compression to the tissue. In some embodiments, the elongate shaft **200**, along with first jaw member **3008A** and second jaw member **3008B**, can be rotated a full 360° degrees, as shown by arrow **3018** (see FIG. **8**), relative to tool mounting portion **300**.

The first jaw member **3008A** and the second jaw member **3008B** may each comprise an elongate slot or channel **3020A** and **3020B** (FIG. **7**), respectively, disposed outwardly along their respective middle portions. Further, the first jaw member **3008A** and second jaw member **3008B** may each have tissue-gripping elements, such as teeth **3022**, disposed on the inner portions of first jaw member **3008A** and second jaw member **3008B**. The lower jaw member **3008B** may define a jaw body with an energy delivery surface or electrode **3024B**. For example, the electrode **3024B** may be in electrical communication with the generator **3002** via the supply conductor **3012**. An energy delivery surface **3024A** on the upper first jaw member **3008** may provide a return path for electrosurgical energy. For example, the energy delivery surface **3024A** may be in electrical communication with the return conductor **3014**. In the illustrated embodiment and in functionally similar embodiments, other conductive parts of the surgical tool **100** including, for example the jaw members **3008A**, **3008B**, the shaft **200**, etc. may form all or a part of the return path. Various configurations of electrodes and various configurations for coupling the energy delivery surfaces **3024A**, **3024B** to the conductors **3012**, **3014** are described herein. Also, it will be appreciated that the supply electrode **3024B** may be provided on the lower jaw member **3008B** as shown or on the upper jaw member **3008A**.

Distal and proximal translation of the axially moveable member **3016** may serve to open and close the jaw members **3008A**, **3008B** and to sever tissue held therebetween. FIG. **9** is a perspective view of one embodiment of the axially moveable member **3016** of the surgical tool **100**. The axially moveable member **3016** may comprise one or several pieces, but in any event, may be movable or translatable with respect to the elongate shaft **200** and/or the jaw members **3008A**, **3008B**. Also, in at least one embodiment, the axially moveable member **3016** may be made of 17-4 precipitation hardened stainless steel. The distal end of axially moveable member **3016** may comprise a flanged “I”-beam configured to slide within the channels **3020A** and **3020B** in jaw members **3008A** and **3008B**. The axially moveable member **3016** may slide within the channels **3020A**, **3020B** to open and close first jaw member **3008A** and second jaw member **3008B**. The distal end of the axially moveable member **3016** may also comprise an upper flange or “c”-shaped portion **3016A** and a lower flange or “c”-shaped portion **3016B**. The flanges **3016A** and **3016B** respectively define inner cam surfaces **3026A** and **3026B** for engaging outward facing surfaces of first jaw member **3008A** and second jaw member **3008B**. The opening-closing of jaw members **3008A** and **3008B** can apply very high compressive forces on tissue using cam mechanisms which may include movable “I-beam” axially moveable member **3016** and the outward facing surfaces **3028A**, **3028B** of jaw members **3008A**, **3008B**.

More specifically, referring now to FIGS. **7-9**, collectively, the inner cam surfaces **3026A** and **3026B** of the distal end of axially moveable member **3016** may be adapted to slidably engage the first outward-facing surface **3028A** and the second outward-facing surface **3028B** of the first jaw member **3008A** and the second jaw member **3008B**, respectively. The channel **3020A** within first jaw member **3008A** and the channel **3020B** within the second jaw member **3008B** may be sized and configured to accommodate the movement of the axially moveable member **3016**, which may comprise a tissue-cut-

ting element **3030**, for example, comprising a sharp distal edge. FIG. **8**, for example, shows the distal end of the axially moveable member **3016** advanced at least partially through channels **3020A** and **3020B** (FIG. **7**). The advancement of the axially moveable member **3016** may close the end effector **3000** from the open configuration shown in FIG. **7**. In the closed position shown by FIG. **8**, the upper first jaw member **3008A** and lower second jaw member **3008B** define a gap or dimension **D** between the first energy delivery surface **3024A** and second energy delivery surface **3024B** of first jaw member **3008A** and second jaw member **3008B**, respectively. In various embodiments, dimension **D** can equal from about 0.0005" to about 0.040", for example, and in some embodiments, between about 0.001" to about 0.010", for example. Also, the edges of the first energy delivery surface **3024A** and the second energy delivery surface **3024B** may be rounded to prevent the dissection of tissue.

FIG. **10** is a section view of one embodiment of the end effector **3000** of the surgical tool **100**. The engagement, or tissue-contacting, surface **3024B** of the lower jaw member **3008B** is adapted to deliver energy to tissue, at least in part, through a conductive-resistive matrix, such as a variable resistive positive temperature coefficient (PTC) body, as discussed in more detail below. At least one of the upper and lower jaw members **3008A**, **3008B** may carry at least one electrode **3032** configured to deliver the energy from the generator **3002** to the captured tissue. The engagement, or tissue-contacting, surface **3024A** of upper jaw member **3008A** may carry a similar conductive-resistive matrix (i.e., a PTC material), or in some embodiments the surface may be a conductive electrode or an insulative layer, for example. Alternatively, the engagement surfaces of the jaw members can carry any of the energy delivery components disclosed in U.S. Pat. No. 6,773,409, filed Oct. 22, 2001, entitled ELECTROSURGICAL JAW STRUCTURE FOR CONTROLLED ENERGY DELIVERY, the entire disclosure of which is incorporated herein by reference.

The first energy delivery surface **3024A** and the second energy delivery surface **3024B** may each be in electrical communication with the generator **3002**. The first energy delivery surface **3024A** and the second energy delivery surface **3024B** may be configured to contact tissue and deliver electrosurgical energy to captured tissue which are adapted to seal or weld the tissue. The control unit **3004** regulates the electrical energy delivered by electrical generator **3002** which in turn delivers electrosurgical energy to the first energy delivery surface **3024A** and the second energy delivery surface **3024B**. The energy delivery may be initiated in any suitable manner (e.g., upon actuation of the robot system **10**). In one embodiment, the electrosurgical tool **100** may be energized by the generator **3002** by way of a foot switch **3034** (FIG. **6**). When actuated, the foot switch **3034** triggers the generator **3002** to deliver electrical energy to the end effector **3000**, for example. The control unit **3004** may regulate the power generated by the generator **3002** during activation. Although the foot switch **3034** may be suitable in many circumstances, other suitable types of switches can be used.

As mentioned above, the electrosurgical energy delivered by electrical generator **3002** and regulated, or otherwise controlled, by the control unit **3004** may comprise radio frequency (RF) energy, or other suitable forms of electrical energy. Further, one or both of the opposing first and second energy delivery surfaces **3024A** and **3024B** may carry variable resistive positive temperature coefficient (PTC) bodies that are in electrical communication with the generator **3002** and the control unit **3004**. Additional details regarding electrosurgical end effectors, jaw closing mechanisms, and elec-

trosurgical energy-delivery surfaces are described in the following U.S. patents and published patent applications: U.S. Pat. Nos. 7,087,054; 7,083,619; 7,070,597; 7,041,102; 7,011,657; 6,929,644; 6,926,716; 6,913,579; 6,905,497; 6,802,843; 6,770,072; 6,656,177; 6,533,784; and 6,500,176; and U.S. Pat. App. Pub. Nos. 2010/0036370 and 2009/0076506, all of which are incorporated herein in their entirety by reference and made a part of this specification.

In one embodiment, the generator **3002** may be implemented as an electrosurgery unit (ESU) capable of supplying power sufficient to perform bipolar electrosurgery using radio frequency (RF) energy. In one embodiment, the ESU can be a bipolar ERBE ICC **350** sold by ERBE USA, Inc. of Marietta, Ga. In some embodiments, such as for bipolar electrosurgery applications, a surgical tool having an active electrode and a return electrode can be utilized, wherein the active electrode and the return electrode can be positioned against, adjacent to and/or in electrical communication with, the tissue to be treated such that current can flow from the active electrode, through the positive temperature coefficient (PTC) bodies and to the return electrode through the tissue. Thus, in various embodiments, the electrosurgical system **150** may comprise a supply path and a return path, wherein the captured tissue being treated completes, or closes, the circuit. In one embodiment, the generator **3002** may be a monopolar RF ESU and the electrosurgical tool **100** may comprise a monopolar end effector **3000** in which one or more active electrodes are integrated. For such a system, the generator **3002** may require a return pad in intimate contact with the patient at a location remote from the operative site and/or other suitable return path. The return pad may be connected via a cable to the generator **3002**.

During operation of electrosurgical tool **100**, the clinician generally grasps tissue, supplies energy to the captured tissue to form a weld or a seal (e.g., by actuating button **214** and/or pedal **216**), and then drives the tissue-cutting element **3030** at the distal end of the axially moveable member **3016** through the captured tissue. According to various embodiments, the translation of the axial movement of the axially moveable member **3016** may be paced, or otherwise controlled, to aid in driving the axially moveable member **3016** at a suitable rate of travel. By controlling the rate of the travel, the likelihood that the captured tissue has been properly and functionally sealed prior to transection with the cutting element **3030** is increased.

Referring now to the embodiment depicted in FIGS. **11-15**, the tool mounting portion **300** includes a tool mounting plate **304** that operably supports a plurality of (four are shown in FIG. **15**) rotatable body portions, driven discs or elements **306**, that each include a pair of pins **308** that extend from a surface of the driven element **306**. One pin **308** is closer to an axis of rotation of each driven element **306** than the other pin **308** on the same driven element **306**, which helps to ensure positive angular alignment of the driven element **306**. Interface **302** may include an adaptor portion **310** that is configured to mountingly engage a mounting plate **304** as will be further discussed below. The illustrated adaptor portion **310** includes an array of electrical connecting pins **312** (FIG. **13**) which may be coupled to a memory structure by a circuit board within the tool mounting portion **300**. While interface **302** is described herein with reference to mechanical, electrical, and magnetic coupling elements, it should be understood that a wide variety of telemetry modalities might be used, including infrared, inductive coupling, or the like in other embodiments.

As can be seen in FIGS. **11-14**, the adapter portion **310** generally includes a tool side **314** and a holder side **316**. A

plurality of rotatable bodies **320** are mounted to a floating plate **318** which has a limited range of movement relative to the surrounding adaptor structure normal to the major surfaces of the adaptor **310**. Axial movement of the floating plate **318** helps decouple the rotatable bodies **320** from the tool mounting portion **300** when levers or other latch formations along the sides of the tool mounting portion housing (not shown) are actuated. Other embodiments may employ other mechanisms/arrangements for releasably coupling the tool mounting portion **300** to the adaptor **310**. In the embodiment of FIGS. **11-15**, rotatable bodies **320** are resiliently mounted to floating plate **318** by resilient radial members which extend into a circumferential indentation about the rotatable bodies **320**. The rotatable bodies **320** can move axially relative to plate **318** by deflection of these resilient structures. When disposed in a first axial position (toward tool side **314**) the rotatable bodies **320** are free to rotate without angular limitation. However, as the rotatable bodies **320** move axially toward tool side **314**, tabs **322** (extending radially from the rotatable bodies **320**) laterally engage detents on the floating plates so as to limit angular rotation of the rotatable bodies **320** about their axes. This limited rotation can be used to help drivingly engage the rotatable bodies **320** with drive pins **332** of a corresponding tool holder portion **330** of the robotic system **10**, as the drive pins **332** will push the rotatable bodies **320** into the limited rotation position until the pins **332** are aligned with (and slide into) openings **334'**. Openings **334** on the tool side **314** and openings **334'** on the holder side **316** of rotatable bodies **320** are configured to accurately align the driven elements **306** (FIG. **15**) of the tool mounting portion **300** with the drive elements **336** of the tool holder **330**. As described above regarding inner and outer pins **308** of driven elements **306**, the openings **304**, **304'** are at differing distances from the axis of rotation on their respective rotatable bodies **306** so as to ensure that the alignment is not 180 degrees from its intended position. Additionally, each of the openings **304** may be slightly radially elongate so as to fittingly receive the pins **308** in the circumferential orientation. This allows the pins **308** to slide radially within the openings **334**, **334'** and accommodate some axial misalignment between the tool **100** and tool holder **330**, while minimizing any angular misalignment and backlash between the drive and driven elements. Openings **334** on the tool side **314** may be offset by about 90 degrees from the openings **334'** (shown in broken lines) on the holder side **316**, as can be seen most clearly in FIG. **14**.

In the embodiment of FIGS. **11-15**, an array of electrical connector pins **340** are located on holder side **316** of adaptor **310** and the tool side **314** of the adaptor **310** includes slots **342** (FIG. **14**) for receiving a pin array (not shown) from the tool mounting portion **300**. In addition to transmitting electrical signals between the surgical tool **100** and the tool holder **330**, at least some of these electrical connections may be coupled to an adaptor memory device **344** (FIG. **13**) by a circuit board of the adaptor **310**.

In the embodiment of FIGS. **11-15**, a detachable latch arrangement **346** is employed to releasably affix the adaptor **310** to the tool holder **330**. As used herein, the term "tool drive assembly" when used in the context of the robotic system **10**, at least encompasses the adapter **310** and tool holder **330** and which have been collectively generally designated as **110** in FIG. **11**. As can be seen in FIG. **11**, the tool holder **330** includes a first latch pin arrangement **337** that is sized to be received in corresponding clevis slots **311** provided in the adaptor **310**. In addition, the tool holder **330** further has second latch pins **338** that are sized to be retained in corresponding latch clevises **313** in the adaptor **310**. See FIG. **11**. A latch assembly **315** is movably supported on the adapter

**310** and has a pair of latch clevises **317** formed therein that is biasable from a first latched position wherein the latch pins **338** are retained within their respective latch clevis **313** and an unlatched position wherein the clevises **317** are aligned with clevises **313** to enable the second latch pins **338** may be inserted into or removed from the latch clevises **313**. A spring or springs (not shown) are employed to bias the latch assembly into the latched position. A lip on the tool side **314** of adaptor **310** slidably receives laterally extending tabs of the tool mounting housing (not shown).

Referring now to FIGS. **5** and **16-21**, the tool mounting portion **300** operably supports a plurality of drive systems for generating various forms of control motions necessary to operate a particular type of end effector that is coupled to the distal end of the elongate shaft assembly **200**. As shown in FIGS. **5** and **16-21**, the tool mounting portion **300** includes a first drive system generally designated as **350** that is configured to receive a corresponding “first” rotary output motion from the tool drive assembly **110** of the robotic system **10** and convert that first rotary output motion to a first rotary control motion to be applied to the surgical end effector. In the illustrated embodiment, the first rotary control motion is employed to rotate the elongate shaft assembly **200** (and surgical end effector **3000**) about a longitudinal tool axis LT-LT.

In the embodiment of FIGS. **5** and **16-18**, the first drive system **350** includes a tube gear segment **354** that is formed on (or attached to) the proximal end **208** of a proximal tube segment **202** of the elongate shaft assembly **200**. The proximal end **208** of the proximal tube segment **202** is rotatably supported on the tool mounting plate **304** of the tool mounting portion **300** by a forward support cradle **352** that is mounted on the tool mounting plate **304**. See FIG. **16**. The tube gear segment **354** is supported in meshing engagement with a first rotational gear assembly **360** that is operably supported on the tool mounting plate **304**. As can be seen in FIG. **16**, the rotational gear assembly **360** comprises a first rotation drive gear **362** that is coupled to a corresponding first one of the driven discs or elements **306** on the holder side **316** of the tool mounting plate **304** when the tool mounting portion **300** is coupled to the tool drive assembly **110**. See FIG. **15**. The rotational gear assembly **360** further comprises a first rotary driven gear **364** that is rotatably supported on the tool mounting plate **304**. The first rotary driven gear **364** is in meshing engagement with a second rotary driven gear **366** which, in turn, is in meshing engagement with the tube gear segment **354**. Application of a first rotary output motion from the tool drive assembly **110** of the robotic system **10** to the corresponding driven element **306** will thereby cause rotation of the rotation drive gear **362**. Rotation of the rotation drive gear **362** ultimately results in the rotation of the elongate shaft assembly **200** (and the surgical end effector **3000**) about the longitudinal tool axis LT-LT (represented by arrow “R” in FIG. **5**). It will be appreciated that the application of a rotary output motion from the tool drive assembly **110** in one direction will result in the rotation of the elongate shaft assembly **200** and surgical end effector **3000** about the longitudinal tool axis LT-LT in a first rotary direction and an application of the rotary output motion in an opposite direction will result in the rotation of the elongate shaft assembly **200** and surgical end effector **3000** in a second rotary direction that is opposite to the first rotary direction.

In embodiment of FIGS. **5** and **16-21**, the tool mounting portion **300** further includes a second drive system generally designated as **370** that is configured to receive a corresponding “second” rotary output motion from the tool drive assembly **110** of the robotic system **10** and convert that second

rotary output motion to a second rotary control motion for application to the surgical end effector. The second drive system **370** includes a second rotation drive gear **372** that is coupled to a corresponding second one of the driven discs or elements **306** on the holder side **316** of the tool mounting plate **304** when the tool mounting portion **300** is coupled to the tool drive assembly **110**. See FIG. **15**. The second drive system **370** further comprises a first rotary driven gear **374** that is rotatably supported on the tool mounting plate **304**. The first rotary driven gear **374** is in meshing engagement with a shaft gear **376** that is movably and non-rotatably mounted onto a proximal drive shaft segment **380**. In this illustrated embodiment, the shaft gear **376** is non-rotatably mounted onto the proximal drive shaft segment **380** by a series of axial keyways **384** that enable the shaft gear **376** to axially move on the proximal drive shaft segment **380** while being non-rotatably affixed thereto. Rotation of the proximal drive shaft segment **380** results in the transmission of a second rotary control motion to the surgical end effector **3000**.

The second drive system **370** in the embodiment of FIGS. **5** and **16-21** includes a shifting system **390** for selectively axially shifting the proximal drive shaft segment **380** which moves the shaft gear **376** into and out of meshing engagement with the first rotary driven gear **374**. For example, as can be seen in FIGS. **16-18**, the proximal drive shaft segment **380** is supported within a second support cradle **382** that is attached to the tool mounting plate **304** such that the proximal drive shaft segment **380** may move axially and rotate relative to the second support cradle **382**. In at least one form, the shifting system **390** further includes a shifter yoke **392** that is slidably supported on the tool mounting plate **304**. The proximal drive shaft segment **380** is supported in the shifter yoke **392** and has a pair of collars **386** thereon such that shifting of the shifter yoke **392** on the tool mounting plate **304** results in the axial movement of the proximal drive shaft segment **380**. In at least one form, the shifting system **390** further includes a shifter solenoid **394** that operably interfaces with the shifter yoke **392**. The shifter solenoid **394** receives control power from the robotic controller **12** such that when the shifter solenoid **394** is activated, the shifter yoke **392** is moved in the distal direction “DD”.

In this illustrated embodiment, a shaft spring **396** is journaled on the proximal drive shaft segment **380** between the shaft gear **376** and the second support cradle **382** to bias the shaft gear **376** in the proximal direction “PD” and into meshing engagement with the first rotary driven gear **374**. See FIGS. **16, 18** and **19**. Rotation of the second rotation drive gear **372** in response to rotary output motions generated by the robotic system **10** ultimately results in the rotation of the proximal drive shaft segment **380** and other drive shaft components coupled thereto (drive shaft assembly **388**) about the longitudinal tool axis LT-LT. It will be appreciated that the application of a rotary output motion from the tool drive assembly **110** in one direction will result in the rotation of the proximal drive shaft segment **380** and ultimately of the other drive shaft components attached thereto in a first direction and an application of the rotary output motion in an opposite direction will result in the rotation of the proximal drive shaft segment **380** in a second direction that is opposite to the first direction. When it is desirable to shift the proximal drive shaft segment **380** in the distal direction “DD” as will be discussed in further detail below, the robotic controller **12** activates the shifter solenoid **390** to shift the shifter yoke **392** in the distal direction “DD”. IN some embodiments, the shifter solenoid **390** may be capable of shifting the proximal drive shaft segment **380** between more than two longitudinal positions. For example, some embodiments, such as those described herein

with respect to FIGS. 83-96, may utilize the rotary drive shaft (e.g., coupled to the proximal drive shaft segment 380) in more than two longitudinal positions.

FIGS. 22-23 illustrate another embodiment that employs the same components of the embodiment depicted in FIGS. 5 and 16-21 except that this embodiment employs a battery-powered drive motor 400 for supplying rotary drive motions to the proximal drive shaft segment 380. Such arrangement enables the tool mounting portion to generate higher rotary output motions and torque which may be advantageous when different forms of end effectors are employed. As can be seen in those Figures, the motor 400 is attached to the tool mounting plate 304 by a support structure 402 such that a driver gear 404 that is coupled to the motor 400 is retained in meshing engagement with the shaft gear 376. In the embodiment of FIGS. 22-23, the support structure 402 is configured to removably engage latch notches 303 formed in the tool mounting plate 304 that are designed to facilitate attachment of a housing member (not shown) to the mounting plate 304 when the motor 400 is not employed. Thus, to employ the motor 400, the clinician removes the housing from the tool mounting plate 304 and then inserts the legs 403 of the support structure into the latch notches 303 in the tool mounting plate 304. The proximal drive shaft segment 380 and the other drive shaft components attached thereto are rotated about the longitudinal tool axis LT-LT by powering the motor 400. As illustrated, the motor 400 is battery powered. In such arrangement, however, the motor 400 interface with the robotic controller 12 such that the robotic system 10 controls the activation of the motor 400. In alternative embodiments, the motor 400 is manually actuatable by an on/off switch (not shown) mounted on the motor 400 itself or on the tool mounting portion 300. In still other embodiments, the motor 400 may receive power and control signals from the robotic system.

The embodiment illustrated in FIGS. 5 and 16-21 includes a manually-actuatable reversing system, generally designated as 410, for manually applying a reverse rotary motion to the proximal drive shaft segment 380 in the event that the motor fails or power to the robotic system is lost or interrupted. Such manually-actuatable reversing system 410 may also be particularly useful, for example, when the drive shaft assembly 388 becomes jammed or otherwise bound in such a way that would prevent reverse rotation of the drive shaft components under the motor power alone. In the illustrated embodiment, the mechanically-actuatable reversing system 410 includes a drive gear assembly 412 that is selectively engagable with the second rotary driven gear 376 and is manually actuatable to apply a reversing rotary motion to the proximal drive shaft segment 380. The drive gear assembly 412 includes a reversing gear 414 that is movably mounted to the tool mounting plate 304. The reversing gear 414 is rotatably journaled on a pivot shaft 416 that is movably mounted to the tool mounting plate 304 through a slot 418. See FIG. 17. In the embodiment of FIGS. 5 and 16-21, the manually-actuatable reversing system 410 further includes a manually actuatable drive gear 420 that includes a body portion 422 that has an arcuate gear segment 424 formed thereon. The body portion 422 is pivotally coupled to the tool mounting plate 304 for selective pivotal travel about an actuator axis A-A (FIG. 16) that is substantially normal to the tool mounting plate 304.

FIGS. 16-19 depict the manually-actuatable reversing system 410 in a first unactuated position. In one example form, an actuator handle portion 426 is formed on or otherwise attached to the body portion 422. The actuator handle portion 426 is sized relative to the tool mounting plate 304 such that a small amount of interference is established between the

handle portion 426 and the tool mounting plate 304 to retain the handle portion 426 in the first unactuated position. However, when the clinician desires to manually actuate the drive gear assembly 412, the clinician can easily overcome the interference fit by applying a pivoting motion to the handle portion 426. As can also be seen in FIGS. 16-19, when the drive gear assembly 412 is in the first unactuated position, the arcuate gear segment 424 is out of meshing engagement with the reversing gear 414. When the clinician desires to apply a reverse rotary drive motion to the proximal drive shaft segment 380, the clinician begins to apply a pivotal ratcheting motion to drive gear 420. As the drive gear 420 begins to pivot about the actuation axis A-A, a portion of the body 422 contacts a portion of the reversing gear 414 and axially moves the reversing gear 414 in the distal direction DD taking the drive shaft gear 376 out of meshing engagement with the first rotary driven gear 374 of the second drive system 370. See FIG. 20. As the drive gear 420 is pivoted, the arcuate gear segment 424 is brought into meshing engagement with the reversing gear 414. Continued ratcheting of the drive gear 420 results in the application of a reverse rotary drive motion to the drive shaft gear 376 and ultimately to the proximal drive shaft segment 380. The clinician may continue to ratchet the drive gear assembly 412 for as many times as are necessary to fully release or reverse the associated end effector component(s). Once a desired amount of reverse rotary motion has been applied to the proximal drive shaft segment 380, the clinician returns the drive gear 420 to the starting or unactuated position wherein the arcuate gear segment 416 is out of meshing engagement with the drive shaft gear 376. When in that position, the shaft spring 396 once again biases the shaft gear 376 into meshing engagement with first rotary driven gear 374 of the second drive system 370.

In use, the clinician may input control commands to the controller or control unit of the robotic system 10 which “robotically-generates” output motions that are ultimately transferred to the various components of the second drive system 370. As used herein, the terms “robotically-generates” or “robotically-generated” refer to motions that are created by powering and controlling the robotic system motors and other powered drive components. These terms are distinguishable from the terms “manually-actuatable” or “manually generated” which refer to actions taken by the clinician which result in control motions that are generated independent from those motions that are generated by powering the robotic system motors. Application of robotically-generated control motions to the second drive system in a first direction results in the application of a first rotary drive motion to the drive shaft assembly 388. When the drive shaft assembly 388 is rotated in a first rotary direction, the axially movable member 3016 is driven in the distal direction “DD” from its starting position toward its ending position in the end effector 3000, for example, as described herein with respect to FIGS. 64-96. Application of robotically-generated control motions to the second drive system in a second direction results in the application of a second rotary drive motion to the drive shaft assembly 388. When the drive shaft assembly 388 is rotated in a second rotary direction, the axially movable member 3016 is driven in the proximal direction “PD” from its ending position toward its starting position in the end effector 3000. When the clinician desires to manually-apply rotary control motion to the drive shaft assembly 388, the drive shaft assembly 388 is rotated in the second rotary direction which causes a firing member (e.g., axially translatable member 3016) to move in the proximal direction “PD” in the end effector. Other embodiments containing the same components are configured such that the manual-application of a rotary con-

trol motion to the drive shaft assembly could cause the drive shaft assembly to rotate in the first rotary direction which could be used to assist the robotically-generated control motions to drive the axially movable member 3016 in the distal direction.

The drive shaft assembly that is used to fire, close and rotate the end effector can be actuated and shifted manually allowing the end effector to release and be extracted from the surgical site as well as the abdomen even in the event that the motor(s) fail, the robotic system loses power or other electronic failure occurs. Actuation of the handle portion 426 results in the manual generation of actuation or control forces that are applied to the drive shaft assembly 388' by the various components of the manually-actuatable reversing system 410. If the handle portion 426 is in its unactuated state, it is biased out of actuatable engagement with the reversing gear 414. The beginning of the actuation of the handle portion 426 shifts the bias. The handle 426 is configured for repeated actuation for as many times as are necessary to fully release the axially movable member 3016 and the end effector 3000.

As illustrated in FIGS. 5 and 16-21, the tool mounting portion 300 includes a third drive system 430 that is configured to receive a corresponding "third" rotary output motion from the tool drive assembly 110 of the robotic system 10 and convert that third rotary output motion to a third rotary control motion. The third drive system 430 includes a third drive pulley 432 that is coupled to a corresponding third one of the driven discs or elements 306 on the holder side 316 of the tool mounting plate 304 when the tool mounting portion 300 is coupled to the tool drive assembly 110. See FIG. 15. The third drive pulley 432 is configured to apply a third rotary control motion (in response to corresponding rotary output motions applied thereto by the robotic system 10) to a corresponding third drive cable 434 that may be used to apply various control or manipulation motions to the end effector that is operably coupled to the shaft assembly 200. As can be most particularly seen in FIGS. 16-17, the third drive cable 434 extends around a third drive spindle assembly 436. The third drive spindle assembly 436 is pivotally mounted to the tool mounting plate 304 and a third tension spring 438 is attached between the third drive spindle assembly 436 and the tool mounting plate 304 to maintain a desired amount of tension in the third drive cable 434. As can be seen in the Figures, cable end portion 434A of the third drive cable 434 extends around an upper portion of a pulley block 440 that is attached to the tool mounting plate 304 and cable end portion 434B extends around a sheave pulley or standoff on the pulley block 440. It will be appreciated that the application of a third rotary output motion from the tool drive assembly 110 in one direction will result in the rotation of the third drive pulley 432 in a first direction and cause the cable end portions 434A and 434B to move in opposite directions to apply control motions to the end effector 3000 or elongate shaft assembly 200 as will be discussed in further detail below. That is, when the third drive pulley 432 is rotated in a first rotary direction, the cable end portion 434A moves in a distal direction "DD" and cable end portion 434B moves in a proximal direction "PD". Rotation of the third drive pulley 432 in an opposite rotary direction result in the cable end portion 434A moving in a proximal direction "PD" and cable end portion 434B moving in a distal direction "DD".

The tool mounting portion 300 illustrated in FIGS. 5 and 16-21 includes a fourth drive system 450 that is configured to receive a corresponding "fourth" rotary output motion from the tool drive assembly 110 of the robotic system 10 and convert that fourth rotary output motion to a fourth rotary control motion. The fourth drive system 450 includes a fourth

drive pulley 452 that is coupled to a corresponding fourth one of the driven discs or elements 306 on the holder side 316 of the tool mounting plate 304 when the tool mounting portion 300 is coupled to the tool drive assembly 110. See FIG. 15.

The fourth drive pulley 452 is configured to apply a fourth rotary control motion (in response to corresponding rotary output motions applied thereto by the robotic system 10) to a corresponding fourth drive cable 454 that may be used to apply various control or manipulation motions to the end effector that is operably coupled to the shaft assembly 200. As can be most particularly seen in FIGS. 16-17, the fourth drive cable 454 extends around a fourth drive spindle assembly 456. The fourth drive spindle assembly 456 is pivotally mounted to the tool mounting plate 304 and a fourth tension spring 458 is attached between the fourth drive spindle assembly 456 and the tool mounting plate 304 to maintain a desired amount of tension in the fourth drive cable 454. Cable end portion 454A of the fourth drive cable 454 extends around a bottom portion of the pulley block 440 that is attached to the tool mounting plate 304 and cable end portion 454B extends around a sheave pulley or fourth standoff 462 on the pulley block 440. It will be appreciated that the application of a rotary output motion from the tool drive assembly 110 in one direction will result in the rotation of the fourth drive pulley 452 in a first direction and cause the cable end portions 454A and 454B to move in opposite directions to apply control motions to the end effector or elongate shaft assembly 200 as will be discussed in further detail below. That is, when the fourth drive pulley 452 is rotated in a first rotary direction, the cable end portion 454A moves in a distal direction "DD" and cable end portion 454B moves in a proximal direction "PD". Rotation of the fourth drive pulley 452 in an opposite rotary direction result in the cable end portion 454A moving in a proximal direction "PD" and cable end portion 454B to move in a distal direction "DD".

The surgical tool 100 as depicted in FIGS. 5-6 includes an articulation joint 3500. In such embodiment, the third drive system 430 may also be referred to as a "first articulation drive system" and the fourth drive system 450 may be referred to herein as a "second articulation drive system". Likewise, the third drive cable 434 may be referred to as a "first proximal articulation cable" and the fourth drive cable 454 may be referred to herein as a "second proximal articulation cable".

The tool mounting portion 300 of the embodiment illustrated in FIGS. 5 and 16-21 includes a fifth drive system generally designated as 470 that is configured to axially displace a drive rod assembly 490. The drive rod assembly 490 includes a proximal drive rod segment 492 that extends through the proximal drive shaft segment 380 and the drive shaft assembly 388. See FIG. 18. The fifth drive system 470 includes a movable drive yoke 472 that is slidably supported on the tool mounting plate 304. The proximal drive rod segment 492 is supported in the drive yoke 372 and has a pair of retainer balls 394 thereon such that shifting of the drive yoke 372 on the tool mounting plate 304 results in the axial movement of the proximal drive rod segment 492. In at least one example form, the fifth drive system 370 further includes a drive solenoid 474 that operably interfaces with the drive yoke 472. The drive solenoid 474 receives control power from the robotic controller 12. Actuation of the drive solenoid 474 in a first direction will cause the drive rod assembly 490 to move in the distal direction "DD" and actuation of the drive solenoid 474 in a second direction will cause the drive rod assembly 490 to move in the proximal direction "PD". As can be seen in FIG. 5, the end effector 3000 includes a jaw members that are movable between open and closed positions upon application of axial closure motions to a closure system.

In the illustrated embodiment of FIGS. 5 and 16-21, the fifth drive system 470 is employed to generate such closure motions. Thus, the fifth drive system 470 may also be referred to as a "closure drive".

The surgical tool 100 depicted in FIGS. 5 and 16-21 includes an articulation joint 3500 that cooperates with the third and fourth drive systems 430, 450, respectively for articulating the end effector 3000 about the longitudinal tool axis "LT". The articulation joint 3500 includes a proximal socket tube 3502 that is attached to the distal end 233 of the distal outer tube portion 231 and defines a proximal ball socket 3504 therein. See FIG. 24. A proximal ball member 3506 is movably seated within the proximal ball socket 3504. As can be seen in FIG. 24, the proximal ball member 3506 has a central drive passage 3508 that enables the distal drive shaft segment 3740 to extend therethrough. In addition, the proximal ball member 3506 has four articulation passages 3510 therein which facilitate the passage of distal cable segments 444, 445, 446, 447 therethrough. In various embodiments, distal cable segments 444, 445, 446, 447 may be directly or indirectly coupled to proximal cable end portions 434A, 434B, 454A, 454B, respectively, for example, as illustrated by FIG. 24A. As can be further seen in FIG. 24, the articulation joint 3500 further includes an intermediate articulation tube segment 3512 that has an intermediate ball socket 3514 formed therein. The intermediate ball socket 3514 is configured to movably support therein an end effector ball 3522 formed on an end effector connector tube 3520. The distal cable segments 444, 445, 446, 447 extend through cable passages 3524 formed in the end effector ball 3522 and are attached thereto by lugs 3526 received within corresponding passages 3528 in the end effector ball 3522. Other attachment arrangements may be employed for attaching distal cable segments 444, 445, 446, 447 to the end effector ball 3522.

A unique and novel rotary support joint assembly, generally designated as 3540, is depicted in FIGS. 25 and 26. The illustrated rotary support joint assembly 3540 includes a connector portion 4012 of the end effector drive housing 4010 that is substantially cylindrical in shape. A first annular race 4014 is formed in the perimeter of the cylindrically-shaped connector portion 4012. The rotary support joint assembly 3540 further comprises a distal socket portion 3530 that is formed in the end effector connector tube 3520 as shown in FIGS. 25 and 26. The distal socket portion 3530 is sized relative to the cylindrical connector portion 4012 such that the connector portion 4012 can freely rotate within the socket portion 3530. A second annular race 3532 is formed in an inner wall 3531 of the distal socket portion 3530. A window 3533 is provided through the distal socket 3530 that communicates with the second annular race 3532 therein. As can also be seen in FIGS. 25 and 26, the rotary support joint assembly 3540 further includes a ring-like bearing 3534. In various example embodiments, the ring-like bearing 3534 comprises a plastic deformable substantially-circular ring that has a cut 3535 therein. The cut forms free ends 3536, 3537 in the ring-like bearing 3534. As can be seen in FIG. 25, the ring-like bearing 3534 has a substantially annular shape in its natural unbiased state.

To couple a surgical end effector 3000 (e.g., a first portion of a surgical tool) to the articulation joint 3500 (e.g., a second portion of a surgical tool), the cylindrically shaped connector position 4012 is inserted into the distal socket portion 3530 to bring the second annular race 3532 into substantial registry with the first annular race 4014. One of the free ends 3536, 3537 of the ring-like bearing is then inserted into the registered annular races 4014, 3532 through the window 3533 in the distal socket portion 3530 of the end effector connector

tube 3520. To facilitate easy insertion, the window or opening 3533 has a tapered surface 3538 formed thereon. See FIG. 25. The ring-like bearing 3534 is essentially rotated into place and, because it tends to form a circle or ring, it does not tend to back out through the window 3533 once installed. Once the ring-like bearing 3534 has been inserted into the registered annular races 4014, 3532, the end effector connector tube 3520 will be rotatably affixed to the connector portion 4012 of the end effector drive housing 4010. Such arrangement enables the end effector drive housing 4010 to rotate about the longitudinal tool axis LT-LT relative to the end effector connector tube 3520. The ring-like bearing 3534 becomes the bearing surface that the end effector drive housing 4010 then rotates on. Any side loading tries to deform the ring-like bearing 3534 which is supported and contained by the two interlocking races 4014, 3532 preventing damage to the ring-like bearing 3534. It will be understood that such simple and effective joint assembly employing the ring-like bearing 3534 forms a highly lubricious interface between the rotatable portions 4010, 3530. If during assembly, one of the free ends 3536, 3537 is permitted to protrude out through the window 3533 (see e.g., FIG. 26), the rotary support joint assembly 3540 may be disassembled by withdrawing the ring-like bearing member 3532 out through the window 3533. The rotary support joint assembly 3540 allows for easy assembly and manufacturing while also providing for good end effector support while facilitating rotary manipulation thereof.

The articulation joint 3500 facilitates articulation of the end effector 3000 about the longitudinal tool axis LT. For example, when it is desirable to articulate the end effector 3000 in a first direction "FD" as shown in FIG. 5, the robotic system 10 may power the third drive system 430 such that the third drive spindle assembly 436 (FIGS. 16-18) is rotated in a first direction thereby drawing the proximal cable end portion 434A and ultimately distal cable segment 444 in the proximal direction "PD" and releasing the proximal cable end portion 434B and distal cable segment 445 to thereby cause the end effector ball 3522 to rotate within the socket 3514. Likewise, to articulate the end effector 3000 in a second direction "SD" opposite to the first direction FD, the robotic system 10 may power the third drive system 430 such that the third drive spindle assembly 436 is rotated in a second direction thereby drawing the proximal cable end portion 434B and ultimately distal cable segment 445 in the proximal direction "PD" and releasing the proximal cable end portion 434A and distal cable segment 444 to thereby cause the end effector ball 3522 to rotate within the socket 3514. When it is desirable to articulate the end effector 3000 in a third direction "TD" as shown in FIG. 5, the robotic system 10 may power the fourth drive system 450 such that the fourth drive spindle assembly 456 is rotated in a third direction thereby drawing the proximal cable end portion 454A and ultimately distal cable segment 446 in the proximal direction "PD" and releasing the proximal cable end portion 454B and distal cable segment 447 to thereby cause the end effector ball 3522 to rotate within the socket 3514. Likewise, to articulate the end effector 3000 in a fourth direction "FTH" opposite to the third direction TD, the robotic system 10 may power the fourth drive system 450 such that the fourth drive spindle assembly 456 is rotated in a fourth direction thereby drawing the proximal cable end portion 454B and ultimately distal cable segment 447 in the proximal direction "PD" and releasing the proximal cable end portion 454A and distal cable segment 446 to thereby cause the end effector ball 3522 to rotate within the socket 3514.

The end effector embodiment depicted in FIGS. 5 and 16-21 employs rotary and longitudinal motions that are trans-

mitted from the tool mounting portion **300** through the elongate shaft assembly for actuation. The drive shaft assembly employed to transmit such rotary and longitudinal motions (e.g., torsion, tension and compression motions) to the end effector is relatively flexible to facilitate articulation of the end effector about the articulation joint. FIGS. 27-28 illustrate an alternative drive shaft assembly **3600** that may be employed in connection with the embodiment illustrated in FIGS. 5 and 16-21 or in other embodiments. In the embodiment depicted in FIG. 5 the proximal drive shaft segment **380** comprises a segment of drive shaft assembly **3600** and the distal drive shaft segment **3740** similarly comprises another segment of drive shaft assembly **3600**. The drive shaft assembly **3600** includes a drive tube **3602** that has a series of annular joint segments **3604** cut therein. In that illustrated embodiment, the drive tube **3602** comprises a distal portion of the proximal drive shaft segment **380**. For example, the shaft assembly **3600**, as well as the shaft assemblies **3600'**, **3600''** described herein with respect to FIGS. 27-45 may be components of and/or mechanically coupled to various rotary drive shafts described herein including, for example, rotary drive shafts **680**, **1270**, **1382**, etc.

The drive tube **3602** comprises a hollow metal tube (stainless steel, titanium, etc.) that has a series of annular joint segments **3604** formed therein. The annular joint segments **3604** comprise a plurality of loosely interlocking dovetail shapes **3606** that are, for example, cut into the drive tube **3602** by a laser and serve to facilitate flexible movement between the adjoining joint segments **3604**. See FIG. 28. Such laser cutting of a tube stock creates a flexible hollow drive tube that can be used in compression, tension and torsion. Such arrangement employs a full diametric cut that is interlocked with the adjacent part via a "puzzle piece" configuration. These cuts are then duplicated along the length of the hollow drive tube in an array and are sometimes "clocked" or rotated to change the tension or torsion performance.

FIGS. 29-33 illustrate alternative example micro-annular joint segments **3604'** that comprise plurality of laser cut shapes **3606'** that roughly resemble loosely interlocking, opposed "T" shapes and T-shapes with a notched portion therein. The annular joint segments **3604**, **3604'** essentially comprise multiple micro-articulating torsion joints. That is, each joint segment **3604**, **3604'** can transmit torque while facilitating relative articulation between each annular joint segment. As shown in FIGS. 29-30, the joint segment **3604D'** on the distal end **3603** of the drive tube **3602** has a distal mounting collar portion **3608D'** that facilitates attachment to other drive components for actuating the end effector or portions of the quick disconnect joint, etc. and the joint segment **3604P'** on the proximal end **3605** of the drive tube **3602** has a proximal mounting collar portion **3608P'** that facilitates attachment to other proximal drive components or portions of the quick disconnect joint.

The joint-to-joint range of motion for each particular drive shaft assembly **3600** can be increased by increasing the spacing in the laser cuts. For example, to ensure that the joint segments **3604'** remain coupled together without significantly diminishing the drive tube's ability to articulate through desired ranges of motion, a secondary constraining member **3610** is employed. In the embodiment depicted in FIGS. 31-32, the secondary constraining member **3610** comprises a spring **3612** or other helically-wound member. In various example embodiments, the distal end **3614** of the spring **3612** corresponds to the distal mounting collar portion **3608D'** and is wound tighter than the central portion **3616** of the spring **3612**. Similarly, the proximal end **3618** of the spring **3612** is wound tighter than the central portion **3616** of

the spring **3612**. In other embodiments, the constraining member **3610** is installed on the drive tube **3602** with a desired pitch such that the constraining member also functions, for example, as a flexible drive thread for threadably engaging other threaded control components on the end effector and/or the control system. It will also be appreciated that the constraining member may be installed in such a manner as to have a variable pitch to accomplish the transmission of the desired rotary control motions as the drive shaft assembly is rotated. For example, the variable pitch arrangement of the constraining member may be used to enhance open/close and firing motions which would benefit from differing linear strokes from the same rotation motion. In other embodiments, for example, the drive shaft assembly comprises a variable pitch thread on a hollow flexible drive shaft that can be pushed and pulled around a ninety degree bend. In still other embodiments, the secondary constraining member comprises an elastomeric tube or coating **3611** applied around the exterior or perimeter of the drive tube **3602** as illustrated in FIG. 33A. In still another embodiment, for example, the elastomeric tube or coating **3611'** is installed in the hollow passageway **3613** formed within the drive tube **3602** as shown in FIG. 33B.

Such drive shaft arrangements comprise a composite torsional drive axle which allows superior load transmission while facilitating a desirable axial range of articulation. See, e.g., FIGS. 33 and 33A-33B. That is, these composite drive shaft assemblies allow a large range of motion while maintaining the ability to transmit torsion in both directions as well as facilitating the transmission of tension and compression control motions therethrough. In addition, the hollow nature of such drive shaft arrangements facilitate passage of other control components therethrough while affording improved tension loading. For example, some other embodiments include a flexible internal cable that extends through the drive shaft assembly which can assist in the alignment of the joint segments while facilitating the ability to apply tension motions through the drive shaft assembly. Moreover, such drive shaft arrangements are relatively easily to manufacture and assemble.

FIGS. 34-37 depict a segment **3620** of a drive shaft assembly **3600'**. This embodiment includes joint segments **3622**, **3624** that are laser cut out of tube stock material (e.g., stainless steel, titanium, polymer, etc.). The joint segments **3622**, **3624** remain loosely attached together because the cuts **3626** are radial and are somewhat tapered. For example, each of the lug portions **3628** has a tapered outer perimeter portion **3629** that is received within a socket **3630** that has a tapered inner wall portion. See, e.g., FIGS. 35 and 37. Thus, there is no assembly required to attach the joint segments **3622**, **3624** together. As can be seen in the Figures, joint segment **3622** has opposing pivot lug portions **3628** cut on each end thereof that are pivotally received in corresponding sockets **3630** formed in adjacent joint segments **3624**.

FIGS. 34-37 illustrate a small segment of the drive shaft assembly **3600'**. Those of ordinary skill in the art will appreciate that the lugs/sockets may be cut throughout the entire length of the drive shaft assembly. That is, the joint segments **3624** may have opposing sockets **3630** cut therein to facilitate linkage with adjoining joint segments **3622** to complete the length of the drive shaft assembly **3600'**. In addition, the joint segments **3624** have an angled end portion **3632** cut therein to facilitate articulation of the joint segments **3624** relative to the joint segments **3622** as illustrated in FIGS. 36-37. In the illustrated embodiment, each lug **3628** has an articulation stop portion **3634** that is adapted to contact a corresponding articulation stop **3636** formed in the joint segment **3622**. See



FIGS. 36-37. Other embodiments, which may otherwise be identical to the segment 3620, are not provided with the articulation stop portions 3634 and stops 3636.

As indicated above, the joint-to-joint range of motion for each particular drive shaft assembly can be increased by increasing the spacing in the laser cuts. In such embodiments, to ensure that the joint segments 3622, 3624 remain coupled together without significantly diminishing the drive tube's ability to articulate through desired ranges of motion, a secondary constraining member in the form of an elastomeric sleeve or coating 3640 is employed. Other embodiments employ other forms of constraining members disclosed herein and their equivalent structures. As can be seen in FIG. 34, the joint segments 3622, 3624 are capable of pivoting about pivot axes "PA-PA" defined by the pivot lugs 3628 and corresponding sockets 3630. To obtain an expanded range of articulation, the drive shaft assembly 3600' may be rotated about the tool axis TL-TL while pivoting about the pivot axes PA-PA.

FIGS. 38-43 depict a segment 3640 of another drive shaft assembly 3600". The drive shaft assembly 3600" comprises a multi-segment drive system that includes a plurality of interconnected joint segments 3642 that form a flexible hollow drive tube 3602". A joint segment 3642 includes a ball connector portion 3644 and a socket portion 3648. Each joint segment 3642 may be fabricated by, for example, metal injection molding "MIM" and be fabricated from 17-4, 17-7, 420 stainless steel. Other embodiments may be machined from 300 or 400 series stainless steel, 6065 or 7071 aluminum or titanium. Still other embodiments could be molded out of plastic infilled or unfilled Nylon, Ultem, ABS, Polycarbonate or Polyethylene, for example. As can be seen in the Figures, the ball connector 3644 is hexagonal in shape. That is, the ball connector 3644 has six arcuate surfaces 3646 formed thereon and is adapted to be rotatably received in like-shaped sockets 3650. Each socket 3650 has a hexagonally-shaped outer portion 3652 formed from six flat surfaces 3654 and a radially-shaped inner portion 3656. See FIG. 41. Each joint segment 3642 is identical in construction, except that the socket portions of the last joint segments forming the distal and proximal ends of the drive shaft assembly 3600 may be configured to operably mate with corresponding control components. Each ball connector 3644 has a hollow passage 3645 therein that cooperate to form a hollow passageway 3603 through the hollow flexible drive tube 3602".

As can be seen in FIGS. 42 and 43, the interconnected joint segments 3642 are contained within a constraining member 3660 which comprises a tube or sleeve fabricated from a flexible polymer material, for example. FIG. 44 illustrates a flexible inner core member 3662 extending through the interconnected joint segments 3642. The inner core member 3662 comprises a solid member fabricated from a polymer material or a hollow tube or sleeve fabricated from a flexible polymer material. FIG. 45 illustrates another embodiment wherein a constraining member 3660 and an inner core member 3662 are both employed.

Drive shaft assembly 3600" facilitates transmission of rotational and translational motion through a variable radius articulation joint. The hollow nature of the drive shaft assembly 3600" provides room for additional control components or a tensile element (e.g., a flexible cable) to facilitate tensile and compressive load transmission. In other embodiments, however, the joint segments 3624 do not afford a hollow passage through the drive shaft assembly. In such embodiments, for example, the ball connector portion is solid. Rotary motion is translated via the edges of the hexagonal surfaces. Tighter tolerances may allow greater load capacity. Using a

cable or other tensile element through the centerline of the drive shaft assembly 3600", the entire drive shaft assembly 3600" can be rotated bent, pushed and pulled without limiting range of motion. For example, the drive shaft assembly 3600" may form an arcuate drive path, a straight drive path, a serpentine drive path, etc.

While the various example embodiments described herein are configured to operably interface with and be at least partially actuated by a robotic system, the various end effector and elongate shaft components described herein, may be effectively employed in connection with handheld tools. For example, FIGS. 46-47 depict a handheld surgical tool 2400 that may employ various components and systems described above to operably actuate an electrosurgical end effector 3000 coupled thereto. It will be appreciated that the handheld surgical tool 2400 may contain and/or be electrically connected to a generator, such as the generator 3002, for generating an electrosurgical drive signal to drive the end effector 3000. In the example embodiment depicted in FIGS. 46-47, a quick disconnect joint 2210 is employed to couple the end effector 3000 to an elongate shaft assembly 2402. For example, the quick disconnect joint 2210 may operate to remove the end effector 3000 in the manner described herein with reference to FIGS. 106-115. To facilitate articulation of the end effector 3000 about the articulation joint 3500, the proximal portion of the elongate shaft assembly 2402 includes an example manually actuatable articulation drive 2410.

Referring now to FIGS. 48-50, in at least one example form, the articulation drive 2410 includes four axially movable articulation slides that are movably journaled on the proximal drive shaft segment 380' between the proximal outer tube segment 2214 and the proximal drive shaft segment 380'. For example, the articulation cable segment 434A' is attached to a first articulation slide 2420 that has a first articulation actuator rod 2422 protruding therefrom. Articulation cable segment 434B' is attached to a second articulation slide 2430 that is diametrically opposite from the first articulation slide 2420. The second articulation slide 2430 has a second articulation actuator rod 2432 protruding therefrom. Articulation cable segment 454A' is attached to a third articulation slide 2440 that has a third articulation actuator rod 2442 protruding therefrom. Articulation cable segment 454B' is attached to a fourth articulation slide 2450 that is diametrically opposite to the third articulation slide 2440. A fourth articulation actuator rod 2452 protrudes from the fourth articulation slide 2450. Articulation actuator rods 2422, 2432, 2442, 2452 facilitate the application of articulation control motions to the articulation slides 2420, 2430, 2440, 2450, respectively by an articulation ring assembly 2460.

As can be seen in FIG. 48, the articulation actuator rods 2422, 2432, 2442, 2452 movably pass through a mounting ball 2470 that is journaled on a proximal outer tube segment 2404. In at least one embodiment, the mounting ball 2470 may be manufactured in segments that are attached together by appropriate fastener arrangements (e.g., welding, adhesive, screws, etc.). As shown in FIG. 50, the articulation actuator rods 2422 and 2432 extend through slots 2472 in the proximal outer tube segment 2404 and slots 2474 in the mounting ball 2470 to enable the articulation slides 2420, 2430 to axially move relative thereto. Although not shown, the articulation actuator rods 2442, 2452 extend through similar slots 2472, 2474 in the proximal outer tube segment 2404 and the mounting ball 2470. Each of the articulation actuator rods 2422, 2432, 2442, 2452 protrude out of the corresponding slots 2474 in the mounting ball 2470 to be operably

received within corresponding mounting sockets **2466** in the articulation ring assembly **2460**. See FIG. **49**.

In at least one example form, the articulation ring assembly **2460** is fabricated from a pair of ring segments **2480**, **2490** that are joined together by, for example, welding, adhesive, snap features, screws, etc. to form the articulation ring assembly **2460**. The ring segments **2480**, **2490** cooperate to form the mounting sockets **2466**. Each of the articulation actuator rods has a mounting ball **2468** formed thereon that are each adapted to be movably received within a corresponding mounting socket **2466** in the articulation ring assembly **2460**.

Various example embodiments of the articulation drive **2410** may further include an example locking system **2486** configured to retain the articulation ring assembly **2460** in an actuated position. In at least one example form, the locking system **2486** comprises a plurality of locking flaps formed on the articulation ring assembly **2460**. For example, the ring segments **2480**, **2490** may be fabricated from a somewhat flexible polymer or rubber material. Ring segment **2480** has a series of flexible proximal locking flaps **2488** formed therein and ring segment **2490** has a series of flexible distal locking flaps **2498** formed therein. Each locking flap **2488** has at least one locking detent **2389** formed thereon and each locking flap **2498** has at least one locking detent **2399** thereon. Locking detents **2389**, **2399** may serve to establish a desired amount of locking friction with the articulation ball so as to retain the articulation ball in position. In other example embodiments, the locking detents **2389**, **2399** are configured to matingly engage various locking dimples formed in the outer perimeter of the mounting ball **2470**.

Operation of the articulation drive **2410** can be understood from reference to FIGS. **49** and **50**. FIG. **49** illustrates the articulation drive **2410** in an unarticulated position. In FIG. **50**, the clinician has manually tilted the articulation ring assembly **2460** to cause the articulation slide **2420** to move axially in the distal direction “DD” thereby advancing the articulation cable segment **434A'** distally. Such movement of the articulation ring assembly **2460** also results in the axial movement of the articulation slide **2430** in the proximal direction which ultimately pulls the articulation cable **434B** in the proximal direction. Such pushing and pulling of the articulation cable segments **434A'**, **434B'** will result in articulation of the end effector **3000** relative to the longitudinal tool axis “LT-LT” in the manner described above. To reverse the direction of articulation, the clinician simply reverses the orientation of the articulation ring assembly **2460** to thereby cause the articulation slide **2430** to move in the distal direction “DD” and the articulation slide **2420** to move in the proximal direction “PD”. The articulation ring assembly **2460** may be similarly actuated to apply desired pushing and pulling motions to the articulation cable segments **454A'**, **454B'**. The friction created between the locking detents **2389**, **2399** and the outer perimeter of the mounting ball serves to retain the articulation drive **2410** in position after the end effector **3000** has been articulated to the desired position. In alternative example embodiments, when the locking detents **2389**, **2399** are positioned so as to be received in corresponding locking dimples in the mounting ball, the mounting ball will be retained in position.

In the illustrated example embodiments and others, the elongate shaft assembly **2402** operably interfaces with a handle assembly **2500**. An example embodiment of handle assembly **2500** comprises a pair of handle housing segments **2502**, **2504** that are coupled together to form a housing for various drive components and systems as will be discussed in further detail below. See, e.g., FIG. **46**. The handle housing segments **2502**, **2504** may be coupled together by screws,

snap features, adhesive, etc. When coupled together, the handle segments **2502**, **2504** may form a handle assembly **2500** that includes a pistol grip portion **2506**.

To facilitate selective rotation of the end effector **3000** about the longitudinal tool axis “LT=LT”, the elongate shaft assembly **2402** may interface with a first drive system, generally designated as **2510**. The drive system **2510** includes a manually-actuatable rotation nozzle **2512** that is rotatably supported on the handle assembly **2500** such that it can be rotated relative thereto as well as be axially moved between a locked position and an unlocked position.

The surgical tool **2400** may include a closure system **3670**. The closure system **3670** may be used in some embodiments to bring about distal and proximal motion in the elongate shaft assembly **2402** and end effector **3000**. For example, in some embodiments, the closure system **3670** may drive an axially movable member such as **3016**. For example, the closure system **3670** may be used to translate the axially movable member **3016** instead of the various rotary drive shafts described herein with respect to FIGS. **64-82**, **83-91** and **92-96**. In this example embodiment, the closure system **3670** is actuated by a closure trigger **2530** that is pivotally mounted to the handle frame assembly **2520** that is supported within the handle housing segments **2502**, **2504**. The closure trigger **2530** includes an actuation portion **2532** that is pivotally mounted on a pivot pin **2531** that is supported within the handle frame assembly **2520**. See FIG. **51**. Such example arrangement facilitates pivotal travel toward and away from the pistol grip portion **2506** of the handle assembly **2500**. As can be seen in FIG. **51**, the closure trigger **2530** includes a closure link **2534** that is linked to the first pivot link and gear assembly **3695** by a closure wire **2535**. Thus, by pivoting the closure trigger **2530** toward the pistol grip portion **2506** of the handle assembly **2500** into an actuated position, the closure link **2534** and closure wire **2535** causes the first pivot link and gear assembly **3695** to move in the distal direction “DD” to cause distal motion through the shaft and, in some embodiments, to the end effector.

The surgical tool **2400** may further include a closure trigger locking system **2536** to retain the closure trigger in the actuated position. In at least one example form, the closure trigger locking system **2536** includes a closure lock member **2538** that is pivotally coupled to the handle frame assembly **2520**. As can be seen in FIGS. **52** and **53**, the closure lock member **2538** has a lock arm **2539** formed thereon that is configured to ride upon an arcuate portion **2537** of the closure link **2534** as the closure trigger **2530** is actuated toward the pistol grip portion **2506**. When the closure trigger **2530** has been pivoted to the fully actuated position, the lock arm **2539** drops behind the end of the closure link **2534** and prevents the closure trigger **2530** from returning to its unactuated position. Thus, the distal motion translated through the shaft assembly to the end effector may be locked. To enable the closure trigger **2530** to return to its unactuated position, the clinician simply pivots the closure lock member **2538** until the lock arm **2539** thereof disengages the end of the closure link **2534** to thereby permit the closure link **2534** to move to the unactuated position.

The closure trigger **2530** is returned to the unactuated position by a closure return system **2540**. For example, as can be seen in FIG. **51**, one example form of the closure trigger return system **2540** includes a closure trigger slide member **2542** that is linked to the closure link **2534** by a closure trigger yoke **2544**. The closure trigger slide member **2542** is slidably supported within a slide cavity **2522** in the handle frame assembly **2520**. A closure trigger return spring **2546** is positioned within the slide cavity **2520** to apply a biasing force to the closure trigger slide member **2542**. Thus, when the clini-

cian actuates the closure trigger **2530**, the closure trigger yoke **2544** moves the closure trigger slide member **2542** in the distal direction “DD” compressing the closure trigger return spring **2546**. When the closure trigger locking system **2536** is disengaged and the closure trigger **2530** is released, the closure trigger return spring **2546** moves the closure trigger slide member **2542** in the proximal direction “PD” to thereby pivot the closure trigger **2530** into the starting unactuated position.

The surgical tool **2400** can also employ any of the various example drive shaft assemblies described above. In at least one example form, the surgical tool **2400** employs a second drive system **2550** for applying rotary control motions to a proximal drive shaft assembly **380'**. See FIG. **55**. The second drive system **2550** may include a motor assembly **2552** that is operably supported in the pistol grip portion **2506**. The motor assembly **2552** may be powered by a battery pack **2554** that is removably attached to the handle assembly **2500** or it may be powered by a source of alternating current. A second drive gear **2556** is operably coupled to the drive shaft **2555** of the motor assembly **2552**. The second drive gear **2556** is supported for meshing engagement with a second rotary driven gear **2558** that is attached to the proximal drive shaft segment **380'** of the drive shaft assembly. In at least one form, for example, the second drive gear **2556** is also axially movable on the motor drive shaft **2555** relative to the motor assembly **2552** in the directions represented by arrow “U” in FIG. **55**. A biasing member, e.g., a coil spring **2560** or similar member, is positioned between the second drive gear **2556** and the motor housing **2553** and serves to bias the second drive gear **2556** on the motor drive shaft **2555** into meshing engagement with a first gear segment **2559** on the second driven gear **2558**.

The second drive system **2550** may further include a firing trigger assembly **2570** that is movably, e.g., pivotally attached to the handle frame assembly **2520**. In at least one example form, for example, the firing trigger assembly **2570** includes a first rotary drive trigger **2572** that cooperates with a corresponding switch/contact (not shown) that electrically communicates with the motor assembly **2552** and which, upon activation, causes the motor assembly **2552** to apply a first rotary drive motion to the second driven gear **2558**. In addition, the firing trigger assembly **2570** further includes a retraction drive trigger **2574** that is pivotal relative to the first rotary drive trigger. The retraction drive trigger **2574** operably interfaces with a switch/contact (not shown) that is in electrical communication with the motor assembly **2552** and which, upon activation, causes the motor assembly **2552** to apply a second rotary drive motion to the second driven gear **2558**. The first rotary drive motion results in the rotation of the drive shaft assembly and the implement drive shaft in the end effector to cause the firing member to move distally in the end effector **3000**. Conversely, the second rotary drive motion is opposite to the first rotary drive motion and will ultimately result in rotation of the drive shaft assembly and the implement drive shaft in a rotary direction which results in the proximal movement or retraction of the firing member in the end effector **3000**.

The illustrated embodiment also includes a manually actuable safety member **2580** that is pivotally attached to the closure trigger actuation portion **2532** and is selectively pivotable between a first “safe” position wherein the safety member **2580** physically prevents pivotal travel of the firing trigger assembly **2570** and a second “off” position, wherein the clinician can freely pivot the firing trigger assembly **2570**. As can be seen in FIG. **51**, a first dimple **2582** is provided in the closure trigger actuation portion **2532** that corresponds to the first position of the safety member **2580**. When the safety member **2580** is in the first position, a detent (not shown) on

the safety member **2580** is received within the first dimple **2582**. A second dimple **2584** is also provided in the closure trigger actuation portion **2532** that corresponds to the second position of the safety member **2580**. When the safety member **2580** is in the second position, the detent on the safety member **2580** is received within the second dimple **2582**.

In at least some example forms, the surgical tool **2400** may include a mechanically actuatable reversing system, generally designated as **2590**, for mechanically applying a reverse rotary motion to the proximal drive shaft segment **380'** in the event that the motor assembly **2552** fails or battery power is lost or interrupted. Such mechanical reversing system **2590** may also be particularly useful, for example, when the drive shaft system components operably coupled to the proximal drive shaft segment **380'** become jammed or otherwise bound in such a way that would prevent reverse rotation of the drive shaft components under the motor power alone. In at least one example form, the mechanically actuatable reversing system **2590** includes a reversing gear **2592** that is rotatably mounted on a shaft **2524A** formed on the handle frame assembly **2520** in meshing engagement with a second gear segment **2562** on the second driven gear **2558**. See FIG. **53**. Thus, the reversing gear **2592** freely rotates on shaft **2524A** when the second driven gear **2558** rotates the proximal drive shaft segment **380'** of the drive shaft assembly.

In various example forms, the mechanical reversing system **2590** further includes a manually actuatable driver **2594** in the form of a lever arm **2596**. As can be seen in FIGS. **56** and **57**, the lever arm **2596** includes a yoke portion **2597** that has elongate slots **2598** therethrough. The shaft **2524A** extends through slot **2598A** and a second opposing shaft **2598B** formed on the handle housing assembly **2520** extends through the other elongate slot to movably affix the lever arm **2596** thereto. In addition, the lever arm **2596** has an actuator fin **2597** formed thereon that can meshingly engage the reversing gear **2592**. There is a detent or interference that keeps the lever arm **2596** in the unactuated state until the clinician exerts a substantial force to actuate it. This keeps it from accidentally initiating if inverted. Other embodiments may employ a spring to bias the lever arm into the unactuated state. Various example embodiments of the mechanical reversing system **2590** further includes a knife retractor button **2600** that is movably journaled in the handle frame assembly **2520**. As can be seen in FIGS. **56** and **57**, the knife retractor button **2600** includes a disengagement flap **2602** that is configured to engage the top of the second drive gear **2556**. The knife retractor button **2600** is biased to a disengaged position by a knife retractor spring **2604**. When in the disengaged position, the disengagement flap **2602** is biased out of engagement with the second drive gear **2556**. Thus, until the clinician desires to activate the mechanical reversing system **2590** by depressing the knife retractor button **2600**, the second drive gear **2556** is in meshing engagement with the first gear segment **2559** of the second driven gear **2558**.

When the clinician desires to apply a reverse rotary drive motion to the proximal drive shaft segment **380'**, the clinician depresses the knife retractor button **2600** to disengage the first gear segment **2559** on the second driven gear **2558** from the second drive gear **2556**. Thereafter, the clinician begins to apply a pivotal ratcheting motion to the manually actuatable driver **2594** which causes the gear fin **2597** thereon to drive the reversing gear **2592**. The reversing gear **2592** is in meshing engagement with the second gear segment **2562** on the second driven gear **2558**. Continued ratcheting of the manually actuatable driver **2594** results in the application of a reverse rotary drive motion to the second gear segment **2562** and ultimately to the proximal drive shaft segment **380'**. The

clinician may continue to ratchet the driver **2594** for as many times as are necessary to fully release or reverse the associated end effector component(s). Once a desired amount of reverse rotary motion has been applied to the proximal drive shaft segment **380'**, the clinician releases the knife retractor button **2600** and the driver **2594** to their respective starting or unactuated positions wherein the fin **2597** is out of engagement with the reversing gear **2592** and the second drive gear **2556** is once again in meshing engagement with the first gear segment **2559** on the second driven gear **2558**.

The surgical tool **2400** can also be employed with an electrosurgical end effector comprising various rotary drive components that are driven differently with a rotary drive shaft at different axial positions. Examples of such end effectors and drive mechanisms are described herein with respect to FIGS. **64-82**, **83-91** and **92-96**. The surgical tool **2400** may employ a shifting system **2610** for selectively axially shifting the proximal drive shaft segment **380'** which moves the shaft gear **376** into and out of meshing engagement with the first rotary driven gear **374**. For example, the proximal drive shaft segment **380'** is movably supported within the handle frame assembly **2520** such that the proximal drive shaft segment **380'** may move axially and rotate therein. In at least one example form, the shifting system **2610** further includes a shifter yoke **2612** that is slidably supported by the handle frame assembly **2520**. See FIGS. **51** and **54**. The proximal drive shaft segment **380'** has a pair of collars **386** (shown in FIGS. **51** and **55**) thereon such that shifting of the shifter yoke **2612** on the handle frame assembly **2520** results in the axial movement of the proximal drive shaft segment **380'**. In at least one form, the shifting system **2610** further includes a shifter button assembly **2614** operably interfaces with the shifter yoke **2612** and extends through a slot **2505** in the handle housing segment **2504** of the handle assembly **2500**. See FIGS. **62** and **63**. A shifter spring **2616** is mounted with the handle frame assembly **2520** such that it engages the proximal drive shaft segment **380'**. See FIGS. **54** and **61**. The spring **2616** serves to provide the clinician with an audible click and tactile feedback as the shifter button assembly **2614** is slidably positioned between the first axial position depicted in FIG. **62** wherein rotation of the drive shaft assembly results in rotation of the end effector **3000** about the longitudinal tool axis "LT-LT" relative to the articulation joint **3500** (illustrated in FIG. **67**) and the second axial position depicted in FIG. **63** wherein rotation of the drive shaft assembly results in the axial movement of the firing member in the end effector (illustrated in FIG. **66**). Thus, such arrangement enables the clinician to easily slidably position the shifter button assembly **2614** while holding the handle assembly **2500**. In some embodiments, the shifter button assembly **2500** may have more than two axial positions, corresponding to more than two desired axial positions of the rotary drive shaft. Examples of such surgical tools are provided herein in conjunction with FIGS. **83-91** and **92-96**.

Referring to FIGS. **64-72**, a multi-axis articulating and rotating surgical tool **600** comprises an end effector **550** comprising a first jaw member **602A** and a second jaw member **602B**. The first jaw member **602A** is movable relative to the second jaw member **602B** between an open position (FIGS. **64**, **66-69**, **71**) and a closed position (FIGS. **70** and **72**) to clamp tissue between the first jaw member **602A** and the second jaw member **602B**. The surgical tool **600** is configured to independently articulate about an articulation joint **640** in a vertical direction (labeled direction V in FIGS. **64** and **66-72**) and a horizontal direction (labeled direction H in FIGS. **64** and **65-68**). Actuation of the articulation joint **640** may be brought about in a manner similar to that described above

with respect to FIGS. **24-26**. The surgical tool **600** is configured to independently rotate about a head rotation joint **645** in a longitudinal direction (labeled direction H in FIGS. **64** and **66-72**). The end effector **550** comprises an I-beam member **620** and a jaw assembly **555** comprising the first jaw member **602A**, the second jaw member **602B**, a proximal portion **603** of the second jaw member **602B**, and a rotary drive nut **606** seated in the proximal portion **603**. The I-beam member **620** and jaw assembly **555** may operate in a manner described herein and similar to that described above with respect to the axially movable member **3016** and jaw members **3008A**, **3008B** described herein above.

The end effector **550** is coupled to a shaft assembly **560** comprising an end effector drive housing **608**, an end effector connector tube **610**, an intermediate articulation tube segment **616**, and a distal outer tube portion **642**. The end effector **550** and the shaft assembly **560** together comprise the surgical tool **600**. The end effector **550** may be removably coupled to the end effector drive housing **608** using a mechanism as described, for example, in connection with FIGS. **106-115**. The end effector connector tube **610** comprises a cylindrical portion **612** and a ball member **614**. The end effector drive housing **608** is coupled to the cylindrical portion **612** of the end effector connector tube **610** through the head rotation joint **645**. The end effector **550** and the end effector drive housing **608** together comprise a head portion **556** of the surgical tool **600**. The head portion **556** of the surgical tool **600** is independently rotatable about the head rotation joint **645**, as described in greater detail below.

The intermediate articulation tube segment **616** comprises a ball member **618** and a ball socket **619**. The end effector connector tube **610** is coupled to the intermediate articulation tube segment **616** through a ball-and-socket joint formed by the mutual engagement of the ball member **614** of the end effector connector tube **610** and the ball socket **619** of the intermediate articulation tube segment **616**. The intermediate articulation tube segment **616** is coupled to the distal outer tube portion **642** through a ball-and-socket joint formed by the mutual engagement of the ball member **618** of the intermediate articulation tube segment **616** and a ball socket of the distal outer tube portion **642**. The articulation joint **640** comprises the end effector connector tube **610**, the intermediate articulation tube segment **616**, and the distal outer tube portion **642**. The independent vertical articulation and/or horizontal articulation of the surgical tool **600** about the articulation joint **640** may be actuated, for example, using independently actuatable cable segments, such as **444**, **445**, **446**, **447** described herein above, connected to the ball member **614** of the end effector connector tube **610**. This independent articulation functionality is described, for example, in connection with FIGS. **24**, **24A** and **25**. Robotic and hand-held apparatuses for allowing a clinician to initiate articulation functionality are described, for example, in connection with FIGS. **6**, **16-21** and **46-50**.

The movement of the first jaw member **602A** relative to the second jaw member **602B** between an open position (FIGS. **64**, **66-69**, and **71**) and a closed position (FIGS. **70** and **72**) may be actuated with a suitable closure actuation mechanism. Referring to FIGS. **73** and **74**, closure of the jaw assembly **555** may be actuated by translation of the I-beam member **620**. The I-beam member **620** comprises a first I-beam flange **622A** and a second I-beam flange **622B**. The first I-beam flange **622A** and the second I-beam flange **622B** are connected with an intermediate portion **624**. The intermediate portion **624** of the I-beam member **620** comprises a cutting member **625**, which is configured to transect tissue clamped between the first jaw member **602A** and the second jaw mem-

ber 602B when the jaw assembly 555 is in a closed position. The I-beam member 620 is configured to translate within a first channel 601A in the first jaw member 602A and within a second channel 601B in the second jaw member 602B. The first channel 601A comprises a first channel flange 605A, and the second channel 601B comprises a second channel flange 605B. The first I-beam flange 622A can define a first cam surface 626A, and the second I-beam flange 622B can define a second cam surface 626B. The first and second cam surfaces 626A and 626B can slidably engage outwardly-facing opposed surfaces of the first and second channel flanges 605A and 605B, respectively. More particularly, the first cam surface 626A can comprise a suitable profile configured to slidably engage the opposed surface of the first channel flange 605A of the first jaw member 602A and, similarly, the second cam surface 626B can comprise a suitable profile configured to slidably engage the opposed surface of the second channel flange 605B of the second jaw member 602B, such that, as the I-beam member 620 is advanced distally, the cam surfaces 626A and 626B can co-operate to cam first jaw member 602A toward second jaw member 602B and move the jaw assembly 555 from an open position to a closed position as indicated by arrow 629 in FIG. 74.

FIG. 73 shows the I-beam member 620 in a fully proximal position and the jaw assembly 555 in an open position. In the position shown in FIG. 73, the first cam surface 626A is engaging a proximal portion of an arcuate-shaped anvil surface 628, which mechanically holds the first jaw member 602A open relative to the second jaw member 602B (FIGS. 69 and 71). Translation of the I-beam member 620 distally in a longitudinal direction (labeled direction L in FIGS. 64 and 66-74) results in sliding engagement of the first cam surface 626A with the length of the arcuate-shaped anvil surface 628, which cams first jaw member 602A toward second jaw member 602B until the first cam surface 626A is engaging a distal portion of the arcuate-shaped anvil surface 628. After the distal translation of the I-beam member 620 for a predetermined distance, the first cam surface 626A engages a distal portion of the arcuate-shaped anvil surface 628 and the jaw assembly is in the closed position (FIG. 74). Thereafter, the I-beam member 620 can be further translated distally in order to transect tissue clamped between the first jaw member 602A and the second jaw member 602B when in the closed position.

During distal translation of the I-beam member 620 after closure of the jaw assembly, the first and second cam surfaces 626A and 626B of the first and second I-beam flanges 622A and 622B slidably engage the opposed surfaces of the first and second channel flanges 605A and 605B, respectively. In this manner, the I-beam member is advanced distally through the first and second channels 601A and 601B of the first and second jaw members 602A and 602B.

The distal, or leading, end of the I-beam member 620 comprises a cutting member 625, which may be a sharp edge or blade configured to cut through clamped tissue during a distal translation stroke of the I-beam member, thereby transecting the tissue. FIGS. 72 and 70 show the I-beam member 620 in a fully distal position after a distal translation stroke. After a distal translation stroke, the I-beam member 620 may be proximally retracted back to the longitudinal position shown in FIG. 74 in which the jaw assembly remains closed, clamping any transected tissue between the first jaw member 602A and the second jaw member 602B. Further retraction of the I-beam member to the fully proximal position (FIGS. 69, 71, and 73) will result in engagement of the first cam surface 626A and the proximal portion of the anvil

surface 628, which cams the first jaw member 602A away from the second jaw member 602B, opening the jaw assembly 555.

Before, during, and/or after the I-beam member 620 is advanced through tissue clamped between the first jaw member 602A and the second jaw member 602B, electrical current can be supplied to electrodes located in the first and/or second jaw members 602A and 602B in order to weld/fuse the tissue, as described in greater detail in this specification. For example, electrodes may be configured to deliver RF energy to tissue clamped between the first jaw member 602A and the second jaw member 602B when in a closed position to weld/fuse the tissue.

Distal and proximal translation of the I-beam member 620 between a proximally retracted position (FIGS. 64, 66-69, 71, and 73), an intermediate position (FIG. 74), and a distally advanced position (FIGS. 70 and 72) may be accomplished with a suitable translation actuation mechanism. Referring to FIGS. 65-72, the I-beam member 620 is connected to a threaded rotary drive member 604. A threaded rotary drive nut 606 is threaded onto the threaded rotary drive member 604. The threaded rotary drive nut 606 is seated in the proximal portion 603 of the second jaw member 602B. The threaded rotary drive nut 606 is mechanically constrained from translation in any direction, but the threaded rotary drive nut 606 is rotatable within the proximal portion 603 of the second jaw member 602B. Therefore, given the threaded engagement of the rotary drive nut 606 and the threaded rotary drive member 604, rotational motion of the rotary drive nut 606 is transformed into translational motion of the threaded rotary drive member 604 in the longitudinal direction and, in turn, into translational motion of the I-beam member 620 in the longitudinal direction.

The threaded rotary drive member 604 is threaded through the rotary drive nut 606 and is located inside a lumen of a rotary drive shaft 630. The threaded rotary drive member 604 is not attached or connected to the rotary drive shaft 630. The threaded rotary drive member 604 is freely movable within the lumen of the rotary drive shaft 630 and will translate within the lumen of the rotary drive shaft 630 when driven by rotation of the rotary drive nut 606. The rotary drive shaft 630 comprising the threaded rotary drive member 604 located within the lumen of the rotary drive shaft 630 forms a concentric rotary drive shaft/screw assembly that is located in the lumen of the shaft assembly 560.

As shown in FIG. 65, the end effector drive housing 608, the end effector connector tube 610, and the intermediate articulation tube segment 616, which together comprise the shaft assembly 560, have open lumens and, therefore, the shaft assembly has a lumen, as shown in FIGS. 66-68. Referring again to FIGS. 66-68, the concentric rotary drive shaft/threaded rotary drive member assembly is located within the lumen of the shaft assembly 560 and passes through the end effector drive housing 608, the end effector connector tube 610, and the intermediate articulation tube segment 616. Although not shown in FIGS. 66-68, at least the rotary drive shaft 630 passes through a lumen of the distal outer tube portion 642 and is operably coupled to a driving mechanism that provides rotational and axial translational motion to the rotary drive shaft 630. For example, in some embodiments, the surgical tool 600 may be operably coupled through the shaft assembly 560 to a robotic surgical system that provides rotational motion and axial translational motion to the rotary drive shaft 630, such as, for example, the robotic surgical systems described in connection with FIGS. 5 and 16-21. For example, the rotary drive shaft 630 may be operably coupled, through the shaft assembly 560, to the proximal drive shaft

segment 380 described herein above. Also, in some embodiments, the surgical tool 600 may be utilized in conjunction with a hand-held surgical device, such as the device described herein above with respect to FIGS. 46-63. For example, the rotary drive shaft 630 may be operably coupled, through the shaft assembly 560, to the proximal drive shaft segment 380' described herein above.

The rotary drive shaft 630 comprises a rotary drive head 632. The rotary drive head 632 comprises a female hex coupling portion 634 on the distal side of the rotary drive head 632, and the rotary drive head 632 comprises a male hex coupling portion 636 on the proximal side of the rotary drive head 632. The distal female hex coupling portion 634 of the rotary drive head 632 is configured to mechanically engage with a male hex coupling portion 607 of the rotary drive nut 606 located on the proximal side of the rotary drive nut 606. The proximal male hex coupling portion 636 of the rotary drive head 632 is configured to mechanically engage with a female hex shaft coupling portion 609 of the end effector drive housing 608.

Referring to FIGS. 66, 67, 69, and 70, the rotary drive shaft 630 is shown in a fully distal axial position in which the female hex coupling portion 634 of the rotary drive head 632 is mechanically engaged with the male hex coupling portion 607 of the rotary drive nut 606. In this configuration, rotation of the rotary drive shaft 630 actuates rotation of the rotary drive nut 606, which actuates translation of the threaded rotary drive member 604, which actuates translation of the I-beam member 620. The orientation of the threading of the threaded rotary drive member 604 and the rotary drive nut 606 may be established so that either clockwise or counterclockwise rotation of the rotary drive shaft 630 will actuate distal or proximal translation of the threaded rotary drive member 604 and I-beam member 620. In this manner, the direction, speed, and duration of rotation of the rotary drive shaft 630 can be controlled in order to control the direction, speed, and magnitude of the longitudinal translation of the I-beam member 620 and, therefore, the closing and opening of the jaw assembly and the transection stroke of the I-beam member along the first and second channels 601A and 601B, as described above.

Referring to FIG. 69, for example, rotation of the rotary drive shaft 630 in a clockwise direction (as viewed from a proximal-to-distal vantage point) actuates clockwise rotation of the rotary drive nut 606, which actuates distal translation of the threaded rotary drive member 604, which actuates distal translation of the I-beam member 620, which actuates closure of the jaw assembly and a distal transection stroke of the I-beam member 620/cutting member 625. Referring to FIG. 70, for example, rotation of the rotary drive shaft 630 in a counterclockwise direction (as viewed from a proximal-to-distal vantage point) actuates counterclockwise rotation of the rotary drive nut 606, which actuates proximal translation of the threaded rotary drive member 604, which actuates proximal translation of the I-beam member 620, which actuates a proximal return stroke of the I-beam member 620/cutting member 625 and opening of the jaw assembly. In this manner, the rotary drive shaft 630 may be used to independently actuate the opening and closing of the jaw assembly and the proximal-distal transection stroke of the I-beam 620/cutting member 625.

Referring to FIGS. 68, 71, and 72, the rotary drive shaft 630 is shown in a fully proximal axial position in which the male hex coupling portion 636 of the rotary drive head 632 is mechanically engaged with the female hex shaft coupling portion 609 of the end effector drive housing 608. In this configuration, rotation of the rotary drive shaft 630 actuates rotation of the head portion 556 of the surgical tool 600 about

rotation joint 645, including rotation of the end effector 550 and the end effector drive housing 608. In this configuration, the portion of the surgical tool 600 that is distal to the head rotation joint 645 (i.e., the head portion 556 of the surgical tool 600, comprising the end effector 550 and the end effector drive housing 608) rotates with rotation of the rotary drive shaft 630, and the portion of the surgical tool that is proximal to the head rotation joint 645 (e.g., the end effector connector tube 610, the intermediate articulation tube segment 616, and the distal outer tube portion 642) does not rotate with rotation of the rotary drive shaft 630. It will be appreciated that a desired rotation speed of the rotary drive shaft 630 to drive the rotary drive nut 606 may be greater than a desired rotational speed for rotating the head portion 556. For example, the rotary drive shaft 630 may be driven by a motor (not shown) that is operable at different rotary speeds.

Referring to FIG. 71, for example, rotation of the rotary drive shaft 630 in a clockwise direction (as viewed from a proximal-to-distal vantage point) actuates clockwise rotation of the end effector 550 and the end effector drive housing 608 (i.e., the head portion 556 of the surgical tool 600) with the jaw assembly 555 in an open position. Rotation of the rotary drive shaft 630 in a counterclockwise direction (as viewed from a proximal-to-distal vantage point) actuates counterclockwise rotation of the end effector 550 and the end effector drive housing 608 with the jaw assembly 555 in an open position. Referring to FIG. 72, for example, rotation of the rotary drive shaft 630 in a clockwise direction (as viewed from a proximal-to-distal vantage point) actuates clockwise rotation of the end effector 550 and the end effector drive housing 608 with the jaw assembly 555 in a closed position. Rotation of the rotary drive shaft 630 in a counterclockwise direction (as viewed from a proximal-to-distal vantage point) actuates counterclockwise rotation of the end effector 550 and the end effector drive housing 608 with the jaw assembly 555 in a closed position. Although not shown, it is understood that the I-beam member 620 may be located in an intermediate position where the jaw assembly is closed but the I-beam is not fully distally advanced (see, e.g., FIG. 74) when the rotary drive shaft 630 is in a fully proximal axial position and the male hex coupling portion 636 of the rotary drive head 632 is mechanically engaged with the female hex shaft coupling portion 609 of the end effector drive housing 608 to actuate rotation of the head portion of the surgical tool.

Thus, the rotary drive shaft 630 may be used to independently actuate the opening and closing of the jaw assembly, the proximal-distal transection stroke of the I-beam 620/cutting member 625, and the rotation of the head portion 556 of the surgical tool 600d.

In various embodiments, a surgical tool may comprise an end effector, a first actuation mechanism, and a second actuation mechanism. The surgical tool may also comprise a clutch member configured to selectively engage and transmit rotary motion to either the first actuation mechanism or the second actuation mechanism. For example, in various embodiments, a clutch member may comprise a rotary drive shaft comprising a rotary drive head as described, for example, in connection with FIGS. 64-72. In various embodiments, a first actuation mechanism may comprise an I-beam member connected to a threaded rotary drive member threaded through a rotary drive nut, as described, for example, in connection with FIGS. 64-74, wherein the I-beam, the threaded rotary drive member, and the rotary drive nut are configured to actuate the closing and opening of a jaw assembly and/or the translation of a cutting member. In various embodiments, a second actuation mechanism may comprise a shaft coupling portion, as described, for example, in connection with FIGS. 64-72,

41

wherein the shaft coupling portion is configured to actuate rotation of a head portion of a surgical tool.

In various embodiments, a surgical tool may comprise an end effector comprising a first jaw member, a second jaw member, and a first actuation mechanism configured to move the first jaw member relative to the second jaw member between an open position and a closed position. The surgical tool may also comprise a shaft assembly proximal to the surgical end effector. The surgical tool may also comprise a rotary drive shaft. The rotary drive shaft may be configured to transmit rotary motions and may also be selectively moveable between a first position and a second position relative to the shaft assembly. The rotary drive shaft may be configured to engage and selectively transmit the rotary motions to the first actuation mechanism when in the first position and the rotary drive shaft may be configured to disengage from the actuation mechanism when in the second position. For example, in various embodiments, the first actuation mechanism may comprise an I-beam member connected to a threaded rotary drive member threaded through a rotary drive nut, as described, for example, in connection with FIGS. 64-74, wherein the I-beam, the threaded rotary drive member, and the rotary drive nut are configured to actuate the closing and opening of a jaw assembly when the rotary drive shaft engages and selectively transmits rotary motion to the drive nut.

In various embodiments, a surgical tool may comprise a surgical end effector comprising a first jaw member, a second jaw member, and a closure mechanism configured to move the first jaw member relative to the second jaw member between an open position and a closed position. The surgical tool may also comprise a shaft assembly proximal to the surgical end effector, wherein the surgical end effector is configured to rotate relative to the shaft assembly. The surgical tool may also comprise a rotary drive shaft configured to transmit rotary motions, the rotary drive shaft selectively movable axially between a first position and a second position relative to the shaft assembly, wherein the rotary drive shaft is configured to apply the rotary motions to the closure mechanism when in the first axial position, and wherein the rotary drive shaft is configured to apply the rotary motions to the surgical end effector when in the second axial position. For example, in various embodiments, the first axial position may correspond to the rotary drive shaft being in a fully distal axial position in which a rotary drive head is mechanically engaged with a rotary drive nut as described, for example, in connection with FIGS. 64-72. In various embodiments, the second axial position may correspond to the rotary drive shaft being in a fully proximal axial position in which a rotary drive head is mechanically engaged with a shaft coupling portion of a shaft member as described, for example, in connection with FIGS. 64-72.

In various embodiments, a surgical tool comprising an end effector, a first actuation mechanism, and a second actuation mechanism, may further comprise a head locking mechanism. For example, referring to FIGS. 75-82, a multi-axis articulating and rotating surgical tool 650 comprises an end effector 570, a shaft assembly 580, and a head locking mechanism 590. The end effector 570 comprises a first jaw member 652A and a second jaw member 652B. The first jaw member 602A is movable relative to the second jaw member 602B between an open position (FIGS. 77 and 79) and a closed position (FIGS. 78 and 80) to clamp tissue between the first jaw member 652A and the second jaw member 652B. The surgical tool 650 is configured to independently articulate about an articulation joint in a vertical direction and a horizontal direction like the surgical tool 600 shown in FIGS.

42

64-72. The surgical tool 650 is also configured to independently rotate about a head rotation joint like the surgical tool 600 shown in FIGS. 64-72. The end effector 570 comprises an I-beam member 670 and a jaw assembly 575 comprising the first jaw member 652A, the second jaw member 652B, a proximal portion 653 of the second jaw member 652B, and a rotary drive nut 656 seated in the proximal portion 653.

The end effector 570 is coupled to a shaft assembly 580 comprising an end effector drive housing 658, an end effector connector tube 660, an intermediate articulation tube segment 666, and a surgical tool shaft member (not shown). The end effector 570 and the shaft assembly 580 together comprise the surgical tool 650. The end effector 570 may be removably coupled to the end effector drive housing 658 using a mechanism as described, for example, in connection with FIGS. 106-115. The end effector drive housing 608 is coupled to the end effector connector tube 660 through the head rotation joint. The end effector 570 and the end effector drive housing 658 together comprise a head portion 578 of the surgical tool 650. The head portion 578 of the surgical tool 650 is independently rotatable about the head rotation joint, as described in greater detail above in connection FIGS. 64-72 showing the surgical tool 600.

The end effector connector tube 660 is coupled to the intermediate articulation tube segment 666 through a ball-and-socket joint formed by the mutual engagement of the ball member of the end effector connector tube 660 and the ball socket of the intermediate articulation tube segment 666. The intermediate articulation tube segment 666 is coupled to a surgical tool shaft member through a ball-and-socket joint formed by the mutual engagement of the ball member of the intermediate articulation tube segment 616 and a ball socket of the surgical tool shaft member. The articulation joint comprises the end effector connector tube 660, the intermediate articulation tube segment 666, and the surgical tool shaft member. The independent vertical articulation and/or horizontal articulation of the surgical tool 650 about the articulation joint may be actuated, for example, using independently actuatable drive cables connected to the ball member of the end effector connector tube 660. This independent articulation functionality is described, for example, in connection with FIGS. 24-25. Robotic and hand-held apparatuses for allowing a clinician to initiate articulation functionality are described, for example, in connection with FIGS. 6, 16-21 and 46-50.

The movement of the first jaw member 652A relative to the second jaw member 652B is actuated using the same actuation mechanism described above in connection with FIGS. 73 and 74. Distal and proximal translation of the I-beam member 670 between a proximally retracted position (FIGS. 77 and 79), an intermediate position (see FIG. 74), and a distally advanced position (FIGS. 78 and 80) may be accomplished with a suitable translation actuation mechanism. Referring to FIGS. 75-80, the I-beam member 670 is connected to a threaded rotary drive member 654. A threaded rotary drive nut 656 is threaded onto the threaded rotary drive member 654. The threaded rotary drive nut 656 is seated in the proximal portion 653 of the second jaw member 652B. The threaded rotary drive nut 656 is mechanically constrained from translation in any direction, but is rotatable within the proximal portion 653 of the second jaw member 652B. Therefore, given the threaded engagement of the rotary drive nut 656 and the threaded rotary drive member 654, rotational motion of the rotary drive nut 656 is transformed into translational motion of the threaded rotary drive member 654 in

the longitudinal direction and, in turn, into translational motion of the I-beam member 670 in the longitudinal direction.

The threaded rotary drive member 654 is threaded through the rotary drive nut 656 and is located inside a lumen of a rotary drive shaft 680. The threaded rotary drive member 654 is not attached or connected to the rotary drive shaft 680. The threaded rotary drive member 654 is freely movable within the lumen of the rotary drive shaft 680 and will translate within the lumen of the rotary drive shaft 680 when driven by rotation of the rotary drive nut 656. The rotary drive shaft 680 comprising the threaded rotary drive member 654 located within the lumen of the rotary drive shaft 680 forms a concentric rotary drive shaft/screw assembly that is located in the lumen of the shaft assembly 580.

Referring to FIGS. 77-80, the concentric rotary drive shaft/screw assembly is located within the lumen of the shaft assembly 560 and passes through the end effector drive housing 658, the end effector connector tube 660, and the intermediate articulation tube segment 666. Although not shown in FIGS. 77-80, at least the rotary drive shaft 680 passes through a lumen of the surgical tool shaft member and is operably coupled to a driving mechanism that provides rotary motion and axial translational motion to the rotary drive shaft 680. For example, in some embodiments, the surgical tool 650 may be operably coupled through the shaft assembly 580 to a robotic surgical system that provides rotary motion and axial translational motion to the rotary drive shaft 680, such as, for example, the robotic surgical systems described in connection with FIGS. 5 and 16-21. In some embodiments, for example, the surgical tool 650 may be operably coupled through the shaft assembly 580 to a hand-held surgical device that provides rotary motion and axial translational motion to the rotary drive shaft 680, such as, for example, the hand-held surgical devices described in connection with FIGS. 46-63. In some embodiments, the threaded rotary drive member 654 has a length that is less than the length of the rotary drive shaft 680 and, therefore, lies within only a distal portion of the rotary drive shaft 680.

The threaded rotary drive member 654 and the rotary drive shaft 680 are flexible so that the portions of the threaded rotary drive member 654 and the rotary drive shaft 680 that are located in the articulation joint can bend without damage or loss of operability during independent articulation of the surgical tool 650 about the articulation joint. Example configurations of the rotary drive shaft 680 are provided herein with reference to FIGS. 28-45.

The rotary drive shaft 680 comprises a rotary drive head 682. The rotary drive head 682 comprises a female hex coupling portion 684 on the distal side of the rotary drive head 682, and the rotary drive head 682 comprises a male hex coupling portion 686 on the proximal side of the rotary drive head 682. The distal female hex coupling portion 684 of the rotary drive head 682 is configured to mechanically engage with a male hex coupling portion 657 of the rotary drive nut 656 located on the proximal side of the rotary drive nut 656. The proximal male hex coupling portion 686 of the rotary drive head 682 is configured to mechanically engage with a female hex shaft coupling portion 659 of the end effector drive housing 658.

Referring to FIGS. 77 and 78, the rotary drive shaft 680 is shown in a fully distal axial position in which the female hex coupling portion 684 of the rotary drive head 682 is mechanically engaged with the male hex coupling portion 657 of the rotary drive nut 656. In this configuration, rotation of the rotary drive shaft 680 actuates rotation of the rotary drive nut 656, which actuates translation of the threaded rotary drive

member 654, which actuates translation of the I-beam member 670. Referring to FIGS. 79 and 80, the rotary drive shaft 680 is shown in a fully proximal axial position in which the male hex coupling portion 686 of the rotary drive head 682 is mechanically engaged with the female hex shaft coupling portion 659 of the end effector drive housing 658. In this configuration, rotation of the rotary drive shaft 680 actuates rotation of the head portion 578 of the surgical tool 650 about rotation joint, including rotation of the end effector 570 and the end effector drive housing 658.

The rotary drive shaft 680 also comprises a spline lock 690. The spline lock 690 is coupled to the rotary drive shaft 680 using shaft flanges 685. The spline lock 690 is mechanically constrained from translation in any direction by the rotary drive shaft 680 and the shaft flanges 685, but the spline lock 690 is freely rotatable about the rotary drive shaft 680. The spline lock 690 comprises spline members 692 disposed circumferentially around the external surface of the spline lock 690 and oriented co-axially with the shaft assembly 580. As shown in FIGS. 75 and 76, the spline lock 690 is located at the rotational joint formed by the coupling of the end effector drive housing 658 and the end effector connector tube 660. The end effector drive housing 658 comprises a spline coupling portion 694 comprising spline members 696 disposed circumferentially around the internal surface of the end effector drive housing 658 and oriented co-axially with the shaft assembly 580. The end effector connector tube 660 comprises a spline coupling portion 662 comprising spline members 664 disposed circumferentially around the internal surface of the end effector connector tube 660 and oriented co-axially with the shaft assembly 580.

The spline members 692, 696, and 664 of the spline lock 690, the end effector drive housing 658, and the end effector connector tube 660, respectively, are configured to mechanically engage with each other when the rotary drive shaft 680 is in a fully distal axial position in which the female hex coupling portion 684 of the rotary drive head 682 is mechanically engaged with the male hex coupling portion 657 of the rotary drive nut 656 to drive rotation of the rotary drive nut 656 and translation of the threaded rotary drive member 654 and the I-beam member 670 (FIGS. 77, 78, and 82). The mechanical engagement of the respective spline members 692, 696, and 664 locks the end effector drive housing 658 into position with the end effector connector tube 660, thereby locking the rotational joint and preventing rotation of the head portion 578 of the surgical tool 650. Because the spline lock 690 is freely rotatable about the rotary drive shaft 680, the mechanical engagement of the respective spline members 692, 696, and 664 does not prevent the rotary drive shaft 680 from actuating the rotary drive nut 656, the threaded rotary drive member 654, and the I-beam member 670.

When the rotary drive shaft 680 is in a fully proximal axial position in which the male hex coupling portion 686 of the rotary drive head 682 is mechanically engaged with the female hex shaft coupling portion 659 of the end effector drive housing 658 to drive rotation of the head portion 578 of the surgical tool 650, the spline lock 690 is completely retracted into the lumen of the end effector connector tube 660 and the spline lock 690 is completely disengaged from the spline coupling portion 694 of the end effector drive housing 658. (FIGS. 79, 80, and 81). In this configuration, the spline members 692 of the spline lock 690 and the spline members 664 of the end effector connector tube 660 are completely engaged, and the spline members 692 of the spline lock 690 and the spline members 696 of the end effector drive housing 658 are completely disengaged. The mechanical disengagement of the spline members 692 of the



spline lock 690 and the spline members 696 of the end effector drive housing 658 when the rotary drive shaft 680 is in a fully proximal axial position unlocks the end effector drive housing 658 from the end effector connector tube 660, thereby unlocking the rotational joint and permitting rotation of the head portion 578 of the surgical tool 650. Because the spline lock 690 is freely rotatable about the rotary drive shaft 680, the mechanical engagement of spline members 692 of the spline lock 690 and the spline members 664 of the end effector connector tube 660 does not prevent the rotary drive shaft 680 from actuating the rotation of the head portion 578 of the surgical tool 650.

The head locking mechanism 590 ensures that the head portion 578 of the surgical tool 650 does not rotate when the rotary drive shaft 680 is in a fully distal axial position engaging the rotary drive nut 656 to drive actuation of the jaw closure mechanism and/or the I-beam translation mechanism as described above (FIGS. 77, 78, and 82). The head locking mechanism 590 ensures that the head portion 578 of the surgical tool 650 is freely rotatable when the rotary drive shaft 680 is in a fully proximal axial position engaging the shaft coupling portion 659 of the end effector drive housing 658 to drive actuation of head rotation as described above (FIGS. 79, 80, and 81).

Referring to FIGS. 77 and 78, for example, rotation of the rotary drive shaft 680 actuates rotation of the rotary drive nut 656, which actuates distal or proximal translation of the threaded rotary drive member 654 (depending on the direction of rotary motion of the rotary drive shaft 680), which actuates distal or proximal translation of the I-beam member 670, which actuates the closing and opening of the jaw assembly 575, and distal and proximal transection strokes of the I-beam member 670/cutting member 675. Simultaneously, the spline lock 690 engages both the end effector drive housing 658 and the end effector connector tube 660 to prevent unintended head rotation.

Referring to FIGS. 79 and 80, for example, rotation of the rotary drive shaft 680 actuates rotation of the end effector drive housing 658, which actuates rotation of the end effector 570. Simultaneously, the spline lock 690 is disengaged both the end effector drive housing 658 and does not prevent head rotation. Thus, the rotary drive shaft 680 may be used to independently actuate the opening and closing of the jaw assembly 575, the proximal-distal transection stroke of the I-beam 670/cutting member 675, and the rotation of the head portion 578 of the surgical tool 650.

In various embodiments, an end effector, such as the end effectors 550 and 570 shown in FIGS. 64-82, may comprise first and second jaw members comprising a first and second distal textured portions, respectively. The first and second distal textured portions of the first and second jaw members of an end effector may be opposed and may allow the end effector to grip, pass, and/or manipulate surgical implements such as needles for suturing tissue, in addition to gripping tissue, for example, during dissection operations. In some embodiments, the distal textured portions may also be electrodes configured, for example, to deliver RF energy to tissue during dissection operations. This gripping, passing, manipulating, and/or dissecting functionality is described, for example, in connection with FIGS. 153-168.

In various embodiments, an end effector, such as the end effectors 550 and 570 shown in FIGS. 64-82, may comprise first and second jaw members comprising first and second gripping portions disposed on outwardly facing surfaces of the first and second jaw members. The first and second gripping portions of the first and second jaw members of an end

effector may function to aid in tissue dissection as described, for example, in connection with FIGS. 116-131.

In various embodiments, an end effector, such as the end effectors 550 and 570 shown in FIGS. 64-82, may comprise at least one electrode disposed on at least one tissue-contacting surface of at least one jaw member. The electrodes may be configured, for example, to deliver RF energy to tissue clamped between the jaw members when in a closed position to weld/fuse the tissue, which in some embodiments, may also be transected by translating an I-beam member comprising a cutting member. In some embodiments, a second jaw member may also comprise an offset electrode located at the distal tip of the jaw member, the electrode configured to deliver RF energy to tissue during dissection operations, for example. This electrode functionality is described, for example, in connection with 153-168.

In various embodiments, an end effector, such as the end effectors 550 and 570 shown in FIGS. 64-82, may comprise jaw members comprising angled tissue-contacting surfaces as described, for example, in connection with FIGS. 132-142.

Referring to FIGS. 83-91, a multi-axis articulating and rotating surgical tool 1200 comprises an end effector 1202 including a jaw assembly 1211 comprising a first jaw member 1204 and a second jaw member 1206. The first jaw member 1204 is movable relative to the second jaw member 1206 through an open position and a closed position to clamp tissue between the first jaw member 1204 and the second jaw member 1206. The surgical tool 1200 is configured to independently articulate about an articulation joint 1208. As described above, the surgical tool 1200 is also configured to independently rotate about a head rotation joint 1210. Referring primarily to FIG. 83, the end effector 1202 further comprises a proximal shaft portion 1212.

The end effector 1202 is coupled to a shaft assembly 1214 comprising an end effector drive housing 1216, an end effector connector tube 1218, an intermediate articulation tube segment 1220, and a distal outer tube portion (not shown in FIGS. 83-91). The end effector 1202 and the shaft assembly 1214 together can comprise the surgical tool 1200. The end effector 1202 may be removably coupled to the end effector drive housing 1216 using a mechanism as described, for example, in connection with FIGS. 106-115. The end effector connector tube 1218 comprises a cylindrical portion 1222 and a ball portion 1224. The end effector drive housing 1216 is coupled to the cylindrical portion 1222 of the end effector connector tube 1218 through the head rotation joint 1210. The end effector 1202 and the end effector drive housing 1216 together comprise a head portion of the surgical tool 1200. The head portion of the surgical tool 1200 is independently rotatable about the head rotation joint 1210.

Referring primarily to FIGS. 85-87, the surgical tool 1200 may include a closure mechanism 1226 for moving the first jaw member 1204 relative to the second jaw member 1206 between an open position (FIG. 86) and a closed position (FIG. 87). As illustrated in FIG. 83, the first jaw member 1204 may include first mounting holes 1228, and the second jaw member 1206 may include second mounting holes (not shown in FIGS. 83-91). The first jaw member 1204 can be arranged relative to the second jaw member 1206 such that a pivot or trunnion pin (not shown in FIGS. 83-91) extends through the first mounting holes 1228 of the first jaw member 1204 and the second mounting holes of the second jaw member 1206 to pivotally couple the first jaw member 1204 to the second jaw member 1206. Other suitable means for coupling the first jaw member 1204 and the second jaw member 1206 are within the scope of this disclosure.

Referring to FIGS. 83-91, the closure mechanism 1226 may comprise a linkage arrangement which may comprise a first link 1230 and a second link (not shown in FIGS. 83-91). The closure mechanism 1226 may also comprise a closure driver in the form of a closure nut 1232 for example. The closure nut 1232 (FIG. 84) may be at least partially positioned within the end effector drive housing 1216. In use, the closure nut 1232 may translate axially between a first position (FIG. 86) and a second position (FIG. 87) relative to the end effector drive housing 1216 and may include a first arm 1234 and a second arm 1236. Referring primarily to FIG. 84, the first arm 1234 and the second arm 1236 may extend distally from a distal portion 1238 of the closure nut 1232, wherein the first arm 1234 may comprise a first opening 1240 and the first arm 1234 may be pivotally connected to the first link 1230 by a first pin (not shown in FIGS. 83-91) through the first opening 1240. Similarly, the second arm 1236 may comprise a second opening 1244, wherein the second arm 1236 may be pivotally connected to the second link by a second pin (not shown in FIGS. 83-91) through the second opening 1244. The first link 1230 and the second link (not shown in FIGS. 83-91) are also pivotally connected to the first jaw member 1204 such that when the closure nut 1232 is advanced distally from the first position (FIG. 86) to the second position (FIG. 87), the first jaw member 1204 is pivoted relative to the second jaw member 1206 towards a closed position. Correspondingly, when the closure nut 1232 is retracted proximally from the second position (FIG. 89) to the first position (FIG. 91), the first jaw member 1204 is pivoted relative to the second jaw member 1206 towards the open position. FIG. 85 illustrates the closure nut 1232 in a first position and the jaw assembly 1211 in an open position. FIG. 87 shows the closure nut 1232 in a second position and the jaw assembly 1211 in a closed position. The closure nut 1232, however, may be constrained from rotation relative to the end effector drive housing 1316 by an indexing feature, for example, abutting against the end effector drive housing 11316.

Referring to FIGS. 83-91, the surgical tool 1200 may include a firing mechanism 1246 having a suitable firing driver. The firing mechanism 1246 may include an I-beam member 1247, a threaded drive member 1248, and a threaded rotary drive nut 1250. The I-beam member 1247 may comprise a first I-beam flange 1252 and a second I-beam flange 1254. The I-beam member 1247 may operate in a manner similar to that described above with respect to the axially movable member 3016 described herein above. For example, the first I-beam flange 1252 and the second I-beam flange 1254 are connected with an intermediate portion 1256. The intermediate portion 1256 of the I-beam member 1247 may comprise a cutting member 1258 on a distal or a leading end thereof. The I-beam member 1247 is configured to translate within a first channel 1260 in the first jaw member 1204 and within a second channel 1262 in the second jaw member 1206. FIG. 84 shows the I-beam member 1247 in a fully proximal position and the jaw assembly 1211 in an open position. The I-beam member 1247 may be translated distally in order for the cutting member 1258 to transect tissue clamped between the first jaw member 1204 and the second jaw member 1206 when in the closed position. The cutting member 1258, which may comprise a sharp edge or blade for example, is configured to cut through clamped tissue during a distal translation (firing) stroke of the I-beam member 1247, thereby transecting the tissue. FIG. 88 shows the I-beam member 1247 in a fully distal position after a firing stroke.

Before, during, and/or after the I-beam member 1247 is advanced through tissue clamped between the first jaw member 1204 and the second jaw member 1206, electrical current

can be supplied to electrodes located in the first jaw member 1204 and/or second jaw member 1206 in order to weld/fuse the tissue, as described in greater detail in this specification. For example, electrodes may be configured to deliver RF energy to tissue clamped between the first jaw member 1204 and the second jaw member 1206 when in a closed position to weld/fuse the tissue.

Distal and proximal translation of the I-beam member 1247 between a proximally retracted position and a distally advanced position may be accomplished with a suitable firing mechanism 1246. Referring to FIGS. 83-91, the I-beam member 1247 is connected to the threaded drive member 1248, wherein the threaded rotary drive nut 1250 is in a threaded engagement with the threaded drive member 1248. Referring primarily to FIG. 83, the threaded rotary drive nut 1250 is positioned within in the end effector drive housing 1216 proximal to the closure nut 1232 between a proximal annular flange 1264 and a distal annular flange 1266. The threaded rotary drive nut 1250 is mechanically constrained from translation in any direction, but is rotatable within the end effector drive housing 1216 around a central axis A. Therefore, given the threaded engagement of the rotary drive nut 1250 and the threaded drive member 1248, rotational motion of the rotary drive nut 1250 is transformed into translational motion of the threaded drive member 1248 along the central axis A and, in turn, into translational motion of the I-beam member 1247 along the central axis A.

The threaded drive member 1248 is threaded through the rotary drive nut 1250 and is located at least partially inside a lumen 1268 of a rotary drive shaft 1270. The threaded drive member 1248 is not attached or connected to the rotary drive shaft 1270. In use, the threaded drive member 1248 is freely movable within the lumen of the rotary drive shaft 1270 and will translate within the lumen of the rotary drive shaft 1270 when driven by rotation of the rotary drive nut 1250. The rotary drive shaft 1270 and the threaded drive member 1248 form a concentric rotary drive shaft/screw assembly that is located in the shaft assembly 1214. In addition, the threaded drive member 1248 extends distally through a lumen 1272 of the closure nut 1232. Similar to the above, the threaded drive member 1248 is freely movable within the lumen 1272 of the closure nut 1232, and, as a result, the threaded drive member 1248 will translate within the lumen 1272 of the closure nut 1232 when driven by rotation of the rotary drive nut 1250.

Referring to FIGS. 83-91, the rotary drive nut 1250 may comprise a threaded distal portion 1274. The closure nut 1232 may comprise a threaded proximal portion 1276. The threaded distal portion 1274 of the rotary drive nut 1250 and the threaded proximal portion 1276 of the closure nut 1232 are in a threaded engagement. As described above, the threaded rotary drive nut 1250 is mechanically constrained from translation in any direction, but is rotatable within the end effector drive housing 1216 around a central axis A. Therefore, given the threaded engagement of the rotary drive nut 1250 and the closure nut 1232, the rotational motion of the rotary drive nut 1250 is transformed into translational motion of the closure nut 1232 along the central axis A and, in turn, into pivotal motion in the jaw assembly 1211.

As shown in FIG. 83, the end effector drive housing 1216, the end effector connector tube 1218, and the intermediate articulation tube segment 1220, which together comprise the shaft assembly 1214, have open lumens and, therefore, the shaft assembly 1214 comprises a lumen extending longitudinally therethrough, as shown in FIGS. 83 and 85-91. Referring again to FIGS. 83 and 85-91, the concentric rotary drive shaft/threaded drive member assembly is located within the lumen of the shaft assembly 1214 and passes through the end

effector drive housing **1216**, the end effector connector tube **1218**, and the intermediate articulation tube segment **1220**. Although not shown in FIGS. **83-91**, at least the rotary drive shaft **1270** passes through a lumen of the shaft assembly **1214** and is operably coupled to a driving mechanism that provides rotational motion and axial translational motion to the rotary drive shaft **1270**. For example, in some embodiments, the surgical tool **1200** may be operably coupled through the shaft assembly **1214** to a robotic surgical system that provides rotational motion and axial translational motion to the rotary drive shaft **1270**, such as, for example, the robotic surgical systems described in connection with FIGS. **5** and **16-21**. For example, the rotary drive shaft **1270** may be coupled, through the shaft assembly, to the proximal drive shaft segment **380** described herein above. In some embodiments, for example, the surgical tool **1200** may be operably coupled through the shaft assembly **1214** to a hand-held surgical device, such as the device described herein above with respect to FIGS. **46-63**. For example, the rotary drive shaft **1270** may be operably coupled, though the shaft assembly **560**, to the proximal drive shaft segment **380'** described herein above.

In some embodiments, the threaded drive member **1248** has a length that is less than the length of the rotary drive shaft **1270** and, therefore, lies within only a distal portion of the rotary drive shaft **1270**, for example. The threaded drive member **1248** and the rotary drive shaft **1270** may be flexible so that the threaded drive member **1248** and the rotary drive shaft **1270** can bend without damage or loss of operability during articulation of the surgical tool **1200** about the articulation joint **1208**.

Described in greater detail elsewhere in the specification, the rotary drive shaft **1270** may comprise a rotary drive head **1278**. The rotary drive head **1278** comprises a female hex coupling portion **1280** on the distal side of the rotary drive head **1278** and the rotary drive head **1278** comprises a male hex coupling portion **1282** on the proximal side of the rotary drive head **1278**. The distal female hex coupling portion **1280** of the rotary drive head **1278** is configured to mechanically engage with a male hex coupling portion **1284** of the rotary drive nut **1250** located on the proximal side of the rotary drive nut **1250**. As described elsewhere, the proximal male hex coupling portion **1282** of the rotary drive head **1278** is configured to mechanically engage with a female hex coupling portion **1286** of the end effector drive housing **1216** in order to rotate the end effector **1202** around the central axis A.

Referring to FIG. **85**, the rotary drive shaft **1270** is shown in a fully proximal axial position in which the hex coupling portion **1282** of the rotary drive head **1278** is mechanically engaged with the female hex shaft coupling portion of the end effector drive housing **1216**. In this configuration, rotation of the rotary drive shaft **1270** causes rotation of the head portion of the surgical tool **1200** about the head rotation joint **1210**, including rotation of the end effector **1202** and the end effector drive housing **1216**. In this configuration, the portion of the surgical tool **1200** that is distal to the head rotation joint **1210** (e.g., a head portion) rotates with rotation of the rotary drive shaft **1270**, and the portion of the surgical tool **1200** that is proximal to the head rotation joint **1210** does not rotate with rotation of the rotary drive shaft **1270**. An example of a head rotation joint **1210** is described in connection with FIGS. **64-82**, **83-91** and **92-96**. Other suitable techniques and rotation means for rotating the end effector **1202** relative to the shaft assembly **1214** are within the scope of the current disclosure. It will be appreciated that a desired rotation speed of the rotary drive shaft **1270** to drive the rotary drive nut **1250** may be greater than a desired rotational speed for rotating the

head portion. For example, the rotary drive shaft **1270** may be driven by a motor (not shown) that is operable at different rotary speeds.

The orientation of the threading of the threaded drive member **1248** and the rotary drive nut **1250** may be established so that either clockwise or counterclockwise rotation of the rotary drive shaft **1270** will cause distal or proximal translation of the threaded drive member **1248** and I-beam member **1247**. Stated another way, the rotary drive shaft **1270**, and the rotary drive nut **1250** can be rotated in a first direction to advance the threaded drive member **1248** distally and correspondingly, rotated in a second opposite direction to retract the threaded drive member **1248** proximally. The pitch and/or number of starts of the threading of the threaded drive member **1248** and the threading of the rotary drive nut **1250** may be selected to control the speed and/or duration of the rotation of the rotary drive nut **1250** and, in turn, the translation of the threaded drive member **1248**. In this manner, the direction, speed, and/or duration of rotation of the rotary drive shaft **1270** can be controlled in order to control the direction, speed, and magnitude of the longitudinal translation of the I-beam member **1247** along the first channel **1260** and second channel **1262**, as described above.

Similar to the above, the orientation of the threading of the threaded distal portion **1274** of the rotary drive nut **1250** and the threading of the threaded proximal portion **1276** of the closure nut **1232** may be established so that either clockwise or counterclockwise rotation of the rotary drive shaft **1270** will cause distal or proximal translation of the closure nut **1232** and in turn closure or opening of the jaw assembly **1211**. Stated another way, threaded distal portion **1274** can be rotated in a first direction to advance the threaded proximal portion **1276** distally and correspondingly, rotated in a second opposite direction to retract the threaded proximal portion **1276** proximally. The pitch and/or number of starts of the threading of the threaded distal portion **1274** of the threaded drive member **1248** and the threading of threaded proximal portion **1276** of the closure nut **1232** may be selected to control speed and/or duration of the rotation of the rotary drive nut **1250** and translation of the closure nut **1232**. In this manner, the direction, speed, and/or duration of rotation of the rotary drive shaft **1270** can be controlled in order to control the direction, speed, and magnitude of the pivoting of the of the jaw assembly **1211**.

Referring to FIGS. **86-88**, the rotary drive shaft **1270** is shown in a fully extended distal axial position in which the female hex coupling portion **1280** of the rotary drive head **1278** is mechanically engaged with the male hex coupling portion **1284** of the rotary drive nut **1250**. In this configuration, rotation of the rotary drive shaft **1270** in a first direction (for example a clockwise direction) around the central axis A begins a firing stroke by causing rotation of the rotary drive nut **1250** in the first direction. The rotation of the rotary drive nut advances the threaded drive member **1248**, which, in turn, advances the I-beam member **1247** distally. Simultaneously, the rotation of the rotary drive nut **1250** advances the closure nut **1232** distally, which closes the jaw assembly **1211**. The closure nut **1232** and the threaded drive member **1248** are advanced distally until the closure nut **1232** is disengaged from threaded engagement with the rotary drive nut **1250** as illustrated in FIG. **88**. Stated another way, the closure nut **1232** can be advanced distally until the threads of the threaded distal portion **1274** of the rotary drive nut **1250** are no longer threadedly engaged with the threads of the threaded proximal portion **1276** of the closure nut **1232**. Thus, as a result, further rotation of the rotary drive nut **1250** in the first direction will not advance the closure nut **1232** distally. The closure nut

1232 will sit idle during the remainder of a firing stroke. Additional rotation of the rotary drive nut 1250, in the same direction, continues the distal advancement of the threaded drive member 1248, which continues the distal advancement of the I-beam member 1247 for the remainder of the firing stroke.

The surgical tool 1200 may comprise a biasing member 1288, a helical spring, and/or a washer spring for example, situated at least partially around the threaded distal portion 1274 of the rotary drive nut 1250. As illustrated in FIG. 86, the biasing member 1288 may include a proximal end abutted against the distal annular flange 1266 of the end effector drive housing 1216, and a distal end abutted against a proximal end 1290 of the closure nut 1232. Once the closure nut 1232 is released from threaded engagement with the rotary drive nut 1250, the biasing member 1288 can keep the closure nut 1232 from reengaging the rotary drive nut 1250 by pushing the closure nut 1232 axially in a distal direction along the central axis A until the distal portion 1238 of the closure nut 1232 abuts against a terminal wall 1294 of the proximal shaft portion 1212 of the end effector 1202. The biasing member 1288 also ensures that the jaw assembly 1211 remains under positive closure pressure by biasing the closure nut 1232 abutted against the terminal wall 1294 of the proximal shaft portion 1212 of the end effector 1202 as the I-beam member 1247 is being advanced distally through the closed jaw assembly 1211.

Referring primarily to FIG. 84, the closure nut 1232 may comprise a cam member 1296 extending distally from the closure nut 1232. Referring primarily to FIG. 87, the cam member 1296 may extend through an opening 1298 of the terminal wall 1294 of the proximal shaft portion 1212 of the end effector 1202 when the distal portion 1238 of the closure nut 1232 is abutted against the terminal wall 1294 of the proximal shaft portion 1212 of the end effector 1202 under positive pressure from the biasing member 1288.

Referring to FIG. 88, the rotary drive shaft 1270 is shown in a fully extended distal axial position in which the female hex coupling portion 1280 of the rotary drive head 1278 is mechanically engaged with the male hex coupling portion 1284 of the rotary drive nut 1250. In this configuration, rotation of the rotary drive shaft 1270 in a second direction opposite the first direction (for example a counter clockwise direction) begins a reverse stroke by causing an opposite rotation of the rotary drive nut 1250, which retracts the threaded drive member 1248, which in turn retracts the I-beam member 1247. At least during the initial phase of the reverse stroke, the closure nut 1232 remains disengaged from the rotary drive nut 1250. However, when the I-beam member 1247 is being retracted, the I-beam member 1247 can engage the cam member 1296 of the closure nut 1232. Any further retraction of the I-beam member 1247 can simultaneously open the jaw assembly 1211 by pushing the closure nut 1232 axially in a proximal direction along the central axis A toward the rotary drive nut 1250. In order for the I-beam member 1247 to push the closure nut 1232 proximally, the I-beam member 1247 must compress the biasing member 1288. As the I-beam member 1247 is retracted, the I-beam member 1247 can push the closure nut 1232 proximally until the closure nut is returned into threaded engagement with the rotary drive nut 1250. At such point, the rotary drive nut 1250 can pull the closure nut 1232 proximally owing to the threaded engagement therebetween. As the closure nut 1232 is retracted proximally, the first link 1230, and the second link will cause the jaw assembly 1211 to open. The retraction of

the I-beam member 1247 and the opening of the jaw assembly 1211 continue simultaneously during the remainder of the reverse stroke.

The sequence of events causing the closure of the jaw assembly 1211, the full extension of the I-beam member 1247, the full retraction of the I-beam member 1247, and the reopening of the jaw assembly 1211 is illustrated in FIGS. 85-91 in a chronological order. FIG. 85 shows the jaw assembly 1211 in a fully open position, the I-beam member 1247 in a fully retracted position, and the rotary drive shaft 1270 in a fully retracted axial position, wherein the female hex coupling portion 1280 of the rotary drive head 1278 is mechanically disengaged from the male hex coupling portion 1284 of the rotary drive nut 1250. In a first phase of operation, returning to FIG. 86, the rotary drive shaft 1270 is advanced axially to mechanically engage the female hex coupling portion 1280 of the rotary drive head 1278 with the male hex coupling portion 1284 of the rotary drive nut 1250. Referring again to FIG. 86, the rotation of the rotary drive shaft 1270 in a first direction (for example a clockwise direction) around the central axis A causes the rotation of the rotary drive nut 1250 in the first direction. The closure nut 1232 and the threaded drive member 1248 are simultaneously advanced distally by rotation of the rotary drive nut 1250 in the first direction. In turn, the closure of the jaw assembly 1211 and the initial advancement of the I-beam member 1247 occur simultaneously during the first phase of operation. In a second phase of operation, referring now to FIG. 87, the closure nut 1232 is disengaged from threaded engagement with the rotary drive nut 1250. During the remainder of the second phase of operation, the rotary drive nut 1250 continues to advance the threaded drive member 1248 independently of the closure nut 1232. As a result, referring primarily to FIG. 88, the jaw assembly 1211 remains closed and the I-beam member 1247 continues to advance until the end of the second phase of operation.

In a third phase of operation, as illustrated in FIG. 89, the rotary drive shaft 1270 is rotated in a second direction opposite the first direction, which causes the rotation of the rotary drive nut 1250 in the second direction. In the third phase of operation, the closure nut 1232 remains disengaged from rotary drive nut 1250. The rotation of the rotary drive nut 1250 retracts the threaded drive member 1248 independent of the closure nut 1232. In result, the jaw assembly 1211 remains closed, and the I-beam member 1247 is retracted in response to the rotation of the rotary drive. In a fourth phase of operation, referring primarily to FIG. 90, the rotary drive nut 1250 continues its rotation in the second direction thereby retracting the threaded drive member 1248 which retracts I-beam member 1247 until the I-beam member 1247 engages the cam member 1296 of closure nut 1232. Any further retraction of the I-beam member 1247 simultaneously opens the jaw assembly 1211 by pushing the closure nut 1232 axially in a proximal direction along the central axis A towards the rotary drive nut 1250 compressing the biasing member 1288. Referring primarily to FIG. 91, the I-beam member 1247 can continue to push the closure nut 1232 proximally until it is returned into threaded engagement with the rotary drive nut 1250. The retraction of the I-beam member 1247 and the opening of the jaw assembly 1211 continue simultaneously during the remainder of the fourth phase of operation.

Referring to FIGS. 92-96, a multi-axis articulating and rotating surgical tool 1300 comprises an end effector 1302 including a jaw assembly 1311 comprising a first jaw member 1304 and a second jaw member 1306. The first jaw member 1304 is movable relative to the second jaw member 1306 between an open position and a closed position to clamp

tissue between the first jaw member **1304** and the second jaw member **1306**. The surgical tool **1300** is configured to independently articulate about an articulation joint **1308**. As described above, the surgical tool **1300** is also configured to independently rotate about a head rotation joint **1310**.

The end effector **1302** is coupled to a shaft assembly **1314** comprising an end effector drive housing **1316**, an end effector connector tube **1318**, an intermediate articulation tube segment **1320**, and a distal outer tube portion (not shown in FIGS. **92-96**). The end effector **1302** and the shaft assembly **1314** together can comprise the surgical tool **1300**. The end effector **1302** may be removably coupled to the end effector drive housing **1316** using a mechanism as described, for example, in connection with FIGS. **106-115**. The end effector connector tube **1318** comprises a cylindrical portion **1322** and a ball portion **1324**. The end effector drive housing **1316** is coupled to the cylindrical portion **1322** of the end effector connector tube **1318** through the head rotation joint **1310**. The end effector **1302** and the end effector drive housing **1316** together comprise a head portion of the surgical tool **1300**. The head portion of the surgical tool **1300** is independently rotatable about the head rotation joint **1310**.

Referring primarily to FIG. **92**, the surgical tool **1300** may include a closure mechanism **1326** for moving the first jaw member **1304** relative to the second jaw member **1306** between an open position (FIG. **93**) and a closed position (FIG. **94**). As illustrated in FIG. **83**, the first jaw member **1304** may include first mounting holes **1328**, and the second jaw member **1306** may include second mounting holes (not shown in FIGS. **92-96**). The first jaw member **1304** can be arranged relative to the second jaw member **1306** such that a pivot or trunnion pin (not shown in FIGS. **92-96**) extends through the first mounting holes **1328** of the first jaw member **1304** and the second mounting holes of the second jaw member **1306** to pivotally couple the first jaw member **1304** to the second jaw member **1306**. Other suitable means for coupling the first jaw member **1304** and the second jaw member **1306** are within the scope of this disclosure.

Referring to FIGS. **92-96**, the closure mechanism may comprise a closure link **1330** which translates axially relative to the end effector drive housing **1316** between a first position and a second position. The closure link **1330** may comprise a distal end **1332** and a proximal end **1334**. The distal end **1332** may be pivotally connected to a proximal portion **1336** of the first jaw member **1304** such that when the closure link **1330** is translated between the first position and the second position, the first jaw member **1304** is moved relative to the second jaw member **1306** between an open and a closed position.

Referring to FIGS. **92-96**, the closure mechanism **1328** may also comprise a closure driver in the form of a barrel cam **1338** for example. The barrel cam **1338** may be positioned within the end effector drive housing **1316**. The barrel cam **1338** may comprise a generally cylindrical shape having a lumen **1340** therethrough. The barrel cam **1338** may include a first arcuate groove **1346**, and a second arcuate groove **1348** defined in a peripheral surface thereof. The first arcuate groove **1346** may receive a first pin **1352** extending from the end effector drive housing **1316**. The second arcuate groove **1348** may receive a second pin (not shown in FIGS. **92-96**) extending from the end effector drive housing **1316**. The first pin **1352** and the second pin (not shown in FIGS. **92-96**) may extend from circumferentially opposite sides of an inner wall of the end effector drive housing **1316**. The barrel cam **1338** may rotate around central axis A, wherein, as the barrel cam **1338** is rotated around central axis A, the first pin **1352** travels along the first arcuate groove **1346**, and the second pin travels along the second arcuate groove **1348** thereby translating the

barrel cam **1338** axially along central axis A. The result is a conversion of the rotational motion of the barrel cam **1338** into an axial motion of the closure link **1330**. Stated another way, the rotation of the barrel cam **1338** in a first direction (for example a clockwise direction) around the central axis A may result in advancing the barrel cam **1338** axially in a distal direction. Correspondingly, the rotation of the barrel cam **1338** in a second direction (for example a counter clockwise direction) opposite the first direction may result in retracting the barrel cam **1338** axially in a proximal direction along the central axis A.

Referring to FIGS. **92-96**, the proximal end **1334** of the closure link **1330** may be operatively engaged with the barrel cam **1338** such that the axially advancement of the barrel cam **1338** may cause the closure link **1330** to be advanced axially, and, in turn close the jaw assembly **1311**. Similarly, the proximal retraction of the barrel cam **1338** may retract the closure link **1330**, which may open the jaw assembly **1311**. As illustrated in FIGS. **92-96**, the barrel cam **1338** may include a circumferential recess **1354** on the external wall of the barrel cam **1338** at a distal portion thereof. The proximal end of the closure link **1330** may comprise a connector member **1356**. The connector member **1356** may be operably engaged with the barrel cam **1338** along the recess **1354**. As a result, the barrel cam **1338** may translate axial motions to the closure link **1330** through the connector member **1356**.

Referring primarily to FIG. **92**, the surgical tool **1300** may include a firing mechanism **1358**. The firing mechanism **1358** may include an I-beam member **1360**, a threaded drive member **1362**, and a threaded rotary drive nut **1364**. The I-beam member **1360** may operate in a manner similar to that of the axially movable member **3016** described herein above and may comprise a first I-beam flange **1367** and a second I-beam flange **1368**. The first I-beam flange **1367** and the second I-beam flange **1368** are connected with an intermediate portion **1370**. The intermediate portion **1370** of the I-beam member **1360** may comprise a cutting member **1372**, which may comprise a sharp edge or blade for example, to transect tissue clamped between the first jaw member **1304** and the second jaw member **1306** when the jaw assembly **1311** is closed. The I-beam member **1360** may translate distally within a first channel (not shown in FIGS. **92-96**) defined in the first jaw member **1304** and within a second channel **1376** defined in the second jaw member **1306** to cut through clamped tissue during a distal translation (firing) stroke. FIG. **96** illustrates the I-beam member **1360** after a firing stroke.

Before, during, and/or after the I-beam member **1360** is advanced through tissue clamped between the first jaw member **1304** and the second jaw member **1306**, electrical current can be supplied to electrodes **1378** located in the first jaw member **1304** and/or second jaw member **1306** in order to weld/fuse the tissue, as described in greater detail in this specification. For example, electrodes **1378** may be configured to deliver RF energy to tissue clamped between the first jaw member **1304** and the second jaw member **1306** when in a closed position to weld/fuse the tissue.

Distal and proximal translation of the I-beam member **1360** between a proximally retracted position and a distally advanced position may be accomplished with a suitable firing mechanism **1358**. Referring to FIGS. **92-96**, the I-beam member **1360** is connected to the threaded drive member **1362**, wherein the threaded drive member **1362** is threadedly engaged with the rotary drive nut **1364**. The threaded rotary drive nut **1364** is positioned within the end effector drive housing **1316** distal to the barrel cam **1338** between a proximal annular flange **1339A** and a distal annular flange **1339B**. The threaded rotary drive nut **1364** is mechanically con-

strained from translation in any direction, but is rotatable within the end effector drive housing 1316. Therefore, given the threaded engagement of the rotary drive nut 1364 and the threaded drive member 1362, rotational motion of the rotary drive nut 1364 is transformed into translational motion of the threaded drive member 1362 along the central axis A and, in turn, into translational motion of the I-beam member 1360 along the central axis A.

The threaded drive member 1362 is threaded through the rotary drive nut 1364 and is located at least partially inside a lumen 1381 of a rotary drive shaft 1382. The threaded drive member 1362 is not attached or connected to the rotary drive shaft 1382. The threaded drive member 1362 is freely movable within the lumen 1381 of the rotary drive shaft 1382 and will translate within the lumen 1381 of the rotary drive shaft 1382 when driven by rotation of the rotary drive nut 1364. The rotary drive shaft 1382 and the threaded drive member 1362 form a concentric rotary drive shaft/threaded drive member assembly that is located in the shaft assembly 1314. In addition, the threaded drive member 1362 extends distally through a lumen 1384 of the barrel cam 1338 wherein the threaded drive member 1362 is freely movable within the lumen 1384 of the barrel cam 1338 and will translate within the lumen 1384 of the barrel cam 1338 when the threaded drive member is driven by rotation of the rotary drive nut 1364.

As shown in FIG. 92, the end effector drive housing 1316, the end effector connector tube 1318, and the intermediate articulation tube segment 1320, which together comprise the shaft assembly 1314, have lumens extending therethrough. As a result, the shaft assembly 1314 can comprise a lumen extending therethrough, as illustrated in FIGS. 92-96. Referring again to FIGS. 92-96, the concentric rotary drive shaft/threaded drive member assembly is located within the lumen of the shaft assembly 1314 and passes through the end effector drive housing 1316, the end effector connector tube 1318, and the intermediate articulation tube segment 1320. Although not shown in FIGS. 92-96, at least the rotary drive shaft 1382 passes through a lumen of the shaft assembly 1314 and is operably coupled to a driving mechanism that provides rotational and/or axial translational motion to the rotary drive shaft 1382. For example, in some embodiments, the surgical tool 1300 may be operably coupled through the shaft assembly 1314 to a robotic surgical system that provides rotational motion and/or axial translational motion to the rotary drive shaft 1382, such as, for example, the robotic surgical systems described in connection with FIGS. 5 and 16-21. For example, the rotary drive shaft 1382 may be operably coupled, through the shaft assembly 1314, to the proximal drive shaft segment 380 described herein above. Also, in some embodiments, the surgical tool 1300 may be utilized in conjunction with a hand-held surgical device, such as the device described herein above with respect to FIGS. 46-63. For example, the rotary drive shaft 1382 may be operably coupled, through the shaft assembly 1314, to the proximal drive shaft segment 380' described herein above.

In some embodiments, the threaded drive member 1362 has a length that is less than the length of the rotary drive shaft 1382 and, therefore, lies within only a distal portion of the rotary drive shaft 1382, for example. The threaded drive member 1362 and the rotary drive shaft 1382 may be flexible so that the threaded drive member 1362 and the rotary drive shaft 1382 can bend without damage or loss of operability during articulation of the surgical tool 1300 about the articulation joint 1308.

The rotary drive shaft 1382 may comprise a rotary drive head 1386. The rotary drive head 1386 may comprise spline

members 1388 disposed circumferentially around an external surface of the rotary drive head 1386 and oriented co-axially with the shaft assembly 1314. The end effector drive housing 1316 may comprise a spline coupling portion 1390 comprising spline members 1392 disposed circumferentially around an internal wall of the end effector drive housing 1316 and oriented co-axially with the shaft assembly 1314. The barrel cam 1338 may comprise a spline coupling portion 1394 comprising spline members 1396 disposed circumferentially around an internal wall of barrel cam 1338 and oriented co-axially with the shaft assembly 1314. The rotary drive nut 1364 may also comprise a spline coupling portion 1397 comprising spline members 1398 disposed circumferentially around an internal wall of rotary drive nut 1364 and oriented co-axially with the shaft assembly 1314. As illustrated in FIG. 93, the rotary drive shaft 1382 may be selectively retracted proximally to bring the rotary drive head 1386 into operable engagement with the spline coupling portion 1390 of the end effector drive housing 1316. In this configuration, rotation of the rotary drive shaft 1382 causes rotation of the head portion of the surgical tool 1300 about the head rotation joint 1310, including rotation of the end effector 1302 and the end effector drive housing 1316. In this configuration, the portion of the surgical tool 1300 that is distal to the head rotation joint 1310 rotates with rotation of the rotary drive shaft 1382, and the portion of the surgical tool 1300 that is proximal to the head rotation joint 1310 does not rotate with rotation of the rotary drive shaft 1382. An example of a head rotation joint 1310 is described in connection with FIGS. 64-82, 83-91 and 92-96. Other suitable techniques and rotation means for rotating the end effector 1302 relative to the shaft assembly 1314 are within the scope of the current disclosure. It will be appreciated that a desired rotation speed of the rotary drive shaft 1382 to drive the rotary drive nut 1364 may be greater than a desired rotational speed for rotating the head portion. For example, the rotary drive shaft 1270 may be driven by a motor (not shown) that is operable at different rotary speeds.

As illustrated in FIG. 94, the rotary drive shaft 1382 may be selectively advanced distally to bring the rotary drive head 1386 into operable engagement with the spline coupling portion 1394 of the barrel cam 1338. In this configuration, rotation of the rotary drive shaft 1382 causes rotation of the barrel cam 1338. As described above, the rotation of the barrel cam 1338 causes axial motions in the closure link 1330. In result, the rotation of the rotary drive shaft 1382 in a first direction (for example a clockwise direction) around the central axis A may cause the closure link 1330 to be advanced distally along the central axis A, which may close the jaw assembly 1311. Alternatively, the rotation of the rotary drive shaft 1382 in a second direction (for example a clockwise direction) opposite the first direction may cause the closure link 1330 to be retracted proximally along the central axis A, which in turn may open the jaw assembly 1311.

As illustrated in FIG. 95, the rotary drive shaft 1382 may be selectively advanced distally to pass the rotary drive head 1386 through the lumen of the barrel cam 1338 into a space 1399 in the end effector drive housing 1316 between the barrel cam 1338 and the rotary drive nut 1364 wherein the rotary drive head 1386 is not in operable engagement with any of the spline coupling portions. The rotary drive shaft 1382 may then be further advanced distally to bring rotary drive head 1386 into operable engagement with the spline coupling portion 1397 of the rotary drive nut 1364 as illustrated in FIG. 96. In this configuration, rotation of the rotary drive shaft 1382 causes rotation of the rotary drive nut 1364. As described above, the rotation of the rotary drive nut 1364 causes axial motions in the threaded drive member 1362. In

result, rotation of the rotary drive shaft **1382** in a first direction (for example a clockwise direction) around the central axis A, may cause the threaded drive member **1362** to be advanced distally, which in turn may advance the I-beam member **1360** distally. Alternatively, rotation of the rotary drive shaft **1382** in a second direction (for example a clockwise direction) opposite the first direction may cause the threaded drive member **1362** to be retracted proximally, which may retract the I-beam member **1360** proximally.

The sequence of events causing the closure of the jaw assembly **1311**, the full extension of the I-beam member **1360**, the full retraction of the I-beam member **1360**, and the reopening of the jaw assembly **1311** is illustrated in FIGS. **93-96** in a chronological order. FIG. **93** shows the jaw assembly **1311** in a fully open position, the I-beam member **1360** in a fully retracted position, and the rotary drive shaft **1382** in a retracted axial position, wherein the rotary drive head **1386** is operably engaged with the spline coupling portion **1390** of the end effector drive housing **1316**. In a first phase of operation, the rotary drive shaft **1382** is rotated to rotate the end effector **1302** into an appropriate orientation, for example relative to a blood vessel. In a second phase of operation, the rotary drive shaft **1382** is advanced axially to bring the rotary drive head **1386** into operable engagement with the spline coupling portion **1394** of the barrel cam **1338**. In this configuration, the rotary drive shaft **1382** may be rotated in a first direction (for example a clockwise direction) around the central axis A to close the jaw assembly **1311** around the blood vessel. The electrodes **1378** in the first jaw member **1304** and the second jaw member **1306** may be activated to seal the blood vessel. In a third phase of operation, the rotary drive shaft **1382** may then be advanced axially to bring the rotary drive head **1386** into operable engagement with the spline coupling portion **1397** of the rotary drive nut **1364**. In this configuration, the rotary drive shaft **1382** may be rotated in a first direction around the central axis A (for example a clockwise direction) to advance the I-beam member **1360** thereby transecting the sealed blood vessel. In a fourth phase of operation, the rotary drive shaft **1382** may be rotated in a second direction (for example a counter clockwise direction) opposite the first direction to retract the I-beam member **1360**.

In a fifth phase of operation, the rotary drive shaft **1382** is retracted axially to bring the rotary drive head **1386** into operable engagement with the spline coupling portion **1394** of the barrel cam **1338**. In this configuration, the rotary drive shaft **1382** may be rotated in a second direction (for example a counter clockwise direction) opposite the first direction to reopen the jaw assembly **1311** thereby releasing the sealed cut blood vessel.

As described above, a surgical tool can utilize a drive system for translating a drive member distally within an end effector of the surgical tool, to advance a cutting member within the end effector, for example, and for translating the drive tube proximally to retract the drive tube and/or cutting member. FIGS. **97** and **98** illustrate an example drive shaft assembly **1400** that may be employed in connection with an end effector **1420** and/or any of the end effectors described herein. For example, the drive shaft assembly **1400** (as well as the assembly **1400'**) may correspond to various threaded rotary drive members described herein including, for example, the threaded rotary drive members **604**, **654**, **1040**, **1248**, **1364**, etc. Further to the above, the drive shaft assembly **1400** can be advanced distally in order to rotate a jaw member **1422** of the end effector **1420** between a closed position and an open position, as illustrated in FIG. **97**, and advance a cutting member between the jaw member **1422** and a jaw member **1424** positioned opposite the jaw member **1422**. In

one example form, the drive shaft assembly **1400** includes a drive member, or tube, **1402** that can comprise a series of annular joint segments **1404** cut therein.

In various example embodiments, the drive member **1402** can comprise a hollow metal tube comprised of stainless steel, titanium, and/or any other suitable material, for example, that has a series of annular joint segments **1404** formed therein. In at least one embodiment, the annular joint segments **1404** can comprise a plurality of loosely interlocking dovetail shapes **1406** that are, for example, cut into the drive member **1402** by a laser and serve to facilitate flexible movement between the adjoining joint segments **1404**. Such laser cutting of a tube stock can create a flexible hollow drive tube that can be used in compression, tension and/or torsion. Such an arrangement can employ a full diametric cut that is interlocked with the adjacent part via a "puzzle piece" configuration. These cuts are then duplicated along the length of the hollow drive tube in an array and are sometimes "clocked" or rotated to change the tension or torsion performance. Further to the above, the interlocking dovetail shapes **1406** are but one example embodiment and, in various circumstances, the drive member **1402** can comprise any suitable array of articulation joints comprising interlocking drive projections and drive recesses. In various circumstances, the drive member **1402** can comprise an articulation joint lattice comprising operably engaged projections and recesses which can be interlocked to transmit linear and/or rotary motions therebetween. In a sense, in various embodiments, the drive member **1402** can comprise a plurality or a multitude of articulation joints defined within the body of the drive member **1402**. The drive member **1402** can include a plurality of articulation joints which are intrinsic to the body of the drive member **1402**.

Further to the above, the drive member **1402** can be pushed distally such that a longitudinal force is transmitted through the drive member **1402** and to a cutting member, for example, operably coupled with a distal end of the drive member **1402**. Correspondingly, the drive member **1402** can be pulled proximally such that a longitudinal force is transmitted through the drive member **1402** and to the cutting member. The interlocking dovetail shapes **1406** can be configured to transmit the longitudinal pushing and pulling forces between the joint segments **1404** regardless of whether the joint segments **1404** are longitudinally aligned, as illustrated in FIG. **98**, and/or articulated relative to each other to accommodate the articulation of the articulation joint **1430** which rotatably connects the end effector **1420** to the shaft of the surgical instrument. More particularly, further to the above, the articulation joint **1430** can comprise one or more articulation segments **1434** which can move relative to one another to permit the end effector **1420** to rotate wherein, in order to accommodate the relative movement of the articulation joint segments **1434**, the joint segments **1404** of the drive member **1402** can rotate or shift relative to each other. In at least the illustrated embodiment of FIG. **97**, the articulation joint segments **1434** can define a passage **1435** extending therethrough which can be configured to closely receive the drive tube **1402** and constrain large transverse movements between the joint segments **1404** while concurrently permitting sufficient relative movement between the joint segments **1404** when the articulation joint **1430** has been articulated. FIGS. **99-101** illustrate alternative example micro-annular joint segments **1404'** of a drive member **1402'** that can comprise a plurality of laser cut shapes **1406'** that roughly resemble loosely interlocking, opposed "T" shapes and T-shapes with a notched portion therein, for example. The laser cut shapes **1406'** can also roughly resemble loosely interlocking, opposed "L" shapes and

L-shapes defining a notched portion, for example. The annular joint segments **1404**, **1404'** can essentially comprise multiple micro-articulating torsion joints. That is, each joint segment **1404**, **1404'** can transmit torque while facilitating at least some relative articulation between each annular joint segment. As shown in FIGS. **99** and **100**, the joint segment **1404D'** on the distal end **1403'** of the drive member **1402'** has a distal mounting collar portion **1408D'** that facilitates attachment to other drive components for actuating the end effector. Similarly, the joint segment **1404P'** on the proximal end **1405'** of the drive member **1402'** has a proximal mounting collar portion **1408P'** that facilitates attachment to other proximal drive components or portions of a quick disconnect joint, for example.

The joint-to-joint range of motion for each particular joint segment **1404'** can be increased by increasing the spacing in the laser cuts. In various circumstances, however, the number and/or density of the laser cuts within any particular region of the drive member **1402'** can cause the drive member **1402'** to be particularly flexible in that region. To ensure that the joint segments **1404'** remain coupled together without significantly diminishing the drive tube's ability to articulate through desired ranges of motion, a secondary constraining member can be employed to limit or prevent the outward expansion of the joint segments **1404'**. In the example embodiment depicted in FIGS. **102** and **103**, a secondary constraining member **1410** comprises a spring **1412** or an otherwise helically-wound member. In various example embodiments, the distal end **1414** of the spring **1412** can correspond to and can be attached to the distal mounting collar portion **1408D'** and can be wound tighter than the central portion **1416** of the spring **1412**. Similarly, the proximal end **1418** of the spring **1412** can correspond to and can be attached to the proximal collar portion **1408P'** and can be wound tighter than the central portion **1416** of the spring **1412**. As a result of the tighter winding, the distal end **1414** and/or the proximal end **1418** can comprise coils which are positioned closer together than the coils of the central portion **1416**. Stated another way, the coils per unit distance of the distal end **1414** and/or the proximal end **1418** can be greater than the coils per unit distance of the central portion **1416**. In any event, the spring **1412** can define a longitudinal aperture **1413** within which the drive member **1402'**, and/or the drive member **1402**, for example, can be positioned. The longitudinal aperture **1413** and the drive member **1402'** can be sized and configured such that the drive member **1402'** is closely received within the longitudinal aperture **1413** wherein, in various circumstances, the coils of the spring **1412** can limit the outward movement of the joint segments **1404'** such that the joint segments **1404'** do not become disconnected from one another when they are articulated relative to one other. As outlined above, the distal end **1414** of the spring **1412** can be fixedly mounted to the distal end **1403'** of the drive member **1402'** and the proximal end **1418** of the spring **1412** can be fixedly mounted to the proximal end **1405'** of the drive member **1402'** wherein the movement of the distal tube end **1403'** can move the distal spring end **1414** and, correspondingly, the movement of the proximal tube end **1405'** can move the proximal spring end **1418**. In various circumstances, the spring ends **1414** and **1418** can be welded, for example, to the tube ends **1403'** and **1405'**, respectively. In at least the illustrated embodiment, the coils of the central portion **1416** may not be fixedly mounted to the drive member **1402'**. In at least one such embodiment, the drive member **1402'** can be configured to at least partially articulate within the coils of the central portion **1416** until the drive member **1402'** contacts the coils wherein, at such point, the coils can be configured to at

least partially expand or shift to accommodate the lateral movement of the drive member **1402'**. In various other embodiments, at least portions of the coils of the central portion **1416** can be fixedly mounted, such as by welding, for example, to the drive member **1402'**.

Further to the above, the constraining member **1410** may be installed on the drive member **1402'** with a desired pitch such that the constraining member **1410** also functions, for example, as a flexible drive thread **1440** which can be threadably engaged with other threaded drive components on the end effector and/or the drive system, as described above. The drive member **1402'** can be constrained from being revolved around its longitudinal axis wherein, when a threaded drive input is engaged with the thread **1440** and is rotated in a first direction by a motor, for example, the drive member **1402'** can be advanced distally within the end effector **1420**. Correspondingly, when the threaded drive input engaged with the thread **1440** is rotated in a second, or opposite, direction, the drive member **1402'** can be retracted proximally. It will be appreciated that the constraining member **1410** may be installed in such a manner that the thread **1440** includes a constant, or at least substantially constant, pitch along the length thereof. In such embodiments, the drive member **1402'** can be advanced and/or retracted at a constant, or an at least substantially constant, rate for a given rate in which the threaded drive input is rotated. It will also be appreciated that the constraining member **1410** can be installed in such a manner that the thread **1440** includes a variable pitch, or a pitch which changes along the length of the drive member **1402'**. For example, the variable pitch arrangement of the constraining member **1410** may be used to slow the drive assembly **1400'** down or speed the drive assembly **1400'** up during certain portions of the firing stroke of the drive assembly **1400'**. For instance a first portion of the thread **1440** can include a first pitch which is smaller than the pitch of a second portion of the thread **1440** wherein the first pitch can drive a closing member at a first rate and the second portion can drive a firing member at a second rate, for example. In at least some forms, for example, the drive shaft assembly comprises a variable pitch thread on a hollow flexible drive shaft that can be pushed and pulled around a ninety degree bend or greater, for example.

As discussed above, the drive member **1402'** can be constrained from revolving about its longitudinal axis. Moreover, the entire drive shaft assembly **1400'** can be constrained from rotating about its longitudinal axis. In various embodiments, the drive member **1402'** can comprise a longitudinal slot defined therein which can be engaged with one or more projections which can extend inwardly from the end effector **1420** and/or the articulation joint members **1434** into the longitudinal slot, for example. Such an arrangement of the longitudinal slot and the projections can be configured to prevent or at least limit the rotation of the drive shaft assembly **1400'** about its own longitudinal axis. As used herein, the longitudinal axis of the drive shaft assembly **1400'**, and/or the drive member **1402'**, can extend along the center of the drive shaft assembly **1400'** regardless of whether the drive shaft assembly **1400'** is in a straight configuration or a bent configuration. As a result, the path and direction of the longitudinal axis of the drive shaft assembly **1400'** may change when the end effector **1420** is articulated and the drive shaft assembly **1400'** articulates to accommodate the articulation of the end effector **1420**. Further to the above, the drive member **1402'** can be fixedly mounted to and extend proximally from a cutting member positioned within the end effector **1420**. As described herein, the cutting member can be closely received within various slots and/or channels defined in the end effec-



tor which can prevent the cutting member, and the drive shaft assembly 1400' extending therefrom, from being rotated, or at least substantially rotated about its longitudinal axis. While the longitudinal axis of the drive shaft assembly 1400' can be defined by the drive member 1402', the longitudinal axis can be defined by the spring 1412. In at least one such embodiment, the center path of the spring coils can define the longitudinal axis of the drive shaft assembly 1400'. In any event, the drive shaft assembly 1400' can be constrained from revolving around its longitudinal axis.

Turning now to FIGS. 104 and 105, the drive shaft assembly 1400' can comprise an internal constraining member, such as a flexible core 1417, for example, which can be configured to limit or prevent the inward movement or collapse of the joint segments 1404' of the drive member 1402'. The drive member 1402' can define an internal longitudinal cavity 1415 which can be configured to closely receive the flexible core 1417. In at least one such embodiment, the internal cavity 1415 defined in the drive member 1402' can comprise a diameter or width which is equal to, or at least substantially equal to, the diameter or width of the flexible core 1417. In various circumstances during the articulation of the end effector 1420, for example, portions of the joint segments 1404' can deflect or be displaced inwardly toward the flexible core 1417 wherein, when the joint segments 1404' contact the flexible core 1417, the core 1417 can inhibit the inward movement of the joint segments 1404' and prevent the drive member 1402' from collapsing inwardly. The flexible core 1417 can be mounted to at least portions of the drive member 1402' such as the distal end 1408D' and/or the proximal end 1408P' thereof, for example. In certain embodiments, the flexible core 1417 may not be fixedly mounted to the drive member 1402' wherein, in such embodiments, the flexible core 1417 can be held in place by the drive member 1402'. In any event, the flexible core 1417 can be sufficiently flexible so as to permit the drive shaft assembly 1400' to bend or articulate as necessary to transmit the pushing and pulling motions applied thereto, as described above.

As outlined above, the shaft assembly 1400', for example, can be configured to bend or flex to accommodate the articulation of the end effector 1420 about the articulation joint 1430. The drive member 1402', the flexible core 1417, and/or the spring 1412 can be resilient such that the shaft assembly 1400' can return to its original longitudinal configuration, for example. In various circumstances, the end effector 1420 can be rotated from its articulated position back to its longitudinal, or straight, position and, as such, the shaft assembly 1400' can be configured to bend or flex in order to accommodate the return of the end effector 1420.

Referring to FIGS. 106-108, a surgical tool 1000 may include a surgical end effector 1001 and a shaft assembly 1003. Surgical end effector 1001 may be configured to perform surgical activities in response to drive motions applied thereto. Shaft assembly 1003 may be configured to transmit such drive motions to surgical end effector 1001. The surgical end effector 1001 may include a first jaw member 1002, and a second jaw member 1004. The first jaw member 1002 may be movable relative to the second jaw member 1004 between a first position and a second position. Alternatively, the first jaw member 1002 and second jaw member 1004 may be moveable relative to each other between a first position and a second position. The first position may be an open position and the second position may be a closed position.

Referring to FIGS. 106-108, the first jaw member 1002 may be pivotally movable relative to the second jaw member 1004 between a first position and a second position. As illustrated in FIG. 108, the first jaw member 1002 may include

mounting holes (not shown), and the second jaw member 1004 may include mounting holes 1008. The first jaw member 1002 can be arranged relative to the second jaw member 1004 such that a pivot or trunnion pin (not shown) is inserted through the mounting holes of the first jaw member 1002 and the mounting holes 1008 of the second jaw member 1004 to pivotally couple the first jaw member 1002 to the second jaw member 1004. Other suitable means for coupling the first jaw member 1002 and the second jaw member 1004 are contemplated within the scope of this disclosure.

Referring to FIGS. 106-108, surgical end effector 1001 may be adapted to perform multiple functions. For example, surgical end effector 1001 may include gripping portions 1010 disposed on exterior surfaces of the first jaw member 1002 and/or the second jaw member 1004. Gripping portions 1010 may be adapted for contacting and bluntly dissecting tissue. Suitable gripping portions 1010 are described, for example, in connection with FIGS. 116-131. Surgical end effector 1001 may also include angled tissue engagement surfaces 1012 for transecting tissue. Suitable angled tissue engagement surfaces 1012 are described, for example, in connection with FIGS. 132-142. The first jaw member 1002 may include an interior surface 1014 and the second jaw member 1004 may include an interior surface 1016. The first 1014 and second 1016 interior surfaces may be configured to grip, pass, and/or manipulate tissue and/or surgical implements such as needles 1015 for suturing tissue. This gripping, passing, and/or manipulating functionality is described, for example, in connection with FIGS. 153-168. Furthermore, surgical end effector 1001 may also include electrodes 1017 and/or another electrically active surface for sealing blood vessels during a surgical procedure. The electrodes 1017 may be configured to deliver radio frequency (RF) energy to tissue clamped between the first jaw member 1002 and the second jaw member 1004 when in a closed position to weld/fuse the tissue, which may be transected by translating a cutting member 1018. Suitable electrodes are described, for example, in connection with FIGS. 153-168.

Referring to FIGS. 108-111, surgical end effector 1001 may be releasably attached to shaft assembly 1003. An operator or a surgeon may attach surgical end effector 1001 to shaft assembly 1003 to perform a surgical procedure. In the embodiment depicted in FIG. 108, shaft assembly 1003 includes a coupling arrangement in the form of a quick disconnect arrangement or joint 1019 that facilitates quick attachment of a distal shaft portion 1020 of the shaft assembly 1003 to a proximal shaft portion 1022 of the surgical end effector 1001. The quick disconnect joint 1019 may serve to facilitate the quick attachment and detachment of a plurality of drive train components used to provide control motions from a source of drive motions to an end effector that is operably coupled thereto.

As illustrated in FIG. 112, surgical end effector 1001 may be interchanged with other surgical end effectors suitable for use with shaft assembly 1003. For example, surgical end effector 1001 may be detached from shaft assembly 1003 and a second surgical end effector 1024 may be attached to shaft assembly 1003. In another example, the second surgical end effector 1024 may be replaced with a third surgical end effector 1026. Surgical end effectors 1001, 1024, and 1026 may include common drive train components that are operably engageable with their counter parts in the shaft assembly 1003. Yet, surgical end effectors 1001, 1024, and 1026 may each include unique operational features suitable for certain surgical tasks.

The surgical end effector 1001 may include an actuation mechanism. The actuation mechanism may comprise a clo-

sure mechanism for moving the first jaw member **1002** relative to the second jaw member **1004**. The actuation mechanism may comprise a firing mechanism for transecting tissue grasped between the first jaw member **1002** and the second jaw member **1004**. The closure and firing may be accomplished by separate mechanisms, which may be driven separately or contemporaneously. Alternatively, the closure and firing may be accomplished via a single mechanism. Suitable closure mechanisms and suitable firing mechanisms are described, for example, in connection with FIGS. **64-82**, **83-91** and **92-96**.

Referring to FIG. **113**, an actuation mechanism **1028** is shown. The actuation mechanism may include a reciprocating member **1030**. The reciprocating member **1030** may define a cam slot **1032** configured to receive a cam pin **1034** coupled to the first jaw member **1002**. Distal and proximal movement of the reciprocating member **1030** may cause the cam pin **1032** to translate within the cam slot **1034**, which may, in turn, cause the first jaw member **1002** to pivot from an open position (e.g., proximal position of the reciprocating member **1030**) to a closed (e.g., distal position of the reciprocating member **1030**). In embodiments where the first **1002** and the second **1004** jaw members are movable, both jaw members **1002** and **1004** may comprise a cam pin and the reciprocating member **1030** may define a pair of cam slots or grooves. The reciprocating member **1030** may comprise an I-beam member adapted to slide over the jaw members **1002** and **1004** to close the jaw members **1002** and **1004**, and/or to provide a clamping force tending to force the jaw members **1002**, and **1004** together. The reciprocating member **1030** may include a cutting blade **1036**. The cutting blade **1036** may be attached to the reciprocating member **1030** and situated such that it can be extended and retracted with the reciprocating member **1030**. The cutting member may be extended to transect tissue or material present between the jaw members **1002**, and **1004**.

Referring to FIGS. **108-111**, the actuation mechanism **1028** may include a rotary drive nut **1038** and a threaded rotary drive member **1040**. The rotary drive member **1040** may extend proximally from the reciprocating member **1030**. The reciprocating member **1030** and the rotary drive member **1040** may be formed together as one piece. Alternatively, the reciprocating member **1030** and the rotary drive member **1040** may be formed separately and welded together. Other techniques for joining the reciprocating member **1030** and the rotary drive member **1040** may be employed and are contemplated within the scope of this disclosure. The rotary drive nut **1038** may be operably supported within the proximal shaft portion **1022** of the surgical end effector **1001**, which extends proximally relative to the jaw members **1002**, and **1004**. The rotary drive nut **1038** may be rotated around a central axis extending through the proximal shaft portion **1022**, for example, as described herein above. The rotary drive member **1040** may extend proximally from the reciprocating member **1030** along the central axis through the rotary drive nut **1038**. The rotary drive nut **1038** and the rotary drive member **1040** may be arranged in a mating arrangement such that rotation of the rotary drive nut **1038** around the central axis in one direction (e.g. clockwise direction) may advance the rotary drive member **1040**, and rotation of the rotary drive nut **1038** around the central axis in the opposite direction e.g. counter clockwise direction) may retract the rotary drive member **1040**. This actuation mechanism and other suitable actuations mechanisms are described, for example, in connection with FIGS. **64-82**, **83-91** and **92-96**.

Referring to FIGS. **108-111**, the surgical tool **1000** may include a rotary drive shaft **1042** disposed longitudinally

through shaft assembly **1003**. The rotary drive shaft **1042** may include a rotary drive head **1044** at a distal portion thereof. The rotary drive nut **1038** may comprise an actuation coupler **1046** for mating arrangement with the rotary drive head **1044** such that when coupled, the rotary drive head **1044** may transmit rotary motions to the actuation coupler **1046**. The rotary drive shaft **1042** may be selectively moved axially between multiple discrete positions. For example, the rotary drive shaft **1042** may be extended axially to bring the rotary drive head **1044** into operable engagement with the actuation coupler **1046** as depicted in FIG. **111**. Alternatively, the rotary drive shaft **1042** may be refracted axially to disengage the rotary drive head **1044** from the actuation coupler **1046**. Such arrangement may allow for a quick and efficient attachment and detachment of a plurality of surgical end effectors to shaft assembly **1003**.

Referring to FIGS. **108-110**, surgical end effector **1001** is shown detached from shaft assembly **1003**. The proximal shaft portion **1022** of surgical end effector **1001** is disengaged from the distal shaft portion **1020** of the shaft assembly **1003**. As depicted in FIG. **108**, the proximal shaft portion **1022** of the surgical end effector **1001** may include a tapered end for mating arrangement with a funneling end on the distal shaft portion **1020** of the shaft assembly **1003**. The rotary drive shaft **1042** may include a hollow distal portion that extends distally along a central axis through the rotary drive head **1044** and terminates at a distal opening thereof. The hollow distal portion may receive a proximal portion of the rotary drive member **1040** when the surgical end effector **1001** is attached to the shaft assembly **1003**. The rotary drive member **1040** may rotate freely in the hollow distal portion of the rotary drive shaft **1042**. As depicted in FIG. **110**, the surgical end effector **1001** is attached to shaft assembly **1003** simply by inserting the proximal portion of the rotary drive member **1040** into the hollow portion of the rotary drive shaft **1042** and guiding the tapered end of the proximal shaft portion **1022** of the surgical end effector **1001** into a mating arrangement with the funneling end of the distal shaft portion **1020** of the shaft assembly **1003**. As depicted in FIG. **111**, once the surgical end effector **1001** is attached to shaft assembly **1003**, the rotary drive shaft **1042** may be advanced to bring the rotary drive head **1044** into operable engagement with the actuation coupler **1046** to transmit rotary motions to the rotary drive nut **1038**. Other attachment means and techniques for releasably attaching the surgical end effector **1001** to the shaft assembly **1003** are contemplated within the scope of this disclosure.

As illustrated in FIGS. **108-110**, the proximal shaft portion **1022** of surgical end effector **1001** and the distal shaft portion **1020** of the shaft assembly **1003** may have aligning features to ensure that the surgical end effector **1001** and the shaft assembly **1003** are correctly aligned upon attachment. In an example embodiment, as illustrated in FIG. **108**, the proximal shaft portion **1022** of surgical end effector **1001** includes a key feature **1048** and the distal shaft portion **1020** of the shaft assembly **1003** may include a slot **1050** for receiving the key feature. Other aligning means and techniques for aligning the surgical end effector **1001** to the shaft assembly **1003** are contemplated within the scope of this disclosure.

Referring to FIG. **114**, the surgical end effector **1001** may include an actuation mechanism wherein the firing and closure are performed separately. This actuation mechanism and other suitable actuation mechanisms are described, for example, in connection with FIGS. **83-91** and **92-96**. In an example embodiment, as illustrated in FIG. **114**, the surgical end effector **1001** comprises a closure mechanism **1052** and a firing mechanism **1054** which are driven separately. The closure mechanism **1052** includes a closure driver **1056** and the

65

firing mechanism **1054** includes a firing driver **1058**. As described above, surgical end effector **1001** may be releasably attached to shaft assembly **1003**. As depicted in FIG. **114**, the proximal shaft portion **1022** of surgical end effector **1001** may be detached from the distal shaft portion **1020** of the shaft assembly **1003**. Once the proximal shaft portion **1022** of surgical end effector **1001** is attached to the distal shaft portion **1020** of the shaft assembly **1003**, the shaft drive **1042** may be extended distally to a first discrete position to be in operable engagement with the closure driver **1056**. Alternatively, the shaft drive may be extended distally to a second discrete position distal to the first discrete position to be in operable engagement with the firing driver **1058**.

As illustrated in FIG. **115**, the surgical tool **1000** may include an articulation joint **1060** for articulating the surgical end effector **1001** about a longitudinal tool axis "LT". In this example embodiment, the articulation joint **1060** is disposed proximal to the distal portion **1020** of the shaft assembly **1003**. The articulation joint **1060** articulates the distal portion **1020** of the shaft assembly **1003**. When the proximal portion **1022** of the surgical end effector **1001** is attached to the distal portion **1020** of the shaft assembly **1003**, articulation of the distal portion **1020** of shaft assembly **1003** will cause the surgical end effector **1003** to articulate.

In an example embodiment, as illustrated in FIG. **115**, the articulation joint **1060** includes a proximal socket tube **1062** that is attached to the shaft assembly **1003** and defines a proximal ball socket therein. See FIG. **115**. A proximal ball member **1064** is movably seated within the proximal ball socket. As can be seen in FIG. **115**, the proximal ball member **1064** has a central drive passage that enables the rotary drive shaft **1042** to extend therethrough. In addition, the proximal ball member **1064** has four articulation passages therein which facilitate the passage of four distal cables **1066** therethrough. As can be further seen in FIG. **115**, the articulation joint **1060** further includes an intermediate articulation tube segment **1068** that has an intermediate ball socket formed therein. The intermediate ball socket is configured to movably support therein a distal ball member **1070** formed on a distal connector tube **1072**. The cables **1066** extend through cable passages formed in the distal ball member **1070** and are attached thereto by lugs **1074**. Other attachment means suitable for attaching cables to the end effector ball **1070** are contemplated within the scope of this disclosure.

Referring to FIGS. **116-120**, a surgical tool **900** may include a surgical end effector extending from a shaft assembly **903**. The surgical end effector **901** may be configured to perform surgical activities in response to drive motions applied thereto. The surgical end effector **901** may include a first jaw member **902**, and a second jaw member **904**. The first jaw member **902** may be movable relative to the second jaw member **904** between a first position and a second position. Alternatively, the first jaw member **902** and second jaw member **904** may be moveable relative to each other between a first position and a second position. The first position may be an open position and the second position may be a closed position.

Referring to FIGS. **116-120**, the first jaw member **902** may be pivotally movable relative to the second jaw member **904** between an open position and a closed position. As illustrated in FIG. **120**, the first jaw member **902** may include mounting holes **906**, and the second jaw member **904** may include mounting holes **908**. The first jaw member **902** can be arranged relative to the second jaw member **904** such that a pivot or trunnion pin (not shown) is inserted through the mounting holes **906** of the first jaw member **902** and the mounting holes **908** of the second jaw member **904** to pivot-

66

ally couple the first jaw member **902** to the second jaw member **904**. Other suitable means for coupling the first jaw member **902** and the second jaw member **904** are contemplated within the scope of this disclosure.

Referring to FIGS. **116-120**, surgical end effector **901** may be adapted to perform multiple functions. For example, surgical end effector **901** may include angled tissue engagement surfaces **910** for transecting tissue. Suitable tissue engagement surfaces **910** are described, for example, in connection with FIGS. **132-142**. The first jaw member **902** may include an interior surface **912** and the second jaw member **904** may include an interior surface **914**. The first interior surface **912** and the second interior surface **914** may be configured to grip, pass, and/or manipulate tissue and/or surgical implements such as needles **915** for suturing tissue. This gripping, passing, and/or manipulating functionality is described, for example, in connection with FIGS. **153-168**.

Referring to FIGS. **116-120**, the surgical end effector **901** may also include electrodes **916** and/or another electrically active surface for sealing blood vessels during a surgical procedure. The electrodes **916** may be configured to deliver radio frequency (RF) energy to tissue clamped between the first jaw member **902** and the second jaw member **904** when in a closed position to weld/fuse the tissue, which may be transected by translating a cutting member. Suitable electrodes **916** are described, for example, in connection with FIGS. **6-10** and FIGS. **153-168**. The surgical end effector **901** may be releasably attached to a shaft assembly **903**. An operator or a surgeon may attach surgical end effector **901** to shaft assembly **903** to perform a surgical procedure. Suitable techniques and mechanisms for releasably attaching the surgical end effector **901** to the shaft assembly **903** are described, for example, in connection with FIGS. **106-115**.

Referring to FIGS. **116-120**, the surgical end effector **901** may include an actuation mechanism. The actuation mechanism may comprise a closure mechanism for moving the first jaw member relative to the second jaw member. The actuation mechanism may comprise a firing mechanism for transecting tissue grasped between the first jaw member and the second jaw member. The closure and firing may be accomplished by separate mechanisms, which may be driven separately or contemporaneously. Alternatively, the closure and firing may be accomplished by a single mechanism. Suitable closure mechanisms and suitable firing mechanisms are described, for example, in connection with FIGS. **64-82**, **83-91** and **92-96**.

As illustrated in FIG. **117** an example actuation mechanism **920** is shown. The actuation mechanism **920** may include a reciprocating member **918** similar to the axially movable member **3016** described herein above. The reciprocating member **918**, or a cam pin **924** thereof, may be received within a cam slot **922**. Distal and proximal movement of the reciprocating member **918** may cause the cam pin **924** to translate within the cam slot **922**, which may in turn, cause the first jaw member **902** to pivot from an open position (e.g., proximal position of the reciprocating member **918**) to a closed (e.g., distal position of the reciprocating member **918**). In embodiments where the first **902** and the second **904** jaw members are movable, both jaw members may comprise cam slot **922** and the reciprocating member **918** may define a pair of cam pins. The reciprocating member **918** may comprise an I-beam member adapted to slide over the first jaw member **902** and the second jaw member **904** to close the first jaw member **902** and the second jaw member **904**, and/or to provide a clamping force tending to force the first jaw member **902** and the second jaw member **904** together. The reciprocating member **918** may include a cutting blade **926**. The

cutting blade **926** may be attached to the reciprocating member **918** and situated such that it can be extended and retracted with the reciprocating member **918**. The cutting blade **926** may be extended to transect tissue or material present between the first jaw member **902** and the second jaw member **904**.

Referring to FIGS. **116-120**, the first jaw member **902** may include an exterior surface **928**. The exterior surface of first jaw member **902** may include a first tissue gripping portion **930**. The second jaw member **904** may also include an exterior surface **932**. The exterior surface **932** of second jaw member **904** may include a second tissue gripping portion **934**. The first tissue gripping portion **930** and second tissue gripping portion **934** may grip tissue by contacting and temporarily adhering to tissue. The first gripping portion **930** and the second gripping portion **934** may contact and bluntly dissect tissue while the first jaw member **902** and the second jaw member **904** is moving relative to each other from the closed position to the open position.

In an example embodiment, the surgical end effector **901** may be utilized during a surgical procedure to dissect tissue. For example, the first gripping portion **930** and the second gripping portion **934** may contact and temporarily adhere to a first and second tissue portions (not shown) respectively such that when the first jaw member **902** is moved relative to the second jaw member **904** from a closed position to the open position, the first tissue portion is separated from the second tissue portion along facial planes while substantially preserving locoregional architecture and structural integrity of vessels and nerves. The first gripping portion **930** and the second gripping portion **934** may be configured to create operative space during a surgical procedure by bluntly separating (dissecting) tissue layers as the first jaw member **902** is moved relative to the second jaw member **904**.

As illustrated in FIG. **121**, the first gripping portion **930** and the second gripping portion **934** may be formed onto distal sections of the exterior surfaces **928** and **932** of the first and second jaw members **902** and **904** by applying a coating. In one embodiment, the first and second gripping portions **930** and **934** are attached to the exterior surfaces **928** and **932** of their respective jaw members by an adhesive. In one embodiment, the first and second gripping portions **930** and **934** are press fitted onto distal portions of the exterior surfaces **928** and **932**. Other techniques and attachment means suitable for attaching or forming a gripping portion onto an exterior surface are contemplated by the current disclosure.

The first and second gripping portions **930** and **934** may include materials with high coefficient of friction to grip tissue as tissue slides relative to the first and second jaw members **902** and **904** upon moving the first and second jaw members **902** and **904** relative to each other to the open position thereby separating (dissecting) tissue layers along fascial planes while substantially preserving locoregional architecture and structural integrity of vessels and nerves. Examples of materials with high coefficient of friction that may be utilized to form the first and second gripping portions **930** and **934** include but are not limited to Silicone based elastomers, styrenic-based thermoplastic elastomers (TPE), polyisoprene, low density polyethylene, polypropylene, sanoprene, silicone, polyurethane, natural rubber, isoplast, liquid crystal polymer (LCP), etc.

The first and second gripping portions **930** and **934** may include a semi-rigid material sufficiently flexible to contour without shearing upon tissue contact. The first and second gripping portions **930** and **934** may include a non-allergenic biocompatible material. In one embodiment, the first and second gripping portions **930** and **934** may comprise a mate-

rial with a low Young's modulus and high yield strain such as an elastomer. Examples of suitable elastomers include but are not limited to Silicone based elastomers, styrenic-based thermoplastic elastomers (TPE), polyisoprene, low density polyethylene, polypropylene, sanoprene, silicone, polyurethane, natural rubber, isoplast, liquid crystal polymer (LCP), etc.

Referring to FIGS. **116-120**, the first and second gripping portions **930** and **934** may include gripping features **936**. The gripping features **936** may be sufficiently flexible to contour without shearing upon tissue contact. The gripping features **936** may be in the form of protrusions **938**. In at least one embodiment, the gripping features **936** may be in the form of depressions **940**.

Referring to FIGS. **121-126**, the gripping features **936** may be spatially arranged in a gripping pattern **942**. Gripping pattern **942** may include a plurality of protrusions **938**. The gripping pattern may include a plurality of depressions **940**. In at least one embodiment, as illustrated in FIG. **127**, the gripping pattern **942** may include a plurality of alternating protrusions **938** and depressions **940**. In one embodiment, as illustrated in FIG. **123**, the gripping pattern **942** may include four protrusions **938**.

As illustrated in FIG. **128**, gripping pattern **942** may include a plurality of protrusions **940** spatially arranged in a circle. Other arrangements are possible and within the scope of the present disclosure. As illustrated in FIG. **122**, gripping pattern **942** may include a plurality of protrusions **938** spatially arranged in multiple rows wherein each row includes several protrusions **938** aligned along the length of the row. Each row may include alternating protrusions **938** and depressions **940**.

Referring to FIG. **123-128**, the gripping pattern **942** may include vertical protrusions **938** that extend horizontally on gripping portion **930**. As illustrated in FIG., the vertical protrusions **938** may extend in opposing directions. In certain embodiments, as illustrated in FIG. **124**, the protrusions **938** may extend in parallel rows. In at least one embodiment, as illustrated in FIG. **125**, gripping pattern **942** includes a first plurality of parallel protrusions **938a**, and a second plurality of parallel protrusions **938b**, wherein the first plurality **938a** is in a slanted arrangement with the second plurality **938b**. In at least one embodiment, as illustrated in FIG. **125**, the gripping portion **930** may include a herringbone pattern.

Referring to FIGS. **129-131**, the gripping pattern **942** may define vertical protrusions **938** that extend horizontally on gripping portion **930** in a non linear fashion. For example, as illustrated in FIG. **129**, the non-linear protrusions **938** may extend in a zigzag fashion. In certain embodiments, as illustrated in FIGS. **130** and **131**, the non-linear protrusions **938** may extend in parallel rows. In certain embodiments, as illustrated in FIGS. **130**, and **131**, the non-linear protrusions **938** may extend in opposing directions.

Referring to FIGS. **132** through **137**, an end effector **500** comprises a first jaw member **502A** and a second jaw member **502B**. The first jaw member **502A** is movable relative to the second jaw member **502B** between an open position (FIGS. **132** and **136**) and a closed position (FIGS. **133**, **134**, and **137**) to clamp tissue between the first jaw member **502A** and the second jaw member **502B**. The first jaw member **502A** comprises angled tissue-contacting surfaces **504A** and **506A**. The second jaw member **502B** comprises angled tissue-contacting surfaces **504B** and **506B**. The first jaw member **502A** comprises a first positively-angled tissue-contacting surface **504A** and a first negatively-angled tissue-contacting surface **506A**. The second jaw member **502B** comprises a second positively-angled tissue-contacting surface **504B** and a second negatively-angled tissue-contacting surface **506B**.

As used herein, the terms “positively-angled” and “negatively-angled” refer to the direction in which a tissue-contacting surface is angled relative to the body of the jaw member comprising the tissue-contacting surface and a clamping plane of the jaw member. Referring to FIG. 138, a first jaw member 502A' and a second jaw member 502B' are shown in a closed position such as to clamp tissue between the opposed jaw members 502A' and 502B'. This closed position is analogous to the closed position shown in FIGS. 133, 134, 135, 137, and 142. The first jaw member 502A' comprises a first jaw body 503A', a first tissue gripping element 507A', and a first clamping plane 505A. The second jaw member 502B' comprises a second jaw body 503B', a second tissue gripping element 507B', and a second clamping plane 505B. Generally, the tissue gripping elements and the clamping planes of the jaw members of an end effector are in an opposed orientation when the jaw members are in a closed position such as to clamp tissue between opposed jaw members.

The first jaw member 502A' comprises a first positively-angled tissue-contacting surface 504A' forming an angle ( $\alpha$ ) relative to the first clamping plane 505A and away from the first jaw body 503A' at the periphery of the first tissue gripping element 507A' of the first jaw member 502A'. The first jaw member 502A' comprises a first negatively-angled tissue-contacting surface 506A' forming an angle ( $\alpha$ ) relative to the first clamping plane 505A and toward from the first jaw body 503A' at the periphery of the first tissue gripping element 507A' of the jaw member 502A'.

Accordingly, as used herein, the term “positively-angled” is used to specify tissue-contacting surfaces that angle away from a clamping plane and that angle away from the jaw body at the periphery of the tissue gripping element of the jaw member comprising the positively-angled tissue-contacting surface. Likewise, as used herein, the term “negatively-angled” is used to specify tissue-contacting surfaces that angle away from a clamping plane and that angle toward the jaw body at the periphery of the tissue gripping element of the jaw member comprising the negatively-angled tissue-contacting surface.

Thus, the second jaw member 502B' comprises a second positively-angled tissue-contacting surface 504B' forming an angle ( $\alpha$ ) relative to the second clamping plane 505B and away from the second jaw body 503B' at the periphery of the second tissue gripping element 507B' of the second jaw member 502B'. The second jaw member 502B' comprises a second negatively-angled tissue-contacting surface 506B' forming an angle ( $\alpha$ ) relative to the second clamping plane 505B and toward from the second jaw body 503B' at the periphery of the second tissue gripping element 507B' of the second jaw member 502B'.

Referring again to FIGS. 132-134, the first jaw member 502A comprises a first jaw body 503A and a first tissue gripping element 507A, and the second jaw member 502B comprises a second jaw body 503B and a second tissue gripping element 507B. The first positively-angled tissue-contacting surface 504A of the first jaw member 502A is angled away from the first jaw body 503A at the periphery of the first tissue gripping element 507A. The first negatively-angled tissue-contacting surface 506A of the first jaw member 502A is angled toward the first jaw body 503A at the periphery of the first tissue gripping element 507A. The second positively-angled tissue-contacting surface 504B of the second jaw member 502B is angled away from the second jaw body 503B at the periphery of the second tissue gripping element 507B. The second negatively-angled tissue-contacting surface

506B of the second jaw member 502B is angled toward the second jaw body 503B at the periphery of the second tissue gripping element 507B.

When the first jaw member 502A and the second jaw member 502B are in a closed position, such as to clamp tissue between the first and second jaw members, the first positively-angled tissue-contacting surface 504A opposes the second negatively-angled tissue-contacting surface 506B. When the first jaw member 502A and the second jaw member 502B are in a closed position, such as to clamp tissue between the first and second jaw members, the first negatively-angled tissue-contacting surface 506A opposes the second positively-angled tissue-contacting surface 504B.

As shown in FIGS. 132-133 and 136-137, the first positively-angled tissue-contacting surface 504A and the first negatively-angled tissue-contacting surface 506A are disposed along substantially the entire length of the first jaw member 502A. The second positively-angled tissue-contacting surface 504B and the second negatively-angled tissue-contacting surface 506B are disposed along substantially the entire length of the second jaw member 502B.

The end effector 500 comprises an “I-beam” member 508, which in some embodiments, may function as a closure member and/or a tissue-cutting member. The I-beam member 508 may operate in a manner similar to that described herein above with respect to the axially movable member 3016 described herein above. The I-beam member 508 may be sized and configured to fit at least partially within channels in the first jaw member 502A and the second jaw member 502B. The I-beam member 508 may operably translate along the channels in the first jaw member 502A and the second jaw member 502B, for example, between a first, proximally retracted position correlating with the jaw members 502A and 502B being at an open position, and a second, distally advanced position correlating with the jaw members 502A and 502B being at a closed position. In this manner, for example, the I-beam member 508 may be configured to operably translate within the channels in the first and second jaw members 502A and 502B to close the jaw members using a camming action and/or to advance a cutting member through the first and second tissue gripping elements 507A and 507B to transect tissue clamped between the first and second jaw members 502A and 502B.

The movement of the first jaw member 502A relative to the second jaw member 502B between an open position (FIGS. 132 and 136) and a closed position (FIGS. 133, 134, and 137) to clamp tissue between the first jaw member 502A and the second jaw member 502B may be actuated with a suitable closure actuation mechanism. Translation of the I-beam member between a retracted position and an advanced position may be actuated with a suitable translation actuation mechanism. Suitable closure actuation mechanisms and suitable translation actuation mechanisms are described, for example, in connection with FIGS. 64-82, 83-91 and 92-96.

Referring to FIGS. 139 and 140, an end effector 510 comprises a first jaw member 512A and a second jaw member 512B. The first jaw member 512A is movable relative to the second jaw member 512B between an open position (FIGS. 139 and 140) and a closed position (not shown) to clamp tissue between the first jaw member 512A and the second jaw member 512B. The first jaw member 512A comprises angled tissue-contacting surfaces 514A and 516A. The second jaw member 512B comprises angled tissue-contacting surfaces 514B and 516B. The first jaw member 512A comprises a first positively-angled tissue-contacting surface 514A and a first negatively-angled tissue-contacting surface 516A. The second jaw member 512B comprises a second positively-angled

tissue-contacting surface 514B and a second negatively-angled tissue-contacting surface 516B.

The first jaw member 512A comprises a first jaw body 513A and a first tissue gripping element 517A, and the second jaw member 512B comprises a second jaw body 513B and a second tissue gripping element 517B. The first positively-angled tissue-contacting surface 514A of the first jaw member 512A is angled away from a first jaw body 513A at the periphery of the first tissue gripping element 517A. The first negatively-angled tissue-contacting surface 516A of the first jaw member 512A is angled toward the first jaw body 513A at the periphery of the first tissue gripping element 517A. The second positively-angled tissue-contacting surface 514B of the second jaw member 512B is angled away from a second jaw body 513B at the periphery of the second tissue gripping element 517B. The second negatively-angled tissue-contacting surface 516B of the second jaw member 512B is angled toward the second jaw body 513B at the periphery of the second tissue gripping element 517B.

When the first jaw member 512A and the second jaw member 512B are in a closed position, such as to clamp tissue between the first and second jaw members, the first positively-angled tissue-contacting surface 514A opposes the second negatively-angled tissue-contacting surface 516B. When the first jaw member 512A and the second jaw member 512B are in a closed position, such as to clamp tissue between the first and second jaw members, the first negatively-angled tissue-contacting surface 516A opposes the second positively-angled tissue-contacting surface 514B.

The first positively-angled tissue-contacting surface 514A is disposed along a proximal portion of the length of the first jaw member 512A. The second positively-angled tissue-contacting surface 514B is disposed along a proximal portion of the length of the second jaw member 512B. The first negatively-angled tissue-contacting surface 516A is disposed along substantially the entire length of the first jaw member 512A. The second negatively-angled tissue-contacting surface 516B is disposed along substantially the entire length of the second jaw member 502B.

The end effector 510 comprises an "I-beam" member 518, which in some embodiments, may function as a closure member and/or a tissue-cutting member. The I-beam member 518 may be sized and configured to fit at least partially within channels in the first jaw member 512A and the second jaw member 512B. The I-beam member 518 may translate along the channels in the first jaw member 512A and the second jaw member 512B, for example, between a first, proximally retracted position correlating with the jaw members 512A and 512B being at an open position, and a second, distally advanced position correlating with the jaw members 512A and 512B being at a closed position. In this manner, for example, the I-beam member 518 may be configured to operably translate within the channels in the first and second jaw members 512A and 512B to close the jaw members using a camming action and/or to advance a cutting member through the first and second tissue gripping elements 517A and 517B to transect tissue clamped between the first and second jaw members 512A and 512B.

The movement of the first jaw member 512A relative to the second jaw member 512B between an open position (FIGS. 139 and 140) and a closed position (not shown) to clamp tissue between the first jaw member 512A and the second jaw member 512B may be actuated with a suitable closure actuation mechanism. Translation of the I-beam member between a retracted position and an advanced position may be actuated with a suitable translation actuation mechanism. Suitable closure actuation mechanisms and suitable translation actuation

mechanisms are described, for example, in connection with FIGS. 64-82, 83-91 and 92-96.

The first jaw member 512A and the second jaw member 512B comprise a first distal textured portion 519A and second distal textured portion 519B, respectively. The first distal textured portion 519A of the first jaw member 512A is disposed distal and directly adjacent to the proximal tissue gripping element 517A of the first jaw member 512A comprising the first positively-angled tissue-contacting surface 514A. The first positively-angled tissue-contacting surface 514A does not extend distally along the length of the first jaw member 512A into the first distal textured portion 519A. The second distal textured portion 519B of the second jaw member 512B is disposed distal and directly adjacent to the proximal tissue gripping element 517B of the second jaw member 512B comprising the second positively-angled tissue-contacting surface 514B. The second positively-angled tissue-contacting surface 514B does not extend distally along the length of the second jaw member 512B into the second distal textured portion 519B. The first and second distal textured portions 519A and 519B of the first and second jaw members 512A and 512B may be opposed and may allow the end effector 510 to grip, pass, and/or manipulate surgical implements such as needles for suturing tissue, in addition to gripping tissue, for example, during dissection operations. This gripping, passing, and/or manipulating functionality is described, for example, in connection with FIGS. 116-131 and 154-164.

The first jaw member 512A and the second jaw member 512B comprise a first gripping portion 521A and second gripping portion 521B, respectively. The first gripping portion 521A is disposed on an outwardly-facing surface of the first jaw member 512A, and the second gripping portion 521B is disposed on an outwardly-facing surface of the second jaw member 512B. The gripping portions 521A and 521B may function to aid in tissue dissection as described, for example, in connection with FIGS. 116-131 and 154-164.

FIG. 141 is a perspective view of an end effector 510' similar to the end effector 510 shown in FIGS. 139 and 140, but comprising electrodes 522 located in the second tissue gripping element 517B of the second jaw member 516B and located between the second positively-angled tissue-contacting surface 514B and the second negatively-angled tissue-contacting surface 516B. The electrodes 522 may be configured to deliver RF energy to tissue clamped between the first jaw member 512A and the second jaw member 512B when in a closed position to weld/fuse the tissue, which may be transected by translating the I-beam member 518 comprising a cutting member. Although FIG. 141 shows two electrodes 522, it is understood that an end-effector in accordance with the embodiments described in this specification may comprise at least one or more electrodes comprising any suitable shape and orientation, as described, for example, in this specification. The second jaw member 516B also comprises an offset electrode 524 at the distal tip 525 configured to deliver RF energy to tissue during dissection operations, for example. In some embodiments, the first distal textured portion 519A and second distal textured portion 519B may also be electrodes configured, for example, to deliver RF energy to tissue during dissection operations. This electrode functionality is described, for example, in connection with FIGS. 154-164.

Referring to FIG. 142, an end effector 530 comprises a first jaw member 532A and a second jaw member 532B shown in a closed position clamping tissue 545 between the jaw members. The first jaw member 532A comprises a first positively-angled tissue-contacting surface 534A and a first negatively-angled tissue-contacting surface 536A. The second jaw

member 532B comprises a second positively-angled tissue-contacting surface 534B and a second negatively-angled tissue-contacting surface 536B. The tissue 545 physically contacts the angled tissue-contacting surfaces 534A, 534B, 536A, and 536B. The physical contact between the tissue 545 and the angled tissue-contacting surfaces 534A, 534B, 536A, and 536B compresses the tissue 545 between the first jaw member 532A and the second jaw member 532B. As shown in FIG. 142, the clamping of the tissue between the first jaw member 532A and the second jaw member 532B compresses the tissue 545 between the mutually opposed tissue-contacting surfaces 536A and 534B, and also between the mutually opposed tissue-contacting surfaces 534A and 536B, which establishes a tortuous deformation in the compressed tissue 545. The tortuous deformation improves the clamping action of the end effector 530 on the tissue 545, which in turn, improves the welding/fusion of the tissue 545 and/or the transection of the tissue 545. The tissue 545 can be welded/fused, for example, by the application of RF energy through electrodes 542 located in the tissue gripping element of the second jaw member 532B and located between the second positively-angled tissue-contacting surface 534B and the second negatively-angled tissue-contacting surface 536B. The tissue 545 can be transected, for example, by translating the I-beam member 538, which translates the cutting member 541 through the clamped tissue 545.

In some embodiments, an end effector may comprise a first jaw member comprising a first positively-angled tissue-contacting surface and a first negatively-angled tissue-contacting surface, and a second jaw member comprising a second positively-angled tissue-contacting surface and a second negatively-angled tissue-contacting surface. The angled tissue-contacting surfaces may form angles (a) relative to a clamping plane as described, for example, in connection with FIG. 138. The magnitude of the angle (a) between a tissue contacting surface and a clamping plane may range from 5-degrees to 85-degrees or any sub-range subsumed therein such as, for example, from 10-degrees to 80-degrees, from 20-degrees to 70-degrees, from 30-degrees to 60-degrees, from 40-degrees to 50-degrees, from 25-degrees to 50-degrees, or from 30-degrees to 45-degrees.

In some embodiments, angled tissue-contacting surfaces may independently form angles relative to respective clamping planes. The angle formed by the angled tissue-contacting surfaces may be substantially the same or different in a given end effector. For example, two opposed angled tissue-contacting surfaces (e.g., a first positively-angled tissue-contacting surface and an opposed second negatively-angled tissue-contacting surface) may both form a common angle ( $\alpha_1$ ) relative to respective clamping planes, and two other opposed angled tissue-contacting surfaces (e.g., a first negatively-angled tissue-contacting surface and an opposed second positively-angled tissue-contacting surface) may both form a common angle ( $\alpha_2$ ) relative to respective clamping planes, wherein  $|\alpha_1| \neq |\alpha_2|$ .

In some embodiments, an angled tissue-contacting surface may extend a predetermined distance normal to a respective clamping plane coincident with a horizontal tissue contacting portion of a jaw member. For example, referring to FIG. 138, the first positively-angled tissue-contacting surface 504A' extends a distance normal to the first clamping plane 505A, and the second positively-angled tissue-contacting surface 504B' extends a distance normal to the second clamping plane 505B. Likewise, the first negatively-angled tissue-contacting surface 506A' extends a distance normal to the first clamping plane 505A, and the second negatively-angled tissue-contacting surface 506B' extends a distance normal to the second

clamping plane 505B. In some embodiments, an angled tissue-contacting surface may extend a distance between 0.025 inch to 0.25 inch normal to a respective clamping plane, or any sub-range subsumed therein such as, for example, 0.025 inch to 0.01 inch or 0.025 inch to 0.05 inch.

While the angled tissue-contacting surfaces shown in FIGS. 132 through 142 are illustrated as being planar surfaces, it is to be appreciated that in some embodiments, the angled tissue-contacting surfaces may be curved surfaces or a combination of planar surfaces and curved surfaces.

In some embodiments, end effectors comprising angled tissue-contacting surfaces may be configured to operably couple to robotic surgical systems such as, for example, the robotic surgical systems described in connection with, for example, FIGS. 1-45. In some embodiments, end effectors having angled tissue-contacting surfaces may be configured to operably couple to hand-held surgical devices such as, for example, the hand-held surgical devices described in connection with FIGS. 46-63.

The angled tissue-contacting surfaces described in connection with FIGS. 132 through 142 provide various advantages to end effectors configured to grip/clamp tissue, weld/fuse tissue, transect tissue, or any combination of these operations. For example, in some embodiments, as illustrated in FIGS. 132 through 142, the positively-angled tissue contacting surfaces are integral with the outer surfaces of the jaw members (i.e., formed from a single piece of material). As such, the positively-angled tissue contacting surfaces provide for a thicker jaw member structure in the thickness dimension (labeled dimension T in FIGS. 141 and 142). The thicker jaw member structure increases the strength and stiffness of the jaw members, which provides improved gripping/clamping load to tissue. In some embodiments, for example, a thicker jaw member structure provided by positively-angled tissue contacting surfaces may increase the moment of inertia of the jaw members by 20-30% relative to jaw members comprising co-planar tissue-contacting surfaces. An increased moment of inertia may provide an improved weld zone for fusing and cauterizing tissue clamped in an end effector comprising angled tissue-contacting surfaces by providing a more focused area for RF energy to enter and fuse tissue.

Any of the electrosurgical tools described herein may be energized utilizing current/energy paths extending from the generator or other signal source (such as generator 3002) through conductors, such as the supply 3012 and return 3014 conductors (see FIG. 6), through the shaft assembly to the electrode or electrodes. Within the shaft assembly, the current paths may be provided by wires that extend through the shaft assembly. Wires, however, must be configured to avoid kinking, twisting or other deformation at the various articulation and rotation joints of the tools, including the articulation joint 3500 described herein. In the illustrated embodiments, an electrosurgical tool may utilize components of the shaft assembly as current paths for energizing electrosurgical electrodes. This may eliminate the need for wires and simplify articulation and rotation of the surgical tool.

In the illustrated embodiments, a rotary connector assembly may be utilized to allow a rotary drive shaft or other internal component of the shaft assembly to provide an energized current path between a generator and the end effector and/or an electrode thereof. The rotary connector may be configured to maintain a connection between the energized current path and the end effector despite rotation of the shaft and/or end effector. In bi-polar configurations, a return path may be formed by conductive components of the shaft and end effector such as, for example, a skin of the shaft, the

I-beam member or other knife, portions of the various jaw members, etc., as described herein

FIGS. 143-146 illustrate one embodiment of a rotary connector assembly 1100 installed in an end effector 550 and shaft assembly 560 as described herein with respect to FIGS. 64-81. FIG. 143 is a cross-sectional view of one embodiment of the end effector 550 and shaft assembly 560 illustrating an example installation of the rotary electrode assembly 1100. FIG. 144 is an exploded view of one embodiment of the end effector 550 and shaft assembly 560 showing the rotary electrode assembly 1100 both installed on the rotary drive shaft 630 (indicated by reference numbers 1100', 1104', 1106') and exploded (indicated by reference numbers 1100, 1104, 1106). FIG. 145 is a cross-sectional view of one embodiment of the end effector 550 and shaft assembly 560 showing the rotary electrode assembly 1100 with a rotary drive head 632 in a proximal position. FIG. 146 is a cross-sectional view of one embodiment of the end effector 550 and shaft assembly 560 showing the rotary electrode assembly 1100 with the rotary drive head 632 in a distal position.

The rotary electrode assembly 1100 may be positioned within the end effector drive housing 608 and may comprise an outer contact 1102 and an inner contact 1103. The outer contact 1102 may be positioned around an inner wall 1108 of the end effector drive housing 608. In the illustrated embodiment, and in functionally similar embodiments, the outer contact 1102 may be in the shape of a cylinder or other figure of revolution. The outer contact 1102 may be in electrical communication with one or more electrodes 1112 in the end effector 550 via one or more leads, such as lead 1110. The lead 1110 may be in physical contact with the outer contact 1102 and may extend through the lower jaw member 602B to the electrode 1112 as shown. The lead 1110 may be fastened to the electrode 1112 in any suitable manner including, for example, with a solder or other similar joint. For example, multiple energized electrodes may be utilized with one lead 1110 directed to each electrode. In the illustrated embodiment, the lead 1110 may be insulated so as to avoid electrical communication with other portions of the end effector 550 and shaft assembly 560.

The inner contact 1103 may be physically coupled to the rotary drive shaft 630, for example, proximal from the hex coupling portion 634, as shown. The inner contact 1103 may be in electrical contact with the outer contact 1102. For example, the inner contact 1103 may be in physical contact with the outer contact 1102. In the illustrated embodiment and in functionally similar embodiments, the inner contact 1103 may maintain electrical contact with the outer contact 1102 as the rotary drive shaft 630 and/or the end effector 560 rotates. For example, the outer contact 1102 may be a figure of revolution such that the inner contact 1103 is in physical contact with the contact 1102 as the rotary drive shaft 630 rotates.

In the illustrated embodiment and in functionally similar embodiments, the inner contact 1103 may also be a figure of revolution. For example, as illustrated, the inner contact 1103 may comprise a ringed brush 1104 and a grooved conductor 1106. The grooved conductor 1106 may be positioned around the rotary drive shaft 630 proximal from the hex coupling portion 634. The grooved conductor 1106 may define a groove 1107 to receive the ringed brush 1104. The ringed brush 1104 may have a diameter larger than that of the groove 1107. In the illustrated embodiment and in functionally similar embodiments, the ringed brush 1104 may define a slot 1105. For example, the slot 1105 may allow the diameter of the ringed brush 1104 to expand and contract. For example, the diameter of the ringed brush 1104 may be expanded in

order to place it over the remainder of the grooved conductor 1106 and into the slot 1107. Also, when the inner contact 1103 is placed within the outer contact 1102, its diameter may be contracted. In this way, the tendency of the ringed brush 1104 to resume its original diameter may cause the ringed brush 1104 to exert an outward force on the outer contact 1102 tending to keep the ringed brush 1104 and outer contact 1102 in physical and electrical contact with one another.

The inner contact 1103 may be in electrical communication with a suitable shaft component, thus completing the current path from the electrode 1112 to a generator, such as the generator 3002 described herein above with respect to FIG. 6 and/or an internal generator. In the illustrated embodiment, the inner contact 1103, and particularly the grooved conductor 1106, is in physical and electrical contact with a coiled wire component 1114 wrapped around the rotary drive shaft 630. The coiled wire component 1114 may extend proximally through the shaft where it may be coupled directly or indirectly to the generator. As described herein, the coiled wire component 1114 may also act as a spring to provide rigidity to the rotary drive shaft 630 around an articulation joint, for example, as described herein with respect to FIGS. 31-31 and spring 3612. In some embodiments, the rotary drive shaft 630 may comprise an outer insulated sleeve. The inner contact 1103 may be in electrical contact with the outer insulated sleeve in addition to or instead of the coiled wire component 1114. An example insulated sleeve 1166 is described herein with respect to FIG. 151. Another example of a potential insulated sleeve is the constraining member 3660 described herein above with respect to FIG. 45.

In the illustrated embodiment, the a current return path from the electrode 1112 may be provided by various components of the end effector 550 and shaft assembly 560 including, for example, the jaw members 602A, 602B, the end effector drive housing 608 and other shaft members extending proximally. Accordingly, portions of the energized current path may be electrically isolated from other components of the end effector 550 and shaft assembly 560. For example, as described above, the lead 1110 between the outer contact 1102 and electrode 1112 may be surrounded by an electrical insulator 1111, as shown. Also, the outer contact 1102 and inner contact 1103 may be isolated from other components of the end effector 550 and shaft assembly 560. For example, an insulator 1118 may be positioned to electrically isolate the outer contact 1102 from the end effector drive housing 608. An insulator 1116 may be positioned to isolate the outer contact 1102 and inner contact 1103 from the rotary drive shaft 630. The insulator 1118 may be an additional component or, in some embodiments, may be provided as a TEFLON or other insulating coating. As illustrated in FIGS. 145-146, the insulator 1116 may extend proximally, also isolating the coiled wire component 1114 from both the rotary drive shaft 630 and from other components of the shaft assembly 560 such as, for example, the end effector drive housing 608.

In the embodiment illustrated in FIGS. 145-146, the outer contact 1102 may be extended proximally and distally such that electrical contact between the outer contact 1102 and inner contact 1103 is maintained with the rotary drive shaft 630 and rotary drive head 632 in different proximal and distal positions. For example, in FIG. 145, the rotary drive shaft 630 and rotary drive head 632 are pulled proximally such that the male hex coupling portion 636 of the drive shaft head 632 is received by hex shaft coupling portion 609 of the end effector drive housing 608. In this position, rotation of the rotary drive shaft 630 may cause rotation of the end effector drive housing 608 and end effector 550, as described herein. Additionally,



as illustrated in FIG. 145, the inner contact 1103 may be in physical and electrical contact with the outer contact 1102. In FIG. 146, the rotary drive shaft 630 and rotary drive head 632 are pushed distally such that the hex coupling portion 634 of the rotary drive head 632 receives the threaded rotary drive nut 606. In this position, rotation of the rotary drive shaft 630 may cause rotation of the threaded rotary drive nut 606 that, in turn, causes rotation of the threaded rotary drive member 604 and distal and/or proximal translation of the I-beam member 620. Additionally, as illustrated in FIG. 146, the inner contact 1103 may be in physical and electrical contact with the outer contact 1102.

FIGS. 147-148 are cross-sectional views of one embodiment of the end effector 550 and shaft assembly 560 where a longitudinal length of the outer contact 1102 is selected such that the rotary connector assembly 1100 alternately creates and breaks an electrical connection limited by the longitudinal position of the inner contact 1103. For example, in FIG. 147, the rotary drive shaft 630 and rotary drive head 632 are positioned proximally such that the male hex coupling portion 636 is received into the hex shaft coupling portion 609 of the distal shaft portion 608. As illustrated, the inner contact 1103 (and specifically the ring brush 1104) may contact not the contact 1102, but instead may contact the insulator 1118. In this way, there may not be a completed electrical connection between the electrode 1112 and the generator when the rotary drive shaft 630 and rotary drive head 632 are in the proximal position shown in FIG. 147. When the rotary drive shaft 630 and rotary drive head 632 are positioned distally to contact the threaded drive nut 606, as illustrated in FIG. 148, the inner contact 1103 may be in electrical (and physical) contact with the contact 1102, completing the current path between the electrode 1112 and generator. The configuration illustrated in FIGS. 147-148 may be useful in various different contexts. For example, it may be undesirable to energize the electrode 1112 when the jaw members 602A, 602B are open. In the illustrated embodiment, the jaw members 602A, 602B are closed by the rotary drive shaft 630 when the shaft 630 is positioned distally (FIG. 148) and not when the shaft 630 is positioned proximally (FIG. 147). Accordingly, in the configuration of FIGS. 147-148, the current path from the generator to the electrode 1112 is complete only when the rotary drive shaft 630 and rotary drive head 632 are positioned distally.

In some of the embodiments described herein, the end effector 550 may be removable from the end effector drive housing 608 and, for example, may be interchangeable with other end effectors (not shown). Examples of mechanisms for implementing interchangeable electrodes are provided herein with respect to FIGS. 106-115. In such implementations, the lead 1110 may comprise an end effector portion and a shaft portion connected by a connector assembly. FIGS. 149-150 illustrate one embodiment of the end effector 550 and shaft assembly 560 showing a configuration including the lead portions 1130, 1132 and connector assembly 1120. For example, as illustrated in FIGS. 149-150 and as described herein, a proximal portion 603 of the jaw member 602B may be received within the end effector drive housing 608. The proximal portion 603 of the jaw member 602B is illustrated within the end effector drive housing 608 in FIG. 149 and separated from the end effector drive housing 608 in FIG. 150. The connector assembly 1120 may comprise an end effector side-lead 1122 and a shaft-side lead 1124. The respective leads may be brought into physical and electrical contact with one another when the proximal portion 603 is received into the distal shaft portion 608, as illustrated in FIG. 149. In various embodiments, the connector assembly 1120

may be configured so as to maintain electrical isolation of the energized current path from other components of the end effector 550 and shaft 560. For example, insulation 1126, 1128 may electrically isolate the connector leads 1122, 1124. In the illustrated embodiment and in functionally similar embodiments, the insulation 1126, 1128 may take the form of plastic or other insulating shrink tubes positioned over all or part of the leads 1122, 1124. In some embodiments, the insulation 1126, 1128 may comprise a TEFLON or other insulating coating applied to portions of the leads 1122, 1124 and/or surrounding material.

FIG. 151 illustrates a cross-sectional view of an alternate embodiment of an end effector 1140 and shaft assembly 1142 showing another context in which a rotary connector assembly 1147 may be utilized. The end effector 1140 may comprise jaw members 1146A, 1146B that may operate similar to the jaw members 3008A, 3008B, 602A, 602B, etc., described herein above. For example, the jaw members 1146A, 1146B may be actuated by an I-beam member 1156 that, in the illustrated embodiment, may comprise a cutting edge 1148 for severing tissue between the jaw members 1146A, 1146B. The I-beam member 1156 may be driven distally and proximally by rotation of a threaded I-beam member shaft 1154. The I-beam member shaft 1154 may be rotated via a main drive shaft 1149. For example, the main drive shaft 1149 may be coupled to a gear 1150. The gear 1150 may be in mechanical communication with a gear 1152 coupled to the I-beam member shaft 1154 as illustrated.

The end effector 1140 may comprise an electrode 1158 that may operate in a manner similar to that of electrode 1112, etc., described herein above. An insulated lead 1160 may be electrically coupled to the electrode 1158 and may extend proximally to an outer contact 1162. The outer contact 1162 may be positioned on an inner wall of a shaft member 1141 in a manner similar to that in which the contact 1102 is coupled to the inner wall 1108 of the end effector drive housing 608. An inner contact 1164 (e.g., brush) may be positioned around the main drive shaft 1149 such that the brush 1164 is in electrical contact with the contact 1162. The brush 1164 may also be in electrical contact with a conductive sleeve 1166 positioned around the main drive shaft 1149. The sleeve 1166 may be electrically isolated from the main drive shaft 1149 and from the remainder of the shaft 1142, for example, by insulators 1168, 1170.

It will be appreciated that the rotary electrode assembly 1100 may be utilized with any of the end effector and/or shaft assembly embodiments described herein. For example, FIG. 152 illustrates a cross-sectional view of one embodiment of the end effector and shaft assembly of FIGS. 83-91 illustrating another example installation of a rotary electrode assembly 1100 including the outer contact 1102 and inner contact 1103 as described herein.

FIGS. 153-168 illustrate various embodiments of an electrosurgical end effector 700 comprising a proximal tissue treatment zone 706 and a distal tissue treatment zone 708. The proximal tissue treatment zone 706 utilizes various electrodes and cutting edges to treat tissue, for example, as described herein above with respect to end effector 3000 shown in FIGS. 6-10. Treatment provided by the proximal tissue treatment zone 706 may include, for example, clamping, grasping, transection, coagulation, welding, etc. The distal tissue treatment zone 708 may also comprise one or more electrodes 742 and may be utilized to apply treatment to tissue and, in some embodiments, to perform other surgical tasks such as grasping and manipulating suturing needles and/or other surgical implements.

FIG. 153 illustrates one embodiment of the end effector 700. The end effector 700 may be utilized with various surgical tools including those described herein. As illustrated, the end effector 700 comprises a first jaw member 720 and a second jaw member 710. The first jaw member 720 may be movable relative to the second jaw member 710 between open positions (shown in FIGS. 153-156) and closed positions (shown in FIGS. 166 and 165). For example, the jaw members 720, 710 may be pivotably coupled at a pivot point 702. The jaw members 710, 720 may be curved with respect to a longitudinal tool axis "LT," as illustrated. In some embodiments, the jaw members 710, 720 may be instead straight, as illustrated with respect to jaw members 3008A, 3008B shown in FIGS. 6-8. In use, the end effector 700 may be transitioned from an open position to a closed position to capture tissue between the jaw members 720, 710. The tissue captured between the jaw members 720, 710 may be clamped or grasped along portions of the jaw members 710, 720 for application of one or more tissue treatments such as transection, welding, dissection, and electrocauterization.

The proximal tissue treatment zone 706 of the end effector 700 may treat tissue in a manner similar to that described above with respect to the end effector 3000. Tissue between the jaw members 720, 710 in the proximal tissue treatment zone 706 may be secured in place, for example, by teeth 734a, 734b. See, e.g., FIGS. 154-159. In the proximal tissue treatment zone 706, the jaw members 720, 710 may each define respective longitudinal channels 812, 810. An I-beam member 820 (FIGS. 155 and 159) may traverse distally and proximally within the longitudinal channels 812, 810, for example, as described herein above with respect to the end effector 3000 and axially movable member 3016. In some embodiments, distal and proximal translation of the I-beam member 820 may also transition the jaw members 720, 710 between open and closed positions. For example, the I-beam member 820 may comprise flanges positioned to contact cam surfaces of the respective jaw members 720, 710, similar to the manner in which flanges 3016A, 3016B contact cam surfaces 3026A, 3026B in the embodiment described with respect to FIGS. 6-10. The I-beam member 820 may also define a distally directed cutting element 822 that may transect tissue between the jaw members 720, 710 as the I-beam member 820 advances distally. In some embodiments, the jaw members 720, 710 may comprise tissue-contacting surfaces 730a, 730b, 732a, 732b similar to the tissue-contacting surfaces 504A, 504B, 506A, 506B described herein above with respect to FIGS. 132-137.

The proximal tissue treatment zone 706 may additionally comprise various electrodes and/or current paths for providing electrosurgical (RF) and/or other energy to tissue. The second jaw member 710 may comprise a supply electrode 848 positioned around the channel 810. See e.g., FIGS. 153-155 and 157. The supply electrode 848 may be in electrical communication with a generator for providing RF energy, such as the generator 3002 described herein above. For example, the supply electrode 848 may be coupled to one or more supply connector leads 846. The supply connector leads 846 may extend distally through a shaft assembly to a tool interface 302 and/or handle 2500 and ultimately to a generator, such as the generator 3002 or an internal generator, as described herein. The supply electrode 848 may be electrically insulated from other elements of the end effector 700. For example, referring to FIG. 10, the supply electrode (indicated on either side of the channel 810 by 848a and 848b) may be positioned on an insulating layer 844 (again indicated on either side of the channel 810 by 844a, 844b). The insulating layer 844 may be made of any suitable insulating material,

such as ceramic, TEFLON, etc. In some embodiments, the insulating layer 844 may be applied as a coating to the jaw member 710. The supply electrode 848 may operate in conjunction with a return path to apply bipolar RF energy to tissue, such as tissue 762 shown in FIG. 159. Current provided via the supply electrode 848 may flow through the tissue 762 and return to the generator via the return path. The return path may comprise various electrically conducting components of the end effector 700. For example, in some embodiments, the return path may comprise bodies of the first and second jaws 720, 710, the I-beam member 820, the tissue-contacting surfaces 730a, 730b, 732a, 732b, etc.

In the illustrated embodiments, the supply electrode 848 is offset from the return path. For example, the supply electrode 848 is positioned such that when the jaw members 720, 710 are in the closed position illustrated in FIG. 159, the electrode 848 is not in electrical contact (e.g., physical contact) with conductive portions of the end effector 700 that may serve and a return path for RF current. For example, the first jaw member 720 may comprise an opposing member 878 (indicated in FIG. 159 as 878a and 878b on either side of the channel 812) positioned opposite the electrode 848 such that upon closure of the jaw members 720, 710, the electrode 848 is in direct contact with the opposing member 878 and not with any other portions of the end effector 700. The opposing member 878 may be electrically insulating. In this way, it may be possible to close the jaw members 720, 710 without shorting the supply electrode 848 to the return path. In some embodiments, the opposing member 878 may be selectively insulating. For example, the opposing member 878 may comprise a positive temperature coefficient (PTC) body, as described above, that is conductive below a temperature threshold (e.g., about 100° C.) and insulating at higher temperatures. In this way, the opposing member 878 may form part of the return path, but only until its temperature exceeds the temperature threshold. For example, if the supply electrode 848 were to be electrically shorted to an opposing member 878 comprising PTC or a similar material, the short would quickly drive the temperature of the opposing member 878 about the threshold, thus relieving the short.

The distal tissue treatment zone 708 may define distal grasping surfaces 790a, 790b positioned on jaw members 710, 720, respectively. The distal grasping surfaces 790a, 790b may be positioned distally from the proximally treatment zone 706. The distal grasping surfaces 790a, 790b may, in some embodiments, be configured to grasp and hold tissue. For example, the distal grasping surfaces 790a, 790b may comprise grip elements 741 for increasing friction between the grasping surfaces 790a, 790b and tissue and/or surgical implements, as described herein below. The grip elements 741 may comprise any suitable texture defined by the surfaces 790a, 790b, a friction enhancing coating applied to the surfaces 790a, 790b, etc.

In some embodiments, the distal tissue treatment zone 708 may also be configured to apply monopolar and/or bipolar electrosurgical (e.g., RF) energy. For example, the surface 790a may be and/or comprise a distal supply electrode 742. For example, the surface 790a itself may be made from a conductive material and therefore be the distal supply electrode 742. In some embodiments, as described herein, the conductive electrode 742 may comprise a conductive material coupled to an insulating layer 845. The insulating layer 845 may be a dielectric layer and/or a coating applied to the jaw member 710. The distal supply electrode 742 may be in electrical contact with a generator, such as the generator 3002 described herein above and/or an internal generator. In some embodiments, the distal supply electrode 742 may be in elec-

trical contact with the supply electrode **848** of the proximal tissue treatment zone **706**. In this way, the distal supply electrode **742** may be energized when the proximal supply electrode **848** is energized. In some embodiments, the distal supply electrode **742** may be energized independent of the proximal supply electrode **848**. For example, the distal supply electrode **742** may be coupled to the generator via a dedicated supply line (not shown).

A return path for electrical energy provided by the distal supply electrode **742** may also comprise any suitable conductive portion of the end effector including, for example, the jaw member **710**, the jaw member **720**, the I-beam member **820**, etc. In some embodiments, the distal grasping surface **790b** may also form a distal return electrode **748** that may be part of the return path from the distal supply electrode **742**. For example, the distal return electrode **748** may be in electrical contact with the jaw member **720** that may, in turn, be in electrical contact with a generator such as the generator **3000**. The distal return electrode **748** may be formed in any suitable manner. For example, the surface **790b** may be conductive, thus forming the electrode **748**. In some embodiments, a conductive material may be applied to the surface **790b**, where the conductive material makes up the electrode **748**.

In the illustrated embodiments, the distal supply electrode **742** is not offset. For example, the distal supply electrode **742** is aligned with the return electrode **748**. Accordingly, the end effector **700** may be configured such that the distal supply electrode **742** does not come into contact with the return electrode **748** when the jaw members **720**, **710** are in the closed position. For example, a gap **780** may exist between the distal supply electrode **742** and the distal return electrode **748** when the jaw members **720**, **710** are in a closed position. The gap **780** is visible in FIGS. **160**, **161**, **162**, **163**, **164** and **165**.

In various embodiments, the gap **780** may be generated as a result of the dimensions (e.g., thickness) of various components of the proximal tissue treatment zone **706**. For example, when the opposing member **878** and the proximal supply electrode **848** may extend towards the axis LT such that when the electrode **848** and member **878** are in physical contact with one another (e.g., when the jaw members **720**, **710** are in the closed position), the distal grasping surfaces **790a,b** are not in physical contact with one another. Any suitable combination of the opposing member **878**, the supply electrode **848** and the insulating layer **844** may be utilized to bring about this result.

Referring now to FIGS. **160**, **163** and **164**, the insulating layer **844** and the insulating layer **845** may be continuous (e.g., form a continuous insulating layer). Similarly, the proximal supply electrode **848** and distal supply electrode **742** may be continuous (form a continuous electrode). The opposing member **878** is also illustrated. As illustrated, the electrode **848** (e.g., the portion of the continuous electrode in the proximal zone **706**) is thicker than the electrode **742**. Accordingly, when the electrode **848** contacts the opposing member **878**, the thickness of the electrode **848** may prevent the distal grasping surfaces **790a,b** from contacting one another, thus forming the gap **780**. FIG. **161** illustrates an alternative embodiment of the end effector **700** where the electrode **742** and the electrode **848** are of the same thickness. The thickness of the opposing member **878**, however, is selected such that when the electrode **848** contacts the opposing member **878**, the distal grasping surfaces **790a,b** do not contact one another, forming the gap **780**. FIG. **162** illustrates another embodiment where the insulating layer **844** is thicker than the insulating layer **845**, thus preventing contact between the distal grasping surfaces **790a, b** and forming the gap **780**.

In some embodiments, the distal supply electrode **742** may extend distally to a portion of a distal edge **886** of the jaw member **710**. For example, FIG. **153** shows a distal electrode portion **744**. The distal electrode portion **744** may be utilized by a clinician to apply electrosurgical energy to tissue that is not necessarily between the jaw members **720**, **710**. In some embodiments, the distal electrode portion **744** may be utilized to provide bipolar and/or monopolar cauterization. In bi-polar embodiments, the distal electrode portion **744** may utilize a return path similar to the return paths described herein. In some embodiments, the respective jaw members may comprise external depressions and/or protrusions **800**, **802** similar to the protrusions described herein with respect to FIGS. **116-131**. The depressions and/or protrusions **800**, **802** may be conductive and may provide possible return paths for current passed via the distal electrode portion **744**. In some embodiments where the distal electrode portion **744** is present, the insulating layer **845** may extend distally under the distal electrode portion, as shown in FIG. **164**.

It will be appreciated that the length of the respective tissue treatment zones **706**, **708** may vary with different implementations. For example, FIG. **165** shows an embodiment where the distal tissue treatment zone **708** is relatively shorter than the zone **708** shown in the other figures. For example, in FIG. **165**, the distal tissue treatment zone **708** extends proximally by a lesser distance from the distal tip of the end effector **700** than the zones **708** illustrated elsewhere.

In some embodiments, the distal tissue treatment zone **708** may be utilized as a general surgical grasper. For example, the distal grasping surfaces **790a,b** may be utilized to grasp and manipulate tissue. Also, in some embodiments, the distal grasping surfaces **790a,b**, may be utilized to grasp and manipulate artificial surgical implements such as needles, clips, staples, etc. For example, FIGS. **160**, **161**, **162** and **163** show a surgical implement **896** secured between the distal grasping surfaces **790a, b**. In FIGS. **160**, **161** and **162** the surgical implement **896** has a round cross-section (e.g., a suturing needle). In FIG. **163**, the surgical implement **896** has a non-round cross-section (e.g., a trailing end of a suturing needle, a clip, etc.). When used as a grasper, the distal treatment zone **708** may or may not apply electrosurgical energy to objects between the tissue surfaces **790a,b**. For example, it may not be desirable to apply electrosurgical energy to a needle or other surgical implement.

It will be appreciated that, as described above, some components of the proximal tissue treatment zone **706** may be common and/or continuous with some components of the distal tissue treatment zone **708**. For example, FIG. **167** illustrates one embodiment of the jaw member **710** with the electrodes **878**, **742** removed to illustrate the insulating layers **845**, **844**. As illustrated, the insulating layers **845**, **844** define a common, continuous layer **899**. A distal portion of the continuous layer **899** may make up the insulating layer **845** while a proximal portion of the insulating layer **899** may make up the insulating layer **844**. The insulating layer **844**, as illustrated, defines a notch **897** corresponding to the channel **810**, as shown, such that the I-beam member **820** may traverse the channel **810** without contacting the continuous layer **899**. Also, as illustrated, the insulating layer **845** defines a distal portion **843** that extends over a part of the distal end **886** of the jaw member **710**. The distal portion **843**, for example, may be positioned under the distal electrode portion **744**.

FIG. **166** illustrates an embodiment of the jaw member **710**, as illustrated in FIG. **167**, with the electrodes **742**, **848** installed. As illustrated, the proximal supply electrode may comprise regions **850a**, **850b**, **850c** and the opposing member **878** may comprise corresponding regions **864a**, **864b**, **864c**.

Regions **850a** and **850b** are positioned on either side of the channel **810**. Region **850c** is positioned distal from a distal-most portion of the channel **810**. FIG. **168** illustrates an alternate embodiment where the third region **850c** is omitted. Accordingly, first and second regions **850a**, **850b** of the electrode **848** extend distally to the distal supply electrode **742**.

#### Non-Limiting Examples

In various embodiments, a surgical instrument can comprise an end effector and a shaft assembly coupled proximal to the end effector. The end effector comprises a first jaw member, a second jaw member, and a closure mechanism configured to move the first jaw member relative to the second jaw member between an open position and a closed position. The shaft assembly comprises an articulation joint configured to independently articulate the end effector in a vertical direction and a horizontal direction. The surgical instrument also comprises at least one active electrode disposed on at least one of the first jaw member and the second jaw member. The at least one active electrode is configured to deliver RF energy to tissue located between the first jaw member and the second jaw member when in the closed position.

In various embodiments, a surgical instrument can comprise an end effector and a shaft assembly coupled proximal to the end effector. The end effector comprises a first jaw member, a second jaw member, and a closure mechanism configured to move the first jaw member relative to the second jaw member between an open position and a closed position. The shaft assembly comprises a head rotation joint configured to independently rotate the end effector. The surgical instrument also comprises at least one active electrode disposed on at least one of the first jaw member and the second jaw member. The at least one active electrode is configured to deliver RF energy to tissue located between the first jaw member and the second jaw member when in the closed position.

A surgical tool can comprise an end effector, comprising a first jaw member, a second jaw member and a closure mechanism configured to move the first jaw member relative to the second jaw member between an open position and a closed position. The surgical tool further comprises a shaft assembly proximal to the surgical end effector, wherein the surgical end effector is configured to rotate relative to the shaft assembly, and a rotary drive shaft configured to transmit rotary motions. The rotary drive shaft is selectively movable axially between a first position and a second position relative to the shaft assembly, wherein the rotary drive shaft is configured to apply the rotary motions to the closure mechanism when in the first axial position, and wherein the rotary drive shaft is configured to apply the rotary motions to the end effector when in the second axial position. In addition, the closure mechanism of the surgical tool comprises an I-beam member configured to translate in an axial direction to cam the first jaw member toward to the second jaw member. The I-beam member is connected to a threaded rotary drive member coupled to a rotary drive nut, wherein the rotary drive shaft is configured to engage with the rotary drive nut to transmit rotary motions to the rotary drive nut. Rotary motions of the rotary drive nut actuate translation of the threaded rotary drive member and the I-beam in the axial direction. Furthermore, the first jaw member and the second jaw member comprise channels configured to slidably engage with the I-beam member, wherein rotary motions of the rotary drive nut actuate translation of the I-beam in the channels between a proximally retracted position and a distally advanced position.

A surgical tool can comprise an end effector, comprising a first jaw member, a second jaw member, and a first actuation mechanism configured to move the first jaw member relative to the second jaw member between an open position and a closed position. The surgical tool further comprises a shaft assembly proximal to the surgical end effector, and a rotary drive shaft configured to transmit rotary motions. The rotary drive shaft is selectively moveable between a first position and a second position relative to the shaft assembly, wherein the rotary drive shaft is configured to engage and selectively transmit the rotary motions to the first actuation mechanism when in the first position, and wherein the rotary drive shaft is configured to disengage from the actuation mechanism when in the second position. In addition, the first actuation mechanism comprises an I-beam member configured to translate in an axial direction to cam the first jaw member toward to the second jaw member, the I-beam member connected to a threaded rotary drive member coupled to a rotary drive nut, wherein the rotary drive shaft is configured to engage with the rotary drive nut to transmit rotary motions to the rotary drive nut, and wherein rotary motions of the rotary drive nut actuate translation of the threaded rotary drive member and the I-beam in the axial direction. Furthermore, the first jaw member and the second jaw member comprise channels configured to slidably engage with the I-beam member, and wherein rotary motions of the rotary drive nut actuate translation of the I-beam in the channels between a proximally retracted position and a distally advanced position.

A surgical tool can comprise an end effector comprising a first jaw member, and a second jaw member, wherein the first jaw member is movable relative to the second jaw member between an open position and a closed position. The surgical tool also comprises first and second actuation mechanisms, and a clutch member configured to selectively engage and transmit rotary motion to either the first or the second actuation mechanism. In addition, the first actuation mechanism comprises an I-beam member configured to translate in an axial direction to cam the first jaw member toward the second jaw member, the I-beam member connected to a threaded rotary drive member coupled to a rotary drive nut, wherein the clutch member is configured to engage with the rotary drive nut to transmit rotary motions to the rotary drive nut, and wherein rotary motions of the rotary drive nut actuates translation of the threaded rotary drive member and the I-beam in the axial direction. Furthermore, the first jaw member and the second jaw member comprise channels configured to slidably engage with the I-beam member, and wherein rotary motions of the rotary drive nut actuate translation of the I-beam in the channels between a proximally retracted position and a distally advanced position.

A surgical tool can comprise an interchangeable end effector, a handle assembly and a shaft assembly. The interchangeable end effector comprises a first jaw member including a first electrode and a second jaw member including a second electrode. The first jaw member is moveable relative to the second jaw member between a first position and a second position. The handle assembly is proximal to said surgical end effector. The shaft assembly extends between the handle assembly and the interchangeable end effector. The shaft assembly comprises a rotary drive shaft configured to transmit rotary motions. The rotary drive shaft is selectively axially moveable relative to the shaft assembly between a plurality of discrete positions. A coupling arrangement can releasably attach the interchangeable end effector to the shaft assembly.

A surgical tool can comprise an interchangeable end and a shaft assembly. The interchangeable end may comprise a first

jaw member including a first electrode, a second jaw member including a second electrode, a closure mechanism configured to move the first jaw member relative to the second jaw member between a first position and a second position, and an actuation driver configured to drive the closure mechanism. The shaft assembly extends proximal to the interchangeable end effector and comprises a rotary drive shaft configured to transmit rotary motions to the actuation driver. A coupling arrangement can releasably attach the interchangeable end effector to the shaft assembly.

A surgical tool can comprise, an interchangeable end effector and a shaft assembly. The end effector comprises a first jaw member including a first electrode, a second jaw member including a second electrode, a closure mechanism configured to move the first jaw member relative to the second jaw member between a first position and a second position, and an actuation driver configured to drive the closure mechanism. The shaft assembly extends proximal to the interchangeable end effector and comprises a rotary drive shaft configured to transmit rotary motions. The interchangeable end effector is releasably attached to the shaft assembly. The rotary drive shaft is selectively extendable axially to operably engage and transmit the rotary motions to the actuation driver.

A surgical end effector can comprise a first jaw member and a second jaw member. The first jaw member defines an exterior surface on a distal portion thereof. The second jaw member defines an exterior surface on a distal portion thereof. The first jaw member is moveable relative to the second jaw member between a first position and a second position. At least one of the exterior surfaces of the first and second jaw members includes a tissue gripping portion.

A surgical tool can comprise a surgical end effector, a handle assembly and a drive shaft. The surgical end effector comprises a first jaw member defining an exterior surface on a distal portion thereof and a second jaw member defining an exterior surface on a distal portion thereof. The first jaw member is moveable relative to the second jaw member between a first position and a second position. At least one of the exterior surfaces of the first and second jaw members includes a tissue gripping portion. The handle assembly is proximal to said surgical end effector. The drive shaft extends between said surgical end effector and said handle assembly and is configured to move the first jaw relative to the second jaw between the first position and the second position in response to actuation motions in the handle.

A surgical tool can comprise an actuation system, a surgical end effector and a shaft assembly. The actuation system is for selectively generating a plurality of control motions. The surgical end effector is operably coupled to said actuation system and comprises a first jaw member and a second jaw member. The first jaw member defines an exterior surface on a distal portion thereof. The second jaw member defines an exterior surface on a distal portion thereof. The first jaw member is movably supported relative to the second jaw member between an open position and a closed position in response to closure motions generated by said actuation system. At least one of the exterior surfaces of the first and second jaw members includes a tissue adhering portion. The shaft assembly is for transmitting said plurality of control motions to the surgical end effector.

An end effector can comprise a first jaw member and a second jaw member. The first jaw member is movable relative to the second jaw member between an open position and a closed position. The first jaw member comprises a first positively-angled tissue-contacting surface. The second jaw member comprises a second positively-angled tissue-contacting surface. At least one of the first jaw member and the

second jaw member comprises at least one active electrode disposed on the jaw member adjacent to the positively-angled tissue-contacting surface. The at least one active electrode is configured to deliver RF energy to tissue located between the first jaw member and the second jaw member when in the closed position.

An end effector can comprise a first jaw member and a second jaw member. The first jaw member is movable relative to the second jaw member between an open position and a closed position. The first jaw member comprises a first positively-angled tissue-contacting surface and a first negatively-angled tissue-contacting surface. The second jaw member comprises a second positively-angled tissue-contacting surface and a second negatively-angled tissue-contacting surface. The first positively-angled tissue-contacting surface opposes the second negatively-angled tissue-contacting surface when the first and second jaw members are in the closed position. The first negatively-angled tissue-contacting surface opposes the second positively-angled tissue-contacting surface when the first and second jaw members are in the closed position.

An end effector can comprise a first jaw member and a second jaw member. The first jaw member is movable relative to the second jaw member between an open position and a closed position. The first jaw member comprises a first proximal tissue-contacting portion, a first distal textured portion adjacent to the first proximal tissue-contacting portion, a first positively-angled tissue-contacting surface disposed along the first proximal tissue-contacting portion, and at least one first electrode located in the first proximal tissue-contacting portion adjacent to the first positively-angled tissue-contacting surface. The second jaw member comprises a second proximal tissue-contacting portion, a second distal textured portion adjacent to the second proximal tissue-contacting portion, a second positively-angled tissue-contacting surface disposed along the second proximal tissue-contacting portion, and at least one second electrode located in the second proximal tissue-contacting portion adjacent to the second positively-angled tissue-contacting surface. The at least one first electrode and the at least one second electrode are in a bipolar configuration to deliver RF energy to tissue located between the first jaw member and the second jaw member when in the closed position.

A surgical tool can comprise an end effector. The end effector can comprise first and second jaw members, a shaft assembly, a rotatable drive shaft, a first electrical contact and a second electrical contact. The first and second jaw members are pivotable relative to one another from an open position to a closed position. An electrode is positioned on the first jaw member. The shaft assembly extends proximally from the end effector, is at least partially hollow, and defines an inner wall. The rotatable drive shaft extends proximally within the shaft assembly. The first electrical contact is coupled to the inner wall of the shaft assembly and positioned around at least a portion of the drive shaft. The second electrical contact is coupled to and rotatable with the drive shaft. The second electrical contact is positioned to be electrically connected to the first electrical contact as the drive shaft rotates.

A surgical end effector for use with a surgical tool can comprise a first jaw member and a second jaw member. The second jaw member is pivotable relative to the first jaw member from a first open position to a closed position, where the first and second jaw members are substantially parallel in the closed position. The second jaw member comprises an offset proximal supply electrode and a distal supply electrode. The offset proximal supply electrode is positioned to contact an opposing member of the first jaw member when the first and

second jaw members are in the closed position. The distal supply electrode is positioned distal of the offset proximal electrode and is aligned with a conductive surface of the first jaw member when the first and second jaw members are in the closed position. When the first and second jaw members are in the closed position, the proximal supply electrode is in contact with the opposing member and the distal supply electrode is not in contact with the conductive surface of the first jaw member.

A surgical end effector for use with a surgical tool can comprise first and second jaw members pivotable from a first open position to a closed position. The first and second jaw members define a proximal tissue treatment region and distal tissue treatment region. The second jaw member comprises, in the proximal tissue treatment region, an offset proximal supply electrode positioned such that when the jaw members are in the closed position the proximal supply electrode is in physical contact with the first jaw member and is not in electrical contact with the first jaw member. The second jaw member further comprises, in the distal tissue treatment region, a distal supply electrode positioned such that when the jaw members are in the closed position, the distal supply electrode is aligned with a conductive surface of the first jaw member. When the jaw members are in the closed position, the jaw members define a physical gap between the distal supply electrode and the conductive surface of the first jaw member.

The devices disclosed herein can be designed to be disposed of after a single use, or they can be designed to be used multiple times. In either case, however, the device can be reconditioned for reuse after at least one use. Reconditioning can include any combination of the steps of disassembly of the device, followed by cleaning or replacement of particular pieces, and subsequent reassembly. In particular, the device can be disassembled, and any number of the particular pieces or parts of the device can be selectively replaced or removed in any combination. Upon cleaning and/or replacement of particular parts, the device can be reassembled for subsequent use either at a reconditioning facility, or by a surgical team immediately prior to a surgical procedure. Those skilled in the art will appreciate that reconditioning of a device can utilize a variety of techniques for disassembly, cleaning/replacement, and reassembly. Use of such techniques, and the resulting reconditioned device, are all within the scope of the present application.

Although the present invention has been described herein in connection with certain disclosed example embodiments, many modifications and variations to those example embodiments may be implemented. For example, different types of end effectors may be employed. Also, where materials are disclosed for certain components, other materials may be used. The foregoing description and following claims are intended to cover all such modification and variations.

Any patent, publication, or other disclosure material, in whole or in part, that is said to be incorporated by reference herein is incorporated herein only to the extent that the incorporated materials does not conflict with existing definitions, statements, or other disclosure material set forth in this disclosure. As such, and to the extent necessary, the disclosure as explicitly set forth herein supersedes any conflicting material incorporated herein by reference. Any material, or portion thereof, that is said to be incorporated by reference herein, but which conflicts with existing definitions, statements, or other disclosure material set forth herein will only be incorporated to the extent that no conflict arises between that incorporated material and the existing disclosure material.

What is claimed is:

1. A surgical instrument, comprising:  
an end effector, comprising:

a first jaw member;  
a second jaw member; and  
a closure mechanism configured to move the first jaw member relative to the second jaw member between an open position and a closed position and wherein said surgical instrument further comprises:

a shaft assembly extending distally from a housing and defining a longitudinal axis and comprising:

a head rotation joint coupled to the end effector to facilitate selective rotation of the end effector in an annular path around said longitudinal axis relative to said shaft assembly; and

an articulation joint located between said housing and to said head rotation joint and operably interfacing therewith, said articulation joint being configured to independently articulate the end effector in a vertical direction and a horizontal direction relative to said longitudinal axis and wherein said surgical instrument further comprises:

at least one active electrode disposed on at least one of the first jaw member and the second jaw member, wherein the at least one active electrode is configured to deliver RF energy to tissue located between the first jaw member and the second jaw member when in the closed position.

2. The surgical instrument of claim 1, further comprising at least one return electrode disposed on at least one of the first jaw member and the second jaw member, wherein the at least one active electrode and the at least one return electrode are in a bipolar configuration.

3. The surgical instrument of claim 2, wherein the at least one return electrode comprises components of the end effector and the shaft assembly.

4. The surgical instrument of claim 1, wherein the articulation joint comprises:

a ball member formed on the head rotation joint;  
an intermediate articulation tube segment comprising a socket for movably supporting the ball member therein; and

cable segments attached to the ball member to facilitate articulation of said end effector in said vertical and horizontal directions relative to said longitudinal axis.

5. The surgical instrument of claim 1, further comprising:  
a lumen in said shaft assembly; and

a rotary drive shaft configured to transmit rotary motions, the rotary drive shaft located in the lumen of the shaft assembly,

wherein the rotary drive shaft is selectively movable axially between a distal axial position and a proximal axial position relative to the shaft assembly,

wherein the rotary drive shaft is configured to apply the rotary motions to the closure mechanism when in the distal axial position, and

wherein the rotary drive shaft is configured to apply the rotary motions to the end effector when in the proximal axial position.

6. The surgical instrument of claim 5, wherein the closure mechanism comprises:

an I-beam member configured to translate in an axial direction to cam the first jaw member toward the second jaw member;

a threaded rotary drive member coupled to the I-beam member; and

89

a rotary drive nut operably interfacing with the threaded rotary drive member, wherein the rotary drive shaft is configured to engage with the rotary drive nut when the rotary drive shaft is in the distal axial position and to transmit rotary motions to the rotary drive nut, and wherein rotary motions of the rotary drive nut actuates translation of the threaded rotary drive member and the I-beam member in the axial direction.

7. The surgical instrument of claim 6, wherein the first jaw member comprises a first jaw channel and wherein the second jaw member comprises a second jaw channel, wherein the I-beam member is configured to slidably engage with the first and second jaw channels, and wherein rotary motions of the rotary drive nut actuate translation of the I-beam member in the first and second jaw channels between a proximally retracted position and a distally advanced position.

8. The surgical instrument of claim 5, further comprising a locking mechanism configured to mechanically prevent rotation of the end effector when the rotary drive shaft is in the distal axial position.

9. The surgical instrument of claim 5, further comprising: an end effector drive housing coupled to the end effector; an end effector connector tube coupled to the end effector drive housing through the head rotation joint; and

a locking mechanism configured to mechanically prevent rotation of the end effector drive housing relative to the end effector connector tube when the rotary drive shaft is in the distal axial position,

the locking mechanism comprising a spline lock connected to the rotary drive shaft, wherein the spline lock engages both the end effector drive housing and the end effector connector tube when the rotary drive shaft is in the distal axial position, and wherein the spline lock disengages from the end effector drive housing when the rotary drive shaft is in the proximal axial position.

10. A surgical instrument, comprising:

an end effector, comprising:

a first jaw member;

a second jaw member; and

a closure mechanism configured to move the first jaw member relative to the second jaw member between an open position and a closed position, and wherein said surgical instrument further comprises:

a shaft assembly coupled to the end effector and a housing, wherein the shaft assembly defines a longitudinal axis and comprises a head rotation joint configured to facilitate independent rotation of the end effector about the longitudinal axis in an annular path relative to said shaft assembly;

an articulation joint supported in the shaft assembly between said head rotation joint and said housing, wherein the articulation joint is configured to facilitate independent articulation of the end effector in a vertical direction and a horizontal direction without moving the first and second jaw members relative to each other; and at least one electrode disposed on at least one of the first jaw member and the second jaw member, wherein the at least one electrode is configured to deliver RF energy to tissue located between the first jaw member and the second jaw member when in the closed position.

11. The surgical instrument of claim 10, wherein the articulation joint comprises:

an end effector connector tube coupled to the end effector and comprising a ball member;

an intermediate articulation tube segment including a socket for rotatably supporting the ball member therein; and

90

cable segments attached to the ball member to facilitate articulation of said end effector in said vertical and horizontal directions relative to said longitudinal axis.

12. The surgical instrument of claim 10, wherein the at least one electrode is an at least one active electrode, wherein the surgical instrument further comprises at least one return electrode disposed on at least one of the first jaw member and the second jaw member, and wherein the at least one active electrode and the at least one return electrode are in a bipolar configuration.

13. The surgical instrument of claim 12, wherein the at least one return electrode comprises components of the end effector and the shaft assembly.

14. The surgical instrument of claim 10, further comprising:

a lumen in said shaft assembly; and

a rotary drive shaft configured to transmit rotary motions, the rotary drive shaft located in the lumen of the shaft assembly,

wherein the rotary drive shaft is selectively movable axially between a distal axial position and a proximal axial position relative to the shaft assembly,

wherein the rotary drive shaft is configured to apply the rotary motions to the closure mechanism when in the distal axial position, and

wherein the rotary drive shaft is configured to apply the rotary motions to the end effector when in the proximal axial position.

15. The surgical instrument of claim 14, wherein the closure mechanism comprises:

an I-beam member configured to translate in an axial direction to cam the first jaw member toward the second jaw member;

a threaded rotary drive member coupled to the I-beam member; and

a rotary drive nut operably interfacing with the threaded rotary drive member, wherein the rotary drive shaft is configured to engage with the rotary drive nut when the rotary drive shaft is in the distal axial position and to transmit rotary motions to the rotary drive nut, and wherein rotary motions of the rotary drive nut actuates translation of the threaded rotary drive member and the I-beam member in the axial direction.

16. The surgical instrument of claim 15, wherein the first jaw member comprises a first jaw channel and wherein the second jaw member comprises a second jaw channel, wherein the I-beam member is configured to slidably engage with the first and second jaw channels, and wherein rotary motions of the rotary drive nut actuates translation of the I-beam member in the first and second jaw channels between a proximally retracted position and a distally advanced position.

17. The surgical instrument of claim 14, further comprising a locking mechanism configured to mechanically prevent rotation of the end effector when the rotary drive shaft is in the distal axial position.

18. The surgical instrument of claim 14, further comprising:

an end effector drive housing coupled to the end effector; an end effector connector tube coupled to the end effector drive housing through the head rotation joint; and

a locking mechanism configured to mechanically prevent rotation of the end effector drive housing relative to the end effector connector tube when the rotary drive shaft is in the distal axial position,

91

the locking mechanism comprising a spline lock connected to the rotary drive shaft, wherein the spline lock engages both the end effector drive housing and the end effector connector tube when the rotary drive shaft is in the distal axial position, and wherein the spline lock disengages 5 from the end effector drive housing when the rotary drive shaft is in the proximal axial position.

\* \* \* \* \*

92