



US 20200367445A1

(19) **United States**

(12) **Patent Application Publication**
Millar

(10) **Pub. No.: US 2020/0367445 A1**

(43) **Pub. Date: Nov. 26, 2020**

(54) **SYSTEMS AND METHODS FOR CREATING A GROW CYCLE**

(52) **U.S. Cl.**

CPC *A01G 7/045* (2013.01); *A01G 9/26* (2013.01); *A01G 9/249* (2019.05); *H05B 45/20* (2020.01); *H05B 47/16* (2020.01); *Y02P 60/14* (2015.11); *H05B 47/155* (2020.01); *A01G 7/04* (2013.01); *H05B 41/44* (2013.01); *Y02B 20/40* (2013.01); *H05B 47/105* (2020.01)

(71) Applicant: **Grow Solutions Tech LLC**, Vineyard, UT (US)

(72) Inventor: **Gary Bret Millar**, Highland, UT (US)

(21) Appl. No.: **16/992,845**

(22) Filed: **Aug. 13, 2020**

(57) **ABSTRACT**

Related U.S. Application Data

(63) Continuation of application No. 16/020,462, filed on Jun. 27, 2018, now Pat. No. 10,779,477, which is a continuation of application No. 14/832,806, filed on Aug. 21, 2015, now Pat. No. 10,034,434.


(60) Provisional application No. 62/124,987, filed on Jan. 9, 2015.

Publication Classification

(51) **Int. Cl.**

A01G 7/04 (2006.01)
A01G 9/26 (2006.01)
A01G 9/24 (2006.01)
H05B 45/20 (2006.01)
H05B 47/16 (2006.01)
H05B 47/105 (2006.01)
H05B 47/155 (2006.01)
H05B 41/44 (2006.01)

Systems and methods for creating a grow cycle are described. One embodiment of a method includes receiving a plant type for providing grow lighting and receiving first data for creating a first grow cycle for a first predetermined period of plant growth, where the first grow cycle includes providing a first wavelength of photon-emitting lighting. In some embodiments, the method includes receiving second data for creating a second grow cycle for a second predetermined period of plant growth, where the second grow cycle includes providing a second wavelength of photon-emitting lighting, determining when the first predetermined period of plant growth begins, and in response to determining that the first predetermined period of plant growth has begun, implementing the first grow cycle. In some embodiments, the method includes determining when the second predetermined period of plant growth begins and, in response to determining that the second predetermined period of plant growth has begun, implementing the second grow cycle.






FIG. 1




FIG. 2




FIG. 4




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11

SYSTEMS AND METHODS FOR CREATING A GROW CYCLE

CROSS REFERENCE

[0001] This application is a continuation of U.S. application Ser. No. 16/020,462, filed Jun. 27, 2018, which is a continuation of U.S. application Ser. No. 14/832,806, filed Aug. 21, 2015, now patented, which claims the benefit of U.S. Provisional Application Ser. No. 61/124,987, filed Jan. 9, 2015, which are hereby incorporated by reference in their entireties.

TECHNICAL FIELD

[0002] Embodiments described herein generally relate to systems and methods for providing grow lighting and, more specifically, to providing low heat photon-emitting lighting that provides a plurality of wavelengths to increase plant growth.

BACKGROUND

[0003] Many plants have evolved to grow in certain conditions and, as such, many current grow lights are not capable of growing these types of plants indoors. As an example, certain plants may only grow in a certain region of the world. Because other regions of the world have different conditions, these plants are not easily transported for growing elsewhere. While some plants may successfully grow in pots with the right soil, other plants may require a particular type of lighting in order to grow.

SUMMARY

[0004] Systems and methods for creating a grow cycle are described. One embodiment of a method includes receiving a plant type for providing grow lighting and receiving first data for creating a first grow cycle for a first predetermined period of plant growth, where the first grow cycle includes providing a first wavelength of photon-emitting lighting. In some embodiments, the method includes receiving second data for creating a second grow cycle for a second predetermined period of plant growth, where the second grow cycle includes providing a second wavelength of photon-emitting lighting, determining when the first predetermined period of plant growth begins, and in response to determining that the first predetermined period of plant growth has begun, implementing the first grow cycle. In some embodiments, the method includes determining when the second predetermined period of plant growth begins and, in response to determining that the second predetermined period of plant growth has begun, implementing the second grow cycle.

[0005] In another embodiment, a system for creating a grow cycle includes a grow lighting assembly that includes a plurality of low heat lighting elements, where a first lighting element of the plurality of low heat lighting elements outputs a first wavelength of photon-emitting light, and where a second lighting element of the plurality of low heat lighting elements outputs a second wavelength of photon-emitting light. Embodiments of the system may also include a computing device that stores logic that, when executed by the computing device, causes the system to provide a user interface for creating a grow cycle, receive a plant type for the grow lighting assembly to provide grow lighting to a plant, and receive first data for creating a first

portion of the grow cycle for a first predetermined period of plant growth, where the first portion of the grow cycle includes providing a first wavelength of photon-emitting lighting. In some embodiments, the logic causes the system to receive second data for creating a second portion of the grow cycle for a second predetermined period of plant growth, where the second portion of the grow cycle includes providing a second wavelength of photon-emitting lighting and implement the grow cycle.

[0006] In yet another embodiment, a non-transitory computer-readable medium stores logic that, when executed by a computing device, causes the computing device to provide a user interface for creating a grow cycle, receive a plant type for a grow lighting assembly to provide grow lighting to a plant, and receive first data for creating a first portion of the grow cycle for a first predetermined period of plant growth, where the first portion of the grow cycle includes providing a first wavelength of photon-emitting lighting via a first plurality of low heat lighting elements. In some embodiments, the logic causes the computing device to receive second data for creating a second portion of the grow cycle for a second predetermined period of plant growth, where the second portion of the grow cycle includes providing a second wavelength of photon-emitting lighting via a second plurality of low heat lighting elements and determine when the first predetermined period of plant growth begins. In some embodiments, the logic causes the computing device to, in response to determining that the first predetermined period of plant growth has begun, implement the first portion of the grow cycle. Similarly, in some embodiments, the logic causes the computing device to determine when the second predetermined period of plant growth begins and, in response to determining that the second predetermined period of plant growth has begun, implement the second portion of the grow cycle.

[0007] These and additional features provided by the embodiments of the present disclosure will be more fully understood in view of the following detailed description, in conjunction with the drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

[0008] The embodiments set forth in the drawings are illustrative and exemplary in nature and not intended to limit the disclosure. The following detailed description of the illustrative embodiments can be understood when read in conjunction with the following drawings, where like structure is indicated with like reference numerals and in which:

[0009] FIG. 1 depicts a computing environment for providing grow lighting, according to embodiments described herein;

[0010] FIG. 2 depicts a grow lighting device, according to embodiments described herein;

[0011] FIG. 3 depicts a user interface for creating a new grow cycle, according to embodiments described herein;

[0012] FIG. 4 depicts a user interface for providing current grow cycles, according to embodiments described herein;

[0013] FIG. 5 depicts a user interface for providing a light tree, according to embodiments described herein;

[0014] FIG. 6 depicts a user interface for providing grow cycle details, according to embodiments described herein;

[0015] FIG. 7 depicts a user interface for providing performance reports, according to embodiments described herein;

[0016] FIG. 8 depicts a user interface for providing administrative settings, according to embodiments described herein;

[0017] FIG. 9 depicts a flowchart for providing grow lighting, according to embodiments described herein;

[0018] FIG. 10 depicts a flowchart for controlling grow lighting, according to embodiments described herein; and

[0019] FIG. 11 depicts a computing infrastructure for providing grow lighting, according to embodiments described herein.

DETAILED DESCRIPTION

[0020] Embodiments disclosed herein include systems and methods for providing grow lighting. Some embodiments may be configured with a lighting device that provides a plurality of different lighting wavelengths of grow lighting. The grow lighting is configured to emit photons that facilitate growth in various plants. Accordingly, embodiments described herein may be configured to determine a lighting cycle, where the lighting cycle includes a plurality of different lighting wavelengths (such as nanometer-scale wavelengths) emitted at different times. As an example, a first lighting element (such as a first LED) may provide a first wavelength of photon-emitting light, and a second lighting element (such as a second LED) may provide a second wavelength of photon-emitting light. In some embodiments, the first lighting element illuminates at a different time than the second lighting element. The lighting cycle may depend on the particular type of plants being grown and the developmental stage of the plant.

[0021] As an example, tomato plants may optimally grow with a first predetermined cycle, while basil may grow with a second predetermined cycle. The first predetermined cycle may include a first wavelength of light during the initial stages of development to optimize stem growth and a second wavelength of light at later stages of development to optimize fruit growth. Similarly, some plants may optimally grow with different light wavelengths at different times of day. Accordingly, embodiments described herein may provide a computing infrastructure for creating and utilizing these cycles for optimizing growth of different plants in a controlled environment. The systems and methods for providing grow lighting incorporating the same will be described in more detail, below.

[0022] Referring now to the drawings, FIG. 1 depicts a computing environment for providing grow lighting, according to embodiments described herein. As illustrated, the computing environment may include a network 100, a grow lighting assembly 102, a remote computing device 104, and a user computing device 106. The network 100 may include any wide area network, such as the internet, a mobile communication network, a public switch telephone network (PSTN), and the like. Similarly, the network 100 may include a local area network, which may include devices for communicating one or more various protocols, such as Ethernet, wireless fidelity (WiFi), Bluetooth™, near field communication, etc.

[0023] The grow lighting assembly 102 may include at least one hub device 108 and at least one grow lighting device 110. The hub may include a memory component 140, which stores cycle logic 144a and lighting logic 144b. As discussed in more detail below, the grow lighting device 110 may include a low heat lighting element (or a plurality of low heat lighting elements), which may be embodied as a

light emitting diode (LED), cold cathode fluorescent lamp (CCFL), and/or other low heat lighting device, so long as the low heat lighting element is configured for outputting photon-emitting light to facilitate plant growth. The grow lighting device 110 may include a plurality of different LEDs, each of which is specifically tuned to output a particular wavelength of photon-emitting light. In operation, the hub device 108 may receive a grow cycle, which may be deciphered via the cycle logic 144a. The lighting logic 144b may then facilitate commands of the grow lighting device 110 to provide the desired lighting output for the plants being grown, as described in more detail below.

[0024] Depending on the particular embodiment, the grow lighting assembly 102 may include one or more positioning devices for raising and/or lowering the grow lighting devices 110 relative to the plants being grown. Similarly, watering devices, fertilizing devices, light filtering devices, light sensing devices, and/or other devices for further facilitating growth of the plants may be included with the grow lighting assembly 102 and may be controlled by the hub device 108, the remote computing device 104 and/or the user computing device 106. Depending on the particular embodiment, one or more sensors (such as a camera, proximity sensor, laser, etc.) may be utilized to determine the height and/or development of the plant such that the positioning device may automatically adjust to provide the desired distance between the grow lighting device 110 and the plant. While the grow lighting assembly 102 may be configured for outdoor operation, oftentimes, indoor operation may be desired to fully control lighting and other environmental conditions for the plants.

[0025] Additionally, the remote computing device 104 and the user computing device 106 may be configured for providing at least one user interface to receive grow cycle cycles from a user, as well as for implementing the grow cycle for a particular grow lighting assembly 102. In one embodiment, the user computing device 106 may be utilized by a creating user for creating a grow cycle, which is received and stored by the remote computing device 104. The user computing device 106 (and/or another computing device) may then provide a command for implementing the grow cycle on the grow lighting assembly 102. The remote computing device 104 may then send the cycle to the hub device 108 for implementation. The hub device may receive the cycle and determine the illumination pattern for implementing the grow cycle. The illumination pattern may include timing for providing power to one or more of the low heat lighting elements to achieve the grow cycle.

[0026] It should be understood that the embodiment depicted in FIG. 1 is merely an example. In some embodiments, the hub device 108 may be part of the user computing device 106. Similarly, some embodiments may be configured such that the user computing device 106 communicates to the hub device 108 and the lighting assembly 102 without use of the remote computing device 104. Other communication configurations that provide the described functionality are also contemplated.

[0027] FIG. 2 depicts a grow lighting device 110, according to embodiments described herein. As illustrated, the grow lighting device 110 may include circuitry to illuminate a plurality of LEDs 210a, 210b, 210c, 210d, 210e, 210f. Depending on the particular embodiment, the grow lighting device may include a processor, which runs store commands based on information from the remote computing device 104, the user computing device 106, and/or the hub 108.

Accordingly, the grow lighting device may include software and/or other logic that utilizes wave-based technology for reducing heat and other undesirable bi-products of the lighting device. Also depending on the particular embodiment, the LEDs **210** may be the same color or at least a portion of the LEDs **210** may be different colors to provide different photon-emitting lighting wavelengths. As an example, the LEDs **210a**, **210b** may output a red wavelength of light. The LEDs **210c**, **210d** may output a blue wavelength. The LEDs **210e**, **210f** may output a yellow wavelength. Some embodiments may be configured with each of the LEDs **210** a different color, and/or with colors beyond the primary colors, such as warm white, cool white, orange, green, violet, black, etc.

[0028] It should be understood that each (or at least a portion) of the LEDs **210** may be independent in that they may be illuminated with or without other LEDs on the grow lighting device **110**. Additionally included is a communication interface **212**, which may take the form of a power cable, an Ethernet cable, and/or other interface for providing power to the grow lighting device **110**, as well as instructions on the lighting cycle for the grow lighting device **110**. In some embodiments, the grow lighting device **110** may be hardwired for illumination as instructed by the hub device **108**. Other embodiments of the grow lighting device **110** may be configured with hardware and/or software for receiving an instruction from the hub device **108** and controlling illumination of the LEDs.

[0029] It should also be understood that by using low heat lighting elements, such as LEDs **210**, the photon-emitting light may be produced with little to no heat. As a consequence, the grow lighting device **110** may be positioned at a place relative to a plant that maximizes optimal growth without the risk of burning the plant with heat from the grow lighting device **110**. Additionally, cooling of a grow room that includes grow lighting devices **110** may be unnecessary because of the minimal amount of heat produced by the grow lighting devices **110**. Additionally, while the grow lighting device **110** of FIG. 2 is depicted with six LEDs, this is also an example. Depending on the embodiment, the grow lighting device **110** may include as few as one low heat lighting element or as many as hundreds of low heat lighting elements to provide the desired illumination.

[0030] FIG. 3 depicts a user interface **330** for creating a new grow cycle, according to embodiments described herein. As illustrated, the user interface **330** may be configured for receiving a new grow cycle. The user interface **330** may include at least one user option, such as a grow cycles option **332**, a grow cycle details option **334**, a light tree option **336**, an input harvest data option **338**, a reports option **340**, a messages option **342**, and a settings option **344**. In response to selection of the grow cycles option **332**, a listing of grow cycles to which the user has access may be provided, as described in more detail in FIG. 4. In response to selection of the grow cycle details option **334**, additional details regarding one or more of the grow cycles may be provided, as described in more detail in FIG. 6. In response to selection of the light tree option **336**, a depiction of the lighting and plant configuration may be provided, as described in more detail in FIG. 5. In response to selection of the input harvest data option **338** data regarding the progress of the plants may be provided. In some embodi-

ments, the user may input this progress data, while other embodiments may receive sensor data to monitor this information.

[0031] In response to selection of the reports option **340** one or more reports may be provided, as described in more detail in FIG. 7. In response to selection of the messages option **342**, one or more messages may be provided. In response to selection of the settings option **344**, the user may be provided with settings for further configuring the grow lighting assembly **102** and/or other components described herein, as described in more detail in FIG. 8.

[0032] Also included are a view option **346** and a start new grow cycle option **348**. In response to selection of the view option **346**, the creating user may be provided with one or more different user interfaces for showing grow cycles that may be implemented for different plants, developmental stages, etc. In response to selection of the start new grow cycle option **348**, the creating user may be provided with additional options for creating a new grow cycle.

[0033] As an example, the additional options may include a name option to create a name for the new grow cycle. Other options may include an option to identify a number, type, and location of the grow lighting devices **110**. The creating user may additionally provide information regarding recommended types of plants, a number of plants, and a position of plants. Options for providing at least one lighting time (such as a first lighting time and a second lighting time) for at least one of the grow lighting devices **110** to illuminate, as well as providing cycle times for at least one of the grow lighting devices **110** to repeat a cycle of illumination of a grow cycle. The cycle time may be set for a predetermined number of minutes, hours, days, weeks, etc. such that the lighting times may change as the plant develops. Accordingly, embodiments may include options for the creating user to select that the lighting scheme changes when it is determined that a plant has reached a predetermined developmental stage. As such, each grow lighting device **110** may operate differently, based on the development of those plants. Some embodiments however operate such that at least a portion of the grow lighting devices **110** provide the same lighting for all plants of a common variety. Other options may also be provided for creating a grow cycle.

[0034] Once created, the grow cycle may be listed in the user interface **330** (and/or the user interface **430** from FIG. 4, described below). The grow cycle may include a name field, a location field, a start date field, a cycle field, an end date field, an input harvest field, a light task field, and a days until next task field. By selecting a previously created grow cycle, the user (either the creating user or other user) may view and/or amend the selected grow cycle.

[0035] FIG. 4 depicts a user interface **430** for providing current grow cycles, according to embodiments described herein. While the user interface **330** of FIG. 3 depicted options that are provided when no grow cycles have been created, the user interface **430** of FIG. 4 illustrates a plurality of grow cycles. Specifically, the user interface **430** includes an alerts section **432** and a cycles section **434**. The alerts section **432** may be configured to provide a notification (e.g., alert and/or message) related to a grow lighting assembly **102**, grow lighting device **110**, an action to take for a particular developmental stage of a plant, and/or a plant to which a cycle is being applied. Accordingly, alerts may include a malfunction alert, a pruning reminder, a harvest reminder, a progress alert, a fertilizer reminder, a water

reminder, and/or other alerts and messages. Selection of a details option **436** may provide additional details regarding the provided notifications.

[0036] The cycles section **434** may include a listing of cycles to which the user may be utilizing. These cycles may have been downloaded from a repository that was populated by a creating user who is an expert in the field of plant growth and/or may be created by any user via selection of a create new cycle option **438**. In response to selection of a details option **440**, details regarding a selected cycle may be provided.

[0037] FIG. 5 depicts a user interface **530** for providing a light tree, according to embodiments described herein. In response to selection of the light tree option **336** from FIG. 3, the user interface **530** may be provided. As illustrated, the user interface **530** provides a graphical depiction of plants and grow lighting devices **110** for a particular grow lighting assembly **102**. The embodiment of FIG. 5 depicts that basil and tomato are being grown and, in response to selection of one of the plants information regarding the lighting cycle and developmental progress of the plant may be provided. In response to selection of one of the racks, information regarding the grow lighting devices **110** may be provided.

[0038] FIG. 6 depicts a user interface **630** for providing grow cycle details, according to embodiments described herein. In response to selection of the grow cycle details option **334** from FIG. 3, the user interface **630** may be provided. As illustrated, the user interface **630** may include a details section **632**, which includes a plurality of tasks for a grow cycle. Specifically, the details section **632** may include a task field **634**, a light setting field **636**, a days field **638**, an on field **640**, an off field **642**, a warm white field **644**, a cool white field **646**, a grow blue field **648**, a grow red field **650**, a total mols field **652**, and a message alert field **654**. A save option **656** is also provided, as well as a create option **658**.

[0039] FIG. 7 depicts a user interface **730** for providing performance reports, according to embodiments described herein. In response to selection of the reports option **340** from FIG. 3, the user interface **730** may be provided. The user interface **730** may include a reports section **732** for providing performance reports, lighting reports, and/or other reports. The user interface **730** illustrates a tomato cycle performance reports with a yield statistic that shows the tomato yield for a plant that has been subject to a plurality of cycles.

[0040] FIG. 8 depicts a user interface **830** for providing administrative settings, according to embodiments described herein. In response to selection of the settings option **344** from FIG. 3, the user interface **830** may be provided. As illustrated, the user interface **830** may include an updates option **832**, an automation settings option **834**, an alerts settings option **836**, and a user preferences option **838**.

[0041] FIG. 9 depicts a flowchart for providing grow lighting, according to embodiments described herein. As illustrated in block **950**, a lighting cycle for a predetermined plant type may be received. In block **952**, a command for implementing the lighting cycle with a predetermined grow lighting assembly **102** may be received, where the grow lighting assembly **102** includes a grow lighting device **110** with a plurality of light emitting diodes (and/or other low heat lighting elements). In block **954**, an illumination pattern for implementing the lighting cycle for the grow lighting assembly **102** may be determined. In block **956** the illumina-

tion pattern (or plurality of different illumination patterns) may be sent to the grow lighting assembly **102** for implementation.

[0042] FIG. 10 depicts a flowchart for controlling grow lighting, according to embodiments described herein. As illustrated in block **1050**, a plant type for grow lighting may be received. In block **1052**, a first lighting cycle may be received for a first predetermined period of plant growth, where the first lighting cycle includes providing a first wavelength of lighting. In block **1054**, a second lighting cycle may be received for a second predetermined period of plant growth, where the second lighting cycle includes a second wavelength of lighting and is different than the first wavelength of lighting. In block **1056**, the first lighting cycle and the second lighting cycle are implemented.

[0043] FIG. 11 depicts a computing infrastructure for providing grow lighting, according to embodiments described herein. The hub device **108** includes a processor **1130**, input/output hardware **1132**, network interface hardware **1134**, a data storage component **1136** (which stores cycle data **1138a**, lighting data **1138b**, and/or other data), and the memory component **140**. The memory component **140** may be configured as volatile and/or nonvolatile memory and as such, may include random access memory (including SRAM, DRAM, and/or other types of RAM), flash memory, secure digital (SD) memory, registers, compact discs (CD), digital versatile discs (DVD), and/or other types of non-transitory computer-readable mediums. Depending on the particular embodiment, these non-transitory computer-readable mediums may reside within the hub device **108** and/or external to the hub device **108**.

[0044] The memory component **140** may store operating system logic **1142**, the cycle logic **144a** and the lighting logic **144b**. The cycle logic **144a** and the lighting logic **144b** may each include a plurality of different pieces of logic, each of which may be embodied as a computer program or module, firmware, and/or hardware, as an example. A local interface **1146** is also included in FIG. 11 and may be implemented as a bus or other communication interface to facilitate communication among the components of the hub device **108**.

[0045] The processor **1130** may include any processing component operable to receive and execute instructions (such as from a data storage component **1136** and/or the memory component **140**). As described above, the input/output hardware **1132** may include and/or be configured to interface with the components of FIG. 11.

[0046] The network interface hardware **1134** may include and/or be configured for communicating with any wired or wireless networking hardware, including an antenna, a modem, a LAN port, wireless fidelity (WiFi) card, WiMax card, mobile communications hardware, and/or other hardware for communicating with other networks and/or devices. From this connection, communication may be facilitated between the hub device **108** and other computing devices, such as those depicted in FIG. 1.

[0047] The operating system logic **1142** may include an operating system and/or other software for managing components of the hub device **108**. As discussed above, the cycle logic **144a** may reside in the memory component **140** and may be configured to cause the processor **1130** to determine one or more cycles that may be utilized for growing a predetermined plant. Similarly, the lighting logic **144b** may

be utilized to coordinate different grow lighting devices **110** for implementing the appropriate cycle.

[0048] It should be understood that while the components in FIG. **11** are illustrated as residing within the hub device **108**, this is merely an example. In some embodiments, one or more of the components may reside external to the hub device **108**. It should also be understood that, while the hub device **108** is illustrated as a single device, this is also merely an example. In some embodiments, the cycle logic **144a** and the lighting logic **144b** may reside on different computing devices. As another example, one or more of the functionalities and/or components described herein may be provided by the remote computing device **104**, the user computing device **106**, the lighting assembly **102**, and/or other computing devices, which may be coupled to the hub device **108** via the network **100**. These computing devices may also include hardware and/or software for performing the functionality described herein.

[0049] Additionally, while the hub device **108** is illustrated with the cycle logic **144a** and the lighting logic **144b** as separate logical components, this is also an example. In some embodiments, a single piece of logic may cause the hub to provide the described functionality.

[0050] As illustrated above, various embodiments for providing grow lighting are disclosed. As the grow lighting may be configured for programming of different wavelength light that provides different photons to the plants at different stages of development, plant growth may be optimized. Additionally, by utilizing LED or other low heat devices, the position of the grow lighting may be optimized based on the lighting needs of the plants.

[0051] While particular embodiments and aspects of the present disclosure have been illustrated and described herein, various other changes and modifications can be made without departing from the spirit and scope of the disclosure. Moreover, although various aspects have been described herein, such aspects need not be utilized in combination. Accordingly, it is therefore intended that the appended claims cover all such changes and modifications that are within the scope of the embodiments shown and described herein.

[0052] It should now be understood that embodiments disclosed herein includes systems, methods, and non-transitory computer-readable mediums for providing grow lighting. It should also be understood that these embodiments are merely exemplary and are not intended to limit the scope of this disclosure.

What is claimed is:

1. A system for creating a grow cycle to grow plants, comprising:

- a grow lighting assembly that comprises a plurality of low heat lighting elements; and
- a computing device that stores logic that, when executed by the computing device, causes the system to perform at least the following:

- provide a first user interface for creating a grow cycle, wherein the first user interface provides a user option for creating the grow cycle, wherein the first user interface is configured for a user, in response to a user selection of the user option, to design the grow cycle, wherein, creating the grow cycle includes receiving from the user: a number of low heat lighting elements that are actuated, a location of at least a portion of the plurality of low heat lighting

- elements that are actuated, a timing of actuation of at least a portion of the plurality of low heat lighting elements, a type of at least one plant received by the grow lighting assembly, a recommended type of plants for the grow cycle, and a position of the at least one plant received by the grow lighting assembly;

- provide a second user interface for providing a light tree, which includes a graphical depiction of the plants and at least a portion of the plurality of low heat lighting elements; and

- implement the grow cycle.

2. The system of claim **1**, wherein the grow lighting assembly comprises a sensor that includes at least one of the following: a camera, proximity sensor, or laser.

3. The system of claim **2**, wherein implementing the grow cycle includes implementing at least one of the following: a malfunction alert, a pruning reminder, a harvest reminder, a progress alert, a fertilizer reminder, or a water reminder, based on information received from the sensor.

4. The system of claim **1**, wherein the logic further causes the computing device to provide an input harvest data option.

5. The system of claim **1**, wherein the grow lighting assembly comprises a positioning device for adjusting a position of the plurality of low heat lighting elements according to the grow cycle.

6. The system of claim **1**, wherein implementing the grow cycle includes at least one of the following: receiving a number of plants that will be grown under the grow cycle, receiving a location of grow lighting devices that will be subject to the grow cycle, receiving a type of grow lighting device that will be subject to the grow cycle, or receiving a position of plants that will be subject to the grow cycle.

7. The system of claim **1**, wherein the logic further causes the system to provide a statistic associated with at least one of the following: at least a portion of the plants that are subjected to the grow cycle or the grow lighting assembly.

8. A non-transitory computer-readable medium for creating a grow cycle for a grow lighting assembly to grow plants that stores logic that, when executed by a computing device, causes the computing device to perform at least the following:

- provide a first user interface for creating a grow cycle, wherein the first user interface provides a user option for creating the grow cycle, wherein the first user interface is configured for a user, in response to a user selection of the user option, to design the grow cycle, wherein, creating the grow cycle includes receiving the following from the user: a number of low heat lighting elements of the grow lighting assembly that are actuated by the grow cycle, a location of at least one of the low heat lighting elements that are actuated by the grow cycle, a timing of actuation of the low heat lighting element, a type of the at least one plant received by the grow lighting assembly, a recommended type of plants for the grow cycle, or a position of the at least one plant received by the grow lighting assembly.

- provide a second user interface for providing a light tree, which includes a graphical depiction of the plants and the low heat lighting element; and

- implement the grow cycle.

9. The non-transitory computer-readable medium of claim 8, wherein the grow lighting assembly comprises a sensor that includes at least one of the following: a camera, proximity sensor, or laser.

10. The non-transitory computer-readable medium of claim 9, wherein implementing the grow cycle includes implementing at least one of the following: a malfunction alert, a pruning reminder, a harvest reminder, a progress alert, a fertilizer reminder, or a water reminder, based on data received from the sensor.

11. The non-transitory computer-readable medium of claim 8, wherein the grow lighting assembly comprises a positioning device for adjusting a position of the low heat lighting element according to the grow cycle.

12. The non-transitory computer-readable medium of claim 8, wherein implementing the grow cycle includes at least one of the following: receiving a number of plants that will be grown under the grow cycle, receiving a location of grow lighting devices that will be subject to the grow cycle, receiving a type of grow lighting device that will be subject to the grow cycle, or receiving a position of at least a portion of the plants that are subject to the grow cycle.

13. The non-transitory computer-readable medium of claim 8, wherein the logic further causes the computing device to provide a statistic associated with at least one of the following: at least a portion of the plants that are subjected to the grow cycle or the grow lighting assembly.

14. A grow lighting assembly for creating a grow cycle to grow plants, comprising:

- a plurality of low heat lighting elements; and
- a computing device that stores logic that, when executed by the computing device, causes the grow lighting assembly to perform at least the following:
 - provide a first user interface for creating a grow cycle, wherein the first user interface provides a user option for creating the grow cycle, wherein the first user interface is configured for a user, in response to a user selection of the user option, to design the grow cycle, wherein, creating the grow cycle includes receiving from the user: a number of low heat lighting elements of the grow lighting assembly that

are actuated, a location of at least one of the plurality of low heat lighting elements that are actuated, a timing of actuation of at least one of the plurality of low heat lighting elements, a type of the at least one plant received by the grow lighting assembly, a recommended type of plants for the grow cycle, and a position of the at least one plant received by the grow lighting assembly;

provide a second user interface for providing a light tree, which includes a graphical depiction of the plants and at least a portion of the plurality of low heat lighting elements; and

implement the grow cycle.

15. The grow lighting assembly of claim 14, further comprising at least one of the following: a camera, proximity sensor, or laser.

16. The grow lighting assembly of claim 15, wherein implementing the grow cycle includes implementing at least one of the following: a malfunction alert, a pruning reminder, a harvest reminder, a progress alert, a fertilizer reminder, or a water reminder.

17. The grow lighting assembly of claim 14, wherein the logic further causes the computing device to provide an input harvest data option.

18. The grow lighting assembly of claim 14, wherein the grow lighting assembly comprises a positioning device for adjusting a position of the plurality of low heat lighting elements according to the grow cycle.

19. The grow lighting assembly of claim 14, further comprising a positioning device for adjusting a position of the plurality of low heat lighting elements according to the grow cycle.

20. The grow lighting assembly of claim 14, wherein implementing the grow cycle includes at least one of the following: receiving a number of plants that will be grown under the grow cycle, receiving a location of grow lighting devices that will be subject to the grow cycle, receiving a type of grow lighting device that will be subject to the grow cycle, or receiving a position of at least a portion of the plants that are subjected to the grow cycle.

* * * * *