



(19) **United States**

(12) **Patent Application Publication**
OKUMURA

(10) **Pub. No.: US 2018/0029617 A1**

(43) **Pub. Date: Feb. 1, 2018**

(54) **AXLE BOX SUSPENSION OF RAILCAR BOGIE**

Publication Classification

(71) Applicant: **KAWASAKI JUKOGYO KABUSHIKI KAISHA**, Kobe-shi, Hyogo (JP)

(51) **Int. Cl.**
B61F 5/26 (2006.01)
(52) **U.S. Cl.**
CPC **B61F 5/26** (2013.01)

(72) Inventor: **Yasufumi OKUMURA**, Kobe-shi (JP)

(57) **ABSTRACT**

(73) Assignee: **KAWASAKI JUKOGYO KABUSHIKI KAISHA**, Kobe-shi, Hyogo (JP)

An axle box suspension of a railcar bogie is configured to couple an axle box, accommodating a bearing supporting an axle, to a bogie frame and includes: an axle beam including an axle beam main body portion and an axle beam end portion, the axle beam main body portion extending from the axle box in a car longitudinal direction, the axle beam end portion being provided at a tip end of the axle beam main body portion and including a tubular portion that is open at both car width direction sides; a core rod inserted into an internal space of the tubular portion in a car width direction; an elastic bushing interposed between the tubular portion and the core rod; and a receiving seat provided at the bogie frame, both end portions of the core rod being connected to the receiving seat, the tubular portion being divided into a first semi-tubular portion and a second semi-tubular portion, the first semi-tubular portion being formed integrally with the axle beam main body portion, the second semi-tubular portion being stacked on the first semi-tubular portion in an upward/downward direction.

(21) Appl. No.: **15/548,360**

(22) PCT Filed: **Jan. 25, 2016**


(86) PCT No.: **PCT/JP2016/000342**

§ 371 (c)(1),

(2) Date: **Aug. 2, 2017**

(30) **Foreign Application Priority Data**

Feb. 2, 2015 (JP) 2015-018102






Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6

AXLE BOX SUSPENSION OF RAILCAR BOGIE

Solution to Problem

TECHNICAL FIELD

[0001] The present invention relates to an axle box suspension of a railcar bogie, and particularly to a coupling mechanism coupling an axle beam and a bogie frame.

BACKGROUND ART

[0002] In a bogie of a railcar, an axle box accommodating a bearing supporting a wheelset is elastically supported by an axle box suspension with appropriate rigidity so as to be displaceable relative to a bogie frame in forward, rearward, leftward, and rightward directions. There exist various types of axle box suspensions. According to an axle beam type axle box suspension, an axle spring constituted by a coil spring is provided between an axle box and a bogie frame, and an axle beam extending from the axle box in a car longitudinal direction is elastically supported by a receiving seat of the bogie frame (see PTL 1, for example).

[0003] The axle beam includes: an axle beam main body portion extending from the axle box in the car longitudinal direction; and an axle beam end portion provided at a tip end of the axle beam main body portion and including a tubular portion that is open at both car width direction sides. A core rod is inserted into the tubular portion through a rubber bushing and is fixed to the receiving seat of the bogie frame. To insert the rubber bushing and the core rod into the tubular portion, the tubular portion is divided in the car longitudinal direction along a parting line extending in an upward/downward direction. Specifically, the tubular portion is divided into a first semi-tubular portion formed integrally with the axle beam main body portion and a second semi-tubular portion stacked on the first semi-tubular portion in the car longitudinal direction. A bolt is inserted into the first semi-tubular portion and the second semi-tubular portion in the car longitudinal direction.

CITATION LIST

Patent Literature

[0004] PTL 1: Japanese Laid-Open Patent Application Publication No. 10-278791

SUMMARY OF INVENTION

Technical Problem

[0005] However, according to a bogie including a tread brake, when a brake shoe is pressed against a wheel tread of a wheel in the car longitudinal direction at the time of braking, brake force applied to the wheel in the car longitudinal direction is transmitted to the axle beam through an axle and the axle box, and force acts in such a direction that the first semi-tubular portion and the second semi-tubular portion are separated from each other in the car longitudinal direction. Therefore, the brake force is applied to the bolt as pulling force acting in a direction (car longitudinal direction) along an axis of the bolt. On this account, strength design such as usage of a high-strength bolt needs to be considered.

[0006] An object of the present invention is to provide a configuration in a mechanism coupling an axle box to a bogie frame through an axle beam, the configuration being advantageous in terms of strength.

[0007] An axle box suspension of a railcar bogie according to one aspect of the present invention is an axle box suspension of a railcar bogie, the axle box suspension being configured to couple an axle box to a bogie frame, the axle box accommodating a bearing supporting an axle, the axle box suspension including: an axle beam including an axle beam main body portion and an axle beam end portion, the axle beam main body portion extending from the axle box in a car longitudinal direction, the axle beam end portion being provided at a tip end of the axle beam main body portion and including a tubular portion that is open at both car width direction sides; a core rod inserted into an internal space of the tubular portion in a car width direction; an elastic bushing interposed between the tubular portion and the core rod; and a receiving seat provided at the bogie frame, both end portions of the core rod being connected to the receiving seat, the tubular portion being divided into a first semi-tubular portion and a second semi-tubular portion, the first semi-tubular portion being formed integrally with the axle beam main body portion, the second semi-tubular portion being stacked on the first semi-tubular portion in an upward/downward direction.

[0008] According to the above configuration, the tubular portion of the axle beam is divided into the first semi-tubular portion formed integrally with the axle beam main body portion and the second semi-tubular portion stacked on the first semi-tubular portion in the upward/downward direction. Therefore, when viewed from a center of the core rod, the first semi-tubular portion extends to an opposite side of the axle beam main body portion. Therefore, the first semi-tubular portion can receive loads transmitted through the axle box to the axle beam in both directions along the car longitudinal direction. On this account, it is possible to prevent a case where the load transmitted through the axle box to the axle beam in the car longitudinal direction acts in such a direction that the second semi-tubular portion is separated from the first semi-tubular portion. Thus, a requirement of attaching strength of the second semi-tubular portion attached to the first semi-tubular portion can be eased.

Advantageous Effects of Invention

[0009] The present invention can provide a configuration in a mechanism coupling an axle box to a bogie frame through an axle beam, the configuration being advantageous in terms of strength.

BRIEF DESCRIPTION OF DRAWINGS

[0010] FIG. 1 is a perspective view of a railcar bogie according to an embodiment.

[0011] FIG. 2 is a side view of the bogie shown in FIG. 1.

[0012] FIG. 3 is an enlarged view of major components of the bogie shown in FIG. 2.

[0013] FIG. 4 is an exploded view of a tubular portion of an axle beam shown in FIG. 3.

[0014] FIG. 5 is a bottom view of the tubular portion of the axle beam shown in FIG. 3.

[0015] FIG. 6 is a sectional view taken along line VI-VI of FIG. 3.

Description of Embodiments

[0016] Hereinafter, an embodiment will be explained in reference to the drawings. In the following explanations, a direction in which a bogie travels and in which a carbody of a railcar extends is defined as a car longitudinal direction, and a crosswise direction perpendicular to the car longitudinal direction is defined as a car width direction. The car longitudinal direction is also referred to as a forward/rearward direction, and the car width direction is also referred to as a leftward/rightward direction.

[0017] FIG. 1 is a perspective view of a railcar bogie 1 according to the embodiment. FIG. 2 is a side view of the bogie 1 shown in FIG. 1. As shown in FIGS. 1 and 2, the bogie 1 includes a bogie frame 3 supporting a carbody 50 through air springs 2 that are secondary suspensions. The bogie frame 3 includes a cross beam 4 located at a longitudinal direction middle of the bogie 1 and extending in the car width direction. However, unlike the configuration of a conventional bogie frame, the bogie frame 3 does not include side sills extending from both respective car width direction end portions 4a of the cross beam 4 in the car longitudinal direction. Axles 5 extending in the car width direction are arranged at both respective car longitudinal direction sides of the cross beam 4, and wheels 6 are fixed to both respective car width direction sides of each of the axles 5. Bearings 7 rotatably supporting the axles 5 are provided at both respective car width direction side end portions of each of the axles 5 so as to be located outside the wheels 6 in the car width direction. The bearings 7 are accommodated in respective axle boxes 8.

[0018] Each of the axle boxes 8 is coupled to the corresponding car width direction end portion 4a of the cross beam 4 by a corresponding axle box suspension 10. The axle box suspension 10 includes an axle beam 11 extending from the axle box 8 toward the cross beam 4 in the car longitudinal direction. To be specific, the bogie 1 is a so-called axle beam type bogie. A tubular portion 29 that is open at both car width direction sides is provided at a tip end portion of the axle beam 11. A core rod 14 is inserted into an internal space of the tubular portion 29 through a rubber bushing 13 (see FIG. 6) as an elastic bushing. A pair of receiving seats 15 and 16 constituting the axle box suspension 10 is provided at the car width direction end portion 4a of the cross beam 4 so as to project outward in the car longitudinal direction. The receiving seats 15 and 16 are provided with groove portions 17 and 18, respectively, and the groove portions 17 and 18 are open downward. Both car width direction end portions of the core rod 14 are fitted to the respective groove portions 17 and 18 from below. In this state, lid members 19 are fixed to the respective receiving seats 15 and 16 from below by bolts (not shown) so as to close lower openings of the groove portions 17 and 18. Thus, the core rod 14 is sandwiched by the receiving seats 15 and 16 and the lid members 19. As above, the core rod 14 is connected to the receiving seats 15 and 16.

[0019] Brake devices 20 configured to brake the wheels 6 are provided at the cross beam 4. Each of the brake devices 20 includes a brake shoe 20a opposing a wheel tread of the wheel 6 from an inner side (the cross beam 4 side) in the car longitudinal direction. The brake device 20 is a tread brake configured to drive the brake shoe 20a by an electric, pneumatic, or hydraulic actuator (not shown) such that the brake shoe 20a is brought into contact with or separated from the wheel tread of the wheel 6. To be specific, the brake

device 20 brakes the wheel 6 in such a manner as to press the brake shoe 20a against the wheel tread of the wheel 6 outward (toward an opposite side of the cross beam 4 side) in the carbody longitudinal direction. Therefore, at the time of braking, a load (brake force) acts on the wheel 6 outward in the car longitudinal direction.

[0020] Each of plate springs 22 extending in the car longitudinal direction is provided between the cross beam 4 and the axle box 8. Longitudinal direction middle portions 22a of the plate springs 22 support both respective car width direction end portions 4a of the cross beam 4 from below. Both longitudinal direction end portions 22b of each of the plate springs 22 are supported by the respective axle boxes 8. To be specific, the plate spring 22 achieves both a function of a primary suspension and a function of a conventional side sill. The longitudinal direction middle portions 22a of the plate springs 22 are arranged so as to extend under the cross beam 4. Pressing members 23 each having a circular-arc lower surface are provided at respective lower portions of the car width direction end portions 4a of the cross beam 4. Each of the pressing members 23 is placed on the longitudinal direction middle portion 22a of the plate spring 22 from above and presses the plate spring 22 from above so as to be separable from the plate spring 22. To be specific, the pressing member 23 presses the middle portion 22a of the plate spring 22 by a downward load, applied from the cross beam 4 by gravity, so as not to fix the plate spring 22 in an upward/downward direction. It should be noted that the pressing member 23 may include a rubber sheet opposing the plate spring 22.

[0021] A supporting member 24 supporting the end portion 22b of the plate spring 22 from below is provided on the axle box 8. To be specific, the car longitudinal direction end portion 22b of the plate spring 22 contacts an upper surface of the supporting member 24 so as to be separable from the upper surface. Specifically, as described below, the supporting member 24 is formed by stacking an upper surface inclined member 25, a rubber stack body 26, and a receiving member 27 in the upward/downward direction. In a side view from the car width direction, the upper surface of the supporting member 24 is inclined obliquely downward toward the cross beam 4. To be specific, the upper surface of the supporting member 24 is inclined such that a car longitudinal direction inner side (the cross beam 4 side) thereof is located lower than a car longitudinal direction outer side thereof. A part of an intermediate portion 22c between the middle portion 22a and the end portion 22b in the plate spring 22 extends through a space sandwiched between the receiving seats 15 and 16 to reach a position under the cross beam 4. In a side view, the end portion 22b and intermediate portion 22c of the plate spring 22 are inclined downward toward the middle portion 22a, and the middle portion 22a of the plate spring 22 is located lower than the end portion 22b of the plate spring 22. To be specific, in a side view, the plate spring 22 is formed in a bow shape that is convex downward as a whole.

[0022] FIG. 3 is an enlarged view of major components of the bogie 1 shown in FIG. 2. FIG. 4 is an exploded view of the tubular portion 29 of the axle beam 11 shown in FIG. 3. FIG. 5 is a bottom view of the tubular portion 29 of the axle beam 11 shown in FIG. 3. To improve visibility in FIG. 3, the rubber bushing 13, the core rod 14, the receiving seats 15 and 16, and the lid members 19 are omitted. As shown in FIG. 3, the supporting member 24 is formed by stacking the

upper surface inclined member 25, the rubber stack body 26, and the receiving member 27 in this order from a lower side. An upper surface of the upper surface inclined member 25 is inclined such that a car longitudinal direction inner side thereof is located lower than a car longitudinal direction outer side thereof in a state where the upper surface inclined member 25 is provided on an upper surface 8a of the axle box 8. The rubber stack body 26 is attached to the upper surface of the upper surface inclined member 25, and the receiving member 27 is attached to an upper surface of the rubber stack body 26. The upper surface inclined member 25, the rubber stack body 26, and the receiving member 27 have such a structure (fitting structure, for example) as to be mutually positioned such that these components 25, 26, and 27 are not displaced relative to one another in a horizontal direction.

[0023] The receiving member 27 includes: a bottom wall portion 27a on which the plate spring 22 is placed from above; an end wall portion 27b projecting upward from a car longitudinal direction outer side of the bottom wall portion 27a; and a pair of side wall portions 27c projecting upward from both respective car width direction sides of the bottom wall portion 27a. An upper surface of the bottom wall portion 27a is inclined such that a car longitudinal direction inner side thereof is located lower than a car longitudinal direction outer side thereof. The end wall portion 27b opposes a longitudinal direction end surface of the end portion 22b of the plate spring 22 and restricts a movement of the plate spring 22 outward in the longitudinal direction. The side wall portions 27c oppose both respective car width direction side surfaces of the end portion 22b of the plate spring 22 and restrict a movement of the plate spring 22 toward both sides in the car width direction.

[0024] A carbody load transmitted from the cross beam 4 (see FIG. 2) to the plate spring 22 is transmitted from the end portion 22b of the plate spring 22 to the supporting member 24. In this case, since the upper surface of the supporting member 24 (the upper surface of the bottom wall portion 27a of the receiving member 27) is inclined, a downward carbody load F transmitted from the end portion 22b of the plate spring 22 to the supporting member 24 is inclined outward in the car longitudinal direction with respect to a vertical direction. Therefore, the carbody load F has a horizontal component F_H and a vertical component F_V , and the horizontal component F_H acts in such a direction that the axle box 8 is displaced outward in the car longitudinal direction (i.e., the axle box 8 is displaced in a direction away from the cross beam 4).

[0025] As shown in FIGS. 3 and 4, the axle beam 11 includes: an axle beam main body portion 11a extending from the axle box 8 in the car longitudinal direction; and an axle beam end portion 11b provided at a tip end of the axle beam main body portion 11a and including the tubular portion 29 that is open at both car width direction sides and has a cylindrical inner peripheral surface. The tubular portion 29 is divided into a first semi-tubular portion 30 and a second semi-tubular portion 31. The first semi-tubular portion 30 is formed continuously from and integrally with the axle beam main body portion 11a. The second semi-tubular portion 31 is stacked on the first semi-tubular portion 30 in the upward/downward direction.

[0026] The first semi-tubular portion 30 is formed continuously from an upper portion of the tip end of the axle beam main body portion 11a and projects inward in the car

longitudinal direction. A lower portion of the tip end of the axle beam main body portion 11a includes an end surface 28 facing inward in the car longitudinal direction. The first semi-tubular portion 30 has a semi-cylindrical shape that is open downward. A lower end surface of the first semi-tubular portion 30 includes first main opposing surfaces 30b and 30c and second main opposing surfaces 30d and 30e. The first main opposing surfaces 30b and 30c are located adjacent to both respective ends of a semi-cylindrical inner surface 30a of the first semi-tubular portion 30. The second main opposing surface 30d is provided at a radially outer side of the first main opposing surface 30b, and the second main opposing surface 30e is provided at a radially outer side of the first main opposing surface 30c. The first main opposing surfaces 30b and 30c are located lower than the second main opposing surfaces 30d and 30e. It should be noted that the first main opposing surfaces 30b and 30c are located higher than a lower end of the axle beam main body portion 11a. The first main opposing surface (30b, 30c) is larger than the second main opposing surface (30d, 30e).

[0027] A first sub opposing surface 30f extending in the vertical direction and facing inward in the car longitudinal direction is formed at a car longitudinal direction inner side of a center of the tubular portion 29 so as to be located between the first main opposing surface 30b and the second main opposing surface 30d. To be specific, a first step that is offset in the vertical direction is formed on the lower end surface of the first semi-tubular portion 30 by the first main opposing surface 30b, the first sub opposing surface 30f, and the second main opposing surface 30d. A second sub opposing surface 30g extending in the vertical direction and facing outward in the car longitudinal direction is formed at a car longitudinal direction outer side of the center of the tubular portion 29 so as to be located between the first main opposing surface 30c and the second main opposing surface 30e. To be specific, a step that is offset in the vertical direction is formed on the lower end surface of the first semi-tubular portion 30 by the first main opposing surface 30c, the second sub opposing surface 30g, and the second main opposing surface 30e. Each of the first sub opposing surface 30f and the second sub opposing surface 30g is smaller than each of the first main opposing surfaces 30b and 30c and the second main opposing surfaces 30d and 30e. The second main opposing surface 30e located at the car longitudinal direction outer side of the center of the tubular portion 29 is continuous with the end surface 28 of the axle beam main body portion 11a.

[0028] The second semi-tubular portion 31 has a semi-cylindrical shape that is open upward. An upper end surface of the second semi-tubular portion 31 includes first main opposing surfaces 31b and 31c and second main opposing surfaces 31d and 31e. The first main opposing surfaces 31b and 31c are located adjacent to both respective ends of a semi-cylindrical inner surface 31a of the second semi-tubular portion 31. The second main opposing surface 31d is provided at a radially outer side of the first main opposing surface 31b, and the second main opposing surface 31e is provided at a radially outer side of the first main opposing surface 31c. The first main opposing surfaces 31b and 31c are located lower than the second main opposing surfaces 31d and 31e. A first sub opposing surface 31f extending in the vertical direction and facing outward in the car longitudinal direction is formed at the car longitudinal direction inner side of the center of the tubular portion 29 so as to be

located between the first main opposing surface **31b** and the second main opposing surface **31d**. A second sub opposing surface **31g** extending in the vertical direction and facing inward in the car longitudinal direction is formed at the car longitudinal direction outer side of the center of the tubular portion **29** so as to be located between the first main opposing surface **31c** and the second main opposing surface **31e**. To be specific, a step that is offset in the vertical direction is formed on the upper end surface of the second semi-tubular portion **31** by the first main opposing surface **31b**, the first sub opposing surface **31f**, and the second main opposing surfaces **31d**, and another step that is offset in the vertical direction is formed on the upper end surface of the second semi-tubular portion **31** by the first main opposing surface **31c**, the first sub opposing surface **31g**, and the second main opposing surface **31e**.

[0029] As shown in FIGS. 3 to 5, bolt holes **30h** are formed on the first main opposing surface **30b** of the first semi-tubular portion **30**, and bolt holes **30i** are formed on the first main opposing surface **30c** of the first semi-tubular portion **30**. Each of the bolt holes **30h** and **30i** are concavely formed so as to extend upward and has an inner peripheral surface on which internal threads are formed. Depressed portions **31h** and **31i** that are depressed upward are formed on a bottom surface of the second semi-tubular portion **31**. A bolt hole **31j** is formed on an upper surface of the depressed portion **31h** as a through hole extending upward so as to reach the first main opposing surface **31b**, and a bolt hole **31k** is formed on an upper surface of the depressed portion **31i** as a through hole extending upward so as to reach the first main opposing surfaces **31c**. The second semi-tubular portion **31** is fixed to the first semi-tubular portion **30** in such a manner that in a state where the second semi-tubular portion **31** is stacked on the first semi-tubular portion **30** from below, bolts B (fastening members) are inserted into the bolt holes **30h**, **30i**, **31j**, and **31k** from below. Head portions Ba of the bolts B are accommodated in the depressed portions **31h** and **31i** of the second semi-tubular portion **31**.

[0030] The first main opposing surface **30b** of the first semi-tubular portion **30** and the first main opposing surface **31b** of the second semi-tubular portion **31** oppose each other in the upward/downward direction and contact each other, and the first main opposing surface **30c** of the first semi-tubular portion **30** and the first main opposing surface **31c** of the second semi-tubular portion **31** oppose each other in the upward/downward direction and contact each other. The second main opposing surface **30d** of the first semi-tubular portion **30** and the second main opposing surface **31d** of the second semi-tubular portion **31** oppose each other in the upward/downward direction and contact each other, and the second main opposing surface **30e** of the first semi-tubular portion **30** and the second main opposing surface **31e** of the second semi-tubular portion **31** oppose each other in the upward/downward direction and contact each other. The first sub opposing surface **30f** of the first semi-tubular portion **30** and the first sub opposing surface **31f** of the second semi-tubular portion **31** oppose each other in the car longitudinal direction and contact each other. The second sub opposing surface **30g** of the first semi-tubular portion **30** and the second sub opposing surface **31g** of the second semi-tubular portion **31** oppose each other in the car longitudinal direction and contact each other. A third sub opposing surface **31m** that is a car longitudinal direction outer end surface of

the second semi-tubular portion **31** opposes and contacts the end surface **28** of the axle beam main body portion **11a**.

[0031] The first sub opposing surfaces **30f** and **31f** restrict displacement of the second semi-tubular portion **31** relative to the first semi-tubular portion **30** outward in the car longitudinal direction. The third sub opposing surface **31m** of the second semi-tubular portion **31** and the end surface **28** of the axle beam main body portion **11a** also restrict the displacement of the second semi-tubular portion **31** relative to the first semi-tubular portion **30** outward in the car longitudinal direction. On the other hand, the second sub opposing surfaces **30g** and **31g** restrict the displacement of the second semi-tubular portion **31** relative to the first semi-tubular portion **30** inward in the car longitudinal direction.

[0032] In a side view from the car width direction, a circumferential length L1 of the semi-cylindrical inner surface **30a** of the first semi-tubular portion **30** is longer than a circumferential length L2 of the semi-cylindrical inner surface **31a** of the second semi-tubular portion **31**. Specifically, in a side view from the car width direction, a radially inner portion (i.e., a portion including the first main opposing surfaces **30b** and **30c**) of the first semi-tubular portion **30** projects toward the second semi-tubular portion **31** beyond a virtual line H extending through a center P of the tubular portion **29** and perpendicular to a direction in which the bolt B is inserted. With this, the first main opposing surfaces **30b** and **30c** of the first semi-tubular portion **30** are located lower than the virtual line H. It should be noted that in a side view, the virtual line H is a line parallel to the upper surface **8a** (surface on which the supporting member **24** is placed) of the axle box **8**.

[0033] FIG. 6 is a sectional view taken along line VI-VI of FIG. 3. As shown in FIG. 6, the core rod **14** is inserted into the internal space of the tubular portion **29** in the car width direction. The core rod **14** includes: a columnar portion **14a**; a pair of conical flange portions **14b** provided at both respective car width direction sides of the columnar portion **14a**; and projecting end portions **14c** each projecting from a side surface of the corresponding flange portion **14b** outward in the car width direction. The rubber bushing **13** is interposed between the tubular portion **29** and the core rod **14**. The rubber bushing **13** includes: a cylindrical portion **13a**; and a pair of flange portions **13b** projecting from both respective car width direction sides of the cylindrical portion **13a** outward in a radial direction. The rubber bushing **13** is externally fitted to the core rod **14**. To be specific, the cylindrical portion **13a** of the rubber bushing **13** contacts the columnar portion **14a** of the core rod **14**, and the flange portions **13b** of the rubber bushing **13** contact the respective flange portions **14b** of the core rod **14**.

[0034] The inner peripheral surface of the tubular portion **29** is formed by the inner surface **30a** of the first semi-tubular portion **30** and the inner surface **31a** of the second semi-tubular portion **31** and contacts outer peripheral surfaces of the cylindrical portion **13a** and flange portions **13b** of the rubber bushing **13**. The core rod **14** is connected to the bogie frame **3** through the receiving seats **15** and **16** in such a manner that in a state where the end portions **14c** of the core rod **14** are fitted to the respective groove portions **17** and **18** that are open downward on the receiving seats **15** and **16**, respectively, the lid members **19** are fixed to the respective receiving seats **15** and **16** from below by bolts. By elasticity of the rubber bushing **13**, the tubular portion **29** is

allowed to be displaced relative to the core rod **14** in the car longitudinal direction, the car width direction, and the vertical direction.

[0035] According to the configuration explained above, the tubular portion **29** of the axle beam **11** is divided into the first semi-tubular portion **30** formed continuously from and integrally with the axle beam main body portion **11a** and the second semi-tubular portion **31** stacked on the first semi-tubular portion **30** in the upward/downward direction. Therefore, when viewed from the center P of the core rod **14**, the first semi-tubular portion **31** is provided so as to extend to an opposite side (the cross beam **4** side) of the axle beam main body portion **11a**. On this account, the first semi-tubular portion **30** can receive loads transmitted through the axle box **8** to the axle beam **11** in both directions along the car longitudinal direction. Thus, it is possible to prevent a case where the load transmitted through the axle box **8** to the axle beam **11** in the car longitudinal direction acts in such a direction that the first semi-tubular portion **30** is separated from the second semi-tubular portion **31**. Therefore, a requirement of attaching strength of the second semi-tubular portion **31** attached to the first semi-tubular portion **30** can be eased. To be specific, since the load applied to the bolts B is reduced, the requirement of the attaching strength of the bolts B is eased, and design burden is therefore reduced.

[0036] In the present embodiment, the horizontal component F_H of the carbody load F transmitted through the plate spring **22** is applied to the axle beam **11** at all times as a load acting outward in the car longitudinal direction. Further, when braking the wheel **6**, the brake force applied to the wheel **6** is applied to the axle beam **11** as a load acting outward in the car longitudinal direction. Therefore, a large load acting outward in the car longitudinal direction tends to be applied the axle beam **11** of the bogie **1** of the present embodiment, so that the above-described configuration of the tubular portion **29** is especially advantageous in terms of strength.

[0037] Further, the first semi-tubular portion **30** includes the first sub opposing surface **30f** and the second sub opposing surface **30g**, and the second semi-tubular portion **31** includes the first sub opposing surface **31f** and the second sub opposing surface **31g**. The first sub opposing surfaces **30f** and **31f** oppose each other in the car longitudinal direction, and the second sub opposing surfaces **30g** and **31g** oppose each other in the car longitudinal direction. Therefore, the sub opposing surfaces **30f**, **31f**, **30g**, and **31g** can receive a load acting in such a direction that the second semi-tubular portion **31** is displaced relative to the first semi-tubular portion **30** in the car longitudinal direction. Especially, the first sub opposing surfaces **30f** and **31f** restrict the displacement of the second semi-tubular portion **31** relative to the first semi-tubular portion **30** outward in the car longitudinal direction, and the second sub opposing surfaces **30g** and **31g** restrict the displacement of the second semi-tubular portion **31** relative to the first semi-tubular portion **30** inward in the car longitudinal direction. Therefore, shear force acting on the bolts B can be adequately suppressed.

[0038] The circumferential length L1 of the inner surface **30a** located at a radially inner side of the first semi-tubular portion **30** is longer than the circumferential length L2 of the inner surface **31a** located at a radially inner side of the second semi-tubular portion **31**. Therefore, the first semi-tubular portion **30** can receive larger force than the second

semi-tubular portion **31**, the force being applied from the core rod **14** through the rubber bushing **13**. Further, at an interface between the tubular portion **29** and the rubber bushing **13**, the load transmitted through the axle box **8** to the axle beam **11** in the car longitudinal direction most largely acts on a horizontal line extending through the center P of the tubular portion **29**. However, since the first semi-tubular portion **30** projects toward the second semi-tubular portion **31** beyond the horizontal virtual line H, and the inner surface **30a** of the first semi-tubular portion **30** exists on the virtual line H, the above load is easily received by the first semi-tubular portion **30**.

[0039] On this account, the load applied to the second semi-tubular portion **31** can be preferably made smaller than the load applied to the first semi-tubular portion **30**. As a result, it is possible to further prevent the case where the load transmitted through the axle box **8** to the axle beam **11** in the car longitudinal direction acts in such a direction that the second semi-tubular portion **31** is separated from the first semi-tubular portion **30**. In addition, the requirement of the attaching strength of the second semi-tubular portion **31** attached to the first semi-tubular portion **30** can be further preferably eased.

[0040] The present invention is not limited to the above embodiment, and modifications, additions, and eliminations may be made within the scope of the present invention. In the present embodiment, the main opposing surfaces of the first semi-tubular portion **30** and the main opposing surfaces of the second semi-tubular portion **31** are parallel to the upper surface **8a** of the axle box **8**. However, these main opposing surfaces may be inclined relative to the upper surface **8a**. To be specific, in FIG. 3, the main opposing surfaces may be inclined relative to the virtual line H. This case only requires that: each of the main opposing surfaces is inclined in such an angular range that a car longitudinal direction component of a normal vector of the main opposing surface is larger than an upward/downward direction component of the normal vector; and therefore, the second semi-tubular portion **31** is stacked on the first semi-tubular portion **30** mainly in the upward/downward direction. Further, in the present embodiment, an upper portion of the tubular portion **29** is the first semi-tubular portion **30** formed integrally with the axle beam main body portion **11a**, and a lower portion of the tubular portion **29** is the second semi-tubular portion **31** formed separately. However, the lower portion of the tubular portion may be the first semi-tubular portion formed integrally with the axle beam main body portion, and the upper portion of the tubular portion may be the second semi-tubular portion formed separately.

[0041] In the present embodiment, the upper surface of the supporting member **24** on which the plate spring **22** is placed is inclined. However, the upper surface of the supporting member **24** may be a horizontal surface. This case only requires that: it is possible to prevent a case where the load applied to the axle beam in the car longitudinal direction at the time of braking acts in such a direction that the second semi-tubular portion is separated from the first semi-tubular portion; and the load applied to a coupling portion where the bogie frame and the axle beam are coupled to each other can be reduced.

[0042] In the present embodiment, the displacement of the second semi-tubular portion **31** relative to the first semi-tubular portion **30** outward in the car longitudinal direction is restricted by both the contact of the first sub opposing

surface **31f** with the first sub opposing surface **30f** and the contact of the third sub opposing surface **31m** with the end surface **28** of the axle beam main body portion **11a**. However, any one of the above contacts may be realized. Further, each of the opposing surfaces is not limited to a flat surface and may be a curved surface. The opposing surfaces opposing each other do not have to be in surface contact with each other and may be in line contact or point contact with each other. The rubber bushing **13** may be formed by an elastic material other than rubber. The axle box suspension **10** of the present embodiment is applied to the bogie **1** including the plate spring **22**. However, it is also preferable to apply the axle box suspension **10** of the present embodiment to a steering bogie in which force in the car longitudinal direction tends to be generated at the axle box. Further, the bogie to which the axle box suspension **10** of the present embodiment is applied is not limited to the bogie including the plate spring or the steering bogie and may be a bogie including a typical axle beam type axle box suspension.

REFERENCE SIGNS LIST

[0043]	1 bogie
[0044]	3 bogie frame
[0045]	5 axle
[0046]	7 bearing
[0047]	8 axle box
[0048]	10 axle box suspension
[0049]	11 axle beam
[0050]	11a axle beam main body portion
[0051]	11b axle beam end portion
[0052]	13 rubber bushing (elastic bushing)
[0053]	14 core rod
[0054]	15, 16 receiving seat
[0055]	29 tubular portion
[0056]	30 first semi-tubular portion
[0057]	30a inner surface
[0058]	30b, 30c first main opposing surface
[0059]	30d, 30e second main opposing surface
[0060]	30f first sub opposing surface
[0061]	30g second sub opposing surface
[0062]	31 second semi-tubular portion
[0063]	31a inner surface
[0064]	31b, 31c first main opposing surface
[0065]	31d, 31e second main opposing surface
[0066]	31f first sub opposing surface
[0067]	31g second sub opposing surface
[0068]	31m third sub opposing surface
[0069]	50 carbody
[0070]	B bolt (fastening member)
[0071]	H virtual line

1. An axle box suspension of a railcar bogie, the axle box suspension being configured to couple an axle box to a bogie frame, the axle box accommodating a bearing supporting an axle,

the axle box suspension comprising:

an axle beam including an axle beam main body portion and an axle beam end portion, the axle beam main body portion extending from the axle box in a car longitudinal direction, the axle beam end portion being provided at a tip end of the axle beam main body portion and including a tubular portion that is open at both car width direction sides;

a core rod inserted into an internal space of the tubular portion in a car width direction;

an elastic bushing interposed between the tubular portion and the core rod; and

a receiving seat provided at the bogie frame, both end portions of the core rod being connected to the receiving seat,

the tubular portion being divided into a first semi-tubular portion and a second semi-tubular portion, the first semi-tubular portion being formed integrally with the axle beam main body portion, the second semi-tubular portion being stacked on the first semi-tubular portion in an upward/downward direction.

2. The axle box suspension according to claim 1, wherein the second semi-tubular portion includes:

a main opposing surface opposing the first semi-tubular portion in the upward/downward direction; and

a sub opposing surface opposing at least one of the first semi-tubular portion and the axle beam main body portion in the car longitudinal direction.

3. The axle box suspension according to claim 2, wherein the sub opposing surface includes:

a first sub opposing surface configured to restrict displacement of the second semi-tubular portion relative to the first semi-tubular portion in one direction along the car longitudinal direction; and

a second sub opposing surface configured to restrict displacement of the second semi-tubular portion relative to the first semi-tubular portion in the other direction along the car longitudinal direction.

4. The axle box suspension according to claim 1, wherein when viewed from the car width direction, a circumferential length of a semi-cylindrical inner surface of the first semi-tubular portion is longer than a circumferential length of a semi-cylindrical inner surface of the second semi-tubular portion.

5. The axle box suspension according to claim 4, further comprising a fastening member inserted into the first semi-tubular portion and the second semi-tubular portion in the upward/downward direction to fix the second semi-tubular portion to the first semi-tubular portion, wherein

when viewed from the car width direction, the first semi-tubular portion projects toward the second semi-tubular portion beyond a virtual line extending through a center of the tubular portion and perpendicular to a direction in which the fastening member is inserted.

6. The axle box suspension according to claim 2, wherein when viewed from the car width direction, a circumferential length of a semi-cylindrical inner surface of the first semi-tubular portion is longer than a circumferential length of a semi-cylindrical inner surface of the second semi-tubular portion.

7. The axle box suspension according to claim 3, wherein when viewed from the car width direction, a circumferential length of a semi-cylindrical inner surface of the first semi-tubular portion is longer than a circumferential length of a semi-cylindrical inner surface of the second semi-tubular portion.

8. The axle box suspension according to claim 6, further comprising a fastening member inserted into the first semi-tubular portion and the second semi-tubular portion in the upward/downward direction to fix the second semi-tubular portion to the first semi-tubular portion, wherein

when viewed from the car width direction, the first semi-tubular portion projects toward the second semi-tubular portion beyond a virtual line extending through

a center of the tubular portion and perpendicular to a direction in which the fastening member is inserted.

9. The axle box suspension according to claim 7, further comprising a fastening member inserted into the first semi-tubular portion and the second semi-tubular portion in the upward/downward direction to fix the second semi-tubular portion to the first semi-tubular portion, wherein

when viewed from the car width direction, the first semi-tubular portion projects toward the second semi-tubular portion beyond a virtual line extending through a center of the tubular portion and perpendicular to a direction in which the fastening member is inserted.

* * * * *