



US 20130018542A1

(19) **United States**
(12) **Patent Application Publication**
CHINNADURAI et al.

(10) **Pub. No.: US 2013/0018542 A1**
(43) **Pub. Date: Jan. 17, 2013**

(54) **POWER BALANCING FOR VEHICLE DIAGNOSTIC TOOLS**

(60) Provisional application No. 61/058,072, filed on Jun. 2, 2008.

(71) Applicant: **SPX CORPORATION**, Charlotte, NC (US)

Publication Classification

(72) Inventors: **Manokar CHINNADURAI**, Owatonna, MN (US); **Troy LIEBL**, Owatonna, MN (US); **Phillip MCGEE**, Owatonna, MN (US)

(51) **Int. Cl.**
G06F 17/00 (2006.01)
(52) **U.S. Cl.** **701/31.4**

(73) Assignee: **SPX CORPORATION**, Charlotte, NC (US)

(57) **ABSTRACT**


(21) Appl. No.: **13/624,377**

(22) Filed: **Sep. 21, 2012**

Related U.S. Application Data

(62) Division of application No. 12/477,030, filed on Jun. 2, 2009, now Pat. No. 8,296,035.

A power balancing system includes a vehicle communication device connected to a data link connector of a vehicle, and a scan tool connected to the vehicle communication device, the scan tool including a handset and a vehicle connector interface (VCI), wherein power can be received from one or more of an external power source being external from the VCI, the vehicle, and an internal power supply of the scan tool, and wherein the system balances the received power.






FIG. 3

**POWER BALANCING FOR VEHICLE
DIAGNOSTIC TOOLS**

PRIORITY

[0001] The present application is a divisional patent application of and claims priority to U.S. patent application Ser. No. 12/477,030 filed Jun. 2, 2009, now U.S. Pat. No. _____, issued _____ 2012, which claims priority to U.S. Provisional Application No. 61/058/072, filed Jun. 2, 2008, the disclosures of which are both hereby incorporated by reference herein in their entirety.

FIELD OF THE INVENTION

[0002] The present invention relates generally to a vehicle diagnostic tool. More particularly, the present invention relates to power balancing of a vehicle diagnostic scan tool.

BACKGROUND OF THE INVENTION

[0003] Vehicle diagnostic scan tools are used to diagnose issues in the vehicle under test. The scan tools are built with increasing capabilities that include larger color screens that are capable of being read in direct sunlight, and internet and networking capabilities and thus require more power. The tool can be directly linked to a vehicle's data link connector (DLC) in order to communicate with the vehicle's on-board diagnostic system, such as OBD-II (On Board Diagnostic). Once the tool is connected to the DLC, it can draw power from the vehicle's battery. However, depending on the usage, the tool can draw too much power from the vehicle's battery and damage the vehicle's battery. Additionally, the scan tool can be equipped with its own internal power supply (battery), however, by using the scan tool's internal power supply the amount of time that a technician can use the scan tool is limited.

[0004] Accordingly, it is desirable to provide a system and method that power balance the scan tool's draw of power between a vehicle, the scan tool's battery and any other available power source.

SUMMARY OF THE INVENTION

[0005] Accordingly, embodiments of the present invention provide a system and method that power balance the scan tool's draw of power between a vehicle, the scan tool's battery and any other available power source.

[0006] An embodiment includes a power balancing system which includes a vehicle communication device connected to a data link connector of a vehicle, and a scan tool connected to the vehicle communication device, the scan tool including a handset and a vehicle connector interface (VCI), wherein power can be received from one or more of an external power source being external from the VCI, the vehicle, and an internal power supply of the scan tool, and wherein the system balances the received power.

[0007] Another embodiment includes a method of balancing power, the method including receiving power from one of more of an external power source being external from a vehicle connector interface (VCI), a vehicle, and an internal power supply of a scan tool connected to a vehicle communication device connected to a data link connector of the vehicle, the scan tool including a handset, and a vehicle connector interface (VCI), and balancing the received power.

[0008] Another embodiment includes a power balancing system, including means for receiving power from one of

more of means for an external power source from a vehicle connector interface (VCI), a vehicle, and means for an internal power supply of a scan tool connected to a vehicle communication device connected to a data link connector of the vehicle, the scan tool including a handset, and means for a vehicle connector interface (VCI), and means for balancing the received power.

[0009] There has thus been outlined, rather broadly, certain embodiments of the invention in order that the detailed description thereof herein may be better understood, and in order that the present contribution to the art may be better appreciated. There are, of course, additional embodiments of the invention that will be described below and which will form the subject matter of the claims appended hereto.

[0010] In this respect, before explaining at least one embodiment of the invention in detail, it is to be understood that the invention is not limited in its application to the details of construction and to the arrangements of the components set forth in the following description or illustrated in the drawings. The invention is capable of embodiments in addition to those described and of being practiced and carried out in various ways. Also, it is to be understood that the phraseology and terminology employed herein, as well as the abstract, are for the purpose of description and should not be regarded as limiting.

[0011] As such, those skilled in the art will appreciate that the conception upon which this disclosure is based may readily be utilized as a basis for the designing of other structures, methods and systems for carrying out the several purposes of the present invention. It is important, therefore, that the claims be regarded as including such equivalent constructions insofar as they do not depart from the spirit and scope of the present invention.

BRIEF DESCRIPTION OF THE DRAWINGS

[0012] FIG. 1 illustrates a front view of a scan tool according to an embodiment of the invention.

[0013] FIG. 2 is an upper view of the scan tool coupled to an optional vehicle connector interface (VCI) according to an embodiment of the invention.

[0014] FIG. 3 illustrates a perspective view of the scan tool and the VCI uncoupled according to an embodiment of the invention.

[0015] FIG. 4 illustrates a wiring diagram of a power balancing system according to an embodiment of the invention.

DETAILED DESCRIPTION

[0016] The invention will now be described with reference to the drawing figures, in which like reference numerals refer to like parts throughout. An embodiment in accordance with the present invention provides a system and a method that allows a scan tool to balance the draw of power from various power sources.

[0017] FIG. 1 illustrates a front view of a scan tool 100 according to an embodiment of the invention. The scan tool 100 includes a display 102, a scroll device 104, a power button 108, LED indicators 110 and function buttons 112. The display can be any type of display including LCD, VGA, OLED, SVGA and other types of displays including touch screen displays. The display may be a colored or non-colored display. The display can display information such as the make, model, year of vehicles that the scan tool can diagnose, the various diagnostic tests the scan tool can run, diagnostic

data the scan tool has received, and baseline data of the various components in a vehicle. Additionally, the display can show videos for the user to view and the accompanying audio can be heard via the built in speakers 114. The speakers 114 can be a single speaker or multiple speakers for stereo sound. In one embodiment, the display allows the user to input selection through the touch screen for interactive navigation and selection, wherein the technician can select a menu item by touching the selection on the screen.

[0018] The scroll device 104 can be used to scroll through information or menus on the display, such as vehicle information or available diagnostic tests. In one embodiment, there is one scroll device 104 and in another embodiment there are two or more scroll devices 104. When two scroll devices 104 are present, the user can have dual controls of the menus or the selections on the display. By having two scroll devices, it may be easier for a technician to use regardless if he were left-handed or right-handed. For example, the scroll device 104 may include an “enter” button 118 so that a user can select a menu item, for example, a vehicle or a diagnostic test. The scroll device 104 may also include a scroll wheel 116 that can rotate around the “enter” button 118. The scroll wheel 116 may also include up, down, left and right arrow controls. The scroll wheel 116 can allow the technician to move an indicator on the screen so that the information including menus can be scrolled and a selection on the screen can be made. The scroll wheel 116 may be configured for a fast response or fast scrolling. The scroll device 104 may also include a scroll button 106, such as an “esc” button, “back” button, “forward” button, or any other button desired by the technician. Any components of the scroll device 104, including the scroll button 106, can be programmed for any desired functionality.

[0019] The face of the scan tool 100 may include the power button 108 that allows the technician to power “on” and “off” the scan tool 100. The power button 108 can also be used to put the tool 100 into a standby mode in order to save battery power when not in use. Also on the face of the scan tool 100 may be LEDs to indicate various status of the functionality of the scan tools, such as wireless connectivity or network connectivity, low battery and any other indicators desired by the technician. The face of the scan tool may further include function buttons 112 that when pressed allows a user to perform a function such as controlling the brightness of the display, volume of the speakers or any other function desired by the technician. A microphone 120 may allow the technician to record information such as the noise being made by the vehicle for later analysis or for comparison with stored data. Further, the technician can also record comments or notes during the testing for later retrieval and analysis.

[0020] FIG. 2 is an upper view of the scan tool 100 coupled to an optional vehicle connector interface (VCI) 200 according to an embodiment of the invention. Turning to the connections available on the scan tool 100, the scan tool 100 can be connected to an A/C power source via the A/C power connector 122. The A/C can power the scan tool 100 and recharge the scan tool’s internal battery (not shown). A VGA video connector 124 may allow the information on the scan tool 100 to be displayed on an external display, such as a display on a personal computer.

[0021] A series of host USB (universal serial bus) connectors 126 may be available to couple additional devices to the scan tool 100. In one embodiment, there are four connectors, but more or fewer connectors are contemplated by the inven-

tion. Additional devices can add functionality to the scan tool 100 or allow the scan tool 100 to add functionality to another device, such as the VCI 200. The functionality can include communications, printing, memory storage, video and other functionality. Two-channel scope connections 128 may allow for a scope to be connected to the scan tool 100. The invention is not limited to the two-channel scope connections 128. The scope can provide various measurement of signals such as volts, ohms, dwell, duty cycle, peak to peak, peak volts, injector pulse width, injector on time, firing kV, burn kV, burn voltage, and other measurement of signals.

[0022] A stereo headphone connection 130 may allow the technician to add a headphone to the scan tool 100. A USB device slot 132 can also add functionality to the scan tool 100 by another device or adds functionality of the scan tool 100 to another device. An express card slot 134 may be provided to add functionality, such as a wireless modem, memory, TV tuner, networking, mouse, remote control, and other functionalities to the scan tool 100. An Ethernet connector 136 allows for a network connection with the scan tool 100 in order to transfer data to and from the scan tool 100 to a remote device such as a server or personal computer. SDIO (Secure Digital Input Output) 140 cards slots 140 can be provided on the scan tool 100 to provide still additional functionality such as GPS receivers, Wi-Fi or Bluetooth adapters, modems, Ethernet adapters, barcode readers, IrDA adapters, FM radio tuners, TV tuners, RFID readers, and other mass storage media such as hard drives. The possible connections are not limited to those shown in FIG. 2, but additional connectors are contemplated such as, without limitation, Firewire, HDMI, parallel, and serial connections.

[0023] When the VCI 200 is docked with the scan tool 100, the VCI 200 will be the device that is connected to the vehicle’s DLC for diagnosis. A vehicle connector 202 on the VCI 200 allows the VCI 200 to connect to the vehicle’s DLC and exchange data via a cable (not shown). The DLC can provide power to the scan tool 100 or the VCI 200 via the vehicle’s battery.

[0024] FIG. 3 illustrates a perspective view of the scan tool 100 and the VCI 200 uncoupled according to an embodiment of the invention. FIG. 3 illustrates a back view of the scan tool 100, wherein a VCI receiving portion 150 is constructed to receive the VCI 200. A VCI connector 155 allows the VCI 200 to connect with the scan tool 100. Once connected, the VCI and the scan tool 100 can communicate with each other. Additionally, the VCI 200 and the scan tool 100 can provide power to each other as needed through the VCI connector 155. A grip portion 165 may be provided on each side of the scan tool 100. The grip portion 165 can be made of any material including an elastomeric material. A handle 160 may be provided on the back side of the scan tool 100 in order for the technician to move the scan tool 100 from one place to another.

[0025] FIG. 4 illustrates an example electrical schematic diagram for a power balancing system 300 according to an embodiment of the invention. The VCI 200 can be powered via a DC jack 302, which can accept a connection from an external battery or other electrical power source. In some embodiments, the VCI 200 can be powered via an optional AC jack and appropriate power conversion circuitry (not shown).

[0026] In one embodiment of the invention, the electrical ground for the DC jack 302 is connected to the chassis ground of the vehicle 312, first through electrical node 304 (DOC_

CGND), next through the current-limiting resistor or equivalent protection device **336** (RT403), then through line **316** (CGND) which is physically connected to the vehicle **312** using the Vehicle Cable Connector **202** (FIG. 2 and FIG. 3). The current-limiting resistor or equivalent protection device **336** (RT403) may be any type of resistor or resistance circuit including a thermistor, or it may be a fuse or any another electronic component with a similar purpose or function.

[0027] In one embodiment of the invention, the electrical power supplied through the DC jack **302** may be conveyed to the core functional elements of the VCI **200** and to the handset device **350** to which the VCI **200** is docked. The core of the VCI **200** receives power through the sequence consisting first of electrical node **306** (EXT_VBAT), next reverse current protection diode **308** (D2), then electrical node **360** (DOC_VBAT), and finally through the current-limiting resistor or equivalent protection device **320** (RT401), to electrical node **324** (VBAT_PRO). The current-limiting resistor or equivalent protection device **320** (RT401) may be of any type of resistor, or alternatively it may be a fuse or any another electronic component with a similar purpose or function. The core of the VCI **200** is protected from overvoltage by protection diode **322** (D401), which may be a transient voltage suppression (TVS) diode or equivalent. Also, the core of the VCI **200** may be protected by optional reverse current protection diode **330** (D400).

[0028] Similarly, the handset device **350** can also receive the electrical power made available on electrical node **360** (DOC_VBAT). This is achieved through the current sensing circuit **318** (U418) and electrical node **362** (CL_DOC_VBAT), which is included within the VCI Docking Connector **155** (FIG. 3).

[0029] Additionally, capability is provided for electrical power to be supplied to the VCI device and the Handset device **350** by the existing battery or other power source typically included within the vehicle **312**. This is accomplished through an electrical connection within the Vehicle Cable Connector **202** (FIG. 2 and FIG. 3) that joins the non-grounded terminal (not shown) of the battery within vehicle **312** to electrical node **310** (VBAT), which then connects through diode **358** (D3), providing electrical power to electrical node **360** (DOC_VBAT). The power is then conveyed as described above.

[0030] In various embodiments of the invention, the handset device **350** also contains one or more of its own power sources, which may include an internal battery (not shown), the handset's A/C Power Connector **122** (FIG. 2), power sourced from the handset's USB Device Slot **132** (FIG. 2), or other power sources not listed. Embodiments of handset device **350** with multiple power sources are capable of selecting one or more of the most appropriate power sources for a given situation, which typically would involve selecting a power source in good working order, prioritizing the use of power from electrical node **362** (CL_DOC_VBAT), and switching to an alternative power source if power from electrical node **362** is interrupted.

[0031] The connection between electrical node **362** and the handset device **350**, along with the presence of other power sources within handset device **350**, could result, under certain particular circumstances, in the reverse flow electrical power from that described above, that is, from one or more power sources within the handset device **350**, then through the VCI Docking Connector **155** (FIG. 3), through electrical node **362** (CL_DOC_VBAT), and into electrical node **360** (DOC_VBAT). This situation would allow the core of the VCI **200** to be powered by the handset device **350**, which would be beneficial when no power is available either from the DC jack **302**

or from the battery within the vehicle **312**. Various embodiments of the invention may be configured to prevent, allow, or otherwise control this reversed power flow, such as through the use of diodes within the handset device **350**, and some embodiments may include other manners of managing, controlling, switching on and off, and selecting other characteristics of reversed power flow if and when allowed to occur.

[0032] An embodiment of the invention reconfigures diode **358** (D3) with other additional and/or replacement components to permit power to flow through electrical node **310**, in the opposite direction from that described above, into vehicle **312**, such as to charge the battery typically contained within vehicle **312** through the use of one or more of the other power sources available to the invention.

[0033] Line **326** also includes a switch **332** that switches from a first position to a second position depending on the power source being utilized so that in some embodiments, the ground utilized by the system can be SGND (signal ground) along line **314** or CGND (chassis ground) along line **316**. In one embodiment, the default is SGND. Line **334** connects to the switch **332** at one end and at the other end to line **316**. Line **316** on one end includes the CGND (chassis ground) in the vehicle and at the other end includes CL_CGND.

[0034] Line **316** includes by-pass line **338** that includes diode **340** (D12). A controller switch **342** is a type of electronic switch that is off when the handset device **350** draws too much power from the VBat of the vehicle and is on to allow the handset to draw power from the VBat when the handset is not drawing too much power. The controller switch **342** can be controlled by the CPLD (not shown) within the VCI. The CPLD also communicates with the current sensing circuit **318** on electrical node **310** to sense the current being drawn by the handset. The CPLD uses the current sensing circuit **318** in conjunction with the controller switch **342** in order for the system to operate on a duty cycle according to one embodiment of the invention. Thus, the system monitors the current being drawn from the vehicle's battery by the scan tool and if the current being drawn exceeds a predetermined amount, such as, for example, 4-6 amps, then the current monitoring system cuts power to the scan tool so that the scan tool uses its own battery source. After a predetermined period of time, the current monitoring system enables power from the vehicle to the scan tool so that the scan tool's battery is not being used at all times. The current monitoring system continues this monitoring process when the scan tool is connected to the VCI or in other embodiments directly with the vehicle.

[0035] The many features and advantages of the invention are apparent from the detailed specification, and thus, it is intended by the appended claims to cover all such features and advantages of the invention which fall within the true spirit and scope of the invention. Further, since numerous modifications and variations will readily occur to those skilled in the art, it is not desired to limit the invention to the exact construction and operation illustrated and described, and accordingly, all suitable modifications and equivalents may be resorted to, falling within the scope of the invention.

What is claimed is:

1. A method of balancing power, the method comprising: receiving power from one or more of:
 - an external power source being external from a vehicle connector interface,
 - a vehicle, and
 - an internal power supply of a scan tool connected to a vehicle communication device connected to a data link connector of the vehicle,

the scan tool comprising:
 a handset; and
 a vehicle connector interface (VCI), and
 balancing the received power.

2. The method of claim 1, wherein balancing the power comprises:
 selecting one or more of the most appropriate power sources for a given situation;
 prioritizing the use of power from a power input node in the scan tool; and
 switching to an alternative power source if power at the power input node is interrupted.

3. The method of claim 2, wherein selecting one or more of the most appropriate power sources comprises selecting a power source in good working order.

4. The method of claim 1, wherein the vehicle connector interface is configured to provide power to one or more of the vehicle and the handset.

5. The method of claim 4, further comprising:
 monitoring a current being drawn from the vehicle by the scan tool; and
 if the current being drawn exceeds a predetermined amount, cutting power to the scan tool.

6. The method of claim 5, wherein, when the power is cut to the scan tool, the scan tool is configured to receive power from the handset.

7. The method of claim 5, further comprising, after a predetermined period of time, enabling power to be supplied from the vehicle to the scan tool.

8. The method of claim 4, wherein, when the power is received from the external power source, one or more of the vehicle and the handset are charged.

9. A method of balancing power, the method comprising:
 receiving power from one or more of:
 an external power source being external from a vehicle connector interface (VCI),
 a vehicle, and

an internal power supply of a scan tool configured to be connected to a vehicle communication device configured to be connected to a data link connector of the vehicle, the scan tool comprising:
 a handset; and
 a vehicle connector interface, and
 balancing the received power received from one or more of the external power source, the vehicle, and the internal power supply of the scan tool.

10. The method of claim 9, wherein balancing the power comprises:
 selecting one or more of the most appropriate power sources for a given situation;
 prioritizing the use of power from a power input node in the scan tool; and
 switching to an alternative power source if power at the power input node is interrupted.

11. The method of claim 10, wherein selecting one or more of the most appropriate power sources comprises selecting a power source in good working order.

12. The method of claim 9, wherein the vehicle connector interface is configured to provide power to one or more of the vehicle and the handset.

13. The method of claim 12, further comprising:
 monitoring a current being drawn from the vehicle by the scan tool; and
 if the current being drawn exceeds a predetermined amount, cutting power to the scan tool.

14. The method of claim 13, wherein, when the power is cut to the scan tool, the scan tool receives power from the handset.

15. The method of claim 13, further comprising, after a predetermined period of time, enabling power to be supplied from the vehicle to the scan tool.

16. The method of claim 12, wherein, when the power is received from the external power source, one or more of the vehicle and the handset are charged.

* * * * *