



US007412273B2

(12) **United States Patent**  
**Jais et al.**

(10) **Patent No.:** **US 7,412,273 B2**  
(45) **Date of Patent:** **Aug. 12, 2008**

(54) **SOFT LINEAR MAPPING CATHETER WITH STABILIZING TIP**

FOREIGN PATENT DOCUMENTS

WO WO 94/16618 8/1994

(75) Inventors: **Pierre Jais**, Pessac-Bordeaux (FR);  
**Irma P. Hill**, La Verne, CA (US); **James K. Lee**, West Covina, CA (US); **Robert A. Mest**, Long Beach, CA (US)

OTHER PUBLICATIONS

International Search Report dated Mar. 29, 2006 for International Application No. PCT/US2005/041284.  
Written Opinion dated Mar. 29, 2006 for International Application No. PCT/US2005/041284.

(73) Assignee: **Biosense Webster, Inc.**, Diamond Bar, CA (US)

\* cited by examiner

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 196 days.

*Primary Examiner*—Lee S Cohen

(74) *Attorney, Agent, or Firm*—Christie, Parker & Hale, LLP

(21) Appl. No.: **10/990,146**

(57) **ABSTRACT**

(22) Filed: **Nov. 15, 2004**

A catheter adapted for mapping near a tubular region of a heart, has an elongated tubular catheter body having proximal and distal ends, an intermediate section distal of the catheter body, and a mapping assembly at the distal end of the intermediate section. The electrode-carrying mapping assembly has a generally circular main segment with a support member having shape-memory, and a generally linear proximal segment which has greater flexibility than either the intermediate section or the generally circular main segment. The generally circular main segment is adapted to releasably anchor itself in the tubular region and to map circumferentially around the tubular region and the generally linear segment is adapted to contact generally along its length heart wall tissue near an ostium of the tubular region. In another embodiment of the present invention, the mapping assembly extends from the distal end of the catheter body, where the generally linear proximal segment of the mapping assembly has greater flexibility than either the catheter body or the generally circular main segment.

(65) **Prior Publication Data**

US 2006/0106295 A1 May 18, 2006

(51) **Int. Cl.**  
**A61B 5/04** (2006.01)

(52) **U.S. Cl.** ..... **600/374; 600/381**

(58) **Field of Classification Search** ..... **600/374, 600/381**


See application file for complete search history.



(56) **References Cited**

U.S. PATENT DOCUMENTS

- 5,487,385 A 1/1996 Avitall
- 5,617,854 A 4/1997 Munsif
- 7,142,903 B2 \* 11/2006 Rodriguez et al. .... 600/374
- 2003/0130572 A1 7/2003 Phan et al.

**37 Claims, 18 Drawing Sheets**









FIG. 3







FIG 5






Fig. 6a




FIG. 6b



FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12





FIG. 13







Fig. 18






FIG. 15






Fig. 17a

Fig. 15a




FIG. 17




Fig. 17b

## SOFT LINEAR MAPPING CATHETER WITH STABILIZING TIP

### FIELD OF INVENTION

The present invention relates to an improved mapping catheter that is particularly useful for mapping electrical activity in a wall region of or near the heart.

### BACKGROUND OF INVENTION

Atrial fibrillation is a common sustained cardiac arrhythmia and a major cause of stroke. Atrial fibrillation results in a fast and irregular cardiac rhythm which often leads to palpitations and a deterioration of cardiac function with cardiac output decreasing by an average of 30%. There is also an increased incidence of intra cardiac thrombosis (blood clotting) which can potentially lead to embolic events such as strokes. Consequently, 20 to 35% of cerebrovascular accidents (CVAs) are related to paroxysmal or chronic atrial fibrillation.

This condition is perpetuated by reentrant wavelets propagating in an abnormal atrial-tissue substrate. Various approaches have been developed to interrupt wavelets, including surgical or catheter-mediated atriotomy. Atrial fibrillations can also be treated by pulmonary vein isolation which proves to be insufficient in 30 to 50% of paroxysmal atrial fibrillation patients and 90% of permanent atrial fibrillation. In such cases, it may be necessary to ablate and perform linear lesions in addition to pulmonary vein isolation, in the right and left atriums. These linear lesions have been done using RF ablation catheters for about a decade. Each lesion should ideally be transmural and continued with adjacent lesions so as to obtain a final linear lesion blocking electrical activity between two natural areas of block. The most common locations of these lines are the mitral isthmus in the left atrium, with a lesion extending from the mitral annulus to the left inferior pulmonary vein. Other possible locations include the roof of the left atrium, with a lesion connecting the ostium of the superior right pulmonary vein to the left superior vein. However, because conventional catheters generally treat tissue in a localized manner, numerous repeated applications of the catheter are typically needed to form a linear lesion. Thus, while the formation of linear lesions is possible, it can be a time-consuming, labor-intensive procedure.

Prior to treating the condition, one has to first determine the location of the wavelets. Various techniques have been proposed for making such a determination. None of the proposed techniques, however, provide sufficient assistance in guiding the formation of the linear lesion or easing the linear line assessment process, particularly for regions of the mitral isthmus and the left atrium roof.

### SUMMARY OF THE INVENTION

A catheter adapted for mapping near a tubular region of a heart, has an elongated tubular catheter body having proximal and distal ends, an intermediate section distal of the catheter body, and a mapping assembly at the distal end of the intermediate section. The electrode-carrying mapping assembly has a generally circular main segment with a support member having shape-memory, and a generally linear proximal segment which has greater flexibility than either the intermediate section or the generally circular main segment. In accordance with the present invention, the generally circular main segment is adapted to releasably anchor itself in the tubular region and to map circumferentially around the tubular region

and the generally linear segment is adapted to contact generally along its length heart wall tissue near an ostium of the tubular region. Advantageously, the mapping assembly is adapted to conduct mapping of said wall tissue along a linear pattern extending radially from the ostium. Moreover, the mapping assembly is adapted to be rotated about the ostium to perform mapping of said wall tissue along different radially-extending linear patterns about the ostium. To that end, the generally linear segment has a proximal portion that is generally devoid of electrodes and the catheter includes a control handle to deflect the catheter along the intermediate section.

In another embodiment of the present invention, a catheter adapted for mapping near a tubular region of a heart, has an elongated tubular catheter body having proximal and distal ends and a mapping assembly at the distal end of the catheter body. The electrode-carrying mapping assembly has a generally circular main segment with a support member having shape-memory, and a generally linear proximal segment which has greater flexibility than either of the catheter body and the generally circular main segment. In accordance with the present invention, the generally circular main segment is adapted to releasably anchor itself in the tubular region and to map circumferentially around the tubular region and the generally linear segment is adapted to contact generally along its length heart wall tissue near an ostium of the tubular region. Advantageously, the mapping assembly is adapted to conduct mapping of said wall tissue along a linear pattern extending radially from the ostium. Moreover, the mapping assembly is adapted to be rotated about the ostium to perform mapping of said wall tissue along different radially-extending linear patterns about the ostium. To that end, the generally linear segment has a proximal portion that is generally devoid of electrodes and the catheter includes a control handle to deflect the catheter along the generally linear segment of the mapping assembly.

In another embodiment, electrodes are carried on both the generally linear segment and the generally circular segment. In a more detailed embodiment, the generally linear segment has a length of about 30 mm and the generally circular main segment has an outer diameter of about 25 mm. Moreover, both the generally linear segment and the generally circular main segment may each carry at least five ring electrode pairs.

The present invention also includes a method for mapping electrical activity of wall tissue near a tubular region of or near the heart, the method using a catheter in accordance with the present invention. In one embodiment, the method includes inserting the generally circular segment of a catheter in accordance with the present invention into a tubular region of or near the heart, releasably anchoring the generally circular segment in the tubular region near its ostium, contacting the generally linear segment of the catheter generally along its length with wall tissue near the ostium, and mapping the electrical activity of the wall tissue along a linear pattern extending radially from the ostium. The method may also include rotating the mapping assembly about the ostium and mapping the electrical activity of the wall tissue along a different linear pattern extending radially from the ostium. The tubular region is selected from the group consisting of pulmonary veins, the coronary sinus, the superior vena cava, and the inferior vena cava.

### BRIEF DESCRIPTION OF THE DRAWINGS

These and other features and advantages of the present invention will be better understood by reference to the following detailed description when considered in conjunction with the accompanying drawings wherein:

FIG. 1 is a side view of an embodiment of the catheter of the present invention.

FIG. 2 is a side cross sectional view of the catheter body of FIG. 1, including the junction between the catheter body and the intermediate section.

FIG. 3 is a side cross sectional view of the catheter body of FIG. 1, including the junction between the intermediate section and the mapping assembly.

FIG. 4 is a schematic perspective view of an embodiment of the mapping assembly according to the present invention.

FIG. 5 is a schematic perspective view of the mapping assembly of FIG. 4 with its distal portion releasably anchored in a tubular region and its proximal portion generally lying against tissue surrounding the tubular region.

FIG. 6 is a side cross sectional view of an embodiment of the junction between the proximal region and the distal region of the mapping assembly.

FIG. 6a is a cross sectional view taken along 6A-6A in FIG. 6.

FIG. 6b is a side cross sectional view of an embodiment of the junction between the proximal region and the distal region of the mapping assembly, having lead wires for electrodes on the distal region.

FIG. 7 is a side view of an embodiment of the mapping assembly according to the present invention in a clockwise formation.

FIG. 8 is a side view of the mapping assembly of FIG. 7 in a counterclockwise formation rotated 90 degrees.

FIG. 9 is a schematic view of an embodiment of the mapping assembly according to the present invention.

FIG. 10 is a schematic view of the mapping assembly according to the present invention depicting the relationship between two electrodes.

FIG. 11 is a schematic view of an alternative embodiment of the mapping assembly according to the present invention.

FIG. 12 is a schematic view of another alternative embodiment of the mapping assembly according to the present invention.

FIG. 13 is a schematic view of yet another alternative embodiment of the mapping assembly according to the present invention.

FIG. 14 is a side view of an alternative embodiment of the catheter of the present invention.

FIG. 15 is a schematic perspective view of an embodiment of the mapping assembly of FIG. 14.

FIG. 15a is a cross sectional view taken along line 15A-15A in FIG. 15.

FIG. 16 is a side cross sectional view of the catheter body of FIG. 1, including the junction between the catheter body and the mapping assembly.

FIG. 17 is a side cross sectional view of an alternative embodiment of the junction between the proximal and distal regions of the mapping assembly, with lead wires for electrodes carried on the distal region.

FIG. 17a is a cross sectional view taken along lines 17a-17a in FIG. 17.

FIG. 17b is a side cross sectional view of an alternative embodiment of the junction between the proximal and distal regions of the mapping assembly.

### DETAILED DESCRIPTION OF THE INVENTION

In a disclosed embodiment of the invention, there is provided a catheter 10 having a mapping assembly at its distal end. As shown in FIG. 1, the catheter comprises an elongated catheter body 12 having proximal and distal ends, an intermediate section 14 at the distal end of the catheter body, a

control handle 16 at the proximal end of the catheter body, and a mapping assembly 17 mounted at the distal end of the catheter to the intermediate section 14.

With reference to FIG. 2, the catheter body 12 comprises an elongated tubular construction having a single, axial or central lumen 18. The catheter body 12 is flexible, i.e., bendable, but substantially non-compressible along its length. The catheter body 12 can be of any suitable construction and made of any suitable material. A presently preferred construction comprises an outer wall 20 made of polyurethane or PEBAX. The outer wall 20 comprises an imbedded braided mesh of stainless steel or the like to increase torsional stiffness of the catheter body 12 so that, when the control handle 16 is rotated, the intermediate section 14 of the catheter 10 will rotate in a corresponding manner.

The outer diameter of the catheter body 12 is not critical, but is preferably no more than about 8 french, more preferably 7 french. Likewise the thickness of the outer wall 20 is not critical, but is thin enough so that the central lumen 18 can accommodate a puller wire, lead wires, and any other desired wires, cables or tubings. If desired, the inner surface of the outer wall 20 is lined with a stiffening tube (not shown) to provide improved torsional stability. A disclosed embodiment, the catheter has an outer wall 20 with an outer diameter of from about 0.090 inch to about 0.94 inch and an inner diameter of from about 0.061 inch to about 0.065 inch.

With further reference to FIG. 2, the intermediate section 14 comprises a short section of tubing 22 having three lumens. The first lumen 30 electrode carries lead wires 50 and the second lumen 32 carries a puller wire 64. There may also be third lumen 34. The tubing 22 is made of a suitable non-toxic material that is preferably more flexible than the catheter body 12. A suitable material for the tubing 22 is braided polyurethane, i.e., polyurethane with an embedded mesh of braided stainless steel or the like. The size of each lumen is not critical, but is sufficient to house the lead wires or the puller wire.

The useful length of the catheter, i.e., that portion that can be inserted into the body excluding the mapping assembly 17, can vary as desired. In one embodiment, the useful length ranges from about 110 cm to about 120 cm. The length of the intermediate section 14 is a relatively small portion of the useful length, and preferably ranges from about 3.5 cm to about 10 cm, more preferably about 4 cm to about 8 cm, and still more preferably about 6.5 cm.

A preferred means for attaching the catheter body 12 to the intermediate section 14 is illustrated in FIG. 2. The proximal end of the intermediate section 14 comprises an outer circumferential notch 26 that receives the inner surface of the outer wall 20 of the catheter body 12. The intermediate section 14 and catheter body 12 are attached by glue or the like.

If desired, a spacer (not shown) can be located within the catheter body between the distal end of the stiffening tube (if provided) and the proximal end of the intermediate section. The spacer provides a transition in flexibility at the junction of the catheter body and intermediate section, which allows this junction to bend smoothly without folding or kinking. A catheter having such a spacer is described in U.S. Pat. No. 5,964,757, the disclosure of which is incorporated herein by reference.

Within the intermediate section 14, the puller wire 64 extends into the second lumen 32. Preferably the puller wire 64 is anchored at its distal end to the distal end of the intermediate section 14, as shown in FIG. 3. Specifically, a T-shaped anchor is formed, which comprises a short piece of tubular stainless steel 80, e.g., hypodermic stock, which is fitted over the distal end of the puller wire 64 and crimped to

fixedly secure it to the puller wire. The distal end of the tubular stainless steel **80** is fixedly attached, e.g., by welding, to a cross-piece **82** formed of stainless steel ribbon or the like. The cross-piece **82** extends through a hole formed in the outer wall and because the cross-piece **82** is larger than the hole and, therefore, cannot be pulled through the hole, the cross-piece **82** anchors the distal end of the puller wire **64** to the distal end of the intermediate section **14**. Within the second lumen **32** of the intermediate section **14**, the puller wire **64** extends through a plastic, preferably Teflon™, puller wire sheath (not shown), which prevents the puller wire **64** from cutting into the wall of the intermediate section **14** when the intermediate section is deflected. It is understood that the puller wire **64** enables the catheter to deflect generally along the length of the intermediate section **14**.

Longitudinal movement of the puller wire **64** relative to the catheter body **12**, which results in deflection of the intermediate section **14** and generally the mapping assembly **17**, is accomplished by suitable manipulation of the control handle **16**. Examples of suitable control handles for use in the present invention are disclosed, for example, in U.S. Pat. Nos. Re 34,502 and 5,897,529, the entire disclosures of which are incorporated herein by reference.

At the distal end of the intermediate section **14** is a mapping assembly **17**, as shown in FIGS. 4 and 5. The mapping assembly comprises a more flexible, generally straight proximal region **38** and a less flexible but pre-shaped distal region **40** having a straight proximal segment **42**, a transitional segment **44** and a generally circular main segment **46**.

The proximal region **38** is mounted on the distal end of the intermediate section **14**, as described in more detail below, so that its axis is generally parallel to the axis of the intermediate section, and preferably has an exposed length, e.g., not contained within the intermediate section **14**, ranging from about 20 mm to about 70 mm, more preferably about 25 mm to about 50 mm, still more preferably about 42 mm, but can vary as desired.

As illustrated in FIGS. 3 and 6, the proximal region **38** comprises a tubing **39** which can be made of any suitable material that is flexible and biocompatible and preferably plastic, such as polyurethane or PEBAX. The tubing **39** may have any cross-sectional shape and may have a single lumen or multiple lumens and is generally free of any interior support members although its lumen is occupied by lead wires **50** or other electrical connections for electrodes or any other electrical or electromagnetic elements that may be mounted on the mapping assembly **17**. A preferred means for attaching the tubing **39** to the intermediate section **14** is illustrated in FIG. 3. The proximal end of the tubing **39** extends over and overlaps with the distal end of the tubing **22**. Glue or the like is applied between the contacting inner surface of the tubing **39** and outer surface of the tubing **22**. Additional glue may be applied immediately proximal of the proximal end of the section **38** to form a seal **41**.

As shown in FIGS. 4 and 5, a series of paired ring electrodes **36** are mounted on the tubing **39** of the proximal region **38**. The ring electrodes **36** can be made of any suitable solid conductive material, such as platinum or gold, preferably a combination of platinum and iridium, and mounted onto the tubing **39** with glue or the like. Alternatively, the ring electrodes can be formed by coating the tubing **39** with an electrically conducting material, like platinum, gold and/or iridium. The coating can be applied using sputtering, ion beam deposition or an equivalent technique.

In a preferred embodiment with reference to FIG. 6, each ring electrode **36** is mounted by first forming a hole in the tubing **39**. An electrode lead wire **50** is fed through the hole,

and the ring electrode **36** is welded in place over the lead wire and tubing **39**. The lead wires **50** extend through the tube **39**. The proximal end of each lead wire **50** is electrically connected to a suitable connector **37** (FIG. 1), which is connected to a source of RF energy (not shown).

The number of the ring electrodes **36** on the assembly **17** can vary as desired. Preferably, the number of ring electrodes ranges from about six to about twenty, preferably from about eight to about twelve. In a disclosed embodiment, the assembly carries ten ring electrodes forming five pairs. The pairs of ring electrodes **36** are preferably approximately evenly spaced along the proximal region **38**, as best shown in FIG. 4. In a disclosed embodiment, a distance of approximately 5 mm is provided between each pair of the ring electrodes **36**, with each electrode within a pair separated by a distance of about 1 mm. Advantageously, the proximal region **38** includes a proximal segment **38a** which is generally devoid of electrodes such that the mapping assembly **17** can generally lie against wall tissue, as shown in FIG. 5. In particular, the proximal segment **38a** enables the distal end of the intermediate section **14** and the proximal end of the mapping assembly **17** (e.g., the proximal segment **38a**) to define an angle phi therebetween ranging between about 45 degrees and about 315 degrees. The proximal segment **38a** may have a length ranging between about 0.5 inch and about 2.0 inches, and more preferably about 1.0 inch.

As for the distal region **40** of the assembly **17**, the straight segment **42** is mounted on the distal end of the proximal region **38**, as described in more detail below, so that its axis is generally parallel to the axis of the proximal region **38** and preferably has an exposed length, e.g., not contained within the proximal region **38**, ranging from about 10-20, more preferably about 15 mm, but can vary as desired.

The generally circular main segment **46** is generally traverse to the catheter body **12** and is preferably generally perpendicular to the catheter body **12**. The generally circular main segment need not form a flat circle, but can be very slightly helical, as shown in FIGS. 4, 7 and 8. The main segment **46** has an outer diameter preferably ranging to about 10 mm to about 35 mm, more preferably about 15 mm to about 30 mm, still more preferably about 25 mm. The transition segment **44** between the segments **42** and **46** is slightly curved and formed such that, when viewed from the side with the segment **42** at the top of the circular main segment **46** as shown in FIG. 7, the proximal segment **42** (along with the proximal region **38**) forms an angle .alpha. with the circular main segment **46** ranging from about 75.degree. to about 95.degree., preferably from about 83.degree. to about 93.degree., more preferably about 87.degree. The main region segment **46** can curve in a clockwise direction, as shown in FIG. 7 or a counterclockwise direction, as shown in FIG. 8. When the assembly **17** is turned 90.degree., as shown in FIG. 8, so that the transition segment **44** is near the center of the main segment **46**, the proximal segment **42** (along with the proximal region **38**) forms an angle .beta. with the main circular segment **46** ranging from about 90.degree. to about 135.degree., preferably from about 100.degree. to about 110.degree., more preferably about 105.degree.

As illustrated in FIG. 6, the distal region **40** of the mapping assembly **17** is formed from a support member **54** covered by a non-conductive covering **56**. The support member **54** is made of a material having shape-memory, i.e., that can be straightened or bent out of its original shape upon exertion of a force and is capable of substantially returning to its original shape upon removal of the force. A suitable material for the support member **54** is a nickel/titanium alloy. Such alloys typically comprise about 55% nickel and 45% titanium, but

may comprise from about 54% to about 57% nickel with the balance being titanium. A preferred nickel/titanium alloy is nitinol, which has excellent shape memory, together with ductility, strength, corrosion resistance, electrical resistivity and temperature stability. The non-conductive covering **56**

A means for attaching the distal region **40** to the proximal region **38** is illustrated in FIG. **6**. At the proximal end of the distal region **40**, a stainless steel tubing **71** is welded onto the distal end of the support member **54** at their respective contacting surface **75**. A proximal end of the tubing **71** is flattened or otherwise shaped to form a spade **73** with an elongated cross-section (FIG. **6A**) which anchors the proximal end of the distal region **40** in the distal end of the proximal region **38**. In particular, the spade **73** sits within a cored-out distal end of the tubing **39** forming a notch **84**. Glue or the like is applied to the distal end of the tubing **39** to form a plug **53** sealing the region of attachment. As such, the elongated cross-section of the spade **73** anchors the distal region **40** against rotational movement about the axis of the support member **54** relative to the proximal region **38**. Moreover, a base **86** of the spade **73** anchors the distal region **40** against distal movement relative to the proximal region **38**.

The proximal end of the support member **54** and the non-conductive covering **56** terminate a short distance within the lumen of the tubing **39** of the proximal section **38**, approximately about 5 mm, so as not to adversely affect the flexibility of the proximal section **38**.

Because the proximal region **38** is generally without any internal structure other than lead wires **50** from the electrodes or perhaps a second puller wire for changing the diameter of the circular segment **46**, the proximal region **38** is more flexible than either the tip section **14** or the distal region **40**. In that regard, the tubing **39** has a flexibility durometer rating lesser than either the intermediate section **14** or the distal region **40** and ranging between about 35D to 60D, more preferably about 55D. The lesser flexibility of the tip section **14** and the distal region **40** relative to the proximal region **38** (due to the underlying tubing structure and/or internal structures or wires extending therethrough) enables the user to manipulate the mapping assembly **17** to reach the target site, and further to manipulate the circular segment **46** to enter into and releasably anchor itself in a tubular region, e.g., a pulmonary vein. With a greater flexibility, the proximal region **38** can then be manipulated to generally lie flat against wall tissue around an ostium of the tubular region, as shown in FIG. **5**. In accordance with a feature of the present invention, the proximal region **38** has greater softness, floppiness and/or flexibility relative to the intermediate section **14** and the distal region **40** of the mapping assembly **17**.

If desired, additional electrodes **58** could be mounted along the circular segment of the distal region distal region **40**. FIG. **9** shows one electrode arrangement for the circular segment **39**. As explained above, the generally circular main segment **39** is very slightly helical, although FIGS. **9** and **11** depict the main segment **39** as a flat circle, as it would generally appear when viewed from the distal end of the catheter. Referring to both FIGS. **9** and **10**, a first ring electrode **58a** is provided, which is the electrode that is on the generally circular main segment **46** closest to the transitional segment **44**. A second electrode **58b** is provided, which is the electrode that is on the generally circular main segment **46** adjacent its tangent location **43** (FIG. **10**). Preferably, the first electrode **58a** is positioned along the circumference of the generally circular main segment **46** at a distance  $\omega$  of no more than about 55.degree. from the tangent location **43**, more preferably no

more than about 48.degree. from the tangent location, still more preferably from about 15.degree. to about 36.degree. from the tangent location. Preferably the second electrode **58b** is positioned along the circumference of the generally circular main segment at a distance  $\omega$  of no more than about 55.degree. degrees from the tangent location, more preferably no more than about 48.degree. from the tangent location **43**, still more preferably from about 15.degree. to about 36.degree. from the tangent location. Preferably the first electrode **58a** is positioned along the circumference of the generally circular segment at a distance  $\gamma$  of no more than 100.degree. from the second electrode **58b**, preferably no more than 80.degree. from the second electrode, still more preferably from about 30.degree. to about 75.degree. from the second electrode. There is also shown an electrode **58c** in FIG. **9**, which is longer than the other ring electrodes, preferably having a length ranging from about 1 mm to about 1.5 mm. The longer ring electrode provides a signal to the user when the catheter is being viewed under fluoroscopy. By having one ring electrode, such as the electrode **58c**, sized differently from the other ring electrodes, the user has a reference point when viewing the catheter under fluoroscopy.

FIG. **11** shows another electrode arrangement for the main segment **46** where generally the single ring electrodes **58** have been configured into electrode pairs **57**. It is understood that lead wires **50b** for the electrodes **58** may extend parallel with the support member **58** through the nonconductive covering **58** of the distal region **40** and through the lumen of the tubing **39** of the proximal region **38**, as shown in FIG. **6b**.

As shown in the embodiment of FIGS. **1-11**, the distal end of the generally circular segment **46** may be capped, preferably with polyurethane glue, to form an atraumatic cap **61** (FIGS. **4** and **5**) and to prevent body fluids from entering the mapping assembly **17**.

In an alternative design as shown in FIGS. **12** and **13**, the mapping assembly **17** includes a generally straight distal segment **48** which forms a tangent relative to the generally circular segment and contacts the main segment at the tangent location. The generally straight distal segment **48** is provided with an atraumatic design to prevent the distal end of the mapping assembly **17** from penetrating tissue. In the depicted embodiment, the distal segment comprises a tightly wound coil spring **44** made, for example, of stainless steel, such as the mini guidewire commercially available from Cordis Corporation (Miami, Fla.) or a coil having a 0.0045 inch wire size and a 0.009 inch inner diameter, such as that commercially available from Microspring. The coil spring **44** is mounted at its proximal end in a short piece of tubing **55** with polyurethane glue or the like, which is then glued or otherwise anchored within the non-conductive covering. The tubing **55** is less flexible than the nonconductive covering **56** but more flexible than that support member **54** to provide a transition in flexibility along the length of the mapping assembly **17**. The distal end of the distal segment **40** is capped, preferably with polyurethane glue **65**, to prevent body fluids from entering the mapping assembly **17**.

In the depicted embodiment, the generally straight distal segment **48** has a length of about 0.5 inch, but can be any desired length, for example, ranging from about 0.25 inch to about 1.0 inch. The generally straight distal segment **48** is preferably sufficiently long to serve as an anchor for introducing the catheter into a guiding sheath, as discussed in more detail below, because the mapping assembly **17** must be straightened upon introduction into the sheath. Without having the generally straight distal segment **48** as an anchor, the mapping assembly **17** has a tendency to pull out of the guiding

sheath upon its introduction into the guiding sheath. Any other atraumatic tip design that prevents the distal end of the mapping assembly from penetrating tissue could be provided. An alternative design in the form of a plastic ball is described in copending patent application Ser. No. 09/370,605, entitled “ATRIAL BRANDING IRON CATHETER AND METHOD FOR TREATING ATRIAL FIBRILLATION”, the entire disclosure of which is incorporated herein by reference. Additionally, if desired, the distal segment **48** can be formed, at least in part, of a radiopaque material to aid in the positioning of the mapping assembly **17** under fluoroscopy. A suitable and similar distal segment is disclosed in U.S. Pat. No. 6,711,428, the entire disclosure of which is incorporated by reference.

The lead wires **50** attached to the ring electrodes **36** extend through the lumen of the tubing **39** of the proximal region **38** (FIG. 6), through the first lumen **30** of the intermediate section **14** (FIG. 3), through the central lumen **18** of the catheter body **12** (FIG. 2), and the control handle **16**, and terminate at their proximal end in the connector **37** (FIG. 1). The portion of the lead wires **50** extending through the central lumen **18** of the catheter body **12**, control handle **16** and proximal end of the intermediate section **14** are enclosed within a protective sheath **62** (FIG. 2), which can be made of any suitable material, preferably polyimide. The protective sheath **62** is anchored at its distal end to the proximal end of the intermediate section **14** by gluing it in the first lumen **30** with polyurethane glue or the like.

The puller wire **64** is provided for deflection of the intermediate section **14**. The puller wire **64** extends through the catheter body **12** (FIG. 2) and the second lumen **32** of the intermediate section **14** (FIG. 3). The puller wire **64** is anchored at its proximal end to the control handle **16**, and is anchored at its distal end to the intermediate section **14**. The puller wire **64** is made of any suitable metal, such as stainless steel or Nitinol, and is preferably coated with Teflon™, or the like. The coating imparts lubricity to the puller wire **64**. The puller wire **64** preferably has a diameter ranging from about 0.006 to about 0.010 inch.

As shown in FIG. 2, a compression coil **66** is situated within the catheter body **12** in surrounding relation to the puller wire **64**. The compression coil **66** extends from the proximal end of the catheter body **12** to the proximal end of the intermediate section **14**. The compression coil **66** is made of any suitable metal, preferably stainless steel. The compression coil **66** is tightly wound on itself to provide flexibility, i.e., bending, but to resist compression. The inner diameter of the compression coil **66** is preferably slightly larger than the diameter of the puller wire **64**. The Teflon™ coating on the puller wire **64** allows it to slide freely within the compression coil **66**. The outer surface of the compression coil **66** is covered by a flexible, non-conductive sheath **68**, e.g., made of polyimide tubing.

The compression coil **66** is anchored at its proximal end to the outer wall **20** of the catheter body **12** by proximal glue joint **70** and at its distal end to the intermediate section **14** by distal glue joint **72**. Both glue joints **70** and **72** preferably comprise polyurethane glue or the like. The glue may be applied by means of a syringe or the like through a hole made between the outer surface of the catheter body **12** and the central lumen **18**. Such a hole may be formed, for example, by a needle or the like that punctures the outer wall **20** of the catheter body **12** which is heated sufficiently to form a permanent hole. The glue is then introduced through the hole to the outer surface of the compression coil **66** and wicks around the outer circumference to form a glue joint about the entire circumference of the compression coil.

In use, a suitable guiding sheath is inserted into the patient with its distal end positioned at a desired mapping location, for example, the left atrium of the heart. An example of suitable guiding sheath for use in connection with the present invention is the Preface™. Braiding Guiding Sheath, commercially available from Cordis Webster (Diamond Bar, Calif.). The distal end of the sheath is guided into one of the atria. A catheter in accordance with the present invention is fed through the guiding sheath until its distal end extends out of the distal end of the guiding sheath. As the catheter is fed through the guiding sheath, the mapping assembly **17** is straightened to fit through the sheath. Once the distal end of the catheter is positioned at the desired mapping location, the guiding sheath is pulled proximally, allowing the deflectable intermediate section **14** and mapping assembly **17** to extend outside the sheath, and the distal region **40** of the mapping assembly **17** returns to its original shape due to the shape-memory of the support member **54**. The distal region **40** of the mapping assembly **17**, in particular, the generally circular main segment **46** (with or without the distal segment **48**) is then inserted into a pulmonary vein **70** (FIG. 5) so that the outer circumference of the generally circular main segment **46** of the assembly is in contact with a circumference inside the tubular region. Preferably at least about 50%, more preferably at least about 70%, and still more preferably at least about 80% of the circumference of the generally circular main segment **46** is in contact with a circumference inside the tubular region. As such, the circular segment **46** is therefore releasably anchored in the tubular region, e.g., a pulmonary vein **70** which enables the more flexible proximal region **38** carrying the electrodes **36** to contact and lay flat against wall tissue near and surrounding an ostium **72** or extending between the ostium **72** and another ostium **74** of another pulmonary vein. Consequently, a user can bridge the linear gap between pulmonary veins for mapping and/or ablation purposes with one placement of the catheter instead of multiple placements. Benefits thereof include the ability to guide burns to locations that do not show yet a complete lesion and the ability to obtain a complete linear lesion with fewer burns. In particular, the configuration including the length of the proximal region **38** enables the proximal region **38** to serve as a generally linear template or guide against which another catheter tip can be moved along.

The releasable anchoring and stabilization provided by the circular segment **46** generally enables the distal region **40** to remain relatively stationary in the tubular region while the proximal region **38** can be manipulated to rotate about the ostium **72** so as to sweep a circular region around the ostium **72**. For example, if an angle zero is defined by an axis extending between the ostia **72** and **74**, the proximal region **38** may be manipulated to sweep out 360 degrees around the ostium **72**. With the generally linear mapping configuration of the electrodes **36** carried on the proximal region **38**, a multitude of radially extending linear mappings can be accomplished about the ostium **72** as the proximal region **38** is rotated about the ostium **72**. Moreover, when such linear mappings are completed, the circular segment **46** can be inserted into the ostium **74** where a multitude of radially extending linear mappings can be accomplished about the ostium **74**.

Where the circular segment **46** carries the electrodes **58**, the circular arrangement of the electrodes **58** permits measurement of the electrical activity at that circumference of the tubular structure so that ectopic beats between the electrodes **58** can be identified. The size of the generally circular main segment **46** permits measurement of electrical activity along a diameter of a pulmonary vein or other tubular structure of or near the heart because the circular main segment has a diam-



eter generally corresponding to that of a pulmonary vein or the coronary sinus. Additionally, because the main segment **46** need not form a flat circle, but can be somewhat helical, it is easier for the user to guide the mapping assembly **17** into a tubular region.

In an alternative embodiment of the present invention, the catheter **10** of FIGS. **14-17**, where similar components are designated by similar reference numerals, generally except as discussed herein, the distal end of the catheter body **12** is joined with the proximal end of a mapping assembly **17'** having a proximal region **38'** and a distal region **40**. The useful length of the catheter may range between about 110 cm and about 120 cm, and more preferably about 115 cm.

In the illustrated embodiment, the proximal region **38'** is more flexible than either the catheter **12** and the mapping assembly **17'** and includes an elongated proximal segment **38a'** that is generally devoid of electrodes serving generally the same function as describe hereinabove in relation to the segment **38a**. The proximal region **38'** comprises a tubing **39'** having a length ranging between about 60 mm and about 70 mm and preferably about 65 mm having at least three lumens **130**, **132** and **134**, which may or may not of equal size but may be about 0.025 inches in diameter. There may also be a fourth lumen **136** which may be occupied by other wires or tubing. In one embodiment, the tubing **39'** comprises pellathane and barium sulfate. In particular, the tubing **39'** comprises pellathane of two different durometer rating and barium sulfate. In a particularly preferred embodiment, the tubing **39'** comprises about 53% pellathane of about 55D durometer, about 10% pellathane of 80A durometer (where A is a lower level hardness scale than D, which defines 80A as softer than 55D), about 36% barium sulfate and about 1% color and other components for use in the extrusion of the tubing **39'**. It is understood that the barium sulfate is used for radio-opacity. In general, the proximal region **38'** is less flexible than the aforementioned proximal region **38** in the first embodiment. Surrounding the tubing **39'** may be a stainless steel braid tubing **100** for increasing torque and stiffness in the tubing **39'**.

Extending through the lumen **130** of the tubing **39'** are lead wires **50a** for the ring electrodes **36** on the proximal region **38'**. The ring electrode pairs on the proximal region **38'** are generally spaced apart a distance of about 5 mm, with each electrode within a pair separated by a distance of about 1.0 mm. Extending through the lumen **132** is the puller wire **64** whose distal end is anchored to the distal end of the proximal tubing **39'** by means of the tubular stainless steel **80** and cross-piece **82**. Accordingly, in this embodiment, it is understood that the puller wire **64** enables the catheter to deflect generally along the length of the proximal region **38'**. Extending through the lumen **134** are lead wires **50b** for the electrodes **57** on the generally circular segment **46** of the distal region **40**. The lead wires **50b** extend alongside the support member **54** and the spade **73** and inside the covering **56** and then through the lumen **134** of the tubing **39**. The lead wires then may extend further proximally through a nonconductive sheath **62b** whose distal end terminates at the proximal end of the tubing **39**. Any other additional wires (such as a contraction wire for the segment **46**), or tubing (such as an irrigation tubing) may extend through the lumen **136**.

It is understood by one of ordinary skill in the art that the distal region **40** may assume other embodiments and configurations. For example, other suitable anchoring mechanisms may include balloons, deflectable tips, expanding mechanisms or needle-type anchoring mechanisms. There may be a pre-curve set in the distal portion of the catheter to allow the floppy proximal region **38** to flop in a desired plane. In that

regard, a passive bend shape is added to the catheter by cooking it at high temperature (but below melting temperature) while bent in the desired shape. It allows for easier catheter placement in specific anatomy, if the pre-curve is optimized for that anatomy, and it also makes the catheter predisposed to bending in a particular manner during active deflection.

If desired, two or more puller wires can be provided to enhance the ability to manipulate the intermediate section **14**. In such an embodiment, a second puller wire and a surrounding second compression coil extend through the catheter body and into an additional off-axis lumen in the intermediate section. The first puller wire is preferably anchored proximal to the anchor location of the second puller wire. Suitable designs of catheters having two or more puller wires, including suitable control handles for such embodiments, are described, for example, in U.S. patent application Ser. No. 08/924,611, filed Sep. 5, 1997; Ser. No. 09/130,359; filed Aug. 7, 1998; Ser. No. 09/143,426, filed Aug. 28, 1998; and Ser. No. 09/157,055, filed Sep. 18, 1998, the disclosures of which are incorporated herein by reference.

Moreover, the control handle can be configured with a contraction wire to manipulate a contraction of the circular segment **46**. The support member **54** is pre-shaped with a curvature ranging between about 340 degrees and 380 degrees, and more preferably about 360 degrees, between the proximal end of the circular segment **46** (at the junction with the distal end of the transition segment **44**) and the distal end of the circular segment **46**. With manipulation of the contraction wire, the diameter of the circular segment is contracted to increase the degree of curvature. The distal end of the circular segment **46** is drawn toward the proximal end by the contraction wire whose distal end is attached to the distal end of the circular segment **46** and whose proximal end is in the control handle. A suitable contraction wire and controlling mechanism are disclosed in pending application U.S. Ser. Nos. 10/386,872 and 10/386,594, the entire disclosures of which are incorporated herein.

The preceding description has been presented with reference to presently preferred embodiments of the invention. Workers skilled in the art and technology to which this invention pertains will appreciate that alterations and changes in the described structure may be practiced without meaningfully departing from the principal, spirit and scope of this invention and that the drawings may not be to scale.

Accordingly, the foregoing description should not be read as pertaining only to the precise structures described and illustrated in the accompanying drawings, but rather should be read consistent with and as support to the following claims which are to have their fullest and fair scope.

What is claimed is:

1. A mapping catheter adapted for mapping near a tubular region of a heart, comprising:

an elongated tubular catheter body having an outer wall, proximal and distal ends, and at least one lumen extending therethrough;

an intermediate section having proximal and distal ends, the intermediate section being distal of the catheter body; and

a mapping assembly at the distal end of the intermediate section, the mapping assembly having:

a generally circular main segment with a support member having shape-memory disposed within at least the main segment of the mapping assembly,

a generally linear segment proximal the generally circular main segment, the generally linear segment having

## 13

greater flexibility than either of the intermediate section and the generally circular main segment, and a plurality of ring electrodes on the generally linear segment, wherein the generally circular main segment is adapted to releasably anchor itself in the tubular region and wherein the generally linear segment is adapted to contact generally along its length heart wall tissue near an ostium of the tubular region.

2. A catheter according to claim 1, further comprising a second plurality of electrodes on the generally circular main segment.

3. A catheter according to claim 1, wherein the proximal segment carrying the electrodes is adapted to conduct mapping of said wall tissue along a linear pattern extending radially from the ostium.

4. A catheter of claim 3, wherein the mapping assembly is adapted to be rotated about the ostium to perform mapping of said wall tissue along different radially-extending linear patterns about the ostium.

5. A catheter of claim 1, wherein the support member is nitinol.

6. A catheter of claim 1, wherein the generally linear segment comprises a tubing with flexibility durometer rating of about 55 D.

7. A catheter of claim 1, wherein the generally linear segment has an exposed length ranging between about 30 mm to 70 mm.

8. A catheter of claim 1, wherein the generally linear segment has an exposed length of about 30 mm.

9. A catheter of claim 1, further comprising a first puller wire to manipulate deflection of the intermediate section.

10. A catheter of claim 1, wherein the mapping assembly further comprises a generally straight distal segment distal of the generally circular segment.

11. A catheter of claim 1, wherein the generally circular main segment has an outer diameter ranging to about 10 mm to about 35 mm.

12. A catheter of claim 1, wherein the generally circular main region has an outer diameter ranging between about 12 mm to about 20 mm.

13. A catheter of claim 1, wherein the plurality of ring electrodes comprises a plurality of ring electrode pairs, wherein a number of ring electrode pairs along the generally linear proximal segment ranges from about two to about twenty.

14. A catheter of claim 1, comprising ten ring electrode pairs along the generally linear segment.

15. A catheter of claim 1, further comprising additional ring electrodes carried on the generally circular segment.

16. A catheter according to claim 1, further comprising means for deflecting the intermediate section without altering the shape of the mapping assembly.

17. A catheter according to claim 16, wherein the deflecting means comprises:

- a puller wire extending through a lumen of the catheter body, said puller wire being fixedly attached at its distal end to the intermediate section near the distal end of the intermediate section; and
- a control handle for moving the puller wire longitudinally relative to the catheter body to thereby cause deflection of at least the intermediate section.

18. A catheter of claim 1, wherein the generally linear segment of the mapping assembly comprises an elongated proximal segment that is generally devoid of electrodes and adapted to define an angle with the intermediate section ranging between about 45 degrees to about 315 degrees.

## 14

19. A method for mapping electrical activity of wall tissue near a tubular region of or near the heart, the method comprising:

- inserting the generally circular segment of a catheter according to claim 1 into a tubular region of or near the heart;
- releasably anchoring the generally circular segment in the tubular region near its ostium;
- contacting the generally linear segment of the catheter generally along its length with wall tissue near the ostium; and
- mapping the electrical activity of the wall tissue along a linear pattern extending radially from the ostium.

20. A method of claim 19, further comprising:

- rotating the mapping assembly about the ostium and mapping the electrical activity of the wall tissue along a different linear pattern extending radially from the ostium.

21. A method according to claim 19, wherein the tubular region is selected from the group consisting of pulmonary veins, the coronary sinus, the superior vena cava, and the inferior vena cava.

22. A method according to claim 19, wherein the tubular region is a pulmonary vein.

23. A mapping catheter adapted for mapping near a tubular region of a heart, comprising:

- an elongated tubular catheter body having an outer wall, proximal and distal ends, and at least one lumen extending therethrough;
- an intermediate section having proximal and distal ends, the intermediate section being distal of the catheter body; and
- a mapping assembly at the distal end of the intermediate section, the mapping assembly having a distal portion and a generally linear segment proximal the distal portion, the generally linear segment having greater flexibility than either of the intermediate section and the distal portion, and a plurality of ring electrodes carried on the generally linear segment,

wherein the distal portion is adapted to releasably anchor itself in the tubular region and wherein the generally linear segment is adapted to contact generally along its length heart wall tissue near an ostium of the tubular region.

24. A catheter according to claim 23, wherein the proximal segment carrying the electrodes is adapted to conduct mapping of said wall tissue along a linear pattern extending radially from the ostium.

25. A catheter of claim 24, wherein the mapping assembly is adapted to be rotated about the ostium to perform mapping of said wall tissue along different radially-extending linear patterns about the ostium.

26. A catheter of claim 23, wherein the generally linear segment comprises a tubing with flexibility durometer rating of about 55 D.

27. A catheter of claim 23, wherein the generally linear segment has an exposed length ranging between about 30 mm to 70 mm.

28. A catheter of claim 23, wherein the generally linear segment has an exposed length of about 42 mm.

29. A catheter of claim 23, further comprising a first puller wire to manipulate deflection of the intermediate section.

30. A mapping catheter adapted for mapping near a tubular region of a heart, comprising:

- an elongated tubular catheter body having an outer wall, proximal and distal ends, and at least one lumen extending therethrough;

15

a mapping assembly distal of the distal end of the catheter body, the mapping assembly having:

a generally circular main segment with a support member having shape-memory disposed within at least the main segment of the mapping assembly,

a generally linear segment proximal the generally circular main segment, the generally linear segment having greater flexibility than both the catheter body and the generally circular main segment, and

a plurality of ring electrodes on the generally linear segment,

wherein the generally circular main segment is adapted to releasably anchor itself in the tubular region and wherein the generally linear segment is adapted to contact generally along its length heart wall tissue near an ostium of the tubular region.

**31.** A catheter according to claim **30**, further comprising a second plurality of electrodes on the generally circular main segment.

16

**32.** A catheter according to claim **30**, wherein the generally linear segment carrying the electrodes is adapted to conduct mapping of said wall tissue along a linear pattern extending radially from the ostium.

**33.** A catheter of claim **32**, wherein the linear segment is adapted to guide a second catheter to move along said linear pattern.

**34.** A catheter of claim **30**, wherein the mapping assembly is adapted to be rotated about the ostium to perform mapping of said wall tissue along different radially-extending linear patterns about the ostium.

**35.** A catheter of claim **34**, wherein the linear segment is adapted to guide a second catheter to move along said linear patterns.

**36.** A catheter of claim **30**, further comprising a puller wire to manipulate deflection of an intermediate section between the catheter body and the mapping assembly.

**37.** A catheter of claim **30**, further comprising a puller to manipulate deflection of the linear segment of the mapping assembly.

\* \* \* \* \*

UNITED STATES PATENT AND TRADEMARK OFFICE  
**CERTIFICATE OF CORRECTION**

PATENT NO. : 7,412,273 B2  
APPLICATION NO. : 10/990146  
DATED : August 12, 2008  
INVENTOR(S) : Pierre Jais

Page 1 of 2

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

**In the Drawings**

Fig. 14, Sheet 14 of 18

Delete Drawing Sheet 14 and substitute therefore the Drawing Sheet, consisting of Fig. 14, as shown on the attached page (Delete wording "Fig. 18")

Column 13, line 24, Claim 6


Delete "with flexibility",  
Insert --with a flexibility--

Column 14, line 54, Claim 26

Delete "with flexibility",  
Insert --with a flexibility--

Signed and Sealed this

Tenth Day of February, 2009



JOHN DOLL  
*Acting Director of the United States Patent and Trademark Office*




Fig. 14




Fig. 16