



US011759929B2

(12) **United States Patent**
Koenig et al.

(10) **Patent No.:** **US 11,759,929 B2**

(45) **Date of Patent:** **Sep. 19, 2023**

(54) **POWER TOOL SOUND DAMPING**

(71) Applicant: **Black & Decker Inc.**, New Britain, CT (US)

(72) Inventors: **Trevor Koenig**, Lancaster, PA (US); **Michael F. Cannaliato**, Bel Air, MD (US); **Brent Kuehne**, Red Lion, PA (US); **Anthony Reth**, Baltimore, MD (US); **Nicholas A. Mondich**, Baltimore, MD (US); **Steven McClaskey**, North Las Vegas, NV (US); **Xin Lei Wang**, Suzhou (CN); **Yufeng Chen**, Suzhou (CN); **Paul G. Gross**, White Marsh, MD (US); **Marco A. Mattucci**, Fallston, MD (US); **Ashok Samuel Baskar**, Lutherville, MD (US)

(73) Assignee: **Black & Decker Inc.**, New Britain, CT (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 401 days.

(21) Appl. No.: **16/901,658**

(22) Filed: **Jun. 15, 2020**

(65) **Prior Publication Data**

US 2020/0306942 A1 Oct. 1, 2020

Related U.S. Application Data

(63) Continuation of application No. 14/747,410, filed on Jun. 23, 2015, now Pat. No. 10,717,179, which is a continuation-in-part of application No. 14/444,982, filed on Jul. 28, 2014, now Pat. No. 10,022,848.

(30) **Foreign Application Priority Data**

Apr. 10, 2015 (WO) PCT/CN2015/076257

(51) **Int. Cl.**
B25C 1/06 (2006.01)
B25F 5/00 (2006.01)

(52) **U.S. Cl.**
CPC **B25C 1/06** (2013.01); **B25F 5/00** (2013.01)

(58) **Field of Classification Search**
CPC B25C 1/06; B25F 5/00
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,193,049 A *	7/1965	Wollek	F16F 9/306 428/152
3,263,770 A *	8/1966	Alm	B25D 17/12 181/230
3,807,281 A *	4/1974	Perkins	B25C 1/047 91/461
3,809,179 A *	5/1974	Delaney, Jr	B25F 5/00 181/230

(Continued)


Primary Examiner — Nathaniel C Chukwurah

Assistant Examiner — Lucas E. A. Palmer

(57) **ABSTRACT**

A power tool having one or more sound damping members which reduce sound and/or vibration from one or more parts of a power tool. The sound damping member can reduce sound and/or vibration from static or dynamic parts of a power tool. The sound damping member can reduce noise and/or vibration from one or more rotating or moving parts of a power tool and its housing or internal structure. Methods, means, controls, systems and practices for reducing or eliminating undesired sound from a power tool are disclosed.

20 Claims, 49 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

4,509,669	A *	4/1985	Elliesen	B25C 1/047 91/243	2010/0123359	A1 *	5/2010	Nishikawa	B25B 21/00 310/58
5,445,232	A *	8/1995	Brannstrom	B25D 17/28 173/100	2010/0181085	A1 *	7/2010	Imada	B25F 5/02 173/162.2
2003/0094294	A1 *	5/2003	Fritz	B25H 3/006 173/171	2011/0314589	A1 *	12/2011	Vito	A42B 1/08 2/181
2004/0219322	A1 *	11/2004	Fisher	B60R 13/08 428/40.1	2012/0160533	A1 *	6/2012	Kamegai	B25D 17/20 173/162.2
2006/0219418	A1 *	10/2006	Arakawa	B25F 5/006 173/162.1	2013/0092408	A1 *	4/2013	Oberheim	B25F 5/006 188/267.2
2007/0295522	A1 *	12/2007	Bohne	B25D 17/24 173/162.2	2014/0360744	A1 *	12/2014	Lawrence	B25B 23/1453 173/218
2008/0025017	A1 *	1/2008	Tadokoro	B25F 5/021 362/119	2016/0023342	A1 *	1/2016	Koenig	B25C 1/06 173/124
2008/0073095	A1 *	3/2008	Henriksson	B25D 17/24 173/162.2	2016/0377139	A1 *	12/2016	Vito	B32B 5/024 267/141
2008/0164043	A1 *	7/2008	Henriksson	B25D 17/24 173/162.1	2018/0187540	A1 *	7/2018	Hanski	E21B 49/003
					2020/0058281	A1 *	2/2020	Luoma	E21B 7/025
					2021/0053201	A1 *	2/2021	Mandal	B25B 21/02

* cited by examiner




FIG. 1





FIG. 2






FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 7A




FIG. 7B




FIG. 7C




FIG. 7C1




FIG. 7C2




FIG. 7D




FIG. 7E




FIG. 7F






FIG. 7G






FIG. 10A




FIG. 10B




FIG. 10C




FIG. 11




FIG. 12A




FIG. 12B




FIG. 13




FIG. 13A




FIG. 14




FIG. 15




FIG. 16A




FIG. 16A1




FIG. 16A2






FIG. 16A3








FIG. 17




FIG. 18A




FIG. 18B




FIG. 18C




FIG. 18D




FIG. 18E




FIG. 18F




FIG. 18G




FIG. 19A




FIG. 19B




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 25




FIG. 26




FIG. 27





FIG. 28






FIG. 30




FIG. 31




FIG. 32




FIG. 33




FIG. 34




FIG. 35




FIG. 36

1

POWER TOOL SOUND DAMPING**CROSS-REFERENCE TO RELATED APPLICATIONS**

This application is a continuation of U.S. patent application Ser. No. 14/747,410 entitled "Sound Damping for Power Tools", filed Jun. 23 2015, which is a continuation-in-part of and U.S. patent application Ser. No. 14/444,982 entitled "Power Tool Drive Mechanism" filed Jul. 28, 2014, now U.S. Pat. No. 10,022,048. This application also claims benefit of PCT Application No. PCT/CN2015/076257 entitled "Sound Damping for Power Tools" filed Apr. 10, 2015. All of the above applications are incorporated herein by reference.

FIELD OF THE INVENTION

The present invention relates to sound damping for power tools.

BACKGROUND OF THE INVENTION

Fastening tools, such as nailers, are used in the construction trades. However, many fastening tools which are available are insufficient in design, expensive to manufacture, heavy, not energy efficient, lack power, have dimensions which are inconveniently large and cause operators difficulties when in use. Further, many available fastening tools do not adequately guard the moving parts of a nailer driving mechanism from damage.

Additionally, many power tools, such as fastening tools, emit excess sound and/or noise. Such excess sound and/or noise can be unpleasant to the user and others within a hearing distance thereof.

Further, many fastening tools which are available are inconveniently bulky and have systems for driving a fastener which have dimensions that require the fastening tool to be larger than desired. For example, drive systems having a motor which turns a rotor can require clutches, transmissions, control systems and kinetic parts which increase stack up and limit the ability of a power tool to be reduced in size while retaining sufficient power to achieve a desired performance.

There is a strong need for a fastening tool having an improved motor and drive mechanism. A strong need also exists for a fastening tool which has improved sound characteristics.

SUMMARY OF THE INVENTION

A power tool, such as a fastening tool, can have one or more sound damping members which can control, manage, reduce and eliminate undesired sound and/or noise emitted from such tools. Herein, "sound" and "noise" are used synonymously.

In an embodiment, the fastening tool can have an electric motor having a rotor which has a rotor shaft which is coupled to a flywheel. The flywheel can have a sound damping member. The sound damping member can have a sound damping material. In an embodiment, the sound damping member can be a sound damping tape. The sound damping member can have a polymer. The sound damping member can be a powder coat and/or a powder coating applied to at least a portion of a power tool member, piece and/or structure, such as a flywheel and/or housing. The

2

powder coat can be a coating which covers a surface of a power tool part in-part or wholly.

In an embodiment, the sound damping member can have one or a plurality of layers. The sound damping member can be a single material and/or a single layer, or the sound damping member can be a laminate having a plurality of layers of the same or different materials.

Herein, a vibration absorption member is a type of sound damping member. In an embodiment, the sound damping member vibration absorption member. In an embodiment, the vibration absorption member can have one or a plurality of layers. The vibration absorption member can be a single material and/or a single layer, or the sound damping member can be a laminate having a plurality of layers of the same or different materials.

In non-limiting example, the flywheel having the sound damping member can have a vibration damping ratio of 0.050% or greater. In another non-limiting example, The frequency response for a flywheel having a sound damping member can be less than $800 \text{ (m/s}^2\text{)/lb}_f$ in a range from 20 Hz to 20,000 Hz.

The electric motor can have an inner rotor. The flywheel can have a portion which is cantilevered over at least a portion of the electric motor. The flywheel can have a contact surface adapted to impart energy from the flywheel when contacted by a moveable member.

In an embodiment, a power tool can have an electric motor having a rotor having a rotor shaft. The rotor shaft coupled to a metal flywheel which can have a contact surface adapted to impart energy from the metal flywheel when contacted with a moveable member. The metal flywheel can have a sound damping member which can receive at least a vibrational energy from the metal flywheel. The metal flywheel can have a vibration absorption member which can receive at least a vibrational energy from the metal flywheel. The metal flywheel can have a portion which is cantilevered over at least a portion of the electric motor. The portion which is cantilevered can overlap at least a portion of the electric motor. The metal flywheel's portion which is cantilevered over at least a portion of the electric motor can be adapted to rotate radially about at least a portion of the electric motor.

In an embodiment, the sound damping member can be affixed to an inner surface of the portion of the metal flywheel which is cantilevered over at least a portion of the electric motor. The sound damping member can comprise a plurality of layers, or be a laminate. The sound damping member can have a sound damping material. In an embodiment, the sound damping member can have a metal layer.

In an embodiment, the power tool can have a sound damping member which is a laminate and which is adhered to at least a portion of the power tool. In an embodiment, the power tool having a sound damping member can be a nailer. In an embodiment, the power tool having a sound damping member can be an impact driver.

In an embodiment, a power tool can have an electric motor having a rotor which has a rotor shaft. The rotor shaft can be coupled to a flywheel which can have a portion which is cantilevered over at least a portion of the rotor. The flywheel can also have a contact surface adapted to impart energy from the flywheel when contacted by a moveable member. The overlapping portion can be adapted to rotate radially about at least a portion of the motor. The power tool can have a motor which has an inner rotor, or a motor which has an outer rotor. The flywheel can have a portion which is cantilevered over at least a portion of the rotor.

In an embodiment, a power tool can have an electric motor having a motor housing and a rotor having a rotor shaft. The rotor shaft can be coupled to a flywheel which can have a portion which is cantilevered over at least a portion of the motor housing. The flywheel can also have a contact surface adapted to impart energy from the flywheel when contacted by a moveable member. The overlapping portion can be adapted to rotate radially about at least a portion of the motor housing. The power tool can have a motor which has an inner rotor, or a motor which has an outer rotor.

The power tool can have an overlapping portion which supports a flywheel ring which can have a contact surface. Optionally, the contact surface can have a geared portion. The contact surface can optionally have at least one grooved portion. The contact surface can optionally have at least one toothed portion.

In an embodiment, the power tool can have a flywheel ring and a rotor shaft which rotate in a ratio in a range of 0.5:1.5 to 1.5:0.5; such as in a range of 1:1.5 to 1.5:1. In an embodiment, the power tool can have a flywheel ring and a rotor shaft which rotate in a ratio of about 1:1. In an embodiment, the power tool can have a flywheel ring and a rotor shaft which rotate in a ratio of 1:1. The power tool can also have a flywheel ring which rotates at a speed in a range of from about 2500 rpm to about 20000 rpm. The power tool can also have a flywheel ring which rotates at a speed in a range of from about 5600 rpm to about 10000 rpm. In another embodiment, the power tool can have a flywheel ring which has a contact surface which has a speed in a range of from about 20 ft/s to about 200 ft/s. In yet another embodiment, the power tool can have a flywheel ring which has an inertia in a range of from about 10 J(kg*m²) to about 500 J(kg*m²).

In an embodiment, the power tool can have a flywheel ring which rotates in a plane parallel to a driver profile centerline plane. The power tool can also have a moveable member which is a driver blade which has a driving action which is energized by a transfer of energy from a contact of the driver blade with the flywheel. The power tool can also have a moveable member which is a driver profile which has a driving action which is energized by a transfer of energy from a contact of the driver profile with the flywheel.

The power tool can be a cordless power tool. The power tool can be a cordless nailer and can be adapted to drive a nail. The power tool can also be driven by a power cord, or be pneumatic, or receive power from another source.

In an embodiment, a fastening device can have a motor having a cantilevered flywheel. The cantilevered flywheel can have a contact surface adapted for frictional contact with a driving member adapted to drive a fastener. The fastening device can have a motor which has an inner rotor, or a motor which has an outer rotor. The motor can be a brushed motor or a brushless motor. The motor can be an inner rotor motor which can be a brushed motor or an outer rotor motor which can be a brushed motor. The motor can be an inner rotor motor which can be a brushless motor or an outer rotor motor which can be a brushless motor.

In an embodiment, the fastening device can also have a cupped flywheel. The cupped flywheel can have a flywheel ring. In an embodiment, at least a portion of the cupped flywheel can be cantilevered over at least a portion of the motor and/or motor housing. The cupped flywheel can have a contact surface. The cupped flywheel can have a geared flywheel ring. Herein, a grooved surface of a flywheel ring is considered to be a type of gearing; and a grooved surface to be a type of geared surface.

In an embodiment, the cupped flywheel can have a mass in a range of from about 1 oz to about 20 oz. In another embodiment, the fastening device can have a cantilevered flywheel which can have a diameter in a range of from about 0.75 to about 12 inches. The cantilevered flywheel can be adapted to rotate at an angular velocity of from about 500 rads/s to about 1500 rads/s. The cantilevered flywheel can be adapted to have a flywheel energy in a range of from about 10 j to about 1500 j.

In an embodiment, the fastening device can have a driving member which is driven with a driving force of from about 2 j to about 1000 j. In another embodiment, the fastening device can have a driving member which is driven at a speed of from about 10 ft/s to about 300 ft/s. The fastening device can have a driving member which is a driver blade. The fastening device can have a driving member which is a driver profile.

The fastening device can have a direct drive mechanism. In an embodiment, the direct drive mechanism can have a cantilevered flywheel. In another aspect, the fastening device can have a drive mechanism which is clutch-free.

The fastening device can be a nailer and can be adapted to drive a fastener which is a nail.

In an embodiment, a power tool can have a motor having a rotor and a flywheel adapted for turning by the rotor. The flywheel can have a flywheel portion which is positioned radially over at least a portion of the motor. In an embodiment, the flywheel portion can be at least a part of a flywheel ring, or can be a flywheel ring. In an embodiment, the flywheel portion can be at least a part of a flywheel body, or a flywheel body. In an embodiment, the flywheel portion can be at least a part of a cupped flywheel, or a cupped flywheel.

In an embodiment, the power tool can have a flywheel which is a cupped flywheel. The flywheel body can have a flywheel inner circumference which is configured radially about at least a portion of the motor. In another embodiment, the power tool can have a flywheel which is a cupped flywheel and which has a flywheel ring having at least a part which positioned radially over at least a portion of the motor.

In an embodiment, the power tool can have a motor housing which houses at least a portion of the motor and a flywheel portion which is positioned radially over at least a portion of the motor housing.

In an embodiment, the power tool can have a flywheel adapted for clutch-free turning by the motor. In another embodiment, the power tool can have a flywheel adapted for transmission-free turning by the motor. In yet another embodiment, the power tool can have a flywheel which can be adapted for turning by the rotor in a ratio of 1 turn of the flywheel to 1 turn of the rotor. In even another embodiment, the power tool can have a flywheel which can be adapted for turning by the rotor in a ratio of 1.5 turn of the flywheel to 1 turn of the rotor to 1.0 turn of the flywheel to 1.5 turn of the rotor.

In an embodiment, the power tool can be a fastening device. In another embodiment, the power tool can be a fastening device adapted to drive a nail into a workpiece.

In an embodiment, a power tool can have a motor having a rotor axis and a flywheel adapted for turning by the motor. The flywheel can have a flywheel portion coaxial to the rotor axis and which is at least in part located over at least a portion of the motor. The power tool can have a flywheel body having a flywheel body portion which radially surrounds at least a portion of the motor. The power tool can have a cupped flywheel having a cupped flywheel portion which radially surrounds at least a portion of the motor. The power tool can have a cupped flywheel having a flywheel

5

ring and in which a portion of the flywheel ring is adapted to rotate coaxial to the rotor axis. The power tool can have a flywheel portion which has a flywheel contact surface which is adapted to rotate coaxial to the rotor axis. In an embodiment, the flywheel contact surface which can be adapted to have a velocity of at least 10 ft/s and in which the flywheel contact surface can be adapted to revolve coaxially about the rotor axis.

In an embodiment, the power tool can have a flywheel portion which is a cantilevered portion. The power tool can have a flywheel portion which is cantilevered over at least a portion of the motor. The flywheel portion which is cantilevered over at least a portion of the motor can have a contact surface.

In another embodiment, the power tool can have a flywheel portion which is cantilevered over at least a portion of the motor and can have a geared flywheel ring. In yet another embodiment, the power tool can have a motor housing which houses at least a portion of the motor and in which the flywheel has a flywheel inner circumference which is configured radially about at least a portion of the motor and which has a flywheel motor clearance of greater than 0.02 mm.

The power tool can be a fastening device.

In addition to the disclosure of articles, apparatus and devices herein, this disclosure encompasses a variety of methods of use and construction of the disclosed embodiments. For example, a method for driving a fastener, can have the steps of: providing a motor and a cantilevered flywheel adapted to be turned by the motor; providing a driving member adapted to drive a fastener into a workpiece; providing a fastener to be driven; configuring the cantilevered flywheel such that at least a portion of the cantilevered flywheel can be reversibly contacted with a portion of the driving member; operating the cantilevered flywheel at an inertia of from about 2 j to about 500 j; causing the driving member to reversibly contact at least a portion of the cantilevered flywheel; imparting a driving force in a range of from about 1 j to about 475 j to the driving member from the cantilevered flywheel; and driving the fastener into the workpiece. The motor which is provided can have an inner rotor or an outer rotor. Additionally, the motor provided can be a brushed motor or a brushless motor.

In an embodiment, the method of driving a fastener can also have the step of operating the cantilevered flywheel at a speed in a range of from about 2500 rpm to about 20000 rpm. In an embodiment, the method of driving a fastener can also have the step of operating the cantilevered flywheel at an angular velocity in a range of from about 250 rads/s to about 2000 rads/s.

In another embodiment, the method of driving a fastener can also have the steps of providing a fastener which is a nail; and driving the nail into the workpiece.

BRIEF DESCRIPTION OF THE DRAWINGS

The present invention in its several aspects and embodiments solves the problems discussed herein and significantly advances the technology of fastening tools. The present invention can become more fully understood from the detailed description and the accompanying drawings, wherein:

FIG. 1 is a knob-side side view of an exemplary nailer having a fixed nosepiece assembly and a magazine;

FIG. 2 is a nail-side view of an exemplary nailer having the fixed nosepiece assembly and the magazine;

6

FIG. 3 is a detailed view of the fixed nosepiece with a nosepiece insert and a mating nose end of the magazine;

FIG. 4 is a perspective view of the latched nosepiece assembly of the nailer having a latch mechanism;

FIG. 5 is a side sectional view of the latched nosepiece assembly;

FIG. 6 is a perspective view illustrating the alignment of the nailer, magazine and nails;

FIG. 7 is a perspective view of a cupped flywheel positioned for assembly onto an inner rotor motor;

FIG. 7A is a perspective view of an embodiment of a sound damping tape;

FIG. 7B is a side view of the embodiment of the sound damping tape of FIG. 7A;

FIG. 7C is a top view of a flattened configuration of the embodiment of the sound damping tape of FIG. 7A;

FIG. 7C1 is a sectional view of an embodiment of a sound damping laminate having a reinforced backing layer;

FIG. 7C2 is a sectional view of a multilayered sound damping laminate;

FIG. 7D is a perspective view of a cupped flywheel;

FIG. 7E is a perspective view of the cupped flywheel having a sound damping material on a flywheel ring inner surface;

FIG. 7F is a perspective view of an inner rotor motor having a sound damping material;

FIG. 7G is a perspective view of the cupped flywheel having a sound damping powder coating;

FIG. 8 is a side view of the cupped flywheel positioned for assembly onto the inner rotor motor;

FIG. 9 is a front view of the cupped flywheel;

FIG. 10A is a side view of a drive mechanism having the cupped flywheel which is frictionally engaged with a driver profile;

FIG. 10B is a cross-sectional view of the drive mechanism having the cupped flywheel which is frictionally engaged with the driver profile;

FIG. 10C is a side view of a drive mechanism having an inner rotor motor which has a sound damping material and the cupped flywheel which has a sound damping material;

FIG. 11 is a perspective view of the drive mechanism having the cupped flywheel and the driver which is in a resting state;

FIG. 12A is a perspective view of the drive mechanism having the cupped flywheel and the driver which is in an engaged state;

FIG. 12B is a perspective view of the drive mechanism having the cupped flywheel and the driver which is in an engaged state showing an embodiment in which a flywheel ring centerline plane is coplanar with a driver centerline plane;

FIG. 13 is a perspective view of a drive mechanism having the cupped flywheel and the driver which is in a driven state;

FIG. 13A is a perspective view of a drive mechanism having the cupped flywheel which has the sound damping material and the driver which is in a driven state;

FIG. 14 is a side view of a partial drive assembly having the cupped flywheel;

FIG. 15 is a top view of the partial drive assembly having the cupped flywheel;

FIG. 16A is a perspective view of the drive assembly having the cupped flywheel shown in conjunction with a magazine for nails;

FIG. 16A1 is an exploded view of the drive assembly having the cupped flywheel and a sound damping tape;

FIG. 16A2 is a side view of the exploded view of the drive assembly of FIG. 16A1 having the cupped flywheel and the sound damping tape;

FIG. 16A3 is a side view of the drive assembly of FIG. 16A1 having the cupped flywheel and the sound damping tape;

FIG. 16A4 is a sectional view of the drive assembly of FIG. 16A1 having the cupped flywheel which has the sound damping tape;

FIG. 16B is a sectional view of the drive assembly having the cupped flywheel taken along the longitudinal centerline plane of the rotor shaft;

FIG. 17 is a sectional view of the drive assembly having the cupped flywheel taken along the longitudinal centerline plan of the driver profile;

FIG. 18A is a perspective view of the cupped flywheel;

FIG. 18B is a view of the cupped flywheel having a number of flywheel openings in a flywheel face;

FIG. 18C is a view of the cupped flywheel having a number of flywheel slots in a flywheel body;

FIG. 18D is a view of the cupped flywheel having a number of flywheel slots in the flywheel body and the flywheel face;

FIG. 18E is a view of the cupped flywheel having a number of flywheel round openings in the flywheel body and the flywheel face;

FIG. 18F is a view of the cupped flywheel having a mesh flywheel body and a mesh flywheel face;

FIG. 18G is a view of a cantilevered flywheel ring supported by a number of flywheel struts;

FIG. 19A is a perspective view of the cupped flywheel having dimensioning;

FIG. 19B is an example of the cupped flywheel having a narrow cup and wide flywheel ring;

FIG. 20 is an embodiment of a cupped flywheel roller drive mechanism;

FIG. 21 is an embodiment of the cupped flywheel having a flywheel ring having axial gears;

FIG. 22 is an embodiment of the cupped flywheel having a flywheel ring grinder portion;

FIG. 23 is an embodiment of the cupped flywheel having a flywheel ring saw portion; and

FIG. 24 is an embodiment of the cupped flywheel having a flywheel ring fan portion;

FIG. 25 is a perspective view of an impact driver;

FIG. 26 is an exploded view of an impact driver having the sound damping material;

FIG. 27 is a sectional view of an impact mechanism having the sound damping material;

FIG. 28 shows a hammer having the sound damping material and an anvil having the sound damping material;

FIG. 29 shows the cupped flywheel without a sound damping member tested in Example 1;

FIG. 30 shows the cupped flywheel having a sound damping member tested in Example 2;

FIG. 31 shows a graph of frequency response data for the cupped flywheel without a sound damping member tested in Example 1;

FIG. 32 shows a graph of frequency response data for the cupped flywheel having a sound damping member tested in Example 2;

FIG. 33 shows an excerpted graph of vibration response data for the cupped flywheel without a sound damping member tested in Example 1;

FIG. 34 shows an excerpted graph of vibration response data for the cupped flywheel having a sound damping member tested in Example 2;

FIG. 35 shows Response versus Time data for testing of the cupped flywheel without a sound damping member tested in Example 1; and

FIG. 36 shows Response versus Time data for testing of the cupped flywheel having a sound damping member tested in Example 2.

Throughout this specification and figures like reference numbers identify like elements.

DETAILED DESCRIPTION OF THE INVENTION

In an embodiment, one or more sound damping materials can be used to reduce the sound emitted from a power tool during its operation. In an embodiment, a power tool can have a sound damping material which can reduce or eliminate sound from the power tool. In an embodiment, the power tool can be a fastening tool. In another embodiment, the power tool can be an impact driver, or other power tool.

In an embodiment, the power tool can have a broad variety of designs and can be powered by one or more of a number of power sources. For example, power sources for the fastening tool can be manual or use one or more of a pneumatic, electric, battery, combustion, solar or other source of energy, or multiple sources of energy. In an embodiment, both battery and electric power can be employed in the same power tool. The fastener can be cordless or can have a power cord. In an embodiment, the fastening tool can have both a cordless mode and a mode in which a power cord is used.

In an embodiment, the power tool can be driven by an inner rotor motor 500 and a flywheel 700 which can be a cantilevered flywheel 899 (e.g. FIG. 7), such as a cupped flywheel 702 (e.g. FIG. 7). The inner rotor motor 500 can be a brushed motor 501, a brushless motor, or of another type. The inner rotor motor 500 can be in instant start motor and can drive an instant start flywheel and/or fastening device driver.

The disclosed use of the cantilevered flywheel 899, such as the cupped flywheel 702 achieves numerous benefits, such as allowing brushed motors to be used, significant reductions in manufacturing cost, smaller and lighter power tools. In embodiments, the inner rotor motor 500 with the flywheel 700 can drive a clutch-free (clutchless) and/or transmission-free direct drive mechanism. The inner rotor motor 500 with the cantilevered flywheel 899 achieves an efficient direct drive system for a flywheel to drive action in a power tool and/or fastening device.

The power tool drive mechanism disclosed herein can be used with a broad variety of fastening tools, including but not limited to, nailers, drivers, riveters, screw guns and staplers. Fasteners which can be used with the magazine 100 (e.g. FIG. 1) can be in non-limiting example, roofing nails, finishing nails, duplex nails, brads, staples, tacks, masonry nails, screws and positive placement/metal connector nails, rivets and dowels.

In an embodiment in which the fastening tool is a nailer. Additional areas of applicability of the present invention can become apparent from the detailed description provided herein. The detailed description and specific examples herein are not intended to limit the scope of the invention. This disclosure and the claims of this application are to be broadly construed.

FIG. 1 is a side view of an exemplary nailer having a magazine viewed from the knob-side 90 (e.g., FIG. 1 and FIG. 3) and showing the pusher assembly knob 140. The embodiment of FIG. 1 shows a magazine 100 which is

constructed according to the principles of the present invention is shown in operative association with a nailer **1**. In this example, FIG. **1**'s nailer **1** is a cordless nailer. However, the nailer can be of a different type and/or a power source which is not cordless.

Nailer **1** has a housing **4** and a motor having an inner rotor, herein as "inner rotor motor **500**", (e.g. FIG. **7**) which can be covered by the housing **4**. In the embodiment of FIG. **1**, the inner rotor motor **500** drives a nail driving mechanism for driving nails which are fed from the magazine **100**. The terms "driving" and "firing" are used synonymously herein regarding the action of driving or fastening a fastener (e.g. a nail) into a workpiece. A handle **6** extends from housing **4** to a base portion **8** having a battery pack **10**. Battery pack **10** is configured to engage a base portion **8** of handle **6** and provides power to the motor such that nailer **1** can drive one or more nails which are fed from the magazine **100**.

Nailer **1** has a nosepiece assembly **12** which is coupled to housing **4**. The nosepiece can be of a variety of embodiments. In a non-limiting example, the nosepiece assembly **12** can be a fixed nosepiece assembly **300** (e.g. FIG. **1**), or a latched nosepiece assembly **13** (e.g. FIG. **4**).

The magazine **100** can optionally be coupled to housing **4** by coupling member **89**. The magazine **100** has a nose portion **103** which can be proximate to the fixed nosepiece assembly **300**. The magazine **100** can engage the fixed nosepiece assembly **300** at a nose portion **103** of the magazine **100** which has a nose end **102**. In an embodiment, the fixed nosepiece assembly **300** can fit with the magazine **100** by a magazine interface **380**. In an embodiment, the magazine screw **337** can be screwed to couple the fixed nosepiece assembly **300** to the magazine **100**, or unscrewed to decouple the magazine **100** from the fixed nosepiece assembly **300**.

The magazine **100** can be coupled to a base portion **8** of a handle **6** at a base portion **104** of magazine **100** by base coupling member **88**. The base portion **104** of magazine **100** is proximate to a base end **105**. The magazine can have a magazine body **106** with an upper magazine **107** and a lower magazine **109**. An upper magazine edge **108** is proximate to and can be attached to housing **4**. The lower magazine **109** can have a lower magazine edge **101**.

The magazine **100** can include a nail track **111** sized to accept a plurality of nails **55** therein (e.g. FIG. **5**). The nails can be guided by a feature of the upper magazine **107** which guides at least one end of a nail, such as a nail head. The lower magazine **109** can guide a portion of a nail, such as a nail tip supported by a lower liner **95**. The plurality of nails **55** can be moved through the magazine **100** towards nosepiece assembly **12** by a force imparted by contact from the pusher assembly **110**.

FIG. **1** illustrates an example embodiment of the fixed nosepiece assembly **300** which has an upper contact trip **310** and a lower contact trip **320**. The lower contact trip **320** can be guided and/or supported by a lower contact trip support **325**. The fixed nosepiece assembly **300** can have a nose **332** which can have a nose tip **333**. When the nose **332** is pressed against a workpiece, the lower contact trip **320** and the upper contact trip **310** can be moved toward the housing **4** which can compress a contact trip spring **330**. A depth adjustment wheel **340** can be moved to affect the position of a depth adjustment rod **350**. In an embodiment, the depth adjustment wheel **340** can be a thumbwheel. The position of the depth adjustment rod also affects the distance between nose tip **333** and insert tip **355** (e.g. FIG. **3**). A detail of a nosepiece insert **410** can be found in FIG. **3**.

The magazine **100** can hold a plurality of nails **55** (FIG. **6**) therein. A broad variety of fasteners usable with nailers can be used with the magazine **100**. In an embodiment, collated nails can be inserted into the magazine **100** for fastening.

FIG. **2** is a side view of exemplary nailer **1** having a magazine **100** and is viewed from a nail-side **58**. Allen wrench **600** is illustrated as reversibly secured to the magazine **100**.

FIG. **3** is a detailed view of a fixed nosepiece with a nosepiece insert and a mating nose end of a magazine. FIG. **3** is a detailed view of the nosepiece assembly **300** from the channel side **412** which mates with the nose end **102** of the magazine **100**.

FIG. **3** detail A illustrates a detail of the nosepiece insert **410** from the channel side **412**. The nosepiece insert **410** has the rear mount screw hole **417** for the nail guide insert screw **421**. Nosepiece insert **410** can also have a blade guide **415** and nail stop **420**. The driver blade **54** can extend from the drive mechanism into channel **52**. Nosepiece insert **410** can be fit to nosepiece assembly **300** and can have an interface seat **425**. Nosepiece insert **410** can also have a nosepiece insert screw hole **422** and a magazine screw hole **336**. Optionally, insert screw **401** for mounting the nosepiece insert **410** to the fixed nosepiece assembly **300** can be a rear mounted screw or a front mounted screw. Optionally, one or more prongs **437** respectively having a screw hole **336** for the magazine screw **337** can be used. In an embodiment, a nail channel **352** can be formed when the nosepiece insert **410** is mated with the nose end **102** of the magazine **100**.

FIG. **3** detail B is a front detail of the face of the nose end **102** having nose end front side **360**. The nose end **102** can have a nose end front face **359** which fits with channel side **412**. The nose end **102** can have a nail track exit **353**. For example, a loaded nail **53** is illustrated exiting nail track exit **353**. FIG. **3** detail B also illustrates a screw hole **357** for magazine screw **337**. In an embodiment, nosepiece insert **410** (FIG. **3**) having nose **400** with insert tip **355** is inserted into the fixed nosepiece assembly **300**.

FIG. **4** is a side view of another embodiment of exemplary nailer **1** viewed from the knob-side **90**. In this embodiment, the nosepiece assembly **12** is a latched nosepiece assembly **13** having a latch mechanism **14**. Also in this embodiment, the magazine **100** is coupled to the housing **4** and coupled to the base **8** of the handle **6** by bracket **11**.

FIG. **5** is a side sectional view of the latched nosepiece assembly **13** having a nail stop bridge **83**. In an example embodiment, channel **52** can be formed from two or more pieces, e.g. nose cover **34** and at least one of groove **50** and nosepiece **28** (and/or nail stop bridge **83**). Nosepiece **28** has a groove **50** formed therein which cooperates with the nose cover **34** (when the nose cover **34** is in its locked position). The locking of nose cover **34** against groove **50** can form an upper portion of channel **52**. The driver blade **54** can extend from the drive mechanism into channel **52**. The driver blade **54** can engage the head of the loaded nail **53** to drive loaded nail **53**. Cam **56** prevents escape of driver blade **54** from the nosepiece **28**. The nail stop bridge **83** that bridges the channel **52** engages each nail of the plurality of nails **55** as they are pushed by the pusher **112** along the nail track **111** of the magazine **100** and into channel **52**. The tips of the plurality of nails **55** can be supported by the lower liner **95**, or a lower support.

FIG. **6** illustrates the nail stop **420**, the nail stop centerline **427**, a longitudinal centerline **927** of the magazine **100**, a longitudinal centerline **1027** of the nail track **111**, a longitudinal centerline **1127** of the plurality of nails **55** and a

11

longitudinal centerline **1227** of the nailer **1**. FIG. **6** illustrates that in an embodiment having fixed nosepiece **300** having nosepiece insert **410** can be mated with the nose end **102** channel centerline **429** can be collinear with nail **1** centerline **1029**. Like reference numbers in FIG. **1** identify like elements in FIG. **6**. In an embodiment, the magazine **100** can have its longitudinal centerline **927** offset from a longitudinal centerline **1227** of nailer **1** by an angle **G**. Angle **G** can be 14 degrees. In an embodiment, nail stop centerline **427** can be collinear with a longitudinal centerline **927** of the magazine **100**. Additionally, in an embodiment, longitudinal centerline **927** of the magazine **100** can be collinear with a longitudinal centerline **1027** of the nail track **111**, as well as collinear with a nail stop centerline **427**. Longitudinal centerline **1127** of the plurality of nails **55** can be collinear with nail stop centerline **427**. Nail stop centerline **427** can be offset as shown in FIG. **6** at an angle **G** measured from nailer **1** channel centerline **429**. In an embodiment, angle **G** aligns the longitudinal centerline **1027** of the nail track **111** with the centerline **1127** of the plurality of nails **55** and also nail stop centerline **427**.

FIG. **7** is a perspective view of the cupped flywheel positioned for assembly onto an inner rotor motor **500**. FIG. **7** illustrates the inner rotor motor **500** having a motor housing **510** and a first housing bearing **520** which bears a rotor shaft **550** driven by an inner rotor **540** (FIG. **10A**). In an embodiment, the motor used can alternatively be a frameless motor which does not include a motor housing, or which can have only a partial motor housing which covers part of a longitudinal length of the motor. FIG. **7** also illustrates a flywheel **700** which is a cantilevered flywheel **899** and which in the embodiment of FIG. **7** is the cupped flywheel **702**. The cupped flywheel **702** is shown in a disassembled state and in coaxial alignment with a rotor centerline **1400**. The cupped flywheel **702** is shown in an assembled state, for example in FIGS. **10A** and **10B**. In an embodiment, the cupped flywheel **702** can have a flywheel body **710** and at least one of a flywheel opening **720** and/or a plurality of flywheel openings **720**. Herein, both a single flywheel opening and a number of flywheel openings are designated by the reference numeral "720". There is no limitation as to the number flywheel openings which can be used. Such openings achieve a reduction and/or tailoring of the mass of the flywheel to meet structural, inertial and power consumption specifications. In an embodiment, the cupped flywheel **702** can have a flywheel ring **750** which can be a geared flywheel ring **760**. Optionally, the cupped flywheel **702** can have a flywheel bearing **770** which interfaces with the rotor shaft **550**.

In non-limiting example, the sound damping material **1010** can be used to reduce noise emitted from any one or more of the flywheel **700**, the flywheel assembly **705**, the driver assembly **800** and the driver return system **900**. In another embodiment, the sound damping material **1010** can be used to reduce noise emitted from any one or more of the motor, the inner rotor motor **500**, brushed motor **501**, a brushless motor, the motor housing **510** and the motor housing **4**. In an embodiment, the sound damping material **1010** can have the form of a sound damping member **1015**. In an embodiment, the sound damping member **1015** can be a vibration absorption member **1020**. A vibration absorption member **1020** can have the sound damping material **1010**.

FIG. **7A** is a perspective view of an embodiment of a sound damping tape **1050**. In an embodiment, the sound damping member **1015** has a sound damping material **1010** which can be a sound damping tape **1050**. FIG. **7A** shows an embodiment in which the sound damping tape **1050** is

12

configured for placement upon a flywheel ring inner surface **1706** (FIG. **7E**) of a flywheel body **710**. The sound damping tape **1050** can have an adhesive surface **1051** having an adhesive material **1053**, as well as a backing layer **1352** having a backing material **1350**. In an embodiment, the sound damping material can be a sound damping tape **1050**, such as 3M™ 2542 sound damping foil tape (3M™, 3M Corporate Headquarters, 3M Center, St. Paul, Minn. 55144-1000; (888) 364-3577).

The sound damping material **1010** can have one or more of a variety of constituents such as in non-limiting example a polymer, an acrylic polymer, a urethane, an acrylic, a viscoelastic acrylic polymer, a viscoelastic material, a cross-linked elastomer, a polyester, an adhesive, an ultra-high adhesion (UHA™) removable adhesive (UHA™ is a trademarked product of Avery Dennison, 207 Goode Avenue, Glendale, Calif. 91205, phone (626) 304-2000, such as Avery Dennison tape product FT 0951), UHA™ adhesive, a foam, a metal, a foil, a sound damping foil, an aluminum foil, a dead soft aluminum foil, a film and a cloth.

The sound damping member **1015** can be a vibration absorption member **1020** which can be made from a sound damping material **1010** which can absorb vibrations from one or more power tool parts, such as the flywheel **700**. A vibration absorption member **1020** is a type of sound damping member. In an embodiment, a vibration absorption member **1020** can absorb vibrations from a member to which it is attached, or from elsewhere.

In an embodiment, the sound damping member **1015** can have one or more of a foil vibration damping portion, a foam vibration damping portion and a foam sheet vibration damping portion. In non-limiting example, the sound damping member **1015** can have one or more of a low-temperature vibration damping portion, a general purpose vibration damping portion, a high-temperature vibration damping portion, a foil vibration damping portion, a foam vibration damping portion, and a foam sheet vibration damping portion.

The sound damping member **1015** can be permanently or reversibly affixed to, mounted on, supported by and/or adjacent to one or more of the following: a stationary member and/or part of the power tool; a portion of a housing, such as the housing **4**; a portion of a motor and/or a motor cover, such as the motor housing **510**; and a moving and/or rotating member of the power tool, such as one or more of the flywheel **700**, the cupped flywheel **702**, the cantilevered flywheel **899** and the driver profile **610**. In an impact driver, The sound damping member **1015** can be permanently or reversibly affixed to, mounted on, supported by and/or adjacent to one or more of the hammer **1111**, the anvil **2222** and the impact driver motor **20** (FIG. **26**).

In an embodiment, the sound damping member can convert vibrational energy which it receives from a part, piece and/or member to heat. In an embodiment, the heat generated through conversion from vibrational energy by the sound damping member is cooled by the flow of air across and/or in contact with the sound damping member. In an embodiment the sound damping member can be a radiator and/or cooling member.

In an embodiment, the sound damping member can be the vibration absorption member which can convert vibrational energy which it receives from a part, piece and/or member to heat. In an embodiment, the heat generated through conversion from vibrational energy by the vibration absorption member is cooled by the flow of air across and/or in

contact with the vibration absorption member. In an embodiment the vibration absorption member can be a radiator and/or cooling member.

FIG. 7B is a side view of the embodiment of the sound damping tape **1050** of FIG. 7A. FIG. 7B shows the sound damping member **1015** configured to have a sound damping tape radius **1056** and a sound damping tape diameter **1058**. The sound damping member **1015** is shown to have a sound damping tape thickness **1055** and a sound damping tape circumference **1059**.

In an embodiment, the sound damping member **1015** can have a thickness in a range of from 0.01 mm to 15.0 mm, or greater; such as 0.025 mm to 0.2 mm, or 0.10 to 0.25 mm, or 0.20 mm to 0.45 mm, or 0.3 to 1.5 mm, or 0.50 mm to 2.0 mm, or 1.5 mm to 3 mm, or 2.0 mm to 4 mm, or 3 mm to 6 mm, or 5 mm to 10 mm or greater.

FIG. 7C is a top view of a flattened configuration of the embodiment of the sound damping tape of FIG. 7A. FIG. 7C shows the dimensions of the sound damping tape **1050** which forms the sound damping member **1015** when in a flattened configuration having a sound damping tape width **1052** and a sound damping tape length **1054**. In this embodiment the backing layer **1352** is shown, with the adhesive surface **1051** on the opposite side.

In an embodiment the sound damping member **1015** can have a backing material **1350** (e.g. FIG. 7C1), optionally in the form of a backing layer **1352** (FIG. 7C2). The backing can be thin, light, firm, strong, stiff, heavy-duty, waterproof, magnetic or protective. The backing can be reinforced internally and/or externally.

In an embodiment, the sound damping member **1015** can have a lined construction in which a releasable liner is adhered to the adhesive surface **1051** of the sound damping material **1010** prior to applying the adhesive surface **1051** to a member and/or surface of a power tool. In non-limiting example, the sound damping tape **1050** can have a liner reversibly against the adhesive surface prior to use or application of the tape. In this example, the liner can be removed to allow application of the sound damping tape to a piece, part, member or surface of a tool, or at least a portion thereof.

In an embodiment, the sound damping member **1015** can have a backing material **1350** which can have a thickness in a range of from 0.025 mm to 10.0 mm or thicker, such as 0.025 mm to 0.19 mm, or 0.10 to 0.25 mm, or 0.20 mm to 0.34 mm, or 0.25 to 1.0 mm, or 0.50 mm to 2.0 mm, or 1.5 mm to 3 mm, or 2.0 mm to 4 mm, or 3 mm to 6 mm, or 5 mm to 10 mm or greater.

In an embodiment, the sound damping member **1015** can have a sound damping laminate **1310**. The sound damping laminate **1310** can have a number of laminate layers which can be made of the same or different materials.

In an embodiment, sound damping laminate **1310** can have a metal laminate **1317**, such as for non-limiting example a foil laminate **1318**. In other non-limiting examples, the sound damping laminate **1310** can have one or more of a metal laminate layer, an aluminum laminate layer, a copper laminate layer, an urethane laminate layer, a polymer laminate layer, a cross-linked material polymer layer, a vibration absorbing laminate layer, a sound absorbing laminate layer and an acrylic laminate.

FIG. 7C1 shows a sectional view of an embodiment of a sound damping laminate having a reinforced backing layer. The sound damping member **1015** can have a laminate and/or multilayered structure. The laminated structure can be a sound damping laminate **1310**. The sound damping tape **1050** can also have a laminate and/or multilayered structure.

FIG. 7C1 is an example of a sound damping laminate **1310** of the sound damping member **1015** and/or of the sound damping tape **1050**. In non-limiting example, the sound damping laminate **1310** can have: a first laminate layer **1311**, which for example can have a first sound damping material **1011**; a second laminate layer **1312**, which for example can have a hardened material layer **1320**; and a third laminate layer **1313**, which for example can have a backing material **1350** which can have a reinforcing material **1360**.

FIG. 7C2 shows a sectional view of a multilayered sound damping laminate. The sound damping laminate **1310** can have many layers; for example 1 . . . n layers, with n being a large number, such as up to 25 layers, or up to 10 layers. The respective layers can be the same or different from one another and can have the same or different materials and/or compositions. The respective layers can have the same or different physical properties, and the respective layers can serve the same or different functions.

FIG. 7C2 shows a sectional view of the sound damping laminate **1310** which can form the sound damping member **1015** and/or of the sound damping tape **1050**. The sound damping laminate **1310** of FIG. 7C is shown to have: a first laminate layer **1311**, which for example can have a first sound damping material **1011**; a second laminate layer **1312**, which for example can have a second sound damping material **1012**; a third laminate layer **1313**, which for example can have a third sound damping material **1013**; a fourth laminate layer **1314**, a fifth laminate layer **1315**, which for example can have a fifth laminate layer **1351**. Optionally, the fifth laminate layer **1351** can be a backing layer **1352**, which for example can have a hardened material layer **1320**. In an embodiment, the sound damping laminate **1310** can have a sound damping member coating **1355**.

FIG. 7D is a perspective view of a cupped flywheel **702**. The cupped flywheel **702** shown in FIG. 7D has a flywheel body **710** and a flywheel ring **750**. The flywheel ring **750** can have a flywheel ring inner surface **1706**, a flywheel ring thickness **1729** and a flywheel ring outer circumference **1724**. The cupped flywheel **702** is shown to have a flywheel inner diameter **706**, a flywheel inner radius **1716** and a flywheel ring inner circumference **707**. The cupped flywheel **702** also has a flywheel outer diameter **704**, a flywheel ring outer radius **1714** and flywheel ring outer circumference **1724**.

FIG. 7E is a perspective view of a cupped flywheel **702** bearing a sound damping material **1010** on the flywheel ring inner surface **1706**. The non-limiting example of FIG. 7E shows a sound damping member **1015** which is a sound damping tape **1050**. The sound damping tape **1050** is shown to have the backing layer **1352** and the adhesive surface **1051** which is adhered to the flywheel ring inner surface **1706**. The adhesive surface **1051** of the sound damping tape **1050** is shown to extend along the flywheel ring inner circumference **707** of the flywheel ring inner surface **1706**. The sound damping tape **1050** can extend along all or part of the flywheel ring inner circumference **707**. The sound damping tape **1050** can cover, be affixed to and/or adhere to all or part of the flywheel ring inner surface **1706**.

The sound damping material can be affixed to one or more portions of the flywheel **700**, the cupped flywheel **702** or the cantilevered flywheel **899**.

FIG. 7F is a perspective view of an inner rotor motor **500** bearing a sound damping material **1010**. The non-limiting example of FIG. 7F shows the sound damping member **1015** which is a sound damping tape **1050** affixed to the motor housing **510**. In an embodiment, the sound damping tape **1050** can be affixed to or be supported by the motor housing

510 around its outside circumference **5101**, or other surface of the motor housing **510**. The sound damping material **1010** can cover the motor housing **510** in part or in whole.

FIG. 7G is a perspective view of a cupped flywheel having a sound damping powder coating. In an embodiment, the sound damping member **1015** can have a coating which can have one or more of a polymer coating and a powder coating. The non-limiting example of 7G shows the sound damping material **1010**, which is a sound damping powder coating **1230** on a flywheel ring inner surface. The sound damping powder coating **1230** can coat in part or in whole the flywheel **700**, the cupped flywheel **702** or the cantilevered flywheel **899**. FIG. 7G shows the cupped flywheel **702** which has the sound damping powder coating **1230** which coats the flywheel ring inner surface **1706** and the flywheel ring **750** across the flywheel ring width surface **7521**.

FIG. 8 is a side view of the cupped flywheel positioned for assembly onto the inner rotor motor **500**. As illustrated in FIG. 8, the cupped flywheel **702** can be positioned such that a flywheel axial centerline **1410** is collinear with a rotor centerline **1400**. In an embodiment, the cupped flywheel **702** can be frictionally attached to the rotor shaft **550** by means of fitting the flywheel bearing **770** onto a portion of the rotor shaft **550**. Herein, in embodiments the flywheel bearing **770** is synonymous to a flywheel hub. In other embodiments, the cupped flywheel **702** can be affixed to the rotor shaft **550** by other means, such as using a lock and key configuration, using a "D" shaped shaft portion mated with a "D" shaped portion of the flywheel bearing **770**, using fasteners such a screw, a linchpin, a bolt, a wed, or any other means which attached the cupped flywheel **702** to the rotor shaft **550**. In an embodiment, the inner rotor **540** and/or the rotor shaft **550** and the cupped flywheel **702** and/or the flywheel bearing **770** can be manufactured as one piece, or multiple pieces.

FIG. 9 is a front view of the cupped flywheel **702** having a number of the flywheel opening **720**. The flywheel ring **750** is shown extending radially away from the center of the cupped flywheel **702** and the flywheel bearing **770**. There is no limitation to the number of flywheel rings which can be used. Optionally, one or more flywheel rings can be located along the length of the cupped flywheel **702**. Each flywheel ring can have a contact surface to impart energy to a moveable member. Multiple flywheel rings can power multiple members, or the same member.

FIG. 10A is a side view of a drive mechanism having the cupped flywheel **702** which is frictionally engaged with a driver profile **610**. In FIG. 10A, the mating of the flywheel ring **750** with the driver profile **610** is shown. There is no limitation as to the means by which the flywheel **700** imparts energy to the driver **600**, driver profile **610** and/or driver blade **54**. In the example of FIG. 10A, the flywheel ring **750** is a geared flywheel ring **760** having a first gear groove **783** and a second gear groove **787** which are shown in frictional contact with driver profile **610** and more specifically a first profile tooth **611** and a second profile tooth **613**. By this frictional contact, at least a portion of the rotational energy developed in the cupped flywheel **702** is imparted to the driver profile **610** propelling the driver profile through a driving action to cause the driver blade **54** born by the driver profile **610** to drive a nail **53**.

FIG. 10B is a cross-sectional view of a drive mechanism having the cupped flywheel **702** which is frictionally engaged with the driver profile **610**. In FIG. 10B, the cross-sectional view illustrates the cantilevered nature of the flywheel ring **750** over at least a portion of the inner rotor motor **500**. In an embodiment, the flywheel ring **750** can be

cantilevered over the entirety of the inner rotor motor **500**, or any portion of the inner rotor motor **500**. In the embodiment of FIG. 10B, the cup shape of the cupped flywheel **702** when coupled to the rotor shaft **550** as illustrated in FIG. 10B configures the flywheel ring **750** radially and in a cantilevered configuration about at least a portion of inner rotor motor **500** and/or motor housing **510** and/or rotor **540**. The flywheel ring **750** can be positioned along the rotor centerline **1400** at a position at which the flywheel ring **750** is positioned such that a portion of each of the motor housing **510**, the stator **530**, the inner rotor **540** and the rotor shaft **550** is radially within a flywheel ring inner circumference **707**. The flywheel ring inner circumference **707** can have a diameter which optionally is the same or different from the flywheel inner diameter **706**. The flywheel ring inner circumference **707** can be separated from the motor housing **510** by a flywheel motor clearance **701**. There is no limitation as to the dimension of the flywheel motor clearance **701**. The clearance **701** can be in a range of from less than a millimeter to one foot or more, such as 0.02 mm, 0.05 mm, 1 mm, 2 mm, 3 mm, 4 mm, 5 mm, 7.5 mm, 10 mm, 15 mm or 25 mm, or greater. For example, in an embodiment of a power tool the clearance can be in a range of from 0.02 mm to 10 mm can be used. In another non-limiting example for larger industrial equipment a clearance of 5 mm to 25 mm or greater, can be used.

In the example embodiment of FIG. 10B, the flywheel ring inner circumference **707** can be the same as a flywheel inner circumference **709**. The flywheel inner circumference **709** can be the same or different from the flywheel ring inner circumference **707**. The flywheel inner circumference **709** can have any dimension which is separated from the motor housing **510** by a clearance. The flywheel inner circumference **709** can be at least in part over at least a portion of the inner rotor motor **500** and/or the motor housing **510**. The flywheel inner circumference **709** can at least in part radially encompass at least a part of inner rotor motor **500** and/or the motor housing **510**.

The driving action of the driver profile **610** can be used to drive a fastener, such as a nail **53**, into a workpiece. FIGS. 11, 12, 12B and 13 disclose a selection of steps taken during a driving action of the driver profile **610**. The driver profile **610** can be driven by a frictional contact with the flywheel **700** which can be the cantilevered flywheel **899**. In an embodiment, the driver profile **610** can have a driver blade **54** which can be propelled to physically contact the fastener such that the fastener is driven into a workpiece. In an embodiment, the fastener can be a nail **53**. The driving action of the driver profile **610** can begin when the driver profile **610** makes contact with the flywheel **700** which can be a cantilevered flywheel **899**, such as the cupped flywheel **702**. Upon contact by the driver profile **610** with the flywheel **700**, the driver profile **610** can be propelled toward the nosepiece **12** and a fastener such as a nail **53** positioned in the nosepiece **12** for driving into a work piece. The driver profile **610** and/or the driver blade **54** can physically contact the fastener such that the fastener is driven into a workpiece. After the fastener is driven into the workpiece, the driver profile **610** can return to its resting position. In an embodiment, the driver profile **610** can be driven by means of frictional contact by the flywheel **750** of the cupped flywheel **702**.

FIG. 10C a side view of a drive mechanism having an inner rotor motor **500** which has the sound damping material **1010** and having the cupped flywheel **702** which has the sound damping material **1010**. The sound damping material **1010** can have a broad variety of shapes, forms, configura-

tions and applications. The sound damping material **1010** can be applied directly to a surface, in pre-formed shapes, tapes, laminates, sheets, or other structure and/or configuration. Methods of application can also broadly vary.

FIG. **10C** shows the sound damping member **1015** which has the sound damping material **1010** and which is in the form of a sound damping sheet **1210**. The sound damping sheet **1210** is shown wrapped around and/or covering in part or wholly a motor housing outside surface **5101** of motor housing **510**. The sound damping sheet **1210** can be adhered to and/or cover all or part of the motor housing **510**.

FIG. **10C** also shows the sound damping member **1015** which has the sound damping material **1010** and which is in the form of the sound damping tape **1050**. The sound damping tape **1050** is shown wrapped around and/or covering a flywheel body outside surface **7101**. The sound damping sheet **1210** can be adhered to and/or cover all or part of the flywheel body outside surface **7101**.

FIG. **11** is a side view of a drive mechanism having the cupped flywheel **702** and a driver profile **610** which is in a resting state. In FIG. **11**, the driver profile **610** has a portion proximate to but not touching the flywheel ring **750** of the cupped flywheel **702**. In FIG. **11**, the driver blade **54** is shown extending from its seating in the driver profile **610** to the latched nosepiece assembly **13** and its parts, such as the nosepiece **28**. The flywheel **700** can rotate at a speed and an angular velocity.

Numeric values and ranges herein, unless otherwise stated, are intended to have associated with them a tolerance and to account for variances of design and manufacturing. Thus, a number is intended to include values "about" that number. For example, a value X is also intended to be understood as "about X". Likewise, a range of Y-Z, is also intended to be understood as within a range of from "about Y-about Z". Unless otherwise stated, significant digits disclosed for a number are not intended to make the number an exact limiting value. Variance and tolerance is inherent in mechanical design and the numbers disclosed herein are intended to be construed to allow for such factors (in non-limiting e.g., ± 10 percent of a given value). Example numbers disclosed within ranges are intended also to disclose sub-ranges within a broader range which have an example number as an endpoint. A disclosure of any two example numbers which are within a broader range is also intended herein to disclose a range between such example numbers. Likewise, the claims are to be broadly construed in their recitations of numbers and ranges.

In the embodiment of FIG. **11**, the cantilevered flywheel **899** is shown to be the cupped flywheel **702**. There is no limitation regarding the diameter or dimensions of any of the various embodiments of the flywheel **700** disclosed herein, such as the cantilevered flywheel **899** which can be the cupped flywheel **702**, or other type of cantilevered flywheel having at least a portion projecting over at least a portion of the inner rotor motor **500**. In other example embodiments, the flywheel **700** can have a number of flywheel struts **713** (FIG. **18G**), or flywheel **700** can have a flywheel mesh structure **740** (FIG. **18F**), or other structure. Any of the flywheels disclosed herein can have a diameter from small to quite large, such as in a range of from less than 0.5 inches to greater than 24 inches. For example cupped flywheel **702** can have a portion, such as a flywheel body portion **710** and/or a flywheel outer diameter **704** (FIG. **19A**) having a diameter which can be 0.05 in, 1.0 in, 1.5 in, 2.0 in, 3.0 in, 4.0 in, 5.0 in, 6.0 in, 7.0 in, 8.0 in, 9.0 in, 10.0 in, 11.0 in, 12.0 in, 12.6 in, 15 in, 18 in, 24 in. The flywheel ring **750** can also have an outer diameter **751** which can be 0.05 in,

1.0 in, 1.5 in, 2.0 in, 3.0 in, 4.0 in, 5.0 in, 6.0 in, 7.0 in, 8.0 in, 9.0 in, 10.0 in, 11.0 in, 12.0 in, 12.6 in, 15 in, 18 in, 24 in. Additionally, there is no limitation to the structural supports for the flywheel ring **750**.

There is no limitation to the speed at which any of the many types and variations of flywheels operate. For example, any of the flywheels disclosed herein can be operated at any rotational speed in the range of from 2500 rpm to 20000 rpm, or greater. In an embodiment, cupped flywheel **702** can be operated at a rotational speed of from less than 2500 rpm to 20000 rpm, or greater. For example, cupped flywheel **702** can be operated at a rotational speed of 1000 rpm, 2500 rpm, 5000 rpm, 5600 rpm, 7500 rpm, 8000 rpm, 9000 rpm, 10000 rpm, 12000 rpm, 12500 rpm, 13000 rpm, 14000 rpm, 15000 rpm, 17500 rpm, 18000 rpm, 20000 rpm, 25000 rpm, 30000 rpm, 32000 rpm, or greater.

There is also no limitation to the angular velocity at which any of the many types and variations of flywheels operate. For example, any of the flywheels disclosed herein can be operated at any rotational speed in the range of from 250 rads/s to 3000 rads/s, or greater. In an embodiment, the cupped flywheel **702** can be operated at a rotational speed of from less than 250 rads/s to 3000 rads/s, or greater. For example, the cupped flywheel **702** can be operated at a rotational speed of 200 rads/s, 300 rads/s, 400 rads/s, 500 rads/s, 600 rads/s, 700 rads/s, 800 rads/s, 900 rads/s, 1000 rads/s, 1200 rads/s, 13000 rads/s, 1400 rads/s, 1500 rads/s, 1600 rads/s, 1750 rads/s, 2000 rads/s, 2200 rads/s, 2500 rads/s, 3000 rads/s, or greater.

There is also no limitation to the velocity of a flywheel portion and/or a portion of the contact surface **715** at which any of the many types and variations of flywheels operate. For example, any of the flywheels disclosed herein can be operated such that the velocity of a flywheel portion and/or a portion of contact surface **715** is in a range of from less than 5 ft/s to 400 ft/s, or greater. For example cupped flywheel **702** can be operated such that velocity of a flywheel portion and/or a portion of contact surface **715** is 2.5 ft/s, 5 ft/s, 7.5 ft/s, 9 ft/s, 10 ft/s, 15 ft/s, 20 ft/s, 25 ft/s, 30 ft/s, 50 ft/s, 75 ft/s, 90 ft/s, 100 ft/s, 125 ft/s, 150 ft/s, 175 ft/s, 190 ft/s, 200 ft/s, 250 ft/s, 300 ft/s, 350 ft/s, 400 ft/s, or greater.

There is no limitation to the mass which any of the many types and variations of flywheels disclosed herein can have. For example, any of the flywheels disclosed herein can have a mass in a range of from less than 1 oz to greater than 50 oz. For example the cupped flywheel **702** can have a mass of less than 0.5 oz, 1.0 oz, 0.75 oz, 1 oz, 2 oz, 3 oz, 4 oz, 5 oz, 7.5 oz, 9 oz, 10 oz, 12 oz, 14 16 oz, 18 oz, 20 oz, 25 oz, 30 oz, 40 oz, 50 oz, or greater. In another example, the cupped flywheel **702** can have a mass of less than 10 g, 25 g, 28 g, 50 g, 75 g, 100 g, 150 g, 200 g, 250 g, 300 g, 500 g, 750 g, 900 g, 1000 g, 1250 g, 1500 g, 2000 g, or greater.

There is no limitation to the inertia of any of the many types and variations of flywheels. For example, any of the flywheels disclosed herein can be operated to have any inertia in the range of from less than 10 J(kg*m²) to 500 J(kg*m²), or greater. For example cupped flywheel **702** can have an inertia of less than 5 J(kg*m²), 7.5 J(kg*m²), 10 J(kg*m²), 25 J(kg*m²), 50 J(kg*m²), 75 J(kg*m²), 90 J(kg*m²), 100 J(kg*m²), 150 J(kg*m²), J(kg*m²), 200 J(kg*m²), 250 J(kg*m²), 300 J(kg*m²), 350 J(kg*m²), 400 J(kg*m²), 450 J(kg*m²), 500 J(kg*m²), 600 J(kg*m²), or greater.

There is also no limitation regarding the flywheel energy which any of the many types and variations of flywheels can possess. For example, any of the flywheels disclosed herein can have a flywheel energy of any value in the range of from

less than 10 j to 1500 j, or greater. For example cupped flywheel **702** can have a flywheel energy of less than 5 j, 10 j, 20 j, 50 j, 100 j, 150 j, 200 j, 250 j, 300 j, 350 j, 400 j, 450 j, 500 j, 550 j, 600 j, 650 j, 700 j, 750 j, 800 j, 900 j, 1000 j, 1100 j, 1250 j, 1500 j, 2000 j, or greater.

FIG. **12A** is a side view of a drive mechanism having the cupped flywheel **702** and a driver profile **610** which is in an engaged state. In FIG. **12A**, the driving process is shown at a point of the sequence in which the driver profile **610** is frictionally engaged with the cupped flywheel **702**. At this stage the cupped flywheel **702** will impart energy to the driver profile **610** which bears the driver blade **54**. This energy will propel the driver profile toward the nosepiece **12**, which in the example of FIG. **12A** is the latched nosepiece **13**.

There is no limitation to the driving force which can be imparted to the driver profile **610** and/or the driver blade **54**. For example, any of the flywheels disclosed herein can impart a driving force in a range of from less than 2 j to 1000 j, or greater. For example cupped flywheel **702** can impart a driving force to the driver profile **610** and/or the driver blade **54** of less than 1 j, 2 j, 4 j, 8 j, 10 j, 15 j, 20 j, 25 j, 50 j, 75 j, 90 j, 100 j, 125 j, 150 j, 175 j, 200 j, 250 j, 300 j, 350 j, 400 j, 500 j, 1000 j, 15000 j, or greater.

There is no limitation to the torque generated by the inner rotor motor **500**. For example, any of the flywheels disclosed herein can be driven by the inner rotor motor **500** which can generate a torque in the range of from less than 0.005 Nm to 10 Nm, or greater. For example, the inner rotor motor **500** can generate any torque in the range of from less than 0.005 Nm, 0.01 Nm, 0.05 Nm, 0.075 Nm, 0.09 Nm, 0.1 Nm, 1.5 Nm, 2 Nm, 2.5 Nm, 3 Nm, 3.5 Nm, 4 Nm, 4.5 Nm, 5 Nm, 6 Nm, 7 Nm, 10 Nm, or greater.

There is no limitation to the velocity of the driver profile **610** at which any of the many types and variations of flywheels operate. For example, any of the driver profile **610** disclosed herein can be operated at any velocity in the range of from less than 10 ft/s to 400 ft/s, or greater. For a power tool and/or fastening device having the cupped flywheel **702** can have the driver profile **610** which can have a velocity of for example, 2.5 ft/s, 5 ft/s, 7.5 ft/s, 9 ft/s, 15 ft/s, 20 ft/s, 25 ft/s, 30 ft/s, 50 ft/s, 75 ft/s, 90 ft/s, 100 ft/s, 125 ft/s, 150 ft/s, 175 ft/s, 190 ft/s, 200 ft/s, 250 ft/s, 300 ft/s, 350 ft/s, 400 ft/s, or greater.

FIG. **12B** is a side view of a drive mechanism having the cupped flywheel and a driver which are in an engaged state and shows an embodiment in which the flywheel ring centerline plane **1600** is coplanar with the driver centerline plane **1500**. FIG. **12B** provides a detailed illustration of the geometry of the example embodiment disclosed in FIG. **12A**. In an embodiment, a cantilevered flywheel member such as the flywheel ring **750** can be positioned along its rotational plane to have a flywheel ring center line plane **1600** coplanar to a driver centerline plane **1500**. There is no limitation to the geometries and configurations which can be used to coordinate a portion of the flywheel **700** to contact the driver profile **610**. In the embodiment shown in FIG. **12A**, the cupped flywheel **702** has a cantilevered position of a portion of cupped flywheel body **710** and flywheel ring **750** such that they are projected over at least a portion of the inner rotor motor **500**.

In the example of FIG. **12B**, the alignment of the flywheel ring center line plane **1600** coplanar to the driver centerline plane **1500** can further be positioned coplanar to a plane extending from the channel centerline **429** shown in FIG. **6**. In the embodiment of FIG. **12B**, the radial centerline **1602**

of the flywheel ring **750**, the driver profile centerline **1502**, driver blade centerline **1554** and the channel centerline **429** can be coplanar.

In an embodiment, the radial centerline **1602** of the flywheel ring **750** and the centerline of the driver profile centerline **1502** can be parallel. In an embodiment, the radial centerline **1602** of the flywheel ring **750** and the centerline of the channel centerline **429** can be parallel. In an embodiment, the driver profile centerline **1502** and the channel centerline **429** can be parallel. In an embodiment, the driver profile centerline **1502** and the driver blade centerline **1554** can be parallel. In an embodiment, the driver profile centerline **1502** and driver blade centerline **1554** can be collinear. In an embodiment, the driver profile centerline **1502**, the driver blade centerline **1554** and the channel centerline **429** can be collinear.

There is no limitation to the geometries that can be used regarding the coordination of the components of the drive mechanism disclosed herein. In another embodiment, the driver blade centerline **1554** can be coplanar with the flywheel ring centerline plane **1600**. This allows for many configurations of the driver blade **54** and flywheel **700** to achieve a successful driving of the driver blade **54**. In another embodiment, the driver profile centerline **1502** can be coplanar with the flywheel ring center line plane **1600**. Many configurations of the driver profile **610** and flywheel **700** can achieve a successful driving of the driver profile **610**. In another embodiment, the channel centerline **429** can be coplanar with the flywheel ring center line plane **1600**. Many configurations of the channel **52** and flywheel **700** can achieve a successful driving of a nail **53**.

While the embodiment of FIG. **12B** shows the radial centerline **1602** of the flywheel ring **750** and the driver profile centerline **1502** in a coplanar arrangement, arrangements which are not coplanar can also be used. For example, configurations can be used in which the driver blade centerline **1554** is not coplanar with the radial centerline **1602** of the flywheel ring **750**. In other examples, configurations can be used in which the radial centerline **1602** of the flywheel ring **750** and the channel centerline **429** are not coplanar. In another embodiment, the driver blade centerline **1554** is not collinear with the driver profile centerline **1502**.

There is also no limitation to an angle of contact which generates friction and/or otherwise transfers energy between the flywheel **700** and the driver profile **610** and/or driver blade **54**. FIG. **12B** illustrates a tangential contact between a portion of the driver profile **610** and the flywheel ring **750**. Any angle sufficient to allow a transfer of energy from the flywheel **700** to the driver profile **610** and/or directly to the driver blade **54** can be used. For example, a contact between the flywheel **700** can be configured such that the flywheel ring centerline plane **1600** intersects the driver centerline plane **1500** at an angle, such as at an angle less than 90°, or less than 67°, or less than 45°, or less than 34°, or less than 25°, or less than 18°, or less than 15°, or less than 10°, or less than 5°, or less than 3°.

FIG. **13** is a side view of a drive mechanism having the cupped flywheel and a driver profile **610** which has progressed in its driving action to a position striking a fastener. FIG. **13** illustrates the driver profile **610** at a position in which is still engaged with the flywheel ring **750**, yet is near the end of its driving motion which terminates when the driver profiles motion toward the nosepiece assembly **12** ceases and the motion of profile **610** toward the nosepiece **12** stops and/or when recoil begins of the driver profile **610** back toward its original configuration as show in FIG. **11**.

Arrow **2000** indicates the direction of motion of the driver profile **610** during a driving action.

FIG. **13A** is a perspective view of a drive mechanism which is in a driven state and which has the cupped flywheel **702**. The cupped flywheel **702** of FIG. **13A** has a sound damping member **1015** having the sound damping material **1010**. The sound damping member **1015** is in the form of a sound damping tape **1050** and can be wrapped around and/or covering a flywheel body outside surface **7101** in part or wholly. FIG. **13A** also shows a sound damping cover **1220** which covers and/or is affixed to at least a portion of the flywheel face **703**. The sound damping cover **1220** can be adhered to and/or cover all or part of the flywheel face **703**.

FIG. **14** is a side view of a drive assembly having the cupped flywheel **702**. FIG. **14** shows an example embodiment of a nailer drive mechanism at the state in which the driver profile **610** has initially and tangentially made frictional contact with the flywheel ring **750**. This is a position analogous to that depicted in FIG. **12**. FIG. **14** illustrates an embodiment of the driver assembly **800** including an activation mechanism **820** which has an activation member **830** which by its movement can impart a force along the engagement axis **1800** (also illustrated in FIG. **12B** as a +y and -y axis) which causes the driver profile **610** to come into frictional contact with flywheel **700** to effect a driving motion of driver profile **610**. The engagement movement of activation member **830** is reversible and illustrated by a double pointed engagement movement arrow **835**. FIG. **14** also illustrates an embodiment of a driver profile return mechanism **1700** which absorbs recoil energy and guides the driver profile **610** back to its resting state, prior to another driving action.

FIG. **15** is a top view of a partial drive assembly having the cupped flywheel. FIG. **15** shows the driver profile **610** at a resting state. FIG. **15** also illustrates the parallel and/or coplanar configuration of the driver profile centerline **1502**, the flywheel ring centerline plane **1600** and the driver blade centerline **1554**.

FIG. **16A** is a perspective view of a drive assembly having the cupped flywheel **702** shown in conjunction with the magazine **100** feeding the plurality of nails **55**. FIG. **16A** illustrates a driver assembly **800** in conjunction with the driver profile **610** and cantilevered drive **1900**. The cantilevered drive can have an inner rotor motor **500** and the cupped flywheel **702**, as well as a geared flywheel ring **760** which can frictionally engage the driver profile **610** when activated by the activation mechanism **820**. In this example embodiment, the power tool is the nailer **1** having the latched nosepiece assembly **13** and the magazine **100** feeding a plurality of nails **55**.

FIG. **16A1** is an exploded view of the drive assembly having the cupped flywheel **702**, which is also configured as the cantilevered flywheel **899** and the sound damping member **1015** which is optionally the sound damping tape **1050**. FIG. **16A1** shows a cantilevered flywheel assembly **1899** having a frame **1260** with a frame cover **1275** which supports a flywheel assembly **705** and a motor assembly **508**. The cantilevered flywheel assembly **1899** can also have an end cap **1295**.

The non-limiting example of FIG. **16A1** shows a flywheel assembly **705** which has a flywheel **700** and which is the cantilevered flywheel assembly **1899** having the cantilevered flywheel **899**. In the embodiment of FIG. **16A1**, the cantilevered flywheel **899** is shown as the cupped flywheel **702**. The flywheel assembly **705** can be at least in part supported by a retaining ring **1265** and a bearing ball **521**. The sound damping member **1015**, which can be the sound

damping tape **1050**, is shown configured and adhered to the flywheel ring inner surface **1706** of the cupped flywheel **702**.

The motor assembly **508** can have the inner rotor motor **500** which has a magnet ring **531**, which can at least in part surround an armature **535**, as well as having an upper brush box **532**, a lower brush box **533** and an end bridge **537** configured with a bearing plug **523** and an end bridge screw **538**. Motor control elements and systems can broadly vary. The example of FIG. **16A1** shows motor control components which include a thermistor **539**, a hall sensor **1285** which can be mounted on a pc board **1290** and which can be engaged with a hall sensor board mount **1280**. The end bridge **537** can optionally be secured by one or more of an end bridge screw **538** and can be covered at least in part by the end cap end cap **1295**.

FIG. **16A2** is a side view of the exploded view of the drive assembly of FIG. **16A1** having the cupped flywheel **702** and the sound damping tape **1050**.

FIG. **16A3** is a side view of the drive assembly of FIG. **16A1** when assembled and having the cupped flywheel **702** and the sound damping tape **1050**. The drive assembly can have a flywheel assembly **705** and a motor assembly **508** supported by a frame **1260** having a frame cover **1275**. The drive assembly can be covered at least in part by the end cap **1295**.

FIG. **16A4** is a sectional view of the assembled drive assembly of FIG. **16A1** having the cupped flywheel **702** and the sound damping tape **1050**. FIG. **16A4** shows a flywheel assembly **705** which is the cantilevered flywheel assembly **1899** and which has a cupped flywheel **702** which is the cantilevered flywheel **899** which can have the flywheel ring **750**. The cantilevered flywheel **899** has the sound damping member **1015** having the sound damping material **1010**. The sound damping member **1015** is shown as the sound damping tape **1050**.

The sound damping tape **1050** is shown to have an adhesive surface **1051** adhered and/or affixed to the flywheel ring inner surface **1706**. The sound damping tape **1050** is shown to extend along at least a portion of, or all of, the flywheel ring inner circumference **707**. The cantilevered flywheel **899** to which the sound damping tape **1050** is affixed cantilevers over at least a portion of the magnet ring **531** (e.g. FIG. **16A4**) and/or the motor housing **510** (e.g. FIG. **10C**, **13A**). The sound damping tape **1050** affixed to the cantilevered portion of the cantilevered flywheel **899** can be in part or wholly cantilevered over at least a portion of the magnet ring **531** and/or the motor housing.

In an embodiment, the sound damping member and/or material can have an adhesion to steel in a range of from 25 N/100 mm to 100 N/100 mm or greater; such as 25 N/100 mm to 50 N/100 mm, 30 N/100 mm to 70 N/100 mm, 50 N/100 mm to 100 N/100 mm, or 75 mm to 100 N/125 mm or greater. In an embodiment the adhesion to steel at a temperature in a range of from -32° C. (negative 32° C.) to 80° C. can be from 25 N/100 mm to 100 N/100 mm or greater; such as 25 N/100 mm to 50 N/100 mm, 30 N/100 mm to 70 N/100 mm, 50 N/100 mm to 100 N/100 mm, or 75 mm to 100 N/125 mm or greater. In an embodiment the adhesion to steel at a temperature in a range of from -25° C. (negative 25° C.) to 50° C. can be from 25 N/100 mm to 100 N/100 mm or greater; such as 25 N/100 mm to 50 N/100 mm, 30 N/100 mm to 70 N/100 mm, 50 N/100 mm to 100 N/100 mm, or 75 mm to 100 N/125 mm or greater. In an embodiment, the adhesion to steel at a temperature in a range of from 0° C. to 40° C. can be from 25 N/100 mm to 100 N/100 mm or greater, such as 25 N/100 mm to 50 N/100

mm, 30 N/100 mm to 70 N/100 mm, 50 N/100 mm to 100 N/100 mm, or 75 mm to 100 N/125 mm or greater.

FIG. 16B is a sectional view of the drive assembly shown in FIG. 16 having the cupped flywheel sectioned along the longitudinal centerline plane of the rotor shaft. FIG. 16 illustrates a cross-section of the activation mechanism 820 and driver profile 610 bearing driver blade 54. In this embodiment, the driver profile 610 is engaged by the flywheel ring 750. The cupped flywheel 702, the flywheel ring 750, the inner rotor motor 500, the rotor shaft 550 and flywheel bearing 770 are shown in cross-section. FIG. 16B also illustrates a bearing support ring 920 which in the cross-section is shown as a ring of extra material having a thickness provided to strengthen the transition of shape (the approximate 90 degree angle) between the flywheel bearing 770 longitudinal axis and the plane of the flywheel face 703. The bearing support ring 920 can be of a single body construction strengthening the transition of material between the bearing 770 and flywheel face 703.

FIG. 17 is a sectional view of a drive assembly having the cupped flywheel 702 taken along the driver centerline plane 1500 of the driver profile. FIG. 17 is a sectional view of the driver assembly 800 example of FIG. 16A, which in FIG. 17 is shown in a cross-sectional view taken along the flywheel ring centerline plane 1600. In the example of FIG. 17, the driver centerline plane 1500 and the flywheel ring centerline plane 1600 are shown in a coplanar configuration. FIG. 17 illustrates an example of the alignment of the flywheel ring 750, the driver profile 610 and the driver blade 54 in conjunction with the activation mechanism 820. The stator 530 and inner rotor 540 of inner rotor motor 500 are shown in cross-section.

FIGS. 18A-G show a variety of embodiments of cantilevered flywheel designs. There is no limitation to the design of the cantilevered flywheels or regarding the means of supporting such flywheels or transferring their energy to a moveable member, such as the driver profile 610. The various cantilevered flywheel designs can have a contact surface 715, as shown in non-limiting example in FIGS. 18A, 20, 21, 22 and 23. The contact surface 715 can be any portion of the flywheel which contacts another member and which imparts energy to another member.

The contact surface 715 in its many types and variations can impart energy to the driver profile 610 and/or driver blade 54. The interface between the contact surface 715 and the driver profile 610 and/or driver blade 54 can have a breadth of variety. For example, the interface can produce a frictional contact (e.g. FIG. 20) or a geared contact (e.g. FIGS. 10A, 10B and 21). The shape of the contact surface 715 can range from flat or flattened, to rough or patterned, to having large gearing. The shape of the contact surface in an axial direction along the -x to +x axis (FIG. 12B) can be any shape in the range of concave to convex. Additionally, the contact surface 715 can have a surface which is sinusoidal, grooved, adapted for a lock and key interface, pitted, nubbed, having depressions, having projections, or any of a variety of topography which can adapt the contact surface 715 to impart energy to another object and/or item, such as the driver profile 610 and/or driver blade 54, or moveable member, gear or other member.

FIG. 18A is a perspective view of the cupped flywheel 702 having the geared flywheel ring 760. In the example of FIG. 18A, the contact surface 715 is shown as a geared surface of the geared flywheel ring 760. In the example of FIG. 20, the contact surface 715 is a flattened surface which can cause another member to rotate or otherwise move. In the example of FIG. 22, the contact surface 715 is a grinding

surface of a flywheel ring grinder portion which can remove material from another article. In the example of FIG. 23, the contact surface 715 is a saw tooth portion of flywheel ring saw portion 767. In the many and varied embodiments, the contact surface 715 can be in a position cantilevered to rotate radially about at least a portion of the motor housing 510 and inner rotor motor 500.

FIG. 18B is a view of the cupped flywheel having a number of flywheel openings in the flywheel face. In the example of FIG. 18B, a number of flywheel openings 720 are present and pass through the flywheel face 703. There is no limitation regarding the shape of the openings which are used with the cupped flywheel 702. If the flywheel cup material is sufficiently thick, grooves or other features which can reduce the weight of the cupped flywheel 702 can be used whether or not an opening is created in any portion of the cupped flywheel 702.

FIG. 18C is a view of the cupped flywheel 702 having a number of flywheel slots in a flywheel body 710. The cupped flywheel can have a flywheel slot 725 or a number of flywheel slots. Herein, a number of flywheel slots are also collectively referenced by the numeral 725. FIG. 18C shows the cupped flywheel 702 which has the number of flywheel slots 725 present in the flywheel body 710. The number of the flywheel slots 725 can reduce the weight of the flywheel 700, achieve a desired rotation balance of the flywheel, achieve inertial specifications of the flywheel 700 and meet performance specifications for the flywheel 700. The number of flywheel slots 725 in the cupped flywheel 702 can be used to achieve design benefits, such as weight control and improved performance, analogous to those achieved by using a number of the flywheel openings 720, or openings of other shapes.

FIG. 18D is a view of the cupped flywheel 702 having the number of slots 725 present in the flywheel body 710 as well as present in the flywheel face 703.

FIG. 18E is a view of the cupped flywheel having a number of flywheel round openings 703 in a flywheel body 710 and flywheel face 703. In the example of FIG. 18E, the cupped flywheel 702 has a number of flywheel round openings 730 present in the flywheel body 710, as well as present in the flywheel face 703. While FIG. 18E illustrates an example having a round opening, there is no limitation regarding the shape of the openings that can be used with any variety of the flywheel 700 disclosed herein. For example, openings can be round, oval, oblong, irregular, slots, decoratively shaped, patterned, triangular, square, polygonal, rectangular, or any desired shape and/or pattern.

FIG. 18F is a view of the cupped flywheel having a mesh flywheel body and mesh flywheel face. There is no limitation as to the nature of the material which supports the contact surface 715 and imparts energy and/or rotational motion from the inner rotor motor 500. Any material which supports the contact surface in a cantilevered position about at least a portion of the inner rotor motor 500 and/or the motor housing 510 can be used. FIG. 18F illustrates an example embodiment in which a flywheel mesh structure 740 is used to support the flywheel ring 750 having a contact surface 715 which is a geared surface.

This disclosure is not limited to a cup-shaped flywheel. The flywheel 700 can be any type of flywheel which supports the contact surface 715 in a cantilevered position about at least a portion of the inner rotor motor 500 and/or the motor housing 510.

FIG. 18G is a view of a cantilevered flywheel ring supported by a number of flywheel struts 713. In the example shown in FIG. 18G, the contact surface 715 is the

25

surface of the geared flywheel ring **760**. In this embodiment, the geared flywheel ring **760** is supported by a number of flywheel struts **713**. In this example, the number of flywheel struts **713** can be coupled to flywheel bearing **770** which can be driven by the rotor shaft **550**.

There is no limitation regarding the relative geometries of the features of the cupped flywheel **702**. FIG. **19A** is a perspective view of the cupped flywheel having dimensions. The example embodiment of FIG. **19** illustrates the flywheel **700** which is the cupped flywheel **702** having a flywheel outer diameter **704** and a flywheel inner diameter **706**. The cupped flywheel **702** is born by the flywheel bearing **770** having a flywheel bearing length **772** and a flywheel bearing thickness **815**. In an embodiment, a bearing support ring **920** having a bearing support ring width **926** of material can be used to transition the flywheel face **703** material and the flywheel bearing **770** between a bearing support ring outer diameter **811** (also shown as support outer diameter **922**) and the flywheel inner diameter **706**. As shown in FIG. **19A**, the bearing support ring **920** and the flywheel bearing **770** can be supported by material at an interfacing portion which can be of one body in construction and which can extend between the bearing support ring inner diameter **924** and bearing support ring outer diameter **811**. The flywheel bearing **770** can be coupled to rotor shaft **550** at an interface between flywheel bearing inner diameter **813** and rotor shaft **550** having a rotor outer diameter **552**. The cupped flywheel **702** can have a flywheel body outside diameter **708** from which a flywheel ring can extend radially in a direction away from the rotor shaft **550** and have a flywheel ring height **752** as measured in FIG. **19A** between the flywheel outer diameter **704** and the flywheel body outside diameter **708**. The flywheel ring **750** can also have an outer diameter **751**.

The cupped flywheel **702** can have a flywheel length **711** which in projection can be composed of a flywheel ring length **754**, a flywheel body length **712** of flywheel body **710** and a flywheel bearing length **772**. A flywheel cup length **714** can have a length which in its projection can be composed of the flywheel ring length **754** and the flywheel body length **712**. Optionally, the flywheel bearing can be flat with the flywheel face **703**, not have a projection and not contribute to the flywheel length **711**. In other embodiments, the flywheel bearing is not used and has no contribution to the flywheel length **711**.

FIG. **19A** illustrates the cupped flywheel **702** having the flywheel ring **750** which has the contact surface **715** which is grooved and/or geared forming the geared flywheel ring **760**. There is no limitation to the type of gearing, grooving or surface characteristics of the contact surface **715**. In the embodiment of FIG. **19A**, the geared flywheel ring **760** has flywheel ring length **754** and a number of gear teeth. As shown in FIG. **19A**, the geared flywheel ring **760** has a first gear tooth **781** having first gear tooth width **791**, a second gear tooth **785** having second gear tooth width **795**, and a third gear tooth **789** having third gear tooth width **799**. The first gear tooth **781** can be separated from the second gear tooth **785** by a first gear groove **783** having first gear groove width **792**. The second gear tooth **785** can be separated from the third gear tooth **789** by a second gear groove **787** having second gear groove width **797**.

FIG. **19B** is an example of cupped flywheel having a narrow cup and wide flywheel ring. FIG. **19B** is an example of another dimensional configuration of the cupped flywheel **702** having the flywheel ring **750**. In the embodiment of **19B** the flywheel body outside diameter **708** is less than that of the embodiment illustrated in FIG. **19A** and the flywheel ring height **752** is greater than that of the embodiment

26

illustrated in FIG. **19A**. Any dimension of the flywheel **700** and the cupped flywheel **702** can be set to meet any design specifications.

The application and use of a flywheel **700** which is a cantilevered flywheel **899**, such as cupped flywheel **702** is not limited by this disclosure. In addition to a nailer **1**, the cantilevered flywheel **899** which can be driven by an inner rotor motor **500** can be used with any power tool which can receive power from a flywheel directly or by means of a mechanism receiving power from the cantilevered flywheel **899**. FIGS. **20** and **21** show examples to drive mechanisms which can use the cantilevered flywheel **899**. FIGS. **22**, **23** and **24** show examples types of power tool applications which can use the cantilevered flywheel **899**. Power tools which can use the technology of this disclosure include but are not limited to fastening tools, material removal tools, grinders, sanders, polishers, cutting tools, saws, weed cutters, blowers and any power tool having a motor, such as in non-limiting example an inner rotor motor, whether brushed or brushless.

FIG. **20** is an embodiment of the cupped flywheel roller drive mechanism. In the example of FIG. **20**, the flywheel ring **750** is a flywheel ring having flattened contact surface **761** having the contact surface **715** which is flattened in shape and which drives a first drive wheel **897** which drives a second drive wheel **898**.

FIG. **21** is an embodiment of the cupped flywheel **702** having a flywheel ring **750** having axial gears. In the example of FIG. **21**, the flywheel ring **750** is a flywheel ring having axial gears **763** which drives a gear **779**.

FIG. **22** is an embodiment of the cupped flywheel **702** having the flywheel ring **750** which has a flywheel ring grinder portion **765**.

FIG. **23** is an embodiment of the cupped flywheel **702** having the flywheel ring **750** which has a flywheel ring saw portion **767**.

The cantilevered flywheel **899** can be used in any appliance which can receive power from a flywheel. FIG. **24** is an embodiment of the cupped flywheel **702** having the flywheel ring **750** which has a flywheel ring fan portion **769**. The cantilever flywheel **899** can also be used in appliances such as fans, humidifiers, computers, printers, devices with brushed inner rotor motors, devices with brushless inner rotor motors and devices with motors having outer rotors. The cantilever flywheel **899** can also be used in automobiles, trains, planes and other vehicles. The cantilever flywheel **899** can be used in any device having an inner rotor motor.

FIG. **25** is a perspective view of an impact driver **1101**. FIG. **1** shows an example of a fastening tool **1001** which is an impact driver **1101** having a housing **4** which houses an impact driver motor **20** (FIG. **26**), drive mechanism **25** (FIG. **26**), a handle **6** and base portion **8** with battery pack **11**. The impact driver also has a driver control system which can control the impact driver motor **20** and a drive mechanism **25** which can have a gearbox **30** and bit holder assembly **15** which can be driven by the drive mechanism **25**. In non-limiting example, the tool can be a screwdriver bit, a drill bit, or other bit which is compatible with driving a given fastener.

FIG. **26** is an exploded view of an impact driver **1101** having sound damping material **1010**. FIG. **3** shows the impact driver **1101** in an exploded state. FIG. **3** shows the housing **4** having a left housing **4L** and a right housing **4R** configured to house a drive mechanism **29** having an impact driver motor **20**, a gearbox **30** and a bit holder assembly **15**. The gearbox can have a hammer **1111** (FIG. **27**) and an anvil

2222 (FIG. 27). FIG. 3 also shows a driver control system 40 which can have a switch assembly 5015 and a pc board 555.

FIG. 27 is a sectional view of an impact mechanism 919 having the sound damping material 1010 applied to the housing 4 and also applied to the hammer 1111. FIG. 4 shows a nose housing 14 covering at least in part the impact mechanism 919 which has a gearbox 30, the hammer 1111, an anvil 2222 and a hammer spring 3013. In the embodiment of FIG. 4, the impact driver motor 20 provides energy to rotate an output spindle 95 in conjunction with gears 31 of the gearbox 30. In the embodiment of FIG. 27, the rotation of the output spindle 95 imparts energy to the hammer 1111 which energizes the hammer 1111 to rotate. Optionally, one or more of a hammer bearing 1102 can be used to guide the motion of the hammer 1111 and can facilitate the axial motion of the hammer 1111 along a length of an output spindle centerline and, optionally, a hammer guide groove. The hammer 1111 has a number of the hammer lug 8110 and which are positioned to respectively contact a corresponding number of an anvil lug 210 of the anvil 2222 (FIG. 28). The rotating hammer 1111 can impart energy to the anvil 2222 to achieve a rotational motion of the anvil 2222. The rotational motion of the anvil 2222 can cause a tool, such as a bit which can be held in the bit holder assembly 15, to turn. The turning of the tool, such as a bit, when applied to a fastener can drive the fastener into a work piece. An impact driver can have a portion of a driving sequence for a fastener which is an impacting phase.

When a resistance to turning of a fastener reaches a hammer retraction resistance, the hammer 1111 will move axially away from a portion of the anvil base 202 along output spindle axis 1000 with the guidance of one or more hammer bearings 1102 and the guide groove and be allowed to clear the anvil in a manner in which the hammer 1111 can rotate faster than the anvil 2222 for at least a part of a revolution of the hammer 1111. Then, the hammer 1111 can move axially along output spindle axis to return to a position to impact against and impart rotational energy to anvil 2222. This impacting sequence can be repeated until a driver release condition exists, or the trigger is released.

Undesired sound and/or noise can be emitted from the impact driver and/or impact mechanism during operation. The application of one or more sound damping members and/or vibration absorption members significantly reduces and/or eliminates such undesired sound. FIG. 27 illustrates a number of the sound damping member 1015 which has the sound damping material 1010. As shown in FIG. 27, a first of the sound damping member 1015 is the sound damping sheet 1210 which has been applied at least a portion of the inner surface of housing 4. A second of the sound damping member 1015 is the sound damping tape 1050 which is applied to at least a portion of the hammer 1111. FIG. 28 shows a hammer 1111 having the sound damping material 1010, which is the sound damping tape 1050. The sound damping tape 1050 of the hammer 1111 is applied to at least a portion of the hammer 1111.

The anvil 2222 of FIG. 28 has the sound damping material 1010, which is the sound damping tape 1050. The sound damping tape 1050 of the hammer 2222 is applied to at least a portion of the hammer 2222.

Example 1 and Example 2

FIGS. 29 through 36 collectively relate to Example 1 and Example 2. FIG. 29 shows the cupped flywheel without a sound damping member tested in Example 1. FIG. 30 shows

of the cupped flywheel having a sound damping member tested in Example 2. FIGS. 31 through 36 collectively regard data and results from Example 1 and Example 2.

Example 1 and Example 2 regard comparative testing between a cupped flywheel 702 without a sound damping member 1015 and a cupped flywheel with a sound damping member 1015. The embodiment of the sound damping member 1015 tested in Example 1 and Example 2 is a vibration absorption member 1020.

Example 1 and Example 2 followed a Vibration And Sound Evaluation Procedure (“VASE Procedure”) which has the following steps:

Step 1. Suspend a part by a means that does not influence the vibration and sound reaction and/or response (string, small wire, etc.) when the part, such as the cupped flywheel 702, is struck by a modal hammer 2530. As shown in FIG. 29, the parts of Example 1 and Example 2 were suspended by a zip tie 2510 which is thin and which is attached to the outside surface of the flywheel bearing 770.

Step 2. Attach the accelerometer 2520 to the part, such as the cupped flywheel 702, in a position that does not influence the vibration and sound reaction and/or response when the part is struck by the modal hammer 2530. In Example 1 and Example 2 the accelerometer 2520 was reversibly attached to the flywheel face 703 at a point proximate to the flywheel bearing 770 and not on the resonating region of the flywheel body 710, as shown in FIG. 30.

Step 3. Impact the part on the outer surface of the flywheel ring 750 with a modal hammer 2530 having an output to a spectrum analyzer. The striking force is normalized by dividing the acceleration (response) by the force (input) of the modal hammer 2530 strike. This data analysis and normalization is achieved by:

Sub-step 3.1. Acquire a signal from the accelerometer and hammer;

Sub-step 3.2. Apply a transfer function or frequency response used to normalize the results, to acceleration/force;

Step 4. Average the results of the data output from Step 3 for a number of trials 1 . . . n, e.g. n=5 trials, where n can be from 2 to a large number, such as 50 trials.

The results for Example 1 and Example 2 from the VASE Procedure identify resonances and damping. The respective data results disclosed herein of Example 1 and Example 2 are the averaged results respectively of the output data from 5 trials for each of Example 1 and Example 2.

The data results for Example 1 are the averaged results of the output data from 5 strikes (also herein as, 5 trials) of the cupped flywheel 702 without a sound damping member 1015 by the modal hammer, i.e. n=5. In Example 1, each strike of the modal hammer and the results produced from that 1 strike are 1 trial.

The data results for Example 2 are the averaged results of the output data from 5 strikes (5 trials) of the cupped flywheel 702 with the sound damping member 1015 by the modal hammer, i.e. n=5. In Example 2, each strike of the modal hammer and the results produced from that 1 strike are 1 trial.

FIG. 29 shows the cupped flywheel without a sound damping member tested in Example 1. FIG. 29 shows a cupped flywheel 702 suspended by a zip tie 2510 in accordance with the VASE Procedure and having an accelerometer 2520 attached. The cupped flywheel 702 used in Example 1 does not have a sound damping member 1015. Modal hammer 2530 is also shown which is used to strike the cupped flywheel 702 along striking arc 2540 for each trial.

FIG. 30 shows the cupped flywheel having a sound damping member 1015 tested in Example 2. FIG. 30 shows the cupped flywheel 702 suspended by a zip tie 2510 in accordance with the VASE Procedure and having an accelerometer 2520 attached. The cupped flywheel 702 used in Example 2 has a sound damping member 1015 which is a sound damping tape 1050. The sound damping tape 1050 has the sound damping material 1010. Modal hammer 2530 is also shown which is used to strike the cupped flywheel 702 along striking arc 2540 for each trial.

For Example 1, FIG. 31 shows a graph of vibration response H1 data for the test of the cupped flywheel 702 without a sound damping member 1015. The frequency response for the cupped flywheel 702 without a sound damping member 1015 of Example 1 was 1,310 (m/s²)/lb at 4,526 Hz.

In an embodiment, the sound damping member, which can be a vibration absorption member, provides vibration damping in a frequency range of at least 80 Hz to 50,000 Hz, such as 1000 Hz to 20,000 Hz, or 500 Hz to 15,000 Hz, or 500 Hz to 15,000 Hz, or 1000 Hz to 10,000 Hz, or 1000 Hz to 8,000 Hz, or 1000 Hz to 5,000 Hz, or 500 Hz to 30,000 Hz, or 500 Hz to 20,000 Hz.

In an embodiment, the sound damping member provides sound damping of noise from a part which is damped in a frequency range of at least 80 Hz to 50,000 Hz, such as 1000 Hz to 20,000 Hz, or 500 Hz to 15,000 Hz, or 500 Hz to 15,000 Hz, or 1000 Hz to 10,000 Hz, or 1000 Hz to 8,000 Hz, or 1000 Hz to 5,000 Hz, or 500 Hz to 30,000 Hz, or 500 Hz to 20,000 Hz.

In an embodiment a decrease in emitted noise from the part and/or vibration of the part can be reflected in a vibration damping ratio. The vibration damping ratio is a measure of the decrease in signal amplitude as a function of time. The vibration damping ratio herein is calculated as follows: Vibration damping ratio=actual damping/critical damping, taken at the resonant frequency.

In example 1 and example 2, the frequency response and vibration damping ratio were tested using a Bruel & Kjaer Noise and Vibration Measurement System (BK NVMS) (433 Vincent Street West, West Leederville, Wash. 6007) which receives input from a modal hammer. Further, in Example 1 and Example 2, a BK NVMS acquisition system was employed in conducting the data analysis and vibration damping ratio calculations.

A vibration damping ratio 0.039% was found for the cupped flywheel 702 without a sound damping member 1015 tested in Example 1.

In Example 1 and Example 2 the frequency response H1 is normalized as acceleration/pounds force, i.e. (m/s²)/lbf (also "(m/s²)/lb_f").

As shown in FIGS. 31 through 36, damping is shown to create the difference in vibration which produces differences and/or reductions in noise and/or sound.

FIGS. 31 and 32 each provide a value of Delta f. Delta F is the half power bandwidth. Delta f 3 dB correlates to two points on either side of the peak at this 3 dB reduction on the FFT (fast Fourier transform output). The larger the Delta f 3 dB or range between the points, the greater damping.

FIG. 32 shows a graph of vibration response dated for the cupped flywheel having a sound damping member 1015 tested in Example 2. The frequency response for the cupped flywheel 702 with a sound damping member 1015, which for Example 1 is the sound damping tape 1050, was 213 (m/s²)/lb_f at 4,436 Hz. In example 2, a vibration damping

ratio is 0.105% was found for the cupped flywheel 702 with the sound damping tape 1050 having sound damping material 1010.

The Delta f 3 dB values found in Example 1 and Example 2 were compared. FIG. 31 shows that that the testing of Example 1, which does not use the sound damping member 1015, yields a Delta f 3 dB of 3.5741 Hz. FIG. 32, shows that that the testing of Example 2, which uses the sound damping member 1015 applied to the cupped flywheel 702 and which is damped, has a Delta f 3 dB of 9.4012 Hz. Comparing the results of Example 2 which is damped by the use of the sound damping member 1015 to Example 1 which is not damped evidences the significant damping achieved. A ratio of the Delta f 3 dB for Example 2 to the Delta f 3 dB for Example 1 can be determined by 9.4012 Hz (Example 2)/3.5741 Hz (Example 1) to be equal to 2.63. It is shown by the ratio of Example 2 Delta f 3 dB to the Example 1 Delta f 3 dB that the half power bandwidth evidences significant damping by the use of a sound damping member 1015 (e.g. Example 2) as compared to an undamped test (e.g. Example 1).

FIGS. 33-36 are time plots which by comparison of results from Example 1 and Example 2 evidence the cupped flywheel 702 with the sound damping tape 1050 has much less energy and decays at a faster rate due to the higher vibration damping ratio.

FIG. 33 shows an excerpted graph of vibration response data displayed as Acceleration (m/s²) against Time (seconds(s)) for the cupped flywheel tested in Example 1 without a sound damping member.

FIG. 34 shows an excerpted graph of vibration response data displayed as Acceleration (m/s²) against Time (seconds(s)) for the cupped flywheel in Example 1 having a sound damping member.

FIG. 35 shows time versus response data for the Example 1 test of the cupped flywheel 702 without a sound damping member.

FIG. 36 shows time versus response data for the Example 2 test of the cupped flywheel 702 having a sound damping member.

The results of Example 1 and Example 2 evidence that the application of a sound damping member 1015 significantly reduces the magnitude of the vibration produced by a power tool and the amplitude of the sound produced by the vibration, as described in the present application. It has also been found that the magnitude of the vibration of a sound producing part, such as the cupped flywheel 702, can be reduced to a large degree, such as up to 80% reduction. For example, the maximum magnitude of a vibration produced by a power tool component or power tool may be reduced by 30% or more; 40% or more; 50% or more; 60% or more; 70% or more; or 80% or more, as compared to a power tool or component without a sound damping member. A sound produced can therefore be reduced. For example, a maximum amplitude of the sound can be reduced by 30% or more; 40% or more; 50% or more; 60% or more; 70% or more; or 80% or more, as compared to a power tool or component without a sound damping member.

The results of Example 1 and Example 2 evidence that the application of a sound damping member 1015 which is a vibration absorption member 1020 can significantly reduce the magnitude of the vibrations produced by a power tool and the noise and/or sound generated by such vibrations.

In non-limiting example, a hearing range for humans can be 20 Hz to 20,000 Hz and can be more sensitive in a narrower range, such as 100 Hz to 15,000 Hz or 1,000 Hz to 4,000 Hz. By reducing the magnitude of sound produced

by the power tool, the maximum value of the sound expressed as acceleration per pound-force ($\text{m/s}^2/\text{lb}_f$) over these frequency ranges can be kept at or below 1,000 ($\text{m/s}^2/\text{lb}_f$); at or below 800 ($\text{m/s}^2/\text{lb}_f$) at or below 600 ($\text{m/s}^2/\text{lb}_f$) at or below 500 ($\text{m/s}^2/\text{lb}_f$). As shown in FIG. 32, the maximum magnitude can be kept to 213 ($\text{m/s}^2/\text{lb}_f$) which occurs at a frequency of 4,436 Hz.

Further, vibrations of the cupped flywheel 702 over the frequency ranges of 20 Hz to 20,000 Hz, or 100 Hz to 15,000 Hz or 1,000 Hz to 4,000 Hz can be kept at or below 1,000 ($\text{m/s}^2/\text{lb}_f$) such as at or below 800 ($\text{m/s}^2/\text{lb}_f$) at or below 600 ($\text{m/s}^2/\text{lb}_f$) at or below 500 ($\text{m/s}^2/\text{lb}_f$) or at or below 500 ($\text{m/s}^2/\text{lb}_f$). As shown in FIG. 32, the maximum magnitude can be kept to 213 ($\text{m/s}^2/\text{lb}_f$) which occurs at a frequency of 4,436 Hz.

Decreasing the maximum magnitude of a sound and/or vibration produced by the power tool over the frequency ranges disclosed herein above can provide a more pleasant user experience by achieving a quieter operation of the power tool.

It has been found that the vibration damping ratio can be greatly improved by use of a sound damping member 1015, which can be a vibration damping member 1020. In non-limiting example, the vibration damping ratio can be increased by 50% or more, or 100% or more, by using a sound damping member 1015 as compared to not using a sound damping member 1015. When the vibration damping ratio is so increased, it can be greater than 0.05%; greater than 0.07%, or greater than 0.09%. As is evidenced by Example 2, the a vibration damping ratio of 0.105% was achieved by using a sound damping member 1015, which was a vibration absorption member 1020. Increasing the vibration damping ratio by the use of a sound damping member 1015, which can be a vibration absorption member 1020, greatly reduces the time during which a noise and/or vibration causing noise can have a significant resonance, as evidenced in the results disclosed in FIGS. 33 and 34. A vibration damping ratio in a range of 0.05% to 20% can be achieved by the use of the sound damping member 1015, which can be a vibration absorption member 1020.

The scope of this disclosure is to be broadly construed. It is intended that this disclosure disclose equivalents, means, systems and methods to achieve the devices, activities and mechanical actions disclosed herein. For each mechanical element or mechanism disclosed, it is intended that this disclosure also encompass and teach equivalents, means, systems and methods for practicing the many aspects, mechanisms and devices disclosed herein. Additionally, this disclosure regards a sound damping member, a vibration absorption member and a motor having a cantilevered flywheel and their many aspects, features, elements uses and applications. Such devices can be dynamic in their use and operation, this disclosure is intended to encompass the equivalents, means, systems and methods of the use of the power tool and its many aspects consistent with the description and spirit of the technologies, devices, operations and functions disclosed herein. The claims of this application are to be broadly construed.

The description of the inventions herein in their many embodiments is merely exemplary in nature and, thus, variations that do not depart from the gist of the invention are intended to be within the scope of the invention. Such variations are not to be regarded as a departure from the spirit and scope of the invention.

We claim:

1. An impact driver, comprising:
 - a housing;
 - a motor housed in the housing;
 - a drive system including a hammer and an anvil;
 - a bit holder assembly; and
 - a sound damping material which reduces sound produced by the impact driver, wherein the sound damping material is disposed between an innermost wall of the housing and the drive system.
2. The impact driver of claim 1, wherein the sound damping material is on the anvil.
3. The impact driver of claim 1, wherein the sound damping material is on the hammer.
4. The impact driver of claim 1, wherein the sound damping material is adjacent to the anvil.
5. The impact driver of claim 1, wherein the sound damping material is adjacent to the hammer.
6. The impact driver of claim 1, wherein the sound damping material is on the innermost wall of the housing.
7. The impact driver of claim 1, wherein the sound damping material is a sound damping tape.
8. The impact driver of claim 1, wherein the sound damping material is configured to absorb vibration from one or more parts of the impact driver.
9. An impact driver, comprising:
 - a housing;
 - a motor housed in the housing;
 - a drive system including a hammer and an anvil;
 - a bit holder assembly; and
 - a sound damping material that is configured to absorb vibration from one or more parts of the impact driver, wherein the sound damping material is disposed between an innermost wall of the housing and the drive system.
10. The impact driver of claim 9, wherein the sound damping material is on the anvil.
11. The impact driver of claim 10, wherein the sound damping material is on the hammer.
12. The impact driver of claim 9, wherein the sound damping material is on the hammer.
13. The impact driver of claim 9, wherein the sound damping material is adjacent to the anvil.
14. The impact driver of claim 13, wherein the sound damping material is adjacent to the hammer.
15. The impact driver of claim 9, wherein the sound damping material is adjacent to the hammer.
16. The impact driver of claim 9, wherein the sound damping material is on the innermost wall of the housing.
17. The impact driver of claim 9, wherein the sound damping material is a sound damping tape.
18. An impact driver comprising:
 - a housing;
 - a motor housed in the housing;
 - a drive system including a hammer and an anvil;
 - a bit holder assembly; and
 - a sound damping material which reduces sound produced by the impact driver, the sound damping material disposed on at least one of the hammer and the anvil.
19. The impact driver of claim 18, further comprising sound damping material disposed on an inside of the housing.
20. The impact driver of claim 18, wherein the sound damping material is configured to absorb vibration from one or more parts of the impact driver.