



US 20240265653A1

(19) **United States**

(12) **Patent Application Publication**  
**NEMETH et al.**

(10) **Pub. No.: US 2024/0265653 A1**

(43) **Pub. Date: Aug. 8, 2024**

(54) **INTEGRATED MANAGEMENT OF SENSITIVE CONTROLLED ENVIRONMENTS AND ITEMS CONTAINED THEREIN**

(71) Applicant: **CURRENT LIGHTING SOLUTIONS, LLC**, Beachwood, OH (US)

(72) Inventors: **Kenneth Craig NEMETH**, Montreal (CA); **Abdul Rahman Mohammed OMAR**, Montreal (CA)

(21) Appl. No.: **18/638,954**

(22) Filed: **Apr. 18, 2024**

**Related U.S. Application Data**


- (63) Continuation of application No. 17/251,631, filed on Dec. 11, 2020, now Pat. No. 11,989,836, filed as application No. PCT/US2019/036701 on Jun. 12, 2019.
- (60) Provisional application No. 62/683,997, filed on Jun. 12, 2018.

**Publication Classification**

- (51) **Int. Cl.**  
**G06T 19/00** (2006.01)  
**G01N 21/01** (2006.01)  
**G01N 21/88** (2006.01)
- (52) **U.S. Cl.**  
CPC ..... **G06T 19/006** (2013.01); **G01N 21/01** (2013.01); **G01N 21/8803** (2013.01); **G01N 2021/0137** (2013.01); **G06T 2219/028** (2013.01)

(57) **ABSTRACT**

A system (100) for monitoring a controlled spatial volume (102) includes a lighting fixture (104) with one or more embedded sensors (106), a communication device (108) to provide monitored sensor data (142) for storage within a data store (140), a server (130) including a data analytic unit (136) in communication with the data store, the data analytic unit accessing the monitored sensor data to analyze the monitored data and provide status information on the spatial volume. The server can include a machine vision unit (138) to analyze the monitored data and create augmented reality renditions (520), which are rendered for display to a user by an augmented reality application (160).






FIG. 1






FIG. 2A



- VISUALIZE ASSETS
- MONITOR AND LOG DATA
- DETERMINE TRENDS
- CONTROL OUTPUTS
- GENERATE ALARMS



THERMAL MAP 330

FIG. 3A

310

ZONES		ALARMS	CONTROL STRATEGY	SCHEDULE	OFF DELAY	OCCUPIED/ VACANT LEVEL	MAX/ MIN LEVEL
<input type="checkbox"/>	TEMPERATURE SENSING						
<input type="checkbox"/>	TEMPERATURE SENSING A						§ 0022810300b011b011b6 NTC 1 26.4°C § 0022810300b011b011b6 NTC 2 26.6°C § 0022810300b011b011b6 NTC 3 27.2°C § 0022810300b011b011b6 NTC 4 26.0°C
<input type="checkbox"/>	TEMPERATURE SENSING B						§ 0022810300b011b011bb NTC 1 27.5°C § 0022810300b011b011bb NTC 2 27.4°C § 0022810300b011b011bb NTC 3 27.0°C § 0022810300b011b011bb NTC 4 26.9°C
<input type="checkbox"/>	TEMPERATURE SENSING C						§ 0022810300b011b01219 NTC 4 28.5°C § 0022810300b011b01219 NTC 4 29.5°C § 0022810300b011b01219 NTC 4 28.2°C § 0022810300b011b01219 NTC 4 28.9°C

320




FIG. 3B

(CLICK A TEMPERATURE BAR ABOVE TO PAUSE THE VALUES)





FIG. 4B

FIG. 4A

INFRARED TRACKING



**FIG. 5**  
AUGMENTED REALITY (AR) DISPLAY



**INTEGRATED MANAGEMENT OF  
SENSITIVE CONTROLLED  
ENVIRONMENTS AND ITEMS CONTAINED  
THEREIN**

CLAIM OF PRIORITY

[0001] This patent application claims the priority benefit, under 35 U.S.C. § 119, of U.S. Provisional Patent Application Ser. No. 62/683,997, filed Jun. 12, 2018, titled “Integrated Management of Sensitive Controlled Environments and Items Contained Therein” the entire disclosure of which is incorporated herein by reference.

BACKGROUND

[0002] Monitoring many sensitive environments and items is often still done manually. There are some automated monitoring systems on the market, but they are not integrated into a lighting system. The existing automated solutions must be installed separately and are visible and accessible by customers. These can consist of environmental sensors with communication devices which sit on the shelf with the products, taking up space and getting in the way of customers and stocking operations. Customer tracking solutions exist, but are separate devices placed outside the environments. These tracking solutions do not have the same point of view as placing vision sensors directly in the monitored environments and therefore cannot gather the same type of data. Other solutions are not known for augmented reality visualization of the conditions of sensitive environments.

BRIEF DESCRIPTION OF THE DRAWINGS

[0003] FIG. 1 depicts a system block diagram for management of a controlled environment in accordance with embodiments;

[0004] FIGS. 2A-2B depict a monitored spatial volume in accordance with embodiments;

[0005] FIGS. 3A-3B depict various formats of data display in accordance with embodiments;

[0006] FIGS. 4A-4B depict sensor placement for the system of FIG. 1 in accordance with embodiments; and

[0007] FIG. 5 depicts aspects of an augmented reality display for data collected on the system of FIG. 1 in accordance with embodiments.

DESCRIPTION

[0008] Embodying systems and methods provide for monitoring the environmental conditions of a controlled spatial volume. The controlled environments can include, but not limited to, freezers, refrigerators, ambient temperature environments for fresh goods subject to potential spoilage, or controlled environment production areas. Embodiments can be suitable for any controlled environment such as, but not limited to: a showcase, refrigeration unit, cabinet, semiconductor fabrication room, clean room, pharmaceutical production facility, textile production facility (e.g., nylon), food preparation facility, and the like. Environmental conditions that are monitored can include, but are not limited to: temperature, humidity, particulate density, airborne chemical and/or biological contamination, and other conditions.

[0009] In accordance with embodiments, the current and/or historical monitored environmental condition(s) can be

presented to a user on an augmented reality (AR) map of the monitored spatial volume. The augmented reality map can be displayed on a mobile computing device (tablet, smart phones, laptop, wearable computing devices (watch, eye-glasses, head mounted devices, etc.), touch screen monitors, gesture-controlled devices, etc.), where the mobile computing device includes an AR application. Embodying systems and methods are not so limited to just these types of mobile computing devices. Current and/or future mobile computing device types are within the scope of this disclosure. A user of embodying systems is not limited to using just one type of mobile computing device, but can switch between devices, or use multiple devices concurrently, based on any number of factors.

[0010] Embodying systems and methods provide an integrated approach to tracking environmental conditions of assets, while being transparent to customers and not disruptive of current business processes. Additionally, some embodiments can track customer and/or personnel interaction within the monitored spatial volume to provide AR maps showing customer and/or interaction patterns. The interaction frequency to specific points within the spatial volume indicated by color coding and/or density of traces showing the path of interaction.

[0011] Embodying systems include the integration of sensors and controls into lighting fixtures to provide monitoring, analytics, and controls in a cost effective and simple manner. The sensor/control integrated lighting fixture(s) can be installed within the spatial volume (e.g., inside a refrigeration display cabinet, or ceiling mounted within a fabrication site). The sensor/control/integrated lighting fixture can provide data for use by the AR application to provide analytics and managerial information on these sensitive environments.

[0012] FIG. 1 depicts system 100 for monitoring and management of a controlled environment in accordance with embodiments. System 100 includes monitored spatial volume 102. For purposes of discussion only, the monitored spatial volume is depicted as a refrigeration/freezer unit. However, embodiments are not so limited, and are equally applicable to other monitored spatial environments as noted above.

[0013] Within the volume are located one or more lighting fixtures 104 (illustrated as a LED light bar). Integral with the lighting fixture are one or more sensors 106. The sensors can be selected to monitor one or more environmental conditions dependent on the particular nature of the controlled environment. In the depicted embodiment, the sensors are monitoring thermal and humidity (i.e., water vapor) conditions.

[0014] The sensors provide data to communication device 108. In some implementations, the communication device 108 provides the monitored data to communication device aggregator 110. In accordance with implementations, communication can be wireless, or wired, and can include various protocols—e.g., radio, cellular, RS 232 communication, Bluetooth, WiFi, Zigbee, TCP/IP, etc.

[0015] The communication device aggregator can be implemented at facilities that can have multiple, monitored spatial volumes each with one or more communication devices 108. For example, a retail food establishment can have walls of individual refrigeration, or freezer units. The communication device aggregator can be local to the facility. Aggregation of data at the local level can provide for efficient use of communication bandwidth when the moni-

tored data is provided to data store **140** across electronic communication network **120**. However, communication device aggregator **110** need not be implemented in all embodiments. In such embodiments, communication device **108** can be in communication with the data store, or retain the monitored data locally for analysis and display.

**[0016]** Electronic communication network **120** can be, can comprise, or can be part of, a private internet protocol (IP) network, the Internet, an integrated services digital network (ISDN), frame relay connections, a modem connected to a phone line, a public switched telephone network (PSTN), a public or private data network, a local area network (LAN), a metropolitan area network (MAN), a wide area network (WAN), a wireline or wireless network, a local, regional, or global communication network, an enterprise intranet, any combination of the preceding, and/or any other suitable communication system. It should be recognized that techniques and systems disclosed herein are not limited by the nature of the electronic communication network.

**[0017]** Data store **140** can include monitored sensor data records **142**. The data records can be organized by a unique identifier representing a particular sensor of a particular lighting fixture.

**[0018]** Server **130** can be in communication with monitored sensor data records **142** across the electronic communication network, and/or by direct communication with the data store **140**. The server can include server control processor **132**, memory **134**, and data analytic unit **136**. The data analytic unit can access the monitored sensor data, analyze the data, and generate information for display to a user in one or more formats. The data analytic unit can include machine vision unit **138** that can analyze the sensor data to create AR data for display to the user. A server application can provide data logging, threshold alarm generation, sensor failure generation, data visualization, control capabilities, etc.

**[0019]** Mobile computing device **150** can include control processor **152** that communicates with other components over internal data/control bus **154**. Control processor **152** accesses computer executable instructions, which can be stored in memory **156**. Mobile computing device **150** can include user interface **162** (e.g., display screen and keyboard). The mobile computing device can include input/output (I/O) unit **158** that communicates wirelessly across an electronic communication network. I/O unit **158** can support one or more hardwire and/or wireless communication protocols including, but not limited to, cellular telephone protocol, Bluetooth, low energy Bluetooth, iBeacon, near field communication, Airplay, etc. Augmented reality app **160** can render an AR display for presentation to the user based on the information generated by the machine vision unit.

**[0020]** FIGS. 2A-2B depict monitored spatial volume **200** in accordance with embodiments. For purposes of discussion, monitored spatial volume **200** is depicted as a refrigeration showcase unit. LED light bar **210** can include one or more printed circuit boards **222**, each having a plurality of LED light sources. Mounted at locations **212**, **214**, **216** can be sensors **230**, to provide information on monitored spatial volume **200**. In some implementations, sensors can be mounted at locations corresponding to predetermined areas of the monitored spatial volume. For example, sensors **230** can be positioned to monitor a corresponding shelf of a showcase. For larger monitored spatial volumes, a sensor

can correspond to positions of workbenches, fabrication equipment, storage tanks, etc.

**[0021]** Data wires **218** for the sensors can be similarly routed as power wires for the LED printed circuit boards. Electronic driver circuit **232** for the LED light sources, and/or the sensors, can be positioned over the door frame, within cable raceways, or an interior side of a mullion. In some implementations, power for the electronic driver circuit, sensors, and LED light sources can be provided by the monitored spatial volume power source. Communication device **108** can also be positioned over the door frame, within cable raceways, or an interior side of a mullion.

**[0022]** Sensors **230** can be embedded into extra mounting holes. Data from the sensors is provided to communication device **108**, which can be part of an open networked wireless control for lighting and building control—for example, a Daintree WSA10 sensor adapter.

**[0023]** Communication device **108** provides sensor data to the communication device aggregator, which can be a wireless area controller (WAC)—for example, a Daintree WAC. Communication device aggregator **110** can provide the aggregated data to other systems and data stores. In some implementations the aggregated data can be provided to third-party services that analyze the data for more advanced monitoring and control capabilities.

**[0024]** FIGS. 3A-3B depict various formats of data display in accordance with embodiments. Data analytics unit **136** can access the monitored sensor data to create tabular data **310**, graphical display data **320**, and thermal map **330**.

**[0025]** The data analytics unit can analyze the monitored data to visualize assets, monitor and log data, determine trends, control outputs, generate alarms. These actions can be applied to, for example, save spoilage of goods, activate backup control systems when main controls fail, provide alerts when environment changes outside expected ranges (e.g., temperature, humidity, contamination, pressure, sound, vibration, etc.).

**[0026]** Data analysis can detect data trends that might determine future environmental control unit failures. To prevent spoilage, the analyzed data can be compared to predetermined thresholds. If an out-of-tolerance condition is determined, a control signal can be generated that turns on an air blade system when door is left open for long periods—for example, the air blade system can prevent air exchange with outside environment. The air blade system creates a thin, high-velocity sheet of air across the entrance of the environment.

**[0027]** Machine vision unit **138** can apply image recognition techniques to examine the monitored data for anomaly detection, for example, condensation via of water droplets, incorrect light levels in the environment, and other parameters.

**[0028]** Machine vision image recognition techniques can also track which products have been removed from a refrigeration showcase. If that product is not processed at a retail checkout station within a time limit, an alert can be generated that the product is left outside of the refrigeration unit and will spoil.

**[0029]** The machine vision unit can also track personnel, customer, and other interaction activity within the monitored spatial volume by implementing thermal vision techniques. Events such as opening/closing the door, and which section/shelf was accessed can be recognized via machine learning and application of thermal thresholds. The monitored data

for these techniques can also include changes in environment (temperature, pressure, lighting, humidity), distance sensors (IR, sonar).

**[0030]** In some implementations, the monitored spatial volume need not be an environmentally controlled space. For example, a retail product showcase can provide thermal and/or motion data (using video and/or infrared cameras/sensors) that can be used by the machine vision unit to track customer interaction with product placement within the showcase.

**[0031]** FIGS. 4A-4B depict placement of infrared grid sensor **410** and infrared strip sensor **420** in accordance with embodiments. In some implementations, an infrared grid solution can involve two infrared grid sensors **410** placed opposite of each other, for example at the top and bottom of a spatial environment to be sensed. The axis of the grid across the front face of the fridge allows for detection of the position across a shelf. The ratio of infrared radiation detected between the two sensors determines which shelf. The machine vision unit can analyze movement (i.e., thermal differences) of a hand in and out of the fridge along the axes of the infrared grids' axis.

**[0032]** In other implementations, infrared strip sensors **410** can be integrated into the monitored spatial environment. For example, the placement of three strip sensors orthogonal to each other (X, Y, Z axes), can provide monitored data for the machine vision unit to determine movement within the spatial volume.

**[0033]** FIG. 5 depicts aspects of AR display **520** of monitored sensor data in accordance with embodiments. Users can be presented with an AR display on the display of mobile computing device **150**. The AR display can be generated by AR app **160** installed on the mobile computing device. Personnel can view an AR rendition of monitored sensor data on the mobile computing device by using a display feature of user interface **162**. For example, the AR rendition view can be thermal map **524** of a refrigeration unit, interaction tracks of customers/personnel within the monitored spatial volume, etc. The AR rendition can include in situ feature details of the monitored spatial volume—for example, refrigeration frame and doors **522** are rendered in AR display **520**.

**[0034]** A unique identifier for each sensor can be encoded into visual marker **510**. Data reported by the sensors can be correlated with the unique identifier as the data is stored in monitored sensor data records **142**. The visual markers can be placed in proximity to the location of sensors **230**, so that a visual camera of the mobile computing device can read the visual marker. Reading the visual marker informs the AR app as to which data records are to be presented in the AR display rendition for the portion of the spatial volume within the field-of-view of the visual camera. The visual marker can also include information conveying the orientation of the data within the spatial volume.

**[0035]** In some embodiments, the visual camera need not be within a mobile computing device. For example, a security system with one or more cameras monitoring the spatial volume can read the visual marker(s) within the security camera's field-of-view. An AR application can then generate an AR rendition for display on a security system monitor and/or website.

**[0036]** AR app **160** can create an overlay of the 3D temperature mapping of the fridge provided by the temperature sensors placed throughout the fridge. Orientation of the

AR rendition can be based on knowing the plane, and relative positioning of the visual markers. The AR rendition can display numerical values or heatmap colors in a gradient across the fridge, using each sensor to provide intensity at their physical locations.

**[0037]** Although specific hardware and methods have been described herein, note that any number of other configurations may be provided in accordance with embodiments of the invention. Thus, while there have been shown, described, and pointed out fundamental novel features of the invention, it will be understood that various omissions, substitutions, and changes in the form and details of the illustrated embodiments, and in their operation, may be made by those skilled in the art without departing from the spirit and scope of the invention. Substitutions of elements from one embodiment to another are also fully intended and contemplated. The invention is defined solely with regard to the claims appended hereto, and equivalents of the recitations therein.

**1.-25.** (canceled)

**26.** A system for monitoring a controlled spatial volume comprising:

- a lighting fixture comprising at least one embedded sensor configured to monitor a controlled spatial volume;
- a first infrared grid sensor positioned opposite a second infrared grid sensor, the first and second infrared grid sensors mounted at a top and bottom of a spatial environment defining a grid sensing area within the controlled spatial volume;
- a first communication device for providing monitored sensor data for storage in a data store;
- a server comprising a data analytic unit and configured to communicate with the data store, wherein the data analytic unit accesses monitored sensor data records to analyze the monitored sensor data, provides status information on the spatial volume, and implements thermal vision techniques to track interaction activity in the grid sensing area.

**27.** The system of claim **26**, further comprising a mobile computing device wirelessly connected to the server, the mobile computing device comprising:

- a control processor operably connected to a memory;
  - an input/output unit operably connected to the control processor; and
  - a user interface operably connected to the control processor;
- wherein the memory includes processor executable instructions which when executed cause the mobile computing device to render a display on the user interface of at least the status information of the controlled spatial volume for presentation to a user.

**28.** The system of claim **27**, wherein the mobile computing device further comprises an augmented reality application, and wherein the control processor runs the augmented reality application and displays an augmented reality rendition of the monitored sensor data on the user interface for viewing by a user.

**29.** The system of claim **28**, wherein the augmented reality application generates an augmented reality rendition for display on the user interface from machine vision analysis of the sensor data.

**30.** The system of claim **26**, further comprising a plurality of visual markers placed in proximity to each of a plurality of embedded sensors, wherein each of the plurality of visual

markers provides orientation information and represents a unique identifier for each of the plurality of embedded sensors.

**31.** The system of claim **30**, further comprising:  
a mobile computing device wirelessly connected to the server, the mobile computing device comprising:  
a control processor operably connected to a memory;  
an input/output unit operably connected to the control processor; and  
a user interface operably connected to the control processor;

wherein the memory includes processor executable instructions and an augmented reality application, and wherein when the processor executable instructions and the augmented reality application are executed the mobile computing device displays on the user interface at least the status information of the controlled spatial volume and an augmented reality rendition including orientation data of the monitored sensor data for presentation to a user.

**32.** The system of claim **26**, further comprising:  
a communication device aggregator operatively connected to the first communication device; and  
an electronic communication network operatively connected to the communication device aggregator and to the data store, wherein the communication device is

configured for aggregating data from a plurality of communication devices associated with a plurality of controlled special volumes.

**33.** The system of claim **26**, wherein the at least one embedded sensor is configured to monitor at least one environmental condition within the spatial volume.

**34.** The system of claim **26**, wherein the at least one embedded sensor comprises at least one of a temperature sensor, a humidity sensor, a particulate density sensor, an airborne chemical sensor, and a biological sensor.

**35.** The system of claim **26**, wherein the status information provided by the data analytic unit comprises at least one of tabular data, graphical display data, and thermal map data.

**36.** The system of claim **26**, wherein the controlled spatial volume comprises one of a freezer, a refrigerator, an environment for goods subject to spoilage, a semiconductor fabrication room, a clean room, a pharmaceutical production facility, a textile production facility, and a food preparation facility.

**37.** The system of claim **26**, wherein the data analytic unit further comprises a machine vision unit, wherein the machine vision unit applies image recognition techniques to examine monitored data for anomaly detection and to track products which have been removed.

\* \* \* \* \*