



US 20160319540A1

(19) **United States**

(12) **Patent Application Publication**
Marsh

(10) **Pub. No.: US 2016/0319540 A1**

(43) **Pub. Date: Nov. 3, 2016**

(54) **MECHANICALLY SECURED BLOCK ASSEMBLY SYSTEMS**

E04C 5/12 (2006.01)

E04C 5/16 (2006.01)

E04B 2/26 (2006.01)

E04C 1/00 (2006.01)

(71) Applicant: **Roger F. Marsh**, Anderson, IN (US)

(72) Inventor: **Roger F. Marsh**, Anderson, IN (US)

(73) Assignee: **3B Construction Solutions Inc.**,
Anderson, IN (US)

(52) **U.S. Cl.**

CPC . *E04B 2/16* (2013.01); *E04B 2/26* (2013.01);

E04C 1/00 (2013.01); *E04C 5/125* (2013.01);

E04C 5/162 (2013.01); *E04B 1/043* (2013.01);

E04B 2002/0202 (2013.01)

(21) Appl. No.: **15/142,422**

(22) Filed: **Apr. 29, 2016**

(57)

ABSTRACT

Related U.S. Application Data

(63) Continuation of application No. 14/551,665, filed on Nov. 24, 2014, now Pat. No. 9,328,501, which is a continuation of application No. 14/098,440, filed on Dec. 5, 2013, now Pat. No. 8,893,447, said application No. 14/551,665 is a continuation-in-part of application No. 11/353,253, filed on Feb. 13, 2006, now Pat. No. 9,206,597.

(60) Provisional application No. 61/733,536, filed on Dec. 5, 2012.


A method for building a mechanical secured block structure, including placing a footer block on a desired surface, inserting two respective starter bar nuts into the footer block, inverting the footer block, placing a first concrete masonry unit over respective first and second anchor bars, aligning the first concrete masonry unit with the footer block, placing second and third footer blocks adjacent the first footer block, placing a second concrete masonry unit adjacent the first concrete masonry unit, positioning each respective concrete masonry unit to equally straddle two adjacent footer blocks, positioning respective anchor bars atop respective concrete masonry units, and bolting respective concrete masonry units to respective footer blocks to interconnect the two respective concrete masonry units and the three respective footer blocks to define a contiguous wall. Each respective masonry unit and each respective footer block are post tensioned to be under compression.




Publication Classification

(51) **Int. Cl.**

E04B 2/16 (2006.01)

E04B 1/04 (2006.01)








Fig. 2 A




Fig. 2 B




Fig. 2 C

138




Fig. 3 D




Fig. 3 A





Fig. 3 C
Section B-B

Fig. 3 B
Section A-A






Fig. 5C




Fig. 5B




Fig. 5A




Fig. 6B




Fig. 6D




Fig. 6A




Fig. 6C

31A




Fig. 7A




Fig. 7B




Fig. 7C




Fig. 7D




Fig. 8B




Fig. 8D




Fig. 8A




Fig. 8C

30




Fig. 9C

Fig. 9B

Fig. 9A












Fig. 9E

Fig. 9D








Fig. 12A




Fig. 12D

Fig. 12E

Fig. 12F

Fig. 12G




Fig. 13A




Fig. 13B




Fig. 14B






Fig. 14D






Fig. 15B





Fig. 15D



40 Fig. 15A




Fig. 15C




Fig. 16A

Fig. 16B




Fig. 16E

Fig. 16C

MECHANICALLY SECURED BLOCK ASSEMBLY SYSTEMS

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This application is a continuation of and claims priority to co-pending U.S. patent application Ser. No. 14/551,665, filed on Nov. 24, 2014, which was a continuation-in-part of then co-pending U.S. patent application Ser. No. 11/353,253, filed on Feb. 13, 2006, and was also a continuation of, then co-pending U.S. patent application Ser. No. 14/098,440, filed on Dec. 5, 2013, which claimed the benefit of then-co-pending U.S. Provisional Patent Application Ser. No. 61/733,536 filed Dec. 5, 2012, now abandoned.

FIELD OF NOVEL TECHNOLOGY

[0002] Embodiments of the present novel technology relate generally to construction materials, and, more particularly, to unitized post tension systems and methods for concrete masonry structures.

BACKGROUND

[0003] Existing unitized post tension systems for concrete masonry structures have until now required special other construction to address larger wall widths over approximately eight inches, to address horizontal decks and to address structural grade beams. The existing taught systems did not easily accommodate those needs in a unitized post tension system.

[0004] The prior art unitized post tension systems address methods and systems to rapidly build structures, including walls with for use as flat deck, wider wall systems and large grade beams. Recent unitized post tension systems facilitated improvements to traditional construction systems and their limitations. The recent systems do not require special skills to construct; does not need water and power; do not require elaborate bracing; provides immediate occupancy or use; needs no curing time; and are re-useable if desired since it is not destroyed when disassembled and moved. While the recent systems are improvements to decrease the time to build or rebuild areas with minimal skilled labor and provide a far superior and more consistent strength structure than the traditional mortar constructed structure, these systems still have room for improved devices and configurations to meet known shortcomings. The problems and limitations of the prior art unitized post tension systems are addressed generally for the use as flat deck, wider wall systems and large grade beams. In the building industry, the masonry, precast concrete and poured in place, tilt-up wall systems often accompany a building type—industrial, commercial, and hi-rise residential—where floor and roof decks are utilized. For example, motel and hotels and office buildings, strip malls and the like will incorporate precast decks or poured in place steel sheet metal and concrete to provide floors and roof decks. Therefore an alternative flat decking means from the unitized post tension system is desirable.

[0005] The unitized post tension system has also found acceptance in the southern building needs in Mississippi and Louisiana. In those locations, the rapid build system afforded by unitized post tension systems still had restrictions with the need for grade beams to be used in the quasi-marsh areas in cooperation with posts or pilings. Here the spans were of such lengths that some consideration for

higher tension strength in the grade beams presented some challenges to the unitized post tension system. Therefore a better adapted and improved grade beam made of unitized post tension components with added features and capabilities is desirable.

[0006] The final desired improvement to unitized post tension systems is not an intuitively obvious need. In the concrete masonry unit (CMU) building systems, the approximately eight inch wide block is the main component. However, over the years, the need for ten inch, twelve inch and larger widths became evident. These were addressed by the industry to provide wide base walls. However, these wider block came at a price: they required all new, wider molds to produce; they were much heavier and usually required two people to lift and transport, and they often needed additional tooling and accessories to match the wider widths. Therefore, it is desirable to build wider, higher capacity wall systems from the unitized post tension components. The new system that addresses this will save the cost of molds, added labor and employee fatigue, and added costs for the wider blocks. However, the new use of the unitized post tension components would need to be as strong or even stronger than the CMU counterparts. These problems or limitations of the desires for the use as flat deck, wider wall systems and large grade beams are described below.

[0007] Historically, no known devices have attempted to address the problem as stated. The building industry has made little progress for a unitized, post tension system so improvements to the recent unitized post tension systems have not yet been attractive to promotion of the technology. Even so, blocks have required very special and often complex configurations to even handle rods and plates and then they have taught only limit rods in special blocks. One such device is an instant levy block system. This is a complex, specially made block for constructing a levy, comprising a plurality of blocks, a plurality of connecting pegs, and a plurality of stakes. Each part is uniquely designed and made whereas the novel technology uses a commonly made block designed for the common bars and bolts. Another block device is a masonry block with an embedded plate. The concrete masonry block has an external plate or plates that are anchored through the concrete masonry block. The external plates are cast into the concrete masonry block in the mold during casting. These plates and metal pieces are not taught as being part of a post tensioning system now shown cast within the hollow cavities as addressed by the improved novel technology.

[0008] Another device for construction is a modular precast construction block system with a wall subsystem and a foundation subsystem. The wall subsystem has a number of wall units having cavities and pre-stressed tension cables are cast therein the cavity. This teaches precast walls and pass through cable which are specially made, require water, and are not readily re-useable like the novel technology. A somewhat re-useable system includes long rods that extend through apertures in the specially cast block and the precast structures. No description of pre or post tensioning is taught or claimed. The configuration of special length rods, special blocks, special plates and a complex system that requires powered equipment to construct is unlike the novel technology.

[0009] One known mortarless wall structure comprises columns of preformed, lightweight, stacked blocks, with the

columns of blocks connected to each other by elongated, vertically oriented, support beams. Preferably, the wall structure is operatively connected to a structure by one or more brackets. The beams and blocks are special configuration, not readily available and with limited uses. These are complex and do not anticipate the novel technology.

[0010] An interlocking, mortar less system is accomplished by some other devices. However, none of them are found to show a structural unitized post tensioning system as described for the novel technology in the materials below. An example of one such interlocking device is a block of concrete or the like for use in constructing a mortar less wall. The device provided includes a spaced parallel pair of upright sidewalls having flat bottoms and tops and bearing integral block interlocking connectors and various configurations on their opposite ends. The sidewalls are integrally connected by means of these configurations. This is not the configuration taught by the novel technology. Another mortarless system is a set of superimposed building blocks with vertically spaced flat bars inter-fitted with the blocks and studs inserted through one bar and then threaded into engagement with bars of lower blocks.

[0011] None of the prior art found with a rigorous search teaches all the features and capabilities of the novel technology. As far as known, there are no systems at the present time which fully meet the need for a unitized, post-tensioned masonry block structure with the described shortfalls which are now resolved by the present novel technology. It is believed that this system is made with component parts, is built with simple tools, and provides a much stronger structure than prior art devices and systems.

SUMMARY

[0012] This technology relates to new modifications and uses of a bolt and bar, mechanically secured block system. New use devices include multi width walls, horizontal decks and structural beams such as grade beams. Taught here are the ways to significantly improve and expand the use of mechanically secured block far beyond anticipation of current/prior art devices nor obvious to one skilled in the art of block construction—mechanical or otherwise.

[0013] One preferred embodiment of the uses for the novel technology are shown in the drawings and further described below. The embodiment is a mechanical secured block building system for constructing structures with concrete masonry units, the system comprising: (a) a masonry block unit with a height and width essentially one-half the length of the unit, with multiple cavities through the block and with a recessed channel; (b) an anchor bar with a plurality of threaded and non-threaded apertures in a special configuration to match the cavities in the block unit and able to lay in the recessed channel of the block; and (c) a fastener wherein the mechanical secured block building system can be assembled in unique ways due to a cube effect of the masonry block to construct multiple width walls, grade beams, and horizontal decks. An alternative embodiment includes the mechanical secured block building system is further comprised of: (d) a footer block and (e) a footer plate.

BRIEF DESCRIPTION OF THE DRAWINGS

[0014] The accompanying drawings, which are incorporated in and constitute a part of this specification, illustrate embodiments of the novel technology. The drawings

together with the summary description given above and a detailed description given below serve to explain the principles of the construction system. It is understood, however, that the novel technology for block construction systems is not limited to only the precise arrangements and instrumentalities shown. While multiple embodiments are disclosed, still other embodiments of the present novel technology will become apparent to those skilled in the art from the following detailed description, which shows and describes illustrative embodiments of the novel technology. Accordingly, the drawings and detailed description are to be regarded as illustrative in nature and not restrictive.

[0015] FIG. 1A is a first perspective view of general mechanical block special enhancements, of multi walls, grade beams and horizontal beam/slabs.

[0016] FIG. 1B is a second perspective view of general mechanical block special enhancements, of multi walls, grade beams and horizontal beam/slabs.

[0017] FIG. 1C is a third elevation view of general mechanical block special enhancements, of multi walls, grade beams and horizontal beam/slabs.

[0018] FIG. 2A is a first perspective view of mechanical systems for unitized post tensioning block, bar and fastener components plus a method to assemble a typical wall.

[0019] FIG. 2B is a second perspective view of mechanical systems for unitized post tensioning block, bar and fastener components plus a method to assemble a typical wall.

[0020] FIG. 2C is a third schematic perspective view of mechanical systems for unitized post tensioning block, bar and fastener components plus a method to assemble a typical wall.

[0021] FIG. 3A is a first partial top plan view of a mechanical system for unitized post tensioning.

[0022] FIG. 3B is a second side plan view of a mechanical system for unitized post tensioning.

[0023] FIG. 3C is a third end plan view of a mechanical system for unitized post tensioning.

[0024] FIG. 3D is a fourth perspective view of a mechanical system for unitized post tensioning.

[0025] FIG. 4A is a first plan view of the bars for the mechanical systems for unitized post tensioning building systems.

[0026] FIG. 4B is a second end view of the bars for the mechanical systems for unitized post tensioning building systems.

[0027] FIG. 4C is a third end view of the bars for the mechanical systems for unitized post tensioning building systems.

[0028] FIG. 4D is a fourth perspective view of the bars for the mechanical systems for unitized post tensioning building systems.

[0029] FIG. 5A is a first perspective view of the general mechanical secured block building system (MSB) wall system walls single, double, and triple.

[0030] FIG. 5B is a second perspective view of the general mechanical secured block building system (MSB) wall system walls single, double, and triple.

[0031] FIG. 5C is a third perspective view of the general mechanical secured block building system (MSB) wall system walls single, double, and triple.

[0032] FIG. 6A is a first perspective view of additional multi walls and piers for the MSB wall system.

[0033] FIG. 6B is a second perspective view of additional multi walls and piers for the MSB wall system.

[0034] FIG. 6C is a third perspective view of additional multi walls and piers for the MSB wall system.

[0035] FIG. 6D is a fourth perspective view of additional multi walls and piers for the MSB wall system.

[0036] FIG. 7A is a first perspective view of MSB walls and components.

[0037] FIG. 7B is a second perspective view of MSB walls and components.

[0038] FIG. 7C is a third perspective view of MSB walls and components.

[0039] FIG. 7D is a fourth perspective view of MSB walls and components.

[0040] FIG. 8A is a first perspective view of the MSB walls with components and features shown from generally a side or perspective views.

[0041] FIG. 8B is a second perspective view of the MSB walls with components and features shown from generally a side or perspective views.

[0042] FIG. 8C is a third perspective view of the MSB walls with components and features shown from generally a side or perspective views.

[0043] FIG. 8D is a fourth perspective view of the MSB walls with components and features shown from generally a side or perspective views.

[0044] FIG. 9A is a first perspective view of the MSB walls made into various sized piers.

[0045] FIG. 9B is a second perspective view of the MSB walls made into various sized piers.

[0046] FIG. 9C is a third perspective view of the MSB walls made into various sized piers.

[0047] FIG. 9D is a fourth perspective view of the MSB walls made into various sized piers.

[0048] FIG. 9E is a fifth perspective view of the MSB walls made into various sized piers.

[0049] FIG. 10A is a first perspective view of the general grade beams made from MSB.

[0050] FIG. 10B is a second perspective view of the general grade beams made from MSB.

[0051] FIG. 10C is a third perspective view of the general grade beams made from MSB.

[0052] FIG. 11A is a first perspective view of grade beams made from MSB. FIG. 11B is a second perspective view of grade beams made from MSB. FIG. 11C is a third perspective view of grade beams made from MSB. FIG. 11D is a fourth perspective view of grade beams made from MSB. FIG. 11E is a fifth perspective view of grade beams made from MSB.

[0053] FIG. 12A is a first perspective view of the grade beams made from MSB.

[0054] FIG. 12B is a second perspective view of the grade beams made from MSB. FIG. 12C is a third perspective view of the grade beams made from MSB.

[0055] FIG. 12D is a fourth perspective view of the grade beams made from MSB.

[0056] FIG. 12E is a fifth perspective view of the grade beams made from MSB.

[0057] FIG. 12F is a sixth perspective view of the grade beams made from MSB.

[0058] FIG. 13A is a first top plan view of a grade beam.

[0059] FIG. 13B is a second perspective view of a grade beam.

[0060] FIG. 14A is a first engineering drawing of the grade beams from MSB.

[0061] FIG. 14B is a second engineering drawing of the grade beams from MSB.

[0062] FIG. 14C is a third engineering drawing of the grade beams from MSB.

[0063] FIG. 14D is a fourth engineering drawing of the grade beams from MSB.

[0064] FIG. 15A is a first perspective view of horizontal Beams/Slabs of the MSB system.

[0065] FIG. 15B is a second perspective view of horizontal Beams/Slabs of the MSB system.

[0066] FIG. 15C is a third perspective view of horizontal Beams/Slabs of the MSB system.

[0067] FIG. 15D is a fourth perspective view of horizontal Beams/Slabs of the MSB system.

[0068] FIG. 16A is a first elevation of the horizontal beam/slabs for MSB systems.

[0069] FIG. 16B is a second elevation of the horizontal beam/slabs for MSB systems.

[0070] FIG. 16C is a third partial elevation of the horizontal beam/slabs for MSB systems.

[0071] FIG. 16D is a fourth elevation of the horizontal beam/slabs for MSB systems.

[0072] FIG. 16E is a fifth partial elevation of the horizontal beam/slabs for MSB systems.

[0073] While the novel technology is amenable to various modifications and alternative forms, specific embodiments have been shown by way of example in the drawings and are described in detail below. The intention, however, is not to limit the novel technology to the particular embodiments described. On the contrary, the novel technology is intended to cover all modifications, equivalents, and alternatives falling within the scope of the novel technology as defined by the appended claims.

DETAILED DESCRIPTION

[0074] The present novel technology relates to new use devices for Mechanically Secured Block (MSB) Assembly Systems. Embodiments of the present novel technology relate generally to systems and methods for concrete masonry structures, and more particularly to unitized post tension systems and methods for concrete masonry structures. The present novel technology relates generally to all types of general construction where a common mortar and hollow block or brick combination is utilized and relates to other construction means, such as reinforced concrete, for structures as well. The embodiments of the novel technology are shown in the accompanying sketches and described below.

[0075] There is shown in FIGS. 1-16E a complete description and operative embodiment of the novel technology. In the drawings and illustrations, FIGS. 1-13 demonstrate the general configuration and use of this product/system. The various example uses are in the operation and use section, below.

[0076] The accompanying drawings, which are incorporated in and constitute a part of this specification, illustrate an embodiment of the novel technology that are preferred. The drawings together with the summary description given above and a detailed description given below serve to explain the principles of the construction system and devices. It is understood, however, that the novel technology are not limited to only the precise arrangements and instru-

mentalities shown. Other examples of similar construction systems within this same scope are still understood by one skilled in the art of construction systems, directly or indirectly associated with block systems, to be within the scope and spirit shown here.

[0077] Some (non-limiting) examples of the new device uses of the system are: A. Permits a way to create long beams, especially grade beams;

[0078] B. Provides cubing of the piers in the building systems with block width=block height=1/2 block length;

[0079] C. Establishes a manner to provide multiple width walls that are integrally tied together for greater strength and durability;

[0080] D. Reduces the cost of wider walls by using one common unit (approximately 16x8x8 inch) rather than 10 or 12 inch widths. This reduces of molds, accessories and labor to handle larger block units;

[0081] E. Allows for horizontal decks, floors and cantilevered building assemblies; and

[0082] F. Capitalizes on the new mechanical block assembly systems and removes the need to use other construction methods for decks, grade beams and wider wall assemblies.

[0083] One embodiment is a mechanical secured block building system for constructing structures with concrete masonry units, the system comprising: (a) a masonry unit, the masonry unit being made of concrete and comprising: a masonry longitudinal length, a masonry width measured perpendicularly to the masonry longitudinal length, wherein the masonry width which is essentially one half the longitudinal length and which is substantially uniform along the masonry longitudinal length, a masonry top surface, the masonry top surface being substantially planar, a masonry bottom surface, the masonry bottom surface being substantially planar, a masonry height which is essentially one half the longitudinal length and which is measured between the masonry top and masonry bottom surfaces, the masonry height being substantially uniform along the masonry longitudinal length, a first through-cavity formed through the masonry unit from the top surface to the bottom surface, a second through-cavity formed through the masonry unit from the top surface to the bottom surface, a third through-cavity formed through the masonry unit from the top surface to the bottom surface, and an anchor bar channel recessed formed in the masonry top surface and oriented substantially along the masonry longitudinal length; (b) an anchor bar, the anchor bar comprising: (i) a first set of apertures, the first set of apertures comprising a first non-threaded aperture and a first threaded aperture, wherein the first non-threaded aperture and the first threaded aperture are located in first and second diagonally opposing quadrants of a coordinate system defined by a longitudinal centerline of the anchor bar and a line that is perpendicular to the longitudinal centerline; and (ii) a second set of apertures neighboring the first set of apertures, the second set of apertures comprising a second non-threaded aperture that is substantially the same as the first non-threaded aperture, and a second threaded aperture that is substantially the same as the first threaded aperture, wherein the second non-threaded aperture and the second threaded aperture are located in third and fourth diagonally opposing quadrants of the coordinate system but spaced longitudinally from the first set of apertures wherein the first set of apertures is aligned with the first through-cavity and

the second set of apertures is aligned with the third through-cavity when the anchor bar is placed into the anchor bar recessed channel of the masonry unit and wherein a width of the anchor bar is smaller than a width of the recessed channel of the masonry unit; and (c) a fastener, the fastener comprising: (i) a first fastener end and a second fastener end, (ii) a head portion at the first fastener end, (iii) a stem portion rigidly affixed to the head portion, the stem portion comprising a threaded portion at the second fastener end wherein the head portion does not fit through the first non-threaded aperture, wherein the stem portion slides freely through the first non-threaded aperture, and wherein the threaded portion is configured to thread ably engage the first threaded aperture wherein the mechanical secured block building system can be assembled in unique ways due to a cube effect of the masonry block to construct multiple width walls, grade beams, and horizontal decks.

[0084] An alternative embodiment includes the previously described mechanical secured block building system further comprised of: (d) a footer block, the footer block being made of concrete and comprising: a footer longitudinal length substantially the same as the masonry longitudinal length; a footer width measured perpendicularly to the footer longitudinal length and essentially one half the longitudinal length, wherein the footer width is substantially uniform along the footer longitudinal length, a footer top surface, the footer top surface being substantially planar, a footer bottom surface, the footer bottom surface being substantially planar, a footer height measured between the footer top and footer bottom surfaces, the footer height being substantially uniform along the footer longitudinal length, a footer recess formed on the footer bottom surface, and a footer through-hole formed from the footer top surface to the footer recess; and (e) a footer plate, the footer plate comprising: a footer threaded aperture, the footer threaded aperture configured to threadably engage the threaded portion of a lower most fastener, wherein the footer plate fits within the footer recess such that, when received by the footer recess, the footer plate does not protrude below the second bottom surface and the footer plate is substantially prevented from rotating within the footer recess.

[0085] FIGS. 1 A through 1C are sketches of the general mechanical block special enhancements, of multi walls 30, grade beams 60, 71 and horizontal beam/slabs 80. The components of the sketches are described in the following paragraphs.

[0086] FIGS. 2A through 2C are sketches of the mechanical systems for unitized post tensioning block 135, longer bar 133A and fastener 134 components plus a method 138 to assemble a typical wall. Assembly Process for FIG. 2C:

Step	Description
1	Place footer block and insert two starter bar nuts, then invert the footer block.
2	Place CMU 35 over the starter anchor/bars
3	Align CMU with footer block
4	Place two additional footer blocks and an additional CMU. Slide the CMUs s they split the footer blocks (i.e. - half a CMU on each of two footers)
5	Place bar and bolts onto the CMUs and tighten the two tendon/through bolts 34 into the threaded apertures in the lowermost starter anchor/bars by means of a wrench or equal which secure the uppermost bar 33 in a tensioned condition with the CMU

-continued

Step	Description
6	Place an additional CMU next to the first two CMUs
7	Place the second CMU 35 over the second set of starter anchor/bars 33; then place an one or more anchor/bars 33 or extended bars 33 A into the upper extended recessed channels 36 of the second course of CMUs, place at least two more tendon/through bolts 34 into the through apertures in the uppermost anchor/bars 33 of the second CMU 35
8	Repeat as needed.

[0087] FIGS. 3A through 3D are sketches of the mechanical systems for unitized post tensioning from a Top, Side, End and Isometric perspective. The features depicted include the ducts 137 and the recess space 136. The overall strength of the demonstrated block 135 is 4000 psi or greater based on the ASTM C 140 specification. One also notes the block length BL; block width BW=approximately 1/2 block length BL; the block height BH=Block width BW=approximately 1/2 block length BL; and the distance BC13 from centerline of core 1 and core 3 and Centerlines C of anchor bar apertures.

[0088] FIGS. 4A through 4D are sketches of the bars for the mechanical systems for unitized post tensioning building systems. Shown in these sketches are an anchor bar 133, extended, relatively longer anchor bar 133A, a bar/anchor aperture pattern 180, one distance X from center point C, a second distance Y from center point C, the center point C, an anchor bar width W; and an anchor bar length L.

[0089] FIGS. 5 A through 5 C are sketches of the general MSB walls single 31, double 32, and triple 33. Multiple width walls inter-connected by perpendicularly placed courses and/or link bars. The multiple width walls inter-connected by perpendicularly placed courses of block 36 and/or link bars 80. These are complemented by the normal securing bar 40 or perpendicular securing bars 41 at wider positions such as corners and at piers 34. One skilled in the art well appreciates there may be two, three, four or more rows. The major improved configuration utilizes a cube of designed block where the block length BL equals two times the block width BW. The cubing is complete in all three directions with the block width BW equal to the block height BH. The additional width structurally improves the strength. The interlocking perpendicularly of the courses from one contiguous wall to the next one beside it (the face of the contiguous block are touching) permits an even greater strength from the separate walls being integrally fastened to each other with interlocked block and anchor bars.

[0090] FIGS. 6A through 6D are sketches of additional multi walls 31, 32, 33 and piers 34 for the mechanical secured block building system (MSB) wall system. The components shown are described above. Here are shown the manner to interconnect piers 34 with the walls in different directions as well as creating cubed piers for stand-alone uses (such as piers as building columns supporting floor decks, roof decks, structural beams and other building structures).

[0091] FIGS. 7A through 7D are more sketches of mechanical secured block building system (MSB) wall system walls and components. The components have been described. One may especially note the long bars 40, the perpendicular bars 41 and the link bars 80.

[0092] FIGS. 8A through 8D are sketches of the mechanical secured block building system (MSB) wall system with

additional multi walls 31, 32, 33, components and features shown from generally a side, top and perspective views.

[0093] FIG. 9A through 9E are sketches of the MSB walls made into various sized piers. Note the cubing shows two block pier configurations in FIG. 9A; three block configuration in FIG. 9B; four block configuration in FIG. 9C with an open cavity or chase (for utilities, pipe, columns and the like); solid eight block configuration in FIG. 9D; and a three width wall in FIG. 9E.

[0094] FIG. 10A through 10C are sketches of the general grade beams 60 made from mechanical secured block building system (MSB) wall system. The multiple width grade beams 60 with potential pier 34 connections or connection to pilings/posts 63 for bridging low capacity bearing conditions such as a bog, marsh, former lake bed, etc. The grade beam 60 shown utilizes cube of designed block (length equals 2xthe width and height). The beam 60 has a long, continuous tension bar 61 along the bottom of the block 36 or footer 35. One means to connect the beam 60 to the piling 63 is to use a “U-like” cradle 62 that is secured to the top of the pilings 63 and the side face of the blocks 36 of the grade beam 60. Where the beam 60 connects with posts or columns above, there can be a series of rebar tendons 65 placed in the cavity of the mechanical secured block building system (MSB) columns. The rebar 65 is then grouted in place in the void 65 around the rebar 65 and in the block unit cavities. One skilled in the art of building construction appreciates the ability to vary the size of the rebar 65, the strength of the grout and the area of the column or long piers 34 to achieve the needed column strength and, importantly, the moment resistance at the beam and column junction.

[0095] FIG. 11A through 11E are sketches of grade beams 60 made from mechanical secured block building system (MSB) wall system. One can appreciate the pier 34 at the beam 60, the block 36, the voids 65 for grout, and the bars 41.

[0096] FIG. 12A through 12F are additional sketches of the grade beams made from mechanical secured block building system (MSB) wall system. The components shown have been identified and discussed above.

[0097] FIGS. 13A and 13B are sketches of a grade beam. FIG. 13A is an engineering drawing for the grade beam 60. FIG. 13B is a sketch of a grade beam 60 used in the “Make-It-Right” rebuilding efforts in New Orleans, La., where nearly 4,000 homes in Lower 9th Ward were destroyed by Hurricane Katrina. These grade beams reduce build time as much as four (4) weeks-even more when one factors in weather conditions.

[0098] FIG. 14A through 14D are additional engineering drawings of the grade beams 60 from mechanical secured block building system (MSB) wall system with components and configurations already discussed above.

[0099] FIG. 15A through 15D and FIG. 16A through 16E are sketches of horizontal Beams/Slabs 80 of the mechanical secured block building system (MSB) wall system. The multiple width beams 80 used for floor and ceiling support on building—single and multiple story. These may be in run parallel in direction of support columns/walls or run perpendicularly. Above the beams are standard flooring or roof membranes and structures. The slabs 80 extend across beams S2 as floor or roof decks S2 or on vertical wall S1 systems or columns. To vary the strength of the slabs, the tendon and anchor bar dimensions can be changed. The

standard $\frac{3}{16}$ diameter and thicknesses can be increased to provide additional tension capacity of the steel and concrete combination.

[0100] The details mentioned here are exemplary and not limiting. Other specific components and manners specific to describing novel technology may be added as a person having ordinary skill in the field of construction block and wall systems and devices and their uses well appreciates.

Operation

[0101] The novel technology have been described in the above embodiment. The manner of how the device operates is described below. One notes well that the description above fully illustrates the concept of the novel technology. The manner of use is well documents and shown in the drawings described above. The anchor bars **133**, **133A** are placed into the block recesses, and then the tendon/bolts **134** are assembled. The method shown in FIG. 2C is essentially the manner of use. The difference for the multi-walls are running courses of block perpendicular and locking with the perpendicular bars **41** into the long bars **40**, **133A** or utilizing link bars **80**. With the grade beams **60** and horizontal decks **80**, one modifies the build to accommodate the long tension bars **61**, the cradle **62** and the rebar **65**. Likewise for the slabs, the intersection with vertical walls **81** may require connections between the bars and tendons.

[0102] Assembly Process Step Description: Place two starter anchors/bars on the ground or foundation surface. Place CMU **35** over the starter anchor/bars. Place two more anchor/bars into the upper extended recessed channels of the CMU. Place two tendon/through bolts into the through apertures in the uppermost anchor/bars. Tighten the two tendon/through bolts into the threaded apertures in the lowermost starter anchor/bars by means of a wrench or equal. Place two additional starter anchors/bars next to the primary CMU. Place the second CMU over the second set of starter anchor/bars. Place two more anchor/bars into the upper extended recessed channels of the second CMU. Place two more tendon/through bolts into the through apertures in the uppermost anchor/bars of the second CMU. Tighten (by means of a wrench or equal) the second set of two tendon/through bolts into the threaded apertures in the lowermost starter anchor/bars placed under the second CMU. Place the third CMU over the first and second CMUs straddling each equally (note this is for a running bond configured wall). Place two more anchor/bars into the upper extended recessed channels of the third CMU. Place two more tendon/through bolts into the through apertures in the uppermost anchor/bars of the third CMU. Tighten (by means of a wrench or equal) the third set of two tendon/through bolts into the threaded apertures in the uppermost anchor/bars of the first and second CMU. Repeat process until structure is completed.

[0103] With this description it is to be understood that the novel technology is not to be limited to only the disclosed embodiment of product. The features of the novel technology are intended to cover various modifications and equivalent arrangements included within the spirit and scope of the description.

[0104] While certain novel features of this novel technology have been shown and described and are pointed out in the annexed claims, it is not intended to be limited to the details above, since it will be understood that various omissions, modifications, substitutions and changes in the

forms and details of the device illustrated and in its operation can be made by those skilled in the art without departing in any way from the spirit of the present novel technology. Without further analysis, the foregoing will so fully reveal the gist of the present novel technology that others can, by applying current knowledge, readily adapt it for various applications without omitting features that, from the standpoint of prior art, fairly constitute essential characteristics of the generic or specific aspects of this novel technology.

[0105] Unless defined otherwise, all technical and scientific terms used herein have the same meaning as commonly understood by one of ordinary skill in the art to which these novel technologies belong. Although any methods and materials similar or equivalent to those described herein can also be used in the practice or testing of the present novel technologies, the preferred methods and materials are now described above in the foregoing paragraphs.

[0106] Other embodiments of the novel technology are possible. Although the description above contains much specificity, these should not be construed as limiting the scope of the novel technology, but as merely providing illustrations of some of the presently preferred embodiments of this novel technology. It is also contemplated that various combinations or sub-combinations of the specific features and aspects of the embodiments may be made and still fall within the scope of the novel technologies. It should be understood that various features and aspects of the disclosed embodiments can be combined with or substituted for one another in order to form varying modes of the disclosed novel technologies. Thus, it is intended that the scope of at least some of the present novel technologies herein disclosed should not be limited by the particular disclosed embodiments described above.

[0107] The terms recited in the claims should be given their ordinary and customary meaning as determined by reference to relevant entries (e.g., definition of "plane" as a carpenter's tool would not be relevant to the use of the term "plane" when used to refer to an airplane, etc.) in dictionaries (e.g., widely used general reference dictionaries and/or relevant technical dictionaries), commonly understood meanings by those in the art, etc., with the understanding that the broadest meaning imparted by any one or combination of these sources should be given to the claim terms (e.g., two or more relevant dictionary entries should be combined to provide the broadest meaning of the combination of entries, etc.) subject only to the following exceptions: (a) if a term is used herein in a manner more expansive than its ordinary and customary meaning, the term should be given its ordinary and customary meaning plus the additional expansive meaning, or (b) if a term has been explicitly defined to have a different meaning by reciting the term followed by the phrase "as used herein shall mean" or similar language (e.g., "herein this term means," "as defined herein," "for the purposes of this disclosure [the term] shall mean," etc.). References to specific examples, use of "i.e.," use of the word "novel technology," etc., are not meant to invoke exception (b) or otherwise restrict the scope of the recited claim terms. Other than situations where exception (b) applies, nothing contained herein should be considered a disclaimer or disavowal of claim scope. Accordingly, the subject matter recited in the claims is not coextensive with and should not be interpreted to be coextensive with any particular embodiment, feature, or combination of features shown herein. This is true even if only a single embodiment

of the particular feature or combination of features is illustrated and described herein. Thus, the appended claims should be read to be given their broadest interpretation in view of the prior art and the ordinary meaning of the claim terms.

[0108] Unless otherwise indicated, all numbers or expressions, such as those expressing dimensions, physical characteristics, etc. used in the specification (other than the claims) are understood as modified in all instances by the term “approximately.” At the very least, and not as an attempt to limit the application of the doctrine of equivalents to the claims, each numerical parameter recited in the specification or claims which is modified by the term “approximately” should at least be construed in light of the number of recited significant digits and by applying ordinary rounding techniques.

[0109] While the novel technology has been illustrated and described in detail in the drawings and foregoing description, the same is to be considered as illustrative and not restrictive in character. It is understood that the embodiments have been shown and described in the foregoing specification in satisfaction of the best mode and enablement requirements. It is understood that one of ordinary skill in the art could readily make a nigh-infinite number of insubstantial changes and modifications to the above-described embodiments and that it would be impractical to attempt to describe all such embodiment variations in the present specification. Accordingly, it is understood that all changes and modifications that come within the spirit of the novel technology are desired to be protected.

What is claimed is:

1. A method for constructing a structure from a mechanical secured block building system with concrete masonry units, comprising:

- a) placing first and second respective anchor bars on a foundation surface;
- b) placing a first concrete masonry unit over the respective starter anchor bars;
- c) placing third and fourth respective anchor bars into respective upper extended recessed channels;
- d) placing respective first and second tendon through bolts into respective through apertures in respective third and fourth anchor bars;
- e) threadedly engaging respective first and second tendon through bolts with respective first and second threaded apertures in respective first and second anchor bars;
- f) placing fifth and sixth respective anchor bars adjacent the first concrete masonry unit;
- g) placing a second concrete masonry unit over the fifth and sixth anchor bars;
- h) placing seventh and eighth respective anchor bars into respective upper extended recessed channels in the second concrete masonry unit;
- i) placing respective third and fourth tendon through bolts into respective third and fourth through apertures in respective seventh and eighth anchor bars;
- j) threadedly engaging respective third and fourth tendon through bolts with respective third and fourth threaded apertures in respective third and fourth anchor bars;
- k) positioning a third concrete masonry unit over the first and second concrete masonry units wherein the third concrete masonry unit straddles the first and second concrete masonry units;

- l) placing respective ninth and tenth anchor bars into respective upper extended recessed channels of the third concrete masonry unit;
- m) placing respective fifth and sixth tendon through bolts into respective fifth and sixth through apertures in the respective ninth and tenth anchor bars; and
- n) threadedly engaging respective fifth and sixth tendon through bolts with respective fifth and sixth threaded apertures in respective ninth and tenth anchor bars;

wherein each respective concrete masonry units further comprises: a masonry longitudinal length, a masonry width measured perpendicularly to the masonry longitudinal length, wherein the masonry width which is essentially one half the longitudinal length and which is substantially uniform along the masonry longitudinal length, a masonry top surface, the masonry top surface being substantially planar, a masonry bottom surface, the masonry bottom surface being substantially planar, a masonry height which is essentially one half the longitudinal length and which is measured between the masonry top and masonry bottom surfaces, the masonry height being substantially uniform along the masonry longitudinal length, a first through-cavity formed through the masonry unit from the top surface to the bottom surface, a second through-cavity formed through the masonry unit from the top surface to the bottom surface, a third through-cavity formed through the masonry unit from the top surface to the bottom surface, and an anchor bar channel recessed formed in the masonry top surface and oriented substantially along the masonry longitudinal length;

wherein each respective anchor bar further comprises: (i) a first set of apertures, the first set of apertures comprising a first non-threaded aperture and a first threaded aperture, wherein the first non-threaded aperture and the first threaded aperture are located in first and second diagonally opposing quadrants of a coordinate system defined by a longitudinal centerline of the anchor bar and a line that is perpendicular to the longitudinal centerline; and (ii) a second set of apertures neighboring the first set of apertures, the second set of apertures comprising a second non-threaded aperture that is substantially the same as the first non-threaded aperture, and a second threaded aperture that is substantially the same as the first threaded aperture, wherein the second non-threaded aperture and the second threaded aperture are located in third and fourth diagonally opposing quadrants of the coordinate system but spaced longitudinally from the first set of apertures, wherein the first set of apertures is aligned with the first through-cavity and the second set of apertures is aligned with the third through-cavity when the anchor bar is placed into the anchor bar recessed channel of the masonry unit; and wherein a width of the anchor bar is smaller than a width of the recessed channel of the masonry unit; and

wherein each respective through tendon further comprises: (i) a first fastener end and a second fastener end, (ii) a head portion at the first fastener end, (iii) a stem portion rigidly affixed to the head portion, the stem portion comprising a threaded portion at the second fastener end; wherein the head portion does not fit through the first non-threaded aperture; wherein the stem portion slides freely through the first non-threaded

aperture; and wherein the threaded portion is configured to threadably engage the first threaded aperture.

2. The method of claim 1 and further comprising:

o) repeat the above steps until a desired structure is completed.

3. A method for building a mechanical secured block structure, comprising:

a) placing a footer block on a desired surface;

b) inserting two respective starter bar nuts into the footer block;

c) inverting the footer block;

d) placing a first concrete masonry unit over respective first and second anchor bars;

e) aligning the first concrete masonry unit with the footer block;

f) placing second and third footer blocks adjacent the first footer block;

g) placing a second concrete masonry unit adjacent the first concrete masonry unit;

h) positioning each respective concrete masonry unit to equally straddle two adjacent footer blocks;

i) positioning respective anchor bars atop respective concrete masonry units; and

j) bolting respective concrete masonry units to respective footer blocks to interconnect the two respective concrete masonry units and the three respective footer blocks to define a contiguous wall;

wherein each respective masonry unit and each respective footer block are post tensioned to be under compression.

* * * * *