



US009970632B2

(12) **United States Patent**
Noeth

(10) **Patent No.:** **US 9,970,632 B2**
(45) **Date of Patent:** **May 15, 2018**

(54) **ENERGY EFFICIENT ILLUMINATION APPARATUS AND METHOD FOR ILLUMINATING SURFACES**

27/48 (2013.01); F21Y 2115/10 (2016.08);
F21Y 2115/30 (2016.08); Y10S 362/812 (2013.01)

(71) Applicant: **Raymond A. Noeth**, West Palm Beach, FL (US)

(58) **Field of Classification Search**
CPC .. F21V 14/04; F21Y 2115/10; F21Y 2115/30; G02B 5/02; G02B 26/10; G02B 27/48; Y10S 362/812

(72) Inventor: **Raymond A. Noeth**, West Palm Beach, FL (US)

See application file for complete search history.

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 295 days.

(56) **References Cited**

(21) Appl. No.: **14/544,235**

U.S. PATENT DOCUMENTS

(22) Filed: **Dec. 12, 2014**

3,541,323 A	11/1970	Stewart et al.	
5,402,324 A	3/1995	Yokoyama et al.	
5,764,315 A	6/1998	Yokota et al.	
5,863,113 A	1/1999	Oe et al.	
6,231,200 B1	5/2001	Shinohara et al.	
6,712,481 B2	3/2004	Parker et al.	
7,391,552 B2*	6/2008	Barton	G02B 6/0043 359/233

(65) **Prior Publication Data**

US 2015/0167934 A1 Jun. 18, 2015

2007/0274075 A1 11/2007 Nagamune
(Continued)

Related U.S. Application Data

Primary Examiner — Stephen F Husar

(63) Continuation-in-part of application No. 13/770,249, filed on Feb. 19, 2013, now Pat. No. 8,939,610, which is a continuation of application No. 12/589,270, filed on Oct. 21, 2009, now Pat. No. 8,376,585.

(57) **ABSTRACT**


(60) Provisional application No. 61/197,412, filed on Oct. 28, 2008.

A system for illuminating an object is provided, the system comprising a coherent or semi-coherent light source and a first diffuser positioned relative to the coherent or semi-coherent light source so as to receive said coherent or semi-coherent light. The first diffuser may diffuse the light to produce diffused light. An actuator having moveable elements, such as a moveable reflective and/or phosphorus surfaces, may be positioned to project the diffused light onto an object, and may be moved to project light onto different portions of the object. This movement may be performed with such rapidity that it is not perceived by a person viewing the object. Rather, the entire object would appear to be illuminated. Movement of the elements may be controlled by a computer, and may be performed according to a predefined routine.

(51) **Int. Cl.**
F21V 14/04 (2006.01)
G02B 5/02 (2006.01)
G02B 26/10 (2006.01)
G02B 27/48 (2006.01)
F21Y 115/30 (2016.01)
F21Y 115/10 (2016.01)

(52) **U.S. Cl.**
CPC **F21V 14/04** (2013.01); **G02B 5/02** (2013.01); **G02B 26/10** (2013.01); **G02B**

6 Claims, 25 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

2008/0187012	A1	8/2008	Yamauchi et al.
2009/0016061	A1	1/2009	Chen et al.
2009/0168424	A1	7/2009	Yamauchi et al.

* cited by examiner




FIG. 1




FIG. 2A




FIG. 2B




FIG. 2C




Fig. 3A




FIG. 3B




FIG. 3C




FIG. 4A




Fig 4B




FIG. 5A




FIG. 5B




FIG. 6A




FIG. 6B




FIG. 7A




FIG. 7B




Fig. 8A




Fig. 8B




FIG. 8C




FIG. 9A




Fig. 9B




Fig. 9C




Fig.9D




Fig.10




FIG. 11




FIG. 12




Fig. 13







FIG. 14






FIG. 16




Fig 17

1

ENERGY EFFICIENT ILLUMINATION APPARATUS AND METHOD FOR ILLUMINATING SURFACES

CROSS-REFERENCE TO RELATED APPLICATIONS

The present application is a continuation in part of continuation patent application Ser. No. 13/770,249 which was allowed but not presently issued and related to U.S. Pat. No. 8,376,585 issued on Feb. 19, 2013 which claims the benefit of the filing date of U.S. Provisional Patent Application No. 61/197,412 filed Oct. 28, 2008, the disclosures of which are hereby incorporated herein by reference.

BACKGROUND OF THE INVENTION

Light sources produce incoherent light (i.e., which has a phase that varies randomly with time and position) or coherent light (i.e., which has a phase that does not vary randomly with time and position). The vast majority of light is produced from incoherent light sources (e.g., halogen bulbs, incandescent lamps, LED lights, etc.). The most common form of coherent light is produced by light amplification by stimulated emission of radiation (i.e., laser).

Typically, lasers produce coherent light by either emitted light in a narrow, low-divergence beam, or converted light into coherent light with the help of optical components such as lenses. The coherent light produced by lasers can be a narrow wavelength spectrum (i.e., monochromatic light), a broad spectrum (i.e., polychromatic light), or in some instances at multiple distinct wavelengths simultaneously (i.e., selectively-chromatic light). Some techniques presently used enable diffusion of the coherent light produced by lasers. For example, a laser beam may pass through a diffuser to spread the beam. Similarly, apertures may be placed in front of light projected from a laser to enable only some

light to pass through the aperture.

The first lasers were gas lasers. Gas lasers require large power sources and generate significant quantities of heat radiation. Presently, there are many forms of lasers (e.g., chemical lasers, excimer lasers, fiber-hosted lasers, photonic crystal lasers, dye lasers, and free electron lasers). However, the advent of solid state lasers and semiconductor lasers have yielded commercial laser diodes capable of emitting coherent light at wavelengths from 375 nm to 1800 nm (and in some instances wavelengths of over 3 μ m). These low power laser diodes require wattages that are less than one watt of power in most instances. Because of their extremely low energy, requirements laser diodes have yielded numerous technological breakthroughs, such as, CD players, DVD Players, Laser pointers, laser printers, and numerous other devices. However, there are still many technological breakthroughs that have yet to be yielded by these low energy diodes.

Presently, the United States and the world are making efforts to reduce energy consumption. For example, there has been a large push in recent years to switch from incandescent light bulbs to compact fluorescent lamps. Some have even begun using LED (Light Emitting Diode) lamps as an even more energy efficient light source than compact fluorescent lamps. While these innovations are a step in the right direction, there is still a need to investigate other means for reducing energy consumption.

For example, a large quantity of electrical energy is consumed in illuminating signs and other surfaces at night.

2

Notably, in Apr. of 2009, the lights reflected off the surfaces of the Leonard P. Zakim Bridge were reported to cost over \$5,000 per month and were thereby shutdown indefinitely. Further, many signs on the roads require lighting by highly inefficient high powered bulbs. Even further, many residential and commercial properties use similar bulbs to reflect off interior and exterior surfaces. Illuminating all of these surfaces creates a large burden, both environmentally and financially, due to the energy consumed. Thus, a need exists to create an energy efficient illumination apparatus and method for illuminating surfaces.

BRIEF SUMMARY OF THE INVENTION

One aspect of the invention provides a system for illuminating, comprising a coherent or semi-coherent light source and a first diffuser positioned relative to the coherent or semi-coherent light source so as to receive said coherent or semi-coherent light. The first diffuser may diffuse the light to produce diffused light. Further, an actuator having a moveable element or moveable elements may be positioned to project the diffused light onto an object. The moveable element or elements may be a reflective surface and/or phosphorous coated surface or can employ multiple surfaces. Movement of the element or elements may be controlled by a computer, and may be performed according to a predefined routine.

According to one aspect, the diffused light may be further reflected off the object and onto a display surface. According to another aspect, the object may be a panel including a concave edge and/or a reflective or phosphorous coating. For example, the diffused light may be reflected off the moveable coated surface of the actuator and through a concave edge of a panel to disperse light throughout the panel. Other edges of the panel may be coated with a reflective coating or phosphors to further spread light throughout the panel, so that a display surface appears illuminated using a decreased amount of light from the source.

According to another aspect, the actuator the moveable element may be positioned within the object and may consist of more than one element and actuator. Alternatively or additionally, a second diffuser capable of moving relative to the first diffuser may be used. Further, the coherent light source, the first diffuser, and the actuator may be sized to fit within the object.

Another aspect of the invention provides a method for illuminating an object, comprising emitting coherent or semi-coherent light, diffusing the coherent or semi-coherent light to produce diffused light, projecting the diffused light onto the object, and scanning the diffused light on and off the object or in a predetermined pattern on the object. Such scanning may form an image, e.g., a particular shape on a display surface. Further, at least one of color, brightness, or scanning pattern of the diffused light may be modified in response to a predetermined condition or light a predetermined condition. Even further, the diffused beam may be reflected off an object onto a display surface, for example, to achieve "backlighting."

Yet another aspect of the invention provides a system for illuminating an object, comprising a sensor for detecting a condition and an illumination device communicatively coupled to the sensor. The illumination device may comprise a coherent or semi-coherent light source, a diffuser positioned relative to the coherent light source so as to diffuse light from the semi-coherent or coherent light source to produce diffused light, and an actuator having a moveable element or actuators with moveable elements positioned to

project the diffused light onto an object. The illumination device may be activated in response to detection of a condition by the sensor. According to one aspect, a processor may be communicatively coupled between the sensor and the illumination device, for example, to control activation of the illumination device. Moreover, the processor may be programmed to determine whether the illumination device requires maintenance. The condition detected by the sensor may relate to at least one of light, sound, pressure, movement, seismic waves, electromagnetic signals, microwaves, and color. Further, the condition detected by the sensor may be the presence of a motor vehicle, and the illumination device may in turn illuminate a road sign.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a side view illustration of diffusion of laser light according to an aspect of the invention.

FIGS. 2A-2C are side view illustrations of a laser light source producing an image on a surface according to an aspect of the invention.

FIGS. 3A-C illustrates several embodiments of reflective diffusers according to the invention.

FIGS. 4A-B are side view illustrations of an illumination system using multiple diffusers according to an aspect of the invention.

FIGS. 5A-B are side view illustrations of an illumination system using shape modifiers for creating a desired pattern according to an aspect of the invention.

FIGS. 6A-B illustrate scanning patterns according to an aspect of the invention.

FIGS. 7A-B are detailed views of viewing surfaces according to an aspect of the invention.

FIGS. 8A-C are schematic diagrams of dynamic lasers illuminating a surface for viewing according to an aspect of the invention.

FIGS. 9A-D illustrate an illumination system using dynamic diffusers according to an aspect of the invention.

FIG. 10 illustrates illumination of a panel using an illumination device according to an aspect of the invention.

FIG. 11 is a detailed cross-sectional view of a surface of an illuminated panel according to an aspect of the invention.

FIG. 12 is a system for illuminating a panel according to an aspect of the invention.

FIG. 13 is a system for illuminating a panel according to another aspect of the invention.

FIG. 14 is a system for illuminating a panel according to another aspect of the invention.

FIGS. 15A-15C illustrate various panel surfaces in an illumination system according to an aspect of the present invention.

FIG. 16 is a diagrammatic representation of a system according to an aspect of the invention.

FIG. 17 illustrates an illumination system using dynamic diffusers according to an aspect of the invention.

DETAILED DESCRIPTION

This disclosed subject matter provides an apparatus and method for illuminating a surface for viewing. The apparatus and/or method include a laser light source and a diffuser for shaping the beam of light to a desired pattern sufficient to enable illuminating a surface for viewing. The desired pattern can be projected or scanned across the surface for viewing in a predetermined path.

The diffuser can be at least one of a reflective coated or phosphorous coated diffuser and lens diffuser. Further, the

diffuser can be any of an optical lens, a convex reflective or phosphorous coated surface, a concave reflective or phosphorous coated surface, and a substantially flat reflective or phosphorous surface or independent surfaces positioned side by side to unilaterally move portions of the beam on or off the object. In some instances, the apparatus and/or method can further include a second diffuser capable of moving relative to the first diffuser. The second diffuser can move the desired pattern through a predetermined path. The second diffuser can be at least one of a second reflective or phosphorous coated diffuser and second lens diffuser. Further, the second diffuser can be any of an optical lens, a convex reflective or phosphorous surface, a concave reflective or phosphorous surface, and a substantially flat reflective or phosphorous surface or surfaces side by side moving independent of each other. The apparatus and/or method can further include an aperture located between the diffuser and the surface for viewing. The aperture can be designed to only allow projecting of the desired pattern onto a specific region of the surface for viewing.

Scanning can be accomplished by various techniques. Scanning techniques can include the use of at least one dynamic diffuser, at least one dynamic laser, and any combination thereof alone or in conjunction. Accordingly, scanning can require driving any one of at least one dynamic laser and at least one dynamic diffuser.

By way of a first example, scanning can be accomplished with the assistance of a first fixator attached to the laser capable of moving the laser in a first axis; and a second fixator attached to the laser capable of moving the laser in a second axis. The first fixator and second fixator can be capable of moving the laser through the predetermined path along the first and second axis thereby causing the desired pattern to move through the predetermined path. For example, the first axis can be horizontal and the second axis can be vertical. Thus, the predetermined path can be designed to scan the desired pattern horizontally and vertically across the surface for viewing.

By way of a second example, scanning can be accomplished with a first reflective or phosphorous coated diffuser and a second reflective or phosphorous diffuser. The first reflective or phosphorous coated diffuser can reflect the desired pattern in a first direction onto the second reflective or phosphorous coated diffuser; and the second reflective or phosphorous coated diffuser can reflect the pattern in a second direction. Thus, the first reflective or phosphorous coated diffuser and second reflective or phosphorous coated diffuser are capable of scanning the desired pattern through the predetermined path. Further, the first and second reflective or phosphorous coated diffuser can be any one of flat, convex, or concave. The first reflective or phosphorous coated diffuser can include multiple sides and can be designed to rotate about itself or can have multiple surfaces working independent of each other in a side by side two dimensional pattern. The second reflective or phosphorous coated diffuser can be mounted on an angle to a rotating shaft or can be a multiple reflective or phosphorous surfaces positioned in a side by side configuration and positioned to the first diffuser. The combination of the first reflective or phosphorous coated diffuser having multiple surfaces or sides and the second reflective or phosphorous coated diffuser mounted on an angle can yield a non-linear pattern.

It is to be understood that throughout the text of this application laser light is referred to in the broad sense of any coherent light source, including semi-coherent light sources. Accordingly, any form of suitable laser light source or coherent light source may be used. For simplicity a single

laser light source is illustratively depicted and described. However, it is envisioned that more than one laser light source may be used collectively for illuminating a surface for viewing.

In some embodiments, an apparatus and method are disclosed that use a low power laser light source (e.g., solid state laser, semiconductor laser, etc.) for producing a laser light. This laser light interacts with a diffuser shaping the light to a desired pattern sufficient for illuminating a surface for viewing. In some instances, this surface for viewing can be a highly reflective surface such as a Department of Transportation (“DOT”) sign (e.g., stop signs) or the surface could be phosphorous coated. Further, in some embodiments, for larger surfaces (e.g., DOT highway signs, billboards, etc.) the desired pattern can be moved (e.g., scanned) through a predetermined path at a substantially high velocity such that the entire surface for viewing is illuminated.

To ease understanding of the disclosed subject matter, the apparatus and method are described as being located on a static surface at an offset from the surface for viewing (e.g., stop signs, DOT highway signs, billboards, etc.). However, the disclosed subject matter can be located on a dynamic surface, for example, to compensate for vibration, adjust scanning, increase/decrease the predetermined path, or for any other reason deemed suitable. Further, the apparatus and method can be modified for a substantially larger scan (e.g., by adjusting aperture, increasing laser power, etc.) for use in a lighting system on, for example, a boat, a vehicle, an aircraft, part of an illumination system for aircraft landing, very large signs, reflectively painted runways, or for any other reason deemed suitable. Alternatively, the disclosed subject matter can be designed for use as a hand held device (e.g., as a hand held illuminator, etc.).

Referring to FIG. 1, in some embodiments, a laser light source **102** produces a light **104** that is incoherently increased by a diffuser **106** expanding light **104** to light **108** that substantially covers the surface area of a surface **110**. Diffuser **106** can be any device capable of expanding (i.e., spreading out or scattering) light. Further, the electrical energy (i.e., wattage) supplied to laser light source **102** can be adjusted thereby providing the appropriate quantity of light needed for illuminating the surface for viewing. For example, the laser light source can be adjusted for reflecting off of a DOT highway sign such that the sign is visible to a driver at a suitable distance from the sign.

Referring to FIG. 2A, an illustrative depiction of laser light source **102** is shown producing light **104** (i.e., a coherent light beam) yielding a laser light spot **200** on surface **110**. Laser light spot **200** is substantially small compared to surface **110** and thus cannot illuminate all of surface **110**.

Referring to FIGS. 2B-C, diffuser **106** is illustratively depicted as a lens diffuser **106a**, in accordance with some embodiments of the disclosed subject matter. Referring to FIG. 2B, light **104** produced by laser light source **102** is illustratively depicted as passing through lens diffuser **106a**. As shown, lens diffuser **106a** modifies the shape of light **104** (i.e., light **104** becomes semi-coherent) to light **108** creating a desired pattern **202** on surface **110**. In some instances, modifying the shape of light **104** to light **108** allows for a greater area of illumination on surface **110**. In some embodiments, lens diffuser **106a** modifies light **104** to a substantially circular pattern. Referring to FIG. 2C, in other embodiments, lens diffuser **106a** is capable of modifying light **104** into a substantially linear desired pattern **204**. Further, although not shown, light **104** can be modified into any desired pattern, such as, but not limited to a circular pattern.

Although described as a lens diffuser, diffuser **106a** can be, but is not limited to, ground glass diffusers,

Teflon® diffusers, holographic diffusers, opal glass diffusers, and greyed glass diffusers. Lens diffuser **106a** can be ground or cut to diffuse the light in many different ways. For example, although not shown, lens diffuser **106a** can modify light **104** into multiple lights. That is, lens diffuser **106a** can be made in such a way as to modify light **104** from a single light to any plurality of lights. Although lens diffuser **106a** is illustrated as a single diffuser, in some embodiments, multi-diffusers (e.g., multiple lens diffusers) can be used to create the desired pattern on surface **110**.

Referring to FIGS. 3A-C, diffuser **106** is shown as a reflective diffuser **106b**. Reflective diffuser **106b** can be, but is not limited to, mirrors, reflective surfaces, and highly reflective surfaces. Further, in some embodiments, reflective diffuser **106b** can be shaped, such as, but not limited to, concave, convex, flat, spheroid, conical, any multisided geometric shape, or any other shape deemed suitable. For example, referring to FIG. 3A, reflective diffuser **106b** includes a concave surface capable of modifying light **104** to light **108** creating desired pattern **302** on surface **110**. Further, referring to FIG. 3B, reflective diffuser **106b** includes a convex surface capable of modifying light **104** to light **108** creating desired pattern **304** on surface **110**. Further still, referring to FIG. 3C, reflective diffuser **106b** includes a flat surface capable of modifying light **104** to light **108** creating desired pattern **306** on surface **110**.

Although reflective diffuser **106b** is illustrated as a single diffuser, in some embodiments, multi-diffusers (e.g., multiple reflective diffusers) can be used to create the desired pattern on surface **110**. Further, in some embodiments, the size and shape of the desired pattern can be modified by changing the angle of deflection off of reflective diffuser **106b**. Further still, in some embodiments any combination of at least one reflective or phosphorous coated diffuser and at least one lens diffuser can be used, alone or in combination, to create the desired pattern on surface **110**.

In some embodiments, laser light source **102** can be selected based on a particular wavelength or frequency interval of light generated by it. This may be done to increase illumination of a surface for viewing by selecting a wavelength interval or frequency interval based on the color of the surface for viewing or a specific region on the surface for viewing. For example, the laser light source can be selected to produce red light (e.g., 700-635 nm wavelength interval 430-480 THz frequency interval), orange light (e.g., 635-590 nm wavelength interval 480-510 THz frequency interval), yellow light (e.g., 590-560 nm wavelength interval 510-540 THz frequency interval), green light (e.g., 560-490 nm wavelength interval 540-610 THz frequency interval), blue light (e.g., 490-450 nm wavelength interval 610-670 THz frequency interval), violet light (e.g., 450-400 nm wavelength interval 670-750 THz frequency interval) or any combination thereof based on the color emitted by the laser light source and the color of the surface for viewing. For example, a laser light source capable of emitting green coherent light may be selected for a red stop sign.

In some embodiments, the desired pattern can be created by a plurality of diffusers capable of moving relative to each other. Referring to FIGS. 4A-B, a first reflective or phosphorous coated diffuser **106b** moves relative to a second reflective or phosphorous coated diffuser **106b'**. Moving a plurality of diffusers is not limited to linear motion, only moving one diffuser, or only two diffusers. Rather, in effort to ease understanding, FIGS. 4A-B illustratively depicts a

simple linear movement of a first reflective diffuser **106b** relative to a second reflective diffuser **106b'**.

Further, although described as reflective diffusers, any type of diffuser can be used to create the desired pattern. For example, FIGS. 4A-B depicts a spheroid/columnar reflective or phosphorous coated diffuser and a concave reflective or phosphorous coated diffuser. Alternatively, any plurality of shapes can be used as diffusers. Further, in some embodiments, moving a plurality of diffusers relative to each can be accomplished by any technique, such as, but not limited to, mechanically motion (e.g., piston/cylinder, screw/thread, etc.), electromechanically motion (e.g., electric motor driven, etc.), electromagnetically driven motion, or by any other technique deemed suitable.

Referring to FIG. 4A, first reflective or phosphorous coated diffuser **106b** is located at an initial offset from second reflective or phosphorous coated diffuser **106b'** creating a first desired pattern **402** on surface **110** (not shown). Referring to FIG. 4B, the offset between first reflective or phosphorous coated diffuser **106b** and second reflective or phosphorous coated diffuser **106b'** is decreased creating a second desired pattern **404** on surface **110** (not shown).

In some embodiments, after passing through or reflective off of the diffuser, the light can be further shape modified. This shape modification may be required, for example, to cleave the light or block the light prior to illuminating a surface for viewing. There are many benefits to shape modifying the light, such as, but not limited to, eliminating any safety risk created by having excessive light outside of a surface for viewing or to outline a region of a surface for viewing.

For example, referring to FIGS. 5A-B, light **104** emitted from laser light source **102** can be shape modified to a desired pattern. As shown in FIG. 5A, after light **104** interacts with lens diffuser **106a** at least some of the light can be blocked by a shield **504** thereby creating a shape modified desired pattern **506** on surface **110**. As shown, the shape modified desired pattern **506** illustratively depicted in FIG. 5A is round with an empty (i.e., lightless) polygon (e.g., heptagon) center. Further, as shown in FIG. 5B, after light **104** interacts with lens diffuser **106a** at least some of the light can be cleaved by an aperture like device **508** thereby creating a shape modified desired pattern **510** on surface **110**. Although shape modifying is described as occurring after the light exits a lens diffuser this is by way of example only. Shape modifying can occur before or after laser light exits or enters any of a single diffuser or a plurality of diffusers. Further, although illustratively depicted as a lens diffuser, any diffuser can be used.

As described below in greater detail, in some embodiments, for illuminating a substantially large surface for viewing a desired pattern may be scanned. Scanning can be accomplished by any suitable technique. Scanning techniques may include the use of a static laser, a dynamic laser, a static diffuser, a dynamic diffuser, or any combination thereof alone. Therefore, scanning techniques using a dynamic laser and/or a dynamic diffuser may incorporate a mechanical, electromechanical, electromagnetic, or robotic device for moving any of the dynamic laser, the dynamic diffuser, or any combination thereof. Accordingly, in some embodiments, scanning/moving can be accomplished by any suitable technique, such as, but not limited to, a crank extending from a motor; electromagnetic induction causing a magnet to move; a cartesian robot; a gantry robot; a cylindrical robot; spherical/polar robot; a SCARA robot; an articulated robot; and a parallel robot.

Referring to FIGS. 6A-B, as discussed above, a desired pattern **602/606** can be scanned through a predetermined path **604/608** on surface **110**. For example, scanning through the predetermined path may be performed so rapidly that one viewing the surface would not see a small illuminated portion being scanned across the screen, but would rather perceive the entire viewing surface as illuminated.

In some embodiments, the desired pattern is raster scanned through a predetermined path. The predetermined path can be any path, such as, but not limited to, a snake like path, an S pattern, spiral pattern, horizontal pattern, vertical pattern, horizontal and vertical pattern, a random pattern, or any other pattern deemed suitable. Further, in some embodiments, as depicted by contrasting FIG. 6A to FIG. 6B, a proportional relationship exists between the desired pattern **602/606** and predetermined path **604/608**. Thus, in some embodiments, the scanning technique can be predicated on a scanning velocity, the size of surface **110**, the desired pattern's (and/or shape modified desired pattern's) shape and size, the predetermined path, and/or the combination of at least one laser light source.

In some embodiments, the scanning technique can be predicated on a phosphorous coated surface and or reflectivity surface for viewing. For example, referring to FIGS. 7A-B, surface **110** can have differing levels of reflectivity and may be combined with phosphorous coatings (not shown). By comparing FIG. 7A to 7B the interaction between reflectivity of surface **110** and the techniques for illuminating surface **110** becomes apparent. For example, surface **110** in FIG. 7A has a substantially lower level of reflectivity than surface **110** in FIG. 7B, which includes a plurality reflective beads **702**. Thus, in some embodiments, the scanning technique can be predicated on the scanning velocity, the reflectivity of surface **110**, phosphorous coatings on **110**, the size of surface **110**, the desired pattern's (and/or shape modified desired pattern's) shape and size, the predetermined path, and/or the combination of at least one laser light source. Accordingly, illuminating a surface for viewing can be accomplished by many various techniques based on any of the above factors. Scanning may also be used to form an image of a predetermined shape. Additionally, scanning may be used to effectively project a wide-angle light for the purpose of lighting large target surfaces in close proximity, to limit light bleeding past the edge of a target, to shape the projected light to correspond the shape of the target surface, or to change a color of the projected light throughout the scan (e.g., to coincide with a color of the target surface).

Scanning may be performed using motors, electromagnetic motion, or any other mechanism for moving the projected light on the target surface. Preferably, such mechanism would be capable of moving the projected light on the target surface quickly enough that the scan pattern would not be perceived. Thus, for example, an actuator used for scanning may implement a mechanical, electromechanical, electromagnetic, or robotic device for moving any one of a laser, a diffuser, or any combination thereof. Further examples include a crank extending from a motor, electromagnetic induction causing a magnet to move, a Cartesian robot, a gantry robot, a cylindrical robot, spherical/polar robot, a SCARA robot, an articulated robot, and a parallel robot. In some instances, this scanning/moving can be computer controlled (e.g., using a microprocessor) and scanning/moving can be based on any of the above factors.

To ease understanding of the disclosed subject matter, below are a few examples of how scanning/moving can be accomplished. However, it is envisioned that any number of

alternative scanning techniques can be used without deviating from the scope of the disclosed subject matter. Further, any of the techniques described below can be used alone or in combination to move/scan any one of at least one laser, at least one diffuser, or any combination thereof alone or in conjunction.

Referring to FIGS. 8A-C, in some embodiments, a dynamic laser light source can be used for illuminating surface for viewing. While FIGS. 8A-C do not illustrate a diffuser, it should be understood that a diffuser may be added to these embodiments to produce a desired shape, as discussed above.

Referring to FIG. 8A, a dynamic laser light source is mechanically moved in a vertical axis in accordance with some embodiments of the disclosed subject matter. As depicted, laser light source **102** can be mounted in a gimbal style mount **802** having a horizontal axis stand **804** and a vertical axis stand **805**. This mount allows movement of laser light source **102** on a horizontal and vertical axis or movement in any angle desired. Although described as a gimbal style mount, laser light source **102** can be mounted in a ball and socket type mount or any type of mount that allows for movement in one or two axis or in any angle desired. As shown, laser light source **102** uses a diffuser (not shown) creating a desired pattern **806** (e.g., a substantially ovoidal pattern) that is scanned along a predetermined path (i.e., up and down a vertical path). Scanning up and down a vertical path with an ovoidal desired pattern illuminates surface **110**.

In some embodiment, vertical movement of laser light source **102** can be induced by a first crank **808** driven by a first motor **810** with a first fixator **812** located at an offset from the center of first crank **808**. As first fixator **812** connects at one end to first crank **808** and at the other end to laser **102**, when first crank **808** rotates first fixator **812** drives laser **102** up and down along a vertical axis.

Referring to FIG. 8B, in some embodiments, horizontal movement can be induced by a second crank **814** driven by a second motor **816** where a second fixator **818** is located at an offset from the center of second crank **814**. As second fixator **818** connects at one end to second crank **814** and at the other end to laser **102**, when second crank **814** rotates second fixator **818** drives laser **102** back and forth along a horizontal axis. In some instances, laser light source **102** uses a diffuser (not shown) creating a desired pattern **820** (e.g., a substantially round pattern) that can be scanned along a predetermined path (i.e., back and fourth along a horizontal path) illuminating surface **110**.

Still referring to FIG. 8B, in some embodiments, vertical and horizontal movement of the laser can be combined. That is, as vertical movement of laser light source **102** is induced by first crank **808** driven by first motor **810** with first fixator **812** located at an offset from the center of first crank **808**; horizontal movement is also induced by second crank **814** driven by second motor **816** with second fixator **818** located at an offset from the center of second crank **814**. This combination can allow for any movement of desired pattern **820** through any predetermined path on surface **110**.

Referring to FIG. 8C, in some embodiments, vertical and horizontal movement of the laser is driven by electromagnetic induction. For example, first fixator **812** can be attached to laser **102** at one end and at a second end can include a first magnet **822** housed in an electromagnetic device **824** capable of varying polarity (i.e., magnetic polarity). By varying polarity first magnet **822** can move in a first and second direction driving first fixator **812** up and down along a vertical axis. Further, second fixator **818** can be

attached to laser **102** at one end and at a second end can include a second magnet **826** housed in an electromagnetic device **828** capable of varying polarity. By varying polarity second magnet **826** can move in a first and second direction driving second fixator **818** back and forth along horizontal axis.

Further, in some embodiments, vertical and horizontal movement of the laser controlled by electromagnetic induction can be combined. For example, as vertical movement is driven by first fixator **812** attached to laser **102** at one end and at a second end including first magnet **822** housed in electromagnetic device **824** capable of varying polarity; horizontal movement is driven by second fixator **818** attached to laser **102** at one end and at a second end including second magnet **826** housed in electromagnetic device **828** capable of varying polarity. As shown, this combination of vertical and horizontal movement allows a desired pattern **830** to scan through a predetermined path thereby illuminating surface **110**. Further, as shown in FIG. 8C surface **110** can, as described above, be any shape thus desired pattern **830** may be required to scan through a substantially complex predetermined path for illuminating surface **110**.

Referring to FIGS. 9A-D, at least one dynamic diffuser can be moved in accordance with some embodiments of the disclosed subject matter. As described above, diffusers can be moved by any technique deemed suitable for producing controlled movement. Electromagnetic induction for moving a reflective diffuser is described with respect to FIGS. 9A-B. A mechanical technique for moving a reflective diffuser is described with respect to FIGS. 9C-D. However, any technique deemed suitable for producing controlled movement of a diffuser can be used without deviating from the scope of the disclosed subject matter. For example, it should be understood that the diffusers depicted in FIGS. 9A-D are not limited to reflective diffusers. Further, one or more lens diffusers may be dynamic. Even further, any additional diffuser can be positioned at any location before/after interacting with a first diffuser and/or before/after any plurality of diffusers.

Referring to FIG. 9A, in accordance with some embodiments, desired pattern **902** can be scanned on surface **110** by moving a plurality of reflective and or phosphorous coated diffusers (i.e., dynamic reflective or phosphorous coated diffusers). The dynamic reflective or phosphorous coated diffuser can be any form of diffuser previously described and can be moved by any technique deemed suitable. As shown, the reflective or phosphorous coated diffusers movement can be driven by electromagnetic induction. For example, laser light source **102** can be statically mounted and the laser light can interact with a first dynamic reflective diffuser **904**. First dynamic reflective or phosphorous coated diffuser **904** can be a reflective or phosphorous coated surface capable of moving by, for example, using a bearing assemblies **908**, an electromagnetic device **910**, and a first fixator **912** including a first magnet **914**. As shown first fixator **912** can be centrally attached to first dynamic reflective or phosphorous coated diffuser **904**. In use, first dynamic reflective or phosphorous coated diffuser **904** can be driven by first dynamic fixator **912** centrally attached to first dynamic reflective or phosphorous coated diffuser **904** at one end and at a second end including first magnet **914** housed in electromagnetic device **910** capable of varying polarity. As the polarity changes first dynamic reflective or phosphorous coated diffuser **904** can be driven in a first and second direction while, for example, being guided by bearing assemblies or hinge points **908**. Further, after interacting

11

with first dynamic reflective diffuser **904** the laser light can further interact with a second dynamic reflective or phosphorous coated diffuser **906**.

By way of example, second dynamic reflective or phosphorous coated diffuser **906** can be driven by electromagnetic induction. For example, after interacting with first dynamic reflective diffuser **904**, laser light can interact with second dynamic reflective or phosphorous coated diffuser **906**. Second dynamic reflective or phosphorous coated diffuser **906** can be a reflective or phosphorous coated surface capable of moving by, for example, using a second bearing assembly or pivot point **916**, a second electromagnetic device **920**, and a second fixator **922** including a second magnet **924**. As shown, second fixator **922** can be attached to second dynamic reflective or phosphorous coated diffuser **906** at an offset from second bearing assembly or pivot point **916**. In use, second dynamic reflective or phosphorous coated diffuser **906** can be driven by second fixator **922** attached to second dynamic reflective or phosphorous coated diffuser **906** at one end and at a second end including second magnet **924** housed in second electromagnetic device **920** capable of varying polarity. As the polarity changes second fixator **922** can be driven in a first and second direction causing second dynamic reflective diffuser **906** to move at an angle relative to the offset from second bearing or pivot point **916**. The combination of first dynamic reflective or phosphorous coated diffuser **904** moving and second dynamic reflective or phosphorous coated diffuser **906** moving scans desired pattern **902** on surface **110** through a predetermined path.

Referring to FIG. 9B, in accordance with some embodiments, desired pattern **902** can be scanned on surface **110** by a single dynamic reflective or phosphorous coated diffuser **926**. Single dynamic reflective or phosphorous coated diffuser **926** can be mounted in, for example, a gimbal or any other style mount that allows for multi axis movement. As shown, single dynamic reflective or phosphorous coated diffuser **926** can include a shaped surface (e.g., concave surface). Further, single dynamic reflective or phosphorous coated surface **926** can be moved by a first and second fixator **928**, **930**. By way of example, first and second fixator **928**, **930** can be moved by any of the techniques previously mentioned, such as, electromagnetic induction. Further, as shown, the location of first and second fixator **928**, **930** can vary driving single dynamic reflective or phosphorous coated diffuser **926** in more than one direction. Driving single reflective or phosphorous coated diffuser **926** in more than one direction scans desired pattern **902** through a predetermined path on surface **110**.

Referring to FIG. 9C, scanning can be accomplished by rotating a dynamic reflective or phosphorous coated diffuser **932** having multiple reflective or phosphorous coated surfaces **934A-F** in accordance with some embodiments of the disclosed subject matter. As shown, dynamic reflective or phosphorous coated diffuser **932** can have a hexagon columnar shape capable rotating about its center axis. As dynamic reflective or phosphorous coated diffuser **932** rotates, each of reflective or coated surfaces **934A-F** reflects the laser light thereby scanning in a first direction **936**. That is, unlike the previous techniques of scanning, this allows for repeated scanning in a single first direction only.

Referring to FIG. 9D, a dynamic reflective or phosphorous coated diffuser **938** can be mounted on an angle to a shaft **910** of a motor **942**. In use, as dynamic reflective or phosphorous coated diffuser **938** rotates laser light **944** reflects thereby scanning through 360 degrees.

12

FIG. 10 illustrates an aspect of the invention where the illuminator is used to illuminate a panel **1030**. Illumination may be performed using a semi coherent scanning beam method. A coherent or semi-coherent beam **1010** may be projected from source **1002** and reflected off a reflective or phosphorous coated surface **1006** of an actuator **1022**. The reflected beam **1012** may pass through an edge **1032** of the panel **1030**. The actuator **1022**, or the reflective or phosphorous coated surface **1006** thereof, may move in any of a number of directions, thereby enabling scanning of the reflected beam **1012** throughout the panel **1030**. For example, the reflective or phosphorous coated surface **1006** may pivot back and forth on an access point **1016**, thereby causing the projected beam **1010** to reflect at various angles. Accordingly, the reflected beam **1012** may scan back and forth across an edge **1032** of the panel **1030**. Such scanning may be performed at a rate which is fast enough that the beam itself is not detected by a human eye. Rather, the eye will perceive the entire panel **1030** as being illuminated.

According to one aspect, the edge **1032** of the panel **1030** may be milled in an angle, curve, or both to act as a lens to diffuse and redirect the reflected beam **1012** to another surface of the panel **1030**. For example, as shown in FIG. 10, the edge **1032** is milled in a concave shape, thus facilitated the spreading of the beam within the panel **1030**.

According to a further aspect, the panel **1030** may include a coating along other edges, through which the reflected beam **1012** does not pass. For example, edges **1034**, **1036** may be coated with a bright, phosphorous, or reflective material to reflect light in any or many directions within the panel **1030**. In addition the edges that are coated can be milled in any angle or curve to further diffuse light within the panel **1030**.

A back side of the panel **1030** may be covered with a bright surface, phosphorous, or a high reflective material that uses microscopic bead or grains to further defuse and reflect light, as illustrated in FIG. 11. For example, as reflected beam **1112** passes through edge **1132** of a panel, the beam **1112** is diffused in many different directions. Because an edge **1138** of the panel is coated with grains **1140**, light is refracted off the grains **1140** and back into the panel, rather than passing through the panel. Additionally, light passing through edge **1132** which travels to an opposing edge **1134** may be reflected off the edge **1134** and dispersed because of the convex shape and or phosphorous coating. Such reflection and dispersion may facilitate illumination by spreading light throughout the panel.

FIG. 12 illustrates illumination of a panel **1230** using a light beam **1210** reflected off a reflective or phosphorous coated surface **1206** of an actuator **1222**. The actuator **1222** may cause the reflective or phosphorous coated surface **1206** to rotate about an axis. As the reflective surface **1206** is rotated, light **1210** may be reflected to different portions of the panel **1230**. The actuator **1222** may include miniature motors or the like which enable it to rotate the reflective or phosphorous coated surface **1206**. According to one aspect, the reflective surface may rotate 360 degrees from a location within the panel. For example, the panel **1230** may include a bore **1250** near its center, and the reflective surface **1206** may be positioned in the bore **1250** so as to distribute light relatively evenly throughout. Thus, for example, the light beam **1210** may reflect off the reflective or phosphorous coated surface **1206** at a right angle through the panel **1230**. As the motor rotates the reflective or phosphorous coated surface **1206**, the beam is reflected 360 degrees around through an edge **1255** of the bore **1250** and into the panel **1230**. According to one aspect, the edge **1255** of the panel

13

adjacent the bore 1255 may be curved to facilitate the distribution of light within the panel 1230. The edge 1255 may also be cut to an angle, curve, or both, and can be phosphorous coated to achieve any desired effect.

FIG. 13 represents another embodiment, wherein a reflective or phosphorous coated surface 1306 positioned within a panel 1330 may be rotated by an actuator 1322 to spread light 1310 from a source 1302 around the panel. In this embodiment, the reflective or phosphorous coated surface 1306 is positioned above the panel 1330. Additionally, the panel 1330 has a top surface 1332 which is milled to a wedge shape. The top surface 1332 may be coated with a reflective or phosphorous coating, so that light is further reflected onto an illumination panel 1370. As shown in the illustration, the shape of the top surface 1332 causes reflected beams 1360 to produce an oval shape 1362 on the illumination panel 1370 that could be phosphorous coated. As the reflective surface 1306 is rotated, thereby scanning light across the entire top surface 1332, the reflected beams 1360 will produce an image 1364 in the shape of a larger oval. Accordingly, the illumination panel 1370 is "backlit" by light source 1302 and the panel 1330 to produce a particular image 1364.

As illustrated in FIG. 14, backlighting may be achieved using a panel 1430 having a curved bottom surface 1434. The bottom surface may be coated with a reflective or phosphorous coating. Reflective surface 1406 may be positioned within a bore in the panel 1430 to reflect light throughout the panel. The light may be reflected off the coated bottom surface 1434, and the reflected beams may project onto an illumination panel (not shown) to form an image. Thus, backlighting is achieved while the bottom surface 1434 of the panel 1430 is protected from weather elements etc.

Backlighting may be achieved using a panel of any of a variety of shapes or coated materials. For example, FIGS. 15A-15C shows portions of panels 1530A, 1530B, and 1530C having different shapes. Panel 1530A includes a slop at an angle such that light may be reflected at approximately 90 degree angles. Panel 1530B is shaped in a concave manner to cause diffusion of light projected thereon. Panel 1530C includes a surface having multiple angles. This allows for a beam to be reflected across a larger panel surface by separating the convex angles with horizontal areas running between them and in parallel with the coherent light in a stair step fashion. A defused coherent light source can also be used if the light from the coherent source is not thick enough to engulf the ground angles in the panel.

It should also be understood that the reflective or phosphorous coated surface may be positioned anywhere within the panel (e.g., closer to an edge, in the center, below the panel, etc.), may be adjusted to reflect light at any of a variety of angles, and may move in a number of different directions. For example, the reflective or phosphorous coated surface may be continually repositioned at different angles during the scanning process. Additionally, the reflective or phosphorous coated surface may oscillate back and forth to scan a panel's edge, as opposed to rotating 360 degrees. Even further, it should be understood that the panel 1330 may be moved relative to the illumination panel 1370 to vary the coverage area and intensity of the image 1364 produced by scanned reflective beams 1360.

As described in the above examples, scanning/moving can be accomplished by various suitable techniques. It will be understood that any of the techniques described in the above examples of scanning can be used for moving and any of examples used for moving can be used for scanning.

14

Again, it is envisioned that any number of alternative scanning/moving techniques can be used without deviating from the scope of the disclosed subject matter. For example, any of the above described examples can be used alone, or in conjunction with scanning/moving by a cartesian robot; a gantry robot; a cylindrical robot; spherical/polar robot; a SCARA robot; an articulated robot; a parallel robot; or in any combination thereof.

In some embodiments, the laser light source can be activated (i.e., produce a laser) when a sensor detects light. That is, if the laser light source requires minimal warm up time then the laser light source can be connected to sensors that detect and/or interact with traffic for illuminating the surface for viewing only when needed. This can reduce maintenance and save energy.

FIG. 16 shows a system according to an aspect of the invention including a computer 1600 connected to a sensor 1640 and an illumination system 1620. The computer 1600 may control the illumination device 1620 based on input from the sensor 1640. For example, sensor 1640 may be a traffic sensor configured to detect the presence of motor vehicles. As traffic sensor 1640 detects the presence of motor vehicle 1630, it may transmit a signal to the computer 1600. The signal may be transmitted via a wired connection or wirelessly. The computer 1600 in turn may instruct the illumination device 1620 to activate and illuminate road sign 1622 according to any of the method described herein. Thus, the road sign 1622 may be illuminated only when necessary (i.e., when a motorist is present to view it).

In accordance with one embodiment, the computer 1600 may include a processor 1602, memory 1610, input/output (I/O) port 1612, and other components typically present in general purpose computers.

Memory 1610 stores information accessible by the processor 1602, including instructions 1618 for execution by the processor 1602 and data 1612 which is retrieved, manipulated or stored by the processor 1602. The memory 1610 may be of any type capable of storing information accessible by the processor, such as a hard-drive, ROM, RAM, CD-ROM, write-capable, read-only, or the like.

The instructions 1618 may comprise any set of instructions to be executed directly (such as machine code) or indirectly (such as scripts) by the processor. In that regard, the terms "instructions," "steps" and "programs" may be used interchangeably herein. The functions, methods and routines of the program in accordance with the present invention are explained in more detail below.

Data 1616 may be retrieved, stored or modified by processor 1602 in accordance with the instructions 1618. The data may be stored as a collection of data. For instance, although the invention is not limited by any particular data structure, the data may be stored in computer registers, in a relational database as a table having a plurality of different fields and records, as an XML. The data may also be formatted in any computer readable format such as, but not limited to, binary values, ASCII or EBCDIC (Extended Binary-Coded Decimal Interchange Code). Moreover, any information sufficient to identify the relevant data may be stored, such as descriptive text, proprietary codes, pointers, or information which is used by a function to calculate the relevant data.

Although the processor 1602 and memory 1610 are functionally illustrated in FIG. 16 within the same block, it will be understood by those of ordinary skill in the art that the processor 1602 and memory 1610 may actually comprise multiple processors and memories that may or may not be stored within the same physical housing. For example, some

or all of the instructions and data may be stored on removable CD-ROM and others within a read only computer chip. Some or all of the instructions and data may be stored in a location physically remote from, yet still accessible by, the processor. Similarly, the processor may actually comprise a collection of processors which may or may not operate in parallel.

As noted above, the computer 1600 may comprise additional components typically found in a computer system such as a display (e.g., an LCD screen), user input (e.g., a keyboard, mouse, game pad, touch-sensitive screen), a modem (e.g., telephone or cable modem), and all of the components used for connecting these elements to one another.

In addition or alternatively to merely illuminating the road sign 1622 in response to sensing traffic, other illumination effects may be used. For example, the illumination device 1620 may change a color of the light emitted, alter the brightness of the light, or modify the scanning routine (e.g., to produce a different shape image on a panel). It should be understood that such modifications of lighting effects by the illumination device 1620 may take place in response to any of a number of conditions. For example, the sensor 1640 may be used to detect light, sound, seismic conditions, color, distance, etc.

Although described as a computer system, it will be understood that computer system 1000 can be a stand-alone microprocessor capable of controlling any of the aforementioned scanning techniques.

According to one aspect, the computer 1600 may also receive information from the illumination system 1620. In this regard, for example, the computer 1600 may provide to a user information pertinent to maintenance of the illumination system 1620.

FIG. 17 further clarifies another aspect where a dynamic diffuser using multiple elements modifies shapes to create desired patterns, whereas 1621 positioned to emit coherent or semi-coherent light onto a diffuser made of multiple elements that are independent reflective or phosphorous coated surfaces as depicted with 1622, 1623, and 1624. Each element with their independent actuators pivots independently on the same plane side by side. The elements can be positioned side by side or in two dimensions along the same plane to create the desired effect. To further illustrate, 1623's reflection is shown as being scanned off the panel or surface 1628 by its

actuator being activated. The elements can be moved by any of the techniques previously mentioned, such as, electromagnetic induction.

Although the present invention has been described with reference to particular embodiments, it should be understood that these examples are merely illustrative of the principles and applications of the present invention. Moreover, it should be understood that numerous other modifications may be made to the illustrative embodiments and that other arrangements may be devised without departing from the spirit and scope of the present invention as defined by the appended claims.

The invention claimed is:

1. A system for illuminating an object, comprising: a light source of coherent or semi-coherent light; a first phosphorus coated diffuser positioned relative to the light source so as to receive said coherent or semi-coherent light, said first phosphorus coated diffuser diffusing the coherent or semi-coherent light to produce diffused light; and an electromagnetically driven actuator having moveable elements positioned to project the diffused light onto an object, wherein at least one of the coherent light source, said first phosphorus coated diffuser, and the actuator are sized to fit within the object.

2. The system for illuminating according to claim 1, wherein the moveable elements are reflective surfaces.

3. The system for illuminating according to claim 1, further comprising a computer, wherein the computer is programmed to control movement of the moveable elements.

4. The system for illuminating according to claim 1, wherein the moveable elements move according to a pre-defined routine.

5. The system for illuminating an object, comprising: a light source of coherent or semi-coherent light; a first diffuser positioned relative to the light source so as to receive said coherent or semi-coherent light, said diffuser diffusing the coherent or semi-coherent light to produce diffused light; and an actuator having a moveable element positioned to project the diffused light onto an object, wherein at least one of the coherent light source, the first diffuser, and the actuator are sized to fit within the object and the moveable elements are phosphorous coated surfaces.

6. The system for illuminating according to claim 5, wherein the moveable element is a phosphorus coated surface.

* * * * *