



(12) **United States Patent**
Chandraker et al.

(10) **Patent No.:** **US 9,965,610 B2**
(45) **Date of Patent:** **May 8, 2018**

- (54) **PHYSICAL SYSTEM ACCESS CONTROL**
- (71) Applicants: **NEC Laboratories America, Inc.**, Princeton, NJ (US); **NEC Hong Kong Limited**, Hunghom, Kowloon (HK)
- (72) Inventors: **Manmohan Chandraker**, Santa Clara, CA (US); **Xiang Yu**, Mountain View, CA (US); **Eric Lau**, Kowloon (HK); **Elsa Wong**, Kowloon (HK)
- (73) Assignees: **NEC Corporation** (JP); **NEC Hong Kong Limited**, Hong Kong (HK)
- (*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

- (56) **References Cited**
- U.S. PATENT DOCUMENTS
- 8,457,367 B1 * 6/2013 Sipe G06K 9/00221 382/118
- 8,856,541 B1 * 10/2014 Chaudhury G06F 21/32 382/115
- (Continued)

- OTHER PUBLICATIONS
- Jee, et al., "Liveness Detection for Embedded Face Recognition System", International Journal of Biological and Medical Sciences, Dec. 2006, pp. 235-238, vol. 1(4).
- (Continued)

(21) Appl. No.: **15/637,569**
(22) Filed: **Jun. 29, 2017**

Primary Examiner — Thomas Alunkal
(74) *Attorney, Agent, or Firm* — Joseph Kolodka

(65) **Prior Publication Data**
US 2018/0025141 A1 Jan. 25, 2018

Related U.S. Application Data
(60) Provisional application No. 62/366,285, filed on Jul. 25, 2016, provisional application No. 62/365,510, filed on Jul. 22, 2016.


(51) **Int. Cl.**
G06F 21/32 (2013.01)
H04L 29/06 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC **G06F 21/32** (2013.01); **G06K 9/00221** (2013.01); **G06K 9/00288** (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC G06F 21/32; G06K 9/00288; G06K 9/00221; G06N 99/005; G07C 9/00158; G07C 9/00166; H04L 63/0861
See application file for complete search history.

(57) **ABSTRACT**
A machine access control system and corresponding method are provided. The machine access control system includes a camera configured to capture an input image of a subject purported to be a person associated with operating a particular workplace machine. The machine access control system further includes a memory storing a deep learning model configured to perform multi-task learning for a pair of tasks including a liveness detection task and a face recognition task. The machine access control system also includes a processor configured to apply the deep learning model to the input image to recognize an identity of the subject in the input image regarding being authorized to use the particular workplace machine and a liveness of the subject. The liveness detection task is configured to evaluate a plurality of different distractor modalities corresponding to different physical spoofing materials to prevent face spoofing for the face recognition task.

20 Claims, 14 Drawing Sheets



- (51) **Int. Cl.** 2014/0016837 A1* 1/2014 Nechyba G06K 9/00228
G07C 9/00 (2006.01) 382/118
G06K 9/00 (2006.01) 2014/0177955 A1 6/2014 Srinivasan et al.
G06N 99/00 (2010.01) 2015/0188912 A1* 7/2015 Hoyos H04L 63/0823
726/10
- (52) **U.S. Cl.** 2016/0140405 A1 5/2016 Graumann et al.
CPC **G06N 99/005** (2013.01); **G07C 9/00158** 2016/0171198 A1* 6/2016 John Archibald G06F 21/32
(2013.01); **G07C 9/00166** (2013.01); **H04L** 726/19
63/0861 (2013.01)

OTHER PUBLICATIONS

(56) **References Cited**

U.S. PATENT DOCUMENTS

- 9,275,269 B1* 3/2016 Li G06K 9/00268
9,665,784 B2* 5/2017 Derakhshani G01S 7/539
2012/0008832 A1* 1/2012 Wang G06K 9/036
382/103

- Kim, et al., "Face Liveness Detection Based on Texture and Frequency Analysis", 5th IAPR International Conference on Biometrics (ICB), Mar. 2012, pp. 67-72.
Szegedy, et al., "Going Deeper with Convolutions", IEEE International Conference on Computer Vision and Pattern Recognition, Jun. 2015. pp. 1-9.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8





FIG. 9



1100 →





FIG. 11






FIG. 13




FIG. 14

PHYSICAL SYSTEM ACCESS CONTROL

RELATED APPLICATION INFORMATION

This application claims priority to U.S. Provisional Patent Application Ser. No. 62/365,510, filed on Jul. 22, 2016, incorporated herein by reference herein its entirety. This application claims priority to U.S. Provisional Patent Application Ser. No. 62/366,285, filed on Jul. 25, 2016, incorporated herein by reference herein its entirety. This application is related to an application entitled "Liveness Detection for Antispoof Face Recognition", having Ser. No. 15/637,264, and which is incorporated by reference herein in its entirety. This application is related to an application entitled "Camera System for Traffic Enforcement", having Ser. No. 15/637,368, and which is incorporated by reference herein in its entirety. This application is related to an application entitled "Security System for Facility Access Control", having Ser. No. 15/637,465, and which is incorporated by reference herein in its entirety. This application is related to an application entitled "Login Access Control for Secure/Private Data", having Ser. No. 15/637,644, and which is incorporated by reference herein in its entirety.

BACKGROUND

Technical Field

The present invention relates to security and more particularly to liveness detection for antispoof face recognition.

Description of the Related Art

Face recognition has been used to recognize individuals. However, current face recognition systems and approaches are often spoofed using inanimate objects. Thus, there is a need for an improvement to current face recognition systems and approaches that is capable of thwarting spoofing attempts.

SUMMARY

According to an aspect of the present invention, a machine access control system is provided. The machine access control system includes a camera configured to capture an input image of a subject purported to be a person associated with operating a particular workplace machine. The machine access control system further includes a memory storing a deep learning model configured to perform multi-task learning for a pair of tasks including a liveness detection task and a face recognition task. The machine access control system also includes a processor configured to apply the deep learning model to the input image to recognize an identity of the subject in the input image regarding being authorized to use the particular workplace machine and a liveness of the subject. The liveness detection task is configured to evaluate a plurality of different distractor modalities corresponding to different physical spoofing materials to prevent face spoofing for the face recognition task.

According to another aspect of the present invention, a computer-implemented method is provided for machine access control. The method includes capturing, by a camera, an input image of a subject purported to be a person associated with operating a particular workplace machine. The method further includes storing, in a memory, a deep learning model configured to perform multi-task learning for

a pair of tasks including a liveness detection task and a face recognition task. The method also includes applying, by a processor, the deep learning model to the input image to recognize an identity of the subject in the input image regarding being authorized to use the particular workplace machine and a liveness of the subject. The liveness detection task is configured to evaluate a plurality of different distractor modalities corresponding to different physical spoofing materials to prevent face spoofing for the face recognition task.

According to yet another aspect of the present invention, a computer program product is provided for machine access control. The computer program product includes a non-transitory computer readable storage medium having program instructions embodied therewith. The program instructions are executable by a computer to cause the computer to perform a method. The method includes capturing, by a camera, an input image of a subject purported to be a person associated with operating a particular workplace machine. The method further includes storing, in a memory, a deep learning model configured to perform multi-task learning for a pair of tasks including a liveness detection task and a face recognition task. The method also includes applying, by a processor, the deep learning model to the input image to recognize an identity of the subject in the input image regarding being authorized to use the particular workplace machine and a liveness of the subject. The liveness detection task is configured to evaluate a plurality of different distractor modalities corresponding to different physical spoofing materials to prevent face spoofing for the face recognition task.

These and other features and advantages will become apparent from the following detailed description of illustrative embodiments thereof, which is to be read in connection with the accompanying drawings.

BRIEF DESCRIPTION OF DRAWINGS

The disclosure will provide details in the following description of preferred embodiments with reference to the following figures wherein:

FIG. 1 shows an exemplary system for physical system access control, in accordance with an embodiment of the present invention;

FIG. 2 shows another exemplary system for liveness detection for antispoof face recognition, in accordance with an embodiment of the present principles;

FIG. 3 shows an exemplary processing system to which the invention principles may be applied, in accordance with an embodiment of the present invention;

FIG. 4 shows the live image recognition system of FIG. 2, in accordance with an embodiment of the present invention;

FIG. 5 shows an exemplary model architecture for the deep learning engine of FIG. 4, in accordance with an embodiment of the present invention;

FIG. 6 shows an inception structure of the inception layers of FIG. 5, in accordance with an embodiment of the present invention;

FIG. 7 shows a loss structure of the loss layers of FIG. 5, in accordance with an embodiment of the present invention;

FIGS. 8-10 show an exemplary method for liveness detection for face recognition, in accordance with an embodiment of the present invention;

FIG. 11 shows yet another exemplary system for traffic enforcement, in accordance with an embodiment of the present invention;

FIG. 12 shows yet another exemplary system for facility access control, in accordance with an embodiment of the present invention;

FIG. 13 shows yet another exemplary system for liveness detection for antispoof face recognition, in accordance with an embodiment of the present invention; and

FIG. 14 shows yet another exemplary system for login access control for secure/private data, in accordance with an embodiment of the present invention.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

The present invention is directed to liveness detection for antispoof face recognition.

The present invention advantageously distinguishes an image of a real face from that of a fake image using liveness detection. The fake image can be implemented, for example, by a high-quality three-dimensional (3D) mask, a paper print-out, an electronic display, or other “distractor” modality. The liveness detection supports face recognition to determine the authenticity of the input and can operate with various hardware. The present invention is hardware independent.

In an embodiment, a single image with purely appearance-based information can be used to distinguish an image of a real face from the image of a paper print-out of a face image. In an embodiment, one or more deep learning methods can be used that capture both local information (such as, for example, but not limited to, texture) as well as global information (such as, for example, but not limited to, shape and illumination) to provide a multi-task deep learning framework for liveness detection (e.g., using a single image).

In an embodiment, a deep network structure is set up to specialize from a generic image classification problem to the binary (alive or not alive) classification problem of liveness detection.

In an embodiment, a multi-task framework is constructed for the liveness detection task along with a large-scale face recognition task. This allows the network to learn better lower level features and improves its generalization ability.

In an embodiment, data augmentation methods are provided for training the deep learning architecture. The data augmentation methods improve detection performance in multiple scenarios.

In an embodiment, liveness detection in accordance with the present invention can be implemented on several platforms where face recognition is deployed such as, for example, but not limited to, vehicle electronic channels, automated authentication kiosks (Automated Teller Machines (ATMs), etc.), passenger electronic channels, mobile devices (such as, for example, but not limited to, cellphones and laptops), and so forth.

FIG. 1 shows an exemplary system 100 for physical system access control, in accordance with an embodiment of the present invention. The system 100 can be used to control access to a workplace machine.

The system 100 includes a camera system 110. While a single camera system 110 is shown in FIG. 1 for the sakes of illustration and brevity, it is to be appreciated that multiple camera systems can be also used, while maintaining the spirit of the present invention.

In the embodiment of FIG. 1, the camera system 110 is mounted on a mounting entity 160. For the sake of illustration, the mounting entity 160 involves a section of a wall (hereinafter “wall section”) 160 and a mounting bracket 161.

While a wall section 160 and a mounting bracket 161 are shown for the sake of illustration, any other mounting entity(ies) can be used, as readily appreciated by one of ordinary skill in the art given the teachings of the present invention provided herein, while maintaining the spirit of the present invention. For example, the camera system 110 can be mounted on a pole, and so forth. The preceding examples are merely illustrative. It is to be appreciated that multiple mounting entities can be located at control hubs and sent to a particular location as needed.

The camera system 110 can be a wireless camera system or can use one or more antennas included on the wall section 160 and/or the mounting bracket 161 (or other mounting entity (e.g., building, pole, drone, etc.) to which the camera system 110 is mounted or proximate).

The system 100 further includes a server 120 for liveness detection for antispoof face recognition for permitting workplace machine use. The server 120 can located remote from, or proximate to, the camera system 110. The server 120 includes a processor 121, a memory 122, and a wireless transceiver 123. The processor 121 and the memory 122 of the remote server 120 are configured to perform liveness detection for antispoof face recognition based on images received from the camera system 110 by the (the wireless transceiver 123 of) the remote server 120. To that end, the processor 121 and memory 122 can be configured to include components of a face recognition system and a live image recognition system. In this way, the face of a person 170 that is to operate a workplace machine 190 can be recognized and a liveness of the person 170 can also be determined. Here, liveness can be correlated to attentiveness, in that a sleeping person can be considered to lack liveness, therefore resulting in an alarm or other action being performed in order to prevent the inattentive employee from operating a workplace machine 190. The face recognition and liveness detection can be performed on multiple operators of multiple workplace machines 190.

Accordingly, some exemplary suitable environments to which the present invention can be applied can include any environments a person must be recognized in order to gain access to a workplace machine. Moreover, further exemplary suitable environments can include any environments where liveness detection can be used to augment a face recognition result for workplace machine use control.

FIG. 2 shows another exemplary system 200 for liveness detection for antispoof face recognition, in accordance with an embodiment of the present principles. System 200 can represent an implementation of system 100, in accordance with an embodiment of the present invention.

The system 200 includes a live image recognition system 220, a face recognition system 230, and a computer processing system 240.

The computer processing system 240 essentially controls the other systems of system 200, including the image recognition system 220 and the face recognition system 230.

The live image recognition system 220 recognizes live images. The image recognition system 220 can, for example, detect an image of a live object versus an image of an inanimate object that is used for spoofing.

The face recognition system 230 recognizes faces. According, the face recognition system 230 can also recognize individuals associated with recognized faces.

The computer processing system 240 performs functions relating, for example, but not limited to: (i) processing image recognition results; (ii) processing face recognition result (iii) performing one or more actions based on the image recognition results and/or the face recognition results.

The live image recognition system 220 and/or the face recognition system 230 and/or the computer processing system 240 can include a camera. For the sake of illustration, a separate camera 271 is shown. The camera 271 can capture images/video of the user. The images/video can then be processed by the computer processing system 240 and/or any of the systems under its control. In an embodiment, the camera 271 can be capable of capturing still and moving images. In an embodiment, the camera can acquire images in the visible and/or infra-red spectrum.

The live image recognition system 220 and/or the face recognition system 230 and/or the computer processing system 240 can include a display. For the sake of illustration, a separate display 272 is shown. The display 272 can show liveness detection (live image) information and/or face recognition information to the user or other personnel (e.g., security personnel). For example, the display 272 can indicate to a security guard that someone is attempting to spoof a face recognition system to allow the security guard to intervene.

The live image recognition system 220 and/or the face recognition system 230 and/or the computer processing system 240 can include a speaker. For the sake of illustration, a separate speaker 273 is shown. The speaker 273 can provide auditory guidance to the user (e.g., regarding face positioning, and so forth) and/or a local alert that someone is attempting to spoof the system in order to draw attention to that person.

In an embodiment, one or more of the elements of system 200 is implemented in the cloud using a cloud-based configuration.

In the embodiment shown in FIG. 2, the elements thereof are interconnected by a bus(es)/network(s) 201. However, in other embodiments, other types of connections can also be used. Moreover, in an embodiment, at least one of the elements of system 200 is processor-based.

Further, while one or more elements may be shown as separate elements, in other embodiments, these elements can be combined as one element. For example, while the camera 211 is shown as a separate entity from the face recognition system 230, in other embodiments the face recognition system 230 can include the camera, obviating the need for a separate camera. Also for example, while the live image recognition system 220 is shown as a separate entity from the face recognition system 230, in other embodiments the live image recognition system 220 can be included in the face recognition system. Additionally for example, while the live image recognition system 220, the face recognition system 230, and the computer processing system 240 are shown as separate entities, in other embodiments, the live image recognition system 220 and the face recognition system 230 can be included in the computer processing system 240. The converse is also applicable, where while one or more elements may be part of another element, in other embodiments, the one or more elements may be implemented as standalone elements.

Moreover, one or more elements of FIG. 2 can be implemented in a cloud configuration including, for example, in a distributed configuration.

Additionally, one or more elements in FIG. 2 may be implemented by a variety of devices, which include but are not limited to, Digital Signal Processing (DSP) circuits, programmable processors, Application Specific Integrated Circuits (ASICs), Field Programmable Gate Arrays (FPGAs), Complex Programmable Logic Devices (CPLDs), and so forth.

These and other variations of the elements of system 200 are readily determined by one of ordinary skill in the art, given the teachings of the present principles provided herein, while maintaining the spirit of the present principles.

FIG. 3 shows an exemplary processing system 300 to which the invention principles may be applied, in accordance with an embodiment of the present invention. The processing system 300 can be used, for example, to implement the server 120 of FIG. 1, the overall system 200 or the computer processing system 240 of FIG. 2.

The processing system 300 includes at least one processor (CPU) 304 operatively coupled to other components via a system bus 302. A cache 306, a Read Only Memory (ROM) 308, a Random Access Memory (RAM) 310, an input/output (I/O) adapter 320, a sound adapter 330, a network adapter 340, a user interface adapter 350, and a display adapter 360, are operatively coupled to the system bus 302.

A first storage device 322 and a second storage device 324 are operatively coupled to system bus 302 by the I/O adapter 320. The storage devices 322 and 324 can be any of a disk storage device (e.g., a magnetic or optical disk storage device), a solid state magnetic device, and so forth. The storage devices 322 and 324 can be the same type of storage device or different types of storage devices.

A speaker 332 is operatively coupled to system bus 302 by the sound adapter 330. A transceiver 342 is operatively coupled to system bus 302 by network adapter 340. A display device 362 is operatively coupled to system bus 302 by display adapter 360.

A first user input device 352, a second user input device 354, and a third user input device 356 are operatively coupled to system bus 302 by user interface adapter 350. The user input devices 352, 354, and 356 can be any of a keyboard, a mouse, a keypad, an image capture device, a motion sensing device, a microphone, a device incorporating the functionality of at least two of the preceding devices, and so forth. Of course, other types of input devices can also be used, while maintaining the spirit of the present invention. The user input devices 352, 354, and 356 can be the same type of user input device or different types of user input devices. The user input devices 352, 354, and 356 are used to input and output information to and from system 300.

Of course, the processing system 300 may also include other elements (not shown), as readily contemplated by one of skill in the art, as well as omit certain elements. For example, various other input devices and/or output devices can be included in processing system 300, depending upon the particular implementation of the same, as readily understood by one of ordinary skill in the art. For example, various types of wireless and/or wired input and/or output devices can be used. Moreover, additional processors, controllers, memories, and so forth, in various configurations can also be utilized as readily appreciated by one of ordinary skill in the art. These and other variations of the processing system 300 are readily contemplated by one of ordinary skill in the art given the teachings of the present invention provided herein.

FIG. 4 shows the live image recognition system 220 of FIG. 2, in accordance with an embodiment of the present invention.

The live image recognition system 220 includes a data collector 401, a data collector 402, a data collector 403, a deep learning engine 410, and application related data 420.

The data collector 401 is for collecting 3D mask data 401A for 3D masks that are used as potential inputs to a face recognition system.

The data collector **402** is for collecting printed paper data **402A** for printed papers that are used as potential inputs to a face recognition system.

The data collector **403** is for collecting electronic display data **403A** for electronic displays that are used as potential inputs to a face recognition system.

Regarding data collectors **401**, **402**, and **403**, 3D masks, 2D printed paper, electronic devices with displays, respectively, are used as spoofing material for face recognition. In an embodiment, a large variety of data samples, which are commonly used in various applications/scenarios, is collected. In an embodiment, the collected data is preferably provided by more than one person, e.g., wearing 3D masks with different accessories (such as, for example, but not limited to, wigs, scarf, glasses, and so forth). In an embodiment, the collected data preferably includes pictures taken using different cameras like Closed Circuit Television (CCTV) cameras, web cameras, mobile device cameras, industrial grade cameras, and so forth. The 2D printed paper and electronic devices also presented in front of the cameras to collect training data. In an embodiment, the collected data involves persons with different nationalities and different postures to collect diverse training data.

The deep learning based engine **410** includes a training portion **410A** and an architecture portion **410B**. The deep learning based engine **410** performs deep learning for liveness detection for face recognition.

Regarding the architecture portion **410B** of the deep learning based engine **410**, in an embodiment, a multi-task learning objective is set up to augment liveness detection with a large-scale face recognition task. In an embodiment, features at the lower layers in the deep learning architecture are shared between these two tasks.

Further regarding the architecture portion **410B** of the deep learning based engine **410**, in an embodiment, data augmentations in the form of chromatic transformations and image contrast enhancements can be used, in addition to spatial transformations.

Regarding the training portion **410A** of the deep learning based engine **410**, in an embodiment, training is achieved by fine tuning the GoogLeNet architecture on a multitask objective that jointly optimizes liveness detection and face recognition. This allows overcoming the challenge of limited data for liveness detection by using large-scale face recognition datasets.

Further regarding the architecture portion **410B** of the deep learning based engine **410**, the architecture differs from a standard GoogLeNet by setting up multi-task learning on top of the original structure, which improves the generalization ability of our model.

Further regarding the training portion **410A** of the deep learning based engine **410**, in an embodiment, all of the layers are frozen except for the last fully connected layer. Then the two tasks of liveness detection and face recognition are combined (jointly optimized) to conduct the multi-task training. During the multi-task training, all weights of the layers are unfrozen.

Regarding the deep learning based engine **410**, data preprocessing is achieved by applying face detection to the data (input images). Then, in an embodiment, the input images are normalized to 256 by 256. By further random central cropping, the final output to the network is 228 by 228. In order to increase the diversity of the training data and improve the model's ability of generalization, a data augmentation layer right after the image input. The image has a fifty percent probability to be horizontally flipped, zoomed, translated or rotated. Also, in an embodiment, an image

contrast enhancement is applied by randomly adding one or more Gaussian distributed instances to the original RGB value. Additionally, in an embodiment, another image contrast enhancement is applied by adding one or more Gaussian distributed instances to the HSV domain and multiplying some coefficients to further adjust the S and V.

The application related data **420** can include data relating to vehicle based applications **420A**, kiosk based applications **420B**, electronic channel based applications **420C**, mobile device based applications **420D**, and Personal Computer (PC) based applications **420E**. It is to be appreciated that the preceding applications are merely illustrative and, thus, the present invention can be applied to many other applications, as readily determined by one of ordinary skill in the art given the teachings of the present invention provided herein, while maintaining the spirit of the present invention.

Regarding vehicle based applications **420A**, the liveness detection engine can be implemented on a novel platform for vehicle automatic clearance channels, which can be used for automated authentication at highways, weighing stations and border control locations.

Regarding the kiosk based applications **420B**, the liveness detection engine can be implemented on a novel platform for automated authentication kiosks, which can be used for access control at airports and so forth.

Regarding the electronic channel based applications **420C**, the liveness detection engine can be implemented on a novel platform for passenger automatic clearance channels, which can be used for automated entry authentication into secure areas, such as immigration at airports or at border control locations.

Regarding the mobile device applications **420D**, the liveness detection engine can be implemented on mobile platforms such as cellphones and laptops, for supporting face recognition in secure access, mobile payments, banking and similar applications, and so forth.

Regarding the Personal Computer (PC) applications **420E**, the liveness detection engine can be implemented on PC platforms such as desktop and laptops, for supporting face recognition in secure access, mobile payments, banking and similar applications, and so forth.

FIG. 5 shows an exemplary model architecture **500** for the deep learning engine **410** of FIG. 4, in accordance with an embodiment of the present invention.

The model architecture **500** includes a convolutional max-pooling Local Response Normalization (LRN) layer **505**, a convolutional max-pooling Local Response Normalization (LRN) layer **510**, an inceptionx4 layer **515**, an inceptionx3 layer **520**, an inceptionby2 layer **525**, a Fully Connected (FC) layer **530**, a loss layer **535**, a FC layer **540**, a FC layer **545**, a loss layer **550**, and a loss layer **555**.

The convolutional max-pooling LRN layers **505** and **510** partition an input image into a set of non-overlapping rectangles and, for each such sub-region, outputs the maximum. The intuition is that the exact location of a feature is less important than its rough location relative to other features. The convolutional max-pooling LRN layers **505** and **510** serve to progressively reduce the spatial size of the representation, to reduce the number of parameters and amount of computation in the network, and hence to also control overfitting.

The convolution layer (e.g., layer **510**) takes in the original image as input and send output to the inception layers **515**, **520** and **525**, which further generates the output for the fully connected (FC) layer **535**, **540**, and **545**. The output of FC layers predict the classification label and

penalized by the loss layers **530**, **550**, and **555**, which conduct back-propagation for the whole structure to update.

The high-level reasoning in the neural network is performed using the FC layers **530**, **540**, and **545**. Neurons in a fully connected layer have full connections to all activations in the previous layer. Accordingly, their activations can be computed with a matrix multiplication followed by a bias offset.

The loss layers **535**, **550**, and **555** specify how training penalizes the deviation between the predicted and true labels. Various loss functions appropriate can be used, while maintaining the spirit of the present invention.

FIG. 6 shows an inception structure **600** of the inception layers **515**, **520**, and **525** of FIG. 5, in accordance with an embodiment of the present invention.

The inception structure **600** includes a depth concatenate element **601**, a convolutional 1×1 (Conv 1×1) element **611**, a convolutional 1×1 (Conv 1×1) element **612**, a Max pooling 3×3 element **613**, a convolutional 1×1 (Conv 1×1) element **621**, a convolutional 5×5 (Conv 5×5) element **622**, a convolutional 1×1 (Conv 1×1) element **623**, and a depth concatenate element **631**.

FIG. 7 shows a loss structure **700** of the loss layers **505** and **510** of FIG. 5, in accordance with an embodiment of the present invention.

The loss structure **700** includes a Fully Connected (FC) layer **701**, a liveness FC layer **711**, a face recognition FC layer **712**, a liveness penalty element **721**, and a face recognition penalty element **722**.

FIGS. 8-9 show an exemplary method **800** for liveness detection for face recognition, in accordance with an embodiment of the present invention. Steps **805** through **815** can be considered to correspond to a training stage **800A** of method **800**, while steps **820** through **825** can be considered to correspond to a recognition stage **800B** of method **800**, and step **830** can be considered to correspond to a post-recognition stage **800C**.

At step **805**, provide images of various types of spoofing materials used for spoofing a face recognition system. The various types of spoofing materials can include, for example, but are not limited to, images of 3D masks, images printed on paper, and images depicted on electronic displays.

At step **810**, perform data preprocessing on the images. The data preprocessing can involve, for example, but is not limited to, image contrast enhancements, normalization, cropping (e.g., random central cropping, etc.), data augmentation, and so forth.

In an embodiment, step **810** includes one or more of steps **810A**, **810B**, **810C**, and **810D**.

At step **810A**, apply an image contrast enhancement to the images by randomly adding one or more Gaussian distributed instances to an original RGB value in a RGB color space. The original image is changed to another image, which shows the variance in the RGB color space for each pixel. This changed image showing certain variance from the original input is served as the network input, which artificially increase the diversity of the input images.

At step **810B**, apply an image contrast enhancement to the images by adding one or more Gaussian distributed instances to a Hue, Saturation, and Value (HSV) domain (cylindrical—coordinate representations of the RGB color space) and multiply some Gaussian distributed coefficients to further adjust S and V (brightness). By doing so, The Hue, Saturation and Value (brightness) are changed to create sufficient diversity for the input of the network.

At step **810C**, normalize the image (e.g., regarding size or some other characteristic).

At step **810D**, perform cropping on the images. In an embodiment, random central cropping can be performed on the images.

At step **815**, train a liveness-based face recognition system using the images preprocessed by step **810** to form a deep learning based model. Step **815** can involve training the deep learning based engine.

In an embodiment, step **815** includes one or more of steps **815A** and **815B**.

At step **815A**, freeze all layers except for the last fully connected layer.

At step **815B**, perform multi-task training involving a liveness detection task and a face recognition task. In an embodiment, all of the weights of the layers can be unfrozen during the multi-task training.

At step **820**, receive an input image of a person to be recognized.

At step **825**, perform a multi-task operation jointly involving liveness detection and face recognition for a particular application, using the deep learning based model. The particular application can include, but is not limited to, a vehicle based application, a kiosk based application, an electronic channel based application, a mobile device application, and a personal computer application.

At step **830**, perform one or more actions based on a result of the multi-task operation. For example, the one or more actions can be directed to one or more of the following: identifying the person and also determining that the person is live; traffic enforcement; facility access control; physical system (e.g., workplace machine) access control; and login access control (e.g., to secure/private data).

In an embodiment, step **830** can include one or more of steps **830A** through **830E**.

At step **830A**, corresponding to identifying the person and also determining that the person is live, perform one or more actions that can include, but are not limited to, one or more of the following: permitting or blocking a purchase of an item; generating local and/or remote alarm; and so forth.

At step **830B**, corresponding to traffic enforcement, perform one or more actions that can include, but are not limited to, one or more of the following: forwarding the input image of the one or more subjects in the motor vehicle to a corresponding traffic enforcement authority, responsive to the motor vehicle committing a traffic violation; forwarding the input image, that depicts a particular one of the one or more subjects that is located in an operating location in the motor vehicle, to a corresponding traffic enforcement authority, responsive to a liveness determination of another one of the one or more subjects in the motor vehicle being determined as not live and a location of the motor vehicle being in a High Occupancy Vehicle (HOV) lane; forwarding the input image, that depicts a particular one of the one or more subjects that is located in an operating location in the motor vehicle and another one of the one or more subjects located in a non-operating position in the motor vehicle, to a corresponding traffic enforcement authority, responsive to a liveness determination of the other one of the one or more subjects being determined as not live and a location of the motor vehicle being in a HOV lane; forwarding an image of the vehicle operator (when a liveness of a passenger “object” has been determined to be “not live”); capturing a more expansive image of the user (who should be proximate to the spoofing object) in order to capture the users’ actual face (or license plate in the case of the user utilizing a fake passenger while driving in the HOV lane) and forwarding that expansive image to a corresponding traffic enforcement authority.

11

It is to be appreciated that the initially listed action can encompass the actions that follow.

At step **830C**, corresponding to facility access control, the one or more actions can include, but are not limited to, one or more of the following: permitting or restricting access to an object and/or a facility; locking a door or area to keep someone out or to keep someone in; generating local and/or remote alarm (e.g., indicative of a security breach of the facility); and so forth.

At step **830D**, corresponding to physical system (e.g., workplace machine) access control, the one or more actions can include, but are not limited to, one or more of the following: powering down or powering up the workplace machine (e.g., the controlled system, machine, and/or device or a portion thereof); locking or unlocking a physical or electronic lock that blocks operation of the workplace machine (e.g., the controlled system, machine, and/or device or a portion thereof); generating local and/or remote alarm (e.g., indicative of unauthorized attempted use of the workplace machine); and so forth.

At step **830E**, corresponding to login access control (e.g., to secure/private data), the one or more actions can include, but are not limited to, one or more of the following: permitting or restricting access (e.g., to secure/private data); generating local and/or remote alarm (e.g., indicative of unauthorized attempted access to, e.g., secure/private data); and so forth. Access restriction can be achieved using, for example, a switch or other physical element to prevent access to the secure data.

As is evident to one of ordinary skill in the art, the action(s) taken is(are) dependent upon the type of application to which the present invention is applied.

FIG. **11** shows yet another exemplary system **1100** for traffic enforcement, in accordance with an embodiment of the present invention.

The system **1100** includes a camera system **1110**. While a single camera system **1110** is shown in FIG. **11** for the sakes of illustration and brevity, it is to be appreciated that multiple camera systems can be also used, while maintaining the spirit of the present invention.

In the embodiment of FIG. **11**, the camera system **1110** is mounted on a mounting entity **1160**. For the sake of illustration, the mounting entity **1160** is a pole **1160**. The pole **1160** is also used to support a stop sign. Of course, a dedicated pole or other mounting entity could also be used. Thus, while a pole **1160** is shown for the sake of illustration, any other mounting entity can be used, as readily appreciated by one of ordinary skill in the art given the teachings of the present invention provided herein, while maintaining the spirit of the present invention. For example, the camera system **1110** can be mounted on a building, a drone, and so forth. The preceding examples are merely illustrative. It is to be appreciated that multiple mounting entities can be located at control hubs and sent to a particular location as needed.

The camera system **1110** can be a wireless camera system or can use one or more antennas included on the pole **1160** (or other mounting entity (e.g., building, drone, etc.) to which the camera system **1110** is mounted or proximate).

The system **1100** further includes a server **1120** for traffic enforcement. The server **1120** can be configured to perform traffic enforcement based on liveness detection for antispoof face recognition. The server **1120** can located remote from, or proximate to, the camera system **1110**. The server **1120** includes a processor **1121**, a memory **1122**, and a wireless transceiver **1123**. The processor **1121** and the memory **1122** of the remove server **1120** are configured to perform liveness detection for antispoof face recognition based on images

12

received from the camera system **1110** by the (the wireless transceiver **1123** of) the remote server **1120**. To that end, the processor **1121** and memory **1122** can be configured to include components of a face recognition system and a live image recognition system. In this way, the face of a person **1170** in a vehicle **1180** can be recognized and a liveness of the person **1170** can also be determined. Accordingly, a vehicle driver can be positively identified and associated with a traffic offense, while the state of liveness of a “passenger object” (false person such as, for example, a mannequin), if present, can also be identified and associated with a traffic offense (violation of the number of persons allowed in a High Occupancy Vehicle (HOV) lane) for the vehicle driver.

Accordingly, some exemplary suitable environments to which the present invention can be applied can include any environments a face recognition result can be associated with traffic enforcement. Moreover, further exemplary suitable environments can include any environments where liveness detection can be used to augment a face recognition result for traffic enforcement.

FIG. **12** shows yet another exemplary system **1200** for facility access control, in accordance with an embodiment of the present invention.

The system **1200** includes a camera system **1210**. While a single camera system **1210** is shown in FIG. **12** for the sakes of illustration and brevity, it is to be appreciated that multiple camera systems can be also used, while maintaining the spirit of the present invention.

In the embodiment of FIG. **12**, the camera system **1210** is mounted on a mounting entity **1260**. For the sake of illustration, the mounting entity **1260** is an arch structure **1260** having a controlled gate **1261**. The gate **1261** can be normally closed and then opened based on a recognition result regarding the person **1270** attempting to gain access to the facility. While an arch structure **1260** with a gate **1261** is shown for the sake of illustration, any other mounting entity can be used, as readily appreciated by one of ordinary skill in the art given the teachings of the present invention provided herein, while maintaining the spirit of the present invention. For example, the camera system **1210** can be mounted on a building, a pole, and so forth. The preceding examples are merely illustrative. It is to be appreciated that multiple mounting entities can be located at control hubs and sent to a particular location as needed.

The camera system **1210** can be a wireless camera system or can use one or more antennas included on the arch structure **1260** (or other mounting entity (e.g., building, drone, etc.) to which the camera system **1210** is mounted or proximate).

The system **1200** further includes a server **1220** for liveness detection for antispoof face recognition. The server **1220** can located remote from, or proximate to, the camera system **1210**. The server **1220** includes a processor **1221**, a memory **1222**, and a wireless transceiver **1223**. The processor **1221** and the memory **1222** of the remove server **1220** are configured to perform liveness detection for antispoof face recognition based on images received from the camera system **1210** by the (the wireless transceiver **1223** of) the remote server **1220**. To that end, the processor **1221** and memory **1222** can be configured to include components of a face recognition system and a live image recognition system. In this way, the face of a person **1270** in a vehicle **1280** can be recognized and a liveness of the person **1270** can also be determined for the purpose of facility access control. The face recognition and liveness detection can be performed on multiple vehicle occupants including the driver. Moreover,

13

persons walking up to the arch structure **1260** (i.e., without being in a vehicle) can also be recognized and so forth in accordance with the present invention.

Accordingly, some exemplary suitable environments to which the present invention can be applied can include any environments a person must be recognized in order to gain access to a facility. Moreover, further exemplary suitable environments can include any environments where liveness detection can be used to augment a face recognition result for facility access control.

FIG. **13** shows yet another exemplary system **1300** for liveness detection for antispooof face recognition, in accordance with an embodiment of the present invention.

The system **1300** includes a camera system **1310**. While a single camera system **1310** is shown in FIG. **13** for the sake of illustration and brevity, it is to be appreciated that multiple camera systems can be also used, while maintaining the spirit of the present invention.

In the embodiment of FIG. **13**, the camera system **1310** is mounted on a mounting entity **1360**. For the sake of illustration, the mounting entity **1360** is a pole **1360**. While a pole **1360** is shown for the sake of illustration, any other mounting entity can be used, as readily appreciated by one of ordinary skill in the art given the teachings of the present invention provided herein, while maintaining the spirit of the present invention. For example, the camera system **1310** can be mounted on a building, a drone, and so forth. The preceding examples are merely illustrative. It is to be appreciated that multiple mounting entities can be located at control hubs and sent to a particular location as needed.

The camera system **1310** can be a wireless camera system or can use one or more antennas included on the pole **1360** (or other mounting entity (e.g., building, drone, etc.) to which the camera system **1310** is mounted or proximate).

The system **1300** further includes a server **1320** for liveness detection for antispooof face recognition. The server **1320** can located remote from, or proximate to, the camera system **1310**. The server **1320** includes a processor **1321**, a memory **1322**, and a wireless transceiver **1323**. The processor **1321** and the memory **1322** of the remove server **1320** are configured to perform liveness detection for antispooof face recognition based on images received from the camera system **1310** by the (the wireless transceiver **1323** of) the remote server **1320**. To that end, the processor **1321** and memory **1322** can be configured to include components of a face recognition system and a live image recognition system. In this way, the face of a person **1370** in a vehicle **1380** can be recognized and a liveness of the person **1370** can also be determined.

Accordingly, some exemplary suitable environments to which the present invention can be applied can include any environments where liveness detection can be used to augment a face recognition result. For example, a mass transit hub or stop, a battlefield, and/or any place where potential causalities can occur and where liveness detection can be used to advantageously augment a face recognition result (e.g., in order to determine a number of injured, a number of non-injured, a ratio of injured versus non-injured, etc.).

FIG. **14** shows yet another exemplary system **1400** for login access control for secure/private data, in accordance with an embodiment of the present invention.

The system **1400** includes a camera system **1410**. While a single camera system **1410** is shown in FIG. **14** for the sake of illustration and brevity, it is to be appreciated that multiple camera systems can be also used, while maintaining the spirit of the present invention.

14

In the embodiment of FIG. **14**, the camera system **1410** is embodied in a laptop **1460**. Hence, the laptop can be considered a mounting entity for the camera system **1410**. While a laptop **1460** is shown for the sake of illustration, any other mounting entity(ies) can be used, as readily appreciated by one of ordinary skill in the art given the teachings of the present invention provided herein, while maintaining the spirit of the present invention. For example, the camera system **1410** can be mounted on a pole, and so forth. The preceding examples are merely illustrative. It is to be appreciated that multiple mounting entities can be located at control hubs and sent to a particular location as needed.

The camera system **1410** can communicate with the server **1420** using a wireless transceiver **1410A** of the laptop **1410**.

The system **1400** further includes a server **1420** for liveness detection for antispooof face recognition for controlled access to secure/private data on a server **1490**. The server **1420** can located remote from, or proximate to, the camera system **1410**. The server **1420** includes a processor **1421**, a memory **1422**, and a wireless transceiver **1423**. The processor **1421** and the memory **1422** of the remove server **1520** are configured to perform liveness detection for antispooof face recognition based on images received from the camera system **1410** by the (the wireless transceiver **1423** of) the remote server **1420**. To that end, the processor **1421** and memory **1422** can be configured to include components of a face recognition system and a live image recognition system. In this way, the face of a person **1470** that is to login to a network (e.g., network **1480**) or device (e.g., server **1490**) can be recognized and a liveness of the person **1470** can also be determined in order to control access to the secure/private data.

The system **1400** can be used to control access to the server **1490** through computer network **1480**. Access control is performed by the server **1420**. The elements shown relative to FIG. **14** are set forth for the sake of illustration. However, it is to be appreciated that the present invention can be applied to other network configurations and other operational environments as readily contemplated by one of ordinary skill in the art given the teachings of the present invention provided herein, while maintaining the spirit of the present invention.

A description will now be given of some of the many attendant advantages of the present invention, in accordance with one or more embodiments of the present invention.

In an embodiment, the present invention uses a single image, thus reducing complexity of the acquisition system compared to the prior art.

In an embodiment, the present invention achieves very high accuracy and negligible false alarms, thus providing a higher quality of the result than previous methods.

In an embodiment, a purely image-based system is used, thus reducing the cost of the system compared to using active sensors.

In an embodiment, the robustness of the present invention is higher than prior art solutions, since passive imaging is not sensitive to deployment configurations.

In an embodiment, the present invention can achieve very high generality, thus being capable of being used to support any application where face recognition is deployed. In an embodiment, no additional hardware is required, as the present invention can be incorporated into an existing face recognition system.

Embodiments described herein may be entirely hardware, entirely software or including both hardware and software elements. In a preferred embodiment, the present invention

is implemented in software, which includes but is not limited to firmware, resident software, microcode, etc.

Embodiments may include a computer program product accessible from a computer-usable or computer-readable medium providing program code for use by or in connection with a computer or any instruction execution system. A computer-usable or computer readable medium may include any apparatus that stores, communicates, propagates, or transports the program for use by or in connection with the instruction execution system, apparatus, or device. The medium can be magnetic, optical, electronic, electromagnetic, infrared, or semiconductor system (or apparatus or device) or a propagation medium. The medium may include a computer-readable storage medium such as a semiconductor or solid state memory, magnetic tape, a removable computer diskette, a random access memory (RAM), a read-only memory (ROM), a rigid magnetic disk and an optical disk, etc.

Each computer program may be tangibly stored in a machine-readable storage media or device (e.g., program memory or magnetic disk) readable by a general or special purpose programmable computer, for configuring and controlling operation of a computer when the storage media or device is read by the computer to perform the procedures described herein. The inventive system may also be considered to be embodied in a computer-readable storage medium, configured with a computer program, where the storage medium so configured causes a computer to operate in a specific and predefined manner to perform the functions described herein.

A data processing system suitable for storing and/or executing program code may include at least one processor coupled directly or indirectly to memory elements through a system bus. The memory elements can include local memory employed during actual execution of the program code, bulk storage, and cache memories which provide temporary storage of at least some program code to reduce the number of times code is retrieved from bulk storage during execution. Input/output or I/O devices (including but not limited to keyboards, displays, pointing devices, etc.) may be coupled to the system either directly or through intervening I/O controllers.

Network adapters may also be coupled to the system to enable the data processing system to become coupled to other data processing systems or remote printers or storage devices through intervening private or public networks. Modems, cable modem and Ethernet cards are just a few of the currently available types of network adapters.

The foregoing is to be understood as being in every respect illustrative and exemplary, but not restrictive, and the scope of the invention disclosed herein is not to be determined from the Detailed Description, but rather from the claims as interpreted according to the full breadth permitted by the patent laws. It is to be understood that the embodiments shown and described herein are only illustrative of the principles of the present invention and that those skilled in the art may implement various modifications without departing from the scope and spirit of the invention. Those skilled in the art could implement various other feature combinations without departing from the scope and spirit of the invention. Having thus described aspects of the invention, with the details and particularity required by the patent laws, what is claimed and desired protected by Letters Patent is set forth in the appended claims.

What is claimed is:

1. A machine access control system, comprising:
 - a camera configured to capture an input image of a subject purported to be a person associated with operating a particular workplace machine;
 - a memory storing a deep learning model configured to perform joint multi-task learning for a pair of tasks including a liveness detection task and a face recognition task; and
 - a processor configured to apply the deep learning model to the input image to recognize an identity of the subject in the input image regarding being authorized to use the particular workplace machine and a liveness of the subject, and wherein the liveness detection task is configured to evaluate a plurality of different distractor modalities corresponding to different physical spoofing materials to prevent face spoofing for the face recognition task.
2. The access control system of claim 1, wherein the processor is further configured to control a powered status of the workplace machine, responsive to results of the liveness detection task and the face recognition task, the powered status selectively being controlled to one of powered and unpowered.
3. The access control system of claim 1, wherein the processor is further configured to control a lock status of a physical or electronic lock that blocks operation of the workplace machine, responsive to results of the liveness detection task and the face recognition task, the lock status selectively being controlled to one of locked and unlocked.
4. The access control system of claim 1, wherein the processor is further configured to generate an alarm indicating an unauthorized attempted use of the workplace machine, responsive to results of the liveness detection task and the face recognition task.
5. The face recognition system of claim 1, wherein the different physical spoofing materials comprise a spoofing materials selected from the group consisting of a 3D mask, a printed image, and an electronic display.
6. The face recognition system of claim 1, wherein the processor is further configured to perform data preprocessing on the plurality of input images selected from the group consisting of image contrast enhancements, data augmentation, and cropping.
7. The face recognition system of claim 1, wherein the processor is further configured to apply an image contrast enhancement to at least one of the plurality of input images by randomly adding one or more Gaussian distributed instances to an original RGB value of the at least one of the plurality of images.
8. The face recognition system of claim 1, wherein the processor is further configured to apply an image contrast enhancement to at least one of the plurality of input images by adding one or more Gaussian distributed instances to a Hue, Saturation, and Value (HSV) domain and multiplying two or more coefficients in the HSV domain to further adjust the Saturation and the Value of the at least one of the plurality of input images.
9. The face recognition system of claim 1, wherein the processor is further configured to perform random central cropping on at least some of the plurality of input images.
10. The face recognition system of claim 1, wherein the processor is further configured to perform a data augmentation process on at least one of the plurality of input images to augment data in the images and increase a generality of the deep learning model to the different distractor modalities.

17

11. The face recognition system of claim 1, wherein the deep learning model is formed to include a plurality of layers, and the processor is further configured to train the deep learning model by freezing each of the plurality of layers except a last fully connected layer therein, and performing multi-task training by combining the liveness detection task and the face recognition task, wherein during the multi-task training, all weights of the plurality of layers are unfrozen.

12. The face recognition system of claim 1, wherein the deep learning model is formed using an inception structure configured to multiply an output of a convolution layer of the deep learning model with at least one of the plurality of input images to produce a new image having amplified extracted features relative to the at least one of the plurality of input images.

13. The face recognition system of claim 1, wherein the deep learning model is formed using a loss structure that includes a face liveness penalty and a face recognition penalty.

14. A computer-implemented method for machine access control, comprising:

capturing, by a camera, an input image of a subject purported to be a person associated with operating a particular workplace machine;

storing, in a memory, a deep learning model configured to perform joint multi-task learning for a pair of tasks including a liveness detection task and a face recognition task; and

applying, by a processor, the deep learning model to the input image to recognize an identity of the subject in the input image regarding being authorized to use the particular workplace machine and a liveness of the subject, and wherein the liveness detection task is configured to evaluate a plurality of different distractor modalities corresponding to different physical spoofing materials to prevent face spoofing for the face recognition task.

15. The computer-implemented method of claim 14, further comprising controlling a powered status of the workplace machine, responsive to results of the liveness detection task and the face recognition task, the powered status selectively being controlled to one of powered and unpowered.

18

16. The computer-implemented method of claim 14, further comprising controlling a lock status of a physical or electronic lock that blocks operation of the workplace machine, responsive to results of the liveness detection task and the face recognition task, the lock status selectively being controlled to one of locked and unlocked.

17. The computer-implemented method of claim 14, further comprising generating an alarm indicating an unauthorized attempted use of the workplace machine, responsive to results of the liveness detection task and the face recognition task.

18. The computer-implemented method of claim 14, wherein the different physical spoofing materials comprise a spoofing materials selected from the group consisting of a 3D mask, a printed image, and an electronic display.

19. The computer-implemented method of claim 14, wherein the processor is further configured to perform data preprocessing on the plurality of input images selected from the group consisting of image contrast enhancements, data augmentation, and cropping.

20. A computer program product for machine access control, the computer program product comprising a non-transitory computer readable storage medium having program instructions embodied therewith, the program instructions executable by a computer to cause the computer to perform a method comprising:

capturing, by a camera, an input image of a subject purported to be a person associated with operating a particular workplace machine;

storing, in a memory, a deep learning model configured to perform joint multi-task learning for a pair of tasks including a liveness detection task and a face recognition task; and

applying, by a processor, the deep learning model to the input image to recognize an identity of the subject in the input image regarding being authorized to use the particular workplace machine and a liveness of the subject, and wherein the liveness detection task is configured to evaluate a plurality of different distractor modalities corresponding to different physical spoofing materials to prevent face spoofing for the face recognition task.

* * * * *