



US009890651B2

(12) **United States Patent**
Heaven et al.

(10) **Patent No.:** **US 9,890,651 B2**

(45) **Date of Patent:** **Feb. 13, 2018**

(54) **BLADE OF A ROTARY FLOW MACHINE WITH A RADIAL STRIP SEAL**

(71) Applicant: **ALSTOM Technology Ltd**, Baden (CH)

(72) Inventors: **Sarah Heaven**, Warwickshire (GB); **Shyam Mavani**, Leicester (GB); **Jiwen Tao**, Rugby Warwickshire (GB); **Stacie Tibos**, Rugby Warwickshire (GB); **Vasileios Stefanis**, Niederrohrdorf (CH); **Sascha Justl**, Zürich (CH); **Rudolf Kellerer**, Waldshut-Tiengen (DE)

(73) Assignee: **ANSALDO ENERGIA SWITZERLAND AG**, Baden (CH)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 449 days.

(21) Appl. No.: **14/467,752**

(22) Filed: **Aug. 25, 2014**

(65) **Prior Publication Data**
US 2015/0064012 A1 Mar. 5, 2015

(30) **Foreign Application Priority Data**
Aug. 29, 2013 (EP) 13182178

(51) **Int. Cl.**
F01D 11/00 (2006.01)
F01D 5/30 (2006.01)

(52) **U.S. Cl.**
CPC **F01D 11/006** (2013.01); **F01D 5/30** (2013.01); **F01D 11/00** (2013.01); **F01D 11/005** (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC .. F01D 11/005; F01D 11/006; F05D 2240/57; F05D 2250/75; F05D 2240/81
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,975,114 A 8/1976 Kalkbrenner
4,523,890 A 6/1985 Thompson
(Continued)

FOREIGN PATENT DOCUMENTS

CN 101929357 A 12/2010
CN 102465718 A 5/2012
(Continued)

OTHER PUBLICATIONS

Office Action (First Office Action) dated Jan. 3, 2017, by the Chinese Patent Office in corresponding Chinese Patent Application No. 201410433623.8, and an English Translation of the Office Action. (17 pages).

(Continued)


Primary Examiner — Atif Chaudry

(74) *Attorney, Agent, or Firm* — Buchanan Ingersoll & Rooney PC

(57) **ABSTRACT**

The invention refers to a blade of a rotary flow machine including an airfoil having a suction surface and a pressure surface joining each other along a trailing and a leading edge. A radially outward directed airfoil tip and a radially inward directed end joining an inner platform connect the airfoil to a shank at a radial end of the airfoil and providing, at least one shank pocket radially encircled by an axially extending portion of the platform. At least one radially extending rim extends from the trailing edge side of the shank and has an essentially radially orientated first slot for receiving a seal. A mount extends radially inwardly from said shank pocket. The first slot has a first aperture on a shank surface orientated in an axial direction.

17 Claims, 6 Drawing Sheets



(52) **U.S. Cl.**
CPC *F05D 2240/57* (2013.01); *F05D 2240/81*
(2013.01); *F05D 2250/75* (2013.01)

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,086,329	A	7/2000	Tomita et al.	
6,561,764	B1	5/2003	Tiemann	
8,226,365	B2	7/2012	Roush et al.	
8,790,086	B2	7/2014	Honkomp et al.	
2010/0178173	A1*	7/2010	Charlton	F01D 11/006 416/248
2010/0272568	A1	10/2010	Roush et al.	
2012/0049467	A1	3/2012	Stewart et al.	
2012/0121423	A1	5/2012	Honkomp et al.	
2012/0237352	A1	9/2012	Boyer et al.	
2013/0094969	A1	4/2013	Amaral et al.	

FOREIGN PATENT DOCUMENTS

CN	103047015	A	4/2013
EP	2 584 151	A2	4/2013
GB	2 452 515	A	3/2009
WO	00/57031	A1	9/2000

OTHER PUBLICATIONS

Office Action (Communication) dated Mar. 3, 2017, by the European Patent Office in corresponding European Patent Application No. 14179109.5. (5 pages).

* cited by examiner





Fig. 1




Fig. 2




Fig. 3




Fig. 4





Fig. 5




Fig. 6

1

BLADE OF A ROTARY FLOW MACHINE WITH A RADIAL STRIP SEAL

CROSS-REFERENCE TO RELATED APPLICATIONS

This application claims priority to European application 13182178.7 filed Aug. 29, 2013, the contents of which are hereby incorporated in its entirety.

TECHNICAL FIELD

The invention concerns a blade of a rotating flow machine. The blade comprising, an airfoil having a suction surface and a pressure surface joined together along a trailing and a leading edge, a radially outwardly extending airfoil tip and a radially inward extending end joining an inner platform connecting the airfoil to a shank located at a radial end of the airfoil. The shank includes at least one shank pocket whose radially outwardly extending point is encircled by a portion of the platform that extends axially. At least one radially extending rim extends from the trailing edge side of the shank and has a radially orientated slot for receiving a seal. A mount extends radially inwardly from the shank pocket.

BACKGROUND

Blades of a rotary flow machine, such as a compressor unit or a turbine stage of a gas turbine arrangement, are typically circumferentially arranged on a plurality of axially ordered rotor wheels. The platforms of each blade delimit the working channel of the rotary flow machine, which in case of a turbine stage is the hot gas channel where hot gases emerging from an upstream combustor expand and convert kinetic energy into rotational mechanical energy. Highly-compressed air is typically extracted from the compressor unit of an axial turbine for the purpose of cooling turbine components, particularly those in the hot gas path downstream of the combustor. The cooling air is required to maintain the temperature of the turbine components at an acceptable level for operation, but comes at a cost to overall turbine efficiency and output. Therefore it is important to reduce any cooling flow leakage out of the turbine components.

The area between adjacent blades in a common blade row of a rotor wheel radially inward of the platforms of each blade is typically referred to as a shank pocket. Typically, cavities between rotating blades and axially adjacent stationary components axially forward and aft of each shank pocket operate at different pressures to enable a natural fluid flow from the higher pressure cavity to the lower pressure cavity through the gaps which are necessary for movement and expansion between adjacent rotating blades. Each of these gaps has a large leakage path for cooling flow to escape from the shank region of the blade. The cooling efficiency can also be impaired by ingress of hot gas from the hot gas path into the shank region.

Document EP 2 584 151 A2 discloses a sealing system for a turbine rotor blade having at least one shank pocket encircled radially outwardly by an axially extending portion of the platform. At least one radially directed rim extending from the trailing edge side of the shank has a radially orientated first slot for receiving a seal. The seal may be a strip seal comprising an arm portion and a hook portion wherein the arm and hook portions are shaped to mate with the slot such that the slot restrains the movement of the seal,

2

wherein size of the seal substantially prevents a cooling flow from leaking through the shank pocket. Further, it is disclosed that the strip like seal bordering the shank portion of a first and a second blade that has a width that substantially prevents a cooling flow from leaking through the shank pocket.

A further sealing arrangement for a turbine blade is disclosed in the document US 2012/0237352 A. The sealing arrangement comprises two circumferentially adjacent arranged blades on a rotor wheel having an enclosed essentially radially oriented groove. The groove has at least one radial seal pin having an essentially uniformly round cross-section.

SUMMARY

It is an object of the invention to provide an enhanced seal arrangement for constricting a leakage flow through a leakage gap between shanks of two adjacent circumferentially arranged blades of a rotary flow machine. A further objective is to simplify the assembling work required to introduce a seal in the slot between two neighboring shanks shall.

Inventively, a blade of a rotary flow machine comprises an air foil having a suction surface and a pressure surface joined together along a trailing and a leading edges, a radially outward directed airfoil tip and a radially inward directed end joining an inner platform that connects the airfoil to a shank at a radial end of the airfoil and further has at least one shank pocket encircled in the radially outward direction by an axially extending portion of the platform. At least one radially extending rim that extends from the trailing edge side of the shank has a radially orientated slot for receiving a seal and a mount that extends radially inwardly from said shank pocket. The blade is characterized by the shank has an aperture on the shank surface oriented in an axial direction.

The axially facing surface of the shank is freely accessible even in the mounted state, i.e. all blades are circumferentially assembled in the rotor wheel. The inventive idea establishes a basis for the possibility to insert a seal after at least two neighboring blades, preferably all blades, are assembled onto a rotor wheel by inserting mounts of each blade into correspondingly shaped recesses in the rotor wheel.

The subsequent introduction of the seals into the slots after complete installation of all blades simplifies installation and reduces installation time associated with the assembling work of a rotary flow machine.

In a preferred embodiment, the shank of each blade has a second slot having an aperture on an opposite surface to the rim. The second slot and aperture preferably are of the same size and shape as the slot and aperture in the at least one radially directed rim. In an assembled state, the shanks of two neighboring blades adjoin each other such that the slot and aperture in the at least one rim of one of the two adjoining blades aligns radially and axially with the second slot and aperture of the other blade. The aligned slots form a cavity with a radially oriented longitudinal extension that preferably has a rectangular cross-section having a circumferential orientation rectangular side that defines the width of the rectangular cavity. In this way both apertures complement each other so as to form a common access opening through which a strip-like seal may be received into the rectangular cavity after the blades are assembled.

Preferably, the strip-like seal received in the rectangular cavity is made of a heat resistant material, most preferable having a length and width which corresponds to the radial extension and width of the rectangular cavity respectively. In

3

other aspects, the shape and size of the seal corresponds to individual arrangements of the slots described in more detail in the following illustrated embodiments.

In all cases the aperture of the slot in the shank and the associated position of the access opening is radially arranged between the platform and the mount of the blade. Preferably, the aperture of the essentially radially oriented slots is arranged at the radially outer end of the slot, that is, the aperture is located radially close to the platform of the blade. This location makes it possible to easily insert the strip-like seal through the access opening of the already assembled blades.

After a seal is introduced into the rectangular cavity precaution must be taken to avoid the strip-like seal escaping through the access opening due to operational centrifugal and axial forces. To overcome this problem, in a preferred embodiment, the slot in the at least one radially directed rim is a grooved-shaped recess having a radially outward end bordered axially by a nose-like contour separating the radially outward end and the slot from the aperture.

The described new design for a radial sealing slot in a shank of a blade enables the insertion of a seal strip after assembly of blades around a rotor wheel. With reference to the accompanying drawings several different embodiments for realizing the slot and the strip seal are described.

An alternative inventive idea for inserting a seal in an essentially radially directed slot in the shank of a blade for reducing or diminishing leakage flow through a gap between the shanks of two adjacent blades to be assembled in one circumferentially row of a rotary wheel will now be described.

In contrast to the previously discussed seal arrangement which allows insertion of strip-like seals after a complete assembly of blade on a rotary wheel a further embodiment enables an easier way of loading the slot with a seal during blade assembly. Furthermore, this embodiment has accurate self-alignment of the seal within the slot bordered by the shanks of two neighboring blades.

In a known arrangement, a blade of a rotary flow machine comprises an airfoil having a suction and a pressure surfaces joining together along a trailing and a leading edge, a radially outward directed airfoil tip and a radially inward directed end joining an inner platform that connects the airfoil to a shank radially opposite airfoil having at least one shank pocket encircled radially outwardly by an axially extending portion of the platform and by at least one radially extending rim of the trailing edge side of the shank having a radially orientated first slot suitable for receiving a seal and a mount extending radially inward from the shank pocket having a second slot arranged on an opposite surface to the rim configured such that when assembling two blades in the circumferential direction of the rotary flow machine both slots form a common gap in which a seal is receivable prior to the assembly the two blades. The received seal is preferably sized to substantially prevent a leakage flow through the shank pocket. The blade is characterized in that one of the two slots has a groove-shaped recess with a width and a depth adapted to a width of a strip-like seal such that a hypotenuse of the width and depth of the groove-shaped recess is of the same size or greater than the width of the strip-like seal. The width of the strip-like seal on the other hand is greater or equal 50% of the length of the hypotenuse, preferably equal or greater than 70% of the length of the hypotenuse.

Due to the geometry and size adaptation between the groove-shaped recess and the strip-like seal it is possible to insert the strip-like seal completely into the groove-shaped

4

recess before assembling the two adjacent blades in circumferentially direction on a rotor wheel. In addition, because the strip-like seal resides completely inside the groove-shaped recess, it is possible to seamlessly join the two adjacent blades in circumferential direction. In order to ensure that the strip-like seal, which is received along the hypotenuse of the recess during assembly, performs the additional function of an axial facing cover for the gap between the shanks of the two adjacent blades, a tool is necessary to slip the strip-like seal from the starting position along the hypotenuse into the axial sealing position.

To facilitate the slipping and rotating motion of the strip-like seal from the position along the hypotenuse to the end position the groove-shaped recess has along its width a wedge-like contour with a flank portion inclined relative to the axial direction so that one side edge of the strip like seal can be slid along the flank while the strip-like seal is rotating around its length extension into the axial direction so as to seal the gap between the shanks of two adjacent blades to prevent a leakage flow through the shank pocket.

The flank of the wedge-like contour is located adjacent to a first limiting wall of the groove-shaped recess while the wedge-like contour limits a first gap with a second limiting wall located opposite to the first limiting wall. In an assembled configuration of the two blades in circumferentially direction the second slot has at least a second gap facing the first gap so that axial ends of the strip-like seal projects into both gaps simultaneously.

A further preferred embodiment has a helical contour along the radial direction of one limiting wall inside the groove-shaped recess such that the strip-like seal, which initially takes the position along the hypotenuse of the groove-shaped recess during assembling the blades, will turn itself without any tooling by means of centrifugal forces applied during the first commissioning. As will be described in more detail with a reference to the figures, the helical contour is provided only in a radial outward region along the groove-shaped recess. Further details of the invention can be derived from the following disclosure describing preferred embodiments shown in the figures.

BRIEF DESCRIPTION OF THE DRAWINGS

The invention shall now be explained in more detail based on exemplary embodiments in conjunction with the drawing. In the drawing

FIG. 1a to d first embodiment of an inventive blade according to a first inventive aspect,

FIG. 2a to c second embodiment of an inventive blade according to the first inventive aspect,

FIG. 3a to c first embodiment of an inventive blade according to the first inventive aspect,

FIG. 4a to d fourth embodiment of an inventive blade according to the first inventive aspect,

FIG. 5a, b1 to b3 first embodiment of an inventive blade concerning to the second inventive aspect, and

FIG. 6a to b second embodiment of an inventive blade concerning to the second inventive aspect.

DETAILED DESCRIPTION

FIG. 1 illustrates a first embodiment of a blade 1 of, for example, a moving low pressure turbine blade for a gas turbine arrangement. FIG. 1a shows a side view in the circumferential direction c of rotary flow machine (not shown) of the radially inner section of the blade 1. The axes shown in FIG. 1a mark the axial direction a, the radial

5

direction r and the circumferential direction c of the rotary flow machine. The further description makes reference to the axes defined in each illustration.

The blade **1** comprises an airfoil **2** having a suction surface **3** and a pressure surface (not shown) joined together along a leading edge **4** and trailing edge **5**. The radially inwardly extending end of the airfoil **2** joins an inner platform **6** connecting the airfoil **2** to a shank **7** at a radial end of airfoil **2**. The shank **7** has at least one shank pocket **8** which is defined as an area recessed in the shank **7** that is radially encircled by an axially a portion of the platform **6** and by at least one radially directed rim **9** that extends from the trailing edge **5** side of the shank **7**. The shank **7** has a slot **10**, as shown in FIG. **1b**, orientated radially r for receiving a seal **11** essentially in the axial direction a . The blade **1** further comprises a mount **12** extending radially inward from the shank pocket **8** for fixing the blade **1** into a counter-contoured recess in a rotor-wheel of the rotary flow machine.

Embodiments of the seal arrangement will be further description with reference to I FIGS. **1a** to **1d**. FIG. **1c** is an enlarged view of the section of FIG. **1a** enclosed by a dashed line. FIG. **1d** shows an enlarged view of the section FIG. **1c** enclosed by a dashed line

FIG. **1c** shows a slot **10** configured as a wedge-like grooved-shaped recess with an axial recess width becoming narrower towards the radially inward direction. The slot **10** has an aperture **13** which merges at a shank surface **14** oriented to face an axial direction a . The aperture **13** is connected to the slot **10** such that a seal **11**, preferably in form of a rectangular strip-like metal seal, as shown in FIG. **1b**, can be inserted through the aperture **13** into the slot **10**. The length of the seal **11** corresponds to the length of the slot **10**. The slot **10** has a longitudinal axis **15** which is incline to the radial direction r by an angle β in the range of $100^\circ \leq \beta \leq 170^\circ$ preferably $130^\circ \leq \beta \leq 150^\circ$. Due to the inclination of the slot **10** the seal **11**, which is inserted into the slot **10**, is pressed against the radial outward surface **16** of the slot **10** by centrifugal forces **17** acting onto the seal **11** during rotation around an axis of rotation of the rotary flow machine. Due to the effect of centrifugal forces **17** onto the seal **11** the seal **11** is ressed in a gastight manner against the surface **16** countering pressure in the shank pocket **8** acting onto the seal **11**.

To avoid an uncontrolled escape of the seal **11** out of the slot **10** through the aperture **13** the slot has at its radially outward end a nose-like contour **18** which separates the radially outward end **19** of the slot **10** from the aperture **13** in the axial direction. In FIG. **1d** it is illustrated clearly that the seal **11** is secured in the radially outward end **19** of the slot **10** by the nose-like contour **18**.

The blade **1** has an opposed side in circumferential direction c to the represented side shown in FIG. **1a** to **d**. At this opposed side the shank **7** has a second slot with an aperture which is a mirror image of the slot and aperture in the rim **9**, so that when assembling two blades in circumferential direction c of the rotary flow machine both slots enclose a common gap and form a common aperture through which the seal **11** can be received wherein the seal is sized to prevent a leakage flow through the shank pocket **8**. FIG. **1b** shows an inserted seal into the slot **10**. The circumferentially c protruding part of the seal **11** extends over the slot **10** into the second slot of a blade assembled adjacent to the blade shown in FIG. **1b**.

In the following description previously referenced reference numbers will be discussed without repeated explanation.

6

FIG. **2a** is a perspective view of the shank portion **7** of a blade that is comparable to the embodiment shown in FIG. **1c**. Slot **10** has a wedge-like grooved-shaped recess that narrower in the radially inward direction r . The slot **10** is connected to an aperture **13** in the region of the radial outward directed end of the slot **10**. In contrast to the embodiment shown in FIG. **1c** the longitudinal axis **15** of the slot **10** is inclined to the radial direction r by an angle β greater than in case of FIG. **1c**. By this means it is possible to configure rim **9** with a smaller axial width than for the configuration shown in FIG. **1c**. Further to ensure that the seal **11** contacts the radial outward surface **16** of the slot **10** the seal **11**, which is a metal strip, has at its radially inner end an overfold feature **20** that is compressed at the radially inner end of the slot **10** such that the seal **11** is forced against the surface **16**. It is further expected that after the rotary flow machines starts up, due to the centrifugal forces **17**, the seal **11** will move to the radially outer end **19**, marked by a ring in FIG. **2b**.

FIG. **3a** to **c** show a third preferred embodiment in which a radial seal is introduced into a slot **10** formed after blades are assembled on a rotary wheel. Here the slot **10** has a contoured grooved-shaped recess adapted for a clasped-like seal **11**. The slot **10** comprises a bent strip having two close together strip ends **11'**, **11''** at the radially outward end **19** of the slot **10** and a curved bent section **21** at the radially inward extending end of the slot **10**.

The curved bent section **21** of the seal **11** pushes the clasped-like seal **11** against the inner axial surfaces of the contoured grooved-shaped recess of the slot **10**. This can be seen in FIG. **3a** to **c**. The contoured grooved-shaped recess further has a longitudinal axis **15** which is slightly inclined to the radial direction r so that the upper strip end **11''**, which does not fit tightly at the radially outward surface **16** of the slot **10** as can be seen in FIG. **3a**, can move into a sealing location shown in FIG. **3b** as a result of centrifugal forces **17** generated during operation of the rotary flow machine. In addition a nose-like contour **18** prevents the strip end **11''** moving through the aperture **13** when the rotary flow machine is in stand still mode.

FIG. **4a** to **d** shows a fourth embodiment of a blade having a radially slot with an aperture formed after blade assembled in a rotary wheel for receiving a seal. The section of the shank **7** shown in FIG. **4a** has a rim **9** which is very small in axial direction and a slot **10** that forms an essentially rectangular grooved recess having a longitudinal axis **15** that is aligned radially without any inclination towards the radial direction r . The slot **10** has at its radially outer end an introduction slot **22** connecting the aperture **13** with the slot **10**. The introduction slot **22** has an axis **23** which intersects the axis **15** of the slot **10** at an angle α in the range of $120^\circ \leq \alpha \leq 150^\circ$, preferably $125^\circ \leq \alpha \leq 140^\circ$, most preferably $\alpha = 131^\circ$.

FIG. **4a**, **b** show an embodiment of a rectangular slot **1** that is suitable for the receiving a specially designed seal arrangement shown in FIGS. **4c** and **d**. The specially designed **11** consists of a multiple strip design that a smaller groove angle α of insertion of the seal through the aperture **13** into the slot **10**. A preferred multiple strip design shown in FIG. **4c** has three strip-like seals **11.1**, **11.2**, **11.3** spot welded together at one common end so that the three strip-like seals form a fan-shaped as shown in FIG. **4c**. In a preferred embodiment one of the three strip-like seals has a greater thickness than the two others, for example a first strip-like seal **11.3** has a thickness of 0.5 mm while the other two **11.1**, **11.2** have a thickness of 0.2 mm. A thicker strip

7

seal has the advantage of avoid buckling while a thinner strip has increased resilience to plastic deformation when bend during assembly.

FIG. 4 *d* shows another embodiment of a strip-like seal **11** also having three strip-like seals **11.1**, **11.2**, **11.3** joined at a common end so that the strip-like seals form a fan-shaped. As shown in FIG. 4*b* one of the strip-like seals **11.1** extends to form a lip **24** for locating the seal arrangement safely in the slot **10**.

The blades shown in the FIG. 1 to 4 commonly has an aperture **13** formed after blade assembly through which a strip-like seal or a multi strip design is receivable into a freely accessible surface oriented to face in an axial direction of the rotary flow machine. The blades shown in the FIGS. 5 and 6 have a slot that extends in the radial direction. The slot is configured to enable the insertion of a seal during assembly work without hindering or impeding the assembly work.

FIG. 5*a* shows a perspective view of a blade **1** without an airfoil that would otherwise extend radially beyond the platform **6** from where cooling openings **25** are arranged.

The shank pocket **8** of the blade **1** is radially encircled by both a portion of the platform **6** that extends axially and by at least one radially directed rim **9** extending from the trailing edge side of the shank **7**. The rim **9** includes a radially oriented slot **10** for inserting a seal. In contrast to the before described embodiments the slot **10** does not have an access aperture for insertion the seal into the slot. Instead, the slot **10** is completely embedded into the rim **9** while having a single circumferentially oriented *c* opening on one side.

FIGS. 5 *b1* to *b3* show a cross-section of the slot **10**. In FIG. 5 *b1* the illustrated upper cross-section shows a slot **10** in the rim **9** of a first blade **1.1** that borders a gap **26** formed in the circumferential direction *c* by a second blade **1.2** that is arranged adjacent to the first blade **1.1** in the circumferential direction of a rotary wheel (not shown).

The slot **10** of the first blade **1.1** has a rectangular cross-section (see dashed line) having a slot width *w* and a slot depth *d*. According to the rectangular geometry of the slot **10** the slot **10** has a hypotenuse *h* wherein $w^2+d^2=h^2$.

In addition, the strip-like seal **11** has a rectangular cross-section having a seal width *ws* equal or less than the length of the hypotenuse *h* but equal or greater than 50% but preferably equal or greater than 70% of the length of the hypotenuse *h*. With the aforementioned mentioned geometrical requirements, it is possible to place the seal **11** inside the slot **10** so that the seal **11** does not project beyond the slot **10** in circumferential direction *c* as shown in FIG. 5 *b1*. Here the seal **11** takes a position along the hypotenuse *h* of the slot **10**. In this position, it is possible to place an adjacent second blade onto the rotor wheel without disturbing with the seal **11** located inside the slot **10**.

After assembling two adjoining blades onto the rotary wheel the strip-like seal **11** has to be moved into a sealing position so as to close the an axial gap **26** axially, as shown in FIG. 5 *b3*. To facilitate the movement of the strip-like seal **11**, slot **10** has along its width, i.e. in an axial direction, a wedge-like contour **27** with a flank **28** inclined relative to the axial direction *a*. In addition, the flank **28** is located adjacent to a first limiting wall **29** of the slot **10**. In this arrangement, the wedge-like contour **27** further limits a first gap **30** with a second limiting wall **31** located facing, in the axial direction, the first limiting wall **29** of the slot. Additionally, the second blade **1.2**, as it is arranged circumferentially to the first blade in the assembled configuration, it has a second gap **32** that faces the first gap **30**.

8

To move the strip-like seal **11** from the position shown in FIG. 5 *b1* to the axial sealing position shown in FIG. 5 *b3* a tool is necessary to slide an end of the strip-like seal **11** along the flank **28** in axial direction whereby the sliding causes the other end of the strip-like seal **11** to enter the second gap **32** of the second blade **1.2**. In the position shown in FIG. 5 *b2*, the strip-like seal **11** has to be pushed using axial force to move from the position **P1** shown in FIG. 5 *b2* to position **P2**, i.e. so that the strip-like seal **11** is axially inside the first and second gap **30**, **32** of the first and second blade **1.1**, **1.2**.

FIG. 6*a*, *b* shows an alternative embodiment of a blade having a radially directed slot **10** having a cross-section that enable the movement of the strip-like seal into the slot **10** after positioning the strip-like seal **10** along the hypotenuse *h* of the cross-section of the slot. In of FIG. 6*a* the slot **10** is extends radially *r* and has a radially inward end having a triangle cross-section that has a depth *d*, a width *w* and a hypotenuse *h*. The slot **10** further has a radially outward end having a cross-section in which the hypotenuse *h* forms a convex contour **33**. There is a transition along the radial height of the slot **10** from a straight hypotenuse *h* at one end of the slot **10** to a convex contoured **33** hypotenuse *h* resulting in a surface of the slot **10** forming a helical contour **34**. FIG. 6*a* shows the strip-like seal **11** located in the slot **10** before the assembly of an adjoining blade into the rotary wheel in circumferential direction. FIG. 6*b* shows the location of strip-like seal **11** in its axial sealing position. The transition from the seal location shown in FIG. 6*a* and the seal location shown in FIG. 6*b* is achieved by centrifugal forces **17** acting onto the strip-like seal **11** during operation of the rotary wheel wherein centrifugal forces move the strip-like seal in a radial direction resulting in a twisting of the strip-like seal as a result of the helical groove-shaped contour **34** of the slot **10** as it is forced up the slot **10**.

The invention claimed is:

1. A blade of a rotary flow machine comprising:

- an airfoil having a suction surface and a pressure surface joined to each other along a trailing and a leading edge;
- a radially outward directed airfoil tip;
- a radially inward directed end joining an inner platform connecting the airfoil to a shank at a radial end of the airfoil;
- at least one shank pocket radially encircled by an axially extending portion of the platform and at least one radially extending rim that extends from the trailing edge side of the shank and has a first slot oriented longitudinally in an essentially radial direction of the rotary flow machine, the first slot configured for receiving a seal; and
- a mount extending radially inwardly from said shank pocket, wherein said first slot has a first aperture, on a shank surface, oriented in an axial direction.

2. The blade of claim 1, wherein the shank includes a second slot having a second aperture on the rim facing axially away from the first aperture of the first slot, wherein the first slot and the second slot are configured and arranged such that when two blades are assembled adjacent to each other the first slot and the second slot form, in circumferential direction of the rotary flow machine, a common gap having a common aperture formed by the first aperture and the second aperture, for receiving a seal for substantially preventing a leakage flow through the shank pocket.

3. The blade according to claim 2, wherein the second slot is a same size and shape as the first slot.

4. The blade according to claim 1, wherein the first aperture is radially between the platform and the mount.

9

5. The blade according to claim 1, wherein the first aperture is arranged at one end of the radially oriented first slot, and said one end is a radially outer end of the slot.

6. The blade according to claim 1, wherein the first slot is a grooved-shaped recess in the at least one radially extending rim and has a radially outward end which is bordered axially by a nose-like contour separating a radially outward end of the first slot from the first aperture.

7. The blade according to claim 1, wherein the first slot is a wedge-like grooved-shaped recess that narrows in a radially inward direction.

8. The blade according to claim 7, wherein the first slot has an inserted strip-like seal having an overfold feature at a radially inward extending end.

9. The blade according to claim 7, wherein the first slot has a longitudinal axis inclined in a radial direction by an angle β in a range of $100^\circ < \beta < 170^\circ$.

10. The blade according to claim 7, wherein the first slot has a longitudinal axis inclined in a radial direction by an angle β in a range of $130^\circ < \beta < 150^\circ$.

11. The blade according to claim 1, wherein the first slot has a contoured grooved-shaped recess and a clasp-like seal received in the contoured grooved-shaped recess, wherein the clasp-like seal comprises:

a bended strip having two strip ends, the contoured grooved-shaped recess and the clasp-like seal being configured close together at the radially outward end of the first slot and with a curved bended section at the radially inward directed end of the slot.

12. The blade according to claim 1, wherein the first slot has a radially aligned slot axis, and an introduction slot connects the first aperture to the first slot, with an axis of the introduction slot intersecting the slot axis at an angle α in a range of $120^\circ < \alpha < 150^\circ$.

10

13. The blade according to claim 12, comprising:
a seal in the first slot, wherein the seal is a multiple strip seal having at least two strip-like seals connected at one end of the seals.

14. The blade of claim 1, wherein the rotary flow machine is a compressor and/or a turbine stage of a gas turbine arrangement.

15. The blade of claim 14 wherein the blade is a compressor blade or turbine blade.

16. The blade according to claim 1, wherein the first slot has a radially aligned slot axis, and an introduction slot connects the first aperture to the first slot, with an axis of the introduction slot intersecting the slot axis at an angle α in a range of $125^\circ < \alpha < 140^\circ$.

17. A blade of a rotary flow machine comprising:
an airfoil having a suction surface and a pressure surface joined to each other along a trailing and a leading edge;
a radially outward directed airfoil tip;
a radially inward directed end joining an inner platform connecting the airfoil to a shank at a radial end of the airfoil;

at least one shank pocket radially encircled by an axially extending portion of the platform and at least one radially extending rim that extends from the trailing edge side of the shank and has an essentially radially orientated first slot for receiving a seal; and

a mount extending radially inwardly from said shank pocket, wherein said first slot has a first aperture, on a shank surface, oriented in an axial direction;

wherein the first aperture is arranged at one end of the radially oriented first slot, and said one end is a radially outer end of the slot.

* * * * *