



US009841602B2

(12) **United States Patent**
Osterhout et al.

(10) **Patent No.:** **US 9,841,602 B2**
(45) **Date of Patent:** ***Dec. 12, 2017**

(54) **LOCATION INDICATING AVATAR IN HEAD WORN COMPUTING**

(71) Applicant: **Osterhout Group, Inc.**, San Francisco, CA (US)

(72) Inventors: **Ralph F. Osterhout**, San Francisco, CA (US); **John N. Border**, Eaton, NH (US)

(73) Assignee: **Osterhout Group, Inc.**, San Francisco, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **14/950,523**

(22) Filed: **Nov. 24, 2015**

(65) **Prior Publication Data**

US 2016/0077342 A1 Mar. 17, 2016

Related U.S. Application Data

(63) Continuation of application No. 14/178,047, filed on Feb. 11, 2014, now Pat. No. 9,229,233.

(51) **Int. Cl.**
G02B 27/01 (2006.01)
G06T 11/00 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC **G02B 27/0172** (2013.01); **G02B 27/017** (2013.01); **G06F 3/011** (2013.01);
(Continued)

(58) **Field of Classification Search**
None
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,897,833 A 2/1933 Benway
2,064,604 A 12/1936 Hempel
(Continued)

FOREIGN PATENT DOCUMENTS

CN 104977785 A 10/2015
EP 368898 A1 5/1990
(Continued)

OTHER PUBLICATIONS

US 8,743,465, 06/2014, Totani et al. (withdrawn)
(Continued)


Primary Examiner — Nicholas Lee

(74) *Attorney, Agent, or Firm* — GTC Law Group PC & Affiliates

(57) **ABSTRACT**

Aspects of the present disclosure relate to visual presentation techniques for indicating a location in a head-worn computer using an avatar. A method may include receiving a location indicative of a human presence at a location in an obscured environment, establishing a virtual location marker in a position that is visually available to a person wearing a head-worn computing system, wherein the virtual marker provides an indication of the location in the obscured environment, and generating an avatar as a representation of the human presence and presenting the avatar in a field of view of the head-worn computing system, wherein the presentation of the avatar is positioned in the field of view by visually associating the avatar with the location marker such that the avatar appears to remain at the location marker location, as perceived by a person wearing the head-worn computing system, independent of the head-worn computing system's viewing angle.

7 Claims, 46 Drawing Sheets



- (51) **Int. Cl.**
G06T 11/60 (2006.01)
G06F 3/01 (2006.01)
G06F 3/0354 (2013.01)
- (52) **U.S. Cl.**
 CPC **G06F 3/012** (2013.01); **G06F 3/013**
 (2013.01); **G06F 3/03542** (2013.01); **G06F**
3/03545 (2013.01); **G06T 11/001** (2013.01);
G06T 11/60 (2013.01); **G02B 2027/0178**
 (2013.01); **G06T 2210/61** (2013.01)

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,305,294 A 2/1967 Alvarez
 3,531,190 A 9/1970 Leblanc
 3,671,111 A 6/1972 Okner
 4,034,401 A 7/1977 Mann et al.
 4,145,125 A 3/1979 Chika
 4,668,155 A 5/1987 Kaufmann et al.
 4,788,535 A 11/1988 Chikara et al.
 4,811,739 A 3/1989 Silver et al.
 4,852,988 A 8/1989 Velez et al.
 4,928,301 A 5/1990 Smoot et al.
 D327,674 S 7/1992 Kuo
 5,151,722 A 9/1992 Massof et al.
 5,257,094 A 10/1993 LaRussa et al.
 D352,930 S 11/1994 Tsuji
 5,483,307 A 1/1996 Anderson
 D375,748 S 11/1996 Hartman
 D376,790 S 12/1996 Goulet et al.
 5,596,451 A 1/1997 Handschy et al.
 5,621,424 A 4/1997 Shimada et al.
 5,699,057 A 12/1997 Ikeda et al.
 5,699,194 A 12/1997 Takahashi
 5,717,422 A 2/1998 Fergason et al.
 D392,959 S 3/1998 Edwards
 5,729,242 A 3/1998 Margerum et al.
 5,767,841 A 6/1998 Hartman
 5,788,195 A 8/1998 Rice
 5,808,589 A 9/1998 Fergason
 5,808,800 A 9/1998 Handschy et al.
 5,808,802 A 9/1998 Hur
 D410,638 S 6/1999 Sheehan et al.
 5,914,818 A 6/1999 Tejada et al.
 5,949,583 A 9/1999 Rallison et al.
 5,991,084 A 11/1999 Hildebrand et al.
 6,028,608 A 2/2000 Jenkins
 6,034,653 A 3/2000 Robertson et al.
 6,046,712 A 4/2000 Beller et al.
 6,147,805 A 11/2000 Fergason
 6,160,552 A 12/2000 Wilsher et al.
 6,160,666 A 12/2000 Rallinson et al.
 6,195,136 B1 2/2001 Handschy et al.
 6,204,974 B1 3/2001 Spitzer
 6,222,677 B1 4/2001 Budd
 6,297,749 B1 10/2001 Smith et al.
 D451,892 S 12/2001 Carrere
 6,347,764 B1 2/2002 Brandon et al.
 6,359,723 B1 3/2002 Handschy et al.
 6,369,952 B1 4/2002 Rallison et al.
 6,379,009 B1 4/2002 Fergason
 6,384,982 B1 5/2002 Spitzer
 6,392,656 B1 5/2002 Someya et al.
 D460,071 S 7/2002 Sheehan et al.
 6,433,760 B1 8/2002 Vaissie et al.
 6,456,438 B1 9/2002 Lee et al.
 6,461,000 B1 10/2002 Magarill
 6,478,429 B1 11/2002 Aritake et al.
 6,480,174 B1 11/2002 Kaufmann et al.
 6,491,389 B2 12/2002 Yaguchi et al.
 D470,144 S 2/2003 Li
 6,535,182 B2 3/2003 Stanton
 D473,871 S 4/2003 Santos
 6,563,626 B1 5/2003 Iwasaki et al.
 D478,052 S 8/2003 Thomas

6,642,945 B1 11/2003 Sharpe et al.
 6,675,030 B2 1/2004 Ciurczak et al.
 6,747,611 B1 6/2004 Budd et al.
 6,771,294 B1 8/2004 Pulli et al.
 6,795,041 B2 9/2004 Ogawa et al.
 6,847,336 B1 1/2005 Lemelson et al.
 6,906,836 B2 6/2005 Parker et al.
 D512,027 S 11/2005 Sarasjoki et al.
 D513,233 S 12/2005 Stauffer
 6,987,787 B1 1/2006 Mick
 D514,525 S 2/2006 Stauffer
 7,003,308 B1 2/2006 Fuoss et al.
 7,016,116 B2 3/2006 Dolgoff et al.
 7,030,925 B1 4/2006 Tsunekawa et al.
 D521,493 S 5/2006 Wai
 7,088,234 B2 8/2006 Naito et al.
 D529,467 S 10/2006 Rose
 D541,226 S 4/2007 Wakisaka et al.
 7,199,934 B2 4/2007 Yamasaki
 7,206,134 B2 4/2007 Weissman et al.
 D559,793 S 1/2008 Fan
 D571,816 S 6/2008 Corcoran et al.
 7,380,936 B2 6/2008 Howell et al.
 7,401,918 B2 7/2008 Howell et al.
 7,414,791 B2 8/2008 Urakawa et al.
 7,417,617 B2 8/2008 Eichenlaub
 7,457,040 B2 11/2008 Amitai
 7,481,531 B2 1/2009 Howell et al.
 7,500,747 B2 3/2009 Howell et al.
 7,522,344 B1 4/2009 Curatu et al.
 7,542,210 B2 6/2009 Chirieleison et al.
 7,543,943 B1 6/2009 Hubby et al.
 7,646,540 B2 1/2010 Dolgoff et al.
 7,677,723 B2 3/2010 Howell et al.
 7,690,799 B2 4/2010 Nestorovic et al.
 7,728,799 B2 6/2010 Kerr et al.
 7,733,571 B1 6/2010 Li
 7,771,046 B2 8/2010 Howell et al.
 7,777,690 B2 8/2010 Winsor et al.
 7,777,723 B2 8/2010 Namiki et al.
 7,777,960 B2 8/2010 Freeman
 7,792,552 B2 9/2010 Thomas et al.
 7,806,525 B2 10/2010 Howell et al.
 7,812,842 B2 10/2010 Gordon et al.
 7,813,743 B1 10/2010 Loeb et al.
 7,830,370 B2 11/2010 Yamasaki et al.
 7,850,301 B2 12/2010 DiChiara et al.
 7,855,743 B2 12/2010 Sako et al.
 D631,881 S 2/2011 Quinn et al.
 D631,882 S 2/2011 Odgers
 7,928,926 B2 4/2011 Yamamoto et al.
 8,004,765 B2 8/2011 Amitai
 8,018,579 B1 9/2011 Krah et al.
 8,079,713 B2 12/2011 Ashkenazi et al.
 8,092,007 B2 1/2012 DiChiara et al.
 8,166,421 B2 4/2012 Magal et al.
 8,212,859 B2 7/2012 Tang et al.
 8,228,315 B1 7/2012 Starner et al.
 8,235,529 B1 8/2012 Raffle et al.
 8,246,170 B2 8/2012 Yamamoto et al.
 D669,066 S 10/2012 Olsson et al.
 8,337,013 B2 12/2012 Howell et al.
 8,376,548 B2 2/2013 Schultz
 8,378,924 B2 2/2013 Jacobsen et al.
 8,384,999 B1 2/2013 Crosby et al.
 D680,112 S 4/2013 Monahan
 D680,152 S 4/2013 Olsson et al.
 8,427,396 B1 4/2013 Kim
 8,430,507 B2 4/2013 Howell et al.
 8,434,863 B2 5/2013 Howell et al.
 D685,019 S 6/2013 Li
 8,467,133 B2 6/2013 Miller et al.
 8,472,120 B2 6/2013 Border et al.
 8,473,241 B2 6/2013 Foxlin
 8,477,425 B2 7/2013 Border et al.
 8,482,859 B2 7/2013 Border et al.
 8,487,838 B2 7/2013 Kipman et al.
 8,488,246 B2 7/2013 Border et al.
 8,489,326 B1 7/2013 Na et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

8,494,215	B2	7/2013	Kimchi et al.	9,116,337	B1	8/2015	Miao
8,505,430	B2	8/2013	Andryukov et al.	D738,373	S	9/2015	Davies et al.
D689,862	S	9/2013	Liu	9,122,054	B2	9/2015	Osterhout et al.
8,531,394	B2	9/2013	Maltz et al.	9,128,281	B2	9/2015	Osterhout et al.
D690,684	S	10/2013	Lee et al.	9,129,157	B2	9/2015	Chao et al.
8,553,910	B1	10/2013	Dong et al.	9,129,295	B2	9/2015	Border et al.
8,564,883	B2	10/2013	Totani et al.	9,143,693	B1	9/2015	Zhou et al.
8,570,273	B1	10/2013	Smith	9,158,115	B1	10/2015	Worley et al.
8,570,656	B1	10/2013	Weissman et al.	9,158,116	B1	10/2015	Osterhout et al.
8,576,276	B2	11/2013	Bar-Zeev et al.	D743,963	S	11/2015	Osterhout
8,576,491	B2	11/2013	Takagi et al.	9,176,582	B1	11/2015	Johnson et al.
8,587,869	B2	11/2013	Totani et al.	D745,007	S	12/2015	Cazalet et al.
8,593,795	B1	11/2013	Chi et al.	9,202,233	B1	12/2015	Siegel et al.
8,594,467	B2	11/2013	Lu et al.	9,225,934	B2	12/2015	Cho
D696,668	S	12/2013	Chen et al.	9,229,233	B2	1/2016	Osterhout et al.
8,611,015	B2	12/2013	Wheeler et al.	9,235,051	B2	1/2016	Salter et al.
8,662,686	B2	3/2014	Takagi et al.	9,269,193	B2	2/2016	Saito
8,670,183	B2	3/2014	Clavin et al.	D751,551	S	3/2016	Ho et al.
8,678,581	B2	3/2014	Blum et al.	D751,552	S	3/2016	Osterhout
8,681,073	B1	3/2014	Robbins et al.	9,286,728	B2	3/2016	Osterhout et al.
8,698,157	B2	4/2014	Hanamura	9,298,001	B2	3/2016	Border et al.
8,711,487	B2	4/2014	Takeda et al.	9,298,002	B2	3/2016	Border et al.
8,730,129	B2	5/2014	Solomon et al.	9,298,007	B2	3/2016	Border
8,743,052	B1	6/2014	Keller et al.	9,299,194	B2	3/2016	Border et al.
8,745,058	B1	6/2014	Garcia-Barrio	D753,114	S	4/2016	Osterhout
8,750,541	B1	6/2014	Dong et al.	9,310,610	B2	4/2016	Border
8,752,963	B2	6/2014	McCulloch et al.	9,316,833	B2	4/2016	Border et al.
8,760,765	B2	6/2014	Gupta et al.	D756,363	S	5/2016	Mathis
8,767,306	B1	7/2014	Miao et al.	D757,006	S	5/2016	Cazalet et al.
8,770,742	B2	7/2014	Howell et al.	9,329,387	B2	5/2016	Border et al.
8,786,675	B2	7/2014	Deering et al.	9,354,445	B1	5/2016	Weaver et al.
8,786,686	B1	7/2014	Amirparviz	9,366,867	B2	6/2016	Border et al.
8,787,006	B2	7/2014	Golko et al.	9,366,868	B2	6/2016	Border et al.
8,803,867	B2	8/2014	Oikawa	9,377,625	B2	6/2016	Border et al.
8,814,691	B2	8/2014	Osterhout et al.	9,400,233	B2	7/2016	Lin et al.
8,823,071	B2	9/2014	Oyamada	9,400,390	B2	7/2016	Osterhout et al.
8,824,779	B1	9/2014	Smyth	9,401,540	B2	7/2016	Osterhout et al.
8,832,557	B2	9/2014	Tang et al.	9,423,612	B2	8/2016	Border et al.
8,836,768	B1	9/2014	Zuccarino et al.	9,423,842	B2	8/2016	Osterhout et al.
8,837,880	B2	9/2014	Takeda et al.	9,436,006	B2	9/2016	Border
8,854,433	B1	10/2014	Rafii	9,448,409	B2	9/2016	Border et al.
8,854,735	B2	10/2014	Totani et al.	9,494,800	B2	11/2016	Border et al.
8,866,702	B1	10/2014	Mirov et al.	2001/0019240	A1	9/2001	Takahashi et al.
8,866,849	B1	10/2014	Chun et al.	2001/0050817	A1	12/2001	Travers et al.
8,867,139	B2	10/2014	Gupta	2002/0005108	A1	1/2002	Ludwig et al.
D716,808	S	11/2014	Yeom et al.	2002/0021498	A1	2/2002	Ohtaka et al.
D716,813	S	11/2014	Deng	2002/0057280	A1	5/2002	Anabuki et al.
8,878,749	B1	11/2014	Wu et al.	2002/0085843	A1	7/2002	Mann
D719,568	S	12/2014	Heinrich et al.	2002/0109903	A1	8/2002	Kaeriyama et al.
D719,569	S	12/2014	Heinrich et al.	2002/0126396	A1	9/2002	Dolhoff et al.
D719,570	S	12/2014	Heinrich et al.	2002/0148655	A1	10/2002	Cho et al.
8,922,530	B2	12/2014	Pance	2002/0149545	A1	10/2002	Hanayama et al.
8,947,323	B1	2/2015	Geiss et al.	2002/0183101	A1	12/2002	Oh et al.
8,948,935	B1	2/2015	Peeters et al.	2002/0191297	A1	12/2002	Gleckman et al.
8,955,973	B2	2/2015	Raffle et al.	2003/0030597	A1	2/2003	Geist
8,964,298	B2	2/2015	Haddick et al.	2003/0030912	A1	2/2003	Gleckman et al.
D724,083	S	3/2015	Olsson et al.	2003/0151834	A1	8/2003	Penn et al.
8,970,495	B1	3/2015	Weaver et al.	2003/0209953	A1	11/2003	Park et al.
8,971,023	B2	3/2015	Olsson et al.	2003/0234823	A1	12/2003	Sato et al.
8,982,014	B2	3/2015	Evans et al.	2004/0008158	A1	1/2004	Chi et al.
8,982,471	B1	3/2015	Starnier et al.	2004/0008177	A1	1/2004	Ahn et al.
D727,317	S	4/2015	Olsson et al.	2004/0024287	A1	2/2004	Patton et al.
9,020,832	B2	4/2015	Fisher et al.	2004/0027312	A1	2/2004	Owada et al.
D728,573	S	5/2015	Deng	2004/0030448	A1	2/2004	Solomon
9,024,842	B1	5/2015	Wheeler et al.	2004/0032392	A1	2/2004	Chi et al.
9,031,273	B2	5/2015	Dong et al.	2004/0066363	A1	4/2004	Yamano et al.
9,033,502	B2	5/2015	Schmidt et al.	2004/0066547	A1	4/2004	Parker et al.
D732,025	S	6/2015	Heinrich et al.	2004/0080541	A1	4/2004	Saiga et al.
9,046,686	B2	6/2015	Saito	2004/0130522	A1	7/2004	Lin et al.
9,046,999	B1	6/2015	King et al.	2004/0132509	A1	7/2004	Glezerman
9,063,563	B1	6/2015	Gray et al.	2004/0150631	A1	8/2004	Fleck et al.
D733,709	S	7/2015	Kawai	2004/0162211	A1	8/2004	Domey et al.
9,076,368	B2	7/2015	Evans et al.	2004/0194880	A1	10/2004	Jiang et al.
9,096,920	B1	8/2015	Gomez	2004/0227994	A1	11/2004	Ma et al.
9,107,622	B2	8/2015	Nistico et al.	2005/0010091	A1	1/2005	Woods et al.
				2005/0010563	A1	1/2005	Gross et al.
				2005/0041289	A1	2/2005	Berman et al.
				2005/0122319	A1	6/2005	Sakurai et al.
				2005/0154505	A1	7/2005	Nakamura et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2005/0156915	A1	7/2005	Fisher et al.	2010/0001572	A1	1/2010	Masunaga et al.
2005/0157949	A1	7/2005	Aiso et al.	2010/0007852	A1	1/2010	Bietry et al.
2005/0212980	A1	9/2005	Miyazaki et al.	2010/0046075	A1	2/2010	Powell et al.
2006/0022993	A1	2/2006	Hammond et al.	2010/0056274	A1	3/2010	Uusitalo et al.
2006/0047386	A1	3/2006	Kanevsky et al.	2010/0060713	A1	3/2010	Snyder et al.
2006/0050146	A1	3/2006	Richardson et al.	2010/0073376	A1	3/2010	Schmale
2006/0061542	A1	3/2006	Stokic et al.	2010/0079508	A1	4/2010	Hodge et al.
2006/0092131	A1	5/2006	Kuroki et al.	2010/0079733	A1	4/2010	Lu et al.
2006/0098293	A1	5/2006	Garoutte et al.	2010/0082368	A1	4/2010	Gecelter et al.
2006/0119794	A1	6/2006	Hillis et al.	2010/0085325	A1	4/2010	King-Smith et al.
2006/0132457	A1	6/2006	Rimas-Ribikauskas et al.	2010/0094161	A1	4/2010	Kiderman et al.
2006/0132924	A1	6/2006	Mimran et al.	2010/0097580	A1	4/2010	Yamamoto et al.
2006/0152686	A1	7/2006	Yeralan et al.	2010/0103075	A1	4/2010	Kalaboukis et al.
2006/0170652	A1	8/2006	Bannai et al.	2010/0113062	A1	5/2010	Lee et al.
2006/0173351	A1	8/2006	Marcotte et al.	2010/0130140	A1	5/2010	Waku et al.
2006/0178827	A1	8/2006	Aoyama et al.	2010/0141555	A1	6/2010	Rorberg et al.
2006/0183986	A1	8/2006	Rice et al.	2010/0149073	A1	6/2010	Chaum et al.
2006/0215111	A1	9/2006	Mihashi et al.	2010/0178101	A1	7/2010	Day et al.
2006/0224238	A1	10/2006	Azar et al.	2010/0194682	A1	8/2010	Orr et al.
2006/0238550	A1	10/2006	Page et al.	2010/0240988	A1	9/2010	Varga et al.
2006/0239629	A1	10/2006	Qi et al.	2010/0241450	A1	9/2010	Gierhart et al.
2006/0250322	A1	11/2006	Hall et al.	2010/0253594	A1	10/2010	Szczerba et al.
2006/0250696	A1	11/2006	McGuire	2010/0254017	A1	10/2010	Martins et al.
2006/0285315	A1	12/2006	Tufenkjian et al.	2010/0280904	A1	11/2010	Ahuja
2006/0288233	A1	12/2006	Kozlay et al.	2010/0283774	A1	11/2010	Bovet et al.
2007/0003168	A1	1/2007	Oliver et al.	2010/0290127	A1	11/2010	Kessler et al.
2007/0004451	A1	1/2007	Anderson et al.	2010/0309426	A1	12/2010	Howell et al.
2007/0024750	A1	2/2007	Wing Chung et al.	2010/0329301	A1	12/2010	Pang et al.
2007/0024763	A1	2/2007	Chung et al.	2011/0006982	A1	1/2011	Rhee et al.
2007/0024764	A1	2/2007	Chung et al.	2011/0007081	A1	1/2011	Gordon
2007/0024820	A1	2/2007	Chung et al.	2011/0012874	A1	1/2011	Kurozuka et al.
2007/0024823	A1	2/2007	Chung et al.	2011/0089325	A1	4/2011	Ottney
2007/0025273	A1	2/2007	Chung et al.	2011/0096100	A1	4/2011	Sprague et al.
2007/0030243	A1	2/2007	Ishii et al.	2011/0102234	A1	5/2011	Adams et al.
2007/0030456	A1	2/2007	Duncan et al.	2011/0118870	A1	5/2011	Sugihara et al.
2007/0035563	A1	2/2007	Biocca et al.	2011/0130958	A1	6/2011	Stahl et al.
2007/0038960	A1	2/2007	Rekimoto et al.	2011/0131495	A1	6/2011	Bull et al.
2007/0058868	A1	3/2007	Seino et al.	2011/0157236	A1	6/2011	Inoue et al.
2007/0069976	A1	3/2007	Willins et al.	2011/0159931	A1	6/2011	Boss et al.
2007/0070859	A1	3/2007	Hirayama	2011/0164047	A1	7/2011	Pance et al.
2007/0100637	A1	5/2007	McCune et al.	2011/0164163	A1	7/2011	Billbrey et al.
2007/0109284	A1	5/2007	Yamazaki et al.	2011/0164221	A1	7/2011	Tilleman et al.
2007/0120806	A1	5/2007	Schmidt et al.	2011/0175925	A1	7/2011	Kane et al.
2007/0120836	A1	5/2007	Yamaguchi et al.	2011/0176106	A1	7/2011	Lewkowski et al.
2007/0132662	A1	6/2007	Morita et al.	2011/0196610	A1	8/2011	Waldman et al.
2007/0178950	A1	8/2007	Lewis et al.	2011/0199171	A1	8/2011	Prest et al.
2007/0233376	A1	10/2007	Gershony et al.	2011/0201213	A1	8/2011	Dabov et al.
2007/0263174	A1	11/2007	Shyu et al.	2011/0202823	A1	8/2011	Berger et al.
2007/0273611	A1	11/2007	Torch	2011/0205209	A1	8/2011	Kurokawa et al.
2007/0274080	A1	11/2007	Negley et al.	2011/0213664	A1	9/2011	Osterhout et al.
2007/0282682	A1	12/2007	Dietz et al.	2011/0221672	A1	9/2011	Osterhout et al.
2007/0296684	A1	12/2007	Thomas et al.	2011/0221896	A1	9/2011	Haddick et al.
2008/0005702	A1	1/2008	Skourup et al.	2011/0227820	A1	9/2011	Haddick et al.
2008/0036653	A1	2/2008	Huston et al.	2011/0234631	A1	9/2011	Kim et al.
2008/0066973	A1	3/2008	Furuki et al.	2011/0248963	A1	10/2011	Lawrence et al.
2008/0071559	A1	3/2008	Arrasvuori	2011/0285638	A1	11/2011	Harris et al.
2008/0121441	A1	5/2008	Sheets et al.	2011/0285764	A1	11/2011	Kimura et al.
2008/0122736	A1	5/2008	Ronzani et al.	2012/0026088	A1	2/2012	Goran et al.
2008/0143954	A1	6/2008	Abreu et al.	2012/0032874	A1	2/2012	Mukawa
2008/0169998	A1	7/2008	Jacobsen et al.	2012/0033080	A1	2/2012	Watanabe et al.
2008/0186255	A1	8/2008	Cohen et al.	2012/0035934	A1	2/2012	Cunningham et al.
2008/0191965	A1	8/2008	Pandozy et al.	2012/0038641	A1	2/2012	Levantovsky et al.
2008/0219025	A1	9/2008	Spitzer et al.	2012/0050140	A1	3/2012	Border et al.
2008/0266645	A1	10/2008	Dharmatilleke et al.	2012/0050493	A1	3/2012	Ernst et al.
2008/0291277	A1	11/2008	Jacobsen et al.	2012/0056093	A1	3/2012	Poteet et al.
2008/0298639	A1	12/2008	Tsunekawa et al.	2012/0062444	A1	3/2012	Cok et al.
2009/0013204	A1	1/2009	Kobayashi et al.	2012/0062594	A1	3/2012	Campbell et al.
2009/0015735	A1	1/2009	Simmonds et al.	2012/0062850	A1	3/2012	Travis
2009/0040296	A1	2/2009	Moscato et al.	2012/0062998	A1	3/2012	Schultz et al.
2009/0108837	A1	4/2009	Johansson et al.	2012/0068913	A1	3/2012	Bar-Zeev et al.
2009/0110241	A1	4/2009	Takemoto et al.	2012/0069413	A1	3/2012	Schultz et al.
2009/0147331	A1	6/2009	Ashkenazi et al.	2012/0075168	A1	3/2012	Osterhout et al.
2009/0183929	A1	7/2009	Zhang et al.	2012/0078628	A1	3/2012	Ghulman et al.
2009/0251441	A1	10/2009	Edgecomb et al.	2012/0081800	A1	4/2012	Cheng et al.
2009/0279180	A1	11/2009	Amitai et al.	2012/0092328	A1	4/2012	Flaks et al.
				2012/0092329	A1	4/2012	Koo et al.
				2012/0096095	A1	4/2012	Bhargava et al.
				2012/0113514	A1	5/2012	Rodman
				2012/0119978	A1	5/2012	Bietry et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2012/0120103	A1	5/2012	Border et al.	2013/0214909	A1	8/2013	Meijers et al.
2012/0120498	A1	5/2012	Harrison et al.	2013/0215149	A1	8/2013	Hayashi et al.
2012/0127062	A1	5/2012	Bar-Zeev et al.	2013/0222919	A1	8/2013	Komatsu et al.
2012/0127284	A1	5/2012	Bar-Zeev et al.	2013/0230215	A1	9/2013	Gurman et al.
2012/0133885	A1	5/2012	Howell et al.	2013/0234914	A1	9/2013	Fujimaki et al.
2012/0154920	A1	6/2012	Harrison et al.	2013/0235331	A1	9/2013	Heinrich et al.
2012/0162270	A1	6/2012	Fleck et al.	2013/0241805	A1	9/2013	Gomez et al.
2012/0163013	A1	6/2012	Buelow, II et al.	2013/0241948	A1	9/2013	Kimura
2012/0169608	A1	7/2012	Forutanpour et al.	2013/0242405	A1	9/2013	Gupta et al.
2012/0176682	A1	7/2012	DeJong et al.	2013/0248691	A1	9/2013	Mirov et al.
2012/0188245	A1	7/2012	Hyatt et al.	2013/0249778	A1	9/2013	Morimoto et al.
2012/0194550	A1	8/2012	Osterhout et al.	2013/0249787	A1	9/2013	Morimoto
2012/0194553	A1	8/2012	Osterhout et al.	2013/0250207	A1	9/2013	Bohn et al.
2012/0194784	A1	8/2012	Shih et al.	2013/0250430	A1	9/2013	Robbins et al.
2012/0200935	A1	8/2012	Miyao et al.	2013/0250503	A1	9/2013	Olsson et al.
2012/0206817	A1	8/2012	Totani et al.	2013/0257622	A1	10/2013	Davalos et al.
2012/0212398	A1	8/2012	Border et al.	2013/0257709	A1	10/2013	Raffle et al.
2012/0212484	A1	8/2012	Haddick et al.	2013/0258111	A1	10/2013	Frank et al.
2012/0212499	A1	8/2012	Haddick et al.	2013/0265212	A1	10/2013	Kato et al.
2012/0212593	A1	8/2012	Na'aman et al.	2013/0265227	A1	10/2013	Julian et al.
2012/0218301	A1	8/2012	Miller	2013/0278631	A1	10/2013	Border et al.
2012/0223885	A1	9/2012	Perez	2013/0293530	A1	11/2013	Perez et al.
2012/0224060	A1	9/2012	Gurevich et al.	2013/0293580	A1	11/2013	Spivack et al.
2012/0229367	A1	9/2012	Magyari et al.	2013/0300637	A1	11/2013	Smits et al.
2012/0233000	A1	9/2012	Fisher et al.	2013/0300652	A1	11/2013	Raffle et al.
2012/0235885	A1	9/2012	Miller et al.	2013/0321265	A1	12/2013	Bychkov et al.
2012/0237085	A1	9/2012	Meier et al.	2013/0321271	A1	12/2013	Bychkov et al.
2012/0242251	A1	9/2012	Kwisthout et al.	2013/0321932	A1	12/2013	Hsu et al.
2012/0242697	A1	9/2012	Border et al.	2013/0335301	A1	12/2013	Wong et al.
2012/0242698	A1	9/2012	Haddick et al.	2013/0335435	A1	12/2013	Ambrus et al.
2012/0249741	A1	10/2012	Macciocci et al.	2013/0335461	A1	12/2013	Rekimoto et al.
2012/0249797	A1	10/2012	Haddick et al.	2013/0336528	A1	12/2013	Itani et al.
2012/0250152	A1	10/2012	Larson et al.	2013/0336629	A1	12/2013	Mulholland et al.
2012/0264510	A1	10/2012	Wigdor et al.	2013/0342564	A1	12/2013	Kinnebrew et al.
2012/0287398	A1	11/2012	Baker et al.	2013/0342571	A1	12/2013	Kinnebrew et al.
2012/0293548	A1	11/2012	Perez et al.	2013/0342591	A1	12/2013	Sagan et al.
2012/0294478	A1	11/2012	Publicover et al.	2013/0342981	A1	12/2013	Cox et al.
2012/0306850	A1	12/2012	Balan et al.	2013/0346245	A1	12/2013	Desore et al.
2012/0307198	A1	12/2012	Ifergan	2014/0028704	A1	1/2014	Wu et al.
2012/0326948	A1	12/2012	Crocco et al.	2014/0043682	A1	2/2014	Hussey et al.
2012/0327040	A1	12/2012	Simon et al.	2014/0062854	A1	3/2014	Cho
2012/0327116	A1	12/2012	Liu et al.	2014/0063054	A1	3/2014	Osterhout et al.
2013/0009366	A1	1/2013	Hannegan et al.	2014/0063055	A1	3/2014	Osterhout et al.
2013/0009907	A1	1/2013	Rosenberg et al.	2014/0063473	A1	3/2014	Pasolini
2013/0044042	A1	2/2013	Olsson et al.	2014/0078043	A1	3/2014	Kim et al.
2013/0044130	A1	2/2013	Geisner et al.	2014/0078282	A1	3/2014	Aoki et al.
2013/0063496	A1	3/2013	Basler et al.	2014/0091984	A1	4/2014	Ashbrook et al.
2013/0063695	A1	3/2013	Hsieh	2014/0101608	A1	4/2014	Ryskamp et al.
2013/0069924	A1	3/2013	Robinson et al.	2014/0104142	A1	4/2014	Bickerstaff et al.
2013/0069985	A1	3/2013	Wong et al.	2014/0104692	A1	4/2014	Bickerstaff et al.
2013/0070344	A1	3/2013	Takeda et al.	2014/0125668	A1	5/2014	Steed et al.
2013/0077049	A1	3/2013	Bohn et al.	2014/0125785	A1	5/2014	Na et al.
2013/0083009	A1	4/2013	Geisner et al.	2014/0129328	A1	5/2014	Mathew
2013/0083055	A1	4/2013	Piemonte et al.	2014/0139655	A1	5/2014	Mimar
2013/0088413	A1	4/2013	Raffle et al.	2014/0146394	A1	5/2014	Tout et al.
2013/0100259	A1	4/2013	Ramaswamy	2014/0147829	A1	5/2014	Jerauld
2013/0106674	A1	5/2013	Wheeler et al.	2014/0152530	A1	6/2014	Venkatesha et al.
2013/0120224	A1	5/2013	Cajigas et al.	2014/0152558	A1	6/2014	Salter et al.
2013/0120841	A1	5/2013	Shpunt et al.	2014/0152676	A1	6/2014	Rohn et al.
2013/0127906	A1	5/2013	Sugita et al.	2014/0153173	A1	6/2014	Pombo et al.
2013/0127980	A1	5/2013	Haddick	2014/0159995	A1	6/2014	Adams et al.
2013/0135198	A1	5/2013	Hodge et al.	2014/0160055	A1	6/2014	Margolis et al.
2013/0141434	A1	6/2013	Sugden et al.	2014/0160137	A1	6/2014	Martin et al.
2013/0154913	A1	6/2013	Genc et al.	2014/0160157	A1	6/2014	Poulos et al.
2013/0154918	A1	6/2013	Vaught et al.	2014/0160170	A1	6/2014	Lyons
2013/0162632	A1	6/2013	Varga et al.	2014/0168056	A1	6/2014	Swaminathan et al.
2013/0169530	A1	7/2013	Bhaskar et al.	2014/0168266	A1	6/2014	Kimura et al.
2013/0176533	A1	7/2013	Raffle et al.	2014/0168716	A1	6/2014	King et al.
2013/0185052	A1	7/2013	Boyd et al.	2014/0168735	A1	6/2014	Yuan et al.
2013/0194389	A1	8/2013	Vaught et al.	2014/0176591	A1	6/2014	Klein et al.
2013/0196757	A1	8/2013	Latta et al.	2014/0176603	A1	6/2014	Kumar et al.
2013/0201080	A1	8/2013	Evans et al.	2014/0177023	A1	6/2014	Gao et al.
2013/0201081	A1	8/2013	Evans et al.	2014/0183269	A1	7/2014	Glaser et al.
2013/0207887	A1	8/2013	Raffle et al.	2014/0204759	A1	7/2014	Orlik et al.
2013/0207970	A1	8/2013	Shpunt et al.	2014/0213280	A1	7/2014	Sandel et al.
				2014/0222929	A1	8/2014	Grossman et al.
				2014/0225814	A1	8/2014	English et al.
				2014/0232651	A1	8/2014	Kress et al.
				2014/0240313	A1	8/2014	Varga

(56)

References Cited

U.S. PATENT DOCUMENTS

2014/0247286	A1	9/2014	Chi et al.	2015/0205135	A1	7/2015	Border et al.
2014/0253588	A1	9/2014	Mandala et al.	2015/0205346	A1	7/2015	Border
2014/0253605	A1	9/2014	Border et al.	2015/0205347	A1	7/2015	Border
2014/0267010	A1	9/2014	Pasquero et al.	2015/0205348	A1	7/2015	Nortrup et al.
2014/0267419	A1	9/2014	Ballard et al.	2015/0205349	A1	7/2015	Nortrup et al.
2014/0285631	A1	9/2014	Janky et al.	2015/0205351	A1	7/2015	Osterhout et al.
2014/0306866	A1	10/2014	Miller et al.	2015/0205373	A1	7/2015	Osterhout et al.
2014/0310075	A1	10/2014	Ricci et al.	2015/0205378	A1	7/2015	Osterhout
2014/0320389	A1	10/2014	Scavezze et al.	2015/0205384	A1	7/2015	Osterhout et al.
2014/0320971	A1	10/2014	Gupta et al.	2015/0205385	A1	7/2015	Osterhout et al.
2014/0341441	A1	11/2014	Slaby et al.	2015/0205387	A1	7/2015	Osterhout et al.
2014/0361957	A1	12/2014	Hua et al.	2015/0205388	A1	7/2015	Osterhout
2014/0361976	A1	12/2014	Mao et al.	2015/0205401	A1	7/2015	Osterhout
2014/0362195	A1	12/2014	Ng-thow-hing et al.	2015/0205402	A1	7/2015	Osterhout
2014/0363797	A1	12/2014	Hu et al.	2015/0205494	A1	7/2015	Scott et al.
2014/0372957	A1	12/2014	Kipman et al.	2015/0205566	A1	7/2015	Osterhout
2014/0375542	A1	12/2014	Bohn et al.	2015/0206008	A1	7/2015	Border et al.
2014/0375545	A1	12/2014	Finocchio et al.	2015/0206173	A1	7/2015	Nortrup et al.
2014/0375680	A1	12/2014	Ackerman et al.	2015/0212324	A1	7/2015	Osterhout
2014/0375683	A1	12/2014	Massey et al.	2015/0212327	A1	7/2015	Osterhout et al.
2015/0002371	A1	1/2015	Herrod et al.	2015/0213584	A1	7/2015	Ishikawa et al.
2015/0002528	A1	1/2015	Bohn et al.	2015/0213650	A1	7/2015	Barzuza et al.
2015/0022542	A1	1/2015	Baba	2015/0213754	A1	7/2015	Amjad
2015/0029088	A1	1/2015	Kim et al.	2015/0226966	A1	8/2015	Osterhout
2015/0035744	A1	2/2015	Robbins et al.	2015/0226967	A1	8/2015	Osterhout et al.
2015/0042544	A1	2/2015	Sugihara et al.	2015/0228099	A1	8/2015	Osterhout
2015/0097719	A1	4/2015	Balachandreswaran et al.	2015/0228119	A1	8/2015	Osterhout et al.
2015/0134143	A1	5/2015	Willenborg	2015/0228120	A1	8/2015	Osterhout et al.
2015/0143297	A1	5/2015	Wheeler et al.	2015/0229019	A1	8/2015	Osterhout
2015/0145839	A1	5/2015	Hack et al.	2015/0234508	A1	8/2015	Cho et al.
2015/0146004	A1	5/2015	Kritt et al.	2015/0235422	A1	8/2015	Lohse et al.
2015/0147000	A1	5/2015	Salvador Marcos et al.	2015/0235429	A1	8/2015	Miller et al.
2015/0153572	A1	6/2015	Miao et al.	2015/0235622	A1	8/2015	Border et al.
2015/0161913	A1	6/2015	Dominguez et al.	2015/0241963	A1	8/2015	Nortrup et al.
2015/0169953	A1	6/2015	Border	2015/0241964	A1	8/2015	Nortrup et al.
2015/0175068	A1	6/2015	Szostak et al.	2015/0241965	A1	8/2015	Nortrup et al.
2015/0178932	A1	6/2015	Wyatt et al.	2015/0241966	A1	8/2015	Nortrup et al.
2015/0181383	A1	6/2015	Schulz et al.	2015/0243039	A1	8/2015	Holz
2015/0186636	A1	7/2015	Tharappel et al.	2015/0245131	A1	8/2015	Facteau et al.
2015/0198807	A1	7/2015	Hirai	2015/0253573	A1	9/2015	Sako et al.
2015/0201834	A1	7/2015	Border et al.	2015/0254882	A1	9/2015	Englert et al.
2015/0201835	A1	7/2015	Border et al.	2015/0260887	A1	9/2015	Salisbury et al.
2015/0201836	A1	7/2015	Border et al.	2015/0260986	A1	9/2015	Nortrup
2015/0202962	A1	7/2015	Habashima et al.	2015/0261015	A1	9/2015	Ha et al.
2015/0205035	A1	7/2015	Border et al.	2015/0277113	A1	10/2015	Border et al.
2015/0205100	A1	7/2015	Border	2015/0277116	A1	10/2015	Richards et al.
2015/0205101	A1	7/2015	Border	2015/0277118	A1	10/2015	Border et al.
2015/0205102	A1	7/2015	Border	2015/0277120	A1	10/2015	Border
2015/0205103	A1	7/2015	Border	2015/0277122	A1	10/2015	Border
2015/0205104	A1	7/2015	Border	2015/0277549	A1	10/2015	Border
2015/0205105	A1	7/2015	Border	2015/0277559	A1	10/2015	Vescovi
2015/0205107	A1	7/2015	Border	2015/0279010	A1	10/2015	Cianfrone et al.
2015/0205108	A1	7/2015	Border et al.	2015/0279104	A1	10/2015	Border et al.
2015/0205111	A1	7/2015	Border et al.	2015/0279107	A1	10/2015	Border et al.
2015/0205112	A1	7/2015	Border	2015/0279108	A1	10/2015	Border
2015/0205113	A1	7/2015	Border et al.	2015/0287048	A1	10/2015	Nortrup et al.
2015/0205114	A1	7/2015	Border et al.	2015/0293587	A1	10/2015	Wilairat et al.
2015/0205115	A1	7/2015	Border et al.	2015/0294156	A1	10/2015	Border et al.
2015/0205116	A1	7/2015	Border et al.	2015/0294627	A1	10/2015	Yoo et al.
2015/0205117	A1	7/2015	Border et al.	2015/0301593	A1	10/2015	Border et al.
2015/0205118	A1	7/2015	Border et al.	2015/0302646	A1	10/2015	Osterhout et al.
2015/0205119	A1	7/2015	Osterhout et al.	2015/0302647	A1	10/2015	Osterhout et al.
2015/0205120	A1	7/2015	Border et al.	2015/0304368	A1	10/2015	Vaccari et al.
2015/0205121	A1	7/2015	Border et al.	2015/0309313	A1	10/2015	Border et al.
2015/0205122	A1	7/2015	Border et al.	2015/0309314	A1	10/2015	Border et al.
2015/0205123	A1	7/2015	Border	2015/0309317	A1	10/2015	Osterhout et al.
2015/0205124	A1	7/2015	Border	2015/0309534	A1	10/2015	Osterhout
2015/0205125	A1	7/2015	Border et al.	2015/0309562	A1	10/2015	Shams et al.
2015/0205126	A1	7/2015	Schowengerdt	2015/0309995	A1	10/2015	Osterhout
2015/0205127	A1	7/2015	Border et al.	2015/0316766	A1	11/2015	Weaver et al.
2015/0205128	A1	7/2015	Border	2015/0316769	A1	11/2015	Border et al.
2015/0205129	A1	7/2015	Border et al.	2015/0316770	A1	11/2015	Border et al.
2015/0205130	A1	7/2015	Border	2015/0316771	A1	11/2015	Border et al.
2015/0205131	A1	7/2015	Border et al.	2015/0316772	A1	11/2015	Border et al.
2015/0205132	A1	7/2015	Osterhout et al.	2015/0331241	A1	11/2015	Haddick et al.
				2015/0332032	A1	11/2015	Alameh et al.
				2015/0338661	A1	11/2015	Osterhout et al.
				2015/0338915	A1	11/2015	Publicover et al.
				2015/0346496	A1	12/2015	Haddick et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2015/0346511 A1 12/2015 Osterhout et al.
 2015/0347823 A1 12/2015 Monnerat et al.
 2015/0355466 A1 12/2015 Border
 2015/0355468 A1 12/2015 Osterhout et al.
 2015/0356772 A1 12/2015 Osterhout et al.
 2015/0356775 A1 12/2015 Osterhout et al.
 2015/0356776 A1 12/2015 Osterhout et al.
 2015/0356777 A1 12/2015 Osterhout et al.
 2015/0356778 A1 12/2015 Osterhout et al.
 2015/0356779 A1 12/2015 Osterhout et al.
 2015/0363975 A1 12/2015 Osterhout et al.
 2015/0382305 A1 12/2015 Drincic
 2016/0005003 A1 1/2016 Norris et al.
 2016/0007849 A1 1/2016 Krueger et al.
 2016/0011417 A1 1/2016 Border et al.
 2016/0015470 A1 1/2016 Border
 2016/0018640 A1 1/2016 Haddick et al.
 2016/0018641 A1 1/2016 Haddick et al.
 2016/0018642 A1 1/2016 Haddick et al.
 2016/0018644 A1 1/2016 Border et al.
 2016/0018645 A1 1/2016 Haddick et al.
 2016/0018646 A1 1/2016 Osterhout et al.
 2016/0018647 A1 1/2016 Osterhout et al.
 2016/0018648 A1 1/2016 Osterhout et al.
 2016/0018649 A1 1/2016 Osterhout et al.
 2016/0018650 A1 1/2016 Haddick et al.
 2016/0018651 A1 1/2016 Haddick et al.
 2016/0018652 A1 1/2016 Haddick et al.
 2016/0018653 A1 1/2016 Haddick et al.
 2016/0018654 A1 1/2016 Haddick et al.
 2016/0019715 A1 1/2016 Haddick et al.
 2016/0019719 A1 1/2016 Osterhout et al.
 2016/0021304 A1 1/2016 Osterhout
 2016/0025974 A1 1/2016 Osterhout et al.
 2016/0025977 A1 1/2016 Osterhout
 2016/0025979 A1 1/2016 Border et al.
 2016/0025980 A1 1/2016 Osterhout et al.
 2016/0026239 A1 1/2016 Border et al.
 2016/0027211 A1 1/2016 Osterhout et al.
 2016/0027414 A1 1/2016 Osterhout et al.
 2016/0035139 A1 2/2016 Fuchs et al.
 2016/0045810 A1 2/2016 Minkovitch
 2016/0048018 A1 2/2016 De Matos Pereira Vieira
 2016/0048019 A1 2/2016 Haddick et al.
 2016/0048021 A1 2/2016 Border
 2016/0048023 A1 2/2016 Haddick et al.
 2016/0048160 A1 2/2016 Haddick et al.
 2016/0049008 A1 2/2016 Haddick et al.
 2016/0054566 A1 2/2016 Osterhout et al.
 2016/0055675 A1 2/2016 Kasahara et al.
 2016/0062118 A1 3/2016 Osterhout
 2016/0062121 A1 3/2016 Border et al.
 2016/0062122 A1 3/2016 Border
 2016/0085071 A1 3/2016 Border
 2016/0085072 A1 3/2016 Haddick et al.
 2016/0085278 A1 3/2016 Osterhout et al.
 2016/0091718 A1 3/2016 Border et al.
 2016/0091719 A1 3/2016 Border
 2016/0109709 A1 4/2016 Osterhout
 2016/0109711 A1 4/2016 Border
 2016/0109713 A1 4/2016 Osterhout
 2016/0116738 A1 4/2016 Osterhout et al.
 2016/0116745 A1 4/2016 Osterhout et al.
 2016/0116979 A1 4/2016 Border
 2016/0117972 A1 4/2016 Yoshiyama et al.
 2016/0131904 A1 5/2016 Border et al.
 2016/0131911 A1 5/2016 Border et al.
 2016/0131912 A1 5/2016 Border et al.
 2016/0132082 A1 5/2016 Border et al.
 2016/0133201 A1 5/2016 Border et al.
 2016/0137312 A1 5/2016 Osterhout
 2016/0147063 A1 5/2016 Border et al.
 2016/0147064 A1 5/2016 Border et al.
 2016/0147065 A1 5/2016 Border et al.
 2016/0147070 A1 5/2016 Border et al.

2016/0154242 A1 6/2016 Border
 2016/0154244 A1 6/2016 Border et al.
 2016/0161743 A1 6/2016 Osterhout et al.
 2016/0161747 A1 6/2016 Osterhout
 2016/0170207 A1 6/2016 Haddick et al.
 2016/0170208 A1 6/2016 Border et al.
 2016/0170209 A1 6/2016 Border et al.
 2016/0170699 A1 6/2016 Border et al.
 2016/0171769 A1 6/2016 Haddick et al.
 2016/0187651 A1 6/2016 Border et al.
 2016/0187658 A1 6/2016 Osterhout et al.
 2016/0202946 A1 7/2016 Osterhout et al.
 2016/0207457 A1 7/2016 Border et al.
 2016/0216516 A1 7/2016 Border
 2016/0216517 A1 7/2016 Border
 2016/0231571 A1 8/2016 Border et al.
 2016/0239985 A1 8/2016 Haddick et al.
 2016/0240008 A1 8/2016 Haddick et al.
 2016/0246055 A1 8/2016 Border et al.
 2016/0252731 A1 9/2016 Border et al.
 2016/0259166 A1 9/2016 Border et al.
 2016/0274361 A1 9/2016 Border et al.
 2016/0274365 A1 9/2016 Bailey et al.
 2016/0282626 A1 9/2016 Border et al.
 2016/0286177 A1 9/2016 Border et al.
 2016/0286203 A1 9/2016 Border et al.
 2016/0286210 A1 9/2016 Border et al.
 2016/0306173 A1 10/2016 Tsukahara et al.
 2016/0329634 A1 11/2016 Osterhout et al.
 2016/0357019 A1 12/2016 Border et al.
 2017/0025091 A1 1/2017 Haddick et al.

FOREIGN PATENT DOCUMENTS

EP 777867 A1 6/1997
 EP 1326121 A2 7/2003
 EP 2207164 A2 7/2010
 EP 2486450 A1 8/2012
 EP 2490130 A1 8/2012
 EP 2502410 A1 9/2012
 EP 2674834 A2 12/2013
 GB 2491984 A 12/2012
 JP 07110735 A 4/1995
 JP 2000102036 A 4/2000
 JP 2005138755 A 6/2005
 JP 2009171505 A 7/2009
 JP 5017989 B2 9/2012
 JP 2012212990 A 11/2012
 KR 1020110101944 A 9/2011
 WO 2011143655 A1 11/2011
 WO 2012040030 A2 3/2012
 WO 2012058175 A1 5/2012
 WO 2012064546 A1 5/2012
 WO 2012082807 A2 6/2012
 WO 2012118573 A1 9/2012
 WO 2012118575 A2 9/2012
 WO 2013043288 A2 3/2013
 WO 2013049248 A2 4/2013
 WO 2013050650 A1 4/2013
 WO 2013103825 A1 7/2013
 WO 2013110846 A1 8/2013
 WO 2013170073 A1 11/2013
 WO 2013176079 A1 11/2013
 WO 2015/109145 A1 7/2015
 WO 2015109145 A9 7/2015
 WO 2015164276 A1 10/2015
 WO 2015179877 A2 11/2015
 WO 2015179877 A3 11/2015
 WO 2015195444 A1 12/2015
 WO 2016/044035 3/2016
 WO 2016073734 A1 5/2016
 WO 2016133886 A1 8/2016
 WO 2017015093 A1 1/2017
 WO PCT/US2017/018277 2/2017
 WO PCT/US2017/019665 2/2017
 WO PCT/US2017/020379 3/2017

(56)

References Cited

OTHER PUBLICATIONS

- US 8,792,178, 07/2014, Totani et al. (withdrawn)
- US 9,195,056, 11/2015, Border et al. (withdrawn)
- “Audio Spotlight”, by Holosonics, <http://www.holosonics.com>, accessed Jul. 3, 2014, 3 pages.
- “Genius Ring Mice”, <http://www.geniusnet.com/Genius/wSite/productCompare/compare.jsp>, Dec. 23, 2014, 1 page.
- “Help Requested! Comments and input needed for new coaxial UAS—DIY Drones”, <http://diydrone.com/profiles/blogs/help-requested-comments-and-input-needed-for-new-coaxial-uas>, Mar. 5, 2015, pp. 1-3.
- “How Ascent AeroSystems is looking to add to your outdoor adventure”, <http://droneblog.com/2015/03/23/how-ascent-aerosystems-is-looking-to-add-to-your-outdoor-adventure/#!prettyPhoto>, Mar. 23, 2015, 1-10.
- “Lightberry”, <https://web.archive.org/web/20131201194408/http://lightberry.eu/>, Dec. 1, 2013, 11 Pages.
- “Meet Nod, the Bluetooth Ring That Wants to Replace Your Mouse”, <http://www.pcmag.com/article2/0,2817,2457238,00.asp>, Apr. 29, 2014, 6 pages.
- “Sound from Ultrasound”, Wikipedia entry, http://en.m.wikipedia.org/wiki/Sound_from_ultrasound, accessed Jul. 3, 2014, 13 pages.
- Allison, Robert S. et al., “Tolerance of Temporal Delay in Virtual Environments”, VR '01 Proceedings of the Virtual Reality 2001 Conference (VR'01), Centre for Vision Research and Departments of Computer Science and Psychology, Mar. 2001, 2-8.
- Bezryadin, Sergey et al., “Brightness Calculation in Digital Image Processing”, Technologies for Digital Fulfillment 2007, Las Vegas, NV, 2007, pp. 1-6.
- Fathi, Alircza et al., “Social interactions: A first-person perspective”, Computer Vision and Pattern Recognition (CVPR), IEEE Conference on. IEEE, 2012., 2012, 8 Pages.
- Huang, Jin-Bin , “Image Completion Using Planar Structure Guidelines”, ACM Transactions on Graphics, vol. 33, No. 4, Article 129, Jul. 2014, 1-10.
- Janin, Adam L. et al., “Calibration of Head-Mounted Displays for Augmented Reality Applications”, Research and Technology Boeing Computer Services MS 7L-48 P.O. Box 24346 Seattle, WA 98124-0346 Virtual Reality Annual International Symposium, 1993., 1993 IEEE., 1993, 10 Pages.
- Lang, Manuel et al., “Nonlinear Disparity Mapping for Stereoscopic 3D”, Jul. 2010, pp. 1-10.
- Logbar Inc., “Ring: Shortcut Everything”, <https://www.kickstarter.com/projects/1761670738/ring-shortcut-everything>, Jun. 2012, 1 page.
- Losev, Oleg et al., “Light-emitting diode”, Nov. 2016, https://en.wikipedia.org/wiki/Lightemitting_diode, pp. 1-25.
- Mastandrea, Nick , “Mycestro, The Next Generation 3D Mouse”, <https://www.kickstarter.com/projects/mycestro/mycestrotm-the-next-generation-3d-mouse>, Dec. 2014, 22 pages.
- Pamplona, Vitor R. et al., “Photorealistic Models for Pupil Light Reflex and Iridal Pattern Deformation”, ACM Transactions on Graphics, vol. 28, No. 4, Article 106, Publication date: Aug. 2009, pp. 1-12.
- PCT/US2015/011697, “International Application Serial No. PCT/US2015/011697, International Search Report and Written Opinion mailed Apr. 13, 2015”, Osterhout Group, Inc., 14 pages.
- PCT/US2015/011697, “International Application Serial No. PCT/US2015/011697, International Preliminary Report on Patentability and Written Opinion mailed Jul. 28, 2016”, Osterhout Group, Inc., 10 pages.
- PCT/US2015/026704, “International Application Serial No. PCT/US2015/026704, International Preliminary Report on Patentability and Written Opinion mailed Nov. 3, 2016”, Osterhout Group, Inc., 10 Pages.
- PCT/US2015/026704, “International Search Report and Written Opinion”, Osterhout Group, Inc., 15 pages.
- PCT/US2015/033379, “International Application Serial No. PCT/US2015/033379, International Preliminary Report on Patentability and Written Opinion mailed Dec. 1, 2016”, Osterhout Group, Inc., 8 Pages.
- PCT/US2015/035192, “International Application Serial No. PCT/US2015/035192, International Search Report and Written Opinion mailed Sep. 3, 2015”, Osterhout Group, Inc., 11 pages.
- PCT/US2015/059264, “International Application Serial No. PCT/US2015/059264, International Search Report and Written Opinion mailed Feb. 19, 2016”, Osterhout Group, Inc., 11 Pages.
- PCT/US2016/018040, “International Application Serial No. PCT/US2016/018040, International Search Report and Written Opinion mailed Jul. 6, 2016”, Osterhout Group, Inc., 10 pages.
- PCT/US2016/038008, “Application Serial No. PCT/US2016/038008, International Search Report and Written Opinion mailed Oct. 27, 2016”, Osterhout Group, Inc., 8 pages.
- PCT/US2016/042440, “Application Serial No. PCT/US2016/042440, The International Search Report and Written Opinion mailed Oct. 13, 2016”, Osterhout Group, Inc., 7 pages.
- PCT/US2015/033379, “International Application Serial No. PCT/US2015/033379, International Search Report and Written Opinion mailed Nov. 30, 2015”, Osterhout Group, Inc., 12 Pages.
- Plainis, Sotiris et al., “The Physiologic Mechanism of Accommodation”, Cataract & Refractive Surgery Today Europe, Apr. 2014, pp. 23-29.
- Walton, Zach, “Wear This Smartphone Controller on Your Finger”, <http://www.webpronews.com/wear-this-smartphone-controller-on-your-finger-2012-06>, 5 pages.
- Ye, Hui et al., “High Quality Voice Morphing”, Cambridge University Engineering Department Trumpington Street, Cambridge, England, CB2 1PZ, 2004, pp. I-9-I-11.
- U.S. Appl. No. 15/395,690, filed Dec. 30, 2016.
- U.S. Appl. No. 15/397,920, filed Jan. 4, 2017.
- U.S. Appl. No. 15/389,387, filed Jan. 4, 2017.
- U.S. Appl. No. 15/400,982, filed Jan. 7, 2017.
- U.S. Appl. No. 29/589,483, filed Dec. 31, 2016.
- U.S. Appl. No. 29/589,676, filed Jan. 4, 2017.
- U.S. Appl. No. 15/446,025, filed Mar. 1, 2017.
- U.S. Appl. No. 15/456,619, filed Mar. 13, 2017.
- Schedwill, “Bidirectional OLED Microdisplay”, Fraunhofer Research Institution for Organics, Materials and Electronic Device Comedd, Apr. 11, 2014, 2 pages.
- Vogel, et al., “Data glasses controlled by eye movements”, Information and communication, Fraunhofer-Gesellschaft, Sep. 22, 2013, 2 pages.




Figure 1





Figure 2



PRIOR ART
Figure 3a




Figure 3b




Figure 4




Figure 4a

202




Figure 4b




Figure 5




Figure 5a




Figure 5b




Figure 5c




Figure 5d




Figure 5e




Figure 6




Figure 7




Figure 8




Figure 8a




Figure 8b




Figure 8c




Figure 9




Figure 10




Figure 10a




Figure 10b




Figure 11a

Relative Spectral Emission
 $V(\lambda)$ = spektral Augenempfindlichkeit / Standard eye response curve
 $I_{rel} = f(\lambda); T_s = 25^\circ\text{C}; I_f = 20 \text{ mA}$




Fig. 11b




Figure 11c

1108




Fig. 11d




Figure 12a




Figure 12b




Figure 12c




Figure 13a




Figure 13b




Figure 13c




Figure 14a




Figure 14b




Figure 14c




Figure 15




Fig. 160A




Fig. 160B




Fig. 160C




Fig. 17A




Fig. 17B






Fig. 17C






Fig. 18B








Fig. 18C










Figure 22




Figure 23




Figure 23a

1

LOCATION INDICATING AVATAR IN HEAD WORN COMPUTING

CROSS REFERENCE TO RELATED APPLICATIONS

This application claims the benefit of priority to and is a continuation of the following U.S. patent application, which is hereby incorporated by reference in its entirety:

U.S. non-provisional application Ser. No. 14/178,047, entitled MICRO DOPPLER PRESENTATIONS IN HEAD WORN COMPUTING, filed Feb. 11, 2014.

BACKGROUND

Field of the Invention

This invention relates to head worn computing. More particularly, this invention relates to micro Doppler presentation techniques used in head worn computing.

Description of Related Art

Wearable computing systems have been developed and are beginning to be commercialized. Many problems persist in the wearable computing field that need to be resolved to make them meet the demands of the market.

SUMMARY

Aspects of the present invention relate to methods and systems for presenting intuitive and useful micro Doppler signatures in head worn computing.

These and other systems, methods, objects, features, and advantages of the present invention will be apparent to those skilled in the art from the following detailed description of the preferred embodiment and the drawings. All documents mentioned herein are hereby incorporated in their entirety by reference.

BRIEF DESCRIPTION OF THE DRAWINGS

Embodiments are described with reference to the following Figures. The same numbers may be used throughout to reference like features and components that are shown in the Figures:

FIG. 1 illustrates a head worn computing system in accordance with the principles of the present invention.

FIG. 2 illustrates a head worn computing system with optical system in accordance with the principles of the present invention.

FIG. 3a illustrates a large prior art optical arrangement.

FIG. 3b illustrates an upper optical module in accordance with the principles of the present invention.

FIG. 4 illustrates an upper optical module in accordance with the principles of the present invention.

FIG. 4a illustrates an upper optical module in accordance with the principles of the present invention.

FIG. 4b illustrates an upper optical module in accordance with the principles of the present invention.

FIG. 5 illustrates an upper optical module in accordance with the principles of the present invention.

FIG. 5a illustrates an upper optical module in accordance with the principles of the present invention.

FIG. 5b illustrates an upper optical module and dark light trap according to the principles of the present invention.

FIG. 5c illustrates an upper optical module and dark light trap according to the principles of the present invention.

FIG. 5d illustrates an upper optical module and dark light trap according to the principles of the present invention.

2

FIG. 5e illustrates an upper optical module and dark light trap according to the principles of the present invention.

FIG. 6 illustrates upper and lower optical modules in accordance with the principles of the present invention.

FIG. 7 illustrates angles of combiner elements in accordance with the principles of the present invention.

FIG. 8 illustrates upper and lower optical modules in accordance with the principles of the present invention.

FIG. 8a illustrates upper and lower optical modules in accordance with the principles of the present invention.

FIG. 8b illustrates upper and lower optical modules in accordance with the principles of the present invention.

FIG. 8c illustrates upper and lower optical modules in accordance with the principles of the present invention.

FIG. 9 illustrates an eye imaging system in accordance with the principles of the present invention.

FIG. 10 illustrates a light source in accordance with the principles of the present invention.

FIG. 10a illustrates a back lighting system in accordance with the principles of the present invention.

FIG. 10b illustrates a back lighting system in accordance with the principles of the present invention.

FIGS. 11a to 11d illustrate light source and filters in accordance with the principles of the present invention.

FIGS. 12a to 12c illustrate light source and quantum dot systems in accordance with the principles of the present invention.

FIGS. 13a to 13c illustrate peripheral lighting systems in accordance with the principles of the present invention.

FIGS. 14a to 14c illustrate a light suppression systems in accordance with the principles of the present invention.

FIG. 15 illustrates an external user interface in accordance with the principles of the present invention.

FIGS. 16a to 16c illustrate distance control systems in accordance with the principles of the present invention.

FIGS. 17a to 17c illustrate force interpretation systems in accordance with the principles of the present invention.

FIGS. 18a to 18c illustrate user interface mode selection systems in accordance with the principles of the present invention.

FIG. 19 illustrates interaction systems in accordance with the principles of the present invention.

FIG. 20 illustrates external user interfaces in accordance with the principles of the present invention.

FIG. 21 illustrates mD trace representations presented in accordance with the principles of the present invention.

FIG. 22 illustrates mD trace representations presented in accordance with the principles of the present invention.

FIG. 23 illustrates an mD scanned environment in accordance with the principles of the present invention.

FIG. 23a illustrates mD trace representations presented in accordance with the principles of the present invention.

While the invention has been described in connection with certain preferred embodiments, other embodiments would be understood by one of ordinary skill in the art and are encompassed herein.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT(S)

Aspects of the present invention relate to head-worn computing ("HWC") systems. HWC involves, in some instances, a system that mimics the appearance of head-worn glasses or sunglasses. The glasses may be a fully developed computing platform, such as including computer displays presented in each of the lenses of the glasses to the eyes of the user. In embodiments, the lenses and displays may be

configured to allow a person wearing the glasses to see the environment through the lenses while also seeing, simultaneously, digital imagery, which forms an overlaid image that is perceived by the person as a digitally augmented image of the environment, or augmented reality (“AR”).

HWC involves more than just placing a computing system on a person’s head. The system may need to be designed as a lightweight, compact and fully functional computer display, such as wherein the computer display includes a high resolution digital display that provides a high level of emersion comprised of the displayed digital content and the see-through view of the environmental surroundings. User interfaces and control systems suited to the HWC device may be required that are unlike those used for a more conventional computer such as a laptop. For the HWC and associated systems to be most effective, the glasses may be equipped with sensors to determine environmental conditions, geographic location, relative positioning to other points of interest, objects identified by imaging and movement by the user or other users in a connected group, and the like. The HWC may then change the mode of operation to match the conditions, location, positioning, movements, and the like, in a method generally referred to as a contextually aware HWC. The glasses also may need to be connected, wirelessly or otherwise, to other systems either locally or through a network. Controlling the glasses may be achieved through the use of an external device, automatically through contextually gathered information, through user gestures captured by the glasses sensors, and the like. Each technique may be further refined depending on the software application being used in the glasses. The glasses may further be used to control or coordinate with external devices that are associated with the glasses.

Referring to FIG. 1, an overview of the HWC system **100** is presented. As shown, the HWC system **100** comprises a HWC **102**, which in this instance is configured as glasses to be worn on the head with sensors such that the HWC **102** is aware of the objects and conditions in the environment **114**. In this instance, the HWC **102** also receives and interprets control inputs such as gestures and movements **116**. The HWC **102** may communicate with external user interfaces **104**. The external user interfaces **104** may provide a physical user interface to take control instructions from a user of the HWC **102** and the external user interfaces **104** and the HWC **102** may communicate bi-directionally to affect the user’s command and provide feedback to the external device **108**. The HWC **102** may also communicate bi-directionally with externally controlled or coordinated local devices **108**. For example, an external user interface **104** may be used in connection with the HWC **102** to control an externally controlled or coordinated local device **108**. The externally controlled or coordinated local device **108** may provide feedback to the HWC **102** and a customized GUI may be presented in the HWC **102** based on the type of device or specifically identified device **108**. The HWC **102** may also interact with remote devices and information sources **112** through a network connection **110**. Again, the external user interface **104** may be used in connection with the HWC **102** to control or otherwise interact with any of the remote devices **108** and information sources **112** in a similar way as when the external user interfaces **104** are used to control or otherwise interact with the externally controlled or coordinated local devices **108**. Similarly, HWC **102** may interpret gestures **116** (e.g. captured from forward, downward, upward, rearward facing sensors such as camera(s), range

finders, IR sensors, etc.) or environmental conditions sensed in the environment **114** to control either local or remote devices **108** or **112**.

We will now describe each of the main elements depicted on FIG. 1 in more detail; however, these descriptions are intended to provide general guidance and should not be construed as limiting. Additional description of each element may also be further described herein.

The HWC **102** is a computing platform intended to be worn on a person’s head. The HWC **102** may take many different forms to fit many different functional requirements. In some situations, the HWC **102** will be designed in the form of conventional glasses. The glasses may or may not have active computer graphics displays. In situations where the HWC **102** has integrated computer displays the displays may be configured as see-through displays such that the digital imagery can be overlaid with respect to the user’s view of the environment **114**. There are a number of see-through optical designs that may be used, including ones that have a reflective display (e.g. LCoS, DLP), emissive displays (e.g. OLED, LED), hologram, TIR waveguides, and the like. In embodiments, lighting systems used in connection with the display optics may be solid state lighting systems, such as LED, OLED, quantum dot, quantum dot LED, etc. In addition, the optical configuration may be monocular or binocular. It may also include vision corrective optical components. In embodiments, the optics may be packaged as contact lenses. In other embodiments, the HWC **102** may be in the form of a helmet with a see-through shield, sunglasses, safety glasses, goggles, a mask, fire helmet with see-through shield, police helmet with see through shield, military helmet with see-through shield, utility form customized to a certain work task (e.g. inventory control, logistics, repair, maintenance, etc.), and the like.

The HWC **102** may also have a number of integrated computing facilities, such as an integrated processor, integrated power management, communication structures (e.g. cell net, WiFi, Bluetooth, local area connections, mesh connections, remote connections (e.g. client server, etc.)), and the like. The HWC **102** may also have a number of positional awareness sensors, such as GPS, electronic compass, altimeter, tilt sensor, IMU, and the like. It may also have other sensors such as a camera, rangefinder, hyperspectral camera, Geiger counter, microphone, spectral illumination detector, temperature sensor, chemical sensor, biologic sensor, moisture sensor, ultrasonic sensor, and the like.

The HWC **102** may also have integrated control technologies. The integrated control technologies may be contextual based control, passive control, active control, user control, and the like. For example, the HWC **102** may have an integrated sensor (e.g. camera) that captures user hand or body gestures **116** such that the integrated processing system can interpret the gestures and generate control commands for the HWC **102**. In another example, the HWC **102** may have sensors that detect movement (e.g. a nod, head shake, and the like) including accelerometers, gyros and other inertial measurements, where the integrated processor may interpret the movement and generate a control command in response. The HWC **102** may also automatically control itself based on measured or perceived environmental conditions. For example, if it is bright in the environment the HWC **102** may increase the brightness or contrast of the displayed image. In embodiments, the integrated control technologies may be mounted on the HWC **102** such that a user can interact with it directly. For example, the HWC **102** may have a button(s), touch capacitive interface, and the like.

As described herein, the HWC **102** may be in communication with external user interfaces **104**. The external user interfaces may come in many different forms. For example, a cell phone screen may be adapted to take user input for control of an aspect of the HWC **102**. The external user interface may be a dedicated UI, such as a keyboard, touch surface, button(s), joy stick, and the like. In embodiments, the external controller may be integrated into another device such as a ring, watch, bike, car, and the like. In each case, the external user interface **104** may include sensors (e.g. IMU, accelerometers, compass, altimeter, and the like) to provide additional input for controlling the HWC **104**.

As described herein, the HWC **102** may control or coordinate with other local devices **108**. The external devices **108** may be an audio device, visual device, vehicle, cell phone, computer, and the like. For instance, the local external device **108** may be another HWC **102**, where information may then be exchanged between the separate HWCs **108**.

Similar to the way the HWC **102** may control or coordinate with local devices **106**, the HWC **102** may control or coordinate with remote devices **112**, such as the HWC **102** communicating with the remote devices **112** through a network **110**. Again, the form of the remote device **112** may have many forms. Included in these forms is another HWC **102**. For example, each HWC **102** may communicate its GPS position such that all the HWCs **102** know where all of HWC **102** are located.

FIG. 2 illustrates a HWC **102** with an optical system that includes an upper optical module **202** and a lower optical module **204**. While the upper and lower optical modules **202** and **204** will generally be described as separate modules, it should be understood that this is illustrative only and the present invention includes other physical configurations, such as that when the two modules are combined into a single module or where the elements making up the two modules are configured into more than two modules. In embodiments, the upper module **202** includes a computer controlled display (e.g. LCoS, DLP, OLED, etc.) and image light delivery optics. In embodiments, the lower module includes eye delivery optics that are configured to receive the upper module's image light and deliver the image light to the eye of a wearer of the HWC. In FIG. 2, it should be noted that while the upper and lower optical modules **202** and **204** are illustrated in one side of the HWC such that image light can be delivered to one eye of the wearer, that it is envisioned by the present invention that embodiments will contain two image light delivery systems, one for each eye.

FIG. 3a illustrates an upper optical module **202** in accordance with the principles of the present invention. In this embodiment, the upper optical module **202** includes a DLP (also known as DMD or digital micromirror device) computer operated display **304** which includes pixels comprised of rotatable mirrors (such as, for example, the DLP3000 available from Texas Instruments), polarized light source **302**, $\frac{1}{4}$ wave retarder film **308**, reflective polarizer **310** and a field lens **312**. The polarized light source **302** provides substantially uniform polarized light that is generally directed towards the reflective polarizer **310**. The reflective polarizer reflects light of one polarization state (e.g. S polarized light) and transmits light of the other polarization state (e.g. P polarized light). The polarized light source **302** and the reflective polarizer **310** are oriented so that the polarized light from the polarized light source **302** is reflected generally towards the DLP **304**. The light then passes through the $\frac{1}{4}$ wave film **308** once before illuminat-

ing the pixels of the DLP **304** and then again after being reflected by the pixels of the DLP **304**. In passing through the $\frac{1}{4}$ wave film **308** twice, the light is converted from one polarization state to the other polarization state (e.g. the light is converted from S to P polarized light). The light then passes through the reflective polarizer **310**. In the event that the DLP pixel(s) are in the "on" state (i.e. the mirrors are positioned to reflect light towards the field lens **312**, the "on" pixels reflect the light generally along the optical axis and into the field lens **312**. This light that is reflected by "on" pixels and which is directed generally along the optical axis of the field lens **312** will be referred to as image light **316**. The image light **316** then passes through the field lens to be used by a lower optical module **204**.

The light that is provided by the polarized light source **302**, which is subsequently reflected by the reflective polarizer **310** before it reflects from the DLP **304**, will generally be referred to as illumination light. The light that is reflected by the "off" pixels of the DLP **304** is reflected at a different angle than the light reflected by the "on" pixels, so that the light from the "off" pixels is generally directed away from the optical axis of the field lens **312** and toward the side of the upper optical module **202** as shown in FIG. 3. The light that is reflected by the "off" pixels of the DLP **304** will be referred to as dark state light **314**.

The DLP **304** operates as a computer controlled display and is generally thought of as a MEMs device. The DLP pixels are comprised of small mirrors that can be directed. The mirrors generally flip from one angle to another angle. The two angles are generally referred to as states. When light is used to illuminate the DLP the mirrors will reflect the light in a direction depending on the state. In embodiments herein, we generally refer to the two states as "on" and "off," which is intended to depict the condition of a display pixel. "On" pixels will be seen by a viewer of the display as emitting light because the light is directed along the optical axis and into the field lens and the associated remainder of the display system. "Off" pixels will be seen by a viewer of the display as not emitting light because the light from these pixels is directed to the side of the optical housing and into a light trap or light dump where the light is absorbed. The pattern of "on" and "off" pixels produces image light that is perceived by a viewer of the display as a computer generated image. Full color images can be presented to a user by sequentially providing illumination light with complementary colors such as red, green and blue. Where the sequence is presented in a recurring cycle that is faster than the user can perceive as separate images and as a result the user perceives a full color image comprised of the sum of the sequential images. Bright pixels in the image are provided by pixels that remain in the "on" state for the entire time of the cycle, while dimmer pixels in the image are provided by pixels that switch between the "on" state and "off" state within the time of the cycle, or frame time when in a video sequence of images.

FIG. 3a shows an illustration of a system for a DLP **304** in which the unpolarized light source **350** is pointed directly at the DLP **304**. In this case, the angle required for the illumination light is such that the field lens **352** must be positioned substantially distant from the DLP **304** to avoid the illumination light from being clipped by the field lens **352**. The large distance between the field lens **352** and the DLP **304** along with the straight path of the dark state light **354**, means that the light trap for the dark state light **354** is also located at a substantial distance from the DLP. For these reasons, this configuration is larger in size compared to the upper optics module **202** of the preferred embodiments.

The configuration illustrated in FIG. 3b can be lightweight and compact such that it fits into a small portion of a HWC. For example, the upper modules 202 illustrated herein can be physically adapted to mount in an upper frame of a HWC such that the image light can be directed into a lower optical module 204 for presentation of digital content to a wearer's eye. The package of components that combine to generate the image light (i.e. the polarized light source 302, DLP 304, reflective polarizer 310 and ¼ wave film 308) is very light and is compact. The height of the system, excluding the field lens, may be less than 8 mm. The width (i.e. from front to back) may be less than 8 mm. The weight may be less than 2 grams. The compactness of this upper optical module 202 allows for a compact mechanical design of the HWC and the light weight nature of these embodiments help make the HWC lightweight to provide for a HWC that is comfortable for a wearer of the HWC.

The configuration illustrated in FIG. 3b can produce sharp contrast, high brightness and deep blacks, especially when compared to LCD or LCoS displays used in HWC. The "on" and "off" states of the DLP provide for a strong differentiator in the light reflection path representing an "on" pixel and an "off" pixel. As will be discussed in more detail below, the dark state light from the "off" pixel reflections can be managed to reduce stray light in the display system to produce images with high contrast.

FIG. 4 illustrates another embodiment of an upper optical module 202 in accordance with the principles of the present invention. This embodiment includes a light source 404, but in this case, the light source can provide unpolarized illumination light. The illumination light from the light source 404 is directed into a TIR wedge 418 such that the illumination light is incident on an internal surface of the TIR wedge 418 (shown as the angled lower surface of the TIR wedge 418 in FIG. 4) at an angle that is beyond the critical angle as defined by Eqn 1.

$$\text{Critical angle} = \arcsin(1/n)$$

Eqn 1

Where the critical angle is the angle beyond which the illumination light is reflected from the internal surface when the internal surface comprises an interface from a solid with a higher refractive index (n) to air with a refractive index of 1 (e.g. for an interface of acrylic, with a refractive index of n=1.5, to air, the critical angle is 41.8 degrees; for an interface of polycarbonate, with a refractive index of n=1.59, to air the critical angle is 38.9 degrees). Consequently, the TIR wedge 418 is associated with a thin air gap 408 along the internal surface to create an interface between a solid with a higher refractive index and air. By choosing the angle of the light source 404 relative to the DLP 402 in correspondence to the angle of the internal surface of the TIR wedge 418, illumination light is turned toward the DLP 402 at an angle suitable for providing image light 414 as reflected from "on" pixels. Wherein, the illumination light is provided to the DLP 402 at approximately twice the angle of the pixel mirrors in the DLP 402 that are in the "on" state, such that after reflecting from the pixel mirrors, the image light 414 is directed generally along the optical axis of the field lens. Depending on the state of the DLP pixels, the illumination light from "on" pixels may be reflected as image light 414 which is directed towards a field lens and a lower optical module 204, while illumination light reflected from "off" pixels (generally referred to herein as "dark" state light, "off" pixel light or "off" state light) 410 is directed in a separate direction, which may be trapped and not used for the image that is ultimately presented to the wearer's eye.

The light trap for the dark state light 410 may be located along the optical axis defined by the direction of the dark state light 410 and in the side of the housing, with the function of absorbing the dark state light. To this end, the light trap may be comprised of an area outside of the cone of image light 414 from the "on" pixels. The light trap is typically made up of materials that absorb light including coatings of black paints or other light absorbing materials to prevent light scattering from the dark state light degrading the image perceived by the user. In addition, the light trap may be recessed into the wall of the housing or include masks or guards to block scattered light and prevent the light trap from being viewed adjacent to the displayed image.

The embodiment of FIG. 4 also includes a corrective wedge 420 to correct the effect of refraction of the image light 414 as it exits the TIR wedge 418. By including the corrective wedge 420 and providing a thin air gap 408 (e.g. 25 micron), the image light from the "on" pixels can be maintained generally in a direction along the optical axis of the field lens (i.e. the same direction as that defined by the image light 414) so it passes into the field lens and the lower optical module 204. As shown in FIG. 4, the image light 414 from the "on" pixels exits the corrective wedge 420 generally perpendicular to the surface of the corrective wedge 420 while the dark state light exits at an oblique angle. As a result, the direction of the image light 414 from the "on" pixels is largely unaffected by refraction as it exits from the surface of the corrective wedge 420. In contrast, the dark state light 410 is substantially changed in direction by refraction when the dark state light 410 exits the corrective wedge 420.

The embodiment illustrated in FIG. 4 has the similar advantages of those discussed in connection with the embodiment of FIG. 3b. The dimensions and weight of the upper module 202 depicted in FIG. 4 may be approximately 8x8 mm with a weight of less than 3 grams. A difference in overall performance between the configuration illustrated in FIG. 3b and the configuration illustrated in FIG. 4 is that the embodiment of FIG. 4 doesn't require the use of polarized light as supplied by the light source 404. This can be an advantage in some situations as will be discussed in more detail below (e.g. increased see-through transparency of the HWC optics from the user's perspective). Polarized light may be used in connection with the embodiment depicted in FIG. 4, in embodiments. An additional advantage of the embodiment of FIG. 4 compared to the embodiment shown in FIG. 3b is that the dark state light (shown as DLP off light 410) is directed at a steeper angle away from the optical axis of the image light 414 due to the added refraction encountered when the dark state light 410 exits the corrective wedge 420. This steeper angle of the dark state light 410 allows for the light trap to be positioned closer to the DLP 402 so that the overall size of the upper module 202 can be reduced. The light trap can also be made larger since the light trap doesn't interfere with the field lens, thereby the efficiency of the light trap can be increased and as a result, stray light can be reduced and the contrast of the image perceived by the user can be increased. FIG. 4a illustrates the embodiment described in connection with FIG. 4 with an example set of corresponding angles at the various surfaces with the reflected angles of a ray of light passing through the upper optical module 202. In this example, the DLP mirrors are provided at 17 degrees to the surface of the DLP device. The angles of the TIR wedge are selected in correspondence to one another to provide TIR reflected illumination light at the correct angle for the DLP mirrors while allowing the

image light and dark state light to pass through the thin air gap, various combinations of angles are possible to achieve this.

FIG. 5 illustrates yet another embodiment of an upper optical module 202 in accordance with the principles of the present invention. As with the embodiment shown in FIG. 4, the embodiment shown in FIG. 5 does not require the use of polarized light. Polarized light may be used in connection with this embodiment, but it is not required. The optical module 202 depicted in FIG. 5 is similar to that presented in connection with FIG. 4; however, the embodiment of FIG. 5 includes an off light redirection wedge 502. As can be seen from the illustration, the off light redirection wedge 502 allows the image light 414 to continue generally along the optical axis toward the field lens and into the lower optical module 204 (as illustrated). However, the off light 504 is redirected substantially toward the side of the corrective wedge 420 where it passes into the light trap. This configuration may allow further height compactness in the HWC because the light trap (not illustrated) that is intended to absorb the off light 504 can be positioned laterally adjacent the upper optical module 202 as opposed to below it. In the embodiment depicted in FIG. 5 there is a thin air gap between the TIR wedge 418 and the corrective wedge 420 (similar to the embodiment of FIG. 4). There is also a thin air gap between the corrective wedge 420 and the off light redirection wedge 502. There may be HWC mechanical configurations that warrant the positioning of a light trap for the dark state light elsewhere and the illustration depicted in FIG. 5 should be considered illustrative of the concept that the off light can be redirected to create compactness of the overall HWC. FIG. 5a illustrates an example of the embodiment described in connection with FIG. 5 with the addition of more details on the relative angles at the various surfaces and a light ray trace for image light and a light ray trace for dark light are shown as it passes through the upper optical module 202. Again, various combinations of angles are possible.

FIG. 4b shows an illustration of a further embodiment in which a solid transparent matched set of wedges 456 is provided with a reflective polarizer 450 at the interface between the wedges. Wherein the interface between the wedges in the wedge set 456 is provided at an angle so that illumination light 452 from the polarized light source 458 is reflected at the proper angle (e.g. 34 degrees for a 17 degree DLP mirror) for the DLP mirror "on" state so that the reflected image light 414 is provided along the optical axis of the field lens. The general geometry of the wedges in the wedge set 456 is similar to that shown in FIGS. 4 and 4a. A quarter wave film 454 is provided on the DLP 402 surface so that the illumination light 452 is one polarization state (e.g. S polarization state) while in passing through the quarter wave film 454, reflecting from the DLP mirror and passing back through the quarter wave film 454, the image light 414 is converted to the other polarization state (e.g. P polarization state). The reflective polarizer is oriented such that the illumination light 452 with its polarization state is reflected and the image light 414 with its other polarization state is transmitted. Since the dark state light from the "off" pixels 410 also passes through the quarter wave film 454 twice, it is also the other polarization state (e.g. P polarization state) so that it is transmitted by the reflective polarizer 450.

The angles of the faces of the wedge set 450 correspond to the needed angles to provide illumination light 452 at the angle needed by the DLP mirrors when in the "on" state so that the reflected image light 414 is reflected from the DLP

along the optical axis of the field lens. The wedge set 456 provides an interior interface where a reflective polarizer film can be located to redirect the illumination light 452 toward the mirrors of the DLP 402. The wedge set also provides a matched wedge on the opposite side of the reflective polarizer 450 so that the image light 414 from the "on" pixels exits the wedge set 450 substantially perpendicular to the exit surface, while the dark state light from the "off" pixels 410 exits at an oblique angle to the exit surface. As a result, the image light 414 is substantially unrefracted upon exiting the wedge set 456, while the dark state light from the "off" pixels 410 is substantially refracted upon exiting the wedge set 456 as shown in FIG. 4b.

By providing a solid transparent matched wedge set, the flatness of the interface is reduced, because variations in the flatness have a negligible effect as long as they are within the cone angle of the illuminating light 452. Which can be f# 2.2 with a 26 degree cone angle. In a preferred embodiment, the reflective polarizer is bonded between the matched internal surfaces of the wedge set 456 using an optical adhesive so that Fresnel reflections at the interfaces on either side of the reflective polarizer 450 are reduced. The optical adhesive can be matched in refractive index to the material of the wedge set 456 and the pieces of the wedge set 456 can be all made from the same material such as BK7 glass or cast acrylic. Wherein the wedge material can be selected to have low birefringence as well to reduce non-uniformities in brightness. The wedge set 456 and the quarter wave film 454 can also be bonded to the DLP 402 to further reduce Fresnel reflections at the DLP interface losses. In addition, since the image light 414 is substantially normal to the exit surface of the wedge set 456, the flatness of the surface is not critical to maintain the wavefront of the image light 414 so that high image quality can be obtained in the displayed image without requiring very tightly toleranced flatness on the exit surface.

A yet further embodiment of the invention that is not illustrated, combines the embodiments illustrated in FIG. 4b and FIG. 5. In this embodiment, the wedge set 456 is comprised of three wedges with the general geometry of the wedges in the wedge set corresponding to that shown in FIGS. 5 and 5a. A reflective polarizer is bonded between the first and second wedges similar to that shown in FIG. 4b, however, a third wedge is provided similar to the embodiment of FIG. 5. Wherein there is an angled thin air gap between the second and third wedges so that the dark state light is reflected by TIR toward the side of the second wedge where it is absorbed in a light trap. This embodiment, like the embodiment shown in FIG. 4b, uses a polarized light source as has been previously described. The difference in this embodiment is that the image light is transmitted through the reflective polarizer and is transmitted through the angled thin air gap so that it exits normal to the exit surface of the third wedge.

FIG. 5b illustrates an upper optical module 202 with a dark light trap 514a. As described in connection with FIGS. 4 and 4a, image light can be generated from a DLP when using a TIR and corrective lens configuration. The upper module may be mounted in a HWC housing 510 and the housing 510 may include a dark light trap 514a. The dark light trap 514a is generally positioned/constructed/formed in a position that is optically aligned with the dark light optical axis 512. As illustrated, the dark light trap may have depth such that the trap internally reflects dark light in an attempt to further absorb the light and prevent the dark light from combining with the image light that passes through the field lens. The dark light trap may be of a shape and depth such

that it absorbs the dark light. In addition, the dark light trap **514b**, in embodiments, may be made of light absorbing materials or coated with light absorbing materials. In embodiments, the recessed light trap **514a** may include baffles to block a view of the dark state light. This may be combined with black surfaces and textured or fibrous surfaces to help absorb the light. The baffles can be part of the light trap, associated with the housing, or field lens, etc.

FIG. **5c** illustrates another embodiment with a light trap **514b**. As can be seen in the illustration, the shape of the trap is configured to enhance internal reflections within the light trap **514b** to increase the absorption of the dark light **512**. FIG. **5d** illustrates another embodiment with a light trap **514c**. As can be seen in the illustration, the shape of the trap **514c** is configured to enhance internal reflections to increase the absorption of the dark light **512**.

FIG. **5e** illustrates another embodiment of an upper optical module **202** with a dark light trap **514d**. This embodiment of upper module **202** includes an off light reflection wedge **502**, as illustrated and described in connection with the embodiment of FIGS. **5** and **5a**. As can be seen in FIG. **5e**, the light trap **514d** is positioned along the optical path of the dark light **512**. The dark light trap **514d** may be configured as described in other embodiments herein. The embodiment of the light trap **514d** illustrated in FIG. **5e** includes a black area on the side wall of the wedge, wherein the side wall is located substantially away from the optical axis of the image light **414**. In addition, baffles **5252** may be added to one or more edges of the field lens **312** to block the view of the light trap **514d** adjacent to the displayed image seen by the user.

FIG. **6** illustrates a combination of an upper optical module **202** with a lower optical module **204**. In this embodiment, the image light projected from the upper optical module **202** may or may not be polarized. The image light is reflected off a flat combiner element **602** such that it is directed towards the user's eye. Wherein, the combiner element **602** is a partial mirror that reflects image light while transmitting a substantial portion of light from the environment so the user can look through the combiner element and see the environment surrounding the HWC.

The combiner **602** may include a holographic pattern, to form a holographic mirror. If a monochrome image is desired, there may be a single wavelength reflection design for the holographic pattern on the surface of the combiner **602**. If the intention is to have multiple colors reflected from the surface of the combiner **602**, a multiple wavelength holographic mirror may be included on the combiner surface. For example, in a three-color embodiment, where red, green and blue pixels are generated in the image light, the holographic mirror may be reflective to wavelengths substantially matching the wavelengths of the red, green and blue light provided by the light source. This configuration can be used as a wavelength specific mirror where pre-determined wavelengths of light from the image light are reflected to the user's eye. This configuration may also be made such that substantially all other wavelengths in the visible pass through the combiner element **602** so the user has a substantially clear view of the surroundings when looking through the combiner element **602**. The transparency between the user's eye and the surrounding may be approximately 80% when using a combiner that is a holographic mirror. Wherein holographic mirrors can be made using lasers to produce interference patterns in the holographic material of the combiner where the wavelengths of the lasers correspond to the wavelengths of light that are subsequently reflected by the holographic mirror.

In another embodiment, the combiner element **602** may include a notch mirror comprised of a multilayer coated substrate wherein the coating is designed to substantially reflect the wavelengths of light provided by the light source and substantially transmit the remaining wavelengths in the visible spectrum. For example, in the case where red, green and blue light is provided by the light source to enable full color images to be provided to the user, the notch mirror is a tristimulus notch mirror wherein the multilayer coating is designed to reflect narrow bands of red, green and blue light that are matched to the what is provided by the light source and the remaining visible wavelengths are transmitted through the coating to enable a view of the environment through the combiner. In another example where monochrome images are provided to the user, the notch mirror is designed to reflect a single narrow band of light that is matched to the wavelength range of the light provided by the light source while transmitting the remaining visible wavelengths to enable a see-thru view of the environment. The combiner **602** with the notch mirror would operate, from the user's perspective, in a manner similar to the combiner that includes a holographic pattern on the combiner element **602**. The combiner, with the tristimulus notch mirror, would reflect the "on" pixels to the eye because of the match between the reflective wavelengths of the notch mirror and the color of the image light, and the wearer would be able to see with high clarity the surroundings. The transparency between the user's eye and the surrounding may be approximately 80% when using the tristimulus notch mirror. In addition, the image provided by the upper optical module **202** with the notch mirror combiner can provide higher contrast images than the holographic mirror combiner due to less scattering of the imaging light by the combiner.

Light can escape through the combiner **602** and may produce face glow as the light is generally directed downward onto the cheek of the user. When using a holographic mirror combiner or a tristimulus notch mirror combiner, the escaping light can be trapped to avoid face glow. In embodiments, if the image light is polarized before the combiner, a linear polarizer can be laminated, or otherwise associated, to the combiner, with the transmission axis of the polarizer oriented relative to the polarized image light so that any escaping image light is absorbed by the polarizer. In embodiments, the image light would be polarized to provide S polarized light to the combiner for better reflection. As a result, the linear polarizer on the combiner would be oriented to absorb S polarized light and pass P polarized light. This provides the preferred orientation of polarized sunglasses as well.

If the image light is unpolarized, a microlouvered film such as a privacy filter can be used to absorb the escaping image light while providing the user with a see-thru view of the environment. In this case, the absorbance or transmittance of the microlouvered film is dependent on the angle of the light. Where steep angle light is absorbed and light at less of an angle is transmitted. For this reason, in an embodiment, the combiner with the microlouver film is angled at greater than 45 degrees to the optical axis of the image light (e.g. the combiner can be oriented at 50 degrees so the image light from the file lens is incident on the combiner at an oblique angle).

FIG. **7** illustrates an embodiment of a combiner element **602** at various angles when the combiner element **602** includes a holographic mirror. Normally, a mirrored surface reflects light at an angle equal to the angle that the light is incident to the mirrored surface. Typically, this necessitates that the combiner element be at 45 degrees, **602a**, if the light

is presented vertically to the combiner so the light can be reflected horizontally towards the wearer's eye. In embodiments, the incident light can be presented at angles other than vertical to enable the mirror surface to be oriented at other than 45 degrees, but in all cases wherein a mirrored surface is employed (including the tristimulus notch mirror described previously), the incident angle equals the reflected angle. As a result, increasing the angle of the combiner **602a** requires that the incident image light be presented to the combiner **602a** at a different angle which positions the upper optical module **202** to the left of the combiner as shown in FIG. 7. In contrast, a holographic mirror combiner, included in embodiments, can be made such that light is reflected at a different angle from the angle that the light is incident onto the holographic mirrored surface. This allows freedom to select the angle of the combiner element **602b** independent of the angle of the incident image light and the angle of the light reflected into the wearer's eye. In embodiments, the angle of the combiner element **602b** is greater than 45 degrees (shown in FIG. 7) as this allows a more laterally compact HWC design. The increased angle of the combiner element **602b** decreases the front to back width of the lower optical module **204** and may allow for a thinner HWC display (i.e. the furthest element from the wearer's eye can be closer to the wearer's face).

FIG. 8 illustrates another embodiment of a lower optical module **204**. In this embodiment, polarized image light provided by the upper optical module **202**, is directed into the lower optical module **204**. The image light reflects off a polarized mirror **804** and is directed to a focusing partially reflective mirror **802**, which is adapted to reflect the polarized light. An optical element such as a $\frac{1}{4}$ wave film located between the polarized mirror **804** and the partially reflective mirror **802**, is used to change the polarization state of the image light such that the light reflected by the partially reflective mirror **802** is transmitted by the polarized mirror **804** to present image light to the eye of the wearer. The user can also see through the polarized mirror **804** and the partially reflective mirror **802** to see the surrounding environment. As a result, the user perceives a combined image comprised of the displayed image light overlaid onto the see-thru view of the environment.

While many of the embodiments of the present invention have been referred to as upper and lower modules containing certain optical components, it should be understood that the image light and dark light production and management functions described in connection with the upper module may be arranged to direct light in other directions (e.g. upward, sideward, etc.). In embodiments, it may be preferred to mount the upper module **202** above the wearer's eye, in which case the image light would be directed downward. In other embodiments it may be preferred to produce light from the side of the wearer's eye, or from below the wearer's eye. In addition, the lower optical module is generally configured to deliver the image light to the wearer's eye and allow the wearer to see through the lower optical module, which may be accomplished through a variety of optical components.

FIG. 8a illustrates an embodiment of the present invention where the upper optical module **202** is arranged to direct image light into a TIR waveguide **810**. In this embodiment, the upper optical module **202** is positioned above the wearer's eye **812** and the light is directed horizontally into the TIR waveguide **810**. The TIR waveguide is designed to internally reflect the image light in a series of downward TIR reflections until it reaches the portion in front of the wearer's eye, where the light passes out of the TIR waveguide **812**

into the wearer's eye. In this embodiment, an outer shield **814** is positioned in front of the TIR waveguide **810**.

FIG. 8b illustrates an embodiment of the present invention where the upper optical module **202** is arranged to direct image light into a TIR waveguide **818**. In this embodiment, the upper optical module **202** is arranged on the side of the TIR waveguide **818**. For example, the upper optical module may be positioned in the arm or near the arm of the HWC when configured as a pair of head worn glasses. The TIR waveguide **818** is designed to internally reflect the image light in a series of TIR reflections until it reaches the portion in front of the wearer's eye, where the light passes out of the TIR waveguide **812** into the wearer's eye.

FIG. 8c illustrates yet further embodiments of the present invention where an upper optical module **202** is directing polarized image light into an optical guide **828** where the image light passes through a polarized reflector **824**, changes polarization state upon reflection of the optical element **822** which includes a $\frac{1}{4}$ wave film for example and then is reflected by the polarized reflector **824** towards the wearer's eye, due to the change in polarization of the image light. The upper optical module **202** may be positioned to direct light to a mirror **820**, to position the upper optical module **202** laterally, in other embodiments, the upper optical module **202** may direct the image light directly towards the polarized reflector **824**. It should be understood that the present invention comprises other optical arrangements intended to direct image light into the wearer's eye.

Another aspect of the present invention relates to eye imaging. In embodiments, a camera is used in connection with an upper optical module **202** such that the wearer's eye can be imaged using pixels in the "off" state on the DLP. FIG. 9 illustrates a system where the eye imaging camera **802** is mounted and angled such that the field of view of the eye imaging camera **802** is redirected toward the wearer's eye by the mirror pixels of the DLP **402** that are in the "off" state. In this way, the eye imaging camera **802** can be used to image the wearer's eye along the same optical axis as the displayed image that is presented to the wearer. Wherein, image light that is presented to the wearer's eye illuminates the wearer's eye so that the eye can be imaged by the eye imaging camera **802**. In the process, the light reflected by the eye passes back through the optical train of the lower optical module **204** and a portion of the upper optical module to where the light is reflected by the "off" pixels of the DLP **402** toward the eye imaging camera **802**.

In embodiments, the eye imaging camera may image the wearer's eye at a moment in time where there are enough "off" pixels to achieve the required eye image resolution. In another embodiment, the eye imaging camera collects eye image information from "off" pixels over time and forms a time lapsed image. In another embodiment, a modified image is presented to the user wherein enough "off" state pixels are included that the camera can obtain the desired resolution and brightness for imaging the wearer's eye and the eye image capture is synchronized with the presentation of the modified image.

The eye imaging system may be used for security systems. The HWC may not allow access to the HWC or other system if the eye is not recognized (e.g. through eye characteristics including retina or iris characteristics, etc.). The HWC may be used to provide constant security access in some embodiments. For example, the eye security confirmation may be a continuous, near-continuous, real-time, quasi real-time, periodic, etc. process so the wearer is effectively constantly being verified as known. In embodi-

ments, the HWC may be worn and eye security tracked for access to other computer systems.

The eye imaging system may be used for control of the HWC. For example, a blink, wink, or particular eye movement may be used as a control mechanism for a software application operating on the HWC or associated device.

The eye imaging system may be used in a process that determines how or when the HWC **102** delivers digitally displayed content to the wearer. For example, the eye imaging system may determine that the user is looking in a direction and then HWC may change the resolution in an area of the display or provide some content that is associated with something in the environment that the user may be looking at. Alternatively, the eye imaging system may identify different user's and change the displayed content or enabled features provided to the user. User's may be identified from a database of users eye characteristics either located on the HWC **102** or remotely located on the network **110** or on a server **112**. In addition, the HWC may identify a primary user or a group of primary users from eye characteristics wherein the primary user(s) are provided with an enhanced set of features and all other user's are provided with a different set of features. Thus in this use case, the HWC **102** uses identified eye characteristics to either enable features or not and eye characteristics need only be analyzed in comparison to a relatively small database of individual eye characteristics.

FIG. **10** illustrates a light source that may be used in association with the upper optics module **202** (e.g. polarized light source if the light from the solid state light source is polarized such as polarized light source **302** and **458**), and light source **404**. In embodiments, to provide a uniform surface of light **1008** to be directed into the upper optical module **202** and towards the DLP of the upper optical module, either directly or indirectly, the solid state light source **1002** may be projected into a backlighting optical system **1004**. The solid state light source **1002** may be one or more LEDs, laser diodes, OLEDs. In embodiments, the backlighting optical system **1004** includes an extended section with a length/distance ratio of greater than 3, wherein the light undergoes multiple reflections from the sidewalls to mix of homogenize the light as supplied by the solid state light source **1002**. The backlighting optical system **1004** can also include structures on the surface opposite (on the left side as shown in FIG. **10**) to where the uniform light **1008** exits the backlight **1004** to change the direction of the light toward the DLP **302** and the reflective polarizer **310** or the DLP **402** and the TIR wedge **418**. The backlighting optical system **1004** may also include structures to collimate the uniform light **1008** to provide light to the DLP with a smaller angular distribution or narrower cone angle. Diffusers or polarizers can be used on the entrance or exit surface of the backlighting optical system. Diffusers can be used to spread or uniformize the exiting light from the backlight to improve the uniformity or increase the angular spread of the uniform light **1008**. Elliptical diffusers that diffuse the light more in some directions and less in others can be used to improve the uniformity or spread of the uniform light **1008** in directions orthogonal to the optical axis of the uniform light **1008**. Linear polarizers can be used to convert unpolarized light as supplied by the solid state light source **1002** to polarized light so the uniform light **1008** is polarized with a desired polarization state. A reflective polarizer can be used on the exit surface of the backlight **1004** to polarize the uniform light **1008** to the desired polarization state, while reflecting the other polarization state back into the backlight where it is recycled by multiple reflections within the backlight **1004**

and at the solid state light source **1002**. Therefore by including a reflective polarizer at the exit surface of the backlight **1004**, the efficiency of the polarized light source is improved.

FIGS. **10a** and **10b** show illustrations of structures in backlight optical systems **1004** that can be used to change the direction of the light provided to the entrance face **1045** by the light source and then collimates the light in a direction lateral to the optical axis of the exiting uniform light **1008**. Structure **1060** includes an angled sawtooth pattern in a transparent waveguide wherein the left edge of each sawtooth clips the steep angle rays of light thereby limiting the angle of the light being redirected. The steep surface at the right (as shown) of each sawtooth then redirects the light so that it reflects off the left angled surface of each sawtooth and is directed toward the exit surface **1040**. The sawtooth surfaces shown on the lower surface in FIGS. **10a** and **10b**, can be smooth and coated (e.g. with an aluminum coating or a dielectric mirror coating) to provide a high level of reflectivity without scattering. Structure **1050** includes a curved face on the left side (as shown) to focus the rays after they pass through the exit surface **1040**, thereby providing a mechanism for collimating the uniform light **1008**. In a further embodiment, a diffuser can be provided between the solid state light source **1002** and the entrance face **1045** to homogenize the light provided by the solid state light source **1002**. In yet a further embodiment, a polarizer can be used between the diffuser and the entrance face **1045** of the backlight **1004** to provide a polarized light source. Because the sawtooth pattern provides smooth reflective surfaces, the polarization state of the light can be preserved from the entrance face **1045** to the exit face **1040**. In this embodiment, the light entering the backlight from the solid state light source **1002** passes through the polarizer so that it is polarized with the desired polarization state. If the polarizer is an absorptive linear polarizer, the light of the desired polarization state is transmitted while the light of the other polarization state is absorbed. If the polarizer is a reflective polarizer, the light of the desired polarization state is transmitted into the backlight **1004** while the light of the other polarization state is reflected back into the solid state light source **1002** where it can be recycled as previously described, to increase the efficiency of the polarized light source.

FIG. **11a** illustrates a light source **1100** that may be used in association with the upper optics module **202**. In embodiments, the light source **1100** may provide light to a backlighting optical system **1004** as described above in connection with FIG. **10**. In embodiments, the light source **1100** includes a tristimulus notch filter **1102**. The tristimulus notch filter **1102** has narrow band pass filters for three wavelengths, as indicated in FIG. **11c** in a transmission graph **1108**. The graph shown in FIG. **11b**, as **1104** illustrates an output of three different colored LEDs. One can see that the bandwidths of emission are narrow, but they have long tails. The tristimulus notch filter **1102** can be used in connection with such LEDs to provide a light source **1100** that emits narrow filtered wavelengths of light as shown in FIG. **11d** as the transmission graph **1110**. Wherein the clipping effects of the tristimulus notch filter **1102** can be seen to have cut the tails from the LED emission graph **1104** to provide narrower wavelength bands of light to the upper optical module **202**. The light source **1100** can be used in connection with a combiner **602** with a holographic mirror or tristimulus notch mirror to provide narrow bands of light that are reflected toward the wearer's eye with less waste light that does not

get reflected by the combiner, thereby improving efficiency and reducing escaping light that can cause faceglow.

FIG. 12a illustrates another light source 1200 that may be used in association with the upper optics module 202. In embodiments, the light source 1200 may provide light to a backlighting optical system 1004 as described above in connection with FIG. 10. In embodiments, the light source 1200 includes a quantum dot cover glass 1202. Where the quantum dots absorb light of a shorter wavelength and emit light of a longer wavelength (FIG. 12b shows an example wherein a UV spectrum 1202 applied to a quantum dot results in the quantum dot emitting a narrow band shown as a PL spectrum 1204) that is dependent on the material makeup and size of the quantum dot. As a result, quantum dots in the quantum dot cover glass 1202 can be tailored to provide one or more bands of narrow bandwidth light (e.g. red, green and blue emissions dependent on the different quantum dots included as illustrated in the graph shown in FIG. 12c where three different quantum dots are used. In embodiments, the LED driver light emits UV light, deep blue or blue light. For sequential illumination of different colors, multiple light sources 1200 would be used where each light source 1200 would include a quantum dot cover glass 1202 with a quantum dot selected to emit at one of the desired colors. The light source 1100 can be used in connection with a combiner 602 with a holographic mirror or tristimulus notch mirror to provide narrow transmission bands of light that are reflected toward the wearer's eye with less waste light that does not get reflected.

Another aspect of the present invention relates to the generation of peripheral image lighting effects for a person wearing a HWC. In embodiments, a solid state lighting system (e.g. LED, OLED, etc), or other lighting system, may be included inside the optical elements of an lower optical module 204. The solid state lighting system may be arranged such that lighting effects outside of a field of view (FOV) of the presented digital content is presented to create an immersive effect for the person wearing the HWC. To this end, the lighting effects may be presented to any portion of the HWC that is visible to the wearer. The solid state lighting system may be digitally controlled by an integrated processor on the HWC. In embodiments, the integrated processor will control the lighting effects in coordination with digital content that is presented within the FOV of the HWC. For example, a movie, picture, game, or other content, may be displayed or playing within the FOV of the HWC. The content may show a bomb blast on the right side of the FOV and at the same moment, the solid state lighting system inside of the upper module optics may flash quickly in concert with the FOV image effect. The effect may not be fast, it may be more persistent to indicate, for example, a general glow or color on one side of the user. The solid state lighting system may be color controlled, with red, green and blue LEDs, for example, such that color control can be coordinated with the digitally presented content within the field of view.

FIG. 13a illustrates optical components of a lower optical module 204 together with an outer lens 1302. FIG. 13a also shows an embodiment including effects LED's 1308a and 1308b. FIG. 13a illustrates image light 1312, as described herein elsewhere, directed into the upper optical module where it will reflect off of the combiner element 1304, as described herein elsewhere. The combiner element 1304 in this embodiment is angled towards the wearer's eye at the top of the module and away from the wearer's eye at the bottom of the module, as also illustrated and described in connection with FIG. 8 (e.g. at a 45 degree angle). The image light 1312 provided by an upper optical module 202

(not shown in FIG. 13a) reflects off of the combiner element 1304 towards the collimating mirror 1310, away from the wearer's eye, as described herein elsewhere. The image light 1312 then reflects and focuses off of the collimating mirror 1304, passes back through the combiner element 1304, and is directed into the wearer's eye. The wearer can also view the surrounding environment through the transparency of the combiner element 1304, collimating mirror 1310, and outer lens 1302 (if it is included). As described herein elsewhere, various surfaces are polarized to create the optical path for the image light and to provide transparency of the elements such that the wearer can view the surrounding environment. The wearer will generally perceive that the image light forms an image in the FOV 1305. In embodiments, the outer lens 1302 may be included. The outer lens 1302 is an outer lens that may or may not be corrective and it may be designed to conceal the lower optical module components in an effort to make the HWC appear to be in a form similar to standard glasses or sunglasses.

In the embodiment illustrated in FIG. 13a, the effects LEDs 1308a and 1308b are positioned at the sides of the combiner element 1304 and the outer lens 1302 and/or the collimating mirror 1310. In embodiments, the effects LEDs 1308a are positioned within the confines defined by the combiner element 1304 and the outer lens 1302 and/or the collimating mirror. The effects LEDs 1308a and 1308b are also positioned outside of the FOV 1305. In this arrangement, the effects LEDs 1308a and 1308b can provide lighting effects within the lower optical module outside of the FOV 1305. In embodiments the light emitted from the effects LEDs 1308a and 1308b may be polarized such that the light passes through the combiner element 1304 toward the wearer's eye and does not pass through the outer lens 1302 and/or the collimating mirror 1310. This arrangement provides peripheral lighting effects to the wearer in a more private setting by not transmitting the lighting effects through the front of the HWC into the surrounding environment. However, in other embodiments, the effects LEDs 1308a and 1308b may be unpolarized so the lighting effects provided are made to be purposefully viewable by others in the environment for entertainment such as giving the effect of the wearer's eye glowing in correspondence to the image content being viewed by the wearer.

FIG. 13b illustrates a cross section of the embodiment described in connection with FIG. 13a. As illustrated, the effects LED 1308a is located in the upper-front area inside of the optical components of the lower optical module. It should be understood that the effects LED 1308a position in the described embodiments is only illustrative and alternate placements are encompassed by the present invention. Additionally, in embodiments, there may be one or more effects LEDs 1308a in each of the two sides of HWC to provide peripheral lighting effects near one or both eyes of the wearer.

FIG. 13c illustrates an embodiment where the combiner element 1304 is angled away from the eye at the top and towards the eye at the bottom (e.g. in accordance with the holographic or notch filter embodiments described herein). In this embodiment, the effects LED 1308a is located on the outer lens 1302 side of the combiner element 1304 to provide a concealed appearance of the lighting effects. As with other embodiments, the effects LED 1308a of FIG. 13c may include a polarizer such that the emitted light can pass through a polarized element associated with the combiner element 1304 and be blocked by a polarized element associated with the outer lens 1302.

Another aspect of the present invention relates to the mitigation of light escaping from the space between the wearer's face and the HWC itself. Another aspect of the present invention relates to maintaining a controlled lighting environment in proximity to the wearer's eyes. In embodiments, both the maintenance of the lighting environment and the mitigation of light escape are accomplished by including a removable and replaceable flexible shield for the HWC. Wherein the removable and replaceable shield can be provided for one eye or both eyes in correspondence to the use of the displays for each eye. For example, in a night vision application, the display to only one eye could be used for night vision while the display to the other eye is turned off to provide good see-thru when moving between areas where visible light is available and dark areas where night vision enhancement is needed.

FIG. 14a illustrates a removable and replaceable flexible eye cover 1402 with an opening 1408 that can be attached and removed quickly from the HWC 102 through the use of magnets. Other attachment methods may be used, but for illustration of the present invention we will focus on a magnet implementation. In embodiments, magnets may be included in the eye cover 1402 and magnets of an opposite polarity may be included (e.g. embedded) in the frame of the HWC 102. The magnets of the two elements would attract quite strongly with the opposite polarity configuration. In another embodiment, one of the elements may have a magnet and the other side may have metal for the attraction. In embodiments, the eye cover 1402 is a flexible elastomeric shield. In embodiments, the eye cover 1402 may be an elastomeric bellows design to accommodate flexibility and more closely align with the wearer's face. FIG. 14b illustrates a removable and replaceable flexible eye cover 1404 that is adapted as a single eye cover. In embodiments, a single eye cover may be used for each side of the HWC to cover both eyes of the wearer. In embodiments, the single eye cover may be used in connection with a HWC that includes only one computer display for one eye. These configurations prevent light that is generated and directed generally towards the wearer's face by covering the space between the wearer's face and the HWC. The opening 1408 allows the wearer to look through the opening 1408 to view the displayed content and the surrounding environment through the front of the HWC. The image light in the lower optical module 204 can be prevented from emitting from the front of the HWC through internal optics polarization schemes, as described herein, for example.

FIG. 14c illustrates another embodiment of a light suppression system. In this embodiment, the eye cover 1410 may be similar to the eye cover 1402, but eye cover 1410 includes a front light shield 1412. The front light shield 1412 may be opaque to prevent light from escaping the front lens of the HWC. In other embodiments, the front light shield 1412 is polarized to prevent light from escaping the front lens. In a polarized arrangement, in embodiments, the internal optical elements of the HWC (e.g. of the lower optical module 204) may polarize light transmitted towards the front of the HWC and the front light shield 1412 may be polarized to prevent the light from transmitting through the front light shield 1412.

In embodiments, an opaque front light shield 1412 may be included and the digital content may include images of the surrounding environment such that the wearer can visualize the surrounding environment. One eye may be presented with night vision environmental imagery and this eye's surrounding environment optical path may be covered using

an opaque front light shield 1412. In other embodiments, this arrangement may be associated with both eyes.

Another aspect of the present invention relates to automatically configuring the lighting system(s) used in the HWC 102. In embodiments, the display lighting and/or effects lighting, as described herein, may be controlled in a manner suitable for when an eye cover 1408 is attached or removed from the HWC 102. For example, at night, when the light in the environment is low, the lighting system(s) in the HWC may go into a low light mode to further control any amounts of stray light escaping from the HWC and the areas around the HWC. Covert operations at night, while using night vision or standard vision, may require a solution which prevents as much escaping light as possible so a user may clip on the eye cover(s) 1408 and then the HWC may go into a low light mode. The low light mode may, in some embodiments, only go into a low light mode when the eye cover 1408 is attached if the HWC identifies that the environment is in low light conditions (e.g. through environment light level sensor detection). In embodiments, the low light level may be determined to be at an intermediate point between full and low light dependent on environmental conditions.

Another aspect of the present invention relates to automatically controlling the type of content displayed in the HWC when eye covers 1408 are attached or removed from the HWC. In embodiments, when the eye cover(s) 1408 is attached to the HWC, the displayed content may be restricted in amount or in color amounts. For example, the display(s) may go into a simple content delivery mode to restrict the amount of information displayed. This may be done to reduce the amount of light produced by the display(s). In an embodiment, the display(s) may change from color displays to monochrome displays to reduce the amount of light produced. In an embodiment, the monochrome lighting may be red to limit the impact on the wearer's eyes to maintain an ability to see better in the dark.

Referring to FIG. 15, we now turn to describe a particular external user interface 104, referred to generally as a pen 1500. The pen 1500 is a specially designed external user interface 104 and can operate as a user interface, such as to many different styles of HWC 102. The pen 1500 generally follows the form of a conventional pen, which is a familiar user handled device and creates an intuitive physical interface for many of the operations to be carried out in the HWC system 100. The pen 1500 may be one of several user interfaces 104 used in connection with controlling operations within the HWC system 100. For example, the HWC 102 may watch for and interpret hand gestures 116 as control signals, where the pen 1500 may also be used as a user interface with the same HWC 102. Similarly, a remote keyboard may be used as an external user interface 104 in concert with the pen 1500. The combination of user interfaces or the use of just one control system generally depends on the operation(s) being executed in the HWC's system 100.

While the pen 1500 may follow the general form of a conventional pen, it contains numerous technologies that enable it to function as an external user interface 104. FIG. 15 illustrates technologies comprised in the pen 1500. As can be seen, the pen 1500 may include a camera 1508, which is arranged to view through lens 1502. The camera may then be focused, such as through lens 1502, to image a surface upon which a user is writing or making other movements to interact with the HWC 102. There are situations where the pen 1500 will also have an ink, graphite, or other system such that what is being written can be seen on the writing

surface. There are other situations where the pen 1500 does not have such a physical writing system so there is no deposit on the writing surface, where the pen would only be communicating data or commands to the HWC 102. The lens configuration is described in greater detail herein. The function of the camera is to capture information from an unstructured writing surface such that pen strokes can be interpreted as intended by the user. To assist in the predication of the intended stroke path, the pen 1500 may include a sensor, such as an IMU 1512. Of course, the IMU could be included in the pen 1500 in its separate parts (e.g. gyro, accelerometer, etc.) or an IMU could be included as a single unit. In this instance, the IMU 1512 is used to measure and predict the motion of the pen 1500. In turn, the integrated microprocessor 1510 would take the IMU information and camera information as inputs and process the information to form a prediction of the pen tip movement.

The pen 1500 may also include a pressure monitoring system 1504, such as to measure the pressure exerted on the lens 1502. As will be described in greater detail herein, the pressure measurement can be used to predict the user's intention for changing the weight of a line, type of a line, type of brush, click, double click, and the like. In embodiments, the pressure sensor may be constructed using any force or pressure measurement sensor located behind the lens 1502, including for example, a resistive sensor, a current sensor, a capacitive sensor, a voltage sensor such as a piezoelectric sensor, and the like.

The pen 1500 may also include a communications module 1518, such as for bi-directional communication with the HWC 102. In embodiments, the communications module 1518 may be a short distance communication module (e.g. Bluetooth). The communications module 1518 may be security matched to the HWC 102. The communications module 1518 may be arranged to communicate data and commands to and from the microprocessor 1510 of the pen 1500. The microprocessor 1510 may be programmed to interpret data generated from the camera 1508, IMU 1512, and pressure sensor 1504, and the like, and then pass a command onto the HWC 102 through the communications module 1518, for example. In another embodiment, the data collected from any of the input sources (e.g. camera 1508, IMU 1512, pressure sensor 1504) by the microprocessor may be communicated by the communication module 1518 to the HWC 102, and the HWC 102 may perform data processing and prediction of the user's intention when using the pen 1500. In yet another embodiment, the data may be further passed on through a network 110 to a remote device 112, such as a server, for the data processing and prediction. The commands may then be communicated back to the HWC 102 for execution (e.g. display writing in the glasses display, make a selection within the UI of the glasses display, control a remote external device 112, control a local external device 108), and the like. The pen may also include memory 1514 for long or short term uses.

The pen 1500 may also include a number of physical user interfaces, such as quick launch buttons 1522, a touch sensor 1520, and the like. The quick launch buttons 1522 may be adapted to provide the user with a fast way of jumping to a software application in the HWC system 100. For example, the user may be a frequent user of communication software packages (e.g. email, text, Twitter, Instagram, Facebook, Google+, and the like), and the user may program a quick launch button 1522 to command the HWC 102 to launch an application. The pen 1500 may be provided with several quick launch buttons 1522, which may be user programmable or factory programmable. The quick launch button

1522 may be programmed to perform an operation. For example, one of the buttons may be programmed to clear the digital display of the HWC 102. This would create a fast way for the user to clear the screens on the HWC 102 for any reason, such as for example to better view the environment. The quick launch button functionality will be discussed in further detail below. The touch sensor 1520 may be used to take gesture style input from the user. For example, the user may be able to take a single finger and run it across the touch sensor 1520 to affect a page scroll.

The pen 1500 may also include a laser pointer 1524. The laser pointer 1524 may be coordinated with the IMU 1512 to coordinate gestures and laser pointing. For example, a user may use the laser 1524 in a presentation to help with guiding the audience with the interpretation of graphics and the IMU 1512 may, either simultaneously or when the laser 1524 is off, interpret the user's gestures as commands or data input.

FIGS. 16A-C illustrate several embodiments of lens and camera arrangements 1600 for the pen 1500. One aspect relates to maintaining a constant distance between the camera and the writing surface to enable the writing surface to be kept in focus for better tracking of movements of the pen 1500 over the writing surface. Another aspect relates to maintaining an angled surface following the circumference of the writing tip of the pen 1500 such that the pen 1500 can be rolled or partially rolled in the user's hand to create the feel and freedom of a conventional writing instrument.

FIG. 16A illustrates an embodiment of the writing lens end of the pen 1500. The configuration includes a ball lens 1604, a camera or image capture surface 1602, and a domed cover lens 1608. In this arrangement, the camera views the writing surface through the ball lens 1604 and dome cover lens 1608. The ball lens 1604 causes the camera to focus such that the camera views the writing surface when the pen 1500 is held in the hand in a natural writing position, such as with the pen 1500 in contact with a writing surface. In embodiments, the ball lens 1604 should be separated from the writing surface to obtain the highest resolution of the writing surface at the camera 1602. In embodiments, the ball lens 1604 is separated by approximately 1 to 3 mm. In this configuration, the domed cover lens 1608 provides a surface that can keep the ball lens 1604 separated from the writing surface at a constant distance, such as substantially independent of the angle used to write on the writing surface. For instance, in embodiments the field of view of the camera in this arrangement would be approximately 60 degrees.

The domed cover lens, or other lens 1608 used to physically interact with the writing surface, will be transparent or transmissive within the active bandwidth of the camera 1602. In embodiments, the domed cover lens 1608 may be spherical or other shape and comprised of glass, plastic, sapphire, diamond, and the like. In other embodiments where low resolution imaging of the surface is acceptable. The pen 1500 can omit the domed cover lens 1608 and the ball lens 1604 can be in direct contact with the surface.

FIG. 16B illustrates another structure where the construction is somewhat similar to that described in connection with FIG. 16A; however this embodiment does not use a dome cover lens 1608, but instead uses a spacer 1610 to maintain a predictable distance between the ball lens 1604 and the writing surface, wherein the spacer may be spherical, cylindrical, tubular or other shape that provides spacing while allowing for an image to be obtained by the camera 1602 through the lens 1604. In a preferred embodiment, the spacer 1610 is transparent. In addition, while the spacer 1610 is

shown as spherical, other shapes such as an oval, doughnut shape, half sphere, cone, cylinder or other form may be used.

FIG. 16C illustrates yet another embodiment, where the structure includes a post 1614, such as running through the center of the lensed end of the pen 1500. The post 1614 may be an ink deposition system (e.g. ink cartridge), graphite deposition system (e.g. graphite holder), or a dummy post whose purpose is mainly only that of alignment. The selection of the post type is dependent on the pen's use. For instance, in the event the user wants to use the pen 1500 as a conventional ink depositing pen as well as a fully functional external user interface 104, the ink system post would be the best selection. If there is no need for the 'writing' to be visible on the writing surface, the selection would be the dummy post. The embodiment of FIG. 16C includes camera(s) 1602 and an associated lens 1612, where the camera 1602 and lens 1612 are positioned to capture the writing surface without substantial interference from the post 1614. In embodiments, the pen 1500 may include multiple cameras 1602 and lenses 1612 such that more or all of the circumference of the tip 1614 can be used as an input system. In an embodiment, the pen 1500 includes a contoured grip that keeps the pen aligned in the user's hand so that the camera 1602 and lens 1612 remains pointed at the surface.

Another aspect of the pen 1500 relates to sensing the force applied by the user to the writing surface with the pen 1500. The force measurement may be used in a number of ways. For example, the force measurement may be used as a discrete value, or discontinuous event tracking, and compared against a threshold in a process to determine a user's intent. The user may want the force interpreted as a 'click' in the selection of an object, for instance. The user may intend multiple force exertions interpreted as multiple clicks. There may be times when the user holds the pen 1500 in a certain position or holds a certain portion of the pen 1500 (e.g. a button or touch pad) while clicking to affect a certain operation (e.g. a 'right click'). In embodiments, the force measurement may be used to track force and force trends. The force trends may be tracked and compared to threshold limits, for example. There may be one such threshold limit, multiple limits, groups of related limits, and the like. For example, when the force measurement indicates a fairly constant force that generally falls within a range of related threshold values, the microprocessor 1510 may interpret the force trend as an indication that the user desires to maintain the current writing style, writing tip type, line weight, brush type, and the like. In the event that the force trend appears to have gone outside of a set of threshold values intentionally, the microprocessor may interpret the action as an indication that the user wants to change the current writing style, writing tip type, line weight, brush type, and the like. Once the microprocessor has made a determination of the user's intent, a change in the current writing style, writing tip type, line weight, brush type, and the like may be executed. In embodiments, the change may be noted to the user (e.g. in a display of the HWC 102), and the user may be presented with an opportunity to accept the change.

FIG. 17A illustrates an embodiment of a force sensing surface tip 1700 of a pen 1500. The force sensing surface tip 1700 comprises a surface connection tip 1702 (e.g. a lens as described herein elsewhere) in connection with a force or pressure monitoring system 1504. As a user uses the pen 1500 to write on a surface or simulate writing on a surface the force monitoring system 1504 measures the force or pressure the user applies to the writing surface and the force monitoring system communicates data to the microproces-

sor 1510 for processing. In this configuration, the microprocessor 1510 receives force data from the force monitoring system 1504 and processes the data to make predictions of the user's intent in applying the particular force that is currently being applied. In embodiments, the processing may be provided at a location other than on the pen (e.g. at a server in the HWC system 100, on the HWC 102). For clarity, when reference is made herein to processing information on the microprocessor 1510, the processing of information contemplates processing the information at a location other than on the pen. The microprocessor 1510 may be programmed with force threshold(s), force signature(s), force signature library and/or other characteristics intended to guide an inference program in determining the user's intentions based on the measured force or pressure. The microprocessor 1510 may be further programmed to make inferences from the force measurements as to whether the user has attempted to initiate a discrete action (e.g. a user interface selection 'click') or is performing a constant action (e.g. writing within a particular writing style). The inferring process is important as it causes the pen 1500 to act as an intuitive external user interface 104.

FIG. 17B illustrates a force 1708 versus time 1710 trend chart with a single threshold 1718. The threshold 1718 may be set at a level that indicates a discrete force exertion indicative of a user's desire to cause an action (e.g. select an object in a GUI). Event 1712, for example, may be interpreted as a click or selection command because the force quickly increased from below the threshold 1718 to above the threshold 1718. The event 1714 may be interpreted as a double click because the force quickly increased above the threshold 1718, decreased below the threshold 1718 and then essentially repeated quickly. The user may also cause the force to go above the threshold 1718 and hold for a period indicating that the user is intending to select an object in the GUI (e.g. a GUI presented in the display of the HWC 102) and 'hold' for a further operation (e.g. moving the object).

While a threshold value may be used to assist in the interpretation of the user's intention, a signature force event trend may also be used. The threshold and signature may be used in combination or either method may be used alone. For example, a single-click signature may be represented by a certain force trend signature or set of signatures. The single-click signature(s) may require that the trend meet a criteria of a rise time between x any y values, a hold time of between a and b values and a fall time of between c and d values, for example. Signatures may be stored for a variety of functions such as click, double click, right click, hold, move, etc. The microprocessor 1510 may compare the real-time force or pressure tracking against the signatures from a signature library to make a decision and issue a command to the software application executing in the GUI.

FIG. 17C illustrates a force 1708 versus time 1710 trend chart with multiple thresholds 1718. By way of example, the force trend is plotted on the chart with several pen force or pressure events. As noted, there are both presumably intentional events 1720 and presumably non-intentional events 1722. The two thresholds 1718 of FIG. 4C create three zones of force: a lower, middle and higher range. The beginning of the trend indicates that the user is placing a lower zone amount of force. This may mean that the user is writing with a given line weight and does not intend to change the weight, the user is writing. Then the trend shows a significant increase 1720 in force into the middle force range. This force change appears, from the trend to have been sudden and thereafter it is sustained. The microprocessor 1510 may

interpret this as an intentional change and as a result change the operation in accordance with preset rules (e.g. change line width, increase line weight, etc.). The trend then continues with a second apparently intentional event **1720** into the higher-force range. During the performance in the higher-force range, the force dips below the upper threshold **1718**. This may indicate an unintentional force change and the microprocessor may detect the change in range however not affect a change in the operations being coordinated by the pen **1500**. As indicated above, the trend analysis may be done with thresholds and/or signatures.

Generally, in the present disclosure, instrument stroke parameter changes may be referred to as a change in line type, line weight, tip type, brush type, brush width, brush pressure, color, and other forms of writing, coloring, painting, and the like.

Another aspect of the pen **1500** relates to selecting an operating mode for the pen **1500** dependent on contextual information and/or selection interface(s). The pen **1500** may have several operating modes. For instance, the pen **1500** may have a writing mode where the user interface(s) of the pen **1500** (e.g. the writing surface end, quick launch buttons **1522**, touch sensor **1520**, motion based gesture, and the like) is optimized or selected for tasks associated with writing. As another example, the pen **1500** may have a wand mode where the user interface(s) of the pen is optimized or selected for tasks associated with software or device control (e.g. the HWC **102**, external local device, remote device **112**, and the like). The pen **1500**, by way of another example, may have a presentation mode where the user interface(s) is optimized or selected to assist a user with giving a presentation (e.g. pointing with the laser pointer **1524** while using the button(s) **1522** and/or gestures to control the presentation or applications relating to the presentation). The pen may, for example, have a mode that is optimized or selected for a particular device that a user is attempting to control. The pen **1500** may have a number of other modes and an aspect of the present invention relates to selecting such modes.

FIG. **18A** illustrates an automatic user interface(s) mode selection based on contextual information. The microprocessor **1510** may be programmed with IMU thresholds **1814** and **1812**. The thresholds **1814** and **1812** may be used as indications of upper and lower bounds of an angle **1804** and **1802** of the pen **1500** for certain expected positions during certain predicted modes. When the microprocessor **1510** determines that the pen **1500** is being held or otherwise positioned within angles **1802** corresponding to writing thresholds **1814**, for example, the microprocessor **1510** may then institute a writing mode for the pen's user interfaces. Similarly, if the microprocessor **1510** determines (e.g. through the IMU **1512**) that the pen is being held at an angle **1804** that falls between the predetermined wand thresholds **1812**, the microprocessor may institute a wand mode for the pen's user interface. Both of these examples may be referred to as context based user interface mode selection as the mode selection is based on contextual information (e.g. position) collected automatically and then used through an automatic evaluation process to automatically select the pen's user interface(s) mode.

As with other examples presented herein, the microprocessor **1510** may monitor the contextual trend (e.g. the angle of the pen over time) in an effort to decide whether to stay in a mode or change modes. For example, through signatures, thresholds, trend analysis, and the like, the microprocessor may determine that a change is an unintentional change and therefore no user interface mode change is desired.

FIG. **18B** illustrates an automatic user interface(s) mode selection based on contextual information. In this example, the pen **1500** is monitoring (e.g. through its microprocessor) whether or not the camera at the writing surface end **1508** is imaging a writing surface in close proximity to the writing surface end of the pen **1500**. If the pen **1500** determines that a writing surface is within a predetermined relatively short distance, the pen **1500** may decide that a writing surface is present **1820** and the pen may go into a writing mode user interface(s) mode. In the event that the pen **1500** does not detect a relatively close writing surface **1822**, the pen may predict that the pen is not currently being used to as a writing instrument and the pen may go into a non-writing user interface(s) mode.

FIG. **18C** illustrates a manual user interface(s) mode selection. The user interface(s) mode may be selected based on a twist of a section **1824** of the pen **1500** housing, clicking an end button **1828**, pressing a quick launch button **1522**, interacting with touch sensor **1520**, detecting a predetermined action at the pressure monitoring system (e.g. a click), detecting a gesture (e.g. detected by the IMU), etc. The manual mode selection may involve selecting an item in a GUI associated with the pen **1500** (e.g. an image presented in the display of HWC **102**).

In embodiments, a confirmation selection may be presented to the user in the event a mode is going to change. The presentation may be physical (e.g. a vibration in the pen **1500**), through a GUI, through a light indicator, etc.

FIG. **19** illustrates a couple pen use-scenarios **1900** and **1901**. There are many use scenarios and we have presented a couple in connection with FIG. **19** as a way of illustrating use scenarios to further the understanding of the reader. As such, the use-scenarios should be considered illustrative and non-limiting.

Use scenario **1900** is a writing scenario where the pen **1500** is used as a writing instrument. In this example, quick launch button **122A** is pressed to launch a note application **1910** in the GUI **1908** of the HWC **102** display **1904**. Once the quick launch button **122A** is pressed, the HWC **102** launches the note program **1910** and puts the pen into a writing mode. The user uses the pen **1500** to scribe symbols **1902** on a writing surface, the pen records the scribing and transmits the scribing to the HWC **102** where symbols representing the scribing are displayed **1912** within the note application **1910**.

Use scenario **1901** is a gesture scenario where the pen **1500** is used as a gesture capture and command device. In this example, the quick launch button **122B** is activated and the pen **1500** activates a wand mode such that an application launched on the HWC **102** can be controlled. Here, the user sees an application chooser **1918** in the display(s) of the HWC **102** where different software applications can be chosen by the user. The user gestures (e.g. swipes, spins, turns, etc.) with the pen to cause the application chooser **1918** to move from application to application. Once the correct application is identified (e.g. highlighted) in the chooser **1918**, the user may gesture or click or otherwise interact with the pen **1500** such that the identified application is selected and launched. Once an application is launched, the wand mode may be used to scroll, rotate, change applications, select items, initiate processes, and the like, for example.

In an embodiment, the quick launch button **122A** may be activated and the HWC **102** may launch an application chooser presenting to the user a set of applications. For example, the quick launch button may launch a chooser to show all communication programs (e.g. SMS, Twitter, In-

stagram, Facebook, email, etc.) available for selection such that the user can select the program the user wants and then go into a writing mode. By way of further example, the launcher may bring up selections for various other groups that are related or categorized as generally being selected at a given time (e.g. Microsoft Office products, communication products, productivity products, note products, organizational products, and the like)

FIG. 20 illustrates yet another embodiment of the present invention. FIG. 2000 illustrates a watchband clip on controller 2000. The watchband clip on controller may be a controller used to control the HWC 102 or devices in the HWC system 100. The watchband clip on controller 2000 has a fastener 2018 (e.g. rotatable clip) that is mechanically adapted to attach to a watchband, as illustrated at 2004.

The watchband controller 2000 may have quick launch interfaces 2008 (e.g. to launch applications and choosers as described herein), a touch pad 2014 (e.g. to be used as a touch style mouse for GUI control in a HWC 102 display) and a display 2012. The clip 2018 may be adapted to fit a wide range of watchbands so it can be used in connection with a watch that is independently selected for its function. The clip, in embodiments, is rotatable such that a user can position it in a desirable manner. In embodiments the clip may be a flexible strap. In embodiments, the flexible strap may be adapted to be stretched to attach to a hand, wrist, finger, device, weapon, and the like.

In embodiments, the watchband controller may be configured as a removable and replaceable watchband. For example, the controller may be incorporated into a band with a certain width, segment spacing's, etc. such that the watchband, with its incorporated controller, can be attached to a watch body. The attachment, in embodiments, may be mechanically adapted to attach with a pin upon which the watchband rotates. In embodiments, the watchband controller may be electrically connected to the watch and/or watch body such that the watch, watch body and/or the watchband controller can communicate data between them.

The watchband controller may have 3-axis motion monitoring (e.g. through an IMU, accelerometers, magnetometers, gyroscopes, etc.) to capture user motion. The user motion may then be interpreted for gesture control.

In embodiments, the watchband controller may comprise fitness sensors and a fitness computer. The sensors may track heart rate, calories burned, strides, distance covered, and the like. The data may then be compared against performance goals and/or standards for user feedback.

Another aspect of the present invention relates to visual display techniques relating to micro Doppler ("mD") target tracking signatures ("mD signatures"). mD is a radar technique that uses a series of angle dependent electromagnetic pulses that are broadcast into an environment and return pulses are captured. Changes between the broadcast pulse and return pulse are indicative of changes in the shape, distance and angular location of objects or targets in the environment. These changes provide signals that can be used to track a target and identify the target through the mD signature. Each target or target type has a unique mD signature. Shifts in the radar pattern can be analyzed in the time domain and frequency domain based on mD techniques to derive information about the types of targets present (e.g. whether people are present), the motion of the targets and the relative angular location of the targets and the distance to the targets. By selecting a frequency used for the mD pulse relative to known objects in the environment, the pulse can penetrate the known objects to enable information about targets to be gathered even when the targets are visually

blocked by the known objects. For example, pulse frequencies can be used that will penetrate concrete buildings to enable people to be identified inside the building. Multiple pulse frequencies can be used as well in the mD radar to enable different types of information to be gathered about the objects in the environment. In addition, the mD radar information can be combined with other information such as distance measurements or images captured of the environment that are analyzed jointly to provide improved object identification and improved target identification and tracking. In embodiments, the analysis can be performed on the HWC or the information can be transmitted to a remote network for analysis and results transmitted back to the HWC. Distance measurements can be provided by laser range finding, structured lighting, stereoscopic depth maps or sonar measurements. Images of the environment can be captured using one or more cameras capable of capturing images from visible, ultraviolet or infrared light. The mD radar can be attached to the HWC, located adjacently (e.g. in a vehicle) and associated wirelessly with the HWC or located remotely. Maps or other previously determined information about the environment can also be used in the analysis of the mD radar information. Embodiments of the present invention relate to visualizing the mD signatures in useful ways.

FIG. 21 illustrates a FOV 2102 of a HWC 102 from a wearer's perspective. The wearer, as described herein elsewhere, has a see-through FOV 2102 wherein the wearer views adjacent surroundings, such as the buildings illustrated in FIG. 21. The wearer, as described herein elsewhere, can also see displayed digital content presented within a portion of the FOV 2102. The embodiment illustrated in FIG. 21 is indicating that the wearer can see the buildings and other surrounding elements in the environment and digital content representing traces, or travel paths, of bullets being fired by different people in the area. The surroundings are viewed through the transparency of the FOV 2102. The traces are presented via the digital computer display, as described herein elsewhere. In embodiments, the trace presented is based on a mD signature that is collected and communicated to the HWC in real time. The mD radar itself may be on or near the wearer of the HWC 102 or it may be located remote from the wearer. In embodiments, the mD radar scans the area, tracks and identifies targets, such as bullets, and communicates traces, based on locations, to the HWC 102.

There are several traces 2108 and 2104 presented to the wearer in the embodiment illustrated in FIG. 21. The traces communicated from the mD radar may be associated with GPS locations and the GPS locations may be associated with objects in the environment, such as people, buildings, vehicles, etc, both in latitude and longitude perspective and an elevation perspective. The locations may be used as markers for the HWC such that the traces, as presented in the FOV, can be associated, or fixed in space relative to the markers. For example, if the friendly fire trace 2108 is determined, by the mD radar, to have originated from the upper right window of the building on the left, as illustrated in FIG. 21, then a virtual marker may be set on or near the window. When the HWC views, through its camera or other sensor, for example, the building's window, the trace may then virtually anchor with the virtual marker on the window. Similarly, a marker may be set near the termination position or other flight position of the friendly fire trace 2108, such as the upper left window of the center building on the right, as illustrated in FIG. 21. This technique fixes in space the trace such that the trace appears fixed to the environmental

positions independent of where the wearer is looking. So, for example, as the wearer's head turns, the trace appears fixed to the marked locations.

In embodiments, certain user positions may be known and thus identified in the FOV. For example, the shooter of the friendly fire trace **2108** may be from a known friendly combatant and as such his location may be known. The position may be known based on his GPS location based on a mobile communication system on him, such as another HWC **102**. In other embodiments, the friendly combatant may be marked by another friendly. For example, if the friendly position in the environment is known through visual contact or communicated information, a wearer of the HWC **102** may use a gesture or external user interface **104** to mark the location. If a friendly combatant location is known the originating position of the friendly fire trace **2108** may be color coded or otherwise distinguished from unidentified traces on the displayed digital content. Similarly, enemy fire traces **2104** may be color coded or otherwise distinguished on the displayed digital content. In embodiments, there may be an additional distinguished appearance on the displayed digital content for unknown traces.

In addition to situationally associated trace appearance, the trace colors or appearance may be different from the originating position to the terminating position. This path appearance change may be based on the mD signature. The mD signature may indicate that the bullet, for example, is slowing as it propagates and this slowing pattern may be reflected in the FOV **2102** as a color or pattern change. This can create an intuitive understanding of where the shooter is located. For example, the originating color may be red, indicative of high speed, and it may change over the course of the trace to yellow, indicative of a slowing trace. This pattern changing may also be different for a friendly, enemy and unknown combatant. The enemy may go blue to green for a friendly trace, for example.

FIG. **21** illustrates an embodiment where the user sees the environment through the FOV and may also see color coded traces, which are dependent on bullet speed and combatant type, where the traces are fixed in environmental positions independent on the wearer's perspective. Other information, such as distance, range, range rings, time of day, date, engagement type (e.g. hold, stop firing, back away, etc.) may also be displayed in the FOV.

Another aspect of the present invention relates to mD radar techniques that trace and identify targets through other objects, such as walls (referred to generally as through wall mD), and visualization techniques related therewith. FIG. **22** illustrates a through wall mD visualization technique according to the principles of the present invention. As described herein elsewhere, the mD radar scanning the environment may be local or remote from the wearer of a HWC **102**. The mD radar may identify a target (e.g. a person) that is visible **2204** and then track the target as he goes behind a wall **2208**. The tracking may then be presented to the wearer of a HWC **102** such that digital content reflective of the target and the target's movement, even behind the wall, is presented in the FOV **2202** of the HWC **102**. In embodiments, the target, when out of visible sight, may be represented by an avatar in the FOV to provide the wearer with imagery representing the target.

mD target recognition methods can identify the identity of a target based on the vibrations and other small movements of the target. This can provide a personal signature for the target. In the case of humans, this may result in a personal identification of a target that has been previously characterized. The cardio, heart beat, lung expansion and other small

movements within the body may be unique to a person and if those attributes are pre-identified they may be matched in real time to provide a personal identification of a person in the FOV **2202**. The person's mD signatures may be determined based on the position of the person. For example, the database of personal mD signature attributes may include mD signatures for a person standing, sitting, laying down, running, walking, jumping, etc. This may improve the accuracy of the personal data match when a target is tracked through mD signature techniques in the field. In the event a person is personally identified, a specific indication of the person's identity may be presented in the FOV **2202**. The indication may be a color, shape, shade, name, indication of the type of person (e.g. enemy, friendly, etc.), etc. to provide the wearer with intuitive real time information about the person being tracked. This may be very useful in a situation where there is more than one person in an area of the person being tracked. If just one person in the area is personally identified, that person or the avatar of that person can be presented differently than other people in the area.

FIG. **23** illustrates an mD scanned environment **2300**. An mD radar may scan an environment in an attempt to identify objects in the environment. In this embodiment, the mD scanned environment reveals two vehicles **2302a** and **2302b**, an enemy combatant **2309**, two friendly combatants **2308a** and **2308b** and a shot trace **2318**. Each of these objects may be personally identified or type identified. For example, the vehicles **2302a** and **2302b** may be identified through the mD signatures as a tank and heavy truck. The enemy combatant **2309** may be identified as a type (e.g. enemy combatant) or more personally (e.g. by name). The friendly combatants may be identified as a type (e.g. friendly combatant) or more personally (e.g. by name). The shot trace **2318** may be characterized by type of projectile or weapon type for the projectile, for example.

FIG. **23a** illustrates two separate HWC **102** FOV display techniques according to the principles of the present invention. FOV **2312** illustrates a map view **2310** where the mD scanned environment is presented. Here, the wearer has a perspective on the mapped area so he can understand all tracked targets in the area. This allows the wearer to traverse the area with knowledge of the targets. FOV **2312** illustrates a heads-up view to provide the wearer with an augmented reality style view of the environment that is in proximity of the wearer.

Although embodiments of HWC have been described in language specific to features, systems, computer processes and/or methods, the appended claims are not necessarily limited to the specific features, systems, computer processes and/or methods described. Rather, the specific features, systems, computer processes and/or methods are disclosed as non-limited example implementations of HWC. All documents referenced herein are hereby incorporated by reference.

We claim:

1. A method, comprising:

receiving a location indicative of a human presence at a location in an obscured environment;
establishing a virtual location marker in a position that is visually available to a person wearing a head-worn computing system, wherein the virtual location marker provides an indication of the location in the obscured environment; and

generating an avatar as a representation of the human presence and presenting the avatar in a field of view of the head-worn computing system, wherein the presentation of the avatar is positioned in the field of view by

visually associating the avatar with the virtual location marker such that the avatar appears to remain at the virtual location marker location, as perceived by a person wearing the head-worn computing system, independent of the head-worn computing system's viewing angle. 5

2. The method of claim 1, further comprising: establishing an identity of the human presence and presenting an indication of the identity in the field of view.

3. The method of claim 2, wherein the indication is a color of the avatar. 10

4. The method of claim 2, wherein the identity is of an enemy combatant.

5. The method of claim 1, wherein the human presence at the location in the obscured environment moves within the obscured environment; and the virtual location marker moves to continue to provide the indication of the location in the obscured environment. 15

6. The method of claim 1, wherein a micro Doppler radar that established the location is remotely located from the person wearing the head-worn computing system. 20

7. The method of claim 1, wherein a micro Doppler radar that established the location is proximate to the person wearing the head-worn computing system.

* * * * *