



US009791221B1

(12) **United States Patent**
Litch

(10) **Patent No.:** **US 9,791,221 B1**
(45) **Date of Patent:** **Oct. 17, 2017**

(54) **CONDENSER ASSEMBLY SYSTEM FOR AN APPLIANCE**

(71) Applicant: **Whirlpool Corporation**, Benton Harbor, MI (US)

(72) Inventor: **Andrew David Litch**, Saint Joseph, MI (US)

(73) Assignee: **WHIRLPOOL CORPORATION**, Benton Harbor, MI (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 553 days.

5,428,973	A *	7/1995	Temmyo et al.	62/452
5,502,983	A *	4/1996	Dasher	62/454
5,592,829	A *	1/1997	Kim	62/428
5,806,585	A *	9/1998	Yoshida et al.	165/171
5,881,567	A *	3/1999	Junge et al.	
6,253,839	B1 *	7/2001	Reagen et al.	165/151
6,389,695	B1 *	5/2002	Dall'Oro et al.	29/890.03
6,640,885	B2 *	11/2003	Jenkins, Jr.	165/171
6,715,539	B2 *	4/2004	Bianco	165/122
6,793,010	B1 *	9/2004	Manole	165/122
7,908,883	B2 *	3/2011	Wu et al.	62/441
2005/0044882	A1 *	3/2005	Hong et al.	62/507
2005/0061021	A1 *	3/2005	Uihlein et al.	62/441
2005/0061926	A1 *	3/2005	Pereira et al.	248/71
2008/0142197	A1 *	6/2008	Van Andel et al.	165/104.26

(Continued)

FOREIGN PATENT DOCUMENTS

GB	184222	A	8/1922
GB	555881	A	9/1943

OTHER PUBLICATIONS

Whirlpool Corp. Part No. W10276898 "Condenser—Formed, FD", May 13, 2009.

Primary Examiner — Justin Jonaitis

Assistant Examiner — Joel Attey

(74) *Attorney, Agent, or Firm* — Price Heneveld LLP

(21) Appl. No.: **13/663,623**

(22) Filed: **Oct. 30, 2012**

(51) **Int. Cl.**

F28F 9/26	(2006.01)
F28D 1/053	(2006.01)
F25B 39/04	(2006.01)
F28D 1/047	(2006.01)
F28F 1/12	(2006.01)

(52) **U.S. Cl.**

CPC **F28F 9/262** (2013.01); **F25B 39/04** (2013.01); **F28D 1/0477** (2013.01); **F28D 1/05391** (2013.01); **F28F 1/122** (2013.01)

(58) **Field of Classification Search**

CPC **F28F 9/262**; **F28F 1/22**; **F28D 1/05391**; **F28D 1/0477**; **F25B 39/04**

USPC 165/144, 145

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS


2,515,972	A *	7/1950	White et al.	62/516
4,490,991	A	1/1985	Griffin	
5,070,708	A *	12/1991	Malosh et al.	62/295

(57)

ABSTRACT

An appliance includes a compact condenser assembly formed with at least two separately and independently produced wire on tube condensers. Each of the at least two wire on tube condensers has a condenser inlet and a condenser outlet. The at least two wire on tube condensers are at least substantially locked and positioned in a matingly engaged configuration forming a compact condenser assembly. The at least two wire on tube condensers are configured to be operationally connected in at least one of a parallel configuration, a series configuration, a selectable configuration, and a bypass configuration.

19 Claims, 23 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

2008/0164016	A1*	7/2008	Lee et al.	165/178
2009/0296346	A1*	12/2009	Van Andel	361/696
2010/0089560	A1	4/2010	Shikazono et al.	
2010/0122805	A1	5/2010	Yang	
2010/0326639	A1*	12/2010	Ando	F28D 1/0472 165/144
2012/0060545	A1*	3/2012	Rafalovich et al.	62/455

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6A




FIG. 6B




FIG. 6C




FIG. 6D




FIG. 7A




FIG. 7B




FIG. 7C




FIG. 8




FIG. 9A




FIG. 9B




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17

1

CONDENSER ASSEMBLY SYSTEM FOR AN APPLIANCESTATEMENT REGARDING FEDERALLY
SPONSORED RESEARCH AND
DEVELOPMENT

This invention was made with government support under Award No. DE-EE0003910, awarded by the U.S. Department of Energy. The government has certain rights in the invention.

FIELD OF THE INVENTION

The present invention generally relates to a condenser assembly and, more specifically, to a compact wire on tube condenser assembly for a refrigerating appliance.

BACKGROUND OF THE INVENTION

Known condensers are formed from a tubular conduit constructed into a serpentine shape with a wire frame attached around the tubular conduit. This type of condenser is often referred to as a wire on tube condenser, a wire and tube condenser, or a WoT condenser. These wire on tube condensers may have a planar lateral profile, a U-shaped lateral profile, a sawtooth lateral profile, or other profiles. A condenser with a lateral profile of a sawtooth are sometimes referred to as a sawtooth condenser, a zig-zag condenser, a wave condenser, or the like.

Currently, in order to increase the amount of heat exchanged from a wire on tube condenser via the method of increasing heat transfer surface area, the heat exchange surface area of at least one of the wires and of the tubular conduit may be increased. In order to increase the length of tubular conduit and retain the current bend radius of the tubular conduit, the overall dimensions of the condenser may increase. The increase in overall volume of the condenser with an increased heat exchange surface area may be unacceptable since the condenser may have to fit into an existing air passageway.

A modified manufacturing process or custom tooling may be needed in order to reduce the bend radius of the tubular conduit and form a condenser with a tighter wound tubular conduit. Using a custom manufacturing process to minimize the increase in dimensions of the condenser is typically not desired due to additional manufacturing or tooling costs.

SUMMARY OF THE INVENTION

One aspect of the present invention relates to a wire on tube condenser assembly that includes at least two separately and independently produced wire on tube condensers where each of the at least two wire on tube condensers has a condenser inlet and a condenser outlet. The at least two wire on tube condensers are at least substantially locked and positioned in a matingly engaged configuration forming a condenser assembly. The at least two wire on tube condensers are configured to be operationally connected in at least one of a parallel configuration, a series configuration, a selectable configuration, a split configuration, and a bypass configuration.

Another aspect of the present invention includes an appliance having a machine compartment that includes a housing with at least one airflow path and a fan configured to cause a flow of cooling air. An air passageway is operationally connected to the machine compartment and configured to

2

allow airflow into the machine compartment. The air passageway contains a condenser assembly that includes at least two separately and independently produced wire on tube condensers that are at least substantially locked and positioned in a matingly engaged configuration and operationally connected in at least one of the following configurations: a parallel configuration, a series configuration, a selectable configuration, a split configuration, and a bypass configuration. The air passageway further contains an exhaust port for discharging heated air radiated from the at least two wire on tube condensers. Each of the at least two wire on tube condensers has a condenser inlet and a condenser outlet.

Yet another aspect of the present invention includes a method of assembling a compact wire on tube condenser assembly that includes the steps of providing at least two separately and independently produced wire on tube condensers, at least substantially locking the at least two condensers within an air passageway of an appliance in a matingly engaged configuration to form the condenser assembly that is typically configured to be used and entirely spaced within the air passageway.

These and other features, advantages and objects of the present invention will be further understood and appreciated by those skilled in the art by reference to the following specification, claims, and appended drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

The foregoing summary, as well as the following detailed description of the invention, will be better understood when read in conjunction with the appended drawings. For the purpose of illustrating the invention, there are shown in the drawings, certain embodiments which are presently preferred. It should be understood, however, that the invention is not limited to the precise arrangements and instrumentalities shown. Drawings are not necessary to scale. Certain features of the invention may be exaggerated in scale or shown in schematic form in the interest of clarity and conciseness.

FIG. 1 is a front, upper left perspective view of an appliance incorporating an embodiment of the condenser assembly of the present invention;

FIG. 2 is an interior front perspective view of the machine compartment portion of the appliance of FIG. 1 incorporating an aspect of the condenser assembly of the present invention;

FIG. 3 shows a cross-sectional perspective view of the portion of the appliance of FIG. 2 taken along line III-III in FIG. 2 according to an aspect of the condenser assembly of the present invention;

FIG. 4 shows an elevated cross-section of the portion of the appliance of FIG. 2 taken along line III-III in FIG. 2 according to an aspect of the condenser assembly of the present invention;

FIG. 5 shows an enlarged, elevated cross-section of the portion of the appliance shown in the circled portion V of FIG. 4;

FIG. 6A shows a front upper left perspective view of a portion of a condenser assembly according to one aspect of the condenser assembly of the present invention;

FIG. 6B shows a top view of the single condenser according to an aspect of the condenser assembly of the invention as shown in FIG. 6A;

FIG. 6C shows an elevated right side view of the single condenser of the condenser assembly of the invention as shown in FIG. 6A;

3

FIG. 6D shows an elevated front end view of the single condenser according to an aspect of the condenser assembly of the invention as shown in FIG. 6A;

FIG. 7A shows an upper left perspective view of a compact condenser assembly according to one aspect of the condenser assembly of the present invention;

FIG. 7B shows an elevated front view of a condenser assembly according to an aspect of the condenser assembly of the invention as shown in FIG. 7A;

FIG. 7C shows an elevated right view of the condenser assembly according to an aspect of the condenser assembly of the invention as shown in FIG. 7A;

FIG. 8 shows a side cross-section exploded view of the condenser assembly elements of the present invention and the surface of the machine compartment of the appliance the condenser assembly engages according to one aspect of the condenser assembly of the present invention;

FIG. 9A shows an upper left perspective view of a compact condenser assembly having three layers with the top layer smaller than the other two layers according to one aspect of the condenser assembly of the present invention;

FIG. 9B shows an elevated cross-sectional view of the portion of the condenser assembly taken along line VI-VI in FIG. 9A according to an aspect of the condenser assembly of the present invention;

FIG. 10 shows an upper left perspective view of a condenser assembly according to yet another embodiment of the condenser assembly of the invention;

FIG. 11 shows an elevated cross-sectional view of a portion of an appliance with the condenser assembly in various optional locations;

FIG. 12 shows a partial elevated cut away side view of the compact condenser assembly of FIG. 5 according to one aspect of the condenser assembly of the invention;

FIG. 13 shows a schematic view of an aspect of the condenser assembly of the present invention where the first condenser and the second condenser are operationally connected in series;

FIG. 14 shows a schematic view of an aspect of the condenser assembly of the present invention where the first condenser and the second condenser are operationally connected in parallel;

FIG. 15 shows a schematic view of an aspect of the condenser assembly of the present invention where the first condenser and the second condenser are operationally selectablely connected in series or in parallel;

FIG. 16 shows a schematic view of an aspect of the condenser assembly of the present invention where the first condenser and the second condenser are operationally selectablely connected in series or in a mode bypassing the second condenser; and

FIG. 17 shows a cut away side perspective view of the condenser assembly of the present invention according to an alternate embodiment where two condensers with a U-shaped lateral profile are assembled together to form a condenser assembly.

DETAILED DESCRIPTION

Before the subject invention is described further, it is to be understood that the invention is not limited to the particular embodiments of the invention described below, as variations of the particular embodiments may be made and still fall within the scope of the appended claims. It is also to be understood that the terminology employed is for the purpose of describing particular embodiments, and is not intended to

4

be limiting. Instead, the scope of the present invention will be established by the appended claims.

Where a range of values is provided, it is understood that each intervening value, to the tenth of the unit of the lower limit unless the context clearly dictates otherwise, between the upper and lower limit of that range, and any other stated or intervening value in that stated range, is encompassed within the invention. The upper and lower limits of these smaller ranges may independently be included in the smaller ranges, and are also encompassed within the invention, subject to any specifically excluded limit in the stated range. Where the stated range includes one or both of the limits, ranges excluding either or both of those included limits are also included in the invention.

In this specification and the appended claims, the singular forms "a," "an" and "the" include plural reference unless the context clearly dictates otherwise.

For purposes of description herein the terms "upper," "lower," "right," "left," "rear," "front," "vertical," "horizontal," and derivatives thereof shall relate to the invention as oriented in FIG. 1. However, it is to be understood that the invention may assume various alternative orientations and step sequences, except where expressly specified to the contrary. It is also to be understood that the specific devices and processes illustrated in the attached drawings, and described in the following specification are simply exemplary embodiments of the inventive concepts defined in the appended claims. Hence, specific dimensions and other physical characteristics relating to the embodiments disclosed herein are not to be considered as limiting, unless the claims expressly state otherwise.

The present disclosure includes an appliance with a heating, cooling, dehumidifying, or refrigerating function having a heat exchange system, alternately referred to as a vapor compression system. Vapor compression systems of the present disclosure typically include at least one evaporator, at least one compressor, at least one expansion device, and a condenser assembly. The appliance may be any appliance incorporating a vapor compression system, including, but not limited to, a refrigerator, a freezer, a dishwasher, a laundry dryer, a combination laundry washer dryer, an air conditioner, an air heater, a water heater, a dehumidifier, and the like.

An evaporator of the present application is a heat exchanger where heat is absorbed into a working refrigerant within the evaporator and the working refrigerant is evaporated. A condenser is a heat exchanger where heat is rejected from the working refrigerant and the refrigerant is then condensed. The condenser assembly of the present application may be used as an evaporator assembly. The condenser assembly may function as an evaporator or a heat exchanger if configured as such in a vapor compression system and such systems are meant to be encompassed by the present application. The words "tube", "tubing", and the phrase "tubular conduit" are used interchangeably and refer to conduit configured to contain and capable of containing and communication of one or more refrigerants, typically fluid refrigerants through the conduit.

The inventions disclosed herein provide a method to assemble a compact condenser assembly while minimizing the increase in overall dimensions, or volume, of the condenser assembly and significantly minimizing or eliminating the need for a custom manufacturing process or custom tooling all while also doing so in a manner that surprisingly also minimizes the decrease in airflow due to the increased heat exchange surface area.

5

Additionally, the condenser assembly includes at least two condenser inlets and at least two condenser outlets. The condenser assembly is operationally configured so that at least two portions of the condenser assembly tubular conduit may be operationally connected and provide a flow of refrigerant(s) or other fluids through the portions of the tubular conduit operationally connected in one or more of the following configurations: in parallel, in series, and/or selectively connected. Selectively connected (i.e. a selectable configuration) is defined as a configuration which allows the user and/or the appliance to selectively operate the sub-condensers in at least one of a parallel configuration, a series configuration, a bypassed configuration where at least one of the sub-condensers is bypassed, and/or a split configuration where at least one of the sub-condensers is operationally connected to a second separate heat exchange system from a first heat exchange system, typically based upon operational needs of the appliance. The appliance or the condenser assembly typically may have at least one or more valve and/or connector that are configured to change the connection between the individual condensers from a parallel configuration to a series configuration (and vice versa).

Alternatively, a portion of the condenser assembly tubular conduit may be operationally connected to a separate heat exchange system, may be selectively bypassed, connected or selectively connected to a heat storage or a heat recovery system, and/or selectively connected to more than one heat exchange circuit.

The direction of flow in a portion of the condenser assembly tubular conduit may be operationally controlled to be in the same direction or in an opposite direction than the flow in a second portion of the condenser assembly tubular conduit. The condenser assembly typically includes at least two separately and independently produced wire on tube condensers. The at least two wire on tube condensers are at least substantially locked or fully locked and positioned in a matingly engaged configuration. The at least two wire on tube condensers may be stacked, layered, spaced apart, or nested together to form a condenser assembly with two condenser inlets and two condenser outlets. When the condenser assembly includes two or more serpentine condensers in a zig-zag or sawtooth configuration, the valleys of the condensers are seated and nested within one another and the bottom facing surface of the upper condenser typically, but does not necessarily, directly engages the upper surface of the condenser below it. Multiple condensers may be stacked to form a condenser assembly. Two, three, four, or a plurality of condensers may be stacked or assembled into a multi-layer condenser assembly.

The stacking of the condensers offsets the tubular conduits to expose the tubular conduits to airflow. The spacing of the tubular conduits and wires minimizes the obstruction of airflow. The wires and/or the tubular conduit of the additional condenser may rest on top of, be spaced above, be spaced apart, and/or fit in the spaces between the wires and tubular conduit of the first condenser. Spacers may be used to position the at least two condensers with respect to each other. The spacers provide/produce a gap between the tubular conduits of each condenser. The spacers may be used to fasten the at least two condensers to each other, to accommodate dimensional differences between the condenser profiles, to improve airflow through the condensers, and/or to prevent movement between the at least two condensers. The spacers may alternatively be one or more of a spacer, a clip, a bracket, a brace, a clamp, a holder, a pad, an insert, a fastener, a screw, a shim, and/or a sheet of metal or plastic

6

or any combination thereof. The spacers may alternatively fasten a first condenser to a surface in an air passageway and fasten a second condenser to a second surface in the air passageway such that the first and second condensers are spaced with a gap between the condensers.

There may be sufficient elasticity in the wire and tube condensers depending upon various factors of their construction to allow layering of at least two condensers to form a condenser assembly without using any spacers. The at least two condensers will typically have a substantially similar or identical lateral profile and may snugly fit together enough to prevent shifting, rubbing, or vibration without the need for any spacers between the two condensers of the condenser assembly.

Optionally, at least one fastener may be used to fasten the condenser assembly to a surface of an air passageway of the appliance or another portion of the appliance. Optionally, at least one fastener may be used to fasten the at least two condensers together to form a condenser assembly.

At least one of a valve and a connector may be assembled as part of or operably engaged with a condenser assembly of the present application. The condenser assembly may have only a single inlet and a single outlet since the connectors to the additional inlet and the additional outlet may be operably engaged in the condenser assembly. Conversely, at least one of a valve and a connector may be alternatively separate from the condenser assembly and assembled as part of the appliance instead.

The condenser assemblies, because they typically include two or more individual condensers that themselves can function as a single condenser, allow for a modular approach and permit the condenser assemblies to be used in multiple applications where more or less surface area of the condenser is needed or would be advantageous. A multiple layer condenser assembly may be used to reduce the space needed for the air passageway if an increase in overall heat exchange surface area is not needed.

FIG. 1 shows an appliance 100 having an appliance exterior 102, an appliance interior volume 104 defined by the appliance exterior 102, and an appliance access 106, which is typically either a drawer such as a pantry slide out drawer (not shown) or one or more hingedly engaged doors that, when opened, allow access to the interior volume 104 of the appliance 100. The appliance exterior 102 has an appliance front 108, an appliance back 110, an appliance first (right) side 112, an appliance second (left) side 114, an appliance top 116, and an appliance bottom 118. The appliance access 106, as mentioned above, may be a drawer (not shown) or a door 120, but could be any structure that permits user access to the interior volume 104 of the appliance 100 or an opening (not shown) in the appliance exterior 102. The appliance exterior 102 may have at least one airflow inlet 121.

Referring to FIG. 1 and FIG. 2, the appliance 100 typically has a machine compartment 122 typically located at least partially inside the appliance 100. The machine compartment 122 may have a machine compartment housing 124 with at least one machine compartment opening 126 to the interior volume of the machine compartment 122. A portion of the machine compartment 122 may be unenclosed 127 by a machine compartment housing 124 of the appliance 100. The machine compartment housing 124 may optionally include one or more: vents, slots, holes, louvers, or the like (not shown) in order to facilitate airflow from the machine compartment 122 and exhaust air that has contacted the condenser assembly 130 and/or components within the machine compartment 122. The machine compartment 122

may include an air passageway **131** (FIGS. 2-3) or may be operationally connected with the at least one machine compartment opening **126** to the air passageway **131**. The air passageway **131** may be operationally connected to at least one airflow inlet **121** to allow airflow **132** into the air passageway **131**. A condenser assembly **130** may be positioned in the air passageway **131**. At least a compressor **133** and optionally a fan **134** are typically spaced or positioned within the machine compartment **122**.

Referring to FIG. 3 and FIG. 4, the air passageway **131** typically includes a condenser assembly **130**, at least one airflow inlet **121** that permits ambient air or air from outside the air passageway ingress to the air passageway, an air passageway upper surface **138**, an air passageway lower surface **140**, and an airflow outlet **142** that permits air egress of air from within the air passageway **131**. The air passageway **131** may include unenclosed portions **144**, which are not enclosed within a housing on one or more sides or enclosed within the appliance walls on one or more sides. The vertical distance between the passageway upper surface **138** and the passageway lower surface **140** is typically from about 20 mm to about 200 mm, more typically between about 100 mm and about 40 mm, and preferably about 66 mm. The condenser assembly **130** (FIG. 4) typically includes at least a first condenser **146**, a second condenser **148**, a first condenser inlet **150**, a first condenser outlet **152**, a second condenser inlet **154**, and a second condenser outlet **156**. FIG. 5 depicts a cross-sectional view of a portion of the air passageway **131** and a portion of the condenser assembly **130** according to one aspect of the present invention. The condenser assembly **130** typically includes at least a first condenser **146** and a second condenser **148** in two layers, but additional condenser layers may also be employed. The condenser assembly **130** may optionally be fastened to one or more surface(s) **138** by a fastener **158**. Typically, the surface **138** is a portion of either or both of the air passageway **131** floor or wall, the ceiling wall or a side wall or a floor of the machine compartment **122**. Most typically, the condenser assembly is fastened to the ceiling wall when it is attached to a surface within the machine compartment **122**. The first condenser **146** and the second condenser **148** are typically at least substantially locked or fully locked together in a frictional manner with one another such that the first condenser **146** and the second condenser **148** do not move and rub against one another during operation. The condensers **146**, **148** used are typically positioned in a mating engaged configuration forming a condenser assembly **130**. As discussed previously, the condenser assembly **130** is typically formed from a plurality of condensers **146**, **148** without the use of any spacers between the first condenser **146** and the second condenser **148**, but spacers may optionally be employed.

FIG. 6A shows an example of a wire on tube condenser **146** with a sawtooth lateral profile suitable for use according to an aspect of the invention. The top view of the condenser **146** is shown in FIG. 6B. A side view of the condenser **146** is shown in FIG. 6C. A front view of the condenser **146** is shown in FIG. 6D.

The first condenser **146** typically includes a first condenser inlet **150**, a first condenser outlet **160**, and a tubular conduit **162** with a passageway therethrough and configured to carry one or more refrigerant(s). Typically, the tubular conduit **162** is a metal conduit, more typically a metal of high thermal conductivity such as steel, copper, aluminum, or the like. The refrigerant is typically a two-phase refrigerant and may be at least one of a fluid, a gas, or a liquid. At least a portion of the tubular conduit **162** is typically

formed into a serpentine shape with the tubular conduit **162** having a plurality of U-shaped tube passes with each pass having at least two substantially straight tube sections **170**, **171** joined by a U-shaped end cap section **172**. The straight tube sections **170**, **171** may be oriented across a width **173** of the condenser **146**. The tubular conduit **162** has a flow path progressing from the first condenser inlet **150**, through the plurality of U-shaped tube sections **171**, **172**, **174**, **176**, **178**, making alternating back and forth passes in a direction along the width **173** of the condenser **146**, progressing along a length **179** of the condenser **146**, and progressing to the condenser outlet **160**. The first condenser **146** further typically includes an extended heat transfer surface **180** arranged connected to the straight tube sections **170**, **171** across the length **179** of the condenser **146**. The extended heat transfer surface **180** may be a plurality of wires **182** wrapped around a length of the tubular conduit **162**. A plurality of thermal transfer fins (not shown) may be in a thermally engaged relationship with the tubular conduits to facilitate heat dissipation to the air flowing past the tubular conduits, fins and the overall condenser or condenser assembly. The tubular conduit **162** (FIG. 6B) is typically made out of steel with a tubing outer diameter **185** of between about 2.0 mm and about 10 mm, more typically between about 3.5 mm and about 7.0 mm, and preferably about or exactly 4.76 mm. The tubular conduit **162** is typically made out of a tubing with a wall thickness **230** of between about 0.4 mm and about 2.0 mm, more typically between about 0.5 mm and about 1.0 mm, and preferably about or exactly 0.63 mm.

The tubular conduit **162** (FIGS. 6B and 6C) is typically configured into a serpentine pattern with a lateral profile of a sawtooth. The width **173** of the condenser **146** is typically less than about 1500 mm, more typically less than about 1000 mm, and preferably less than about 500 mm and most preferably about or exactly 479 mm. The length **179** of the condenser **146** is typically less than about 1500 mm, more typically less than about 1000 mm, and preferably less than about 500 mm, and most preferably about or exactly 440 mm. The height **183** of the condenser **146** (FIG. 5) is typically less than about 200 mm, more typically less than about 150 mm, and preferably less than about 75 mm.

The condenser **146** (FIG. 6B) has typically between about 3 to about 15, more typically between about 5 to about 12, and preferably about 6 to about 10 substantially straight sections **170** of U-shaped passes **171** per about 100 mm of condenser length **179**. The number of substantially straight sections **170** of U-shaped passes **171** per unit of condenser length **179** may vary within a condenser **146**. The contour of each U-shaped pass **171**, the orientation of each U-shaped end cap section **172**, the bend radius of each U-shaped end cap section **172**, the distance between each U-shaped end cap section **172**, the inverted angle **147**, and the upward facing angle **151** affect the amount of U-shaped passes **171** per unit of condenser length **179**.

The contour of the individual U-shaped passes **171**, the radius of the U-shaped end cap sections **172**, the length of the individual substantially straight sections **170**, the condenser width **173**, the condenser length **179**, the condenser height **183**, and the tubular conduit **162** tube diameter **185** may be and typically are substantially similar or identical between the at least two condensers **146**, **148**, may be substantially different between the at least two condensers **146**, **148**, and optionally may vary within a specific condenser **146**. Likewise, the placement, profile, wire diameter **187**, wire material, and number of wires **180** may vary between the at least two condensers **146**, **148**. The tubular conduit **162** may be any suitable cross-sectional shape

including: round, substantially oval, oval, oblong, parallelogram, or rectangular over at least a portion of the tubular conduit length. The tubular conduit **162** has a conduit diameter **185** and the wires **180** of the condenser having a wire diameter **187** (FIG. 6B). Wires **180** are typically steel wires with a diameter of typically between about 0.5 mm and about 2.0 mm, more typically between about 0.8 mm and about 1.5 mm, and preferably about or exactly 1.39 mm wire diameter **187** (outer surface to opposite outer surface). The wires **180** are typically attached across the length **179** of the serpentine tubular conduit **162**. Typically between about 10 and about 400, more typically about 100 to about 300, and preferably about or exactly 148 wires are distributed over the upper and lower surfaces of the serpentine tubular conduit **162**. While the wire **180** typically has a circular or substantially circular cross-section, the wire could also have another cross-sectional shape such as a rectangle, square, or diamond shape cross-section.

FIG. 6C shows a side perspective view of the condenser **146** according to one embodiment of the invention as shown in FIG. 6A. The condenser **146** has a length **179** and an overall wire height **194**. An angle **196** is measured between a U-shaped tubular section **198** parallel to the general plane of the condenser **146** and an adjacent U-shaped tubular section **200**. The angle **196** is typically from about 20 to about 160 degrees, more typically from about 35 to about 120 degrees and most typically about or exactly 54 degrees. A profile angle **202** is the angle between a U-shaped tubular section **200** located off the general plane of the condenser **146** and an adjacent U-shaped tubular section **204** located off the general plane of the condenser. The profile angle **202** is typically from about 20 to about 160 degrees, more typically from about 30 to about 140 degrees, even more typically from about 35 to about 150 degrees, even more typically from about 50 to about 110 degrees, and most typically about or exactly 72 degrees. The wires **206** extend past the U-shaped tubular passes **200** a distance **208** and meet one another where they are engaged via a weld, a mechanical attachment, a crimp, glue, or other bonding mechanism. The wires **206** extend past the tubular U-shaped sections **198**, **204** typically between about 1 mm and about 25 mm, more typically between about 5 mm and about 20 mm, and preferably about or exactly 12 mm. Each tubular U-shaped pass **210** has a width **212**. The width of each tubular U-shaped pass **210** may be approximately uniform across all of the tubular U-shaped passes **210** or the widths of the various tubular U-shaped pass **210** may be varied.

FIG. 6D shows an elevated front-end view of the condenser **146** shown in FIG. 6A. The overall height **194** of the wires **214**, the overall height **216** of the tubular conduit **218**, the width **220** of each tubular U-shaped pass **222**, and the width **173** of the condenser **146** are illustrated. The bend radiuses **224**, **226** of the tubular U-shaped passes **222** are also illustrated. Each tubular U-shaped pass **222** consists of two straight sections **218** separated by a radius bend **224**.

Referring to FIG. 6C and FIG. 6D, the distance **212** between two adjacent straight sections **222** is typically between about 5 mm and about 40 mm, more typically between about 15 mm and about 30 mm, and preferably about or exactly 22 mm. The overall height **194** of the condenser **146** measured across the wires **206** is typically between about 30 mm and about 100 mm, more typically between about 40 mm and about 70 mm, and preferably about or exactly 52 mm. Each of the condensers **146**, **148** (see FIGS. 5 and 6A-6D) typically have an inclined portion **238** and a declined portion **240** that invert about the top side

bend at an angle **242** and an upwardly facing bottom bend at an angle **244**. The inverted angle **242** is typically between about 20 to about 160 degrees, more typically between about 35 to about 150 degrees and most typically about or exactly 72 degrees. The upward facing angle **244** is typically between about 20 to about 160 degrees, more typically between about 35 to about 150 degrees and meet typically about or exactly 72 degrees. The inverted angle **242** and the upward facing angle **244** may be substantially about the same or identical or may vary within a condenser.

Referring to FIGS. 7A-7C, a condenser assembly **130** typically employs at least two sub-condensers **146**, **148**. The condenser assembly **130** typically includes at least a first condenser **146** and a second condenser **148** but may employ additional sub-condensers beyond the first **146** and second **148** condensers. FIGS. 7A-7C show a condenser assembly **130** where two separately and independently produced wire on tube condensers **146**, **148** have been substantially locked together and positioned in a matingly engaged, typically frictionally matingly engaged, configuration forming the condenser assembly **130** according to one embodiment of the invention. FIG. 7C shows the alignment of the first condenser **146** and the second condenser **148** of FIG. 7A. Some of the wires **245** typically employed have been omitted from the Figures for clarity. As shown in FIG. 7A, the condenser assembly **130** typically has a first condenser inlet **150**, a first condenser outlet **160**, a second condenser inlet **154**, and a second condenser outlet **156**. The length and width dimensions of the condenser assembly **130** are about the same as for a single condenser **146** due to the interlocking of the condensers **146**, **148**.

The overall height **246** of the condenser assembly **130** (FIG. 7B) when two condensers are employed to form the condenser assembly **130** is typically between about 40 mm and about 150 mm, more typically between about 50 mm and about 100 mm, and preferably about or exactly 63 mm. The increase in height of a condenser assembly **130** over a single condenser **146** is typically between about 5 mm and about 50 mm, more typically between about 8 mm and about 20 mm, and preferably about or exactly 11 mm (for each additional condenser added to form the condenser assembly). The increase in overall height of the condenser assembly is related to the number of condensers **146** layered to form a condenser assembly **130** and the contour of the individual condensers **146**. A stack of three condensers may have an increase in height over a stack of two condensers. When two substantially similar condensers **146** are assembled into a condenser assembly **130**, the heat transfer surface area may be doubled with only about 5 mm to about 30 mm increase in overall condenser assembly height.

The energy usage was measured on two refrigerators with a single condenser. The energy usage was measured after the refrigerators were fitted a condenser assembly with two condensers connected in series.

Exemplary energy usage is provided in Tables I and III from the two side by side refrigerators of the same model (WHIRLPOOL® GSS26C4XXW03) when tested in accordance with AHAM HRF-1-2007 (Section 8). Unit 1 and Unit 2 were fitted with a single condenser and evaluated for energy usage. Exemplary energy usage is provided in Tables II and IV from Unit 1 and Unit 2 fitted with two substantially similar condensers connected in series.

11

TABLE I

Exemplary energy usage for a single condenser in unit 1			
Test	Freezer Temperature ° F.	Cabinet Temperature ° F.	Energy Usage kW-hr/Day
1	-3.2	41.4	1.73
2	3.3	49.7	1.44
3	5.0	51.9	1.36
4	-0.4	45.0	1.61

TABLE II

Exemplary energy usage for a single condenser in unit 2			
Test	Freezer Temperature ° F.	Cabinet Temperature ° F.	Energy Usage kW-hr/Day
1	-0.5	38.3	1.61
2	6.0	48.4	1.30
3	5.0	46.8	1.35
4	3.8	45.0	1.40

TABLE III

Exemplary energy usage for a condenser assembly of the present disclosure with two condensers connected in series in unit 1			
Test	Freezer Temperature ° F.	Cabinet Temperature ° F.	Energy Usage kW-hr/Day
1	-3.3	41.3	1.71
2	2.9	49.3	1.43
3	5.0	52.0	1.33
4	-0.4	45.0	1.58

TABLE IV

Exemplary energy usage for a condenser assembly of the present disclosure with two condensers connected in series in unit 1			
Test	Freezer Temperature ° F.	Cabinet Temperature ° F.	Energy Usage kW-hr/Day
1	-0.3	39.4	1.54
2	5.9	48.5	1.26
3	5.0	47.1	1.30
4	3.5	45.0	1.37

The freezer temperature and the cabinet temperature show the average freezer compartment air temperature and the average fresh food compartment air temperature, respectively, in degrees F. as measured per AHAM HRD-1-2007 (Section 8). The Energy Usage is the energy consumption in kW-hr/day as measured per AHAM HRD-1-2007. Comparing the energy usage at similar average compartment temperatures shows the condenser assembly connected in series used about 0.69% to about 4.3% less kw-hr/day during any given test. The average energy usage for a single condenser was 1.475 kW-hr/day. The average energy usage for a condenser assembly connected in series was 1.44 kW-hr/day. Based on this data, an average energy savings of about 2.3% was obtained by using a condenser assembly of the present disclosure employing two nested condensers over a single condenser.

This exemplary data shows that by using a condenser assembly of the present disclosure employing two nested condensers an overall reduction in energy usage was obtained. The overall width and length of the condenser

12

assembly was substantially similar to the overall width and length of a single condenser. The overall height of the exemplary condenser assembly increased about 11 mm. Depending on the available clearance in an air passageway, the condenser assembly may fit within the air passageway with no changes to the air passageway.

As discussed above, the first condenser **146** and the second condenser **148** may be affixed to a surface of the air passageway **131** or machine compartment **122** or other surface of the appliance **100** using one or more fasteners **158** (FIG. **8**). The one or more fasteners **158** typically are a threaded bolt, screw, clip, pin, bracket, brace, or the like that passes through apertures in the first condenser **146** and second condenser **148** typically at the top side bend portion(s). The at least one fastener **158** is typically matingly engaged with an attachment recess or aperture of an attachment portion **248** that receives the fastener **158**. The tubular conduit inclined portions **238** and declined portions **240** have U-shaped portions off the general plane of the condenser **148** and a U-shaped portion **250** aligned or substantially aligned with the general plane of the condenser **148**. The wires **252**, **254**, the upper tip of the wires **256**, and the wire lower bends **258**, **260** of the second condenser **148** are aligned with the upper tip of the wires **262** the wire lower bends **264**, **266** of the first condenser **146**. When assembled, the tubular conduit U-shaped passes **250**, **268** in the general plane of the condenser **146**, **148** may align with each other and provide a planar mounting surface for the fastener(s) **158**, when fasteners are employed.

Referring to FIG. **8**, the first condenser **146** is inserted into the air passageway **131**. The second condenser **148** is aligned and positioned in matingly engaged configuration with the first condenser **146**. A fastener **158** may be inserted through the tubular conduit U-shaped pass **250**, **268** to fasten the condenser assembly **130** to the air passageway **131**. At least one of a valve or a connector (not shown) for the condenser assembly **130** may then be assembled into operative engagement with the condenser assembly **130**.

As shown in FIG. **9A**, a condenser assembly **272** according to an embodiment of the invention includes a first condenser **274**, a second condenser **276**, and a third condenser **278**. Optional spacers **280**, **282**, **284** may be located between the condensers **274**, **276**, **278** (see FIG. **9B**). The condensers **274**, **276**, **278** are sub-condensers of the overall condenser assembly **272**. These condensers are shown in FIG. **9B** and profiled in such a way as to present from a side view and relative to at least one part of its length an inclination in the direction of which is suddenly inverted **286** at least once relative to a plane which is substantially parallel to the general plane of the condensers **274**, **276**, **278**. The condensers **274**, **276**, **278** typically have a second inclination of which is progressively inverted **288** compared to and relative to the sudden invention **286** at least once relative to a plane, which is substantially parallel to the general plane of the condenser **276**. The profile of the condensers **274**, **276**, **278** or the profile of any of the condensers of a condenser assembly **272** according to any aspect of the present invention may be adjusted based on the shape of the air passageway **131** and/or the machine compartment **122** and/or adjusted to fit around other components in the air passageway **131** or in the machine compartment **122**.

A condenser assembly **300** (FIG. **10**) may include a first condenser **302** and a second condenser **304** having a similar or identical lateral profiles over at least a portion of the first condenser **302** and a portion of the second condenser **304**. The first condenser **302** may have a longer or shorter length **306** and optionally a longer or shorter width **308** than the

second condenser **304**. The first condenser **302** and the second condenser **304** may have different amounts of wires **310**, and varied placement of the wires **310** on the condensers **302**, **304**. Different configurations of U-shaped passes **312** of the tubular conduit **314** and optionally different amounts of tubular conduit **314** U-shaped passes **312** may also be employed. The first condenser **302** and the second condenser **304** are at least substantially locked and positioned in a matingly engaged (typically frictionally matingly engaged) configuration forming a condenser assembly **300** with a positional alignment between the first condenser **302** and the second condenser **304**. The first condenser **302** and the second condenser **304** may be positioned in various configurations based on the application. The second condenser **304** may be aligned in any position and orientation where the lateral profiles of the two condensers **302**, **304** are similar over at least a portion of both condensers **302**, **304**.

A condenser assembly **130** may be positioned in a variety of alternate locations in an appliance **100** (FIG. 11). The condenser assembly **130** may be located in an air passageway **131** near the bottom of the appliance **370**, along the back of the appliance **372** above the machine compartment **122**, in the interior **374** of the appliance **100**, near the top **116** of the appliance **100** (not shown), or on the exterior surface **376** of the appliance **100**. The airflow over the condenser assembly **130** may be by natural convention or assisted by one or more than one fan (not shown).

The airflow path **400** through the condenser assembly **130** is shown in FIG. 12. A portion, but typically multiple portions, of the airflow **402** moving generally substantially parallel from one side to the other across the condenser assembly is able to flow through the condenser assembly **130** unimpeded. A portion of the airflow **404** is obstructed by the tubular conduit **406** and is diverted around the tubular conduit **406**. The air flowing through the condenser assembly **130** flows over additional tube segments **406** due to the plurality of sub-condensers **146**, **148** that make up the overall condenser assembly **130**. This increase in number of tube segments **406** increases the resistance to air flow and typically results in an increased air pressure drop.

The alignment of the at least two condensers **146**, **148** in the condenser assembly **130** may be adjusted to minimize the air pressure drop. When the at least two condensers **146**, **148** are at least substantially locked and positioned in a matingly engaged configuration where the at least two condensers **146**, **148** are nested, stacked, spaced apart, or layered, the tubular conduit U-shaped passes are typically spaced in such a way that the airflow is distributed more evenly across the face area of the condenser assembly **130**. The "face area of the condenser assembly" is the width **407** of the condenser assembly **130** multiplied by the height **246** of the condenser assembly **130** (FIG. 7B). This results in a more even distribution of the heat transfer across all the tubes and wires of the condenser assembly **130**. Spacers may be used to adjust the airflow path through the condenser assembly **130**.

The contour of each condenser **146**, **148** can be adjusted to optimally improve the airflow and heat transfer when at least two condensers **146**, **148** are stacked, nested, layered, spaced apart, or assembled together to form the condenser assembly **130**. The wire tips **408**, **410** of the first condenser **146** are typically aligned with the wire tips **412**, **414** of the second condenser **148**. The wire frame **416** of the first condenser **146** rests on the wire frame **418** of the second condenser **148**. The tubular straight sections **420** of the first condenser **146** are typically offset from the tubular straight sections **406** of the second condenser **148**.

The first condenser **450** is operationally connected to a second condenser **452** in series in the schematic view of an appliance heat exchange circuit **454** shown in FIG. 13. The outlet **456** of a compressor **458** is operationally connected or engaged to the inlet **460** of the first condenser **450** to allow refrigerant flow **461**. The direction of refrigerant flow **461** in the heat exchange circuit is shown with arrows **461**. The outlet **462** of the first condenser **450** is operationally connected to the inlet **464** of a second condenser **452** to allow refrigerant flow. The outlet **466** of the second condenser **452** is operationally connected to the inlet **468** of an expansion device, such as a capillary tube, which is part of a suction line heat exchanger assembly **470** to allow refrigerant flow. The outlet **472** of the suction line heat exchanger **470** is operationally connected to the inlet **474** of an evaporator **476**. The outlet **478** of the evaporator **476** is operationally connected to the inlet **480** on the return side or suction line of suction line heat exchanger assembly **470**. The outlet **482** on the return side of the suction line heat exchanger **470** is operationally connected to the inlet **484** of the compressor **458**.

The heat exchange circuit **550** of FIG. 14 shows the inlets and outlets of the condenser assembly **552** operationally connected in parallel. The heat exchange circuit **554** includes a compressor **554**, a condenser assembly **552**, a suction line heat exchanger assembly **556**, and an evaporator **558**. The condenser assembly **552** includes a first condenser **560** and a second condenser **562** operationally connected in parallel. A suction line heat exchanger assembly **556** typically includes both an expansion device, such as a capillary tube (not shown), and a suction line (not shown). The heat exchange circuit **550** may include an expansion device (not shown) without having an optional capillary tube. A suction line heat exchanger assembly **556** typically includes a suction line in mechanical contact with a capillary tube in order to conduct heat away from the capillary tube to the suction line.

The first condenser **644** and the second condenser **648** in a schematic view of an appliance heat exchange circuit **650** as shown in FIG. 15 may be selectively connected in parallel **652** or in series **654**. The heat exchange circuit **650** typically includes a compressor **656**, a compact condenser assembly **658**, a suction line heat exchanger **660**, and an evaporator **662**. A two-position valve **664** is typically used to connect the first condenser **644** and the second condenser **648** operationally in parallel **652** or operationally in series **654**. The appliance includes a controller **668** which can selectively operate the two-position valve **664** to switch between an operation mode where the system operates with the two-position valve **664** in the series position **654**, and another operation mode where the system operates with the two-position valve **664** in the parallel position **652**. The two-position valve **664** may be actuated electrically, mechanically, hydraulically, pneumatically, thermally, or the like. The two-position valve **664** may be moved from the series position **654** to the parallel position **652** (and vice versa) using a wax motor, a motor, a solenoid, an electrically operated switch, a spring, a timing cam, and the like. The two-position valve **664** is shown as laterally movable in FIG. 15. The controller **668** can selectively operate the two-position valve **664** automatically, based upon sensor input **670**, and/or based on a user input such as a selectable switch **672**. The controller **668** may be a computer system with a CPU and memory subsystem that stores code for use in dynamically controlling the use of the condenser assembly **658**. The controller **668** may be an electromechanical timer. The controller **668** may also employ one or more micropro-

15

cessors, which typically incorporates the functions of a computer system's central processing unit (CPU) or a single integrated circuit (IC). In FIG. 15, the encircled "A" elements show where the controller 668 connects with the two-position valve 664 for clarity.

An appliance utilizing a condenser assembly may be configured to operate each individual condenser of the condenser assembly independently. Depending on the needs of the application, the appliance may be configured to operationally connect the at least two condensers in parallel, in series, or in a selectable configuration using valves or conduit connectors. The pairs of inlets and outlets of the individual condensers may be operationally connected to different heat exchange circuits, to different ports on a compressor, typically a two-stage compressor, linear compressor, or a variable speed compressor, or connected together as discussed previously. Alternatively, the selectable configuration may operationally reverse the direction of refrigerant flow through at least one of the individual condensers, restrict the amount of refrigerant flow through at least one of the individual condensers, and/or block refrigerant flow through at least one of the individual condensers.

The appliance may have a controller that selectively controls the flow of refrigerant through the condensers. The appliance may have at least one sensor to monitor the ambient air temperature, the refrigerant air temperature, the refrigerator air temperature, the freezer air temperature, the refrigerant pressure, and/or ambient humidity and the like. The controller may selectively control the at least one valve or connector based on the sensed input and/or based on input from one or more sensors, a timing chart, a switch, an algorithm, a cycle profile, a user selected input or option, opening or closing a door, drawer, or other access to the appliance interior, temperature of an internal volume in the appliance, ambient temperature outside of the appliance, an signal from outside of the appliance, thermal loading of an internal volume in the appliance, temperature or pressure of the refrigerant, a defrost step, an ice making step, time of day, time of year, energy consumption of the appliance, and the like.

The first condenser 750 and the second condenser 752 of the schematic view of an appliance heat exchange circuit 754 of FIG. 16 may be selectively connected in series 756 or configured such that one of the condensers is bypassed 758. The heat exchange circuit 754 typically includes a compressor 760, a compact condenser assembly 762, a suction line heat exchanger 764, and an evaporator 766. A two-position valve 768 is used to connect the first condenser 750 and the second condenser 752 in a series configuration when the two-position valve 768 is in the series position 756. The first condenser 750 and the second condenser 752 are connected in a bypass configuration when the two-position valve 768 is in the bypass position 758. The two-position valve 768 is shown in FIG. 16 assembled as part of the condenser assembly 762. The appliance may have a controller (not shown) to selectively operate the two-position valve 768.

As shown in FIG. 17, a condenser assembly 850 may employ two condensers 852, 854 each having a cross-section U-shaped profile 856, 858 where both condensers are nested together to form the condenser assembly 850 by inserting a straight section 860 of one condenser 852 into the space between the two straight sections 862, 864 of the second condenser 854. Optional spacers 866, 868 are shown.

A condenser assembly increases the amount of heat transfer surface area while minimizing the increase in the overall dimensions of the condenser assembly. The condenser assembly can be assembled as a unit and then placed

16

into an appliance as a unit. Alternatively, the condensers can be assembled into the appliance individually and then fastened to each other or fastened to one or more mounting surfaces. The individual condensers may be positioned in a matingly engaged configuration in the appliance without using fasteners or spacers.

The at least one of a valve or a connector between the inlets and outlets of the individual condensers in the condenser assembly, may be assembled into the condenser assembly prior to placement in an appliance. Alternatively, the at least one of a valve or a connector may be assembled as part of the appliance. The inlets and outlets of the condenser assembly may be connected to the at least one of a valve or a connector when the condenser assembly is located in the appliance or before the condenser assembly is placed into the appliance.

By using at least two separately and independently produced condensers to form a condenser assembly, the individual condensers may be used as a sole condenser in certain applications where less heat transfer surface area is needed, but also used as a modular system for multiple appliances or when greater heat transfer surface area is more beneficial based upon appliance configuration or energy efficiency or both.

The above description is considered that of the preferred embodiment only. Modifications of the invention will occur to those skilled in the art and to those who make or use the invention. Therefore, it is understood that the embodiments shown in the drawings and described above is merely for illustrative purposes and not intended to limit the scope of the invention, which is defined by the following claims as interpreted according to the principles of patent law, including the Doctrine of Equivalents.

The invention claimed is:

1. A wire on tube condenser assembly comprising:

a first individual wire on tube condensers and a second individual wire on tube condenser, where each of the individual wire on tube condensers has a condenser inlet and a condenser outlet;

wherein the individual wire on tube condensers are at least substantially locked and positioned in matingly engaged plural inverted V-shaped configurations forming the condenser assembly; and

wherein the individual wire on tube condensers are configured to be operationally connected;

wherein each of the individual wire on tube condensers further comprise a tubular conduit comprising a plurality of substantially straight tube sections interconnected by a plurality of U-shaped tube passes,

wherein a first substantially straight tube section of the first individual wire on tube condenser is positioned adjacent to a corresponding second substantially straight tube section of the of the second individual wire on tube condenser such that the adjacent corresponding substantially straight tube sections are spatially offset in reference to an airflow path of the condenser assembly, wherein the offset of at least two of the corresponding substantially straight tube sections is offset both vertically and horizontally in relation to the airflow path.

2. The wire on tube condenser assembly of claim 1, wherein each of the individual wire on tube condensers further comprise:

a serpentine tubular conduit having a serpentine tubular conduit inlet, a serpentine tubular conduit outlet, a plurality of U-shaped tube passes, each pass having two substantially straight tube sections joined by a

17

U-shaped bend section, the two substantially straight tube sections oriented across a width of the serpentine tubular conduit, and the serpentine tubular conduit having a flow path progressing from the serpentine tubular conduit inlet, through the plurality of U-shaped tube passes, making alternate back and forth passes in a direction along the width of the serpentine tubular conduit, progressing along a length of the serpentine tubular conduit, and progressing to the serpentine tubular conduit outlet, and an extended heat transfer surface arranged connected to the two substantially straight tube sections across the length of the serpentine tubular conduit wherein the extended heat transfer surface comprises a plurality of wires wrapped around a length of the serpentine tubular conduit.

3. The wire on tube condenser assembly of claim 1, wherein the wire on tube condensers are configured to be operationally connected in at least one of the following: a parallel configuration, a series configuration, a configuration where the condensers are operationally connected in a parallel configuration and a series configuration, a bypass configuration where at least one condenser is operationally disconnected from the condenser assembly, a reverse configuration where the inlet and outlet of at least one condenser is operationally reversed, and a split configuration where at least one of the condensers is operationally connected to a separate heat exchange circuit.

4. The wire on tube condenser assembly of claim 1, wherein the wire on tube condensers are configured to be operationally connected in at least two of the following: a parallel configuration, a series configuration, a configuration where the condensers are operationally connected in a parallel configuration and a series configuration, a bypass configuration where at least one condenser is operationally disconnected from the condenser assembly, a reverse configuration where the inlet and outlet of at least one condenser is operationally reversed, and a split configuration where at least one of the condensers is operationally connected to a separate heat exchange circuit.

5. The wire on tube condenser assembly of claim 1, wherein each of the individual wire on tube condensers are profiled in such a way to present from a lateral side view and relative to at least one part of its length an inclination in a direction of which is inverted at least once relative to a plane which is substantially parallel to the general plane of the wire on tube condenser.

6. The wire on tube condenser assembly of claim 1, wherein the individual wire on tube condensers are separated by at least one spacer, wherein the at least one spacer directly connects to two condensers.

7. The wire on tube condenser assembly of claim 1, wherein a plurality of the corresponding substantially straight tube sections of the V-shaped configuration is offset both perpendicular to and along the airflow path.

8. An appliance comprising:

a machine compartment having a housing with at least one airflow path; an air passageway, operationally connected to the machine compartment and configured to provide an airflow path into the machine compartment, containing:

at least two sets of individual wire on tube condensers; where each of the at least two sets of individual wire on tube condensers has a condenser inlet and a condenser outlet; and

an exhaust port for discharging heated air radiated from the at least two sets of individual wire on tube condensers;

18

where the at least two sets of individual wire on tube condensers are at least substantially locked and positioned in matingly engaged plural inverted V-shaped configurations forming a condenser assembly; and where the at least two sets of individual wire on tube condensers are operationally connected;

wherein each of the at least two sets of individual wire on tube condensers comprises a plurality of substantially straight tube sections arranged adjacent a corresponding plurality of substantially straight tube section of a neighboring individual wire on tube condenser,

wherein each of the corresponding substantially straight tube sections of the neighboring individual wire on tube condensers is offset spatially both perpendicular to and along the airflow path.

9. The appliance of claim 8, wherein each of the at least two sets of individual wire on tube condensers further comprises:

a serpentine tubular conduit having a serpentine tubular conduit inlet, a serpentine tubular conduit outlet, a plurality of U-shaped tube passes,

each pass having two substantially straight tube sections joined by a U-shaped bend section,

the two substantially straight tube sections oriented across a width of the serpentine tubular conduit, and

the serpentine tubular conduit having a flow path progressing from the serpentine tubular conduit inlet, through the plurality of U-shaped tube passes, making alternate back and forth passes in a direction along the width of the serpentine tubular conduit, progressing along a length of the serpentine tubular conduit, and progressing to the serpentine tubular conduit outlet, and an extended heat transfer surface arranged connected to the two substantially straight tube sections across the length of the serpentine tubular conduit

wherein the extended heat transfer surface comprises a plurality of wires wrapped around a length of the serpentine tubular conduit.

10. The appliance of claim 8, wherein the wire on tube condensers are operationally connected in at least one of the following: parallel configuration, a series configuration, a configuration where the condensers are operationally connected in a parallel configuration and a series configuration, a bypass configuration where at least one condenser is operationally disconnected from the condenser assembly, a reverse configuration where the inlet and outlet of at least one condenser is operationally reversed, and a split configuration where at least one of the condensers is operationally connected to a separate heat exchange circuit.

11. The appliance of claim 8, wherein each of the at least two sets of individual wire on tube condensers are profiled in such a way to present from a lateral side view and relative to at least one part of its length an inclination in a direction of which is suddenly or progressively inverted at least once relative to a plane which is substantially parallel to the general plane of the wire on tube condenser.

12. The appliance of claim 11, wherein the wire on tube condensers are operationally connected in at least one of the following: parallel configuration, a series configuration, a configuration where the condensers are operationally connected in a parallel configuration and a series configuration, a bypass configuration where at least one condenser is operationally disconnected from the condenser assembly, a reverse configuration where the inlet and outlet of at least one condenser is operationally reversed, and a split configuration where at least one of the condensers is operationally connected to a separate heat exchange circuit.

19

13. The appliance of claim 8, wherein the at least two sets of individual wire on tube condensers are separated by at least one spacer, wherein the at least one spacer directly connects to two condensers.

14. The appliance of claim 8, wherein the at least two sets of individual wire on tube condensers are fastened to a surface of the air passageway with at least one fastener.

15. The appliance of claim 8, wherein the machine compartment further comprises a fan spaced within an interior volume of the machine compartment and configured to cause a flow of cooling air into the machine compartment from outside the machine compartment.

16. The appliance of claim 8, wherein the appliance is a refrigerator.

17. The appliance of claim 8, wherein the substantially straight tube sections of the individual wire on tube condensers are arranged perpendicular to the V-shaped configuration such that a plurality of the substantially straight tube sections of the neighboring individual wire on tube condenser are offset laterally in an outboard direction in relation to the V-shaped configuration.

18. A method for assembling a condenser assembly comprising the step of:

producing at least two sets of individual wire on tube condensers;

configuring the at least two wire on tube condensers to be operationally connected such that an air flow path is established through the condenser assembly; and

engaging the at least two wire on tube condensers with one another such that the condensers are at least

20

substantially locked and positioned in matingly engaged plural inverted V-shaped configurations thereby forming the condenser assembly;

wherein the at least two sets of individual wire on tube condenser assembly includes a plurality of stacked inverted V-shaped configurations; and

wherein the two sets of individual wire on tube condensers further comprise a tubular conduit comprising a plurality of substantially straight tube sections interconnected by a plurality of U-shaped tube passes, wherein an adjacent pair of the substantially straight tube sections of each of the individual wire on tube condensers is offset both perpendicular to and along the air flow path forming the two wire on tube condensers of the condenser assembly.

19. The method of claim 18, further wherein the at least two separately and independently produced wire on tube condensers comprise a first condenser and a second condenser; and the method further comprising the steps of:

installing the first condenser within an appliance in an operational configuration, and

installing the second condenser in an operational configuration and within the appliance such that the second condenser is substantially locked and positioned in the matingly engaged configuration with the first condenser thereby forming the condenser assembly within the appliance.

* * * * *