



(12) **United States Patent**
Quanci et al.

(10) **Patent No.:** **US 9,708,542 B2**
(45) **Date of Patent:** **Jul. 18, 2017**

(54) **METHOD AND SYSTEM FOR OPTIMIZING COKE PLANT OPERATION AND OUTPUT**

1,140,798 A 5/1915 Carpenter
(Continued)

(71) Applicant: **SUNCOKE TECHNOLOGY AND DEVELOPMENT LLC**, Lisle, IL (US)

FOREIGN PATENT DOCUMENTS

(72) Inventors: **John Francis Quanci**, Haddonfield, NJ (US); **Chun Wai Choi**, Chicago, IL (US); **Mark Anthony Ball**, Richland, VA (US); **Dexter Junior Mounts**, Raven, VA (US); **Roy Jimmy Griffey, II**, Grundy, VA (US)

CA 1172895 8/1984
CA 2775992 A1 5/2011
(Continued)

OTHER PUBLICATIONS

(73) Assignee: **SUNCOKE TECHNOLOGY AND DEVELOPMENT LLC**, Lisle, IL (US)

U.S. Appl. No. 14/655,003, filed Jun. 23, 2015, Ball, Mark A., et al.
U.S. Appl. No. 14/655,013, filed Jun. 23, 2015, West, Gary D., et al.
U.S. Appl. No. 14/655,204, filed Jun. 24, 2015, Quanci, John F., et al.
U.S. Appl. No. 14/839,384, filed Aug. 28, 2015, Quanci, John F., et al.
U.S. Appl. No. 14/839,493, filed Aug. 28, 2015, Quanci, John F., et al.
U.S. Appl. No. 14/839,551, filed Aug. 28, 2015, Quanci, John F., et al.
U.S. Appl. No. 14/865,581, filed Sep. 25, 2015, Sarpen, Jacob P., et al.

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **14/839,588**

(22) Filed: **Aug. 28, 2015**

(65) **Prior Publication Data**

US 2016/0060533 A1 Mar. 3, 2016

Related U.S. Application Data

(60) Provisional application No. 62/043,359, filed on Aug. 28, 2014.

Primary Examiner — In Suk Bullock
Assistant Examiner — Jonathan Pilcher

(51) **Int. Cl.**

C10B 5/00 (2006.01)
C10B 15/02 (2006.01)

(Continued)

(74) *Attorney, Agent, or Firm* — Perkins Coie LLP

(52) **U.S. Cl.**

CPC **C10B 25/02** (2013.01); **C10B 31/00** (2013.01); **C10B 31/02** (2013.01); **C10B 31/06** (2013.01);

(Continued)

(57) **ABSTRACT**

The present technology is generally directed to methods of increasing coke production rates for coke ovens. In some embodiments, a coal charging system includes a false door system with a false door that is vertically oriented to maximize an amount of coal being charged into the oven. A lower extension plate associated with embodiments of the false door is selectively, automatically extended beyond a lower end portion of the false door in order to extend an effective length of the false door. In other embodiments an extension plate may be coupled with an existing false door having an angled front surface to provide the existing false door with a vertically oriented face.

(58) **Field of Classification Search**

CPC C10B 45/02; C10B 9/00; C10B 37/02; C10B 37/04; C10B 31/00; C10B 31/02;


(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

469,868 A 3/1892 Thomas et al.

12 Claims, 29 Drawing Sheets



(51)	Int. Cl.		3,912,091 A	10/1975	Thompson
	<i>C10B 31/00</i>	(2006.01)	3,917,458 A	11/1975	Polak
	<i>C10B 31/06</i>	(2006.01)	3,928,144 A	12/1975	Jakimowicz
	<i>C10B 31/08</i>	(2006.01)	3,930,961 A	1/1976	Sustarsic et al.
	<i>C10B 25/02</i>	(2006.01)	3,957,591 A	5/1976	Riecker
	<i>C10B 31/02</i>	(2006.01)	3,959,084 A	5/1976	Price
	<i>C10B 37/04</i>	(2006.01)	3,963,582 A	6/1976	Helm et al.
	<i>C10B 39/06</i>	(2006.01)	3,969,191 A	7/1976	Bollenbach et al.
	<i>C10B 31/10</i>	(2006.01)	3,975,148 A	8/1976	Fukuda et al.
	<i>C10B 57/08</i>	(2006.01)	3,984,289 A	10/1976	Sustarsic et al.
	<i>C10B 57/02</i>	(2006.01)	4,004,702 A	1/1977	Szendroi
	<i>C10B 37/02</i>	(2006.01)	4,004,983 A	1/1977	Pries
	<i>C10B 15/00</i>	(2006.01)	4,040,910 A	8/1977	Knapstein et al.
(52)	U.S. Cl.		4,059,885 A	11/1977	Oldengott
	CPC	<i>C10B 31/08</i> (2013.01); <i>C10B 31/10</i> (2013.01); <i>C10B 37/02</i> (2013.01); <i>C10B 37/04</i> (2013.01); <i>C10B 39/06</i> (2013.01); <i>C10B 57/02</i> (2013.01); <i>C10B 57/08</i> (2013.01); <i>C10B 5/00</i> (2013.01); <i>C10B 15/00</i> (2013.01); <i>C10B 15/02</i> (2013.01)	4,067,462 A	1/1978	Thompson
			4,083,753 A	4/1978	Rogers et al.
			4,086,231 A	4/1978	Ikio
			4,100,033 A	7/1978	Holter
			4,111,757 A	9/1978	Ciarimboli
			4,124,450 A	11/1978	MacDonald
			4,141,796 A	2/1979	Clark et al.
			4,145,195 A	3/1979	Knapstein et al.
			4,147,230 A	4/1979	Ormond et al.
			4,162,546 A	7/1979	Shortell et al.
			4,189,272 A	2/1980	Gregor et al.
(58)	Field of Classification Search		4,194,951 A	3/1980	Pries
	CPC	C10B 31/04; C10B 31/06; C10B 31/08; C10B 33/00; C10B 33/08; C10B 33/10; C10B 37/00; C10B 31/10; C10B 25/06; C10B 25/08; C10B 25/12; C10B 25/16	4,196,053 A	4/1980	Grohmann
		See application file for complete search history.	4,211,608 A	7/1980	Kwasnoski et al.
			4,211,611 A	7/1980	Bocsanczy
			4,213,489 A	7/1980	Cain
			4,213,828 A	7/1980	Calderon
			4,222,748 A	9/1980	Argo et al.
			4,222,824 A	9/1980	Flockenhaus et al.
			4,224,109 A	9/1980	Flockenhaus et al.
(56)	References Cited		4,225,393 A	9/1980	Gregor et al.
	U.S. PATENT DOCUMENTS		4,235,830 A	11/1980	Bennett et al.
			4,239,602 A	12/1980	La Bate
	1,424,777 A	8/1922	4,248,671 A	2/1981	Belding
	1,430,027 A	9/1922	4,249,997 A	2/1981	Schmitz
	1,486,401 A	3/1924	4,263,099 A	4/1981	Porter
	1,572,391 A	2/1926	4,285,772 A	8/1981	Kress
	1,721,813 A	7/1929	4,287,024 A	9/1981	Thompson
	1,818,370 A	8/1931	4,289,584 A	9/1981	Chuss et al.
	1,818,994 A	8/1931	4,289,585 A	9/1981	Wagener et al.
	1,848,818 A	3/1932	4,296,938 A	10/1981	Offermann et al.
	1,955,962 A	4/1934	4,303,615 A	12/1981	Jarmell et al.
	2,075,337 A	3/1937	4,307,673 A	12/1981	Caughy
	2,394,173 A	2/1946	4,314,787 A	2/1982	Kwasnick et al.
	2,424,012 A	7/1947	4,330,372 A	5/1982	Cairns et al.
	2,667,185 A	1/1954	4,334,963 A	6/1982	Stog
	2,756,842 A	7/1956	4,336,843 A	6/1982	Petty
	2,873,816 A	2/1959	4,340,445 A	7/1982	Kucher et al.
	2,902,991 A	9/1959	4,342,195 A	8/1982	Lo
	3,015,893 A	1/1962	4,344,820 A	8/1982	Thompson
	3,033,764 A	5/1962	4,366,029 A	12/1982	Bixby et al.
	3,462,345 A	8/1969	4,373,244 A	2/1983	Mertens et al.
	3,511,030 A	5/1970	4,375,388 A	3/1983	Hara et al.
	3,545,470 A	12/1970	4,391,674 A	7/1983	Velmin et al.
	3,616,408 A	10/1971	4,392,824 A	7/1983	Struck et al.
	3,630,852 A	12/1971	4,395,269 A	7/1983	Schuler
	3,652,403 A	3/1972	4,396,394 A	8/1983	Li et al.
	3,676,305 A	7/1972	4,396,461 A	8/1983	Neubaum et al.
	3,709,794 A	1/1973	4,431,484 A	2/1984	Weber et al.
	3,710,551 A	1/1973	4,439,277 A	3/1984	Dix
	3,746,626 A	7/1973	4,440,098 A	4/1984	Adams
	3,748,235 A	7/1973	4,445,977 A	5/1984	Husher
	3,784,034 A *	1/1974	4,446,018 A	5/1984	Cerwick
			4,448,541 A	5/1984	Wirtschaffter
			4,452,749 A	6/1984	Kolvek et al.
			4,459,103 A	7/1984	Gieskieng
			4,469,446 A	9/1984	Goodboy
			4,498,786 A	2/1985	Ruscheweyh
			4,508,539 A	4/1985	Nakai
			4,527,488 A	7/1985	Lindgren
			4,568,426 A	2/1986	Orlando
			4,570,670 A	2/1986	Johnson
			4,614,567 A	9/1986	Stahlherm et al.
			4,643,327 A	2/1987	Campbell
			4,645,513 A	2/1987	Kubota et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

4,655,193 A 4/1987 Blacket
 4,655,804 A 4/1987 Kercheval et al.
 4,666,675 A 5/1987 Parker et al.
 4,680,167 A 7/1987 Orlando et al.
 4,704,195 A 11/1987 Janicka et al.
 4,720,262 A 1/1988 Durr et al.
 4,726,465 A 2/1988 Kwasnik et al.
 4,793,931 A 12/1988 Stevens et al.
 4,824,614 A 4/1989 Jones et al.
 4,919,170 A 4/1990 Kallinich et al.
 4,929,179 A 5/1990 Breidenbach et al.
 4,941,824 A 7/1990 Holter et al.
 5,052,922 A 10/1991 Stokman et al.
 5,062,925 A 11/1991 Durselen et al.
 5,078,822 A 1/1992 Hodges et al.
 5,087,328 A 2/1992 Wegerer et al.
 5,114,542 A 5/1992 Childress et al.
 5,227,106 A 7/1993 Kolvek
 5,228,955 A 7/1993 Westbrook, III
 5,318,671 A 6/1994 Pruitt
 5,447,606 A 9/1995 Pruitt
 2,723,725 A 11/1995 Keiffer
 5,480,594 A 1/1996 Wilkerson et al.
 5,622,280 A 4/1997 Mays et al.
 5,670,025 A 9/1997 Baird
 5,687,768 A 11/1997 Albrecht et al.
 5,787,821 A 8/1998 Bhat et al.
 5,810,032 A 9/1998 Hong et al.
 5,857,308 A 1/1999 Dismore et al.
 5,928,476 A 7/1999 Daniels
 5,968,320 A 10/1999 Sprague
 6,017,214 A 1/2000 Sturgulewski
 6,059,932 A * 5/2000 Sturgulewski C10B 15/02
 201/40
 6,139,692 A 10/2000 Tamura et al.
 6,152,668 A 11/2000 Knoch
 6,187,148 B1 2/2001 Sturgulewski
 6,189,819 B1 2/2001 Racine
 6,290,494 B1 9/2001 Barkdoll
 6,412,221 B1 7/2002 Emsbo
 6,596,128 B2 7/2003 Westbrook
 6,626,984 B1 9/2003 Taylor
 6,699,035 B2 3/2004 Brooker
 6,758,875 B2 7/2004 Reid et al.
 6,907,895 B2 6/2005 Johnson et al.
 6,946,011 B2 9/2005 Snyder
 6,964,236 B2 * 11/2005 Schucker C10B 37/02
 110/101 R
 7,056,390 B2 6/2006 Fratello
 7,077,892 B2 7/2006 Lee
 7,314,060 B2 1/2008 Chen et al.
 7,331,298 B2 2/2008 Barkdoll et al.
 7,497,930 B2 3/2009 Barkdoll et al.
 7,611,609 B1 11/2009 Valia et al.
 7,644,711 B2 1/2010 Creel
 7,722,843 B1 5/2010 Srinivasachar
 7,727,307 B2 6/2010 Winkler
 7,803,627 B2 9/2010 Hodges
 7,827,689 B2 11/2010 Crane et al.
 7,998,316 B2 8/2011 Barkdoll et al.
 8,071,060 B2 12/2011 Ukai et al.
 8,079,751 B2 12/2011 Kapila et al.
 8,152,970 B2 4/2012 Barkdoll et al.
 8,236,142 B2 8/2012 Westbrook et al.
 8,266,853 B2 9/2012 Bloom et al.
 8,398,935 B2 3/2013 Howell, Jr. et al.
 2002/0170605 A1 11/2002 Shiraiishi et al.
 2003/0014954 A1 1/2003 Ronning et al.
 2003/0015809 A1 1/2003 Carson
 2006/0102420 A1 5/2006 Huber et al.
 2007/0116619 A1 5/2007 Taylor et al.
 2007/0251198 A1 11/2007 Witter
 2008/0028935 A1 2/2008 Andersson
 2008/0169578 A1 7/2008 Crane et al.
 2008/0179165 A1 7/2008 Chen et al.

2008/0257236 A1 10/2008 Green
 2008/0271985 A1 11/2008 Yamasaki
 2008/0289305 A1 11/2008 Girondi
 2009/0152092 A1 6/2009 Kim et al.
 2009/0217576 A1 9/2009 Kim et al.
 2009/0283395 A1 11/2009 Hippe
 2010/0095521 A1 4/2010 Bertini et al.
 2010/0115912 A1 5/2010 Worley et al.
 2010/0287871 A1 11/2010 Bloom et al.
 2010/0300867 A1 12/2010 Kim et al.
 2011/0048917 A1 3/2011 Kim et al.
 2011/0120852 A1 5/2011 Kim et al.
 2011/0174301 A1 7/2011 Haydock et al.
 2011/0192395 A1 8/2011 Kim et al.
 2011/0223088 A1 9/2011 Chang et al.
 2011/0253521 A1 10/2011 Kim
 2011/0315538 A1 12/2011 Kim et al.
 2012/0024688 A1 2/2012 Barkdoll
 2012/0030998 A1 2/2012 Barkdoll
 2012/0152720 A1 6/2012 Reichelt et al.
 2012/0228115 A1 9/2012 Westbrook
 2012/0247939 A1 10/2012 Kim et al.
 2012/0305380 A1 12/2012 Wang et al.
 2013/0216717 A1 8/2013 Rago et al.
 2013/0220373 A1 8/2013 Kim
 2013/0306462 A1 11/2013 Kim et al.
 2014/0033917 A1 2/2014 Rodgers et al.
 2014/0048402 A1 2/2014 Quanci et al.
 2014/0048404 A1 2/2014 Quanci et al.
 2014/0048405 A1 2/2014 Quanci et al.
 2014/0061018 A1 3/2014 Sarpen et al.
 2014/0083836 A1 3/2014 Quanci et al.
 2014/0182195 A1 7/2014 Quanci et al.
 2014/0182683 A1 7/2014 Quanci et al.
 2014/0183023 A1 7/2014 Quanci et al.
 2014/0183024 A1 7/2014 Chun et al.
 2014/0183026 A1 7/2014 Quanci et al.
 2014/0224123 A1 8/2014 Walters
 2014/0262139 A1 9/2014 Choi et al.
 2014/0262726 A1 9/2014 West et al.
 2015/0122629 A1 5/2015 Freimuth et al.
 2015/0247092 A1 9/2015 Quanci et al.
 2015/0287026 A1 10/2015 Yang et al.

FOREIGN PATENT DOCUMENTS

CA 2822841 7/2012
 CA 2822857 A1 7/2012
 CN 2064363 U 10/1990
 CN 1092457 A 9/1994
 CN 1255528 A 6/2000
 CN 1358822 A 7/2002
 CN 2509188 Y 9/2002
 CN 2528771 Y 1/2003
 CN 1468364 A 1/2004
 CN 2668641 Y 1/2005
 CN 101157874 A 4/2008
 CN 100510004 C 7/2009
 CN 101497835 A 8/2009
 CN 202226816 U 5/2012
 CN 103468289 A 12/2013
 DE 212176 C 7/1909
 DE 3315738 A1 11/1983
 DE 3231697 C1 1/1984
 DE 3329367 C1 11/1984
 DE 19545736 A1 6/1997
 DE 19803455 C1 8/1999
 DE 10154785 A1 5/2003
 DE 102005015301 10/2006
 DE 102006004669 8/2007
 DE 102009031436 A1 1/2011
 DE 102011052785 B3 12/2012
 EP 0208490 1/1987
 EP 2295129 3/2011
 FR 2339664 A1 8/1977
 GB 441784 A 1/1936
 GB 606340 A 8/1948
 GB 611524 A 11/1948
 GB 725865 A 3/1955

(56)

References Cited

FOREIGN PATENT DOCUMENTS

GB 871094 A 6/1961
 JP 50148405 A 11/1975
 JP 54054101 A 4/1979
 JP S5453103 A 4/1979
 JP 57051786 A 3/1982
 JP 57051787 A 3/1982
 JP 57083585 A 5/1982
 JP 57090092 A 6/1982
 JP 58091788 A 5/1983
 JP 59051978 A 3/1984
 JP 59053589 A 3/1984
 JP 59071388 A 4/1984
 JP 59108083 A 6/1984
 JP 59145281 A 8/1984
 JP 60004588 A 1/1985
 JP 61106690 A 5/1986
 JP 62011794 A 1/1987
 JP 62285980 A 12/1987
 JP 01103694 A 4/1989
 JP 01249886 A 10/1989
 JP H0319127 A 1/1991
 JP 06264062 9/1994
 JP 07188668 A 7/1995
 JP 07216357 A 8/1995
 JP 08127778 A 5/1996
 JP H10273672 A 10/1998
 JP 2000204373 A 7/2000
 JP 2001200258 A 7/2001
 JP 03197588 A 8/2001
 JP 2002106941 A 4/2002
 JP 200341258 A 2/2003
 JP 2003071313 A 3/2003
 JP 2003292968 A 10/2003
 JP 2003342581 A 12/2003
 JP 2005263983 A 9/2005
 JP 2007063420 A 3/2007
 JP 04159392 A 10/2008
 JP 2008231278 A 10/2008
 JP 2009144121 A 7/2009
 JP 2012102302 A 5/2012
 JP 2013006957 A 1/2013
 KR 1019990054426 A 7/1999
 KR 20000042375 A 7/2000
 KR 100296700 B1 10/2001
 KR 1020050053861 A 6/2005
 KR 100797852 B1 1/2008
 KR 10-2011-0010452 A 2/2011
 KR 101318388 B1 10/2013
 WO 9012074 A1 10/1990
 WO 9945083 A1 9/1999
 WO WO2005023649 3/2005
 WO WO2005115583 12/2005
 WO 2007103649 A2 9/2007
 WO 2008034424 A1 3/2008
 WO 2010107513 A1 9/2010
 WO 2011000447 A1 1/2011

WO 2012029979 A1 3/2012
 WO 2013023872 A1 2/2013
 WO WO2014021909 2/2014

OTHER PUBLICATIONS

ASTM D5341-99(2010)e1, Standard Test Method for Measuring Coke Reactivity Index (CRI) and Coke Strength After Reaction (CSR), ASTM International, West Conshohocken, PA, 2010.
 Clean coke process: process development studies by USS Engineers and Consultants, Inc., Wisconsin Tech Search, request date Oct. 5, 2011, 17 pages.
 Crelling, et al., "Effects of Weathered Coal on Coking Properties and Coke Quality", Fuel, 1979, vol. 58, Issue 7, pp. 542-546.
 Database WPI, Week 199115, Thomson Scientific, Lond, GB; AN 1991-107552.
 Diez, et al., "Coal for Metallurgical Coke Production: Predictions of Coke Quality and Future Requirements for Cokemaking", International Journal of Coal Geology, 2002, vol. 50, Issue 1-4, pp. 389-412.
 JP 03-197588, Inoqu Keizo et al., Method and Equipment for Boring Degassing Hole in Coal Charge in Coke Oven, Japanese Patent (Abstract Only) Aug. 28, 1991.
 JP 04-159392, Inoue Keizo et al., Method and Equipment for Opening Hole for Degassing of Coal Charge in Coke Oven, Japanese Patent (Abstract Only) Jun. 2, 1992.
 Rose, Harold J., "The Selection of Coals for the Manufacture of Coke," American Institute of Mining and Metallurgical Engineers, Feb. 1926, 8 pages.
 International Search Report and Written Opinion issued for PCT/US2015/047542 and mailed on Oct. 20, 2015, 11 pages.
 U.S. Appl. No. 14/952,267, filed Nov. 25, 2015, Quanci et al.
 U.S. Appl. No. 14/959,450, filed Dec. 4, 2015, Quanci et al.
 U.S. Appl. No. 14/983,837, filed Dec. 30, 2015, Quanci et al.
 U.S. Appl. No. 14/984,489, filed Dec. 30, 2015, Quanci et al.
 U.S. Appl. No. 14/986,284, filed Dec. 31, 2015, Quanci et al.
 U.S. Appl. No. 14/987,625, filed Jan. 4, 2016, Quanci et al.
 U.S. Appl. No. 15/014,547, filed Feb. 3, 2016, Choi et al.
 Basset, et al., "Calculation of steady flow pressure loss coefficients for pipe junctions," Proc Instn Mech Engrs., vol. 215, Part C. IMechIE 2001.
 Costa, et al., "Edge Effects on the Flow Characteristics in a 90 deg Tee Junction," Transactions of the ASME, Nov. 2006, vol. 128, pp. 1204-1217.
 U.S. Appl. No. 15/139,568, filed Apr. 27, 2016, Quanci et al.
 Waddell, et al., "Heat-Recovery Cokemaking Presentation," Jan. 1999, pp. 1-25.
 Westbrook, "Heat-Recovery Cokemaking at Sun Coke," AISE Steel Technology, Pittsburg, PA, vol. 76, No. 1, Jan. 1999, pp. 25-28.
 Yu et al., "Coke Oven Production Technology," Lianoning Science and Technology Press, first edition, Apr. 2014, pp. 356-358.
 "Resources and Utilization of Coking Coal in China," Mingxin Shen ed., Chemical Industry Press, first edition, Jan. 2007, pp. 242-243, 247.

* cited by examiner




FIG. 1
(PRIOR ART)




FIG.2B




FIG.2A




FIG. 3A




FIG. 3B




FIG. 4A




FIG. 4B




FIG.5




FIG.6




FIG. 7




FIG. 8




FIG. 9A







FIG. 9B

FIG. 9C

FIG. 9D








FIG. 11C






FIG. 12A




FIG. 12B




FIG. 12C




FIG. 13




FIG. 14




FIG. 15






FIG.16






FIG. 20




FIG. 19




FIG. 21




FIG. 22






FIG.23

106







FIG. 25B




FIG. 26




FIG.27




FIG.28




FIG.29




FIG. 30
(PRIOR ART)




FIG. 31
(PRIOR ART)




FIG. 32

514

544

548

546

550

524

504

516

522

542

176




FIG. 33

552

554

556




FIG. 34A




FIG. 34B




FIG. 34C




FIG. 35A




FIG. 35B




FIG. 35C

METHOD AND SYSTEM FOR OPTIMIZING COKE PLANT OPERATION AND OUTPUT

CROSS-REFERENCE TO RELATED APPLICATIONS

This application claims the benefit of priority to U.S. Provisional Patent Application No. 62/043,359, filed Aug. 28, 2014, the disclosure of which is incorporated herein by reference in its entirety.

TECHNICAL FIELD

The present technology is generally directed to optimizing the operation and output of coke plants.

BACKGROUND

Coke is a solid carbon fuel and carbon source used to melt and reduce iron ore in the production of steel. In one process, known as the "Thompson Coking Process," coke is produced by batch feeding pulverized coal to an oven that is sealed and heated to very high temperatures for approximately forty-eight hours under closely-controlled atmospheric conditions. Coking ovens have been used for many years to convert coal into metallurgical coke. During the coking process, finely crushed coal is heated under controlled temperature conditions to devolatilize the coal and form a fused mass of coke having a predetermined porosity and strength. Because the production of coke is a batch process, multiple coke ovens are operated simultaneously.

Much of the coke manufacturing process is automated due to the extreme temperatures involved. For example, a pusher charger machine ("PCM") is typically used on the coal side of the oven for a number of different operations. A common PCM operation sequence begins as the PCM is moved along a set of rails that run in front of an oven battery to an assigned oven and align a coal charging system of the PCM with the oven. The pusher side oven door is removed from the oven using a door extractor from the coal charging system. The PCM is then moved to align a pusher ram of the PCM to the center of the oven. The pusher ram is energized, to push coke from the oven interior. The PCM is again moved away from the oven center to align the coal charging system with the oven center. Coal is delivered to the coal charging system of the PCM by a tripper conveyor. The coal charging system then charges the coal into the oven interior. In some systems, particulate matter entrained in hot gas emissions that escape from the oven face are captured by the PCM during the step of charging the coal. In such systems, the particulate matter is drawn into an emissions hood through the baghouse of a dust collector. The charging conveyor is then retracted from the oven. Finally, the door extractor of the PCM replaces and latches the pusher side oven door.

With reference to FIG. 1, PCM coal charging systems **10** have commonly included an elongated frame **12** that is mounted on the PCM (not depicted) and reciprocally movable, toward and away from the coke ovens. A planar charging head **14** is positioned at a free distal end of the elongated frame **12**. A conveyor **16** is positioned within the elongated frame **12** and substantially extends along a length of the elongated frame **12**. The charging head **14** is used, in a reciprocal motion, to generally level the coal that is deposited in the oven. However, with regard to FIGS. 2A, 3A, and 4A, the prior art coal charging systems tend to leave voids **16** at the sides of the coal bed, as shown in FIG. 2A,

and hollow depressions in the surface of the coal bed. These voids limit the amount of coal that can be processed by the coke oven over a coking cycle time (coal processing rate), which generally reduces the amount of coke produced by the coke oven over the coking cycle (coke production rate). FIG. 2B depicts the manner in which an ideally charged, level coke bed would look.

The weight of coal charging system **10**, which can include internal water cooling systems, can be 80,000 pounds or more. When charging system **10** is extended inside the oven during a charging operation, the coal charging system **10** deflects downwardly at its free distal end. This shortens the coal charge capacity. FIG. 3A indicates the drop in bed height caused by the deflections of the coal charging system **10**. The plot depicted in FIG. 5 shows the coal bed profile along the oven length. The bed height drop, due to coal charging system deflection, is from five inches to eight inches between the pusher side to the coke side, depending upon the charge weight. As depicted, the effect of the deflection is more significant when less coal is charged into the oven. In general, coal charging system deflection can cause a coal volume loss of approximately one to two tons. FIG. 3B depicts the manner in which an ideally charged, level coke bed would look.

Despite the ill effect of coal charging system deflection, caused by its weight and cantilevered position, the coal charging system **10** provides little benefit in the way of coal bed densification. With reference to FIG. 4A, the coal charging system **10** provides minimal improvement to internal coal bed density, forming a first layer **d1** and a second, less dense layer **d2** at the bottom of the coal bed. Increasing the density of the coal bed can facilitate conductive heat transfer throughout the coal bed which is a component in determining oven cycle time and oven production capacity. FIG. 6 depicts a set of density measurements taken for an oven test using a prior art coal charging system **10**. The line with diamond indicators shows the density on the coal bed surface. The line with the square indicators and the line with the triangular indicators show density twelve inches and twenty-four inches below the surface respectively. The data demonstrates that bed density drops more on the coke side. FIG. 4B depicts the manner in which an ideally charged, level coke bed would look, having relatively increased density layers **D1** and **D2**.

BRIEF DESCRIPTION OF THE DRAWINGS

Non-limiting and non-exhaustive embodiments of the present invention, including the preferred embodiment, are described with reference to the following figures, wherein like reference numerals refer to like parts throughout the various views unless otherwise specified.

FIG. 1 depicts a front perspective view of a prior art coal charging system.

FIG. 2A depicts a front view of a coal bed that was charged into a coke oven using a prior art coal charging system and depicts that the coal bed is not level, having voids at the sides of the bed.

FIG. 2B depicts a front view of a coal bed that was ideally charged into a coke oven, without voids at the sides of the bed.

FIG. 3A depicts a side elevation view of a coal bed that was charged into a coke oven using a prior art coal charging system and depicts that the coal bed is not level, having voids at the end portions of the bed.

FIG. 3B depicts a side elevation view of a coal bed that was ideally charged into a coke oven, without voids at the end portions of the bed.

FIG. 4A depicts a side elevation view of a coal bed that was charged into a coke oven using a prior art coal charging system and depicts two different layers of minimal coal density formed by the prior art coal charging system.

FIG. 4B depicts a side elevation view of a coal bed that was ideally charged into a coke oven having two different layers of relatively increased coal density.

FIG. 5 depicts a plot of mock data of bed height over bed length and the bed height drop, due to coal charging system deflection.

FIG. 6 depicts a plot of test data of surface and internal coal bulk density over bed length.

FIG. 7 depicts a front, perspective view of one embodiment of a charging frame and charging head of a coal charging system according to the present technology.

FIG. 8 depicts a top, plan view of the charging frame and charging head depicted in FIG. 7.

FIG. 9A depicts a top plan view of one embodiment of a charging head according to the present technology.

FIG. 9B depicts a front elevation view of the charging head depicted in FIG. 9A.

FIG. 9C depicts a side elevation view of the charging head depicted in FIG. 9A.

FIG. 10A depicts a top plan view of another embodiment of a charging head according to the present technology.

FIG. 10B depicts a front elevation view of the charging head depicted in FIG. 10A.

FIG. 10C depicts a side elevation view of the charging head depicted in FIG. 10A.

FIG. 11A depicts a top plan view of yet another embodiment of a charging head according to the present technology.

FIG. 11B depicts a front elevation view of the charging head depicted in FIG. 11A.

FIG. 11C depicts a side elevation view of the charging head depicted in FIG. 11A.

FIG. 12A depicts a top plan view of still another embodiment of a charging head according to the present technology.

FIG. 12B depicts a front elevation view of the charging head depicted in FIG. 12A.

FIG. 12C depicts a side elevation view of the charging head depicted in FIG. 12A.

FIG. 13 depicts a side elevation view of one embodiment of a charging head, according to the present technology, wherein the charging head includes particulate deflection surfaces on top of the upper edge portion of the charging head.

FIG. 14 depicts a partial, top elevation view of one embodiment of the charging head of the present technology and further depicts one embodiment of a densification bar and one manner in which it can be coupled with a wing of the charging head.

FIG. 15 depicts a side elevation view of the charging head and densification bar depicted in FIG. 14.

FIG. 16 depicts a partial side elevation view of one embodiment of the charging head of the present technology and further depicts another embodiment of a densification bar and a manner in which it can be coupled with the charging head.

FIG. 17 depicts a partial, top elevation view of one embodiment of a charging head and charging frame, according to the present technology, and further depicts one embodiment of a slotted joint that couples the charging head and charging frame with one another.

FIG. 18 depicts a partial, cutaway side elevation view of the charging head and charging frame depicted in FIG. 17.

FIG. 19 depicts a partial front elevation view of one embodiment of a charging head and charging frame, according to the present technology, and further depicts one embodiment of a charging frame deflection face that may be associated with the charging frame.

FIG. 20 depicts a partial, cutaway side elevation view of the charging head and charging frame depicted in FIG. 19.

FIG. 21 depicts a front perspective view of one embodiment of an extrusion plate, according to the present technology, and further depicts one manner in which it may be associated with a rearward face of a charging head.

FIG. 22 depicts a partial isometric view of the extrusion plate and charging head depicted in FIG. 21.

FIG. 23 depicts a side perspective view of one embodiment of an extrusion plate, according to the present technology, and further depicts one manner in which it may be associated with a rearward face of a charging head and extrude coal that is being conveyed into a coal charging system.

FIG. 24A depicts a top plan view of another embodiment of extrusion plates, according to the present technology, and further depicts one manner in which they may be associated with wing members of a charging head.

FIG. 24B depicts a side elevation view of the extrusion plates of FIG. 24A.

FIG. 25A depicts a top plan view of still another embodiment of extrusion plates, according to the present technology, and further depicts one manner in which they may be associated with multiple sets of wing members that are disposed both forwardly and rearwardly of a charging head.

FIG. 25B depicts a side elevation view of the extrusion plates of FIG. 25A.

FIG. 26 depicts a front elevation view of one embodiment of a charging head, according to the present technology, and further depicts the differences in coal bed densities when an extrusion plate is used and not used in a coal bed charging operation.

FIG. 27 depicts a plot of coal bed density over a length of a coal bed where the coal bed is charged without the use of an extrusion plate.

FIG. 28 depicts a plot of coal bed density over a length of a coal bed where the coal bed is charged with the use of an extrusion plate.

FIG. 29 depicts a top plan view of one embodiment of a charging head, according to the present technology, and further depicts another embodiment of an extrusion plate that may be associated with a rearward surface of the charging head.

FIG. 30 depicts a top, plan view of a prior art false door assembly.

FIG. 31 depicts a side elevation view of the false door assembly depicted in FIG. 30.

FIG. 32 depicts a side elevation view of one embodiment of a false door, according to the present technology, and further depicts one manner in which the false door may be coupled with an existing, angled false door assembly.

FIG. 33 depicts a side elevation view of one manner in which a coal bed may be charged into a coke oven according to the present technology.

FIG. 34A depicts a front perspective view of one embodiment of a false door assembly according to the present technology.

FIG. 34B depicts a rear elevation view of one embodiment of a false door that may be used with the false door assembly depicted in FIG. 34A.

5

FIG. 34C depicts a side elevation view of the false door assembly depicted in FIG. 34A and further depicts one manner in which a height of the false door may be selectively increased or decreased.

FIG. 35A depicts a front perspective view of another embodiment of a false door assembly according to the present technology.

FIG. 35B depicts a rear elevation view of one embodiment of a false door that may be used with the false door assembly depicted in FIG. 35A.

FIG. 35C depicts a side elevation view of the false door assembly depicted in FIG. 35A and further depicts one manner in which a height of the false door may be selectively increased or decreased.

DETAILED DESCRIPTION

The present technology is generally directed to coal charging systems used with coke ovens. In various embodiments, the coal charging systems, of the present technology, are configured for use with horizontal heat recovery coke ovens. However, embodiments of the present technology can be used with other coke ovens, such as horizontal, non-recovery ovens. In some embodiments, a coal charging system includes a charging head having opposing wings that extend outwardly and forwardly from the charging head, leaving an open pathway through which coal may be directed toward the side edges of the coal bed. In other embodiments, an extrusion plate is positioned on a rearward face of the charging head and oriented to engage and compress coal as the coal is charged along a length of the coking oven. In still other embodiments, a false door is vertically oriented to maximize an amount of coal being charged into the oven. In some embodiments, a lower extension plate associate with the false door is selectively, automatically extended beyond a lower end portion of the false door in order to extend an effective length of the false door. In other embodiments, an extension plate may be coupled with an existing false door having an angled front surface. The extension plate provides the existing false door with a vertically oriented face.

Specific details of several embodiments of the technology are described below with reference to FIGS. 7-29 and 32-35C. Other details describing well-known structures and systems often associated with pusher systems, charging systems, and coke ovens have not been set forth in the following disclosure to avoid unnecessarily obscuring the description of the various embodiments of the technology. Many of the details, dimensions, angles, and other features shown in the Figures are merely illustrative of particular embodiments of the technology. Accordingly, other embodiments can have other details, dimensions, angles, and features without departing from the spirit or scope of the present technology. A person of ordinary skill in the art, therefore, will accordingly understand that the technology may have other embodiments with additional elements, or the technology may have other embodiments without several of the features shown and described below with reference to FIGS. 7-29 and 32-35C.

It is contemplated that the coal charging technology of the present matter will be used in combination with a pusher charger machine ("PCM") having one or more other components common to PCMs, such as a door extractor, a pusher ram, a tripper conveyor, and the like. However, aspects of the present technology may be used separately from a PCM and may be used individually or with other equipment associated with a coking system. Accordingly, aspects of the

6

present technology may simply be described as "a coal charging system" or components thereof. Components associated with coal charging systems, such as coal conveyers and the like that are well-known may not be described in detail, if at all, to avoid unnecessarily obscuring the description of the various embodiments of the technology.

With reference to FIGS. 7-9C, a coal charging system 100 is depicted, having an elongated charging frame 102 and a charging head 104. In various embodiments, the charging frame 102 will be configured to have opposite sides 106 and 108 that extend between a distal end portion 110 and proximal end portion 112. In various applications, the proximal end portion 112 may be coupled with a PCM in a manner that permits selective extension and retraction of the charging frame 102 into, and from within, a coke oven interior during a coal charging operation. Other systems, such as a height adjustment system that selectively adjusts the height of the charging frame 102 with respect to a coke oven floor and/or a coal bed, may also be associated with the coal charging system 100.

The charging head 104 is coupled with the distal end portion 110 of the elongated charging frame 102. In various embodiments, the charging head 104 is defined by a planar body 114, having an upper edge portion 116, lower edge portion 118, opposite side portions 120 and 122, a front face 124, and a rearward face 126. In some embodiments, a substantial portion of the body 114 resides within a charging head plane. This is not to suggest that embodiments of the present technology will not provide charging head bodies having aspects that occupy one or more additional planes. In various embodiments, the planar body is formed from a plurality of tubes, having square or rectangular cross-sectional shapes. In particular embodiments, the tubes are provided with a width of six inches to twelve inches. In at least one embodiment, the tubes have a width of eight inches, which demonstrated a significant resistance to warping during charging operations.

With further reference to FIGS. 9A-9C, various embodiments of the charging head 104 include a pair of opposing wings 128 and 130 that are shaped to have free end portions 132 and 134. In some embodiments, the free end portions 132 and 134 are positioned in a spaced-apart relationship, forwardly from the charging head plane. In particular embodiments, the free end portions 132 and 134 are spaced forwardly from the charging head plane a distance of six inches to 24 inches, depending on the size of the charging head 104 and the geometry of the opposing wings 128 and 130. In this position, the opposing wings 128 and 130 define open spaces rearwardly from the opposing wings 128 and 130, through the charging head plane. As the design of these open spaces is increased in size, more material is distributed to the sides of the coal bed. As the spaces are made smaller, less material is distributed to the sides of the coal bed. Accordingly, the present technology is adaptable as particular characteristics are presented from coking system to coking system.

In some embodiments, such as depicted in FIGS. 9A-9C, the opposing wings 128 and 130 include first faces 136 and 138 that extend outwardly from the charging head plane. In particular embodiments, the first faces 136 and 138 extend outwardly from the charging plane at a forty-five degree angle. The angle at which the first face deviates from the charging head plane may be increased or decreased according to the particular intended use of the coal charging system 100. For example, particular embodiments may employ an angle of ten degrees to sixty degrees, depending on the conditions anticipated during charging and leveling opera-

tions. In some embodiments, the opposing wings **128** and **130** further include second faces **140** and **142** that extend outwardly from the first faces **136** and **138** toward the free distal end portions **132** and **134**. In particular embodiments, the second faces **140** and **142** of the opposing wings **128** and **130** reside within a wing plane that is parallel to the charging head plane. In some embodiments, the second faces **140** and **142** are provided to be approximately ten inches in length. In other embodiments, however, the second faces **140** and **142** may have lengths ranging from zero to ten inches, depending on one or more design considerations, including the length selected for the first faces **136** and **138** and the angles at which the first faces **136** and **138** extend away from the charging plane. As depicted in FIGS. 9A-9C, the opposing wings **128** and **130** are shaped to receive loose coal from the rearward face of the charging head **104**, while the coal charging system **100** is being withdrawn across the coal bed being charged, and funnel or otherwise direct loose coal toward the side edges of the coal bed. In at least this manner, the coal charging system **100** may reduce the likelihood of voids at the sides of the coal bed, as shown in FIG. 2A. Rather, the wings **128** and **130** help to promote the level coal bed depicted in FIG. 2B. Testing has shown that use of the opposing wings **128** and **130** can increase the charge weight by one to two tons by filling these side voids. Moreover, the shape of the wings **128** and **130** reduce drag back of the coal and spillage from the pusher side of the oven, which reduces waste and the expenditure of labor to retrieve the spilled coal.

With reference to FIGS. 10A-10C, another embodiment of a charging head **204** is depicted as having a planar body **214**, having an upper edge portion **216**, lower edge portion **218**, opposite side portions **220** and **222**, a front face **224**, and a rearward face **226**. The charging head **204** further includes a pair of opposing wings **228** and **230** that are shaped to have free end portions **232** and **234** that are positioned in a spaced-apart relationship, forwardly from the charging head plane. In particular embodiments, the free end portions **232** and **234** are spaced forwardly from the charging head plane a distance of six inches to 24 inches. The opposing wings **228** and **230** define open spaces rearwardly from the opposing wings **228** and **230**, through the charging head plane. In some embodiments, the opposing wings **228** and **230** include first faces **236** and **238** that extend outwardly from the charging head plane at a forty-five degree angle. In particular embodiments, the angle at which the first faces **236** and **238** deviate from the charging head plane from ten degrees to sixty degrees, depending on the conditions anticipated during charging and leveling operations. The opposing wings **228** and **230** are shaped to receive loose coal from the rearward face of the charging head **204**, while the coal charging system is being withdrawn across the coal bed being charged, and funnel or otherwise direct loose coal toward the side edges of the coal bed.

With reference to FIGS. 11A-11C, a further embodiment of a charging head **304** is depicted as having a planar body **314**, having an upper edge portion **316**, lower edge portion **318**, opposite side portions **320** and **322**, a front face **324**, and a rearward face **326**. The charging head **300** further includes a pair of curved opposing wings **328** and **330** that have free end portions **332** and **334** that are positioned in a spaced-apart relationship, forwardly from the charging head plane. In particular embodiments, the free end portions **332** and **334** are spaced forwardly from the charging head plane a distance of six inches to twenty-four inches. The curved opposing wings **328** and **330** define open spaces rearwardly from the curved opposing wings **328** and **330**, through the

charging head plane. In some embodiments, the curved opposing wings **328** and **330** include first faces **336** and **338** that extend outwardly from the charging head plane at a forty-five degree angle from a proximal end portion of the curved opposing wings **328** and **330**. In particular embodiments, the angle at which the first faces **336** and **338** deviate from the charging head plane from ten degrees to sixty degrees. This angle dynamically changes along lengths of the curved opposing wings **328** and **330**. The opposing wings **328** and **330** receive loose coal from the rearward face of the charging head **304**, while the coal charging system is being withdrawn across the coal bed being charged, and funnel or otherwise direct loose coal toward the side edges of the coal bed.

With reference to FIGS. 12A-12C, an embodiment of a charging head **404** includes a planar body **414**, having an upper edge portion **416**, lower edge portion **418**, opposite side portions **420** and **422**, a front face **424**, and a rearward face **426**. The charging head **400** further includes a first pair of opposing wings **428** and **430** that have free end portions **432** and **434** that are positioned in a spaced-apart relationship, forwardly from the charging head plane. The opposing wings **428** and **430** include first faces **436** and **438** that extend outwardly from the charging head plane at a forty-five degree angle. The angle at which the first face deviates from the charging head plane may be increased or decreased according to the particular intended use of the coal charging system **400**. For example, particular embodiments may employ an angle of ten degrees to sixty degrees, depending on the conditions anticipated during charging and leveling operations. In some embodiments, the free end portions **432** and **434** are spaced forwardly from the charging head plane a distance of six inches to twenty-four inches. The opposing wings **428** and **430** define open spaces rearwardly from the curved opposing wings **428** and **430**, through the charging head plane. In some embodiments, the opposing wings **428** and **430** further include second faces **440** and **442** that extend outwardly from the first faces **436** and **438** toward the free distal end portions **432** and **434**. In particular embodiments, the second faces **440** and **442** of the opposing wings **428** and **430** reside within a wing plane that is parallel to the charging head plane. In some embodiments, the second faces **440** and **442** are provided to be approximately ten inches in length. In other embodiments, however, the second faces **440** and **442** may have lengths ranging from zero to ten inches, depending on one or more design considerations, including the length selected for the first faces **436** and **438** and the angles at which the first faces **436** and **438** extend away from the charging plane. The opposing wings **428** and **430** are shaped to receive loose coal from the rearward face of the charging head **404**, while the coal charging system **400** is being withdrawn across the coal bed being charged, and funnel or otherwise direct loose coal toward the side edges of the coal bed.

In various embodiments, it is contemplated that opposing wings of various geometries may extend rearwardly from a charging head associated with a coal charging system according to the present technology. With continued reference to FIGS. 12A-12C, the charging head **400** further includes a second pair of opposing wings **444** and **446** that each include free end portions **448** and **450** that are positioned in a spaced-apart relationship, rearwardly from the charging head plane. The opposing wings **444** and **446** include first faces **452** and **454** that extend outwardly from the charging head plane. In some embodiments, the first

faces **452** and **454** extend outwardly from the charging head plane at a forty-five degree angle. The angle at which the first faces **452** and **454** deviate from the charging head plane may be increased or decreased according to the particular intended use of the coal charging system **400**. For example, particular embodiments may employ an angle of ten degrees to sixty degrees, depending on the conditions anticipated during charging and leveling operations. In some embodiments, the free end portions **448** and **450** are spaced rearwardly from the charging head plane a distance of six inches to twenty-four inches. The opposing wings **444** and **446** define open spaces rearwardly from the opposing wings **444** and **446**, through the charging head plane. In some embodiments, the opposing wings **444** and **446** further include second faces **456** and **458** that extend outwardly from the first faces **452** and **454** toward the free distal end portions **448** and **450**. In particular embodiments, the second faces **456** and **458** of the opposing wings **444** and **446** reside within a wing plane that is parallel to the charging head plane. In some embodiments, the second faces **456** and **458** are provided to be approximately ten inches in length. In other embodiments, however, the second faces **456** and **458** may have lengths ranging from zero to ten inches, depending on one or more design considerations, including the length selected for the first faces **452** and **454** and the angles at which the first faces **452** and **454** extend away from the charging plane. The opposing wings **444** and **446** are shaped to receive loose coal from the front face **424** of the charging head **404**, while the coal charging system **400** is being extended along the coal bed being charged, and funnel or otherwise direct loose coal toward the side edges of the coal bed.

With continued reference to FIGS. **12A-12C**, the rearwardly faced opposing wings **444** and **446** are depicted as being positioned above the forwardly faced opposing wings **428** and **430**. However, it is contemplated that this particular arrangement may be reversed, in some embodiments, without departing from the scope of the present technology. Similarly, the rearwardly faced opposing wings **444** and **446** and forwardly faced opposing wings **428** and **430** are each depicted as angularly disposed wings having first and second sets of faces that are disposed at angles with respect to one another. However, it is contemplated that either or both sets of opposing wings may be provided in different geometries, such as demonstrated by the straight, angularly disposed opposing wings **228** and **230**, or the curved wings **328** and **330**. Other combinations of known shapes, intermixed or in pairs, are contemplated. Moreover, it is further contemplated that the charging heads of the present technology could be provided with one or more sets of opposing wings that only face rearwardly from the charging head, with no wings that face forwardly. In such instances, the rearwardly positioned opposing wings will distribute the coal to the side portions of the coal bed when the coal charging system is moving forward (charging).

With reference to FIG. **13**, it is contemplated that, as the coal is being charged into the oven and as the coal charging system **100** (or in a similar manner charging heads **526**, **300**, or **400**) is being withdrawn across the coal bed, loose coal may begin to pile onto the upper edge portion **116** of the charging head **104**. Accordingly, some embodiments of the present technology will include one or more angularly disposed particulate deflection surfaces **144** on top of the upper edge portion **116** of the charging head **104**. In the depicted example, a pair of oppositely faced particulate deflection surfaces **144** combine to form a peaked structure, which disperses errant particulate material in front of and

behind the charging head **104**. It is contemplated that it may be desirable in particular instances to have the particulate material land primarily in front of or behind the charging head **104**, but not both. Accordingly, in such instances, a single particulate deflection surface **144** may be provided with an orientation chosen to disperse the coal accordingly. It is further contemplated that the particulate deflection surfaces **144** may be provided in other, non-planar or non-angular configurations. In particular, the particulate deflection surfaces **144** may be flat, curvilinear, convex, concave, compound, or various combinations thereof. Some embodiments will merely dispose the particulate deflection surfaces **144** so that they are not horizontally disposed. In some embodiments, the particulate surfaces can be integrally formed with the upper edge portion **116** of the charging head **104**, which may further include a water cooling feature.

Coal bed bulk density plays a significant role in determining coke quality and minimizing burn loss, particularly near the oven walls. During a coal charging operation, the charging head **104** retracts against a top portion of the coal bed. In this manner, the charging head contributes to the top shape of the coal bed. However, particular aspects of the present technology cause portions of the charging head to increase the density of the coal bed. With regard to FIGS. **13** and **14**, the opposing wings **128** and **130** may be provided with one or more elongated densification bars **146** that, in some embodiments, extend along a length of, and downwardly from, each of the opposing wings **128** and **130**. In some embodiments, such as depicted in FIGS. **13** and **14**, the densification bars **146** may extend downwardly from bottom surfaces of the opposing wings **128** and **130**. In other embodiments, the densification bars **146** may be operatively coupled with forward or rearward faces of either or both of the opposing wings **128** and **130** and/or the lower edge portion **118** of the charging head **104**. In particular embodiments, such as depicted in FIG. **13**, the elongated densification bar **146** has a long axis disposed at an angle with respect to the charging head plane. It is contemplated that the densification bar **146** may be formed from a roller that rotates about a generally horizontal axis, or a static structure of various shapes, such as a pipe or rod, formed from a high temperature material. The exterior shape of the elongated densification bar **146** may be planar or curvilinear. Moreover, the elongated densification bar may be curved along its length or angularly disposed.

In some embodiments, the charging heads and charging frames of various systems may not include a cooling system. The extreme temperatures of the ovens will cause portions of such charging heads and charging frames to expand slightly, and at different rates, with respect to one another. In such embodiments, the rapid, uneven heating and expansion of the components may stress the coal charging system and warp or otherwise misalign the charging head with respect to the charging frame. With reference to FIGS. **17** and **18**, embodiments of the present technology couple the charging head **104** to the sides **106** and **108** of the charging frame **102** using a plurality of slotted joints that allow relative movement between the charging head **104** and the elongated charging frame **102**. In at least one embodiment, first frame plates **150** extend outwardly from inner faces of the sides **106** and **108** of the elongated frame **102**. The first frame plates **150** include one or more elongated mounting slots **152** that penetrate the first frame plates **150**. In some embodiments, second frame plates **154** are also provided to extend outwardly from the inner faces of the sides **106** and **108**, beneath the first frame plates **150**. The second frame plates **154** of the elongated frame **102** also include one or more

elongated mounting slots **152** that penetrate the second frame plates **154**. First head plates **156** extend outwardly from opposite sides of the rearward face **126** of the charging head **104**. The first head plates **156** include one or more mounting apertures **158** that penetrate the first head plates **156**. In some embodiments, second head plates **160** are also provided to extend outwardly from the rearward face **126** of the charging head **104**, beneath the first head plates **156**. The second head plates **160** also include one or more mounting apertures **158** that penetrate the second head plates **158**. The charging head **104** is aligned with the charging frame **102** so that the first frame plates **150** align with first head plates **156** and the second frame plates **154** align with the second head plates **160**. Mechanical fasteners **161** pass through the elongated mounting slots **152** of the first frame plates **150** and second frame plates **152** and corresponding mounting apertures **160**. In this manner, the mechanical fasteners **161** are placed in a fixed position with respect to the mounting apertures **160** but are allowed to move along lengths of the elongated mounting slots **152** as the charging head **104** move with respect to the charging frame **102**. Depending on the size and configuration of the charging head **104** and the elongated charging frame **102**, it is contemplated that more or fewer charging head plates and frame plates of various shapes and sizes could be employed to operatively couple the charging head **104** and the elongated charging frame **102** with one another.

With reference to FIGS. **19** and **20**, particular embodiments of the present technology provide the lower inner faces of each of the opposite sides **106** and **108** of the elongated charging frame **102** with charging frame deflection faces **162**, positioned to face at a slightly downward angle toward a middle portion of the charging frame **102**. In this manner, the charging frame deflection faces **162** engage the loosely charged coal and direct the coal down and toward the sides of the coal bed being charged. The angle of the deflection faces **162** further compress the coal downwardly in a manner that helps to increase the density of the edge portions of the coal bed. In another embodiment, forward end portions of each of the opposite sides **106** and **108** of the elongated charging frame **102** include charging frame deflection faces **163** that are also positioned rearwardly from the wings but are oriented to face forwardly and downwardly from the charging frame. In this manner, the deflection faces **163** may further help to increase the density of the coal bed and direct the coal outwardly toward the edge portions of the coal bed in an effort to more fully level the coal bed.

Many prior coal charging systems provide a minor amount of compaction on the coal bed surface due to the weight of the charging head and charging frame. However, the compaction is typically limited to twelve inches below the surface of the coal bed. Data during coal bed testing demonstrated that the bulk density measurement in this region to be a three to ten unit point difference inside the coal bed. FIG. **6** graphically depicts density measurements taken during mock oven testing. The top line shows the density of the coal bed surface. The lower two lines depict the density at twelve inches and twenty-four inches below the coal bed surface, respectively. From the testing data, one can conclude that bed density drops more significantly on the coke side of the oven.

With reference to FIGS. **21-28**, various embodiments of the present technology position an extrusion plate **166** operatively coupled with the rearward face **126** of the charging head **104**. In some embodiments, the extrusion plate **166** includes a coal engagement face **168** that is

oriented to face rearwardly and downwardly with respect to the charging head **104**. In this manner, loose coal being charged into the oven behind the charging head **104** will engage the coal engagement face **168** of the extrusion plate **166**. Due to the pressure of the coal being deposited behind the charging head **104**, the coal engagement face **168** compacts the coal downwardly, increasing the coal density of the coal bed beneath the extrusion plate **166**. In various embodiments, the extrusion plate **166** extends substantially along a length of the charging head **104** in order to maximize density across a significant width of the coal bed. With continued reference to FIGS. **20** and **21**, the extrusion plate **166** further includes an upper deflection face **170** that is oriented to face rearwardly and upwardly with respect to the charging head **104**. In this manner, the coal engagement face **168** and the upper deflection face **170** are coupled with one another to define a peak shape, having a peak ridge that faces rearwardly away from the charging head **104**. Accordingly, any coal that falls atop the upper deflection face **170** will be directed off the extrusion plate **166** to join the incoming coal before it is extruded.

In use, coal is shuffled to the front end portion of the coal charging system **100**, behind the charging head **104**. Coal piles up in the opening between the conveyor and the charging head **104** and conveyor chain pressure starts to build up gradually until reaching approximately 2500 to 2800 psi. With reference to FIG. **23**, the coal is fed into the system behind the charging head **104** and the charging head **104** is retracted, rearwardly through the oven. The extrusion plate **166** compacts the coal and extrudes it into the coal bed.

With reference to FIGS. **24A-25B**, embodiments of the present technology may associate extrusion plates with one or more wings that extend from the charging head. FIGS. **24A** and **24B** depict one such embodiment where extrusion plates **266** extend rearwardly from opposing wings **128** and **130**. In such embodiments, the extrusion plates **266** are provided with coal engagement faces **268** and upper deflection faces **270** that are coupled with one another to define a peak shape, having a peak ridge that faces rearwardly away from the opposing wings **128** and **130**. The coal engagement faces **268** are positioned to compact the coal downwardly as the coal charging system is retracted through the oven, increasing the coal density of the coal bed beneath the extrusion plates **266**. FIGS. **25A** and **25B** depict a charging head similar to that depicted in FIGS. **12A-12C** except that extrusion plates **466**, having coal engagement faces **468** and upper deflection faces **470**, are positioned to extend rearwardly from the opposing wings **428** and **430**. The extrusion plates **466** function similarly to the extrusion plates **266**. Additional extrusion plates **466** may be positioned to extend forwardly from the opposing wings **444** and **446**, which are positioned behind the charging head **400**. Such extrusion plates compact the coal downwardly as the coal charging system is advanced through the oven, further increasing the coal density of the coal bed beneath the extrusion plates **466**.

FIG. **26** depicts the effect on the density of a coal charge with the benefit of the extrusion plate **166** (left side of the coal bed) and without the benefit of the extrusion plate **166** (right side of the coal bed). As depicted, use of the extrusion plate **166** provides area "D" of increased coal bed bulk density and an area of lesser coal bed bulk density "d" where the extrusion plate is not present. In this manner, the extrusion plate **166** not only demonstrates an improvement in the surface density, but also improves the overall internal bed bulk density. The test results, depicted in FIGS. **27** and **28** below, show the improvement of bed density with the use of the extrusion plate **166** (FIG. **28**) and without the use of

13

the extrusion plate 166 (FIG. 27). The data demonstrates a significant impact on both surface density and twenty-four inches below the surface of the coal bed. In some testing, an extrusion plate 166 having a ten inch peak (distance from back of the charging head 104 to the peak ridge of the extrusion plate 166, where the coal engagement face 168 and the upper deflection face 170 meet). In other tests, where a six inch peak was used, coal density was increased but not to the levels resulting from the use of the ten inch peak extrusion plate 166. The data reveals that the use of the ten inch peak extrusion plate increased the density of the coal bed, which allowed for an increase in charge weight of approximately two and a half tons. In some embodiments of the present technology, it is contemplated that smaller extrusion plates, of five to ten inches in peak height, for example, or larger extrusion plates, of ten to twenty inches in peak height, for example, could be used.

With reference to FIG. 29, other embodiments of the present technology provide an extrusion plate 166 that is shaped to include opposing side deflection faces 172 that are oriented to face rearwardly and laterally with respect to the charging head 104. By shaping the extrusion plate 166 to include the opposing side deflection faces 172, testing showed that more extruded coal flowed toward both sides of the bed while it was extruded. In this manner, extrusion plate 166 helps to promote the level coal bed, depicted in FIG. 2B, as well as an increase in coal bed density across the width of the coal bed.

When charging systems extend inside the ovens during charging operations, the coal charging systems, typically weighing approximately 80,000 pounds, deflect downwardly at their free, distal ends. This deflection shortens the coal charge capacity. FIG. 5 shows that the bed height drop, due to coal charging system deflection, is from five inches to eight inches between the pusher side to the coke side, depending upon the charge weight. In general, coal charging system deflection can cause a coal volume loss of approximately 1 to 2 tons. During a charging operation, coal piles up in the opening between the conveyor and the charging head 104 and conveyor chain pressure starts to build up. Traditional coal charging systems operate at a chain pressure of approximately 2300 psi. However, the coal charging system of the present technology can be operated at a chain pressure of approximately 2500 to 2800 psi. This increase in chain pressure increases the rigidity of the coal charging system 100 along a length of its charging frame 102. Testing indicates that operating the coal charging system 100 at a chain pressure of approximately 2700 psi reduces deflection of the coal charging system deflection by approximately two inches, which equates to a higher charge weight and increased production. Testing has further shown that operating the coal charging system 100 at a higher chain pressure of approximately 3000 to 3300 psi can produce a more effective charge and further realize greater benefit from the use of one or more extrusion plates 166, as described above.

With reference to FIGS. 30 and 31, various embodiments of the coal charging system 100 include a false door assembly 500, having an elongated false door frame 502 and a false door 504, which is coupled to a distal end portion 506 of the false door frame 502. The false door frame 502 further includes a proximal end portion 508, and opposite sides 510 and 512 that extend between the proximal end portion 508 and the distal end portion 506. In various applications, the proximal end portion 508 may be coupled with a PCM in a manner that permits selective extension and retraction of the false door frame 502 into and from within a coke oven interior during a coal charging operation. In some embodi-

14

ments, the false door frame 502 is coupled with the PCM adjacent to and, in many instances, beneath the charging frame 102. The false door 504 is generally planar, having an upper end portion 514, a lower end portion 516, opposite side portions 518 and 520, a front face 522, and a rearward face 524. In operation, the false door 504 is placed just inside the coke oven during a coal charging operation. In this manner, the false door 504 substantially prevents loose coal from unintentionally exiting the pusher side of the coke oven until the coal is fully charged and the coke oven can be closed. Traditional false door designs are angled so that the lower end portion 516 of the false door 504 is positioned rearwardly of a top end portion 514 of the false door 504. This creates an end portion of a coal bed having a sloped or angled shape that typically terminates twelve inches to thirty-six inches into the coke oven from its pusher side opening.

The false door 504 includes an extension plate 526, having an upper end portion 528, a lower end portion 530, opposite side portions 530 and 534, a front face 536, and a rearward face 538. The upper end portion 528 of extension plate 526 is removably coupled to the lower end portion 516 of the false door 504 so that the lower end portion 530 of the extension plate 526 extends lower than the lower end portion 516 of the false door 504. In this manner, a height of the front face 522 of the false door 504 may be selectively increased to accommodate the charging of a coal bed having a greater height. The extension plate 526 is typically coupled with the false door 504 using a plurality of mechanical fasteners 540 that form a quick connect/disconnect system. A plurality of separate extension plates 526, each having different heights, may be associated with a false door assembly 500. For example, a longer extension plate 526 may be used for coal charges of forty-eight tons; whereas, a shorter extension plate 526 may be used for a coal charge of thirty-six tons, and no extension plate 526 might be used for a coal charge of twenty-eight tons. However, removing and replacing the extension plates 526 is labor intensive and time consuming, due to the weight of the extension plate and the fact that it is manually removed and replaced. This procedure can interrupt coke production at a facility by an hour or more.

With reference to FIG. 32, an existing false door 504 that resides within a body plane, which is disposed at an angle away from vertical, may be adapted to have a vertical false door. In some such embodiments, a false door extension 542, having an upper end portion 544, a lower end portion 546, a front face 548, and a rearward face 550, may be operatively coupled with the false door 504. In particular embodiments, the false door extension 542 is shaped and oriented to define a replacement front face of the false door 504. It is contemplated that the false door extension 542 can be coupled with the false door 504 using mechanical fasteners, welding, or the like. In particular embodiments, the front face 548 is positioned to reside within a false door plane that is substantially vertical. In some embodiments, the front face 548 is shaped to closely mirror a contour of a refractory surface 552 of a pusher side oven door 554.

In operation, the vertical orientation of the front face 548 allows the false door extension 542 to be placed just inside the coke oven during a coal charging operation. In this manner, as depicted in FIG. 33, an end portion of the coal bed 556 is positioned closely adjacent the refractory surface 552 of the pusher side oven door 554. Accordingly, in some embodiments, the six to twelve inch gap left between the coal bed and the refractory surface 552 can be eliminated or, at the very least, minimized significantly. Moreover, the

vertically disposed front face **548** of the false door extension **542** maximizes the use of the full oven capacity to charge more coal into the oven, as opposed to the sloped bed shape created by the prior art designs, which increases the production rate for the oven. For example, if the front face **536** of the false door extension **542** is positioned twelve inches back from where the refractory surface **552** of the pusher side oven door **554** will be positioned when the coke oven is closed on a forty-eight ton coal charge, an unused oven volume equal to approximately one ton of coal is formed. Similarly, if the front face **536** of the false door extension **542** is positioned six inches back from where the refractory surface **552** of the pusher side oven door **554** will be positioned, the unused oven volume will equal approximately one half of a ton of coal. Accordingly, using the false door extension **542** and the aforementioned methodology, each oven can charge an additional half ton to a full ton of coal, which can significantly improve the coke production rate for an entire oven battery. This is true despite the fact that a forty-nine ton charge may be placed into an oven typically operated with forty-eight ton charges. The forty-nine ton charge will not increase the forty-eight hour coke cycle. If the twelve inch void is filled using the aforementioned methodology but only forty-eight tons of coal are charged into the oven, the bed will be reduced from an expected forty-eight inches high to forty-seven inches high. Coking the forty-seven inch high coal charge for forty-eight hours buys one additional hour of soak time for the coking process, which could improve coke quality (CSR or stability).

In particular embodiments of the present technology, as depicted in FIGS. **34A-34C**, the false door frame **502** may be fitted with a vertical false door **558**, in place of the false door **504**. In various embodiments, the vertical false door **558** has an upper end portion **560**, a lower end portion **562**, opposite side portions **564** and **566**, a front face **568**, and a rearward face **570**. In the embodiment depicted, the front face **568** is positioned to reside within a false door plane that is substantially vertical. In some embodiments, the front face **568** is shaped to closely mirror a contour of a refractory surface **552** of a pusher side oven door **554**. In this manner, the vertical false door may be used much in the same manner as that described above with regard to the false door assembly that employs a false door extension **542**.

It may be desirable to periodically coke successive coal beds of different bed heights. For example, an oven may be first charged with a forty-eight ton, forty-eight inch high, coal bed. Thereafter, the oven may be charged with a twenty-eight ton, twenty-eight inch high, coal bed. The different bed heights require the use of false doors of correspondingly different heights. Accordingly, with continued reference to FIGS. **34A-34C**, various embodiments of the present technology provide a lower extension plate **572** coupled with the front face **568** of the vertical false door **558**. The lower extension plate **572** is selectively, vertically moveable with respect to the vertical false door **558** between retracted and extended positions. At least one extended position disposes a lower edge portion **574** of the lower extension plate **572** below the lower edge portion **562** of the vertical false door **558** such that an effective height of the vertical false door **558** is increased. In some embodiments, relative movement between the lower extension plate **572** and the vertical false door **558** is effected by disposing one or more extension plate brackets **576**, which extend rearwardly from the lower extension plate **572**, through one or more vertically arranged slots **578** that penetrate the vertical false door **558**. One of various arm assemblies **580** and

power cylinders **582** may be coupled to the extension plate brackets **576** to selectively move the lower extension plate **572** between its retracted and extended positions. In this manner, the effective height of the vertical false door **558** may be automatically customized to any height, ranging from an initial height of the vertical false door **558** to a height with the lower extension plate **572** at a full extension position. In some embodiments, the lower extension plate **558** and its associated components may be operatively coupled with the false door **504**, such as depicted in FIGS. **35A-35C**. In other embodiments, the lower extension plate **558** and its associated components may be operatively coupled with the extension plate **526**.

It is contemplated that, in some embodiments of the present technology, the end portion of the coal bed **556** may be slightly compacted to reduce the likelihood that the end portion of the coal charge will spill from the oven before the pusher side oven door **554** can be closed. In some embodiments, one or more vibration devices may be associated with the false door **504**, extension plate **526**, or vertical false door **558**, in order to vibrate the false door **504**, extension plate **526**, or vertical false door **558**, and compact the end portion of the coal bed **556**. In other embodiments, the elongated false door frame **502** may be reciprocally and repeatedly moved into contact with the end portion of the coal bed **204** with sufficient force to compact the end portion of the coal bed **556**. A water spray may also be used, alone or in conjunction with the vibratory or impact compaction methods, to moisten the end portion of the coal bed **556** and, at least temporarily, maintain a shape of the end portion of the coal bed **556** so that portions of the coal bed **556** do not spill from the coke oven.

EXAMPLES

The following Examples are illustrative of several embodiments of the present technology.

1. A coal charging system, the system comprising:
 - a elongated charging frame; and
 - a charging head operatively coupled with the distal end portion of the elongated charging frame;
 - an elongated false door frame having a distal end portion, proximal end portion, and opposite sides; and
 - a generally planar false door operatively coupled with the distal end portion of the elongated false door frame; the false door having an upper edge portion, lower edge portion, opposite side portions, a front face, and a rearward face; the front face of the false door residing within a false door plane that is substantially vertical.
2. The coal charging system of claim **1** further comprising:
 - a lower extension plate operatively coupled with the front face of the false door; the lower extension plate being selectively, vertically moveable with respect to the false door between retracted and extended positions; wherein at least one extended position disposes a lower edge portion of the lower extension plate below the lower edge portion of the false door such that an effective height of the false door is increased.
3. The coal charging system of claim **2** further comprising:
 - a linkage arm assembly operatively coupled with the lower extension plate and at least one power cylinder that may be selectively activated to move the lower extension plate between the retracted and extended positions.

17

4. The coal charging system of claim 3 further comprising:
 at least one extension plate bracket operatively coupled with the lower extension plate and the linkage arm assembly; the at least one extension plate bracket extending through at least one slot that penetrates the false door.
5. The coal charging system of claim 1 wherein the false door is comprised of:
 a false door body that resides within a body plane that is disposed at an angle away from vertical; and
 a face plate operatively coupled with the false door body that is shaped and oriented to define the front face of the false door.
6. The coal charging system of claim 5 further comprising:
 a lower extension plate operatively coupled with the front face of the false door; the lower extension plate being selectively, vertically moveable with respect to the false door between retracted and extended positions; wherein at least one extended position disposes a lower edge portion of the lower extension plate below the lower edge portion of the false door such that an effective height of the false door is increased.
7. A false door system for use with a coal charging system, having an elongated charging frame with a charging head coupled with a distal end portion of the charging frame, the system comprising:
 an elongated false door frame having a distal end portion, proximal end portion, and opposite sides; and
 a generally planar false door operatively coupled with the distal end portion of the elongated false door frame; the false door having an upper edge portion, lower edge portion, opposite side portions, a front face, and a rearward face;
 a lower extension plate operatively coupled with the front face of the false door; the lower extension plate being selectively, moveable in a generally parallel fashion with respect to the false door between retracted and extended positions; wherein at least one extended position disposes a lower edge portion of the lower extension plate below the lower edge portion of the false door such that an effective height of the false door is increased.
8. The coal charging system of claim 7 further comprising:
 a linkage arm assembly operatively coupled with the lower extension plate and at least one power cylinder that may be selectively activated to move the lower extension plate between the retracted and extended positions.
9. The coal charging system of claim 8 further comprising:
 at least one extension plate bracket operatively coupled with the lower extension plate and the linkage arm assembly; the at least one extension plate bracket extending through at least one slot that penetrates the false door.
10. A method of increasing a coal charge in a coke oven, the method comprising:
 positioning a coal charging system, having an elongated charging frame and a charging head operatively coupled with the distal end portion of the elongated charging frame, at least partially within a pusher side opening of a coke oven;
 positioning a false door system, having an elongated false door frame and a generally planar false door opera-

18

- tively coupled with a distal end portion of the elongated false door frame, at least partially within the pusher side opening of the coke oven; the false door having a front face that resides within a false door plane that is substantially vertical;
 charging coal into the coke oven with the coal charging system in a manner that defines a coal charge having a generally vertical end portion; and
 operatively coupling an oven door with the coke oven in a manner that closes the pusher side opening of the coke oven.
11. The method of claim 10 wherein the generally vertical end portion of the coal charge is positioned closely adjacent a refractory face of the oven door.
12. The method of claim 10 wherein the generally vertical end portion of the coal charge is positioned no more than six inches from a refractory face of the oven door.
13. The method of claim 10 wherein the generally vertical end portion of the coal charge is positioned no more than twelve inches from a refractory face of the oven door.
14. The method of claim 10 further comprising:
 reciprocally impacting the end portion of the coal face with the false door in a manner that at least partially compacts a portion of the coal face and resists portions of the coal face from spilling from the pusher side opening of the coke oven.
15. The method of claim 10 further comprising:
 applying a fluid to the coal face with the false door in a manner that wets a portion of the coal face and resists portions of the coal face from spilling from the pusher side opening of the coke oven.
16. The method of claim 10 further comprising:
 vibrating the end portion of the coal face with the false door in a manner that at least partially compacts a portion of the coal face and resists portions of the coal face from spilling from the pusher side opening of the coke oven.
- Although the technology has been described in language that is specific to certain structures, materials, and methodological steps, it is to be understood that the invention defined in the appended claims is not necessarily limited to the specific structures, materials, and/or steps described. Rather, the specific aspects and steps are described as forms of implementing the claimed invention. Further, certain aspects of the new technology described in the context of particular embodiments may be combined or eliminated in other embodiments. Moreover, while advantages associated with certain embodiments of the technology have been described in the context of those embodiments, other embodiments may also exhibit such advantages, and not all embodiments need necessarily exhibit such advantages to fall within the scope of the technology. Accordingly, the disclosure and associated technology can encompass other embodiments not expressly shown or described herein. Thus, the disclosure is not limited except as by the appended claims. Unless otherwise indicated, all numbers or expressions, such as those expressing dimensions, physical characteristics, etc. used in the specification (other than the claims) are understood as modified in all instances by the term "approximately." At the very least, and not as an attempt to limit the application of the doctrine of equivalents to the claims, each numerical parameter recited in the specification or claims which is modified by the term "approximately" should at least be construed in light of the number of recited significant digits and by applying ordinary rounding techniques. Moreover, all ranges disclosed herein are to be understood to encompass and provide support for

19

claims that recite any and all subranges or any and all individual values subsumed therein. For example, a stated range of 1 to 10 should be considered to include and provide support for claims that recite any and all subranges or individual values that are between and/or inclusive of the minimum value of 1 and the maximum value of 10; that is, all subranges beginning with a minimum value of 1 or more and ending with a maximum value of 10 or less (e.g., 5.5 to 10, 2.34 to 3.56, and so forth) or any values from 1 to 10 (e.g., 3, 5.8, 9.9994, and so forth).

We claim:

1. A coal charging system for charging a coke oven, the system comprising:

an elongated charging frame; and

a charging head operatively coupled with the distal end portion of the elongated charging frame;

an elongated false door frame having a distal end portion, proximal end portion, and opposite sides;

a generally planar false door operatively coupled with the distal end portion of the elongated false door frame; the false door having an upper edge portion, lower edge portion, opposite side portions, a front face, and a rearward face; the front face of the false door residing within a false door plane that is substantially vertical; and

a lower extension plate operatively coupled with the front face of the false door; the lower extension plate being automated, such that it is selectively and incrementally moveable with respect to the false door between an infinite number of vertically retracted and extended positions when the false door is disposed within the coke oven; wherein at least some of the infinite number of vertically extended positions disposes a lower edge portion of the lower extension plate below the lower edge portion of the false door such that an effective height of the false door is increased.

2. The coal charging system of claim 1 further comprising:

a linkage arm assembly operatively coupled with the lower extension plate and at least one power cylinder that may be selectively activated to move the lower extension plate between the retracted and extended positions.

3. The coal charging system of claim 2 further comprising:

at least one extension plate bracket operatively coupled with the lower extension plate and the linkage arm assembly; the at least one extension plate bracket extending through at least one slot that penetrates the false door.

4. A false door system for use with a coal charging system to charge a coke oven, having an elongated charging frame with a charging head coupled with a distal end portion of the charging frame, the system comprising:

an elongated false door frame having a distal end portion, proximal end portion, and opposite sides; and

a generally planar false door operatively coupled with the distal end portion of the elongated false door frame; the false door having an upper edge portion, lower edge portion, opposite side portions, a front face, and a rearward face;

a lower extension plate operatively coupled with the front face of the false door; the lower extension plate being automated, such that it is selectively and incrementally moveable with respect to the false door between an infinite number of vertically retracted and extended positions when the false door is disposed within the

20

coke oven; wherein at least some of the infinite number of vertically extended positions disposes a lower edge portion of the lower extension plate below the lower edge portion of the false door such that an effective height of the false door is increased.

5. The coal charging system of claim 4 further comprising:

a linkage arm assembly operatively coupled with the lower extension plate and at least one power cylinder that may be selectively activated to move the lower extension plate between the retracted and extended positions.

6. The coal charging system of claim 5 further comprising:

at least one extension plate bracket operatively coupled with the lower extension plate and the linkage arm assembly; the at least one extension plate bracket extending through at least one slot that penetrates the false door.

7. A method of increasing a coal charge in a coke oven, the method comprising:

positioning a coal charging system, having an elongated charging frame and a charging head operatively coupled with the distal end portion of the elongated charging frame, at least partially within a pusher side opening of a coke oven;

positioning a false door system, having an elongated false door frame and a generally planar false door operatively coupled with a distal end portion of the elongated false door frame, at least partially within the pusher side opening of the coke oven; the false door having an upper edge portion, lower edge portion, opposite side portions, a front face, and a rearward face; wherein the false door system further comprises a lower extension plate operatively coupled with the front face of the false door; the lower extension plate being automated, such that it is selectively and incrementally moveable with respect to the false door between an infinite number of vertically retracted and extended positions when the false door is disposed within the coke oven; wherein at least some of the infinite number of vertically extended positions disposes a lower edge portion of the lower extension plate below the lower edge portion of the false door such that an effective height of the false door is increased;

charging coal into the coke oven with the coal charging system in a manner that defines a coal charge having a generally vertical end portion; and

operatively coupling an oven door with the coke oven in a manner that closes the pusher side opening of the coke oven.

8. The method of claim 7 wherein the generally vertical end portion of the coal charge is positioned closely adjacent a refractory face of the oven door.

9. The method of claim 7 wherein the generally vertical end portion of the coal charge is positioned no more than six inches from a refractory face of the oven door.

10. The method of claim 7 wherein the generally vertical end portion of the coal charge is positioned no more than twelve inches from a refractory face of the oven door.

11. The method of claim 7 further comprising:

reciprocally impacting the end portion of the coal face with the false door in a manner that at least partially compacts a portion of the coal face and resists portions of the coal face from spilling from the pusher side opening of the coke oven.

12. The method of claim 7 further comprising:
applying a fluid to the coal face with the false door in a
manner that wets a portion of the coal face and resists
portions of the coal face from spilling from the pusher
side opening of the coke oven.

5

* * * * *