



US009592482B2

(12) **United States Patent**
Piotrowski et al.

(10) **Patent No.:** **US 9,592,482 B2**
(45) **Date of Patent:** ***Mar. 14, 2017**

(54) **SYSTEM, METHOD AND APPARATUS FOR PROCESSING FIBER MATERIALS**

(58) **Field of Classification Search**
CPC B02C 19/22; B01F 7/00258; E04F 21/085
(Continued)

(71) Applicant: **CERTAINEED CORPORATION**,
Malvern, PA (US)

(56) **References Cited**

(72) Inventors: **Tony S. Piotrowski**, Winter Haven, FL (US); **Jack D. Coulter**, Winter Haven, FL (US); **Bruce A. Hartzell**, Mickleton, NJ (US)

U.S. PATENT DOCUMENTS

3,254,777 A 6/1966 Vandusen
3,787,161 A * 1/1974 Frye B01F 7/00125
241/191

(73) Assignee: **CERTAINEED CORPORATION**,
Malvern, PA (US)

(Continued)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 603 days.

This patent is subject to a terminal disclaimer.

OTHER PUBLICATIONS

Martin Sprocket & Gear, Inc., Catalog 2001, CEMA Standards, 2 pages.

Primary Examiner — Mark Rosenbaum

(74) *Attorney, Agent, or Firm* — Abel Law Group, LLP; Alexander H. Plache

(21) Appl. No.: **14/023,732**

(22) Filed: **Sep. 11, 2013**

(57) **ABSTRACT**

(65) **Prior Publication Data**

US 2014/0010039 A1 Jan. 9, 2014

A system for processing material has a power supply and a machine having a hopper for receiving and passing material to an auger. The auger has a shaft with an axis about which it rotates, a helical fighting mounted to the shaft, pins mounted to the helical fighting, and paddles mounted to the shaft. The radial outer edge of the helical fighting is crenelated with periodic notches that form rectangular blades on the helical fighting. The pins are rotationally and angularly aligned with leading edges of the rectangular blades. The system may include a vehicle, such as a trailer, having first and second compartments separated by a partition. The power supply is located in the first compartment and has a power supply member extending through the partition. The machine is located in the second compartment and coupled to the power supply member.

Related U.S. Application Data

(62) Division of application No. 12/981,657, filed on Dec. 30, 2010, now Pat. No. 8,556,200.
(Continued)


(51) **Int. Cl.**

B02C 19/22 (2006.01)
B01F 7/00 (2006.01)
E04F 21/08 (2006.01)

(52) **U.S. Cl.**

CPC **B01F 7/00258** (2013.01); **B02C 19/22** (2013.01); **E04F 21/085** (2013.01)

20 Claims, 12 Drawing Sheets



Related U.S. Application Data

(60) Provisional application No. 61/304,543, filed on Feb. 15, 2010.

(58) **Field of Classification Search**

USPC 241/260.1

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,337,902	A	7/1982	Markham	
4,465,239	A	8/1984	Woten	
5,403,128	A	4/1995	Thomas	
5,433,577	A *	7/1995	Roycraft B02C 19/22 198/677
5,443,588	A *	8/1995	Loppoli A01C 3/063 198/662
5,462,238	A	10/1995	Smith et al.	
5,601,239	A	2/1997	Smith et al.	
5,732,892	A	3/1998	Neier	
6,088,968	A	7/2000	Williston, Jr. et al.	
6,161,784	A	12/2000	Horton	
6,273,350	B1	8/2001	Kirby et al.	
6,668,534	B2	12/2003	Sheedy et al.	
6,732,960	B2	5/2004	Shaw et al.	
6,796,748	B1	9/2004	Sperber	
7,090,441	B1	8/2006	Borgman et al.	
7,207,506	B1	4/2007	Dickson et al.	
8,556,200	B2 *	10/2013	Piotrowski E04F 21/085 241/260.1

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12

SYSTEM, METHOD AND APPARATUS FOR PROCESSING FIBER MATERIALS

CROSS-REFERENCE TO RELATED APPLICATIONS

The present application is a continuation of U.S. application Ser. No. 12/981,657, filed Dec. 30, 2010, which claims priority under 35 U.S.C. §119(e) of U.S. provisional application No. 61/304,543, filed Feb. 15, 2010. The entire disclosures of these applications are expressly incorporated by reference herein.

BACKGROUND

Field of the Disclosure

This invention relates generally to providing insulation materials for application to and installation in buildings or other structures and, in particular, to an improved system, method and apparatus for the economical and efficient application of particulate insulation materials from bales or bags of insulation to the surfaces of buildings or other structures by processing and pneumatically blowing or spraying such materials.

Description of the Related Art

Insulation materials such as fibers of granulated rock wool, granulated mineral fiber wool, glass fiber materials, cellulose fibers, expanded mica, etc., may comprise a particulate form. They are typically either blown dry or sprayed through a nozzle with a liquid to form an insulating and sealing coating on a surface. These materials are blown on conventional walls, attics and ceilings in places of habitation or working areas, but also may be sprayed on any other surface as desired.

The insulation material used in conventional insulation spraying and blowing machines is usually in a relatively loose condition. However, it is packed under high compression in bales, bags or sacks for shipment to the user. Upon being opened, the bales or bags are typically manually placed into the receiving hopper of the insulation spraying and blowing machine. The compressed masses of insulation material normally would render the insulation material difficult to use in a conventional apparatus that requires feeding through an air hose to a dispensing nozzle. To reduce the masses of insulation, which may include nodules of material, separation into particulate form must be performed. To some extent the insulation material may be entwined rather than discreet in form. The particulate may include not only particles but also intertwined or overlapping fibers.

To apply insulation materials not only in particulate form but also economically and efficiently, the desirable insulation blowing apparatus would be on a wheeled vehicle for convenience and economy of application. This necessitates a near continuous supply of insulation filled bags with the insulation being emptied into the hopper of the insulation blowing machine.

Accordingly, some commercial hoppers are quite large and operate to fill machines with a series of material separation and movement devices for sequentially chopping, mixing and churning the material, which significantly increases the overall size and complexity of the machine. In contrast, small volume machines have hoppers with minimal capacity and require continuous attention. Small machines also require the insulation to be broken up into smaller pieces for introduction into the feeding hoppers. Moreover, all small machines are electric and do not have their own power supply, with many requiring a dual electric circuit to

provide power to their chopper and blower. An improved design for processing and distributing insulation would be desirable.

SUMMARY OF THE INVENTION

Embodiments of a system, method and apparatus for processing material are disclosed. For example, an embodiment of an apparatus for processing material comprises a power supply and a machine powered by the power supply and having a hopper for receiving and passing material to an auger. The auger has a shaft with an axis about which it rotates, a helical flighting mounted to the shaft, pins mounted to the helical flighting, and paddles mounted to the shaft.

In some embodiments, the radial outer edge of the helical flighting is crenelated with periodic notches that form rectangular blades on the helical flighting. The pins are rotationally and angularly aligned with leading edges of the rectangular blades, and extend radially beyond the helical flighting. The axial end of the helical flighting forms a distal edge that may be rotationally aligned with at least one of the paddles.

Embodiments also comprise a system for processing insulation material, including a vehicle, such as a trailer, having first and second compartments separated by a partition. The power supply is located in the first compartment and has a power supply member extending through the partition. The machine is located in the second compartment and coupled to the power supply member.

BRIEF DESCRIPTION OF THE DRAWINGS

The present disclosure may be better understood, and its numerous features and advantages made apparent to those skilled in the art by referencing the accompanying drawings.

FIG. 1 is a front isometric view of one embodiment of an insulation processing apparatus;

FIG. 2 is another isometric view of a portion of another embodiment of the apparatus, shown with a cover removed;

FIG. 3 is an exploded isometric view of another embodiment of the apparatus;

FIG. 4 is an isometric view of an embodiment of an auger for the apparatus;

FIG. 5 is a side view of an embodiment of an auger;

FIG. 6 is an end view of an embodiment of an auger;

FIG. 7 is an isometric view of another embodiment of the apparatus, shown installed in a trailer (with some walls removed for illustration purposes);

FIG. 8 is a front isometric view of an embodiment of a power supply for the apparatus installed in a compartment of a trailer;

FIG. 9 is an isometric view of another embodiment of the apparatus, shown installed in a trailer and with a bale of insulation material;

FIG. 10 is an isometric view of an alternate embodiment of the apparatus; and

FIGS. 11 and 12 are enlarged front views of different portions of the apparatus of FIG. 10.

The use of the same reference symbols in different drawings indicates similar or identical items.

DETAILED DESCRIPTION

FIGS. 1-12 disclose embodiments of a system, method and apparatus for processing material. For example, as shown in FIGS. 1-3, the apparatus 21 may comprise a power

supply **23** and a machine **25** that is coupled to and powered by the power supply **23** for processing insulation materials. In the embodiment shown, the power supply **23** comprises an internal combustion engine that is coupled to the machine **25** via a drive shaft **27** (FIG. 3). In other embodiments, however, the power supply **23** may comprise other types of mechanical or electrical power generators. The power supply **23** may be coupled to the machine **25** via various means such as the pulleys, belts, shafts and gears depicted, as is known to those of ordinary skill in the art.

The machine **25** has a hopper **29** for receiving and passing material to an auger **31** (FIG. 3) that rotates within the machine **25**. The hopper **29** may be provided with a horizontal platform **30** for supporting a bale, sack or bag of material **33** (see, e.g., FIG. 9). In the embodiment shown, the hopper **29** has a capacity of approximately 1.5 bales and passes the material directly to the auger **31** by gravity. The hopper **29** has a generally rectangular opening **35** (FIG. 1) that is configured to and slightly larger than the profile of the bale **33** of material to limit the intake of material. The horizontal platform **30** transitions to a substantially vertical chute **37** downstream from the opening **35**. The vertical chute **37** is located directly over a portion of the auger **31**.

In the illustrated embodiment, the auger **31** is located in a trough **41** (FIGS. 2 and 3) and coupled to and rotated by the power supply **23** without contacting the surfaces of the trough **41**. As best shown in FIGS. 4-6, the auger **31** comprises a shaft **43** with an axis **45** about which the auger **31** rotates. In the embodiment shown, a single spiral or helical flighting **47** (e.g., a helix) is mounted to the shaft. Pins **49** are mounted to the helical flighting **47**, and a series of paddles **51** are mounted to the shaft **43**.

The embodiment shown depicts a radial outer edge of the helical flighting **47** being crenelated or castellated with periodic notches **53** that form generally rectangular blades **55** on the helical flighting **47**. The pins **49** are rotationally and angularly aligned with the leading edges **57** of the generally rectangular blades **55**. The pins **49** extend radially beyond the radial outer edge of the helical flighting, such that the radial outer edge has a shorter radial length **59** (FIG. 6) than a pin radial length **61** of pins **49** relative to the axis **45**. The pins **49** have distal ends that define the pin radial length **61** relative to the axis **45**. The paddles **51** have distal ends that define a paddle radial length **63** relative to the axis **45**, and the pin and paddle radial lengths **61**, **63** are equal in some embodiments.

Embodiments of an axial end **65** (FIG. 5) of the helical flighting **47** form a distal edge thereof that is rotationally aligned (e.g., at the 12 o'clock position in FIG. 6) with at least one of the paddles **51** (e.g., one paddle **51** in the embodiment shown). The distal edge **65** extends in a radially orthogonal direction relative to the axis **45**. In addition, the helical flighting **47** has an axial pitch **67** (FIG. 5) that is cyclical and defines an axial length. The distal edge **65** of the helical flighting **47** is spaced apart from the one aligned paddle **51** by an axial distance **69** that is less than the axial pitch **67**. In some embodiments, the helical flighting **47** has at least three axial pitches.

Again referring to the embodiment of FIG. 5, each paddle **51** comprises a plate **71** with a surface **73** that is flat, elongated and rectangular. Each plate **71** protrudes radially from the shaft **43** such that the surface **73** is parallel to the axis **45**. Each plate **71** also is supported by a support bracket **75** extending from the shaft **43**.

In some embodiments, the paddles **51** comprise a first set **81** (FIGS. 5 and 6) of two paddles **51** at an axial end of the shaft **43**. The first set **81** is rotationally opposed (e.g., at the

12 and 6 o'clock positions) to each other relative to the axis **43**. A second set **83** of two paddles **51** are axially spaced apart from and rotationally orthogonal to the first set **81**. The second set **83** also is rotationally opposed to each other at, for example, the 3 and 9 o'clock positions. A single paddle **85** is axially spaced apart from and rotationally orthogonal to the second set **83** and axially opposite the first set **81**. The single paddle **85** rotationally aligns with one of the two paddles **51** of the first set **81** (e.g., at the 6 o'clock position).

In operation (FIG. 9), the bale **33** is opened and any packaging material or binding for the material is discarded. The material is put in hopper **25** and moved by the operator from the platform through opening **35** and falls through vertical chute **37** onto the rotating auger **31**. The whirling helical flighting **47** and pins **49** pick apart the insulation material and axially propagate or push it right to left (in the illustrated embodiment) toward paddles **51**. Thus, only some of the insulation material entering through the hopper **25** makes immediate contact with paddles **51**. Paddles **51** then push the separated material away from the auger **31** out of the trough **41** and into a feeder **91** (FIGS. 2 and 3) having an airlock for maintaining pneumatic pressure in the system. A blower **93** provides air pressure to feeder **91** and propels the separated material through hoses **95** for delivery to and installation in a building or the like, as is known by those of ordinary skill in the art.

Referring now to FIGS. 7-9, some embodiments comprise a system for processing insulation material. For ease of transportation, a vehicle **101** (e.g., a utility tow trailer, or mid-size box truck or van), has first and second compartments **103**, **105** separated by a partition **107**. The power supply **23** is located in the first compartment **103** and has a power supply member (e.g., drive shaft) extending through the partition. In other embodiments, only the drive shaft extends through the partition **107**, which is sealed to avoid exposing the operator in compartment **105** to the noise, heat and fumes generated by the power supply **23**.

The machine **25** may be located in the second compartment **105**, coupled to the power supply member and operates as described herein. In FIG. 7, the machine **25** has an optional spool **109** for coiling the hose **95**. In some embodiments, the first and second compartments **103**, **105** are completely separated interior compartments within the vehicle or trailer **101**. The partition **107** may comprise a solid insulated wall that completely separates and isolates the first and second interior compartments **103**, **105**.

Referring now to FIGS. 10-12, an alternate embodiment of the apparatus **121** is shown. Apparatus **121** may employ any of the features, elements and components disclosed herein, and may be incorporated into the systems as described herein. Apparatus **121** further employs features that adjust the amount of material and air pressure utilized to perform some types of operations. The features allow the apparatus to adapt to different types of material applications, such as open blow attic or sidewall applications for the material.

For example, as shown in FIGS. 10 and 11, apparatus **121** has a material flow rate adjustment system **123** that is manually adjustable to vary the size of the opening between the distal end of the trough **41** and the feeder **91** or airlock. In the embodiment shown, material flow rate adjustment system **123** has a slide gate **125** that is horizontally movable (left and right in FIG. 11) within a lower channel **127**. Effectively, slide gate **125** is a thin door that regulates the size of the aperture and material flow rate of material from trough **41** to feeder **91**. Slide gate **125** is operated by a lever **129** that can position slide gate **125** for maximum material

flow (e.g., “open blow attic” position **126**). This position **126** is depicted in FIG. **11**. The lever **129** may be lifted slightly and moved to the right, thereby pivoting and moving or sliding slide gate **125** to the left. These positions reduce the amount of material entering feeder **91**. In the embodiment shown, there are two, lower material flow rate positions **131** and **133**. In FIG. **10**, lever **129** is shown in the lowest material flow rate position **133**. The lever **129** and material flow rate adjustment system **123** are provided with features such as pins and detents to facilitate movement and locking of each of these positions, as is known to those of ordinary skill in the art.

As shown in FIGS. **10** and **12**, apparatus **121** also may be provided with an air bleed system **141** comprising a manually-operated valve **143** and air pressure gage **145**. Operation of the air bleed system **141** may be used in conjunction with the material flow rate adjustment system **123** to suitably adjust the overall operation of the apparatus for the desired application, such as open blow attic or sidewall applications.

In the embodiment of FIG. **12**, the handle **147** of valve **143** is vertical and in a closed position **144** for maximum air flow pressure. This is suitable for open blow attic applications. Accordingly, the needle of gage **145** is at zero, which shows no loss or “bleed” in the air pressure from the system. The air flow pressure in the system may be reduced by intentionally losing or “bleeding” some of the air pressure. Reducing the air pressure in the system is suitable for applications such as sidewall material installations. In the illustrated embodiment, the air pressure may be reduced by rotating handle **147** counter-clockwise to partially open valve **143**, such as to sidewall zone **149** (FIG. **12**). Such movement of the valve will correspond in gage **145** showing the amount of air pressure that is being bled from the system.

The invention has numerous advantages. An insulation machine installation system in accordance with the invention is self-supported by its own power supply and may be mounted in a trailer or van. The design is a simple, less expensive system for installing loose fill insulation that is transported by or in a conventional trailer, truck or van.

Unlike conventional small capacity machines, the invention does not require the insulation to be broken up into smaller pieces for introduction into the feeding hopper. In contrast, this machine permits full bags to be fed, with the hopper holding a full bag plus the entry of the second bag. This is a significant advantage over small machines.

The power supply, such as a small internal combustion engine, is separated from the machine and operator area to minimize exposure of the operator to the noise, exhaust fumes and elevated temperatures originating from the power supply. The engine is located and started in one compartment, which may be baffled and ventilated, and closed with a door or hatch. Only the drive shaft of the engine extends to the machine. The operator may use a wireless radio remote to control the machine functions. This design improves work environment conditions to users operating the equipment for an extended period of time.

In some embodiments, the small to mid-size insulation machine system is designed to operate out of a mid-size van or enclosed tow utility trailer. The system has a unique design unlike any insulation system currently on the market today with its full single bag feed hopper and its stand alone power supply. Other features include taking the highly compressed fiberglass insulation and processing it with a single material dispersement mechanism. The process also efficiently feeds material into the airlock unlike conventional machines.

This written description uses examples to disclose the embodiments, including the best mode, and also to enable those of ordinary skill in the art to make and use the invention. The patentable scope is defined by the claims, and may include other examples that occur to those skilled in the art. Such other examples are intended to be within the scope of the claims if they have structural elements that do not differ from the literal language of the claims, or if they include equivalent structural elements with insubstantial differences from the literal languages of the claims.

Note that not all of the activities described above in the general description or the examples are required, that a portion of a specific activity may not be required, and that one or more further activities may be performed in addition to those described. The order in which activities are listed is not necessarily the order in which they are performed.

In the foregoing specification, the concepts have been described with reference to specific embodiments. However, one of ordinary skill in the art appreciates that various modifications and changes can be made without departing from the scope of the invention as set forth in the claims below. Accordingly, the specification and figures are to be regarded in an illustrative rather than a restrictive sense, and all such modifications are intended to be included within the scope of invention.

As used herein, the terms “comprises,” “comprising,” “includes,” “including,” “has,” “having” or any other variation thereof, are intended to cover a non-exclusive inclusion. For example, a process, method, article, or apparatus that comprises a list of features is not necessarily limited only to those features but may include other features not expressly listed or inherent to such process, method, article, or apparatus. Further, unless expressly stated to the contrary, “or” refers to an inclusive-or and not to an exclusive-or. For example, a condition A or B is satisfied by any one of the following: A is true (or present) and B is false (or not present), A is false (or not present) and B is true (or present), and both A and B are true (or present).

Also, the use of “a” or “an” are employed to describe elements and components described herein. This is done merely for convenience and to give a general sense of the scope of the invention. This description should be read to include one or at least one and the singular also includes the plural unless it is obvious that it is meant otherwise.

Benefits, other advantages, and solutions to problems have been described above with regard to specific embodiments. However, the benefits, advantages, solutions to problems, and any feature(s) that may cause any benefit, advantage, or solution to occur or become more pronounced are not to be construed as a critical, required, or essential feature of any or all the claims.

After reading the specification, skilled artisans will appreciate that certain features are, for clarity, described herein in the context of separate embodiments, may also be provided in combination in a single embodiment. Conversely, various features that are, for brevity, described in the context of a single embodiment, may also be provided separately or in any subcombination. Further, references to values stated in ranges include each and every value within that range.

What is claimed is:

1. An apparatus for processing material, comprising:
 - a power supply;
 - a machine configured to be powered by the power supply and having a hopper for receiving and passing material to an auger, the auger comprising a shaft with an axis about which the auger rotates, a flighting mounted to

7

- the shaft, and pins mounted to the flighting, wherein the pins extend radially beyond a perimeter of the flighting; and
- an edge of the flighting comprises notches that form blades.
- 2. The apparatus of claim 1, wherein the edge of the flighting is patterned.
- 3. The apparatus of claim 1, wherein the pins are aligned with portions of the notches.
- 4. The apparatus of claim 1, wherein the auger is located in a trough configured to supply material to a feeder; and further comprising:
 - a material flow rate adjustment system configured to vary a size of an opening between the trough and the feeder; and
 - a blower configured to provide air pressure to the feeder and propel separated material through hoses to deliver and install in a building, and an air bleed system configured to reduce air pressure from the blower.
- 5. The apparatus of claim 1, further comprising a paddle mounted to the shaft.
- 6. The apparatus of claim 5, wherein the pins have a pin radial length relative to the axis, the paddle has a paddle radial length relative to the axis, and the pin and paddle radial lengths are substantially equal.
- 7. The apparatus of claim 5, wherein an end of the flighting forms a distal edge that is rotationally aligned with the paddle.
- 8. The apparatus of claim 5, wherein the flighting has an axial pitch that is cyclical and defines an axial length, and an edge of the flighting is spaced apart from the paddle by an axial distance that is less than the axial length.
- 9. The apparatus of claim 5, wherein the paddle comprises a plate with a surface that is flat.
- 10. The apparatus of claim 5, wherein the paddle comprises a first set of paddles, and a second set of paddles spaced apart from the first set.
- 11. An auger, comprising:
 - a shaft with an axis about which the auger rotates;
 - a flighting mounted to the shaft;

8

- pins mounted to the flighting, and the pins are aligned with edges of the flighting; and
- a distal edge of the flighting comprises notches that form blades.
- 12. The auger of claim 11, wherein the pins extend radially beyond a perimeter of the flighting.
- 13. The auger of claim 11, further comprising a paddle mounted to the shaft.
- 14. The auger of claim 13, wherein the pins have a pin radial length relative to the axis, the paddle has a paddle radial length relative to the axis, and the pin and paddle radial lengths are substantially equal.
- 15. The auger of claim 13, wherein the flighting has a pitch with an axial length, and the flighting is spaced apart from the paddle by an axial distance that is less than the axial length.
- 16. The auger of claim 13, wherein the paddles comprise a first set of paddles, a second set of paddles spaced apart from the first set.
- 17. An apparatus for processing material, comprising:
 - a power supply;
 - a machine configured to be powered by the power supply and having a hopper for receiving and passing material to an auger, the auger is located in a trough configured to supply material to a feeder;
 - the auger comprises a shaft with an axis about which the auger rotates, a flighting mounted to the shaft, and pins mounted to the flighting, wherein the pins extend radially beyond a perimeter of the flighting; and
 - a material flow rate adjustment system configured to vary a size of an opening between the trough and the feeder.
- 18. The apparatus of claim 17, further comprising a blower configured to provide air pressure to the feeder and propel separated material through hoses to deliver and install in a building.
- 19. The apparatus of claim 18, further comprising an air bleed system configured to reduce air pressure from the blower.
- 20. The apparatus of claim 17, wherein an edge of the flighting comprises notches that form blades.

* * * * *