



US009588515B2

(12) **United States Patent**  
**Coombs et al.**

(10) **Patent No.:** **US 9,588,515 B2**

(45) **Date of Patent:** **Mar. 7, 2017**

(54) **SYSTEMS AND METHODS FOR REMOTE CONTROL OF A NON-DESTRUCTIVE TESTING SYSTEM**

USPC ..... 702/34, 81, 108, 122, 188, 94; 340/505; 382/141; 700/258; 715/752; 726/21; 324/240; 345/173

See application file for complete search history.

(71) Applicant: **General Electric Company**,  
Schenectady, NY (US)

(56) **References Cited**

(72) Inventors: **Kevin Andrew Coombs**, Syracuse, NY (US); **Rajeshkumar Venugopal**, Skaneateles, NY (US); **Eugene Carl Schiefer**, Baldwinsville, NY (US); **Michael Stanton Reeder, Jr.**, Munnsville, NY (US)

U.S. PATENT DOCUMENTS

6,317,039 B1 11/2001 Thomason  
6,830,545 B2 12/2004 Bendall  
7,252,633 B2 † 8/2007 Obata  
7,370,532 B2 † 5/2008 Osterkamp  
8,059,882 B2 11/2011 Amidi  
8,108,168 B2 1/2012 Sharp et al.  
8,138,755 B2 † 3/2012 Drummy

(Continued)

(73) Assignee: **General Electric Company**,  
Schenectady, NY (US)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 1073 days.

FOREIGN PATENT DOCUMENTS

KR 100997194 B1 11/2010  
WO 2008157170 A2 12/2008

(Continued)

(21) Appl. No.: **13/732,252**

(22) Filed: **Dec. 31, 2012**

OTHER PUBLICATIONS

(65) **Prior Publication Data**

US 2014/0188435 A1 Jul. 3, 2014

U.S. Appl. No. 13/732,238, filed Dec. 31, 2012, Michael Christopher Domke.

(Continued)

(51) **Int. Cl.**

**G01B 15/00** (2006.01)  
**G05B 23/00** (2006.01)  
**H04N 5/232** (2006.01)  
**H04N 5/225** (2006.01)

Primary Examiner — John H Le

(74) Attorney, Agent, or Firm — Fletcher Yoder, P.C.

(52) **U.S. Cl.**

CPC ..... **G05B 23/00** (2013.01); **G01B 15/00** (2013.01); **H04N 5/23206** (2013.01); **H04N 5/23216** (2013.01); **H04N 5/23296** (2013.01); **H04N 2005/2255** (2013.01)


(57) **ABSTRACT**

A system may include a non-destructive testing (NDT) device. The NDT device may further include a wireless system configured to communicate control data from an external system, wherein the NDT device is configured to use the control data to control a component included in the NDT device.

(58) **Field of Classification Search**

CPC ..... G06F 3/0484; G06F 3/0488; G01B 15/00; G05B 23/00; G08C 17/02; G08C 2201/42; H04N 2005/2255; H04N 5/23206; H04N 5/23216; H04N 5/23296

**20 Claims, 12 Drawing Sheets**



(56)

References Cited

U.S. PATENT DOCUMENTS

8,255,170 B2 † 8/2012 Kollgaard  
 8,732,823 B2 † 5/2014 Yokota  
 8,798,940 B2 † 8/2014 Imbert  
 9,152,304 B2\* 10/2015 Schiefer ..... G06F 3/0484  
 2002/0198997 A1 12/2002 Linthicum et al.  
 2003/0089183 A1 † 5/2003 Jacobsen  
 2011/0295427 A1\* 12/2011 Motzer ..... B25J 9/162  
 700/258  
 2013/0179801 A1\* 7/2013 Audet ..... G06F 9/4443  
 715/752

FOREIGN PATENT DOCUMENTS

WO 2011021788 A2 2/2011  
 WO 2011149582 A1 12/2011

OTHER PUBLICATIONS

U.S. Appl. No. 13/732,261, filed Dec. 31, 2012, Eugene Schiefer.  
 U.S. Appl. No. 13/732,281, filed Dec. 31, 2012, Jason Howard Messinger.  
 U.S. Appl. No. 13/732,293, filed Dec. 31, 2012, Jason Howard Messinger.  
 U.S. Appl. No. 13/732,303, filed Dec. 31, 2012 Thomas Eldred Lambdin.  
 U.S. Appl. No. 13/732,268, filed Dec. 31, 2012, Scott Leo Sbihli.  
 U.S. Appl. No. 13/732,309, filed Dec. 31, 2012, Jason Howard Messinger.  
 U.S. Appl. No. 13/732,272, filed Dec. 31, 2012, Jason Howard Messinger.  
 U.S. Appl. No. 13/732,319, filed Dec. 31, 2012, Michael Christopher Domke.  
 U.S. Appl. No. 13/732,327, filed Dec. 31, 2012, Michael Christopher Domke.  
 U.S. Appl. No. 13/747,408, filed Jan. 22, 2013, Michael Christopher Domke.  
 U.S. Appl. No. 13/747,435, filed Jan. 22, 2013, Jason Howard Messinger.  
 U.S. Appl. No. 13/747,438, filed Jan. 22, 2013, Jason Howard Messinger.  
 U.S. Appl. No. 13/747,457, filed Jan. 22, 2013, Jason Howard Messinger.

U.S. Appl. No. 13/747,453, filed Jan. 22, 2013, Sekhar Soorianarayanan.  
 U.S. Appl. No. 13/747,429, filed Jan. 22, 2013, Sekhar Soorianarayanan.  
 U.S. Appl. No. 13/747,464, filed Jan. 22, 2013, Sekhar Soorianarayanan.  
 U.S. Appl. No. 13/747,443, filed Jan. 22, 2013, Jason Howard Messinger.  
 U.S. Appl. No. 13/747,449, filed Jan. 22, 2013, Michael Christopher Domke.  
 U.S. Appl. No. 13/747,456, filed Jan. 22, 2013, Michael Christopher Domke.  
 U.S. Appl. No. 13/747,416, filed Jan. 22, 2013, Michael Christopher Domke.  
 U.S. Appl. No. 13/800,015, filed Mar. 13, 2013, Kevin Andrew Coombs.  
 PCT Search Report and Written Opinion issued Apr. 10, 2014 in connection with corresponding PCT Patent Application No. PCT/US2013/075595.  
 Sorrel, Charlie, iControlPad Ships at Last [online], [retrieved on Mar. 21, 2013]. Retrieved from the Internet <URL: <http://www.wired.com/gadgetlab/2011/11/iconcontrolpad-ships-at-last/>>.  
 OmniScan MX [online]. p. 5. Olympus, 2010 [retrieved on Mar. 28, 2013]. Retrieved from the Internet: <URL: [www.olympus-ims.com/en/omniscan-mx/](http://www.olympus-ims.com/en/omniscan-mx/)>.  
 Georgeson, Gary. [online], [retrieved on Mar. 28, 2013]. <http://www.meetingdata.utcd Dayton.com/agenda/airworthiness/2012/proceedings/presentations/P5526.pdf>.  
 Phasor XS User's Manual [online]. General Electric: Measurement & Control Solutions. [retrieved on Mar. 28, 2013]. Retrieved from the Internet: <URL: [www.ge-mcs.com/download/ultrasound/portable-flaw-detectors/Phasor%20Series/om-phasor-en\\_rev10.pdf](http://www.ge-mcs.com/download/ultrasound/portable-flaw-detectors/Phasor%20Series/om-phasor-en_rev10.pdf)>.  
 USM Vision 1.2—A Total Weld Inspection Solution to Increase Productivity in New Process Pipework Fabrication [online]. General Electric: Measurement & Control. [retrieved on Mar. 28, 2013]. Retrieved from the Internet: <URL: [www.ge-mcs.com/download/ultrasound/portable-flaw-detectors/usm-vision/GEIT-USMVision-20058EN\\_LR.pdf](http://www.ge-mcs.com/download/ultrasound/portable-flaw-detectors/usm-vision/GEIT-USMVision-20058EN_LR.pdf)>.  
 D. Suo et al., "The Wireless Remote Control System for Portable X-ray Machines," 2009 World Congress on Computer Science and Information Engineering, 2008 IEEE, pp. 354-358. †  
 H. Leon-Rodriguez et al., "A Compact Wall-Climbing and Surface Adaptation Robot for Non-Destructive Testing," 2012 12th International Conference on Control, Automation and Systems. †

\* cited by examiner  
 † cited by third party




FIG. 2





FIG. 3






FIG. 4




FIG. 5




FIG. 6








FIG. 7








FIG. 10




FIG. 11

22




FIG. 12




FIG. 13

## SYSTEMS AND METHODS FOR REMOTE CONTROL OF A NON-DESTRUCTIVE TESTING SYSTEM

### BACKGROUND

The subject matter disclosed herein relates to non-destructive testing (NDT) systems, and particularly to systems and methods for the remote control of NDT systems.

Certain equipment and facilities, such as power generation equipment and facilities, oil and gas equipment and facilities, aircraft equipment and facilities, manufacturing equipment and facilities, and the like, include a plurality of interrelated systems, and processes. For example, power generation plants may include turbine systems and processes for operating and maintaining the turbine systems. Likewise, oil and gas operations may include carbonaceous fuel retrieval systems and processing equipment interconnected via pipelines. Similarly, aircraft systems may include airplanes and maintenance hangars useful in maintaining airworthiness and providing for maintenance support. During equipment operations, the equipment may degrade, encounter undesired conditions such as corrosion, wear and tear, and so on, potentially affecting overall equipment effectiveness. Certain inspection techniques, such as non-destructive inspection techniques or non-destructive testing (NDT) techniques, may be used to detect undesired equipment conditions.

In a conventional NDT system, data may be shared with other NDT operators or personnel using portable memory devices, paper, or through the telephone. As such, the amount of time to share data between NDT personnel may depend largely on the speed at which the physical portable memory device is physically dispatched to its target. Accordingly, it would be beneficial to improve the data sharing capabilities of the NDT system, for example, to more efficiently test and inspect a variety of systems and equipment.

### BRIEF DESCRIPTION

Certain embodiments commensurate in scope with the originally claimed invention are summarized below. These embodiments are not intended to limit the scope of the claimed invention, but rather these embodiments are intended only to provide a brief summary of possible forms of the invention. Indeed, the invention may encompass a variety of forms that may be similar to or different from the embodiments set forth below.

In one embodiment, a system includes a wireless system configured to communicate control data from an external system, wherein the NDT device is configured to use the control data to control a component included in the NDT device.

In another embodiment, a non-transitory computer readable medium comprises instructions configured to wirelessly receive control data by using a non-destructive testing (NDT) device, wherein the NDT device is configured to use the control data to control a component included in the NDT device.

In yet another embodiment, a method includes wirelessly receiving control data by using a non-destructive testing (NDT) device, wherein the NDT device is configured to use the control data to control a component included in the NDT device.

### BRIEF DESCRIPTION OF THE DRAWINGS

These and other features, aspects, and advantages of the present invention will become better understood when the

following detailed description is read with reference to the accompanying drawings in which like characters represent like parts throughout the drawings, wherein:

FIG. 1 is a block diagram illustrating an embodiment of a distributed non-destructive testing (NDT) system, including a mobile device;

FIG. 2 is a block diagram illustrating further details of an embodiment of the distributed NDT system of FIG. 1;

FIG. 3 is a front view illustrating an embodiment of a borescope system 14 communicatively coupled to the mobile device of FIG. 1 and a "cloud;"

FIG. 4 is an illustration of an embodiment of a pan-tilt-zoom (PTZ) camera system communicatively coupled to the mobile device of FIG. 1;

FIG. 5 is a flowchart illustrating an embodiment of a process useful in using the distributed NDT system for planning, inspecting, analyzing, reporting, and sharing of data, such as inspection data;

FIG. 6 is a block diagram of an embodiment of information flow through a wireless conduit;

FIG. 7 is a block diagram of an embodiment of information flow through a wireless conduit of information useful in remote control of the NDT inspection system of FIG. 1;

FIG. 8 is a screen view of an embodiment of a virtual joystick;

FIG. 9 is a view of embodiments of a plurality of virtual controls;

FIG. 10 is a view of a plurality of positions for the virtual joystick of FIG. 8, in accordance with one embodiment;

FIG. 11 is a view of an embodiment of a translucent control pad;

FIG. 12 is a view of a plurality of gesture controls, in accordance with one embodiment; and

FIG. 13 is a perspective view on an embodiment of the mobile device of FIG. 1 suitable for motion and/or voice control.

### DETAILED DESCRIPTION

One or more specific embodiments will be described below. In an effort to provide a concise description of these embodiments, not all features of an actual implementation are described in the specification. It should be appreciated that in the development of any such actual implementation, as in any engineering or design project, numerous implementation-specific decisions must be made to achieve the developers' specific goals, such as compliance with system-related and business-related constraints, which may vary from one implementation to another. Moreover, it should be appreciated that such a development effort might be complex and time consuming, but would nevertheless be a routine undertaking of design, fabrication, and manufacture for those of ordinary skill having the benefit of this disclosure.

When introducing elements of various embodiments of the present invention, the articles "a," "an," "the," and "said" are intended to mean that there are one or more of the elements. The terms "comprising," "including," and "having" are intended to be inclusive and mean that there may be additional elements other than the listed elements.

Embodiments of the present disclosure may apply to a variety of inspection and testing techniques, including non-destructive testing (NDT) or inspection systems. In the NDT system, certain techniques such as borescopic inspection, weld inspection, remote visual inspections, x-ray inspection, ultrasonic inspection, eddy current inspection, and the like, may be used to analyze and detect a variety of conditions,

3

including but not limited to corrosion, equipment wear and tear, cracking, leaks, and so on. The techniques described herein provide for improved NDT systems suitable for borescopic inspection, remote visual inspections, x-ray inspection, ultrasonic inspection, and/or eddy current inspection, enabling enhanced data gathering, data analysis, inspection/testing processes, and NDT collaboration techniques.

The improved NDT systems described herein may include inspection equipment using wireless conduits suitable for communicatively coupling the inspection equipment to mobile devices, such as tablets, smart phones, and augmented reality eyeglasses; to computing devices, such as notebooks, laptops, workstations, personal computers; and to “cloud” computing systems, such as cloud-based NDT ecosystems, cloud analytics, cloud-based collaboration and workflow systems, distributed computing systems, expert systems and/or knowledge-based systems.

Indeed, the techniques described herein may provide for enhanced NDT data gathering, analysis, and data distribution, thus improving the detection of undesired conditions, enhancing maintenance activities, and increasing returns on investment (ROI) of facilities and equipment.

In one embodiment, a tablet may be communicatively coupled to the NDT inspection device (e.g., borescope, transportable pan-tilt-zoom camera, eddy current device, x-ray inspection device, ultrasonic inspection device), such as a MENTOR™ NDT inspection device, available from General Electric, Co., of Schenectady, N.Y., and used to provide, for example, enhanced wireless display capabilities, remote control, data analytics and/or data communications to the NDT inspection device. While other mobile devices may be used, the use of the tablet is apt, however, insofar as the tablet may provide for a larger, higher resolution display, more powerful processing cores, an increased memory, and improved battery life. Accordingly, the tablet may address certain issues, such as providing for improved visualization of data, improving the manipulatory control of the inspection device, and extending collaborative sharing to a plurality of external systems and entities.

Keeping the foregoing in mind, the present disclosure is directed towards sharing data acquired from the NDT system and/or control of applications and/or devices in the NDT system. Generally, data generated from the NDT system may be automatically distributed to various people or groups of people using techniques disclosed herein. Moreover, content displayed by an application used to monitor and/or control devices in the NDT system may be shared between individuals to create a virtual collaborative environment for monitoring and controlling the devices in the NDT system.

By way of introduction, and turning now to FIG. 1, the figure is a block diagram of an embodiment of distributed NDT system 10. In the depicted embodiment, the distributed NDT system 10 may include one or more NDT inspection devices 12. The NDT inspection devices 12 may be divided into at least two categories. In one category, depicted in FIG. 1, the NDT inspection devices 12 may include devices suitable for visually inspecting a variety of equipment and environments. In another category, described in more detail with respect to FIG. 2 below, the NDT devices 12 may include devices providing for alternatives to visual inspection modalities, such as x-ray inspection modalities, eddy current inspection modalities, and/or ultrasonic inspection modalities.

In the depicted first example category of FIG. 1, the NDT inspection devices 12 may include a borescope 14 having one or more processors 15 and a memory 17, and a trans-

4

portable pan-tilt-zoom (PTZ) camera 16 having one or more processors 19 and a memory 21. In this first category of visual inspection devices, the bore scope 14 and PTZ camera 16 may be used to inspect, for example, a turbo machinery 18, and a facility or site 20. As illustrated, the bore scope 14 and the PTZ camera 16 may be communicatively coupled to a mobile device 22 also having one or more processors 23 and a memory 25. The mobile device 22 may include, for example, a tablet, a cell phone (e.g., smart phone), a notebook, a laptop, or any other mobile computing device. The use of a tablet, however, is apt insofar as the tablet provides for a good balance between screen size, weight, computing power, and battery life. Accordingly, in one embodiment, the mobile device 22 may be the tablet mentioned above, available from General Electric Co., of Schenectady, N.Y., and providing for touchscreen input. The mobile device 22 may be communicatively coupled to the NDT inspection devices 12, such as the bore scope 14 and/or the PTZ camera 16, through a variety of wireless or wired conduits. For example, the wireless conduits may include WiFi (e.g., Institute of Electrical and Electronics Engineers [IEEE] 802.11X), cellular conduits (e.g., high speed packet access [HSPA], HSPA+, long term evolution [LTE], WiMax), near field communications (NFC), Bluetooth, personal area networks (PANs), and the like. The wireless conduits may use a variety of communication protocols, such as TCP/IP, UDP, SCTP, socket layers, and so on. In certain embodiments, the wireless or wired conduits may include secure layers, such as secure socket layers (SSL), virtual private network (VPN) layers, encrypted layers, challenge key authentication layers, token authentication layers, and so on. Wired conduits may include proprietary cabling, RJ45 cabling, co-axial cables, fiber optic cables, and so on.

Additionally or alternatively, the mobile device 22 may be communicatively coupled to the NDT inspection devices 12, such as the borescope 14 and/or the PTZ camera 16, through the “cloud” 24. Indeed, the mobile device 22 may use the cloud 24 computing and communications techniques (e.g., cloud-computing network), including but not limited to HTTP, HTTPS, TCP/IP, service oriented architecture (SOA) protocols (e.g., simple object access protocol [SOAP], web services description languages (WSDLs)) to interface with the NDT inspection devices 12 from any geographic location, including geographic locations remote from the physical location about to undergo inspection. Further, in one embodiment, the mobile device 22 may provide “hot spot” functionality in which mobile device 22 may provide wireless access point (WAP) functionality suitable for connecting the NDT inspection devices 12 to other systems in the cloud 24. Accordingly, collaboration may be enhanced by providing for multi-party workflows, data gathering, and data analysis.

For example, a borescope operator 26 may physically manipulate the borescope 14 at one location, while a mobile device operator 28 may use the mobile device 22 to interface with and physically manipulate the bore scope 14 at a second location through remote control techniques. The second location may be proximate to the first location, or geographically distant from the first location. Likewise, a camera operator 30 may physically operate the PTZ camera 16 at a third location, and the mobile device operator 28 may remote control PTZ camera 16 at a fourth location by using the mobile device 22. The fourth location may be proximate to the third location, or geographically distant from the third location. Any and all control actions performed by the operators 26 and 30 may be additionally performed by the operator 28 through the mobile device 22. Additionally, the



5

operator **28** may communicate with the operators **26** and/or **30** by using the devices **14**, **16**, and **22** through techniques such as voice over IP (VOIP), virtual whiteboarding, text messages, and the like. By providing for remote collaboration techniques between the operator **28**, operator **26**, and operator **30**, the techniques described herein may provide for enhanced workflows and increase resource efficiencies. Indeed, nondestructive testing processes may leverage the communicative coupling of the cloud **24** with the mobile device **22**, the NDT inspection devices **12**, and external systems coupled to the cloud **24**.

In one mode of operation, the mobile device **22** may be operated by the bore scope operator **26** and/or the camera operator **30** to leverage, for example, a larger screen display, more powerful data processing, as well as a variety of interface techniques provided by the mobile device **22**, as described in more detail below. Indeed, the mobile device **22** may be operated alongside or in tandem with the devices **14** and **16** by the respective operators **26** and **30**. This enhanced flexibility provides for better utilization of resources, including human resources, and improved inspection results.

Whether controlled by the operator **28**, **26**, and/or **30**, the borescope **14** and/or PTZ camera **16** may be used to visually inspect a wide variety of equipment and facilities. For example, the bore scope **14** may be inserted into a plurality of borescope ports and other locations of the turbomachinery **18**, to provide for illumination and visual observations of a number of components of the turbomachinery **18**. In the depicted embodiment, the turbo machinery **18** is illustrated as a gas turbine suitable for converting carbonaceous fuel into mechanical power. However, other equipment types may be inspected, including compressors, pumps, turbo expanders, wind turbines, hydroturbines, industrial equipment, and/or residential equipment. The turbomachinery **18** (e.g., gas turbine) may include a variety of components that may be inspected by the NDT inspection devices **12** described herein.

With the foregoing in mind, it may be beneficial to discuss certain turbomachinery **18** components that may be inspected by using the embodiments disclosed herein. For example, certain components of the turbomachinery **18** depicted in FIG. 1, may be inspected for corrosion, erosion, cracking, leaks, weld inspection, and so on. Mechanical systems, such as the turbomachinery **18**, experience mechanical and thermal stresses during operating conditions, which may require periodic inspection of certain components. During operations of the turbomachinery **18**, a fuel such as natural gas or syngas, may be routed to the turbomachinery **18** through one or more fuel nozzles **32** into a combustor **36**. Air may enter the turbomachinery **18** through an air intake section **38** and may be compressed by a compressor **34**. The compressor **34** may include a series of stages **40**, **42**, and **44** that compress the air. Each stage may include one or more sets of stationary vanes **46** and blades **48** that rotate to progressively increase the pressure to provide compressed air. The blades **48** may be attached to rotating wheels **50** connected to a shaft **52**. The compressed discharge air from the compressor **34** may exit the compressor **34** through a diffuser section **56** and may be directed into the combustor **36** to mix with the fuel. For example, the fuel nozzles **32** may inject a fuel-air mixture into the combustor **36** in a suitable ratio for optimal combustion, emissions, fuel consumption, and power output. In certain embodiments, the turbomachinery **18** may include multiple combustors **36** disposed in an annular arrangement. Each combustor **36** may direct hot combustion gases into a turbine **54**.

6

As depicted, the turbine **54** includes three separate stages **60**, **62**, and **64** surrounded by a casing **76**. Each stage **60**, **62**, and **64** includes a set of blades or buckets **66** coupled to a respective rotor wheel **68**, **70**, and **72**, which are attached to a shaft **74**. As the hot combustion gases cause rotation of turbine blades **66**, the shaft **74** rotates to drive the compressor **34** and any other suitable load, such as an electrical generator. Eventually, the turbomachinery **18** diffuses and exhausts the combustion gases through an exhaust section **80**. Turbine components, such as the nozzles **32**, intake **38**, compressor **34**, vanes **46**, blades **48**, wheels **50**, shaft **52**, diffuser **56**, stages **60**, **62**, and **64**, blades **66**, shaft **74**, casing **76**, and exhaust **80**, may use the disclosed embodiments, such as the NDT inspection devices **12**, to inspect and maintain said components.

Additionally, or alternatively, the PTZ camera **16** may be disposed at various locations around or inside of the turbo machinery **18**, and used to procure visual observations of these locations. The PTZ camera **16** may additionally include one or more lights suitable for illuminating desired locations, and may further include zoom, pan and tilt techniques described in more detail below with respect to FIG. 4, useful for deriving observations around in a variety of difficult to reach areas. The borescope **14** and/or the camera **16** may be additionally used to inspect the facilities **20**, such as an oil and gas facility **20**. Various equipment such as oil and gas equipment **84**, may be inspected visually by using the borescope **14** and/or the PTZ camera **16**. Advantageously, locations such as the interior of pipes or conduits **86**, underwater (or underfluid) locations **88**, and difficult to observe locations such as locations having curves or bends **90**, may be visually inspected by using the mobile device **22** through the borescope **14** and/or PTZ camera **16**. Accordingly, the mobile device operator **28** may more safely and efficiently inspect the equipment **18**, **84** and locations **86**, **88**, and **90**, and share observations in real-time or near real-time with location geographically distant from the inspection areas. It is to be understood that other NDT inspection devices **12** may be use the embodiments described herein, such as fiberscopes (e.g., articulating fiberoscope, non-articulating fiberoscope), and remotely operated vehicles (ROVs), including robotic pipe inspectors and robotic crawlers.

Turning now to FIG. 2, the figure is a block diagram of an embodiment of the distributed NDT system **10** depicting the second category of NDT inspection devices **12** that may be able to provide for alternative inspection data to visual inspection data. For example, the second category of NDT inspection devices **12** may include an eddy current inspection device **92**, an ultrasonic inspection device, such as an ultrasonic flaw detector **94**, and an x-ray inspection device, such as a digital radiography device **96**. The eddy current inspection device **92** may include one or more processors **93** and a memory **95**. Likewise, the ultrasonic flaw detector **94** may include one or more processors **97** and a memory **104**. Similarly, the digital radiography device **96** may include one or more processors **101** and a memory **103**. In operations, the eddy current inspection device **92** may be operated by an eddy current operator **98**, the ultrasonic flaw detector **94** may be operated by an ultrasonic device operator **100**, and the digital radiography device **96** may be operated by a radiography operator **102**.

As depicted, the eddy current inspection device **92**, the ultrasonic flaw detector **94**, and the digital radiography inspection device **96**, may be communicatively coupled to the mobile device **22** by using wired or wireless conduits, including the conduits mentioned above with respect to FIG. 1. Additionally, or alternatively, the devices **92**, **94**, and **96**

may be coupled to the mobile device **22** by using the cloud **24**, for example the borescope **14** may be connected to a cellular “hotspot,” and use the hotspot to connect to one or more experts in borescopic inspection and analysis. Accordingly, the mobile device operator **28** may remotely control various aspects of operations of the devices **92**, **94**, and **96** by using the mobile device **22**, and may collaborate with the operators **98**, **100**, and **102** through voice (e.g., voice over IP [VOIP]), data sharing (e.g., whiteboarding), providing data analytics, expert support and the like, as described in more detail herein.

Accordingly, it may be possible to enhance the visual observation of various equipment, such as an aircraft system **104** and facilities **106**, with x-ray observation modalities, ultrasonic observation modalities, and/or eddy current observation modalities. For example, the interior and the walls of pipes **108** may be inspected for corrosion and/or erosion. Likewise, obstructions or undesired growth inside of the pipes **108** may be detected by using the devices **92**, **94**, and/or **96**. Similarly, fissures or cracks **110** disposed inside of certain ferrous or non-ferrous material **112** may be observed. Additionally, the disposition and viability of parts **114** inserted inside of a component **116** may be verified. Indeed, by using the techniques described herein, improved inspection of equipment and components **104**, **108**, **112** and **116** may be provided. For example, the mobile device **22** may be used to interface with and provide remote control of the devices **14**, **16**, **92**, **94**, and **96**.

FIG. 3 is a front view of the borescope **14** coupled to the mobile device **22** and the cloud **24**. Accordingly, the borescope **14** may provide data to any number of devices connected to the cloud **24** or inside the cloud **24**. As mentioned above, the mobile device **22** may be used to receive data from the borescope **14**, to remotely control the borescope **14**, or a combination thereof. Indeed, the techniques described herein enable, for example, the communication of a variety of data from the borescope **14** to the mobile device **22**, including but not limited to images, video, and sensor measurements, such as temperature, pressure, flow, clearance (e.g., measurement between a stationary component and a rotary component), and distance measurements. Likewise, the mobile device **22** may communicate control instructions, reprogramming instructions, configuration instructions, and the like, as described in more detail below.

As depicted the borescope **14**, includes an insertion tube **118** suitable for insertion into a variety of location, such as inside of the turbomachinery **18**, equipment **84**, pipes or conduits **86**, underwater locations **88**, curves or bends **90**, various locations inside or outside of the aircraft system **104**, the interior of pipe **108**, and so on. The insertion tube **118** may include a head end section **120**, an articulating section **122**, and a conduit section **124**. In the depicted embodiment, the head end section **120** may include a camera **126**, one or more lights **128** (e.g., LEDs), and sensors **130**. As mentioned above, the borescope’s camera **126** may provide images and video suitable for inspection. The lights **128** may be used to provide for illumination when the head end **120** is disposed in locations having low light or no light.

During use, the articulating section **122** may be controlled, for example, by the mobile device **22** and/or a physical joy stick **131** disposed on the borescope **14**. The articulating sections **122** may steer or “bend” in various dimensions. For example, the articulation section **122** may enable movement of the head end **120** in an X-Y plane X-Z plane and/or Y-Z plane of the depicted XYZ axes **133**. Indeed, the physical joystick **131** and/or the mobile device

**22** may both be used alone or in combination, to provide control actions suitable for disposing the head end **120** at a variety of angles, such as the depicted angle  $\alpha$ . In this manner, the borescope head end **120** may be positioned to visually inspect desired locations. The camera **126** may then capture, for example, a video **134**, which may be displayed in a screen **135** of the borescope **14** and a screen **137** of the mobile device **22**, and may be recorded by the borescope **14** and/or the mobile device **22**. In one embodiment, the screens **135** and **137** may be multi-touchscreens using capacitance techniques, resistive techniques, infrared grid techniques, and the like, to detect the touch of a stylus and/or one or more human fingers. Additionally or alternatively, images and the video **134** may be transmitted into the cloud **24**.

Other data, including but not limited to sensor **130** data, may additionally be communicated and/or recorded by the borescope **14**. The sensor **130** data may include temperature data, distance data, clearance data (e.g., distance between a rotating and a stationary component), flow data, and so on. In certain embodiments, the borescope **14** may include a plurality of replacement tips **136**. For example, the replacement tips **136** may include retrieval tips such as snares, magnetic tips, gripper tips, and the like. The replacement tips **136** may additionally include cleaning and obstruction removal tools, such as wire brushes, wire cutters, and the like. The tips **136** may additionally include tips having differing optical characteristics, such as focal length, stereoscopic views, 3-dimensional (3D) phase views, shadow views, and so on. Additionally or alternatively, the head end **120** may include a removable and replaceable head end **120**. Accordingly, a plurality of head ends **120** may be provided at a variety of diameters, and the insertion tube **118** may be disposed in a number of locations having openings from approximately one millimeter to ten millimeters or more. Indeed, a wide variety of equipment and facilities may be inspected, and the data may be shared through the mobile device **22** and/or the cloud **24**.

FIG. 4 is a perspective view of an embodiment of the transportable PTZ camera **16** communicatively coupled to the mobile device **22** and to the cloud **24**. As mentioned above, the mobile device **22** and/or the cloud **24** may remotely manipulate the PTZ camera **16** to position the PTZ camera **16** to view desired equipment and locations. In the depicted example, the PTZ camera **16** may be tilted and rotated about the Y-axis. For example, the PTZ camera **16** may be rotated at an angle  $\beta$  between approximately  $0^\circ$  to  $180^\circ$ ,  $0^\circ$  to  $270^\circ$ ,  $0^\circ$  to  $360^\circ$ , or more about the Y-axis. Likewise, the PTZ camera **16** may be tilted, for example, about the Y-X plane at an angle  $\gamma$  of approximately  $0^\circ$  to  $100^\circ$ ,  $0^\circ$  to  $120^\circ$ ,  $0^\circ$  to  $150^\circ$ , or more with respect to the Y-Axis. Lights **138** may be similarly controlled, for example, to active or deactivate, and to increase or decrease a level of illumination (e.g., lux) to a desired value. Sensors **140**, such as a laser rangefinder, may also be mounted onto the PTZ camera **16**, suitable for measuring distance to certain objects. Other sensors **140** may be used, including long-range temperature sensors (e.g., infrared temperature sensors), pressure sensors, flow sensors, clearance sensors, and so on.

The PTZ camera **16** may be transported to a desired location, for example, by using a shaft **142**. The shaft **142** enables the camera operator **30** to move the camera and to position the camera, for example, inside of locations **86**, **108**, underwater **88**, into hazardous (e.g., hazmat) locations, and so on. Additionally, the shaft **142** may be used to more permanently secure the PTZ camera **16** by mounting the shaft **142** onto a permanent or semi-permanent mount. In

this manner, the PTZ camera **16** may be transported and/or secured at a desired location. The PTZ camera **16** may then transmit, for example by using wireless techniques, image data, video data, sensor **140** data, and the like, to the mobile device **22** and/or cloud **24**. Accordingly, data received from the PTZ camera **16** may be remotely analyzed and used to determine the condition and suitability of operations for desired equipment and facilities. Indeed, the techniques described herein may provide for a comprehensive inspection and maintenance process suitable for planning, inspecting, analyzing, and/or sharing a variety of data by using the aforementioned devices **12**, **14**, **16**, **22**, **92**, **94**, **96**, and the cloud **24**, as described in more detail below with respect to FIG. **5**.

FIG. **5** is a flowchart of an embodiment of a process **150** suitable for planning, inspecting, analyzing, and/or sharing a variety of data by using the aforementioned devices **12**, **14**, **16**, **22**, **92**, **94**, **96**, and the cloud **24**. Indeed, the techniques described herein may use the devices **12**, **14**, **16**, **22**, **92**, **94**, **96** to enable processes, such as the depicted process **150**, to more efficiently support and maintain a variety of equipment. In certain embodiments, the process **150** or portions of the process **150** may be included in non-transitory computer-readable media stored in memory, such as the memory **17**, **21**, **25**, **95**, **99**, **103** and executable by one or more processors, such as the processors **15**, **19**, **23**, **93**, **97**, **101**.

In one example, the process **150** may plan (block **152**) for inspection and maintenance activities. Data acquired by using the devices **12**, **14**, **16**, **22**, **42**, **44**, **46**, an others, such as fleet data acquired from a fleet of turbomachinery **18**, from equipment users (e.g., aircraft **54** service companies), and/or equipment manufacturers, may be used to plan (block **152**) maintenance and inspection activities, more efficient inspection schedules for machinery, flag certain areas for a more detailed inspection, and so on. The process **150** may then enable the use of a single mode or a multi-modal inspection (block **154**) of desired facilities and equipment (e.g., turbomachinery **18**). As mentioned above, the inspection (block **154**) may use any one or more of the NDT inspection devices **12** (e.g., borescope **14**, PTZ camera **16**, eddy current inspection device **92**, ultrasonic flaw detector **94**, digital radiography device **96**), thus providing with one or more modes of inspection (e.g., visual, ultrasonic, eddy current, x-ray). In the depicted embodiment, the mobile device **22** may be used to remote control the NDT inspection devices **12**, to analyze data communicated by the NDT inspection devices **12**, to provide for additional functionality not included in the NDT inspection devices **12** as described in more detail herein, to record data from the NDT inspection devices **12**, and to guide the inspection (block **154**), for example, by using menu-driven inspection (MDI) techniques, among others.

Results of the inspection (block **154**), may then be analyzed (block **156**), for example, by using the NDT device **12**, by transmitting inspection data to the cloud **24**, by using the mobile device **22**, or a combination thereof. The analysis may include engineering analysis useful in determining remaining life for the facilities and/or equipment, wear and tear, corrosion, erosion, and so forth. The analysis may additionally include operations research (OR) analysis used to provide for more efficient parts replacement schedules, maintenance schedules, equipment utilization schedules, personnel usage schedules, new inspection schedules, and so on. The analysis (block **156**) may then be reported (block **158**), resulting in one or more reports **159**, including reports created in or by using the cloud **24**, detailing the inspection and analysis performed and results obtained. The reports **159**

may then be shared (block **160**), for example, by using the cloud **24**, the mobile device **22**, and other techniques, such as workflow sharing techniques. In one embodiment, the process **150** may be iterative, thus, the process **150** may iterate back to planning (block **152**) after the sharing (block **160**) of the reports **159**. By providing for embodiments useful in using the devices (e.g., **12**, **14**, **16**, **22**, **92**, **94**, **96**) described herein to plan, inspect, analyze, report, and share data, the techniques described herein may enable a more efficient inspection and maintenance of the facilities **20**, **106** and the equipment **18**, **104**. Indeed, the transfer of multiple categories of data may be provided, as described in more detail below with respect to FIG. **6**.

FIG. **6** is a data flow diagram depicting an embodiment of the flow of various data categories originating from the NDT inspection devices **12** (e.g., devices **14**, **16**, **92**, **94**, **96**) and transmitted to the mobile device **22** and/or the cloud **24**. As mentioned above, the NDT inspection devices **12** may use a wireless conduit **162** to transmit the data. In one embodiment, the wireless conduit **112** may include WiFi (e.g., 802.11X), cellular conduits (e.g., HSPA, HSPA+, LTE, WiMax), NFC, Bluetooth, PANs, and the like. The wireless conduit **162** may use a variety of communication protocols, such as TCP/IP, UDP, SCTP, socket layers, and so on. In certain embodiments, the wireless conduit **162** may include secure layers, such as SSL, VPN layers, encrypted layers, challenge key authentication layers, token authentication layers, and so on. Accordingly, an authorization data **164** may be used to provide any number of authorization or login information suitable to pair or otherwise authenticate the NDT inspection device **12** to the mobile device **22** and/or the cloud **24**. Additionally, the wireless conduit **162** may dynamically compress data, depending on, for example, currently available bandwidth and latency. The mobile device **22** may then uncompress and display the data. Compression/decompression techniques may include H.261, H.263, H.264, moving picture experts group (MPEG), MPEG-1, MPEG-2, MPEG-3, MPEG-4, DivX, and so on.

In certain modalities (e.g., visual modalities), images and video may be communicated by using certain of the NDT inspection devices **12**. Other modalities may also send video, sensor data, and so on, related to or included in their respective screens. The NDT inspection device **12** may, in addition to capturing images, overlay certain data onto the image, resulting in a more informative view. For example, a borescope tip map may be overlaid on the video, showing an approximation of the disposition of a borescope tip during insertion so as to guide the operator **26** to more accurately position the borescope camera **126**. The overlay tip map may include a grid having four quadrants, and the tip **136** disposition may be displayed as dot in any portion or position inside of the four quadrants. A variety of overlays may be provided, as described in more detail below, including measurement overlays, menu overlays, annotation overlays, and object identification overlays. The image and video data, such as the video **84**, may then be displayed, with the overlays generally displayed on top of the image and video data.

In one embodiment, the overlays, image, and video data may be "screen scrapped" from the screen **135** and communicated as screen scrapping data **166**. The screen scrapping data **166** may then be displayed on the mobile device **22** and other display devices communicatively coupled to the cloud **24**. Advantageously, the screen scrapping data **166** may be more easily displayed. Indeed, because pixels may include both the image or video and overlays in the same frame, the

mobile device **22** may simply display the aforementioned pixels. However, providing the screen scraping data may merge both the images with the overlays, and it may be beneficial to separate the two (or more) data streams. For example, the separate data streams (e.g., image or video stream, overlay stream) may be transmitted approximately simultaneously, thus providing for faster data communications. Additionally, the data streams may be analyzed separately, thus improving data inspection and analysis.

Accordingly, in one embodiment, the image data and overlays may be separated into two or more data streams **168** and **170**. The data stream **168** may include only overlays, while the data stream **170** may include images or video. In one embodiment, the images or video **170** may be synchronized with the overlays **168** by using a synchronization signal **172**. For example, the synchronization signal may include timing data suitable to match a frame of the data stream **170** with one or more data items included in the overlay stream **168**. In yet another embodiment, no synchronization data **172** data may be used. Instead, each frame or image **170** may include a unique ID, and this unique ID may be matched to one or more of the overlay data **168** and used to display the overlay data **168** and the image data **170** together.

The overlay data **168** may include a tip map overlay. For example, a grid having four squares (e.g., quadrant grid) may be displayed, along with a dot or circle representing a tip **136** position. This tip map may thus represent how the tip **136** is being inserted inside of an object. A first quadrant (top right) may represent the tip **136** being inserted into a top right corner looking down axially into the object, a second quadrant (top left) may represent the tip **136** being inserted into a left right corner looking down axially, a third quadrant (bottom left) may represent the tip **136** being inserted into a bottom left corner, and a fourth quadrant (bottom right) may represent the tip **136** being inserted into a bottom right corner. Accordingly, the borescope operator **26** may more easily guide insertion of the tip **136**.

The overlay data **168** may also include measurement overlays. For example, measurement such as length, point to line, depth, area, multi-segment line, distance, skew, and circle gauge may be provided by enabling the user to overlay one or more cursor crosses (e.g., "+") on top of an image. In one embodiment a stereo probe measurement tip **136**, or a shadow probe measurement tip **136** may be provided, suitable for measurements inside of objects, including stereoscopic measurements and/or by projecting a shadow onto an object. By placing a plurality of cursor icons (e.g., cursor crosses) over an image, the measurements may be derived using stereoscopic techniques. For example, placing two cursors icons may provide for a linear point-to-point measurement (e.g., length). Placing three cursor icons may provide for a perpendicular distance from a point to a line (e.g., point to line). Placing four cursor icons may provide for a perpendicular distance between a surface (derived by using three cursors) and a point (the fourth cursor) above or below the surface (e.g., depth). Placing three or more cursors around a feature or defect may then give an approximate area of the surface contained inside the cursors. Placing three or more cursors may also enable a length of a multi-segment line following each cursor.

Likewise, by projecting a shadow, the measurements may be derived based on illumination and resulting shadows. Accordingly, by positioning the shadow across the measurement area, then placing two cursors as close as possible to the shadow at furthestmost points of a desired measurement may result in the derivation of the distance between the

points. Placing the shadow across the measurement area, and then placing cursors at edges (e.g., illuminated edges) of the desired measurement area approximately to the center of a horizontal shadow may result in a skew measurement, otherwise defined as a linear (point-to-point) measurement on a surface that is not perpendicular to the probe **14** view. This may be useful when a vertical shadow is not obtainable.

Similarly, positioning a shadow across the measurement area, and then placing one cursor on a raised surface and a second cursor on a recessed surface may result in the derivation of depth, or a distance between a surface and a point above or below the surface. Positioning the shadow near the measurement area, and then placing a circle (e.g., circle cursor of user selectable diameter, also referred to as circle gauge) close to the shadow and over a defect may then derive the approximate diameter, circumference, and/or area of the defect.

Overlay data **168** may also include annotation data. For example, text and graphics (e.g. arrow pointers, crosses, geometric shapes) may be overlaid on top of an image to annotate certain features, such as "surface crack." Additionally, audio may be captured by the NDT inspection device **12**, and provided as an audio overlay. For example, a voice annotation, sounds of the equipment undergoing inspection, and so on, may be overlaid on an image or video as audio. The overlay data **168** received by the mobile device **22** and/or cloud **24** may then be rendered by a variety of techniques. For example, HTML5 or other markup languages may be used to display the overlay data **168**. In one embodiment, the mobile device **22** and/or cloud **24** may provide for a first user interface different from a second user interface provided by the NDT device **12**. Accordingly, the overlay data **168** may be simplified and only send basic information. For example, in the case of the tip map, the overlay data **168** may simply include X and Y data relative to the location of the tip, and the first user interface may then use the X and Y data to visually display the tip on a grid.

Additionally sensor data **174** may be communicated. For example, data from the sensors **126**, **140**, and x-ray sensor data, eddy current sensor data, and the like may be communicated. In certain embodiments, the sensor data **174** may be synchronized with the overlay data **168**, for example, overlay tip maps may be displayed alongside with temperature information, pressure information, flow information, clearance, and so on. Likewise, the sensor data **174** may be displayed alongside the image or video data **170**.

In certain embodiments, force feedback or haptic feedback data **176** may be communicated. The force feedback data **176** may include, for example, data related to the borescope **14** tip **136** abutting or contacting against a structure, vibrations felt by the tip **136** or vibration sensors **126**, force related to flows, temperatures, clearances, pressures, and the like. The mobile device **22** may include, for example, a tactile layer having fluid-filled microchannels, which, based on the force feedback data **176**, may alter fluid pressure and/or redirect fluid in response. Indeed, the techniques describe herein, may provide for responses actuated by the mobile device **22** suitable for representing sensor data **174** and other data in the conduit **162** as tactile forces.

The NDT devices **12** may additionally communicate position data **178**. For example, the position data **178** may include locations of the NDT devices **12** in relation to equipment **18**, **104**, and/or facilities **20**, **106**. For example, techniques such as indoor GPS, RFID, triangulation (e.g., WiFi triangulation, radio triangulation) may be used to determine the position **178** of the devices **12**. Object data **180** may include data related to the object under inspection.

For example, the object data **180** may include identifying information (e.g., serial numbers), observations on equipment condition, annotations (textual annotations, voice annotations), and so on. Other types of data **182** may be used, including but not limited to menu-driven inspection data, which when used, provides a set of pre-defined “tags” that can be applied as text annotations and metadata. These tags may include location information (e.g., 1<sup>st</sup> stage HP compressor) or indications (e.g., foreign object damage) related to the object undergoing inspection. Other data **182** may additionally include remote file system data, in which the mobile device **22** may view and manipulate files and file constructs (e.g., folders, subfolders) of data located in the memory **25** of the NDT inspection device **12**. Accordingly, files may be transferred to the mobile device **22** and cloud **24**, edited and transferred back into the memory **25**. By communicating the data **164-182** to the mobile device **22** and the cloud **24**, the techniques described herein may enable a faster and more efficient process **150**. By communicating the data **164-182** to the mobile device **22** and the cloud **24**, the techniques described herein may enable a faster and more efficient process **150**. Indeed, the transfer of multiple categories of data may be provided, as described in more detail below with respect to FIGS. 7-10.

Turning now to FIG. 7, the figure is a data flow diagram illustrating an embodiment of the flow of various data categories originating from the mobile device **22**, devices inside the cloud **24**, and/or devices communicatively connected to the cloud **24** (e.g., computing system **29**) and directed, for example, towards the NDT inspection devices **12** (e.g., borescope **14**, PTZ camera **16**, eddy current inspection device **92**, ultrasonic flaw detector **94**, digital radiography device **96**). Such data may include control data suitable for controlling the NDT device. As described herein, the control of the NDT inspection devices **12** includes both control of positioning apparatus, such as the articulating section **122** of the borescope **14**, apparatus used to pan, tilt, and zoom the PTZ camera **16**, as well as the remote control of file systems in the NDT devices **12**, screen(s) included in the NDT devices **12**, and the setting of parameters used to operate or to configure the NDT devices **12**, as described in more detail below.

In the depicted embodiment, a wireless conduit **200** may be used to communicate the data (e.g. control data) to the NDT devices **12**. Similar to the conduit **162**, the wireless conduit, in certain embodiments, may include WiFi (e.g., 802.11X), cellular conduits (e.g., HSPA, HSPA+, LTE, WiMax), NFC, Bluetooth, PANs, and the like. The wireless conduit **162** may use a variety of communication protocols, such as TCP/IP, UDP, SCTP, socket layers, and so on. In certain embodiments, the wireless conduit **162** may include secure layers, such as SSL, VPN layers, encrypted layers, challenge key authentication layers, token authentication layers, and so on. It is to be noted that, in other embodiments, wired conduits may be used alternative to or in lieu of the wireless conduits **162, 200**.

Authorization data **202** may be communicated, and used, for example, in conjunction with the authorization data **164** to enable secure access to the NDT devices **12**. A variety of secure authentication techniques may be used, including but not limited to login/password combinations, maintaining a list of secure MAC addresses, challenge-response authentication between two or more of the devices **12, 22**, and cloud **24**, secure NFC authentication, using a third-party authentication server (e.g., by using certificate authentication, key exchange authentication), and so on.

Position control data **204** may additionally be communicated, useful to move or otherwise position components of the NDT devices **12**. Indeed, certain components of the NDT devices **12** may be physically moved remotely by using, for example, a virtual joystick described in more detail below with respect to FIG. 8. Any number of systems (e.g., mobile devices **22**, computing systems **29**, web-based virtual controllers), such as devices connected to the NDT devices **12** locally (e.g., WiFi, Bluetooth) and/or via the cloud **24**, may be used to remotely communicate the data **204** and used to remotely position components of the NDT devices **12**.

Advantageously, a variety of remote operations, training, and collaboration may be enabled. For example, an expert operator may train a new borescope operator on the job. The new borescope operator may hold the borescope **14** and observe while the expert operator controls the borescope **14** by using the mobile device **22**. The expert operator may then point out tip control techniques, relate what type of observations are correlative to corrosion, show how to make annotations, and so on. In other cases, the expert operator may be located at a different geographic location and may collaborate and/or train the new borescope operator by the use of VOIP, whiteboarding, and the like, or may use the mobile device **22** to perform a full inspection remotely. In another training example, the new borescope operator may be using the mobile device **22** and/or borescope **14**, and receive training from remote locations, such as web-based locations. For example, the screen **137** of the mobile device **22** may be portioned into multiple viewing areas (e.g., “splitscreens”) so that one viewing area shows borescope **14** images or video while a second viewing area shows a training video, and a third area shows an online equipment manual procured wirelessly. Indeed, the borescope **14** may receive data, including targeted multimedia inspection data from external sources (e.g., mobile device **22**, cloud **24**, computing system **29**).

Additionally, fine control data **206** may be communicated. For example, “jogging” data suitable for moving the borescope’s articulating section **122** and/or the PTZ camera **16** at smaller increments than the position control data **204**. More specifically, the fine control data **206** may include a step to move (e.g., 0.5 mm, between 0.05 mm and 1 cm or more), and a number of steps to move (e.g., 1, 2, 3, 4, 5 or more). Accordingly, components of the NDT device **12** may be more precisely disposed to better observe certain features undergoing inspection. The position control data **204** and fine control data **206** may be produced by virtual controllers or physical controllers communicatively connected to the NDT devices **12**.

Images, video, text, and/or audio data **208** may be additionally communicated. For example, the mobile device **22**, the cloud **24**, and/or devices coupled to the cloud (e.g., computing system **29**) may send images and/or video, as well as overlay annotations useful in illustrating to the borescope operator certain features to inspect further, along with audio detailing explanations of how to proceed with the inspection. In certain embodiments, the data **208** may be training data useful in detailing inspection procedures. In other embodiment, the data **208** may include data transmitted from experts, detailing instructions on how to more thoroughly inspect certain equipment. In yet another embodiment, the data **208** may include data sent through automated entities (e.g., expert systems, fuzzy logic systems, neural network systems, state vector machines) based on received data from FIG. 6 useful in directing and/or focusing the inspection after automatically analyzing the received data.

Configuration data **210** may also be communicated. For example data used to update file systems included in the NDT devices **12**, to reprogram the NDT devices **12**, to set parameters useful in operating the NDT devices **12**, and/or to reconfigure electronic components of the device **12** (e.g., flash upgrade) may be sent to the NDT inspection devices **12** remotely. Indeed, programming and parameter-setting may be done remotely, thus providing for techniques to more easily maintain the NDT devices up to date, and to improve device operations. It is to be understood that different NDT devices **12** may use different parameter sets. As a non-limiting example only, some parameters, e.g., used during operations of the NDT device **12** and useful to remote control the NDT devices **12** may include parameters for starting acquisition of data, stopping acquisition of data, saving a file, naming or renaming a file, adjusting a gain, adjusting a time base, compensating for lift off—zeroing signal during eddy current inspection, adjusting phase rotation, adjusting persistence, balancing a probe, adjusting gate (e.g., amplitude adjustment, position adjustment), adjusting color palette—soft gain, changing signal rectification, changing pulser filter, zooming in and out, adjusting a pulse width, adjusting a data filter (e.g., bandwidth), adjusting pulse repetition frequency, adjusting sweep angle start/stop, adjusting sweep angle increment, turning channels on/off, freezing data, clearing/erasing data, adjusting span, adjusting filters, changing spot positions, changing display types (e.g., spot display, timebase display, waterfall display), and/or changing channel views.

In one embodiment, client-server techniques, such as virtual network computing (VNC), remote desktop protocol (RDP), desktop sharing, among others, may be used to send configuration data **210** and receive data correlative with screen control of the NDT devices **12**. Likewise, remote file system control may be provided by using techniques such as secure file transfer protocol (ftp), ftp over secure shell (SSH), remote file sharing (RFS), and/or distributed file systems (e.g., using the cloud **24** to store and retrieve files through the NDT devices **12**). Files may be added, renamed, deleted, and/or updated. Likewise, file folders and other file storage structures may be similarly renamed, deleted, and/or updated.

Force feedback data **212** may additionally be communicated. For example, a more forceful push onto the mobile device's **22** touchscreen may translate into data **212** useful in moving the borescope's articulating section **122** more quickly. Likewise, a haptic controller may be coupled to the computing device **29** and provide the force feedback data. The more force applied, the faster the correlative movement of components such as the articulating section **122** of the borescope **14**. It is to be noted that force feedback data **212** may be provided by other devices, such as the physical joystick **131**, a virtual joystick described in more detail with respect to FIG. **8** below, haptic controllers wirelessly coupled to the NDT devices **12**, including controllers coupled through the cloud **24** or mobile device **22** (e.g., when the mobile device **22** is providing for WAP functionality). Other data **214** may include updated digital manuals or help manuals useful in operating the NDT devices **12**, manuals relating to the equipment (e.g., turbomachinery **18**, aircraft **54**) undergoing inspection, and so on. Accordingly, the wireless conduit **200** would be used to communicate and to change or otherwise modify NDT device **12** information, such as borescope-specific information including but not limited to measurement information (cursor placement, measurements, stereo matches), MDI information (current stage, asset information, reference material), current menu

selections, tip temperatures/pressures, tip orientation (tip map, artificial horizon), 3-dimensional phase measurement (3DPM) range indication, text annotation, and so on. Software control applications may render native graphics with touchscreen buttons or softkey labels as described in more detail below, and if appropriate, accept user input. Hard physical buttons with either fixed or dynamic functionality can also be used to accept input. It is to be noted that the NDT device **12** may be controlled by a first entity (or more than one remote entities) at the same time as the NDT device **12** is used by a second entity. Indeed, the control embodiments described herein enable multiple parties to control the device at the same time, including multiple remote parties.

FIG. **8** is illustrative of an embodiment of a screen view **220** useful in remote controlling the NDT devices **12**. The screen view **220** may be included in the mobile device **22** (e.g., tablet, cell phone, notebook touchscreen). The screen view **220** may be implemented by using non-transitory computer-readable instructions stored, for example, in the memory **25** of the mobile device **22**. In the depicted embodiment, an interface bar **222** may be activated, for example, by “swiping” a tab control **224**. Once activated, the tab control **224** may change icons, from a right arrow icon **226** to a left arrow icon **228**, denoting preferred swiping direction.

In a section **230** of the interface bar **222**, a plurality of virtual controls may be displayed. The depicted virtual controls include a virtual joystick **232**, a virtual control pad **234**, a slider **236**, and a tip map **238** showing a position **239** of the tip **136**. Other virtual controls may be provided, as described in more detail below with respect to FIG. **9**. The virtual controls may be displayed on a screen **240** of a control software application executable, for example, by the processor **23** of the mobile device **22**, and used to control one or more components of the NDT devices **12**. In the depicted example, a finger **242** is used to move the virtual joystick **232** into a desired location. Indeed, all of the virtual controls **234**, **236**, **238** may be similarly disposed onto any area of the screen **240**. The virtual controls **232**, **234**, **236**, **238** are resizable. Additionally, techniques such as “pinch-to-zoom,” may be used to resize the controls **232**, **234**, **236**, **238** to a desired size.

Once the virtual controls are positioned into desired locations of the screen **240**, a section **244** of the screen may store a customized template **246** that include the saved positions and sizes for the screen **240** controls. Other templates **248** may be provided, for example, via the cloud **24**, from a variety of sources, including the manufacturer for the NDT devices **12**, equipment **18**, **54** manufacturers, shops that service the equipment **18**, **54**, software vendors, and the like. The templates **248** may store a plurality of virtual controls and certain placement and sizes originally provided by the template **248**. In certain embodiments, the template(s) **248** may be downloaded automatically based on the type of NDT device **12** selected (e.g., **14**, **16**, **92**, **94**, **96**), the location of the NDT device **12**, such as proximity to a specific model and/or serial number of the equipment **18**, **54**. Indeed, control templates **248** specific to certain equipment and/or facilities may be automatically downloaded based on the selected NDT device **12** and/or proximity of the NDT device **12** to the aforementioned equipment or facility.

In the depicted example of the screen **240**, the virtual joystick **232** may be used to control the articulating section **122** of the borescope **14**. The tip map **238** may then be used to show a location of the tip **136** when disposed inside of the equipment undergoing inspection. Lights **128**, **138** may be controlled by using the slider **236**, and a temperature may be displayed by using a text control **250**. The entirety of the

screen 240, or a portion of the screen 240, may then be used to display an image or video captured, for example, by using the borescope camera 126 or the camera 16. By providing for dynamic, reconfigurable screens 240, the techniques described herein may enable a more efficient and thorough inspection 154.

Turning to FIG. 9, the figure depicts a non-exhaustive list of embodiments of virtual controls that may be disposed on the screen 240 of FIG. 8. For example, a button control 254 may be used to activate or deactivate components (hardware or software components) of the NDT device 12 and/or mobile device 22. A radio button 256 may be used to select or deselect components of the NDT device 12 and/or mobile device 22. The textbox control 250, also shown in FIG. 8, may be used to display any number of textual data (e.g., sensor data, annotations, notes, time/date, parameter settings, and so on). A keyboard control 260 may be used to display a virtual keyboard suitable for the typing of data. A checkbox control 262 may be used to check or uncheck features (hardware or software features) of the NDT device 12 and/or mobile device 22. A menu control 264 may be used to display MDI data and other menu related data. A label control 266 may be used to display a static text or graphic label, as desired. A tip map control 268 may be used to display a current tip 136 position.

Likewise, the slider control 236 (also shown in FIG. 8) may be used to adjust any number of hardware or software components, parameters, and so on by “sliding” to a desired level. A jog control 272 may be used to “jog” the fine control data 206, or to set properties associated with the fine control data 206 (e.g., steps to move, number of steps to move). A voice control 274 may be used to provide voice commands, voice annotations, VOIP conversations, and so on. An arrow control 276 may be used to point to image or video features. The joystick 232 and control pad 234 (also shown in FIG. 8) may be used to manipulate certain components (e.g., articulating section 122 of the borescope 14) to dispose the components into a desired position.

Similarly, a grouping control 278 may be used to “lasso” or group components in order to move the components, delete the components from the screen 240, and so on. A cross 280 cursor may be used to mark or otherwise indicate certain locations on the screen 240 correlative with features of an image or video. A measure component 282 may then use, for example, the one or more crosses 280 to derive measurements, such as the stereoscopic and/or shadow measurements described above with respect to FIG. 6. Zoom controls 284 and unzoom controls 286 may be used to zoom into or out of certain portions (or all) of the screen 240. By providing for resizable, repositionable virtual controls 252, the techniques described herein may enable a more efficient use of space of the screen 240, and provide for customizable, dynamic screens 240.

Some of the controls, such as the virtual joystick 232, may be disposed in a variety of orientations as shown in an embodiment illustrated in FIG. 10. In the depicted embodiment, the virtual joystick 232 is shown in four different orientations 300, 302, 304, and 306. More specifically, the orientation 300 positions the joystick 232 parallel to the Y axis with a joystick head 307 in an “up” position, the orientation 302 positions the joystick 232 parallel to the X axis with the joystick head 307 in a “left” position, the orientation 304 positions the joystick 232 parallel to the Y axis with the joystick head 307 in a “down” position, and the orientation 306 positions the joystick 232 parallel to the X axis with the joystick head 307 in a “right” position. Other orientations may be chosen to position the virtual joystick

232, for example, orientations parallel to the Z-axis, or at any angle with respect to the XY plane, XZ plane, and or YZ plane. Additionally, the virtual joystick 232 and/or virtual control pad 234 may be adjusted to vary a sensitivity of manipulation. That is, when using the touchscreen 135, 137, it may be useful to allow user control of the sensitivity of the joystick, such that the user may configure what level of touch or movement is desired to “move” the virtual control (e.g., 232, 234) a given amount. Accordingly, the joystick 232 may provide for a more flexible interface useful in controlling a variety of NDT devices 12.

In some embodiments, such as the embodiment depicted in FIG. 11, the virtual controls shown in FIG. 9 may be displayed as opaque or translucent visualizations. For example, the control pad 234 is shown as having a transparent body with certain features 308 visualized in outline form. By providing for opaque or translucent visualizations, images or video displayed underneath the controls of FIG. 9 may be more easily viewed, and the inspection 154 may be more easily performed.

In some cases, it may be desirable to control to the NDT devices 12 by using gesture control in lieu of the joystick 232 or the control pad 234, or additional to the controls 232, 234. Accordingly, screen 240 space may be maximized. FIG. 12 depicts a non-inclusive example of embodiments of a plurality of gestures that may be used to control the NDT devices 12. A single digit or finger gesture 390 may be used to define a vector AB with a starting point A and an ending point B. The direction of the vector AB may then be used to move desired components along the vector AB, and the length of the vector AB may provide for the length of the movement. Pinch-to-zoom gestures 392 may also be used. For example, spreading two fingers outwardly along a line 394 may zoom certain portions of the screen 240. Likewise moving two fingers inwardly along a line 396 may unzoom certain portions of the screen 240.

Rotational gestures 398 may also be provided. For example, rotating one or two fingers to follow arcs 400 and 403 may correlative rotate desired components of the NDT device 12. Multi-gesture control 404 is also provided. For example, using three fingers or more and swiping in directions 406, 408 may shift the screen 240 to display an entirely new screen, such as a screen containing a different set of virtual controls or a different software application. Force feedback gestures 410 or techniques may additionally be used. For example, pressing a finger with a force 412 may result in a movement of a desired component correlative to the force 412. The stronger the force 412, the faster the movement. Likewise, the force 412 may be used, such as when tapping on the screen 240, to provide for jogging or fine control of desired components.

In certain embodiments, the mobile device 22 may include accelerometers, gyroscopes, and other sensors useful in deriving motion and/or orientation of the mobile device 22. Accordingly, as depicted in FIG. 13, moving and/or changing orientations of the mobile device 22 may be used to control features of the NDT devices 12, such as the articulating section 122 of the borescope 14. Indeed, by virtually “driving” the mobile device 22 it may be possible to remotely control the NDT devices 12. Six degrees of freedom of movement may be derived with respect to the axes 133, such as movements perpendicular to the X, Y, Z axes 133 (e.g., translation in the axes 133), rotations about the X, Y, Z axes 133, and/or rotative movements with respect to each of the axes 133 (e.g., pitch, yaw, roll). The movements may be derived and subsequently mapped to correlative movements of the NDT devices 12, such as movements

of the articulating section **122** of the borescope **14**, and pan/tilt/zoom movements of the PTZ camera **16**. By providing for the virtual driving of the mobile device **22**, it may be possible to further maximize screen **240** space, for example, by not including the joystick **232** and the control pad **234**.

Voice commands may be provided, additional or alternative to the aforementioned virtual controls. For example, voice may be processed by the NDT devices **12**, by the mobile device **22**, by the cloud **24**, by devices coupled to the cloud **24** (e.g., device **29**), or by a combination thereof, to parse voice into useful commands. All aspects of the NDT devices **12** may be controlled using voice, including positioning components of the NDT devices **12** (e.g., articulating section **122** of the borescope **12**), recording images and video, providing for annotations, controlling parameters as described above, and so on.

Accordingly, the user **28** may view live video from the borescope **14** on the mobile device **22**, and may articulate the borescope tip **136** by swiping on the screen or tapping on the edges to indicate a jog direction. The user **28** may additionally or alternatively view live video from the borescope **14** on the mobile device **22**, and may summon the virtual joystick **232** or control pad **234** to the screen **240** on the mobile device **22**. The virtual joystick **232** or control pad **234** may then be used to articulate the borescope **14**. Likewise, the user **28** may view live video on the mobile screen **240**, find a region of interest, and command the borescope **14** to take a snapshot (still image). Similarly, the user **28** may view live video on the mobile screen **240**, find a region of interest, and command the borescope **14** to take a snapshot (still image), and then perform a measurement (e.g., by using cursor placements on the image, including 3DPM captures, shadow captures, stereo captures). The user **2** may also view live video on the mobile screen **249**, and then command a view of the borescope's file system in order to view and transfer previously captured still images and videos to the mobile device **22**, to the cloud **24** and to systems (e.g., computing system **29**) coupled to the cloud **24**. The mobile device **22** can command viewing and/or execution of any of the borescope's menus. Indeed, all functions that may be done by the operator **26** may be done remotely by the operator **28** using the mobile device **22** and/or computing system **29**. Indeed, the entire screen of the NDT device **12**, such as the screen **135**, may be recreated in the mobile device's screen **240** and used to control the NDT device.

Technical effects of the invention include enabling remote control of the NDT devices **12**. The remote control may include positional control of mechanical components, remote control of the file systems included in the NDT devices **12**, remote control of parameters of the NDT devices **12**, including parameters used for operations of the NDT devices **12** and parameters used to configure the NDT devices **12**. Further, the NDT devices **12** may be reprogrammed remotely. A variety of virtual controls may be provided and used for remote control, including virtual controllers (e.g., joystick, pad), gesture control, motion control, and voice commands.

This written description uses examples to disclose the invention, including the best mode, and also to enable any person skilled in the art to practice the invention, including making and using any devices or systems and performing any incorporated methods. The patentable scope of the invention is defined by the claims, and may include other examples that occur to those skilled in the art. Such other examples are intended to be within the scope of the claims

if they have structural elements that do not differ from the literal language of the claims, or if they include equivalent structural elements with insubstantial differences from the literal languages of the claims.

The invention claimed is:

1. A system comprising:

A handheld non-destructive testing (NDT) device comprising:

a handheld borescope comprising an articulating section connected to a head end section; a display screen, a processor and;

a wireless system configured to receive a control data from an external system, wherein the NDT device is configured to transform the control data via the processor into articulation commands configured to control the articulation section included in the NDT device so as to reposition the head end section, wherein the head end section comprises a sensor, a camera, or a combination thereof, disposed in the head end section, and wherein the NDT device is configured to capture an image, a measurement, or a combination thereof, after the reposition.

2. The system of claim 1, wherein the NDT device is configured to use the control data to apply a jogging signal to the component, and wherein the jogging signal comprises a jogging step and a jogging number of steps used to move the component.

3. The system of claim 2, wherein the external system comprises a display configured to display the position of the tip in a tip map and wherein the display screen and the display both simultaneously display the position of the tip in the tip map.

4. The system of claim 1, wherein external system comprises a tablet having a touchscreen configured to display an image provided via the camera disposed in the head end section and a tablet processor, and wherein the tablet processor is configured to transform touch gestures on the touchscreen into the control data.

5. The system of claim 1, wherein the control data comprises a gesture control data configured to use at least one digit or a stylus to define a gesture.

6. The system of claim 1, wherein the NDT device comprises a physical control, and wherein the control data is used to replace the physical control.

7. The system of claim 1, wherein the control data comprises a virtual control data derived by using a virtual control.

8. The system of claim 7, wherein the virtual control is displayed on a touchscreen included in the external system and comprises a virtual joystick, a virtual control pad, or a combination thereof, and wherein the control data is derived by manipulating the virtual joystick, the virtual control pad, or the combination thereof, by using the touchscreen included in the external device.

9. The system of claim 1, wherein the external system comprises a physical joystick, a physical control pad, or a combination thereof, communicatively coupled to the NDT device by using the wireless system.

10. The system of claim 1, wherein the external system comprises a mobile device, a computing system, or a combination thereof, communicatively coupled to the NDT device by using the wireless system.

11. The system of claim 1, wherein the wireless system is configured to communicate with the external system by using a cloud computing network.



## 21

12. A non-transitory computer readable medium comprising executable instructions which, when executed by a processor, cause the processor to:

wirelessly receive a control data via a non-destructive testing (NDT) device, wherein the control data is wirelessly transmitted from an external system, the NDT device comprising a handheld borescope comprising an articulating section connected to a head end section; a display screen, and a processor;

transform the control data via the processor into articulation commands configured to control the articulation section included in the NDT device so as to reposition the head end section, wherein the head end section comprises a sensor, a camera, or a combination thereof, disposed in the head end section; and

capture an image, a measurement, or a combination thereof, via the NDT device, after the reposition.

13. The non-transitory computer readable medium of claim 12, comprising instructions configured to:

receive images, video, audio data, or a combination thereof by using the NDT device, and wherein the NDT device is configured to display the images or video the display screen of the NDT device and to play the audio data in a speaker component of the NDT device, in an earphone port component of the NDT device, or in a combination thereof.

14. The non-transitory computer readable medium of claim 12, wherein the processor is configured to transform the control data into a parameter of the NDT device that reconfigures observations of the NDT device, a file system command of the NDT device, or a combination thereof.

15. The non-transitory computer readable medium of claim 12, comprising instructions configured to display a virtual joystick, a virtual control pad, or a combination thereof, and to send the control data based on touchscreen manipulation of the virtual joystick, the virtual control pad, or the combination thereof.

## 22

16. The non-transitory computer readable medium of claim 12, comprising instructions configured to use touchscreen gesture control, voice commands, or a combination thereof, to produce the control data.

17. The non-transitory computer readable medium of claim 12, comprising instructions configured to use a virtual button, a radio button, a text box, a virtual keyboard, a check box, a menu, a slider, a jog control, cursor, a measure control, a zoom control, a unzoom control, or the combination thereof, to produce the control data.

18. A method comprising:

wirelessly receiving control data via a non-destructive testing (NDT) device, wherein the control data is wirelessly transmitted from an external system, the NDT device comprising a handheld borescope comprising an articulating section connected to a head end section; a display screen, and a processor;

transforming, via the processor, the control data articulation commands configured to control the articulation section included in the NDT device so as to reposition the head end section, wherein the head end section comprises a sensor, a camera, or a combination thereof, disposed in the head end section; and

capturing an image, a measurement, or a combination thereof, via the NDT device, after the reposition.

19. The method of claim 18, comprising using a tablet having a touchscreen displaying an image provided via the camera disposed in the head end section and a tablet processor, and wherein the tablet processor is configured to transform touch gestures on the touchscreen into the control data.

20. The system of claim 18, comprising using a physical joystick or a physical control pad communicatively coupled to the NDT device to transmit the control data.

\* \* \* \* \*