



US009463476B2

(12) **United States Patent**
Greiner-Perth et al.

(10) **Patent No.:** **US 9,463,476 B2**

(45) **Date of Patent:** **Oct. 11, 2016**

(54) **DISPENSER FOR DISPENSING LIQUIDS**

(56) **References Cited**

(71) Applicants: **Juergen Greiner-Perth**, Gottmadingen (DE); **Nicole Schwarz**, Radolfzell (DE)

(72) Inventors: **Juergen Greiner-Perth**, Gottmadingen (DE); **Nicole Schwarz**, Radolfzell (DE)

(73) Assignee: **APTAR RADOLFZELL GMBH**, Radolfzell (DE)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 118 days.

(21) Appl. No.: **14/180,452**

(22) Filed: **Feb. 14, 2014**

(65) **Prior Publication Data**
US 2014/0231540 A1 Aug. 21, 2014

(30) **Foreign Application Priority Data**
Feb. 16, 2013 (DE) 10 2013 202 531

(51) **Int. Cl.**
B05B 1/14 (2006.01)
B05B 1/18 (2006.01)
B05B 11/00 (2006.01)

(52) **U.S. Cl.**
CPC . **B05B 1/14** (2013.01); **B05B 1/18** (2013.01);
B05B 11/0064 (2013.01); **B05B 11/0067**
(2013.01)

(58) **Field of Classification Search**
CPC B05B 1/14; B05B 1/185; B05B 11/0064;
B05B 11/0067; B05B 1/18
USPC 239/461-524, 548-568
See application file for complete search history.

U.S. PATENT DOCUMENTS

2,017,467 A	10/1935	Loomis	
4,884,750 A *	12/1989	Werding B05B 1/3006 137/517
5,271,533 A	12/1993	Joulia	
6,053,372 A	4/2000	Abedi	
6,196,219 B1	3/2001	Hess et al.	
6,338,442 B1 *	1/2002	De Laforcade B65D 83/207 222/402.21
6,341,735 B1 *	1/2002	Baudin B05B 1/323 137/845

(Continued)

FOREIGN PATENT DOCUMENTS

DE	201 02 271 U1	6/2001
EP	0 516 498 A1	12/1992

(Continued)

OTHER PUBLICATIONS

Office Action of European Patent Office issued in European Application No. EP 14 15 3198 with English translation of category documents dated Oct. 16, 2014 (14 pages).


(Continued)

Primary Examiner — Arthur O Hall
Assistant Examiner — Juan C Barrera
(74) *Attorney, Agent, or Firm* — Flynn, Thiel, Boutell & Tanis, P.C.

(57) **ABSTRACT**

Dispenser with a liquid storage unit, a dispensing head with a perforated plate component which has at least 25 dispensing openings in a dispensing opening region, with a pre-chamber connected upstream of the dispensing openings of the perforated plate component and from which the dispensing openings are supplied, and a connecting channel which connects the liquid storage unit to the pre-chamber. The perforated plate component is fastened on the dispensing head in an edge region and the dispensing opening region is pressed into a curved form by means of a curvature body which is arranged in the pre-chamber and acts with force upon the perforated plate.

13 Claims, 9 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

6,695,171 B2 * 2/2004 Walters B05B 11/3059
 222/153.13
 7,481,382 B2 * 1/2009 Christ B05B 1/14
 239/333
 7,703,634 B2 4/2010 Roehrig
 7,748,647 B2 * 7/2010 Clerget B05B 1/14
 222/402.13
 8,006,870 B2 8/2011 Stadelhofer et al.
 8,827,124 B2 9/2014 Painchaud et al.
 2006/0060591 A1 3/2006 Rohrig
 2006/0213408 A1 9/2006 Christ
 2007/0210114 A1 9/2007 Stadelhofer et al.
 2007/0210115 A1 9/2007 Stadelhofer et al.
 2007/0210121 A1 9/2007 Stadelhofer et al.
 2008/0006719 A1 1/2008 Clerget et al.
 2012/0305599 A1 12/2012 Painchaud et al.

FOREIGN PATENT DOCUMENTS





EP 0 923 957 A1 6/1999

EP 1 052 191 A1 11/2000
 EP 1 520 797 A1 4/2005
 EP 1 637 232 A1 3/2006
 EP 1 698 399 A1 9/2006
 EP 1 834 703 A2 9/2007
 EP 1 878 507 A2 1/2008
 FR 2 524 348 10/1983
 WO WO 2004/065247 A1 8/2004
 WO WO 2011/030063 A1 3/2011
 WO WO 2012/074045 A1 6/2012

OTHER PUBLICATIONS

Search Report of European Patent Office issued in European Application No. 14153198.8 with English translation of category documents dated Jun. 24, 2014 (8 pages).
 German Office Action of German Patent Office issued in German Application No. 10 2013 202 531.9 dated Jul. 8, 2013 (5 pages).

* cited by examiner






Fig. 2a




Fig. 2b




Fig. 3a

Fig. 3b




Fig. 4




Fig. 5a




Fig. 5b




Fig. 5c






Fig. 6a


630a:




630b:




630c:




630d:




630e:




630f:



630g:



630h:



630i:




Fig. 6b




Fig. 6c




Fig. 7a




Fig. 7b

Fig. 7c




Fig. 8a




Fig. 8b

DISPENSER FOR DISPENSING LIQUIDS**CROSS-REFERENCE TO RELATED APPLICATION**

This application claims the priority of German Application No. 10 2013 202 531.9, filed on Feb. 16, 2013, the disclosure of which is hereby incorporated by reference in its entirety into this application.

FIELD AND BACKGROUND OF THE INVENTION

The invention relates to a dispenser for dispensing liquids, said dispenser having a liquid storage unit, a dispensing head with a perforated plate component which has at least 25 dispensing openings in a dispensing opening region, a pre-chamber which is connected upstream of the dispensing openings of the perforated plate component and from which the dispensing openings are supplied and a connecting channel which connects the liquid storage unit to the pre-chamber.

The use of perforated plates for dispensing liquids is known in particular from the area of such dispensers which have a vibration device by means of which liquid is pressurized in a pulsed manner in a dosing chamber and, as a result, is pressed through the dispensing openings. The result of such dispensing is a fine mist. A dispenser with such a perforated plate is known, for example, from EP 0 923 957 A1. Although the measures according to the invention which are proposed within the framework of this document are basically also usable in the case of such a realization of dispensers, the invention does relate in particular to dispensers which are not provided with electric actuators such as vibration devices, but instead obtain the liquid pressure to generate the dispensing either as a result of bringing in mechanical energy during the actuation or, however, from the pressurization of the liquid in the liquid storage unit which is already present at delivery.

SUMMARY OF THE INVENTION

It is the object of the invention, with regard to dispensers, in particular with regard to dispensers that are not electrically operated, to make it possible to influence the dispensing characteristics thereof in an advantageous manner, the intention being, in particular, to enable dispensers with different dispensing characteristics by way of a comparatively large number of matching components.

According to a first aspect of the invention, this is achieved in that in the case of a dispenser of the type mentioned in the introduction, the dispensing opening region is fastened on the dispensing head or a housing component in an edge region and is pressed into a curved form by means of a curvature body which is arranged in the pre-chamber and acts with force upon the dispensing opening region.

In the case of a dispenser according to the invention, there is provided a liquid storage unit in which the liquid is present before the dispensing. In this case, the liquid, which is preferably a cosmetic or pharmaceutical liquid, can be present unpressurized, in this case part of the dispenser being a pumping device which enables pressurization to generate the desired dispensing. As an alternative to this, liquid which is already pressurized and which can be output to the surrounding area by opening an outlet valve can also be present in the liquid storage unit. The liquid is output

through a dispensing head which includes the named perforated plate component which, in turn, has the dispensing openings. In this case, this is in particular preferably a plastics material component which can consist, for example, of polypropylene (PP), polyethylene (PE), polyoxymethylene (POM), polybuteneterephthalate (PBT) or cycloolefin copolymer (COC). The at least 25 dispensing openings are provided in said component, which is preferably produced using the injection moulding method and which has in particular preferably a thickness of between 0.1 mm and 1.5 mm, in particular of between 0.2 mm and 0.8 mm. In particular, there can preferably be a higher number of dispensing openings, in particular preferably more than 50 dispensing openings. The perforated plate component is fastened on the edge of a housing of the dispensing head or can also be realized integrally with the same. The dispensing opening region of the perforated plate component is preferably flat in the non-mounted state of said component. In the installed state, in contrast, it is curved, this being achieved in that it is pressed into the curved form by means of a curvature body which is arranged in the pre-chamber or defines the pre-chamber.

It is consequently provided in the case of said realization according to the invention that the perforated plate component and in particular the dispensing opening region thereof is deformed in the mounted state in relation to the non-mounted state and that for this purpose force is applied from the pre-chamber.

The outward curvature allows for the creation of a diverging alignment of the dispensing jet which consists of individual jets. This is expedient for a plurality of applications, thus, for example, in order to be able to distribute the liquid over a large area, for example on the skin of a user. The diverging dispensing characteristics, however, can also be advantageous for special fields of application where a multitude of areas are to be acted upon with liquid in a targeted manner, such as, for example, in the event of a throat spray dispenser which is to be able to reach rear throat areas of the patient with liquid past on the left and right of the uvula of a patient.

The development of the dispenser according to the invention with a deformed dispensing opening region in the mounted state in relation to the non-mounted state also allows, in particular, proceeding from identically designed non-deformed perforated plate components, for adaptation to special fields of application to be undertaken from case to case by influencing, among other things, the degree of curvature.

This can be achieved, for example, by utilizing different curvature bodies. As an alternative to this, the relative arrangement of the curvature body and of the perforated plate component can also be developed variably in the mounted state. In the case of a realization which is particularly advantageous in this respect, it is provided that the perforated plate component and the curvature body are adapted to one another and, where applicable, to a housing of the dispensing head in such a manner that they allow for a variable relative position of assembly of this type. Thus, for example, the curvature body or the perforated plate component could be fastened in one of several discrete positions on the other component or on the housing of the dispensing head. A stepless possibility for the variable spacing can also be provided as an alternative to this, for example by the perforated plate component or the curvature body being realized so as to be fixed in a force-fitting manner on the other component or on the housing of the dispensing head.

Although it is advantageous for adapting the dispensing characteristics of a dispensing head according to the invention if the curvature body is provided as a separate component to a housing of the dispensing head, the invention also includes other developments where a housing, which forms, at least in portions, outside faces of the dispensing head, is at the same time integrally connected to the curvature body or the inside body.

The named adjustability can, but does not have to, be limited to the time of production, in particular of assembly. A realization where the possibility of the relative displacement of the perforated plate component, in particular of the edge region thereof, on the one hand, and of the curvature body, on the other hand, is possible for the user or patient, can also be conceivable and, depending on the purpose of the application, advantageous. Thus, for example, a curvature body which is displaceable by means of a thread could allow for the degree of curvature of the dispensing opening region to be adjusted from case to case.

Along with the possibility of a realization where the perforated plate component is realized in a planar manner in the dispensing opening region pointing towards the pre-chamber and is deformed as a result of a curvature body which, in turn, protrudes or is curved, there is principally also the possibility of providing even on the inside surface in the dispensing opening region an elevation which points in the direction of the curvature body and in the mounted state brings about the curvature of the dispensing opening region. Such a curvature spin can be realized in production in a simple manner with a variable length such that at little expense it is possible to produce perforated plate components which do not differ from one another up to the extension of the elevation/of the curvature spin.

According to a further aspect of the invention which is realized preferably together with the aspects of the invention already named, it is possible to provide in the inside of the dispensing opening region, that is in the region of the pre-chamber, a cover body which has at least one closing face, at least one of the dispensing openings being closable or closed as a result of the at least one closing face abutting against an inside surface of the dispensing opening region.

With regard to its particular function, said named body is called a cover body in this context. However, it can be identical to the already-described curvature body where the aforementioned features of the invention are realized.

The characteristic according to said aspect of the invention is that at least when no pressurized liquid is present in the pre-chamber, at least some of the dispensing openings are closed by the cover body.

In this case, said closing of at least one dispensing opening can be a permanent state. This means that the dispensing opening remains closed irrespective of the liquid pressure in the pre-chamber and consequently when the dispenser is used correctly the dispensing opening will never be traversed by liquid. Other dispensing openings, in contrast, are not closed by closed openings and consequently are provided for the actual dispensing of the liquid.

The permanent partial closing of dispensing openings allows identically designed perforated plate components to be used for different application purposes, adapted from case to case, where different spray patterns are provided. Thus, for example, a cover body could be realized in such a manner that it keeps the dispensing openings open in only two regions of the dispensing opening region that are spaced apart from one another, whilst it closes the other ones. Consequently, it could be possible to generate two separate jets or jet bundles which are dispensed in a diverging manner

and consequently, for example, are really suitable for the above-mentioned purpose of a throat spray dispenser.

Above all, however, the permanent closing of dispensing openings allows the volume flow to be dispensed to be adapted case by case. Thus, with components of a dispenser or at least of the dispensing head that are unchanged for the rest, depending on the liquid used or the intended area of application, it is possible to generate different liquid flows.

Along with the possibility of closing dispensing openings permanently by means of the cover body by the cover body abutting against the inside surface of the perforated plate in the region of the dispensing opening in question irrespective of the liquid pressure during the dispensing operation, it is also possible to develop the cover body and to adapt it to the perforated plate component as well as the correct liquid pressures in such a manner that when the liquid is pressurized the closing face is separated from the dispensing opening such that the latter then allows liquid to pass in a correct manner. A type of valve action is achieved with such a realization. The cover body prevents the ingress of contaminants by way of its closing face when the dispenser is not utilized. As soon as the dispenser is used, the closing body is separated from the dispensing opening region under the liquid pressure and allows the liquid to be dispensed. The separation of the closing body from the dispensing opening region is preferably achieved as a result of the dispensing opening region being curved or displaced under the influence of the liquid pressure.

In the case of the aforementioned variants where the cover body closes the dispensing openings permanently, there are preferably provided on the cover body, on its side pointing towards the dispensing opening region, free regions such as grooves or indentations through which the liquid is able to pass to the dispensing openings which are not closed by the closing face. The cover body consequently serves not only for selectively closing dispensing openings, but also for forming channels which serve to supply the non-closed dispensing openings.

The inflow of liquid, in this case, can be effected from outside into a gap region between the dispensing opening region and the cover body/inside body. Depending on the development of the dispenser, however, it has also proved to be structurally expedient when the cover body itself is penetrated by an inflow channel which, for example, allows the direct supply of the liquid to be dispensed into a central region of the dispensing opening region.

Along with the described valve action which can be achieved, in particular, as a result of the deformability of the dispensing opening region, in the case of a further aspect of the invention it is provided that a generic dispenser has an outlet valve which has two valve components, of which one is a valve seat which is fixed in position with respect to an outside housing of the dispensing head and the other is a valve body which is movable in relation to said valve seat and controls the inflow of liquid to the dispensing opening together with the valve seat, wherein one of the valve components is formed by the perforated plate component.

According to said variant for forming an outlet valve, it is consequently provided that there are provided two valve components, which are movable towards one another as one unit, one of which is the perforated plate component. Said valve components are preferably pressed one against another by a spring means such as a helical spring, said components being matched to one another in such a manner that a spacing between the valve components in opposition to the force of said spring means can be achieved as a result of the liquid pressure. It can be provided that the liquid pressure

5

necessary for the opening relative displacement is built up directly in the region in front of the dispensing openings. However, developments are also conceivable where a pressurization face is provided locally on the movable valve component in front of the dispensing openings such that liquid does not pass into a gap between the valve components in the region of the dispensing openings until the valve components are displaced towards one another.

In the case of a further aspect of the invention, it is provided that in the case of a generic dispenser there is provided in the pre-chamber an inflow control body which, at least in the region of a dispensing opening, together with the perforated plate body defines a gap, the inside width of which preferably does not exceed 0.3 mm and in particular preferably does not exceed 0.1 mm. In the case of such a development it is consequently provided that there is an extremely narrow gap between the inflow control body and the at least one dispensing opening, preferably all of the dispensing openings. The small width of less than 0.3 mm, in particular of preferably less than 0.1 mm, has proved to be advantageous as it allows the dispensing characteristics to be modified by varying the roughness of the surface of the inflow control body in a targeted manner.

The inside width can even be 0 mm when using an inflow control body with a rough surface such that the inflow control body abuts directly against the dispensing opening region. It is proposed to this end that the end face of the inflow control body is realized in such a case with a peak-to-valley height R_z of between 10 μm and 100 μm . This allows an inflow of liquid to the dispensing openings without requiring a relative movement between the inflow control body and the dispensing opening region towards one another. The peak-to-valley height alone is sufficient to enable the inflow of liquid to the dispensing openings. It is also possible to adjust the volume flow in a precise manner as a result of the targeted choice of the peak-to-valley height R_z .

BRIEF DESCRIPTION OF THE DRAWINGS

Along with the claims, further aspects and advantages of the invention are also produced from the following description of preferred exemplary embodiments of the invention which are explained below by way of the figures, in which:

FIGS. 1a-1d show various perspective views of a perforated plate component for a dispenser according to the invention,

FIGS. 2a and 2b show a variant of the perforated plate component of FIGS. 1a to 1d,

FIGS. 3a and 3b show a first variant of a dispenser according to the invention with the perforated plate component of FIGS. 2a and 2b,

FIG. 4 shows a detail of the dispensing head of a dispenser realized as an alternative to the development in FIG. 3,

FIGS. 5a to 5c show a further development of a dispenser according to the invention,

FIG. 6a shows a further development of a dispenser according to the invention,

FIGS. 6b and 6c show different inside components for use with a dispenser according to the invention and by way of the example of the interaction of one of them with the perforated plate component,

FIGS. 7a to 7c show a further development of a dispenser according to the invention and

6

FIGS. 8a to 8b show a further development of a dispenser according to the invention.

DETAILED DESCRIPTION

FIGS. 1a to 1d show various perspectives of a perforated plate component 10 to be used with dispensers according to the invention. Said perforated plate component 10, in the case of the embodiments shown below in the realization according to FIGS. 1a to 1d or the similar realizations according to FIGS. 2a and 2b, provide an application which is fastened in the dispensing head of a dispenser. In principle, developments where the perforated plate component is realized integrally with an outside housing of the dispensing head are conceivable.

With reference to FIG. 1a, a perforated plate component of this type has a circumferential edge region 12 with latching means 12a which are provided for latching in a latching groove of a dispensing head housing 12b. The circumferential edge region 12 bears a plate-like dispensing opening region 16 which spans over an inner region 14 of the perforated plate component and is penetrated by a plurality of dispensing openings 18. In total, the perforated plate component 10 of FIGS. 1a to 1d has more than 300 dispensing openings 18 which are arranged in the manner of a matrix. The thickness of the plate-like dispensing opening region which is penetrated by the dispensing openings in the present case is approximately 0.3 mm. The matrix-like arrangement of the dispensing openings 18 can be seen well in FIGS. 1b and 1c which show the perforated plate component 10 from an inside surface and an outside surface. With reference to FIG. 1d which shows the dispensing openings 18 from the inside surface, it can be seen that the dispensing openings are in each case in the form of a negative truncated pyramid and consequently taper from an inside surface 16a to an outside surface 16b of the dispensing opening region 16.

As can also be seen by way of the further exemplary embodiments, it is provided at least in the case of some developments of dispensers according to the invention that the dispensing opening region 16 is curved in the mounted state of the dispenser. Consequently, in the mounted state there is deformation of the dispensing opening region which consists of plastics material and is curved outwards as a result proceeding from the non-mounted state of FIG. 1a.

The second variant 110 of the perforated plate component which is shown in FIGS. 2a and 2b has a modification in relation to the embodiment of FIGS. 1a to 1d which is provided with regard to such a curvature. Thus, on the dispensing opening region 116 a pin or projection 117 which points towards the inside surface 116a is integrally formed on the dispensing opening region 116.

FIG. 3a shows a dispenser 200 according to the invention utilizing the perforated plate component 110 of FIGS. 2a and 2b.

The dispenser 200 shown has a dispensing head 202 which is connected in a manner not shown in any detail to a pump device 203 or a supply valve 203 in such a manner that in reaction to the dispensing head 202 being depressed in the direction 2a, liquid is supplied out of the liquid storage unit through the connecting channel 204 to the perforated plate component 110.

A pre-chamber 220, in which an inside body 230 is arranged or which is defined by said inside body 230, is connected upstream of the perforated plate component 110. Said inside body 230 fills out the pre-chamber 220 extensively. Over and above this, it has an end face 232 which

points to the dispensing opening region **116** and has a curvature. The pin **117** of the perforated plate component **110** is supported on said end face **232** such that the dispensing opening region **116** is deformed and a gap of an approximately constant width is produced between the inside surface **116a** of the dispensing opening region **116** and the end face **232** in the region of the dispensing opening region **116**. The width of said gap in the present case is approximately 0.2 mm.

The dispensing opening region **116** is accordingly curved by the inside component **230** such that a diverging alignment of the dispensing openings **118** is produced. This leads to a spray jet as is indicated in the enlarged representation of FIG. **3b**. Said spray jet consists of a plurality of individual jets.

As a result of its composition from individual jets, such a spray jet is suitable for the targeted planar dispensing of liquid, for example on the skin of a user. The spray jet is perceived to be very soft and pleasant as a result of the individual jets.

The development of FIG. **4** shows a very simple use of the perforated plate component **10** of FIGS. **1a** to **1d** in a dispenser which on the other side of the region shown in FIG. **4** can have the identical design as that of FIG. **3a**. The perforated plate component **10** is not deformed in the case of said development. However, there is provided an inside component **330** which, in a manner not shown in any more detail, enables in an edge region **305** an inflow of liquid out of the connecting channel **304** as far as up to the dispensing opening region **16**. Additional grooves can be provided for this purpose in the edge region. The end face **332** of the inside component **330** is positioned very close to the inside surface **16a** of the dispensing opening region **16**. An inside gap between the inside surface **16a** and the end face **332** is only 0.1 mm.

It has been shown that such a very narrow gap is advantageous, in particular as it allows the flow resistance of the liquid up to the dispensing openings **18** to be influenced purely as a result of the choice of a certain surface roughness on the end face **332**. Consequently, different dispensing characteristics can be achieved purely as a result of the surface roughness on the end face **332** and with one constant perforated plate component **10**.

In the case of the development according to FIGS. **5a** to **5c**, the perforated plate component of FIGS. **1a** to **1d** is used once again. Said perforated plate component interacts with an inside component **430** which has a similar development to that inside component **230** of FIG. **3a**. The inside component **430** also has a curved end face **432** which points in the direction of the dispensing opening region **16** of the perforated plate component **10**. In the non-active state of the dispenser there is interaction, as shown on the bottom left-hand side in FIG. **5b**. The inside surface **16a** of the dispensing opening region **16** abuts flatly against the end face **432** and consequently in said non-active state closes the dispensing openings **18**, in particular also against the ingress of contaminants. If the pre-chamber **420** is then supplied with pressurized liquid through the supply channel **404**, a liquid pressure builds here which, as a result of the very narrow dispensing openings, is suitable to raise the dispensing opening region **16** in its totality from the end face **432**. The previously closed dispensing openings **18** are opened as a result of this and a diverging spray jet which is comparable with that of FIG. **3b** is formed. As soon as the liquid pressure falls away, the dispensing opening region **16** returns into the position in FIG. **3a** and consequently closes the dispensing openings **18** again.

FIG. **6a** shows a variant of the dispenser or of the dispensing head thereof where such deformation of the dispensing opening region **16** is not provided. Instead of which set-back free regions **534** are provided in the inside component **530** on the end face **532** thereof, through which free regions the liquid is able to pass selectively to some of the dispensing openings **18**, whilst others are permanently blocked by the end face **532**. As a result, a spray pattern, which does not require different perforated plate components **10** but is able to be realized purely by different inside components, can be adjusted from case to case.

FIG. **6b** shows a plurality of possible inside components.

The inside component **630a** corresponds with the inside component which is used in the case of the developments of FIGS. **3a**, **3b**, **5a**, **5b** and **5c**. The other inside components **630b** to **630i** lead to particular spray patterns as, in each case, they cover some of the dispensing openings **18** or, however, the inflow of liquid is influenced in another manner.

Thus, for example, only two left-hand and right-hand part regions of the dispensing opening region of the perforated plate component **10** are not closed by the inside component **630g**. By way of FIG. **6c** it can be seen that the predominant part of the dispensing openings **18** can serve not for dispensing liquid. The liquid only exits in the two part regions **16c**, **16d** of the dispensing opening region **16** and consequently brings about a diverging spray pattern divided into two.

A particular mention is also advisable with regard to the inside component **630h**. In this case, the inside component **630h** is provided with penetrating channels **636h** which supply the indentations on one end face **632h** and consequently the dispensing openings of the perforated plate component with liquid to be dispensed. Consequently, no care has to be taken to ensure that the liquid is able to pass laterally past the inside component as far as up to the dispensing opening region **16**.

The representation of the inside component **630b** acts to explain a particular surface roughness in the region of the end face. The surface on said end face of the component has an average peak-to-valley height R_z of between 10 μm and 100 μm , preferably of between 20 μm and 50 μm . When such an inside component **630b** is used with the dispensing head of FIG. **6a**, the liquid, which has flowed laterally past the inside component **630b**, is able to pass to the dispensing openings **18** without requiring displacement or deformation of the dispensing opening region **16** or of the inside component as a result of the named peak-to-valley height on the end face. By varying the peak-to-valley height, in this case, it is possible to influence the size of the corresponding volume flow.

The development of FIGS. **7a** to **7c** is comparable with the development of FIGS. **5a** to **5c** with regard to its intended action. Here too a valve, which is able to close the dispensing openings **18** of the perforated plate unit **10**, is provided. However, said valve includes an inside body **730** which is displaceable in contrast in its totality and is acted upon with force in the direction of the closed position by means of a spring **738** which is supported on the housing of the dispensing head. This can be seen in particular in FIG. **7c**.

The result of said application of force is that in the case of a lack of liquid supply, an end face **732** of the inside body **730**, which acts as the valve body, abuts against an inside surface **16a** of the dispensing opening region **16** of the perforated plate component **10** and consequently closes the dispensing opening region **18**. As soon as the liquid flows in,

it passes into a narrow gap between the end face 732 and the perforated plate component 10 and then presses the valve body 730 against the force of the valve spring 738 into its open position, which is shown in FIG. 7b. It is possible to dispense liquid in said open position. Once the dispensing has been terminated and the liquid pressure has fallen away, the valve assumes its closed position again of FIG. 7a.

The development of FIGS. 8a and 8b shows an alternative development where the perforated plate component and the valve body 830 are adapted to one another and have a gradation as a result of which a circumferential valve pressure chamber 834 is formed. The incoming liquid is initially collected during dispensing in said valve pressure chamber 834, but is not yet able to pass to the dispensing openings 18. Not until the valve body 830 has been displaced sufficiently rearwards as a result of the liquid pressure of the liquid in the valve pressure chamber 834 does the liquid pass into an intermediate region between the valve body and the dispensing opening region of the perforated plate component 10 and is dispensed from there. As a result of said design with the circumferential gradation, it is accordingly achieved that the unobstructed inflow to all the dispensing openings 18 is created at the same time.

The invention claimed is:

1. A dispenser for dispensing liquids, said dispenser having:

- a liquid storage unit;
- a dispensing head with a perforated plate component which has at least 25 dispensing openings in a dispensing opening region;
- a pre-chamber which is connected upstream of the dispensing openings of the perforated plate component and from which the dispensing openings are supplied; and
- a connecting channel which connects the liquid storage unit to the pre-chamber,

wherein the dispensing opening region is fastened on the dispensing head in an edge region, and a curvature body is arranged in the pre-chamber, the curvature body being disposed in direct contact with a portion of the dispensing opening region so as to act with force upon the dispensing opening region and press the dispensing opening region into a curved form.

2. The dispenser according to claim 1, wherein the edge region and the curvature body are displaceable towards one another during assembly or in a mounted state of the dispenser in such a manner that a curvature of the perforated plate component is influenced as a result.

3. The dispenser according to claim 1, wherein the dispensing openings of the dispensing opening region surround a central region of the dispensing opening region, and the portion of the dispensing opening region is an elevation disposed on an inside surface of the central region and the elevation projects inwardly and abuts against the curvature body of the dispensing head.

4. The dispenser according to claim 1, wherein the perforated plate component is realized as plastics material component or the dispensing openings are arranged in a density of at least 5 dispensing openings/mm².

5. The dispenser according to claim 1, wherein the curvature body has an outwardly convexly-shaped surface disposed in facing relation with the dispensing opening region and in direct contact with the portion of the dispensing opening region.

6. The dispenser according to claim 5, wherein the dispensing opening region has an inwardly facing surface disposed in facing relation with the outwardly convexly-

shaped surface of the curvature body and the portion projects from a central area of the inwardly facing surface towards, and is in direct contact with, the outwardly convexly-shaped surface, and a gap of substantially constant width is defined between the inwardly facing surface of the dispensing opening region and the outwardly convexly-shaped surface of the curvature body in areas disposed outwardly of the portion.

7. The dispenser according to claim 6, wherein the curved form of the dispensing opening region orients spray jets corresponding to the respective dispensing openings such that the spray jets diverge outwardly relative to the central area.

8. A dispenser for dispensing liquids, said dispenser having:

- a liquid storage unit;
- a dispensing head with a perforated plate component which has at least 25 dispensing openings in a dispensing opening region;
- a pre-chamber which is connected upstream of the dispensing openings of the perforated plate component and from which the dispensing openings are supplied; and
- a connecting channel which connects the liquid storage unit to the pre-chamber,

wherein the perforated plate component is fastened on the dispensing head in an edge region and the dispensing opening region is pressed into a curved form by a curvature body arranged in the pre-chamber and acting with force upon the dispensing opening region, the dispensing opening region surrounding a central region, and the perforated plate component has on an inside surface of the central region an inwardly pointing elevation which abuts against the curvature body of the dispensing head.

9. A liquid dispenser comprising:

- a liquid storage unit;
- a dispensing head mounted on said liquid storage unit and comprising:
 - a housing;
 - a perforated plate component having a dispensing region defining therein a plurality of dispensing openings and having an edge region fastened to said housing, said dispensing region having an inner surface and an outer surface facing away from said inner surface and adjacent which fluid exits from said plurality of dispensing openings;
 - a pre-chamber disposed upstream, with respect to a flow direction of fluid through said dispenser, of said plurality of dispensing openings and being in fluid communication with said plurality of dispensing openings;
 - a channel disposed to provide fluid communication between said liquid storage unit and said pre-chamber; and
 - a body disposed in said pre-chamber and having a surface disposed in facing relation with said inner surface of said dispensing region, said surface of said body being disposed in direct contact with part of said dispensing region so as to act with force on said dispensing region and press said dispensing region into a curved form.

10. The liquid dispenser according to claim 9, wherein said surface of said body has an outwardly convex curvature disposed in direct contact with said part of said dispensing region.

11. The liquid dispenser according to claim 10, wherein said part of said dispensing region includes a projection which extends towards said surface of said body and is in direct contact therewith.

12. The liquid dispenser according to claim 11, wherein said projection is disposed at a central area of said inner surface, and a gap of substantially constant width is defined between said inner surface of said dispensing region and said surface of said body in areas outwardly of said projection.

13. The liquid dispenser according to claim 12, wherein said curved form of the dispensing opening region orients spray jets corresponding to the respective dispensing openings such that the spray jets diverge outwardly in a direction away from said central area.

* * * * *