



US009416653B2

(12) **United States Patent**
Hammer et al.

(10) **Patent No.:** **US 9,416,653 B2**

(45) **Date of Patent:** **Aug. 16, 2016**

(54) **COMPLETION SYSTEMS WITH A BI-DIRECTIONAL TELEMETRY SYSTEM**

(71) Applicants: **Aaron C. Hammer**, Houston, TX (US);
Robert S. O'Brien, Katy, TX (US)

(72) Inventors: **Aaron C. Hammer**, Houston, TX (US);
Robert S. O'Brien, Katy, TX (US)

(73) Assignee: **BAKER HUGHES INCORPORATED**, Houston, TX (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 306 days.

(21) Appl. No.: **14/133,122**

(22) Filed: **Dec. 18, 2013**

(65) **Prior Publication Data**
US 2015/0167425 A1 Jun. 18, 2015

(51) **Int. Cl.**
E21B 47/12 (2012.01)

(52) **U.S. Cl.**
CPC **E21B 47/12** (2013.01)

(58) **Field of Classification Search**
CPC E21B 34/06; E21B 47/06; E21B 47/065;
E21B 47/002; E21B 49/08

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2011/0042064 A1* 2/2011 Martin E21B 43/04
166/66
2012/0043079 A1* 2/2012 Wassouf E21B 31/00
166/250.01

* cited by examiner


Primary Examiner — William P Neuder

(74) *Attorney, Agent, or Firm* — Cantor Colburn LLP

(57) **ABSTRACT**

An apparatus for use in a wellbore for performing a treatment operation is disclosed that in one non-limiting embodiment may include an inner string that further includes a first tubular having a first communication link, and a service tool including a cross-over tool having a fluid flow passage therein for supplying a treatment fluid under pressure from an inside of the service tool to an outside of the service tool, and wherein the service tool includes a second communication link operatively coupled to the first communication link and wherein the second communication link runs across or through the fluid flow passage in the cross-over tool that is protected from direct flow of the fluid under pressure from the inside of the service tool to the outside of the service tool.

22 Claims, 6 Drawing Sheets






FIG. 1




FIG. 2




FIG. 2A




FIG. 3




FIG. 4




FIG. 5

COMPLETION SYSTEMS WITH A BI-DIRECTIONAL TELEMETRY SYSTEM

BACKGROUND

1. Field of the Disclosure

This disclosure relates generally to apparatus and methods for completing a wellbore for the production of hydrocarbons from subsurface formations, including fracturing, gravel packing and flooding selected zones and for communicating information in real-time about various downhole operations.

2. Background of the Art

Wellbores are drilled in subsurface formations for the production of hydrocarbons (oil and gas). Modern wells can extend to great well depths, often more than 6000 meters (about 20,000 ft.). Hydrocarbons are trapped in various traps in the subsurface formations at different depths. Such sections of the formation are referred to as reservoirs or hydrocarbon-bearing formations or zones. Some formations have high mobility, a measure of the ease of the hydrocarbons flow from the reservoir into a well drilled through the reservoir under natural downhole pressures. Other formations possess low mobility and the hydrocarbons trapped therein are unable to move with ease from the reservoir into the well. Stimulation methods are typically employed to improve the mobility of the hydrocarbons through the reservoirs. One such method, referred to as fracturing (also referred to as “fracing” or “fracking”), is often utilized to create cracks in the reservoir to enable the fluid from the formation (formation fluid) to flow from the reservoir into the wellbore. To sand control, frac-pacing and gravel packing multiple zones, an assembly containing an outer string with an inner string therein is run in or deployed in the wellbore. The outer string is conveyed in the wellbore with a tubing attached to its upper end and it includes various devices corresponding to each zone to be fractured for supplying a fluid with proppant to each such zone. The inner string (also referred to as the “service string”) includes devices or tools attached to a tubing (which tubing can extend over 1,000 meters (about 3,000 feet) to perform a number of operations during treatment or service operations, including, but not limited to, setting an upper packer with a packer setting tool, setting a tool at selected locations of the outer string, setting packers, opening and closing valves, flowing fracture fluid from the inner string into the production zones via a frac port, and performing reverse flow and return flow operations. In such systems, it is desirable to obtain real-time information about the various operations performed in a wellbore using the inner string and outer string, including determining location of a device or element downhole, setting a device, fluid flow, temperature and pressure profiles, quality of the performed operations, etc. from various location along the inner string, including locations below the frac port. However, commercially utilized inner strings that include a packer setting tool and frac port are not available with a control line or communication link that runs from the surface to a location below the frac.

The disclosure herein provides systems and methods for use in wellbore operations that include a two-way communication system for providing real-time information between a surface location and downhole devices and operations, including information from locations below the frac port.

SUMMARY

In one aspect, an apparatus for use in a wellbore for performing a treatment operation is disclosed that in one non-limiting embodiment may include an inner string that further

includes a first tubular having a first communication link, and a service tool including a cross-over tool having a fluid flow passage therein for supplying a treatment fluid under pressure from an inside of the service tool to an outside of the service tool, and wherein the service tool includes a second communication link operatively coupled to the first communication link and wherein the second communication link runs across or through a through passage in the cross-over tool that is protected from direct flow of the fluid under pressure from the inside of the service tool to the outside of the service tool.

In another aspect, a method of performing a treatment operation in a wellbore is disclosed that in one non-limiting embodiment may include: providing an outer string; providing an inner string for placement inside the outer string, wherein the inner string includes a cross-over tool for supplying fluid under pressure from the inner string to the outer string; and running a communication link across or through the crossover tool that is protected from direct flow of the fluid from the inner string to the outer string through the cross-over tool.

Examples of the more important features of a well treatment system and methods that have been summarized rather broadly in order that the detailed description thereof that follows may be better understood, and in order that the contributions to the art may be appreciated. There are, of course, additional features that will be described hereinafter and which will form the subject of the claims.

BRIEF DESCRIPTION OF THE DRAWINGS

For a detailed understanding of the apparatus and methods disclosed herein, reference should be made to the accompanying drawings and the detailed description thereof, wherein like elements are generally given same numerals and wherein:

FIG. 1 shows an exemplary cased hole multi-zone wellbore system configured for a well treatment operation such as frac-packing. The wellbore system is shown to include a wellbore that has been lined with a casing

FIG. 2 shows certain details of an exemplary embodiment of the packer setting tool shown in FIG. 1 with the routing of the control line there through, according to one non-limiting embodiment of the disclosure;

FIG. 2A shows an exploded view of a section of FIG. 2;

FIG. 3 shows certain details of an exemplary cross-over tool shown in FIG. 1 with the routing of the control line there through, according to one non-limiting embodiment of the disclosure;

FIG. 4 shows a section of an exemplary cross-over tool shown FIG. 3 through which the control line shown in FIG. 3 may be routed; and

FIG. 5 shows placement of certain sensors in the system of FIG. 1 for determining certain parameters of interest in real time relating to downhole operations.

DETAILED DESCRIPTION OF THE DRAWINGS

FIG. 1 is a line diagram of a section of an exemplary multi-zone wellbore system **100** that is shown to include a wellbore **101** formed in formation **102** for performing a treatment operation therein, such as fracturing the formation (also referred to herein as fracing or fracking), frac-packing, gravel packing, etc. and for determining, in real time or near real time, parameters of interest relating to such operations from sensors deployed in the system **100** and taking actions in response to such determined parameters of interest. The wellbore **101** is lined with a casing **104**, such as a string of jointed

metal pipe sections, known in the art. The space or annulus **103** between the casing **104** and the wellbore **101** is filled with cement **106**. The system **100** is described herein in reference to a cased-hole; however, the concepts, apparatus and methods as described herein or with obvious modifications may equally be utilized for open holes. The particular embodiment of FIG. **1** is shown for selectively treating one or more zones in any selected sequence or order. However, wellbore **101** may be configured to perform other treatment or service operations, including, but not limited to, gravel packing and flooding a selected zone to move fluid in the zone toward a production well (not shown). The formation **102** is shown to include multiple zones **Z1-Zn** (also referred to as production zones) which may be fractured or treated for the production of hydrocarbons therefrom. Each such zone is shown to include perforations that extend from the casing **104**, through cement **106** and to a certain depth in the formation **102**. In FIG. **1**, Zone **Z1** is shown to include perforations **108a**, Zone **Z2** to include perforations **108b**, and Zone includes **Zn** to include perforations **108n**. The perforations provide fluid passages for fracturing corresponding zones. The perforations also provide fluid passages for formation fluid **150** to flow from the formation **102** to the casing **104**. The wellbore **101** includes a sump packer **109** proximate to the bottom **101a** of the wellbore **101**. [open hole mentioned in paragraph 0009 below]

After casing, cementing, sump packer deployment, perforating and cleanup operations, the wellbore **101** is ready for treatment operations. Although system **100** is described in reference to fracturing and gravel packing production zones, the concepts, apparatus and methods as described herein or with obvious modifications may also be utilized for other well treatment operations, including, but not limited to, fracturing and gravel packing. Furthermore, the concepts, apparatus and methods disclosed herein may equally be utilized for open hole applications. The formation fluid **105** is at the formation pressure (**P1**) and the wellbore **101** is filled with a fluid **152**, such as completion fluid, which fluid provides hydrostatic pressure (**P2**) inside the wellbore **101**. The hydrostatic pressure **P2** is greater than the formation pressure **P1** along the depth of the wellbore **101**, which prevents flow of the fluid **105** from the formation **102** into the casing **104** and prevents blow-outs.

Still referring to FIG. **1**, to fracture (treat) one or more zones **Z1-Zn**, a system assembly **110** is deployed in the wellbore **101**, which includes an outer string **120** and an inner string **160** placed inside the outer string **120**. The outer string **120** includes a pipe **122** and a number of devices associated with each of the zones **Z1-Zn** for performing treatment operations. In one non-limiting embodiment, the outer string **120** includes a lower packer **124a**, an upper packer **124m** and intermediate packers, such as packer **124b**. The lower packer **124a** isolates the sump packer **109** from hydraulic pressure exerted in the outer string **120** during fracturing and sand packing of the production zones **Z1-Zn**. In one aspect, packers **124a-124m** may be hydraulically set or deployed packers. In another aspect, packers **124a-124m** may be mechanically set or deployed. Still referring to FIG. **1**, the outer string **120** further includes a screen adjacent to each zone **Z1-Zn**. For example, screen **S1** is shown placed adjacent to zone **Z1**, screen **S2** adjacent zone **Z2** and screen **Sn** adjacent to zone **Zn**. The lower packer **124a** and intermediate packer **124b** are deployed to isolate zone **Z1** from the remaining zones. Other zones are similarly isolated for treatment operations. Each packer has an associated packer setting or activation device, such as packer setting device **125a** for packer **124a**, packer setting device **125b** for packer **124b** and packer setting device

125m for packer **124m**. In the case of a hydraulically-activated packer, any suitable device known in the art, including a piston device, may be utilized as the hydraulic activation device, and in case of a mechanically-activated packer, the device may include a mechanical member that is moved to set the packer.

In one aspect, each screen has one or more associated flow control devices, such as sliding sleeve valves **132a** and **132b** shown on screen **S1**. Other screens have similar devices. The outer string **120** also includes, for each zone, a flow control device, referred to as the slurry outlet or a gravel exit, such as a sliding sleeve valve or another valve, uphole or above its corresponding screen to provide fluid communication between the inside **120a** of the outer string **120** and its corresponding zone. FIG. **1** shows an exemplary slurry outlet **140a** for zone **Z1** between screen **S1** and the intermediate packer **124b**.

Still referring to FIG. **1**, the inner string **160** includes an upper section **160a** that includes a tubular **161** made by joining pipe sections (such as drill pipe) and a lower section **150** (referred to as the service tool) connected to the upper section **160a**. The service tool **150** includes a pipe or tubular **158**, which may be a flush joint tubular, known in the art. The service tool **150** also may include an interface sub **154** attached to the bottom end **161a** of the tubular **161** to provide a connection for a communication link **182** in the tubular **161** to a communication link or line **184** in the service tool **150**, as described in more detail in reference to FIGS. **2-5**. The phrase "communication link" or "communication line" means a link for communicating signals, data and/or power from one location to another. The communication link may be any suitable link, including, but not limited to, electric lines, fiber optic lines and other links, such as acoustic links or a combination of such links.

Still referring to FIG. **1**, the service tool **150** includes a packer setting tool **156** for setting the upper packer **124m**. In a multi-zone well system, the tubular **158** may extend to over 3,000 feet. The service tool **150** further includes an opening shifting tool **162** and a closing shifting tool **164** along the lower end **160a** of the inner string **160**. The inner string **160** further may include a reversing valve **166** that facilitates the removal of treatment fluid from the wellbore after treating each zone, and an up-strain locating tool **168** for locating one or more locations uphole of a set-down location, such as a locations **194b** for zone **Z1** when the inner string **160** is pulled uphole, and a set down tool or set down locating tool **170**. In one aspect, the set down tool **170** may be configured to locate each zone and then set down the inner string **160** at each such location for performing a treatment operation. The service tool **150** further includes a cross-over tool **174** (also referred to herein as the "frac port") for providing a fluid path **175** between the inner string **160** and the outer string **120**. In one aspect, the frac port **174** also includes flow passages **176** therethrough, which passages may be gun-drilled through the frac port **174** to provide fluid communication between space **172a** below the frac port **174** and space **172b** above the frac port **174**. The size of passages **176**, however, are sufficient to provide fluid flow and thus pressure communication between spaces **172a** and **172b**.

To perform a treatment operation in a particular zone, for example zone **Z1**, lower packer **124a** and upper packer **124m** are set or deployed. Setting the upper packer **124m** and lower packer **124a** anchors the outer string **120** inside the casing **104**. The production zone **Z1** is then isolated from all the other zones. To isolate zone **Z1** from the remaining zones **Z2-Zn**, the inner string **160** is manipulated to cause the opening tool **164** to open a monitoring valve **133a** in screen **S1**. The inner

string **160** is then manipulated (moved up and/or down) inside the outer string **120** so that up-strain locating tool **168** locates a profile **194b**. The set down tool **170** is then manipulated to cause it to set down in the set down profile **194a**. When the set down tool **170** is set down at location **194a**, the frac port **174** is adjacent to the slurry outlet **140a**. The packer **124b** is then set to isolate zone **Z1**. Once the packer **124b** has been set, frac sleeve **140a** is opened to supply slurry or another fluid to zone **Z1** to perform a fracturing or a treatment operation. Once zone **Z1** has been treated, the treatment fluid in the wellbore is removed by closing the reversing valve **166** to provide a fluid path from the surface in the space (or annulus) between the outer string **120** and the inner string **160** so that a fluid supplied from the surface into such annulus will cause the treatment fluid to move to the surface, which process is referred to as reverse circulation or reversing. After reverse circulation, the inner string **160** may then be moved to set down device **170** at another zone for treatment operations.

Still referring to FIG. 1, as described earlier, the inner string **160** includes a control line, also referred as the “communication link” for providing communication between a location in the service tool and the surface. The phrase “control line” or “communication link” means a link for communicating signals, data and/or power from one location to another. In one non-limiting embodiment, a communication link **182**, which may be a conductor, runs through the tubular **161**, referred to as the wired pipe in the art. Interface sub **154** reflects the communication link **182** to a communication link **184** associated with the service tool **150** that runs to a control circuit **185** below the cross-over tool **174**. In one non-limiting embodiment, the communication link **184** passes through the packer setting tool **156**, as described in more detail in reference to FIG. 2. The communication link **184** then runs along the tubing **158** and then through the cross-over tool **174**, as described in more detail in reference to FIGS. 3 and 4. The communication link **184** then may pass other devices, such as the set down locating tool **170**, the up-strain locating tool **168**, reversing valve **166** and then along the tubing **158** below such devices. The control circuit **185** may be placed at any suitable location in the communication link **184** to receive signals from various sensors placed in the casing **104**, outer string **120** and the inner string **160**, as described in more detail in reference to FIG. 5. An exemplary packer setting tool **200** and a manner for running the communication link **184** through such a packer is described below in reference to FIG. 2.

FIG. 2 shows an exemplary embodiment of a packer setting tool **200** configured to set a packer **280**. FIG. 2A shows an exploded view of a section of FIG. 2. Referring now to FIGS. 2 and 2A, in one aspect, the packer setting tool **200** may be utilized as the packer setting tool **156** for setting the upper packer **125m** shown in system **100** of FIG. 1. The packer setting tool **200** includes an upper connection **201** that connects the packer setting tool **200** to the interface sub **154** (FIG. 1) and a lower connection **202** that connects the packer setting tool **200** to a connection pipe **214** downhole of the packer setting tool **200**. The packer setting tool **200** includes a flow through pipe **210** that provides a fluid passage **212** between the inner string (**160**, FIG. 1) and the surface. The packer setting tool **200** includes a connection device **260** that may include a number of spaced connection members, such as fingers **262a**, **262b**, etc., each such finger having a connection end, such as dogs **264a**, **264b**, which connect to or engage with a packer member **281**. Spacing between adjacent fingers may be utilized to run the communication link **184**, FIG. 1 as described later. The packer setting tool **200** further includes a device **270** that enables the packer setting tool **200** to disen-

gage from the packer **280** after the packer has been set. The packer setting tool **200** further includes a piston **230** outside the flow through pipe **210** and a shroud **222** over the piston **230**. The packer setting tool **200** also includes a movable outer sleeve **220** coupled to the piston **230**. Packer **280** further includes a movable packer setting member **284**, which member when moved causes the packer setting elements **282** to extend and engage with the casing (**104**, FIG. 1). To set the packer **280** against the casing, fluid under pressure is supplied to the piston **230**, which moves the piston **230** downhole (to the right in FIG. 2). The piston **230** moves the outer sleeve **220** to the right, which moves the packer setting member **284** to the right to set the packer elements **282** against the casing (**104**, FIG. 1). In one aspect, the communication link **184** may be routed or placed under the shroud **222** and over the piston and over a part of the outer sleeve **220**, as shown by label **290a**. The communication link **184** is then run through a bore **221** in the outer sleeve **220** as shown by label **290b** and then between fingers **262a**, **262b** as shown by label **290c** and then outside **214a** of the connection pipe **214** and below the packer **280**, as shown by label **290c**. The communication link **184** then continues to run along the outside of the tubing **158**, as shown by label **290d**. The communication link **184** may be secured to the tubing **158** by any suitable mechanism, including but not limited to, clamps. Routing the communication link **184** through the outer sleeve **220** and the connection device **260** of the packer setting tool **200** and then between the ID of the packer **280** and the inner string as described herein enables the communication link **184** to pass from a location above the packer setting tool **200** to a location below the packer setting tool **200** without being exposed to high velocity frac slurry.

FIG. 3 shows certain details of an exemplary cross-over tool **300** with the routing of the communication link **184** therethrough, according to one non-limiting embodiment of the disclosure. The cross-over tool **300** has an upper connection **301** that connects the cross-over tool to the pipe **158** and a lower connection **302** that connects the cross-over tool to a section **303** of the service tool **150** below the cross-over tool **300**. The cross-over tool **300** includes a cross-over assembly **310** for supplying a treatment fluid **352** to a production zone, as described in reference to FIG. 1. The treatment fluid **352** may be any suitable fluid for performing a treatment operation, including, but not limited to, a mixture of water or gel and a proppant, such as sand or manufactured proppants. In one non-limiting embodiment, the cross-over assembly **310** includes a housing **320** that includes a number of through holes **322a**, **322b**, etc., along the length of the body **320**. The body **320** further includes a number of radially spaced fluid inlets **324a**, **324b**, etc. (hidden in FIG. 3 but depicted in FIG. 4), etc. around the body **320**. The body **320** further includes inserts **330a**, **330b**, etc. over the fluid inlets **324a**, **324b**, respectively, as shown in more detail in reference to FIG. 4. Each such insert includes a number of ports or fluid passages, such as ports **340a** in insert **330a**, ports **340b** in insert **330b**, etc. for supplying the treatment fluid **152** to the production zones, such as zones **Z1-Zn** shown on FIG. 1. Although the cross-over tool is shown to contain a number of elements, in aspects, it may only contain a frac port or another configuration known in the art.

FIG. 4 shows a section **400** of the cross-over assembly **310** shown in FIG. 3. The section **400** includes the housing **320** with through holes **322a**, **322b**, **322c** and **322d** drilled through the housing **320**. The section **400** includes a number of fluid inlets **324a**, **324b**, etc., wherein inlet **324a** is configured to be covered by insert **330a**, inlet **324b** by **333b**, etc., and wherein insert **330a** includes ports **340a** and insert **330b** includes ports **340b**, etc.

Referring to FIGS. 3 and 4, in one aspect, the communication link 184 may be run through one or more holes, such as through holes 322a, 332b, etc. of the cross-over assembly 310. FIG. 3 shows communication link 184 running or passing through hole 322a from above the cross-over tool to below the cross-over tool. During a fracing operation, the treatment fluid 158, which can be extremely abrasive due to the high velocity and presence of proppant and other chemicals, such as acids, passes through the ports 340a, 340b, etc. under high pressure and can damage control lines, such as communication link 184. Routing the communication link 184 through passages 322a, 322b, prevents the communication link from coming in direct contact with the flow of the treatment fluid 352 through the cross-over tool 300.

FIG. 5 shows placement of exemplary sensors in system 100 for determining various parameters of interest during a treatment operation. The parameters of interest may include, but, are not limited to, weight or load on a device in the inner string 160, tension on a device in the inner string 160, a location in the inner string or the outer string, location temperature at one or more locations and/or a temperature profile, pressures at one or more locations and/or a pressure profile, micro-seismic signals produced by the flow of a treatment fluid into the formation and/or cracking of the formation during a fracing operation, one or more flow rates of the fluid, and opening or closing of a device, such a sleeve valve. In one non-limiting embodiment, the system 100 may include on the inner string one or more weight and tension sensors 510, one or more pressure and temperature sensors P/T to determine the pressures and temperatures in the wellbore, one or more flow sensors 520 for determining the flow of a fluid, such as the flow of the treatment fluid 152 at one or more locations in the wellbore, and micro-seismic sensors 530, such acoustic sensors, for determining sound wave during a fracing operation to determine the effectiveness of the fracing operation. In another aspect, tags 544a, 544b, etc., such as magnetic tags, may be placed spaced apart on or proximate to a moving member, such as a sleeve of a sliding sleeve valve 140a for determining the movement of the sleeve and to ensure that the valve 140a has been correctly opened or closed. Tags, such as tags 544a, 544b also may be utilized to locate devices in the outer string 120 and/or to position a device, such as the set down tool 170, in the inner string 160 at a selected location inside the outer string 120. One or more tag detection sensors, such as sensors 545, may be placed in the inner string to detect the presence of the tags in the outer string 120. The tags may be of any suitable type, including, but not limited to, radiation tags, acoustic tags, electrical or resistive tags, and any other tags known in the art. Tags may also be utilized to locate other positions on the outer string 120 for any other purpose, including, but not limited to, use by the opening tool 162, closing tool 164, reverse valve 166 and the like. In another aspect, one or more suitable sensors, such as sensor 550 may be placed on the outside of the outer string 120 and a transmitter 552 may be placed on the inside of outer string 120. The sensor may include a battery for power and transmits signals to a receiver 554 in the inner string 160. Power to the control circuit 185 may be provided via a conductor in the communication link 184 by batteries 186 in the control circuit 185.

Still referring to FIG. 5, the sensors 520, 530, 544a, 544b, 550, etc. in the system 100 provide signals corresponding to their selected parameters of interest to the control circuit 185. In one aspect, the control circuit 185 may preprocess the received signals, such as pre-amplifying and digitizing the received signals, and transmit the digitized signals via the control line to a surface controller 590 (such as a computer or

computer-based system) for further processing and for providing real-time information to the operator for taking actions as necessary. In another aspect, the control circuit 185 may include a processor, such as a microprocessor 586, a memory device 587, such as a solid state memory and programmed instruction 588 accessible to the processor 586 for executing instructions contained in the programs 588. The processor 586 may also be configured to receive signals from the surface controller 590, process the signals from the downhole sensors and transmit information as directed by the surface controller. Although the embodiment of FIG. 5 is described in reference to a wire-type links (which for example may include electric conductor(s) or a fiber optic link(s)) run in or along the inner string 160, other links, including acoustic links, may also be utilized for the purposes of this disclosure. For example, an acoustic link may include a transceiver 580 that receives signals from the control circuit 185 and transmits such signals via the inner string 160 to the surface. For long distances, repeaters 582a, 582b, 582c, etc., may be placed in the inner string 160 to receive, amplify, condition and retransmit the signals to the next repeater or the surface as the case may be. Thus, in one aspect, the disclosure provides real-time two-way communication between a surface location and one or more locations in a wellbore via the inner string 160.

The foregoing disclosure is directed to the certain exemplary embodiments and methods. Various modifications will be apparent to those skilled in the art. It is intended that all such modifications within the scope of the appended claims be embraced by the foregoing disclosure. The words "comprising" and "comprises" as used in the claims are to be interpreted to mean "including but not limited to". Also, the abstract is not to be used to limit the scope of the claims.

The invention claimed is:

1. An apparatus for use in a wellbore, comprising:

an inner string that includes a service tool, the service tool including:

a packer setting tool that includes a moveable outer member that sets a packer and a shroud on an outside portion of the packer, wherein the communication link runs under the shroud and at least partially through the moveable outer member to a location below the packer setting tool, and

a cross-over tool having a fluid flow passage for supplying a fluid under pressure from an inside of the service tool to an outside of the service tool, wherein the service tool includes a protective passage for the communication link, wherein the protective passage runs through the cross-over tool and protects the communication link from direct flow of the fluid passing through the fluid flow passage from an inside of the service tool to an outside of the service tool.

2. The apparatus of claim 1, wherein the protective passage is formed in a housing of the cross-over tool and extends along a length of the housing.

3. The apparatus of claim 1, wherein the communication link extends from the service tool to a surface location via a tubular uphole of the service tool having a second communication link.

4. The apparatus of claim 1, wherein the service tool includes a control circuit.

5. The apparatus of claim 4, wherein the service tool includes at least one sensor for providing information relating to at least one parameter of interest to the control circuit.

6. The apparatus of claim 5, wherein the sensor is selected from a group consisting of: a weight sensor, a tension sensor,

a temperature sensor, a pressure sensor, a flow rate sensor, an acoustic sensor, an imaging sensor, an optical sensor and a tag.

7. The apparatus of claim 4, wherein the parameter of interest is selected from a group consisting of: weight; tension; temperature; pressure; flow rate; an image; a location on an outer string; fluid density; fluid composition; chemical composition; effectiveness of a fracturing operation; opening of a valve; and closing of a valve.

8. The apparatus of claim 1, wherein the communication link is coupled to a wired pipe.

9. The apparatus of claim 8, wherein the communication link in the service tool includes an acoustic communication link.

10. The apparatus of claim 1 further comprising an outer string, wherein the inner string is deployed inside the outer string.

11. The apparatus of claim 10, wherein at least one sensor is deployed in the outer string.

12. A method of performing a treatment operation in a wellbore, comprising:

providing an outer string in the wellbore;

providing an inner string for placement inside the outer string, wherein the inner string includes:

a packer setting tool that includes a moveable outer member that sets a packer and a shroud on an outside portion of the packer, wherein the communication link runs under the shroud and at least partially through the movable outer member to a location below the packer setting tool, and

a cross-over tool for supplying a fluid under pressure from inside the inner string to the outer string via a port and a protective passage through the cross-over tool for a communication link, wherein the protective passage protects the communication from the fluid passing through the port from the inner string to the outer string;

placing the outer string and the inner string in the wellbore; and

supplying the fluid under pressure from the inner string to the outer string to perform the treatment operation.

13. The method of claim 12 further comprising;

providing at least one sensor in one of the inner string and the outer string for providing information about a parameter of interest relating to the treatment operation; and

determining the parameter of interest from the information provided by the at least one sensor in real time at a location below the cross-over tool.

14. The method of claim 13, wherein the parameter of interest is selected from a group consisting of: a location in the outer string, pressure, temperature; weight; tension; flow rate; fluid density; fluid composition; chemical composition; effectiveness of a fracturing operation; opening of a valve; and closing of a valve.

15. The method of claim 13, wherein the sensor is selected from a group consisting of: a weight sensor; a tension sensor; a temperature sensor; a pressure sensor; a flow rate sensor; a fluid density sensor; a chemical composition sensor; a fluid composition sensor; a tag; an optical sensor; an image sensor; and an acoustic sensor.

16. The method of claim 13 further comprising taking an action relating to the treatment operation in response to information provided by the at least one sensor.

17. The method of claim 12, wherein the communication link includes an upper section and a lower section and wherein the method further comprises running the upper section of the communication link through a jointed pipe.

18. The method of claim 12, wherein the cross-over tool includes a body having one of a through passage and a shroud that is protected from the direct passage of the fluid flow under pressure and wherein the method further comprises running the communication link under the shroud or through the through passage.

19. The method of claim 12, wherein the communication link is one of an electric line, a fiber optic line, an acoustic transmission or a combination thereof that runs from a location below the cross-over tool to a location above the cross-over tool.

20. An apparatus for use in a wellbore, comprising:

an inner string that includes a tubular and a service tool connected to a bottom end of the tubular, wherein: the tubular includes an upper section of a communication link; and

the service tool includes:

a lower section of the communication link,

a packer setting tool that includes a moveable outer member that sets a packer and a shroud on an outside portion of the packer, wherein the communication link runs under the shroud and at least partially through the movable outer member to a location below the packer setting tool.

21. The apparatus of claim 20, wherein the service tool further comprises:

a cross-over tool having a fluid flow passage for supplying a fluid under pressure from an inside of the service tool to an outside of the service tool, wherein the communication link runs across the flow passage in the cross-over tool that protects the communication link from direct flow of the fluid under pressure from the inside of the service tool to the outside of the service tool.

22. The apparatus of claim 20, wherein the packer setting tool further includes a connection device that connects the packer setting tool a packer in the outer string and wherein the method further comprises running the communication link along a passage in the connection device that is below the packer.

* * * * *