



US006800016B2

(12) **United States Patent**  
**Wittenberg et al.**

(10) **Patent No.:** **US 6,800,016 B2**  
(45) **Date of Patent:** **Oct. 5, 2004**

(54) **FLEXIBLE DOLLS AND POSABLE ACTION FIGURES**

1,551,250 A	11/1922	Henry
1,626,533 A	12/1925	Hergershausen
1,709,432 A	3/1927	Hill
2,017,023 A	10/1932	Rendle
2,089,376 A	12/1932	Jacobson
1,998,864 A	7/1934	Dodge
2,073,723 A	5/1936	Woolnough

(75) Inventors: **Mark S. Wittenberg**, Rossmoor, CA (US); **Ahmad A. Asbaghi**, El Segundo, CA (US)

(73) Assignee: **Mattel, Inc.**, El Segundo, CA (US)

(List continued on next page.)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

**FOREIGN PATENT DOCUMENTS**

AU	2719077	1/1979
CA	831223	7/1916

(List continued on next page.)

(21) Appl. No.: **10/448,943**

(22) Filed: **May 30, 2003**

(65) **Prior Publication Data**

US 2004/0002279 A1 Jan. 1, 2004

**Related U.S. Application Data**

(60) Provisional application No. 60/384,884, filed on May 31, 2002.

(51) **Int. Cl.**<sup>7</sup> ..... **A63H 3/02**; A63H 3/04

(52) **U.S. Cl.** ..... **446/373**; 446/376

(58) **Field of Search** ..... 446/369, 370, 446/373, 374, 375, 376, 379, 380, 381, 382, 383, 486

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

164,582 A	6/1875	Miller
280,986 A	7/1883	Wishard
593,592 A	11/1897	Lyons
807,895 A	12/1905	Allert
1,141,459 A	6/1915	Gregg
1,189,585 A	7/1916	Kruse
1,255,446 A	2/1918	Lofgren
1,259,782 A	3/1918	Savage
1,355,799 A	10/1920	Bradish
1,590,898 A	5/1922	McAuley

**OTHER PUBLICATIONS**

Mattel 1969 Scuba figure.  
Mattel 1970 Rock Flower doll.  
1981 Jenny doll.  
GI Joe Action Soldier 1994 Commemorative Edition.  
Mattel 2000 Millenium Barbie.  
Mary Kate & Ashley Oct. 07, 2002 version.  
1994 TMP Toys Ghoul with pivoted mouth.


*Primary Examiner*—Jacob K. Ackun, Jr.

(74) *Attorney, Agent, or Firm*—Kolisch Hartwell, P.C.

(57) **ABSTRACT**

An improved posable figure having extended life and resistance to failure, and being repeatedly posable in a realistic fashion. The posable figure has an inner skeleton including one or more primary members constructed of a bendable material such as metal wire, and an outer molded body covering constructed of a flexible substance such as an elastomer material. The inner skeleton also may include one or more secondary members molded over portions of the primary members, to limit flexion of the primary members and/or to connect the primary members to form an articulated structure.

**25 Claims, 9 Drawing Sheets**



U.S. PATENT DOCUMENTS

2,156,573	A	7/1936	Schaeffer	
2,109,422	A	10/1936	Haughton	
2,134,974	A	8/1937	Hurwitz	
2,202,805	A	10/1939	Wood	
2,340,172	A	3/1941	Buchanan	
2,392,024	A	2/1945	Couri	
2,451,023	A	12/1945	Dusko	
2,606,398	A	7/1947	Miller	
2,601,740	A	5/1948	Schippert	
2,474,236	A	8/1948	Durbin	
2,684,503	A	11/1949	Silver	
2,767,517	A	8/1953	Hooper	
2,812,616	A	12/1954	Ford	
2,753,659	A	* 7/1956	Cohn .....	446/373
2,845,748	A	2/1957	Derham	
3,009,284	A	7/1959	Ryan	
3,055,119	A	7/1961	McEwen	
3,277,601	A	1/1964	Ryan	
3,350,812	A	4/1965	Lindsay et al.	
3,284,947	A	5/1965	Dahl	
3,395,484	A	6/1966	Smith	
3,325,939	A	11/1966	Ryan et al.	
3,432,581	A	10/1967	Rosen	
3,019,552	A	9/1968	Schleich	
3,574,968	A	4/1971	Schau et al.	
3,693,292	A	4/1971	Di Leva	
3,584,409	A	6/1971	Chang et al.	
3,624,691	A	11/1971	Robson et al.	
3,699,714	A	3/1972	Johnson et al.	
3,706,330	A	12/1972	Rightmire et al.	
3,716,942	A	2/1973	Garcia et al.	
3,852,389	A	12/1974	Adler et al.	
3,895,451	A	7/1975	Smrcka	
3,918,196	A	11/1975	Schleich	
3,921,332	A	11/1975	Terzian et al.	
3,939,604	A	2/1976	Nishizawa	
3,955,309	A	5/1976	Noble	
3,955,312	A	5/1976	Pugh	
4,028,845	A	6/1977	Licitis	
4,118,888	A	10/1978	Ogawa	
4,123,872	A	11/1978	Silva	
4,136,484	A	1/1979	Abrams	
4,169,336	A	10/1979	Kuhn	
4,170,425	A	10/1979	Brown	
4,170,840	A	10/1979	Ogawa	
4,197,358	A	4/1980	Garcia	
4,206,564	A	6/1980	Ogawa	
4,219,958	A	9/1980	Shulyak	
4,233,775	A	11/1980	Neufeld	
4,274,224	A	6/1981	Pugh et al.	
4,295,291	A	10/1981	Fukui	
4,440,784	A	4/1984	Katsumi et al.	
4,470,784	A	9/1984	Piotrovsky	
4,565,376	A	1/1986	Croll	
4,613,315	A	9/1986	Kataoka	
4,666,417	A	5/1987	Hillman	
4,767,505	A	8/1988	Satoh et al.	
4,802,858	A	2/1989	Lindskog et al.	
4,802,878	A	2/1989	Terzian et al.	
4,884,991	A	12/1989	Terzian	
4,892,501	A	1/1990	Girelli	
4,908,001	A	3/1990	Kopian	
4,932,919	A	6/1990	Shapero	
4,952,190	A	8/1990	Tarnoff et al.	
4,954,118	A	9/1990	Refabert	
4,955,844	A	9/1990	Miller, Jr.	
4,964,836	A	10/1990	Kamei	
5,017,173	A	5/1991	Shapero et al.	
5,083,732	A	1/1992	Akamine	
5,083,966	A	1/1992	Blank	

5,090,936	A	2/1992	Satoh et al.	
5,162,013	A	11/1992	Von Mohr	
5,162,190	A	11/1992	Zahn et al.	
5,255,457	A	10/1993	Lipson	
5,297,443	A	3/1994	Wentz	
5,516,314	A	5/1996	Anderson	
5,630,745	A	5/1997	Yeh	
5,741,140	A	4/1998	Bristol	
5,762,531	A	6/1998	Witkin	
5,766,701	A	6/1998	Lee	
5,800,242	A	9/1998	Clokey	
5,800,243	A	9/1998	Berman	
5,836,802	A	11/1998	Harnett	
5,939,480	A	8/1999	Lee et al.	
5,989,658	A	11/1999	Miura et al.	
6,074,270	A	6/2000	Wilcox et al.	
6,110,002	A	8/2000	Langton	
6,155,904	A	12/2000	Spector	
6,170,721	B1	1/2001	Chen	
6,176,756	B1	1/2001	Panec	
6,217,406	B1	* 4/2001	Ross .....	446/370
6,220,922	B1	4/2001	Lee et al.	
6,237,759	B1	5/2001	Wotton	
6,264,526	B1	7/2001	Meeker	
6,267,640	B1	7/2001	Akashi et al.	
6,350,664	B1	2/2002	Haji et al.	
6,353,263	B1	3/2002	Dotta et al.	
6,365,840	B1	4/2002	Honda et al.	
6,524,519	B1	2/2003	Ohba et al.	

FOREIGN PATENT DOCUMENTS

DE	343128	10/1921
DE	412263	4/1925
DE	456557	8/1928
DE	887474	7/1953
DE	4040737	3/1991
DE	4138736	6/1992
DE	4208081	9/1993
DE	19960540	1/2001
DE	10000309	4/2001
DE	10016378	5/2001
EP	0566799	10/1993
EP	1010784	6/2000
EP	1057506	6/2000
EP	1052002	11/2000
EP	0743083	12/2000
EP	1108454	6/2001
EP	1097740	9/2001
FR	632811	3/1927
FR	1060435	4/1954
GB	155806	12/1921
GB	0279157	10/1927
GB	0581338	10/1946
GB	1137642	12/1968
GB	1402235	8/1975
GB	1571352	7/1980
GB	2134303	7/1984
GB	2184032	6/1987
GB	2197800	6/1988
GB	2215227	9/1989
GB	2239625	7/1991
GB	2346815	8/2000
GB	2348847	10/2000
GB	2350308	11/2000
GB	2354181	3/2001
GB	2361194	10/2001
JP	56049211	5/1981
JP	58127679	2/1983
JP	60157815	8/1985
JP	62071616	4/1986
JP	6194720	5/1986

# US 6,800,016 B2

Page 3

---

JP	6194721	5/1986	JP	3292984	12/1991
JP	6194722	5/1986	JP	4005987	1/1992
JP	6194723	5/1986	JP	4288187	10/1992
JP	61125367	5/1986	JP	5208077	8/1993
JP	61169217	7/1986	JP	8182864	7/1996
JP	61191496	8/1986	JP	9313740	12/1997
JP	63103685	7/1988	JP	1022278	1/1998
JP	11221369	4/1989	JP	10118340	1/1998
JP	1080391	6/1989	JP	10165656	12/1998
JP	1221192	6/1989	JP	10258186	12/1998
JP	1036422	7/1989	JP	2000061151	2/2000
JP	1314584	9/1989	JP	2000061152	2/2000
JP	2295587	6/1990	WO	WO9939793	8/1999
JP	2243184	9/1990	WO	WO0010665	6/2000
JP	2114983	10/1990	WO	WO0032288	8/2000
JP	2104386	11/1990	WO	WO0038810	10/2000
JP	2252509	11/1990	WO	WO0108776	7/2001
JP	2159291	12/1990	WO	WO0187443	11/2001
JP	3016581	1/1991			
JP	3015401	4/1991			

\* cited by examiner




FIG. 4

FIG. 1





FIG.2






FIG. 5




FIG. 6






FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG.13

1

## FLEXIBLE DOLLS AND POSABLE ACTION FIGURES

### CROSS REFERENCE TO RELATED APPLICATIONS

The present application claims priority from U.S. Provisional Patent Application Ser. No. 60/384,884, filed May 31, 2002, incorporated herein by reference in its entirety for all purposes.

### FIELD OF THE INVENTION

The present disclosure relates generally to flexible doll toys and posable action figure toys. More particularly, it includes dolls and action figures with an outer surface constructed from a soft, flesh-like material, and a bendable inner skeleton.

### BACKGROUND OF THE INVENTION

Many different varieties of flexible dolls and action figures have been developed over the years, mainly for the purposes of entertainment and display. Creation of a flexible or posable figure generally requires creation of a movable articulated body and limbs, ideally configured to retain whatever pose the figure is placed into. Furthermore, it is desirable that the figure be posable a large number of times without failure of the structure.

One class of posable figures includes an inner armature or skeleton, possibly including joints to recreate the articulation of a human skeleton, and a molded outer covering or body constructed of a flexible material that surrounds and is bonded or otherwise anchored to the inner skeleton. Examples of such toys are found in U.S. Pat. Nos. 280,986, 1,189,585, 1,551,250, 1,590,898, 2,017,023, 2,073,723, 2,109,422, 2,392,024, 2,601,740, 2,684,503, 3,325,939, 3,284,947, 3,395,484, 3,624,691, 3,955,309, 4,123,872, 4,136,484, 4,233,775, 4,932,919, 4,954,118, 4,964,836, 5,516,314, 5,630,745, 5,762,531, 5,800,242, 6,155,904, and 6,217,406, and in publications JP49-18954, JP49-18955, JP60-97067, JP61-94090, JP61-94091, JP61-94092, JP62-53686, JP62-164092, JP63-103685, JP11-212369, WO0067869, and WO0010665. Other examples of flexible doll toys and action figure toys are found in U.S. Pat. Nos. 3,277,601, 3,716,942, 4,470,784, 4,932,919, 5,017,173, and 6,074,270, and in publication WO0108776. The disclosures of all of these patents and publications are incorporated herein by reference.

### SUMMARY OF THE INVENTION

An improved posable figure is provided, having extended life and resistance to failure, and being repeatedly posable in a realistic fashion. The posable figure has an inner skeleton including one or more primary members constructed of a bendable material such as metal wire, and an outer molded body covering constructed of a flexible substance such as an elastomer material. The inner skeleton also may include one or more secondary members molded over portions of the primary members, to limit flexion of the primary members and/or to connect the primary members to form an articulated structure.

The advantages of the posable figure provided will be understood more readily after a consideration of the Drawings and the Detailed Description of the Preferred Embodiment.

### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view of an inner skeleton for a posable figure, according to an embodiment of the invention.

2

FIG. 2 is a front elevational view of several primary members of the inner skeleton of FIG. 1.

FIG. 3 is a front elevational view of the inner skeleton of FIG. 1, showing primary members disposed within the skeleton.

FIG. 4 is a magnified view of a portion of an inner skeleton for a posable figure, showing locating pins and related structure.

FIG. 5 is a front elevational view of a partially formed posable figure according to an embodiment of the invention, showing an inner skeleton disposed within the figure.

FIG. 6 is a front elevational view of the posable figure of FIG. 5, after an additional body molding step.

FIG. 7 is a partial front sectional view of a portion of an alternative embodiment of a posable figure.

FIG. 8 is a partial front sectional view of a portion of another alternative embodiment of a posable figure.

FIG. 9 is a partial front sectional view of a portion of another alternative embodiment of a posable figure.

FIG. 10 is a partial front sectional view of a portion of another alternative embodiment of a posable figure.

FIG. 11 is a partial front sectional view of a portion of another alternative embodiment of a posable figure.

FIG. 12 is a partial front sectional view of a portion of another alternative embodiment of a posable figure.

FIG. 13 is a partial front sectional view of a portion of another alternative embodiment of a posable figure.

### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

Referring to FIG. 1, an inner skeleton for a posable figure is shown and generally indicated at **10**. Although it is anticipated that inner skeleton **10** will eventually be enclosed by and bonded to an outer covering, such as an injection-molded body of a posable figure, FIG. 1 shows the inner skeleton in isolation for clarity. Skeleton **10** includes one or more flexible primary members that may be coated and/or joined together to form an articulated structure. The primary members may be joined in an insert molding process, referred to hereinafter as a skeleton-forming process, that molds one or more secondary members over portions of the primary members, as described below.

FIG. 2 shows several primary members of the skeleton of FIG. 1, before the skeleton-forming process. In this embodiment, skeleton **10** includes a primary upper member **12**, extending from a first hand portion **14** to a second hand portion **16** of the skeleton and defining arm portions **18** and **20**. The skeleton also includes a primary torso member **22** defining a waist portion **24** and a chest portion **26**, and two primary leg members **28** and **30** extending from foot portions **32** and **34** to a hip portion **36** and defining leg portions **38** and **40**.

The primary members may be constructed from any flexible, resilient material, such as strands of metal wire. In the embodiment depicted in FIG. 2, each wire of the primary members has the same diameter and is constructed from the same material. In particular, the primary members depicted in FIG. 2 are constructed from stainless steel wires, each with a diameter of approximately 1.4 millimeters. However, it will be appreciated that wires of other diameters and/or constructed from other materials may be equally suitable or more suitable for various skeleton designs, depending on the overall size of the posable figure and its intended use. For instance, two or three strands of twisted wire could be used to define some or all of the primary members.

As seen in FIG. 2, primary upper member 12 includes a single wire extending from one hand portion to the other, so that a single wire is found in a cross-section of each arm portion 18 and 20. The wire of primary upper member 12 is bent or doubled over in a neck portion 42, so that two wires are found in a cross-section of the neck portion. Primary leg members 28 and 30 each include a single wire extending from one of the foot portions to hip portion 36, so that a single wire is found in a cross-section of each leg portion. Primary torso member 22 includes two wires extending through waist portion 24, and both are doubled over so that four wires are found in a cross-section of the waist portion.

Each primary member has two ends, with at least one intermediate bend between the two ends. The intermediate bends are provided to retain secondary members that will be molded to partially surround the primary members, as described in more detail below. Specifically, primary upper member 12 has a first end 44 disposed in hand portion 14, and a second end 46 disposed in hand portion 16. An intermediate bend 48 is disposed near first end 44, three other intermediate bends 50, 52, and 54 are disposed in neck portion 42, and yet another intermediate bend 56 is disposed near second end 46 of the primary upper member.

Primary torso member 22 has a first end 58 and a second end 60, and includes a first intermediate bend 62 disposed near first end 58, another intermediate bend 64 disposed in hip portion 36, and another intermediate bend 66 disposed near second end 60. Primary leg member 28 has a first end 68 and a second end 70, with an intermediate bend 72 disposed near first end 68 and another intermediate bend 74 disposed near second end 70. Similarly, primary leg member 30 has first and second ends 76 and 78, with intermediate bends 80 and 82 disposed near the first and second ends, respectively.

Referring back to FIGS. 1–2 in conjunction with each other, the wires forming the primary members are held within a mold (not shown) shaped to define the finished skeleton, and bonded into an integral structure in a skeleton-forming process. During the skeleton-forming process, portions of the wires forming the primary members are coated with a layer of polymer resin material, generally indicated at 84. Coating the wires in this manner may decrease the likelihood of a wire fraying and/or poking through an outer covering surrounding the skeleton, thus increasing the safety and durability of the posable figure. Also during the skeleton-forming process, various secondary members, also covering portions of the primary members, are formed from substantially thicker layers of resin.

FIG. 3 shows a front plan view of inner skeleton 10 after the skeleton-forming process has molded polymer resin around portions of the primary members. The resin material, which may be polypropylene, is flexible enough to allow bending in portions where it covers the primary members in a relatively thin layer. By varying the thickness of resin material surrounding the various portions of wire, different amounts of flexibility may be imparted to different portions of the skeleton, even though only a single layer of resin is injected around the wires in the first injection or insert molding step. In particular, polypropylene is flexible enough to allow bending of the wires in portions where the polypropylene is molded to be less than about 2 millimeters (2-mm) thick, and preferably to be about 1-mm thick.

In the embodiment depicted in FIG. 3, waist portion 24, arm portions 18 and 20, leg portions 38 and 40, and neck portion 42 are all covered with a layer of polypropylene, approximately 1-mm thick, during the skeleton-forming

process, so that these portions of the skeleton remain bendable. During the same process, various secondary members are formed from substantially thicker layers of resin. The secondary members cover portions of the primary members and couple the primary members together to form an integral structure.

As shown in FIG. 3, the secondary members may include a secondary hip member 86, a secondary chest member 88, secondary hand members 90 and 92, and secondary foot members 94 and 96. Due to their thickness, the secondary members limit flexion of various portions of the skeleton. In particular, flexion of the skeleton is limited in portions of the skeleton where the primary members are covered by the secondary members, and also in portions of the skeleton occupied by the secondary members but not by the primary members.

As described previously and as best seen in FIG. 2, the primary members of the skeleton each include at least one intermediate bend. Each intermediate bend of the primary members is designed to securely retain one of the secondary members at a predefined location on the primary member, when the secondary members are molded over the primary members. Secure retention of the secondary members is accomplished, for example, due to increased surface area provided by each bend of the primary members, and also due to the curvature of each bend providing resistance to tensional forces that might be exerted on the skeleton to pull it apart.

For example, as seen in FIG. 3, intermediate bends 64, 74, and 82 retain secondary hip member 86. Similarly, intermediate bends 50, 54, 62, and 66 retain secondary chest member 88. Intermediate bends 48 and 56 retain secondary hand members 90 and 92, respectively, and intermediate bends 72 and 80 retain secondary foot members 94 and 96, respectively. A retaining clip 98 for a head of the toy may be molded during the same skeleton-forming process that forms the secondary members, from the same material. Intermediate bend 52 in primary upper member 12 retains clip 98 in a manner analogous to retention of the secondary members by the other intermediate bends.

Still referring to FIG. 3, various support members also may be molded during the skeleton-forming process. These support members may include various locating pegs 100, 102, 104, 106, and 107, and locating sprues 108, among others. The support members may extend outward from the primary and/or secondary members, adding structure and stability to inner skeleton 10. As described in more detail below, the support members may also be configured to allow inner skeleton 10 to be located accurately and conveniently in a mold in preparation for another injection molding step.

FIG. 4 shows a close-up view of an arm portion of the posable figure of FIG. 1, showing in detail one of locating pegs 100 used to center the armature within a subsequent mold. It will be noted in FIG. 4 that small portions 109 of the wire of primary upper member 12 remain exposed after the skeleton-forming process, until the skeleton is covered with resilient material in one or more subsequent molding processes. Portions 109 of exposed wire are the result of intrusions into the mold used in the skeleton-forming process, the intrusions (not shown) holding the wire in place as skeleton-forming resin is injected around the primary members.

The support members are formed during the same skeleton-forming process that forms the secondary members, and are therefore constructed from the same material as the secondary members, typically a polymer

## 5

resin material such as polypropylene or polyethylene. The support member material may also be a thermoplastic elastomer material such as polyvinylchloride (PVC), or a styrene-based elastomer such as a Kraton material manufactured by Kraton Polymers of Houston, Tex., among others. In some embodiments, this material may be chosen to bond and/or be otherwise compatible with a material used for the outer covering of the toy figure.

As is best seen in FIG. 1, the locating pegs each may extend substantially radially outward from the primary members, and may be configured to assist in positioning inner skeleton **10** in a desired location within a mold prior to a subsequent injection molding step. For example, a particular locating peg may be configured to substantially span a radius of the mold, thereby holding a portion of the inner skeleton spaced away from the walls of the mold. This may allow material to be injected into the mold to form a continuous molded body, encasing and bonded to the inner skeleton, with the inner skeleton spaced away from the surface of the body.

In particular, in the embodiment of FIG. 1, locating pegs **100** extend radially away from the primary upper member and the primary leg members in the plane of skeleton **10**. When skeleton **10** is placed into a mold, pegs **100** may abut the walls of the mold to securely hold the skeleton in place. When an outer covering (or body) material is placed in the mold, it will surround the skeleton by filling in the empty portions of the mold, so that the locating pegs extend to an outer surface of the finished figure. Thus, pegs **100** may define a width of the arms and lower legs of the finished posable figure in the plane of the skeleton.

Locating pegs **102** are similar to pegs **100**, but extend further from the primary leg members and may define a width of the upper legs of the finished figure in the plane of the skeleton. Locating pegs **104** extend radially away from the primary members in directions orthogonal to the plane of the skeleton, and may define widths of the arms and legs in those directions. Similarly, locating pegs **106** of the secondary chest member extend above the secondary chest member, and locating pegs **107** of the secondary chest member extend laterally from the secondary chest member. These pegs may help to securely locate the secondary chest member within a mold and to define the dimensions of the finished figure.

It will be appreciated that although one convenient configuration of locating pegs is depicted in FIG. 1, alternative placements of locating pegs relative to the primary and secondary members of the skeleton are possible. In addition, although the locating pegs are depicted in FIG. 1 as substantially cylindrical, they may have any other suitable shape. For example, the locating pegs may be substantially conical or frustoconical, and they may also have rounded ends to conform to the curvature of an inner surface of a mold.

Sprues **108** may be substantially cylindrical or toroidal, and may serve to further locate inner skeleton **10** in a mold during further subsequent body molding steps. For example, the sprues may be placed in corresponding depressions or recesses in a mold, to hold the inner skeleton in position while a surrounding body or a portion thereof is injection molded around the inner skeleton. As is best seen in FIG. 1, sprues **108** may be variously disposed near secondary hand members **90** and **92**, secondary hip member **86**, and secondary foot members **94** and **96**.

As described previously, inner skeleton **10** is located in a mold in order to form a resilient, flexible body covering

## 6

around the inner skeleton. In some embodiments, the body covering is molded in a two-step body molding process, and is formed from two different materials which differ in their elastic properties. In other embodiments, the body covering may be molded in a single body molding step, and therefore may be formed from a single elastic material. Various embodiments are described below and depicted in the Drawings.

In cases where the body covering is molded from two different materials, it may be desirable to mold some portions of the body covering from a relatively soft material, and to mold other portions of the body covering from a relatively hard material. For example, the Shore hardness of the soft material may be approximately 14, and the Shore hardness of the hard material may be approximately 40. More specifically, the first material (Shore hardness 14) may be obtained from the Riken Corporation of Tokyo, Japan, under the identifier Leostemer LFR9904N, and the second material (Shore hardness 40) may also be obtained from Riken, under the identifier Leostemer LFR9810N.

FIG. 5 depicts inner skeleton **10** of FIG. 1 with a first resilient, flexible body material, generally indicated at **110**, molded around various portions of the skeleton in a first body molding step. The first body material defines finished lower legs **112** and **114**, finished arms **116** and **118**, a finished upper chest **120**, and a finished neck **122**. In addition, the first body material has been molded around upper portions **124** and **126** of the primary leg members and around a middle portion **128** of the primary torso member, to form an unfinished surface extending only partially towards the outer surface of the finished figure. The first body material thickens portions **124**, **126**, and **128** around the primary members, limiting flexion of the figure in those portions.

In FIG. 5, the first body material is shown molded around upper portions **124** and **126** of the primary leg members and around middle portion **128** of the primary torso member to a diameter of approximately 2-mm. Thus, in this embodiment these portions are each covered first with approximately 1-mm of a resin material during the skeleton-forming process, and then with approximately 2-mm of the first body material during the first body molding step. As described below, a second body material will be molded around the first body material to form the finished body in portions **124**, **126**, and **128**.

FIG. 5 also shows how the first body material is molded into a frustoconical shape, or a taper **130**, at the proximal end of each finished lower leg. Such a taper may improve the outer appearance, bending properties, and durability of the posable figure at a juncture of the two body materials in the legs. Similarly, the particular juncture structure **131** shown in the chest region of the toy improves the outer appearance, bending properties, and durability of the toy.

FIG. 6 depicts the posable figure of FIG. 5 after a second body molding step in which a second resilient, flexible body material, generally indicated at **132**, has been molded around portions **124**, **126**, and **128** to form a finished body. As described previously, the second body material is typically an elastomer similar to the first body material, but with a different Shore hardness. As seen in FIGS. 5-6, sprues **108** protrude from the finished body, and are typically removed during final manufacturing steps. Other final manufacturing steps may include adding a head, clothing, paint, and/or other accessories (not shown) to the posable figure.

FIG. 7 depicts a partial sectional view of an alternative embodiment of a posable figure formed in a multi-step molding process. The figure depicted in FIG. 7 includes an

inner skeleton **210** similar to inner skeleton **10** of FIG. 1, including a primary torso member **212**, and primary leg members **214** and **216**. The primary members of this embodiment are joined together in a skeleton-forming process as previously described, except that the primary members are not coated with a thin layer of resin during the initial skeleton-forming molding process. Furthermore, in this embodiment, primary torso member **212** of the skeleton includes only a single wire. After the skeleton-forming process, the embodiment of FIG. 7 is then molded with first and second surrounding body materials **110** and **132**. Body materials **110** and **132** may be applied to skeleton **210** in a two-step process, as described previously and as shown in the embodiment of FIGS. 5–6.

Another alternative embodiment of a posable figure is depicted in FIG. 8. The inner skeleton of the depicted embodiment is substantially identical to skeleton **10**, which is shown in FIG. 1 and which has been described previously. First resilient, flexible body material **110** is molded over arm portions **18** and **20**, and leg portions **38** and **40** of the skeleton. However, first body material **110** is not applied to the neck or upper chest portions of the skeleton as in the previous embodiments, nor is it used to thicken the remaining exposed primary members. Second body material **132** is then molded over waist portion **24** of skeleton **10**, and also over the leg, neck and upper chest portions that were left exposed when the first body material was molded.

Still another alternative embodiment of a posable figure is depicted in FIG. 9. The embodiment of FIG. 9 includes inner skeleton **10**, and is similar to the embodiment described above and depicted in FIG. 8. However, first body material **110** is molded around waist portion **24** and leg portions **38** and **40** of the skeleton during the first body molding process, to limit flexion of the skeleton in those portions. Second body material **132** is then molded over waist portion **24** of the skeleton, and also over the leg, neck and upper chest portions that were left exposed when the first body material was molded.

Another alternative embodiment of a posable figure is depicted in FIG. 10. The embodiment of FIG. 10 is similar to the embodiment depicted in FIG. 9, including inner skeleton **10**. However, in FIG. 9, first resilient flexible body material **110** is also molded over neck portion **42** of primary upper member **12** during the first body molding step, to limit flexion of the neck portion.

Another alternative embodiment of a posable figure is depicted in FIG. 11. The embodiment of FIG. 11 includes inner skeleton **10** as depicted in FIG. 1, but second body material **132** is molded only over an inner part of leg portions **38** and **40**, and waist portion **24** of the skeleton. In this embodiment, second body material **132** is molded over the skeleton before first body material **110** is molded, since the first body material encloses the second body material.

Still another alternative embodiment of a posable figure is depicted in FIG. 12. The embodiment of FIG. 12 includes inner skeleton **10** as depicted in FIG. 1, with a thickening layer of first body material **110** over all of the primary members of the skeleton. Then, an outer layer of second body material **132** is molded over the skeleton, to form the outer surface of the posable figure.

Yet another alternative embodiment of a posable figure is depicted in FIG. 13, which includes inner skeleton **10** as depicted in FIG. 1, with a single resilient, flexible body material **300** molded around the inner skeleton to form a finished body. Body material **300** may be similar to one of materials **110** or **132**, or it may have any other desired elasticity.

Various other alternative embodiments of the toy may include one or more of the bare wire, taper in the legs, over-molded upper leg and waist portions of the skeleton, second-material neck, and inner-portion only of the upper legs or waist, as depicted in FIGS. 7–13. Similarly, other materials may be used to form the inner skeleton and as the first and second resilient, flexible body materials. These other alternative embodiments have not been depicted separately in the drawings.

While the present description has been provided with reference to the foregoing embodiments, those skilled in the art will understand that many variations may be made therein without departing from the spirit and scope defined in the following claims. The description should be understood to include all novel and non-obvious combinations of elements described herein, and claims may be presented in this or a later application to any novel and non-obvious combination of these elements. The foregoing embodiments are illustrative, and no single feature or element is essential to all possible combinations that may be claimed in this or a later application. Where the claims recite “a” or “a first” element or the equivalent thereof, such claims should be understood to include incorporation of one or more such elements, neither requiring, nor excluding, two or more such elements.

We claim:

1. A posable figure comprising:

a body having a torso and limbs, the body made of at least one soft flesh-like outer layer molded over an inner skeleton, the skeleton including:

at least one continuous primary member having first and second ends, the primary member being configured to flex in response to an externally applied force; and

at least one secondary member, molded over a portion of the primary member, the secondary member being configured to substantially limit flexion of the primary member where the secondary member is molded over the primary member;

wherein the primary member includes at least one intermediate bend between the first and second ends, the intermediate bend being configured to retain the at least one secondary member at a predefined location on the primary member.

2. The posable figure of claim 1, wherein the at least one primary member includes a primary upper member extending from a first hand portion to a second hand portion and defining arm portions, a primary torso member defining a waist portion, and two primary leg members extending from foot portions to a hip portion and defining leg portions.

3. The posable figure of claim 2, wherein an intermediate bend of the primary upper member defines a neck portion.

4. The posable figure of claim 3, wherein the skeleton further includes a plurality of support members extending outward from the primary members.

5. The posable figure of claim 4, wherein the support members include a plurality of locating pegs extending substantially radially outward from the primary members.

6. The posable figure of claim 5, wherein the support members include a plurality of locating sprues.

7. The posable figure of claim 3, wherein the primary members include metal wires.

8. The posable figure of claim 7, wherein the wires are coated with a thin layer of polymer resin.

9. The posable figure of claim 8, wherein the polymer resin is polypropylene and wherein the layer is approximately 1 millimeter thick.



9

10. The posable figure of claim 9, wherein the primary upper member and the primary leg members each include exactly one wire, and wherein the primary torso member includes exactly two wires.

11. The posable figure of claim 10, wherein the wires of the primary torso member are bent double along substantially their entire length.

12. The posable figure of claim 3, wherein the at least one secondary member includes a secondary hip member that couples the primary leg members to the primary torso member, and a secondary chest member that couples the primary torso member to the primary upper member.

13. The posable figure of claim 12, wherein the secondary members include secondary hand members and secondary foot members.

14. The posable figure of claim 13, wherein the secondary members are constructed from polyethylene.

15. The posable figure of claim 12, wherein a first body material is molded over the skeleton to form finished lower legs, finished arms, a finished upper chest, and a finished neck.

16. The posable figure of claim 15, wherein the first body material has a Shore hardness between 30 and 50.

17. The posable figure of claim 16, wherein the first body material has a Shore hardness of approximately 40.

18. The posable figure of claim 15, wherein the first body material is molded around upper portions of the primary leg members and around a middle portion of the primary torso member, to form an unfinished surface extending partially towards an outer surface of the figure.

19. The posable figure of claim 18, wherein the unfinished surface has a diameter of approximately 2 millimeters.

20. The posable figure of claim 15, wherein the first body material is molded into a frustoconical shape at a proximal end of each finished lower leg.

10

21. The posable figure of claim 15, wherein a second body material is molded around the upper portions of the primary leg members and around the middle portion of the primary torso member, to form a finished body.

22. The posable figure of claim 21, wherein the second body material has a Shore hardness between 5 and 15.

23. The posable figure of claim 22, wherein the second body material has a Shore hardness of approximately 10.

24. A method of manufacturing a posable figure, comprising:

bonding a plurality of primary members, each having first and second ends and at least one intermediate bend between the first and second ends, into an integral skeleton in an insert molding process that includes molding secondary members to partially surround the primary members, the intermediate bends being configured to retain the secondary members at predefined locations on the primary members;

covering first portions of the skeleton with a first elastic body material in a first body molding step; and

covering second portions of the skeleton with a second elastic body material in a second body molding step.

25. The method of claim 24, wherein the first body molding step includes molding the first body material around some portions of the primary members to form an unfinished surface extending partially towards an outer surface of the figure, and molding the first body material around other portions of the primary members to form finished portions of the figure.

\* \* \* \* \*